

LAFAYETTE LEADS IN EVERY PHASE OF

LRE

**CATALOG
720
1972
OUR 51st YEAR**



**LR-440 STEREO RECEIVER WITH
170 WATT 4 CHANNEL AMPLIFIER**
See Page 6



**LA-2525 DISCRETE 4 CHANNEL
40 WATT STEREO AMPLIFIER**
See Page 2



**LA-44 DISCRETE 4 CHANNEL
170 WATT STEREO AMPLIFIER**
See Page 4

CHANNEL STEREO

LAFAYETTE MODEL RK-48



**COMPATIBLE 2 AND 4 CHANNEL
STEREO 8 TRACK CARTRIDGE TAPE DECK**
ONLY 89.95 — See page 3

LAFAYETTE 4 CHANNEL ADAPTER



**CONVERT YOUR PRESENT
2 CHANNEL STEREO SYSTEM TO
DERIVED 4 CHANNEL STEREO**
ONLY 29.95 See Page 468

LAFAYETTE

RADIO ELECTRONICS

Mail Order and Sales Center

111 Jericho Turnpike, Syosset, L. I., New York 11791

Index: Page 811
Easy Pay Plan:
Page 22
Store addresses:
Page 20
International &
Industrial Divisions:
Page 23
Associate
Stores
Coast-to-Coast

NOW... Lafayette Brings 4-Channel Stereo to Everyone

4 Amplifiers in 1
For Your Supreme Stereo Pleasure!

ONLY
1195
with case

- Thrill To The 4 Channel Dimensional Sound Realism From 4-Channel Program Sources!
- Exclusive "Composer" Derived 4-Channel Dimensional Circuitry
- Listen To The Extra 2-Channels in Your Stereo Records, Tapes and FM Broadcasts!

AAA 2-year guarantee

see page 415
for terms



LA-2525

NEW

LAFAYETTE 40 Watt Compatible 4-Channel Stereo Amplifier

Hear The Full Performance in True Dimensional Depth... Not Just Part of It!

The Lafayette Model LA-2525 combines 4 outstanding amplifiers with new in-reel 4-channel control circuitry. The new disc, 4-channel program source from 4 Channel 8-track tape cartridges, 4-channel reel-to-reel tapes, and when they become available, from 4-channel cassettes, 4-channel FM broadcasts and 4-channel records. In addition the LA-2525 features the utmost in compatibility through its exclusive "Composer" circuit and derives rich four channel dimensional sound from existing conventional stereo records, stereo tapes and FM stereo broadcasts. You will be amazed at this full dimensional exciting room-filling realistic sound! You get much greater enjoyment from your present 2-channel stereo program sounds as well as from the ever growing new discrete 4-channel sources.

The LA-2525 incorporates separate Volume controls for front left, front right, rear left, and rear right channels;


Specifications

Power Output: 40 Watts \pm 1 db at 8 ohms. **Frequency Response:** 20-20,000 Hz \pm 1.5 db; **Total Harmonic Distortion:** at 1 kHz, 8 ohms, 1 watt = 0.125%; **Input Sensitivity:** Aux = 275 mV, Tuner = 500 mV, Phono Mag. = 3.5 mV, Phono

separate ganged Bass and Treble controls for front and rear channels; Headphone jack for private listening from front amplifiers (Channels); 4-channel master focker switches for Mono/Stereo Mode, Loudness, Hi-Filter, Front Speakers Main/Remote and Rear Speakers Main/Remote; 6 position function selector for 2-Channel-Front, Rear, 4-Channel Composer and 4-Channel-Stereo, Reverse, and Front plus Rear; 3 position Input Selector for Aux., Tuner, Phono. The rear panel features 16 input jacks—4 each for record output jack facilities for 2 and 4-channel tape inputs; and unswitched AC Convenience outlet. Operates on 105-120 volts, 50/60 Hz AC. Size: 4 $\frac{3}{8}$ "x13 $\frac{1}{2}$ "x8 $\frac{3}{4}$ "D. Imported. Shpg. wt., 14 lbs.

Net 119.95

99 R 02628W



Function Mode Selector With Composer



Concentric Volume Controls

Front and Rear Main-Remote Speaker Switches

Derived 4 Channel Tape Output Jacks (Rear)

Enjoy THE SPECTACULAR NEW SOUND of 4 Channel Stereo Tapes



NEW LAFAYETTE RK-48 Compatible 2 and 4 Channel Stereo 8-Track Cartridge Tape Deck

89⁹⁵

- Automatic Mode Selection for 2- or 4-Channel Tapes
- Spill-Proof Capstan Mechanism
- 4 Solid-State Stereo Playback Pre-amplifiers
- Individual Illuminated Channel Indicator Lights

- Plays 4-Channel Stereo 8-Track Cartridges thru a 4-Channel Stereo Amplifier
- Plays 2-Channel Stereo 8-Track Cartridges thru either a 4-Channel or 2-Channel Stereo Amplifier

Add the sensational new dimension of 4-channel stereo sound to your listening area. With the RK-48, you can play exciting new discrete 4-channel stereo tape cartridges through any Lafayette or other brand 4-channel stereo amplifier or receiver system. The RK-48 is fully compatible. Can be used as the playback tape deck in conventional 2-channel stereo 8 Track systems. Or, in 2 channel stereo systems that incorporate the exclusive Lafayette Composer Circuit, the RK-48 can be used either to derive 4 channel stereo sound from conventional 2-channel 8 Track cartridges or play discrete 4-channel 8 Track Stereo Tape cartridges, by adding a stereo amplifier and 2 speakers. The RK-48 has fully automatic mode selection—insert

either a 2-channel or 4-channel stereo tape and the deck instantly plays in the correct mode. Individual illuminated program track indicators. Pushbutton program selectors. Manual 2 or 4-channel mode selector button. Spill-proof mechanism stops tape from wrapping around capstan. Four built-in solid-state stereo playback pre-amplifiers. Specifications: Max output 1 volt; Hum & Noise —49db.; Channel Separation —45db.; Distortion 1%; Wow & Flutter 0.2%; Frequency response 30-10,000 Hz. ±2db. For 105-120V, 60 Hz. AC Power Fuse. Size: 9½" x 10½" x 4½" H. Imported. Shpg. wt., 10 lbs. 3 oz. 99 R 15950W No Money Down* Net 89.95

LAFAYETTE 4-Channel Stereo 8 Track Demo Tape

Ideal tape cartridge to make sure your 4-channel 8-Track stereo system is properly set up. Program 1 on the tape includes 400 Hz signals for left front speaker, right front speaker, left rear speaker, right rear speaker. Next you will hear Leonard Bernstein and the New York Philharmonic play excerpts of Tchaikovsky's 1812 overture first in Mono, then in 2 channel stereo, and lastly—magnificent 4 channel stereo. Program 2 consists of excerpts from Tchaikovsky's Swan Lake Ballet in breathtaking 4 channel stereo. Shpg. wt., 6 oz.

28 R 01413L Net 3.98

RCA 4-Channel Stereo 8-Track Cartridges—7.95 each

28 R 14036 Hair-Original Broadway Recording—Aquarius, Good Morning Starshine, Where Do I Go, Hair, I Got L.I.E., plus many more.

28 R 14002 Boston Pops—MUSIC FROM MILLION DOLLAR MOVIES—Laura, Gigi, Love is a Many Splendid Thing, Song from Moulin Rouge, Around the World in 80 Days, plus 5 more.

28 R 14010 Best of Boston Pops—More, On the Trail (from "Grand Canyon Suite"), Hello Dolly, plus 9 more selections.

28 R 14069 Best of Henry Mancini—Pink Panther Theme, Breakfast at Tiffany's, Soldier in the Rain, plus 5 more selections.

28 R 14028 Highlights From Madame Butterfly, Puccini-Leinsdorf: Conductor, Price, Tucker, Elias, Maero.

28 R 14051 Best of Eddie Arnold—Just a Little Loving, Make the World Go Away, Anytime, plus 9 more selections.

28 R 14044 Best of Charlie Pride—Just Between You and Me, The Easy Part's Over, Kaw-Liga plus 9 more selections.

Shipping wt., 2 oz. ea.

3⁹⁸
LAFAYETTE 4 Channel
Stereo 8 Track
Demonstration Tape
"Listening is Believing"

Made for LAFAYETTE
by Columbia



RCA 4 Channel Stereo
8 Track Tape Cartridges

YOUR CHOICE

795

*See Page 22 for Full Credit Details on Easy Pay Plan

A NEW ERA IN HI-FI

4

CHANNEL STEREO

LAFAYETTE 170-Watt Compatible 4 Channel Stereo Amplifier



MODEL LA-44

FOR YOUR GREATER STEREO PLEASURE

The Fabulous LAFAYETTE LA-44

- ★ 4 Superb Amplifiers in One Versatile Unit.
- ★ Thrill To The 4-Channel Surround Sound Channel Program Sources!
- ★ Discover The Exciting 4 Dimensional Audio Richness Of Your Present 2-Channel Stereo Records, Tapes, and FM Stereo Broadcasts!
- 170 Watts \pm 1 db Output Power at 4 Ohms

219⁹⁵
No Money Down*
2 YR. AAA GUARANTEE
See Page 418 for Details

- ★ Use This Fine Quality 4-Amplifier Unit as 2 Independent 2-Channel Stereo Amplifiers For Two Different Stereo Program Sources Simultaneously!
- ★ Build a Derived 4-Channel Stereo Library on Tape From Your Present Favorite Stereo Records, Tapes and FM Stereo Broadcasts
- 4 FET's, 39 Transistors, 4 Diodes and 4 Thermistors

Now you can hear the full performance in true dimensional depth, not just a part of it... from 4-channel 8-track cartridges, 4-channel reel-to-reel tapes and, when they are available 4-channel cassettes, FM Broadcasts and 4-channel records. Another feature and exclusively Lafayette's is the "Composer" circuit which takes existing conventional stereo records, tapes and FM Broadcasts and recreates, from this material, rich four dimensional sound in your living room. It also enables the tape recording of derived 4-channel stereo from your present favorite stereo records, stereo tapes, and FM stereo broadcasts. In addition the 4-amplifier LA-44 can be used as the heart of two completely independent stereo systems, supplying two different stereo programs to two different locations from two different stereo sources simultaneously, i.e., phono and tuner, plus the flexibility of additional remote speaker locations for each pair of channels.

The LA-44 features separate volume controls for front left and front right channels, rear left and rear right channels; separate Bass controls for front and rear and separate Treble controls for front and rear channels; Headphone jacks for front and rear channels; front and rear channel tape output jacks provided on both front and rear of amplifier chassis for your convenience; a "Reverb" position for use with an external-reverberation unit to the rear channels only. The rear panel features input jacks for two-channel and 4-channel stereo for tape playback; magnetic and ceramic phono; tuner; Auxiliary I and Auxiliary II; Main and Remote speaker outputs for all four channels. Includes one switched and one unswitched convenience outlet. Operates on 105-120 volts, 50/60 Hz AC. Size: 13 $\frac{1}{2}$ "W x 4" H x 9 $\frac{1}{2}$ "D. Imported. Shipping weight 16 $\frac{1}{2}$ lbs. Net 219.95
99 R 02537W No Money Down*



Input Mode Selector with Composer



Concentric Volume Controls


SPECIFICATIONS

Power Output: 170 Watts \pm 1db music power; 42.5W/CH—4 ohms) 100 Watts RMS (1 kHz, 0.6% THD), 25W/Ohm—4 ohms. Total Harmonic Distortion (1 kHz, 8 ohms, 1 Watt Output): 0.07%. Power Bandwidth: 15-25 kHz. Frequency Response: (Aux to Spkr, 8 ohms): 20-20,000 Hz \pm 1.5 db; Input Sensitivity: Phono Mag. 3.5 mV, Phono Cer. 125 mV, Tuner 500 mV, Tape Mon. 500 mV, Aux-1 & Aux-2 250 mV. Hum and Noise: Aux 70 db, Phono Mag. 60 db, Phono Cer. 57 db, Tuner 70 db, Tape Mon. 83 db. Channel Separation: 60 db (1kHz 8-ohm Spkr.). Semiconductors: 4 FET's, 39 Transistors, 4 Diodes, 4 Thermistors Power Consumption: 210 VA (At Max Output).

See Page 33 For LA-44 4 Channel Systems



Push-button Input Function Selector



Derived 4-Channel Tape Output Jacks (rear)

NEW

A NEW ERA IN HIGH LAFAYETTE LR-440

170-Watt Compatible 4-Channel FM/AM Stereo Receiver



Plays Discrete 4-Channel Stereo Programs. Derives and Plays 4-Channel Stereo from Present Stereo Records, Tapes, and FM Broadcasts

SUPREME DISCRETE and DERIVED 4-CHANNEL STEREO ENJOYMENT!

ONLY
369.95
with case

AAA 2-year
guarantee

See page 415 For Terms

with
4 AMPLIFIERS
For Discrete 4-Channel
Stereo Reception

with
SUPERB AM-FM
Stereo Reception

with
EXCLUSIVE "COMPOSER"
For Derived 4-Channel
Stereo Reception

- Hear The Thrilling New Discrete 4-Channel Program Sources with Amazing Concert Hall Realism!
- Listen to the Exciting Dimensional 4-Channel Audio Derived from Your Present 2-Channel Stereo Records, Stereo Tapes, and FM Stereo Broadcasts
- Use It as 2 Independent 2-Channel Stereo Amplifiers for Two Different Stereo Program Sources Simultaneously
- Build a Derived 4-Channel Stereo Tape Library from Your 2-Channel Stereo Records, Tapes, and FM Broadcasts!

The Lafayette LR-440 compatible 4-channel AM/FM stereo receiver brings you the full performance in amazing dimensional depth. Now you can listen to the audio richness of the new discrete 4-channel programs from 4-channel 8-track cartridges and 4-channel reel-to-reel tapes, and as soon as they become available, to 4-channel cassettes, 4-channel FM broadcasts and 4-channel records. In addition, the LR-440's four ingeniously engineered preamplifier-amplifiers plus its exclusive "Composer" derived 4-channel circuitry with full control flexibility take our present concepts from 2-channel FM stereo broadcasts to 4-channel sound in your living room, den, etc. The LR-440 can also be used as two completely independent stereo systems, supplying two different locations from two different stereo sources simultaneously, i.e., phono and tuner, plus the flexibility of additional remote speaker locations for each pair of speakers.

The LR-440 features an excellently designed FM stereo tuner with 1.65µV sensitivity, AM and FM signal strength tuning meter, automatic FM stereo indicator which lights up when tuned to a stereo broadcast, and "Acrifitune" precision tuning indicator which lights when receiver is precisely tuned to an FM station.

features Phono, Aux, and Monitor indicator jewels. Separate volume controls plus left and right balance controls for front and rear channels; concentric Bass and Treble controls for front and rear channels; Headphone jacks for front and rear channels; front and rear channel tape output jacks provided on 2 and 4-channel rear panels for convenience; an input Mode rotary selector for 2 and 4-channel inputs; front and rear channel pushbutton switches for Aux 1, Aux 2, Tuner, and Phono inputs; a Tuner Selector rotary switch; a rotary Main-Remote Speaker selector switch with Phone position; and pushbutton switches for Tape Monitor, Loudness, Stereo/Mono, Hi-Filter, and Mute (for minimizing inter-station noise when tuning FM).

The rear panel features input jacks for 2-channel and 4-channel stereo for tape playback, magnetic and ceramic phono, and Auxiliary 1 and 2. Main and Remote speaker outputs for all four channels are also provided. Includes one switched and one unswitched AC convenience outlet. Operates on 105-120 volts, 50/60 Hz AC. Size: 18½" x 13¾" x 4¾". Imported. Shpg. wt., 41 lbs. Net 369.95

SPECIFICATIONS

Amplifier Power Output: 170 Watts ±1db (42.5 W/CH) at 4 ohms, 110 Watts ±1db (27.5 W/CH) at 8 ohms, 100 Watts RMS (25 W/CH) at 4 ohms, 80 Watts RMS (20 W/CH) at 8 ohms. Frequency Response: 20-20,000 ±1.5db Total Harmonic Distortion: 0.07% at 1-watt output, 0.8% at rated output. Power Bandwidth: 15-25,000 Hz. Input Sensitivity: Phono Mag. 3.5 mV, Phono Cer. 125 mV, Tuner 500 mV, Tape Play 500 mV, Aux-1 and Aux-2 250 mV, Hum and Noise: Aux —70db, Phono Mag. —60db, Phono Cer. —57db, Tuner —70db, Tape Play —83db. Channel Separation: 60db.

Output Impedance: 4 and 8 ohms. Tuner FM: 4 Gang Tuning Condenser. Useable Sensitivity (IHF): 1.65 µV; Stereo Separation: 40db at 400 Hz; Signal-to-Noise Ratio: 75db; Spurious Response Rejection: 95db; Harmonic Distortion: 0.3% at 100% Mod.; Capture Ratio: 1.5db; Cross Modulation Index: 90db; Antenna: Built-in plus 300-ohm balanced for external antenna. AM: 3 Gang Tuning Condenser, Terminal Sensitivity: 18 µV, Antenna: Built-in swivel type ferrite rod.



METER: Shows relative signal strength of received AM or FM. Also shows when an AM station is properly tuned. AUTOMATIC FM STEREO INDICATOR: Lights when tuned to a stereo broadcast (with Mode in "Stereo"). "ACRIFITUNE" indicator lamp lights when receiver is precisely tuned to an FM station.



Input Mode Selector with "Composer"



Volume and Balance Controls



Derived 4-Channel Tape Output Jacks (Rear)



Front and Rear Channel Tape Output and Phone Jacks

For more details on the Lafayette LR-440, see page 415



NEW LAFAYETTE LRK 900

**Combination AM/FM
Stereo Receiver and Stereo
Cassette Tape Recorder**

*With Built-in 4 Channel
Composer & Adapter*

199⁹⁵

CASSETTE RECORDER FEATURES

- 7 Pushbutton Functions: Play, Record, Fast Forward Rewind, Pause, Stop, Cassette Up
- Large Illuminated Dual Record Level Meters
- STD/CrO₂ Bias Equalizer Switch
- Sound with Sound Mixing • Front Panel Mike Input Jacks

Our exciting new cassette music center combines a top-quality AM/FM Stereo Receiver and an advanced Stereo Cassette Recorder in a handsome low profile cabinet. In addition this Cassette/Receiver has built in 4 channel stereo facilities by means of 2 specially designed circuits—Lafayette Composer and Lafayette 4 Dimensional Adapter. The LRK-900 features ACRITUNE circuitry for foolproof visual FM tuning accuracy. An FM stereo indicator light illuminates when a FM stereo broadcast is being received. The STD/CrO₂ bias equalizer switch permits choice of recording with either a standard cassette tape or the new improved chromium dioxide tapes (CrO₂). The Cassette Recorder turns off both electrically and mechanically at end of a tape in either Play, Record, or Fast Forward Mode. Also includes 3 digit tape counter with reset button; separate bass and treble controls; Pushbutton switches for: Loudness, Stereo/Mono, Hi-Filter, Tape, Power On/Off, and a front panel stereo headphone jack. Input jacks are provided for Aux, cer. or mag. phono. Rear Panel also includes Tape Recorder Output jacks and an AC Con-

LRK-900 4 CHANNEL FEATURES Special Built-in Circuitry that Lets You Listen to the 2 Extra Channels on Your Stereo Records, Stereo Tapes, Stereo FM Broadcasts or from Specially Encoded 4 Channel Material

LAFAYETTE 4 CHANNEL STEREO COMPOSER CIRCUIT—The built-in Composer Circuit derives 4 channel stereo material. By adding an external stereo amplifier and 2 additional speakers to your 2 speaker LRK-900 system, you now have 4 channels of amplification with 4 speakers. You can also record any 2 channel stereo program source in 4 dimensional stereo using a 4 channel recorder. In addition, the LRK-900 can now be used with discrete 4 channel input sources.

LAFAYETTE 4 DIMENSIONAL STEREO ADAPTER—The built in adapter also derives 4 channel stereo material. You need only add 2 additional speakers to your 2 speaker LRK-900 system. This gives you 4 speakers and 4 channels of matrixed program material. No extra amplifiers are required.

AM/FM STEREO RECEIVER FEATURES

- 20 Watt \pm 1db Stereo Amplifier
- Advanced Solid State Circuitry
- Main, Remote, or Main and Remote Speaker Selection
- FM Stereo Indicator Light with Acritune®
- Magnet and Ceramic Phone Inputs

venience Outlet. Built-in AM and FM Antenna—provisions for external AM and FM antennas. Output transistors are fused for overload protection. Specifications: Receiver, Power Output, 20 Watts total \pm 1db. Input Sensitivity Phono (mag.) 4 mV (cer.) 130mV Aux, 275 mV. FM tuner IHF Sensitivity 3.5 μ V. Stereo MPX Separation 35db @ 400 Hz. Cassette Recorder, AC Bias Erase Freq. 98 kHz, S/N Ratio better than 48 db., Mike Input sensitivity 1 mV, Wow & flutter less than .25%. Freq. Response 50-10 kHz. Walnut Wrap around metal case with Brushed Gold Aluminum trim. For 117 VAC 60 Hz. Size: 19 $\frac{1}{4}$ "W x 4H x 11 $\frac{7}{8}$ "D. Imported. Shpg. wt., 25 lbs.

99 R 02529 No Money Down	Net 199.95
99 R 46161 Dynamic Mike for LRK-900. Wt., 1 lb.	Net 6.95
CrO ₂ , 60 Min. Chromium Dioxide Tape. Wt., 4 oz.	
28 R 47002	Net 2.99
Standard 60 min. Cassette Recording Tape	
28 R 01223 Wt., 4 oz.	Net .99

*See Page 22 for Full Credit Details on Easy Pay Plan

NEW LAFAYETTE LRK 855

Combination AM/FM Stereo Receiver and 8-Track Stereo Tape Cartridge Recorder

With Built-in 4 Channel
Composer & Adapter

219⁹⁵



8 TRACK RECORDER FEATURES

- Automatic Stop—Motor Shuts Off
- Remove Tape Indicator Light
- Record Safety Interlock Button
- Front Panel Mike Input Jacks
- Pushbutton Track Selector
- Illuminated Track Indicator Lights

AM/FM STEREO RECEIVER FEATURES

- 20 Watt ± 1 db Stereo Amplifier
- Advanced Solid-State Circuitry
- Main, Remote, or Main and Remote Speaker Selection
- FM Stereo Indicator Light with Acrltine
- Magnetic and Ceramic Phono Inputs

Here is one of the most advanced home stereo music systems you can own. The deluxe LRK-855 features two major innovations: 4-channel stereo compatibility by means of 2 specialty designed circuits: a Lafayette Composer, and a Lafayette 4 Dimensional adapter. In addition, this magnificent AM/FM stereo receiver/8-track recorder-player has a full complement of professional quality features: automatic stop and motor shut-off after last channel has been recorded, direct 8-track recording from the AM/FM stereo receiver, front panel dual-concentric left and right channel record level controls, 2 illuminated VU-record level meters, FM-MPX filter, FM-stereo indicator light, Acrltine circuitry for foolproof visual FM tuning accuracy, separate Bass and Treble controls, pushbutton controls for Loudness, Stereo/Mono, Hi-Filter, front panel stereo headphone jack, inputs for Aux, Phono (Cer. & Mag.), Tape Recording Outputs, unswitched AC convenience outlet, built-in AM and FM antennas with provisions for external AM & FM antennas. Output transistors are

LRK-855 4-CHANNEL FEATURES—Special Built-in Circuitry Lets You Listen to the 2 Extra Channels on Your Stereo Records, Tapes, FM-Broadcasts, or From Specially Encoded 4-Channel Material

LAFAYETTE 4-CHANNEL STEREO COMPOSER CIRCUIT—The built-in Composer Circuit derives 4-channel stereo material. By adding an external stereo amplifier and 2 additional speakers to your 2 speaker LRK-855 system, you now have 4 channels of amplification with 4 speakers. You can also record any 2-channel stereo program source in 4 dimensional stereo using a 4-channel recorder. In addition, the LRK-855 can now be used with discrete 4-channel input sources.

LAFAYETTE 4 DIMENSIONAL STEREO ADAPTER—The built-in adapter also derives 4-channel stereo material. You need only add 2 additional speakers to your 2-speaker LRK-855 system. This gives you 4-speakers and 4-channels of matrixed program material. No extra amplifiers are required.

fused for overload protection. SPECIFICATIONS: Amplifier Power Output: 20 Watts ± 1 db IHF, Freq. Response: 20-20,000 Hz ± 1.5 db, Harmonic Distortion: 0.2% at 1 watt, Input Sensitivity—Phono (Mag.) 4 mV, (Cer.) 130 mV, Aux. 275 mV, Output Impedance: 4 and 8 ohms, Tuner FM Sensitivity: 3.5 μ V, S/N Ratio: 53db, Stereo MPX Separation: 35db at 400 Hz. 8-Track Recorder—Mike Input Sensitivity: 1 mV, Mike Impedance: 3.3k ohms, Bias Freq.: 80 kHz, Freq. Response: 30-10,000 ± 2 db, Flutter: 0.25%, Channel Separation: 30db, Solid-state Circuitry: 45 Transistors, 31 Diodes. Walnut-finished metal wrap around case. Brushed gold anodized aluminum trim. For 117 VAC, 60 Hz. Size: 4 1/2 x 19 1/2 x 13 1/4" D. Imported. Shpg. wt. 25 lbs.

99 R 02511 No Money Down* Net 219.95

Dynamic Mike for LRK-855. Shpg. wt., 1 lb.

99 R 46161

Net ea. 5.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 9



NEW LAFAYETTE LRK-480

**AM/FM Stereo Receiver with
Built-In 2 and 4-Channel
8-Track Stereo Tape Player**

**With Built-in 4-Channel
Composer & Adapter**

179⁹⁵

CARTRIDGE TAPE PLAYER FEATURES

- Automatic Mode Selection for 2 or 4-Channel Tapes
- 4 Solid-State Stereo Playback Pre-amplifiers
- Individual Illuminated Program Track Indicator Lights
- Remove Tape Indicator Light
- Spill-Proof Capstan Mechanism

Newly designed and engineered with the latest refinements and innovations found in today's stereo high fidelity components. This versatile AM/FM Stereo Receiver features 4-CHANNEL STEREO COMPATIBILITY by means of 2 specially designed built-in circuits—the exclusive Lafayette 4-Channel Composer and the Lafayette 4-Dimensional Stereo Adapter. In addition, the LRK-480 includes a 2 and 4-channel 8-Track Stereo Tape Player. By adding an external stereo amplifier and 2 speakers you can play the new 4-channel 8-Track Stereo Tape Cartridges thru the LRK-480. Using the Composer circuit, you can also derive 4-channel stereo material from conventional 2-channel 8-Track Stereo Cartridges. FM Stereo broadcasts, and records (when you connect a stereo record changer with either a ceramic or magnetic pick-up). An exclusive Remove Tape Indicator Illuminates with the power turned off and a tape cartridge left fully inserted in the player. This feature will preserve the life

10 Lafayette Cat. No. 720

LRK-480 4-CHANNEL FEATURES

BUILT-IN 4-CHANNEL 8-TRACK STEREO TAPE PLAYER—Plays 4-channel stereo 8-track cartridges with the addition of an external stereo amplifier and 2 speakers.

LAFAYETTE 4-CHANNEL STEREO COMPOSER CIRCUIT—The built-in Composer Circuit derives 4-channel stereo material from your 2-channel stereo tapes, records, and FM broadcasts, or from specially encoded 4-channel material. By adding an external stereo amplifier and 2 additional speakers to your 2 speaker LRK-480 system, you now have 4-channels of amplification with 4 speakers. You can also record any 2-channel stereo program source in 4-dimensional stereo using a 4-channel recorder. You can also plug in a 4-channel reel-to-reel tape deck.

LAFAYETTE 4-DIMENSIONAL STEREO ADAPTER—The built-in adapter also derives 4-channel stereo material from 2-channel stereo tapes, records, and FM broadcasts. However, you need only add 2 additional speakers to your 2 speaker LRK-480 system. This gives you 4 speakers and 4 channels of matrixed program material. No extra amplifiers are required.

AM/FM STEREO RECEIVER FEATURES

- 20 Watt \pm 1db Stereo Amplifier
- Advanced Solid-State Circuitry
- Main, Remote, or Main and Remote Speaker Selection
- FM Stereo Indicator Light With Acritune
- Magnetic and Ceramic Phono Inputs
- Front Panel Stereo Headphone Jack

of your cartridges and the player's tape head. The Receiver Section features an FM stereo indicator light and ACRITUNE circuitry for foolproof visual FM tuning accuracy. Aux inputs, Tape Record Outputs and an AC convenience jack are provided on the rear panel. Separate bass and treble controls. Pushbutton switches for Tape/off, Loudness, Stereo/Mono, Hi-Filter.

SPECIFICATIONS: Power Output: 20 Watts \pm 1db; Freq. Response 20-20,000 Hz \pm 1.5db; Harmonic Distortion 0.2% at 1-Watt; Input Sensitivity: Phono (mag.) 4 mV, (ceram.) 130 mV, Auxiliary 275 mV; Output Impedance, 4 & 8 ohms. Tuner-FM Sensitivity 3.5 μ V; S/N Ratio 63 db; Stereo MPX Separation 35 db at 400 Hz. Built-in AM and FM antennas. Provisions for external AM and FM antennas. Size: 4 1/2 x 19 1/2 x 13 1/4" D. For 117 VAC, 60 Hz. Shpg. wt., 30 lbs. Imported.
99 R 02677WX No Money Down* Net 179.95

*See Page 22 for Full Credit Details on Easy Pay Plan

SUPERB LAFAYETTE "LRC-70" SOLID-STATE 50 WATT AM/FM STEREO RECEIVER TURNTABLE CONTROL CENTER



Model LRC-70

259⁹⁵

No Money Down*

SAVE \$20⁰⁰

On the Purchase of 2 Lafayette Criterion 50A Speaker Systems when bought with the LRC-70

LRC-70 plus 2 Criterion 50A Bookshelf Systems: See page 57 for description of the Criterion 50A. Shpg. wt., 100 lbs. Imported. 99 R 02404WXM Net 299.85

- Professional Garrard Model 40B Stereo Automatic Turntable
- Pickering V15/AC-3 Dustomatic™ Stereo Cartridge with Diamond Needle
- Stereo Mike Input—Can use as a PA Amplifier
- Main and/or Remote Speaker Outputs


The "low profile" LRC-70 has been created for the connoisseur who demands magnificent stereo hi-fidelity performance from a compact, gracefully styled control unit. The LRC-70 has been designed for complete ease of installation and use. This has been accomplished by integrating a superb Lafayette AM/FM Stereo Receiver and a professional Garrard stereo record changer onto handsome base. The LRC-70 contains a powerful solid-state 50-watt AM/FM Stereo Receiver with 2 FET's, 31 Transistors, 25 Diodes, and 2 Thermistors. Features an illuminated AM/FM signal strength tuning meter, automatic FM Stereo switching, MX Filter, FM stereo indicator light, and a 4-Gang FM tuning condenser for extra sensitivity. The renowned Garrard 40B stereo turntable features a full viscous damped tone arm and single lever cueing. Plays 7", 10", and 12" records at 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45, and 78 rpm. A Deluxe Pickering V15/AC-3 Dustomatic™ stereo cartridge is already installed in the tone arm. LRC-70 controls

- Power Output 50 Watts at 4 ohms \pm 1db
- Tape Input and Output Jacks
- Tape Monitor Pushbutton
- Front Panel Stereo Headphone Jack
- Automatic FM Stereo Switching

include: pushbutton loudness, tape monitoring, high filter, and stereo/mono mode selection, concentric volume/balance, bass, treble, and a mode selector. Outputs for use of Main, Remote, Main and Remote speakers are provided. 2 Front panel stereo Mike Inputs, Tape Inputs, Front and rear panel Tape Outputs, 2 AC convenience outlets, external FM antenna jack. Specifications: Amplifier; Response, 20-20,000 Hz \pm 1.5 db, Output, 50 watts at 4 ohms (both channels) \pm 1 db, 40 watts IHF. Input Sensitivity: Phono Mag. 4 mV, Aux. 250mV, Mic. 6 mV. FM sensitivity: 2.5 μ V. IHF, Selectivity: Adjacent Channel: 40db, AM Selectivity: \pm 20 kHz 35 db. Size: 17 x 9 x 16 $\frac{1}{4}$ " D. Imported. For 117 VAC 50/60 Hz. 99 R 02347WX Shpg. wt., 36 lbs. Net 259.95

Beautiful, Heavy Gauge, Tinted Plexiglass Dust Cover for LRC-70. 24 R 09050W Shpg. wt., 2 lbs. Net 8.95

CONVERT THE LRC-70 TO DAZZLING 4-CHANNEL 4-DIMENSIONAL STEREOHONIC SOUND



Complete System
As Low As

379⁷⁰

No Money Down*



Save 30⁰⁰

From individual catalog prices
Magnificent sounding 4 dimensional stereo system featuring the Lafayette 4 channel adapter (see page 46A for description) with the LRC-70 Control Center and 4 Criterion 50A Speaker Systems. As you listen to your records, tapes or FM-stereo radio broadcasts, the acoustics of the original recording hall are literally superimposed in your own room with this brilliant performing system. Shpg. wt., 157 lbs. 99 R 99913WXM Net 379.70
Same System as above but with deluxe Lafayette/Pickering Phase 44 Elliptical Diamond Stylus Stereo Cartridge. Shpg. wt., 57 lbs. 99 R 99921WXM Net 415.65

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 11

**Our
Finest...**

Imitated But Never Duplicated!

LAFAYETTE LR-1500TA
240 Watt Deluxe Solid State AM/FM Stereo Receiver



ONLY 319⁹⁵
with case
No Money Down*

LAFAYETTE'S

AWARD-WINNING LR-1500TA

AAA 2-YEAR GUARANTEE

See Page 415 for Terms

4 IC's ♦ 6 FET's ♦ 39 Transistors ♦ 35 Diodes ♦ 2 Thermistors

- 240 Watts \pm 1 db., 190 Watts (IHF) at 4 ohms
- IHF FM Sensitivity 1.5 μ v
- Automatic Stereo FM Switching
- Adjustable Automatic FM Interstation Muting
- Center Channel Monaural Output
- Built-in AM and FM Antennas
- Illuminated Selector Function Indicator Jewels
- Exclusive Front and Rear Panel Tape Output Jacks
- Massive, Regulated Power Transformer Insures Proper Tuner/Amplifier Operation

Lafayette's latest and better than ever deluxe solid state AM/FM stereo receiver in the acclaimed and award winning LR-1500 series! The LR-1500TA stereo receiver is expressly engineered to blend the ultimate in high fidelity sound with superb performance, long life, and space-age reliability. In addition to its complement of fine quality transistors, the LR-1500TA includes integrated circuits (IC's) and 5 high-level FM stereo reception and audio reproduction. You'll hear more stations—the weak as well as the strong, with amazing, noise-free clarity and tonal purity! Features patent pending computer designed protective circuitry for virtually foolproof protection against burnout or failure of audio driver and power output transistors, and "ACRITUNE" circuitry for foolproof visual tuning accuracy. Utilizes a complete set of automatic and manual controls such as: Automatic FM stereo/mono switching; sharp, adjustable muting circuit to silence the receiver when tuning between stations; dual system speaker switch which permits enjoyment of stereo in one or two rooms separately or simultaneously!

direct tape monitor switch and tape monitor, jeweled indicator light for tape monitoring without changing connections; a front panel stereo headphone jack for enjoyable private stereo listening; and a center channel low level output for monaural amplifier and speaker. Separate input jacks provide for switchable high, low and medium range, hi-fi, phono and ceramic crystal tuning condensers and AM for stereo accompaniment. The full sound potential of standard AM broadcasting is incorporated, built-in FM and AM antennas plus connections for external local and distant FM and AM antennas. Distinctively styled to enhance any decor. Features a handsome gold anodized extruded aluminum front panel with matching knobs and includes an attractive vinyl-clad metal enclosure finished with the simulated look of rich walnut wood-grain. For 117v., 50/60 Hz AC. Imported. Size 16 $\frac{1}{2}$ x 4 $\frac{1}{4}$ x 14 $\frac{1}{4}$ "D". Shpg. wt., 34 $\frac{1}{2}$ lbs.

Net 319.95
99 R 01950W
Attractive Oiled Walnut Wood Cabinet for LR-1500TA.
21 R 01982W Shpg. wt., 8 $\frac{1}{2}$ lbs. Net 19.95



Softly Illuminated Diurnal Signal Strength Meter Permits Fast Accurate Tuning. On FM & AM and Accurately Indicator Light Assures Foolproof Accuracy on FM Tuning. A foolproof switching circuit with stereo indicating signal light automatically switches the receiver to either mono or stereo.



Sensitive FM "Front End" With Field Effect Transistors. Completely shielded FM "Front End" with F.E.T. RF amplifier and F.E.T. mixer plus a 4-gang variable capacitor and four tuned circuits assure top reception of mono or stereo FM stations.



Revolutionary Integrated Circuits. Four superior integrated circuits (IC's) in the FM IF stages provide excellent noise-free FM stereo reception and assure you of top performance for years to come.

With ACRITUNE Precision Tuning Indicator And COMPUTOR-MATIC Automatic Overload Protection.

SPECIFICATIONS

AMPLIFIER SECTION: Power: 240 watts \pm 1 db., 190 Watts (IHF), 140 watts RMS at 4 ohms. Total Harmonic Distortion @ rated output: under 1% @ 1 watt .07%. Frequency Response: 20-20,000 Hz \pm .75 db. Power Bandwidth: 18-55,000 Hz. Hum and Noise: High Level Inputs —75 db; Low Level Inputs —60 db. Input Sensitivity: CER phono, 64mV(H), 150 mV(M), 400 mV(L); Mag phono 1.8 mV(H), 4.5 mV(M), 12 mV(L); Aux. 225 mV; Tape play 500 mV. Output Impedance: 4, and 8 ohms;

FM SECTION: 4 Gang Tuning condenser. Tuning Range: 88-108 MHz, IHF FM Sensitivity 1.5 μ v. Capture Ratio: 1.25 db. Selectivity: 50 db. FM Distortion @ 400 Hz: 0.3%. Stereo Separation: 40 db @ 400 Hz. S/N Ratio (100% Modulation): 75 db. Spurious Response Rejection: 95 db. Cross-modulation Index: 90 db. Antenna Impedance: 300 ohms balanced input for external antenna. **AM SECTION:** 3 Gang Tuning Condenser. Tuning Range: 535-1605 KHZ. Ext. Antenna Sensitivity: 15 μ v.



"Computor-Matic" . . . Fuseless Automatic Overload Protection for Audio Transformers. Hundreds of times faster than a fuse, this special circuitry cuts off operation of the amplifier before damage can result. Permits resumption of normal operation when cause of overload is removed.

**AAA 2 YEAR
GUARANTEE**

See Page 415 For Terms



METER

Shows relative signal strength of received AM or FM station. Also shows when an AM station is properly tuned in.

AUTOMATIC FM STEREO INDICATOR

Lights up when you are tuned to a stereo broadcast (with Mode in "Stereo.")

"ACRITUNE"


Indicator lamp lights when receiver is precisely tuned to a FM station.



7-GANG VARIABLE FM/AM TUNING CAPACITOR
Unusually high Selectivity is achieved by the use of a 4-gang variable capacitor in the FM front-end. The AM tuner features a 3-gang variable capacitor resulting in excellent AM selectivity.



COLORLED LIGHTS indicate Phone, Auxiliary, or Tape Monitor settings of Selector and Mode switch.



PUSHBUTTON FUNCTION

SWITCHES for Loudness, Low Filter, High Filter, and Mute for minimizing interference and minimizing noise between FM stations.



LR-1000B with **ACRITUNE**
Precision Tuning Indicator

259.95
WITH CASE

No Money Down! •

**Lafayette Deluxe 150-Watt Solid-State
AM/FM Stereo Receiver**

4 IC's + 32 Transistors + 5 FET's + 29 Diodes

- 150 Watts \pm 1 db, 120 Watts IHF Output Power at 4 ohms
- IHF Sensitivity 1.65 μ V
- Interstation FM Muting Control Switch
- Automatic FM Stereo Switching
- Center Channel Output
- Built-In FM Antenna Plus Flexible Swivel-Mount AM Antenna
- High/Low Phono Sensitivity Switch
- Front Panel Stereo Headphone and Tape Output Jacks

Every performance feature that you'd expect to find along with many extras to obtain the superb character of brilliant sound. The LR-1000B features the new space age miracle, integrated Circuits (IC's), plus FET's in the tuner front end to assure outstanding selectivity, stability and superior capture ratio. Advanced circuitry is complemented by all the controls you need to adjust the sound to your particular taste. Fine features include ACRITUNE indicator for fool-proof FM visual tuning accuracy, special high and low frequency switchable noise filters, front panel 4 and 8 ohm headphone output jack for silent listening, tape output jack for direct tape recording, tape monitor plus tape monitor illuminated jewel indicator, loudness

switch, signal strength tuning meter, colored function lights, and automatic FM stereo indicator light. Complete input and output facilities designed for easy installation and connection to any program source or external component. Has 1 switched and 1 unswitched AC receptacle. The LR-1000B's professional styling is enhanced by an attractive 2 tone anodized extruded aluminum front panel, and a simulated walnut grain metal case. For 105-120 VAC, 50/60 Hz. Size: 15 7/8" x 5 x 13 1/2" (incl. rear projections). Imported.
 89 R 01384W Shpg. wt., 31 lbs.; Net **259.95**
 Offered in Walnut Wood Cabinet For LR-1000B. Shpg. wt., 38 lbs.; Net **279.95**
 21 R 01574W

SPECIFICATIONS

FM TUNER SECTION—4 Gang Tuning Condenser, Usable FM Sensitivity IHF: 1.65 μ V; FM Stereo Separation: 100% @ 100 Hz. Sigmatic Distortion @ 100% Modulation: 0.3%; Capture Ratio: 1.5db; Cross Modulation Index: 90db; FM Antenna Impedance: 300 ohms balance; AM Section: 3 gang tuning condenser. IHF Terminal Sensitivity: 18 μ V.

AMPLIFIER SECTION—Power: 150 watts \pm 1db, 120 watts IHF at 4 ohms; Resistor: 22-22,000 Hz—1db Harmonic Distortion; less than 1% at rated maximum output. Hum and Noise: Phono (mag) —60db; auxiliary —75db. Power Bandwidth: 13-35,000 Hz. Input Sensitivity: Phono (high) mag. 2.2mv., cer. 75 mv.; Phono (low) mag. 7 mv., cer. 190 mv.; Tape-in 500 mv.; Aux. 250mv. Output Imped.: 4-8 ohms; 8 ohm stereo headphones.

See Pages 42 and 43 for LR-775 2-Channel and Derived 4-Channel Stereo HI-FI Systems with LR-1000B

Amazing Performance
plus
Space Age Styling of
Distinction!

AAA 2-YEAR
GUARANTEE
See Page 419 For Terms



Illuminated Tuning Meter for accurate tuning of FM and AM stations.



Automatic FM Stereo Headphone indicator light and lights indicate when you tune to a stereo station.



Front Panel Stereo Head-phones, removable, and lights indicate when you tune to a stereo station.



Speaker Made switches sound to main or remote speakers separately or to both sets simultaneously, plus a headphone only position for private listening.

Pushbutton Function Switches for activation of Loudness, Stereo or Monaural, Tape Monitor, or High Filter functions.



LR-775

ONLY
199.95
WITH
CASE

Lafayette 100-Watt Solid State AM/FM Stereo Receiver

4 INTEGRATED CIRCUITS, + 4 FET'S + 24 TRANSISTORS + 25 DIODES + 2 THERMISTORS

- 100-Watts ± 1 db, 80-Watts IHF, at 4 Ohms
- 4-Gang FM Tuning Condenser
- Fused Output Transistors

This 100-watt stereo receiver is one of Lafayette's finest with its distinctive styling and advanced solid-state circuitry truly giving you top-notch stereo performance. The large tuning panel is black when the power is off, thus blending harmoniously even with the most luxurious decors. When the power is turned on, the tuning meter, FM Stereo Indicator and AM and FM dials light up and are revealed with the utmost clarity, thus enhancing the attractive appearance of the LR-775 and that of the room in which it performs. Another styling innovation is the aluminum and black knobs which contrast nicely with the gold anodized brushed aluminum panel trim. The LR-775's sensitive FM Stereo circuitry will receive even the weakest signals while maintaining excellent fidelity and freedom from distortion. The AM tuner section offers very good selectivity plus a built-in, flexible-mount ferrite loopstick

- Automatic FM Stereo Switching and Stereo Indicator Light
- Front and Rear Panel Tape Output Jacks

antenna for optimum sensitivity. A meticulously designed amplifier section gives faithful reproduction with more than adequate volume from any program source. Output transistors are used for full power and a selector switch for the illustrated selected features the LR-775 also has a selector switch for Aux, Phono, FM, MPX Filter, and AM; Front and rear panel jacks for tape outputs; Rear panel stereo inputs for magnetic and ceramic phono, Aux, Tape Record, and Tape Play; and one switched plus one unswitched AC convenience outlets. Complete with built-in FM antenna and provision for external AM and FM antennas. Power requirements: 105-120 VAC, 50/60 Hz. Size: 14 $\frac{1}{2}$ "x9 $\frac{1}{2}$ "x4 $\frac{1}{2}$ " 10 $\frac{1}{4}$ " D. Imported. Shag. wt. 20 lbs. 99 R 02186W No Money Down

Net 199.95
Net 199.95

21 R 01681WX Oiled Walnut Wood Cabinet for LR-775. 6 $\frac{1}{2}$ lbs. Net 19.95

AMPLIFIER: Power Output: 100 Watts ± 1 db, 80 watts IHF, at 4 ohms; Frequency Response: 20-20,000 Hz ± 1 db; Power Bandwidth: 15-30,000 Hz; Harmonic Distortion: Less than 1% at rated output, 0.07% at 1 watt; Hum and Noise: Aux. —75db, Phono (mag) —63db; Input Sensitivity: Phono (mag) 2.3 mv, (ceramic) 80 mv, Aux. 250 mv, Tape Monitor, 500 mv; Output Impedance: 4-8 ohm speaker (main and remote), Headphone jack impedance: 8 ohms.

SPECIFICATIONS

TUNER, FM: 4-Gang Tuning Condenser; 88-108 MHz; IHF Sensitivity: 1.7 μ v; S/N Ratio: 75db (100% Mod); Distortion: 0.25% (at 400 Hz 100% Mod); Capture Ratio: 1.5db; Stereo MPX Separation: 40db (400 Hz); Cross Modulation Index: 90db; Image Rejection: 80db; **TUNER, AM:** 5-Gang Tuning Condenser; 550-1630 kHz; IHF External Antenna Sensitivity: 20 μ v; Image Rejection: 55db.

Compare the Features! Compare the Price!

ONLY

149⁹⁵

With Case

AAA 2-YEAR

GUARANTEE

See page #15 for terms.



LR-100

LAFAYETTE 50-Watt Solid-State AM/FM Stereo Receiver

SPECIFICATIONS

TUNER SECTION

FM: 4 Gang Tuning Condenser; Tuning Range: 88-108 MHz; HF Sensitivity: 2.5µv, S/N Ratio: -60 db; Distortion: 0.1%; Stereo Capture Rate: 5% Steady; Mod. Capture: 35 db at 400 Hz; Selectivity: 40 db; AM: 3 Gang Tuning Condenser; Tuning Range: 535-1605 kHz.

AMPLIFIER SECTION

Power Output: 50 watts ±1 db at 4 ohms, 40 Watts HF at 4 ohms; Frequency Response: 35-30,000 Hz; Power Bandwidth: 20-20,000 Hz ±1.5 db; Harmonic Distortion: 0.1% at 100m; Inputs: 75 db (Aux), 60 db (Line), 60 db (Mag. Phono), Input Sensitivity: Mag. Phono, 2.3mv; Ceramic Phono, 80 mv; Aux., 250mv; Output Impedance: 4-8 ohms; 8 ohm headphones.

50-Watts ±1 db Stereo Amplifier

- Automatic FM Stereo Switching and Stereo Indicator Light
- 4-Gang FM Tuning Condenser
- Illuminated Signal Strength Tuning Meter

An outstanding hi-fi value, the Lafayette LR-100 features deluxe decorator-designed styling plus full-range, full-fidelity sound from thrilling stereo or mono FM broadcasts, AM broadcasts, as well as phono or tape. A full complement of front panel tone controls (bass, treble, volume/balance) and push-button switches (loudness, stereo/mono, high filter) adds versatility to be tailored to the actual characteristics of any type of audio source. The sound characteristics of virtually any phono cartridge, tape player or speaker system—performance features normally included only on much more expensive hi-fi components. Excellent sensitivity, selectivity, and capture ratio are inherent in the technologically advanced and long-life circuitry of the LR-100. You will be delighted with the clear

- 33 Transistors, 25 Diodes, 2 Thermistors
- Built-in FM plus Flexible-Mount AM Antenna
- Front and Rear Panel Tape Output Jacks
- Front Panel Stereo Headphone Jack
- High Frequency Filter

reception of the weak as well as the stronger stations! The amplifier section has power to spare and can easily drive main and remote stereo speakers to produce clean, room-filling, wall-to-wall sound. Some additional fine features of the LR-100 are: automatic stereo switching; signal-strength tuning meter for more accurate tuning; MPX filter; FM stereo decoder; 4-channel stereo recording; 4-speaker outputs for easier long recording; stereo speaker outputs for enjoyable private listening; fused speaker outputs; distinctively styled front panel and attractively simulated walnut grain vinyl-clad metal case. Size: 14½" x 4½" x 10½" D. For 105-120 VAC 50/60 Hz. Imported. Shug. wt. 19 lbs.

99 R 02214W Net 149.95

See Pages 38 and 39 for LR-100 2 Channel and Derived 4 Channel Stereo Hi-Fi Systems



4-gang FM Tuning Condenser
In extra sensitive FM Front End provides outstanding sensitivity and selectivity.



FM Stereo Indicator Light
Works in conjunction with automatic FM Stereo Switching Circuit to indicate reception of FM stereo station.



Illuminated Signal Strength Tuning Meter
Calibrated from 1-10, permits accurate tuning of FM or AM.



Speaker Mode Switch
Switches sound to main or remote speakers separately, or simultaneously, plus a headphone only position.

Lafayette Brings Stereo Enjoyment To Everyone!

**SENSATIONAL
LOW PRICE!**

ONLY

119⁹⁵
WITH CASE

AAA 2-YEAR

GUARANTEE

LR-75

See page 415 for terms.



LAFAYETTE 25-Watt Solid-State AM/FM Stereo Receiver

- 25-Watts \pm 1 db Stereo Amplifier
- Automatic FM Stereo Indicator
- Built-In FM plus Flexible-Mount AM Antennas
- Front Stereo Headphone Jack
- Front Panel Tape Output Jack

NOW AT A SENSATIONALLY LOW PRICE for the music lovers who want the "very best" but must consider their budgets, the LR-75 is the modern solution to big AM/FM stereo sound at a low price! All solid-state circuitry (24 transistors, 21 diodes) delivers clean, crisp stereo realism with a maximum degree of freedom from unwanted interference and noise. Among the many convenient features there are **AUTOMATIC STEREO/MONO SWITCHING** and a simultaneously **STEREO INDICATOR LIGHT** that automatically signals the presence of an FM stereo broadcast. The LR-75 features the following desirable controls: **PHONO/MX SELECTOR** (Auxiliary, Phono, CER., FM, MPX Filter, and AM); **BASS** and **TREBLE** controls; dual Concentric

See Page 37 For LR-75 Stereo Hi-Fi Systems

SPECIFICATIONS

AMPLIFIER SECTION
Power Output: 25 watts \pm 1 db, 20-Watts (1HF); Power Bandwidth: 40-25,000 Hz; Frequency Response: 20-20,000 Hz; \pm 1 db; Harmonic Distortion: 0.2% at 1-watt; Input Sensitivity: AUX., 250 mV; Phono CER., 240 mV; Hum and Noise: AUX., 55 db; Phono CER., 55 db; Impedance: 4-8 ohm.

TUNER SECTION
FM—88-108 MHz; IHF Sensitivity: 3.5 μ V; S/N Ratio: —50 db; Distortion: 0.7% at 100% mod.; Spurious: R, MPX Separation: 80 db; 20 db @ 400 Hz; Alternate Channel Selectivity: 35 db; Tuning AM—535-1605KHz.; 3 Gang Tuning Capacitor.

Light Indicator works when receiver has been tuned to stereo station and receiver has switched to FM Stereo operation.



Two-speaker system selected. You can turn 'On or Off' either Main, and Receiver has Remote or both of two stereo speaker systems.



Front panel stereo jack provides private listening.



Automatic LOCK (AFC) assures drift-free FM listening.



Loudness control to provide tonal balance at low volume.



SAVE 7.00
From Individual Catalog Prices

Lafayette 4-Channel Stereo Adapter with 2 Lafayette Criterion 25A Speaker Systems
COMPLETE PACKAGE 62⁸⁵



SAVE 10.00
From Individual Catalog Prices

Lafayette 4-Channel Stereo Adapter with 2 Lafayette Criterion 50A Speaker Systems
COMPLETE PACKAGE 79⁸⁵

MONEY SAVING PACKAGES
Featuring the **LAFAYETTE 4-CHANNEL STEREO ADAPTER**
See Page 468 for Complete Description of the Lafayette 4-Channel Stereo Adapter



SAVE 15.00 From Individual Catalog Prices
Lafayette 4-Channel Stereo Adapter with 2 Lafayette Criterion 100B Speaker Systems
COMPLETE PACKAGE 114⁸⁵




SAVE 20.00 From Individual Catalog Prices
Lafayette 4-Channel Stereo Adapter with 2 Lafayette Criterion 4X Speaker Systems
COMPLETE PACKAGE 168⁸⁵

Convert to 4 Channel with These Money Saving Packages

SAVE an ADDITIONAL 9.00 When You Buy the NEW LAFAYETTE/Pickering Phase 44 Elliptical Diamond Needle Cartridge with the Above Package

See page 83 for description of Lafayette/Pickering Phase 44 Stereo Cartridge.



SAVE 7.00 When You Buy the Lafayette 4-channel adapter and 2 Lafayette Criterion 25A 2-way 2-speaker systems. (See page 56 for description of the 25A's). Shpg. wt., 28 lbs.
99 R 99855WMM No Money Down* Net 62.85
Same package as above plus Deluxe Lafayette/Pickering Phase 44 Elliptical Diamond Needle Cartridge. Shpg. wt., 28 lbs.
99 R 99863WMM No Money Down* Net 98.80

SAVE 15.00 When You Buy the Lafayette 4-Channel adapter and 2 Lafayette Criterion 100B 3-way 3-speaker systems (See page 58 for description of the 100B's). Shpg. wt., 65 lbs.
99 R 99897WXM No Money Down* Net 114.85
Same package as above plus Deluxe Lafayette/Pickering Phase 44 Elliptical Diamond Needle Stereo Cartridge. Shpg. wt., 65 lbs.
99 R 99905WXM No Money Down* Net 150.80

SAVE 10.00 When you Buy the Lafayette 4-channel adapter and 2 Lafayette Criterion 50A deluxe 2-way 2-speaker systems (See page 57 for description of the 50A's). Shpg. wt., 47 lbs.
99 R 99871WUXM No Money Down* Net 79.85
Same package as above plus Deluxe Lafayette Pickering Phase 44 Elliptical Diamond Needle Stereo Cartridge. Shpg. wt., 47 lbs.
99 R 99889WUXM No Money Down* Net 115.80

SAVE 20.00 When You Buy the Lafayette 4-channel adapter and 2 Lafayette Criterion 4X 4-way 4-speaker systems (See page 60 for description of the Criterion 4X's). Shpg. wt., 83 lbs.
99 R 99830WXM No Money Down* Net 168.85
Same package as above plus Deluxe Lafayette/Pickering Phase 44 Elliptical Diamond Needle Stereo Cartridge. Shpg. wt., 83 lbs.
99 R 99848WXM No Money Down* Net 204.80

CONVERT to a Discrete 4-Channel Stereo System with the new Lafayette LA-424 QUADNAURAL AUXILIARY AMPLIFIER

AAA 2-YEAR GUARANTEE

See Page 415 for Terms



ONLY

59⁹⁵

No Money Down*

OUTSTANDING FEATURES

- Exclusive Master Gain Control For All 4-Channels of Both Amplifiers
- Dual Bass and Treble Controls For 2 Rear Channels
- Main and Remote Speaker Selection For 2 Rear Channels
- Loudness Control to Enhance Bass Quality at Low Listening Levels
- Comes Supplied with All Interconnecting Amplifier Cables
- Power Output 50 Watts \pm 1 db


• Your present 2-channel stereo system is not obsolete. Just add the LA-424 Quadnaural Auxiliary Amplifier and 2 more speakers and thrill to the spectacular realism of discrete 4-channel sound reproduced thru 4 separate amplifiers.

• The Quadnaural Amplifier also has built-in Lafayette 4-channel "Composer" circuitry to derive 4-dimensional sound from 2-channel stereo records, tapes, and FM broadcasts without the need for any additional external adapter.

The LA-424 Quadnaural Auxiliary Amplifier has been designed for converting regular 2-channel stereo systems into magnificent discrete 4-channel stereo systems. It cannot be used as a regular 2-channel stereo amplifier by itself. With the addition of the LA-424 and 2 more speakers you are now ready to plug-in a discrete 4-channel input source such as a 4-channel 8-Track cartridge or reel-to-reel deck. The LA-424 has another exclusive feature built-in, the Lafayette Composer Circuit. This enables the listener to derive 4-dimensional sound from 2-channel stereo records, tapes, and FM broadcasts without the need for any additional external amplifier or adapter. Specifications: Power output: 50 watts \pm 1 db, 40 Watts IHF; Frequency Response: 20-20,000 Hz \pm 1.5db; Harmonic Distortion 0.07% at 1 kHz at 1-watt; Channel Separation: 60db at 1 kHz; Power Bandwidth 35-30,000 Hz; Speaker Impedance 4, 8, 16 ohms; Stereo Headphones, 8-ohms. Controls: Dual Master Volume—Front and Rear, Dual Bass and Treble, Switches for "Composer" On/Off, Mono/Stereo Mode, Loudness On/Off, Speakers—Main/Remote. Front panel headphone jack. 1-AC Convenience Output (unswitched) on rear panel. Only 10%W x 3 1/2"H x 8 3/4"D. Complete with simulated walnut vinyl-clad metal case. For 105-120 VAC, 50/60 Hz with AC power fuse. Imported. 99 R 02727W No Money Down*. Shpg. wt., 10 lbs. Net 59.95

DISCRETE 4-CHANNEL SYSTEM HOOK-UP

Front Speakers



*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 19

YOU CAN DEPEND ON *Lafayette*[®]

3 CONVENIENT WAYS TO SHOP

by mail

Shop in the comfort of your home at any time no matter where you live. Simply fill in order blank and mail. See pages 416 and 417 for helpful ordering information.

in person

Visit any of our 53 large modern Lafayette Stores listed below and on the facing page, or any of the 260 Associate Stores from Coast to Coast. See the Catalog come to Life and many other exciting displays. Consult your telephone Directory for the Store nearest you.

and by phone

Enjoy the extra convenience of shopping by phone. Simply dial 516-921-7500. Just give your C.O.D. order to our personal service shopper and your shopping is done, quickly and easily.

OUTSTANDING QUALITY

Outstanding quality is the hallmark of all Lafayette products. Exacting specifications, thorough inspection and double checking are your assurances of the best merchandise for the price.

WIDEST SELECTION

Widest selection of the finest hi-fi, stereo, components, systems, C.B., and radio electronic equipment is at your fingertips in this catalog, along with tape-recorders, musical instruments, accessories, and useful items of all kinds.

BETTER SERVICE

To serve you better, automated computer order filling system with the latest in mail order processing means most orders are shipped within 24 hours.

LOW PRICES

Low prices are assured by Lafayette's huge buying power combined with minimum overhead and operating costs. We try to price every item in this catalog to be as low or lower than the same merchandise in any other mail order catalog. We will meet any price you find lower than ours that is being honored by any competitor.

LIBERAL GUARANTEES

See page 415 for Lafayette's Liberal Guarantees.

MAIL ORDER and SALES CENTER

111 Jericho Turnpike

Syosset, L. I., N. Y. 11791

All Departments 516 921-7700



C.O.D. Orders Only 516 921-7500

53 CONVENIENT SHOPPING LOCATIONS

NEW YORK

BROOKLYN 2265 Bedford Ave. (cor. Snyder Ave.) Phone: 212 469-8900	11226	NEW ROCHELLE 278 North Ave. (Opp. Macy's Mall) Phone: 914 235-5101	10801	SCARSDALE 691 Central Ave. (1/2 mile north of Ardsley Rd.) Phone: 914 472-2700	10583
BUFFALO (Amherst) 3600 Sheridan Dr. (At Millersport Hwy.) Phone: 716 833-2826	14226	N.Y.C.—45th STREET 49 West 45 St. (Between 5th-6th Aves.) Phone: 212 757-3121	10036	SYOSSET 111 Jericho Turnpike (West of So. Oyster Bay Rd.) Phone: 516 921-7700	11791
HEMPSTEAD 120 N. Franklin St. (2 blocks N. of Fulton Ave.) Phone: 516 538-6464	11550	N.Y.C.—UNION SQUARE 17 Union Square West (cor. 15th St.) Phone: 212 924-4433	10003	SYRACUSE (WEST) 3548 West Genesee St. (Opp. Fairmont Fair) Phone: 315 488-4921	13219
JAMAICA 92-35 Merrick Blvd. NEW (Bet. Jamaica & Archer Aves.) Phone: 212 291-7000	11433	N.Y.C.—WARREN ST. 45 Warren St. (Between Church and W. Broadway) Phone: 212 964-0334	10007	SYRACUSE (EAST) 2544 Erie Blvd. East (East of Midler Ave.) Phone: 315 446-3800	13224
LAKE GROVE 2848 Middle Country Rd. (Rt. 25—1/4 mile E. of Smithhaven Mall) Phone: 516 585-3600	11755	ROCHESTER-IRONDEQUOIT 999 Ridge Road East (Carter St. exit of Keeler Expressway) Phone: 716 467-1310	14621		
LYNBROOK 381 Sunrise Highway (2 miles East of Green Acres) Phone: 516 887-9800	11563	ROCHESTER—PITTSFORD 3330 Monroe Av. (Adjoining Arlan's) (Opposite Pittsford Plaza) Phone: 716 586-6331	14618		

For Store Hours —
Check The Store
In Your Location

53 CONVENIENT SHOPPING LOCATIONS

MASSACHUSETTS

- BOSTON** 02215
584 Commonwealth Ave.
(½ block above Kenmore Sq.)
Phone: 617 267-8900
- NATICK** 01760
1400 Worcester St.
(Rt. 9 opp. Shopper's World)
Phone: 617 875-6146
- SAUGUS** 01906
Saugus Plaza Shopping Center
(Rt. 1 & Walnut St.)
Phone: 617 233-6710
- WEST ROXBURY** 02132
1530 V. F. W. Parkway
(1 mile north of Dedham Mall)
Phone: 327-0300

OHIO

- COLUMBUS** 43228
4676 West Broad St. (Adj. Zoyres)
(Lincoln Plaza Shopping Center)
Phone: 614 878-6462
- COLUMBUS** 43213
Great Eastern Shopping Center
(Hamilton Rd. & Main St.)
Phone: 614 861-8660
- COLUMBUS** 43224
3395 Cleveland Avenue
(Northern Lights Shopping Center)
Phone: 614 267-3106
- MENTOR** 44060
7531 Mentor Ave.
(¼ Mile W. of Great Lakes Shopping Center)
Phone: 216 951-8400
- NORTH OLMSTED** 44070
Great Northern Blvd. (At Brookpark Rd.)
NEW (Olmsted Plaza—Adj. to Tops)
Fall 1971
- PARMA-HEIGHTS** 44130
6425 Pearl Road
(3 Blocks W. of Stumph Rd.)
Phone: 216 884-2393
- TOLEDO** 43613
Miracle Mile Shopping Center
(Jackman and Lasky Roads)
Phone: 419 479-9167
- TOLEDO**
Woodville Rd.
(Opp. Woodville Mall)
Winter 1971
NEW
- WARRENSVILLE HTS.** 45222
Emery Rd. at North Field Rd.
NEW (Across from Uncle Bills)
Fall 1971

CONNECTICUT

- BRIDGE PORT** 06603
Lafayette Plaza
NEW (Exit 27 on Conn. Tpke.)
Fall 1971
- HAMDEN** 06514
2100 Dixwell Ave.
(Hamden Plaza Shopping Center)
(Adjoining Pegnotaro's)
Phone: 203 248-2182
- WEST HARTFORD** 06117
357 North Main St. (Cor. Albany Ave.)
Bishop's Corner Shopping Center
Phone: 203 236-0693

PENNSYLVANIA

- BRIDGEVILLE** 15017
Washington Pike (Adj. Zoyres)
(Great Southern Shopping Center)
Phone: 412 221-7888
- KING OF PRUSSIA** 19406
King of Prussia Shopping Center
(Routes 202 and 23)
Phone: 215 265-3300
- LANCASTER** 17603
2152 Lincoln Plaza
(Adjoining Two Guys)
Phone: 717 397-3681
- MONROEVILLE** 15146
4045 William Penn Highway
Monroe Plaza Shopping Center
Phone: 412 373-0060
- PHILADELPHIA** 19095
8156 Ogontz Ave.
Wyncote (Cheltenham Township)
(Opp. Cheltenham Shopping Center)
Phone: 215 885-2140
- PITTSBURGH** 15237
North Hills Village Shopping Ctr.
4801 McKnight Road
Phone: 412 366-0810

ILLINOIS

- ARLINGTON HTS.** 60000
Rand Rd. (At Arlington Hgts. Rd.)
(2 Mi. N. of Randhurst Shopping Center)
NEW North Point Shopping Center
Fall 1971
- CHICAGO** 60652
Ford City Shopping Center
(7601 South Cicero Ave., Adj. Weiboldst.)
Phone: 312 767-5400
- MORTON GROVE** 60053
7032 Golf Road
(Golfview Shopping Center)
Between Harlem & Waukegan Rd.
Phone: 312 966-4034

NEW JERSEY

- NEWARK** 07102
24 Central Ave. (west of Broad St.)
Phone: 201 622-1661
- PARAMUS** 07652
182 Route 17
(1 mile north of Garden State Plaza)
Phone: 201 261-8800
- PLAINFIELD** 07060
139 W. 2nd St.
(1 block east of Front St.)
Phone: 201 756-5100
- TOTOWA** 07512
410 Route 46
(½ Mile E. of Willow Brook Shopping Center)
Phone: 201 785-1763

MARYLAND

- BALTIMORE/CATONSVILLE** 21227
NEW Rolling Rd. (No. of Rt. 40)
Fall 1971
- GLEN BURNIE** 21228
316 S. Ritchie H'way
Glen Burnie Shopping Center
(So. of Old Annapolis Rd.)
Phone: 301 760-5700
- MT. RAINIER/HYATTSVILLE** 20822
3191 Queens Chapel Rd. (Rt. 500)
At Chillum Ave.
Phone: 301 779-7020
- ROCKVILLE** 20852
824 Rockville Pike
NEW (So. of Vierns Mill Rd.)
Fall 1971
- TOWSON** 21204
815 Taylor Avenue
(Loch Raven Plaza)
Phone: 301 825-7750

VIRGINIA

- FALLS CHURCH** 22044
Plaza 7 Shopping Center
(cor. Wilson & Roosevelt Blvd.)
(across from 7 corners)
Phone: 703 534-5772

GEORGIA

- ATLANTA** 30327
47 West Paces Ferry Road N.W.
West Paces Ferry Shopping Center
(opposite Sear's)
Phone: 404 237-8206
- DECATUR** 30032
4610 Memorial Drive
(Grant City Shopping Center)
Phone: 404 292-3474

WOULD YOU LIKE TO OWN A LAFAYETTE ASSOCIATE STORE?
(See Insert Card next to Page 362)

OPEN AN EASY-PAY CREDIT ACCOUNT TODAY

EXTENDED PLAN

**TAKE UP TO
2 Years To Pay**

2 EASY PAY CREDIT PLANS

TO SUIT YOUR INDIVIDUAL NEEDS
Pay balance in 30 days and save the entire FINANCE CHARGE.

STANDARD PLAN

**TAKE UP TO
16 Months To Pay**

NO MONEY DOWN

- It's easy to open a credit account. Simply fill in application on back of order blank when you send your order.
- Add-on any time you like. No money down and usually at no increase in monthly payment.

EASY PAY PAYMENT SCHEDULE

\$250.01 to \$500.00		STANDARD PLAN		EXTENDED PLAN	
If Unpaid Balance (Amount Financed) Is From	To	Add for FINANCE CHARGE	Monthly Payment Is	Add for FINANCE CHARGE	Monthly Payment Is
\$490.01	\$500.00	\$64.75	\$35.00	\$98.00	\$25.00
480.01	490.00	63.50	34.50	96.00	24.50
470.01	480.00	62.25	33.50	94.00	24.00
460.01	470.00	61.00	33.00	92.00	23.50
450.01	460.00	59.50	32.50	90.00	23.00
440.01	450.00	58.25	31.50	88.00	22.50
430.01	440.00	57.00	31.00	86.00	22.00
420.01	430.00	55.75	30.00	84.00	21.50
410.01	420.00	54.25	29.50	82.00	21.00
400.01	410.00	53.00	29.00	80.00	20.50
390.01	400.00	51.75	28.00	78.00	20.00
380.01	390.00	50.50	27.50	76.00	19.50
370.01	380.00	49.00	26.50	74.00	19.00
360.01	370.00	47.75	26.00	72.00	18.50
350.01	360.00	46.50	25.00	70.00	18.00
340.01	350.00	45.25	24.50	68.00	17.50
330.01	340.00	43.75	24.00	66.00	17.00
320.01	330.00	42.50	23.00	64.00	16.50
310.01	320.00	41.25	22.50	62.00	16.00
300.01	310.00	40.00	22.00	60.00	15.50
290.01	300.00	38.50	21.00	58.00	14.50
280.01	290.00	37.25	20.00	56.00	14.00
270.01	280.00	36.00	19.50	54.00	13.50
260.01	270.00	34.50	19.00	52.00	13.00
250.01	260.00	33.25	18.00	50.00	12.50

\$100.01 to \$250.00		STANDARD PLAN		EXTENDED PLAN	
If Unpaid Balance (Amount Financed) Is From	To	Add for FINANCE CHARGE	Monthly Payment Is	Add for FINANCE CHARGE	Monthly Payment Is
\$240.01	\$250.00	\$32.00	\$17.50	\$48.00	\$12.00
230.01	240.00	30.50	17.00	46.00	11.50
220.01	230.00	29.25	16.00	44.00	11.00
210.01	220.00	28.00	15.50	42.00	10.50
200.01	210.00	26.50	15.00	40.00	10.00
195.01	200.00	25.75	14.50	39.00	9.75
190.01	195.00	25.25	14.00	38.00	9.50
185.01	190.00	24.50	13.75	37.00	9.25
180.01	185.00	23.75	13.50	36.00	9.00
175.01	180.00	23.25	13.00	35.00	8.75
170.01	175.00	22.50	12.50	34.00	8.50
165.01	170.00	22.00	12.00	33.00	8.25
160.01	165.00	21.25	11.50	32.00	8.00
155.01	160.00	20.50	11.00	31.00	7.75
150.01	155.00	20.00	10.75	30.00	7.50
145.01	150.00	19.25	10.50	29.00	7.25
140.01	145.00	18.50	10.50	28.00	7.00
135.01	140.00	16.75	10.50	27.00	6.75
130.01	135.00	16.25	10.25	26.00	6.50
125.01	130.00	14.50	10.25	24.00	6.50
120.01	125.00	14.00	10.00	23.00	6.25
115.01	120.00	12.50	10.00	21.00	6.25
110.01	115.00	12.00	10.00	20.00	6.00
105.01	110.00	10.50	10.00	18.35	6.00
100.01	105.00	9.25	10.00	17.50	5.75

The ANNUAL PERCENTAGE RATE of each FINANCE CHARGE set forth in the above tables is 17.75%. The number of payments will be the Total of Payments (Amount Financed plus the FINANCE CHARGES) divided by the amount of one monthly payment.

\$50.01 to \$100.00		STANDARD PLAN			EXTENDED PLAN		
If Unpaid Balance (Amount Financed) Is From	To	Add for FINANCE CHARGE	Monthly Payment Is	ANNUAL PERCENTAGE RATE	Add for FINANCE CHARGE	Monthly Payment Is	ANNUAL PERCENTAGE RATE
\$95.01	\$100.00	\$9.25	\$10.00	18.50%	\$15.65	\$5.50	17.50%
90.01	95.00	9.25	9.75	19.50	14.85	5.50	17.50
85.01	90.00	9.25	9.50	22.50	13.45	5.25	17.75
80.01	85.00	9.25	9.25	23.75	12.00	5.25	17.75
75.01	80.00	9.00	9.00	24.50	10.70	5.00	17.75
70.01	75.00	8.40	8.00	24.50	10.00	5.00	18.75
65.01	70.00	7.80	7.50	24.50	10.00	5.00	21.25
60.01	65.00	7.20	7.00	24.50	10.00	5.00	24.50
55.01	60.00	6.65	6.50	24.50	8.55	5.00	24.50
50.01	55.00	6.10	6.00	24.50	7.25	5.00	24.50

\$20.00 to \$50.00		STANDARD PLAN			
If Unpaid Balance (Amount Financed) Is From	To	Add for FINANCE CHARGE	Monthly Payment Is	ANNUAL PERCENTAGE RATE	
\$45.01	\$50.00	\$6.00	\$5.00	24.50%	
40.01	45.00	5.25	4.75	26.00	
35.01	40.00	4.75	4.25	26.75	
30.01	35.00	4.50	3.70	29.25	
25.01	30.00	3.50	3.35	30.00	
20.00	25.00	3.00	2.70	32.00	

OVER \$500.00. Please write for terms for amounts to be financed over \$500.00.
minimum ORDER - \$30
minimum "ADD-ON" - \$20

Number of payments will be Total of Payments (Amount Financed plus the FINANCE CHARGE) divided by the amount of one monthly payment.

MAKE LAFAYETTE YOUR ONE DEPENDABLE SOURCE FOR EVERYTHING IN ELECTRONICS

COMMERCIAL SALES DEPARTMENT

The Commercial Sales Department services state, county, and Purchasing Departments; educational and medical facilities, police fire, and civil defense departments; churches, civic and social organizations; as well as commercial and manufacturing

organizations. A special staff is prepared to give advice, quotations and prompt service.

Original electronic equipment manufacturers consult our Industrial Electronics Division.

For Personalized Service, Phone or Write
Lafayette Commercial Sales Department
P.O. Box 260 Syosset, L.I., N.Y. 11791
Phone (516) 921-7700

INDUSTRIAL ELECTRONICS DIVISIONS

Lafayette's Industrial Electronics Divisions, SPECIALIZE IN SEMI-CONDUCTORS and TANTALUM CAPACITORS. Overnight delivery can be made to all parts of U.S.A. via AIR CARRIERS. Large OEM quantity prices and availability from Lafayette's

vast inventories can fill your production needs immediately. In addition to the material in this catalog, the following are some of the leading lines of semi-conductors supplied by Lafayette:

IC's and SEMICONDUCTORS

- Texas Instruments • Dickson
- Amelco • Teledyne • Continental Devices • R.C.A. • TRW/IRC • Micro-semiconductors • Silicon Transistor* • Sensitron

Lafayette supplies from stock the above brands and others: JAN, JAN-TX, S1N type transistors and diodes.

HEAT SINKS

- Thermalloy

TANTALUM CAPACITORS (CSR types)

- Dickson • Mallory • Sprague

VOLTAGE REGULATORS*

- General Radio Variacs®

SENSING RESISTORS (SENSISTORS®)

- Texas Instruments

For productions quantity OEM needs or for R&D requirements write or phone for complete, expert personalized service.

NEW YORK AREA

1327 Second Avenue
New Hyde Park, L. I., N. Y. 11040
Phone: (516) 488-6600

NEW ENGLAND AND CANADA

1400 Worcester Street
Natick, Mass. 01760
Phone: (617) 875-6146 (Natick)
(617) 969-6100 (Boston)

IMMEDIATE SHIPMENTS _____

OEM PRICES (always competitive) _____

DEEP INVENTORIES (single shipments) _____

QUALITY PRODUCTS (leading mfrs.) _____

PROMISES KEPT _____

Cut costs of production delays!

Cut costs of purchases!

Cut costs of receiving!

Cut costs of production failures!

Cut costs of expediting!

Enterprise Number In Major Cities

*Natick, Mass. only.

INTERNATIONAL SALES DIVISION

Specializes in export shipment for quantity industrial and dealer orders as well as single item purchases throughout the world. An expert knowledge

of shipping and routing gives you the fastest and most dependable service.

WRITE TO: Lafayette Radio Electronics Corporation
International Sales Division
P.O. Box P
Syosset, L.I., N.Y., U.S.A.

Export Terms

Full payment must accompany your order. Enclose check or draft; or remit international Postal Money Order or confirmed, irrevocable Letter of Credit. All payments should be in U.S. Dollars payable at U.S. Bank. Include 20% above merchandise value to cover international postage, insurance, consular fees and other export shipping and handling costs. Slightly more should be allowed for heavy items and ocean or air freight shipments. These charges can-

not be accurately predetermined—overpayments are promptly refunded.

We reserve the right to route order by the best method when order does not indicate routing or when method suggested is impractical or not possible. All prices F.O.B. our warehouses and subject to change without notice. Enclose Import License and/or Consular Declaration where so required by your government.

WHEN IN JAPAN VISIT OUR TOKYO SHOWROOM

Planet Research Inc.
Minamizuka Bldg.
17-3 Shibuya 2 Chome
Shibuya-Ku, Tokyo, Japan

LAFAYETTE MODEL RK-850 20-WATT SOLID-STATE 8-TRACK STEREO AMPLIFIER/PLAYER

79⁹⁵
Less
Speakers
No Money Down*

with EXCLUSIVE
"REMOVE TAPE
INDICATOR LIGHT"

Insures That You Do Not
Damage The Tape Head
and Your Cartridges

- 20-Watts ± 1 db of Stereo Power
- Inputs For Phono, Tuner, Tape
- Tape Outputs • Stereo Headphone Jack

The RK-850 combines a complete 8-track stereo playback system with a powerful 20-watt full feature stereo amplifier on one integrated chassis. Advanced solid-state circuitry (16 transistors, 3-diodes, and 2-thermistors) provides instant-on play with superb high fidelity performance and reliability. The RK-850's exclusive "Remove Tape" indicator light will provide years of trouble-free 8-track performance . . . no longer will you have to worry about damaging the playback head by leaving a tape inserted in the player after you have turned the power off; a "Remove Tape" bulb illuminates with the power turned off and a tape cartridge left fully inserted in the player. This feature will also preserve the life of your cartridges. Convenient operating features include: Pushbutton Track Selector; 4-Illuminated Track Indicator lights; Selector Switch for choice of inputs: Phono (with ceramic cartridge), Tuner,

- Main and Remote Speaker Switch
- Individual Illuminated Track Indicator Lights
- Pushbutton Track Selector

and Auxiliary; plus tape output for external tape recorder. Pushbutton Switches for: Main and Remote speakers; Loudness Stereo/Mono mode; Power on/off with Pilot Lamp. Separate controls for Volume/Balance, Treble, Bass. Stereo headphone jack for private listening. SPECIFICATIONS: Tape Section—Response: 30 Hz to 10 kHz; S/N: 50 db; Wow and Flutter: 0.3% rms. Amplifier Section—Frequency Response: 20 Hz to 20 kHz; Separation: 60db; H/D: 0.2%; Input Sensitivity (Aux., Tuner, Phono CER.): 250 mV; Hum and Noise (Aux., Tuner, Phono CER.): 70 db. Distinctive styling features a black front panel accented by brushed gold anodized aluminum trim and simulated walnut grain case. For 105/120 VAC., 60 Hz. Imported. Size: 12W x 3 $\frac{3}{4}$ H x 9 $\frac{1}{8}$ "D.

99 R 15836W Shpg. wt., 15 $\frac{1}{2}$ lbs. Net 79.95

20-WATT 8-TRACK STEREO PLAYBACK SYSTEMS



Criterion 2X



RK-850



Criterion 2X

2 CHANNEL
SYSTEM PRICE

98⁹⁵

SAVE 10.90

From Individual
Catalog Prices

2 CHANNEL STEREO SYSTEM

An excellent stereo system that consists of the Lafayette RK-850 20-watt Solid-State 8-Track Stereo Amplifier/Player with its hi-fidelity 8-track tape playback and exclusive "Remove Tape Indicator Light", 2 Lafayette Criterion 2X 2-speaker, 2-way acoustic suspension speaker systems, and speaker cable. Shpg. wt., 31 $\frac{1}{4}$ lbs.

21 R 90437WXM No Money Down* Net 98.95

4 CHANNEL
SYSTEM PRICE

152⁹⁵

SAVE 16.75

From Individual
Catalog Prices



RK-850

Lafayette
4-Channel Adapter

4 CHANNEL DIMENSIONAL STEREO SYSTEM

Enjoy the enriched audio of derived 4-channel dimensional stereo sound! Complete 20-watt 8-track stereo playback system as above PLUS Lafayette 4-Channel Adapter and 2 Lafayette Criterion 2X 2-speaker, 2-way acoustic suspension speaker systems.

Shpg. wt., 52 $\frac{1}{2}$ lbs.
21 R 90445WXM No Money Down* Net 152.95

See Pages 18 and 56 for Details on Above Components.

Criterion 2X

Criterion 2X

LAFAYETTE 160 Watt Solid State Stereo Amplifier

Enjoy the Richness of Superb Stereophonic Sound!



AAA 2-YEAR GUARANTEE

See Page 415 For Terms

Solid-state stereo amplifier with more than adequate audio power for even the lowest efficiency speakers. Gives exemplary frequency response over a wide power bandwidth. Cool transistorized circuitry and compact distinctive styling make this an ideal amplifier for any location in your home. Its full range of controls provide complete operational flexibility. Selector switch permits choice of program source from phono, tuner, auxiliary input or special microphone/musical instrument inputs which allow amplification of microphone and/or instrument in either a mono or stereo mode; Mode switch directs program source into stereo, mono, left or right channel; or tape monitor stereo, left or right modes. Speaker Mode switch; Concentric Balance/Volume, Treble, and Bass controls; Two pushbutton High and Low filter controls, and Two pushbutton Loudness controls that compensate treble and bass loss at low volume. Additional easy access front panel features include: Tape Output, 2 Mic/Musical Inputs, Headphone Output, Pilot Light, and Power switch. Rear panel has provisions for 6 stereo inputs including switchable high and low inputs for magnetic and ceramic phono cartridges, Auxiliary, and Tape input for a tape deck; a stereo output for tape recording through amplifier; Main and Remote Speaker terminals; phono sensitivity switch; and 2 AC convenience outlets (1 switched). For 117 VAC, 50/60 Hz. Size: 13x3 7/8x9 1/4". Imported. Shpg. wt., 19 1/2 lbs. 99 R 02305WX Net \$139.95

Model LA-125B
ONLY **139⁹⁵** with case
NO MONEY DOWN*

- 160 Watts ± 1 db, 125 Watts IHF Output Power into 4 Ohms
- 2 FET's, 18 Transistors, 6 Diodes and 2 Thermistors
- 2 Front Panel Microphone/Musical Instrument Jacks for Voice, and Musical Instrument Inputs
- Main-Remote Speaker Mode Switch
- High Gain Plus Low Gain Phono Inputs
- High Gain Plus Low Gain Tuner Inputs
- Front and Rear Tape Output Jacks
- Low and High Frequency Filters
- Front Panel Stereo Headphone Jack
- Distinctive Styling

SPECIFICATIONS

Power Output: 160 Watts ± 1 db, 125 Watts IHF, at 4 ohms. Frequency Response: 22-20,000 Hz ± 1 db. Power Bandwidth: 13-35,000 Hz. Harmonic Distortion: Less than 1% at rated power; 0.05% at 1 watt (1kHz). Channel Separation: 65 db at 1kHz. Hum and Noise: Aux. and tuner —75 db, mag. phono and

mic/musical —56 db. Input Sensitivity: Aux. 250 mV; Tuner: (high) 750 mV, (low) 115 mV; Tape Play: 500 mV; Phono (mag.): (high) 2.2 mV, (low) 7 mV; Phono (ceramic): (high) 75 mV, (low) 240 mV. Low Frequency Filter: —17 db at 20 Hz. High Frequency Filter: —10 db. at 10 kHz.

See Page 48 for LA-125B 2 Channel and Derived 4 Channel Stereo Hi-Fi Systems



Speaker Mode Switch selects Main or Main and Remote, Remote speakers, or headphones only.



Front panel stereo headphone jack for private listening.



2 Microphone/Musical Instrument jacks conveniently located on front panel.



Pushbutton switches for Low Filter, High Filter, and Loudness for tonal balance at low volumes.

DEPENDABLE
PERFORMANCE

plus
STYLING OF
DISTINCTION

89⁹⁵
No
Money Down*

AAA 2-YEAR GUARANTEE

See Page 415 for Terms

LA-750

Lafayette 100 Watt Solid State Stereo Amplifier

- 100-Watts ± 1 db, 80-Watts IHF at 4 ohms
- Fused Output Transistors
- 2 FET's, 16 Transistors, 6 Diodes, 2 Thermistors
- High Frequency Noise Filter
- Main-Remote Separate/Simultaneous Speaker Switch
- Front Panel Stereo Headphone Jack
- Front and Rear Tape Output Jacks
- Decorator Styling of Distinction

Distinctive styling and performance is the accent with the Lafayette LA-750 stereo amplifier. Black front panel contrasting with gold lettering, aluminum and black knobs surrounded by a brushed gold anodized aluminum trim make this unit stand out and complement most any decor. Features outstanding versatility for even the largest of living rooms as well as for a den or bedroom with maximum fidelity and fine stereo reproduction. All solid state for the utmost in dependable service with such advanced features as push on/push off switches for main power, loudness, stereo/mono, tape monitor, and high filter. . . . plus all the additional controls found on much more expensive units: separate bass, treble, and volume/balance controls for adjusting the amplifier to suit individual tastes. Speaker Mode switch selects main, main plus remote, remote speakers, or stereo

SPECIFICATIONS

Power Output: 100 Watts ± 1 db, 80 Watts IHF at 4 ohms;
Frequency Response: 20-20,000 Hz ± 1 db; **Power Bandwidth:** 15-30,000 Hz; **Harmonic Distortion:** Less than 1% at rated output, 0.07% at 1 Watt; **Channel Separation:** 65 db at 1

See Page 47 for LA-750 2-channel & Derived 4-channel Stereo Hi-Fi Systems.

headphones. Permits maximum enjoyment of selected Hi-Fi programs in any predetermined location in your home. The headphone jack on the front panel has audio power at all times but with the Speaker Mode switch in the "phones" position, only the headphones receive power offering truly private listening. Convenient tape output jacks on front and rear panels. Rear panel includes stereo inputs for Aux., tuner, phono, Tape Play, and Tape Record; Pused right and left channels for protection against shorts and overloads; Remote and main speaker outputs for stereo sound anywhere in your home; 40 ohm extra amplifiers or switches; 1 switched AGC outlet; AC power line; 0-33% trimmer.

99 R 02149W SHPE. wt., 14 lbs. Net 89.95

kHz; Hum and Noise: Aux and Tuner —75 db, Phono (Mag) —63 db; **Input Sensitivity:** Aux 250 mv, Phono (Mag) 2.3 mv, Phono (Cer) 80 mv, Tuner and Tape Monitor 500 mv; **Output Impedance:** 4 and 8 ohm speakers, 8 ohm headphones.

*See Page 22 for Full Credit Details on Easy Pay Plan



Speaker Mode
Switches sound to main or remote speakers separately or to both sets simultaneously, plus a telephone only position.



Tape Out
Front and rear output jacks for recording through your tape recorder or deck.



Pushbutton Function Switches
Activate Loudness, Stereo/Mono, Tape Monitor, and/or High Filter functions.



Input Selector
Selects Auxiliary, Tuner, Magnetic or Ceramic cartridge input.

Phones


Front panel stereo jack for private listening.

Accepts 8 ohm stereo headphones.

LAFAYETTE
Stereo Amplifier

LAFAYETTE

50-Watt Solid State Stereo Amplifier



LA-324A

Only

69⁹⁵

No Money Down*

AAA 2-YEAR GUARANTEE

See Page 415 for Terms

A fine Hi-Fi amplifier at an extremely low price. New distinctive styling features interesting black and silver knobs and switches that contrast neatly with the black and brushed anodized aluminum faceplate. With more than adequate power for any room in the home, the LA-324A will drive most speaker systems to maximum volume while maintaining very good frequency response and low distortion. Its pleasing sound will afford hours of tireless enjoyment to even the most critical listener. 18 transistors, 4 diodes and 2 thermistors are incorporated into the advanced circuitry of the LA-324A. It features a front panel stereo headphone jack, fused right and left channel output transistors for protection against overloads, and full complement of front panel controls which include concentric volume/Balance control, Treble and Bass controls, Input Selector for Aux., Tuner, Mag Phono, and Ceramic Phono. Also included are rocker switches for Mono/Stereo Mode, Remote/Main Speakers, and Loudness. Rear panel features stereo inputs for unswitched Tape Phono; 2 AC convenience outlets (1 Speaker terminals for 4" and 8" Output jacks; and 1 Main active design, only 10%w/31/2H28%*D will come present in your home decor. Complete with simulated walnut vinyl-clad metal case. For 105-120 VAC, 50/60 Hz with AC power fuse, imported, Shpg. wt., 10 1/2 lbs.

Net \$69.95

95 R 02339W

*See Page 22 for Full Credit Details on Easy Pay Plan

Functionally designed input control for switching to Auxiliary, Tuner, Magnetic or Ceramic cartridge input sources.

Speaker rocker switch permits amplifier output switching to main system speakers or to remote speakers in any desirable room in your home.

Loudness rocker switch for tonal balance at low volume levels.

2 AC convenience outlets (1 switched, 1 unswitched) in rear provide power to associated equipment.

Front panel headphone jack permits private listening to your favorite stereo programs.

See Page 46 for LA-324A 2-channel & Derived 4-Channel Stereo Hi-Fi Systems.



SPEAKERS



LOUDNESS



Front panel headphone jack permits private listening to your favorite stereo programs.

SPECIFICATIONS

Power Output: 50-Watts ± 1 db, 40-Watts IHF, at 4 ohms
 Frequency Response: 20-20,000 Hz ± 1.5 db
 Harmonic Distortion: 0.7% at 1 kHz at 1-watt
 Channel Separation: 60 db at 1 kHz
 Input Sensitivity: Aux: 250 mv, Tuner 500 mv, Phono Mag 2.3 mv, Phono Ceramic 80mv
 Hum and Noise: High Level Inputs: -75db, Low Level Inputs: -55 db.
 Power Bandwidth: 35-30,000 Hz
 Speaker Impedance: 4, 8-ohms
 Stereo Headphones: 8-ohms

Lafayette®

"Stereo 25" 20-Watt Solid State Stereo Amplifier



Only
39⁹⁵
with case
No Money Down*

- 20 Watts ± 1 db of Stereo Power †

The Stereo 25 offers a full 20 watts of stereo music power. Faithfully reproduces the full spectrum of audio sound with adequate volume and very low distortion. Solid state design assures minimum heat for safe placement anywhere and years of top-notch performance. Convenient operating features include front panel rocker switches for activation of source (tuner, phono or auxiliary), selection of stereo or mono output, selection of remote or main speakers, and power on/off. A full complement of controls is supplied for best stereo effects and permits you to "tailor" the sound to suit your taste! Front panel controls include separate bass, treble,

- Main/Remote Speaker Switch
- 20-20,000 Hz ± 1 db Frequency Response
- Front Panel Stereo Headphone Jack

concentric volume/balance and stereo headphone jack for private listening. Stereo outputs are available for 4-16 ohm main and remote speakers. Permits placement of speakers in main listening area plus in the recreation room, den, dining room or patio area. Attractive, modern styling with a matte black and satin gold front panel is complemented by a handsome walnut grained vinyl clad metal enclosure. Fused AC line and separately fused speaker outputs prevent damage to output transistors. Operates on 105-120 VAC, 50/60 Hz. Size: 10 1/4" W x 3 1/2" H x 6 3/4" D. Imported.

"STEREO 25" SPECIFICATIONS
Power Output: 20 watts ± 1 db (10 watts per channel) at 4 or 8 ohms. Frequency Response: 20-20,000 Hz ± 1 db. Power Bandwidth: 40-25,000 Hz. Harmonic Distortion: 0.1% at 1 watt. Hum and Noise: -70 db. Channel Separation: 60 db. Input Sensitivity: Aux., 250 mv; Tuner, 500mv; Phono, 250 mv. Stereo Outputs: main speakers, re-

mote speakers, stereo headphones. Controls: concentric Volume/Balance; master Bass; master Treble; Rocker switches for: Aux., Phono, Tuner, Stereo/Mono Mode, Remote/Main Speakers, and On/Off Power. With front panel pilot light and rear panel AC convenience outlet. †Rating standard used by major hi-fi audio manufacturers.

Net 39.95

Specially Matched 20-Watt Stereo Phono Systems



Garrard Model 30

103⁹⁵
with case
No Money Down*
SAVE 11.88
From Individual Catalog Prices

Criterion 2X

Stereo 25



Criterion 50A

Garrard Model 30

130⁹⁵
with case
No Money Down*
SAVE 14.88
From Individual Catalog Prices

Stereo 25

Superior 20-Watt Stereo System

This specially matched value-packed stereo system includes the Lafayette "Stereo 25" 20-Watt Solid State Stereo Amplifier; Garrard Model 30 4-Speed Automatic Turntable with oversized turntable, ceramic stereo cartridge and long-life diamond stylus; Matching turntable base; and 2 decoratively designed fine performing Lafayette Criterion 2X oiled-walnut 2-way bookshelf speaker systems with 6" woofer, and 3 1/2" direct radiator cone tweeter. With speaker cable. Shpg. wt., 35 lbs.

21 R 93340WXM Net 103.95


Special 20-Watt Stereo System

An outstanding value for performance and price this stereo system consists of: the Lafayette "Stereo 25" 20-Watt Solid State Stereo Amplifier; Garrard Model 30 4-Speed Automatic Turntable with ceramic stereo cartridge and diamond stylus; Matching turntable base; and 2 famous Lafayette Criterion 50A 30-Watt 2-way speaker systems with 8" woofer, 3 1/2" tweeter and tuned ducted port in an attractive oiled walnut finished enclosure for bookshelf and wall placement. Complete with speaker cable. Shpg. wt., 59 lbs.

21 R 93357WXM Net 130.95
21 R 40267W Net 5.50

See Pages 56, 57 and 84-88 for full description of system components

"Stereo 10A" Solid State Stereo Amplifier




Only
27⁹⁵
with case

- Compact Size
- Neat Styling
- Big Performance

Attractive, neat styling, plus compact size and big performance characterize this moderately priced stereo amplifier. The "Stereo 10A" is ideal for the hi-fi beginner or for use as a second stereo system for the living room, den, bedroom, or business. Perfect for areas where space is a limiting factor, the "Stereo 10A" can be installed easily on a bookshelf or end table. It can be used with record players, AM, FM, and FM Stereo tuners. Solid-state circuitry consisting of 10 transistors, and 2 diodes provides clean sound for cool, instantaneous operation. Input impedance: 400 K Ohms. Cross Talk: 45 db. Hum and Noise: 55 db. below rated output. Output stages couple directly to the speaker for smooth frequency response with high impedance crystal or ceramic phono cartridges.

Front panel features: Separate volume controls for Left/Right channels; Tone control for Bass and Treble; Rotary selector switch for Phono, Tuner and Auxillary; Individual slide switches for Mono/Stereo Mode, Power-On/Off and speakers—Main/Remote; stereo headphone jack for private listening; Power On/Off Indicator light. Rear panel features: Left/Right channel inputs for phono, tuner and auxillary; Left/Right channel outputs for main and remote speakers; switched AC convenience outlet. Beautifully finished brushed aluminum front panel with complementary metal knobs and attractive metal case. Size: 9W x 3½H x 6½"D. For 105-125 VAC, 50/60 Hz. Imported. Shpg. wt., 5½ lbs. 99 R 02289 Net 27.95

Popular Stereo Phono Music Systems With "Stereo 10A"




Criterion 2X



Lafayette AC50B

SAVE 9.78
From individual catalog price
ONLY **83⁹⁵**
With Case



Criterion 25A



Lafayette AC50B

SAVE 10.78
From individual catalog price
ONLY **92⁹⁵**
With Case



Stereo 10A

This popular hi-fi beginner's 2nd stereo system consists of: Lafayette Stereo 10A Compact stereo amplifier; Lafayette Model AC50B 4-speed automatic push-button stereo record changer with stereo turnover ceramic cartridge and diamond LP needle, with professional lever cueing; matching walnut finished wood base for record changer. 2 Lafayette fine-performing Criterion 2X 2-way bookshelf speaker systems with 5" woofer and 3½" direct radiator cone tweeter; with speaker cable. Shpg. wt., 32 lbs. 21 R 93365WXM No Money Down* Net 83.95



Stereo 10A

This fine performing 2nd stereo music system consists of: Lafayette Stereo 10A stereo amplifier; Lafayette Model AC50B 4-speed automatic push-button stereo record changer with stereo turnover ceramic cartridge and diamond LP needle; matching record changer base; 2 Lafayette Criterion 25A 2-way 25-watt speaker systems with extra efficient 8" woofer and 2½" tweeter in oiled walnut finished enclosure. Complete with speaker cable. Shpg. wt., 40½ lbs. 21 R 93373WXM No Money Down* Net 92.95

See Pages 56 and 91 for full description of system components.

*See Page 22 for Full Credit Details on Easy Pay Plan

LAFAYETTE Solid-State AM/FM Stereo Tuner Model LT-725A



AAA 2-YEAR GUARANTEE
See Page 415 for Terms

*Designed For Performance..
...Styled for Distinction!*

ONLY **119⁹⁵** No
Money
Down*

4 IC's, 2 FET's, 14 Transistors, 19 Diodes

- 1.7 μ v IHF Sensitivity • 1.5 db Capture Ratio
- Front and Rear Panel Tape Output Jacks
- Pushbutton FM Mute Switch
- Automatic Stereo Switching and Stereo Indicator Light
- Internal FM Antenna plus Flexible-Mount AM Loopstick Antenna
- Beautifully Styled Dial That Illuminates with "Power-On"
- 40db Stereo Separation

OUTSTANDING FEATURES



Illuminated Signal Strength Tuning Meter for normal and center scale tuning of FM and AM stations.



Automatic FM Stereo
Automatically switches to stereo mode and lights indicator when you tune to a stereo station.



Tape Out
Front and rear tape output jacks for recording through your tape recorder.

Pushbutton Function Switches for Signal Strength on AM and FM plus Center Channel Tuning on FM; Stereo/Mono mode; MPX High Frequency Filter; FM Mute; and Selector Button for AM or FM reception.



The Lafayette LT-725A establishes pace-setting standards for excellence in performance, flexibility of controls, ease of operation, and convenience. Its distinctive styling will compliment any home decor. Yet with all these features it is priced within the budget of the music lover who seeks superior performance and design at a moderate cost. In addition to high performance and unique circuit design, the LT-725A boasts an ultra-modern exterior with space-age styling. The most striking of these is the elegant ebony face-plate with gold embossed lettering; when the unit is turned "On", the logging scale, tuning meter and stereo indicator are illuminated into a highly attractive soft, rich blend from behind the face-plate. The front panel also features a row of push-buttons for the functions of Stereo/Mono mode, MPX Filter, Mute Switch for minimum noise while tuning FM stations, FM/AM reception, and tuning meter for center channel tuning and signal strength indication. There are tape output jacks at the rear and front panels; and rear inputs for external FM and AM antennas. Complete with built-in FM and AM antennas, AC fuse holder and grounding post. Output suitable for any quality stereo amplifier. Size: 12Wx3 $\frac{3}{4}$ Hx9 $\frac{1}{2}$ "D. Imported. For 105-120 Volts AC, 50/60 Hz. 99 R 02297W Shpg. wt., 13 lbs. Net 119.95

SPECIFICATIONS

FM SECTION: 4 Gang Tuning Condenser, Range: 88-108MHz. Sensitivity: 1.7 μ v. Harmonic Distortion: @ 400 Hz, 100% modulation: 0.25%. Selectivity: 50db. Capture Ratio: 1.5db. Stereo Separation: 40db @ 400Hz. Cross Modulation Index: 90db. Signal-to-Noise Ratio: 75db (100% Mod.) Image Rejection: 80db. External Antenna Impedance: 300 ohms balanced. **AM SECTION:** 3 Gang Tuning Condenser, Range: 535-1650 kHz. Sensitivity (Antenna Terminal): 20 μ v.

LAFAYETTE Solid-State AM/FM Stereo Tuner Model LT-670



AAA 2-YEAR GUARANTEE

See Page 415 for Terms

**Amazing
Low
Price**

ONLY

79⁹⁵

No Money Down*

14-Transistors Plus 16-Diodes

- Automatic Stereo Switching and Stereo Indicator Light
- Front Panel Tape Output Jack
- Automatic FM Station Lock
- 30 db Stereo Separation
- Multiplex Filter
- Internal FM Antenna plus Flexible-Mount AM Antenna
- Attractively Styled To Blend With All Decors

Enjoy the full measure of high priced AM/FM stereo reception at an "Amazingly" low price. Solid-state circuitry combines advanced design and electronic principles to provide a level of performance that far exceeds the cost! Included are **AUTOMATIC MULTIPLEX CIRCUITRY** which instantly switches the tuner to stereo operation when stereo is being broadcast. A "STEREO" INDICATOR LIGHT gives instantaneous visual indication of stereo broadcasts. Every control feature for outstanding performance has been included: switchable (On/Off) **MPX FILTER** for reduction of external interference on FM stereo; **AUTO LOCK (AFC)** assures drift-free reception. Other features include a **MODE selector** (Mono or Stereo); and a **SELECTOR** for AM or FM reception. There are even tape output jacks on front and rear for recording directly to a tape recorder. Has built in FM antenna and Ferrite bar for AM; plus terminals for adding a FM external antenna. With simulated walnut grain vinyl covered, metal enclosure and anodized brush aluminum front panel and knobs. For 105/120 VAC., 50/60 Hz. Size: 10 $\frac{1}{2}$ "Wx3 $\frac{1}{2}$ "Hx8 $\frac{3}{8}$ "D. Shpg. wt., 11 $\frac{1}{2}$ lbs. 99 R 02313W Net 79.95

SPECIFICATIONS

FM SECTION: 3-Gang Tuning Condenser. Range: 88-108 MHz. Sensitivity: 3.5 μ V. Harmonic Distortion: @ 400 Hz, 100% modulation: 0.7%; Selectivity (Alternate Channel): 35 db. Capture Ratio: 5 db. Stereo Separation: 30 db @ 400 Hz. Signal-to-Noise Ratio: 50 db (100% mod.). Image Rejection: 50 db. Tape Output Level: Average — 350 mV., 1 Volt max. External Antenna Impedance: 300 ohm balanced. **AM SECTION:** 3-Gang Tuning Condenser. Range: 535-1650 kHz. Sensitivity (Antenna Terminals): 20 μ V. S/N: 40 db @ 1 mV input.

OUTSTANDING FEATURES



Automatic FM Stereo automatically switches to stereo mode and lights indicator when you tune to a stereo station.

TAPE OUT



Tape Out Front and rear tape output jacks for recording through your tape recorder.

MPX FILTER



MPX Filter Rocker Switch (On/Off) for reduction of external interference when tuned to an FM Stereo Station.



Auto Lock Rocker Switch (on/Off for Automatic Frequency Control to assure drift-free FM reception.

Lafayette® 170-Watt 4-Channel
Stereo Systems Featuring
Model LR-440 Compatible
4-Channel AM-FM
Stereo Receiver

4 CHANNEL TAPE
and FM BROADCAST
STEREO SYSTEM

Criterion 50A



LR-440

RK-48

You will be thrilled by the spectacular dimensional surround sound of this outstanding 4 channel stereo system. The complete system consists of the superb Lafayette LR-440 170-Watt compatible 4-channel AM-FM stereo receiver which embodies 4 excellent amplifiers, exclusive "Composer" derived 4 channel circuitry, plus an outstanding AM-FM stereo tuner to bring you discrete 4 channel stereo programs from present 4 channel tapes as well as from discrete 4 channel stereo records and FM stereo broadcasts as soon as they become available. In addition the LR-440 brings you exciting derived 4 channel stereo from present stereo records, stereo tapes and FM stereo broadcasts. Also included are the Lafayette RK-48 compatible 2 and 4 channel stereo 8-track cartridge tape deck; 4 Lafayette Criterion 50A 2 speaker, 2-way bookshelf speaker systems in handsome oiled walnut finished enclosure; and speaker cable. Shpg. wt., 140 lbs.
21 R 91666WXM No Money Down* Net 521.95

Save 60³²

From Individual Catalog Prices

Only **521⁹⁵**



Lafayette/Pickering
Phase 44

4 CHANNEL TAPE,
FM BROADCAST and
PHONO STEREO SYSTEM

Save 90²⁷

From Individual Catalog Prices

Only **586⁹⁵**



Garrard 40B

In addition to the exciting enjoyable 4-channel tape and 4-channel FM stereo broadcast programs rendered by this LR-440 system, you will discover a new world of derived 4 channel audio richness in your present stereo records. This expertly matched system consists of the superb Lafayette LR-440 Compatible 4-channel FM-AM Stereo Receiver, the Lafayette RK-48 compatible 2 and 4 channel stereo 8 track cartridge tape deck, the dependable Garrard Model 40B, 3 speed automatic turntable with attractive matching base, the Lafayette/Pickering Phase 44 high efficiency elliptical stereo cartridge with high compliance diamond stylus, 4 Lafayette Criterion 50A 2-speaker, 2-way bookshelf speaker systems in handsome oiled walnut finished enclosures, and speaker cable. Shpg. wt., 152³/₄ lbs.
21 R 91674WXM No Money Down* Net 586.95

See Pages 3, 6, 7, 57, 82, 83, and 84-88 For Full Description of Above Components.

LAFAYETTE 170 Watt 4-Channel Stereo Systems

Featuring
Model LA-44 Compatible 4 Channel Stereo Amplifier




4-CHANNEL TAPE STEREO SYSTEM

Only **386.95** No Money Down*

Save \$45.23 From Individual Catalog Prices

Listen to the spectacular new sound of 4-channel stereo tapes in your home and add immeasurable joy to your audio listening! This 4-channel stereo system consists of the remarkable Lafayette LA-44 170-Watt Compatible 4-Channel Stereo Amplifier which is capable of playing 4-channel stereo programs from 4-channel stereo tape and other 4-channel program sources as soon as they become available, as well as of deriving 4-Channel stereo from existing 2-Channel program sources (stereo records, tape, FM broadcasts); the Lafayette RK-48 compatible 2 and 4-channel stereo 8-track cartridge tape deck; 4-Lafayette Criterion 50A 2-speaker, 2-way bookshelf speaker systems in handsome oiled walnut enclosures; and speaker cable. Shpg. wt., 115 $\frac{3}{4}$ lbs.

21 R 90833WXM Net 386.95



Criterion 50A



Criterion 50A



4-CHANNEL TAPE and PHONO STEREO SYSTEM

Only **451.95** No Money Down*

Save \$75.27 From Individual Catalog Prices

In addition to superb discrete and derived 4-channel tape stereophonic playback from the new 4 channel stereo tapes and the abundant 2 channel stereo tapes, you will discover a new world of exciting derived 4 channel audio richness available in your present stereo records. This ingeniously matched system consists of the Lafayette LA-44 Compatible 4 Channel Stereo Amplifier; the Lafayette RK-48 compatible 2 and 4 channel stereo 8 track cartridge tape deck; the Garrard 40B 3-speed automatic turntable; matching turntable base; the Lafayette/Pickering Phase 44 highly efficient elliptical stereo cartridge with diamond stylus; 4 Lafayette Criterion 50A 2-way, 2 speaker bookshelf speaker systems in handsome oiled walnut finish enclosures; and interconnecting cables. Shpg. wt., 128 lbs.

21 R 90841WXM Net 451.95



Criterion 50A



Garrard 40B



Criterion 50A



Phase 44 Cartridge

See Pages 3, 4, 5, 57, 82, 83, 84-88 for description of components in above systems

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette®

4 CHANNEL STEREO SYSTEMS FOR EVERYONE!

featuring MODEL LA-2525
40-Watt Compatible 4-Channel Stereo Amplifier

ONLY **260⁹⁵**
No Money Down*

SAVE **31.32**
From Individual Catalog Prices!

Criterion 25A

4 CHANNEL TAPE STEREO SYSTEM

Now everyone can afford to own and enjoy a fine hi-fidelity 4-channel stereo system! You will thrill to the 4-channel tapes in your home and add immeasurable joy to your audio listening. This 4-channel stereo system consists of the Lafayette LA-2525 40-Watt Compatible 4-Channel Stereo Amplifier which can play discrete 4-channel stereo tapes as well as discrete 4-channel records and discrete FM stereo programs as soon as they become available. The LA-2525 is also capable of deriving and playing 4-channel stereo from existing 2-channel stereo records, stereo tapes, and FM stereo broadcasts. In addition the system includes the Lafayette RK-48 Compatible 2 and 4-channel stereo 8-track cartridge tape deck; 4-Lafayette Criterion 25A 2 speaker, 2-way speaker systems, each with 8" woofer, 2 1/2" tweeter and L/C crossover network in attractive oiled walnut finish enclosure, and speaker cables. 21 R 96202WXM wt. 75 lbs. Net 260.95



4 CHANNEL TAPE AND FM BROADCAST STEREO SYSTEM

ONLY **332⁹⁵**
SAVE **39.27**
From Individual Catalog Prices!

4 CHANNEL TAPE AND PHONO STEREO SYSTEM

ONLY **325⁹⁵**
SAVE **61.27**
From Individual Catalog Prices!

4 CHANNEL TAPE, PHONO AND FM BROADCAST STEREO SYSTEM

ONLY **397⁹⁵**
SAVE **69.22**
From Individual Catalog Prices!



LT-670
Same 4-channel stereo system as above plus the Lafayette LT-670 solid-state AM/FM stereo tuner. Adds exciting derived 4-channel FM stereo programs from the multitude of excellent FM stereo broadcasts on the air. Shpg. wt. 8 1/2 lbs. No Money Down* 21 R 96210WXM Net 332.95



Garrard 40B
In addition to the superb discrete 4-channel tape stereo reproduction, you will thrill to the exciting derived 4-channel audio richness in your present stereo records. This matched system consists of the Lafayette LA-2525 Compatible 4-Channel Stereo Amplifier, the Lafayette RK-48 Compatible 2 and 4-Channel Stereo 8-Track Cartridge Tape Deck, 4 Lafayette Criterion 25A 2-speaker, 2-way speaker systems; the dependable Garrard 40B 3-speed automatic turntable with matching base, the Lafayette/Pickering Phase 44 efficient elliptical stereo cartridge with high compliance diamond stylus; speaker cables. wt., 8 1/4 lbs. No Money Down* 21 R 96228WXM Net 325.95



LT-670
Same 4-channel stereo system as 21 R 96228 WXM plus the Lafayette LT-670 AM/FM stereo tuner for addition of derived 4-channel FM stereo broadcasts. Shpg. wt., 9 3/4 lbs. No Money Down* 21 R 96236WXM Net 397.95

See Pages 2, 3, 31, 56, 82-88 for Description of Components in Above Systems.

LAFAYETTE AM/FM Stereo 8-Track Record/Playback Systems Featuring LRK-855 8-Track/Receiver†

†See Page 9 For Description of LRK-855



LRK-855



6—70 Minute 8-Track Mylar Recording Tapes



Pickering PAT/E

Matched 2-Channel Stereo AM/FM 8-Track Phono System

SYSTEM PRICE 311⁹⁵

SAVE 54.55
From Individual Catalog Prices

With this superb performing system you can record 8-track stereo tape cartridges directly from the AM/FM stereo section of the LRK-855. Or you can record your library of phonograph records using the Garrard 40B 3-speed automatic turntable with attractive matching base. As a starter you get 6 seventy minute mylar 8-track recording tapes. Sound is reproduced thru 2 Lafayette Criterion 50A 2 speaker 2-way systems. The pick-up cartridge is the Pickering PAT/E with diamond stylus. System is complete with speaker cable. Shpg. wt., 84 lbs.

99 R 99947WXM No Money Down* Net 311.95
Same as Above Except With Shure M55E Elliptical Cart. Net 316.95
99 R 99954WXM Shpg. wt., 84 lbs. Net 316.95
Same as Above Except With Laf/Pickering Phase 44 Elliptical Stereo Cartridge. Shpg. wt., 84 lbs. Net 326.95
99 R 99962WXM No Money Down* Net 326.95

Garrard 40B 2 Criterion 50A Speaker Systems

Alternate Cartridges





Shure M55

Lafayette/Pickering Phase 44 Cartridge




LRK-855



3—70 Minute 8-Track Mylar Recording Tape



Garrard SL55

Matched Derived 4-Channel Stereo AM/FM 8-Track Phono System

SYSTEM PRICE 457⁹⁵

SAVE 76.60
From Individual Catalog Prices

The LRK-855 has built-in derived 4-channel circuitry for listening to the 2 extra channels on your records, tapes, and FM stereo broadcasts. This magnificent 4 dimensional 4 channel system consists of the LRK 855 AM/FM 8-Track receiver, Garrard SL55 3-speed automatic turntable with matching base, Laf/Pickering Phase 44 Elliptical diamond needle cartridge, 4 Lafayette Criterion 100B 3-way speaker systems, 3 mylar 8-track recording tapes, and speaker cable. Shpg. wt., 154 lbs.

99 R 99970WXM No Money Down* Net 457.95



Lafayette/Pickering Phase 44 Cartridge




2 Crit. 100B



2 Crit. 100B

*See Page 22 for Full Credit Details on Easy Pay Plan

Magnificent 4-Channel Stereo System featuring the LAFAYETTE LRK-480 AM/FM 8-Track Stereo Playback Receiver



Stereo 25 & LRK-480

COMPLETE 4-CHANNEL SYSTEM **304⁹⁵**
YOU SAVE 34⁷⁵
 From Individual Catalog Prices

Sensational system that plays the new 4-Channel Stereo 8-Track Tapes—and derives 4-dimensional sound from conventional 2-channel 8-Track Tapes, FM stereo broadcasts, and records. Heart of this magnificent performing system is the Lafayette LRK-480 AM/FM Stereo Receiver with built-in 2 and 4-Channel 8-Track Stereo Tape Deck. (See page 10 for description of the LRK-480). When you add the Lafayette Stereo 25 Stereo Amplifier to the LRK-480 you now have the 4 amplifiers needed for listening to discrete 4-Channel stereo. Also included are 4 Lafayette Criterion 50A 2-speaker 2-way systems, and speaker hook-up cable. Shpg. wt., 80 lbs. 99 R 98006WXM No Money Down* Net 304.95



4 Criterion 50A's



Garrard 408



Lafayette/Pickering Phase 44 Elliptical Cartridge

Same deluxe system as above but also includes the Garrard 408 4-speed automatic record changer with matching base, and the Lafayette/Pickering Phase 44 Elliptical diamond needle stereo cartridge. Shpg. wt., 94 lbs. 99 R 98014WXM No Money Down* 369.95

Deluxe AM/FM Stereo Cassette Phono Systems featuring the LAFAYETTE LRK-900 Cassette Receiver




LRK-900

2 Dynamic Microphones

SYSTEM PRICE **354⁹⁵**
YOU SAVE 59⁹⁹
 From Individual Catalog Prices

This versatile system provides complete 2-channel stereo cassette recording facilities as well as provisions for listening to both 2 and derived 4-Channel 4-dimensional stereo music sources. The Lafayette LRK-900 AM/FM Stereo Cassette/Receiver has the built-in Lafayette 4-Channel Composer and adapter circuitry. (See page 8 for complete description of the LRK-900). This system also includes 6-60 minute blank Lafayette cassette tapes, 2 dynamic microphones, the Garrard 408 4-speed automatic record changer with matching base, Lafayette/Pickering Phase 44 Elliptical diamond needle stereo cartridge, 2 Lafayette Criterion 100B 3-way speaker systems, and speaker cable. Shpg. wt., 104 lbs. 99 R 99988WXM No Money Down* Net 354.95



2 Criterion 100B's

6-60 Minute Blank Lafayette Cassette Tapes



Garrard 408



Lafayette Phase 44 Cartridge

Same deluxe system as above but with 4 Criterion 100B speaker systems instead of two in order to listen to breathtaking derived 4-Channel 4-dimensional sound. Shpg. wt., 166 lbs. 99 R 99996WXM No Money Down* Net 442.95

Lafayette®

FULL STEREO ENJOYMENT FOR EVERYONE!

Criterion 2X

System Price

SAVE

175⁹⁵

19.79

From Individual
Catalog Prices

Criterion 2X

25-Watt Stereo System with LR-75 Receiver

AM-FM

Garrard Model 30

LR-75



Value-Packed Economy 25-watt Stereo System

A truly exciting value in a complete 25-watt stereo system package! Matched for performance as well as economy, this stereo system features the Lafayette LR-75 25-watt Solid State AM-FM Stereo Receiver with full stereo performance capability and with pleasing complementary styling; Garrard Model 30 4-Speed Automatic Turntable with oversized turntable, efficient ceramic stereo cartridge

and long-life diamond stylus; Attractive Matching Turntable base for Model 30; and 2 Lafayette Criterion 2X neatly styled, highly efficient 2-way oiled walnut finish bookshelf speaker systems with fine performing 5" woofer and 3 1/2" cone-type tweeter. Shpg. wt., 43 1/4 lbs.

21 R 93522WXM (No Money Down)* Net 175.95

4 Channel Stereo Systems With LR-75

Criterion 2X

Criterion 2X

System Price

SAVE

256⁹⁵

30.32

From Individual
Catalog Prices

LA-424

LR-75

Garrard Model 30



You'll be amazed at the wonderful derived 4 Channel stereo sound that emanates from this highly versatile economical compatible 4 channel stereo system. It derives 4 channel dimensional surround sound from your present stereo records as well as from FM stereo programs, and is ready to play discrete 4 channel stereo tapes already available, as well as discrete 4 channel records and discrete 4 channel FM stereo broadcasts as soon as they become available. This exciting 4 channel stereo system consists of the Lafayette LR-75 25-watt Solid State AM-FM Stereo Receiver; Garrard Model 30 4 speed automatic turntable with ceramic cartridge and long-life diamond

stylus; matching turntable base; the amazing highly versatile Lafayette LA-424 4 channel Complimentary Amplifier which reproduces discrete and derived 4 channel programs in conjunction with the LR-75; 4 Lafayette Criterion 2X 2-speaker 2-way acoustic suspension speaker systems, each with a 5" acoustic suspension woofer for substantial bass reproduction and a 3 1/2" cone-type tweeter for exemplary sound of up to 19,000 Hz., enclosed in a rich oiled walnut finish cabinet; and speaker cable. Shpg. wt., 76 lbs.

21 R 93993WXM No Money Down* Net 256.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 37

Lafayette®

50-Watt AM-FM Stereo Systems with LR-100 Receiver

SAVE 44.74

From Individual Catalog Prices!

220⁹⁵
with Case

No Money Down*



Super-Value 50-Watt AM-FM Stereo Systems

Extraordinary value in a complete 50-watt stereo system! Features the Lafayette LR-100 50-Watt Solid State AM-FM Stereo Receiver which offers full-feature stereo versatility with controls and inputs from every source, handsomely styled in black and gold anodized front panel and with simulated walnut vinyl clad metal case; Garrard Model 40B 3-Speed Automatic Turntable with viscous damped, single lever cueing, complete with Matching base; Pickering P/ATE-1 Elliptical Stereo Cartridge with high compliance diamond stylus; 2 Lafayette Criterion 25A 25-Watt 2-Way speaker systems, each featuring an extra-efficient 8" woofer and 2½" tweeter. Speakers are housed

in attractive enclosures with hand-rubbed oiled walnut finish, Complete with speaker cable, Shpg. wt., 58½ lbs.

21 R 94769WXM Net 220.95

Same system as above except with Shure M55E elliptical stereo cartridge. Shpg. wt., 58½ lbs.

21 R 90734WXM Net 225.95

Same system as above except with Lafayette/Pickering Phase 44 elliptical diamond stereo cartridge. Shpg. wt., 58½ lbs.

21 R 90742WXM Net 235.95

You Save 49.74 From Individual Catalog Prices!

Specially Matched 50-Watt AM-FM Stereo Systems



Criterion 50A

Garrard Model 40B



SAVE From Individual Catalog Prices!
46.74

238⁹⁵

No Money Down*



LR-100

This specially selected 50-Watt AM-FM stereo phono system features the Lafayette LR-100 50-Watt Solid State AM-FM Stereo Receiver with full stereo capability; the Garrard Model 40B 3-speed Automatic Turntable with matching base; Pickering P/ATE-1 Elliptical Stereo Cartridge with high compliance diamond stylus; 2 famous Lafayette Criterion 50A 30-watt 2-way bass reflex ducted port speaker systems with heavy duty 8" woofer and 3½" direct radiator tweeter in attractive hand-rubbed oiled walnut finished enclosures. With cable.

21 R 93472WXM Shpg. wt., 77½ lbs. Net 238.95

Above system but with Shure M55E elliptical stereo cartridge.

21 R 90759WXM Shpg. wt., 77½ lbs. Net 243.95

Above system but with Lafayette/Pickering Phase 44 elliptical diamond stereo cartridge.

21 R 90767WXM Shpg. wt., 77½ lbs. Net 253.95

You Save 51.74 From Individual Catalog Prices!

See Page 16, 56, 57, 82-88 for Complete

Deluxe 50-Watt AM-FM Stereo Systems

SAVE From Individual Catalog Prices!
48.74

256⁹⁵

No Money Down*



Garrard Model 40B

Criterion 77



LR-100

This deluxe LR-100 stereo system consists of Lafayette LR-100 50-watt Solid-State AM/FM Stereo Receiver; Garrard Model 40B 3-speed Automatic Turntable with matching base; Pickering P/ATE-1 Elliptical Stereo Cartridge with high compliance diamond stylus; 2 Lafayette Criterion 77 3 speaker 3-way acoustic suspension bookshelf speaker systems each with 8½" woofer, 3½" midrange and 1½" direct radiator type tweeter in a handsome oiled walnut finished enclosure; with cables.

21 R 90775WXM Shpg. wt., 75¼ lbs. Net 256.95

Above system but with Shure M55E elliptical stereo cartridge.

21 R 90783WXM Shpg. wt., 75¼ lbs. Net 261.95

Above system but with Lafayette/Pickering Phase 44 high efficiency elliptical stereo cartridge with diamond stylus.

21 R 90791WXM Shpg. wt., 75¼ lbs. Net 271.95

You Save 53.74 From Individual Catalog Prices!

Description of Components on this Page

*See Page 22 for Full Credit Details on Easy Pay Plan

4 CHANNEL STEREO SYSTEMS

Featuring
LR-100 AM/FM
Stereo Receiver

4 Criterion 25A Speakers



Lafayette/Pickering
Phase 44

4 Channel Adapter

4 Criterion 77
Speakers



Garrard 40B

LR-100



System Price

298⁹⁵

No Money Down*

**SAVE
55.70**

From
Individual
Catalog
Prices

System Price

370⁹⁵

No Money Down*

**SAVE
63.70**

From
Individual
Catalog
Prices

Experience the thrilling delight of derived 4-channel dimensional stereophonic sound! This rewarding system features the Lafayette LR-100 Solid-State AM/FM Stereo Receiver which offers full-feature stereo versatility. Garrard Model 40B 3-speed Automatic Turntable with low mass tubular tone arm and viscous damped single lever cueing, neatly designed matching base for turntable, Lafayette/Pickering Phase 44 highly efficient elliptical stereo cartridge with high compliance diamond stylus tailored to get the utmost in performance from 2-channel and derived 4-channel stereo. 4 Lafayette Criterion 25A 2-way speaker systems, each featuring an extra-efficient 8" woofer and 2½" tweeter in an attractive hand-rubbed oiled walnut finish enclosure, and the ingeniously designed Lafayette 4-Channel Adapter.

Shpg. wt., 86¼ lbs.

21 R 90809WXM

Net 298.95

This fine performing derived 4-channel stereo system consists of the Lafayette LR-100 Solid-State AM/FM Stereo Receiver, the Garrard 40B 3-speed Automatic Turntable with matching base, the Lafayette/Pickering Phase 44 elliptical stereo cartridge with high compliance diamond stylus, the Lafayette 4-Channel Adapter, and 4 Lafayette Criterion 77 3-speaker 3-way acoustic suspension bookshelf speaker systems each with 8½" woofer, 3½" midrange and 1½" tweeter in an attractive oiled walnut finished enclosure. Shpg. wt., 120¼ lbs.

21 R 90817WXM

Net 370.95

Same derived 4-channel stereo system as above except with 4 Lafayette Criterion 100B 3-way speaker systems each with 10" woofer, 3½" midrange, 1½" super tweeter, loaded sonic port and high frequency brilliance control in attractive oiled walnut finish enclosure. Shpg. wt., 160¼ lbs.

21 R 90825WXM

Net 406.95

See Page 16, 18, 56, 57, 58, 82-86 for Complete Description of Components on this Page

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 39

Lafayette®

100-Watt AM-FM Stereo Systems with LR-775 Receiver

SAVE 50.85

From Individual Catalog Prices

283⁹⁵

No Money Down*



A Choice 100-Watt AM-FM Stereo Systems

This complete versatile stereo system consists of Lafayette LR-775 100-Watt Solid-State AM-FM Stereo Receiver with advanced solid-state stereo circuitry; Garrard Model 40B 4-Speed Automatic Turntable; Matching base for turntable; Pickering P/ATE-1 Elliptical stereo Cartridge with high-compliance diamond stylus; and 2 famous Lafayette Criterion 100B 2-way bass reflex ducted port speaker systems with 8" woofer and 3½" tweeter in oiled walnut finish enclosure for horizontal or vertical placement. With cable.

21 R 93381WXM Shpg. wt., 68¾ lbs. Net 283.95
 Same as above but with Shure M55E elliptical stereo cartridge. Shpg. wt., 68¾ lbs. Net 288.95
 21 R 90856WXM Net 288.95
 Same as above but with Lafayette/Pickering Phase 44 elliptical stereo cartridge with diamond stylus. Shpg. wt., 68¾ lbs. Net 298.95
 21 R 90866WXM Net 298.95

B Selected 100-Watt AM-FM Stereo Systems

This specially matched stereo system features the Lafayette LR-775 100-Watt Solid-State AM-FM Stereo Receiver; Garrard Model 40B 4-Speed Automatic Turntable; Matching base for Turntable; Pickering P/ATE-1 Elliptical Stereo Cartridge; and 2 Lafayette Criterion 100B 3-speaker, 3-way bookshelf system featuring 10" woofer with 5½ lb. magnet, 3½" mid-range speaker and 1½" super tweeter and brilliance control in decorator styled oiled walnut finish enclosure for delightful room-filling sound. With audio cable. Shpg. wt., 91 lbs.

21 R 90874WXM Net 319.95
 Same as above except with Shure M55E elliptical stereo cartridge. Shpg. wt., 91 lbs. Net 324.95
 21 R 90882WXM Net 324.95
 Same as 21 R 90874WXM except with Lafayette/Pickering Phase 44 diamond elliptical stereo cartridge. Shpg. wt., 91 lbs. Net 334.95
 21 R 90890WXM Net 334.95

C Deluxe 100-Watt AM-FM Stereo Systems

A truly deluxe stereo system that consists of the Lafayette LR-775 100-Watt Solid-State AM-FM Stereo Receiver; Garrard Synchronab Model SL-55B Automatic Turntable with synchronous motor, adjustable anti-skating control and viscous damped cueing; Matching base for turntable; Pickering Phase IV/ACE Elliptical Stereo Cartridge with high compliance diamond stylus; and 2 Lafayette Criterion 150A deluxe 3-way acoustic suspension speaker systems with 10" acoustic suspension woofer, 3" cone-type midrange and lower high frequency speaker, and 1½" super-tweeter and high frequency level control. Housed in handsome oiled-walnut finished enclosure. With speaker cable.

21 R 90908WXM Shpg. wt., 73 lbs. Net 352.95
 Same as above except with Shure M93E elliptical stereo cartridge. Shpg. wt., 73 lbs. Net 357.95
 21 R 90916WXM Net 357.95
 Same as above except with Lafayette/Pickering Phase 44 diamond elliptical stereo cartridge. Shpg. wt., 73 lbs. Net 362.95
 21 R 90924WXM Net 362.95

See Pages 15, 57, 58, 59, 82-88 for complete description of components on this page.



Criterion 100B

SAVE 55.83
From Individual
Catalog Prices

319⁹⁵

No Money Down*

B



Garrard
Model 40B



LR-775

C



Criterion 150A

352⁹⁵
with
case

SAVE 61.85
From Individual
Catalog Prices



LR-775



Garrard
SL-55B

4 CHANNEL STEREO SYSTEMS

Featuring
LR-775 100-Watt AM-FM Stereo Receiver



Lafayette/Pickering Phase 44



4 Channel Adapter



LR-775



Garrard Model 40B

Criterion 50A

SYSTEM PRICE 379.95 **SAVE 64.70**
 No Money Down* From Individual Catalog Prices

SYSTEM PRICE 451.95 **SAVE 72.70**
 No Money Down* From Individual Catalog Prices

*You will be thrilled at the surprising audio depth of this derived 4 channel stereo system. The complete system consists of the Lafayette LR-775 100-Watt Solid State AM-FM Stereo Receiver; the famous Garrard Model 40B 3-speed Automatic Turntable; an attractive matching turntable base; the ingenious Lafayette 4-Channel Adapter for derived four channel stereo sound; the Lafayette/Pickering Phase 44 elliptical stereo cartridge with high compliance diamond stylus designed for superb stereo performance; and 4 popular Lafayette Criterion 50A 2-way bass-reflex ducted port speaker systems with 8" woofer and 3 1/2" direct radiator tweeter in oiled walnut finish enclosure for horizontal or vertical placement. Shpg. wt., 119 3/4 lbs. 21 R 90932WXM Net 379.95

This highly versatile derived four channel stereo system consists of the Lafayette LR-775 100-Watt Solid-State AM-FM Stereo Receiver with advanced solid-state circuitry; the Garrard Model 40B 3-speed automatic turntable with low mass tone arm and viscous damped cueing; a neatly designed matching turntable base; the amazing Lafayette 4-Channel Adapter for superb 4 dimensional sound; the Lafayette/Pickering Phase 44 highly efficient elliptical stereo cartridge with high compliance diamond stylus; and 4 Lafayette famous Criterion 100B 3-way loaded sonic port speaker systems with 10" woofer, 3 1/2" mid-range, 1 1/2" super tweeter and brilliance control in an attractively styled oiled-walnut finish enclosure. 21 R 90940WXM Shpg. wt., 153 3/4 lbs. Net 451.95

See Pages 15, 18, 57, 82-88 for complete description of components in above systems.

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette® 150-Watt AM-FM Stereo Systems with LR-1000B Receiver




373⁹⁵ **SAVE 61.83**
 No Money Down* From Individual Catalog Prices

A Selected 150-Watt AM-FM Stereo Systems

This fine stereo system features the Lafayette LR-1000B Solid-State AM-FM Stereo Receiver distinguished for its outstanding performance characteristics and fine circuitry innovations; the Garrard Model 40B 3-Speed Automatic Turntable; matching base for turntable; Pickering P/ATE-1 Elliptical Stereo Cartridge with high compliance diamond stylus; and 2 Lafayette Criterion 100B 3-way loaded sonic speaker systems with 10" woofer, 3½" midrange, 1½" super tweeter and brilliance control in an attractively styled oiled-walnut finished enclosure. Includes speaker cable.

21 R 89819WXM Shpg. wt., 106½ lbs. Net 373.95
 Same system as above except with Shure M55E elliptical stereo cartridge. Net 378.95
 21 R 90957WXM Shpg. wt., 106½ lbs. Net 378.95
 Same as above except with Lafayette/Pickering Phase 44 diamond elliptical stereo cartridge. Net 378.95
 21 R 90965WXM Shpg. wt., 106½ lbs. Net 388.95



Criterion 150A

391⁹⁵ **SAVE 63.83**
 No Money Down* From Individual Catalog Prices

B Special 150-Watt AM-FM Stereo Systems

This specially matched stereo system features the exceptionally fine Lafayette LR-1000B Solid State AM-FM Stereo Receiver; Garrard Model 40B 3-Speed Automatic Turntable; matching base for turntable; Pickering P/ATE-1 Elliptical Stereo Cartridge; and 2 Lafayette Criterion 150A deluxe 3-way acoustic suspension speaker systems with 10" air suspension woofer with 2½ lb. magnet structure, 3" cone type midrange and lower high frequency driver, 1½" super tweeter with aluminum cone, and high frequency level control in attractive, luxurious oiled walnut finished enclosure. With cable.

21 R 90973WXM Shpg. wt., 88½ lbs. Net 391.95
 Same as above except with Shure M55E elliptical stereo cartridge. Net 396.95
 21 R 90981WXM Shpg. wt., 88½ lbs. Net 396.95
 Same as above except with Lafayette/Pickering Phase 44 diamond elliptical stereo cartridge. Net 406.95
 21 R 90999WXM Shpg. wt., 88½ lbs. Net 406.95



Garrard Model 40B




LR-1000B

C Deluxe 150-Watt AM-FM Stereo Systems


Includes superb Lafayette LR-1000B Solid State AM/FM Stereo Receiver; Garrard Synchronab Model SL55B 3-Speed Automatic Turntable with synchronous motor and viscous damped cueing; Base for turntable; Pickering Phase IV/ACE Elliptical Stereo Cartridge with high-compliance diamond stylus; and 2 Lafayette Deluxe Criterion VI 6-speaker 4-way systems that feature a 12" woofer with ½ lb. magnet structure, 5" midrange in sealed sub-enclosure, 2-3" cone tweeters, 2-1½" aluminum cone super tweeters, and tuned "sonic tube" in smart oiled walnut finish enclosure. With cable.

21 R 91708WXM Shpg. wt., 128½ lbs. Net 478.95
 Same as above except with Shure M93E elliptical stereo cartridge. Net 483.95
 21 R 91716WXM Shpg. wt., 128½ lbs. Net 483.95
 Above except with Lafayette/Pickering Phase 44 diamond elliptical stereo cartridge. Net 488.95
 21 R 91724WXM Shpg. wt., 128½ lbs. No Money Down* Net 488.95

See Pages 14, 58, 59, 61, 82-88 for full description of components on this page.




Criterion VI



Garrard Model SL55B

478⁹⁵ **SAVE 76.83**
 No Money Down* From Individual Catalog Prices



LR-1000B

Lafayette® 150-Watt

Criterion 77

4 CHANNEL STEREO SYSTEMS

Featuring
Model LR-1000B
AM-FM Stereo Receiver


Criterion
77

Save 74.70

From Individual Catalog Prices

System Price

469.95
No Money
Down*



Lafayette 4 Channel Adapter

LR-1000B

This outstanding derived 4-Channel stereo system consists of the Lafayette LR-1000B 150-Watt Solid-State AM-FM Stereo Receiver; the Garrard Model 40B 3-speed automatic turntable; matching turntable base; Lafayette/Pickering Phase 44 elliptical stereo cartridge with high compliance diamond stylus; Lafayette 4-Channel Adapter with interconnecting cables; and four Lafayette Criterion 77 3-way acoustic suspension speaker systems, each with a heavy-duty 8½" woofer, 3½" midrange and 1½" tweeter in a neat walnut finish enclosure. 21 R 91732WXM Shpg. wt., 131¼ lbs. Net 469.95


Same system as above except with four Lafayette Criterion 100B 3-way speaker systems each with 10" woofer with 5½ lb. magnet, 3½" mid-range, 1½" super tweeter, and brilliance control in attractive oiled walnut finish enclosure instead of the Criterion 77's. 21 R 91740WXM Shpg. wt., 171¼ lbs. Net 505.95 See 21 R 91757WXM system below for Criterion 100B speakers.



Garrard
Model 40B



Lafayette/Pickering
Phase 44



Criterion
100B

System Price

515.95
No Money
Down*

Save 83.70

From
Individual
Catalog
Prices



Garrard
Model SL55B


This fine deluxe derived 4-Channel stereo system includes: the Lafayette LR-1000B Solid-State AM-FM Stereo Receiver; Garrard Model SL-55B 3-speed stereo automatic turntable; Garrard Matching Base; Lafayette/Pickering Phase 44 high efficiency elliptical stereo cartridge with high compliance diamond stylus; Lafayette 4-Channel Adapter with interconnecting cables; and four Lafayette Criterion 100B 3 speaker, 3-way speaker systems. 21 R 91757WXM Shpg. wt., 171¼ lbs. Net 515.95

Same system as above except with four Lafayette Criterion 150A 3-speaker acoustic suspension systems each with 10" acoustic suspension woofer, closed back 3" high frequency driver, 1½" super tweeter, and high frequency level control in oiled walnut finish enclosure instead of Criterion 100B's. 21 R 91765WXM Shpg. wt., 135¼ lbs. Net 551.95 You save 87.70 from individual catalog prices.




Lafayette/Pickering
Phase 44

See Pages 14, 18, 57,
59, 83-88 for description
of above components.



Criterion
150A

Alternate Speakers



Criterion
150A

*See Page 22 for Full Credit Details on Easy Pay Plan

240-Watt AM-FM Stereo Systems

WITH

LAFAYETTE LR-1500TA Stereo Receiver

SAVE 67.83

From Individual Catalog Prices

427⁹⁵
With Case

No Money Down*

A



A Selected 240-Watt AM-FM Stereo Systems

This expertly matched stereo system includes our finest receiver, the outstanding Lafayette LR-1500TA 240-Watt Solid State AM-FM Stereo Receiver which features advanced solid-state circuitry with 4 integrated circuits, 5 F.E.T.'s, 39 discrete transistors, Computer-Matic® protective circuitry and ACRTUNE precision visual tuning for extraordinary performance; Garrard Model 40B 3-Speed Automatic Turntable with attractive Garrard matching base; Pickering P/ATE-1 Elliptical Stereo Cartridge with high compliance diamond stylus; and 2 Lafayette Criterion 100B 3-way speaker systems with 10" woofer, 3½" mid-range, 1½" super tweeter, loaded sonic port and high frequency brilliance control in attractive oiled-walnut finished enclosures. Complete with speaker cable. Shpg. wt., 113 lbs.

21 R 91773WXM Net 427.95
Same system as above except with Shure M55E elliptical stereo cartridge.

21 R 91781WXM Shpg. wt., 113 lbs. Net 432.95

Same system as above except with Lafayette/Pickering Phase 44 high efficiency elliptical stereo cartridge with high compliance diamond stylus.

21 R 91799WXM Shpg. wt., 113 lbs. Net 442.95

You save 72.83 from individual catalog prices!

B Feature-Packed 240-Watt AM-FM Stereo Systems

This excellent feature-packed stereo system consists of the acclaimed Lafayette LR-1500TA 240-Watt Solid State AM-FM Stereo Receiver with advanced solid-state design and Computer-Matic® protective circuitry; Garrard Synchro-Lab Model SL55B 3-Speed Automatic Turntable with neatly styled Garrard matching base; Pickering Phase IV/ACE Elliptical Stereo Cartridge with high compliance diamond stylus; and 2 Lafayette Criterion 150A 3-speaker acoustic suspension systems, each consisting of a 10" woofer, 3" closed back high frequency driver, 1½" super tweeter, LC crossovers at 6600 Hz and 10,000 Hz and high frequency level control in a rich oiled-walnut finish enclosure. Complete with speaker cable. Shpg. wt., 95 lbs.

21 R 91807WXM Net 460.95

Same as above except with Shure M93E elliptical stereo cartridge.

21 R 91815WXM Shpg. wt., 95 lbs. Net 465.95

Same system as above except with Lafayette/Pickering Phase 44 elliptical stereo cartridge with high compliance diamond stylus.

21 R 91823WXM Shpg. wt., 95 lbs. Net 470.95

See Pages 12, 13, 58, 59, and 82-88 for full description of components on this page.

SAVE 74.73

From Individual Catalog Prices

460⁹⁵
With Case

No Money Down*

B



4 Criterion
100B Speakers

4 CHANNEL AM-FM STEREO SYSTEMS with Acclaimed LR-1500TA Stereo Receiver



Lafayette/Pickering
Phase 44



Lafayette
4 Channel Adapter

4 Criterion 150A
Speakers



Garrard Model 40B



LR-1500TA

SYSTEM PRICE **559⁹⁵** **SAVE 84.70**
From Individual Catalog Prices
No Money Down*

SYSTEM PRICE **605⁹⁵** **SAVE 93.70**
From Individual Catalog Prices
No Money Down*

You will be thrilled by the superb derived 4-channel dimensional stereophonic sound of this fine system. Carefully matched for outstanding performance and value, this superior system includes our finest receiver, the outstanding Lafayette LR-1500TA Solid-State AM-FM Stereo Receiver with advanced solid state design, Computer-Matic® protective circuitry and ACRTUNE precision visual tuning; the Garrard Model 40B 3-Speed Automatic Turntable with attractive matching base; the Lafayette/Pickering Phase 44 highly efficient elliptical stereo cartridge with high compliance diamond stylus; the Lafayette neatly designed derived 4 Channel Adapter; and 4 Lafayette Criterion 100B 3-way speaker systems each with a 10" heavy duty woofer, 3 1/2" mid-range, 1 1/2" super tweeter, loaded sonic port and high frequency brilliance control in an attractive oiled walnut finished enclosure.

21 R 91831WXM Shpg. wt., 177 3/4 lbs. Net 559.95

An expertly matched derived 4 channel stereo system that includes the famous Lafayette LR-1500TA 240 Watt Solid State AM-FM Stereo Receiver which features advanced solid state circuitry with 4 integrated circuits (IC's), 5 F.E.T.'s, 39 discrete transistors, Computer-Matic® protector circuitry and ACRTUNE precision visual tuning for superb performance; the Garrard Synchro-Lab Model SL55B 3-Speed Automatic Turntable with built-in stylus force adjustment and optical scale, viscous damped single-lever cueing, and fully adjustable anti-skating; also includes a Garrard turntable matching base; the Lafayette/Pickering Phase 44 elliptical stereo cartridge with high compliance diamond stylus; the Lafayette 4 Channel Adapter; and 4 Lafayette Criterion 150A 3-speaker acoustic suspension systems, each with 10" acoustic suspension woofer, 3" upper mid-range and lower high frequency driver, 1 1/2" super tweeter and high frequency level control in a handsome oiled walnut finish enclosure. Shpg. wt., 141 3/4 lbs.

21 R 91856WXM Net 605.95

Same system as above except with 4 Lafayette Criterion 150A 3-speaker acoustic suspension system, each with 10" acoustic suspension woofer, 3" closed back upper midrange and lower high frequency driver, 1 1/2" super tweeter, and high frequency level control in a neatly designed enclosure with hand rubbed oiled walnut veneer finish. Instead of the Criterion 100B speakers.

21 R 91849WXM Shpg. wt., 141 3/4 lbs. Net 595.95

Same derived 4 channel stereo system as above except with 4 Lafayette Criterion 4X 4 speaker, 4-way speaker systems, each with a 12" woofer with 4 1/2 lb magnet structure and large 2" voice coil, 5" mid-range driver, 3" high frequency tweeter, 1 1/2" super tweeter, 3 LC crossover networks, and high frequency and mid-range controls in a handsome oiled walnut finish enclosure, instead of the Criterion 150A speaker systems.

21 R 91864WXM Shpg. wt., 213 3/4 lbs. Net 677.95

See Pages 12, 13, 18, 58

59, 60, 82-88 for full description of components on this page.

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 45

Lafayette® 50-Watt Stereo Phono Systems with LA-324A

SAVE 36.83

From Individual Catalog Prices

148⁹⁵



Budget-Priced 50-Watt 2-Channel Stereo Phono Systems

A budget-priced system with high performance, this Lafayette matched stereo system consists of the new Lafayette LA-324A 50-Watt Solid State Stereo Amplifier; Garrard Model 40B 4-Speed Automatic Turntable with neatly designed matching base; Pickering P/ATE-1 Elliptical Stereo Cartridge with high compliance diamond stylus; and 2 Lafayette Criterion 25A efficient 25-Watt 2-Way air-suspension speaker systems with 8" woofer, and 2½" tweeter in decorative hand-rubbed oiled-walnut finished enclosure. With cable. Shpg. wt., 48 lbs. 21 R 93696WXM No Money Down* Net 148.95

Same as above except with Shure M55E elliptical stereo cartridge. 21 R 91922WXM Shpg. wt., 48 lbs. No Money Down* Net 153.95

Same as above except with Lafayette/Pickering Phase-44 elliptical stereo cartridge. 21 R 91930WXM Shpg. wt., 48 lbs. No Money Down* Net 163.95

Same stereo system as 21 R 91930WXM above except with 2 popular Lafayette Criterion 50A 2-way speaker systems each with heavy duty 8" woofer and 3½" direct radiator tweeter in oiled-walnut finished enclosure instead of the Criterion 25A's. Shpg. wt., 67½ lbs. 21 R 91948WXM No Money Down* Net 181.95



Criterion 50A


Alternate Speakers

50 Watt 4 Channel Stereo Systems

SAVE 47.70

From Individual Catalog Prices

System Price 226⁹⁵



Criterion 25A



Garrard 40B




LA-324A

See Pages 18, 27, 56, 57, 82-88 for Description of Components in Above Systems.



Criterion 25A



Criterion 50A Alternate Speakers



Lafayette/Pickering Phase 44



Lafayette 4-Channel Adapter

You'll marvel at the derived 4-channel dimensional sound of this high performance economy system. The complete system consists of the Lafayette LA-324A 50-Watt Solid State Stereo Amplifier; the Garrard Model 40B 4-Speed automatic turntable with neatly designed matching base; the Lafayette/Pickering Phase 44 elliptical stereo cartridge with high compliance diamond stylus; the Lafayette 4-Channel Adapter; and 4 Lafayette Criterion 25A efficient 2 way air suspension speaker systems, each with 8" woofer and 2½" tweeter in decorative hand-rubbed oiled-walnut finished enclosure. 21 R 91955WXM Shpg. wt., 76 lbs. No Money Down* Net 226.95

Same derived 4-channel system as above except with 4 Lafayette popular Criterion 50A 2-way bass reflex ducted-port speaker systems, each with heavy duty 8" woofer and 3½" cone type direct radiator tweeter in handsome oiled-walnut finished enclosure, instead of the Criterion 25A's. Shpg. wt., 114 lbs. 21 R 91963WXM No Money Down* Net 262.95

Lafayette® 100-Watt Stereo Phono Systems with LA-750

SAVE 40.83

184⁹⁵

No Money Down*



Feature-Packed 100-Watt 2-Channel Stereo Phono Systems

A 100-watt stereo phono system that features the Lafayette LA-750 100-watt Solid State Stereo Amplifier; Garrard Model 40B 3-Speed Automatic Turntable with matching base; Pickering P/ATE-1 Elliptical Cartridge with diamond stylus; plus 2 Lafayette Criterion 50A 2-way bass reflex ducted-port speaker systems with 8" woofer and 3½" cone type direct radiator tweeter in decorative oiled-walnut finished enclosures.

21 R 93621WXM Complete with speaker cable. Shpg. wt., 65¼ lbs. Net 184.95

21 R 91971WXM Above but with Shure M55E Elliptical Stereo Cartridge Net 189.95
Above but with Lafayette Pickering Phase 44 Elliptical Stereo Cartridge.

21 R 91989WXM No Money Down* Net 199.95

Same stereo system as above but with 2 Lafayette Criterion 100B 3-speaker 3-way systems in handsome oiled-walnut finished enclosures. Shpg. wt., 88 lbs.

21 R 91997WXM Net 235.95

Lafayette matching AM/FM Stereo Tuner Model LT-725A for above systems.

99 R 02297WX Shpg. wt., 13 lbs. Net 119.95



Alternate Speakers

100-Watt

4 Channel Stereo Systems



Criterion 50A



Garrard 40B



LA-750

See Pages 16, 26, 27, 58, 82-88 for Description of Components in Above Systems.

SAVE 53.70
From Individual Catalog Prices

System Price
280⁹⁵



Criterion 50A



Lafayette/Pickering Phase 44



Alternate Speakers
Criterion 100B



Lafayette 4-Channel Adapter

An outstanding carefully matched system for derived 4 channel dimensional stereo performance. In addition to the Lafayette LA-750 100-Watt Solid State Stereo Amplifier the system includes the Garrard Model 40B 3-Speed Automatic Turntable with matching turntable base; the Lafayette/Pickering Phase 44 highly efficient elliptical stereo cartridge with high compliance diamond stylus; the Lafayette 4-Channel Adapter and 4 popular Lafayette Criterion 50A 2-way ducted port speaker systems, each with heavy duty 8" woofer and 3½" direct radiator tweeter in oiled-walnut finished enclosure.

21 R 91682WXM Shpg. wt., 113¾ lbs. Net 200.95

Above system but with 4 famous Lafayette Criterion 100B 3 speaker, 3-way speaker systems, each with powerful 10" woofer with a 5½ lb magnet, 3½" mid-range, 1½" direct radiator super tweeter, and brilliance control in a neat oiled-walnut finished enclosure, instead of the Criterion 50A's.

21 R 91690WXM Shpg. wt., 152¾ lbs. Net 352.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette®

160 Watt Stereo Systems

With LA-125B

Criterion 100B



Garrard Model 40B

System Price **265⁹⁵**
No Money Down*

Save **49.83**
From Individual Catalog Prices



LA-125B

Alternate Speakers Criterion 150A

Packed with audio features, this outstanding 2-channel stereo system consists of the Lafayette LA-125B Stereo Amplifier with superbly designed solid-state circuitry for unexcelled stereophonic sound reproduction; the dependable Garrard Model 40B 3-Speed Automatic Turntable with professionally designed matching turntable base; the Pickering P/ATE-1 Elliptical Stereo Cartridge with high compliance diamond stylus; and 2 famous Lafayette Criterion 100B 3-way, 3 speaker systems, each with 10" woofer with 5½ lb. magnet, 3½" mid-range, 1½" super tweeter, 2 L/c crossover networks and brilliance control in a handsome oiled-walnut finished enclosure, with cable. Shpg. wt., 93 lbs.

21 R 89B76WXM Net 265.95
Same system as above except with Shure M55E elliptical stereo cartridge. Shpg. wt., 93 lbs.
21 R 91B72WXM Net 270.95

Same stereo system as above except with Lafayette/Pickering Phase 44 elliptical stereo cartridge with high compliance diamond stylus. Shpg. wt., 93 lbs.
21 R 91B80WXM Net 280.95

Same stereo system as 21 R 91B80WXM except with 2 Lafayette Criterion 150A 3 speaker acoustic suspension systems, each with 10" acoustic suspension woofer, 3" closed back high frequency driver, 1½" super tweeter, 2 L/c crossover networks, and high frequency level control in an attractive oiled walnut finished enclosure instead of the Criterion 100B's. Shpg. wt., 76 lbs.
21 R 91B90WXM Net 298.95


See Page 18, 25, 58, 59, 82-88 For Detailed Description of Components in Above Systems.

Matched

4 CHANNEL STEREO SYSTEMS



Criterion 100B



Criterion 100B



Alternate Speakers Criterion 150A

Save **66⁷⁰**
From Individual Catalog Prices

System Price **397⁹⁵**
No Money Down*



Garrard 40B



Lafayette/Pickering Phase 44



4 Channel Adapter



LA-125B

You will thrill to the enriched dimensional audio quality of this outstanding derived 4-channel stereo system. In addition to the superb Lafayette LA-125B 160-Watt Solid-State Stereo Amplifier, the system includes the dependable Garrard Model 40B 3 Speed Automatic Turntable with attractive matching base; the Lafayette/Pickering highly efficient Phase 44 Elliptical Stereo Cartridge with high compliance diamond stylus; the Lafayette 4-Channel Adapter; and 4 famous Lafayette Criterion 100B 3-speaker, 3-way speaker systems, each with 10" woofer with 5½ lb. magnet, 3½" mid-range, 1½" super tweeter, cross-over networks and brilliance control in a fine oiled walnut finished enclosure.
21 R 91906WXM Shpg. wt., 158¾ lbs. Net 397.95


Same derived 4-channel stereo system as above except with 4 Lafayette Criterion 150A acoustic suspension speaker systems, each with 10" acoustic suspension woofer, 3" high frequency driver, 1½" super tweeter, cross-over networks and high frequency level control in attractive oiled walnut finish enclosure. Shpg. wt., 122¾ lbs.
21 R 91914WXM Net 433.95

See Pages 18, 25, 58, 59, 82-88 For Component Description

*See Page 22 for Full Credit Details on Easy Pay Plan

SCOTT SOLID-STATE HI FIDELITY COMPONENTS

NEW! Model 495 2/4-Channel Stereo Quadrant® Amplifier



349⁹⁰

No Money Down*

with black vinyl clad case

- Power Output (RMS) 100 Watts, 4x25 or 2x50 Watts
- 4-Channel Main and Remote Speaker Buttons

Fine performing Model 495 has four 25 Watt RMS amplifiers. Plays discrete 4-channel material, has built-in circuitry to convert 2-channel source material to derived 4-channel, and accommodates encoded 4-2-4 channel systems. Sliding type controls: volume and balance, both front and rear. Inputs: 2 pair phono, 1 pair mic, 2 or 4-ch. tape, 4-ch. extra, and high level (tuner). Outputs: 2 front panel headphones, main & remote Quadrant® speakers, 4-ch. tape, and switched 117V outlet. Phono Input Sensitivity 3.0/6.0 mV. Extra 0.5V. S/N Ratio 65db/75db high level. Harmonic Distortion 0.5%. Added features: Pushbutton switches for speaker selector, hi-filter, loudness, tape mon., and "muting" (to temporarily lower speaker volume to answer phone, door, etc.). Size: 6 x 17½ x 17". For 117VAC, 60 Hz. **21 R 49508WX Wt., 31 lbs. Net 349.90**

NEW! Model 444 2/4 Channel Stereo FM/AM Quadrant Receiver



449⁹⁰

No Money Down*

with black vinyl clad case

- Power Output (RMS) 100 Watts, 4x25 or 2x50 Watts
- Automatic FM Stereo Light
- Automatic Quadrant Light

Same 4-channel amplifier as the Model 495 plus a sensitive AM/FM Stereo Receiver. Features include preamp sensitivity switch for both phono inputs, equalization switch for phono B/microphone. "Muting" switch to temporarily lower volume. Inputs: 2 pair phono, 1 pair mic, 4-ch. extra, 4-ch. tape, and preamp input jack. Outputs: 2 front panel headphones, main & remote Quadrant® speakers, 4-ch. tape, Multipath scope and Multiplex (to facilitate future 4-channel adapters), and 117V switched outlet. Phono Input Sensitivity 3.0/6.0 mV, 75db high level. Distortion 0.5%. Tuner, Sensitivity-FM 1.9 μV. AM 100 μV/meter. Silver plated FET front end. Separate meters for AM signal strength and FM center tune functions. Size: 6 x 17½ x 17". For 117VAC, 60 Hz. **21 R 49516WX Wt., 32 lbs. Net 449.90**

NEW! Model 477 AM/FM Stereo Receiver



399⁹⁰

No Money Down*

with black vinyl clad case

- Power Output: 2x70 Watts (RMS) into 8 Ohms
- 2 Meters: Signal Strength and Center Tuning

The Model 477 FM/AM Receiver features a front panel, six-way speaker switching circuit which allows any two of three stereo pairs of speakers to be used in any combination. "Muting" switch to temporarily lower volume. Inputs: 2 pair phono hi and lo, tape, mic, and extra. Separate pre-amp output jacks and power amp. input jacks. Front panel: microphone and headphone jacks, tape in/out jacks, switchable phono inputs, and FM mono/stereo function light. 5 input function lights; silver plated FET front end. Dual tuning meters show signal strength and precise center station tuning simultaneously with switching. Electronic protection circuits. S/N Ratio 65db phono, 75db extra input. FM Sensitivity (IHF) 1.9 μV. AM 100 μV/meter. Detector output for 4-channel multiplex adaptor. Size: 6 x 17½ x 15½"D. For 117VAC, 60 Hz. **21 R 49524WX Wt., 34 lbs. Net 399.90**

NEW! Model 377 AM/FM Stereo Receiver



319⁹⁰

No Money Down*

with black vinyl clad case

- Power Output: 2x40 Watts (RMS) into 8 Ohms
- Signal Strength Tuning Meter
- Tape Monitor

Highly sensitive AM/FM Stereo Receiver. Features new angled 9½" dial to increase visibility and tuning ease. Silver plated FET front end receives more stations with less distortion. Tape monitoring, speaker switches for two systems, phono level sensitivity switch, and "muting" switch for temporarily lowering volume. Inputs: AM and 300 ohm antenna terminals, mic, phono hi and lo, extra, and tape monitor. Unswitched accessory output. Microphone and headphone jacks. FM and AM function lights. Electronic circuit protection and speaker line fuses. Phono Input Sensitivity 3.0/6.0 mV, mic 5/10 mV, Extra Input 0.5 mV. S/N Ratio 65db phono, 75 db extra input. Harmonic Distortion 0.5%. FM (IHF) Sensitivity 1.9 μV. AM 100 μV/meter. Size: 6 x 17½ x 11¼"D. For 117 VAC, 60 Hz. Shpg. wt., 24 lbs. **21 R 49532WX Net 319.90**

NEW! Model 490 Stereo Pre-Amp Amplifier



299⁹⁰

No Money Down*

with black vinyl clad case

- Power Output: 2x70 Watts (RMS) into 8 Ohms
- 2-VU Meters w/ht Switchable Ranges

Powerful 2-channel solid-state stereo amplifier with complete flexibility. Built-in six-way speaker switching allows any two of three stereo pairs to be used in any combination. Audio 20db "mute" switch. Master level control, dual front and rear panel tape recorder inputs and outputs permit connection of two recorders simultaneously. Inputs: phono 1 and 2, tuner, extra 1 and 2, and mic. 2-VU meters with meter range switch; function indicator lights. Front panel headphone jack, Pre-amp sensitivity control. Harmonic Distortion 0.5% at rated output; IHF Power Bandwidth 15-40 d/kHz; Hum & Noise —75db/high level, —65db/low level inputs; Input Sensitivity, Phono-8 mV/high, 4 mV/low, Mic 5.5 mV, Tape, extra .55V. Size: 6 x 17½ x 15½"D. For 117VAC, 60 Hz. Shpg. wt., 32 lbs. **21 R 49540WX Net 299.90**

NEW! Model 431 AM/FM Stereo Tuner



219⁹⁰

No Money Down*

with black vinyl clad case

- 2 Meters—AM, FM-Multipath
- 12-Pole IF Filter
- FET RF Front End

Deluxe AM/FM Stereo Tuner features FET muting circuitry which eliminates interstation hiss without transients. Four and six-pole jumped filters in the AM and FM-IF section maintains accurate alignment for the lifetime of the tuner. Two meters, one for center channel tuning and one for signal strength and multipath indication, increase tuning ease. Four-channel decoder output is provided for future use. Stereo noise filter, output level controls, and multipath scope outputs. 300 or 75-ohm antenna terminals and balun switch. Has Scott's famous silver plated FET front end. Sensitivity—FM 1.7 μV (IHF), AM 100 μV/meter. S/N Ratio 70db, Distortion 0.5%, Capture Ratio 2.5db, Selectivity (alternate channel)—70db. For 117 VAC, 60 Hz. Size: 6 x 17½ x 15"D. Shpg. wt., 20 lbs. **21 R 49557WX Net 219.90**

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 49



Fisher Solid-State 4 Channel Stereo Receiver

DELUXE MODEL 701 250 Watt 4 Channel Stereo AM/FM Receiver

REPRODUCES:

- Conventional 2-channel stereo
- New 4 channel stereo

CREATES:

- 4 channel derived sound from conventional 2 channel stereo
- Autoscan FM Touch Tuning
- FM Stereo Beacon
- Advanced Solid State Circuitry



699⁹⁵
Less
Enclosure

- 4 Tape outputs, 4 Tape Monitor Inputs
- Main, Remote, Main and Remote Speaker Selector
- Separate Front and Rear Speaker Volume Controls

Compatible Two and 4 channel solid state AM/FM Stereo Receiver. Reproduce conventional 2-channel stereo and NEW 4 channel stereo. Also creates derived 4 channel sound from conventional 2 channel program material. The 701 has 4 tape recorder outputs, and 4 tape monitor inputs. Simultaneous monitoring and recording of tapes is possible on all 4 channels. The 701 has 3 methods of tuning: (1) Autoscan FM Touch Tuning—Automatic FM Station Scanning (2) Remote Control Autoscan Tuning with optional RK40 Remote control unit, (3) Manual Flywheel Tuning. Baxandall Tone Controls work on the front, rear, or both channels to provide full tonal balance. The 701 can drive any 4 speakers in the main listening area, as well as 4 speakers in another room giving you 4 channel stereo in any 2 rooms of your home. Separate volume controls for both

front and rear channels. Specifications: 250 watts \pm 1 db Music Power total for 4 channels, RMS: 40/40/40/40 watts per channel. Power Bandwidth: 20-25,000 Hz. FM Tuner Sensitivity: 1.7 μ V, S/N Ratio: 66 db; FM Stereo Separation 36 db; AM Tuner Selectivity 50 db. Mag. phono input sensitivity: 2.7 mV. Aux. Sensitivity Aux 1 and Aux 2, 200 mV. Front panel stereo Headphone jack. Size: 16 $\frac{1}{2}$ "W x 5 $\frac{1}{4}$ "H x 14"D. Shpg. wt., 35 lbs.

21 R 33726WX No Money Down* Net 699.95
Walnut Enclosure for 701 Shpg. wt., 7 lbs.
21 R 33734W Net 24.95
RK40 Remote Control Unit Shpg. wt., 1 lb.
21 R 33742 Net 9.95

NEW MODEL 601 200 Watt 4 Channel Stereo AM/FM Receiver

- Reproduces Conventional 2-Channel Stereo
- Reproduces Starting 4-Channel Stereo
- Creates 4-Channel Sound from 2-Channel
- Drives up to 8 Speaker Systems



599⁹⁵
Less
Enclosure

A truly fine performing receiver. The sensitive FM tuner section utilizes 2 FET's and 5 IC's. Stereo Beacon[®] indicates the presence of an FM stereo station and automatically switches to stereo. Baxandall tone controls, 4-channel tape monitor inputs and outputs, separate main and remote switching of two four-channel hook-ups. Headphone jack. Specifications: FM Tuner Section—IHF Sensitivity: 1.8 μ V; FM Stereo Separation: 35 db. Amplifier Section—Music Power: 200 watts +1 db at 8 ohms. Sensitivity: Phono 2.7 mV; AUX 1 and 2, 200 mV; Monitor, 300 mV. For 117 VAC 60 Mz. Size: 16 $\frac{1}{2}$ " x 5 $\frac{1}{4}$ " x 16 $\frac{1}{2}$ ". Shpg. wt., 35 lbs.


21 R 33759WX No Money Down* Net 599.95
Walnut Cabinet for 601. Shpg. wt., 7 lbs.
21 R 33734W Net 24.95

Model K-10 "Spacexpander" Electronic Reverberation System

**Add A New Dramatic Sound
To Your Listening Pleasure
With One Simple Control.**

Add concert hall realism to your listening area. Supplies the reverberation normally heard in an acoustically perfect concert hall. Samples sound output from amplifier, and re-injects the same sound after a short time delay thus adding the reverberation effect. May be used with any mono or stereo home music system using separate preamplifiers or tape monitoring facilities. Connects to any signal from 0.2 to 5.0 volts. Simple to operate and easy to install. Tubes: 2-12AX7, 1-7247 plus a selenium rectifier. Size: 9 $\frac{1}{2}$ "L x 1 $\frac{1}{2}$ "W x 6 $\frac{3}{4}$ "H. Shpg. wt., 7 $\frac{1}{4}$ lbs.

21 R 3650S No Money Down* Net 79.95




79⁹⁵
No
Money Down*



Fisher Solid State Stereo Receivers & Amplifiers

NEW Model 301 140 Watt AM-FM Stereo Receiver



349⁹⁵
With
Rosewood
Enclosure
No Money Down*

- Baxandall-Type Tone Controls
- 4 Way Speaker Selector Switch
- FM Stereo Indicator Light
- FM Muting

Quality AM/FM stereo receiver with a vast array of features: Baxandall-type tone controls—provides distortionless bass and treble boost and cut; loudness contour switch, pushbutton FM muting to reduce interstation noise and hiss on FM, high filter switch; speaker selector switch for listening to your main speakers, your remote speakers, or both sets of speakers simultaneously; front panel stereo headphone jack and record output jack. Specifications: FM Tuner Section—Sensitivity—2.0 μ V, harmonic distortion—less than 0.5%, separation—30 db. Amplifier Section—Music power 140 watts \pm 1 db, at 4 ohms, RMS power 42/42 watts, harmonic distortion—0.5%, power bandwidth, IHF 25 Hz to 20,000 Hz. Input Sensitivity: Phono, 2.8 mV; Aux., 200 mV; Mon, 300 mV. With rosewood finished cabinet. Dimensions: 18 $\frac{1}{2}$ x5 $\frac{1}{2}$ x16". For 117 V, 60 Hz AC.

21 R 3376WX Shpg. wt., 29 $\frac{1}{2}$ lbs. Net 349.95

NEW Model 401 150 Watt Remote Control AM-FM Stereo Receiver



449⁹⁵
With
Rosewood
Enclosure
No Money Down*

- Includes Remote Control Unit
- Automatic Stereo Switching
- Baxandall-Type Tone Controls
- 4-Way Speaker Selector Switch

Deluxe AM/FM Stereo Receiver with accessory Remote Control Unit (included). Features: Automatic stereo switching—patented Stereo-beacon Circuit indicates whether the incoming FM broadcast is in stereo or mono and switches to the correct mode of operation automatically; Baxandall-type tone controls provides distortionless bass and treble boost and cut, pushbutton FM muting eliminates FM interstation noise, 4-way speaker selection—main, remote, main and remote, headphones. Specifications: FM Tuner Section sensitivity—2.0 μ V, harmonic distortion—less than 0.5%, stereo separation—30 db, AM Tuner Section sensitivity—250 μ V, Amplifier Section music power—150 watts \pm 1 db, RMS 45/45 watts, power bandwidth—25 Hz to 20,000 Hz. Input Sensitivity: Phono, 2.8 mV, Aux, 200 mV, Mon, 300 mV. With rosewood finished cabinet. For 117V 60 Hz, AC. Size: 18 $\frac{1}{2}$ x5 $\frac{1}{2}$ x16".

21 R 33775WX Shpg. wt., 29 $\frac{1}{2}$ lbs. Net 449.95

New Model 201 80 Watt AM/FM Stereo Receiver



219⁹⁵
less
enclosure

- Audio Attenuator
- Tape Monitoring
- 4-Way Speaker Selector
- Tuning Meter

The 201 features 80 watt music power, tape monitoring facilities, audio attenuator for headphone usage, Baxandall tone controls for bass and treble, four-way speaker selector, two AUX inputs. Specifications: FM Tuner Section—IHF Sensitivity 3.0 μ V; Harmonic Distortion: 0.6%; Separation 35 db. Amplifier Section: Music Power—80 watts \pm 1 db at 8-ohms, RMS Power 25/25 watts @ 8 ohms, Power bandwidth, 25 to 20,000 Hz. Sensitivity: Phono 4 mV AUX 1 and 2; 200 mV; Monitor 200 mV. For 117 VAC, 60 Hz. Shpg. wt., 18 $\frac{1}{2}$ lbs. No Money Down* 21 R 33783WX Net 219.95 Walnut Cabinet for 201. Shpg. wt. 4 lbs. 21 R 33760W Net 14.95

NEW Model 202 100 WATT AM/FM STEREO RECEIVER



269⁹⁵
less
enclosure

- Tape Monitoring Facilities
- 4 Way Speaker Control
- FM Tuning Meter

Moderately priced AM/FM stereo Receiver featuring 100 watts music power, tape monitoring facilities, muting, mono/stereo modes of operation, lighted program selector, Baxandall feedback circuit for bass and treble, and main, remote, main and remote speaker selector. Specifications: FM Tuner Section—IHF Sensitivity: 2.5 μ V; Harmonic Distortion: 0.6%; S/N ratio: 64 dB; FM Stereo Separation: 35 db; AM Tuner Section—Selectivity: 44 db; Amplifier Section: Music Power: 100 Watts \pm 1 db at 8 ohms; IHF Power at 8 ohms: 40/40 watts; RMS Power at 8 ohms: 28/28 watts; Power Bandwidth IHF: 25 to 20,000 Hz; Sensitivity: Phono Low: 2.5 mV, Phono High: 8mV, Aux 1 & 2: 200 mV. Size: 15 $\frac{1}{2}$ "W x 4 $\frac{3}{4}$ "H x 14 $\frac{1}{4}$ "D. Wt., 23 $\frac{3}{4}$ lbs For 117 VAC 60 Hz. 21 R 33692WX Net 269.95 Walnut Cabinet for 202. Shpg. wt., 4 lbs. 21 R 33700W Net 14.95

Model TX-50 65-Watt Stereo Control Amplifier



159⁹⁵
less
enclosure

- 4-Way Speaker Selector: Main, On/Off; Remote,
- Front Panel Head-phone Jack
- Overload Protective Circuitry

Provides a full complement of controls plus full tape and phono facilities. Loudness contour switch restores natural tonal balance at low and high volume levels. High frequency filter switch eliminates annoying high frequency noise. Has front panel headphone jack with complementary speaker silencing switch, 4-way speaker switch selects main, on/off and remote, on/off. Power Output: 65 watts \pm 1 db at 8 ohms. Harmonic Distortion: 0.5% at 1 kHz. Power Bandwidth: 25-25,000 Hz, at 8 ohms. Stereo Separation: better than 45 db. Hum and Noise: —85 db. For 117 Volts AC 60 Hz. Size: 15 $\frac{1}{4}$ "Wx4 $\frac{1}{4}$ "Hx 9"D. Shpg. wt., 16 lbs. 21 R 33585W Net 159.95 Oiled Walnut Cabinet, Wt. 6 $\frac{1}{2}$ lbs. 21 R 36414W Net 22.95

Professional Solid State Components by **Dynaco**

Quadaptor® 4-Dimensional Stereo Adapter

NEW

KIT 19⁹⁵
WIRED 29⁹⁵



Add the Quadaptor and two speakers to your 2-channel stereo amplifier or receiver—and listen to 4-dimensional stereo sound from your present records, tapes, and FM-Stereo broadcasts. The Dynaco Quadaptor 4-dimensional system provides faithful reproduction of the original "recording studio sound", the added ambience (reflected sound) in stereo recordings—which is normally not heard in a conventional 2-speaker system. The Quadaptor is also compatible for recordings using other related matrix-type systems. The Quadaptor actually serves as a junction box between the stereo amplifier and the 4 speakers. It provides the essential circuitry for recovering (to de-matrix) the 4 separate signals from the 2 stereo channels. Shpg. wt., 3 lbs. Size 7" x 7" x 8". No Money Down*

21 R 23586 Quadaptor Kit Net 19.95
21 R 23594 Quadaptor Wired Net 29.95

FM-5 Stereo FM Tuner



NEW

KIT 149⁹⁵ | **WIRED 249⁹⁵**

All transistorized. Has "DynaTune®" which automatically fine tunes a desired station to the minimum distortion point in both mono and stereo. Highly effective 19 and 38 kHz filters to prevent interference when making off-the-air tape recordings. Low phase shift permits more than 40 db stereo separation at mid-frequencies and 30 db to beyond 10 kHz. Includes an auxiliary high level input for any future developments requiring additional circuitry, such as four-channel multiplexing. SPECIFICATIONS: IMF sensitivity (noise and distortion-30 db @ 100% modulation): 1.75 µV. Freq. response, 50 Hz to 15 kHz ± 1 db. Capture ratio: 1.5 db. Ultimate Signal to Noise ratio: 65 db. Front panel controls: Power/Volume; Tuning; Circuit Mode (off; muting; and DynaTune®); Mono-Stereo Filter; Output (FM; Auxiliary). Size: 13½ x 9 x 4¼" H. 10 Watts, 100-120V, 220-240V, 50/60 Hz AC. Shpg. wt., 11 lbs. No Money Down*

21 R 23560WX FM-5 Kit Net 149.95
21 R 23578WX FM-5 Wired Net 249.95

PAT-4 STEREO PRE-AMPLIFIER



KIT 89⁹⁵ | **WIRED 159⁹⁵**

• Dyna Tone Control Circuit
Deluxe solid state stereo pre-amplifier offering complete control facilities for any conceivable stereo or music system source. Features exclusive "Dyna Tone Control Circuit" to assure truly flat response (Patent Pending). Also features a switch selected high frequency filter @ 7, 10, and 15 kHz. Plus flat position. SPECIFICATIONS: Freq. Response: ±0.5 db from 10 to 100,000 Hz. Harmonic Distortion less than 0.05% at 2 volts output between 20 Hz and 20,000 Hz. IM: less than 0.5% at 2 volts output; Tone Control Range ±12 db at 50 Hz and 10,000 Hz. Noise: less than 2 mv. 8 silicon Transistors, 2 diodes. For 120 or 240 volts 50 or 60 Hz. Shpg. wt., 9 lbs. Size: 13½x4¼x18".
21 R 23255W PAT-4 Kit Net 89.95
PAT-4A Factory Wired and Tested
21 R 23263W Net 159.95

"STEREO-80" POWER AMPLIFIER



• 40-Watts RMS Power Output Per Channel

KIT 119⁹⁵ | **WIRED 159⁹⁵**

The Stereo-80 is a conservatively designed stereo amplifier rated at 40-watts RMS per channel with both channels operating simultaneously. Excellent frequency response with low distortion levels, incorporates current limiting protection which eliminates the inconvenience or replacing fuses or resetting circuit breakers whenever the amplifier is overdriven. Illuminated rocker power switch. Frequency response; 15 Hz to 50 kHz ± .5 db. Harmonic distortion: less than 0.5% up to 40 watts per channel; IM distortion: less than 0.5% up to 40 watts per channel. Power bandwidth; 6 Hz to 50 kHz. Input sensitivity: 1.3 volts. Hum and Noise: 95 db below rated output. For 100-120/220-240 VAC 50/60 Hz. Size: 13½x4¼x9"D. Shpg. wt., 14 lbs. Stereo-80 Kit No Money Down*

21 R 23289W Net 119.95

Stereo-80 Factory Wired and Tested
21 R 23297W Net 159.95

"STEREO-120" POWER AMPLIFIER



• 60 Watts RMS Power Output Per Channel

KIT 159⁹⁵ | **WIRED 199⁹⁵**

A solid state stereo power amplifier which offers superb performance. Perfect companion to the PAT-4. No interstage or output transformers are used. Power output per channel: 60 watts RMS @ 8 ohms. Features: Electronic protection against open circuits or shorts; by means of a current limiting biasing circuit. No fuses or circuit breakers are needed. SPECIFICATIONS: Frequency Response: 10 Hz to 100kHz; ±0.5 db. Harmonic Distortion: less than 0.5% at any power level up to 60 watts. IM Distortion: less than 0.5% up to 60 watts. Noise: 95 db below rated output. 15 Transistors, 15 diodes. Size: 13x10½x4". For 120/240 VAC 50/60 Hz. Shpg. wt., 19 lbs. No Money Down*

21 R 23230W Kit Net 159.95

Factory Wired and Tested
21 R 23248W Net 199.95

SCA-80 INTEGRATED STEREO AMPLIFIER



KIT 169⁹⁵ | **WIRED 249⁹⁵**

Solid state, integrated stereo control amplifier combining the power amplifier of the Stereo-80 and a preamplifier incorporating most of the features of the PAT-4. 40-watts RMS per channel @ less than 0.5% H.D. from 20-20,000 Hz at full power. Power Bandwidth: 6 Hz to 50 kHz. Input Sensitivity: Phono, 3 mv; High Level, 0.13 v. Hum and Noise: Phono, better than -80 db. Tape monitor switch, speaker selector switch, front panel stereo headphone jack. Size: 13½x4¼x10"D. For 100-120/200-240 VAC 50/60 Hz. Shpg. wt., 17 lbs. No Money Down*

21 R 23271W SCA-80 Kit Net 169.95

SCA-80 Factory Wired and Tested
21 R 23305W Net 249.95

OTHER DYNA COMPONENTS

PAS-3X Stereo Pre-Amplifier Kit. Shpg. wt., 10 lbs.

21 R 23016W Net 79.95

PAS-3XA Stereo Pre-Amplifier Wired. Shpg. wt., 9½ lbs.

21 R 23024W Net 109.95

Stereo 70 70-watt Stereo Basic Amplifier. Shpg. wt., 30 lbs.

21 R 23032W Net 99.95

Stereo 70 70-watt Stereo Basic Amplifier. Shpg. wt., 31½ lbs.

21 R 23040W Net 129.95

EICO Solid State Hi-Fi Components

CORTINA 3780 50-WATT AM/FM STEREO RECEIVER



KIT
109⁹⁵
WIRED
169⁹⁵

• All Silicon Audio Amplifier Section Delivers
50-Watts ± 1 db at 4 Ohms

• Pre-Assembled and Pre-Aligned RF, IF and MPX Sections

Features time switching multiplex tuner circuit, plus FET and all silicon solid-state circuitry. FM SECTION—Sensitivity (IHF): 3.5 μV for 30 db quieting. Harmonic Distortion: less than 1.75%. Stereo Separation; 33 db @ 1 kHz. AMPLIFIER SECTION—Frequency Response: 20 to 20,000 Hz. Channel Separation; 45 db. Input Sensitivity: 3.8 mV mag. phono; 300 mV all others. Input Impedance: 47K mag. phono; 100K all others. Output Impedance: 4-16 ohms. For 105-130VAC., 50/60 Hz. Size: 4x16½x9¼". Shpg. wt., 14 lbs.

21 R 26043WX Model 3780 Kit No Money Down* Net 109.95
21 R 26050WX Model 3780 Wired No Money Down* Net 169.95

NEW EICO "QUATRASONIC" 4 DIMENSIONAL ADAPTER



KIT
17⁹⁵
WIRED
29⁹⁵

Convert your present stereo system to 4 dimensional stereo sound. Just add the Quatrasonic adapter and two speakers. No additional stereo amplifier is needed. You will be able to listen to the reflected sounds already present on your records and tapes that cannot normally be heard on a conventional 2 speaker stereo system. Requires no AC power. Size 3¼Hx6Wx6¼"D. Shpg. wt., 2 lbs.

Quatrasonic Kit
21 R 26068 Net 17.95
Quatrasonic Wired
21 R 26076 Net 29.95

CORTINA 3080 50-WATT STEREO AMPLIFIER



KIT
69⁹⁵

Extremely compact, "low silhouette" design. Output: 50-watts ± 1 db @ 4 ohms. Response: 20 to 20,000 Hz ± 3 db. Separation: 45 db. Sensitivity: Mag. Phono 3.8 mV; Aux., and Tape 300 mV. Impedance: Mag phono 47K; Aux., and Tape 100K ohms. Power Bandwidth: 20 to 30,000 Hz. Output Imped., 4-16 Ohms. Front panel stereo headphone jack. Includes vinyl clad metal cabinet. For 105-130 VAC., 50/60 Hz. Size: 3¼x12x6¾". Shpg. wt., 9 lbs.

Model 3080 Kit
21 R 26001W No Money Down* Net 69.95
Model 3080 Wired
21 R 26019W No Money Down* Net 109.95

CORTINA 3300 FET AM/FM STEREO TUNER



KIT
69⁹⁵

Pre-Assembled and pre-aligned RF, IF and MPX sections. Advanced FET wideband circuitry for maximum sensitivity, selectivity, separation and stability. Outputs for direct "off-the-air" tape recording. Features disappearing black tuning dial. Specification FM SECTION—Sensitivity (IHF): 3.5 μV. Harmonic Distortion: less than 1.75%. Capture Ratio: less than 4%. S/N Ratio: 60 db. Stereo Separation: 33 db @ 1 kHz. AM SECTION—Usable Sensitivity (IHF): 200 μV/m. S/N Ratio: 45 db. Selectivity: 30 db. Includes vinyl metal cabinet. Size: 4¼x12x6¾". Shpg. wt., 6 lbs.

21 R 26027W Model 3300 Kit Net 69.95
21 R 26035WX Model 3300 Wired 109.95

CORTINA 3070 80-WATT STEREO AMPLIFIER




KIT
99⁹⁵

"All Silicon Solid State Design" offers powerful performance and true-to-life sound. Delivers 40 watts of continuous power per channel ± 1 lb at 4 ohms, 35 watts IHF @ 4 ohms. Freq. Response: 5-100,000 Hz ±1.5 db; 8-60,000 Hz ±0.5 db. Hum and Noise: 72 db below rated output. Input Sensitivity: 4.2 mv on magnetic phono; 270 mv on auxiliary, tuner and tape. Input Impedance: 47k ohm on magnetic phono; 110k minimum on other inputs. Danish walnut vinyl clad case. For 105-130V 50/60 Hz Ac. 3½x12x8"D. Shpg. wt., 13½ lbs.

21 R 25375W Model 3070 Kit Net 99.95
21 R 25383W Model 3070 Wired 139.95

Acoustic Research Solid State Hi-Fi Components

120 WATT SOLID STATE STEREO AMPLIFIER



250⁰⁰
With Black Anodized Aluminum Cover

All silicon solid state circuitry. Response: 20-20,000 Hz ± 1 db at full power or below. Distortion is less than 0.5% from 20-20,000 Hz up to full power. Input sensitivity: phono circuit—2 mv. to 5 mv. (adjustable); tape playback and tuner inputs—200 mv. for full power levels plus speaker fuses. For 110-120 volts AC, 60 Hz. 15¼x10¼x10". Shpg. wt., 28 lbs.

21 R 72666WX No Money Down* Net 250.00
Walnut wood cover for above. Wt., 4 lbs.
21 R 72674W Net 15.00

120 WATT SOLID-STATE STEREO FM RECEIVER



420⁰⁰

FET front end with 4-section capacitor, multisection crystal IF filter, IC IF amplifiers, and 2μV sensitivity insure superb FM reception. Power output: 60 watts rms @ 4 ohms. Self-resetting thermostatic circuit breakers in both channels, tape monitor and speaker-head-and-switch. Outputs for tape recorder, center channel, headphone, and 4-16 ohm speakers. For 110-120 VAC, 60 Hz. Size: 17¼x16x6H 11¼"D.

21 R 72799WX Shpg. wt., 32 lbs. No Money Down* Net 420.00
Walnut Wood Cover for above.
21 R 72807W Shpg. wt., 5½ lbs. Net 20.00

*See Page 22 for Full Credit Details on Easy Pay Plan

EICO Environmental Color Lights



Model 3450 4-Channel Color Organ with Active Filters

Kit **79⁹⁵** Wired **109⁹⁵**

- Easily Connects to Speaker Leads
- Watch the Music You Love Spring to Life As a Vibrant Interplay of Colors

- Individual External Color-Crossover Controls for Precise Color Mixing
- All electronic solid-state color organ provides true frequency synchronization of sound with color. See every tone, every note, every combination of instruments create its own vivid pattern. Electronically converts music into color.

org light. The color (hue) is controlled by the pitch (frequency) of the music, and the brightness by the loudness of each frequency band. 4 color frequencies—red, blue, green, and yellow with positive switching of colors. Attractive walnut grain cabinet with shatterproof plastic front. Comes in kit or factory wired. Size: 30 x 15 x 11"D. Shpg. wt., 31½ lbs. For 117 VAC., 60 Hz. No Money Down*

21 R 2588WX Model 3450 Kit Net 79.95
21 R 2589WX Model 3450 Wired Net 109.95

NEW Model 3430 3-Channel Color Organ

Kit **34⁹⁵** Wired **49⁹⁵**

No Money Down*

- Individual External Color-Crossover Controls for Precise Color Mixing



Music transformed into color electronically. True frequency synchronization—color that pulses and beats, ebbs and swells, responding to every note of the sounds. Easily connects to speaker leads. The color (hue) is controlled by the pitch (frequency) of the music, and the brightness by the loudness of each frequency band. Attractive walnut grain cabinet with shatterproof plastic front. Comes in kit or factory wired. For 117 VAC, 60 Hz. Size: 24 x 12 x 7"D. Shpg. wt., 11 lbs.

21 R 25433W Model 3430 Kit Net 34.95
21 R 25441W Model 3430 Wired Net 49.95

Model 3475 Deluxe Audio Activated Strobe Light

Kit **39⁹⁵**
Wired **59⁹⁵**



No Money Down*

The music itself continuously controls the flash rate. Just attach to the speaker leads of your sound system. Each music beat creates a different flash rate automatically. Features aluminum deflector and shield. Sensitivity control. Easily replaceable plug-in type Xenon bulb. For 117 VAC, 60 Hz. Size: 6½ x 9½ x 5¼". Shpg. wt., 6¼ lbs.

21 R 25813 Model 3475 Kit Net 39.95
21 R 25821 Model 3475 Wired Net 59.95
Model 3470 "Adjustable Rate" Electronic Strobe. Flash rate is adjusted by speed rate control. Same size as above. Shpg. wt., 5¼ lbs.
21 R 25839 Model 3470 Kit Net 24.95
21 R 25847W Model 3470 Wired Net 39.95

Model 3465 3-Channel Sound Lite Translator

Kit **49⁹⁵**
Wired **69⁹⁵**




No Money Down*

- Transforms Sound Waves to Light Waves
- Solid-State Active Filter Design

Varies intensity of light by means of a change in frequency (high, low, or mid-range) from the output of a sound source (PA, Hi-Fi System, Phono). 3 separate 400-watt light sources can be hooked up to output receptacles on the translator. Using an arrangement of color bulbs, you can project on a wall or screen a spectacular lighting effect in rhythm with the music played. Exclusive EICO solid-state active filter design. Vinyl-clad metal cabinet. For 117 VAC, 60 Hz. Size: 6½ x 9½ x 5¼". Shpg. wt., 6¼ lbs.
21 R 25771 Model 3465 Kit Net 49.95
21 R 25789W Model 3465 Wired Net 69.95

NEW Model BLS-10 High Intensity Blacklite/Strobe



Kit **24⁹⁵** Wired **34⁹⁵**

Instant-starting 18 inch fixture features a rugged high intensity 15-watt UV bulb in a polished chrome reflector—almost equals 75 watts of ordinary light. Easily mounts over paintings in windows, etc., with multi-positional mounting "Key Hole" type slots. Throws its mystifying illumination as far as 25 feet or more. Exclusive added feature of Solid-State "Strobe" (pulse) circuit for adjustability of on-off rate. Enables you to synchronize illumination with the rhythm of your music for extraordinary effects. Jet Black cabinet. Size: 4½ x 18 x 4". Shpg. wt., 9 lbs.

Model BLS-10 Kit Net 24.95
21 R 25458W Net 24.95
Model BLS-10 Wired
21 R 25466W No Money Down* Net 34.95

NEW Model CS-3 Three Channel Color Organ/2-Way Speaker System

Kit **39⁹⁵** Wired **59⁹⁵**



Speakers and a color organ all-in-one. Walnut-grained enclosure fits anywhere—bookshelf, table, etc. Full fidelity sound from powerful 6" woofer and 3" tweeter. Color lights of reds, blues, and greens individually respond to volume and corresponding frequencies of the music. Each color channel has its own sensitivity control. Size: 24 x 12 x 7". Shpg. wt., 15 lbs.
21 R 25979W Model CS-3 Kit Net 39.95
Model CS-3 Wired
21 R 25987W No Money Down* Net 59.95

NEW Model 4600 "Light Sequencer"



Kit **19⁹⁵** Wired **29⁹⁵**

Remember the "moving" lights on the theatre marquee? . . . With the EICO 4600 you can produce, in any custom serial arrangement of any color lamps, a similar sequence of "on-off" states that create the appearance of light "running around" in that configuration. The Speed Control makes possible a wide latitude of sequencing or light "chasing." All solid-state design. 3 lamp channels—up to 150 watts maximum per channel. Maximum wattage per channel 150 watts. Size: 3½ x 6 x 3". Shpg. wt., 1½ lbs.

21 R 25953 Model 4600 Kit Net 19.95
21 R 25961 Model 4600 Wired Net 29.95

COLOR LIGHTS, STROBES & ACCESSORIES

Deluxe



4 CHANNEL FREQUENCY SYNCHRONIZED SOUND ACTUATED COLOR LIGHTS

59⁹⁵

- Giant 28½" by 13½" Screen
- 4 Adjustable Color Controls
- Continuously Flowing Color Images

A sophisticated electronics system that provides true synchronization of color and sound. See every tone, each note, and every combination of instruments create its own vivid color pattern. The system includes 4 color channels: red, blue, green and yellow that are everchanging, interweaving, and blending to produce fantastic, spontaneous, frequency synchronized multi-color patterns to the music reproduced by your speakers. Connects in seconds to your HI-FI system or guitar amplifiers without any loss in sound quality or volume. All solid state integrated circuitry. Handsome walnut vinyl covered wood cabinet. Size: 30x15x11". For 117 VAC 60 Hz. Shpg. wt., 24 lbs. **21 R 03000WX No Money Down* Net 59.95**

3-Sided Prismatic Color Audio Lites



New Low Price 24⁹⁵

Color Lights priced to fit your budget. One piece 3 sided prismatic lens produces a panorama of colors that have a 3 dimensional effect. Solid state electronic control transposes music sound impulses into multi-color flashing light patterns. Hooks up to speaker leads of any sound source. For 117 VAC 60 Hz. Size 18x11x7". Walnut vinyl grained wood cabinet. Shpg. wt., 8½ lbs. **13 R 75526W Net 24.95**

4-Color Sound-Actuated Color Lights

34⁹⁵

- Easily Connects to Speaker Leads

Top quality, 4-color, solid-state sound actuated color organ. You can actually see every note and tone converted to a brilliantly moving panorama of colored, dancing images with each note and tone produced by the music. Flashing red, blue, green and yellow colors create an entertaining display of multi-color, 3-dimensional spontaneity which varies to the amplitude of the sound source. HI/low inputs allows you to adjust for music power levels; exclusive 4-in-1 color control. Housed in walnut wood grained cabinet. For 110 VAC 60 Hz. Size: 24x12x10". Shpg. wt., 15 lbs. **21 R 25904W No Money Down* Net 34.95**

WIRELESS 4 COLOR AUDIO LIGHTS. Same as above except with built-in microphone. No speaker leads to connect. Size: 24x12x10". **21 R 26084W Shpg. wt., 10 lbs. Net 39.95**

"Color Column" Audio Lites


44⁹⁵

- 21" H x 7" D
- Full Spectrum of Abstract Color Lighting

No Money Down*

Handsome table-top color columns only 21"Hx7"D. Magnificent abstract color images in everchanging motion. These unique color cylinders, make flashing patterns of colored lights pulsating to the rhythm of your music. Hooks up to the speaker leads of your HI-FI system, tape recorder, or guitar amplifier. Column is constructed of prismatic polycarbonate plastic with "Brite" chrome base. For 117 VAC. Shpg. wt., 5½ lbs. **13 R 75534W Net 44.95**

"Mini" Electronic Strobe Light



ONLY **19⁹⁵**

- Fully Transistorized
- Only 5¼" High

A compact electronic strobe light unit in attractive walnut finished cabinet. Use for special lighting effects in photography, combo groups, or discotheques. Adjustable speed control can be varied to the beat of music from 1 to 12 flashes per second. A 4

inch chrome reflector, clear plastic lens cover and Xenon flash tube deliver a powerful light flash over a 60° arc. For 117 VAC 60 Hz. Size 5¼x5¼x4¼". Shpg. wt., 3 lbs. **13 R 48010 Net 19.95**

3-Channel Color Light Control Center

39⁹⁵

- True Frequency Division
- 500 Watts Per Channel (1500 Watts Total)
- Easily Connects to Any Speaker




Transform a large room into a total light-sound environment! Translates musical patterns into dynamic patterns of throbbing, flashing lights precisely synchronized to the music. Provides 500 watts per channel (1500 watts total). Audio spectrum is divided into 3 ranges, low, medium and high, by 3 separate, transistorized frequency selective amplifiers. Accepts nine 150 watt or eighteen 75 watt lights at once; on/off switch; 3 intensity adjustments; on/off pilot light and three channel indicator lights. For 110-120 VAC, 15 amps. max. **13 R 48002 Shpg. wt., 3 lbs. No Money Down* Net 39.95**

*See Page 22 for Full Credit Details on Easy Pay Plan

Ultra-Compact Criterion Hi-Fi Speaker Systems

CRITERION "2X" 2-Speaker 2-Way Acoustic Suspension System



11"W x 7"D x 8 1/4"H.

Ideal for low-powered amplifiers or receivers

Ideal for use as extension or remote speakers in any hi-fi system

Ideal replacement speakers for upgrading sound quality in modular compact phono systems

A Truly Compact High Fidelity Speaker System with a Power Handling Capacity of 20 watts

14⁹⁵
each


2 For 29⁹⁰

- 5" Acoustic Suspension Woofer with 7/8" voice coil and 1 lb. magnet structure
- 3 1/2" cone-type Tweeter
- 60-19,000 Hz overall response

A low-cost, ultra-compact 2-way speaker system only 11"W x 7"D x 8 1/4"H. Provides astonishing music reproduction for its size. Perfect for use as main speakers with low-powered stereo amplifiers or receivers... as remote or extension speakers in any existing stereo hi-fi system—even as replacement speakers to upgrade sound quality in modular compact phono systems. Small size and handsome walnut finish lets you use them anywhere in the home or office... on a bookshelf, end-table, desk—locations are actually unlimited. Fine sound quality results from the use of techniques employed in high-priced hi-fi speaker systems. 5" woofer in a sealed cabinet uses the well-known acoustic suspension principle to produce substantial bass from a system this size. A 3 1/2" tweeter provides smooth, crystal-clear sound up to 19,000 Hz—beyond the limit of hearing for most people. Interior of rigidly constructed enclosure is fiberglass-loaded to reduce unpleasant resonances—Finished on four sides in rich oiled walnut veneer, with grille cloth in subdued dark brown color. Overall response 60-19,000 Hz. Crossover frequency 4000 Hz. Power Handling Capacity 20 watts. Impedance 8 ohms. Imported.

99 R 02388W Shpg. wt., 9 lbs. Net Each 14.95
2 for 29.90


CRITERION "25A" 2-Speaker 2-Way Air Suspension 8" System



12 3/8"W x 7"D x 10 1/4"H

Only
19⁹⁵

PERFECTLY MATCHED COMPONENTS



POWER HANDLING CAPACITY 25 WATTS

5 Year AAA Guarantee
See page 415
for terms

- 8" Woofer, 2 1/2" Tweeter
- Frequency Response: 55-19,500 Hz.
- Rich, Hand Rubbed Oiled Walnut Finish

FULL SIZE PERFORMANCE... this outstanding ultra-compact Lafayette 2 speaker 2-way system achieves a purity of sound and music quality that is astounding for a speaker system measuring only 12 3/8"W x 7"D x 10 1/4"H. Perfect for use anywhere in your home or office. You get rich styling plus true high fidelity music reproduction at a low, low price. System consists of a powerful 8" woofer which provides smooth bass sound reproduction down to 55 Hz, and a 2 1/2" cone tweeter that gives you sparkling clean high frequency response. Also includes a built-in 8,000 Hz. electrical crossover network. Power handling capacity of 25 watts makes it compatible for use with most amplifiers and receivers. Interior of cabinet is designed to damp out standing waves and other spurious vibrations. Specifications: Frequency Response: 55-19,500 Hz. Voice Coil Impedance: 8 ohms. Woofer 8" high compliance with 32.6 oz. magnet structure; rolled edge suspension. Tweeter: 2 1/2" cone type with 2.4 oz. magnet structure. Electrical Crossover: 8,000 Hz. Imported. Shpg. wt., 12 1/2 lbs.

99 R 02255W Net 19.95


Quality Speaker Systems at Popular Prices

CRITERION "50A" True 2-Way Bookshelf Speaker System


ONLY
29⁹⁵

**POWER HANDLING
CAPACITY
30 WATTS**

- Powerful 8" Woofer with 1" Voice Coil
- "Tuned" Enclosure with Tube-Type Ducted Port
- Overall Response 50-19,000 Hz
- 7,000 Hz Electrical Crossover
- 3½" Cone Type Direct Radiator Tweeter
- Rich Hand-Rubbed Oiled Walnut Finish



**5 Year AAA Guarantee
see Page 415**



Improved version of our best-selling Criterion "50". Provides impressive hi-fi sound, yet measures only 10½" H x 19" W x 8¾" D. An 8" heavy-duty woofer with 36 oz. magnet structure and 1" voice coil is acoustically matched to a 3½" cone-type direct radiator tweeter. Provides deep, rich bass down to 50 Hz with sparkling mid-range and high frequency reproduction to beyond audibility. Electrical crossover operates at 7,000 Hz. Enclosure is bass reflex design using a ducted port of the tube type to provide proper acoustic "tuning" of the enclosure. The ducted port provides a special path for the low frequency sound waves radiated from the rear of the woofer so that they emerge "in-step" with those radiated from the front of the speaker, providing substantially greater bass sound power from the system. Finished on all four sides in a rich, hand-rubbed oiled walnut veneer with beige acoustic grill material. Rated at 30-watts. Designed for vertical or horizontal placement. Overall response: 50-19,000 Hz. Nominal Impedance: 8 ohms. Imported. Shpg. wt., 1.8 lbs.

99 R 02131W

Net 29.95


CRITERION "77"

3-Speaker 3-Way Bookshelf Acoustic Suspension Speaker System

ONLY
39⁹⁵

**POWER HANDLING
CAPACITY
30 WATTS**

- 8½" Woofer with 1½ Lb. Magnet Structure and 1" Voice Coil
- 3½" Mid-Range Speaker with 1/2" Voice Coil
- 1½" Direct-Radiator Type Tweeter
- Crossover Frequencies: 3,000 and 10,000 Hz
- High Frequency Brilliance Control
- Rich, Hand-Rubbed Oiled Walnut Finish



**5 Year AAA Guarantee
see Page 415**

Expert combining of components for outstanding performance at an unbelievable low price! Heavy-duty 8½" woofer in a sealed fiberglass-filled enclosure uses the well-known acoustic suspension principle to extend response down to a low 40 Hz, assuring deep, natural bass with outstanding clarity and impact. Reliable 3½" cone-type mid-range speaker reproduces clean, full bodied sound throughout the important middle frequency range. Sharply detailed high frequency reproduction is accomplished with a 1½" direct radiator type tweeter... response is true, complete and unmarred by rattle or breakup. Electrical crossover network at 3,000 and 10,000 Hz assures smooth, balanced distribution of sound over the audio spectrum. Compensating high frequency level control (on rear) permits you to tailor the sound to your specific room acoustics. Handsome walnut finish on four sides with tastefully accented brown grill cloth to blend with any decorating scheme. Overall response: 40 Hz to 19,000 Hz. Impedance: 8 ohms. Imported. Size: 19¾" W x 10½" H x 8¾" D. Shpg. wt., 1.9¾ lbs.


99 R 02321W No Money Down*

Net 39.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette CRITERION[®] '100B'

40-Watt 10" 3-Speaker 3-Way Bookshelf System



POWER HANDLING CAPACITY 40 WATTS

49⁹⁵

No Money Down*


Magnificent Full Range Sound Reproduction from a 10-inch System

5 Year A.A.A. Guarantee

A Lafayette quality product that is guaranteed against defects in material and workmanship for 5 years. If this unit fails to operate due to such defects, simply return it prepaid with your original sales slip or order. Lafayette will repair it without charge including return transportation.

- ★ Powerful 10" Woofer with 5½ Lb. Magnet Structure and 2" Diameter Voice Coil
- ★ 3½" Mid-Range Speaker
- ★ 1½" Direct Radiator Super Tweeter
- "Tuned" Enclosure with Tube-Type Ducted Port
- Full 12 db/Octave Electrical Crossover Network at 3,500 and 10,000 Hz
- Overall Response 30-19,000 Hz
- High Frequency Brilliance Control

System Design Perfectly Matched Components



Top quality, moderately priced 3-speaker 3-way system that delivers really "big" sound. Equipped with 3 separate speakers for wide-range response—a powerful 10-inch woofer with a 5½ lb. magnet structure, a 3½" mid-range speaker, and a 1½" direct radiator type super tweeter. All 3 speakers are acoustically matched and employ a full 12 db/octave L/C crossover network at 3,500 Hz and 10,000 Hz. Features High Frequency Control at rear of cabinet. The use of an acoustically "tuned" enclosure results in a reinforcement of the low frequencies, and produces enhanced bass response. Superb "Criterion" styling blends in with the most elegant decor. The enclosure is finished on all four sides in a rich, hand-rubbed oiled walnut veneer and tastefully framed in an ebony and gold picture frame molding with white and gold acoustic grill material. Highly efficient operation assures rich, full-bodied sound even with low-power amplifiers. For vertical or horizontal placement. Dimensions are 21½" W x 11¾" H x 9¾" D. Overall frequency response: 30-19,000 Hz; crossover frequencies—3,500 and 10,000 Hz; nominal impedance: 8 ohms; power handling capacity 40 watts program material. Imported. Shpg. wt., 29 lbs.

99 R 02115W

Net 49.95

SYSTEM DESIGN

The enclosure is a bass-reflex design using a "sonic tube" to provide proper acoustic "tuning" of the enclosure. The tube provides a special path for the low frequency sound waves radiated from the rear of the woofer so that they emerge "in-step" with those radiated from the front and thus provides substantially greater bass sound power from the system. Solid wood construction plus the use of sound absorbent material ensures an extremely rigid enclosure free of undesirable resonances. A powerful 10-inch speaker with a 5½ lb. magnet structure provides reproduction of the low frequencies down to 30 Hz. A 3½" cone-type mid-range speaker covers the mid-range frequencies, and a 1½" direct radiator type super tweeter reproduces the high frequencies. Smooth transition is achieved by means of electrical crossover at 3,500 and 10,000 Hz.

Lafayette CRITERION "150A"

3-Way Acoustic Suspension Speaker System



59⁹⁵

No Money Down*

POWER HANDLING CAPACITY 40 WATTS

Popular Priced Superb Quality Acoustic Suspension System

- Overall Response 30 to 20,000 Hz
- 10" Acoustic Suspension Woofer with 2 1/2 lb. Magnet Structure and 1 1/4" Edge-Wound Copper Voice Coil
- 3" Cone Type Mid-Range/Tweeter
- 1 1/2" Direct Radiator Super Tweeter
- L/C Crossover at 1600 Hz and 10,000 Hz
- High Frequency Level Control
- Fine Furniture Oiled Walnut Finish

5 Year A.A.A. Guarantee

A Lafayette quality product that is guaranteed against defects in material and workmanship for 5 years. If this unit fails to operate due to such defects, simply return it prepaid with your original sales slip or order. Lafayette will repair it without charge including return transportation.

Everything you'd expect to find in a larger system is here. A full, 3-way acoustic suspension design with 3 speakers—but using an enclosure only 1 cubic foot in size. Advanced acoustic design with skillful blending of all speakers provides wide-range natural sound—the ideal system for those wanting the finest possible reproduction from a compact enclosure. The system's main working element is a special 10 inch highly compliant woofer with a 2 lb. 8 oz. magnet structure and a 1 1/4" ribbon-type copper voice coil, edge-wound on an aluminum form. The cone of this woofer is loose and free from the usual stiff mechanical suspension. Instead, the woofer cone actually uses the air within the sealed enclosure to provide the spring suspension element. The extremely long cone travel combines with this type of suspension to give bass reproduction that is outstanding in its depth and power. A closed-back 3" cone-type driver provides natural reproduction of the upper mid-range and lower-high frequencies and assures authentic "presence". The extreme high frequencies are extended cleanly to beyond the limits of hearing by a 1 1/2" super-tweeter with an aluminum cone. Smooth, balanced reproduction over the entire sound spectrum is assured by the use of a full L/C crossover network, 1,600 & 10,000 Hz. The Criterion 150A also features a high frequency "brilliance" control on the rear of the cabinet. This enables balance of high frequency tones to suit individual tastes and match various room conditions. The enclosure is of solid 5/8" wood construction with fiberglass packing to virtually eliminate undamped resonance. All four sides are finished in luxuriant hand-rubbed oiled walnut with handsome beige grille. Imported. Shelf size: 19W x 11H x 8 7/8"D. Shpg. wt., 21 3/4 lbs.

99 R 02222W

Net 59.95

SPECIFICATIONS

System Response: 30-20,000 Hz; Woofer: 10" acoustic suspension high compliance with long excursion cone and a 2 lb. 8 oz. magnet structure and a 1 1/4" edge wound copper voice coil; Mid-Range/Tweeter: 3" Cone Type 1/2" voice coil, 4 oz. magnet; Super Tweeter: Direct Radiator type; 1 1/2", Crossover Network; Electrical (L-C) energy transfer circuit; Crossover Frequencies: 1600 & 10,000 Hz; Power Capacity: 40 Watts; Impedance: 8 ohms.

Superb 3-Way System In a Completely Sealed Enclosure

1 1/2" Super-Tweeter with Aluminum Cone 10" Acoustic Suspension Woofer with 2 1/2 lb. Magnet



Rich Hand-Rubbed Oiled Walnut Finish on Four Sides

Solid 5/8" Hardwood Cabinet Fully Air Tight and Fiberglass-Filled

3" Cone-Type High Frequency Driver

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette CRITERION[®] "4X" Deluxe 4-Speaker, 4-Way, 12" Speaker System



69⁹⁵

No Money Down*

- Overall Response 25 to 20,000 Hz
- Enclosure Uses "Sonic Tube" for Enhanced Bass
- 12" Woofer has 4½ lb. Magnet Structure and 2" Voice Coil
- 5" Midrange Driver in its Own Sub-Enclosure
- 3" High Frequency Tweeter
- 1½" Super-High Frequency Tweeter
- Fine Furniture Finish in Rich, Oiled Walnut

Here's a bookshelf speaker system that offers big, full-voiced sound at an extremely modest price—a combination that is sure to make this system one of our most popular. It's a carefully engineered 4-speaker system with a full 4-way electrical crossover, housed in a deluxe oiled walnut enclosure to give it the look of fine furniture. 4 separate speakers, each a brilliant performer over its assigned range, work in harmony to provide superb overall sound. The entire music range is reproduced effortlessly...thrillingly life-like in its quality. A big 12" woofer operating in a rigid fiberglass-filled enclosure with a tube-type ducted port (sonic tube), provides deep, enhanced bass. A 5" mid-range speaker housed in its own fiberglass-filled chamber and acoustically isolated from the main bass enclosure, assures smooth, peak-free reproduction in the important mid-range. Two high frequency units cover the upper musical ranges—a 3" speaker from 5,000 to 10,000 Hz, and a 1½" super tweeter from 10,000 Hz to 20,000 Hz. These units provide brilliant reproduction of the highs right out to inaudibility. System finished in rich oiled walnut veneer (on four sides for vertical or horizontal placement) plus a subdued dark brown grille cloth. Includes high frequency and mid-range controls which permit adjustment of the tonal response, polarized input terminals. Dimensions: 22 x 14¼ x 11¾" D. Imported. Shpg. wt, 39¼ lbs.

99 R 02370WX

Net 69.95

SPECIFICATIONS


Overall Response: 25 to 20,000 Hz. Speaker Units: 12" woofer, 5" mid-range, 3" tweeter, 1½" super-tweeter. Crossover Network: 4-way LC (coil-capacitor) at 800, 5,000 and 10,000 Hz. Enclosure Design: Tube-type ducted port enclosure, fiberglass-filled. Acoustic Controls: Continuously variable high frequency and mid-range level controls (off to maximum). Nominal Impedance: 8 ohms. Power Handling Capacity: 50 watts.

POWER HANDLING CAPACITY 50 WATTS

5 Year A/A/A Guarantee


A Lafayette quality product that is guaranteed against defects in material and workmanship for 5 years. If this unit fails to operate due to such defects, simply return it prepaid with your original sales slip or order. Lafayette will repair it without charge including return transportation.

Perfectly Matched Components



Lafayette CRITERION® "VI"

Deluxe 50 Watt 6-Speaker 4-Way Bookshelf System



Only **99⁹⁵**

No Money Down*


- Enclosure Uses "Sonic Tube" for Deep, Reinforced Bass
- 12" Woofer with 4 1/2 lb. Magnet Structure and Large 2" Voice Coil
- 5" Midrange Speaker Housed in a Sealed Fiberglass-Filled Sub-Enclosure
- 4 Separate High Frequency Speakers
- Frequency Response: 20-20,000 Hz
- Fine Furniture in Rich, Hand-Rubbed Oiled Walnut on 4 Sides
- Individual Midrange and High Frequency Level Controls

5 Year AAA Guarantee

A Lafayette quality product that is guaranteed against defects in material and workmanship for 5 years. If this unit fails to operate due to such defects, simply return it prepaid with your original sales slip or order. Lafayette will repair it without charge including return transportation.

A quality bookshelf system with the big, multi-dimensional sound that only multiple speakers can produce... and at an unbeatable price too! Every musical instrument is reproduced with brilliant realism because there are 6 speakers covering four portions of the entire audio spectrum. There's a big 12" speaker for the lows, a 5" unit for the midrange, two 3" tweeters for the highs and two 1 1/2" super-tweeters for the ultra high frequencies. The enclosure is also equipped with a tuned "sonic tube" that makes use of the acoustic output from the rear of the woofer to produce deep, reinforced bass for which this type of system is famous. And best of all, this system is efficient enough for use even with low powered stereo components—actually makes them sound better too! Yet, because it can handle up to 50 watts of power, you can also use this system safely with high powered components, either now or in the future. Includes continuously variable midrange and high frequency level controls and polarized terminals. Enclosure is of 3/4" construction and is fiberglass filled. Tastefully styled with a fine furniture finish on four sides for vertical or horizontal placement, either on shelf or floor standing. Snap-out front panel with a brown tweed grille cloth that blends unobtrusively with your decor. SPECIFICATIONS: Overall Response: 20-20,000 Hz. Power Handling Capacity: Up to 50 Watts. Impedance: 8 ohm. Crossover Frequencies: 800 and 5,000 Hz (6 db/octave LC network). 12,000 Hz (mechanical). Controls: Continuously Variable Midrange and High frequency. Enclosure: Ducted-Port System using a Tuned "Sonic Tube". Speaker Components: 12" Bass Speaker (20-800 Hz), 5" midrange (800-5,000 Hz), two 3" High Frequency Units (5,000-12,000 Hz), two 1 1/2" Super High Frequency Units (12,000-20,000 Hz). Dimensions: 24 x 14 1/2 x 12"D. Imported. Shpg. wt., 41 lbs.

SYSTEM DESIGN



99 R 02263WUX

Net 99.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 61

NEW Lafayette **CRITERION ES85**

ELECTROSTATIC SPEAKER SYSTEM



Power Handling Capacity-50 Watts

SPEAKER COMPONENTS

- 4** Electrostatic Tweeter Elements—Consists of A Movable Flat Metal Diaphragm and A Non-Movable Metal Electrode Capable of Reproducing High Frequencies Up To 25,000 Hz With Extreme Clarity
- 1** 8" Low Frequency Transducer That Reproduces Deep Bass Response Down To 45 Hz.
- 1** 5000 Hz. Electrical Crossover Network

64⁹⁵

5 Year AAA Guarantee
See Page 415

Lafayette introduces a newly designed electrostatic speaker system with 4 tweeter elements and a low frequency transducer at an amazing low price. This outstanding system is characterized for its ability to faithfully reproduce the high frequencies with crystal clear clarity because of the electrostatic tweeter elements. As these type of tweeters require a power source, the ES85 has a 117 VAC line cord and switch. The current consumption is so low, the speaker can be kept on at all times. It is recommended that the ES85 be used with amplifiers rated over 12 watts per channel. The handsome oiled walnut wood enclosure is sealed air-tight to extend bass response. Includes a variable high frequency control. Impedance is 8 ohms. Two terminals on the rear of speaker are color coded for proper phasing. Size 11³/₄x21³/₄x8¹/₂". Imported. Shpg. wt., 20 lbs. 89 R 02719W No Money Down* Net 64.95

DELUXE Lafayette **CRITERION "5XB"**

75-WATT 12" 4-WAY ACOUSTIC SUSPENSION SYSTEM



5 Year AAA Guarantee
See Page 415

129⁹⁵

12" Acoustic Suspension Woofer with Massive 6 lb. 2 oz. Magnet Structure

6¹/₂" Midrange Speaker with 12.4 oz. Magnet Structure Acoustically Isolated from Main Enclosure

Fully air-tight 3/4" Wood Fiberglass Loaded Enclosure

Individual Mid and Treble Range Controls (rear)

1¹/₂" Super Tweeter

3" Cone Type Tweeter

System Design 711

Employing the acoustic suspension principle, the Criterion 5XB provides astonishing overall range and clarity, with a deep, solid bass response that makes a stunning impact on the listener. Four outstanding speakers are used to cover the full spectrum of sound. A 12" acoustic suspension woofer with 6 lb. 2 oz. magnet structure produces remarkably low bass response—undistorted even at high power levels. An acoustically isolated 6¹/₂" mid-range speaker with 12.4 oz. magnet structure provides flawless reproduction of the mid-range—free of annoying peaks, yet adding true "presence" to

the system. Extending response to beyond are 3" and 1¹/₂" tweeters. Low loss 12 db/octave crossover at 3,000 Hz and 4,500 Hz, 6 db/octave crossover at 19,000 Hz. Air-tight. Separate, continuously variable mid and treble range controls. Enclosure has a fine furniture finish in oiled walnut on all four sides. Specifications—Overall Response: 18 to 25,000 Hz. Impedance: 8-ohms. Size: 23⁷/₈x14³/₈x11¹/₂"D. Imported. Shpg. wt., 46 lbs. 89 R 02230WUX No Money Down* Net 129.95

LAFAYETTE'S BEST Floor Standing Speaker Systems

NEW

LAFAYETTE Criterion "88" 3-Speaker 3-Way Acoustic Suspension Console Speaker System



FEATURES Exclusive "Program Optimizer"—
changes speaker characteristics according to program material being reproduced



- 1 NORM**—Produces Flat Response Over Entire Audio Spectrum When Listening to a Full Symphonic Orchestra
- 2 POPULAR**—Emphasizes Hi-Frequency and Low-Frequency Response for Rock, Folk, Jazz, and Popular Music Listening
- 3 VOCAL**—Emphasizes Mid-Range Frequencies to Project Voice Reproduction—thus Adding Presence

Handles Up To 40-Watts Program Material

- 10" Woofer
- 3" High Frequency Driver
- 1½" Super Tweeter
- LC Crossovers at 6,600 Hz and 10,000 Hz

89⁹⁵

5 Yr. AAA Guarantee
See Page 415

Introducing an exciting new innovation in speaker design—an extraordinary performing system with a built-in "program optimizer" to tailor the sound to the characteristics of the material being reproduced. Full 3-way acoustic suspension design with 3 speakers—a big 10" air-suspension woofer with a 2 lb. 8 oz. magnet structure to extend bass down to 20 Hz. A closed back 3" cone-type driver provides natural reproduction of the upper mid-range and lower high frequencies. The extreme high frequencies

are extended cleanly beyond the limits of hearing by a 1½" super-tweeter with an aluminum cone. Full range response from 20 to 20,000 Hz. In addition to the "program optimizer" there is a high frequency brilliance control on the rear. The Criterion 88 is finished on all 4 sides in rich, hand-rubbed oiled walnut veneer. Impedance 8 ohms. Imported. Size: 24½x15w x 9¼"D. Shpg. wt., 32 lbs. No Money Down* 99 R 02693W Net 89.95

NEW

LAFAYETTE Criterion "90" 100 Watt 6-Speaker 4-Way Acoustic Suspension Console Speaker System



*The Finest Reproducer of Sound
Offered by LAFAYETTE
for the Home . . .*

159⁹⁵

5 Yr. AAA Guarantee
See Page 415

- Overall Response 18-25,000 Hz
- Powerful 12" Acoustic Suspension Woofer with over 5.1-lb. Magnet Structure and Edge-Wound Ribbon-Type Copper Voice Coil on an Aluminum Form
- 6½" Acoustically Isolated Midrange Speaker with 12-oz. Magnet Structure
- Four Tweeters—Two 3" Tweeters and Two 1½" Super Tweeters
- Separate Midrange and High Frequency Level Controls
- ¾" Enclosure in Rich, Hand-rubbed Oiled Walnut Finish

Improved version of our best selling Criterion 80. A no-compromise 6-speaker system created for just one purpose—the authentic reproduction of a massive symphony orchestra. Brings the spectacular realism of a living performance right into your home. This major accomplishment was achieved by careful selection and design of speaker units enclosure. A specially designed 12" acoustic suspension woofer in a large air-tight enclosure over 3½ cubic feet in overall size results in remarkably powerful, solid bass. Added to this is an acoustically isolated 6½" midrange speaker that affers natural "presence" without exaggerated midrange peaks. Four tweeters spread across the front

in a calculated configuration ensure a wide dispersion of the highs and reduce high frequency "beaming." Two of these are 3" units covering the 3,500 to 5,000 Hz range, and two are ultra-high frequency 1½" aluminum cone units that extend response to well beyond audibility Crossover frequencies: electrical at 650 and 3,500 Hz, mechanical at 5,000 HZ. Handsome enclosure is finished in a rich, hand-rubbed oiled walnut with dark brown tweed grille cloth. Impedance 8 ohms. Dimensions: 30"Hx18"Wx12"D. Imported. Shpg. Wt., 67, lbs. No Money Down* 99 R 02701 Net 159.95

Top Quality UTAH HI-FI Speakers & Speaker Systems

<p>A Model MF8JXC-2 8" 2 Way</p> <p>16⁹⁵</p>	<p>B Model CBJC-3C 8" 3 Way</p> <p>19⁹⁵</p>	<p>E Model A-130 12" 3 Way System</p> <p>129⁹⁵</p>
<p>C Model HF12PC-2 12" 2 Way</p> <p>28⁵⁰</p>	<p>D Model C12PC-3C 12" 3 Way</p> <p>37⁵⁰</p>	<p>F Model MK-17 12" 3 Way System</p> <p>99⁹⁵</p>
		<p>G Model A-70 10" 3 Way System</p> <p>69⁹⁵</p>

A NEW Model MF8JXC-2 8" Two-Way Coaxial Speaker
Rigid, die-cast frame. Spring loaded fingertip terminals are color coded for easy phasing in stereo systems. Magnet wt. 12 oz. Power Handling Capacity 30 Watts. Frequency response 32-19,000 Hz. Resonant Frequency 55 Hz. Impedance, 8-ohms.
21 R 47346W Shpg. wt., 5 lbs. Net 16.95

B NEW Model CBJC-3C 8" Three-Way Coaxial Speaker
Rigid, pressure cast frame. Spring loaded color coded finger tip terminals. Baked on lacquer finish. Shallow profile only 3 1/4" total depth. 10 oz. Alnico VIII magnet. Voice coil diameter 1 inch. Power handling capacity 30 watts. Response 35-20,000 Hz. Resonant frequency 55 Hz. Impedance, 8-ohms. Shpg. wt., 6 lbs.
21 R 47353W Net 19.95

C NEW Model HF12PC-2 12" Two-Way Coaxial Speaker
12" version of above model MF8JXC-2. Magnet weight 20 oz. Voice coil diameter 1 1/2". Power handling capacity 45 watts. Response 23-19,000 Hz. Resonant frequency 25 Hz. Impedance 8 ohms. Shpg. wt., 12 lbs.
21 R 47361W Net 28.50

D NEW Model C12PC-3 12" Three-Way Coaxial Speaker
12" version of above model CBJC-3C. 20 oz. Alnico VIII magnet. Voice coil diameter 1 1/2". Power handling capacity 45 watts. Frequency 25-20,000 Hz. Resonant frequency 25 Hz. Impedance 8-ohms. Shpg. wt., 12 lbs.
21 R 47379W No Money Down* Net 37.50

E NEW Deluxe Model A-130 12" 3-Way Acoustic Suspension System
One of Utah's finest systems. Features a powerful 12" woofer with a 2 1/2 lb. magnet structure. 1 1/2" voice coil, and a cloth roll suspension. The 3 1/2"x8" midrange compression horn has a 8 oz. magnet structure. Uses a horn loaded dome radiator tweeter for the upper frequencies. L/C crossovers at 9,000 & 4,500 Hz. Mid-Range & High frequency controls. Power handling capacity 60 watts. Response 30-20,000 Hz. Impedance 8 ohms. 3/4" Walnut veneer enclosure. Size 14x24x12 3/4". Shpg. wt., 37 lbs.
21 R 47387WX No Money Down* Net 129.95

F NEW Model MK-17 12" 3-Way Acoustic Suspension System
Big 12" high compliance woofer, 8" midrange speaker, and sealed 3 1/2" tweeter. Electrical crossover with high frequency level control. Power handling capacity: 50 watts. Response 32 to 18,000 Hz. Imp., 8 ohms. Oiled walnut veneer enclosure. Size: 14x23x10".
21 R 47395WX No Money Down* Shpg. wt., 33 lbs. Net 99.95

G NEW Model A-70 10" 3 Way Acoustic Suspension System
Features 10" woofer with 1 1/4 lb. magnet structure, 6 inch cone type midrange speaker, and a 3 1/2" tweeter. Electrical crossover network at 5,000 Hz. and 2,500 Hz. Power handling capacity 40 watts. Response: 45-18,000 Hz. Impedance, 8-ohms. Oiled walnut veneer enclosure. Size: 12x22x8". Shpg. wt., 23 lbs.
21 R 47403WX No Money Down* Net 69.95

NEW LAFAYETTE Criterion W4 3 Speaker Thin Line System



Hang On Wall Place on an Optional Floor Stand Place on a Bookshelf



ONLY
34⁹⁵
With Legs

5 Year
AAA Guarantee
See Page 445

- Ideal For Use As Rear Speakers in 4 Channel Systems
- 5" High Compliance Woofer
- Two 3" Cone Type Tweeters
- Power Handling Capacity—25 Watts
- Frequency Response 50-19,000 Hz.

Space saving full-fidelity system in a convenient thin-line configuration. A unique innovation has been incorporated in the design of the Criterion W4. The 3 speaker system utilizes a drone cone to increase low frequency response normally minimized in an ultra thin enclosure. In conjunction with the powerful 5" high compliance woofer, this results in deep, resonant bass response down to 50 cycles. The 2 high frequency tweeters disperse clear, brilliant highs up to 19,000 Hz. Electrical crossover is present at 4kHz. Impedance, 8 ohms. The cabinet is hand finished in oiled walnut with a luxurious textured brown grill cloth. Features adjustable high freq. level control. Size 19 1/2"x14 1/2"x2 1/2" D. Imported.
99 R 02651W Shpg. wt., 12 lbs. Net 34.95



High Performance Loudspeaker Systems



Model 17

74⁹⁵



Model 22

54⁹⁵



Model 5

189⁹⁵



Model 6

134⁰⁰

Model Seventeen 10" 2-Way Acoustic Suspension System

Full-range two-way system offering a high level of musical enjoyment. 10" acoustic suspension woofer provides extended bass response; 1 3/4" direct radiator type tweeter provides smooth peak-free highs, as well as exceptional performance at the mid-frequencies. 3-position high frequency control permits matching the system to any acoustic environment. Housed in a completely sealed, fiberglass filled, oiled walnut, 3/4" furniture grade cabinet. All four sides finished for vertical or horizontal placement. Impedance: 8 ohms. For use with amplifiers of 12 watts IHF or more. Size: 11 3/4 x 23 1/4 x 9"D. Shpg. wt., 30 lbs.

21 R 44210W No Money Down* Net 74.95

Model Twenty Two 8" 2-Way Acoustic Suspension System

Big enough to have all the requirements for excellent performance. Yet small enough to fit unobtrusively into any living room. Bass frequencies are reproduced through the use of an 8" acoustic suspension woofer, mid and high-frequency performance is provided by a 2" direct radiator tweeter. Tightly sealed cabinet is oiled walnut finished on all four sides for vertical or horizontal placement. Impedance: 8 ohms. For amplifiers with as little as 12 watts IHF per channel. Size: 18 x 10 1/4 x 7 1/2"D. Shpg. wt., 17 lbs.

21 R 44244W No Money Down* Net 54.95

Model Five 4 Speaker Acoustic Suspension System

Offers the best low-frequency and power handling capabilities of the KLIH bookshelf-size speaker systems. Speaker compliment includes: big 12" acoustic suspension woofer with heavy magnet and cone assemblies; two 3" miniature heavy-magnet mid-range speakers; and a 1 3/4" high-frequency speaker mounted in a sub-enclosure. Two 3-position switches adjust the 2500-7000 Hz and 7000-20,000 Hz ranges. Cabinet of 3/4" plywood finished in oiled walnut veneer. 8-Ohms Impedance. Minimum power: 40 watts IHF. Size: 26 x 13 3/4 x 11 1/2"D. Shpg. wt., 53 1/2 lbs.

21 R 44251WX No Money Down* Net 189.95


Model Six 12" 2-way Acoustic Suspension System

Designed to handle high power and deliver a full-range of rich sound. Has big 12" acoustic suspension woofer employing a heavy, oriented-ceramic magnet assembly and four-layer voice coil; 1 3/4" cone-type direct radiator tweeter, plus 3-position high frequency level control. Frequency Response: 32 to over 16,000 Hz. Crossover: 1500 Hz. Impedance: 8 ohms. Ideal for floor or shelf mounting. For amplifiers of 25 watts IHF or more. Oiled walnut finish on four sides. Size: 23 1/2 x 12 3/4 x 11 7/8"D. Shpg. wt., 42 1/2 lbs.

21 R 44061WUX No Money Down* Net 134.00

dynaco APERIODIC SPEAKER SYSTEMS

Only
79⁹⁵
No Money
Down*



Model A-25 10" 2-Way System

- 10" Extended Range Woofer
- Soft Dome Tweeter
- Acoustic Impedance Enclosure Principle

Non-resonant aperiodic design combines with acoustic impedance principle to assure uniform wide range response. Uses a 10" extended excursion woofer and new soft dome tweeter to achieve truly natural sound. Non-inductive Crossover Network of 1500 Hz. 5-position tweeter control. Designed for use with amplifiers rated at 15 watts or more RMS. Freq. Response: 35-20,000 Hz. Impedance: 8 ohms. Wall mounting brackets are provided for hanging the speaker flush on the wall. Oiled walnut finish. Size: 20 x 11 1/2 x 10"D.

21 R 23545W Shpg. wt., 24 3/4 lbs. Net 79.95

Only
179⁹⁵
No Money
Down*



NEW Model A-50 10" 3 Speaker System


- Two 10" Extended Range Woofers
- High Dispersion Dome Tweeter
- Acoustic Impedance Enclosure Principle

The A-50 features Dynaco's exclusive "dual-spectrum damping"—two acoustically connected chambers each containing a 10" woofer for smoother and extended low frequency performance. A newly designed high-dispersion dome tweeter coupled to a non-inductive network crossing over at 1000 Hz results in extended mid and high frequency response. Minimum power required: 25 watts RMS. Freq. response: 30-20,000 Hz. Impedance: 8 ohms. Hand-rubbed walnut enclosure. Size: 28 x 21 1/2 x 10"D. Shpg. wt., 47 lbs.


21 R 23552W Net 179.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Wharfedale, ADC, & EMPIRE Speaker Systems



Wharfedale W25 2-way Acoustic Suspension System



Wharfedale W35 3-way Shelf/Corner Speaker System

49⁹⁵

Big 8" woofer provides rich, deep bass. Crystal clear treble from a new ultracurvilinear tweeter for smooth, wide-angle dispersion of sound. Components are front-loaded. Cabinet is genuine oiled walnut and uses new "unitized" construction to eliminate spurious buzzing. Response: 35-18,500 Hz; Imp. 8 ohms. Power: Min. 10 watts, Max. 35 watts (IHF per channel). Size: 15½ x 10 x 8"D. Imported. No Money Down*.
21 R 7557W Shpg. wt., 16 lbs. — Net 49.95

ADC 303AX 2-Way Loudspeaker System



New
LOW PRICE
89⁹⁵

- 10" Woofer and Wide Dispersion Tweeter
- Frequency Response 37-20,000 Hz

Outstanding bookshelf system with newly designed high compliance 10" woofer, and a wide dispersion super tweeter. Crossover frequency: 1500 Hz. Response: 37-20,000 Hz. Impedance 8 ohms. Power required: 10 watts RMS min. Size: 23¾H x 13W x 11¾"D. Shpg. wt., 38 lbs.
21 R 13348W No-Money Down* Net 89.95

Wharfedale W60E 3-way Speaker System

129⁹⁵

- 12" Woofer With 9½ lb. Magnet Structure
- 5" Midrange
- 1" Mylar Dome Super Tweeter

Redesigned 12" woofer with molded one-piece cone, high excursion neoprene surround, and massive 9½ lbs. magnet assembly. 5" midrange, in isolated non-reflecting cylindrical chamber. 1" mylar dome super tweeter has phase compensating diffuser. All speakers are front-loaded. Genuine oiled walnut cabinet. Response: 30-20,000 Hz; Impedance 8 ohms. Power: Min. 10 watts, Max. 50 watts (IHF per channel). Size: 24x15x12" deep, imported.
21 R 75537WX No Money Down* Shpg. wt., 52 lbs. — Net 129.95

Wharfedale W70E 3-way Floor Standing Speaker System



189⁵⁰

Big 15" woofer has massive 10½ lb. magnet assembly. Midrange is special 5" unit with high compliance suspension in separate cylindrical chamber. 1" mylar dome omnidirectional super tweeter has compensation diffuser to reduce phase distortion. Genuine oiled walnut cabinet. Response: 25-20,000 Hz; Impedance 8 ohms. Power: Min. 15 watts, Max. 60 watts (IHF per channel). Size: 24 x 22¾ x 13¾" deep. Shpg. wt., 63 lbs. Imported.
21 R 75545WX No Money Down* — Net 189.50

NEW! ADC 450A Deluxe 2-Way Loudspeaker System




Only
134⁰⁰
Handsome Oiled Walnut Cabinet

- Power Handling Capacity 40 Watts RMS
- Response: 25-30,000 Hz

Laboratory quality system featuring 12" low frequency driver with viscous coated cone and high compliance foam suspension; plus a wide range dome radiator tweeter for the upper frequencies. Imped. 8 ohms. Oiled walnut finish. Size: 25x14½x12"D. Shpg. wt., 50 lbs.
21 R 13363WX No Money Down* — Net 134.00

NEW! Empire 6000M 3-Way Floor Standing System



ONLY
119⁹⁵

- Can easily be positioned for 4-channel stereo

Quality 3-way system in a rigid, non-resonating cylindrical type cabinet—only 18" in diameter and 24¾" high. Features 10" woofer, midrange radiator, and wide angle ultrasonic tweeter. Power handling capacity —75 watts. Response: 30-20,000 Hz. Imp.: 8 ohms. Satin walnut finish with marble top. Shpg. wt., 60 lbs.
21 R 34989 No Money Down* Net 119.95

Acoustic Suspension Speaker Systems by

AR INC.



AR SPEAKER BASES



Size: 11x14½x13

Shipping Weight 4 lbs.

21 R 72419W Oiled Wal. . . Net 10.00
21 R 72401W Unf. Birch . . . Net 10.00

AR's 5-YR. SPEAKER GUARANTEE

AR speakers are sold under the manufacturer's 5-year guarantee covering parts, labor, freight both ways, and packaging if necessary.

AR-4X 2-WAY ACOUSTIC SUSPENSION SYSTEM



As Low As

57⁰⁰

No Money Down*

Low cost acoustic suspension speaker system. Designed to give a superbly clean, realistic bass response and clear, crisp highs by utilizing the famous acoustic suspension principle. It incorporates an 8" woofer and a 2½ inch direct radiator tweeter with level control to compensate for different acoustic conditions of your listening room. Electrical crossover frequency is 1200 Hz. A compact (19Wx10Hx9"D) unit for floor or shelf-mounting. Suitable for use with amplifiers of 15 watts RMS or more per chan. Imp: 8 ohms. wt., 23 lbs.
21 R 72492W Oiled Walnut . . . Net 53.00
21 R 72500W Unfinished Pine . . . Net 57.00

NEW AR-6 2-WAY ACOUSTIC SUSPENSION SYSTEM



As Low As

72⁰⁰

No Money Down*

Outstanding performing 2-way acoustic suspension system at a modest cost. Uses only 2 drivers—an 8" woofer with heavy molded cone supported at the outer edge with a urethane polymer suspension, and a wide dispersion 1½" tweeter with smooth response beyond 20 kHz. Designed for use with amplifiers rated at 20 watts RMS per channel. Crossover frequency 1500 Hz. High Frequency Level Control. Size: 19½ x 12 x 7"D. Shpg. wt., 24 lbs.
21 R 72623W Oiled Walnut . . . Net 81.00
21 R 72631W Unfinished Pine . . . Net 72.00

AR-2AX 3-WAY ACOUSTIC SUSPENSION SYSTEM



As Low As

109⁰⁰

No Money Down*

Precision-made components plus the famous acoustic suspension design deliver truly magnificent sound. Includes 10" woofer for natural bass response; 3½" direct radiator mid-range for realism and a ¾" dome type super tweeter providing highs out to the limits of audibility. Frequency response, 42-20,000 Hz, ±2½ db. Less than 2% harmonic distortion down to 20 Hz. Has 2 level controls. Designed for use with amplifiers rated at 20 watts RMS per channel. Finished on 4 sides. 24 x 11½ x 13½". Imp.: 8 ohms. Shpg wt., 41½ lbs.
21 R 72070W Oiled Walnut . . . Net 128.00
21 R 72054W Unfinished Pine . . . Net 109.00

AR-5 3-WAY ACOUSTIC SUSPENSION SYSTEM



As Low As

156⁰⁰

No Money Down*

Deluxe AR bookshelf system! Provides superb full-range frequency response. System features a new 10" acoustic suspension woofer utilizing AR's most advanced cone design, 1½" mid-range and ¾" tweeter each have independent frequency driver controls with crossover at 650 and 5,000 Hz respectively. Frequency response: 38-20,000 Hz. Impedance: 8 ohms. Designed for use with amplifiers rated at 20 watts RMS per channel. Size: 13½ x 24 x 11½"D. Shpg. wt., 46 lbs.
21 R 72716WUX Oiled Walnut . . . Net 175.00
21 R 72724WUX Unfinished Pine . . . Net 156.00

AR-3A DELUXE 3-WAY ACOUSTIC SUSPENSION SYSTEM



As Low As

225⁰⁰

No Money Down*

Acoustic Research's finest speaker system. Features a powerful 12" woofer with ¾ lb. magnet, hemispherical direct radiators for the mid-range and tweeter units with 1½" and ¾" domes, respectively. Frequency response from 38 Hz to 20,000 Hz (±2db). Woofer crossover frequency at 575 Hz; mid-range from 575 Hz to 5kHz; and the tweeter from 5 kHz up. Designed for use with amplifiers rated at 25 watts RMS per channel. Impedance: 4 ohms. Cabinet finished on 4 sides. Size: 14H x 25W x 11¾"D. Shpg. wt., 61 lbs.
21 R 72658WX Oiled Walnut . . . Net 250.00
21 R 72708WX Unfinished Pine . . . Net 225.00

Rectilinear's BEST SELLING SPEAKER SYSTEMS

MODEL XI 2-WAY BOOKSHELF SYSTEM



79⁵⁰

No Money Down*

Max. Power Handling Capacity 40 watts RMS.

Two-way speaker system utilizing an extended range 10" woofer and an extended-range 3" tweeter. The enclosure uses tubed-vented bass reflex design for high efficiency without loss of bass response. Crossover frequency: 1800 Hz. Minimum Power Requirement, 10 watts RMS. Max. Power 40 watts RMS. Impedance 8 ohms. Response 45 to 17,000 Hz. Tweeter level control. Oiled walnut wood cabinet. Size: 23" x 12" x 10 1/2". Shpg. wt., 32 lbs.

21 R 86054W No Money Down* Net 79.50

MODEL X A 3 WAY BOOKSHELF SYSTEM



199⁰⁰


No Money Down*

Max. Power Handling Capacity 75 watts RMS.

Designed to provide the listener with a loudspeaker of more accurate response and lower distortion than exceeding the dimensions of a bookshelf type system. Utilizes a 10" woofer, 5" midrange with a 2" whizzer cone, and 2 1/2" tweeter. Completely enclosed cabinet incorporates an airtight internal shelf that isolates the woofer from the midrange and tweeter. Freq. response 30-20,000 Hz ±4 db. Crossover Freq. 100 Hz and 8000 Hz. Oiled walnut finish. Impedance 4-ohms. Size: 25" x 14" x 10 3/4".

21 R 86062WX Shpg. wt., 50 lbs. Net 199.00

MODEL III 6 SPEAKER 4-WAY CONSOLETTA SYSTEM



Handles up to 100 Watts

279⁰⁰

No Money Down*

Provides concert hall realism. Brilliant smooth response from 22 to 18,500 Hz. 12" woofer has a 10 pound magnetic structure. Mid-range driver operates from 250 to 3000 Hz and is mounted in a fiber sub enclosure within the main cabinet. Two tweeters cover the 3,000 to 11,000 Hz range with two additional super tweeters carrying audio frequencies to inaudibility. Min. power requirements: 20 watts RMS; Max. power 100 watts RMS. Two controls: Midrange, tweeter. Impedance: 8-ohms. Oiled walnut finish. Size: 35 x 18 x 12 1/4"D.


21 R 86039WX Wt., 68 lbs. Net 279.00

Finest LAFAYETTE Hi-Fi Speaker Enclosures

8" Bookshelf Speaker Enclosure



22⁹⁵




- Ideal For Use With All 8" Wide Range Hi-Fi Speakers
- Solid 3/4" Wood Construction

Handsome, decorator styled bookshelf speaker enclosure. Finished in oiled walnut veneer with picture frame moulding to lend a note of elegance to any decor. Features vented port design for improved bass response. Has fiberglass acoustic lining, solid 3/4" wood construction, plus factory mounted luxurious brown tweed grill cloth. Back has two lug terminal strip. 18 x 11 x 9" deep. Shpg. wt., 20 lbs.


20 R 01519W

Net 22.95

12" Bookshelf Speaker Enclosure



32⁹⁵



- Ideal For Use With Any 12" Hi-Fi Speaker
- Solid 3/4" Wood Construction

Beautiful, oiled walnut veneer 12" bookshelf speaker enclosure with picture frame moulding. Features quality construction plus contemporary styling. Custom designed to accept all 12" speakers, including 2 and 3 way types. Solid 3/4" wood construction. Dual vented port design plus fiberglass lining gives improved bass response. Acoustically transparent brown tweed grill cloth lets the sound come through without attenuating the highs. All four sides finished in oiled walnut veneer to match the decor of any room. For vertical or horizontal placement. Size: 14 3/4 x 23 3/4 x 12 1/4".

20 R 01501W Shpg. wt., 35 1/2 lbs.

Net 32.95

Luxurious Hi-Fi Furniture For Your Home



49⁹⁵

NEW! CONTEMPORARY OPEN BENCH DESIGN THAT HOLDS ALL OF YOUR HI-FI EQUIPMENT

- Space For
- Receiver
 - Amplifier and Tuner
 - Records • Tape • TV
 - Pull-out Shelf for Record Changer

Striking all-purpose shelf unit for your hi-fi components—provides impressive display and easy accessibility. Ample space is provided for records and tapes. The shelf for the record player moves in and out. (Speaker compartments are separated for the utmost stereo effect.) Rear has outlet holes to run wires to and from the Receiver or Amplifier. The pressed-wood shelves have a remarkable new surfacing material of rigid walnut colored vinyl called PERMANEER. Permeener is stain resistant. Wipes clean with a damp cloth. Heat resistant. Needs no special polishing care. Keeps its beautiful woodlike finish. Size: 65 1/2" W x 15 1/2" D x 30 1/2" H. Comes KD (Knocked down), Shpg. wt., 85 lbs.


Walnut Permaneer Finish

20 R 16004WX No Money Down* Net 49.95

Deluxe LAFAYETTE Floor-Standing Hi-Fi Enclosure



Entire Cabinet 3/4" Lumber



Kit 44⁹⁵	Assembled 64⁹⁵
-------------------------------	-------------------------------------

- 3/4" Wood Construction
 - Precision Cut—Fits Together Smoothly
 - Ideal For Single Wide Range, 2-3-Way Speaker Systems
- range (with 6" adapter), and adapters to accommodate either round or rectangular tweeters. Separate wood blanks are supplied if no midrange speaker or tweeter is used. Kit is supplied unfinished, smoothly sanded and ready for finishing. Dimensions (less base) 27"H x 22"W x 16"D. Island type base is 2 3/4" high. Complete with instructions, all parts, hardware, and grille. Shpg. wt., 58 lbs.
- 20 R 01493WX Kit Net 44.95
20 R 01451WX Factory Assembled Net 64.95


All pieces of this carefully designed high fidelity speaker enclosure are accurately pre-cut of 3/4" lumber to fit snugly together and virtually eliminate all spurious resonances. White birch surface is finished on all 4 sides for either high or low boy styling. Front panels feature edge moulding and plastic acoustic grilles to blend with any finish and room decor. Lined with acoustic material that prevents reverberation and cabinet resonance. Flexible design includes cut-outs for 15" woofer (with 12" adapter), 8 1/2" or 8" mid-

*See Page 22 for Full Credit Details on Easy Pay Plan

Full Range LAFAYETTE 8" Hi Fidelity Speakers

NEW! Deluxe SK-228 8" 3-Way Hi-Fi Speaker

Power Handling Capacity: 35 Watts



Only
19⁹⁵

- 1½" Voice Coil
- 4 lb. Magnet Structure
- Response: 28-19,500 Hz
- Rigid One-Piece Die-Cast Frame
- Cloth Roll Suspension For Low, Smooth Bass

Superb 3-way, 8" speaker delivers exceptionally clean and natural sound over a full frequency range. Rigid one-piece, pressure die-cast frame maintains precision alignment of critically spaced speaker elements. Powerful, high compliance woofer has cloth roll suspension for low, smooth bass, down to 28 Hz. Separate midrange cone for distortion-free middle frequencies. Cone type super tweeter disperses clean, brilliant high frequencies up to 19,500 Hz. Large 1½" voice coil absorbs power peaks. Solderless terminals are phase coded for easy phasing, spring loaded for fast wiring and freedom from buzzing. Power handling: 35 watts. Impedance: 8 ohms.


21 R 01749W Shpg. wt., 7 lbs.

Net 19.95

DELUXE SK-128 8" BIAXIAL SPEAKER



Only
16⁹⁵



Eccentric Tweeter Mounting and Unique Elliptical Baffle Completely Eliminates Interaction Between Woofer and Tweeter

8" Bixial Speaker offers full, even coverage of the entire audio range with no distortion or coloration to mar your listening pleasure. Specially treated woofer cone has a unique "Conical Stiffener" at the apex which, coupled with its high compliance, enables the cone to operate in a piston-like manner—delivering a clean, powerful bass response. The 2-inch tweeter has its own voice coil and magnetic field. Special treatment of cone and cone edge provides even distribution of the high frequencies with no peaks or resonance. 2,500 Hz electrical crossover. Adjustable brilliance control. Overall depth, 5 7/8". Imported. Shpg. wt., 5 lbs.

99 R 00325W

Net 16.95

SK-98® 8" DUO-CONE HI-FI SPEAKER

Power Handling Capacity: 15 Watts, 30 Watts Peak

Only
9⁹⁵

- Mechanical 2-Way Design
- Overall Response 40-16,000 Hz
- Large Magnet Structure
- Patented Cone Construction and Material High Excursion Woofer

The dual-cone construction used in this high quality 8" speaker provides the same type of wide-range response normally found in true coaxial speakers or multiple speaker systems. The woofer and tweeter cones "float" on flexible corrugated edges. This mounting results in true mechanical crossover, so that both cones operate at low frequencies, but only the tweeter cone operates at high frequencies. Patented cone materials provide extremely smooth response over the range of 40-16,000 Hz. Magnets are large and heavy with a flux density of 10,500 gauss and total flux of 56,000 maxwells. Free air resonance is 55-70 Hz; Impedance is 8 ohms. 4½" deep. Shpg. wt., 4½ lbs. Imported.

99 R 00275W

Net 9.95



LAFAYETTE'S Finest Hi-Fidelity Speakers

DELUXE LAFAYETTE SK-315 15" 3-WAY DIE CAST SPEAKER

5 Year AAA Guarantee
See Page 415

- Massive 15 lb. Magnet Structure
- Free-Edge Cone Suspension
- 3" Woofer Voice Coil
- Pre-wired 12 db/octave Crossover Network with Calibrated Brilliance Control
- Compression Type, Horn Loaded Tweeter is Co-Axially Mounted
- Frequency Response: 20-20,000 Hz.
- Cone Resonance — 24 Hz

79⁹⁵

No Money
Down*

Made in U.S.A.

Lafayette's engineers teamed-up with America's leading speaker manufacturer to develop this outstanding 15" 3-way co-axial speaker so it could deliver more than you are ever likely to ask of it. The enormous 15 lb. magnet structure delivers an amazing 13,000 Gauss flux density . . . total flux is almost 300,000 Maxwells! The extra thick walls of the cast frame minimize "ringing" tendencies. Features aluminum wire for the 3" voice coil to achieve high conversion efficiency. The woofer cone is suspended by chemically treated cloth edges and a flat spider for a low, low free air resonance of only 24 Hz. This suspension also damps standing waves which tend to develop across the cone. The co-axially mounted mid-range radiator and compression tweeter assure reproduction of all frequencies in the audible range. The tweeter level control lets you adjust the speaker to suit room acoustics and your personal taste in response. Engineered to mount to either front or rear of baffle board; extra gaskets furnished.

21 R 01715WX Shpg. wt., 24 lbs. Net 79.95

SPECIFICATIONS:

Free Air Resonance: 24 Hz.; Overall Frequency Response: 20-20,000 Hz.; Flux Density: 13,000 lines per sq. cm.; Crossover: Mechanical at 2,500 Hz., electrical at 5,000 Hz.; Power: 40 Watts program, 80 Watts peak; Woofer Voice Coil: 3" dia., tweeter, 3/4" dia.; Impedance: 8 ohms; Outside Diameter: 15 1/4"; Overall Depth: 8"

Power Handling
Capacity 80 Watts Peak

DELUXE LAFAYETTE SK-312 12" 3-WAY DIE CAST SPEAKER

5 Year AAA Guarantee See Page 415

- Free-Edge Cone Suspension
- 2" Woofer Voice Coil
- Pre-wired Crossover Network with Calibrated Brilliance Control
- Direct Radiator Super Tweeter is Co-Axially Mounted
- Power Handling — 70 Watts Peak

39⁹⁵

No Money
Down*

This outstanding 12" speaker is the result of a joint effort between Lafayette's engineering group and the engineering staff of one of America's most respected speaker manufacturers. Features a rigid pressure die-cast frame with phase coded speaker terminals. 6 3/4 lb. magnet structure delivers an amazing 9,000 gauss flux density. The woofer cone is suspended by chemically treated cloth edges for a low, low free air resonance of only 25 Hz. This suspension also damps standing waves which tend to develop across the cone. The separate mid-range cone and direct radiator super tweeter assure reproduction of all frequencies in the audible range. The brilliance control permits adjustment of the high frequency response to satisfy room acoustics and the owner's taste. You can mount this speaker to either the front or rear of the baffle; extra gaskets for front mounting are included.

21 R 01707W Shpg. wt., 12 lbs. Net 39.95

SPECIFICATIONS:

Free Air Resonance: 25 Hz.; Overall Frequency Response: 20-19,500 Hz.; Flux Density: 9,000 lines per sq. cm.; Crossover: Mechanical at 1,000 Hz., electrical at 3,500 Hz.; Power: 35 Watts program, 70 Watts peak; Woofer Voice Coil: 2" dia.; tweeter, 3/4" dia.; Impedance: 8 ohms; Outside Diameter: 12 1/4"; Overall Depth: 6 1/2"

Power Handling
Capacity 70 Watts Peak

Made in U.S.A.

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 71



HEAVY DUTY, 3-WAY CO-AX SPEAKERS

A 12", 3-WAY

17⁹⁵

- 4 lb. Magnet structures in heavy steel return circuits.
- 4" TWEETERS are protected by beautiful, anodized screen which is trimmed in polished chrome . . . attractive durable finishes.
- DELUXE phase-coded, spring-loaded terminals with Teflon insulation. No tools needed.
- Magnet covers and chassis feature baked-on enamel to corrosion-proof the vital, critically dimensioned steel elements for years.

A 12" 3-WAY SPEAKER HANDLES 45 WATT PEAKS

Large voice coil (1½" Dia.) and large 4 lb. magnet structure for efficient, smooth handling of bass frequencies. 4" tweeter, with an Alnico V magnet, is coaxially mounted; has electrical crossover at 4,500 Hz. The midrange cone is mechanically coupled to the woofer voice coil. Handles 23 watts program material, 45 watts peak. Res., 45 Hz. Response, 35-20,000 Hz. Impedance 8 ohms.

21 R 47262W Shpg. wt., 8¾ lbs. Net 17.95

B 15" 3-WAY SPEAKER HANDLES 50 WATT PEAKS

Same heavy-duty combination of voice coil and magnet as the 12" version, above, plus the benefit of the extra cone area of a 15" speaker. Tweeter and midrange cone are also identical to above 12" speaker. Handles 25 watts of program material, 50 watts peak. Resonance, 40 Hz. Response, 30-20,000 Hz. Impedance, 8 ohms.

21 R 47254W Shpg. wt., 11 lbs. Net 21.95



B 15", 3-WAY

21⁹⁵

12" WIDE RANGE CO-AX SPEAKERS

C 12" HI-POWER

16⁹⁵

C 12" WIDE-RANGE HI-POWER HI-FI SPEAKER

- 4 Pound magnet structure, 1½" voice coil
- Deluxe, finger-tip operated, phase-coded terminals
- Magnet cover and chassis have baked-on lacquer finish
- Co-axially mounted high frequency cone extends range

An excellent, general purpose 12" speaker built to take power peaks up to 45 watts. 20 ounce ceramic magnet, 1½" voice coil. Impedance, 8 ohms; response, 35-17,000 Hz.; resonance, 45 Hz. Co-axially mounted high frequency cone extends range. Shpg. wt. 7 lbs.

21 R 47122W Net 16.95

D 12" CO-AXIAL HI-FI SPEAKER

- 4" Co-axially mounted tweeter with built-in crossover
- Magnet cover and chassis have baked-on lacquer finish

A wide range, efficient speaker for medium power amplifiers. Will handle 12 watt program material, 25 watt peaks. Excellent for the hi-fi enthusiast with a limited budget. Response, 40-18,500 Hz.; impedance, 8 ohms; 5.5 ounce ceramic magnet; resonance, 60 Hz.; voice coil diameter 1". Shpg. wt. 5¾ lbs.

21 R 47155 Net 11.95



D 12" CO-AX

11⁹⁵

8" SPEAKERS, EXTENDED RANGE & CO-AX

E 7⁹⁵

E 8" CO-AX WITH 3" TWEETER

Wide range response at moderate power; 8 watts program, 15 watts peak. 3 ounce ceramic magnet; impedance, 8 ohms; resonance, 75 Hz.; resp., 60-17,500 Hz.; solder lugs; baked-on lacquer finish. Wt., 2 lbs.

21 R 47171 Net 7.95

F 8" WIDE-RANGE HIGH POWER SPEAKER

Easily handles 30 watts peak (15 watts normal). Smooth output, high performance. Big 10 oz. ceramic magnet. Magnet covered with vinyl seal. Durable baked-on lacquer finish. Deluxe phase coded terminals—no soldering. Imp. 8 ohms. Response 45-16,000 Hz. Shpg. wt., 6 oz.

21 R 47221 Net 8.95

G 8" EXTENDED RANGE SPEAKER

Separate high frequency cone extends response, 5.5 ounce ceramic magnet. Baked-on lacquer finish. Handles 11 watts program material, 22 watts peak. Impedance, 8 ohms; resonance, 70 Hz.; resp., 45-16,000 Hz.; solder lugs. Voice coil diameter, 1".


21 R 47080 Shpg. wt., 2½ lbs. Net 5.95



F 8⁹⁵

G 5⁹⁵

6½" CO-AXIAL SPEAKER



7⁹⁵

6½" woofer with heavy magnet for maximum efficiency and low distortion. 2" tweeter is co-axially mounted in a protective sealed housing; a mesh dispersion screen provides smooth wide angle high frequency propagation. Ideal for use in pairs for stereo music systems of up to 8-10 watts. Frequency range, 50-16,000 Hz. Resonant freq., 70 Hz.; impedance, 8 ohms; built-in electrical crossover network. Requires 5½" dia. cutout. 6½" dia., 3¾" deep, imported. Shpg. wt. 3½ lbs.

99 R 00283 Net 7.95

Deluxe Woofers, Tweeters & Mid-Range Speakers for Do-It-Yourself Systems



LAFAYETTE

Speakers

WOOFERS FOR ALL POPULAR CABINET SIZES

A 15" WOOFER HANDLES 55 WATT PEAKS

A powerful, woofer capable of reproducing bass frequencies, at power levels you can feel. A mammoth 40 ounce ceramic magnet in a magnetic structure weighing 7¾ pounds. The oversize, 2" diameter voice coil easily handles 28 watts continuously and absorbs 55 watt peaks. The baked-on lacquer finish on the magnet cover and chassis protects against corrosion of the critically dimensioned steel elements. Deluxe, phase-coded, fingertip terminals with Teflon insulation. Res. freq., 50 Hz.; resp., 20-5,000 Hz.; imp., 8 ohms; Shpg. wt., 14 lbs.

21 R 47197W Net 28.95



A 28⁹⁵

B 12" WOOFER HANDLES 50 WATT PEAKS

This 12" woofer uses the same enormous magnet assembly and the same 2" voice coil we feature in our 15" woofer. Even though the cone is smaller, the resonance is held to a mere 30 Hz. by using a highly compliant cloth cone edge. Power handling is 25 watts continuous and 50 watts peak. Includes all the deluxe features you've come to expect from Lafayette: baked-on lacquer finish on magnet cover and chassis, and fingertip terminals with Teflon insulation. Response, 20-4,500 Hz.; impedance, 8 ohms. Shpg. wt., 12¼ lbs.

21 R 47205W Net 26.95



B 26⁹⁵

C 8" WOOFER HANDLES 40 WATT PEAKS

A space-saving 8" diameter woofer that makes every effort to rival its larger counterparts in frequency response and power handling ability. Features a 20 ounce magnet (4 pounds total structure), a 1½" voice coil and highly compliant cloth-roll cone suspension. Handles 20 watts of program material, 40 watts peak. Free air resonance is 55 Hz. Deluxe features include phase-coded, finger-tip terminals with Teflon insulation, baked-on lacquer on magnet cover and chassis. Response, 35-7,500 Hz.; impedance, 8 ohms; Shpg. wt., 6¾ lbs.

21 R 47213 Net 13.95



C 13⁹⁵

MIDRANGE COMPONENTS — HORN & DIRECT RADIATOR

D 8" HI-FI MIDRANGE HAS SEALED BASKET

The closed basket, (chassis) of this midrange speaker prevents inter-modulation from the back pressure of a woofer used in the same cabinet. A 10 ounce ceramic magnet and 1" voice coil are used for high sensitivity. When used with the proper crossover, this speaker will handle the midrange and high frequency power of a 30 watt program, ideal for use with a 700 Hz. crossover. Baked-on lacquer finish, magnet cover and chassis; deluxe phase-coded, finger-tip terminals; resp., 350-14,000 Hz.; impedance, 8 ohms. Shpg. wt., 4¼ lbs.

21 R 47189 Net 8.95



D 8⁹⁵

E MIDRANGE HORN OFFERS HIGH EFFICIENCY

High efficiency means more sound output per watt input. Now hear cymbals and brass with outstanding brilliance. Enjoy, too, the wide dispersion angle of this die-cast horn. Rewired crossover operates at 1,000 Hz., attach to your woofer with two simple solder connections. Will handle the midrange and high frequency power of a 30 watt program. Response, 600-12,000 Hz.; impedance, 8 ohms; voice coil diameter, ¾"; magnet, 1.4 ounce Alnico V; 10½x3¼x11" deep. Baked-on lacquer finish. Shpg. wt., 3¾ lbs.

21 R 47247 Net 9.95



E 9⁹⁵

TWEETERS-COMPRESSION AND DIRECT RADIATOR

F HIGH PERFORMANCE 2½" CONE TYPE HI-FI TWEETER

High performance remarkably compact low cost tweeter handles 3 watts input music power. Frequency response of 3,000 to 15,000 Hz. Magnet weighs 1.3 oz. Depth 1¾" impedance, 8 ohms. Imported. Shpg. wt., 6 oz.

99 R 01455 Net 1.95

G DIRECT RADIATOR SUPER TWEETER

Direct radiator type super tweeter with aluminum cone, enclosed metal case, and leads. Offers high sensitivity and wide dispersion angle. Handles up to 20 watts. Response, 4,000-18,000 Hz.; Voice coil, dia. ¾"; 1.23 oz. magnet. Recommended crossover frequency: 5,000 Hz or higher; Imp. 8 ohms. Imported. Requires 2¾" dia. mounting. Shpg. wt., ½ lb.

99 R 01208 Net 2.95

H DELUXE 3" CONE TYPE METAL-CASE HI-FI TWEETER


Cone type tweeter particularly efficient in the high end of the audio spectrum where ordinary cone tweeters tend to lose clarity and volume. Entirely enclosed in metal case with stand and cabinet mounting bracket. Handles 20 watts. Frequency response: 2,000-20,000 Hz. Diameter 3". Depth 2¼". Voice coil impedance: 8-16 ohms. Imported. Shpg. wt., 2 lbs.

99 R 00455 Net 5.95

I HIGH EFFICIENCY TWEETER HORN

Die-cast, compression type tweeter horn featuring high sensitivity, wide dispersion angle and rewired crossover operating at 4,500 Hz. Handles highs of 30 watts. Response, 2,000-18,000 Hz.; imp., 8 ohms; 1.4 ounce magnet; ¾" voice coil; baked-on lacquer finish; 7¼" x 3 x 6¾"; Shpg. wt., 1¾ lbs.


21 R 47239 Net 7.95



F 1⁹⁵



G 2⁹⁵



H 5⁹⁵



I 7⁹⁵

Miniature Lafayette High Compliance Hi-Fi Speakers

Specially designed, miniature, hi-fidelity speakers with heavy magnets. For the hi-fi enthusiast who requires quality performance in a compact area.


(A) LAFAYETTE 3" TWEETER. Fresh sounding foam-mounted cone tweeter delivers 1,200 to 20,000 Hz frequency response. Power handling capacity 8 watts peak. Depth 1 3/4". Impedance: 8 ohms. Imported. Shpg. wt., 1 lb. 99 R 01562 Net 2.95

(B) LAFAYETTE 4" FULL RANGE HI-FI SPEAKER. Fine performance from a speaker only 2" in depth. Frequency response 50 to 16,000 Hz. Power handling capacity 8 watts. Rugged steel frame construction. Heavy 8.11 oz. magnet. Impedance: 8 ohms. Imported. Wt., 2 lbs. 99 R 01729 Net 5.95

(C) DELUXE LAFAYETTE 5" WOOFER. Superb bass response is achieved through careful matching of large 1 1/2 pound magnet, 1" voice coil, and specially treated cloth surrounded cone. Frequency response: 40 to 12,000 Hz. Will handle 15 watt peak power. Depth 4 3/8". Imported. Shpg. wt., 5 lbs. 99 R 01554 Net 6.95


(D) LAFAYETTE 5" COAXIAL HI FI SPEAKER. Super miniature speaker handles up to 25 watt power. Frequency range 38 to 19,000 Hz. Magnificent sound reproduction. Heavy magnet weight 1.1 lb. Rugged steel frame construction. Impedance: 8 ohms. Only 2 3/4" in depth. Imported. Shpg. wt., 3 lbs. 99 R 01703 Net 9.95

(E) LAFAYETTE 6 1/2" DUAL-CONE HI FI SPEAKER. Powerful 6 1/2" speaker only 2 1/2" in depth. Large 1 lb. magnet. Frequency response 50-16,000 Hz. Power handling capacity—15 watts. Rugged steel frame construction. Impedance: 8 ohms. Imported. Shpg. wt., 4 lbs. 99 R 01737 Net 7.95



As Low As
2.95
ea.

NEW! LAFAYETTE HI-FI ACOUSTIC SUSPENSION SPEAKERS



Model SK118
8" Speaker
7.95

Model SK112
12" Speaker
9.95

- Cloth Roll Suspension
- Peak Power Capacity — 30 Watts
- 1" Voice Coil Diameter
- Magnet Structure 1 3/4 lbs.

Professionally designed hi-fi speakers for acoustic suspension systems. Both models feature cloth roll suspension, powerful 1 3/4 lb. magnet structure, 1" voice coils, and 8 ohm impedance. Cabinet plans are included with each speaker. Permanently viscous edge roll treatment seals each speaker and smooths treble response. Frequency response: SK118 30-20,000 Hz; SK112 28-18,500 Hz; Peak Handling Power: 30 Watts; Dimensions: SK118 Depth 3"; Outside Diameter 8 3/8"; SK112 Depth 4 3/4", Outside Diameter 12 1/2".

Stock No.	Model No.	Type	Shpg. wt.	Net ea.
21 R 01756	SK118—8" Speaker		3 lbs.	7.95
21 R 01764	SK112—12" Speaker		4 lbs.	9.95

LAFAYETTE CROSSOVER NETWORKS

2.95

(A) 2-WAY CROSSOVER NETWORK



(B) DELUXE 2-WAY CROSSOVER NETWORK **8.95**

(C) 2- AND 3-WAY L/C CROSSOVER **15.95**

(A) 2-WAY CROSSOVER NETWORK

Crossover network designed for 8 ohm woofers and tweeters. Crossover frequency, 3,000 Hz. Easily accessible lug terminals. Rugged metallic case 3 1/4 x 1 7/8 x 1 1/4". Fibre mounting reducing extraneous pickup. Mount on inside of speaker cabinet. Complete with simplified instructions. Imported. Shpg. wt., 6 oz.

99 R 01406 Net 2.95

(B) DELUXE 2-WAY CROSSOVER NETWORK

A carefully designed capacitive-inductive 2-way crossover network with crossover frequency easily set to either 2500 or 5000 Hz. Has a built-in continuously variable high-frequency "Brilliance" level control to match room acoustics perfectly. Control has a 2 1/2 ft. cable to mount on rear or side of speaker cabinet, and a long shaft for thick wood panels. Has an attractive brushed-gold finish escutcheon plate. For use with 8-16 ohm speakers. Easily accessible screw terminals. Metal case 5 3/4" x 2 3/8" x 2 1/2" D. Complete with simplified instructions. Imported. Shpg. wt., 2 lbs.

99 R 00218 Net 8.95

(C) DELUXE 2 and 3-WAY L/C CROSSOVER NETWORK


Can be used either as a 2-way or 3-way 6 db per octave network. Six crossover combinations are available—2-way crossover with 2000-3000 Hz or 5000 Hz crossover, and 3-way with crossover frequencies of 350 and 5000, 350 and 2000-3000, 700 and 2000-3000 or 700 and 5000 Hz for 8-16 ohm speakers. Brilliance and Presence controls—are mounted on the front panel. Level controls may be removed. Escutcheon plate, for external mounting; 3 ft. leads. 99 R 00226 Imported. Shpg. wt., 4 lbs. Net 15.95

Revolutionary LAFAYETTE "Poly-Planar" Speakers

Super-Thin Electro Dynamic Speakers

Lafayette "Poly-Planar" wafer-type component loudspeakers employ a lightweight acoustic panel supported by a frame of polystyrene plastic material to reproduce a range of frequencies from 30 Hz to 20,000 Hz. This material also permits the speakers to be made impervious to extremes of temperature, humidity, shock and vibration. There is also a minimum of piston motion resulting in low distortion and high electromagnetic efficiency.


- Super-Thin Construction Permits New Design And Installation Ideas
- Wide-Range High-Fidelity Performance



5 inch SPEAKER **5⁹⁵**

12 inch SPEAKER **10⁹⁵**

Deluxe 12" SPEAKER **12⁹⁵**



8⁹⁵ EA.

12" POLY-PLANAR WIDE RANGE SPEAKER—
Unique physical and audio characteristics permit a wide range of uses: Hi-Fidelity speaker systems, TV or radio, automotive, public address, architectural application (Build Poly-Planars into walls, closet doors, ceilings), and marine application. Use it as it is or cover it, baffle it, enclose it. Specifications: Power Capacity 25 watts Peak; Frequency Range, 40-30,000 Hz; Voice Coil diameter, 1"; Magnet weight, 4.8 oz.; Imp. 8 ohms; Maximum operating temperature, +175°F. Size: 1 1/4"D x 14 1/4"H x 1 1/4"W. Shpg. wt. 2 1/4 lbs.

DELUXE 12" POLY-PLANAR WIDE RANGE SPEAKER
Same as above but power handling capacity is 40 watts peak, 25 watts RMS. Freq. response, 30-20,000 Hz. Shpg. wt., 1 1/2 lbs.

5" POLY-PLANAR WIDE RANGE SPEAKER—
Same physical and audio characteristics as above 12" speaker. Especially designed for small space high performance applications such as automobile speakers, extension speakers. Specifications: Power capacity, 5 watts Peak; Imp., 8 ohms; Frequency range, 60 Hz to 20,000 Hz; Operating temperature range, -20°F to +175°F; Voice coil diameter, 3/4". Size: 3/4"D x 8 1/2"H x 4 1/2"W. Shpg. wt., 1 1/4 lbs.

SPEAKER GRILLS FOR POLY-PLANAR SPEAKERS

- For Surface or Custom Flush Mount Two types for either 12" or 5" speakers. Will provide beautiful custom flush mount installations in your home, office, boat, or car. High impact plastic with walnut grain finish.

As Low As **1⁹⁵**

20 Watt 8 Inch Round Poly Planar Super Thin High Fidelity Speaker

- Replaces 8" Conventional Cone Speakers in All Applications

New addition to Lafayette's series of polystyrene acoustic panel type speaker systems. Only 1" deep. Its unique construction makes it impervious to extremes of temperature, humidity, shock and vibration. Shallow depth permits mounting on doors, walls, ceilings or ordinary speaker enclosure. Specifications: Power cap: 10W; Freq. Range: 40-20,000 Hz; Voice Coil: 3/4"; Impedance: 8 ohms; Size: 8" dia., 1.05"D, Shpg. wt., 1 lb.

All Weather Outdoor Poly Planar Hi-Fi Speaker Systems

12" SYSTEM **17⁹⁵**

5" SYSTEM **12⁹⁵**

- Fully Weatherproof
- Can be Mounted, Can be Hung, or Can Stand

12" system: Fully weatherproof! Can be used outdoors or indoors for hi-fi or bidirectional PA paging. Handsome, high-impact white styrene enclosure with accessory walnut wood stand contains 12" Poly Planar hi-fi speaker. Includes 8 ft. hook-up wire, and all necessary hardware to simply let you stand, hang, or mount the system. Power: 20 watts peak. Frequency Response: 40-20,000 Hz handling capacity. Input Impedance: 8 ohms. Size: 1 1/4 x 13 1/4 x 16 1/4". Shpg. wt., 4 lbs.

5" system: Same as above, but with 5" poly-planar speaker. Power handling capacity: 5 watts peak. Frequency Response: 70 Hz to 20 Hz; Impedance: 8 ohms, Size: 3/8" x 6" x 10". Shpg. wt., 2 lbs.

Specialty Hi-Fi Speakers For The Home and Car

NEW Matched Pair Of Dome Hi-Fi Tweeters



14⁹⁵
per pair

Add to an Existing Speaker System for Superior High Frequency Performance

Specially developed high powered 3 1/2" hi-fidelity tweeters. The diaphragm is dome shaped, providing a nearly ideal polar pattern. Frequency response is 1500 Hz to 20 KHz. Because of low cone mass, transient distortion is negligible. Power handling capacity is 40 watts RMS with recommended crossover frequency at 4000 Hz or higher. Magnet weight 9 oz, ideal for use in 2 and 3 way 8-ohm speaker system. Shpg. wt., 3 lbs. Imported.

21 R 29500 Net 14.95

LAFAYETTE "Omni II" 10" 2-Way 360° Multi-Directional Hi-Fi Speaker System

ONLY

59⁹⁵

5 Year AAA Guarantee see page 415

Multi-Directional Sound spreads sound through entire room. You sit anywhere you want and hear perfect stereo.



- Power Handling: 40 Watts
- Response: 50-20,000 Hz
- 6 db/octave LC Crossover Network

Here is a multidirectional acoustic suspension system that provides undeniably realistic sound in any room...and with virtually any arrangement. Placement is not critical. Use 2 anywhere in the room...sit where you like—hear a natural blend of direct and reflected 360° sound. Features a powerful 10" woofer with a 40.6 oz. magnetic structure and a 1 1/4" voice coil, plus a direct radiator type 3 1/2" super tweeter. Handsome hand rubbed oiled walnut finish with charcoal brown grill cloth. 6 db/octave crossover network at 2600 Hz. Freq. Response: 50-20,000 Hz ±10 db. Power handling capacity: 40 watts. Brilliance level control. Impedance 8 ohms. Size 13" x 13" x 19 1/4". Imported. Shpg. wt., 29 lbs.

99 R 02438 WX No Money Down* Net 59.95

LAFAYETTE CRITERION® "R-10" SOLID STATE TRINARY REVERB AMPLIFIER/SPEAKER SYSTEM

ACTUALLY 3 QUALITY AMPLIFIERS IN 1

- 1) Use as a Reverb Amplifier and Speaker;
- 2) Use as a Stereo Center Channel Amplifier and Speaker;
- 3) Use as a Phono Amplifier and Speaker

34⁹⁵

Engineered to fill an important void in today's high fidelity market. Enhances your stereo listening by adding a center channel to your amplifier or receiver. Creates concert-hall realism when used as a reverb amplifier and speaker in stereo or mono systems. Or you can plug in a record changer with a ceramic cartridge—and you have a complete hi-fi system. Wide-range high compliance speaker delivers rich natural sound. Power output is 1.7 watts RMS. Sensitivity—ceramic phono—100 mv, center channel—150 mv. Inputs—Reverb, Center channel, phono (all inputs use RCA jacks and require leads with RCA plugs). Space-age solid state circuitry. Front panel volume control with push type on/off switch. Rear panel AC convenience jack. Size: 11 3/4" W x 8 1/4" H x 5 1/2" D. For 117 VAC 60 Hz. Imported. Shpg. wt., 8 lbs.

99 R 02446 No Money Down* Net 34.95



Handsome Hand Rubbed Oiled Walnut Cabinet

The Amazing LAFAYETTE Sound Reproducer

Turns virtually any Surface into a Speaker


Remarkable concept in providing sound almost anywhere. Coneless reproducer attaches to wall, doors, ceilings, or most any object. Transforms the whole surface into a sounding board for beautiful "sound reproduction". Easily connects to speaker leads of any radio, phono, tape player, amplifier, receiver or other sound equipment. Perfect for use in background music or PA systems. For 4, 8, or 16 ohm solid-state or tube equipment. Can be used in a car. Built-in magnet for attaching to metal objects and screw for attaching to wood, plastic, etc. Size: 2" dia. x 1 1/2" H. Shpg. wt., 1 lb.

21 R 01590 Net 7.95

ONLY

795

MADE IN U.S.A.



Attractive Cabinet Kits For Records and Components



(A)
COMBINATION
RECORD AND
COMPONENT
HUTCH

59⁹⁵

(B)
COMBINATION
RECORD AND
COMPONENT
CABINET



27⁹⁵

(A) COMBINATION RECORD AND COMPONENT HUTCH

Handsomely styled hutch designed to accommodate your high fidelity components, records, and tapes. Can also be used to store books. 2 shelves are adjustable for placement of your tape recorder, phonograph, or even a television set. Oiled walnut finish on

hardboard. Comes knocked-down. Simple to assemble with easy-to-follow instructions. Includes all mounting hardware. Overall size: 63"Hx14¼"Dx24"W. Lower compartment with sliding doors 16"Hx14¼"Dx24"W. Shpg. wt., 55 lbs.
20 R 23018WX Net 59.95

(B) COMBINATION RECORD AND COMPONENT CABINET

Striking contemporary design in a cabinet made specially for installation of your high-fidelity components and records. Provides maximum capacity for areas where space is limited. Cabinet is shipped knocked-down in easy-to-assemble form complete with all

necessary instructions and hardware. Oiled walnut finish on hardboard. Overall measurements 36"Wx16"Dx30"H. Inside measurements: Record storage section 15"Hx15"D; Component shelf section 16"Dx9"H. Shpg. wt., 30 lbs.
20 R 23026W Net 27.95

CONTEMPORARY ALL-PURPOSE CABINET

NEW ONLY 24⁹⁵

- Holds Up to 300 Records

All-purpose contemporary cabinet complements your decor; adds charm to your room. Walnut grain Permaeneer finish is scuff resistant, heat resistant, stain resistant, and easy to clean. Holds up to 300 records. Console design, 3 sliding grooved doors on island base. Easy to assemble. Inside dim: 46W x 13¾H x 13½"D. Overall size: 48Wx19Hx16"D. Shpg. wt., 54 lbs.
20 R 16012WX Net 24.95



ALL PURPOSE RECORD CABINET



Only
12⁹⁵

- Stores Up To 200 Records

DELUXE ALL PURPOSE RECORD CABINET



Only
29⁹⁵

- Holds Up To 400 Records

Roomy storage section with sliding doors allows for dust-free storage of up to 200 records. Sturdy construction. Mar-proof, walnut Styleite finish. Size: 29½W x 15½D x 25"H. Easily assembled.
20 R 58063W Shpg. wt., 17 lbs. Net 12.95

Handsome soft walnut una-vener finish. Solid construction—stain, mar, and heat resistant. Sliding doors. Holds up to 400 records. Top can be used as a bar or serving table. Easy to assemble. Size 40Wx16Dx26"H. Shpg. wt., 24 lbs.
20 R 23034W Net 29.95

To Speed Your Mail Order—Please Give Your Zip Code Number

Lafayette-Cat. No. 720 77

LAFAYETTE Stereo Headphones For Magnificent Private Listening

Lafayette MODEL SP55 STEREOPHONIC HEADPHONES

- Frequency Response 30-15,000 Hz
- Air-Cushioned Headband
- Soft Foam Rubber Ear Cushions for Maximum Comfort and Bass Response
- Two 2½" Wide Range Transducers

11⁹⁵

with 5 ft. cable

Provides outstanding full-fidelity private stereo listening. Extremely comfortable headband is covered with an air-filled vinyl bag which serves as a gentle cushion. Soft foam rubber ear pads keep out external noise and provide maximum bass response. Sensitivity is very high—a signal power of 1 to 2mw will produce adequate listening volume. Two specially designed full range 2½" transducers are precisely matched to each ear cup. Complete with attached stereo phone plug, junction box for connection of the headphones to equipment which does not have stereo phone jacks, 5 ft. cable, and instructions. Frequency Response: 30-15,000 Hz. Impedance: 8 ohms per phone. Imported. Shpg. wt., 1½ lbs.

99 R 01935

Net 11.95



**OUR
BEST
SELLER!**

Lafayette MODEL F-880 STEREO HEADPHONES

- Soft Rubber Air-Cushioned Ear Pads
- Actually Two 2½" Hi-Fi Speakers
- Frequency Response 25 to 15,000 Hz

17⁹⁵

with 5 ft. cable

Comfort-oriented design makes music listening a real pleasure. Provides dazzling wide range sound. The F-880 stereo headphones are actually two 2½" high fidelity dynamic speakers with a frequency response range of 25 to 15,000 Hz and are rated at ½ watt maximum input; impedance, 8 ohms per phone. The soft rubber air-cushioned ear pads provide extremely comfortable listening, help to keep out noise and maintain an excellent bass response. With 5 ft. cable and standard ¼" phone plug. Imported. Shpg. wt., 2 lbs.

99 R 02040

Net 17.95



Lafayette MODEL 8X STEREO HEADPHONES

- Soft Rubber Cushion Earcups
- With 5 ft. Coiled Cord
- Frequency Response: 35-15,000 Hz

7⁹⁵

with 5 ft. coiled cord

Wonderfully comfortable—features soft rubber cushion earcups which block out most external noise. Lightweight vinyl covered headband adjusts to fit easily . . . lets you listen to your favorite programs hour after hour without fatigue. The big 2" transducers in each earcup bring to your ears smooth, full fidelity sound and complete stereo separation. The headset weighs only 11 oz. Frequency response: 35 to 15,000 Hz. Output: 100 mw. Matches 8 or 16-ohm impedance. Supplied complete with 5-ft. coiled cord and standard ¼" phone plug. Imported. Shpg. wt., 1½ lbs.

99 R 01802

Net 7.95



Lafayette SP22 STEREO HEADPHONES

**Ideal For Use With Stereo Phonographs
and Low-Power Stereo Receivers
and Amplifiers**

- Frequency Response: 35-12,000 Hz
- Lightweight, Only 10 oz.
- Adjustable Headband

**ONLY
5⁹⁵**

with 6 ft. cable

Quality, private listening stereo headphones at a price everyone can afford. Perfect for stereo or mono. Designed for use with low priced stereo receivers, amplifiers, and phonographs. Adjustable headband and comfortable foam-filled vinyl ear pads. Large, 2½" diameter transducers for full-range response. Impedance: 8-ohms. With 6-foot of cable and standard stereo phone plug. Imported. Shpg. wt., 1 lb.

99 R 02123

Net 5.95



LAFAYETTE'S Best Headphones

NEW

Lafayette F-2001 Electrostatic Stereo Headphone

- Super, Wide Range Response 5-35,000 Hz
- Maximum Power Handling Capacity—10 Watts
- Adjustable Vinyl Cushioned Headband
- 5" x 4½" Earphone Cushions
- Weighs only 16 oz.

The absolute super-realism of live sound is reproduced by this vastly superior, comfortable lightweight, headphone. The substance and delicate tone of each instrument is spectacularly captured either individually or in harmony with all the other instruments of the orchestra. Listening to the F2001 stereo phones is truly a magnificent experience. Uses the electrostatic principle—a moving diaphragm is suspended between 2 metal plates. A static electrical field is set up that controls the motion of the diaphragm. A self energizer included is required to convert an audio signal into a DC polarizing voltage needed to charge the diaphragm. No extra AC power supply is required. Delivers 3 octaves of sound beyond conventional phones. Freq. Response is 5-35,000 Hz. Energizer has a speaker/phone switch and comes with color coded speaker cables. Impedance is 4-16 ohms. Imported. Shpg. wt., 10 lbs.
99 R 02636 No Money Down* Net 59.95



ONLY **59.95**

Includes:
 Electrostatic Headphone
 with 10 ft. Coiled Cord and
 Connector, and Self Energizer
 With Color Coded Speaker Cables

NEW

Lafayette F-500 4-Speaker Stereo Headphone



49.95
 with 6 ft.
 coiled cord

Each Earcup Contains 3½" Woofer,
 3" Tweeter, and L/C Cross-over Network.

- Frequency Response 16-22,000 Hz
- Adjustable Vinyl Cushioned Headband

Pure, true, uncolored stereo sound. Each earpiece contains a 2 speaker 2-way sound system featuring a dynamic 3½" woofer and a super mylar cone type tweeter with a 400 Hz. L/C cross-over network. The sound is tailored to complement ear sensitivity in order to enhance listening pleasure. Absolute smooth response is virtually distortion free. Rugged shockproof construction. Headband adjustment for added comfort. Extra wide foam filled ear cushions seal out ambient noise, and extends bass response. Meets the rigid requirements of professional use. Impedance 8 to 16 ohms. With coiled cord that extends to 6 ft. Shpg. wt., 4 lbs. Imported.
99 R 02685 No Money Down* Net 49.95

Lafayette F1000 Two-Way Stereo Headphone with Individual Volume Controls

- Individual Left and Right Channel Volume Controls
- Response: 20-20,000 Hz
- Two 2¼" 2-Way Woofer/Tweeter Transducers

With the F1000 you can enjoy the realism of virtually distortion free wide range stereo headphone listening. Each earcup contains a specifically designed 2-way woofer/tweeter transducer and a volume control for critical, controlled sound monitoring. For private music listening you can tailor the sound to your personal taste without having to get up and adjust the volume controls on your amplifier. Comfortable, lightweight, form fitting design permits you to enjoy extended listening without tiring—hour after hour—stereo or mono. Impedance, 8-ohms. With coiled cord that extends up to 6 feet. Imported.
 Shpg. wt., 2½ lbs.
99 R 02552 No Money Down* Net 39.95



39.95
 With 6 Ft.
 Coiled Cord

Wide Form Fitting,
 Adjustable Foam-Filled
 Leatherette Headband

Soft, Foam-Filled Ear
 Cushion For Comfortable,
 Excellent Seal

Left and Right Channel
 Volume Controls

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 79

FAMOUS LAFAYETTE F-990 Stereo Headphones

- Two large 3½" Wide Range Transducers
- Frequency Response 20-20,000 Hz
- Air-tight Earphone Cushions
- Fully Adjustable, Cushioned Vinyl Headband

ONLY **29⁹⁵** With 6½' Cable*

Now the listener in his home can own a pair of stereo headphones similar to the one used in laboratories, recording studios and broadcast stations. Superbly engineered to provide brilliant, full-dimensional stereo sound. Two large 3½" transducers provide complete full-range coverage from 20-20,000 Hz. A comfortably soft, but airtight seal to the ear is provided by foam filled earphone cushions. Fully adjustable, cushioned vinyl headband will give you hours of listening comfort without any fatigue. Comes with 6½ ft. cable and standard stereo phone plug. Impedance: 8 ohms. Imported. Shpg. wt., 2½ lbs.

99 R 02099 Net 29.95




SENNHEISER HD-414 STEREO HEADPHONES

33⁹⁵ With 10' Cable

- Lightweight and Compact
- "Open Air" Design

Totally natural, full-fidelity reproduction with a minimum of distortion. Unique "open air" foam ear cushions drastically reduce weight and bulk of the headset (only 5 oz. without cord). Eliminates need for closed cavities on either side of earphone diaphragms. Features 1¾" wide range transducers. Frequency response: 20-20,000 Hz. 2000 ohm impedance. Connects directly to either high or low impedance outputs. With 10 ft. cable and stereo phone plug. Shpg. wt., 1½ lbs. Imported.

21 R 58004 No Money Down* Net 33.95



SUPEREX MODEL PRO-B-V

59⁹⁵ with 15 ft. coiled cord

- Tuned Bass Ports
- Response 16-25,000 Hz

Professional quality stereo headphones. Each phone cup has a calibrated and matched 2-way (woofer/tweeter) speaker system with crossover network. Each system is individually tuned and ported. Luxuriously comfortable—the Pro-B-V features a replaceable, soft vinyl covered urethane "com-form" ear cushion. 4-16 ohm impedance. Shpg. wt., 3 lbs.

21 R 80073 No Money Down* Net 59.95

Suprex Model ST-Pro-B—same as above but less bass ports. Frequency response: 18-22,000 Hz. With 7 ft. cord and plug.

21 R 80057 Shpg. wt., 2¼ lbs. No Money Down* Net 49.95



STEREO HEADPHONE ACCESSORIES

STEREO HEADPHONE REMOTE CONTROL BOX

Only **4⁹⁵**

Designed to connect 1 or 2 stereo headphones to an existing system without the need of continually disconnecting speakers. Separate volume controls are provided for each side of the headset. Speaker muting switch permits using stereo headphones and speakers together, or stereo phones only for private listening. Impedance: 4-16 ohms. 4¾" x 1¾" x 1¾" D. Imported. Shpg. wt., ¾ lbs.

99 R 00366 Net 4.95



25 FT. UNIVERSAL STEREO HEADPHONE EXTENSION CORD

2⁹⁵ Now with Coiled Cord

- Plugs Directly Into Front Panel Stereo Headphone Jacks

Listen to stereo through your favorite stereo headphone anywhere in the room. Ideal for use with Lafayette, Koss, Suprex, Jensen, Sharp and many other headsets. Flexible 3-conductor coiled cable. With a ¼" 3-circuit plug on one end, a 3-circuit jack on the other end. Imported. Shpg. wt., ¾ lb.

99 R 01166 Net 2.95



STEREO HEADPHONE VOLUME CONTROL

- Ideal for Stereo Headphones that don't have self-contained volume controls



Permits the listener to individually control the volume of his stereo headphone to his personal taste. Features left and right channel volume controls and 3-way switch (right, left, stereo). With 6-foot cord standard and plug on one end for connection to stereo amplifier jack, and 2 foot cord and jack on other end for connection to stereo headphone. Shpg. wt., 1 lb. Imported.

99 R 00242 Net 4.95

4⁹⁵

10-FT. STEREO HEADPHONE EXTENSION CORD

- For Stereo Amplifiers Without Headphone Jack

1⁶⁹

Terminates in 3 spade-lug terminals instead of phone plug. Imported. Shpg. wt., ½ lb.

99 R 01695 Net 1.69



"Y" ADAPTER CABLE FOR DUAL STEREO HEADPHONE LISTENING

1⁷⁹

For connecting 2 stereo headphones to 1 output jack. Permits 2 persons to listen to same program. Two 3-circuit ¼" plugs on one end, 3 circuit jack on other end. 3-feet long. Shpg. wt., 6 oz.

24 R 71001 Net 1.79



KOSS DYNAMIC and ELECTROSTATIC STEREO PHONES

Koss Professional Model PRO-4AA

60⁰⁰
with 10 ft. coiled cord

No Money Down*

- Equipped For Boom Mike Attachment



Gives smooth, fatigue-free response, 2 octaves beyond conventional dynamic phones. Adjustable wide headband cushion for maximum comfort. Patented, liquid-filled, removable cushions. Designed for use with all stereo hi-fi amplifiers, will operate on any unit from 1 to 500 watts. High quality drivers mounted in acoustically designed enclosures provide smooth frequency response from 10 to 20,000 Hz. With 10 ft. coiled cord and plug, 4 ohms impedance. Shpg. wt., 2½ lbs.

21 R 45209

Net 60.00

Koss ESP-6 Electrostatic Stereo Phone

95⁰⁰

with 10' coiled cord, connector box, and portable carrying case



Totally new concept in stereo headphones! Uses electrostatic principle . . . self-energized diaphragms will reproduce 3 octaves of sound beyond the limits of voice coil and cone type driven headphones. Frequency Response: 30-19,000 Hz. ±2db; Usable Response: 10 Hz to 20 kHz. Input Impedance: 4 to 16 ohms. Cushioned foam rubber headband for maximum comfort. Liquid-filled ear cushions minimizes annoying external noise. Pilot lamps on each ear piece indicates sound level. Including 10' coiled cord, T-3 connector box with speaker on/off switch, and carry case. Shpg. wt., 6¼ lbs.

21 R 45167L No Money Down* Net 95.00

Koss Model KO-727B

34⁹⁵
with 10 ft. coiled cord

No Money Down*

- With 10-ft. Coiled Cord



Enjoy full dimensional stereo music with maximum comfort. Highly sensitive stereophonic reproducers will accept up to 60 watts per channel from any normal program source and can be used in any system with a 4, 8 or 16 ohm output. Foam-filled ear cushions are removable for easy cleaning. 10-ft. coiled cord for added convenience. Distortion—less than 1% at maximum output. Response: 10-15,000 Hz. Fully adjustable for comfortable private listening—even during long listening periods. Shpg. wt., 2¼ lbs.

21 R 45076

Net 34.95

NEW Koss KRD-711 "Red Devil" Stereophones

29⁹⁵

with 10' coiled cord 1" voice coil



Lightweight stereophone weighs only 12 ounces and still delivers exciting sound. The flexible high strength polypropylene headband conforms to any head size. Has neoprene foam ear cushions for ambient noise isolation. Frequency response 20 - 20,000 Hz. Impedance 20 ohms each channel. Can be used with systems having 4, 8, or 16 ohms output taps. 1" voice coil, Mylar diaphragm. Color: Devil Red. With 10 ft. cord & plug. Shpg. wt., 2 lbs.

21 R 45217

Net 29.95

Koss Model SP-3XC



19⁹⁵

with 10 ft. coiled cord

Low cost SP-3XC Stereophones are a specially constructed headset that provide a wide frequency range of 10-15,000 cps by means of unusual 3½" dynamic reproducers incorporated into each earphone. Foam cushioned earcups are extremely comfortable to wear, light and rugged. Ideal for Stereo, they can also be used for monaural sound. Impedance of 4-16 ohms. With 10 ft. cord and plug. Shpg. wt., 2 lbs.

21 R 45134

Net 19.95

Koss Model K-6



26⁵⁰

with 10 ft. coiled cord

Combines famous Koss sound with comfortable efficient fit. Spring steel headband and foam-filled ear cushions form effective seal to achieve a freq. response of 10-16,000 Hz. Vinyl-covered cushions removable for easy cleaning with soap and water. Sponge foam headband for comfort during extended listening periods. Impedance: 4-16 ohms. 10-ft. coiled cord with standard stereophone plug for direct connection to most amplifier and receiver systems. Shpg. wt., 2 lbs.

21 R 45175

Net 26.50

ACCESSORIES FOR KOSS PHONES

A T-1 Monitoring Box



B T-5 Remote Control Box

A Model T-1 Monitoring Box

For use in monitoring tapes from high impedance sources such as tape-recorders with preamp only. Contains matching transformers for 600 to 10,000 ohm outputs. Shpg. wt., 2 lbs.

21 R 45035

Net 7.95


B Model T-5 Headset Control Box

Provides stereophone and speaker control from remote location. Has jacks for 2-sets of stereophones. Left and right channel volume controls and speaker on-off switch. Impedance: 4-16 ohms. Metal cabinet.

21 R 45043 Shpg. wt., 1½ lbs. Net 9.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Pickering, Empire, Shure, Stanton Cartridges



PICKERING MAGNETIC STEREO CARTRIDGES

To simplify cartridge mounting all Pickering cartridges will be supplied with a universal mounting platform which will snap into any standard tone arm head. The Pickering cartridge will then easily snap onto the platform.

A DELUXE XV-15 ELLIPTICAL SERIES—Pickering's Premiere Cartridges. Includes "Dustamatic Brush" which automatically cleans the grooves in advance of the stylus. Specifications: Channel separation 35 db; Normal output: XV-15/750E—5.5 mv; XV-400E—5.5 mv, XV-15/200E—8 mv. Frequency response: 10 to 25,000 Hz. Stylus type: XV-15/750E—.0002 x .0009" elliptical; XV-15/400E—.0003 x .0009" elliptical; XV-15/200E—.0004 x .0007" elliptical. Tracking force: XV-15/750E—1/2 to 1 gram; XV-15/400E—3/4 to 1½ grams; XV-15/200E—2 to 4 grams. Shpg. wt., 8 oz. No Money Down*

Stock No.	Model	For	Net
21 R 53864L	XV-15/750E	Manual turntables	65.00
21 R 53757L	XV-15/400E	Manual turntables	54.95
21 R 53781L	XV-15/200E	Automatic turntables	49.95

B V-15 PHASE IV Series incorporates all of the fine characteristics of the XV-15 Series. Narrow and low profile design for simplified mounting. Improved high frequency tracking, is accomplished through lower moving mass of the stylus assembly. The DUSTAMATIC brush assembly automatically cleans records as you play them. The brush is hinged independent of the stylus and never interferes with tracking force. Specifications: Nominal output: IV-AME 5.5 mv, IV-ATE 6.5 mv, IV-ACE 8.0 mv. Separation: IV-AME 30 db, IV-ATE 28 db, IV-ACE 26 db. Tracking force: IV-AME 1¼ grams ±1/2, IV-ATE 3 grams ±1, IV-ACE 4 grams ±1. Response: IV-AME 20 to 20,000 Hz, IV-ATE 20-18,000 Hz, IV-ACE 20 to 17,000 Hz. Stylus OV-AME .0003 x .0007, IV-ATE and IV-ACE .0004 x .0007 AVERAGE. Shpg. wt., 5 oz.

Stock No.	Model	Net
21 R 53906L	Phase IV-AME No Money Down*	49.95
21 R 53922L	Phase IV-ATE No Money Down*	39.95
21 R 53930L	Phase IV-ACE	29.95

C P-SERIES STEREO CARTRIDGES—Frequency response: 20 to 15,000 Hz. Nominal output: P/ATE-1, 8 mv.; P/AT-1, 8.5 mv.; P/AC-1, 9 mv. Channel separation: 20-25 db. Tracking force: P/ATE-1, P/AT-1, 2 to 5 grams; P/AC-1, 3 to 7 grams. P/AC-1, P/AT-1 with .7 mil conical diamond stylus; P/ATE-1 with .0005 x .0008 elliptical stylus. Shpg. wt., 4 oz.

21 R 53880L	P/ATE-1 Elliptical	Net 24.95
21 R 53567L	P/AT-1 Conical	Net 19.95
21 R 53575L	P/AC-1 Conical	Net 17.95

EMPIRE MAGNETIC STEREO CARTRIDGES

K 90EE/X Elliptical Cartridge—15° vertical tracking angle. Fully compatible for stereo or mono. Freq. Response 15-25,000 Hz. Output 8.0 mv, Channel Separation 30db. Tracking Force: 1½ to 4 grams. Shpg. wt., 2 oz.
21 R 34955L Net 24.95

L 909E Elliptical Cartridge—15° vertical tracking angle. Induced field moving magnetic armature. Fully compatible for stereo or mono. Freq. Response 12-25,000 Hz, Channel Separation 30 db, Output 8.0mv Tracking force: 1 to 4 grams. Shpg. wt., 2 oz.
21 R 34948L Net 29.95

SHURE MAGNETIC STEREO CARTRIDGES

D MODEL M44E ELLIPTICAL STEREO CARTRIDGE. Features an elliptical stylus (.0004"x.0007") designed for automatic turntables. Tracks from 1¼ to 4 grams. Specifications: Frequency response: 20-20,000 Hz, channel separation: 25 db, Output voltage: 9.3 mv. Compliance: 15.0x10⁻⁴ cm/dyne. Shpg. wt., 3 oz.
21 R 62360L Net 24.95

E MODEL M-55E ELLIPTICAL STEREO CARTRIDGE. Features elliptical diamond stylus and 15° vertical tracking angle. For outstanding performance use with tone arm at a tracking force of 3/4 to 2 grams. Separation over 25 db. Output voltage: 9.3 mv. Compliance 25 x 10⁻⁴ cm/dyne. Shpg. wt., 3 oz.
21 R 62410L Net 29.95

F MODEL M93E ELLIPTICAL STEREO CARTRIDGE. Hi-Track Elliptical cartridge with easy snap-in mount. Tracking force between 1½ to 3 grams. Provides outstanding results in automatic or manual turntables. With Bi-Radial .0004" x .0007" diamond stylus. Freq. Response 20 to 20,000 Hz. Separation 25 db at 1,000 Hz. Wt., 6 oz.
21 R 62436L No Money Down* Net 39.95

G MODEL M91E DELUXE HI-TRACK ELLIPTICAL STEREO CARTRIDGE with optimized design parameters for trackability. For use in automatic and manual turntables. With Bi-Radial .0002" x .0007" diamond stylus. Freq. Response 20 to 20,000 Hz. Separation at 25 db at 1,000 Hz. Tracking force: 3/4 to 1½ grams. Shpg. wt., 3 oz.
21 R 62444L No Money Down* Net 49.95

H V-15 TYPE II SUPER-TRACK IMPROVED STEREO DYNETIC ELLIPTICAL CARTRIDGE. Shure's premiere cartridge featuring increased trackability in the low and mid-frequency ranges. Recreates music with transcendent purity. Retractable elliptical .0007" x .0002" diamond stylus. Specifications: Frequency response: 20 to 25,000 Hz. Channel separation: 25 db at 1,000 Hz. Output voltage: 3.5 mv. Tracking force: 3/4 to 1½ grams. Shpg. wt., 8 oz.
21 R 62386L No Money Down* Net 67.50

I MODEL M7/M21D STEREO CARTRIDGE. Frequency response: 20 to 20,000 Hz. Channel Separation: More than 20 db at 1000 Hz. Output voltage: 4 mv. per channel at 1000 Hz. Tracking force: 2 to 5 grams. Tracks perfectly in all record changer arms with .7 mil conical diamond stylus. Shpg. wt., 3 oz.
21 R 62063L Net 12.95

STANTON MAGNETIC STEREO CARTRIDGE

J MODEL 801EE—Designed for low-distortion tracking with minimum stylus force. High compliance, low mass, and low pressure assure perfect safety of all records. Response: 10-20,000 Hz. Separation: 35 db, nominal. Output: 0.7 mV/cm/sec, nominal. Tracking force: 3/4-1½ grams. Diamond elliptical stylus, and stylus brush. Shpg. wt., 6 oz.
21 R 24006L No Money Down* Net 72.00

M 999 Elliptical Series—Empire premiere cartridges. All stylus are hand polished bi-radial. 15° vertical tracking angle. For stereo or mono use. 4 coil system gives complete freedom from hum pick-up. Easily replaceable stylus assembly. Specifications: Output 999E/X and 999SE/X, 8mv; 999TE/X, 6mv; Channel separation 35db; Frequency Response: 999E/X 10-30,000 Hz; 999SE/X 8-32,000 Hz; 999TE/X 6-36,000 Hz. Tracking Force: 999E/X—¾ to 2 grams, 999SE/X and 999TE/X ½ to 1½ grams. Shpg. wt., 6 oz.
21 R 34930L 999E/X 39.95
21 R 34922L 999SE/X 49.95
21 R 34914L 999TE/X 64.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Tone Arms, Cartridges, Replacement Diamond Styli

Exclusive LAFAYETTE/PICKERING Phase 44 Elliptical Diamond Needle Stereo Magnetic Cartridge



44⁹⁵
No Money
Down*

• Designed Especially
To Be Used In Derived
4-Channel Systems

The Lafayette/Pickering Phase 44 was especially designed to be used as the stereo cartridge in the derived 4-channel stereo systems that use the Lafayette and other brand 4 channel adapters. The Phase 44 cartridge will perform equally well when used in a conventional 2-channel stereo system. The playback characteristics of the Phase 44 have been tailored to achieve the utmost in performance. Channel separation exceeds 35 db. A special .4 x 9 elliptical diamond stylus tracks at 1 1/2 (±1/2) grams. Frequency range is 10-25,000 Hz. Nominal output 5.5 mv. The patented Dustmatic stylus will protect your records from dust and preserve their natural sound. Shpg. wt., 4 oz.

21 R 01731L Net 44.95
Replacement Diamond Stylus for Phase 44
21 R 01723L Net 14.95

ADC and GRADO Stereoc Cartridges



ADC 220XE



Grado F Series

220XE ELLIPTICAL STEREO CARTRIDGE. Channel separation: 20 db. Response: 10-18,000 Hz ±3 db. Tracking force: 1 1/2 to 4 gms. Elliptical Diamond Stylus. Output: 5 mv.

21 R 13306L Shpg. wt., 6 oz. Net 22.00

GRADO F SERIES STEREO CARTRIDGES. Frequency Response: 10 to 35,000 Hz. Channel separation: 25 db. Output: 4 mv @ 3.54 CMV. Recommended Tracking Force: 1 1/2 to 3 1/2 grams. Shpg. wt., 4 oz.

21 R 41356L FTR .6 Spherical 9.95
21 R 41364L FTE 7 x .3 Elliptical 19.95

Shure M232 Stereo Tone Arm

32⁷⁵



Quality 12" tone arm that ACCEPTS MOST CARTRIDGES and permits them to operate at their maximum potential performance. Features precision ball bearings at all pivot joints, plus in head with positive alignment lock and variable height adjustment. Positive visual control over balance without altering overall arm length. Tracking force 1 1/2 to 6 grams. Comes with arm rest, mounting template, mounting hardware. Shpg. wt., 2 1/4 lbs.

21 R 62519L No Money Down* Net 32.75

MODEL M236 Same as Model M232, but for 16" Records in broadcast use. Shpg. wt., 2 1/4 lbs.

21 R 62527L No Money Down* Net 35.00

Shure A23H Extra Plug In Head. Shpg. wt., 5 oz.
21 R 62535L Net 3.00



Replacement Diamond Styli for Stereo Hi-Fi Cartridges



• Wide Selection To Fit The Most Popular Selling Stereo Cartridges—Both Past And Current

• For Pickering, Shure, Empire, Grado, ADC, Stanton, and GE • Manufacturer's Exact Replacement Styli

Stock No.	MFR.	Type	STYLUS	For	Net
21 R 53450L	Pick.	D1500AME-2	-ELLIP	V15/AME-1, AME-2	20.95
21 R 53468L	Pick.	D1507AM-2	.7 MIL	V15/AM-1, AM-2	12.95
21 R 53476L	Pick.	D1507AT-2	.7 MIL	V15/AT-1, V15/AT-2	11.50
21 R 53484L	Pick.	D1507AC-2	.7 MIL	V15/AC-1, V15/AC-2	10.50
21 R 53500L	Pick.	D1527	2.7 MIL	V15 Series	12.95
21 R 53591L	Pick.	P/D07-T	.7 MIL	P/AT-1	10.50
21 R 53609L	Pick.	P/D07-C	.7 MIL	P/AC-1	9.90
21 R 53698L	Pick.	PDE	ELLIP	PATE-1	15.95
21 R 53021L	Pick.	D3807AT	.7 MIL	U38AT	12.95
21 R 53070L	Pick.	D3807A	.7 MIL	380A	13.95
21 R 53062L	Pick.	D3807C	.7 MIL	380C	12.95
21 R 53534L	Pick.	D3810C	1 MIL	U38AT, 380C	12.50
21 R 53138L	Pick.	D3827C	2.7-MIL	U38AT, 380C	13.50
21 R 53112L	Pick.	D9007	.7 MIL	MARK/II	12.95
21 R 53633L	Pick.	D1500ATE-2	ELLIP	V15/ATE-2	18.95
21 R 53641L	Pick.	D1500AME-3	ELLIP	V15/AME-3	26.25
21 R 53658L	Pick.	D1500ATE-3	ELLIP	V15/ATE-3	23.65
21 R 53674L	Pick.	D1507AT-3	.7 MIL	V15/AT-3	14.50
21 R 53815L	Pick.	D400	ELLIP	XV-15/400E	28.50
21 R 53823L	Pick.	D200	ELLIP	XV-15/200E	26.25
21 R 53807L	Pick.	D100	ELLIP	XV-15/100	14.70
21 R 53690L	Pick.	D1527-3	2.7 MIL	V15-3 Series	15.25
21 R 53831L	Pick.	D1507AC-3	.7 MIL	V15AC-3	12.50
21 R 53849L	Pick.	D1500ACE-3	ELLIP	V15ACE-3	21.50
21 R 53872L	Pick.	D750	ELLIP	XV-15/750E	31.50
21 R 53914L	Pick.	DIV-AME	ELLIP	Phase IV/AME	28.95
21 R 53948L	Pick.	DIV-ATE	ELLIP	Phase IV/ATE	23.65
21 R 53955L	Pick.	DIV-ACE	ELLIP	Phase IV/ACE	20.50
21 R 34047L	Empire	S880P-6RD	.6 MIL	880P	12.95
21 R 34401L	Empire	S888PE-ERD	ELLIP	888PE	20.95
21 R 34419L	Empire	S888P-6RD	.6 MIL	888P	14.95
21 R 34971L	Empire	S999TE/X-ERD	ELLIP	999TE/X	32.95
21 R 34963L	Empire	S999SE/X-ERD	ELLIP	999SE/X	24.95
21 R 34492L	Empire	S999E/X-ERD	ELLIP	909E/X	19.95
21 R 34484L	Empire	S909E/X-ERD	ELLIP	909E/X	14.95
21 R 34476L	Empire	S90E/X-ERD	ELLIP	90E/X	13.95
21 R 34450L	Empire	S888-7RD	.7 MIL	888	12.95
21 R 34617L	Empire	S888E-ERD	ELLIP	888E	16.95
21 R 34625L	Empire	S888SE-ERD	ELLIP	888SE	22.95
21 R 34724L	Empire	S999VE-ERD	ELLIP	999VE	36.95
21 R 34732L	Empire	S888TE-ERD	ELLIP	888TE	24.95
21 R 34823L	Empire	S888VE-ERD	ELLIP	888VE	29.95
21 R 62022L	Shure	N3D	.7 MIL	M3D, M7D	7.85
21 R 62071L	Shure	N21D	.7 MIL	M7D, M3D	11.00
21 R 62170L	Shure	N44-5	.5 MIL	M44-5	11.00
21 R 62188L	Shure	N44-7	.7 MIL	M44-7	9.75
21 R 62543L	Shure	VN15E	ELLIP	V15, V15/II	27.00
21 R 62246L	Shure	N55E	ELLIP	M80, M55	14.95
21 R 62253L	Shure	N99	.7 MIL	M99	15.00
21 R 62378L	Shure	N44E	ELLIP	M54E	12.50
21 R 62402L	Shure	N32E	ELLIP	M32E	14.50
21 R 62477L	Shure	N91E	ELLIP	M91E	24.50
21 R 62469L	Shure	N93E	ELLIP	M93E	19.50
21 R 13108L	ADC	R-4E	ELLIP	P/4-E	18.00
21 R 13124L	ADC	R-770	.7 MIL	770	9.00
21 R 13157L	ADC	R-6E	ELLIP	660/E	15.00
21 R 13207L	ADC	R-12E	ELLIP	10E/II, 10/E	22.50
21 R 13280L	ADC	R-9E	ELLIP	20E, 990E	12.00
21 R 13330L	ADC	R20X/E	ELLIP	220X/E	10.00
21 R 38048L	GE	DR-7D	.7 MIL	V1000-7	8.40
21 R 38063L	GE	VR222	.7 MIL	VR-22	5.00
21 R 38051L	GE	DR3D	ELLIP	VR-10003	16.00
21 R 41372L	Grado	FTR/S	.6 MIL	SPHERICAL	7.50
21 R 41380L	Grado	FTE/S	.7 x .3 MIL	ELLIP.	12.50
21 R 24014L	Stanton	D6800EE	ELLIP	681EE	36.00

*See Page 22 for Full Credit Details on Easy Pay Plan

DELUXE *Garrard* / *Synchro-Lab Automatic* *Turntables Featuring...*

Money Saving Combinations *Save up to 39.95* From Individual Catalog Prices

When you purchase your choice of Below Elliptical Cartridge with a Garrard Turntable Listed on Page 84 or 85

(See Page 82 and 83 For Description of cartridges)



Lafayette/Pickering
Phase 44
44.95



Pickering
Phase IV/ATE
39.95



Shure M91E
39.95



Pickering
Phase IV/ACE
29.95



Shure M93E
29.95



SL95B 3 Speed Advanced AUTOMATIC TRANSCRIPTION TURNTABLE with Choice of Elliptical Stereo Cartridge

139⁵⁰
 less cartridge, less
 base

139⁵¹
 choice of deluxe
 elliptical cartridge,
 less base

144⁵⁰
 Plus Lafayette/Picker-
 ing Phase 44 Car-
 ridge, Less base

No Money Down*

Built-in calibrated stylus pressure gauge permits accurate audible/visible click settings in 1/4 gram increments. Viewing window in tonearm for easy reading.

Tonearm floats virtually friction-free within a gyroscopically gimbaled mounting on jewel-like needle pivots for lightest possible tracking.

Garrard's finest 3-speed Automatic Stereo Transcription turntable with synchronous motor for perfectly constant speed. Plays 33 1/3, 45, and 78 RPM Records. Advanced ultra-low mass tonearm of Afromosia wood set into aluminum, floats virtually friction free on jewel-like pivots in gyroscopically gimbaled mounting. Fully adjustable counterweight. Fully damped single-control cusing/pausing. Viscous damped slow descent of tonearm during manual and automatic play. Exclusive 2-point record support at center and edge during automatic play. Permanently accurate anti-skating control of patented sliding weight design. Calibrated stylus pressure gauge adjustable in 1/4 gram increments with window scale for easy reading. Slide-in cartridge clip. Full size, light-weight turntable. Two interchangeable spindles. All connecting cables for 110-130V 60 Hz AC Size: 15 1/4" W x 14 1/4" L, above motor board 4 3/8", below 2 1/4". Imported. Wt., 13 lbs. Less Base.

- 21 R 40440WX SL95B No Money Down* Net 139.50
- 21 R 90569WXM SL95B Plus Pickering Phase IV/ATE Net 139.51
- 21 R 40911WXM SL95B Plus Shure M93E Net 139.51
- 21 R 90577WXM SL95B Plus Laf/Pickering Phase 44 Net 144.50



SYNCHRO-LAB MOTOR For flawless, silent synchronous speed . . .



VISCOUS DAMPED setdown of tonearm in automatic play . . . an exclusive SL95B, SL75B, SL72B feature.



ADJUSTABLE ANTI-SKATING CONTROLS prevent record and stylus wear.



TWO-POINT RECORD SUPPORT on SL95B, SL75B, SL72B at both center and edge.



SLIDE-IN CARTRIDGE CLIP assures positive alignment.

MODEL SL55B 3-SPEED SYNCHRO-LAB AUTOMATIC TURNTABLE

with Choice of Elliptical Stereo Cartridges

59⁵⁰ less cartridge and base

Money-Saving SL55B/Cartridge Combinations—See Below Listings




No Money Down*

MODEL SL65B 3-SPEED SYNCHRO-LAB AUTOMATIC TURNTABLE

with Choice of Elliptical Stereo Cartridges

74⁵⁰ less cartridge and base

Money-Saving SL65B/Cartridge Combinations—See Below Listings



No Money Down*

Plays 33 $\frac{1}{3}$, 45, and 78 RPM Records. Light weight, tubular aluminum tonearm with fixed-position damped counterweight and slide-in cartridge clip. Built in stylus force adjustment and optical scale. Viscous damped, single-lever cueing. Fully adjustable anti-skating. Oversized turntable with all connecting cables. For 110-130V 60 Hz AC. Size: 14 $\frac{3}{4}$ "Wx12 $\frac{1}{2}$ "L; above motor board 4 $\frac{3}{4}$ ", below 2 $\frac{3}{4}$ ". Imported. Wt., 9 $\frac{1}{2}$ lbs. less base.

21 R 40481W SL55B only.	Net 59.50
21 R 90486WM SL55B Plus Pickering Phase IV/ACE	Net 59.51
21 R 40614WM SL55B and Shure M55E	Net 59.51
21 R 90494WM SL55B Plus Pickering Phase IV/ATE	Net 64.50
21 R 40945WM SL55B plus Shure M93E	Net 64.50
21 R 90502WM SL55B Plus Laf/Pickering Phase 44	Net 69.50

Plays 3 Speeds: 33 $\frac{1}{3}$, 45, and 78 RPM. Features: Synchro-Lab Motor, large turntable of heavy aluminum, low-mass tubular aluminum tonearm dynamically balanced with adjustable counterweight, adjustable anti-skating control, viscous damped, single lever cueing. Precision stylus pressure gauge with optical scale. Connecting cables. For 110-130V, 60 Hz. AC. Size: 15"Wx13 $\frac{1}{4}$ "L; above motor board 4 $\frac{3}{4}$ ", below 3". Imported. Wt., 10 $\frac{1}{4}$ lbs. less base.

21 R 40473W SL65B only.	Net 74.50
21 R 90538WM SL65B Plus Pickering Phase IV/ACE	Net 74.51
21 R 40655WM SL65B Plus Shure M55E	Net 74.51
21 R 90544WM SL65B Plus Pickering Phase IV/ATE	Net 79.50
21 R 40952WM SL65B Plus Shure M93	Net 79.50
21 R 90551WM SL65B Plus Laf/Pickering Phase 44	Net 84.00

SL72B 3-SPEED SYNCHRO-LAB AUTOMATIC TRANSCRIPTION TURNTABLE

with Choice of Elliptical Stereo Cartridges

99⁵⁰ Less cartridge, and base

99⁵¹ choice of deluxe, elliptical cartridge, less base

104⁵⁰

Plus Lafayette/Pickering Phase 44 Cartridge, Less base

No Money Down*



Plays 33 $\frac{1}{3}$, 45, and 78 RPM Records. Synchro-Lab Motor for perfectly constant speed, unwavering musical pitch. Record platform for safe, two-point support during automatic play. Low-mass tubular aluminum tonearm of advanced design floats on needle pivots within a gyroscopically gimbal-mounted for flawless tracking. Fully adjustable counterweight. Slide-in cartridge clip. Patented, permanently accurate sliding weight anti-skating control. Calibrated stylus pressure gauge with visible scale. Damped set-down of tonearm in manual and automatic play. Single control viscous damped cueing. Simplified finger-tip tab operating controls. Full size turntable. Two interchangeable spindles. All connecting cables. For 110-130V 60 Hz. AC. Dimensions: 15 $\frac{1}{2}$ "Wx14 $\frac{1}{4}$ "L; above motorboard 4 $\frac{3}{4}$ ", below 2 $\frac{3}{4}$ ". Imported. Shpg. wt., 11 lbs. less base.

21 R 40465W SL72B only.	Net 99.50
21 R 90510WM SL72B plus Pickering Phase IV/ATE	Net 99.51
21 R 40960WM SL72B plus Shure M93E	Net 99.51
21 R 90528WM SL72B plus Laf/Pickering Phase 44	Net 104.50

Gyroscopically gimbal-mounted mounting, plus needle-pivots assure friction-free tonearm movement . . . vertically and horizontally . . . and light tracking.

Ultra-low-mass, lightweight tonearm of advanced hexagonal shaped design and adjustable counterweight provides perfect balance and flawless tracking.

*See Page 22 for Full Credit Details on Easy Pay Plan

Garrard

THE NAME STANDS FOR
ZERO TRACKING ERROR —
UP TO 160 TIMES LESS
THAN WITH ANY
CONVENTIONAL
TONE ARM

REVOLUTIONIZES THE AUTOMATIC
TURNTABLE WITH THE NEW

ZERO 100



189⁵⁰

True-Tangent Tracking
Geometry. The Stylus is
Perpendicularly
Tangent to the
Groove Through-
out the Record



Another Lafayette Exclusive!


Buy the Deluxe Lafayette/Pickering
Phase 44 Elliptical Diamond Needle
Cartridge

for Only **1¢**
Purchase of the
ZERO 100

SAVE
44.95

From Individual Catalog Prices

The Lafayette/Pickering Phase 44 was designed to extract the maximum in 4-dimensional sound from records (both 2 channel and specially cut 4 channel) and to provide a high level of performance for conventional 2 channel reproduction (See page 83 for description of the Lafayette/Pickering Phase 44).
Zero 100 Plus Lafayette/Pickering Phase 44. Shpg. wt., 15¼ lbs.
21 R 90726WXM No Money Down* Net 189.51



ZERO 100 PLUS
PHASE 44 CARTRIDGE
189⁵¹

Magnetic
Anti-Skating
Control

Illuminated
Stroboscope

15° Vertical
Tracking
Adjustment

Cartridge
Overhang
Adjustment


Slide Weight
for Setting
Stylus Force

Patented Synchro
Lab Motor

Exclusive Garrard
Two-Point Record
Support

Variable
Speed Control
±3¼ @ 33½ RPM
±2½ @ 45 RPM

Comparison of Tracking
Diagrams Zero 100 vs.
Standard Tone Arms



The brilliant ZERO 100 meets the demands placed on the automatic turntable for higher performance standards in today's sophisticated high fidelity market. Heart of the ZERO 100 "super changer" is a revolutionary new tone arm engineered to provide zero tracking error for preserving the record grooves and obtaining the finest sound reproduction. The arm is designed so that the cartridge housing is pivoted directly above the stylus tip, resulting in the stylus itself always being perpendicularly tangent to the groove. Other fine features are 15° vertical tracking adjustment, cartridge overhang adjustment, magnetic anti-skating control, interchangeable spindles, long spindle accommodates a stack of six records, short one for single play. Kinetically matched turntable. Separate control tabs for auto, manual, and cueing/pausing. 2 speeds, 33½, and 45 rpm. Satin aluminum finish with sparkling white unit plate. Size: 15¼" W x 14¼" D. Above motor board 4¾", below motor board 2¼". For 100-130 volts, 60 cycle AC. Imported from England. Shpg. wt., 15 lbs. 21 R 40994 WX No Money Down* Net 189.50

Garrard

Automatic Turntables and Manual Record Players

MODEL 40B 3 SPEED AUTOMATIC TURNTABLE

Plays 33 $\frac{1}{3}$, 45, and 78 rpm records. Full viscous damped, single lever cueing. Low mass, tubular aluminum tonearm with fixed isolated counter-weight. Slide-in cartridge clip assures positive cartridge alignment. Easy to adjust stylus pressure control and visible scale. Swingaway overarm moves to the rear, out of the way for manual play. Two interchangeable spindles. Oversize turntable with handsome safety mat. Size: 14 $\frac{3}{4}$ "x12 $\frac{1}{2}$ "L. Requires 4 $\frac{3}{4}$ " above and 3" below motor board. With all connecting cables. Less base. For 110-130-VAC, 60 Hz. Imported. Shpg. wt., 9 $\frac{1}{2}$ lbs.
21 R 40499W Model 40B only Net 44.50

Model 40B and Pickering PAT/E-1 Elliptical Cartridge. Shpg. wt., 9 $\frac{3}{4}$ lbs.
21 R 40556WM Net 44.51
Model 40B and Shure M44E Elliptical Cartridge. Shpg. wt., 9 $\frac{3}{4}$ lbs.
21 R 40564WM Net 44.51
Model 40B and Empire 90EE/X Elliptical Cartridge. Shpg. wt., 9 $\frac{1}{2}$ lbs.
21 R 40861WM Net 44.51
Model 40B and Pickering Phase IV/ACE Elliptical Cartridge. Shpg. wt., 9 $\frac{3}{4}$ lbs.
21 R 90585WM Net 49.50
Model 40B and Shure 55E Elliptical Cartridge. Shpg. wt., 9 $\frac{3}{4}$ lbs.
21 R 40598WM Net 49.50
Model 40B and Empire 909E/X Elliptical Cartridge. Shpg. wt., 9 $\frac{1}{2}$ lbs.
21 R 40879WM Net 49.50
Model 40B and Lafayette/Pickering Phase 44 Elliptical Cartridge. Shpg. wt., 9 $\frac{3}{4}$ lbs.
21 R 90593WM Net 59.50



44⁵⁰

Less
Cartridge
and Base

No Money
Down*

Save up to 29⁹⁵ from Individual Catalog Prices

on GARRARD 40B and Elliptical Stereo Cartridge
Combinations (See listing to left)

MODEL SP20B 4 SPEED MANUAL RECORD PLAYER With Choice of Stereo Elliptical Cartridge

37⁵⁰ Less
Cartridge
and Base

42⁵⁰
With
Pickering PAT/E-1
Elliptical Cartridge,
Less Base

52⁵⁰
with
Lafayette/Pickering
Phase 44 Elliptical
Cartridge, less base



A compact, efficient manual player with high fidelity features. Low-mass tubular aluminum arm with fixed counter-weight, isolated in a resilient housing to effectively damp out tonearm resonances. Fully adjustable stylus pressure control with optical scale. Slide-in cartridge clip accommodates all the latest cartridges and assures positive alignment. Automatic return of tonearm after record has played. Full-size turntable. Supersensitive trip. Size: 14 $\frac{3}{4}$ "x12 $\frac{1}{2}$ "x3 $\frac{1}{2}$ "H above and 2 $\frac{1}{2}$ " below motor board. Imported. Less base. For 110-130V 60 Hz AC. Shpg. wt., 9 lbs.
21 R 40507W SP20B only No Money Down* Net 37.50
SP20B plus Pickering PAT/E-1 Elliptical Cartridge. Shpg. wt., 9 $\frac{1}{4}$ lbs. 21 R 40853WM No Money Down* Net 42.50
SP20B Plus Lafayette/Pickering Phase 44 Elliptical Cartridge. Shpg. wt., 9 $\frac{1}{4}$ lbs. 21 R 90601WM No Money Down* Net 52.50

MODEL 30 4 SPEED AUTOMATIC TURNTABLE

39⁵⁰
With
Diamond Needle
Ceramic Cartridge,
Less Base



Garrard 4-speed automatic stereo turntable designed especially for use in low priced hi-fi systems, and perfect for replacement in consoles and phonographs. Features oversized, weighted turntable, one piece cast aluminum tone arm, ultra compact size. Plays 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45 and 78 RPM records. Intermix automatic operation when desired. Two spindles—short for manual, center drop for automatic play. With ceramic cartridge, diamond stylus. All connecting cables. Dim.: 14 $\frac{3}{4}$ "x12 $\frac{1}{2}$ " above motor board 4 $\frac{3}{4}$ ", below 2 $\frac{1}{4}$ ". For 110-130 VAC, 60 Hz. Less base. Imported. Shpg. wt., 9 $\frac{1}{4}$ lbs.
21 R 37325W No Money Down* Net 39.50
24 R 30239 Replacement Cartridge 3 oz. Net 6.90
24 R 03335 Replacement Diamond Needle 3 oz. Net 2.49

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 87

Garrard MODULE TURNTABLE ENSEMBLES



Module XII Garrard 4-Speed Automatic "Demi" Changer with Pre-Installed Stereo Ceramic Diamond Needle Cartridge, Base & Dust Cover

Miniature automatic record changer. Small enough to fit on a bedside table or a small shelf. Can play up to 8 records in automatic play . . . 4 Speeds: 16 1/2, 33 1/2, 45, 78 rpm. Tubular aluminum tonearm precisely balanced for correct tracking. Automatic shut-off after last record has played. With all hook-up leads. Size: 13 1/4" x 10" x 6 3/4" H. Imported. For 110-130 VAC 60 Hz. 21 R 40523W Shpg. wt., 8 1/4 lbs. Net 39.95

39⁹⁵

Complete
No Money
Down*

Module X10 Precision Automatic Turntable with Pre-Installed Stereo Ceramic Diamond Needle Cartridge, Base & Dust Cover.

Features ultra-low-mass tubular aluminum tonearm. Large oversize turntable. Single lever control for convenient cueing and pausing. Simplified speed/size controls. Plays 7", 10", 12" records at 33 1/2, 45 or 78 rpm. For 110-130 VAC, 60 Hz. Size (on base): 15" x 13 1/4" x 7 3/4" H. Imported. With all connecting cables. Shpg. wt., 15 lbs. 21 R 40846W Net 52.50

52⁵⁰

Complete
No Money
Down*

Module SLX-2 Synchronous 3-Speed Automatic Turntable with Pre-Installed Stereo Magnetic Diamond Needle Cartridge, Base & Dust Cover

Synchro-lab® motor for constant synchronous speed, dynamically balanced tone arm with ball bearing pivots, cueing and pause control, adjustable stylus pressure gauge built into tone arm—adjustable from 0 to 5 grams. Plays 33 1/2, 45, or 78 rpm records (12", 10", or 7"). For 110-130 VAC 60 Hz. Dim. (on base): 15" x 13 1/4" x 7 3/4" H. With all connecting cables. Imported. Shpg. wt., 16 lbs. 21 R 40432W Net 69.50

69⁵⁰

Complete
No Money
Down*


Module SLX-3 Synchronously Powered 3-Speed Automatic Turntable with Pre-Installed Magnetic Elliptical Cartridge, Base & Dust Cover

Synchro-Lab® motor guarantees perfectly constant record speed . . . unwavering musical pitch. Exclusive two-point record support at center and edge during automatic play. Stylus force adjustment with window scale. Ultra-low-mass tubular aluminum tonearm. Permanently accurate sliding weight anti-skating control. Fully damped, single control cueing. Viscous damped tonearm. Finger-tip controls. Oversize turntable. With all audio cables. Size (includes base and cover): 15 1/2" x 14 1/2" x 8" H. For 110-130 V AC. 60 Hz. Imported Shpg. wt., 18 lbs. 21 R 40515W Net 99.50

99⁵⁰

Complete
No Money
Down*

ACCESSORIES FOR GARRARD AUTOMATIC TURNTABLES



Stock No.	FIG.	MODEL NO.	DESCRIPTION	FOR	SHPG. WT.	NET EA.
21 R 40226W	A	B1	Ebony Pin-Seal Plastic Base	SL65B, SL55B, 40B, 30, SP20B	2 1/2 lbs.	5.50
21 R 40234W	A	B2	Ebony Pin-Seal Plastic Base	SL95B, SL75B, SL72B, Zero 100	2 1/2 lbs.	6.50
21 R 40242W	B	B1P	Power-Matic Base w/Auto. Shut-off	SL65B, SL55B, 40B, 30, SP20B	2 1/2 lbs.	14.95
21 R 40259W	B	B2P	Power-Matic Base w/Auto. Shut-off	SL95B, SL75B, SL72B, Zero 100	3 lbs.	15.95
21 R 40820W	C	WB1	Deluxe Walnut Wood Base	SL65B, SL55B, 40B, 30, SP20B	4 lbs.	19.95
21 R 40838W	C	WB2	Deluxe Walnut Wood Base	SL95B, SL75B, SL72B, Zero 100	4 lbs.	19.95
21 R 40267W	D	D1	Plastic Dust Cover†	SL65B, SL55B, 40B, 30, SP20B	3 1/2 lbs.	5.50
21 R 40275W	D	D2	Plastic Dust Cover‡	SL95B, SL75B, SL72B, Zero 100	3 3/4 lbs.	6.50
24 R 12096W	E		Wood Mounting Board—Unfinished	SL65B, SL55B, 40B, 30, SP20B	1 lb.	1.95
24 R 12161W	E		Wood Mounting Board—Unfinished	SL95B, SL75B, SL72B, Zero 100	1 lb.	1.95
21 R 40531	F	FLRS35	45 rpm Spindle	65B, 55B, 40B, 30, SLX-2, X10	3 oz.	1.95
21 R 37974	F	LRS25	45 rpm Spindle	SL95B, SL75B, SL72B, SLX-3	6 oz.	3.80
21 R 28007	F	LRS100	45 rpm Spindle	Zero 100	6 oz.	3.80
21 R 40549	F	F40	45 rpm Spindle	X11	3 oz.	1.95
21 R 37982	G	C1	Cartridge Clip Holder	SL75B	2 oz.	1.75
21 R 37966	G	C2	Cartridge Clip Holder	SL95B, SL72B, SL65B, SL55B, 40B, 30, SP20B	2 oz.	1.75
21 R 28015	G	C3	Cartridge Clip Holder	Zero 100	2 oz.	1.75

†Can be used with only B1 or B1P Bases

‡Can be used with only B2 or B2P Bases

*See Page 22 for Full Credit Details on Easy Pay Plan

Professional Automatic Stereo Turntables by

YOUR CHOICE OF ELLIPTICAL STEREO CARTRIDGE

For Only

1¢ more

With Purchase of
A Dual Turntable



Picking
Phase IV/ATE
39.95



Shure M93
39.95

For Only

5⁰⁰ more

With Purchase of
A Dual Turntable



Lafayette/Picking
Phase 44
44.95

united
audio **Dual**


SAVE UP TO 39⁹⁵

From Individual
Catalog Prices

Dual 1219 Professional Automatic Turntable With Choice of Stereo Elliptical Cartridge

Dual's finest automatic stereo turntable combines unrestricted flexibility of operation with complete professional quality. Three speeds: 33 $\frac{1}{3}$, 45, and 78 RPM. Fully automatic and manual operation. Two spindles: Multiple play—holds up to 6 records, and rotating single play. Mode selector lowers tone arm base to provide perfect 15° stylus tracking (zero degree vertical tracking error) when set for single play, and raises the tonearm base for multiple play. True four-point gyroscopic gimbal suspension for virtually friction-free tonearm movement. Separate antiskating for conical and elliptical styli. Adjustable stylus overhang. Full 12" diameter turntable with dynamically balanced 7 lb. platter. Synchronous/continuous pole motor combines high torque with absolute speed accuracy regardless of line voltage. Cue control system is damped to prevent bounce. Counterbalance is elastically damped and has 0.01 gm. click stops for precision balancing. Pitch control for "tuning" records over a 6% range. 110/220 VAC 60 Hz. Size: 14 $\frac{3}{4}$ "x12 $\frac{1}{4}$ "W, 6" above and 3" clearance below rotor board. Imported. Shpg. wt., 18 $\frac{1}{2}$ lbs.

21 R 65827W 1219 Less Cartridge	Net 175.00
21 R 90619WXM 1219 Plus Pick. Phase IV/ATE	Net 175.01
21 R 68011WXM 1219 Plus Shure M93	Net 175.01
21 R 90627WXM 1219 Plus Laf/Pick. Phase 44	Net 180.00



MODEL 1219

Less Cartridge

175⁰⁰

Less Base
No Money Down*

MODEL 1219

With Choice of
Picking
Phase IV/ATE
or Shure M93

175⁰¹

Less Base

MODEL 1219

With
Lafayette/Picking
Phase 44
Ellip. Cart.

180⁰⁰

Less Base

NEW DUAL 1218 Automatic Turntable with Choice of Stereo Elliptical Cartridge

Deluxe 3-speed automatic stereo turntable with Synchronous/hit-torque motor. Major features include: Twin-ring tone-arm gimbal suspension; one piece non-ferrous cast turntable platter; pitch control (6% variation); cue-control; conical/elliptical anti-skating control; damped click-stop counterbalance; and Mode Selector—provides 15° vertical tracking in single-play mode and at center of stack in Multiple-play mode, simple, fool-proof setting made within cartridge holder. Multiple-play spindle holds up to 6 records. Other features include: Adjustable stylus overhang, direct-dial stylus force, 3 speeds: 33 $\frac{1}{3}$, 45 and 78 RPM. Dimensions 13" x 10 $\frac{3}{4}$ " — 6" above and 3" clearance below mounting board. Imported. For 110/120 VAC, 60 Hz. Shpg. wt., 15 lbs.

21 R 68128WX No Money Down*	Net 139.50
21 R 90635WXM 1218 Plus Pick. Phase IV/ATE	Net 139.51
21 R 90643WXM 1218 Plus Shure M93	Net 139.51
21 R 90650WXM 1218 Plus Laf/Pick. Phase 44	Net 144.50



MODEL 1218

Less Cartridge

139⁵⁰

Less Base
No Money Down*

MODEL 1218

With Choice of
Picking
Phase IV/ATE
or Shure M93

139⁵¹

Less Base

MODEL 1218

With
Lafayette/Picking
Phase 44
Ellip. Cart.

144⁵⁰

Less Base

Dual 1215 Automatic Turntable

With Choice of Stereo Elliptical Cartridge

Quality 3-speed stereo turntable with new improved, low mass counterbalanced tonearm. Tracks flawlessly as low as 1 gm. Features direct dial tracking force, synchronized anti-skating, pitch control for all three speeds: 33 $\frac{1}{3}$, 45, and 78 RPM, silicone damped cue control, and adjustable stylus overhang. Multiple play spindle holds up to 6 records. Size: 12 $\frac{3}{4}$ " x 10 $\frac{1}{2}$ " — 6" above and 3" clearance below mounting board. 110/120 VAC, 60 Hz. Shpg. wt., 12 lbs.

21 R 68003W 1215 Less Cartridge Net 99.50


21 R 90668WX 1215 Plus Pick. Phase IV/ATE Net 99.51

21 R 68086WM 1215 Plus Shure M93E Net 99.51

21 R 90676WM 1215 Plus Laf/Pick. Phase 44 Net 104.50

ACCESSORIES FOR DUAL TURNTABLES

Stock No.	Mfg. No.	Description	For	Shpg. Wt.	Net
21 R 65835W	WB12	Walnut Base	1215, 1218	4 lbs.	10.95
21 R 66007W	WB19	Walnut Base	1219	4 lbs.	14.95
21 R 65843W	DC2	Dust Cover	WB12 Base	2 lbs.	10.95
21 R 66015W	DC9	Dust Cover	WB19 Base	2 lbs.	12.95
21 R 65868	CH12	Cart. Holder	1215, 1219	3 oz.	3.95
21 R 68110	CH22	15° Cart. Holder	1218	9 oz.	8.95
21 R 65850	AS12	45 Spindle	1215, 1218, 1219	4 oz.	5.95



MODEL 1215

Less Cartridge

99⁵⁰

Less Base
No Money Down*

MODEL 1215

With Choice of
Picking
Phase IV/ATE
or Shure M93

99⁵¹

Less Base

MODEL 1215

With
Lafayette/Picking
Phase 44
Ellip. Cart.

104⁵⁰

Less Base

*See Page 22 for Full Credit Details on Easy Pay Plan

AR and Miracord Stereo Turntables




Model XA Two-Speed Manual Stereo Turntable

Save 29⁹⁵

From Individual Catalog Prices
When you purchase an AR
Turntable with the Deluxe
Lafayette/Pickering Phase
44 Elliptical
Stereo Cartridge

(See Page 83 for Description of the Phase 44)



Outstanding turntable featuring a rugged 3.3 lb. balanced aluminum platter belt driven from synchronous motors operating at 33½ and 45 RPM. Turntable and arm are shock-mounted from the top plate eliminating vibration. Meets NAB specifications for broadcast equipment on wow, flutter and speed accuracy. Includes cables, overhang adjustment device and needle force gauge. Size with cover—12¾x16¾x5¼". Shpg. wt., 18 lbs.

21 R 72013W XA less cartridge. No Money Down* Net 87.00

XA Turntable and Lafayette/Pickering Phase 44 Net 102.00
21 R 90700WM Shpg. wt., 18½ lbs.

Model XA/UNIVERSAL TURNTABLE—Same deluxe features as above but can be used anywhere
In the world. For 110 or 220 volts, 50 or 60 Hz operation. Shpg. wt., 17½ lbs.

21 R 72617W XA/U less cartridge Net 87.00

XA/U Turntable and Lafayette/Pickering Phase 44 Net 102.00
21 R 90718WM Shpg. wt., 18½ lbs.

Extra cartridge shell for AR turntables. Wt., 3 oz.
21 R 72575 Net 2.00

Turntable Comes Complete
With Tone Arm, Walnut Wood
Base And Plastic Dust Cover

87⁰⁰
Less Cartridge

102⁰⁰ with Lafayette/Pickering Phase 44 Elliptical Cartridge

Benjamin Miracord 50H 4-speed Automatic Stereo Turntable



175⁰⁰
Less Cartridge
Less Base

180⁰⁰ with Lafayette/Pickering Phase 44 Elliptical Cartridge, less base

44⁹⁵ Lafayette/Pickering Phase 44 Elliptical Cartridge

SAVE 39.95

when you buy a Lafayette/Pickering Phase 44 Elliptical Cartridge with the 50H.

Superb, 4-speed automatic turntable: 16½, 33½, 45, and 78 RPM—Pushbutton controls: stop/reject, 7", 10", 12". Papst hysteresis motor. Dynamically balanced tone arm with vernier counterweight permits tracking to below 1 gram. Precise Cueing device. Built-in anti-skating compensation. Stylus overhang adjustment. Heavy 12" dynamically balanced turntable. Size 14½x12½"D; requires 5½" above plate/3¾" below. 110V 60 cycle AC. Imported. Less base. Shpg. wt., 18 lbs.

21 R 16358WX 50H Less Cartridge Net 175.00

Model 50H plus Lafayette/Pickering Phase 44 Net 180.00

21 R 90692WXM Shpg. wt., 24½ lbs.

Accessories for 50H

21 R 16580W WB700 Walnut wood base. Wt. 5 lbs. 15.00

21 R 16598W DCP-7 Dust cover. Wt., 2 lbs. 12.95

Benjamin/Miracord 770H 4-Speed Automatic Stereo Turntable



225⁰⁰
Less Cartridge
and Base

225⁰¹ with Lafayette/Pickering Phase 44 Elliptical Cartridge, Less Base

44⁹⁵ Lafayette/Pickering Phase 44 Elliptical Cartridge

SAVE 44.95

When You Buy a Lafayette/Pickering Phase 44 Elliptical Cartridge with the 770H.

Miracord finest stereo Automatic Turntable. Pushbutton operation. Exclusive features: Built-in illuminated strobe, Digital stroboscopic read out of 33½ and 45 RPM speeds, Ionic elapsed-time stylus wear timer. Variable speed—plus or minus 3%. Papst hysteresis motor, precision cueing, anti-skating, dynamically balanced tone arm. Gold anodized trim. For 78, 45, 33, and 16 RPM records. Size: 14½x12½"D, requires 5½" above, 3¾" below. 110V 60 cycles AC. Imported. Less base. Shpg. wt., 18 lbs.

21 R 16531WX Net 225.00

Model 770H plus Lafayette/Pickering Phase 44 Net 225.01

21 R 90684WXM Shpg. wt., 24½ lbs.

Accessories for 770H

21 R 16580W WB700 Walnut wood base. Wt. 5 lbs. 15.00

21 R 16598W DCP-7 Dust cover. Wt., 2 lbs. 12.95

Quality LAFAYETTE Record Changers at Popular Prices

Deluxe LAFAYETTE AC50B 4-Speed Automatic Pushbutton Stereo Record Changer

- 4-Speeds: 16, 33 $\frac{1}{3}$, 45, 78 RPM
- Pushbutton Operation for Automatic Play, Manual Play, Stop
- Automatic Shut-Off After Last Record

A superb, 4-speed automatic record changer with professional single lever cueing. Handsomely styled and engineered to provide the highest standard of performance and dependability. Ideal for playing both stereo and monaural 12", 10", and 7" records. Can play up to 7 records automatically. Intermixes records of the same speed. Shuts off after last record has been played. Features oversized turntable with ribbed record mat; one-piece low mass cast aluminum tone arm; 4-position speed selector side switch; two spindles: one for manual play and a center drop for automatic play. All controls are always perfectly accessible even with 12" records on the turntable. Heavy duty, constant speed motor. Ceramic stereo turn over cartridge with diamond LP needle. Mainplate has beautiful leather-like finish with black rubber turntable mat and chrome trim. For 117 VAC, 60 Hz. Size: 13 $\frac{1}{4}$ "x11"D. Requires 3 $\frac{1}{2}$ " above and 3" below motor board. Imported. Shpg. wt., 7 lbs.

21 R 01699W Net 29.95

ACCESSORIES FOR MODEL AC50B

Walnut Wood Base. Shpg. wt., 2 $\frac{1}{4}$ lbs.

21 R 01657W Net 4.95

Plastic Dust Cover. Shpg. wt., 1 $\frac{1}{2}$ lbs.

24 R 09043W Net 4.50

45 RPM Spindle. Shpg. wt., 4 oz.

21 R 01673 Net 1.95

Replacement Stereo Cart. Wt., 3 oz.

21 R 01665 Net 4.95



- Professional, Single Lever Cueing
- Low Mass, Aluminum Tone Arm
- Heavy-Duty, Constant Speed Motor
- 2 Spindles: Manual, Center Drop for Automatic Play
- Main Plate has Beautiful Leather-Like Finish
- Chrome Plated Plug-in Head

NEW LAFAYETTE "Mini" 4-Speed Automatic Stereo Record Changer Ensemble



Model MC-22B

34.95

Pre-Mounted on a Simulated Black Leather Base with Walnut Vinyl Trim, Heavy Gauge Tinted Plastic Dust Cover, and Diamond Needle Cartridge.

Model MC22B Features:

- Perfect Companion For Shelf Component Systems
- Automatic or Manual Play at 16, 33 $\frac{1}{3}$, 45, 78 RPM
- Intermixes 10" and 12" Records Of The Same Speed
- Automatic Shut-off After Last Record



Diamond Needle

A versatile, dependable 4-speed automatic stereo record changer premounted on a simulated Black Leather base with walnut vinyl trim—completely ready to plug into your audio equipment. Especially suited for bookshelf width component systems and compact equipment installations. Features low-mass tone arm, high quality ceramic turnover stereo cartridge with diamond LP needle, detachable spindle, vibration-free dynamically balanced 2-pole motor. Handles stack of 6-records automatically or can be operated as a manual player. Also includes tinted plastic dust cover, UL listed AC cord, and all audio cables. Size includes Base, 14 $\frac{3}{8}$ x 5 x 10". Shpg. wt., 10 lbs. For 110-130 volts AC, 60 Hz. Made in England.

21 R 01772W No Money Down* Net 34.95

ACCESSORIES FOR MODEL MC-22B

Replacement Diamond LP Needle. Wt., 3 oz.

24 R 02386 Net 2.79


45 RPM Spindle. Wt. 3 oz.

24 R 02568 Net 1.49

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Audio Cables and Adapters

High quality extension cables "tailor made" for users of recorders, hi-fi equipment, etc. All plugs molded directly to various cable combinations. Shielded cable for low impedance (micro, etc.) connections; parallel wire for high impedance (speaker, etc.) connections. Imported. Avg. shpg. wt., 5 oz.



PIN TYPE PHONO PLUG (B) TO VARIOUS CONNECTIONS. All Cables shielded. Imported. Avg. Shpg. wt., 5 oz.

Stock No.	One Termination	Cable Length	Other Termination	Net
99 R 00648	pin plug (B)	36 in.	pin plug (B)	.75
99 R 00580	pin plug (B)	60 in.	pin plug (B)	.79
99 R 00598	pin plug (B)	72 in.	Straight phone plug (G)	1.10
99 R 00655	pin plug (B)	48 in.	Phono Jack (D)	.98
99 R 00614	pin plug (B)	60 in.	Phono Jack (D)	1.09
99 R 00846	pin plug (B)	36 in.	Stripped & tinned ends (I)	.55
99 R 00853	pin plug (B)	48 in.	Stripped & tinned ends (I)	.65
99 R 00861	pin plug (B)	60 in.	Stripped & tinned ends (I)	.70
99 R 00879	pin plug (B)	72 in.	Stripped & tinned ends (I)	.75
99 R 00887	pin plug (B)	144 in.	Stripped & tinned ends (I)	1.10
99 R 01125	pin plug (B)	120 in.	90° pin plug (E)	1.10

90° PHONE PLUG (A) TO VARIOUS CONNECTIONS. Std. 1/4" sleeve; completely shielded. All cables shielded. Imported.

99 R 00671	90° phone plug (A)	72 in.	Pin plug (B)	1.10
99 R 00721	90° phone plug (A)	72 in.	90° pin plug (E)	1.21

90° PIN PLUG (E) TO VARIOUS CONNECTIONS. All cables shielded Imported.

99 R 01026	90° pin plug (E)	18 in.	90° pin plug (E)	.79
99 R 01067	90° pin plug (E)	120 in.	90° pin plug (E)	1.10
99 R 01109	90° pin plug (E)	120 in.	Phono Jack (D)	1.23

PHONE PLUG (G) TO VARIOUS CONNECTIONS. Std. 1/4" diam. sleeve; completely shielded. All cables shielded. Imported.


99 R 00630	Phone plug (G)	72 in.	Phone Jack (D)	1.23
99 R 00754	Phone plug (G)	72 in.	Mike connector (F)	1.99

MINIATURE PHONE PLUG (L) TO VARIOUS TERMINATIONS

Shielded audio cables with molded miniature phone plug (1/4" diameter finger). For use with Sony, Concord, and most Japanese tape recorders and radios. Cables are 69" long. Imported. Shpg. wt., 6 oz.

99 R 10365	mini phone plug (L)	69 in.	stripped & tinned ends (I)	.69
99 R 10373	mini phone plug (L)	69 in.	alligator clips (I)	1.09
99 R 10381	mini phone plug (L)	69 in.	pin plug (B)	.89
99 R 10399	mini phone plug (L)	69 in.	phono jack (D)	1.09
99 R 10407	mini phone plug (L)	69 in.	phone plug (G)	.96
99 R 10415	mini phone plug (L)	69 in.	phone jack (C)	1.09
99 R 10423	mini phone plug (L)	69 in.	mini phone plug (L)	.99
99 R 10431	mini phone plug (L)	69 in.	mini phone jack (M)	.99

36" AUDIO COILED CABLES



Set of Four Coiled Cables **1.79**

A set of 4 color coded shielded cables terminated at each end with phono plugs. 36" extended, retract to only 14". Plugs molded directly to cable. One each red, grey, yellow and green colored cable and phono plugs for easy installation and instant identification. Imported. Shpg. wt., 6 oz.

99 R 01372		Net 1.79
------------	--	----------


92 Lafayette Cat. No. 720

AUDIO ADAPTERS



- (P) Phono plug coupler, accepts phono plug at each end. Net .49
- 32 R 52012 Shpg. wt., 3 oz.
- (S) 2-conductor phone jack input to phono plug output. Net .79
- 99 R 62309 Shpg. wt., 3 oz.
- (T) Phono jack input to standard 2-conductor phone plug output. Net .69
- 99 R 62168 Shpg. wt., 3 oz.
- (U) Phono jack input to a mini-plug (1/4" dia. finger) output. Net .83
- 99 R 63448 Shpg. wt., 3 oz.
- (V) 2-conductor mini-jack (1/4" dia. sleeve) input to phono plug output. Net .77
- 99 R 63455 Shpg. wt., 3 oz.
- (W) 2-conductor mini-jack (1/4" dia. sleeve) input to standard 2-conductor phone plug output. Net .83
- 99 R 63463 Shpg. wt., 3 oz.
- (X) 2-conductor subminiature jack (3/16" dia. sleeve) input to mini-plug (1/4" dia. finger) output. Net .79
- 99 R 63471 Shpg. wt., 3 oz.
- (Y) 2-conductor standard phone jack input to 2-conductor subminiature plug (3/16" dia. finger) output. Net .79
- 99 R 63488 Shpg. wt., 3 oz.

D.I.N. ADAPTER CABLES FOR EUROPEAN RECORDERS



Adapts European 3 contact (180°) and 5 contact (180°) DIN connectors to mate with standard domestic RCA type phono jacks and plugs. For use with Ampex, Norelco, Grundig, Korting, Uher SONY, and other cassette or tape recorders, radios, phonos, amplifiers etc. All phono plugs and jacks are color coded, 69" shielded cables. Imported. Shpg. wt., 6 oz.

- (N) 5-pin adapter connects to 4 RCA-type color coded phono plugs. Net 1.99
- 99 R 63539
- (O) 5-pin adapter connects to 4 RCA-type color coded phono jacks. Net 2.49
- 99 R 63547
- (P) 5-pin adapter connects to 2 RCA-type color coded phono plugs. Net 2.49
- 99 R 63554
- (Q) 3-pin adapter connects to 2 RCA-type color coded phono plugs. Net 2.10
- 99 R 63562
- (R) 3-pin adapter connects to 2 RCA-type color coded phono jacks. Net 1.95
- 99 R 63570

UNIVERSAL CABLE KIT



249

Kit contains: 2 phono plugs with 69" connecting cable; phono plug connected to 2 alligator clips by 4" cable, coupler with phono jack and phono jack; phono plug output with phono jack input. All connecting cables are shielded and insulated. Ideal for connecting tape recorder to phonograph, radio or TV, or tuner to amplifier. Imported. 99 R 01356 Shpg. wt., 6 oz. Net 2.49

4-WAY ADAPTER PLUG

4 Most Popular Plugs **99c**

A versatile 4-in-1 adapter plug for most popular transistor radios and cassette type recorders. Has four different terminations in parallel compactly molded in a single housing; a 3.0mm miniature plug; 2.5mm subminiature plug; 3.5mm power jack and 2.5mm coaxial power plug. Imported.

99 R 61046	Shpg. wt., 4 oz.	Net .99
------------	------------------	---------

STEREO AUDIO CABLES



Two shielded insulated cables, (of different color tones, for easy identification of channels) inside a common chrome grey plastic jacket, providing two completely isolated channels. Avg. shpg. wt., 8 oz. Imported.

Type	Length	Net
99 R 01133	36"	Phono pin 1.49
99 R 01141	6'	plugs at 1.69
99 R 01158	10'	all ends. 2.19

Depend on Lafayette For Complete Stocks, Lowest Prices, Fastest Service

Phono And Hi-Fi Installation Accessories

STEREO VU BALANCE METER

12⁹⁵



- Two Meters in One
- Balances Stereo Systems

Ends the problem of balancing your stereo system. Two precisely damped loudness meters provide a continuous comparison of speaker levels. Scales calibrated in "Volume Units" and percent. 1.2 volts input sensitivity for 0 VU or 100 percent indication. The special calibrating switch and 20 db attenuation controls permit exact matching of channels. Greater than 8,000 ohm impedance permits connecting to output circuits without loading. The entire unit is housed in an attractive plastic case 6"wx3 3/4"hx2 1/2". Imported. 99 R 50387 Shpg. wt., 1 1/4 lbs. Net 12.95

LONG LIFE HI-FI BLOWER

- Motor Shunt Varies Both Volume of Air Moved and Noise level

A venturl fan for use with hi-fi, TV, Ham radio and other electronic installations, to ventilate equipment and give maximum life and best performance. With shunt delivers 50CFM at low noise level, shunt removal delivers 75 CFM with slight increase in noise level. Front and back grilles. Permanently lubricated. Rated 115VAC, 60 Hz. Size: 5 1/2x6x2 3/8". Complete with grill bracket, mounting hardware and instruction sheet. 24 R 39016 Shpg. wt., 2 1/2 lbs. Net 10.50

10⁵⁰



HI-FI BOXER FAN




- Ideal For Cooling TV And Hi-Fi Equipment
- Super Silent, Compact
- Sturdy Metal Construction

14⁸⁵

Exceptionally low-noise fan for cooling hi-fi equipment. Slow rotating 5-blade impeller delivers 50 cfm, enough air to exhaust the average enclosure 10 to 30 times per minute, to minimize thermal drift and increase equipment life. Airflow is reversible. Has heavy non-warp all metal frame and motor mounting acts as an efficient heat sink, adding life to motor and bearing. Pre-lubricated for years of maintenance-free operation. Only 4 1/4" square by 1 1/2" deep, fits any cabinet. Easy to install. Comes with complete mounting kit including special heavy duty brackets for mounting versatility, hardware, grommets, shock-absorbing spring mounting pad, A.C. power cord and clip on plug, template and instruction sheet. Rated 115 VAC, 60 HZ. 24 R 43018 Shpg. wt., 2 1/4 lbs. Net 14.85

BALL BEARING HEAVY DUTY SLIDES

Drawer slides made of 16 gauge steel. Supports 50 lbs. Ball bearing, double-extension type, drawer slides. Length 15", travel length 11", extended 22". Shpg. wt., 2 lbs. 20 R 52017



SHORT TYPE. Same construction as above but 13" long; travels 9"; extends to 18". Shpg. wt., 2 lbs. 20 R 52025

per pair Net 2.19

per pair Net 1.99

LEVEL AND LEVELING SCREWS

3¹⁰




- Permits Accurate Turntable Leveling

For stereo and mono Hi-Fi systems. Prevents unnecessary needle and record groove wear. Precision, circular bubble type level indicator for accurate turntable leveling. Circular 4-way spirit level mounts to top deck of turntable. Four adjustable leveling screws and T nuts. Provides quick, easy adjustment. 24 R 80341 Shpg. wt., 4 oz. Net 3.10

FIBERGLASS INSULATION

- 1 Inch Thick
- As Low As 1⁷⁵



Excellent sound absorbing material. For lining interiors of speaker cabinets, consoles, phonos, TV's, etc. Damps medium and high frequency reverberation and distortion. Suitable for many other installation purposes. 9 sq. ft. 1" thick with glue and applicator. 20 R 15014 Shpg. wt., 1 1/2 lbs. Net 1.75
DELUXE BASS REFLEX KIT: Same as above but contains 20 square ft. 16" x 16" x 1" thickness fiberglass. Shpg. wt., 2 1/2 lbs. 20 R 15022 Net 3.25


LAFAYETTE HI-FI TEST RECORD

- For Both Stereo And Monaural



This two sided 12" LP record uses easy to make tests to check the performance of stereo and monaural high fidelity equipment. Simple narrative and complete instructions enable you to check frequency response, level balance, channel identification and separation, hum, rumble, and other characteristics of your hi-fi system. 24 R 45070 Shpg. wt., 1 lb. Net 2.95

Decorative Grille Cloth



Choice selection of latest patterns and beautiful decorator colors. Made of finest quality vinyl plastic, woven with proper mesh for

passage of high frequencies as well as low. Shpg. wt., (36" x 36") 1 1/4 lbs. (18" x 24") 8 oz.

Description	For Use With	36 x 36		18 x 24		
		Fig.	Stock No.	Net	Stock No.	Net
Natural linen with random fleck	Walnut, Mahog., Ebony, Blonde	A	20 R 12532	3.50	20 R 12540	1.95
Dark linen and gold flecks	Walnut, Blonde	A	20 R 12557	3.50	20 R 12565	1.95
Random silver metallic	Ebony, light colors	A	20 R 12417	3.50	20 R 12425	1.95
Mahogany waffle weave with ivory threads	Mahogany, Blonde	B	20 R 12029	3.95	20 R 12037	2.10
Solid black waffle with interwoven black luster	Walnut, Ebony, Blonde	B	20 R 12573	3.95	20 R 12581	2.10
Beige waffle weave with walnut threads	Walnut, Fruitwood, Mahog.	D	20 R 12391	3.95	20 R 12409	2.10
Fine gold mesh	Walnut, Ebony, Blonde	D	20 R 12128	3.95	20 R 12201	2.10
raised Walnut gimp on gold ground	Walnut, Ebony, Blonde	F	20 R 12599	3.95	20 R 12607	2.10
Silver metallic waffle with blue and black threads	Ebony, light colors	C	20 R 12615	4.75	20 R 12623	2.50
Black ground with Metallic gold scroll	Walnut, Ebony, Blonde	E	20 R 12136	4.75	20 R 12218	2.50
Blended walnut diamond with random rust threads	Walnut, Ebony, Fruitwood	F	20 R 12433	4.75	20 R 12441	2.50
DELUXE CANE GRILLE CLOTH						
Interwoven natural cane	Walnut, Mahogany, Ebony	C	20 R 12169	3.95	20 R 12243	2.10
Raise hexagon walnut cane on black ground	Walnut, Fruitwood, Ebony	F	20 R 12631	3.95	20 R 12649	2.10
Interwoven walnut box on black and rust ground	Walnut, Mahogany, Fruitwood	G	20 R 12490	4.75	20 R 12508	2.50
Woven wood effect on black ground	Walnut, Ebony, Blonde	G	20 R 12656	4.75	20 R 12664	2.50

Specialty Phonographs

LAFAYETTE 4-SPEED SOLID-STATE PHONOGRAPH With Built-in Color Lights

29⁹⁵

- Beautiful Color Lights Are Activated When Record is Playing
- 3x5" Front Mount Speaker

Become the center of attraction, the hit of the party with your psychedelic phonograph. Beautiful array of color lights are activated when a record is playing. Large, 3x5" front mounted speaker provides fine tonal quality. Plays all size monaural and stereo records at 16 $\frac{1}{2}$, 33 $\frac{1}{3}$, 45 and 78 RPM. A single lever selects any speed. 2 controls: On-Off/Volume (light intensity) and tone. Built-in 45 RPM adapter disc. Dual turnover cartridge with 2 synthetic sapphire needles. Case colors: bottom section—psychedelic blue, white, and orange; top section—blue; white portable carrying strap. Size: 12 $\frac{1}{2}$ Wx7 $\frac{1}{2}$ Hx11"D. Shpg. wt., 6 $\frac{3}{4}$ lbs.

24 R 02915W

Net 29.95



Made in U.S.A.

LAFAYETTE 4-SPEED MANUAL PHONO

- Instant-On Solid State Circuitry
- 4-Speeds: 16 $\frac{1}{2}$, 33 $\frac{1}{3}$, 45, 78 RPM
- Built-In 45 RPM Record Adapter

ONLY **14⁹⁵**



Made in U.S.A.

Ideal phono for the youngster in your family. Plays up to 12" monaural and stereo records at 16 $\frac{1}{2}$, 33 $\frac{1}{3}$, 45 or 78 RPM. A single lever selects any speed. "Feather-light" retractable tone arm is equipped with a single crystal cartridge. Volume control with on-off switch. Built-in 45 RPM record adapter. Fine quality 4" speaker. Attractive blue and white leatherette covered case. For 110-120 Volts, 60 Hz. Size: 12Wx9 $\frac{1}{2}$ Dx5 $\frac{1}{2}$ H. Shpg. wt., 5 $\frac{3}{4}$ lbs.

24 R 02725W

Net 14.95

NEW Panasonic SG-675 4-Speed Stereo Phono with AM/FM Radio

- 4 Speeds
16 $\frac{1}{2}$, 33 $\frac{1}{3}$,
45, & 78 RPM

99⁹⁵



Instant-On
Solid-State
Circuitry

Operates on batteries or household 117VAC to insure complete portability. Features 4-speed turntable with custom ceramic cartridge and automatic shut-off. Twin 4" speakers deliver full-range sound. Tone control and dual volume controls. Sensitive FM/AM Radio. Built-in Antennas. Size: 17 $\frac{3}{4}$ x 6 x 12 $\frac{1}{2}$ ". Imported.

24 R 41251W Shpg. wt., 15 lbs. No Money Down* Net 99.95
99 R 62564 Extra "D" Batteries (6 req.) Net ea. .18

NEW Panasonic AC/Battery Portable Phonographs

SG-336

Phono
Only

19⁹⁵

With Batteries

SG-356

Phono
with AM
Radio
with Batteries

29⁹⁵

SG-376

Phono
with AM
FM Radio
with Batteries

39⁹⁵

No
Money
Down*

Convenient and dependable solid-state Panasonic phonographs operate on batteries or 117 VAC to insure complete portability. Plays 33 $\frac{1}{3}$ and 45 RPM records. Includes ceramic cartridge with synthetic sapphire stylus. 3" dynamic speaker for fine tonal quality. Earphone or external speaker jack. Operates on 4 "D" batteries (included) or 117 VAC. Convenient carrying handle. Radio models SG-356 and SG-376 come with built-in antennas. Imported. Size: (all) 3 $\frac{1}{2}$ Hx10 $\frac{1}{2}$ Wx9 $\frac{1}{2}$ "D.

Stock No.	Model No.	Shpg. Wt.	Net Ea.
24 R 41228W	SG-335 Phono	3 $\frac{1}{2}$ lbs.	19.95
24 R 41236W	SG-356 Phono w/built-in AM Radio	4 lbs.	29.95
24 R 41244W	SG-376 Phono w/built-in AM/FM Radio	4 $\frac{1}{2}$ lbs.	39.95

Extra "D" batteries for above phonographs—4 required.

99 R 62564

Net ea. .18



Model SG-376

NEW 99⁹⁵

Made in USA



Diamond Needle




OUR BEST PORTABLE PHONOGRAPHS

DELUXE MODEL TPS35 4-Speed Solid-State Stereo Phonograph with Detachable Speaker Enclosures

- Garrard 4-Speed Automatic Changer
- Solid-State Stereo Amplifier with 8 Transistors, 2 Diodes, and 2 Silicone Rectifiers
- 4 Speakers: Two 8" Heavy-Duty Woofers Two 3 1/4" Tweeters Provide Magnificent Tone
- Stereo Headphone Jack plus 4 Controls: Loudness, Balance, Bass, Treble

Each detachable speaker enclosure with 6 ft. extension cord, contains a heavy-duty 8" woofer and a 3 1/2" tweeter for magnificent hi-fi sound reproduction. Powerful 10-watt solid-state stereo amplifier features a stereo headphone jack for private listening plus 4 controls: Loudness, Balance, Bass, Treble. Quality Garrard 4-speed automatic record changer plays all record sizes and speeds—7", 10" and 12" records at 16 2/3, 33 1/3, 45, and 78 RPM. Intermixes all size records of the same speed. Changer automatically shuts off after last record has been played and is equipped with a stereo turnover cartridge with diamond needle. Decorator designed wood cabinet is covered with simulated walnut and black washable vinyl material. Size: 21 1/4 x 12 1/2 x 14 1/4". For 110-120 VAC 60 Hz. Shpg. wt., 33 1/2 lbs. 24 R 03434WX No Money Down* Net 99.95

24 R 02543 Replacement Diamond Needle for TPS35 Net 2.79
24 R 02170 45 RPM Spindle for TPS35 Net 3.80



Made in USA

MODEL TPS30 4 Speed Solid-State Stereo Phonograph

- Garrard 4-Speed Automatic Record Changer
- Each Detachable Speaker Contains a Wide-Range High Compliance 4" Air Suspension Speaker
- Front Panel Stereo Headphone Jack
- Solid-State Stereo Amplifier with 6 Silicon Transistors and 3 Diodes

NEW 64⁹⁵



Diamond Needle

Convenient size lets you take this phonograph anywhere you like. Two detachable acoustically matched 4" speakers can be separated up to 12 ft. for magnificent full dimensional sound. Garrard changer plays all size records at 16 2/3, 33 1/3, 45 and 78 RPM. Intermixes 12" and 10" records of the same size. Instant-on solid-state stereo amplifier has 3 controls, volume left, volume right, and tone. Phono turns off after last record has been played. Equipped with stereo turnover cartridge with diamond LP needle. Size 23W x 7 1/2 D x 13 1/2 H. For 117VAC 60 Hz. Shpg. wt., 24 lbs. 24 R 03442 No Money Down* Net 64.95

24 R 02543 Replacement Diamond Needle for TPS30 Net 2.79
24 R 02170 45 RPM Spindle for TPS30 Net 3.80

Deluxe 4-Speed Manual Phonograph

- Speaker Front-Mounted for Full-Tone Sound Dispersion
- Front Mounted Controls for Convenience
- Built-in 45 RPM Adapter Disc
- Instantaneous ON Solid-State Circuitry

Plays stereo and monaural records of all speeds... 16 2/3, 33 1/3, 45, and 78 RPM... all sizes 12", 10", 7", 4" wide range speaker is set in front grill for full-tone sound dispersion. 2 front mounted controls —on/off volume and tone. Tone arm has usual turnover cartridge. Attractive blue washable pyroxin coated fabric with silver metal grill cloth. Size: 13 1/2 W x 6 1/2 H x 10 1/2 D. For 110-120 VAC, 60 Hz. Built-in 45 RPM record adapter. 24 R 02899W Shpg. wt., 7 1/4 lbs. Net 19.95



ONLY
19⁹⁵

Made in USA

*See Page 22 for Full Credit Details on Easy Pay Plan

KLH, Mastertone, and Lafayette Music Systems



**NEW
LOW PRICE
279⁹⁵**
No Money Down*

KLH Model 24 Solid State FM Stereo Music System

35 Watt (IHF) system provides superb FM stereo listening plus quality phono sound reproduction. Control center has a sensitive FM stereo tuner with vernier tuning, zero tuning meter and stereo indicator. Garrard 4-speed automatic turntable uses a Pickering V15 cartridge with diamond stylus. Speakers have 8" acoustic suspension woofers and 2" wide dispersion tweeters. Other features include tape and headphone outputs, auxiliary inputs, and deluxe oiled walnut cabinetry. Dim: Control Center, 18W x 4H x 14"D.; Speakers, 18W x 10 1/4"H x 7 1/2"D.
24 R 44099WX Shpg. wt. 75 1/2 lbs. Net 279.95
Model 24 with AM: Same components as above but with high performance AM circuitry. For 110-120V, 60 Hz AC. Shpg. wt. 58 1/2 lbs.
24 R 44180WX Net 309.95




**NEW
LOW PRICE
349⁹⁵**
No Money Down*

KLH Model 20 Solid State FM Stereo Music Center

Stylish 50 watt (IHF) music system integrates a FM stereo tuner, preamp, and power amplifier into one convenient control center. Includes Garrard 4-speed automatic turntable and two walnut finished speaker systems with 10" acoustic suspension woofers and 1 3/4" tweeters. Incorporates tape and headphone outputs, auxiliary inputs, zero tuning meter, and FM stereo indicator. Dim: Control Center, 18 1/4"W x 8 3/4"H x 14"D.; Speakers, 11 3/4"W x 23 3/4" x 9"D. For 110-120V, 60 Hz AC.
24 R 44032WX Shpg. wt., 85 lbs. Net 349.95
KLH Model 20 With AM: Same components as above but with high performance AM circuitry. Shpg. wt., 87 1/2 lbs.
24 R 44172WX Net 379.95

Dust Covers For Model 20 and 24
24 R 44115W Lift Type. Wt., 8 1/2 lbs. Net 29.95
24 R 44123W Hinge Type. Wt., 3 3/4 lbs. Net 9.95

NEW Mastertone SV-17W Solid-State 3-Piece AM/FM Stereo Console




- Striking New Design
- Adapts its Size to Fit Space Available—Detachable Speakers Have 10 ft. Cables

199⁹⁵
with DETACHABLE
STAND
No Money Down*

Ultra-modern AM/FM Stereo Phono System—it's a console stereo—it's a bookshelf stereo—or it's a 3-piece modular console. Both the speakers and stand are detachable. Can even be used as a room divider. Both front and back are finished in scuff-resistant vinyl walnut. Full hinged blue plexi-glass dust cover. Ebony-finished speakers have midnight blue grille cloths. Powerful solid-state AM/FM Stereo Receiver features: FM Stereo Indicator Light, separate balance and tone controls, AFC on FM to prevent drift, and built-in AM and FM Antennas. Each speaker enclosure contains an acoustically matched high compliance wide-range duocone speaker with mechanical crossover network for superb sound reproduction. Famous BSR 4-speed Automatic Record Changer plays 12", 10", and 7" records at 16 2/3, 33 1/3, 45, and 78 rpm. Tubular tone arm contains turnover stereo cartridge. Size with speakers and stand: 24 3/4"H x 43 1/2"L x 17"D. For 117 VAC, 60 Hz.
24 R 62000WX Shpg. wt., 55 lbs. Net 199.95

Lafayette LSC-888B 3-Piece Stereo Phonograph and 8-Track Tape System



129⁹⁵
with PLASTIC
DUST COVER
No Money
Down*

- Garrard 4-Speed Automatic Record Changer with Cueing
- 20-Watt Solid-State Stereo Amplifier
- Each Speaker Enclosure Contains an 8" Woofer and a 4" Tweeter

Deluxe 3-Piece Stereo Music System plays both stereo records and 8-Track Stereo Tape Cartridges. Professional 4-speed Garrard changer has tubular tone arm, cueing, and diamond stylus. 8-Track Stereo Cartridge Tape Player features illuminated track indicators and a pushbutton channel selector. Includes 45 rpm spindle. Size: Control Center: 23 1/2" x 4H x 14"D. Speakers: 15H x 10W x 4 7/8"D. For 110-120 VAC, 60 Hz. Shpg. wt. 49 1/4 lbs.
24 R 03343WX Net 129.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 97

SONY

and

PANASONIC**Home Entertainment Phono Systems****NEW SONY HP 149****3-Piece AM/FM Stereo
Cassette-Phono System**

Handsomely styled with a quality AM/FM Stereo Receiver, BSR 4-speed mini-automatic record changer, pushbutton stereo cassette recorder, and 2 separate speaker enclosures—each containing a 6½" woofer and a 2" tweeter. Recorder features built-in cassette storage compartment and automatic record level control. You can record direct from the record changer or AM/FM stereo tuner, or live with the optional stereo mike. Front panel stereo headphone jack. Comes with 45 RPM adapter, FM dipole antennas, and plastic dust cover. Size: each speaker 11½x11½x5½"D. Control Unit—8x22¼x12"D. For 117 VAC, 60 Hz. Imported.

24 R 32003WX Shpg. wt., 32 lbs. Net 229.95
Stereo Microphone for HP 149. Shpg. wt., 1 lb.
24 R 32029 No Money Down* Net 21.95

**NEW PANASONIC RS 257
Stereo Cassette Phono/Radio
Home Entertainment Center**

Everything in one beautifully designed package. Stereo Cassette Recorder features pushbutton controls, slide-in cassette system, and end of tape shut-off. 4-speed stereo record changer has Panasonic whisper-touch cartridge, tubular tone arm, and diamond LP stylus. FM/AM/FM stereo radio has AFC on FM, FET tuner, and black-out dial. Matching speaker enclosures each housing a 6½" woofer and 2¾" tweeter. Slidelever bass, treble, volume and balance controls. Solid-state circuitry. Jacks for microphone, aux. input and headphones. With cassette storage compartment, changer dust cover, pre-recorded cassette and microphone with stand. Walnut wood cabinetry. For 117 VAC, 60 Hz. Shpg. wt., 48 lbs. Imported. Size: Control unit—10¾ x 21½ x 14". Each Speaker System—14¾ x 16¾ x 5½".

24 R 41285WX No Money Down* Net 299.95

**NEW PANASONIC SC 8700
AM/FM Stereo Music Center
with 4-Channel Amplifier**

Exciting solid-state 4-channel quadrasonic—ready stereo music center. By just adding a 4-channel program source such as a 4-channel reel or cartridge deck, and two rear speakers (see listing below), you can listen to discrete 4-channel stereo music in your home. The receiver can also be operated to provide separate simultaneous stereo programs for 2 areas of your home. SC-8700 features: (1) pre-mounted 4-speed Garrard automatic turntable equipped with a Pickering diamond stylus magnetic cartridge, and dust cover, (2) full Feature 60 watt (IHF) AM/FM stereo Receiver with 4 amplifiers, (3) two matching acoustic suspension speaker systems, each containing an 8" woofer, 5" mid-range, and 2" tweeter. Walnut wood cabinetry. Size: Receiver—5½ x 17½ x 14¾". Each Speaker—21¾ x 13¾ x 7½". Changer—8¾ x 17½ x 15½". For 117 VAC, 60 Hz. Imported.

24 R 41277WX Shpg. wt., 75 lbs. Net 429.95
PAIR OF SB-170 SPEAKERS FOR 4 CHANNEL SYSTEM.
Same specifications as SC 8700's speaker system.
24 R 41269WX Shpg. wt., 30 lbs. Net 99.95



NEW! Deluxe Lafayette LSC-55

Solid-State 3-Piece Stereo Modular Hi-Fi Phono System

Each Speaker Enclosure Contains an 8" Wide-Range Speaker



89⁹⁵
With Dust Cover



Diamond Needle

- Deluxe Full Size BSR 4-Speed Automatic Record Changer Features Cueing Lever, and Anti-Skating Control
- Front Panel Stereo Headphone Jack
- Aux. inputs Jacks For Plugging-in a Stereo FM Tuner or Tape Player
- Solid-State Stereo Amplifier has 4 Controls—Volume, Balance, Bass, Treble
- Walnut Wood Cabinetry

Our Beautiful 3-piece stereo compact phono system provides superb hi-fi music reproduction at a modest cost. Has many features usually found on higher price component systems. Famous full size BSR 4-speed record changer with cueing control plays 7", 10", and 12" records at 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45, and 78 RPM. Tubular tone arm has stereo turnover cartridge with diamond LP needle. System turns off after the last record has been played. Input jacks are provided on the rear panel for plugging in an FM Stereo Tuner or Tape Player. Powerful solid-state stereo amplifier has a stereo headphone jack for private listening. Acoustically matched pair of 8" wide-range speakers are housed in walnut wood cabinets. Each Spk. System measures 13 $\frac{7}{8}$ "H x 5 $\frac{3}{8}$ "W x 5 $\frac{3}{4}$ "D". Size of Control Unit: 16 $\frac{3}{8}$ "D x 3 $\frac{5}{8}$ "H x 14 $\frac{1}{8}$ "D". For 117 VAC, 60 Hz. Comes with plastic dust cover and 45 RPM Spindle. Imported. Shpg. wt., 36 lbs.

24 R 03200WX No Money Down[®] Net 89.95
Replacement Needle for LSC-55 Shpg. wt., 3 oz. Net 2.79
24 R 02580 Net 2.79

Lafayette LSC-25 Solid State 3-Piece Stereo Modular Hi-Fi Phono System

- Two 4" Wide-Range Acoustically Matched Speaker Systems
- Ultra-Modern Low Profile Styling
- Stereo Headphone Jack for Private Listening
- Famous BSR 4-speed Automatic "Mini" Record Changer

49⁹⁵
With Dust Cover



Diamond Needle

Component inspired design. Now a stereo hi-fidelity phonograph with the advantages of separate components. Our handsome 3-piece modular hi-fi phono system features a control unit containing a reliable solid-state stereo amplifier and a BSR 4 speed automatic "mini-changer" mounted in a simulated black leather high-impact plastic base with walnut vinyl trim. Each matching speaker system can be ideally spaced for proper stereo separation. They can be placed on a bookshelf, hung on a wall, or set on end-tables. The amplifier has a stereo headphone jack for private listening and 3 controls: volume left, volume right and tone. BSR 4-speed automatic "mini-changer" features automatic shutoff after last record has been played. Plays

all size records—7", 10", 12" and all speeds—16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45, and 78 RPM. Intermixes 12" and 10" records of the same speed. Tone arm is equipped with a stereo turnover cartridge with a diamond LP needle. Includes a tinted plastic dust cover for the control unit. Size: Control Unit—10 $\frac{1}{4}$ "W x 16 $\frac{1}{2}$ "L x 6 $\frac{1}{2}$ "H; Speaker—7 $\frac{3}{8}$ "W x 9 $\frac{1}{2}$ "L x 4"D. For 110 VAC, 60 Hz. Shpg. wt., 13 $\frac{1}{2}$ lbs.

24 R 03236WX No Money Down[®] Net 49.95
ACCESSORIES for LSC-25
Replacement Needle for LSC-25. Wt., 3 oz. Net 2.79
24 R 02386 Net 1.49
24 R 02568 45 RPM Spindle for LSC-25 Net 1.49

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 99

Deluxe LAFAYETTE LSC-100B AM/FM Stereo Modular Hi-Fi System



Diamond Needle

149⁹⁵
W/†
Dust Cover

- Garrard 4-Speed Automatic Record Changer with Cueing
- Powerful Solid State Stereo Amplifier
- Electronic FM Stereo Indicator Light
- Stereo Headphone Jack for Private Listening

- Each Speaker Contains an 8" Woofer and 4" Speaker
- Guitar Microphone Input Jack
- Tape Input and Output Jacks
- Main and Remote Speaker Jacks

Our finest stereo phonograph with built-in stereo FM/AM radio is fully solid-state and features magnificent ultra-modern styling. The control center's stereo amplifier provides 20-watts Music Power and has provisions for tape input and output, guitar mike input, and stereo headphones. Also includes AC convenience outlet on rear panel. Features remote speaker output jack for hooking up an additional pair of speakers for another room. Tunes in regular FM & AM radio and receives full-dimensioned stereo FM broadcasts. Built in AM/FM antennas. Provision for attaching external FM antenna. Calibrated slide rule tuning, AFC switch for drift-free FM reception. Garrard 2025 4-speed automatic stereo record changer with cueing lever plays 7", 10" and 12" records at 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45, and 78 rpm. Operates automatically or manually. Shuts off both changer and

amplifier automatically after last record. Features tubular tone arm with Vaco TN-4 stereo turnover cartridge with diamond LP needle. Each 2-way speaker system contains an 8" woofer and 4" tweeter for brilliant concert hall realism. You also get a handsome tinted plastic dust cover for the complete control unit, speaker hook-up cable and a 45 rpm spindle. The components are mounted in beautiful walnut vinyl veneer covered wood cabinets. Size: Control unit 23 $\frac{3}{8}$ " x 14" x 10 $\frac{3}{8}$ " H (with dust cover). Includes tinted plastic dust cover and 45 RPM spindle. Speaker Encl.: 15 $\frac{3}{8}$ " H x 10 $\frac{1}{4}$ " W x 4 $\frac{1}{2}$ " D. For 110-120 VAC, 60 Hz. Shpg. wt., 45 lbs.
24 R D325WX No Money Down* Net 149.95

24 R 03202 Replacement needle for LSC-100B Net 2.79

NEW LAFAYETTE LSC-90 3-Piece Solid-State Stereo Hi-Fi Phono with Built-in AM/FM Radio



Diamond Needle

69⁹⁵
W/†
Dust Cover

- 2 Wide Range 4" Acoustically Matched Speaker Systems
- Famous BSR 4-Speed Automatic "Mini" Record Changer
- Front Panel Stereo Headphone Jack

Highly styled compact AM-FM music system at a low, low Lafayette Price. BSR "mini" stereo record changer plays 12", 10", & 7" records at 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45, and 78 RPM. Features precision-balanced turntable, low mass pick-up arm for accurate tracking and diamond LP stylus ceramic cartridge. Solid-state stereo amplifier has 5 controls—Volume Left, Volume Right, Bass-Treble, selector (Phono, FM, AM), Tuning. AM-FM Radio has slide-rule tuning dial, and built-in

AM & FM antenna. Black leatherette and walnut grained plastic cabinetry. Size Control unit 16 $\frac{3}{4}$ " W x 9 $\frac{7}{8}$ " D x 6 $\frac{1}{2}$ " H. Each speaker 7 $\frac{3}{8}$ " W x 9 $\frac{1}{2}$ " L x 4" D. For 117 VAC 60 Hz. With tinted plastic dust cover. Imported. Shpg. wt., 14 lbs.
24 R 03426W No Money Down* Net 69.95
24 R D2386 Replacement Needle. Wt., 3 oz. Net 2.79
24 R D2568 45 RPM Spindle. Wt., 3 oz. Net 1.49

LAFAYETTE'S BEST

229⁹⁵

With Dust Cover*



Two 3-Speaker Acoustic Suspension Speaker Systems

The ultimate in a 3 piece Modular stereo phono system. Start with a handsome Control Center containing a powerful solid state 100 watt, AM/FM stereo Tuner/Amplifier. Add: (1) A famous Garrard 4-speed Automatic stereo record changer with cueing control, (2) a deluxe 8-Track Stereo Cartridge Player. Take the two perfectly balanced full range 3-Speaker Acoustic Suspension Systems and plug them into the control center (cable included). You now have a magnificent performing system that permits you to enjoy the finest in hi-fidelity music listening. Specifications: Garrard changer: 4-speeds—16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45, 78 RPM. Intermixes records of the same speed. Tone arm has turnover stereo ceramic cartridge with Diamond LP needle. 8 Track Stereo Tape Cartridge Player: Individual Illuminated Track Indicators, Pushbutton Track Selector. Stereo Tuner Amplifier: Black-out calibrated tuning dial—Separate slide controls for Balance, Bass, Treble, and Volume. Rocker switches for On/Off, AFC, Rumble Filter, Scratch Filter, and Loudness. Front panel guitar mike input jack. Tape Input jacks; AC Convenience outlet. Each Acoustic Suspension Speaker System contains one 6 $\frac{1}{2}$ " woofer, and two 3 $\frac{1}{2}$ " tweeters. Beautiful walnut vinyl wood cabinetry. Includes Plastic Dust Cover and 45 RPM Spindle. Size: Control Center: 23 $\frac{1}{2}$ "W x 9 $\frac{3}{4}$ "H x 15"D. Ea. Speaker System: 14 $\frac{1}{8}$ "H x 11 $\frac{1}{4}$ "W x 6 $\frac{1}{2}$ "D. For 110-120 VAC, 60 Hz. Shpg. wt., 63 lbs. Net 229.95
24 R 03418WX No Money Down* Net 2.79
24 R 03202 Replacement needle for LSC-8000B Net 2.79

NEW Deluxe Model LSC-8000B Solid State AM/FM Stereo 8-Track Phono System

- Slide Lever Controls for Balance, Bass, Treble and Volume
- FM Stereo Indicator Light and Tuning Meter
- Garrard 2025 4-Speed Automatic Record Changer with Cueing
- Power Output—100 Watts Music Power
- Stereo Headphone and Remote Speaker Outputs
- Individual Illuminated Track Indicator Lights

NEW Model LSC-6000 Solid-State AM/FM Stereo 8-Track Phono System

- BSR 4-Speed Automatic Record Changer with Cueing Control and Diamond Needle
- Powerful Solid-State Stereo Amplifier/Tuner features Separate Slide Controls for Balance, Bass, Treble
- 8-Track Stereo Tape Cartridge Player features Individual Channel Indicator Lights and Push-button Track Selector
- Each Air Suspension Speaker System Contains an 8" Woofer, 2" Tweeter, Crossover Network, and a Multicellular Horn Type Duct

Enjoy the sound and performance of 8-track stereo tape cartridges, records, and AM/FM stereo broadcasts from this "luxurious-low price" 3-piece phono system. The handsome walnut wood cabinetry with low silhouette styling will blend into any decor. The powerful solid-state AM/FM stereo tuner-amplifier features a black-out tuning dial, FM-Stereo indicator light, front panel stereo headphone jack, and a six position selector switch: AM, FM, FM-AFC, FM-Stereo, Phono/Aux, Tape. Built-in 8-track stereo tape cartridge player has color coded channel indicator lights. BSR 4-speed record changer plays 12", 10", and 7" records at 16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45, and 78 RPM—and contains many professional features such as anti-skating control,



179⁹⁵

With Dust Cover

cueing lever, and tubular tone arm equipped with ceramic stereo turnover cartridge with diamond LP stylus. Tape inputs and outputs are provided on the rear of the unit. Built-in AM and FM antennas. Provision for external antenna. Size: Control Unit—17 $\frac{1}{2}$ "L x 14 $\frac{1}{4}$ "D x 9"H. Each Speaker—15 $\frac{3}{4}$ "H x 11W x 6 $\frac{1}{2}$ "D. Comes with Plastic Dust Cover, 45 RPM Spindle, and FM dipole Antenna. For 117VAC, 60 Hz. Imported. Shpg. wt., 50 lbs. Net 179.95
24 R 03392WX No Money Down*

Replacement Diamond Needle for LSC-6000. Net 2.79
24 R 02980

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 101

LAFAYETTE LR-828



Solid State 3 Piece AM/FM/FM Stereo 8-Track Playback System

NEW

SENSATIONALLY PRICED

99⁹⁵ With FM
Dipole Antenna

Features Separate Slide Controls
for Balance, Bass, & Treble

- Front Panel Stereo Headphone Jack
- Pushbutton Track Selector
- FM Stereo Indicator Light
- Black-Out Lighted Slide Rule Dial
- Inputs for Record Changer
- Tape Recorder Output Jacks

- Each Speaker Enclosure Contains an Acoustically Matched Wide Range 6½" Speaker
- Illuminated Track Indicator Lights

Exceptionally fine performing system you'll be proud to own and delighted to listen to. Beautifully styled and engineered to sell at a price everyone can afford. Its two separate 6½" wide range speaker systems provide rich full frequency stereophonic sound. Enjoy the ease and pleasure of listening to pre-recorded 8-Track stereo tape cartridges. Listen to magnificent FM stereo radio broadcasts as well as FM mono and AM programs. Black out and illuminated slide rule tuning dial. Illuminated FM stereo indicator. Six position selector switch for AM, FM, FM-AFC, FM-MPX, Phono, Tape. Separate slide controls for balance, bass, and treble. Front panel stereo headphone jack for private listening. Built-in 8-Track cartridge player has a pushbutton channel selector and individual illuminated channel indicators. Record changer input (ceramic) and tape record output jacks. AC convenience jack on rear panel. Powerful 2 watt RMS solid state stereo amplifier. FM sensitivity: 5 mV. Stereo Separation: 30db. Walnut vinyl covered wood cabinetry. Size: Control Unit: 19"L x 4½"H x 8½"D. Each Speaker System, 10"H x 8"W x 4½"D. For 117VAC 60 Hz. Imported. Shpg. wt., 24 lbs.

17 R 01168WX No Money Down^o Net 99.95
Lafayette MC22B 4 Speed Automatic Record Changer Ensemble. (See page 91 for complete description of MC22B.)
21 R 01772 No Money Down^o Net 34.95

LAFAYETTE 'Profile 80' Full Feature Solid-State AM/FM/FM Stereo 8-Track Player/Receiver



129⁹⁵ • Tape Recorder Output
• FM Stereo Indicator Light
• Pushbutton Track Selector
• Spill-Proof Capstan Mechanism

- Main and Remote Speaker Controls
- Individual Illuminated Track Indicator Lights

Magnificent performing solid-state home entertainment control center. Play brilliant 8-Track stereo tape cartridges without using an accessory tape deck. Receive AM, FM, and FM stereo radio broadcasts. Plug-in and play a record changer with a ceramic cartridge, or plug-in and play a cassette or reel-to-reel tape deck or recorder. In addition, tape recorder output jacks are available for taping all the music reproduced by this fine receiver. Separate volume, balance, bass, and treble controls; Individual switches for loudness, stereo/mono, hi-filter, main or remote speaker. Built-in AM and FM antenna. Provisions for external FM antenna. Spill-proof mechanism

on the 8 Track Player stops the tape from wrapping around capstan. FM IHF Sensitivity: 5µV; Power Output: 18 watts music power. Tape Output: maximum 1 volt-average 300µV. Cartridge Player: S/N Ratio: better than 38 db; Wow and Flutter: less than 0.36% RMS. Housed in a handsome walnut and metal enclosure. AC convenience outlet. Size: 20½"W x 4½"H x 10¾"D. For 117V 60 Hz. AC. Imported. 99 R 02354W Shpg. wt., 24½ lbs. Net 129.95
Criterion 25A Speakers for "Profile 80". (See page 56 for 25A description.)
99 R 02255W Shpg. wt., 12 lbs. Net 19.95 ea.

Deluxe LAFAYETTE RK-890A Solid-State Stereo 8-Track Cartridge Recorder/Player Tape Deck

NEW 129⁹⁵
Less Mikes



Record 8-Track Cartridges
Thru Your Stereo Amplifier
Or Receiver, or Live with Mikes
Using the RK-890A

RECORD FEATURES

- Stop after each Channel and Automatic Eject, or Stop after Channel 1 thru 4 and Eject
- Sound with Sound Mixing
- Pushbutton Manual Eject
- Pushbutton Fast Forward
- Front Panel Left and Right Channel Microphone Input Jacks
- Record Safety Interlock Button
- Illuminated Track Indicator Lights
- Dual Recording VU Level Meter
- Separate Dual Concentric Microphone and Aux. Volume Controls

PLAYBACK FEATURES

- Continuous and Repeat Play
- Pre-Select and Play any 1 Channel and Stop and Automatic Eject
- Pushbutton Track Selector
- Illuminated Track Indicator Lights
- Pushbutton Fast Forward
- Pushbutton Manual Eject

EXCLUSIVE FEATURES

- Automatic Cartridge Ejector—Insures you do not damage the tape head and your cartridge
- Specially Designed Built-In Lafayette Solid-State Stereo Record/Playback Pre-Amplifiers

Even better than our widely acclaimed RK-890. The Improved RK-890's new features include a repeat program selector, stereo-mono mode switch, meter overload protection circuitry, automatic return of all function buttons to neutral (off positions) after cartridge ejection, and increased bias frequency to 82 kHz. Offers unsurpassed 8-track cartridge record and playback facilities. Enjoy hours of listening pleasure from your own pre-recorded stereo cartridges. The RK-890A will become the ideal companion to your present high fidelity system. Exclusive Automatic Cartridge Ejector will provide years of trouble-free 8-track performance—no longer will you damage the heads of your recorder or the roller of any cartridge by leaving a tape inserted after you have turned off the power. The fast forward feature permits quick selection of tape sections. And, most important, you can automatically record each track individually and stop.

Specifications: 2 Mike Inputs, (Sensitivity ea., 1 mV and 100 mV). Bias Freq.: 82 kHz, AC erasing system, Freq. response: 30-12,000 Hz, Wow & Flutter: less than 0.25%, Channel Separation: 30db, Output level: 1 volt Max, 300 mV Average, 17 Transistors, 13 Diodes. Walnut metal wrap around case. Brushed gold anodized aluminum trim. AC Power Fuse. For 117 VAC, 50-60 Hz. Size: 12 x 3 3/4 x 9 1/4"D. Imported. Shpg. wt., 12 lbs.

99 R 15668W No Money Down* Net 129.95

Microphone for RK-890A, Imported, Shpg. wt., 8 oz.
99 R 46161 Net 6.50

Lafayette 60 Min. 8-Tr. Mylar Recording Tape. Shpg. wt., 6 oz.
28 R 01348 Net ea. 1.95

Deluxe LAFAYETTE RK-800A 8-Track Stereo Cartridge Playback Deck

- Built-in Solid-State Stereo Playback Preamp/ifier
- Pushbutton Track Selector
- Individual Illuminated Track Indicator Lights
- Spill-Proof Capstan Mechanism

Improved version of our best selling 8-Track stereo playback deck. Designed to complement the finest stereo systems. Unique capstan bearing assembly insures long-life operation without damage to your tapes. Spill-proof mechanism stops tape from wrapping around capstan. Built-in solid-state stereo playback pre-amplifiers. Connects to your stereo amplifier or receiver tape input. Tape plays continuously. Four indicator lights tell you which track is playing at any given time. In sequence you may switch tracks by depressing the pushbutton track selector button. Power Output: 1-volt. Freq. Response: 30-12,000 Hz \pm 3db, S/N Ratio: better than 47 db, Wow & Flutter: less than 0.2% rms. Tape Speed: 3 3/4 ips, 4-pole AC condenser motor. Walnut grain finished metal case. Brushed aluminum front panel. Size: 9W x 4 1/4H x 9 1/4"D. For 117 VAC., 60 Hz. Imported. Wt., 10 1/4 lbs.
99 R 15893W No Money Down* Net 54.95


54⁹⁵



Update Your Home
Stereo System to Play 8-Track
Stereo Tape Cartridges

*See Page 22 for Full Credit Details on Easy Pay Plan

NEW LAFAYETTE RK-520 Solid-State 3-Piece Stereo Cassette Tape Recorder with Switchable Bias Equalizer



- 7 Pushbutton Functions—Play, Record, Fast Forward, Rewind, Pause, Stop, Cassette-Up
- Main Or Remote Speaker Outputs
- Front Panel Mike Input Jacks
- Large Illuminated Dual Record Level Meters

Our exciting new professional home stereo cassette playback and recording system delivers truly magnificent wide-range sound from its powerful built-in solid-state stereo amplifier and the 2 matching acoustic suspension speaker systems. The STD/CrO₂ bias equalizer switch permits choice of recording with either a standard cassette tape or the new improved chromium-dioxide tapes (CrO₂). These tapes increase high frequency levels up to 8 db, and reduce inherent tape noise (hiss). Dual concentric left and right channel microphone and input source record level controls permit sound-with-sound mixing. Illuminated VU level meters, front panel stereo headset push-button tape controls, front panel stereo editing, choice of microphone, speakers, loudness button, stereo-mono switch, separate bass and treble controls, dual concentric volume and balance controls, front panel left and right channel mike inputs, tape recorder output jacks, input jacks for playing a record changer, tuner, or another tape deck thru the recorder's amplifier are provided. Records and plays back 4-track

- Sound-With-Sound Mixing • Stereo-Mono Switch
- Mike And Input Source Record Level Controls
- Semi-slot Tape Loading
- 3-Digit Tape Counter With Reset Button
- Input For Record Changer, Tuner, Or Tape Deck

stereo and 2-track monaural. AC convenience outlet on rear panel. SPECIFICATIONS: Each speaker system contains 5" acoustic suspension woofer with 1 lb. magnet structure and 3 1/2" cone-type tweeter. Laminated heads. Power Output: 10b, 20 watts HF. Freq. response: 50-11,000 Hz. AC Bias. Erase frequency, 98 kHz. S/N Ratio, Better than 40db. 95db at 0-VU. Amplifier input sensitivity, 155 mV (Acceptor Phonon, Tuner) Mike input sensitivity, 25 mV for 0-VU Wow & Flutter, less than 25%. Size: 434-H x 11D x 151/2-W. Imported. For 117 VAC/60 Hz Beautiful walnut grained case. Ship. wt., 37 1/2 lbs.

99 R 99665WXMU No Money Down	Net \$79.95
99 R 15943WX RK-520 less speakers	Net \$59.95
CrO ₂ , 60 min. Chromium-Dioxide Tape	Net 2.99
28 R 47002	Net 2.99
Standard 60 min. Cassette Recorder Tape	Net 2.99
28 R 01223	Net 2.99

* See Page 22 for Full Credit Details on Easy Pay Plan

179.95 With 2 Dynamic Mikes and Two 2-way Acoustic Suspension Speaker Systems



Std/CrO₂, Switch On Front Panel For Recording With Chromium Dioxide Tape


OUTSTANDING FEATURES

AUTO OFF POWER

Automatic Shut Off—RK-520 Completely Turns Off—Mechanically And Electrically At End Of Tape In Either Play, Record, Or Fast Forward Function

LAFAYETTE'S Finest Record/Playback Stereo Cassette Decks

LAFAYETTE RK-760A Solid-State Stereo Cassette Tape Deck with Switchable Bias Equalizer



9995

Face Microphone

- Sound-with-sound Mixing
- 3 Digit Tape Counter with Reset Button
- Semi-slot Tape Loading
- Illuminated Dual Channel VU Record Level Meter

- Records 4-Track Stereo and 2-Track Monaural
- Plays Back 4- and 2-Track Stereo and Monaural
- STD/CrO₂ Switch on Front Panel for Recording with Chromium-Dioxide Tape
- 7-Pushbutton Tape Functions Including Pause for Cueing and Editing

Top quality solid-state stereo cassette tape deck featuring **Switchable Bias Equalization**. An STD/CrO₂ bias equalizer switch on the front panel permits choice of recording on the RK-760A with either a standard cassette tape or the new revolutionary chromium dioxide (CrO₂) cassette tapes; CrO₂ tape increases high frequency level up to 8db, and reduces inherent tape noise (hiss) for superb studio type stereo cassette amplifiers. Connects into a standard amplifier or receiver with an output Full set of pushbutton controls for all tape functions: Record, Play, Stop, Rewind, Fast-Forward, Pause and Cassette Eject. The record button incorporates a safety-interlock to prevent accidental erasures. Includes left and right channel dual concentric record level controls —enables you to make sound with sound recordings. Simultaneously record live with mikes and thru an external source such as record-changer, Tuner, or another tape recorder. Tape speed is a constant 1 7/8 ips.

99 R 158659W No Money Down* Net 99.95

99 R 46161 Dynamic Mike. Imported. Shpg. wt., 15 oz.


Standard 60 Min. Cassette Recording Tape

28 R 01223 Net ea., .99

CrO₂, 60 Minute Cassette Recording Tape

28 R 47002 Net ea., 2.99

LAFAYETTE RK-D40 DOLBY SYSTEM Stereo Cassette Record/Playback Deck



17995

Face Microphone

Noise Reduction System, Manufactured Under License from Dolby Laboratories, Inc.—Reduces High Frequency Noise (Hiss) by 90%

- Special Low Impedance Stereo Amplifier For Private Headphone Monitoring
- STD/CrO₂ Pushbutton Control • Illuminated Dual Channel Record Meter
- Automatic Shut-off At End Of Tape In Play, Record, F.F. Mode—Both Electrotronically And Mechanically • Sound-With-Sound Mixing

Professional studio quality Dolby System Stereo Record/Playback Cassette Deck. For recording utilizes famous Dolby circuitry for noise reduction now used by major recording companies for master taping. Major recording studios and independent private playback stores use the Dolby system cassette tapes. Features provisions for using advanced CrO₂ tape. Connects into any advanced amplifier or receiver tape input and output. Records and plays back 4-track stereo and 2-track monaural. Also has special built-in low impedance stereo amplifier for private headphone monitoring and listening. Full set of pushbutton controls—Record, Play, Stop, Rewind, Fast Forward, Pause, and Cassette. Record button incorporates safety-interlock. Separate dual-concentric front panel record level controls for microphone and external source. Front panel pushbuttons for STD/CrO₂, Stereo-Mono, Dolby. Visual Record and Dolby indicator lights. Tape

Speed 1 7/8 IPS. SPECIFICATIONS: 4-pole hysteresis synchronous AC motor, AC biasing and erase frequency: 100 KHz. 40 Playback output, 1 volt, freq. Dispersion: 2.5%; 99 R 46161 Dynamic Mike. Imported. Shpg. wt., 15 oz. Standard 60 Min. Cassette Recording Tape

28 R 01223 Net ea., .99

CrO₂, 60 Min. Cassette Tape

28 R 47002 Net ea., 2.99

LAFAYETTE'S BEST!



Deluxe LAFAYETTE RK-86 Battery/AC Portable Cassette Tape Recorder

39⁹⁵

Includes Dynamic Microphone With Remote Control Switch, 60 Minute Cassette Recording Tape, AC Line Cord, 4 "C" Batteries, and Earphone.

- Instant-On Solid-State Circuitry
- Professional Recording System
AC Bias, AC Erase
- Dual Battery/Record Level Indicator
- Separate Tone and Volume Controls

Beautifully designed portable cassette recorder of exceptional quality. One of the easiest recorders to operate. Features semi-slot tape loading and pushbutton controls. No reels to thread. Operates on 4 "C" batteries for portable use, or on 117 VAC 60 Hz in the home or office. Utilizes professional AC bias and erase recording system for accurate and precise record and playback performance. Separate pushbuttons for record, play, rewind, fast forward, and stop/Cassette-up. Safety interlock on record button prevents acci-

dental erasures. Aux. input jack is provided for recording from external sources such as phono, TV set, or radio tuner directly onto tape. Integrated carrying handle. Size 9 $\frac{3}{8}$ x 7 $\frac{3}{8}$ x 2 $\frac{3}{8}$ ". Imported. Shpg. wt., 4 lbs.

99 R 15935L No Money Down*	Net 39.95
60 Minute Lafayette Cassette Tape	
28 R 01223 Shpg. wt., 4 oz.	Net .99
99 R 62572 Extra "C" batteries, 4 req.	ea. .16

NEW Deluxe LAFAYETTE RK-166 Battery/AC Portable AM/FM Radio Cassette Recorder

59⁹⁵

With 4 "C" batteries, AC line cord, earphone, remote control mike with stand, 60-minute blank cassette, accessory pouch.

- Direct Recording From AM or FM Radio
- Pop-up Cassette Ejector Button
- Automatic Level Control • Built-in AFC
- Recording Level/Battery Meter
- Slide Control for Adjusting Volume



Handsome full-feature AM/FM Radio Cassette Recorder. Operates on 4 "C" batteries or 117V AC. Simple to use—no tape threading. Precision slide rule tuning on the AM/FM radio. Recorder features rotary controlled function knob for play, stop, rewind, fast forward. Record safety interlock button prevents accidental erasures. Swivel telescopic FM antenna and built-in ferrite core AM antenna. Handy slide control for adjusting volume. External speaker or earphone

jack. Automatic level control for perfect voice recordings. Powerful 3 $\frac{1}{2}$ " acoustically matched speaker provides rich, full frequency sound. Integrated carrying handle. Size: 11 $\frac{3}{4}$ " x 7 $\frac{1}{4}$ " x 3". Imported. Shpg. wt., 7 lbs.

27 R 01159L No Money Down*	Net 59.95
28 R 01223 Lafayette 60 Minute Tape Cassette, 4 oz.	.99
99 R 62572 Extra "C" batteries (4 required)	ea. .16

New LAFAYETTE Battery | AC Cassette Recorders

LAFAYETTE RK-76



32⁹⁵

With Remote Control Mike, AC Line Cord, 4 "C" Batteries, 30 Min. Cassette, Earphones, Carrying Strap

- Instant-on Solid-State Circuitry
- Semi-slot Tape Loading
- Automatic Record Level Control

Quality portable cassette recorder is just perfect for instant recording in the classroom, office, home, car or outdoors. Operates on 4 "C" batteries (included) or 117 VAC line (Included). Built-in Automatic Level Control circuit assures perfect voice recording level regardless of volume control position. Remarkably easy to use semi-slot tape loading; there are no reels to thread. Plays back both monaural and stereo music cassettes. Piano key pushbuttons for easy selection of Play, Record, Fast Forward, Rewind, and Stop. Jacks are provided for

Mike, Remote Control, Aux. Input, and Earphone Monitor. Size: 9 1/4 x 5 1/2 x 2 1/2 "H. Handsome charcoal cabinet with chrome trim. Imported. Shpg. wt., 6 lbs.

99 R 15976L No Money Down* Net 32.95

ACCESSORIES FOR ABOVE RECORDER

99 R 62572 Extra "C" Batteries (4 req.) Net ea. .16

99 R 15880 Footswitch for Remote Playback, 3/4 lb. Net 3.95

28 R 01223 Lafayette 60 minute Tape Cassette Net ea. .99

Five Pushbutton Controls

- Pushbutton Controls for Stop, Play, Record, Fast Forward, and Rewind
- Record Safety Interlock

LAFAYETTE RK-68



24⁹⁵

With Remote Control Mike

Handsome beige and brown compact cassette recorder. Operates on 4 "C" batteries or 117 VAC with AC line cord (Included). Plays and records up to 2 hours using a standard 120-minute cassette. Start/Stop switch on microphone allows for remote control operation of the recorder. Dynamic speaker provides fine voice and music reproduction. Record Safety Interlock button prevents accidental erasures.

- Instant-on Solid State Circuitry
- Record Safety Interlock Button
- Single Tape-Function Control for: Record, Stop, Play, Fast Forward, Rewind

Single Tape-Function control. Molded carrying handle. Input jack for earphone/extension speaker. Size: 11 "L x 5 1/2 "W x 2 1/2 "H. Imported. Shpg. wt., 4 1/2 lbs.

99 R 16024L Net 24.95

28 R 01223 Lafayette 60-Minute Tape Cassette Net .99

99 R 62572 "C" Batteries—4 required Net ea. .16

* See Page 22 for Full Credit Details on Easy Pay Plan

LAFAYETTE RK-225



ONLY
44⁹⁵

With Remote Mike with Stand, 4 "C" Batteries, and AC Line Cord

- Direct Recording Facilities From AM/FM Radio to Recorder
- Semi-Slot Tape Loading
- Record Level Indicator Light
- Selector Knob For Rewind, Stop, Play
- Fast Forward Lever
- Record Safety Interlock Lever
- Built-in Telescopic FM Antenna

NEW Solid-State Battery/AC AM/FM Radio Cassette Tape Recorder

Make your own cassettes directly "off the air" anytime, anyplace. Or, record live with the remote control dynamic mike. This fine performing Radio/Recorder operates as a portable on 4 "C" batteries (included), or in the home on 117 VAC. Record Indicator light permits you to adjust the volume for proper recording level. 3" dynamic speaker provides Tone tone. Single function knob for rewind, stop, play, Unique levers for fast forward, and record safety interlock. Built-in AM antenna, telescoping FM antenna, Aux, and External

Speaker/Earphone jacks. Attractive black cabinet with chrome and ivory trim. Integrated carrying handle. Size: 11½Wx6Dx3"H. Imported. Shpg. wt., 6 lbs.

99 R 16016L No Money Down* Net 44.95

ACCESSORIES FOR RK-225

28 R 01223 Lafayette 60 Minute Tape Cassette Net ea. .99
99 R 62572 Extra "C" batteries, 4 req. Net ea. .16

LAFAYETTE RK-65



**Portable
Solid-State
Cassette Recorder**

19⁹⁵

- Record Safety Interlock Button
- Single Tape Function Control: Record, Stop, Play, Fast Forward, Rewind

With remote control mike, and integrated carrying handle

So easy to use! Just snap in a cassette and you are ready to record or play. No tape to thread. Operates on 4 "C" batteries (not included) or 117 VAC house current with optional AC adapter. Instant-on solid state circuitry. Includes dynamic start-stop microphone for remote control operation. Big 2¾" speaker for excellent sound reproduction. Input jack for earphone or extension speaker. Built-in integrated carrying handle. Size: 9Lx5¾Wx2½"H. Shpg. wt., 4 lbs. Imported.

99 R 15828L Net 19.95

Accessories for RK-65

98 R 35115 AC Adapter for RK-65. Shpg. wt., 6 oz. Net 3.95
28 R 01223 Lafayette 60 minute Tape Cassette Net ea. .99
99 R 62572 "C" Batteries, 4 Required Net ea. .16



Solid State Cassette AM & FM Radio Tuners

AM Radio
Tuner

FM Radio
Tuner

6⁹⁵

12⁹⁵

- Converts Most Cassette Tape Recorders and Players into a Sensitive Radio

Miniaturized, solid-state radio tuner circuit with self-contained battery (included). Same size as any standard blank or prerecorded cassette. Take it anywhere, play it anywhere. Plays directly through the amplifier and speaker system of your cassette player or recorder. High-impact break resistant case. Size 4x2½x¾". Imported. Wt., ½ lb.

28 R 43019L AM Radio Tuner Net 6.95
28 R 43027L FM Radio Tuner Net 12.95

108 Lafayette Cat. No. 720

*See Page 22 for Full Credit Details on Easy Pay Plan

Portable Solid-State Cassette Tape Recorders

NEW NORELCO 1420

NEW SONY TC-60

49⁹⁵
No Money Down*



With Carrying Case, Remote Control Microphone, Patch Cord and 60 Min. Cassette

• Battery Operated

Extremely lightweight—carry it everywhere! Records voice and music on 2 tracks at 1 7/8 IPS with perfect fidelity. Fully transistorized for instant playback. Easy to use. No tape threading, Semi-automatic cassette insert. Pushbutton cassette eject. Single master control starts, stops, and rewinds tape. Uses 5 "C" size flashlight cells. Recording level battery life meter. Size: 7 3/4"x4 1/2"x2 1/4". Imported.
27 R 48408L Shpg. wt., 4 lbs. Net 49.95

ACCESSORIES FOR MODEL 1420

Universal Car-Mount For Carry-Corder. Size 11 1/2"x3x5 1/2". Imported. Net 29.95
27 R 48150 Shpg. wt., 2 1/4 lbs. Net 29.95
99 R 62572 "C" Type Battery, 5 required Net .16
27 R 48085 117 VAC Adapter. wt., 8 oz. Net 6.95
BP2204 Recharge Ni-cad Battery Pack. Shpg. wt., 1 1/2 lbs. Net 24.95
27 R 48267 Net 24.95
Model TP 86 Telephone Pickup Coil. Shpg. wt., 5 oz. Net 7.95
27 R 48143 Net 7.95

49⁹⁵
No Money Down*



With Remote Control Microphone, 4 "C" Batteries, Carrying Case, Patch Cord, and Blank Cassette

• Battery or AC Operation

Popular priced cassette tape recorder with famous Sony performance and dependability. Operates on 4 "C" cell batteries (included) or 117 VAC. Pushbutton operation. Locking fast-forward and rewind buttons. Synomatic automatic recording control. Separate tone and volume controls. Record safety interlock button. Solid-state circuitry. 7 transistors, 3 diodes. 2 1/2" dynamic speaker. Size: 5 1/2"x2 3/4"x9 3/4". Imported. Shpg. wt. 5 lbs. Net 49.95
27 R 60635L No Money Down* Net 49.95
99 R 62572 Extra "C" Batteries—4 req. Net ea. .16
28 R 01223 Lafayette 60 minute tape Cassette Net .99

NEW HITACHI TRQ-286

AMPEX MICRO-14

Battery or AC Operation



With Remote Control, Mike, Batteries, Blank Cassette and Earphone

69⁹⁵

- 3 Digit Tape Counter
- Built-in Condenser Mike
- Levelmatic Circuitry
- VU Record Meter

Highly sensitive cassette tape recorder operates on 4 "C" batteries (included) or 117 VAC with built-in AC line cord. Many outstanding features: built-in condenser mike or accessory remote control microphone; automatic record level circuitry (levelmatic); 3 digit tape counter; piano key type pushbutton for record, playback, stop, fast forward, rewind, and eject; VU level meter, and rotary tone control. Large 4" speaker. Size 10 1/4"x2 3/4"x7 1/4". Imported. Shpg. wt., 7 lbs. Net 69.95
27 R 23088L No Money Down* Net 69.95
99 R 62572 Extra "C" Batteries—4 req. Net ea. .16



With Carrying Case, Earphone, and Six 60 Minute Tape Cassettes

79⁹⁵
No Money Down*

- Battery or AC Operation
- Built-in Ni-Cad Battery Recharger
- Unique "Floating Mike"

Deluxe performing portable cassette recorder. Operates on 4 "C" batteries, 117 VAC, or in your car with optional adapter. Built-in Auto-Charge Circuit automatically recharges Ni-Cad Batteries. 6 pushbutton function controls. "Floating" mike plugs into Micro 14 or removes for use as regular remote control mike. Record level/battery condition meter. Switchable Automatic Record Level Control. Separate Tone control. Size: 2 3/4" x 5 3/4" x 9". Imported.
27 R 25554L Shpg. wt., 9 1/4 lbs. Net 79.95
27 R 25513 12 DC Car Adapter Wt., 3/4 lb. Net 17.95
99 R 62572 "C" type Batteries (4 req.) Wt., 4 oz. Net ea. .16
32 R 48887 "C" type Ni-Cad (4 req.) Wt., 5 oz. Net ea. 3.90

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 109

Deluxe Portable and Miniature Solid-State Cassette Recorders

NEW!

**Concord F-26 AC/DC
Miniature Cassette Recorder**



59⁷⁹

with AC
Adapter and
Blank cas-
sette

- Built-in Condenser Microphone
- Pause Control
- Automatic or Manual Record Level

Hardly larger than a cassette and the three "C" batteries that power it, the F-26 recorder uses Integrated Circuits (IC's) for extreme reliability. High-sensitivity condenser microphone is built right into the die-cast case. Features: Pause control in the record mode; Automatic level control—a must for speech and conference recording; Manual record level control and Servo-drive motor for optimum performance. Batteries disconnect automatically when you plug in the external AC adapter supplied. Input: Auxiliary; Output: Earphone; Size: 4½x7¼x2¼"D. Imported.

27 R 35439L No Money Down* Shpg. wt., 2½ lbs. Net 59.79
99 R 62572 "C" Batteries for F-26: 3 required Net ea. .16
28 R 01223 Lafayette 60 min. Blank Cassette Net .99

NEW!

**Sharp RD-428U Pocket
Portable Cassette Tape Recorder**



69⁹⁵

with
4 "AA" Batteries,
Nickel Cadmium
Battery Pack, AC
Adapter, Remote
Control Cord,
Blank Cassette

- Built-in Con-
denser Mike
- Battery/Level
Meter
- Automatic Level Control

Small enough to fit into your jacket pocket, this deluxe solid-state recorder features advanced integrated circuitry. Built-in condenser mike for quick, easy recording. Automatic Level Control for uniform recording at every sound level. "One-touch" pushbutton controls. Remote control cord for convenient start/stop operation, 2¼" dynamic speaker. Electronic governor controlled DC motor. Battery/level meter. Earphone jack. Speed: 1½. Includes nickel cadmium battery pack, 4 "AA" batteries, and AC adapter. Imported. Size: 6¼x4¼x1½"D.

27 R 22015L No Money Down* Shpg. wt., 2 lbs. Net 69.95
99 R 62580 Extra "AA" Batteries—4 req. Net ea. .10
28 R 01223 Lafayette 60 min. Blank Cassette Net .99

NEW!

**Sony/Superscope TC-40 Miniature
Battery Operated Cassette-Corder**



99⁵⁰

with
Remote on/off
Switch Ear-
phone, Case, 4
"AA" Batteries

- Built-in Condenser Microphone

Fine performing miniature cassette recorder. Small enough to fit snugly into one's hand, or attaché case. Features built-in condenser microphone, record level and battery strength indicator, accessory remote on/off switch (included), Sonymatic Recording control, built-in dynamic speaker. Operates in any carrying position. Dual-differential balanced flywheels eliminates variations in tape speed when TC-40 is being carried. Tape speed: 1½ IPS. Size: 1¾x7¼x4¾"D. Shpg. wt., 2½ lbs. Imported.

27 R 60593L No Money Down* Net 99.50
Model AK-2 Rechargeable Ni-Cad Battery/AC Adapter. Wt., 1 lb.
27 R 60601 Net 27.95
28 R 01223 Lafayette 60 Minute Blank Cassette Net .99

NEW!

**Deluxe Sony/Superscope 110A
AC/DC Cassette-Corder**



119⁹⁵

with
Remote Control
Microphone,
Carrying Case,
Earphone, Patch
Cord, 4 "C" Bat-
teries, 1 Blank
Cassette

- Built-in Condenser Microphone

Improved version of Sony's best selling Model 110. Has a built-in condenser microphone. Also, is handy for dictation purposes, since it includes a remote start/stop microphone. A Back-Space Review Button and three-digit tape counter make it easy to transcribe cassettes. Features locking fast-forward and rewind buttons, Sonymatic Recording Level, separate tone and volume controls, extended range speaker, and built-in recharging circuit for optional BP-9 Nickel Cadmium Battery Pack. Tape Speed 1½ IPS. Size: 5¾x2½x9½"D. Imported.

27 R 60643L Shpg. wt., 5 lbs. No Money Down* Net 119.95
BP-9 Nickel Cadmium Rechargeable Battery Pack. Wt., 1 lb.
27 R 60221 Net 14.95


Solid-State AM/FM Radio Cassette Recorders and Car Players

NEW! HITACHI KCT 1210 Battery/AC AM/FM Cassette Radio Recorder

- Includes: Dynamic Microphone, 60 Minute Tape Cassette, Earphone, and AC Line Cord

Convenient, portable AM/FM radio and cassette tape recorder/ player let's you take your favorite music with you—anywhere. Operates on 110 VAC or 4 optional "D" batteries. Solid-state circuitry and silicon transistors ensure crisp, clear reception, permits direct radio recording. "Levelmatic" circuitry adjusts sound to best recording level. Also features continuous tone control, speaker on/off switch, and 6 pushbutton cassette functions: record, play, stop, re-wind, fast forward, and reject. Battery replacement meter. Size: 12W x 8 1/4H x 3 3/8" Imported, Less Batteries, Shpg. wt., 8 lbs.
27 R 24293L Net 69.95
99 R 62564 'D' battery for above (4 req.) Net ea. .18

ONLY
69⁹⁵
No Money Down*



NEW! CONCORD F104 Battery/AC FM/AM Cassette Radio Recorder

- Built-in Condenser Microphone
- Includes AC Line Cord, and Blank Tape Cassette

Magnificent performing 5 watt AM/FM Radiorecorder combines a highly sensitive AM/FM radio and a convenient cassette tape recorder in one handsomely styled compact unit. Operates on 117 V, 60 Hz AC, or 6 'C' batteries (not included) for true portability. Features AFC on FM for drift-free direct radio recording. Calibrated VU level/battery check and switchable automatic level control for distortion-free recording. Built-in condenser microphone plus jack for external microphone. Pushbutton tape controls plus level and tone controls. Has built-in AM and telescoping FM antennas. Size: 11 3/4 x 10 1/2H x 3 3/4"D. Imported.
27 R 35413L Shpg. wt., 7 lbs. Net 79.95
CA-18 12 Volt Car Adapter. Shpg. wt., 1 lb.
27 R 35421 Net 7.95
99 R 62572 'C' batteries for above (6 req.) Net ea. .16

ONLY
79⁹⁵
No Money Down*



NEW! PANASONIC RF 7280 Cassette Recorder with AM/FM/Weather Band Radio

- Includes: Remote Control Mike and Stand, Pre-recorded Cassette, Batteries and Earphone.

Operates from any 6 or 12 volt car battery with optional accessory mounting bracket, or as a portable with 4 'D' batteries (included), or on 117 V., 60Hz AC with optional 117 VAC adapter. Built-in FM and AM antennas, 6 x 4" dynamic speaker. AFC on FM. Continuous bass/treble tone control. Pretuned 162.55 MHz. weather band gives 24 hour weather information. Built-in cassette recorder features pushbutton controls, recording level control, sound monitor system, and earphone/external speaker jack. With earphone. Size: 10 1/2 x 10 3/4H x 3 1/2"D. Imported.
27 R 12297L Shpg. wt., 10 lbs. Net 99.95
27 R 12305 Car Bracket. Shpg. wt., 4 lbs. Net 19.95
27 R 12313 AC Adapter. Shpg. wt., 6 oz. Net 9.95

ONLY
99⁹⁵
No Money Down*



DELUXE Ampex Micro 44 Solid-State Car Stereo Cassette Player with FM/FM Stereo Radio

- Simple Push-in Slot Loading Of Cassette Tapes
- Automatic Eject and Turn-Off At End Of Tape
- FM Stereo Indicator Light

Enjoy the convenience of stereo cassette tapes in your car . . . plus the luxury of standard FM and FM Stereo broadcasts from one compact unit. Features fully automatic operation; fast slot load "Star System"; single lever function control for Eject/Off, Fast Forward and Rewind; illuminated FM tuning dial; stereo indicator light; AFC, Local/Long distant switch and Mono/Stereo FM reception. Thumb-wheel control for Volume, Balance, Tone and FM tuning. Has built-in noise suppression filters. 20-watts output power. Response: 40-15,000 Hz Radio; 40-10,000 Hz Tape. Sensitivity (FM); 4 μ V. For 12V., neg/grnd., car system. Size: 9 1/2 x 5 1/4 x 4 1/2". Imported.
17 R 57012WX Shpg. wt., 12 lbs. No Money Down* Net 169.95
Deluxe Set of 2-Lafayette Rear Deck Matched Speakers. Imported.
99 R 62986 Shpg. wt., 3 lbs. Net 9.95

169⁹⁵

With Universal Mounting Bracket, Wiring Harness and Antenna Adapter Cable



*See Page 22 for Full Credit Details on Easy Pay Plan

Solid-State Stereo Cassette Players and Recorders for the Car

HITACHI TRQ-206 CAR/PORTABLE CASSETTE PLAYER/RECORDER



AMPEX MICRO-42 CAR CASSETTE STEREO TAPE PLAYER/RECORDER



99⁹⁵
Less Speakers.

Includes Mounting Bracket with Lock and Key, Connecting Cable, Remote Control Microphone, Power Cord, Demonstration Tape

- 3-Way Operation—AC, Battery, or Car Battery
- Stereo Playback in the Car and Home Using Optional Speakers
- Monaural Record/Playback

Sensational and versatile cassette tape system. Features special bracket for auto mounting with lock and key included for 12 volt DC Neg. ground systems. Removable for use as a portable with its own batteries (operates on 8 "C" Cells not included)—or operates in the home on 117VAC 60 Hz. Built-in wide range speaker. Semi-slot tape loading. Automatic stop and eject. Fast Forward and rewind. Separate Tone and balance controls. External speaker jacks for stereo. Size 9 $\frac{1}{2}$ " x 3 $\frac{1}{8}$ " x 10 $\frac{1}{2}$ ". Imported. Shpg. wt., 8 $\frac{1}{2}$ lbs.

27 R 23054W No Money Down* Net 99.95

Deluxe Set of 2 Rear Deck Matched Speaker Systems. Imported. 99 R 62986 Shpg. wt., 3 lbs. Imported. Net 9.95
99 R 62572 "C" Batteries—8 Req. Wt. 1 lb. Net ea. .16

SONY/SUPERSCOPE TC-20 CAR STEREO CASSETTE PLAYER



99⁹⁵

With Mounting Hardware, Head Cleaning Pencil Less Speakers

- Automatic Cassette Eject
- Tone Control
- Pushbutton Operation
- 12 Watts RMS Output

Deluxe stereo playback car cassette system. Features single action "Letter-Box loading." Provides instant playback at a power output of 12-watts RMS. Cassettes can be ejected either automatically or manually. Has push-button Fast-Forward* and "Rewind"; Volume, Stereo Balance, and Tone controls. SPECIFICATIONS: Frequency Response 50-10,000 Hz; Wow/Flutter 0.28%; Signal-to-Noise Ratio 45 db; Tape Speed 1 $\frac{1}{2}$ ips. Switchable for negative or positive ground 12VDC electrical systems. Complete with mounting bracket, hardware and head cleaning pencil. Size: 7 $\frac{1}{2}$ " x 2 $\frac{1}{8}$ " x 8 $\frac{1}{4}$ ". Imported. Shpg. wt., 8 lbs.

17 R 50017W No Money Down* Net 99.95

Deluxe Set of 2-Rear Deck Matched Speaker Systems. Imported. 99 R 62986 Shpg. wt., 3 lbs. Net 9.95

NEW LOW PRICE

79⁹⁵
Less Speakers

With All Mounting Hardware, and Remote Control Mike

- Makes Recordings in Your Car
- 20-Watts Peak Music Power
- Unique Slide-Out Storage Tray

Enjoy your favorite cassettes in your automobile. Instant playback of all prerecorded stereo and monaural cassette tapes, plus instant monaural record with remote control mike supplied. Gives you 20-watts music power. Uses slot load system for fast, easy loading. Automatic eject at end of tape. Recessed pushbutton function controls: Fast-Forward, Rewind plus drum-style Volume and Tone controls. Has pilot light and separate record indicator light. Slim-line style blends with any car interior. Slide-out storage tray holds microphone and 4-cassette tapes. For 12VDC negative ground systems. Mounting bracket and all hardware supplied. Size: 9 $\frac{1}{4}$ " x 4 $\frac{1}{4}$ " x 9"D. Shpg. wt., 11 lbs.

17 R 57004W No Money Down* Net 79.95

Deluxe Set of 2-Rear Deck Matched Speaker Systems. Imported. 99 R 62986 Shpg. wt., 3 lbs. Net 9.95

NEW TEAC AC-7 Automatic Reversing Car Stereo Cassette Player



129⁵⁰

with Mounting Hardware, Demo Tape, Less Speakers

- Continuous Playback
- Servo Controlled Drive Motor
- Continuous Tone Control
- Power Output 12 Watts

Provides continuous playback in both directions—automatically reverses at the end of tape. Features advanced solid-state circuitry; servo controlled drive motor; separate volume, tone, and balance controls; stop and cassette ejection button, forward play button, reverse play button, and unique and easy cassette loading system. Ready-to-play light. For 12 volt negative ground systems. Power Output: 12 watts. Wow and flutter 0.25%. Tape speed 1 $\frac{1}{2}$ ips. Response 40-10,000 Hz. Includes mounting hardware. Size: 9W x 7 $\frac{1}{2}$ x 2 $\frac{3}{4}$ " H. Imported. Shpg. wt., 8 lbs. Less Speakers.

17 R 35000W No Money Down* Net 129.50

Deluxe Set of 2-Rear Deck Matched Speaker Systems. Imported. 99 R 62986 Net 9.95

Solid-State Stereo Record/Playback Cassette Tape Decks

Sony Superscope TC 127 Cassette Tape Deck



149⁹⁵

- 2 Record VU Level Meters
- 3 Digit Tape Counter
- Lockable Fast Forward and Rewind Buttons

Record and playback stereo or mono cassette tapes through your home music system with this quality stereo tape deck. Features Sonymatic automatic gain control with a manual record defeat complete with limiter circuit. Includes 7 pushbutton controls: eject, fast forward, stop, play, rewind, record, and pause for editing. 2 VU record level meters, stereo headphone jack, variable line output. Specifications: Freq. Response: 30-12,000 Hz, S/N Ratio: 49 db. Inputs: 2 mike, 2 Aux. Outputs 2 line, 1 headphone, mike input impedance 600 ohms. Size: 15 $\frac{3}{4}$ x3 $\frac{7}{8}$ x8 $\frac{5}{8}$ ". Less microphone. For 117 VAC 60 Hz. Imported. Shpg. wt., 16 lbs.

27 R 60544W No Money Down* Net 149.95

NEW Sony Superscope TC-160 Deluxe Cassette Tape Deck



199⁹⁵

- Calibrated Illuminated VU-Meters
- 3-Digit Tape Counter
- Low Noise FET Circuitry

TC-160's fine features include straight-line record level controls, low-noise FET circuitry, built-in peak limiter for distortion-free recording, tape select switch for standard and new Chromium Dioxide cassettes, long-wearing high-performance heads with 1.5 Micron gap, stereo headphone jack with two-position headphone level switch, three-digit tape counter, calibrated illuminated VU meters, automatic eject. SPECIFICATIONS: Response, 20-16,000 Hz, Wow & Flutter 0.1%; Signal-to-Noise Ratio 49db; 2 low impedance mike inputs; 2 Aux inputs. Walnut wood base. Size: 15 $\frac{3}{4}$ Wx5Hx10 $\frac{7}{8}$ "D. For 117 VAC, 60 Hz. Imported. Shpg. wt., 17 $\frac{1}{2}$ lbs.

27 R 60627W No Money Down* Net 199.95

NEW Concord Mark IX Dolby Cassette Deck with Endmatic




249⁹⁵

- Dolby Noise Reduction System
- CrO₂/Standard Tape Selector
- Two Elevating VU-Meters
- 3 Microphone Inputs

Professional quality Mark IX is designed for use with both conventional and the new chromium dioxide tape cassettes, with switch-selected bias. And it has Dolby noise reduction built-in, with its own pushbutton control and indicator light, and a tape head with an ultra-narrow 1 micron gap. The Mark IX is built like a recording console in miniature. Professional sliders on its sloping front panel give you individual control over input and output levels in each channel. And a fifth control over input and output levels in each channel. And a fifth control over input and output levels in each channel. "Endmatic" feature disengages tape and transport when each cassette ends to prevent uneven wear and tension. SPECIFICATIONS: Wow and Flutter less than 0.2% rms; Freq. Response 30-15,000 Hz; Signal-to-Noise Ratio better than 50db; Overall distortion less than 1.5%. Bias Frequency over 100 kHz; Channel Separation better than 35db. Inputs: Three microphone; High level and low level jacks; Outputs: Stereo line, headphone. For 117 VAC, 60 Hz. Size: 16Wx4 $\frac{1}{2}$ Hx10 $\frac{1}{8}$ "D. Includes 4 patchcords. Imported. Shpg. wt., 15 lbs.

27 R 35405WX No Money Down* Net 249.95

NEW Professional Teac 360 Dolby Cassette Tape Deck



279⁹⁵

- Dolby Noise Reduction System
- 4 Linear Record Level/Output Controls
- Expanded Scale VU-Meters
- Peak Recording Level Indicator

The Teac 360 stereo cassette deck incorporates the Dolby system for both record and playback functions. Developed specifically for home tape recording, it dramatically reduces inherent noise and hiss in the recording process without altering the musical integrity of the recorded signal. The 360 utilizes a MIC/Line selector switch. When recording from a tuner or aux source, the signal is fed directly to the Dolby circuitry, bypassing the mike preamplifiers. Outstanding features: Unique peak recording level indicator, expanded scale VU-meters, automatic end sensor/automatic shut off mechanism, 4 linear record level/output controls, hysteresis synchronous outer rotor motor, 4-digit tape counter, and complete compatibility for conventional, high density, high energy, or Grolyn tapes. SPECIFICATIONS: Wow and Flutter 0.13%, Freq. response 30-13,000 Hz \pm 3db measured at -20db. Signal-to-Noise Ratio 50db, 58db (with Dolby process). Inputs—mike: 600 ohms, line 0.1V, Output 0.3V. For 117 VAC, 60 Hz. Walnut wood base. Size: 4 $\frac{3}{8}$ Hx16 $\frac{1}{4}$ Wx9 $\frac{7}{8}$ "D. Imported. Shpg. wt., 14 lbs.


27 R 15100WX No Money Down* Net 279.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 113

SOLID STATE CASSETTE STEREO TAPE RECORDERS

HITACHI TRQ-232 Portable Battery/Electric 4-Track Stereo Cassette Recorder



99⁹⁵


INCLUDING
1 Dynamic Mike
with Remote
Control Switch,
Demo Tape, AC
Power Cord.

- Operates on 6 "D" Batteries or 117 VAC House Current
- Detachable Swing Out Speakers
- Large Twin VU Record Level Meters
- Separate Slide Controls For Volume And Tone

Enjoy Convenient stereo recording and playback anywhere—indoors or outdoors. Operates on 117 60 Hz. AC, house current, or on standard "D" type flashlight batteries (not included). Two swing-out extension cabinets each contain a 5" speaker. Provides excellent stereo sound reproduction and full dimensional stereo separation. Features "Levematic" (automatic record level control). Also has: speaker ON/OFF monitor switch; pushbutton cassette controls;

two record level VU meters and remote control jack. Frequency Response: 100 to 10,000 Hz. Speed; 1 1/2 ips. Instant-on solid state circuitry. Size: 11 x 6 1/4 x 8 3/4". Imported. Shpg. wt., 14 lbs.
27 R 23070W No Money Down* Net 99.95
"D" Batteries for above (6 req.)
99 R 62564 Net ea. .18
28 R 01223 60 Minute Blank Cassette Tape Net .99

PANASONIC. RF7490 FM/AM/FM Stereo Portable Radio Cassette Recorder



149⁹⁵

With 6 "D"
batteries, remote
control mike,
earphone and
pre-recorded
tape cassette

- Operates on 6 "D" Batteries or 117 VAC House Current
- VU/Battery/Stereo Meter
- Continuous Tone Control
- Two 6" Wide-Range Speakers

Its unique twin-case fold-away concept with hide-away carrying handle offers the ultimate in portable stereo radio/cassette entertainment. The Radio's separate FM and AM tuning dials permit accurate station selection on both bands. AFC on FM locks in signal for crystal clear, drift-free reception. Two 6" wide-range speakers deliver excellent sound with full tonal range most pleasing to your ear. The "tri-Purpose" meter tells you when you are precisely tuned, also functions as a VU meter, and as a battery drain indicator. Built-

in stereo cassette recorder features push-button controls, and easy-change cassette pop-up for easy and convenient operation. Input for plugging in a record changer. Instant on Solid State circuitry for extreme reliability and constant high-level performance. Size: 13 1/2 x 11 x 5". Imported. Shpg. wt., 13 lbs.
27 R 12263W No Money Down* Net 149.95
99 R 62564 Extra "D" batteries—6 req. Net ea. .18

Deluxe AMPEX 87R Modular AM/FM/FM Stereo Cassette Recorder System

Beautiful walnut wood and smoked plexi-glass cabinet houses a stereo cassette tape player/recorder, FM Stereo/FM/AM tuner, and stereo control center with 50 watts of peak music power. Positouch cassette function controls and velvet-touch sliding volume, bass, and treble controls give you professional operating control with maximum ease of use. Each matching walnut grained speaker system contains a 6" x 9" dual cone speaker. The 87R features switchable automatic record level control, 2VU illuminated record meters, inputs for magnetic phono and a 3 digit tape counter. Size: Recorder Unit: 16 1/4" x 10 1/4" x 5 3/4"; Speakers—14 1/2" x 9" x 7 1/4". Imported. Shpg. wt., 44 lbs. No Money Down*
27 R 25588WUX Net 269.95



269⁹⁵

With 2 dynamic mikes,
and a demonstration tape

FREE

With Purchase of BSR

Deluxe BSR 4-Speed Automatic Turntable with Base, Dust Cover, and Shure Magnetic Cartridge

When you purchase the AmpeX 87R you will receive a certificate. Attach your warranty card to this certificate and mail both direct to AmpeX. Enclose \$5.00 to cover postage and handling—and AmpeX will ship a deluxe BSR 4-Speed Automatic Turntable Ensemble directly to your home.

Duration of special offer subject to manufacturers withdrawal without prior notice.



BSR Changer Ensemble

Reel-to-Reel Tape Recorders and Accessories

Sony/Superscope 252 Solid-State Stereo Tape Recorder



219⁹⁵ with 2 F-25
Cardioid mikes

- 4 Digit Tape Counter
- Pause Control with Lock
- Stereo Headphone Monitor Jack
- Front Panel Sound-on-Sound Controls

Complete portable solid-state 4-Track stereo tape system. Offers many deluxe features: sound-with-sound, sound-on-sound, built-in amplifiers, and 2 full-range lid-integrated stereo speakers that provide exceptionally rich, beautiful sound. Take reels up to 7". 3-speeds: 1 1/2, 3 1/4, 7 1/2 IPS. Vibration free motor. Stereo headphone jack. 2 record VU level meters, 4-digit tape counter, Retractable pinch roller, and non-magnetizing record head. Power Output, 12-watts IHF. Inputs 2 AUX. (100K ohms), 2 mike (600 ohms). Response 30 to 18,000 Hz @ 7 1/2 IPS. S/N ratio 50 db. Size 16 1/2" W x 10 1/4" H x 15" D. For 117 VAC 60 Hz. Imported. Shpg. wt., 33 1/2 lbs. 27 R 60585WX No Money Down* Net 219.95

- Mike and Line Mixing
- 2 VU Meters

Sony/Superscope 330 Solid-State Reel and Cassette Recorder




349⁹⁵

includes 2 dynamic mikes,
2 stereo patch cords,
7" empty reel,
and 30 minute tape cassette.

Sony/Superscope 330 Solid-State Stereo Reel and Cassette Recorder. The versatile 330 offers the best of both reel-to-reel and cassette recording in one portable unit! At the flip of a switch, you can record and playback on either a stereo Cassette-Recorder or a reel-to-reel tape deck, or record from reel-to-reel to cassette and vice versa. With the addition of a tuner and record changer, the 330 is the heart of one of the most complete stereo systems you can buy. 2 wide range lid-type speaker systems are detachable for true stereo separation. Two separate illuminated VU meters, separate tape counters for reel and cassette, front microphone jacks, speaker monitor switch, individual right and left channel volume controls, pushbutton cassette controls. Freq. Response Reel: 30 to 18,000 Hz 7 1/2 ips, cassette: 50-10,000 Hz. Inputs: 2 mike, 2 aux., 2 mag. phone. S/N Ratio-Reel: 50 db, cassette: 45 db. Size: 21 1/4" x 11 1/4". For 117 VAC, 60 Hz. Imported. Shpg. wt., 53 lbs. 27 R 60577WX No Money Down* 349.95

New Concord and TEAC Dolby Equalizers

**NEW Concord DBA-10 Dolby
Tape Adapter**



**ONLY
99⁷⁹**

- Lowers Noise—Provides An Extra 10db of Usable Dynamic Range
- 2 VU Record Meters
- Built-in Calibration Tone—Eliminates Need For External Calibration Tape

Reduces high frequency noise and hiss that plagues wide-range open reel, cassette, and 8-track recording at low speeds by 90%. Can be added to any tape deck or any self-contained recorder with audio inputs and outputs. Includes line inputs, calibration meter, and all controls necessary to Dolbyize tapes. Specs: Input Impedance: 47 k ohms, Input Sensitivity: 30 mV, Output Voltage: 0.58 V (adjustable), Output Impedance: 5,000 ohms, Frequency Response: 20-20,000 Hz \pm 0.5db, Harmonic Distortion: Less than 0.4%, Noise Reduction: 8 db @ 5,000 Hz. Sizes: 13 1/2 x 3 1/2 x 7 1/4" H. 117 VAC, 60 Hz. Includes 4 patchcords. Imported. 27 R 35264W No Money Down* Wt., 5 3/4 lbs. Net 99.79

**NEW TEAC AN-50 Dolby
Noise Reduction Unit**



**ONLY
49⁵⁰**

- Lowers Noise Level 90% (10db)
- 20-15,000 Hz \pm 1.5db
- Does Not Require External Calibration Tape
- For Use With Cassette, Open Reel, or 8-Track Recorders

Compact low priced DOLBY NOISE Reduction unit. Recommended for use with low priced stereo recorders or tape decks with audio inputs and outputs. Reduces high frequency noise at low speeds by 90%. Controls: separate left and right record levels. Switches: Record Calibrate (In/Out), Mode (Rec/Play), Dolby (In/Out), and Power (On/Off). SPECIFICATIONS: Input Sensitivity: 30 mV, Input Impedance: 35K ohms or greater, Output Level: 1 V, S/N Ratio: 65db or better, Increased S/N Ratio: 10 kHz-10db. Power requirements 117 VAC, 60 Hz. Power consumption 4 Watts. Imported. Shpg. wt., 3 1/2 lbs. 27 R 15126 No Money Down* Net 49.50

*See Page 22 for Full Credit Details on Easy Pay Plan

Solid-State 2-Channel Reel-To-Reel Stereo Tape Decks

Sony/Superscope 252-D
Stereo Record/Playback Tape Deck



139⁹⁵

• With Two Patch Cords

Walnut Wood Base

Fine performing stereo tape deck. With self contained solid-state stereo preamplifiers for the recording and playback of 4-track stereo and 4-track mono thru your home hi-fi system. Two speeds: 7½ or 3¾ IPS. Vertical or horizontal operation. Features: sound with sound mixing, dual VU recording level meters, 3 digit tape counter, vibration free motor, stereo headphone monitor jack, single knob control, automatic tape lifter, scrape flutter filter, record interlock, non-magnetizing record head and automatic shut off. Specifications: Takes reels up to 7". Freq. res.: 30-18,000 Hz @ 7½ IPS, 40-13,000 Hz @ 3¾ IPS, Wow/flutter 0.12% @ 7½ IPS, 0.15% @ 3¾ IPS. Signal-to-Noise ratio: 52 db. Size and weight: 15¼" x 7½" x 13¾". 18 lbs. Imported. For 117 VAC 60 Hz. Shpg. wt., 20¼ lbs. 27 R 60568W No Money Down* Net 139.95

27 R 60379—F98 Mike for 252-D-1 lb. Net 13.50

Sony/Superscope 352D 3 Head
3 Speed Stereo Record/Playback Tape Deck



179⁵⁰

Walnut Wood Base

Deluxe 3-head four track solid state stereo/mono, record, and playback tape deck featuring sound-on-sound—Multiple recordings may be produced by combining new material with previously recorded material on a separate track. Other desirable features are tape and source monitor switches, dual VU record level meters, 4-digit tape counter, pause control, retracto-matic pinch roller stereo headphone monitor jack, and single function tape control knob. Specifications: Takes reels up to 7". 3 Speed—1½, 3¾, 7½ IPS. Freq. res.: 30 to 20,000 Hz @ 7½ IPS, Wow and flutter 0.12% @ 7½ IPS, S/N ratio 52 db @ 7½ IPS. Inputs—2 mike (600 ohms) 2 Aux. Outputs —2 line 1 headphone. Size: 15¾" x 7½" x 13¾". For 117 VAC, 60 Hz. Imported. Shpg. wt., 30 lbs. 27 R 60551WX No Money Down* Net 179.50

27 R 60379 F98 Mike for 352-D Wt., 1 lb. Net 13.50

KLH Model 41 Dolby System
3 Head Stereo Record/Playback Tape Deck



199⁹⁵

Walnut Wood Base

Designed to make wide-range, noise-free recordings utilizing the Dolby Noise Reduction System. The signal-to-noise ratio at 3¾ IPS is 66 db, @ 7½ IPS is 68 db. With the Model 41 you can record the most demanding musical source material at 3¾ IPS—doubling the amount of playing time of any reel of tape. Features: 4 track stereo record/playback, 2 record VU level meters, 4 digit tape counter, single tape function control for rewind, stop, play, pause, and fast forward. Specifications: Takes reels up to 7". Tape Speeds, 3¾, 7½, 1½ IPS, separate erase, record, and playback heads. Input sensitivity: for "0" VU level—Mic. 0.5 mV, Hi-Aux—500 mV, Lo-Aux 160 mV. Output level 2.5V RMS. Bias Frequency—Nominally 110,000 Hz. Freq. Response @ 3¾ IPS—50 Hz to 12,000 Hz ±3 db, @ 7½ IPS—50 Hz to 15,000 Hz ±3 db. Size: 11¼"D x 14¼"W x 5¾"H. Shpg. wt., 22 lbs. For 117 VAC 60 Hz. 27 R 45024W No Money Down* Net 199.95

116 Lafayette Cat. No. 720

NEW Professional TEAC-H1230 3 Head
Stereo Record/Playback Tape Deck



349⁹⁵

Walnut Side Panels

Professional 2 channel record/playback stereo tape deck with many outstanding features: dual bias position switch, front panel pause control, 3-motor drive system, Edi-Q system for editing and cueing, built-in mike and line mixer, dual speed hysteresis-synchronous capacitor motor, and reel table height adjustment. Specifications: Tape speed 7½ IPS, 3¾ IPS. Three, 4 track, 2 channel, stereo or monaural; erase, record and playback heads. Signal-to-noise ratio, 50db. Frequency response at 7½ ips is 30-22 kHz., at 3¾ ips is 30-16 kHz. Output; 0.3V, for load impedance of 10K ohms or more. Input; Mike —10K ohms, 0.3mV minimum, Line—100K ohms, 0.1V minimum. 100 to 240 VAC, 50/60 Hz. 14½"H x 17¼"W x 8"D. Imported.

27 R 15068WX Shpg. wt., 47 lbs. No Money Down* Net 349.50

Model A1250—Same Specs and Features as above but includes Automatic Reverse.

27 R 15076WX Shpg. wt., 5 lbs. Net 449.95

*See Page 22 for Full Credit Details on Easy Pay Plan

4 & 2 Channel Reel Stereo Record/Playback Tape Decks

NEW! AKAI Model 1730-SSD

299⁹⁵

With
4" Channel
Demo Tape,
7" Takeup
Reel,
Connecting
Cables



- 4 Channel Stereo Record/Playback

Fine performing reel to reel tape deck has complete facilities for 4-track 4 and 2-channel stereo recording and playback. Connects to any 4-channel stereo receiver or amplifier with tape input or output jacks. Features: 4 heads—record/playback and two erase; Automatic shut-off control—the power of the entire unit is shut off when tape comes to the end or is broken; Front and rear headphone jacks; 2 twin VU meters; Pause control for editing; 4-digit index counter with reset button; and universal voltage selector. Specifications: Tape speed—7½ & 3¼ IPS. Frequency response—30 to 22,000 Hz. S/N Ratio—50 db. Recording Bias Frequency—100K Hz. 4-mic input jacks: 0.4 mV/30K. 4-line input jacks—40 mV/100K. Hysteresis synchronous 2-speed motor. For 100 to 240 VAC, 50/60 Hz. Size: 16½x18 x9½". Imported. Shpg. wt., 33 lbs. 27 R 56005WX No Money Down* Net 299.95

NEW! Panasonic RS-740US

399⁹⁵

With
7" Take up Reel,
Connecting Cables,
Reel Holders,
Splicing Tape



- 4 Channel Stereo Record/Playback

Record and playback your own 4-channel and 2-channel stereo reel-to-reel tapes thru your hi-fi system with this two-speed (7½ & 3¼) tape deck. Enjoy 4-channel sound from the growing catalog of pre-recorded tapes; or record from auxiliary 4-channel sources (there are 4-line inputs, one for each channel) or live by using the four microphone inputs. Features: Four separate record VU meters, Hot Pressed Ferrite heads, Automatic shut off at the end of the tape, 2 Stereo headphone outputs, 4-digit Tape counter, Tape Pause, Separate record level controls for channels 1-4. Specifications: Frequency Response 30—23,000 Hz. at 7½ IPS. Inputs: Mic. sensitivity, 0.56 mv, Line in 30 mv. Mike input impedance, 5K to 20K ohms. For AC 120 V, 60 Hz. Imported. Size: 15¼ x 16¾ x 8¾". Shpg. wt., 28¾ lbs. 27 R 12289WX No Money Down* Net 399.95

NEW! SONY/Superscope 366-4

499⁹⁵

With:
7" Take Up Reel,
Connecting Cables,
4 VU meters,
Record Equalization
Selector
Switch



- 4 Channel Stereo Record/Playback

High-quality Quadradial 2 and 4 channel record/playback stereo tape deck. Features: Automatic total-mechanism shut-off; Hyperbolic Heads which require no pressure pads; Tape/source monitoring; Record equalization selector switch; Vibration-free motor; Noise suppressor switch; Sound-on-sound capability; Servo-controlled back tension; Microphone/line mixing; Two stereo headphone monitor jacks; Mic. & aux. inputs. 4-digit tape counter; Specifications: 2-speeds: 3¾, 7½ IPS. Response @ 7½ IPS, 20—20,000 Hz. Max. reel size, 7". Bias frequency, 125 kHz. Signal-to-noise: std. tape, 52 db; Low input mike impedance. Wow & Flutter @ 7½ IPS, .09%. Handsome walnut base, slanted for easy operating convenience. Size: 17 x 18¾ x 9¾". For 117 VAC, 60 Hz. Imported. Shpg. wt., 43 lbs. 27 R 60619WX No Money Down* Net 499.95

PROFESSIONAL TEAC TCA-42

695⁰⁰

- 4 Channel Stereo Record/Playback
- 2 Channel 1/4 Track Stereo Record/Playback
- Automatic Reverse in 2 Channel Playback Mode



With Dust Cover
Connecting Cables,
and Empty 4"
Take Up Reel

Complete 2 and 4 channel record/playback facilities. 4 channel solid-state playback pre-amplifiers and built-in 4 channel stereo record pre-amplifiers are external (included). 4 large illuminated VU level meters. Professional mixing circuit for mike and line inputs. 4 digit index counter. Specifications: 100 kHz bias oscillator. Four heads: in-line play, in-line record, staggered erase. Reel size 7". Wow and flutter @ 7½ ips, 0.12% rms. Response: 50—15,000 Hz at 7½ IPS S/N ratio 50 db @ 7½ IPS. Inputs: 4 microphone: 10k ohms, 0.25 mv, 4 AUX: 100 ohms, 0.14V minimum. Output: 4 line, 1 volt rms. Tape speed: 7½ & 3¼ IPS. Size: 12 x 17½ x 7" (Tape Transport); 5½ x 17½ x 7" (Record Pre-amps). Imported. For 117 VAC 60 Hz. Shpg. wt., 73 lbs. 27 R 15043XY No Money Down* Net 695.00 27 R 15084Y Tape Transport Dust Cover 2 lbs. Net 20.00 27 R 15082Y Cradle (Stand) for Teac 42. 4 lbs. Net 14.50

4-Channel 8-Track Stereo Tape Cartridge Players

NEW! PANASONIC/LAFAYETTE 2 and 4 Channel 8 Track Stereo FM/AM/FM Music Systems



**Panasonic
RE7750 FM/AM/FM
Stereo Radio with
4-channel Amplifier System**

PANASONIC RE-7750 FM/AM/FM Stereo Radio Featuring Quadrasonic 4-Channel Amplifier and 4 Speakers. Play discrete 4-channel input sources such as a 4-channel 8-Track Tape Deck or a 4-channel reel deck thru the RE-7750. Also has Panasonic's quadruplex derived 4 channel circuitry built-in, 4-speaker sound separation from 2-channel sound sources. Each speaker enclosure has a 6½" air suspension speaker. Amplifier provides 40 watts of peak music power. Solid-State Circuitry. Built-in FM and AM antennas. Blackout and illuminated slide-rule tuning dial. FM Stereo indicator light. AFC on FM. Loudness control. Separate continuous tone controls for bass and treble. 4 separate slide lever volume controls. Output jacks for phono and 4 channel tape. External antenna and speaker terminals. In distinctive walnut wood cabinetry. Size: Amplifier, 4¾"x17½"x11¼", each speaker system 11¾"x8¾"x6¾". For 117 VAC, 60 Hz. Shpg. wt., 34 lbs. Imported. 17 R 31140WX No Money Down* Net 179.95

PANASONIC RE-7750 System and LAFAYETTE RK-48 2 and 4 channel 8 Track Stereo Tape Deck. Same as above but with 4 channel deck included to play new 4 channel 8 Track Stereo Tape Cartridges. (See page 3 for description of RK-48). Shpg. wt., 45 lbs. 99 R 92124WXM No Money Down* Net 269.90



**Lafayette RK-48
2 and 4-channel 8-Track
Stereo Tape Deck**

FM/AM/FM Stereo Radio
with 4-channel amplifier

179⁹⁵
including
4 speakers

FM/AM/FM Stereo Radio
with 2 and 4-channel
8-Track Stereo Tape Deck

269⁹⁰
including
4 speakers

NEW! Qaudio Compatible 2 and 4-Channel 8-Track Stereo Playback Sound System



229⁹⁵

featuring 4 Lafayette
Criterion 2x Speaker Systems

Provides a totally new dimension in stereo sound. The Qaudio Playback/Amplifier plays the new 4-Channel and 2-Channel 8-track Stereo Cartridges. 4-channel stereo tapes reproduce 4 separate sound tracks simultaneously—gives you complete multi-dimensional stereo. System comes with 4 Lafayette Criterion 2x Speaker Systems. (See page 56 for description of 2x's). All solid-state circuitry. Output has 80 watts of music power (20 per channel). Controls: volume, balance, rear balance, tone, bass, treble, channel select. Program and channel indicator lights, 4 play-back level meters. Size of Playback/Amplifier 18¾"Wx5½"Hx9¾"D. Imported. For 117 VAC 60 Hz. 99 R 99939WXM Shpg. wt., 76 lbs. No Money Down* Net 229.95

QAUDIO 2 and 4-CHANNEL STEREO PLAYBACK AMPLIFIER only (less speakers). 27 R 52004WX Shpg. wt., 38 lbs. No Money Down* Net 169.95

4 Channel Stereo
For the Car



129⁹⁵
less Speakers

Compatible 4 and 2-channel 8-Track Stereo Cartridge Playback Tape Player for the Car. Listen to the magnificent sound of 4-channel stereo in your car. Also plays conventional 2-channel 8 Track Stereo Tapes. For 12V. negative ground systems. Separate controls for volume, balance, tone, program shifter, and channel selector. Program and channel indicator lights. Comes less speakers. Includes mounting hardware. Size: 11½"x9"x3". Imported. Shpg. wt., 9 lbs. No Money Down* Net 129.95

17 R 36008WX Net 129.95
Custom Indoor Set of 4 Speakers and Matching Grills.
99 R 62861 Net 8.95

SEE Page 3 for Selection of 4-channel 8 Track Stereo Tape Cartridges.

Compatible 2 and 4 Channel 8 Track

STEREO TAPE PLAYERS

Fisher CP-100 2 and 4 Channel 8 Track Solid State Stereo Tape Deck



NEW

- Compatible—Plays both 2 and 4 Channel 8 Track Stereo Tape Cartridges

169⁹⁵

Plays both 4-channel and 2-channel eight-track tape cartridges. Can be used to convert your present stereo playback system to a discrete 4-channel system with the addition of a stereo amplifier and two speakers . . . or it can be hooked up to a 4-channel AM/FM stereo receiver or amplifier such as the Lafayette LR-440, LA-44, LA-2525, or the Fisher 701 and 601. The CP-100 automatically switches to the correct mode (2 or 4 channel) indicated by red jewel lights. It has three program controls: REPEAT—the same program played repeatedly; CHANGE—advance to the next program each time you push the button, with your selection indicated by a corresponding numbered red jewel light; CONSEC—plays continuously through all the programs and returns to the beginning. Specifications: Plays—8-track/2 & 4 channel, Frequency Response, 50-12,000 Hz., Tape Speed, 3 $\frac{3}{4}$ ips, Size: 4 $\frac{5}{8}$ x 10 $\frac{1}{2}$ x 10 $\frac{1}{4}$ inches. For 117 VAC 60 Hz. Shpg. wt., 10 lbs. 27 R 3302WX No Money Down* Net 169.95

Fisher TX-420 2 and 4 Channel 8-Track Solid State Stereo Converter



NEW

- 2 and 4 Channel 8-Track Tape Cartridge Player With Self-Contained Stereo Amplifier

299⁹⁵


By addition of just two speakers and the Model TX-420, all types of existing stereo arrangements—component systems, consoles or compacts—can be turned into discrete 4-channel systems. The TX-420 Converter is compatible with units now on the market and plays both 4-channel and standard 2-channel 8-track tape cartridges. In addition, it has input facilities for other 4-channel or 2 channel sources. TX-420 is rated at 50 watts total music power or 15 watts RMS per channel. Features front panel mounted volume, bass, treble and balance controls. Red jewel lights on the front of the walnut finish cabinet indicate the track being heard and whether 2-channel or 4-channel is being played. Connects to present systems through the auxiliary input, tuner input or the tape input of the existing amplifier or receiver. Size: 16 $\frac{1}{2}$ x 11 $\frac{1}{2}$ x 4 $\frac{1}{2}$ inches. For 117 VAC 60 Hz. Shpg. wt., 18 lbs. 27 R 33012WX No Money Down* Net 299.95

Specialty 8 Track Stereo Tape Players and Recorders

AKAI 2 and 4-channel Stereo 8 Track Record/Playback Tape Deck

- Includes 4 channel cartridge demo tape, all connecting cables, and head cleaning brush
- 4 Record and Playback Solid State Stereo Preamplifiers

249⁹⁵ NEW



Now you can record and playback 4 channel, 8 track stereo tape cartridges through your 4-channel stereo receiver or amplifier. The CR-80DSS is fully compatible—you can also record and playback 2 channel 8 track tape cartridges. Features: 4 VU Record meters, fast forward control. Heads: 4 Track 4 Channel stereo Recording/Playback, 4 Track Erase. Input jacks: 4 mic-input level/impedance: 0.4mV /30K ohms, 4 line input jacks: input level/impedance: 40mV, 300 K ohms. 4 line output jacks, 1 headphone jack, 19 transistors, 18 diodes. Tape Speed 3 $\frac{3}{4}$ IPS. Freq. Response, 50 to 16,000 Hz, Signal to Noise Ratio—better than 47 db, Recording bias frequency 65 kHz.

Size: 19.4" x 5.5" x 11.2"D. For 100V to 240V AC 50/60 Hz. Shpg. wt., 26 lbs. Imported.

27 R 56013WX No Money Down* Net 249.95

AKAI Model CR-80SS—2 and 4 Channel 8 Track Stereo Tape Recorder—same features & specs as above but with 48 watt 4 channel stereo Power Amplifier built-in. All you need for a complete 4 channel system is to add 4 speakers, for 100V to 240 VAC 50/60 Hz. Imported. Shpg. wt., 36 lbs.

27 R 56021WX No Money Down* Net 299.95

Qatron Automatic 8-Track Stereo Tape Player/Changer

- Plays Up To 12 Cartridges
- Instant-on Solid State Circuitry

New Low Price

269⁹⁵

With Dust Cover

Up to 12 hours of continuous play. Automatically switches and selects 12 8-track tape cartridges in an easily removable rotary magazine. 4 Modes of operation—(1) Plays all channels of all tapes in sequence, (2) Plays random selection of tapes, (3) Plays individual tracks of each tape, (4) Repeat-play same cartridges. Aux. inputs for AM/FM stereo tuner. Power output—30 watts (15 per channel). Requires set of 2 external speakers for complete playback system. Has Pre-Amp output for use with existing home stereo system. Separate tone and balance controls. For 117 VAC 60 Hz. Size: 18 $\frac{1}{4}$ x 9" x 16 $\frac{1}{4}$ " D. Walnut vinyl finish base. Shpg. wt., 34 $\frac{3}{4}$ lbs.

27 R 28004WX No Money Down* Net 269.95



8 TRACK STEREO TAPE RECORDERS and TAPE DECKS

PANASONIC RS-820S 3-PIECE SOLID-STATE AM/FM STEREO
8-TRACK CARTRIDGE RECORDER SYSTEM

- Each Speaker Enclosure Contains a 6½" Woofer and 2¾" Tweeter
- Handsome Walnut Wood Cabinetry

Luxurious in every way—from its distinctive walnut wood cabinetry and black and silver control panel to its magnificent sound performance, 8-Track Recorder section provides superb Record-Playback performance. Features track selector button, four illuminated track indicators, fast-forward control, accidental erasure guard, Mono/Stereo playback change-over switch, speaker switch, and two large VU Record meters. AM/FM Stereo radio features: 'Black-Out' dial face, FET tuner, AFC on FM, and separate sliding bass and treble controls. Brilliant sound is assured by 2 separate two way full range speaker systems, 32-watt peak music power, super sensitive stereo balance control. Imported. For 110VAC 60 Hz. Size: 20½ x 6¾ x 14¾" D. Shpg. wt., 59½ lbs.
17 R 3186WX No Money Down* Net 299.95



299⁹⁵

With 1 Mike and Stand

- 8 Track Recorder Features FAST Forward, Accidental Erasure Guard
- 2 VU Record Meters
- Hide-Away Cartridge Bin

DELUXE VIKING 811R 8-TRACK SOLID STATE HOME STEREO CARTRIDGE RECORD/PLAYBACK DECK



NEW LOW PRICE

149⁹⁵

High quality 8-track stereo tape cartridge RECORD/PLAYER deck in a handsome walnut cabinet with built-in record/playback amp for use with existing stereo equipment in the home. Features a special Logic Circuit that permits choice of continuous play or auto-stop at end of tape in PLAY mode, and, allows choice of auto-stop at end of single track or completion of all 4-tracks in RECORD mode. Unit automatically plays when cartridge is inserted; has automatic and pushbutton track selection; 40-15,000Hz response; 0.3% rms wow and flutter; numerical track indicator; VU meter; record button interlock, and pilot light. For 117 VAC. 60 Hz. Size: 15¼ x 11 x 4". Shpg. wt., 18 lbs.
27 R 68091W No Money Down* Net 149.95

PANASONIC RS-803US SOLID STATE 8-TRACK STEREO CARTRIDGE RECORD/PLAY DECK



Only

99⁹⁵

- Fast Forward Control

Solid-State 8-Track Stereo Cartridge Record/Play Deck with fast wind permits quick selection of the tape sections you wish to hear. Two easy-see VU meters for visual indication of recording level on both channels. Separate volume controls for left and right channel, push button controls for recording and program selection. Auto-Stop switch for shutting the recorder off when the tape reaches the end of the last track. Safety lock record button guards against accidental erasing or recording. Lighted channel indicators. Solid State circuitry. 2 mike, 2 Aux input jacks. Stereo Headphone output. With 4 connecting cords, one head cleaning bar. 16¾ x 4½ x 9¾". For 117 VAC 60 Hz. Imported.
27 R 12271W Shpg. wt., 13½ lbs. No Money Down* Net 99.95

CONCORD MARK 8 REEL-TO-REEL STEREO RECORDER with Built-in 8 Track Cartridge Recorder




289⁹⁵

- Internal Copying from Reel-to-Reel to 8 Track

Records stereo 8 cartridges from reel-to-reel tapes, or from aux. (tuner, tape) and phono inputs. Also records and plays back 4 track stereo and mono reel-to-reel tapes. Features self-contained wide range speakers, monitoring amplifiers, external speaker output jacks, stereo headphone output jack, 2 illuminated VU record level meters, 4 digit tape counter, illuminated 8 track channel lights, pushbutton 8 track selector button, separate slide controls for left and right channel volume, 8 track fast forward pushbuttons. Freq. response—Reel: 50 to 19,000 Hz. at 7½ ips, 8 track: 50 to 12,000 Hz. S/N Ratio: 45db. Mike input impedance: 600 ohms. Reel recorder takes up to 7" reels. Size: 10½ x 13¾ x 18¾". For 117 VAC 60 Hz. Imported. Shpg. wt., 47½ lbs.
27 R 35397WX No Money Down* Net 289.95

SONY/SUPERSCOPE TC-8W "8 TRACK" SOLID STATE STEREO CARTRIDGE RECORDER/PLAYER DECK



139⁹⁵

- Stand-by Switch
- Cartridge Alignment Indicator

Now with the exciting Sony TC-8W, you can select and record your own library of stereo 8-track cartridges for automobile and home use. Instantly connects to your home system for recording or playback. Features "Sonomatic" AGC which automatically adjusts recording level. Perfect track alignment is assured by alignment indicator light and automatic power mechanism which turns unit on only when cartridge is properly inserted and shuts it off at the end of the tape. Also has record interlock to prevent accidental erasure. Illuminated Track Indicator, Stereo Headphone Jack, Track Selector Switch, and Stand-by switch. Mike and Aux. Input jacks. Frequency Response: 40-12,000 Hz. Wow and Flutter: 0.32%. Size: 10¾" x 13" x 6¾". Imported. Shpg. wt., 14¾ lbs.
27 R 60510WX No Money Down* Net 139.95


PORTABLE 8-TRACK TAPE CARTRIDGE PLAYERS

Portable Battery/Electric 8-Track Stereo Tape Player

ONLY **59⁹⁵**
With Batteries

- Includes 117VAC line cord for home use, and a 12V adapter cord for car or boat use.
- Instant-on Solid State Circuitry
- Slide Rule Tone and Volume Control

Truly portable! Listen to 8-Track Stereo Cartridges wherever you go on the beach, on a picnic, in the country, or in your backyard. This deluxe instant-on solid state 8-Track Tape Cartridge player operates on 117 VAC or 8 "D" cell batteries. Separate left and right slide rule volume controls and slide rule tone controls. Two quality hi-fi speakers assure many hours of listening pleasure. Channel selection is automatic or manual with pushbutton and has indicator light. Highly




attractive units fold together and latch securely for the ultimate in portability and handling. Also has high impact plastic case with modern grip-type carrying handle. Size: 11Wx9Hx6¼"D. Imported. Shpg. wt., 8½ lbs.

17 R 69488W No Money Down* Net **59.95**
99 R 62564 "D" Batteries for above, 8 req. Net ea. **.18**

Portable 8-Track Tape Player* and AM/FM/FM/Stereo Radio

114⁹⁵
With 8 "D"
Batteries,
AC Line Cord
Car Adapter



FEATURES 3-WAY OPERATION:

- 1) Self-Contained Battery
- 2) 117VAC Home Current
- 3) 12V DC Neg. Ground Car System

Deluxe all Transistor portable 8-Track Tape Cartridge Sound System with built-in AM-FM stereo radio. Unique player operates on 117 VAC, or on 8 "D" batteries (included). A cigarette lighter adapter cord (included) also permits this amazing player to be used in car and boats with a 12 VDC negative ground electrical source. Magnificent sound quality is achieved thru use of 2 high compliance 3"x6" speakers each mounted in an acoustically matched enclosure that can be placed as

far as 5 feet apart for maximum stereo effect. Also features channel selector button, channel indicator lights, continuous tone control, FM stereo indicator light, built-in telescoping FM antenna, and left and right channel volume control. Size: 9x11x6¼"D. Imported. Shpg. wt., 14½ lbs.

No Money Down* Net **114.95**
17 R 26397W Net **114.95**
Extra "D" Batteries, 8 required
99 R 62564 Net ea. **.18**

Portable 8-Track Player

34⁹⁵
With
Car Cigarette
Lighter Adapter



- Listen to 8-Track Tape Cartridges Wherever You Go

An exciting way to listen to 8-track stereo tape cartridges. Portable instant-on solid state tape player operates on 6 "D" batteries (not included) or may be plugged into the cigarette lighter of any car or boat with a 12V neg. ground electrical source. Continuous tone control and dynamic speaker for quality sound reproduction. Earphone jack for private listening. Channel indicator. Integrated carrying handle. Includes 6 transistors and 1 thermistor. 8"Hx7"Wx3¼"D. Imported. Shpg. wt., 5¾ lbs.

17 R 26330 Net **34.95**
"D" Batteries, 6 required
99 R 62564 Net ea. **.18**

Portable Auto/Home 8-Track Stereo Tape Player

- Operates on 117 VAC Household Current or Car 12 Volt Negative Ground System By Plugging Unit into Car Cigarette Lighter
- Instant-on Space Age Solid-State Circuitry

79⁹⁵
with 12 VDC
Car Adapter,
and AC Line
Cord.

Completely self-contained 8-track stereo tape cartridge player provides outstanding hi-fi sound reproduction everywhere. At home, all you do is plug the player into any 117 VAC electrical outlet, insert the cartridge, and sit back and listen to beautiful music. When you are driving, just place the player on the floor or on the seat next to you—plug the car adapter cord (included) into the cigarette lighter socket for hours of musical motoring. When not being used in the car, the player can be stored in the trunk to prevent theft. Features separate slide controls for volume, balance, and tone plus a push-button channel selector. Two built-in 5" wide range dynamic speakers. Also includes external speaker terminals. Power output: 5 watts per channel. Size: 7½Wx7½Hx8"D. Imported. Shpg. wt., 12 lbs.

17 R 44002W No Money Down* Net **79.95**



FOR YOUR CAR



FOR YOUR HOME



*See Page 22 for Full Credit Details on Easy Pay Plan

LAFAYETTE Stereo 8-Track Listening in the Car

Deluxe LAFAYETTE "Stereo 88" Solid State 8-Track Car Tape Player



Renowned LAFAYETTE Hi-Fi Stereo Quality and Performance For The Car

59⁹⁵

Complete with Adjustable Mounting Bracket, and all Mounting Hardware. Less Speakers.

- Power Output: 12 Watts
- Instant-On Space Age Solid-State Circuitry
- Individual Illuminated Track Indicator Lights

- Pushbutton Track Selector
- Volume, Balance, and Tone Controls
- For 12 Volt Negative Ground System

Beautifully designed stereo car tape system superbly engineered to provide high quality stereo sound playback of 8-Track Stereo Pre-Recorded Tape Cartridges. Features a built-in Burglar Alarm System to prevent theft. The "Stereo 88" measures only 2 3/8" H x 7" W x 7 3/4" D, and can be easily mounted under the dash of your car with attached adjustable mounting bracket. Fully automatic—just slip in an 8-track tape cartridge and the "Stereo 88" plays instantly. Removal of cartridge automatically switches player off. Illuminated

track indicator shows track that is playing. Tracks change automatically after end of each program or instantly by operating the selector button. Frequency Response: 50 to 10,000 Hz; Signal-To-Noise Ratio: more than 40 db. Wow and Flutter: less than 0.3%. 12-transistors, 1-diode, 4-thermistors; Output Impedance: 4-ohms. For 12 volt negative ground systems. With mounting bracket and hardware. Imported. Shpg. wt. 8 1/2 lbs. Less Speakers. 99 R 15521W No Money Down* Net 59.95

LAFAYETTE "Micro 8" Stereo 8 Track Car Tape Player

At A Price Everyone Can Afford

39⁹⁵

No Money Down* With Mounting Bracket, Less Speakers

- Compact Size—For Easy Installation
- Individual Illuminated Channel Lights
- Pushbutton Channel Selector Button
- "Instant-on" Solid State Circuitry


Listen to beautiful 8-track stereo track cartridges in your car. Compact design permits simple installation—even where space is at a premium. Player is only 7 3/8" D x 5 1/2" W x 2 3/8" H in size. Fully automatic operation—turns on when a tape is inserted, changes tracks automatically at the end of each program. A selector button permits you to instantly change tracks. Individual illuminated lights tell you which track is playing. Balance control to adjust for proper stereo channel separation. Separate volume and tone controls. Power output 10 watts. Freq. Response 30-10,000 Hz. For 12 volt neg. ground systems. Adjustable mounting bracket. Imported.

17 R 01143W Shpg. wt., 5 1/4 lbs. Net 39.95

Pair of Two 3 x 5" matching speaker systems

99 R 62994 Shpg. wt., 2 1/2 lbs. Net 6.95

* See Page 22 for Full Credit Details on Easy Pay Plan



8-TRACK Stereo Tape Players for the Car

NEW! TENNA TC-82-T 8-TRACK STEREO TAPE PLAYER



OUTSTANDING FEATURES

- Built-in Burglar Alarm
- Self-Cleaning Tape Head
- Hidden Channel Indicator
- Fine Tuning
- Fast Forward
- Automatic Eject
- Tape Light
- Motor On/Off Switch

79⁹⁵

WITH ALL MOUNTING
HARDWARE, LESS SPEAKERS

Deluxe, highly styled solid-state 8 Track Stereo Tape Player with exciting features: Built-in Head Cleaner cleans the head each time the cartridge is inserted; Fast Forward Button advances tape at a faster rate to pinpoint exact selection desired. Eject Button automatically ejects cartridge when ignition is shut off protecting cartridge pinch rollers. Built-in Tape Light for easy selection reading at night. Motor Switch reduces ignition noise and battery drain when a cartridge radio pack is operating in the player. Theft-proof Built-in Burglar Alarm blows horn continuously when an attempt is made to steal a properly installed player. Fine Tuning adjusts for worn or defective cartridges, tunes out crosstalk. Hidden Channel Indicator


...single channel number is illuminated; each number in a different color. Highly Styled Slide Controls for easy Tone, Volume and Balance adjustment. Reverse polarity for 12 volt negative/positive ground cars. Also includes automatic or pushbutton track selection. Peak audio output: 14 watts. Measures only 7½" x 3H x 7½"D. Frequency Response: 40-12,000 Hz. Impedance: 4 ohms. With universal mounting bracket. Imported.

17 R 74686W No Money Down*, Shpg. wt., 7 lbs. Net 79.95

Set of 2 Matched Rear Deck Speakers. Imported.

99 R 62986 Shpg. wt., 3 lbs. Net 9.95

Ranger 4 and 8-Track Solid State Car Stereo Tape Player



With
Built-In
BURGLAR
ALARM

NEW
LOW
PRICE

74⁹⁵

less
speakers

- For All 12 Volt Neg./Pos. Ground Car Systems
- Thumbwheel Type Control Knobs Conform With Federal Safety Regulations
- Fully Automatic—Instant Operation
- Illuminated Channel Indicator Light

A fully automatic 4 and 8-track stereo tape player with exclusive fine tuning control and built-in Burglar Alarm. Any attempt by unknown persons to remove a properly installed player will result in setting off the built-in alarm system—continuous horn blowing to scare the would-be thief away. Handsomely styled in black and chrome, this compact unit measures only 2¾ x 7¾ x 8" and can be easily mounted under the dash of your car with attached universal bracket. Fully automatic-no switches or lever to select choice of cartridge. Either 4 or 8-track cartridge slips in easily and plays instantly. Provides superb tape reproduction. Removal of cartridge automatically switches player off. Fine tuning control tunes out undesirable crosstalk in worn or defective 8-track cartridges by adjusting the playback head to precision alignment with the recorded tracks, illuminate channel indicator shows channel that is playing. Channel changes automatically after each program or instantly by operating the selector bar. Specifications: Peak Audio Output: 20 watts; Impedance: 4 ohms each channel; Transistors: 12, Thermistors 4; Battery drain: .75 amp; Tone Control. For 12 volt neg./pos. ground. Imported.

17 R 74496W Shpg. wt., 8 lbs. No Money Down* Net 74.95

Set of 2 Matched Lafayette Car Speaker Systems

99 R 62994 Shpg. wt., 2½ lbs. Net 6.95

Custom In-Dash 8-Track Stereo Tape Player For Volkswagen Cars



For 1967-1971 Series 1200 And 1300 Cars. Can Be Used in Prior Year VW Cars with Optional Voltage Adapter.

74⁹⁵

- Includes All Mounting Hardware and Two 4" Speakers

Custom installation. In addition when using the FM Stereo Tuner adapter listed below, the 8-track player becomes a fine performing FM stereo car radio. Pushbutton track selector or changes tracks automatically. Instant on solid state circuitry. For 12 volt, neg. ground systems. Includes two 4" speakers. Imported. Shpg. wt., 9 lbs.

17 R 26421W No Money Down* Net 74.95

WC 8525 6-volt voltage Adapter for 1955 thru 1966 Cars. Shpg. wt., 2 lbs.

17 R 26439 Net 14.95

FMX 8401 Universal FM Stereo Tuner Cartridge Input. Shpg. wt., 2¼ lbs.

17 R 26348L No Money Down* Net 48.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 123


8-TRACK Car Stereo Tape Players with Built-In Stereo Radio

NEW 8-Track Solid-State Car Stereo Tape Player

With FM/FM Stereo Radio

ONLY **89⁹⁵**

With All Mounting Hardware, Less Speakers



- Balance & Volume Slide Controls
- Channel Indicator Lights
- Channel Selector Button
- Channel Repeat Button
- FM Stereo Indicator Light
- Local/Distance Switch

Attractively styled 8-track car stereo tape cartridge player with built-in FM/FM stereo radio. Incorporates the latest solid state integrated circuitry. Power output per channel is 7 watts. Features slide control for volume and balance, tone control, FM stereo indicator light, slide-rule tuning, pushbutton track selector, and channel repeat button. For 12-Volt negative ground systems. Size: 8"Wx8 1/4"Dx3 1/8"H. Imported. Shpg. wt., 8 lbs.

17 R 80063W No Money Down* Net 89.95
Set of two Lafayette Matched Car Speaker Systems. Imported.
99 R 62994 Shpg. wt., 2 1/2 lbs. Net 6.95

NEW Deluxe Tenna TC83-MPX Solid-State Car Stereo Tape Player with FM/FM Stereo Radio



ONLY **119⁹⁵**

With All Mounting Hardware, Less Speakers


- Built-in Burglar Alarm
- Self Cleaning Tape Head
- Fine Tuning
- Fast Forward
- Automatic Eject
- Tape Lite
- Separate Slide Controls for Balance, Volume, And Tone

Combination of a deluxe performing 8-track stereo car tape player and FM/FM stereo radio. Features all the latest innovations for improved 8-track listening pleasure. The FM/FM stereo radio provides crisp, clear, static-free reception. Built-in burglar alarm helps prevent theft. Fast forward button advances tape at a faster rate to pinpoint exact selection desired. Instant on solid-state circuitry. For 12-Volt negative ground systems. Size 7 1/2"Wx8 1/4"Dx3 3/8"H. Imported. Shpg. wt., 11 lbs.

17 R 74678 No Money Down* Net 119.95
Set of 2 Deluxe Lafayette Rear Deck Speakers. Imported.
99 R 62986 Shpg. wt., 3 lbs. Net 9.95

NEW "In-Dash" 8-Track Car Stereo Tape Player

With AM/FM/FM Stereo-Radio



ONLY **149⁹⁵**

With Universal Face Plate, And Mounting Hardware

CUSTOM INSTALLATION KITS

Custom Installed Kits Are Available For Most Cars Specify Make, Model, And Year of Car. Allow 3 Weeks For Delivery. No COD's. Shpg. wt., 2 lbs.

17 R 80089Z Net 6.95

One of the most complete universal car sound systems ever designed. Includes an AM/FM stereo radio and 8-track stereo tape player in one compact case with adjustable shafts. For in-dash installation optional Custom kits are available. Features advanced solid-state circuitry—6 IC's, 14 silicon transistors, and 14 diodes. 7-watts output per channel. Controls: volume, tone, balance, channel selector stereo/mono switch. Also has channel indicator lamps, and FM stereo indicator light. For 12 Volt neg. ground systems. Size: 7 3/8"Wx2 5/8"Hx7 3/8"D. Imported.

17 R 80071W No Money Down* Shpg. wt., 8 lbs. Net 149.95
Set of 2 Deluxe Lafayette Rear Deck Speakers. Imported.
99 R 62986 Shpg. wt., 3 lbs. Net 9.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Speakers and Mounts for 8-Track Car Tape Players

LAFAYETTE "QUICK MOUNT" STEREO HI-FI CAR SPEAKERS

NEW only **14.95**
per pair



- Handles 10 Watts Per Speaker
- Easily Fastens to the Fire Wall, Kick Panel or Under Seat

Quality pair of 5 1/4" speakers with 5.5 oz. ceramic magnets, and cloth roll suspension for true hi-fi sound in the car. Impedance, 8 ohms. Will mount in minutes. No holes to cut or saw. Just drive screws through the convenient flanges on the outer plastic grill. Includes wire, hardware, and illustrated mounting instructions. Wt., 6 lbs. 32 R 01977 Per Pair Net 14.95



PAIR OF TRUSONIC DIE-CAST STEREO HI-FI SPEAKERS FOR THE CAR

29.95 Pair

With Grills and Mounting Hardware

- Power Handling: 12-Watts
- For Door or Rear Deck Mounting
- Frequency Response: 50-18,000 Hz

The ultimate in auto speaker design. Powerful 5" full-range speaker delivers brilliant clean highs to 18,000 Hz and deep solid bass down to 50 Hz. Features rigid die-cast frame, free cone suspension, 2 lb. magnet structure and 1" edge-wound wire ribbon voice coil. Handles 12 full watts of power. Custom mounts in door panels or on rear deck.

32 R 49489 2-Speaker Kit. Shpg. wt., 8 lbs. Net 29.95

LAFAYETTE Speakers for 8-Track and Cassette Car Stereo Tape Players

"VARY-MOUNT" FLUSH MOUNTING SPEAKER


- Beautiful Chrome Grill



3.95

Ideal for use as an auto speaker or anywhere shallow depth is required. Full range speaker has heavy magnet and offers outstanding sound quality. Can also be used as a ceiling or wall mount speaker in your home. Imp., 8 ohms. Overall dia., 6 1/4". Imported. Shpg. wt., 1 3/4" lbs. 99 R 01794 Net 3.95

PAIR OF 3 x 5 UNDER-DASH MATCHING SPEAKER SYSTEMS



6.95

Handsome pair of two 3 x 5" wide-range ceramic speakers mounted in plastic housing will mount under dash, under seats, on kick panels, doors, or rear package shelf. Includes all necessary cables and mounting hardware. Impedance, 8-ohms. Imported. Shpg. wt., 2 1/2 lbs. 99 R 62994 Net 6.95

CUSTOM INDOOR SET OF FOUR SPEAKERS & MATCHING GRILLES



8.95

Ready for quick installation. Improves the sound of any car tape player. Kit includes: Four 4 3/4" extended range 8-ohm PM speakers; four round custom mount plastic speaker grills; hookup wire with solderless connectors; mounting hardware and easy instructions. Imported. Wt., 3 1/2 lbs. 99 R 62861 Net 8.95


DELUXE PAIR OF REAR DECK MATCHING SPEAKER SYSTEMS



9.95

Set of two powerful 4" speakers mounted in handsome ebony plastic cabinets with silver trim. Designed to mount on car's rear deck. 5 watts peak handling power. Provides outstanding sound reproduction. Includes all necessary cables and mounting hardware. Imp. 8 ohms. Wt., 3 lbs. 99 R 62986 Net 9.95

TAPE PLAYER FLOOR AUTO MOUNT



7.95

- Adjustable—Fits all Tape Players

Screws firmly to floor. 1" strap holds tape players firmly in place. Easy access to all controls. Steel construction. Size: 10 1/4" to 14 1/4" wide, 10 3/4" long. Rear height: 5 3/8", front height 9". Shpg. wt., 5 1/2 lbs. 42 R 68099W. Net 7.95

CAR SPEAKER SWITCH

2.95



Now use your car radio speakers to play your stereo tape player. No need to buy additional speakers. Comes complete with wire, chrome plate, and mounting instructions. 17 R 63036 Shpg. wt., 4 oz. Net 2.95

UNIVERSAL Lock Mount For Car Tape Players

Prevents Theft **7.95**



- Remove Your Tape Player When Your Car is Unprotected

Prevent the theft of your car stereo tape player. Makes your player removable. Takes minutes to install. Adjustable mount adapts to car stereo tape players or CB transceivers. Once installed, no screws or wires are needed to disconnect player from mount. Plugs-in and locks. For 6 or 12 V. neg or positive ground. Dim.: 6 1/4" x 7 1/4" x 1 1/4". 17 R 63010 Shpg. wt., 2 1/4 lbs. Net 7.95

REPLACEMENT GRILLS FOR CUSTOM CAR SPEAKERS



As Low As **88¢** ea

For 5" speakers. Two types to choose from: perforated steel or black molded plastic.

Supplied with all necessary hardware. Shpg. wt., 1 lb. Perforated steel—diameter 5 3/4". 32 R 49547 Net .99 Black molded plastic—diameter 5 3/4". 32 R 49554 Net .88

Accessories For Car 8-Track Stereo Tape Players

NEW

Deluxe Lafayette Home Power Supply For Car Tape Player

16⁹⁵

Made In U.S.A.

- Converts 115 VAC to 12 VDC
- Handles Up To 4 amps
- Heavy Duty Binding Posts
- Neon Indicator Light
- Accessible Fuse On Front Panel



Double the use of a car stereo tape player, car radio, or mobile CB transceiver by using it in your home or office. Converts 115 volts AC to 12 volts DC. Handles a load of 4 amps. Features on/off switch, heavy duty color coded binding posts, neon indicator light, and accessible fuse in front. Black metal cabinet. For 117 VAC, 60 Hz. Size: 4 3/8" W x 6 1/2" D x 3" H. Shpg. wt., 6 lbs. 17 R 01945

Net 16.95

MOBILE BURGLAR ALARM FOR CAR TAPE PLAYERS AND RECORDERS



4⁹⁵

- Prevent Theft of Your Equipment
- Solid State Integrated Circuit
- For 12 V. Neg or Pos Ground

Burglar alarm connects to your horn and Tape Player or 2-Way Radio. Horn automatically blows when someone tries to steal equipment. Two-way switch permits you to remove your unit without sounding alarm. Features reliable, solid-state IC circuitry. Complete with instructions, wire and mounting hardware. 42 R 71011 Shpg. wt., 4 oz. Net 4.95

CARRYING CASE FOR 8-TRACK TAPE CARTRIDGES

- Holds up to 10 Cartridges

2⁹⁵

Keep tape cartridges for your car neat, orderly, dust free. Compact. 9x6x6" case stores 10 tapes of any standard brand. Shpg. wt., 1 3/4 lbs. 28 R 20124

Net 2.95



126 Lafayette Cat. No. 720

UNIVERSAL POWER CONNECTOR HARNESS FOR CAR TAPE PLAYERS



1⁹⁵

Ideal for installing tape players in cars. Features one plug-universal to all car stereo tape players. In-line fuse holder and speaker leads. Complete instructions for: 5 pin, 4 pin, 4 pin "Y", and 4 pin "odd" connections. Shpg. wt., 6 oz. 17 R 63028

Net 1.95

AUTOMATIC 4-TRACK TAPE CARTRIDGE ADAPTER



- Permits 4-Track Tape Cartridges To Be Played on 8 Track Tape Players

Universal adapter that turns any 4-track cartridge into an 8-track cartridge. Simply insert adapter into your 4-track cartridge—can easily be moved from cartridge to cartridge. Shpg. wt., 6 oz. 17 R 26132

Net 2.95

DELUXE CARRYING CASE FOR 8-TRACK TAPE CARTRIDGES

- Holds Up To 24 Cartridges

7⁹⁵

Deluxe Lafayette all wood carrying case. Measures 17 1/2" W x 6 1/2" H x 7 1/4" D. Black simulated alligator vinyl covering. Felt inserts, brass fasteners, and handle. Shpg. wt., 4 1/4 lbs. 28 R 78064W

Net 7.95



Lafayette Stocks A Complete Line Of Tape Accessories

UNIVERSAL FM Stereo Tuner Cartridge

29⁹⁵

with Auto-Y antenna



Converts Stereo 8-Track and 4-Track Car Tape Players Into an FM Stereo Radio

- FM Stereo Indicator Light
- Built-in AFC

Listen to full dimensional FM stereo radio broadcasts in your car. Inserts into your car tape player just like a regular tape cartridge. Requires a 9-volt battery (not included). Features instant-on solid-state circuitry, FM stereo indicator light, built-in AFC to prevent station drift, roll-bar FM tuning, and an auto-Y antenna. Size: 7 1/2" x 3 1/8" x 7/8" D. Imported.

17 R 43053L Shpg. wt., 1 lb. Net 29.95
99 R 60212 9V Bat. for above Net .29

FM TUNER CARTRIDGE FOR 8-TRACK CAR TAPE PLAYERS

19⁹⁵

With Antenna and Battery



- Turns Your 8-Track Tape Player Into an FM Car Radio

Converts any car, boat or home 8-track tape player to an FM radio with full, rich sound. Solid state circuitry with 8 transistors. Built-in AFC locks in stations. Precision slide rule tuning dial. Tuning range: 88-108 MHz. Imported. Shpg. wt., 1 3/4 lbs. 17 R 61006L

Net 19.95
99 R 60212 Extra 9V battery Net .29

8-Track Recording Tape, Test Tapes and Accessories

Lafayette 8-Track Cartridge Mylar Recording Tape




As Low
As
1.29

Continuous loop 8-track cartridges well lubricated to preserve tape life. Fits all standard 8-track recorders and players. With UNI-tension pressure pads, precision molded tape guide. Shpg. wt., 6 oz.

Stock No.	Record Time	Net Ea.		
		1-5	6-11	12 up
28 R 01421	35 Min.	1.69	1.49	1.29
28 R 01439	70 Min.	1.95	1.79	1.49
28 R 01355	80 Min.	2.25	2.05	1.85

Lafayette 8-Track Tape Head Demagnetizers



3.95

A must for all owners of 8-track tape cartridge recorders and players. Removes excessive magnetic build-up on heads. Use after every 15 hours of player use. Shpg. wt., ¾ lb. Imported.
For 117 VAC Home Players
99 R 15091 Net 3.95
For 12 VDC Car Players
99 R 15422 Net 5.95

Tape Cartridge Home Storage Cabinet



7.95

- Holds Up to 30 Cartridges
- Store in Bookcase, on Wall, or on Top of Desk or Stereo Cabinet

Economy and styling are combined in this new cabinet. The one piece molded insert stores tapes in individual compartments and assures neat stocking and easy cataloging of titles. Size 24 x 3 3/8 x 7 1/4". Shpg. wt., 5 1/2 lbs.
28 R 78130W Net 7.95

Lazy Susan Type 8-Track Tape Cartridge Storage Rack



ONLY
10.95

- Holds Up To 48 Tapes
- Lazy Susan Type Base

Easy access to your 4 and 8-track tape cartridge. No more misplaced tapes. Attractively styled wood and masonite storage rack with simulated walnut vinyl finish. Has "Lazy Susan" type base. Holds up to 48 tapes. Size: 9 1/2" W x 9 1/2" D x 12 1/2" H.
28 R 78049W Shpg. wt., 5 lbs. Net 10.95

Scotch 8-Track Cartridge For Extra Reliability



As Low
As
1.97

For use with all standard 8-track stereo tape recorders. 1 mil tensilized polyester. Includes cardboard storage half box and indexing label. Shpg. wt., 6 oz.

Stock No	Type	Record	Net ea.	
			1-11	12-up
28 R 33481	S-8TR-40	40 min.	2.17	1.97
28 R 33499	S-8TR-80	80 min.	2.53	2.27

Non-Abrasive 8-Track Head Cleaning Cartridge



1.29

- Minimize Tape Head Wear

A safe, non-abrasive method of cleaning your tape head and capstan. Removes dust, oxide, grit and other foreign matter, assuring maximum fidelity and performance. Complete cartridge and special cleaning liquid. Easy to use. Shpg. wt., 6 oz.
28 R 78122 Net 1.29

8-Track Test and Head Cleaning Tape Cartridge



1.49

3-In-1 Cartridge

- 1) Tests For Proper Head Alignment
- 2) Tests For Stereo Balance
- 3) Cleans Tape Head

Keep your stereo 8-track tape player sounding new with this professionally calibrated test tape. Cleans tape and restores full richness of tone. Checks for proper alignment of heads to eliminate crosstalk. Checks for proper equalization of channels.
28 R 92016 Net 1.49


8-Track Tape Cartridge Maintenance Kit



1.95

An all-in-one kit for your 8-track cartridge tape system, can also be used for your cassette tape system... keeps heads in top operating condition. Contains cleaner, lubricant, applicators, brush and convenient storage case. Simple operation with descriptive instructions. Brushes fit together to reach depths of player system. Ideal for all 4 and 8 track systems. Shpg. wt., 1/2 lb.
28 R 78015 Net 1.95

8-Track Tape Head Cleaning Cartridge




99¢

- Automatically Cleans Tape Head

A must for removing coating deposits from tape heads to restore high frequency response and volume. For use in any 8-track player accepting 8-track cartridges. Easy to use and reuse. Simply run the cartridge for a short period.
28 R 12923 Shpg. wt., 5 oz. Net 99

Super Deluxe Tape Cartridge Storage Cabinet




19.95

- Holds 45 Cartridges
- True Wood Finished Door

The ultimate in tape storage featuring a true wood finish hinged drop down door and molded insert which stores tapes in individual compartments. Construction similar to fine speakers. Size 24 1/4 x 6 3/4 x 11 1/2". Shpg. wt., 8 1/2 lbs.
28 R 78148W Net 19.95

ROBINS® CASSETTE AND CARTRIDGE RECORDER/PLAYER TAPE ACCESSORIES



CASSETTE AND CARTRIDGE BULK TAPE ERASERS. Removes recorded sound from the entire tape in seconds, restoring tapes to "like-new" blank condition to a lower level than that of your recorder. Now erase permanently recorded cassettes when desired. Operation: 110V., 50/60 Hz AC.

(A) TMC-1 for Cassettes. Shpg. wt., 2½ lbs. Net 13.20
28 R 72265

(B) TMC-2 for Cartridges. Shpg. wt., 4 lbs. Net 19.79
28 R 72273

(C) TMC-3 UL listed Professional Bulk Eraser for Cartridges. Shpg. wt., 9¼ lbs. Net 36.40
28 R 72281 No Money Down

CASSETTE RECORDER AND CARTRIDGE PLAYER HEAD DEMAGNETIZERS. Recommended by equipment manufacturers to remove excessive magnetic build-up on heads. Use every 15-20 hours of player use. Built-into Cassette and Cartridge.

(D) TD-10 for Cassette Players. Built-in pilot light. 110V., 50/60 Hz AC. Shpg. wt., 7 oz. Net 6.19
28 R 72299

(E) TD-12 for Home Cartridge Players. 110V., 50/60 Hz AC. Shpg. wt., 11 oz. Net 8.39
28 R 72307

TD-15 for Auto Cartridge Players. (Not illus.). 12 Volt DC model. Wt., 10 oz. Net 10.49
28 R 72315

TBT-8 "PRE-TEST" 8-TRACK CARTRIDGE. (Not illus.) Special limited length blank test tape permits rapid check of recording program.

28 R 72612 Shpg. Wt., 6 oz. Net 2.19

TRL-8 8-TRACK CARTRIDGE TITLE LABELS. (Not illus.) Replace worn labels. Color-code tapes by category. Package of 20, self-stick; in 5 colors. Net 1.25
28 R 72620 Shpg. wt., 4 oz.

THC-7 CASSETTE HEAD-KLEEN TAPE. (Not illus.) Safely cleans and polishes player heads. Removes accumulated oxides and other particles to maintain top sound performance. Shpg. wt., 3 oz. Net 1.25
28 R 72349

TCW-2 CASSETTE TAPE TENSIONING WINDERS. (Not illus.) Set of two winders. Insert in holes of Cassette. Winds in either direction to take-up slack and unravel tape. Net .99
28 R 72398 Shpg. wt., 3 oz.

TTK-1 CASSETTE RE-RECORD KIT. 50 reusable plastic erase control tabs to replace removed tabs of permanently recorded cassettes. Handy tool and instructions for simple insertion. Can be removed and replaced at will. Shpg. Wt., 6 oz. Net 1.49
28 R 72646 (Not illus.)

(I) TK-3 CASSETTE AND CARTRIDGE PLAYER/RECORDER HEAD-KLEEN KIT. 2-oz. bottles of Head Cleaner, Head and Guide Lubricant, and 25 extra-long Cleaning Swabs for cleaning and lubricating hard to reach parts of equipment. Shpg. Wt., 11 oz. Net 1.49
28 R 72406



CASSETTE TAPE SPLICERS. Professional editing and repairing of Cassette .150 tapes are now possible. Strip in sound effects and passages into existing tapes, repair broken tapes, etc.

(F) TS-115 Economy model "Cut-N-Splice." Cuts at 45° angle. 25 pre-cut, self-stick splicing patches included. Shpg. wt., 5 oz. Net 2.98
28 R 72356

(G) TS-215 Precision pocket size splicing block with choice of either 45° or 90° angle cut. Block comes in self-contained plastic carrying case with cutting blade and 25 pre-cut splicing patches. Wt., 5 oz. Net 6.29
28 R 72364

CASSETTE AND CARTRIDGE TEST STROBES. With Strobe Tape and Light built-in. Check your player/recorder for proper speed. Too fast produces flutter. Too slow, creates tape drag or wow. 110 V. 50-60 Hz. A.C.

(J) TSC-9 Cassette. Shpg. wt., 6 oz. Net 4.10
28 R 72414

(K) TSC-8 8-Track Cartridge. Shpg. wt., 8 oz. Net 4.95
28 R 72422

(H) TCC-9 "CARTRIDGE" COMPACT CARRYING CASE. Attractive, low cost, heavy duty vinyl, alligator grain, carrying case. Stores 12 8-track cartridge tapes. Ideal for home, auto, outdoors.

28 R 72588 Shpg. wt., 1 lb. Net 3.29

TT-15 Splicing patches for splicers. Pre-cut, self-stick, Pkg. of 100. Wt., 2 oz. Net .99
28 R 72380 (Not illus.)



(L) **PHONE PICK-UP TRP-4.** Record phone conversations with friends and relatives. Attaches by suction cup to receiver of phone. Plug attached. Simple, easy to use. Net 2.95
28 R 72430 Shpg. wt., 5 oz.

(M) **TCA-8 8 TRACK CARTRIDGE TAPE ALBUM.** Stores 8 8-track cartridges in their original canisters or packs. Ideal for bookshelves. Net 3.69
28 R 72596 Shpg. wt., 1½ lbs.


(N) **TK-36 CASSETTE TAPE EDITING KIT.** Has TS-115 "Cut-N-Splice" splicer, 25 splicing patches, TCW-2 cassette tape tension winder, supply of TCL-20 color-coded self-stick cassette replacement title labels, TL-80 color-coding numbered index spots, and TCL-30 color coded owner identification cassette end labels. An excellent value. Net 5.69
28 R 72604 Shpg. wt., 8 oz.

TCM-1 CASSETTE MAINTENANCE AND STORAGE CASE. Hold 10 Cassettes, Head Demagnetizer, "3-in-One" Head Clean and Test Tape, 240 Color-Coded Index Spots and Log Book. Shpg. wt., 1 lb. Net 10.99
28 R 72471 (Not illus.)



TSK-2 CASSETTE SOUND SALVAGE KIT. (Not illus.) Restore valued recorded tapes in broken or damaged Cassettes to original operating state. Kit has complete Cassette housing and parts with simple illustrated instructions for salvaging tape and assembling cassette.

28 R 72562 Shpg. wt., 4 ozs. Net .75
TSP-140 CASSETTE SENSING AND CUEING TAPE. (Not illus.) Aluminum foil tape can be cut to any length and placed on any desired section of cassette tapes to cue automatic stop, reverse, and other electronic sensing controls. .140"x150" L. Net 1.89
28 R 72570 Shpg. wt., 3 ozs.



(O) **TSA-1W BOOK TYPE C CASSETTE STORAGE ALBUM.** Holds 12 Cassettes neatly in recessed compartments. Decorative walnut grain cover. Extra sturdy construction. Shpg. Wt., 11 oz. Net 2.19
28 R 72752



(P) **CASSETTE AND CARTRIDGE COLOR-CODE LOG KIT.** TK-35. Catalog and index your tapes by category: Red-Jazz, Yellow-Shows, etc. Kit contains: 120 page log book, 240 numbered index spots in 2 sets, 120 title labels, all self-stick, in 5 basic Colors. Net 3.29
28 R 72539 Shpg. wt., ¾ lb.

(Q) **CASSETTE COLOR-CODE REPLACEMENT TITLE LABELS.** TCL-20. Self-stick, die-cut to fit Cassettes. Pkg. of 20 in 5 Colors. Net .95
28 R 72547 Shpg. wt., 3 oz.

(R) **CASSETTE OWNER IDENTIFICATION END LABELS.** TCL-30. Printed "Property Of—." Apply to Cassette end for identification of ownership. Package of 30, self-stick. Net .89
28 R 72554 Shpg. wt., 2 oz.

TC-2-12 CASSETTE STORAGE CANISTERS AND UTILITY BOXES. Two piece, rigid styrene Canisters for safe storage of Cassettes. Built-in tape stops. Package of 12 boxes. Shpg. Wt., 1 lb. Net 1.99
28 R 72760

PRE-RECORDED STEREO

8 Track and Cassette Tapes

BIG NAME Pre-Recorded Long Play 8 Track Stereo Tape Cartridges

3⁴⁹
ea



NEW RELEASES

8-Track Stereo Cartridge Best Sellers

- 28 R 44025 Frank Sinatra—Nevertheless I'm in Love with You.
- 28 R 44033 Sergio Mendes—So Nice.
- 28 R 44041 Nat King Cole—Love is a Many Splendored Thing.
- 28 R 44058 Nat King Cole—Stay as Sweet as You Are.
- 28 R 44066 Dean Martin—Young and Foolish.
- 28 R 44074 Dean Martin—I Can't Give You Anything But Love.
- 28 R 44082 Jackie Gleason—The More I See You.
- 28 R 44090 Pete Fountain—New Orleans Style.
- 28 R 44108 Harry James—You Made Me Love You.
- 28 R 44116 Glen Campbell—A Satisfied Mind.
- 28 R 44181 Patsy Cline—I Can't Forget You.
- 28 R 44199 Tennessee Ernie Ford—I Can't Help It if I'm Still in Love with You.
- 28 R 44231 Today's Pops #2—Midnight Cowboy; Raindrops Keep Falling, Jean, plus others.
- 28 R 44249 Today's Pops #3—Bridge Over Troubled Waters. If I Were A Carpenter, Kentucky Rain, plus others.
- 28 R 44264 The Music and Songs from "Hair".
- 28 R 44272 Johnny Cash—I Walk The Line, Born To Lose, Cry, Cry, Cry, Straight A's in Love.
- 28 R 44322 Sounds of the Woodstock Age—Sung and Played by Tribe.
- 28 R 44314 David Clayton Thomas—The Super Voice of Blood, Sweat and Tears, and Linda Ronstadt & the Stone Ponies.
- 28 R 44280 Rod McKuen—Love's Been Good to Me.
- 28 R 44306 Get Together—Snowbird, We've Only Just Begun, Candida, Look What They've Done To My Song, and others. Played and Sung by the Young Lovers.
- 28 R 44298 The Guess Who—Wild One, Pretty Blue Eyes, Don't Be Scared, Shot of Rhythm and Blues.
- 28 R 44173 Hank Locklin—Queen of Hearts, Lessons In Love, The Red Rose, I Always Lose.

- 28 R 44355 The Glen Campbell Album—Only the Lonely, That's All Right, Woman's World, Same Old Places, plus more.
- 28 R 44363 Woodstock—Vol. III
- 28 R 44371 Nancy Wilson—Goin' Out of My Head, The Shadow of Your Smile, Yesterday, Uplight, and I Love Him, plus more.
- 28 R 44389 Johnny Cash—Rock Island Line, The Wreck of the Old 97, Come in Stranger, Hey Porter, I Heard that Lonesome Whistle.
- 28 R 44397 Love Story—Melachrino Strings.
- 28 R 44405 Jesus Christ Superstar—Musical Excerpts from the Rock Opera. I Don't Know How To Love Him and Others.
- 28 R 44413 Tribes Sing—the Creative Genius of George Harrison/John Lennon/Paul McCartney—Let It Be, My Sweet Lord, Why, Something, Isn't it a Pity, Junk, plus more.
- 28 R 44421 Beach Boys—Famous Hits.
- 28 R 44439 Tennessee Ernie Ford—Jesus Loves Me—Onward Christian Soldier, Shall We Gather at the River, plus more.
- 28 R 44447 Tennessee Ernie Ford—Standing In the Need of Prayer.
- 28 R 44454 The Four Seasons—the Brotherhood of Man.
- 28 R 44462 Roger Miller—Engine, Engine 9.
- 28 R 44470 The Cowbills—the Serendipity Singers—the Mindbenders—the Lincoln Park Zoo.
- 28 R 44488 Big Bands—Original Big Band Theme Songs Played by the Original Artists—Benny Goodman, Harry James, Les Brown, Glen Gray, and others.
- 28 R 44496 Lynn Anderson—Flower of Love, Games People Play, Okie from Muskogee, Stand By Your Man, and others.
- 28 R 44504 Hank Thompson—Simple Simon, Simple Heart.
- 28 R 44512 Merle Haggard/Bonnie Owens—That Makes Two of Us—I'll Take a Chance, I Wanta Live Again, Forever and Ever, Stranger in My Arms, Plus more.
- 28 R 44520 Buck Owens—If You Ain't Lovin'.
- 28 R 44538 Guest Stars of the "Haw'N' Show"—Buck Owens, Faron Young, Ferlin Husky, Sonny James, Wynn Stewart, George Jones.

BIG NAME Pre-recorded Stereo Cassette Tapes



3⁴⁹
ea

- 28 R 37003 Dean Martin—You Can't Love Em All
- 28 R 37011 Glen Campbell—A Satisfied Mind
- 28 R 37029 Sergio Mendes Trio—So Nice
- 28 R 37037 Frank Sinatra—Just One of Those Things
- 28 R 37045 Buck Owens—If You Ain't Lovin'
- 28 R 37052 Sunny James—Invisible Tears
- 28 R 37060 Jackie Gleason—Plays Pretty for Pretty People
- 28 R 37078 Rod McKuen—About Me
- 28 R 37086 Patsy Cline—In Care of the Blues
Average Shpg. wt., 2 oz.

Lafayette Stereo Check Out and Demonstration Tapes

2⁹⁵
ea.



- Excerpts From Gayne Suite
- Tests and Balances Your Equipment
- Separate Tapes For 8 Track, Cassette, Reel to Reel

Every owner of a 2 channel stereo Tape Recorder or Tape Deck should have one or all of these tapes. Tests and balances your equipment for optimum audio reproduction. Test portion of tape includes speaker phasing, channel separation, balance, and wow and flutter checks. Demonstration portion of tape includes sound effects and excerpts from Gayne Suite by Khachaturian. Average Shpg. wt., 10 oz.

Stock No.	Type	Net ea.
28 R 01389	7" Reel to Reel	2.95
28 R 01371	8 TR. Tape Cartridge	2.95
28 R 01397	Cassette	2.95

Accessories For Cassette Players and Recorders

DELUXE CASSETTE TAPE STORAGE CABINET




- Holds Up To 36 Cassettes
- Store in Bookcase or on Wall, on Top of Desk or Stereo Cabinet

7⁹⁵

Economy and styling are combined in this new cabinet. A one piece molded insert stores tapes in individual compartments and assures neat stocking and easy cataloging of titles. Size: 21x23/4x8 1/2". Shpg. wt., 4 lbs. 28 R 78155 Net 7.95

CASSETTE TAPE CARTRIDGE STORAGE RACK



- Holds Up To 48 Tapes
- Lazy Susan Type Base

10⁹⁵

Attractively styled wood and masonite cassette cartridge storage rack with simulated walnut vinyl finish. Has "Lazy Susan" type base for easy access to your cassettes. Size: 7 7/8x7 7/8x10 1/4". Shpg. wt., 3 3/4 lbs. 28 R 78056W Net 10.95

DELUXE CASSETTE TAPE CARRYING CASE



- Holds up to 30 Cassettes

Only **7⁹⁵**

Solid wood construction. Durable black alligator vinyl covering with attractive red plush interior. Horizontal storing of cassettes permits immediate visibility of all titles. Equipped with lock and key and handle. 28 R 78072 Shpg. wt., 3 3/4 lbs. Net 7.95

LAFAYETTE CASSETTE DEMAGNETIZER



New low price
3⁹⁵

In normal use, build-up of residual magnetism is unavoidable, resulting in loss of fidelity. This cassette demagnetizer will remove it to restore frequency response and improve sound performance. Operates on 110V 50-60 Hz. AC. With pilot light. Imported.

99 R 16057 Shpg. wt., 8 oz. Net 3.95

TELEPHONE PICKUP COIL

2⁹⁸



Extremely sensitive loop type telephone pickup coil for use with recorders, amplifiers and dictating machines. Loop easily slips on ear piece of phone. 3 ft. shielded cable with miniature 1/4" plug. Imported. Shpg. wt., 6 oz. 28 R 65129 Net 2.98

CASSETTE HEAD CLEANER AND TEST TAPE



1⁴⁹

3-in-1 Cassette

- 1) Tests for Proper Head Alignment
- 2) Tests for Stereo Balance
- 3) Cleans Tape Head

Keep your cassette player sounding like new with this professionally calibrated test tape. Cleans tape heads to restore full richness of tone. Checks for proper alignment of heads to eliminate crosstalk. Checks for proper balance and equalization of channels. Shpg. wt. 3 oz. 28 R 92024 Net 1.49

AMPEX DEMAGNETIZING/CLEANING CASSETTE



4⁹⁵

Cleans and demagnetizes cassette recorder heads and guides in one brief pass through the recorder. Since it requires no power, fits all cassette recorders including slot-loaded ones. Non-abrasive cleaning tape won't damage tape heads. 28 R 54008 Shpg. wt., 4 oz. Net 4.95

LAFAYETTE FOOT SWITCH

3⁹⁵



Ideal for Stenographic Transcribing

Gives your cassette recorder the versatility of a dictating machine. Plays when the foot switch is depressed, stops when released. Simply plugs into "remote" jack. 5 ft. cable with micro-miniature plug. Imported. Shpg. wt. 3/4 lb. 99 R 15810 Net 3.95

NON-ABRASIVE CASSETTE TAPE HEAD CLEANER



- Cleans Head With Minimum Wear

1²⁹

A safe non-abrasive method of cleaning your tape head and capstan. Proper use will remove dust, oxide, grit and other foreign matter assuring maximum fidelity and performance. Comes complete with cassette plus stereo tape player cleaning solution. Shpg. wt., 5 oz. 28 R 78163 Net 1.29

TAPE HEAD CLEANER

99^c



Use in any cassette recorder, removes coating deposits from tape heads, restores both volume and high frequency response. Can be reused many times. Shpg. wt., 7 oz. 28 R 16015 Net .99

CASSETTE "CARRY-ALL" PORTABLE CASE

7⁹⁵



Holds up to 6 Cassettes and all Portable Cassette Recorders up to 5 1/2x10" in size

Carry your cassette recorder, tapes and accessories in one handy case. Rich leather textured vinyl with sturdy compartments in a suede-like finished interior. 28 R 78114 Shpg. wt., 2 lbs. Net 7.95

UNIVERSAL CARRYING CASE for PORTABLE CASSETTE RECORDERS



2⁹⁵

- Measures 9 1/2"Dx 5 3/4"Wx2 1/2"H

Durable black texon carrying case for most portable cassette recorders. Double adjustable strap. Shpg. wt., 3/4 lb. Inside Dimensions of Case. 28 R 27020 Net 2.95

CASSETTE CARRYING CASE

2¹⁹



- Holds 12 Cassettes

Black vinyl with chrome trim, shoulder strap, and spring snap lock. Dim: 6 1/2x5 3/4x3 3/8". 28 R 27012 Shpg. wt., 3/4 lb. Net 2.19

Lafayette Blank Tape Cassettes

LAFAYETTE'S FAMOUS MONEY-BACK GUARANTEE
YOU BE THE JUDGE!

Lafayette's cassettes are made by outstanding nationally known manufacturers. It is first quality, trouble free, red oxide coated, with full frequency response, uniform output and no "dropouts." Resistant to moisture, heat, cold and abrasion.

We guarantee absolute satisfaction or your money back. If for any reason you are dissatisfied, return the tape within 30 days and we will refund your money less only transportation charges. You are the sole judge.



LAFAYETTE STANDARD BLANK TAPE CASSETTES



As Low As
69¢

High quality tape assures full fidelity recording. Records and plays 2-tracks at 1 1/2 ips. Super strong polyester base. Proper lubrication for longer tape life. Protects heads. Imported. Shpg. wt., 4 oz.

Stock No.	Model No.	Playing Time	NET EACH	
			1-9	10 Up
28 R 01280	C-30	30 Minutes	.79	.69
28 R 01223	C-60	60 Minutes	.99	.89
28 R 01207	C-90	90 Minutes	1.49	1.39
28 R 01215	C-120	120 Minutes	2.19	1.99

CRITERION® DELUXE BLANK TAPE CASSETTES



- Head Cleaning Tape on Each Cassette
- Super-Calendered Tape to Minimize Wear and Improve Frequency Response

- Sensing Foils to Actuate Machines with Reversing Mechanisms
- With Plastic Album Storage Box

Lafayette's best recording tape cassettes manufactured to our specifications, with extra deluxe features. Deep lubricated, super-calendered tape in an improved black plastic cassette, minimizes tape head wear and provides better low and high frequency response. Head cleaning tape at one end removes accumulated material from recorder heads. Sensing foils at each end actuate recorders having automatic reversing capabilities, but may also be used on all cassette recorders. Comes in hard plastic album storage box. Imported. Shpg. wt., 5 oz.

Stock No.	Model No.	Playing Time	NET EACH	
			1-9	10 up
28 R 01298	C-30	30 Minutes	1.09	.99
28 R 01306	C-60	60 Minutes	1.29	1.15
28 R 01314	C-90	90 Minutes	1.99	1.79
28 R 01322	C-120	120 Minutes	2.99	2.69

ADVOCATE CROLYN® CASSETTES



- Increases High Frequency Levels
- Reduces Inherent Tape Noise

C-60
2 99

A revolutionary 60 minute cassette recording tape using a chromium based coating rather than iron based coatings found in conventional tapes. It can be used in standard recorders to increase the high frequency level up to 8 db, reduce tape hiss, and provide an exciting experience in high fidelity listening. Hard plastic storage box. Shpg. wt., 4 oz.

28 R 47002 Net ea. 2.99

C-90 CROLYN CASSETTE. Same high quality chromium tape as above in a 90 minute cassette. Shpg. wt., 5 oz.
28 R 47010 Net 3.74

CASSETTE TAPE SPLICER



1 95

Sturdy precision instrument for use in all splicing and editing of cassette tapes. Imported. Shpg. wt., 7 oz.
99 R 15992 Net 1.95

CRITERION® UD HI-FI CASSETTES



C-60 UD 1.99
C-90 UD 2.99
C-120 UD 3.99

- Wide Dynamic Range—30-20,000 Hz Response
- Low Noise—High Output

- Super-Calendering Minimizes Wear and Improves Frequency Response
- Head Cleaning Tape on Each Cassette
- Sensing Foils to Activate Machines With Reversing Mechanisms

These Lafayette ultra-dynamic hi-fi cassettes are the only ones having all of these deluxe features and represent the peak of cassette excellence. Advanced oxide formulation provides a wide dynamic range with a frequency response of 30-20,000 Hz. The low noise, distortion-free high output results in the highest performance that can be expected of a cassette tape. Each tape has a section of head cleaner at one end and sensing foils at each end to actuate equipment having automatic reversing capabilities, but may be used on all cassette recorders. In hard clear plastic hinged album storage box. Imported. Shpg. wt., 5 oz.

C-60UD 60 MINUTE HI-FI CASSETTE	
99 R 15851	Net ea. 1.99
C-90UD 90 MINUTE HI-FI CASSETTE	
99 R 15801	Net ea. 2.99
C-120UD 120 MINUTE HI-FI CASSETTE	
99 R 16032	Net 3.99

TDK HI-FI CASSETTES



- Low Noise Level.
- Frequency Response 30-20,000 Hz.

1 99

60 MINUTE C-60SD

This 60 minute hi-fi tape uses a new gamma ferric oxide developed for high-density recording. The wide dynamic recording range 32-20,000 Hz. Makes available low noise, distortion-free output for the highest performance that can be expected of a cassette tape. Imported. Shpg. wt., 5 oz.

28 R 01249 Net 1.99

90 MINUTE C-90SD

A 90 minute cassette having the same high quality characteristics, specifications and performance as the C-60SD cassette above. Imported.

28 R 01363 Shpg. wt., 4 oz. Net 2.99

PLASTIC CASSETTE STORAGE BOX



Snap-open plastic box for individual cassettes. Clear hinged cover for instant identification. Built-in stops prevent tape slack and unwinding. Shpg. wt., 3 oz.
28 R 17054 Net ea., .25 Lot of 5.99

LAFAYETTE Recording Accessories

LAFAYETTE BULK TAPE ERASERS



11⁹⁵
Deluxe Model

29⁹⁵
Professional Model

A carefully designed and precisely manufactured tape "degasser" for complete erasing of tapes. Just place the tape reel on spindle of demagnetizer, slowly rotate 2 or 3 turns, make off, and that's all. Reduce tape hiss to the level of new "virgin" tape. Two completely separate coils are used for doubly-effective erasures, even of large, 10 1/2" reels. Will erase 1" wide tape. An extra powerful unit for heavy-duty use—draws over 9 amperes. Can be used to demagnetize tape, magnetically stripped film, plus tools and watches. Has a heavy, custom finished case, a rugged non-magnetic top, heavy duty on-off switch and power cord. Has built-in fuse. Pilot light prevents accidentally leaving it turned on. Size 6 1/4 x 7 7/8 x 3 1/2". 105-125V, 60 Hz. Imported. Shpg. wt. 12 3/4 lbs.

99 R 15166 Professional Model Net 29.95

Deluxe Model

Similar to professional model for all size reels but handles only standard size 1/4" tapes or smaller and reel must be turned over once. Has separate spindle positions for 10 1/2" and 3, 5, and 7" reels; non-magnetic bakelite plate for reel rest. One powerful coil consumes 5 amps. Metal case 7 1/4 x 4 1/4 x 3 1/2". Imported. Shpg. wt., 4 3/4 lbs.

99 R 15182 Net 11.95

HAND HELD BULK ERASER

- Utmost Versatility—Demagnetizes Cassettes, Cartridges All Size Reels and Equipment



10⁹⁵

Easily erases tapes or sound films regardless of reel size. Convenient, comfortable hand held design. Also demagnetizes capstans, tape guides, etc. Lowers background noise better than new tape. Safe, durable plastic case and control switch. High intensity field with low power consumption.

28 R 30016 Shpg. wt., 2 3/4 lbs. Net 10.95

LAFAYETTE CORDLESS 3-WAY TAPE ERASER

- Universal Tape Eraser for Cassettes, 8-Track Cartridges and Reel-to-Reel Tapes



8⁹⁵

A compact, easy-to-use universal tape eraser which works on a self-contained DC source. Powerful rotating magnets provide the strong field which removes previous recordings and noise from cassettes, 8-track cartridges and open reel tapes. Requires 4-inexpensive AA penlite cells (not supplied). Has On-Off slide switch; plastic case. Size: 4 1/4 x 3 7/8 x 2 1/4". Imported. Shpg. wt., 1 1/4 lbs.

99 R 15877 Eraser (less batteries) Net 8.95

1 1/2 volt AA cells for above (4-required).

99 R 62580 Net ea. .10

LAFAYETTE TAPE HEAD DEMAGNETIZER WITH SWITCH

Pencil shaped head demagnetizer with one extending probe. Styling allows you to reach all heads in all positions. Features switch control... no need to leave unit on constantly. Turn on when needed and off to conserve unit's life. Operates on standard 110-120 VAC 60 Hz. Imported. Shpg. wt., 9 oz.

99 R 15331 Net 2.95

TAPE CLEANER

Tape is impregnated with special formula cleaner. Simply run through like regular roll of tape. Entire job done in 2 minutes. Can be reused many times. Shpg. wt., 5 oz.

28 R 20017 Tape Cleaner on 5" reel Net 1.88

28 R 20025 Tape Cleaner on 3" reel Net .99

1200 FT. LEADER TAPE ON 7 INCH REEL

Lafayette brings you this jumbo reel of leader tape at a tremendous savings over the cost of leader tape customarily available in 100 ft. quantities. 1 1/2 mil mylar tape, 1200 ft. x 1/4" wide on 7" clear plastic reusable reel. Individually boxed.

28 R 77017 Shpg. wt., 3/4 lb. Net 2.69

- For Indexing and Cueing

LAFAYETTE TAPE SLICER



2⁸⁹

- Two Operations—Cuts & Trims
- Clean Splices in Seconds
- For Reel-To-Reel and 8-Track Recording Tape
- Splicing Tape Supplied

A sturdy precision instrument for professional use in all splicing and editing applications. Gives clean, quick cuts on all tapes without losing a significant portion of the sound track. Splicing tape fed from below will not foul and waste tape. Sharp long lasting blades provide trouble-free operation. A must for professionals and demanding audio hobbyists. Imported. Shpg. wt., 9 oz.

28 R 09051 Net 2.89

Replacement splicing tape for above.

28 R 09069 Shpg. wt., 3 oz. Net .39

TELEPHONE PICKUP FOR CRADLE OR UPRIGHT PHONES



1⁴⁹

Induction telephone pickup for cradle or upright phones. Simply place base on pickup and connect leads to high impedance input of an audio amplifier or directly to a tape recorder. Imported. Shpg. wt., 5 oz.

99 R 10340 Net 1.49



HUM-BUCKING TELEPHONE PICKUP COIL

Designed with symmetrical hum cancelling pick-up coils to eliminate high stray hum pickup usually encountered with conventional coils. For use with high impedance tape recorders, amplifiers and dictating machines. Double suction cup for easy mounting. 5' cable with stripped leads. Shpg. wt., 4 oz.

28 R 32012 Net 4.95

TELEPHONE PICKUP COIL



1³⁹

Designed to feed into the microphone input of a tape recorder or any high gain amplifier. Easily attached to the telephone by rubber suction-type attachment. Has 5 foot shielded cable with stripped ends. Imported. Shpg. wt., 4 oz.

99 R 61970 Net 1.39

Tape Recording Accessories


COUSINO AUDIO VENDOR

- Continuous Repeating Magnetic Magazine Tape

Endless tape loop magazines provide continuous play. Ideal for sales messages, language study, sleep learning, exhibits, etc. Fits most standard recorders. Running time in minutes at 3 1/4 ips. Counter-clockwise. 1500 Series 2 3/4" dia., 1310 Series 3 3/4" diam. 1210 Series 5 3/4" dia. Avg. wt., 9 oz.

STOCK NO.	TYPE	RUNNING TIME	NET EACH
28 R 35031	150003	3 Min.	3.95
28 R 35049	150005	5 Min.	4.75
28 R 35056	131008	8 Min.	7.15
28 R 35072	131012	12 Min.	8.00
28 R 35080	131015	15 Min.	8.95
28 R 35098	121024	24 Min.	9.75
28 R 35106	121030	30 Min.	12.95

TWIST-LOCK STYRENE CANS



- Buy the set.— save and GET THE CHEST FREE!

12 dust-free, moisture-proof unbreakable styrene tape cans in storage chest. Can has foolproof twist lock feature and is ribbed for convenient stacking. Center locking stud prevents reel movement on all 7" reels and most 3" and 5" reels. Shpg. wt., 4 1/2 lbs.
28 R 65103w Net 4.75

TWIST-LOCK CANS ONLY

28 R 65111 Wt., 6 oz. Lots of 6 ea. .40 Single ea. .45

LAFAYETTE RECORDER PATCH CORD



99c

Ideal For Making Connections From Radio, Phono or TV To Tape Recorder

Handy 6 ft. lead has insulated alligator clips at one end and RCA phono plug at the other. Supplied with shielded phono plug adapter to adapt the RCA phono plug to standard phono plug if necessary. Attach alligator clips to speaker terminals and simply plug other end into tape recorder. Ideal for recording from Radio, Phono or TV. Imported. Shpg. wt., 5 oz.

99 R 15174 Net .99

LAFAYETTE STEREO RECORDER PATCH CORD



1.39

Ideal for making tape recorder connections from stereo receivers, tuners and amplifiers having front panel tape output jacks. A convenient 6 foot cable has stereo 3 conductor phono plug at one end and two standard color coded RCA type phono plugs at the other. Insert phono plug into front panel tape output jack of receiver, tuner or amplifier and connect phono plugs to inputs of tape recorder for convenient connection. Imported. Shpg. wt., 5 oz.

99 R 63364 Net 1.39

HEAD AZIMUTH ALIGNMENT TAPE



For accurate alignment of recorder heads for maximum sound output. 100 ft.

on 2 1/2" reel. Tape has 6 kHz steady tone in either direction. Instructions included. Shpg. wt., 3 oz.

28 R 71184 Net 1.29

TAPE THREADER



85c

Eliminates awkward fumbling. Place tape against reel, slip threader on—turn

crank—tape is threaded. Use with all 5" and 7" reels. Shpg. wt., 3 oz.

28 R 60211 Net .85

CLEAR PLASTIC REELS



As Low As 11c IN LOTS OF 4

Sturdy, non-warp plastic reels for recording tape. All clear plastic. Avg. Shpg. wt., 4 oz., singly.

28 R 23052 3" reel lots of 4, Ea. .11

Singly, Ea. .13

28 R 23011 3 1/4" reel lots of 4, Ea. .12

Singly, Ea. .15

28 R 23029 5" reel lots of 4, Ea. .26

Singly, Ea. .29

28 R 23037 7" reel lots of 4, Ea. .31

Singly, Ea. .34

LOW TORQUE REELS

Professional type clear plastic reels with large hubs for smooth tape feed and reduced flutter. Shpg. wt., 4 oz. ea.

5" Low Torque Reel—Holds 400 ft. 1 1/2 mil,

600 ft. 1 mil, 800 ft. 1/2 mil or 1200 ft.

1/2 mil triple play tape.

28 R 23060 lots of 4, Ea. .49

Singly, Ea. .54

7" Low Torque Reel—Holds 960 ft. 1 1/2 mil,

1440 ft. 1 mil, 1920 ft. 1/2 mil or 2880 ft.

1/2 mil triple play tape.

28 R 23045 lots of 4, Ea. .54

Singly, Ea. .60

RECORDER TEST TAPE



98c

Checks speed, timing, wow and flutter. For 7 1/2 IPS. Accurate within 1/10 of one percent. Shpg. wt., 2 oz.

28 R 50014 Net .98

REUSABLE CLEAN-LUBE CLOTHS



Protects recording tape by depositing a silicone film. Eliminates tape squeal & chatter. Cloths are washable. Pkg. of 4 cloths. Shpg. wt., 4 oz.

28 R 72638 Net .79

REEL LOCKS



45c

Set of Two

Holds tape recorder reel in place by locking spindle to reel. Especially useful if recorder is in vertical position. Will not interfere with normal operation of reels. Easily removable. Imported. Shpg. wt., 3 oz.

99 R 15190 Set of two Net .45

METAL STORAGE CANS



35c Lots of 6

Cans are ribbed for easy storage. Precision fit. Baked enamel finish. Av. wt., 8 oz.

28 R 63066 5" Can lots of 6, Ea. .35

Singly, Ea. .39

28 R 63074 7" Can lots of 6, Ea. .38

Singly, Ea. .45

METAL TAPE STORAGE CHEST



3.98

STANDARD CASE: Sturdy all steel carrying case. Holds 12 7", 5" or 3" intermixed reels and cans. Twin snap locks. Platinum gray hammerdrol finish. Metal separators. Index cards.

28 R 15017 Shpg. wt., 4 3/4 lbs. Net 3.98

DELUXE CASE: Holds 12 7", 5" or 3" intermixed reels and cans. Finger touch roll-out action, drop-front with spring lock. Exterior and interior index.

28 R 15025 Shpg. wt., 7 1/4 lbs. Net 6.50

PROFESSIONAL EDITALL TAPE EDITING KIT



All you need for a complete professional editing job. The cutting block is made of duraluminum precisely machined and polished (makes straight or diagonal cut). All accessories such as grease pencil, blades, splicing tape (66 ft. roll of 3/4") supplied. Comes with instruction booklet—in a smart plastic case. Shpg. wt., 7 oz.

28 R 38050 Net 10.00

EDITALL KP-2 TAPE EDITING And SPLICING KIT



Easy to use, makes perfect splices without trimming or damage. Complete kit consists of editall plastic block, 30 pre-cut editall splices, cutting blade, grease pencil, instruction booklet and tape guide. Shpg. wt., 4 oz.

28 R 38068 Net 3.50

Package of 50 pre-cut Editall splices.

28 R 38076 Shpg. wt., 3 oz. Net 1.50

To Speed Your Mail Order—Please Give Your Zip Code Number

Lafayette Cat. No. 720 133

ROBINS® TAPE SPLICERS AND EDITING ACCESSORIES



(A) TK-9 COMPLETE TAPE EDITING WORKSHOP. Tape Winders for reels to 7", Deluxe Tape Splicer with Splicing Tape. Sturdy walnut grained base has Calibrated Tape Timing and Editing Scale, Editing Pencil and Editing Guide Book included. Shpg. wt., 2 3/4 lbs. **28 R 71069** Net **16.75**

(B) TS-8D DELUXE STEREO SPLICER. Precision diagonal cut and "Gibson Girl" trim. "See-thru" windows show "Cut" and "Trim." Tape guide and fingers secure tape. Tape dispenser has 1/2" x 100' roll Splicing Tape. Replaceable cutter pad and blades. Blade centering adjustment for accuracy. Of super-strength Cycloc. Instructions. **28 R 60096** Shpg. wt., 1 lb. Net **8.69**

(C) TS-75 STANDARD STEREO SPLICER. Same features as TS-8D. Made of plated steel and plastic. Dispenser has 3/4" x 100' roll Splicing Tape. Instructions. **28 R 71416** Shpg. wt., 9 oz. Net **6.29**

TS-7J JUNIOR "STEREO" SPLICER. (Not illus.) Same as TS-7S, less dispenser and tape. Uses 3/4" wide splicing tape. **28 R 71424** Shpg. wt., 8 oz. Net **5.45**

(D) TS-6 DELUXE "CUT-N-SPLICE." Cuts tape at 30°, 45°, or 90° angle. 25 self-stick Splicing Patches included in built-in tray of splicer. **28 R 70863** Shpg. wt., 6 oz. Net **2.99**

TS-5 "CUT-N-SPLICE" METAL SPLICING BLOCK. (not illus.) With 25 self-stick Splicing Patches. **28 R 70871** Shpg. wt., 5 oz. Net **2.29**

(E) TS-14 PROFESSIONAL STUDIO PRECISION TAPE-SPLICING BLOCK. Has 90° and 45° cutting guide. Burnishing plate and roller provided. Sturdy cast base has rubber bumpers. Includes cutting blade and supply of 100 Splicing Patches. Shpg. wt., 4 lbs. **28 R 72059** For 3/4" tape. Net **16.50**

SPLICING TAPE. Mylar. Wt. ea. 2 oz. (Not illus.)

Stock No.	Type	Width	Length	Net
28 R 70889	TST-235	1/4"	x 300'	.75
28 R 70897	TSY-376	3/8"	x 275'	.75
28 R 70905	TST-501	1/2"	x 250'	.75

TST-233 Pkg. of 75 Self-Stick Splicing Patches for TS-14, TS-6, TS-5 Splicers.
28 R 70921 (not illus.) Net **7.75**

(F) TM-2 MAGNETIC TAPE EDITING PEN. Erase single sounds, noise, etc. from recordings. Fade in and out for special sound effects. **28 R 71549** Shpg. wt., 3 oz. Net **1.65**

TL-240 COLOR-CODE SPLICING PATCHES. (Not illus.) 12 each of 6 colors, Orange, Yellow, Red, Blue, Green and White. Splice color patches between subjects on reel for indexing. **28 R 71135** Shpg. wt., 3 oz. Net **1.09**

TSP-50 SENSING AND CUEING PATCHES. (not illus.) Aluminum foil, 1/4" wide x 3/4" lengths. For recorder with automatic stop and reverse control. Pkg. of 50, wt., 2 oz. **28 R 71150** Net **1.05**

TSP-240 SENSING AND CUEING TAPE. Roll of aluminum foil tape .240" wide x 150" length. Prepares tapes for use with recorders having automatic stop and reverse controls. (Not illus.) **28 R 72653** Shpg. wt., 4 oz. Net **1.98**

(K) TK-1 COLOR-COOLING TAPE LOG KIT. Color-code indexing by title, artist, category. 120 page color-indexed Log Book, 240 Title Labels, 72 Tape End Tabs, 48 Numbered Cueing Spots, 30 Box Ends, in 6 Colors, and Pen. **28 R 71457** Shpg. wt., 1 lb. Net **5.79**



(G) TK-30 TAPE EDITING KIT. Contains: TS-6 "Cut-N-Splice" Splicer, 25 self-stick Patches, White Leader Tape - 1/4" x 100' on a 2 1/2" reel, 12 Tape Clips, Tape Cleaning Cloth, 3" reel of Tape-Clean, and 120 Color Title Labels. **28 R 72067** Shpg. wt., 9 oz. Net **5.98**

(H) TK-80LX DELUXE KIT. Contains: TS-8D Splicer, Splicing Tape, Threader, Head Clean and Lube 2 oz. bottles, Clips, Reel Title Labels, Reel Holders, and Editing Guide Book. Shpg. wt., 2 1/4 lbs. **28 R 70442** Net **13.78**

(I) TK-14 RECORDER MAINTENANCE KIT. Contains: Head Demagnetizer, 2 Tape Cleaning Cloths, and 3" reel of Tape Clean. **28 R 71598** Shpg. wt., 9 oz. Net **4.79**

(J) TK-7 RECORDER KARE KIT. 2 oz. bottles of Head Cleaner, Head and Guide Lubricant, Tape Drive Oil, Non-Slip for Tape Drives, and 50 Cleaning Swabbies. **28 R 70491** Shpg. wt., 1 3/4 lbs. Net **2.75**

TK-6 HEAD-CLEAN AND LUBE KIT. (Not illus.) 2 oz. bottles - Head Cleaner and Head and Guide Lubricant. **28 R 70855** Shpg. wt., 11 oz. Net **1.39**

TT-16 COLOR-CODING LEADER TAPES. (Not illus.) Color-Code subjects, 100 ft. each Red, Blue, Yellow, Green, White on 2 1/2" reels. **28 R 71499** Shpg. wt., 6 oz. Net **2.85**

TT-100C CLEAR LEADER TAPE. (Not illus.) 100 ft. x 1/4" wide on a 2 1/2" reel. **28 R 71887** Shpg. wt., 3 oz. Net **.81**

TC-75 TAPE CLIPS. (Not illus.) Plastic. Reusable. Keeps tape from unwinding. Fits all reels. 72 clips in handy plastic container. **28 R 71093** Shpg. wt., 4 oz. Net **.99**

TL-80 TAPE AND BOX INDEX SPOTS. (Not illus.) Pkg. of 240. Numbered 1 to 24, 2 sets in 5 basic Colors. Self-stick. Index tapes and their matching boxes or canisters. Wt. 3 oz. **28 R 72075** Net **.99**

TL-240 COLOR-CODE TITLE LABELS. (Not illus.) 2" x 1/2" self-stick, 40 each of 5 Colors. Write or type. Label reels, boxes, canisters, etc. Pkg. of 240. Wt. 4 oz. **28 R 71507** Net **1.19**

TK-2 TAPE KARE KIT. (Not illus.) 2 oz. bottle of Head Cleaner and Tape Cleaning Cloth. **28 R 70483** Shpg. wt., 7 oz. Net **1.39**

TK-20 TAPE HEAD CLEANER. (Not illus.) 2 oz. bottle with applicator. **28 R 60310** Shpg. wt., 6 oz. Net **.75**

TK-33 TAPE DRIVE OIL. (Not illus.) 2 oz. bottle with applicator. Inhibits rust and oxidation. **28 R 72083** Shpg. wt., 7 oz. Net **.57**

TK-22 HEAD AND GUIDE LUBRICANT. (Not illus.) 2 oz. bottle with applicator. Silicone base liquid. Provides friction-free tape path. **28 R 71937** Shpg. wt., 6 oz. Net **.75**

LB-1 LOG BOOK. 120 page Log Book for indexing recordings on reel-to-reel tapes, cassettes, 8-track cartridges and phono records, by title, artist and category. (Not illus.) **28 R 72661** Shpg. wt., 6 oz. Net **1.29**



(L) TLA-1 TAPE-CLEAN-LUBE SYSTEM. Self-stick base mounts to deck of any recorder. Applies liquid Silicone Lubricant and Cleaner to both sides of tape while playing. Reduces recorder head and guide wear. Stops tape squeal. Reduces drag. Includes extra Lube-Cleaner. **28 R 71911** Shpg. wt., 7 oz. Net **3.29**

TLA-2 TAPE LUBE-STICK. (Not illus.) Lubricates both sides of tape at same time while in use. Stops squeal, reduces drag. Self-stick base mounts to recorder deck. **28 R 71929** Shpg. wt., 3 oz. Net **2.19**

TZ-9 REPLACEMENT KIT FOR TLA-1 TAPE CLEAN LUBE SYSTEM. Bottle of tape cleaner and lubricant with two felt applicators. **28 R 72679** Shpg. wt., 6 oz. Net **1.79**

TZ-11 REPLACEMENT KIT FOR TLA-2 TAPE LUBE STICK. Two replacement lube sticks. **28 R 72687** Shpg. wt., 3 oz. Net **1.15**

HEAD DEMAGNETIZERS. In normal use, heads build-up magnetism resulting in loss of fidelity. Demagnetizers safely remove magnetism from heads to improve recorder sound performance.

(M) TD-6 PROFESSIONAL UL LISTED HEAD DEMAGNETIZER. 110 VAC. Wt., 10 oz. **28 R 60260** Net **7.65**

(N) TD-3 DELUXE HEAD DEMAGNETIZER. Fully encapsulated components. 110 VAC, wt., 8 oz. **28 R 60278** Net **4.39**

(O) TRP-5 HIGH GRAIN PROFESSIONAL "SOUND-RING" TELEPHONE INDUCTION PICK-UP. High sensitivity for "full depth" recording of phone conversation. Attaches to phone with ease. Slips over and surrounds the earpiece of the phone. 3 ft. shielded cable is complete with mini-plug for use with all tape recorders. **28 R 72695** Shpg. wt., 6 oz. Net **3.99**

BULK TAPE ERASERS



MAGNETIC BULK TAPE ERASERS. Erase tapes in seconds to below normal recorder erase head level. Restores tapes to "blank" condition. For magnetic striped film also. All units 110-120 V, 50-60 Hz. AC.

(P) TM-77 DELUXE BULK ERASER. For 1/4" tape, reels to 7". Erasure 2 to 4 db below normal erase head level. Size: 2 3/4" x 3 3/4" x 6 1/4". Shpg. wt., 4 1/4 lbs.
28 R 60252 Net 18.40

(S) TM-99 PROFESSIONAL UL LISTED BULK ERASER. For tape to 1/2" wide, reels to 1D 1/2". Erasure 3 to 6 db below erase head level. Size: 5 1/4" x 6 3/4" x 3 3/4". Wt., 9 3/4 lbs.
28 R 60245 Net 33.00

TPP-2 RECORDER REPLACEMENT PRESSURE PADS (Not illus.) Pkg. of 44 self-stick assorted sizes in two thicknesses for most recorders. Shpg. wt., 4 oz.
28 R 71119 Net .85

(BB) TSD-1 AUTOMATIC TAPE SHUT-OFF. Attaches to side of recorder. Recorder plugs into side of unit. 110 VAC, 3 amp. rating. Arm gently contacts recording tape. When tape plays through and ends, automatically shuts off recorder or other devices.
28 R 72158 Shpg. wt., 8 oz. Net 5.49

(Y) TK-12 AUDI/O VISUAL ACCESSORY KIT. For language labs, recording studios, audio/visual depts. and serious home recordists. Contains: TS-8D Splicer, 6 rolls 1/2" Splicing Tape, Tape Threader, Tape Cleaning Cloths, Head Cleaner, Lubricant, 24 Tape Clips, 180 Title Labels, Tape Strobe and Light Kit, U.L. Listed TM-99 Bulk Tape Eraser and TD-6 Demagnetizer. Shpg. wt., 14 1/4 lbs.
28 R 70517 Net 58.25

(Z) TRP-2 PHDNE PICK-UP. Fastens to phone by suction cup. Provides clear recording of phone conversations. Has 5 ft. cable with stripped ends to attach connector to fit recorder.
28 R 70947 Shpg. wt., 3 oz. Net 2.49

(AA) TK-4H TAPE EDITING AND CARE KIT. Contains TS-2 Tape splicer assembly mounted to recorder, 1/2" x 100" roll of splicing tape, tape cleaning cloths, 12 tape clips and tape editing and splicing guide. Shpg. wt., 8 oz.
28 R 72703 Net 2.44

TL-9 LONG TITLE LABELS. (Not illus.) 3/8" x 9 1/2". Self-stick. Label canisters, boxes, etc.
28 R 72166 Pkg. of 50. Wt. 4 oz. Net .79

EMPTY REELS FOR ALL RECORDERS. Packaged clear plastic reels in all sizes, except * is pkg. of six 3" reels in assorted colors. + indicates Low Torque reel. Avg. wt. per pkg., 10 oz.

Stock No.	Mfr's Type	Size	Pkg. Qty.	Net
28 R 70954	TR20-6	2"	6	.75
28 R 70962	TR25-6	2 1/2"	6	.75
28 R 70970	TR30-6	3"	6	.69
28 R 70988	TR32-4	3 1/4"	4	.69
28 R 71259	TR36-6*	3"	6	.85
28 R 70996	TR40-4	4"	4	.85
28 R 71002	RS50-2	5"	2	.75
28 R 71017	TR53-2+	5"	2	1.19
28 R 71110	TR70-2	7"	2	.85
28 R 71028	TR74-2-	7"	2	1.35

(CC) TCP-12 SET OF 12 DELUXE INDIVIDUAL MDLDEO TAPE SAFES. Protects 7" tapes from dust, dirt, aging. Hinge covers. Bottoms have dovetail grooves to fit metal wall mount bracket included. (less tape and reels). Shpg. wt., 6 3/4 lbs.
28 R 71226 Net 12.60

TB-15 CARDBOARD TAPE MAILING BOXES. (Not illus.) Package of 15. For up to 3 1/4" reels.
28 R 71580 Shpg. wt., 8 oz. Net .89



RECORDER AND TAPE CARE ACCESSORIES

TAPE-CLEAN. (Not illus.) Chemically treated cloth tape cleans and lubricates heads and guides of recorder when played. Deposits film of Silicone for friction-free tape path.
THC-3, 3" reel Wt. 3 oz.
28 R 71168 Net 1.35

THC-5, 5" reel. Wt., 5 oz.
28 R 60351 Net 2.29

(U) THC-12 QUICK-CLEAN FELT PEN. With pocket clip. Applies efficient fast drying solvent to remove dirt, accumulated oxide from recorder heads to improve sound fidelity. Includes fluid supply. Imported.
28 R 72091 Shpg. wt., 3 oz. Net 1.10

(W) TK-5 TAPE STROBE AND LIGHT KIT. Tests speed accuracy of recorder at 15, 7 1/2, and 3 1/4 ips. Strobe tape, neon lamp. 110 V. A.C.
28 R 72125 Shpg. wt., 5 oz. Net 1.99

(X) BLDWER BRUSH "TBB-1." Squeeze blower and soft camel's hair brush. Blows away dust and other particles from delicate recorder heads, guides, and other parts. Ideal for phono, records, delicate parts, fine optical lenses, etc.
28 R 72133 Shpg. wt. 4 oz. Net 1.35

RMC-6 PLASTIC TAPE MAILING CANISTERS. (Not illus.) Impact resistant. Reusable. For up to 3 1/4" reels. With 2-sided address cards. Pkg. of 6. Wt. 8 oz.
28 R 71564 Net 1.19

TMC-30 DOUBLE-SIDED ADDRESS CARDS. (Not illus.) Pkg. of 30 for RMC-6 Tape Mailers.
28 R 71572 Shpg. wt., 6 oz. Net .85

TCB-18 CARDBOARD CASSETTE MAILERS. (Not illus.) Package of 18. Features "built-in stops" to prevent tape unwinding or becoming slack.
28 R 71952 Shpg. wt., 8 oz. Net .99

TL-5 COLOR-CODE TAPE BOX ENDS. (Not illus.) 30 self-stick, textured book binding strips in 6 colors. Reinforce and hinge lids.
28 R 71481 Shpg. wt., 6 oz. Net 1.99

THS-1 HEAD-KLEEN SPRAY. (Not illus.) 4 oz. Aerosol formula Head Cleaner removes accumulated oxide, grime, and other particles from recorder heads. Extension nozzle included for easy access to hard to reach heads.
28 R 71945 Shpg. wt., 6 oz. Net 1.39

THC-1 HEAD-KLEEN POLISHING TAPE. (Not illus.) 3" reel, 225 ft. Removes oxide and all particles from heads when played.
28 R 71606 Shpg. wt., 3 oz. Net 1.42

(T) MSW-125 "SWABBIES." Soft cotton tips wound on 6" applicators for cleaning and oiling hard to reach parts of equipment. Package of 125.
28 R 72117 Shpg. wt., 6 oz. Net .79

(V) TW-1 PRECISION TAPE STROBE. Metal, chrome plated. Needle bearings. Tests speed accuracy, wow, and flutter of 7 1/2 and 3 1/4 ips recorders. Instructions.
28 R 71176 Shpg. wt., 10 oz. Net 7.69



CASSETTE AND 8-TRACK CARTRIDGE ACCESSORIES

(DD) THC-15 "DOUBLE-HEADER" 8-TRACK CARTRIDGE ADVANCED MAINTENANCE KIT. Has special formula Non-Abrasive cloth Head-Cleaner Tape at one end, and Recorder-Drive Cleaner at the other end. Either end of cartridge fits equipment. Includes bottle of head cleaner solution.
28 R 72711 Shpg. wt., 1 lb. Net 2.99

(EE) THC-14 "DOUBLE-HEADER" 8-TRACK "TUNE-UP" CARTRIDGE. Has deeper head cleaner tape at one end, and tape drive cleaner at other end. Deeper cleaning tape has recorded beep signals to indicate number of times tape passes and contacts head of player-recorder during cleaning operation.
28 R 72729 Shpg. wt., 10 oz. Net 2.29

(FF) TSA-33 "MINI" CASSETTE STORAGE ALBUMS. Set of 3 library albums. Each stores 3 cassettes.
28 R 72737 Shpg. wt., 7 oz. Net 1.99

(GG) TSA-24 CASSETTE "TOTE-ALBUM." Fold-out album has 4 trays with recessed compartments and built-in "stops" to protect 24 Cassette tapes. Album has snaplock for secure closing and convenient carry handle. Complete with tape logs for listing recordings. Ideal for home shelves and outdoors.
28 R 72745 Shpg. wt., 1 1/2 lbs. Net 4.99

LAFAYETTE RECORDING TAPES

LAFAYETTE'S FAMOUS MONEY-BACK GUARANTEE

YOU BE THE JUDGE!



Lafayette's tape is made by outstanding nationally known manufacturers. It is first quality, splice free, red oxide coated, with full frequency response, uniform output and no "drop-outs." Resistant to moisture, heat, cold and abrasion.

We guarantee absolute satisfaction or your money back. If for any reason you are dissatisfied, return the tape within 30 days and we will refund your money less only transportation charges. You are the sole judge.

LAFAYETTE ACETATE BASE RECORDING TAPE

Provides wide range high fidelity response over the audio spectrum. Features noise free reproduction, low abrasion and uniform output. Average shpg. wt., 1 lb.

Stock No.	Feet	Reel	Mils	Wt. lbs.	Net Per Reel		
					1-4	5-24	25 up
28 R 01025	600	5"	1 1/2	1/2	.99	.90	.85
28 R 01033	900	5"	1 1/2	1/2	1.20	1.10	.99
28 R 01017	1200	7"	1 1/2	1	1.59	1.49	1.35
28 R 01041	1800	7"	1	1	1.98	1.88	1.79

LAFAYETTE MYLAR®* BASE RECORDING TAPE

Mylar base is especially strong, durable and break resistant, and is virtually impervious to heat, cold or humidity. All in clear plastic reels, individually boxed. Average shpg. wt., 1 lb.

Stock No.	Feet	Reel	Mils	Wt. lbs.	Net Per Reel		
					1-4	5-24	25 up
28 R 01058	1200	5"	1 1/2	1/2	1.75	1.58	1.42
28 R 01056	1800	7"	1	1	2.14	1.93	1.75
28 R 01074	2400	7"	1	1	3.10	2.79	2.51

LAFAYETTE TENSILIZED MYLAR®* TAPES

Tensitized mylar gives you the most permanent type of base and is therefore ideal for your most treasured recordings. All are 1/2 mil, thus permitting the maximum amount of footage per reel. Individually boxed.

Stock No.	Feet	Reel	Mils	Wt. lbs.	Net Per Reel		
					1-4	5-24	25 up
28 R 01090	300	3"	1/2	1/4	.60	.63	.59
28 R 01108	600	3 1/4"	1/2	1/4	.99	.90	.81
28 R 01116	1200	5"	1 1/2	1/2	2.25	2.03	1.83
28 R 01082	2400	7"	1 1/2	1	3.49	3.14	2.86
28 R 01231	3600	7"	1	1 1/4	4.88	4.49	3.99

* Mylar is the registered DuPont trademark for its polyester film.

LAFAYETTE TAPE FOR AUTOMATIC REVERSING TAPE RECORDERS

These tapes are specifically intended for tape recorders providing automatic reversing of tape. Each tape has a green color coded leader, a red color coded trailer, and a metal sensing strip at each end to activate the automatic reversing mechanism in tape machines having this feature. This tape may also be used on machines which do not reverse tapes. Average Shpg. wt., 1 lb.

Stock No.	Feet	Reel	Description	Net Per Reel		
				1-4	5-24	25 up
28 R 01165	1200	5"	1/2 mil mylar	1.99	1.84	1.67
28 R 01173	1200	7"	1/2 mil acetate	1.84	1.73	1.62
28 R 01181	1800	7"	1 mil mylar	2.89	2.69	2.43
28 R 01199	2400	7"	1/2 mil tens mylar	3.99	3.74	3.52

NORTONICS TAPE HEADS and ACCESSORIES

QUICK-KIT MOUNTING HARDWARE

Stock No.	QK No.	Description	Net Ea.
28 R 57357	18	SIDE-MOUNT All erase	1.25
28 R 57340	20	3000 RP series	1.25
28 R 57332	38	Other RP	1.25
28 R 57381	19	BASE-MOUNT All erase	1.25
28 R 57373	21	3000 RP	1.25
28 R 57365	66	Other RP	1.25
28 R 57928	102	SPECIALS Sony RP	1.75
28 R 57953	119	Sony RP	1.25
28 R 58256		Sony erase	1.50

FREE TAPE HEAD REPLACEMENT INFORMATION

Below is a partial tape head replacement listing. We can supply information and Nortronic replacements for over 2800 recorder models. If yours is not listed, write to us supplying manufacturer and model number, tape head function and track configuration.

AT-100 Alignment tape. Full-track 7 1/2 ips. For head azimuth alignment & NAB testing frequency response of any recorder or tape head. Shpg. wt., 6 oz.
28 R 57589 Net 9.90

AUTO AND HOME 8-TRACK CARTRIDGE REPLACEMENT HEAD

Record/Playback replacement head for practically all auto and home 8-track cartridge tape players. Shpg. wt., 3 oz.
28 R 58272 Nortronics 5800 Net 10.90

DIRECT REPLACEMENTS FOR POPULAR TAPE RECORDERS

Premium quality no-mount heads for replacement and conversion purposes. Use with mounting kits, below, for easy installation. Response 40-20,000 Hz at 7 1/2 ips. Crosstalk rejection 55 db. For

frequencies to 100 kHz. Av. Shpg. wt., 4 oz.
R-Record; P-Play; E-Erase. *Mounting hardware where required. (See below). With instructions.

Stock No.	Mfrs. Type	Func-tion	For WECOR Models—Some Prefixed CP, EP, LT, PB, TP			*Quik Kit	Net Ea.
			2008, 2208, 2323(-1, 1A)	2007, 2107(-1), 2150, 2007(-1), 2208(-1), 2250(-1), 2328(-1), 2356(-1, 1A, 1B), 2357(-1), 2360(-1), 2366-1B, 2391, 3392, 3393, 4007-1.	—		
For CONCORD							
28 R 57084	3101	RP	320, 330	—	66	10.60	
28 R 57019	1000	RP	400D, 401, 400RP	—	19	9.50	
28 R 57100	1401	E	440	—	66	21.50	
28 R 58090	1007	R	880	—	66	21.50	
28 R 58090	1007	RP	990, 994	—	66	21.50	
28 R 57100	1401	E	All above	—	19	0.50	
For VM Models							
28 R 57084	3101	RP	710(A), 711(A), 714, 730, 750(A), 1000	—	20	10.60	
28 R 58066	1009	RP	710Q, 720, 722, 735 (add A track) 740(1), 741, 755, 1001(-1, 2), 1002(-1, 2)	—	38	21.50	
28 R 57100	1401	E	710Q, 720, 722, 755, 1001(-1, 2), 1002(-1, 2)	—	18	9.50	
28 R 57282	6002	RPE	740, 740-1, 741	—	38	24.00	

Stock No.	Mfrs. Type	Func-tion	For SDNY SUPERSCOPE Some Prefixed TC, SSA			*Quik Kit	Net Ea.
			262(D, SL), 464(C, S, D, SL)	300, 500, 501, 521	200, 250, 260, 350, 530, 600		
28 R 57019	1000	RP	262(D, SL), 464(C, S, D, SL)	—	102	21.50	
28 R 57019	1000	RP	300, 500, 501, 521	—	119	21.50	
28 R 58090	1007	RP	200, 250, 260, 350, 530, 600	—	102	21.50	
28 R 57100	1401	E	260, 350, 530	—	306	9.50	

For REVERE, WOLLENSAK, 3M

Stock No.	Mfrs. Type	Func-tion	For REVERE, WOLLENSAK, 3M			*Quik Kit	Net Ea.
			10, 11, 15-27, 200, 202, 700, 700D, 750, 752, 762, 800, 800D, 826, 850, 852, 900, 905, 925, 926, 1000, 1005, 1025, 1026, 1100, 1105, 1125, 1126, 1200, 1205, 1225, 1226, 1400 (B, C, D, E), 1405, 1425, 1426, 1500, 1520, 1570, 1600, 1700, 1800, 2000, 2005, 2025, 7805, 7000 series	—	22.00		
28 R 56033	**RPE-20 or **RPE-23 (See Note)	RPE	10, 11, 15-27, 200, 202, 700, 700D, 750, 752, 762, 800, 800D, 826, 850, 852, 900, 905, 925, 926, 1000, 1005, 1025, 1026, 1100, 1105, 1125, 1126, 1200, 1205, 1225, 1226, 1400 (B, C, D, E), 1405, 1425, 1426, 1500, 1520, 1570, 1600, 1700, 1800, 2000, 2005, 2025, 7805, 7000 series	—	—	22.00	
28 R 57423	**RPE-23 (See Note)	RPE	100, 300, 301, older 2TR	—	—	18.05	
28 R 57423	RPE-23	RPE	115, 500, 555	—	—	18.05	
28 R 57282	6002	RPE	1280, 1281	—	—	24.00	

**RPE-20 replaces original Nortronics. RPE-23 replaces original Shure. *Quik-Kits purchased separately; see table above.

For PARASONIC

Stock No.	Mfrs. Type	Func-tion	Description	*Quik Kit	Net Ea.
28 R 57084	3101	RP	101S, 102S, 152S	21	10.60
28 R 57084	3101	RP	115, 500, 555	—	10.50
28 R 58165	1008	RP	755, 755S	66	21.50
28 R 57100	1401	E	755, 755S	19	9.50



Scotch

RECORDING TAPE AND ACCESSORIES



TYPE 111 STANDARD TAPE—1½ Mil Acetate Coated with red oxide. Popularly used for high fidelity all purpose recordings. On plastic reels. Av. shpg. wt., 1 lb. ea.

TYPE 150 EXTRA-PLAY TAPE—1 Mil extra strong Polyester base high fidelity tapes. Withstands high tension and break resistant. All plastic reels. Av. shpg. wt., 1 lb.

Stock No.	Type No.	Reel	Length Feet	Net Each	
				1-11	12 Up
28 R 33044	111-1.5	3"	150	.55	.49
28 R 33069	111-6	5"	600	1.77	1.60
28 R 33077	111-12	7"	1200	2.67	2.40

Stock No.	Type No.	Reel	Length Feet	Net Each	
				1-11	12 Up
28 R 33168	150-9	5"	900	2.40	2.16
28 R 33176	150-18	7"	1800	4.11	3.70

TYPE 202, 203 "DYNARANGE" SERIES—Designed primarily for professionals, but now available for home recording. Permits slower speeds without loss of fidelity. Low noise level, long wear. Ideal for transcribing. Shpg. wt., 1 lb.

TYPE 200 TENSITIZED—Tensitized Polyester .50 mil tapes. Provides twice as much playing time as the 1.5 mil standard tape. Stronger and more durable than usual long-play tapes. On plastic reel. Av. shpg. wt., 2¼ lbs.

Stock No.	Type No.	Base	Reel Lgth. Ft.	Net Each	
				1-11	12 Up
28 R 33382	202-6	1.5 Mil Poly.	5"	600	2.09
28 R 33390	202-12	1.5 Mil Poly.	7"	1200	3.50
28 R 33408	203-9	1 Mil Poly.	5"	900	2.97
28 R 33366	203-18	1 Mil Poly.	7"	1800	5.05

Stock No.	Type No.	Reel	Length Feet	Net Each	
				1-11	12 Up
28 R 33218	200-24	7"	2400	6.68	6.02
28 R 33226	200-48RPS	10½"	4800	15.11	13.60

TYPE 206, 207 HIGH OUTPUT-LOW NOISE TAPE—Professional mastering tape with 50% increase in output over standard low noise tapes "Posittrak" backing extends tape life, eliminates dropouts. Available in 60 and 90 minute lengths, recording both directions at 7½ IPS. Shpg. wt., 1¼ lbs.

TYPE 290—½ Mil polyester tensitized tape super strong 50% extra playing time has silicon lubricant to give minimum of friction wear.

Stock No.	Type No.	Playing Time at 7½ IPS	Net Each	
			1-11	12 Up
28 R 33507	206-¼-R60	60 minutes	4.49	4.04
28 R 33515	206-¼-R90	90 minutes	5.59	5.12

Stock No.	Type No.	Reel	Length Feet	Net Each	
				1-11	12 Up
28 R 33242	290-18	5"	1800	4.92	4.43
28 R 33267	290-36	7"	3600	7.99	7.19

TYPE 175 TENZAR—½ Mil tenzar coated with a high potency oxide, offers 16 times greater tear resistance than acetate backing. For continuous play, fast stops and starts non-drying silicone lubricated to protect recorder heads. Av. shpg. wt., 1 lb.

SCOTCH RECORDING ACCESSORIES

Stock No.	Type No.	Reel	Length Feet	Net Each	
				1-11	12 Up
28 R 33275	175-6	5"	600	1.68	1.51
28 R 33283	175-12	7"	1200	2.58	2.32

SPLICING TAPE

Pressure-sensitive tape made especially for splicing and editing magnetic tape. Av. shpg. wt., 2 oz.

SCOTCH 41-½-12.5 ½x150"	Roll in bag.		
28 R 33291	Lots of 12, Ea.	.43	Singly, Ea. .48
SCOTCH 41-½-1 ½x66"	Less dispenser.		
28 R 33309	Lots of 12, Ea.	.64	Singly, Ea. .71

SCOTCH CASSETTE TAPE
"Posittrak" backing eliminates "wow" and assures jam-free cassette performance. In plastic storage boxes. Av. Shpg. wt., 6 oz.
EXTENDED ENERGY CASSETTES — Highest quality, low noise, dependable cassette unsurpassed in dynamic range.

SENSING TAPE
Type 51 7/325—To actuate automatic stop and reverse on recorders so equipped. 150" long x ¾" wide. One side foil, other adhesive. Shpg. wt., 2 oz.
28 R 33150..... Lots of 12, Ea. 1.70 Singly, Ea. 1.89

Stock No.	Type	Minutes	Net Each	
			1-11	12 Up
28 R 33473	S-C-30	30	1.69	1.52
28 R 33416	S-C-60	60	1.99	1.79
28 R 33457	S-C-90	90	2.99	2.69
28 R 33465	S-C-120	120	3.99	3.59

LEADER-TIMER TAPE
Type 24-1W—Has 1 second interval markings for 7½" and 15" per second speeds. 100 ft. ¼" wide roll. Individually boxed. 2 oz.
28 R 33325..... Lots of 12, Ea. .54 Singly, Ea. .60

HIGH ENERGY CASSETTES — New cobalt-energized oxide provides 3 to 5 db increase in signal-to-noise ratio. Fully compatible with all cassette recorders.

7" SELF-THREADING REEL
Type PRST-7—Just lay recording tape inside and start recorder. Threads automatically. Snap-tight collar seals edges against dust. Shpg. wt., 8 oz.
28 R 33317..... Lots of 12, Ea. .90 Singly, Ea. 1.00

Stock No.	Type	Minutes	Net Each	
			1-11	12 Up
28 R 33523	S-C-30HE	30	2.39	2.15
28 R 33531	S-C-60HE	60	2.79	2.51
28 R 33549	S-C-90HE	90	3.99	3.59

LAFAYETTE
QUADRUPLE-PLAY
¼ MIL. RECORDING TAPE



- Four Times More Recording Time Than Standard Tapes
- Up To 32 Hours Recording

"LIVING LETTERS" 3 INCH TAPE IN PLASTIC MAILERS
3" reels providing ¼, ½ or 1 hour recordings. In convenient hinged plastic mailers meeting postal standards. Shpg. wt., 5 oz.

Greatly extends the playing time of all recorders, particularly 3¼" reel machines. An ultra-thin ¼ mil tensitized mylar recording tape with high-density magnetic coating. Offers excellent frequency response for sharper, brighter recordings. Outstanding performance with capstan-drive recorders.

Stock No.	Type	Lgth. Ft.	Net Each	
			1-11	12 Up
28 R 33424	111-1.5LL	150 (¼ hour)	.72	.65
28 R 33432	200-3LL	300 (½ hour)	1.46	1.31
28 R 33259	290-6LL	600 (1 hour)	1.99	1.79

1100 Ft. on 3¼" Reel. Records 7 hours 20 minutes (all four tracks) at 1½ ips; 3 hours 40 minutes at 3¼ ips. Shpg. wt., 4 oz.
28 R 01256..... Net 2.20

2400 Ft. on 5" Reel. Records 16 hours (all four tracks) at 1½ ips; 8 hours at 3¼ ips. Stereo 2-track records 8-hours at 1½ ips, 4-hours at 3¼ ips. Shpg. wt., ½ lb.
28 R 01264..... Net 4.65


4800 Ft. on 7" Reel. Records 32 hours (all four tracks) at 1½ ips; 16-hours at 3¼ ips; 8-hours at 7½ ips. Stereo 2-track records 16 hours at 1½ ips, 8-hours at 3¼ ips, 4- hours at 7½ ips. Shpg. wt., ¾ lb.
28 R 01272..... Net 8.95

#11 ADDRESS LABELS FOR LL MAILING CONTAINERS. Package of 10 additional pressure-sensitive adhesive address labels for "Living Letters" plastic mailing boxes. Shpg. wt., 3 oz.
28 R 33440..... Lots of 12, ea. .45 Singly, Ea. .50

Lafayette Stocks A Complete Line Of Tape Accessories

Electro-Voice and Astatic Cartridges

EXACT DUPLICATE PLUG-IN CARTRIDGE-STYLI COMBINATIONS



Exact duplicate replacements with styli. STYLI CODE: D Diamond, S Synthetic sapphire. 1 is 1 mil point for monoaural LP; 2 is 2 mil for mono LP & 78; 7 is .7 for stereo; 3 is 3 mil for 78 RPM. We will ship either Electro-Voice, Astatic or cartridge of original manufacturer. Color given to assist identifying original part sometimes is a color dot. Avg. shpg. wt., 3 oz.

FOR RCA

Stock No.	Fig.	Mfr. No.	Ast. No.	E.V. No.	Styli	Net
24 R 50203	A-1	105836,37	83-1	83	S-1	2.70
24 R 50229	A-1	108555	89-1	—	S-1	2.55

FOR WEBCOR

24 R 50237	A-2	A1919	White	91T	76	S-1, S-3	2.37
24 R 50245	A-2	A1920	Pink	91TX	76D	D-1, S-3	4.17

FOR ZENITH

24 R 50260	B	S15222	Green	97-1	113	S1	2.97
24 R 50278	B	S15780	Red & Green	97-2	112	S2	2.97
24 R 50302	C	142-72	Yellow	99-2	110	S2	3.00
24 R 50054	A-2	142-80	Blue	93T	56	S1, S3	2.37
24 R 50062	A-2	142-83	Orange	93TX	56D	D1, S3	4.17
24 R 50146	A-2	142-90	Red	93T-1	51	S1, S3	2.37
24 R 50393	E	142-103	Green	13AT	—	S7, S3	4.77
24 R 50195	E	142-106	Green	13ATX	—	D7, S3	6.57
24 R 50401	F	142-108	Blue	111	106	S7, S3	4.17
24 R 50419	F	142-109	Blue & Gold	111D	106D	D7, S3	5.97
24 R 50427	G	142-119	Dark Green	13T	13	S7, S3	5.37
24 R 50013	G	142-120	Dark Green	13TX	13D	D7, S3	5.37

OTHER STEREO-MONAUURAL TYPES

24 R 50096	E	Blue-Silver	105	66	S7, S3	4.17
24 R 51334	F	Brown-White	115	108	S7, S3	4.35
24 R 51342	F	Brown-White	115D	108D	D7, S3	5.97

REPLACEMENT CARTRIDGES FOR LAFAYETTE RECORD CHANGERS AND PHONOGRAPHS

STOCK NO.	For LAF. Model	MFR/TYPER	NET
24 R 29017	200	ST2VSS	3.60
24 R 30018	400	1116D	9.90
24 R 01665	AC50, AC50B		4.95
24 R 30239	30	5026D	6.90
24 R 29025	LSC45, LSC45B, LSC100B	TN48D	7.65
24 R 51524	MC22, LSC90	SC5M/667	5.37
24 R 40097	LSC25, LSC50, MS24, T60	SK5H	2.49
24 R 29033	M5B	SNH44	2.67
24 R 29041	MC10C	TDH44	3.00
24 R 29058	T33, TPS30, TPS35	CN72D	5.10
24 R 64006	LSC6000, LSC55	1A3D	3.99

EXACT REPLACEMENTS FOR PLUG-IN AND POWER POINT CARTRIDGES


Exact replacement for the popular Electro-Voice power points, Astatic Sound-flow and Jensen combination cartridge-styl. Made in U.S.A. Shpg. wt., 3 oz.

Replacement for Astatic 13TX, Electrovoice 13D, and Jensen A-44XSD. Has diamond .7 mil and synthetic sapphire 3 mil styli.

24 R 37036 Net 4.25
Replacement for Astatic 13T, Electrovoice 13, and Jensen A-44X. Same as above but both tips synthetic sapphire.

24 R 37028 Net 2.95
Replacement for Astatic 81T, Electrovoice 81, and Jensen A-41. Has 1 mil and 3 mil styli—both synthetic sapphire.


24 R 37010 Net-1.89



As Low As

189

STEREO PLUG-IN COMBINATION CARTRIDGE AND STYLI



- Monoaural or Stereo
- 0.5 V. Output

Play either stereo or monoaural. 4 terminals, channel separation: 20 db, response 20-15,000 Hz except * is 25 db and 30-20,000 Hz with 350 mw output. RIAA equalized. Output 0.5 V, tracking force 6 gm. Select unit with mount if making an original installation in a standard arm; units less mount just slip into original mount. We will ship either Astatic or Electro-Voice. Shpg. wt., 3 oz.

Stock No.	Ast. No.	E.V. No.	Styli	Mount	Net
24 R 50120	11T7	11	S7, S7	Less	3.57
24 R 50138	13TB	13B	S7, S3	With	4.17
24 R 50427	13T	13	S7, S3	Less	3.57
24 R 50161	13TBX	13DB	D7, S3	With	5.97
24 R 50013	13TX	13D	D7, S3	Less	5.37
24 R 50393	13AT*	—	S7, S3	Less	4.77
24 R 50195	13ATX*	—	D7, S3	Less	6.57

24 R 50435 STEREO MOUNT for all above 60

WIDE RANGE AND HI-FI PLUG-IN MONAUURAL CARTRIDGES



All are turnover type ceramic cartridges with dual 1 mil and 3 mil styli. Styli code same as all other cartridges on page. We will ship either Astatic or Electro-Voice. Shpg. wt., 3 oz.

WIDE RANGE TYPES

Replaces Sonotone 2T, Shure PC-2, 4 series and many others.

Stock No.	Ast. No.	E.V. No.	Styli	Mount	Net
24 R 50443	81TB	81B	S1, S3	With	2.97
24 R 50021	81T	81	S1, S3	Less	2.37
24 R 50476	81TX	81D	D1, S3	Less	4.17

HIGH FIDELITY TYPES

Replaces Sonotone 3T series, Shure PC-6, etc.

Stock No.	Ast. No.	E.V. No.	Styli	Mount	Net
24 R 50484	89TB	89B	S1, S3	With	3.57
24 R 50492	89T	89	S1, S3	Less	2.97
24 R 50518	89TX	89D	D1, S3	Less	4.77

24 R 50526 MONAUURAL MOUNT for all above 60

ASTATIC STEREO MONAUURAL CARTRIDGES

All crystal turnover cartridges except * which are ceramic turnover. All are equipped with .7 mil and 3 mil synthetic sapphire styli except † has .7 mil diamond and 3 mil synthetic sapphire styli to play stereo. LP and std. 78 RPM. Shpg. wt., 3 oz.


M	Stock No.	Fig.	Mfr. No.	Output	Net
	24 R 50534	M	70-TS	2.0V	4.35
	24 R 50542	M	74-TS	2.0V	4.35
	24 R 50559	N	76T5B	2.0V	4.77
	24 R 50567	M	80-TS	0.8V	4.50
	24 R 50575*	P	17	0.4V	7.05
N	24 R 50583†	P	17D	0.4V	9.45
	24 R 50591†	N	86D	0.8V	8.10
	24 R 50609	N	86T5B	0.8V	5.10
	24 R 51359*	Q	133	0.5V	5.85
	24 R 51367†	Q	133D	0.5V	8.25
P	24 R 51318	R	140	1.0V	4.50
	24 R 51326†	R	140D	1.0V	7.50
	24 R 51375	R	142	2.0V	4.35
	24 R 51425†	R	142D	2.0V	7.35
	24 R 51433	R	142R	2.0V	5.55
	24 R 51441†	R	142RD	2.0V	7.35
	24 R 51383	R	146	3.0V	3.87
	24 R 51458	R	710	0.5V	5.97
R	24 R 51466†	R	710D	0.5V	9.90

ASTATIC REPLACEMENTS FOR VACO CARTRIDGES

Crystal cartridges to replace Vaco cartridges used in many changers such as BSR, Glaser-Steers etc. Turnover type equipped with 2 needles. Tip Code: LS 1 mil and 3 mil; LT 7 mil and 3 mil. Shpg. wt., 3 oz.

Stock No.	Ast. No.	Tip	Fig.	Vaco Equiv.	Output	Net.
24 R 50617	470	LS	S	TO-45 X(G)	3.0	3.57
24 R 50625	472	LT	T	ST-2X, 100X, 20X, 20G	0.8	4.50
24 R 50633	474	LT	T	ST-200X, 40X, 4X, 40G	2.0	4.35

Astatic and Electro-Voice Cartridges



MONAURAL REPLACEMENT CARTRIDGES

Order by stock number. We will ship either Astatic or Electrovoice.

TURNOVER TYPES

All are equipped with dual synthetic sapphire stylus; 1 mil (LP) and 3 mil (std 78). Average shpg. wt., 3 oz.

Stock No.	AST No.	E.V. No.	Fig.	NET	Stock No.	AST No.	E.V. No.	Fig.	NET
24 R 50658	40T	—	AA	4.17	24 R 50781	310T	62	U	3.27
24 R 50666	40TB	—	B	5.07	24 R 50799	310TS	63	V	3.27
24 R 50690	55T	38	PP	4.77	24 R 50823	314TS	68	R	3.27
24 R 50716	62TY	43	J	4.77	24 R 50864	420	80	BB	3.27
24 R 50724	64TS	84	RR	4.17	24 R 50872	422	82	BB	3.57
24 R 50732	66TS	48	RR	4.35	24 R 30205	445	38	L	4.44
24 R 50740	66TY	49	J	3.90	24 R 50765	120	—	V-1	3.87
24 R 50757	118	91	V-1	3.87					

MICRO-GROOVE TYPES

All with synthetic sapphire 1 mil stylus for LP only. Except * has .7 mil. Shpg. wt., 3 oz.

Stock No.	AST No.	E.V. No.	Fig.	NET	Stock No.	AST No.	E.V. No.	Fig.	NET
24 R 51011	62-1	41	Q	2.97	24 R 51045	414-1	77	U	2.67
24 R 51029	310-7	58	T	2.37					

ALL GROOVE TYPES

All equipped with single 2 mil synthetic sapphire stylus for all speeds except * is osmium tip and † is less needle. Shpg. wt., 3 oz.


Stock No.	AST No.	E.V. No.	Fig.	NET	Stock No.	AST No.	E.V. No.	Fig.	NET
24 R 51052	16†	17	H	2.37	24 R 51102	66-2	—	H	2.97
24 R 51391	18	18	M	1.95	24 R 51128	310-2	59	T	2.97
24 R 51094	51-2	—	O	4.44	24 R 51144	414-2	78	U	2.67

REPLACEMENT FOR MAGNAVOX

Complete with mounting hardware and dual synthetic sapphire stylus except the LP needle in types ending in D are diamond. † indicates stereo cartridge. Shpg. wt., 3 oz.

Stock No.	Mrf. No.	Fig.	Replaces Magnavox No.	NET
24 R 51169	463	1	560216-1-2, 560217-2, 560218-1-2	6.30
24 R 51177	463D	1	560219-2, 560228-1-2, 560229-2	8.70
24 R 51185	461†	2	560281-1-4, 560296-3-7	6.30
24 R 51193	461D†	2	560290-1-3*	8.70
24 R 51201	459†	3	56029-1-2, 560275-1-2	6.30
24 R 51219	459D†	3	560290-1-3*	8.70
24 R 51409	163D†	4	560350-1	8.70
24 R 51417	165D†	4	560355-1	7.50
24 R 51516	195D	4	560365-2	7.50

* for Magnavox 560290-1 or -3 use Astatic 459 series for 2 hole mount, use Astatic 461 series for single hole mount.



REPLACEMENT CARTRIDGE FOR RCA

• Replacement for cartridges in many thousands of RCA-45 and many LP record changers • 1 mil Synthetic Sapphire Stylus • 2.3 volt output • High Impedance Crystal • Takes 7-10 grams pressure • 5/8" Mounting Centers

Exact replacement for many standard 45 RPM and 33 1/3 RPM cartridges. For RCA: 74067, 74625, 75476, 75575, 76318; and Shure: W31AR, P73, P73A, P73AR, P73R. 24 R 60012 Imported Net 1.25



Synthetic Sapphire replacement stylus for above. 24 R 02055 Net .99

E-V SERIES 20 HI-FI STEREO-MONOPHONIC CARTRIDGES



Hi-Fi Ceramic cartridges. Exclusive design eliminates tuntable rumble. 21 series are single needle types with .7 mil stylus to play stereo and LP monaural. 26 series are turnover types with .7 mil and 3 mil stylus to play stereo and all monaural records. TIP CODE S = SYNTHETIC SAPPHIRE, D = DIAMOND. Shpg. wt., 3 oz.

Stock No.	E.V. No.	Stylus	NET
24 R 30056	21	S-7	6.30
24 R 30072	21D	D-7	9.00
24 R 30098	26	S-7, S-3	6.90
24 R 30114	26D	D-7, S-3	9.90

ELECTRO-VOICE FEATHERIDE WIDE-RANGE CERAMIC



- Absolutely Scratch Proof
- Plays Stereo or Monaural

Protect your records with these fine floating-action spring-suspension cartridges which makes it practically impossible to damage either record or stylus. Reduces distortion caused by warped records. Both are Hi-Fi quality and will fit all standard arms with 1/4" or 1/2" mtg. centers. Excellent separation and low distortion. Equipped with .7 mil diamond and 3 mil synthetic sapphire stylus. Shpg. wt., 3 oz.

TYPE 149DF Track pressure 2-4 grams. Net 10.50
TYPE 150DF Tracking pressure 4-6 grams. Net 10.50
24 R 30171




REPLACEMENTS FOR RCA STEREO

All equipped with dual .7 mil and 3 mil styli. Types with * have diamond .7 mil and synthetic sapphire 3 mil; others both tips synthetic sapphire. Series 475 in phase; series 477 out of phase. Series 487 feather action. We will ship either E.V. or Astatic. Shpg. wt., 3 oz.

Stock No.	AST No.	E.V. No.	Replaces RCA	NET
24 R 51227	475	54	108213, A 11021	6.00
24 R 51235	*475D	54D	106960, A 11023	11.40
24 R 51243	477	133	106771, A, B	6.00
24 R 51250	*477D	133D	106770, A, B	11.40
24 R 51276	*487D	195D	111348	11.61

BSR STEREO AND MONAURAL TURNOVER CARTRIDGES



The BSR TC8S/SX1H stereo and TC8M/X1HE output monaural cartridges are designed for quality performance. Both are turnover types. Complete with turnover mechanism. Imported. Shpg. wt., 3 oz.


MONAURAL TYPE (Fig. A) Replaces BSR TC8M, TC8H/1, TC8H/2 and X1HE with 1 and 3 mil stylus, mtg. bracket. Net 1.79
24 R 40014
STEREO/MONAURAL (Fig. B) Replaces BSR, TC8S, TC8SM and SX1H. With .7 and 3 mil stylus, mtg. bracket. Net 2.25
24 R 40022

To Speed Your Mail Order—Please Give Your Zip Code Number

Lafayette Cat. No. 720 139

Popular Replacement Cartridges

ASTATIC - SONOTONE CERAMIC CARTRIDGES



High performance ceramic cartridge now in use by many phono manufacturers and ideal for either general replacement or updating present equipment. All are stereo, stereo-monaural except series 3T which is for monaural use only. Series 21T, 24TA are designed

for use with transistorized equipment. Series 9TAF, 16TAF, 18T, 21T, and 24TA feature the accident-proof, drop-proof Sono-flex "F" stylus. All have standard mounting dimensions. Styli code for all below: D—diamond, S—synthetic sapphire. Avg. shpg. wt. 3 oz.

Stock No.	Model	Fig.	Styli	Net	Stock No.	Model	Fig.	Styli	Net
24 R 79012	3T-S	1	S1-S3	5.85	24 R 79210	16TAF-S	5	S.7-S.3	4.92
24 R 79020	3T-SD	1	D1-S3	7.92	24 R 79236	16TAF-SD	5	D.7-S3	6.99
24 R 79079	8TA-4S	2	S.7-S3	6.60	24 R 79244	18TA -S	5	S.7-S3	4.53
24 R 79087	8TA-4SD	2	D.7-S3	8.70	24 R 79269	18TA -SD	5	D.7-S3	6.60
24 R 79095	8TA-4S7	2	S.7-S.7	6.60	24 R 79509	21T-S	6	S.7-S3	5.37
24 R 79178	9TAFHC-S	3	S.7-S3	7.05	24 R 79525	21T-SD	6	D.7-S3	7.35
24 R 79194	9TAFHC-SD	3	D.7-S3	9.09	24 R 79533	24TA-S	6	S.7-S3	6.60
24 R 79343	10T2-LB-S	4	S.7-S3	4.89	24 R 79556	24TA-SD	6	D.7-S3	8.79
24 R 79350	10T2-LB-SD	4	D.7-S3	6.96					

REPLACEMENT CARTRIDGE FOR GARRARD 30



Exact replacement cartridge for Garrard Model 30 automatic turntable. Ceramic turnover cartridge has .7 mil diamond stylus and 3 mil synthetic sapphire stylus. Shpg. wt., 3 oz. Net 6.90
 Replacement stylus assembly for above. Shpg. wt., 2 oz. Net 2.49
 24 R 30239
 24 R 03335

REPLACEMENT CARTRIDGES FOR VACO and RONETTE



Replacements for thousands of changers and players both imported and domestic. All types equipped with synthetic sapphire styli and turnover mechanism. Imported. Shpg. wt., 3 oz.

Stereo/monaural with .7 mil and 3 mil styli, mtg. bracket and knob. Output 7 volts. Replaces VACO ST-2, ST2X, ST-20, ST20X, ST-100, ST-100X; Ronette types 1, 2, 3, 4, 92 and 105 series; stereo OV series and stereo T series; Astatic 86TSB, 80TS, and EV 95 and 97. Imported. Net 1.99
 99 R 10167

REPLACEMENT STYLI

99 R 10175 .7 mil for stereo Net .99
 99 R 10183 3 mil for 78 Net .99
 Diamond .7 mil for stereo
 24 R 01586 Net 2.49

Stereo/monaural. Same as above but output is 2 volts. Replaces VACO ST4, ST4X, ST5, ST5X, ST40, ST40X, ST200, ST200X and Ronette 106 series, 208 series, Astatic 76TSB, 70TS and E.V. 96 and 98. Imported. Net 2.99
 24 R 79103

Monaural with 1 mil and 3 mil styli, mtg. bracket and knob. Output: 2-3 volts. Replaces VACO types T45, T045, T045X. Ronette types 15, 18, 21, 24, 7825, DC395, DC395S, DC400, DC-400-222, DC-400-222S, DC500, TO-284 series, T0285T, T0287 series, TO-395 series, TO-400-200, TO-400-222; Astatic 420, 120 and E.V. 80, 88. Imported. Net 1.79
 99 R 10225

BSR 45 RPM SPINDLES



Fig. A



Fig. C

For automatic operation of a stack of 45 R.P.M. records on BSR Changers. Shpg. wt., 4 oz.

Fig. A. For use with BSR Model UA-15 Net 1.75
 24 R 40055

Fig. C. Flat spindle for use with UA-15SS, UA-25, UA-40. McDonald 400, 500, 500A, 600; BSR 1500, 2500, 15, 25, 65 and 75 series. Net 1.49
 24 R 02204

Fig. C. For use with Mini-Changer UA-50. Net t.49
 24 R 02568

REPLACEMENT FOR SONOTONE 2TA-S CERAMIC CARTRIDGES



3 95

This high fidelity monaural turnover cartridge is equipped with dual styli to play all types of both monaural and stereo records. Has .7 mil and 3 mil synthetic styli. Replaces a host of cartridges including previous Sonotone models of 2T series, 9980 series which were used in thousands of record changers and players. Frequency response: 20-20,000 Hz—flat to 12,000 Hz; output 1-volt; compliance 2.0x10⁻⁴ cm/dyne; tracking force 6 grams. Ceramic element highly immune to heat and humidity. Imported. Net 3.95
 24 R 79111 Shpg. wt., 3 oz.

G.E. CARTRIDGES



VR-1000



VR-II

VR-1000 STEREO CARTRIDGES

Variable reluctance stereo cartridges featuring extended frequency response and low tracking pressure. Supplied with diamond stylus.

VR-1000-3 ELLIPTICAL DIAMOND NEEDLE STEREO CARTRIDGE. For any quality changer or tone arm that tracks from 3-7 grams vertical force. Shpg. wt., 5 oz. Net 20.84
 21 R 38493L

VR-1000-5 FOR TURNTABLES. Complete with .5 mil. diamond stylus for use with automatic turntables or professional tone arms that track at 4 grams or less. Shpg. wt., 5 oz. Net 15.10
 21 R 38014L

VR-1000-7 FOR CHANGERS. Essentially the same as VR-1000-5 but designed for the greater 3-7 gram tracking force required by most record changers. .7 mil diamond stylus. 21 R 38030L Shpg. wt. 5 oz. Net 12.59

VR-II MONAURAL CARTRIDGES

Variable reluctance monaural cartridges featuring smooth frequency response and extremely high compliance. Utilizes clip-in tip stylus assembly for simple installation. Cartridges supplied less stylus. Select stylus type(s) to suit your particular application from listing below.

VR-115 SINGLE-TYPE CARTRIDGE. "Single-Play" cartridge accommodating one stylus. Supplied less stylus. Select stylus from listing below. Shpg. wt., 3 oz. Net 5.42
 21 R 38519L Cartridge less stylus

VR-110 DUAL TYPE CARTRIDGE. Convenient dual stylus "Triple-Play" cartridge. A twist of the knob brings either microgroove (LP or 45 RPM) or standard, 78 RPM stylus into position. Supplied less stylus. Select stylus from listing below. Shpg. wt., 3 oz. Net 6.67
 21 R 38535L Cartridge less stylus

G.E. STYLI

Individual stylus tips for VR-II series cartridges. D—diamond stylus. S—synthetic stylus. Shpg. wt., 3 oz.

Stock No.	GE Type	Stylus	Net
21 R 38188L	4G-07S	.7 mil S	1.42
21 R 38196L	4G-02S	2.5 mil S	1.42
21 R 38204L	4G-03S	3 mil S	1.42
21 R 38212L	4G-07D	.7 mil D	3.33
21 R 38220L	4G-02D	2.5 mil D	3.33
21 R 38238L	4G-03D	3 mil D	3.33

MODELS C100A and C200 STEREO CERAMIC CARTRIDGES



C100A



C200

MODEL C100A—A quality stereo ceramic replacement cartridge for thousands of phono graphs and changers in use today. Freq. response 20 thru 12,000 Hz. output 450 millivolts. With .0007 dia. and .003 synthetic sapphire stylus. Net 8.07
 21 R 38469L Shpg. wt., 3 oz.

MODEL C200—Essentially same as Model C100A except frequency response 20 thru 17,000 Hz. output 300 millivolts. Net 8.07
 21 R 38477L Shpg. wt., 3 oz.
 TA-1 Replacement stylus for C100A and C200. Net 4.17
 21 R 38485L Shpg. wt., 3 oz.

Phono Preamps, Amplifiers & Accessories

LAFAYETTE PHONO PREAMPLIFIERS

- Ideal For Use With Amplifiers That Do Not Have Low Level Inputs For Magnetic Cartridges

LAFAYETTE SOLID STATE STEREO PHONO PREAMP

- 4 Silicon Transistor Circuitry
- Compact Size Permits Concealed Mounting

A self-powered, compact solid-state stereo phono preamplifier especially designed for use with Hi-Fi stereo amplifiers not having magnetic cartridge inputs. The exceptional feature of this preamplifier is that its compact size permits mounting quickly and simply to the sides or back of the record changer/player base, without marring the appearance of your matched Hi-Fi system.

Frequency response: 30-20,000 Hz. RIAA Playback Curve. Gain: 6 mv input for 0.5 volt output. Input Impedance: 50,000 ohms. S/N ratio over 60 db. Input: 2 RCA type phono jacks. Output: 2 RCA type phono jacks. Power Supply: 117 VAC 50/60 Hz. Power consumption: 1 watt. Size: 4x2½x1½". Imported Shpg. wt., 1 lb. Net 7.95
99 R 02198

7⁹⁵




MONAURAL PHONO PREAMP

A self powered monaural preamplifier for use with any Hi-Fi amplifier that does not have a low level input for magnetic cartridges, tape head, or microphone. Response: ±2 db 30-20,000 Hz. Gain (Phono): 40 db, 5 mv input for 1 volt output. Gain-Mike 60 db, 1 mv input for 1 volt output. Output impedance: 100,000 ohms. Phono-Tape Equalization

switch, 2 input jacks, 16 inch output lead with RCA phono plug. Power supply: 105-125 VAC, 50/60 Hz, 4 watts. Size: 3½x3¾x3¼". Polished chrome chassis. Less 12AX7A tube. Imported. Shpg. wt., 2 lbs. Net 6.95
99 R 01380
12AX7A tube for above. Shpg. wt., 4 oz. Net 1.40
36 R 31900

6⁹⁵




STEREO PHONO PREAMP

Self-powered stereo preamplifier for use with any stereo amplifier that does not have low level inputs for magnetic cartridge, tape head, or microphone. Response: ±2 db 30-20,000 Hz. Gain (Phonograph): 40 db, 5 mv input for 1 volt output. Gain (Microphone): 60 db, 1 mv input for 1 volt output. Output impedance: 100,000 ohms. Preamp has Phono-

Tape Equalization Switch, 4 input jacks, 2 16-inch output leads with RCA phono plugs. Power supply: 105-125 VAC, 50/60 Hz, 8 watts. Size: 5¾x3¾x4½". Polished chrome chassis. Less 2 12AX7A tubes. Imported. 99 R 01398 Shpg. wt., 2¼ lbs. Net 9.95
12AX7A tube for above (2 required) Net 1.40
36 R 31900

9⁹⁵



THREE TUBE AC-DC PHONO AMPLIFIER

4⁹⁸ (Less Tubes)

- Output Transformer
- Variable Tone Control




Equipped with a variable tone control and volume control with off position. Delivers up to 2 watts output to 3 ohm speaker. Uses 3 tubes: 35W4, 50C5, 12AV6. Input impedance: 150 K ohms. Features top mounted output transformer. Less tubes. Size: 5¾ x 2¾ x 4". Imported. Shpg. wt. 1½lbs. Net 4.98
99 R 01539
36 R 90013M Kit of 3 tubes. Shpg. wt., 9 oz. Net 3.38

4 TUBE AC/DC STEREO PHONO AMPLIFIER

6⁹⁵ (Less Tubes)

- 2 Output Transformers
- 2 Separate Tone Controls



Powerful yet compact stereo amplifier produces up to 2 watts per channel. Uses 4 tubes: 2 12AV6 2 50C5. Selenium rectifier power supply. Output impedance: 3 ohms. Separate volume controls for each channel. Size: 6½x4½x4". Less tubes. Imported. Wt., 3lbs. Net 6.95
99 R 01547
36 R 90021M Kit of 4 tubes. Shpg. wt., 12 oz. Net 5.24


4-SPEED PHONO MOTOR

Quiet dependable AC operation assured by shock-mounted friction drive motor. Speed change control through idler driving rim of 8" turntable having retractable 45 RPM center adapter. Requires 2½" below base plate. Shpg. wt., 2¼ lbs. Net 5.95
24 R 27029 Motor and turntable
24 R 35014 Mounting boards. Wt., 2 lb. Net 1.50



STEREO/MONAURAL PICKUP

2¹⁹



High output crystal turnover cartridge for either stereo or monaural operation. Synthetic sapphire needles (1 mil and 3 mil) for LP and standard 78 RPM use. Replacement for most manual players. Mounts in ¾" dia. circular hole. Imported. Net 2.19
99 R 10241 Shpg. wt., 5 oz. Net 2.19
Synthetic Sapphire LP replacement needle. Net .99
99 R 10274 Shpg. wt., 2 oz. Net .99
Synthetic Sapphire STD replacement needle. Net .99
99 R 10282 Shpg. wt., 2 oz. Net .99

AUTOMATIC HI-FI SHUTOFF

5²⁵



Shuts off Hi-Fi equipment at the end of the last record. A 3-position switch allows the use of this one unit for all record changers, domestic and imported. This switch also permits manual operation if the automatic shut-off feature is not desired. Housed in a rugged drawn-steel case with mounting ears, amplifier outlet, and 6 ft. AC cord. Size: 2½x4¾x1½". Shpg. wt., 10 oz. Net 5.25
24 R 28019

RADIO BROADCASTER/PHONO OSCILLATOR


5²⁹



Have fun making announcements and broadcasting music through your own radio—with this broadcaster. Simply connect high impedance microphone or phono pickup to broadcaster and tune in broadcaster on radio. No wiring between the broadcaster and radio set. Pretuned to 1600 on radio dial but easily retuned. With 12BE6 and 35W4 tubes, phono jack, 2 feet of antenna, schematic and line cord. Completely wired. Chassis size: 4x2". For 110-125V AC-DC operation. Imported. Net 5.29
99 R 01778 Shpg. wt., 1¼ lbs. Net 5.29

LAFAYETTE Replacement Styli

MADE FOR LAFAYETTE BY THE FOREMOST AMERICAN MANUFACTURERS



KEY TO POINT CODES

The symbols in the column headed "PT SIZE" are explained in the table below.

LP = Monaural 1 MIL DIAMOND MICROGROOVE FOR 33 $\frac{1}{3}$ AND 45 RPM

COMB = MONAURAL DUAL 1 MIL DIAMOND AND 3 MIL SYNTHETIC SAPPHIRE

S = STEREO .7 MIL DIAMOND

SST = STEREO .7 MIL DIAMOND AND 3 MIL SYNTHETIC SAPPHIRE

SLP = STEREO .7 MIL DIAMOND AND 1 MIL SYNTHETIC SAPPHIRE

ANY STYLI ON THIS PAGE

279

EXCEPT THOSE NOTED



LAFAYETTE DIAMOND STYLI ARE MADE FROM WHOLE DIAMONDS, PRECISION GROUND AND POLISHED. SAPPHIRE STYLI ARE FINEST SYNTHETIC.

HOW TO ORDER

Identify your needle by cartridge number and illustration on this and the facing page. Order by the appropriate stock number. Shpg. wt., 3 oz.

Stock No.	Size Pt.	Fig.	Cartridge
-----------	----------	------	-----------

FOR ACOS CARTRIDGES

24 R 01602 SST 1 73-1

FOR ADMIRAL CARTRIDGES

24 R 01156 LP 2 409A11, B11, B12, A12

24 R 01180 Comb. 3 409B20

24 R 01206 LP 4 409A30

24 R 01529 S 5 409B33-1 (2-1)

24 R 01537 S 6 409C37-1

FOR ASTATIC CARTRIDGES

24 R 01206 LP 4 Q, 44, 46, 166T Series

24 R 01214 LP 7 AC, 40, 1, 2, 166T

24 R 01222 LP 8 40B, 410L

24 R 01248 Comb. 9 GCD, 409, SST, SST1, SSTM

24 R 01297 LP 10 K Series, 64, 66, 68, 94

24 R 01644 SST 11 17, 17D

24 R 01792 LP 12 118, 120, 124, 310, 420 Series

24 R 01859 SST 13 133, 137, 233

24 R 02295 S 12 ST-100, 70, 74, 76, 78

24 R 02303 SST 14 153, 157, 461, 481

24 R 02311 SST 15 138, 140, 142, 146

24 R 02329 SST 16 167D, 169D, 181D

24 R 02766 S 17 346, 348

24 R 02774 SST 18 165, 353, 355

24 R 02931 SST 19 393

24 R 02945 SST 20 271, 273, 349, 351

24 R 04028 SST 81 215

24 R 04036 SST 81 207

24 R 04044 SST 81 233

24 R 04051 SST 82 201, 205, 209

24 R 04069 SST 82 213

FOR BSR CARTRIDGES

24 R 01586 S 12 TC8S, TC-8SH, TC8S

24 R 02386 SST 21 C-1

24 R 02758 Comb. 22 X1M, X1H, X1HE

FOR COLUMBIA CARTRIDGES

24 R 01560 S 23 SC1, 2, 7, 8

FOR ELAC-MIROTWIN CARTRIDGES

24 R 01701 SST 24 KST-104, PE-182

FOR ELECTRO-VOX CARTRIDGES

24 R 01529 S 5 21 and 26 Series

24 R 01867 SST 26 117, 131, 131D

24 R 01875 SST 27 132

24 R 01883 SST 28 141, 149

24 R 02337 SST 29 198, 199

24 R 02345 SST 30 194

24 R 02782 SST 31 500D, 500S

Stock No.	Size Pt.	Fig.	Cartridge
-----------	----------	------	-----------

24 R 02956 SST 32 5015

24 R 02964 SST 33 5050, 5051

24 R 03335 SST 80 5026

24 R 04077 S 83 5078

24 R 04085 SST 84 5082

24 R 04093 SST 84 5076

24 R 04101 SST 84 5026, 5080

24 R 04119 SST 84 5083, 5084

24 R 04127 SST 85 5093, 5094

FOR EUPHONICS CARTRIDGES

24 R 01851 S 34 E1-3

24 R 01719 S 35 U-1, 2-4-5

24 R 01784 SST 36 U-8

24 R 01891 SST 36 U-10, U-11

24 R 02352 SST 36 U-12, U-13

FOR GENERAL ELECTRIC CARTRIDGES

24 R 01347 LP 37 RPX040, 041, 042

24 R 01362 LP 38 RPX040A, 050A, 063A

24 R 01370 LP 39 VR11 Series, 46-050

24 R 01594 S 40 GC-7

24 R 01610 S 40 VR227

24 R 01776 SST 41 C100

24 R 02360 SST 41 C200, C100A

24 R 02378 SST 42 C500

24 R 01354 Comb. 43 RPJ-013, -A

24 R 01435 SST 42 C-650 (REV)

24 R 04143 S 86 C-660

FOR MAGNAVOX CARTRIDGES

24 R 01180 Comb. 3 560177, 88-1

24 R 01396 Comb. 44 560151, 58, 69, 70, 81

24 R 01461 Comb. 45 560161

24 R 01792 LP 12 560176, 80

24 R 01529 S 5 560233-4

24 R 01669 SST 46 560260-1

24 R 01875 SST 27 560305-1

24 R 02576 SST 47 560344-45

24 R 02774 SST 18 560355

24 R 02782 SST 31 560365

FOR MASTERCRAFT CARTRIDGES

24 R 02584 SST 48 RP100

FOR MOTOROLA CARTRIDGES

24 R 01529 S 6 59K643335

24 R 01537 S 5 59K64395

FOR PERPETUUM-EBNER CARTRIDGES

24 R 01420 Comb. 49 PE-8, PE-10

24 R 01537 S 6 PE90 (M, N)

24 R 02790 SST 51 PE-186

24 R 02808 SST 51 PE-188

FOR PHILCO CARTRIDGES

24 R 01404 Comb. 44 M20, 22, 25, 45-9612

Stock No.	Size Pt.	Fig.	Cartridge
-----------	----------	------	-----------

24 R 01529 S 5 35-2809, 24, 25

24 R 01537 S 6 35-2820, 26

24 R 01586 S 12 35-2827, 29

FOR PHILLIPS CARTRIDGES

24 R 01909 SST 52 AG3306, 3310

FOR RCA CARTRIDGES

24 R 01156 LP 2 55652, 76257

24 R 01214 LP 7 76257, 988370-2

24 R 01222 LP 8 74067

24 R 01248 Comb. 9 100329

24 R 01347 LP 37 74466

24 R 01461 Comb. 45 76748, 100653

24 R 01537 S 6 RM P200, T, T-1

24 R 01578 SST 53 106770, T, 106960A

24 R 01768 SST 54 110021

24 R 02394 SST 54 11348, 200-A2

24 R 02402 S 55 115059

24 R 02592 SST 56 RMP-204, 115276

24 R 02600 SST 57 117330

24 R 02816 S 58 116931

24 R 03277 S 59 126316

24 R 04150 SST 87 131779

24 R 04168 S 88 131788, 132034

FOR RONETTE CARTRIDGES

24 R 01537 S 6 8F40, 105, 106

24 R 01792 LP 12 T0284, 400; RA204

24 R 02469 LP 6 8F40, 105

DUAL DIAMOND STEREO STYLI

Styli listed below have 2 stereo points so that as one wears out you can use the other. Use to replace original stylus with one stereo and one 78 RPM point if you are no longer using 78 RPM records. Figures shown at top of two facing pages. (FIG. 11). Replaces Astatic N41SD stylus in 17D cartridge.

24 R 01800 Net 3.49

(FIG. 53). Replaces RCA styli 11020 and 110022 in cartridge series RPM, 106960-A, 108213A, 106770-A and 106771-A.

24 R 01818 Net 3.49

(FIG. 46). Replaces Sonotone styli N-8TAS SD, DD in cartridge 8T, 8TA.

24 R 01826 Net 3.49



(FIG. 64). Replaces Sonotone styli N-9TS, SD, DD in cartridge series 9T.

24 R 01834 Net 3.49

(FIG. 64). Replaces Sonotone styli N16TS, SD, DD in cartridge series 16T.

24 R 01842 Net 3.49

For Stereo And Monaural Cartridges



FOR KEY TO STYLUS POINT CODES AND HOW TO ORDER, SEE TOP OF PRECEDING PAGE

279

ANY STYLUS ON THIS PAGE EXCEPT THOSE NOTED

Stock No.	Pt. Size	Fig.	Cartridge
-----------	----------	------	-----------

FOR SHURE CARTRIDGES

24 R 01180	Comb.	3	PC2, 3, 4, 5; WC10
24 R 01156	LP	2	W21, -2; WC24, -5; P80

FOR SOMOTONE CARTRIDGES

24 R 01461	Comb.	45	2T, ST; 9980
24 R 01305	Comb.	51	3T
24 R 01545	SST	46	8T and 8TA
24 R 01552	SLP	46	8T and 8TA
24 R 01677	SST	62	9T
24 R 01685	SST	63	12THS
24 R 01727	SST	64	16T Series
24 R 01735	SST	64	18T Series
24 R 01743	SST	79	12THSR
24 R 02410	SST	65	21T, 22T, 23T, 24T
24 R 02428	SST	66	26T, 27T
24 R 02436	SST	66	25T, 28T
24 R 02824	SST	67	32T, 39T
24 R 03285	SST	68	51, 52, 54

FOR TELEFUNKEN CARTRIDGES

24 R 01487	Comb.	69	TTSA
24 R 01628	SST	70	T20-2
24 R 02618	SST	71	T-23

FOR TETRAD CARTRIDGES

24 R 02626	SST	72	11, 31
24 R 02634	SST	72	21, 41
24 R 02642	SST	72	32
24 R 02659	SST	72	13, 33
24 R 02667	SST	72	52, 62
24 R 02675	SST	72	42

RECORD STATIC AND DUST ELIMINATOR

Sprays a fine mist which keeps your record clear of surface noise created by static (common to all vinyl records) and clean of dust attracted by the static charge. Prevents groove and needle wear caused by static-dust and keeps records lustrous. Extends their life. Two applications a year are sufficient. Enough for hundreds of records. Shpg. wt., 10 oz.

24 R 70037 Net .99



RECORD CLEANER KIT

Deep clean your records the modern way. Specially prepared silicone anti-static record cleaning fluid protects your valuable records as it cleans. Just a few drops on new velvet applicator will give your records a professional cleaning job. Supplied with anti-static fluid, velvet applicator.

24 R 70045 Shpg. wt., 3 oz. Net. 1.19



Stock No.	Pt. Size	Fig.	Cartridge
-----------	----------	------	-----------

TETRAD (Cont.)

24 R 02832	S	72	10, 40, 60
24 R 02840	SST	72	23, 24
24 R 02972	SST	72	51, 61
24 R 02980	SST	72	53, 63
24 R 02998	SST	72	54, 64
24 R 03004	S	72	20, 40
24 R 03012	S	72	10, 30
24 R 03020	S	72	80
24 R 03038	SST	72	71, 91
24 R 03046	SST	72	73, 93
24 R 03053	SST	72	14, 34
24 R 03293	SST	72	24, 44
24 R 03301	SST	72	74, 94

FOR VARCO (VACO) CARTRIDGES

24 R 01016	LP	73	T-45, S-45
24 R 02543	SST	74	CN Series
24 R 02550	SST	75	TN Series
24 R 03202	SST	76	TN-4

FOR VM CARTRIDGES

24 R 01529	S	5	16707-A
24 R 01545	SST	46	16708-F


FOR WEBCOR CARTRIDGES

24 R 01529	S	5	21P573
24 R 01537	S	6	21P596, 21P598
24 R 01545	SST	46	21P700-1-2-3-4

FOR ZENITH CARTRIDGES

24 R 01537	S	6	142-99B
24 R 02857	SST	77	142-126.12 7, 12a, 13b
			137, 138
24 R 02865	SST	77	142-150, 151
24 R 03327	SST	78	142-167

SHURE STYLUS GAUGE



Mdel SFG-2 Stylus Force Gauge. The ideal way to have your tone arm set to exactly the correct tracking force. Detects both excessive or insufficient tracking forces. Accuracy to within 1/10 of a gram in the 1/2 to 1 1/2 gram primary operating range; extended range to 3 grams. Wt., 4 oz.

21 R 62584 Net 4.95



DELUXE CASE FOR 12" RECORDS

Handsome case holds 60-12" records without jackets, 36 with. Solid wood frame lock corner construction. Covered with Pyroloxin coated cloth, washable. Two tone. Sure-hold lock. 13 1/4 x 7 1/4 x 1 1/2". Shpg. wt. 4 3/4 lbs.


24 R 82016 Net 5.75

SYNTHETIC SAPPHIRE STYLUS FOR ASTATIC, PHILCO, MAGNAVOX AND RONETTE

(FIG. 12). For ASTATIC 310T, 310TB, 310TS, 310-2, 414-1, 420-TS, 422-TS, 424-TS; PHILCO 35-8014, 325-8021; MAGNAVOX 560176; RONETTE Series DT-60, RA-284, TO-284. 3 Mil for 78 RPM Records

24 R 01982 Net .99
2 Mil for 78 & Mono LP Net .99
24 R 01990 Net .99
24 R 02014 1 Mil for Mono LP Net .99

POPULAR REPLACEMENT DIAMOND STYLUS FOR SHURE AND EMPIRE CARTRIDGES



(FIG. A) .7 Mil Diamond Stylus For Shure M7D and M3D Stereo Cartridges.

24 R 01636 Net 7.50

(FIG. B) .7 Mil Diamond Stylus For Shure M44 Stereo Cartridge.

24 R 03061 Net 8.75


(FIG. C) .6 Mil Diamond Stylus For Empire 880P Stereo Cartridge.

24 R 03079 Net 7.95

(FIG. D) .7 Mil Diamond Stylus For Empire 888 Stereo Cartridge.

24 R 03087 Net 7.95

THE WATTS "DUST BUG"



Automatically removes dirt and dust on each playing. Light plastic arm mounted by suction cup. Can be permanently mounted by rubber cement. The bottle of antistatic cleaning fluid has a built-in wick for application to a brush and pad at the end of arm. Imported. Shpg. wt., 4 oz.

24 R 25015 Net 6.50


DISPENSER OF ACTIVATING FLUID. For Dust ported. Shpg. wt., 2 oz.

24 R 25049 Net 2.50

Replacement Push Pad and Nylon Brush. Shpg. wt., 2 oz.

24 R 25031 Net 3.00

RECORD DUST REMOVER



For a dust-free record collection. The "Preener" penetrates each groove, removing all dust and grit and deposits a non-toxic ionic compound. Leaves no trace of film or residue. Ideal for keeping new records new.

24 R 25056 Shpg. wt., 4 oz. Net 4.00

Prices and Specifications are Subject to Change Without Notice

ROBINS[®] PHONO AND RECORD ACCESSORIES



(A) PK-11 COMPLETE DELUXE RECORD CARE KIT. Record Sweep mounts to any phono deck by suction cup. Cleans and lubricates records as they play. Includes Anti-Static Cleaner and Lubricant, Stylus Pressure Gauge, Stylus Microscope, and "Rob-O-Stat" Record Care Kit consisting of a super-soft velvet and foam applicator mitt, 1½ oz. anti-static cleaner-lubricant, and poly-foam pad. Shpg. wt., 10 oz. Net 7.95
24 R 80648

(D) PX-8 ANTI-STATIC RECORD-KLEEN SPRAY. Silicon lubricant and cleaner prevents dust accumulation on records. Eliminates static pops and clicks to improve fidelity. 8 oz. 24 R 80689 Shpg. wt., 13 oz. Net 1.29

(E) PK-5M PROFESSIONAL PHONO STROBE AND LIGHT KIT. 4-speed metal strobe disk and neon lamp. Tests phono speed accuracy at 16 2/3, 33 1/3, 45, and 78 rpm. 110 V. 50-60 Hz. A.C. Instructions included. 24 R 80358 Shpg. wt., 5 oz. Net 2.45

(G) PB-3 ADJUSTABLE STYLUS BRUSH FOR ALL U.S. AND IMPORTED PHONOS. Spring secured flexible brush adjusts from 3/4" to 2 1/4" height. Removes blob accumulation on stylus when tone-arm is cycled. Self-stick base for easy mount to phono deck. 24 R 80549 Shpg. wt., 3 oz. Net .89

(B) PSG-3 STYLUS PRESSURE GAUGE. Accurately calibrated gauge and counter balancer, weight. Measures pressure to 1/2 gram. 24 R 80556 Shpg. wt., 4 oz. Net 1.09

(F) PCO-1 RECORD CUEING CONTROL. For manual turntables. Raise or lower tone-arm without touching it. Floats to desired track of record with pin-point accuracy. 24 R 80820 Shpg. wt., 8 oz. Net 7.69

(H) PB-9 DISC-WHISK RECORD CLEANER. Cleans and lubricates LP and 45 rpm records on both sides in one operation by rotating record. Deposits Anti-Static Silicon to improve fidelity. Record handling disc included. 24 R 80671 Shpg. wt., 4 oz. Net 1.35

(C) PM-1 STYLUS MICROSCOPE. Inspect stylus tip for signs of wear, chips, etc., to prevent record damage. Precision ground lenses, 50X magnification. Knurled focusing adjustment. Pocket clip. Slot at end of scope holds stylus. Size: 3 3/4 x 1 1/2". Imported. Shpg. wt., 3 oz. Net 2.10
24 R 80168

PB-2 COMBINATION TONE-ARM LIFT AND RECORD BRUSH. (Not illus.) Clips to tone-arm. Sweeps dust and particles from records. Convenient finger lift prevents record scratches. 24 R 80028 Shpg. wt., 2 oz. Net .69

PG-2D DISPOSABLE DISC-KLEEN CLOTHS. (Not illus.) Package of 18 Anti-Static, Silicone impregnated cloths. Cleans and lubricates records. 24 R 80812 Shpg. wt., 4 oz. Net 1.05

PC-2 TWO ANTI-STATIC RECORD CLEANING CLOTHS AND CLIP-ON RECORD BRUSH. Shpg. wt., 4 oz. 24 R 80440 (Not illus.) Net .81



(I) PNT-1 PHONO STYLUS TIMER. Records elapsed time phono is in operation. 400 hour calibrated gauge indicates stylus wear to prevent needless record damage. Also indicates time for cleaning and general maintenance of equipment. Has self-stick back to mount to phono deck. 24 R 80770. Wt. 7 oz. Imported. Net 5.49

(L) PB-10 PROFESSIONAL RECORD SWEEP. Sweeps dust and particles from delicate sound grooves of records. Deposits Anti-Static Silicone Cleaner and Lubricant. Improves sound fidelity. Mounts to phono by suction cup. Includes Cleaner and Lubricant. 24 R 80663 Shpg. wt., 5 oz. Net 3.29

(N) PS-3 AUTOMATIC SHUT-OFF FOR HI-FI/STEREO SYSTEMS. All solid-state circuitry for reliability. Let's you fall asleep to your favorite music without "equipment burn-up". Automatically shuts off hi-fi system after last record plays. Switch permits manual operation. Amplifier and phono plug into separate outlets of unit. For all U.S. and imports equipment. Rated at 3 amps, 350 watts. Durable metal housing. Can be mounted. Size: 6 1/2" x 2 1/2" x 1 3/4". With 6 ft. line cord. 110 V. 50-60 Hz A.C. 24 R 80721 Shpg. wt., 2 lbs. Net 7.49

MSW-125 "AUDIO-CLEAN" SWABBIES. Package of 125 soft cotton-tips wound on extra long applicators for safe cleaning and oiling of hard to reach parts of equipment. Shpg. wt., 4 oz. (Not illus.) Net .79
28 R 72117

(J) PJ-18 ROUND BOTTOM PLASTIC RECORD COVERS. Protects 12" records. Pkg. of 18. 24 R 80564 Shpg. wt., 5 oz. Net .81

PB-75 CLIP-ON RECORD BRUSH. (Not illus.) Clips to tone-arm. Sweeps dust from records. 24 R 80036 Shpg. wt., 2 oz. Net .49

(K) PSD-4 METAL 5" DIA. 4-SPEED STROBE DISC. Checks 16, 33 1/3, 45, and 78 rpm. 24 R 80424 Shpg. wt., 3 oz. Net 1.19

(M) PB-88 "CLEAN-SWEEP." Large soft hair brush cleans entire tracking surface of records up to 12". Self-stick base mount to any phono deck. Swings out of way when not in use. 24 R 80010 Shpg. wt., 6 oz. Net 4.99

PRA-50 RECORD SPIDERS. (Not illus.) 50 hi-impact plastic, reusable 45 rpm adapters. Easy insertion in records. Shpg. wt., 4 oz. 24 R 80465 Net .89



(O) PRS-12 POLY-LINED RECORD SLEEVES. Paper protective sleeves for 12" records. Has clear poly windows to show labels of records. Seals out dust and grime to preserve records. Pkg. of 12. Net 1.35
24 R 80366

(Q) PJ-25 ALBUM COVERS. 12 heavy weight plastic window clear covers with thumb notch for easy insertion and removal of record albums. 24 R 80705 Shpg. wt., 8 oz. Net 1.66

(R) PK-9 "TENDER LOVING CARE" RECORD KIT. Contains super-soft Velvet and Foam Applicator Mitt, 1 1/2 oz. bottle of Anti-Static Record Cleaner and Lubricant, Polyfoam Pad for cleaning the velvet side of the mitt, Adjustable Stylus Brush, and Combination Tone-Arm Lift and Record Brush. Stylus Brush mounts to phono deck by self-stick base. Adjusts from 3/4" to 2 1/4" height for use with all turntables. Removes dust blob accumulation from stylus when tone-arm is cycled. Tone Arm Lift and Record Brush clips to tone-arm. Provides convenient finger lift to prevent fumbling and scratching of records. Gently sweeps dust from delicate record grooves. Shpg. wt., 10 oz. 24 R 80853 Net 2.99

(P) PK-6 "ROB-O-STAT" RECORD CLEANING KIT. Super-soft foam applicator mitt. 1 1/2 oz. Anti-Static cleaner and lubricant, and poly-foam pad. Shpg. wt., 5 oz. Net 1.59

PL-2 ROUND TURNTABLE LEVEL. Assures accurate leveling of turntable for correct tracking. Minimizes stylus and record wear. Self-stick base for mount to phono. (Not illus.) Shpg. wt., 3 oz. Net 1.79
24 R 80184


TURNTABLE COVERS. (not illus.) Soft, heavy-gauge durable plastic covers. Fits most changers. Shpg. wt., 8 oz.

PG-4 TWO RECORD CLOTHS AND A 45 RPM SPINDLE ADAPTER. (Not illus.) Wt. 3 oz. 24 R 80523 Net .81

Stock No.	Mfr's No.	Size	Net
24 R 80275	PJ-1	13x13 1/2 x 8"	1.69
24 R 80838	PJ-3	22x16 1/2 x 8"	1.99
24 R 80846	PJ-5	17x15x18 3/4"	1.99

TX-56 NON-SLIP FOR PHONO DRIVES. Stops slippage of drive wheels, belts, etc. 2 oz. Not illus. Shpg. wt., 6 oz. Net .99
24 R 80804

Auto Antennas — Accessories — Vibrators



(1) CONTINENTAL SINGLE SIDE MOUNT
Continental single side mount. For trucks, Volkswagens and other foreign cars. Flexible adjustments with unique vertical locking. 3 section. Extends to 55" from 20". 32" lead cable.
11 R 88010 Shpg. wt., ¾ lb. Net 2.89

(2) "FLEX-O-MATIC" UNIVERSAL ANTENNA
Heavy-duty, bounce-back, spring mount. Fully adjustable—mounts anywhere. 3 sections. 63" extended, 28" collapsed. 48" lead.
11 R 74077 Shpg. wt., 9 oz. Net 3.49

(3) UNIVERSAL MOUNT AERIAL
Can be mounted anywhere on car. Adjusts to any angle, 3 section, measures 20" collapsed, extends to 59". Complete with 48" lead.
11 R 74119 Shpg. wt., 1 lb. Net 2.39

(4) DISAPPEARING ANTENNA
For concealed installation. Extends to 52" from 6½". Fully collapsible—only mounting protrudes. 54" lead.
11 R 74028 Shpg. wt., 1 lb. Net 3.49


(5) LO-BOY DISAPPEARING ANTENNA
For shallow installations, foreign and sports cars. Takes only 9½" below fender or deck. Extends to 25" collapses to 19½". 48" permanent lead. Shpg. wt., 1 lb.
11 R 74036 Net 2.29



REPLACEMENT AND EXTENSION LEADS

54" Universal replacement lead. Shpg. wt., 5 oz.
11 R 74085 Net 1.19
24" Universal extension lead,
11 R 74093 Net .89
36" Universal extension lead,
11 R 74101 Net 1.09

ADAPTERS/JACKS/PLUGS/CONNECTORS



(A) Adapter converts Motorola to Delco fitting
11 R 66016 Net .19
11 R 66024 (B) Motorola Jack Net .29
11 R 66032 (C) Motorola plug Net .19



UNIVERSAL 6 & 12 VOLT VIBRATORS

Direct replacements for most popularly-used types.

6-VOLT 4-PRONG


Replacement for MALLORY 294, 859, 901M, 160L, Radiart 5300, 5301 and many others.
32 R 56013 Shpg. wt., 4 oz. Net 2.55

12-VOLT 3-PRONG

Replacement for Buick, Olds, Pontiac and GM part no. 122-0155; Mallory G874, CD 6330, Delco 8550; and Vokar 3129.
32 R 56021 Shpg. wt., 4 oz. Net 2.95

12-VOLT 4-PRONG

Replacement for Mallory G859, Motorola 45B22000, Philco and Mepar 83-0025-1, ATR 1840, Vokar 4124; and most later 12-volt car-radio vibrators.
32 R 56039 Shpg. wt., 4 oz. Net 2.95



(6) DISAPPEARING KEY-TENNA
Slides completely into mounting base. Locks with key rendering the antenna theft proof. 16½" below fender, ext. 43". With 48" leads; 2 keys. Shpg. wt., 1 lb.
11 R 74044 Net 2.90

(7) DISAPPEARING FM-KEY-TENNA
3-section disappearing safety-lok antenna. Extends to 31" for top FM performance. Complete with 48" leads; 2 keys. Shpg. wt., 1 lb.
11 R 74127 Net 3.39

(8) SPRING BACK REPLACEMENT STAFF
One piece, stainless steel, spring mounted replacement staff. 27½" long overall. Mounts over stub of old antenna. Fits all cars. Simple set screw installation. Shpg. wt., 9 oz.
11 R 74069 Net 1.19


(9) REPLACEMENT ANTENNA STAFF
3 section 57" replacement staff. Telescoping staff replaces antenna lost through accident or vandalism. Mounts on stub of broken antenna. Simple lock on mount. Shpg. wt., 9 oz.
11 R 74051 Net 1.59

(10) TOP MOUNT FOR VOLKSWAGEN CARS
For 1967 Models and Up. Three section top-mount antenna extends to 38" collapses to 15". Fits the pre-punched hole which Volkswagen has incorporated into its cars. Chrome plated. Complete with 42" cable. Shpg. wt., 1 lb.
11 R 74135 Net 2.99

DYNAMIC AUTO TENNA BOOSTER

- For New Transistor Auto Radios
- Increases Radio Range and Reception
- Electronically Equivalent to 110-ft. Antenna

Increase the signal strength and range of your auto radio with the new Dynamic Auto Antenna Booster. Brings in distant and weak stations... stops station-fade. Installs easily in 4 simple steps. Fits all except 4 sect. Antennas. Shpg. wt., 1/2 lb.
11 R 89026 Net 2.89



NOISE SUPPRESSOR KITS

279


For all 6 and 8-cylinder cars suppresses wide band pulse noise created by the distributor, spark plugs and generator "hash". Includes spark plug suppressors, generator and light or ammeter by-pass capacitors. Complete with easy installation instructions. Shpg. wt., 6 oz.
11 R 71057 for 6-cylinder cars Net 2.79
11 R 71065 for 8-cylinder cars Net 3.19



CAR STEREO NOISE ELIMINATOR

Effectively kills the interference of noise caused by ignition system or alternator in some cars. Consists of choke and capacitor and instruction for hook up. Shpg. wt., 6 oz.
11 R 60506 Net 1.74

INSIDE WINDOW AUTO ANTENNA



- For AM-FM Reception
- Eliminates Theft-Breakage

295

Now you can have the latest type of AM/FM auto window antenna similar to Detroit's 1971 models. The antenna fits all cars, and can be installed in minutes. The antenna wire is laminated between 2 plies of crystal clear self-adhering tape. Complete with easy to follow instructions, and a fender replacement cap to cover the hole of your old antenna mount to preserve your car's appearance. Shpg. wt., 6 oz.
11 R 65562 Net 2.95

POWER HOUSE AUTO ANTENNA

- Built-in Booster 450

New! 3-section universal mount (for all cars) auto antenna designed to increase the range and signal strength of your auto radio. Built-in booster coil lets you tune twice as many stations. TWICE AS STRONG! Stainless steel mount withstands severe shock, eliminates constant replacement of broken antenna staffs. Swivel base permits mounting at any surface angle. Comes with 48" lead cable. Wt., 1 lb.
11 R 71073 Net 4.50



"TENNAMATIC" ELECTRIC AUTO ANTENNA

- Electrically Raises and Lowers Automatically
- Eliminates Vandalism

As Low As 1995

Operate the antenna at the flip of a switch. Designed to fit most 12 volt cars. Max. extends to 35" and retracts to 1¼". Antenna cable is copper shielded. External parts are plated with chrome. Positive 15 lbs. thrust insures "free action" even in sub zero temperatures. Complete with cable, clips, brackets, switch and plate, screws, wiring harness and instructions. Shpg. wt., 6¾ lbs. REAR MOUNT: 18 feet of antenna lead and 20 feet electric harness.
11 R 71024 Net 21.95

FRONT MOUNT ANTENNA 54" of antenna lead and 72" electric harness.
11 R 71016 Net 19.95



Quality Solid-State Radios For The Car

DELUXE SOLID STATE FM STEREOPHONIC CAR RADIO



The Ultimate in FM Car Radio Entertainment

69⁹⁵

Less Speakers

- For 12 Volt Negative Ground Systems

Enjoy rich, vibrant FM stereophonic programming in your car with this magnificent performing FM stereo radio. Simple to install under the dash with adjustable brackets—only 2 screws are required to mount the radio. Features powerful Hi-Fi audio circuit for true stereo sound reproduction on both channels. Stereo Indicator Lamp illuminates when station is receiving stereophonic sound. Dual channel tone and volume controls. Balance control permits adjustment of

channel separation for perfect sound balance. Illuminated slide rule dial. Specifications: 23 Transistors, 11 Diodes, Output 7 watts per channel. Sensitivity: 5 μ v. For 12V negative ground systems. Size: 9"W x 1 1/2"H x 6 1/4"D. Shpg. wt., 4 lbs. Imported.
17 R 74561 No Money Down* Net 69.95
Set of 2 rear deck 3" x 5" speaker systems, imported. Wt., 3 lbs. 99 R 62994 Net 8.95

SOLID-STATE PUSHBUTTON AM/FM CAR RADIO



- Includes Free Antenna
- Large 5 x 7" External Speaker
- For 12 Volt Neg./Positive Ground System

54⁹⁵

All solid state circuitry. 11 transistors, 8 diodes, 2 thermistors. Push-pull Hi-Fi output. AFC for FM drift free performance. High sensitivity for long distance reception on both AM and FM. Four i.f. stages on F.M. for maximum noise limiting. Large 5 x 7" external speaker. Radio mounts neatly under dash. Overall size: 6 1/2"W x 2 3/8"H x 6 3/8"D. Imported. Shpg. wt., 7 lbs.
17 R 74124 No Money Down* Net 54.95

NEW! UNIVERSAL AM/FM/FM STEREO PUSHBUTTON CAR RADIO



- 3 IC's and 2 FET's
- 8 Tuned FM Circuits
- 6-Watt Output Per Channel

99⁹⁵

Less Speakers

Powerful Solid-State AM/FM/FM Stereo Radio features: integrated circuitry, 3 I.C.'s coupling 30 silicon transistors, 2 "Field-Effect" transistors, and 18 diodes to produce more than 6-watts per channel of stable, drift-free output. 5 tuned AM circuits, 8 tuned FM circuits, automatic frequency control, AFC On-Off switch, Stereo-Mono switch, Stereo indicator light. Reversible inset panel resulting in 3-way die-cast face plate. Flexible antenna lead connector. 12 volt negative or positive ground operation. Size: 6 1/2" wide, 6 1/8" deep, 2" high. Shpg. wt., 8 lbs. Imported.
17 R 80055W No Money Down* Net 99.95
Set of 2 Rear Deck 3" x 5" Speaker Systems. Imported. Net 6.95
99 R 62994 Shpg. wt., 3 lbs. Net 6.95

MANUAL AM CAR RADIO



- Built-in Speaker
- Removable Face Plate
- Tone Control Switch
- For 12 Volt Negative Ground Systems

19⁹⁵

Universal Solid State AM radio that is easy to install under the dash. Offers fine sound reproduction. Features built-in speaker and tone control slide switch, 7 transistors, 2 diodes, RF stage, AVC, Removable face plate. For 12 volt negative ground system. Size: 2 1/4" x 4 1/2" x 6 1/2". Imported. Shpg. wt., 2 3/4 lbs.
17 R 74256 Net 19.95

DELUXE PUSHBUTTON AM CAR RADIO




- 6 Watt Push/Pull Output
- Large 5" by 7" External Speaker
- For 12 Volt Neg./Pos. Ground Systems

32⁹⁵

Attractively styled under-dash solid state AM push-button car radio with reversible face plate—black on one side, walnut on the other. 6-watt push-pull output with AGC. External 5 x 7" speaker. Size: 6 1/4" x 4 3/4" x 2"H. Shpg. wt., 5 lbs. Imported.
17 R 80048 No Money Down* Net 32.95

RANGER SOLID-STATE FM CAR RADIO CONVERTER



- Converts Your Existing 12 Volt Negative Ground AM Radio to the FM Band

39⁹⁵

Complete auto radio entertainment at a minimum cost. All solid state circuit (6 transistors, 8 diodes) gives instant operation. Built-in AFC permits drift-free reception of distant FM stations. AM/FM switch allows instant selection of AM or FM stations. Simplified installation. Sensitivity: 4 μ v. Size: 1 7/8" x 4 x 9". Imported. Shpg. wt., 3 1/4 lbs.
17 R 74207 No Money Down* Net 39.95

Custom Deluxe Solid-State Radios For Volkswagen Cars

PUSHBUTTON AM CAR RADIO



34⁹⁵

- For All Standard Models from 1958-1971
- Will also custom fit "Super Beetle"
- Complete with 5" Diameter External Speaker and All Mounting Hardware

Just a snap to install. All transistor circuitry provides 3-watts of audio power. AVC provides constant, even comfort-level listening. Continuously variable tone control. Five quick-set pushbuttons. Seven tuned circuits including RF stage, give maximum sensitivity. For 6/12 volts D.C., negative ground. Imported. Shpg. wt., 6 lbs.

17 R 26447 No Money Down* Net 34.95
Manual solid-state AM car radio for 1958-71 Volkswagen Cars. Same as above but manual tuning. Shpg. wt., 5 lbs.
17 R 74264 Net 27.95

DELUXE PUSHBUTTON FM-AM CAR RADIO



69⁹⁵

- For 1967 Thru 1971 1300 Series Models
- Will Also Custom Fit Super Beetle
- 6-Inch External Speaker
- 11-Transistors, 2-Diodes
- Snap-in Front Mount for Easy Installation

Deluxe solid-state custom AM-FM radio for all standard Volkswagen 1967-1971 models. Will also custom fit the new Super Beetle. All solid-state circuitry. 11-transistors, 2-diodes. AFC on FM for drift-free performance. Push-pull output. High sensitivity for long distance reception on both AM & FM. 4-IF stages on FM. Continuous variable tone control. Snap-in front mount. Large 6" external speaker. Imported. Shpg. wt., 6 lbs.

17 R 74405 For 1967-1971 Volkswagens Net 69.95

Custom Deluxe Solid-State Radios For Toyota Cars

PUSHBUTTON AM RADIO FOR TOYOTA CORONA AND COROLLA



34⁹⁵

- With External 5x7" Speaker
- Push-Pull Output With AGC

No Money Down* Fits All Cars From 1967 Thru 1971 Models

Fine performing custom radio. All silicon solid-state circuitry. External 5x7" speaker for fine sound reproduction. Tone Control. Push-pull output with AGC. For 12-volt negative ground systems. Shpg. wt., 5 lbs. Imported.

17 R 80030 Net 34.95

Pushbutton AM Radio for Toyota Mark II

Same specs and features as above but specifically designed for custom installation in Toyota Corona Mark II cars. (1967 thru 1971). Shpg. wt., 5 lbs. Imported.

17 R 80014 Net 34.95

PUSHBUTTON AM/FM RADIO FOR TOYOTA CORONA AND COROLLA



69⁹⁵

- With External 5x7" Speaker
- AFC For Drift Free FM Performance
- Fits All Cars From 1967 To 1971

No Money Down*

All silicon solid state circuitry with 8-watt output. Features: built-in AFC to prevent drift on FM and AGC. Colored dial lights for AM and FM. External 5x7" speaker. For 12 volt negative ground systems. Imported. Shpg. wt., 6 lbs.

17 R 80006 Net 69.95

Pushbutton AM/FM Radio for Toyota Mark II

Same specs and features as above, but specifically designed for custom installation in Toyota Corona Mark II cars (1967 thru 1971). Imported. Shpg. wt., 6 lbs.

17 R 80022 Net 69.95

NEW TENNA "Mini" IC Solid-State Car Radios

FM Stereo Car Radio

79⁹⁵

less speakers



FM STEREO CAR RADIO

Enjoy FM stereo broadcasts in your car. Features FM stereo Indicator Light, balance slide control, tone control, mono/stereo switch, and powerful solid state IC circuitry—4 IC's, 5 transistors, and 8 diodes. Peak Audio Power 4-watts per channel. Measures only 2 3/8" H x 4 1/8" W x 6 5/8" D. With mounting bracket and hardware. Less speakers. Imported. Shpg. wt., 2 1/2 lbs.
17 R 74652 No Money Down* Net 79.95



AM Car Radio

29⁹⁵

less speaker

Easily Mounts Under the Any Car Dash of Any Car

AM CAR RADIO

Measures on 1 1/2" x 4 1/8" x 5 3/4"—high styled chrome and black finish. For 12 volt negative ground systems. Powerful Solid State integrated circuitry. Power output: 3 watts music power at 8-ohms. 5 Transistors, 1 IC. Less speaker. With mounting bracket and hardware. Imported.

17 R 74660 Shpg. wt., 1/2 lb. Net 29.95

See Page 263 for Lafayette's Complete listing of Car Speakers

Car Reverb Units and FM Converters

LAFAYETTE SOLID-STATE CAR REVERBERATION AMPLIFIER



Only
9⁹⁵

Including
Mounting Bracket
Less Speakers

Recreates Concert Hall Listening In Your Car

- Can Be Used With Any 12-Volt Negative Ground Car Radio—AM or FM

NOW—listen to the most dramatic sound of music you have ever heard in a car with the Lafayette solid state Automobile Reverberation amplifier. When used with your present 12-volt negative ground AM or FM car radio, the Lafayette Reverb amplifier creates a second set of reflected sound waves reproduced through a rear seat speaker (not included). These reflected sound waves provide this exciting new dimension in sound reproduction. Features a push/pull Fader/Balance control. Balances regular car radio speaker and reverb speaker. Also controls amount of reverberation—from 0 to maximum. Separate isolation transformer for ultimate matching conditions. For underdash mounting. Dim.: 7½" Dx 3½" W x 1¼" H. Includes mounting bracket. Imported. Shpg. wt., 2¼ lbs.

99 R 85193 Net 9.95

See Page 263 For Rear Seat Speakers

DELUXE SOLID-STATE CAR REVERBERATION SOUND SYSTEM



19⁹⁵

Complete with 6x9" speaker
and chrome grill.

- Tuneable . . . Electronic Tuning Control. "Custom Fits" the Sound to your Car, to your Ear
- For 12 Volt Negative Ground AM and FM Auto Radios—Convenient Under Dash Mounting

Deluxe solid state tuneable reverberation unit converts your present car radio into a magnificent sound system offering concert hall realism. Beautifully styled to enhance the decor of your car. Consists of the tuneable amplifier control unit which easily mounts under the dash panel of your car by means of adjustable brackets. 6 x 9" dynamic speaker and chrome grill for rear seat mounting, and all connecting cables. Includes simple instructions for connecting the reverb unit to your regular car radio system and for separate rear seat speaker. "REVERBERATION," tones are created thru the rear speaker thus providing a truly 3 dimensional sound system in your car. Simplified controls permit balance of sound between front and rear seat speaker. Verb-A-Tone control adjusts the amount of reverberation to your taste. Specifications for 12 volt negative ground cars, peak audio output—4 watts, 2 transistors. Size: 1⅞" x 4" x 9" Shpg. wt., 4¼ lbs.

17 R 01093

Net 19.95

HITACHI KMT-880 SOLID-STATE FM CONVERTER FOR AM CAR RADIOS

NEW



24⁹⁵

Complete with all
mounting hardware.

Convert your present AM Car Radio to an AM/FM radio. Operates on 12 volt negative ground systems. Advanced solid-state circuitry consists of 7 transistors, 1 varistor, and 1 Zener Diode. Tuning Range: 88-108 MHz. Features: AFC for drift free FM reception, dial light and adjustable brackets for easy installation under the dash. Precision slide rule tuning dial with logging scale. With all mounting hardware. Size: 4¾" x 1¾" x 4¾". Imported. Shpg. wt., 3 lbs.

17 R 24269

Net 24.95

See Page 263 for Big
Selection of Car Speakers

SOLID-STATE FM STEREO CONVERTER FOR AM CAR RADIOS

NEW



49⁹⁵

No Money
Down*

Includes: Mounting Bracket for Under Dash Installation, Fastener for Top of Dash or Console Installation, Antenna and Patch Cord.

Converts your AM Car Radio to an AM/FM Stereo Radio. Automatic stereo switching for the utmost in enjoyment. FM stereo light illuminates when stereo broadcast is being received. Tone and Volume Control to blend stereo broadcasting to perfection. Underdash mounting. Tuning Range 88-108 MHz. Local/distance switch for optimum reception. All solid-state circuitry includes 12 transistors and 15 diodes. Speaker Impedance—4 or 8 ohms. Stereo separation 3 db. For 12-volt negative ground systems. (does not include speakers). Size: 2¼Hx4½Dx5¼W. Imported. Shpg. wt., 3 lbs.

17 R 41016

Net 49.95

FM Converter For AM Car Radios—Similar to above, but only converts your AM car radio to tune standard FM Broadcasts. For 12 volt neg. ground systems. Size: 1¾Hx4½Dx5¼W. Imported.

17 R 41008

Net 29.95

Solid-State Car/Portable Radios

New Sharp FX200A FM-AM Car/Portable Radio



Complete with Car Bracket, Lock and Key, Batteries, AC Line Cord, Earphone

39⁹⁵

- Install In Any 6 or 12 Volt Car or Boat System
- Use As A Portable, or On 117VAC 60 Hz. With Built-in AC Line Cord

Multi-purpose AM/FM solid-state radio designed to provide outstanding reception anywhere. Used as an AM/FM car radio, it locks into its specially designed under-the-dash bracket and operates thru the car's electrical system (6 or 12 volts pos./neg. ground). Slips easily out of bracket for use outdoors—and plays on 4 "C" Batteries (included). For indoor use, it operates on regular 117VAC household current with the AC line cord provided. Illuminated slide rule tuning, variable tone control, earphone/external speaker jack, AFC for drift free FM reception. Ferrite bar AM antenna, telescoping FM antenna. Wide range 4x2 3/4" oval speaker. Imported. U.L. listed. Dimensions: 9 1/2" W x 5 7/8" H x 2 3/4" D. Shpg. wt., 5 lbs.
 17 R 53185 No Money Down* Net 39.95
 99 R 62572 Extra "C" cells (4 required) Net ea. 16

New Sharp FY300PA 3-Band AM/FM/FM VHF Car/Portable Police Radio



Complete with Car Bracket, Lock and Key, Batteries, AC Line Cord, Earphone

49⁹⁵

TUNES:
 FM-VHF 148-176 MHz, High Band Police and 162.55 MHz, U.S. Weather Bureau Forecasts
 AM 550-1600 kHz
 FM 88-108 MHz

Deluxe, multi-purpose 3-way solid state radio specially designed for use in car, as a portable, or in the home. Features dramatic FM-VHF High Band (148-176 MHz) reception of police, fire, civil defense, and U.S. Weather Bureau forecasts. Also tunes the standard AM and FM broadcast bands. As a car radio, it locks into its specially designed, under-the-dash bracket (supplied) and operates thru the car's 6 or 12-volt electrical system. Outdoors it plays on 4 "C" size flashlight cells. Indoors it plays on 117 VAC with an AC line cord (supplied). Features: dynamic oval speaker and 1-watt output for excellent sound quality; precision vernier slide-rule illuminated tuning dial; variable tone control; earphone jack an earphone for personal listening; telescoping FM and FM-VHF antenna; ferrite core AM antenna. Dimensions: 9 1/2" W x 5 7/8" H x 2 3/4" D. U.L. listed. Imported. Shpg. wt., 5 lbs.
 17 R 53193 No Money Down* Net 49.95
 99 R 62572 Extra "C" cells, 4 Required Net ea. 16

Deluxe Nordmende 15-Band Globetraveler III AM/FM/SW Radio

Only
 169⁹⁵



For Use As A Portable,
 Home Radio, Auto Radio, Boat Radio

The entire world of radio listening pleasure and excitement is at your finger tips. Includes standard AM broadcast band, FM, Marine Band, LW Weather-Navigation Band and 11 shortwave bands. Outstanding features: Built in AC with compartment for AC cord, Drum dial for all 11 spread shortwave bands, and I.F. Bandwidth switch. 2-Speakers: 5x7" woofer, 2 1/2" tweeter. Separate jacks for earphone, external speaker, phonograph, tape recorder, and separate amplifier. A built-in ferrite antenna for AM, a telescopic antenna for FM, and an additional telescopic antenna for SW increases its sensitivity and selectivity. Also includes tuning meter and battery tester, AFC on FM, noise filter on AM and SW. Separate bass and treble control. 15 transistors and 12 diodes. Wood cabinet covered with scuff-proof black vinyl. 12 1/2" W x 8 1/2" H x 4" D. Imported. Shpg. wt., 11 lbs.

17 R 72177W No Money Down* Net 169.95
 Globetraveler IV 16 Band AM/FM/SW/FM-VHF Police Radio. Same features and specifications as Globetraveler III, except cannot be used as a car or boat radio. Operates only on 5 "D" batteries, or 117VAC with built-in AC line cord. Includes 147-174 MHz FM-VHF band enabling you to listen to police and fire calls.
 17 R 72185W No Money Down* Shpg. wt., 11 lbs. Net 189.95


15 Exciting Bands:

AM Broadcast	540—1600 kHz
FM Band	88—108 MHz
MB Marine	1.5—3.5 MHz
LW Weather	145—420 kHz
80 meter band	3.61 to 3.84 MHz
61 meter band	4.60 to 4.89 MHz
59 meter band	4.84 to 5.13 MHz
49 meter band	5.90 to 6.26 MHz
41 meter band	6.96 to 7.40 MHz
31 meter band	9.35 to 9.90 MHz
25 meter band	11.50 to 12.16 MHz
20 meter band	13.80 to 14.50 MHz
19 meter band	14.85 to 15.70 MHz
16 meter band	17.38 to 18.35 MHz
13 meter band	20.95 to 22.10 MHz

Accessories for Globetraveler Radios
 Universal 6 or 12 volt car boat mounting Bracket with lock, 4 lbs.
 17 R 72094W Net 22.95
 99 R 62564 "D" type Flashlight Batteries, 5 required Net 18

Panasonic, Sony, and Sharp Solid-State Portable Radios

Panasonic RF-561 FM/AM Battery/AC Portable Radio



NEW 29.95

With Batteries, AC Power Cord, and Earphones

FM/AM personal portable radio with 117 VAC or battery operation. Features solid-state Integrated Circuitry for high reliability. Built-in FM whip and AM ferrite core antennas, 3" dynamic speaker. Vertical slide-rule tuning dial, and AFC on FM. Continuous tone control. Band selector. Slide down metal handle. Earphone/external speaker jack. In black cabinet with chrome trim. Complete with "AA" batteries, AC power cord, earphone, and gift box. Size: 6 $\frac{1}{2}$ "x5 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "D. Imported. Shpg. wt., 3 $\frac{1}{2}$ lbs.

17 R 31124L Net 29.95
Extra "AA" battery (4 req.)
99 R 62580 Net ea. .10

Panasonic RF511 FM/AM Pocket Portable



NEW 17.88

With Batteries, carrying strap, and earphone

Pocket-Size FM/AM Portable Radio operates on inexpensive 9V battery. Built-in FM whip and AM ferrite core antennas. 2 $\frac{1}{2}$ " dynamic speaker. Easy-see vernier tuning. Band selector switch. Earphone/external speaker jack. Solid-state circuitry. Complete with 9V battery, earphone, carrying strap and gift box. Size: 4 $\frac{1}{4}$ "x3-5/36x1 $\frac{1}{4}$ "D. Shpg. wt., 1 lb. Imported.

17 R 31132L Net 17.88
Extra 9v. battery
99 R 60212 Net ea. .29

Deluxe Panasonic RF-930 Battery/Electric AM/FM Portable

39⁹⁵

Gift-boxed
With Earphone
and Batteries
No Money Down*



Handsome midnight black padded leatherette cabinet. Operates on 4 "AA" batteries or regular house current. The sensitive FM and AM antennas assure excellent reception from stations far and near. Sliderule tuning. AFC on FM locks in signal for crystal clear, drift-free reception. The 4" PM dynamic speaker reproduces brilliant sound. The earphone jack lets you enjoy your own private listening. Size: 8 $\frac{3}{4}$ " x 5 $\frac{1}{2}$ "x3". Shpg. wt., 4 $\frac{1}{4}$ lbs. Imported.

17 R 31967L Net 39.95
Extra "AA" batteries, 4 req.
99 R 62580 Shpg. wt., 4 oz. Net ea. 10

- Calibrated Slide controls for bass and treble
- Large 4" Speaker

NEW

Sharp FY302W FM/AM Portable Radio with Pushbutton Weather Band

34⁹⁵

with earphone and battery



Compact, lightweight FM/AM Portable with Solid-State integrated circuitry. Pushbutton Weather Band on 162.55 MHz. Features: Precision slide-rule tuning, rotary handle for carrying case, instant band selection with FM/AM push-button. Automatic Gain Control and Automatic Frequency Control assure stable and reliable drift-free performance. Operates on 4 "AA" batteries or AC. Size: 8 $\frac{3}{4}$ "x5 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "D. Imported. Shpg. wt., 4 lbs.

17 R 53201L No Money Down* Net 34.95
Extra "AA" batteries, 4 req.
99 R 62580 Net ea. .10

- Battery or AC Operation
- Pushbutton Weather Band Set on 162.55 MHz
- AFC on FM Produces Sensitive and Drift-Free Performance.

Deluxe Sony TFM-1600W 7 Band AM/FM/SW Portable Radio

99⁹⁵

With Earphone
and Batteries
No Money Down*



Deluxe 6-band portable radio pulls in world-wide programs on 4 Short Wave Bands. Also receives standard FM and AM broadcasts with sharp, velvety sound. Impressive 1.7W power output through a big 4 x 6" oval speaker. Tuned RF amplification for FM and AM increases selectivity and sensitivity. Flywheel tuning for smooth and accurate station selection. Features: AFC switch, Local/Distant switch, continuous tone control and tuning meter, high power antenna system and dial light. Operates on 4 "D" batteries (Included) or AC house current (AC cord built-in). Antenna system, FM/SW telescope antenna, AM built-in ferrite bar antenna, external antenna terminal. Dark grey and chrome cabinet. Size: 11 $\frac{1}{2}$ "x8 $\frac{3}{4}$ "x3 $\frac{1}{4}$ "D. Shpg. wt., 8 lbs. Imported.

17 R 32924L Net 99.95
Extra "D" batteries. Shpg. wt., 5 oz.
99 R 62564 Net .18

FREQUENCY RANGE:

FM 87.5-108 MHz SW2 3.5-7 MHz
AM 530-1,605 kHz SW3 7-14 MHz
SW1 1.6-3.5 MHz SW4 14-26.1 MHz

Portable Black and White VHF-UHF Solid-State TV Sets

Sharp TM-85P AC-Operated

Hitachi TWU-68 AC-Operated

Sony TV-740 Battery/AC



69⁹⁵
With Earphone
UL Listed



79⁹⁵



109⁹⁵

- 9" Picture Measured Diagonally
- 82 Channel UHF/VHF Reception

Styled in a modern mood, off-white and ebony with accents of silver, transistorized circuitry, 44 square inch, 90° deflection aluminumized picture tube. Front-mounted 3" speaker for fine sound. Front-mounted controls for greater convenience. Separate UHF and VHF tuning knobs. With "Split-Second-Start" for instant picture... Instant sound. Telescopic VHF and loop UHF antennas. Earphone and jack for personal listening. Size: 9 3/4" x 13 3/4" x 9 3/4" D. For 117 VAC, 60 Hz. Imported. Shpg. wt., 16 1/2 lbs. **17 R 53169WX No Money Down* Net 69.95**

- 12" Picture Measured Diagonally
- 82 Channel UHF/VHF Reception

Outstanding performance from this handsome solid-state portable TV, 75 sq. in. picture (12 inches measured diagonally), 100% transistorized. Instant picture and sound. Extremely stable image obtainable every time due to Set-and-Forget memory fine-tuning, Automatic Gain Control and noise diminator circuits. With VHF monopole and UHF loop antennas. Operates on 117 VAC, 60 Hz. Size: 16 1/4" x 11 1/4" x 11 1/4" D. Imported. Shpg. wt., 16 lbs. **17 R 24277WX No Money Down* Net 79.95**

- 7" Picture Measured Diagonally
- 82 Channel UHF/VHF Reception

Streamlined styling with chrome accents. Operates on 117V., 60 Hz AC; optional rechargeable 12-volt battery, or, 12VDC car/boat battery. Keyed AGC system for sensitive reception. Black screen for better picture both indoors and outdoors. Built-in VHF telescoping antenna and front mounted 3 3/4" speaker. With earphone, UHF loop antenna. Size: 9 3/4" x 8 1/4" x 10 3/4". For 117 VAC, 60 Hz. Imported. Shpg. wt., 9 lbs. **17 R 33005WX No Money Down* Net 109.95**

Sony TV-940 Battery/AC

Sony TV-112 Battery/AC

Panasonic TR-425 Battery/AC



119⁹⁵



129⁹⁵



159⁹⁵

- 8" Picture Measured Diagonally
- Channel Coverage VHF 2-13, UHF 14-83

Features 8" non-glare picture tube measured diagonally, 25-transistors plus 15 diodes and 1 rectifier assures sensitive reception even in fringe areas. Operates on optional rechargeable 12-volt battery, 12VDC car/boat battery, or 117 VAC, 60 Hz. Built-in VHF telescoping antenna, front mounted controls, and front mounted 4 x 2 1/2" speaker. Compact lightweight cabinet. Black with chrome trim. Size: 10 1/2" x 9 1/2" x 10 1/2" D. Imported. Shpg. wt., 12 lbs. **17 R 33013WX No Money Down* Net 119.95**

- 11" Picture Measured Diagonally
- Channel Coverage VHF 2-13, UHF 14-83

Big 11" screen measured diagonally. Snap-in non-glare filter provides clear, vivid reception in any light. Super sensitive solid-state circuitry. Built-in VHF adjustable telescoping antenna. Front mounted oval 3 1/7 x 4 3/4" speaker. 23 transistors, 1 IC, 15 diodes, and 1 rectifier. Keyed AGC and AFC systems. Front mounted illuminated tuning knobs makes channel changing easy and accurate. Contemporary styling in black with silver trim. Size: 11 3/4" x 11 1/4" x 11 1/4" D. Imported. For 117 VAC, 60 Hz. Shpg. wt., 17 lbs. **17 R 33021WX No Money Down* Net 129.95**

POP-UP TV with AM/FM RADIO

- 5" Picture Measured Diagonally
- Built-in Rechargeable Batteries
- 82 Channel UHF/VHF Reception

"The solid-state TV that lives in a radio." With the screen down, the set turns "off" automatically and you have a smart attached FM/AM radio. Pop-up the screen and it becomes a TV. Plays on Panaloid rechargeable batteries (included). With the AC adapter (included) you can recharge the batteries while the set operates. Telescopic monopole/bowtie antennas. Front-mounted dynamic speaker. Slide rule UHF and radio tuning. With sun shield and an earphone for private listening. Size 5 1/2" x 11 x 12". Imported. Shpg. wt., 18 lbs. **17 R 31892WX No Money Down* Net 159.95**

17 R 33013WX No Money Down* Net 119.95

ACCESSORIES for SONY 720U, 740, 920U, 940, 110V and 112 TV's

Model BP/7 564. Shoulder rechargeable battery pack.

17 R 32296 Shpg. wt., 7 3/4 lbs.

Net 22.95

Model OCC-2AW. Car battery cord. For 12V/neg. ground systems.

17 R 32304 Shpg. wt., 1 1/4 lbs.

Net 14.95

17 R 32601 Model VCA-14 Car window antenna. Wt., 2 1/4 lbs.

Net 22.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Deluxe TV Sets—Color and Black & White

NEW

Sony Trinitron Single Gun Color TV Sets



MODEL KV 1710
17" Picture
Measured Diagonally
399⁹⁵

MODEL KV 1201
12" Picture
Measured Diagonally

299⁹⁵



• All Solid-State Circuitry

Model KV 1201—12" picture measured diagonally. Features: Sony Single Gun Trinitron Color System for magnificent true-to-life color, automatic color control, lighted channel indicators, instant picture and sound. Charcoal grey cabinet with chrome trim. Convenient carrying handle. With VHF dipole antenna and UHF loop antenna. Size: 13 1/8 x 17 1/4 x 15 1/2". For 117VAC, 60 Hz. Imported. Shpg. wt., 32 lbs.

17 R 32973WX No Money Down* Net 299.95
Model KV 1710—Same features as above but with 17" Picture measured diagonally and automatic fine tuning. Size: 13 1/4" x 18 1/2" x 15 1/2". Shpg. wt., 35 lbs. Imported.
17 R 33039WX No Money Down* Net 399.95

Panasonic Portable Color TV Sets



NEW MODEL CT 603
16" Picture
Measured Diagonally

324⁹⁵

MODEL CT 97P 18" Picture
Measured Diagonally

359⁹⁵

• Channel Reception: VHF 2-13, UHF 14-83

Model CT 603—16" picture measured diagonally. Transistorized circuitry includes 3 IC's. Features illuminated AFT (Automatic Fine Tuning) Control, automatic degaussing, Set-and-Forget tuning, slide lever controls for volume, color, and tint, VHF dipole and UHF bow-tie antennas. Diecast handle. Rosewood grained cabinet. With earphone. Size: 17 1/2" x 23 x 20 1/4". For 117VAC, 60 Hz. Imported. Shpg. wt., 63 lbs.
17 R 31983WX No Money Down* Net 324.95

Model CT 97P—18" Picture measured diagonally. Slide-lever controls, Panalock AFT Control, automatic degaussing, Set-and-Forget tuning. Includes VHF dipole and UHF bow-tie antennas, 3 x 5" oval speaker. Diecast handle. Vinyl-clad walnut cabinet. With earphone. Size: 23 3/4 x 18 1/2 x 18 1/2". For 117VAC, 60 Hz. Imported. Shpg. wt., 81 lbs.
17 R 31942WX No Money Down) Net 359.95

NEW Hitachi SU-86 B & W Solid-State TV Set



109⁹⁵

- 16" Picture Measured Diagonally
- VHF 2-13, UHF 14-83
- Memory Tuning
- Instant-on Picture and Sound

141 sq. in. viewable picture. All-transistorized chassis. Exceptionally clear picture is attained by adopting Set-and-Forget memory fine-tuning. Also features Automatic Gain Control, noise eliminator, and power regulator circuits. Instant picture and sound. Compact, lightweight, and easily portable with retractable carrying handle. VHF monopole and UHF loop antennas. Imported. Size: 21 1/4 x 14 1/2 x 14 1/2". For 117 VAC, 60 Hz. Shpg. wt., 31 lbs.
17 R 24285WX No Money Down* Net 109.95

Panasonic AN-112T B & W TV with Digital Clock



119⁹⁵

- 12" Picture Measured Diagonally
- Earphone for Private Viewing
- VHF 2-13, UHF 14-83

An exciting portable TV—with full feature digital clock, sleep timer, alarm and slide-lever controls. Set TV to turn off automatically, pre-set it to wake you up to TV or alarm in time to view your favorite show. Monopole VHF and bowtie UHF antennas pull in signals strongly and clearly. Up-front dynamic speaker. The clock face lights up for easy nighttime viewing. The sleep timer shuts the set off automatically after up to 3 hours of viewing. Complete with personal earphone. For 117 VAC 60 Hz. Size: 11 1/2" x 18 1/4" x 11 1/2". Imported, Shpg. wt. 23 1/4 lbs.
17 R 31918WX No Money Down* Net 119.95

NEW Sharp CY-61PA Color TV Set



269⁹⁵

- 15" Picture Measured Diagonally
- Channel Coverage: VHF 2-13, UHF 14-83

Intimate enough for personal pleasure . . . large enough for the family to watch a spectacular. Walnut-grain cabinet with ebony and brushed chrome trim. The screen is a full 15" of rich, true color. AGC for excellent reception even in fringe areas, AFC push-button control fine-tuned, locked-in pictures. "Split-Second Start" instant picture, instant sound. Front mounted speaker for full-fidelity sound. Includes dipole telescopic VHF and loop UHF antennas. UL Listed. Imported. Size: 21 x 16 3/4 x 14 1/2". For 117VAC, 60 Hz.
17 R 53219WX No Money Down* Net 269.95

Panasonic RC-6551 Digi-Dater FM/AM Digital Clock Radio

A
54⁹⁵



• Unique Clock Radio Has a Built-In Day and Date Calendar

Panasonic RC-6900 FM/AM Clock Radio Announces the Time!

D **129⁹⁵**

- Announces Time Whenever You Depress a Button
- May Be Set To Announce Time Every Hour On The Hour



Sony 8F11W Hi-Rise FM/AM Table Radio

B
29⁹⁵



Handsome Radio Set On a Sculptured White Pedestal

NEW
Ultra-Modern
Quality
Radios

SOLID-STATE

Panasonic RF-60 Solid State FM Stereo Headset

E
New Low Price
75⁰⁰
With Batteries

Your Own
Private Portable
FM Music Chamber



Panasonic RE-6231 FM/AM Table Radio With One-Way Intercom

C **22⁸⁸**

Can Serve As An Excellent Babysitter
When Used With An Optional Mike



KLH Model 21 Professional FM Table Radio

F
89⁹⁵

Beautiful
Walnut Cabinet

- Acoustic Suspension Speaker



A PANASONIC RC-6551 FM DIGITAL DIGI-DATER CLOCK RADIO. Big bold numbers that tell you the time and big bright letters and numbers that tell you the day of the week and the exact date, 24-hour full feature digital clock, 60-minute sleep timer with automatic shut-off, Music or gentle alarm wake-up, Auto/alarm indicator light, Extra-wink "nap-bar." Solid-State integrated circuitry. Built-in FM and AM antennas, AFC on FM. Illuminated radio and clock dials, 4" dynamic speaker. Earphone/pillow speaker jack, Midnight black cabinet. Complete with personal earphone. For 117 VAC, 60 Hz. Size: 5½"Hx14½"Wx6¼"D. Shpg. wt., 5½ lbs. Imported.
17 R 31108 No Money Down* Net 54.95

B SONY 8F11W AM/FM TABLE RADIO. Pushbutton AM, FM with AFC for drift free listening. Accurate tuning with a large vertical tuning dial. Powerful Solid-State circuitry for extended frequency response. Built-in AM and FM Antennas. Provision for using FM external antenna. Large 4" speaker for rich tone. Size: 10½"Hx9¼"Wx4¾"D. Shpg. wt., 4 lbs. Imported.
17 R 32981 Net 29.95

C PANASONIC RE-6231 FM/AM TABLE RADIO. Functions as one-way intercom that can serve as an excellent babysitter. Simply place optional microphone in room you wish to monitor. Built-in FM and AM antennas, 3" dynamic speaker. Large vernier circular tuning dial. Band selector switch. Finger-rip controls for tuning and volume. Microphone jack on the rear panel. May be placed on table or nightstand or may be hung from kitchen, den or bedroom wall. Solid-State circuitry. For 117 VAC 60 Hz. Size: 7¼"Wx4¾"Hx8¾"D. Shpg. wt., 3 lbs. Imported.
17 R 31116 Net 22.88
RD-9662 Microphone for above. Imported.
17 R 31082 Shpg. wt., 8 oz. Net 4.95

D PANASONIC RC-6900 FM/AM CLOCK RADIO. In place of the usual alarm, you can set the clock to announce the time every ten seconds for up to three minutes. Full-feature clock, 4-step on/off/auto/call function switch. Dual 60-minute sleep timer and alarm setting control. Built-in FM and AM antennas, illuminated slide-rule tuning, AFC on FM. Continuous tone control, 4" dynamic speaker. Earphone/pillow speaker jack. FM external antenna terminal. In midnight black and brushed aluminum cabinet. Solid-state circuitry. Complete with personal earphone. For 117 VAC, 60 Hz. Size: 9½"Hx15¾"Wx7¼"D. Imported. Shpg. wt., 13 lbs.
17 R 31090WX No Money Down* Net 129.95

E PANASONIC RF-60 FM HEADSET. Portable, operates on 3 "AA" batteries, included. Built-in super sensitive FM/FM Stereo Radio. Two sensitive antennas pull in both local and distant stations loud and clear. Tone control switch for instant selection of preferred bass or treble tones. Two 2½" full range transducers. Imported. Shpg. wt., 3½ lbs.
17 R 31660L No Money Down* Net 75.00
99 R 62500 Net ea. .10

F KLH 21. High performance monaural FM receiving system. Sealed oiled walnut cabinet combines with an outstanding built-in acoustic suspension speaker to provide truly full range sound. Stable solid state circuitry utilizes vernier tuning, built-in antenna, bass, and treble controls. Powers external accessory speaker and supplies signals directly to tape recorder for quality reproduction of FM broadcasts. Dim.: 12Wx6½Hx6¾"D. For 110-120V, 60 Hz AC. Shpg. wt., 10 lbs.
24 R 44073WX No Money Down* Net 89.95

*See Page 22 for Full Credit Details on Easy Pay Plan



Model LR-30

69⁹⁵

MODEL LR-30 FEATURES:

- Separate Slide Controls for Volume, Balance and Tone
- Two 5" Wide Range Speakers in Walnut Wood Enclosures
- FM Stereo Indicator Light
- Front Panel Stereo Headphone Jack for Private Listening
- Input Jack for Record Changer
- Tape Input and Output Jacks
- AFC on FM to Prevent Station Drift
- Handsome Walnut Grain Cabinetry

LAFAYETTE 3 PIECE SOLID STATE AM/FM/FM STEREO RADIO/RECEIVER

This handsome 3 piece modular system provides brilliant AM/FM/FM Stereo radio performance. Each rich sounding speaker system can be separated for the utmost in stereo effect. The radio section features an illuminated slide rule dial with logging scale for precise station selection. Includes features normally found in more expensive component systems: Full complement of controls: volume, tone, and balance slide controls. AFC on FM to prevent station drift. FM stereo indicator light which identifies stations broadcasting in FM stereo. Stereo tape recorder outputs to record programs heard on the radio. External inputs for record changer or tape recorder. Built in AM and FM antennas. Provisions for external FM antenna. Each separate speaker enclosure contains a full range 5" speaker. Walnut grain cabinetry with black and silver trim. Size: Receiver 15 $\frac{3}{4}$ "W x 4 $\frac{3}{8}$ "H x 9 $\frac{1}{4}$ "D. Speakers 8 $\frac{1}{4}$ "W x 9 $\frac{1}{2}$ "H x 5 $\frac{1}{2}$ "D. For 110-120V 60Hz. Imported. Shpg. wt., 20 lbs.

17 R 02315W No Money Down* Net 69.95
 Lafayette MC-22B Mini 4 Speed Record Changer Ensemble for above (see page 91 for description). Shpg. wt., 7 lbs.
 21 R 01772W No Money Down* Net 34.95

Deluxe LAFAYETTE Solid-State AM/FM Walnut Table Radio

- Tuned RF FM and 4 IF Stages
- Tape Recorder Output Jack
- External Speaker Output Jack

39⁹⁵

A deluxe high-fidelity AM/FM radio employing an advanced solid-state circuit with 12-transistors and 14-diodes. However, it is more than just an AM/FM radio, it combines a super-sensitive AM and FM receiving section with a tuned RF FM stage and 4 IF's, a high-fidelity amplifier, and a full-range acoustic suspension loudspeaker in one compact and handsomely designed 3/8" walnut wood enclosure. Built-in AM and FM antenna system. Separate Band Selector. Continuous Tone control, and Volume control. AFC for drift-free FM. Jack at the rear of the radio marked REC may be used to plug in a tape recorder to record any programs heard on radio. Also includes provisions for hooking up an external 8-ohm speaker as well as external FM or AM antenna. Beautiful oiled walnut wood cabinet with woven tan grill. For 105-120V., 50/60 Hz AC. Size: 13L x 5 $\frac{1}{2}$ D x 8 $\frac{3}{8}$ "H. Imported. Shpg. wt., 10 $\frac{1}{4}$ lbs.
 99 R 35644W Net 39.95



Magnificent Hi-Fidelity Sound Reproduction from a Powerful 5" Acoustic Suspension Speaker

*See Page 22 for Full Credit Details on Easy Pay Plan

LAFAYETTE'S BEST

Deluxe LAFAYETTE Solid State AM/FM Digital Clock Radio



FEATURES

Revolutionary General Time Clock
and Rosewood Swivel Pedestal Base

49⁹⁵
With
Earphone

- Full Feature Backlighted Digital Movement
- Wake up to Music, or Music Followed by an Alarm 15 Minutes Later
 - 60 Minute Sleep Switch
 - 15 Minute Snooze Button
- 2 Speakers—4" Woofer and 2" Tweeter delivers Rich Hi-Fi Sound
- Precision Engineered Sliding Volume and Tone Controls
 - Blackout Slide-Rule Dial lights up when Radio is On

The most beautiful, and the best performing AM/FM clock radio Lafayette has ever offered. Handsomely styled on a Rosewood pedestal swivel base with Rosewood side panels. Features new revolutionary full feature General Time clock with backlighted digital movement that provides large easy-to-see numerals. A blackout slide-rule dial lights up when the radio is on. Separate precision sliding controls for Tone and Volume. Front panel clock lever control for on, off, auto, and alarm. Convenient "sleep" slide lever control can be set to automatically shut the radio off (up to 60 minutes) when you go to sleep. Wake up at a preset time to music, or music followed by an alarm 15 minutes later. By depressing the snooze button, the radio turns off, and you can have an extra 15 minutes of sleep. Switchable AFC lock prevents drift on FM. Magnificent hi-fi sound is provided by a 2 speaker 2-way system consisting of a 4" woofer and 2" tweeter with crossover network. Built-in AM and FM AC line cord antenna. Size: 12" x 5" x 3 1/2". For 117 VAC/60 Hz. Shpg. wt., 8 lbs. Imported. 17 R 01911W No Money Down* 49.95

LAFAYETTE Solid State AM/FM Digital Clock Radio with Slide Controls

- Convenient Slide Lever Clock Controls Are Located On The Front Panel
- Wake Up To Music, Or Music Followed By An Alarm 15 Minutes Later
- 60 Minute Sleep Switch
- 15 Minute Snooze Button

This superb performing solid-state AM/FM clock radio features the new General Time clock radio features the new General Time back-lighted digital movement—a light shines thru the clock numbers making it easy to read the time in the darkest room. Unique, simple sliding lever clock controls are located on the front panel. So simple to use, even children and adults alike can operate this radio. Convenient sleep slide switch can be set to automatically shut the radio off (up to 60 minutes) when you go to sleep. Choose whatever you would like to wake up to at a pre-set time, music only or music followed by a soft alarm 15 minutes later. Catch an extra 15 minutes of sleep by engaging the "snooze" feature after the alarm sounds. Large 3 1/2" speaker assures rich full bodied sound. Built-in AFC keeps FM stations from fading in and out. FM antenna is built into the AC line cord for sensitive FM reception. The entire slide rule station panel lights up when listening, making it easy to tune even in a darkened room. Cabinet is of hi-impact polystyrene, black with walnut side panels. Operates on 117V AC, 60 Hz. Size: 9 3/4" W x 5 1/2" D x 3 1/2" H. Imported. Shpg. wt., 5 lbs. 17 R 01150W No Money Down* Net 34.95



Revolutionary General Time Clock

34⁹⁵
With
Earphone

- Large, Easy-To-Read Digital Clock Numerals
- Full Feature Back-Lighted Digital Movement

Quality Clock Radios

LAFAYETTE Solid-State Full Feature Clock Radios

Low Profile AM/FM Radio

Combines a fully automatic full feature Westclox clock with Soft Glow Electro-Luminescent Night Light and a superb FM/AM radio in a handsome low profile styled walnut grained plastic cabinet with black and silver trim. Handy sleep-switch permits you to slowly drift-off to dreamland while the radio automatically shuts itself off (up to 60 minutes). Beautiful FM or AM music will awaken you at a preset time. Even includes a snooze button so that the Radio can again be turned off to permit you an extra 10 minutes of sleep. All solid state circuitry with 10 transistors, 4 diodes and 1 thermistor provides high sensitivity and selectivity enabling you to pull in stations crystal clear, both near and far. Size: 9½ x 5½ x 3¼". For 117 V AC, 60 Hz. Imported, wt., 3½ lbs. 17 R 01895W Net 29.95



29⁹⁵

With Earphone

- Full Feature Westclox Clock Movement
- 60 Minute Sleep Switch
- Precision Slide Rule Dial
- 10 Minute Snooze Button
- Large 3½" Speaker

Digital AM/FM Radio

An exceptionally fine performing AM/FM Solid State Clock Radio. Handsome walnut veneer wood cabinet. Illuminated 24 hour full feature leaf-type digital clock has large 3/4" numerals, and needs to be set only once. Thereafter it will wake you up every morning at the same time without additional adjustment. A timer can be set to lull you to sleep with up to 60 minutes of music. Large prismatically lit slide rule tuning dial. Wide-range 3½ speaker provides rich sound. Continuous tone control, AFC for drift-free FM performance. FM AC line cord antenna. Ferrite core AM antenna. Size: 4¼" x 12" x 5¼". Shpg. wt., 5 lbs. Imported. For 117 VAC 60 Hz. 17 R 01135W No Money Down* Net 39.95



39⁹⁵

- Full Feature Illuminated 24-Hour Leaf Type Digital Clock
- 60 Minute Sleep Switch
- Walnut Wood Cabinet

Panasonic RE-6600 AM/FM Digital Clock Radio with Built-In Cassette Recorder



99⁹⁵ With Remote Control Mike

Wake Up to Alarm, Radio, or Pre Recorded Cassette Tape

Solid State AM Clock Radio



14⁹⁵

- Big 3" Speaker
- Compact Styling
- Precision Automatic Clock

Combination Full-Feature Digital Clock FM/AM radio and a custom Cassette Tape Recorder. Clock Radio features: 24 hour timer, continuous tone control, full range 4" dynamic speaker, and AFC on FM. Cassette Recorder features: Auto-stop, Easy-matic Recording Level Control, and push button controls. All solid state circuitry of extreme reliability. Built-in FM line cord and AM ferrite core antennas. Earphone/EXL speaker jack; phono and mike input jack. With earphone and remote control mike. Size: 4¼" H x 18¾" W x 10" D. Shpg. wt., 10 lbs. For 120VAC, 60 Hz. Imported. 17 R 31066W No Money Down* Net 99.95

Wake up to beautiful music or news at a pre-set time. Compact, low profile, decorator design. Ideal for bedside, table, bookshelf, or desk. The full size clock makes for easy, accurate time telling. Only 4¼ x 8¾ x 3". Attractive walnut-grained plastic cabinet. You will enjoy sensitive AM reception on all your favorite stations. Features powerful 3" speaker for fine tonal quality. Automatic gain control circuitry, and built-in AM antenna. Solid state circuitry for Instant-on play. No warm-up. For 110 VAC 60 Hz. Imported. Shpg. wt., 2¾ lbs. 17 R 69454 Net 14.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 157

Our Best Selling Personal Portable Radios

LAFAYETTE Battery/Electric Solid State AM/FM Portable Radio



17⁹⁵

- With Earphones and Batteries
- Plugs into any AC Outlet or Plays Anywhere on 4 "C" Batteries
- Powerful 3" Speaker

Handsome, full-sized personal AM/FM portable. Smartly styled leatherette cabinet with beige and chrome trim. Provides excellent FM as well as AM reception. Comes gift packed with earphone and batteries included. Features precision slide rule dial, and wide range 3" dynamic speaker for clear, crisp tonal quality. Telescopic FM antenna and ferrite core AM antenna. Leatherette carrying handle. Size: 9"W x 5"H x 3"D. Imported. Shpg. wt., 3½ lbs.

17 R 01903L Net 17.95
99 R 62572 Extra "C" bat. (4 req.) Net ea. .16

LAFAYETTE Solid-State AM/FM Portable Radio



9⁹⁵

- Built-In AFC
- With Earphone, Battery and Carrying Strap

Handsomely styled, personal pocket-size AM/FM portable radio. Powerful solid-state circuitry provides sparkling performance. Precision slide-rule tuning dial. Large 2¼" dynamic speaker. Built-in AFC. Ferrite rod antenna for AM, telescoping antenna for FM. Powered by single inexpensive 9-volt battery. Earphone for private listening. Black with walnut and chrome trim. Size: 5 x 3 x 1½". Imported. Shpg. wt., 1 lb.

17 R 01937L Net 9.95
Extra 9V batt.
99 R 60212 Net .29

LAFAYETTE Solid-State AM Pocket Radio



4⁹⁸

- With Earphone, Battery, and Carrying Case

Low priced pocket AM Radio provides fine tone from a 2¼" dynamic speaker. Attractive styling with separate unique volume and tuning indicators. Comes with Earphone for private listening. Instant-on solid state circuitry. Built-in AM antenna. Operates on one inexpensive 9-volt battery. Black case. Size: 4½"H x 2½"W x 1¼"D. Shpg. wt., 1½ lbs. Imported.

99 R 35123L Net 4.98
99 R 60212 Extra 9-Volt Battery Net .29

Panasonic R-70 Spherical AM Portable



9⁸⁸

- Gift-boxed with Earphone and Battery
- Instant-on Solid State Circuitry

Funloving spherical styling, unique easy-grip controls and carrying chain. Sensitive built-in ferrite core antenna pulls in both local and distant stations loud and clear. A 2¼" PM dynamic speaker delivers rich sound. Size: 4¾"D. Imported.

17 R 31975L Shpg. wt., 2 lbs. Net 9.88
99 R 60212 Extra 9V Battery Net .29

Blue shown. May come in red or white.

Micro Solid-State AM Wrist Radio



13⁹⁵

- Gift Packed with Earphone and Wrist-Strap

Shaped like a wrist watch, but actually a sensitive AM radio, only 2¾" x 1¾" in size. Utilizes space-age instant-on miniaturized solid state circuitry. Operates on 2 MS41 batteries (not included). Ferrite bar AM antenna. When you plug in earphone (included) radio speaker is cut off. Includes earphone and wriststrap. Imported. Shpg. wt., 4 oz.

17 R 21026L Net 13.95
MS41 Batteries for wrist radio. Package of six. Shpg. wt., 3 oz.
32 R 46931 Net 1.80

Solid State Multi-Band Portable Radios

LAFAYETTE BATTERY/ELECTRIC 4-BAND AM/FM/SW/MARINE PORTABLE RADIO

FEATURES

- Built-in AC Line Cord
- AFC on FM to Prevent Drift
- Fine Tuning, Tone Controls
- SW: 9-18 Mhz, MB: 2.5-6.5 Mhz
- Horizontal Slide Rule Tuning

One of the most versatile and handsome multiband portable radios we've ever offered. Provides superb performance and magnificent tonal quality. You can listen to standard AM and FM broadcasts, thrilling international shortwave programs on the 9-18 MHz band, and marine navigation and weather reports on the 2.5 to 6.5 Mhz band. Fine tuning control for precise and accurate station selection on the shortwave band. Powerful reception from 23 solid state devices—12 transistors, 10 diodes, 1 thermistor. Richly styled black and chrome cabinet with walnut grained side panels. Plays on 4 "C" batteries (included) or 117 VAC with self storing AC line cord. Also features separate Tone control, telescoping FM, SW, and Marine antenna. Built-in AM antenna plus provision for using external wire antenna. Size: 10 $\frac{3}{4}$ x 7 $\frac{1}{2}$ x 3 $\frac{3}{4}$ ". Shpg. wt., 7 lbs. Imported.

17 R 02323L No Money Down* Net 34.95
Extra "C" bat. (4 req.) _____ Net ea. .16
99 R 62572 _____



NEW 34⁹⁵

With 4 "C" Batteries,
External Antenna Wire,
Earphone, Dial-c-Map,
and Shortwave Guide

3-Band Battery/Electric AM/FM/SW Portable



27⁹⁵

With Batteries Tunes 3 Bands
AM: 530-1600 kHz
FM: 88-108 MHz SW: 3.8-12 MHz

Enjoy the finest in drift-free reception—hear your favorite news, sports, weather and special events on AM radio. Hear symphony concerts, world renowned soloists, jazz bands on FM radio. Tune in Paris, Rome, London, Moscow and dozens of other cities on the International Shortwave band. This superb radio operates on 4 "C" batteries or on standard 117 VAC house current. Comes with convenient carrying handle for effortless portability. Features AC/DC switch, logging scale for precise tuning, color-coded band indicator, and AFC for drift-free FM reception. Telescoping antenna for FM and SW. Ferrite bar antenna for AM. Instant-on solid-state circuitry, earphone jack for private listening. Black padded, simulated leatherette cabinet. Size: 8 $\frac{3}{4}$ W x 7 $\frac{1}{4}$ H x 3"D. Imported. Shpg. wt., 4 $\frac{1}{2}$ lbs.

17 R 02307L _____ Net 27.95

Deluxe LAFAYETTE Battery/AC AM/FM Portable Radio



22⁹⁵

With Batteries

- AFC for Drift-free Reception
- Precision Slide Rule Tuning
- Superb Tone with Wide Range 3 $\frac{1}{2}$ " Speaker

Superb-performing AM/FM portable radio in a deluxe cabinet with a big 3 $\frac{1}{2}$ " wide range speaker for magnificent tone. Features one RF and three IF stages for extremely high sensitivity and selectivity enabling the listener to hear more stations. Precision Vernier slide rule tuning dial with logging scale. AFC on FM to prevent drift. Telescoping FM and ferrite core AM antennas. 10 transistors and 5 diodes. AC/DC switch. Rugged black leatherette cabinet with convenient carrying handle for effortless portability. Includes earphone and 4 "C" batteries. Size: 5 $\frac{5}{8}$ x 9 x 2 $\frac{1}{2}$ ". Imported.

17 R 01929L Shpg. wt., 4 lbs. _____ Net 22.95
99 R 62572 Extra "C" bat. (4 req.) _____ Net ea. .16

LAFAYETTE'S Best Selling Police and Aircraft Portables

**"Air Master 400 4-Band 17 Transistor FM/AM/Police/Aircraft Radio
Tunes 4 Exciting Bands!"**



**High Band
Police and Fire**

147-174MHz FM/VHF



**FM Broadcast
88-108 MHz**

**AM Broadcast
540-1600 kHz**



**Aircraft Band
108-136 MHz
AM/VHF**



44⁹⁵ With Batteries
and Earphone
No Money Down*

- Operates on 4 "D" Batteries or 117 VAC
- Variable Squelch Control for Tuning FM, AIR and Police Bands
- Record Output Jack
- Large 4" Speaker for Magnificent Tonal Quality
- Precision Slide Rule Tuning Dial
- Tunes U.S. Weather Broadcasts on 162.55 KHz



The "Air Master 400" is a professionally designed portable radio that tunes Standard AM Broadcasts, Standard FM Broadcasts, FM-VHF High Band Police Calls, AM-VHF Aircraft Band (monitor planes in flight awaiting instructions from the control tower), and U.S. Weather Bureau Forecasts. Individually tuned front end circuits for each band provides higher sensitivity—assuring sharp response with exceptional stability. Variable Squelch control while tuning Police and Aircraft Bands—also serves as Interstation muting on FM Broadcast Band. Self-Storing AC line cord for 117 VAC house current. Also operates on 4 "D" cell batteries. Telescoping antenna for FM, Police and Aircraft; built-in loopstick antenna for AM, 17 transistors, 11 diodes; 2 thermistors. Jack for Ext. Ant, Phone; Record output. Padded black vinyl case with handle. Size: 11½ x 7½ x 3½" D.
99 R 35578W Imported. Shpg. wt., 7 lbs. Net 44.95
99 R 62564 Extra "D" bat., 4 req. Shpg. wt., 5 oz. Net ea. .18

Guardian II 2-Band Solid State FM-VHF and AM Police Radios



HIGH BAND

LOW BAND

FM-VHF—147-174 MHz
AM —540-1600 kHz

FM-VHF—30-50 MHz
AM —540-1600 kHz

21⁹⁵ with earphones
and batteries

21⁹⁵ with earphones
and batteries

"Guardian 300" 3 Band Battery/Electric Solid-State FM-VHF/FM/AM Police Radios



HIGH BAND

LOW BAND

FM-VHF—147-174 MHz
AM —540-1600 kHz
FM —88-108 MHz

FM-VHF—30-50 MHz
AM —540-1600 kHz
FM —88-108 MHz

29⁹⁵ with earphones
and batteries

29⁹⁵ with earphones
and batteries

HIGH BAND FM-VHF POLICE AND AM RADIO. Listen to the drama of everyday life with this exciting radio. Monitor local and state police, as well as fire departments. 162.55 MHz. U.S. Weather Bureau stations, civil defense, and emergency public services. Includes standard AM band. Loaded with these outstanding features: 2 RF stages, 4 IF stages, slide rule logging scale for precise tuning, ferrite rod AM antenna, telescoping VHF antenna, large 3" speaker for superb fidelity. Handsome black case with silver trim. Earphone jack for private listening. Operates on 4 "AA" type batteries (included) or 117 VAC with optional AC adapter. 11 transistors, 4 diodes, 1 thermistor. 7W x 4½H x 2¼"D. Imported.

99 R 35222L Shpg. wt., 2¼ lbs. Net 21.95

LOW BAND FM VHF POLICE AND AM RADIO. Same deluxe features and specifications as above Police radio but tunes low band 30-50 MHz instead of High Band. Imported. Shpg. wt., 2¼ lbs.

99 R 35347L Net 21.95

ACCESSORIES FOR GUARDIAN II POLICE RADIOS

Stock No.	Description	Shpg. Wt.	Net Ea.
99 R 35362	AC Adapter	12 oz.	.395
99 R 62580	Extra "AA" Batteries (4 required)	3 oz.	.10

HIGH BAND FM-VHF POLICE AND AM/FM RADIO. Listen to Police and fire calls . . . ANYWHERE—ANYPLACE. Deluxe 3-band radio operates on 4 "C" batteries or 117 VAC 60 Hz by means of a self-storing AC line cord. Powerful space age solid-state circuitry with 12 transistors, 6 diodes, and 2 thermistors. Variable 6-gang capacitor tuning for extremely high sensitivity and selectivity enables you to pull in even the weakest stations. Complete coverage includes high-band FM-VHF 147-174 MHz including 162.55 U.S. Weather Bureau Forecasts and standard AM and FM broadcast bands. Slide rule dial for precise tuning, ferrite rod antenna for AM, telescoping antenna for FM-VHF and FM bands, and an external antenna input jack. Padded black leatherette case with silver trim. Includes batteries, earphone and self-storing AC line cord. Size: 8½"W x 4½"H. x 2½"D. Imported. Shpg. wt. 3¼ lbs.

99 R 35461L Net 29.95

LOW BAND FM-VHF POLICE AND AM/FM RADIO. Same deluxe features and specifications as above but tunes low band FM-VHF 30-50 MHz instead of High Band. Imported. Shpg. wt., 3¼ lbs.

99 R 35479L Net 29.95

99 R 62572 Extra "C" bat. for above—4 req. Net ea. .16

DELUXE! LAFAYETTE "Guardian 5000" 5-Band Solid-State AC and Battery-Operated AM/FM/SW/FM-VHF Public Service Radio

Tunes 5 Exciting Bands!



For Police
and Fire

Low Band FM-VHF 30-50 MHz



For Police,
Fire, Weather

High Band FM-VHF 147-174 MHz



For Sports
and News

Standard AM 540-1600 kHz

Listen to London,
Vatican, Moscow
and Voice of America



Shortwave 4-12 MHz



World Famous
Symphonic
Orchestras

Standard FM 88-108 MHz

- Two Separate Front-End RF Tuning Sections For Both High and Low Police FM-VHF Bands

Monitor the airwaves of the world! Listen to Police, Fire, Civil Defense, 2-way Business and U.S. Weather forecast on BOTH THE HIGH (147-174 MHz) and LOW (30-50 MHz) FM-VHF band. Tune the 4-12 MHz International Shortwave Bands. Enjoy outstanding music on the standard FM band (88-108 MHz), as well as news, weather and sports on the standard AM band (540-1600 kHz). Advanced space age solid-state circuitry permits instant operation—no loss of precious time due to warmup—permits immediate response to emergency situations. Two separate 4 gang tuning capacitor front ends for both high and low FM-VHF Police bands for greater sensitivity and more dependable selectivity—weak stations can be heard clearly—while outside noise and interference are drastically reduced. Operates on



ONLY
59⁹⁵
with batteries, earphone
for private listening,
and AC adapter

- Variable Squelch Control While Tuning FM-VHF Bands... Also Serves As Interstation Muting on Standard FM Band

4 "C" batteries or 117 VAC household current with AC adapter (included). Excellent quality of tone from large 3 1/2" speaker makes this a true hi-fidelity portable radio. Telescoping antenna for FM, FM-VHF, and SW bands. Built-in ferrite core antenna for AM band. Accessory jack for use of separate external antenna. Slide rule logging scale for precise tuning. AFC circuitry prevents drift on FM. Beautiful walnut wood grain molded case with metal grill, gold trim, and handle. Includes 4 "C" batteries, earphone, and AC adapter. Dim.: 8 3/4" x 6 1/2" x 2 3/4" D. (Metal handle 3 1/2" x 1/2") Imported. Shpg. wt., 6 lbs.
99 R 35438L No Money Down^{*} Net 59.95
Extra "C" batteries—4 required
99 R 62572 Net .16

LAFAYETTE 4-BAND TV-FM-FM/VHF POLICE PORTABLE RADIO



39⁹⁵

With Batteries
and Earphone

TUNES

- TV Low: Channels 2 thru 6
- TV High: Channels 7 thru 13
- Standard FM Broadcasts: 88-108 MHz
- FM-VHF High band Police: 146-175 MHz
- Instant-on Solid State Circuitry

- Listen to TV Privately Without Disturbing Others
- Listen to TV Anywhere Without Viewing

A unique and truly different concept in the design of a radio. Allows you to tune TV channels 2 thru 13. Listen to the many outstanding sporting events, variety shows and special normally transmitted only on TV. At night, use your TV for the picture but control the sound from the radio—earphone lets you listen without disturbing others. Monitor Police and Fire emergency calls. Listen to U.S. Weather Bureau forecasts on 162.55 MHz. Also receives standard FM broadcasts. Operates on 4 "C" batteries or 110 VAC with optional adapter. Super-sensitive, instant-on solid-state circuitry. Precision sliderule tuning dial. Built-in telescoping antenna, external antenna jack, leatherette carrying handle, earphone, and batteries. Black plastic cabinet. Size: 9 x 5 1/4 x 2 5/8" D. Imported.
99 R 35636L Shpg. wt., 4 lbs. No Money Down^{*} Net 39.95
99 R 62572 Extra "C" batteries. 4 req. Net ea. .16
99 R 35362 110 VAC Adapter. Wt., 10 oz. Net 3.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 161

DELUXE

Lafayette GUARDIAN "6000" 6-Band Battery/Electric AM-FM-Police-Aircraft-Marine Portable Radio

Radio Direction Finder
180° Rotatable Ferrite Loopstick Antenna for LW, AM, and MB Reception PLUS Direction Finding on these Bands.




Optional Mounting Bracket for Marine use so that Radio can be secured. **ONLY 3.95**

Signal Strength Tuning Meter/Battery Condition Meter

TUNES 6 BANDS

- 1 LW: 180-380 kHz Beacon Band
- 2 AM: 540-1600 kHz Standard Broadcast
- 3 MB: 1.6-4.0 MHz Marine Band
- 4 FM: 88-108 MHz Standard Broadcast
- 5 AIR: 108-136 MHz AM/VHF Aircraft
- 6 POLICE: 147-174 MHz FM/VHF High Band Public Service and U.S. Weather Bureau Forecasts & New VHF/FM Marine Band

Professionally designed 6-band portable radio with individually tuned circuits to provide extra sharp reception on each band. Tunes Long Wave Beacon Band, Standard AM & FM broadcast Bands, Marine Band, Aircraft Communications Band, and FM-VHF Police and Public Service High Band including the 162.55 MHz U.S. Weather Bureau Forecasts. Can be operated on 4 "C" batteries for portable use, or from 117 volt, 60 Hz AC with built-in AC line cord for home use. In addition the Guardian "6000" also has Radio Direction Finding Facilities. This will permit the boat owner to obtain bearings from marine beacon stations on the Long Wave Beacon Band, from broadcast stations on the AM Band, and small craft stations on the Marine Band. Also includes a calibrated optical sighting arrangement for visual bearings. Other features include a combined Tuning Meter/Battery Condition Indicator; adjustable telescoping whip antenna



Tunes 6 Bands

Squelch Control

79⁹⁵


With Batteries and Earphone

No Money Down*

- Individually Tuned Circuits
- Instant-on Solid State Circuitry

(plus an external antenna jack) for reception on FM, AM/VHF (Air) and FM/VHF Police Band; adjustable squelch control to eliminate background noise on the FM, Air, and Police Bands; output jacks for use with headphone or external speaker; and Automatic Gain Control to vary the sensitivity of the radio and tuning meter for direction-finding purposes. Slide Rule dial has a logging scale for precise tuning and a push-button dial light. Large 4" Speaker for exceptional tonal quality. Steel handle for ease of portability. 18 Transistors, 14 Diodes, and 2 Thermistors. Size: 11½" x 9" x 3". Imported. 99 R 35065W Shpg. wt., 6½ lbs. No Money Down* Net 79.95 Mounting Bracket For Fixed Marine Use. Imported. Wt. 6 oz. 17 R 64000 Net 3.95 Extra "C" Batteries (4 req.) wt., 4 oz. 99 R 62572 Net ea. .16

LAFAYETTE "Air Master" 10 Transistor AM and VHF Aircraft Portable Radio



19⁹⁵

With Batteries, Earphone, and Carrying Strap

- 108-136MHz VHF AM Aircraft Band
- 540-1600kHz AM Band
- Precision Slide Rule Logging Scale
- Large 3" Speaker

Listen to the exciting frequencies of aircraft communications in your home, car, or office on the 108-136MHz aircraft band. Monitor aviation control tower transmissions, listen to planes in flight, get their landing patterns and weather reports. You are actually with the pilot as he receives instructions for take-offs and landings. Also includes AM band. Features large 3" speaker, slide rule dial with logging scale, ferrite rod AM antenna, telescoping VHF antenna. Operates on 4 "AA" batteries (included) or on 117V AC with optional AC adapter. Earphone for private listening. 10 transistors, 2 diodes, 1 thermistor. Size: 7" x 4½" x 2½". Imported.

99 R 35230L Shpg. wt., 2¼ lbs. Net 19.95
99 R 35362 AC Adapter for above. Shpg. wt., 12 oz. Net 3.95
Extra "AA" batteries (4 required) wt., 3 oz. 99 R 62580 Net ea. .10

NEW Exclusive From LAFAYETTE

Deluxe Guardian 7000 Multiband Portable Radio

with **3** BIG POLICE BANDS!

FM/UHF ULTRA
HI 450-470 MHz

FM/VHF HI
147-174 MHz

FM/VHF LOW
30-50 MHz



89.95

With Batteries
and Earphones

COVERS ALL 3 PUBLIC SERVICE BANDS

Monitor: Police • Fire • Civil Defense • Highway
Maintenance • U.S. Weather Bureau • Forestry
• Conservation • Railroad

ALSO TUNES

International Shortwave: 4-12 MHz

Standard AM: 54-1600 kHz Standard FM: 88-108 MHz

Our new solid-state multiband radio provides the professional listener or hobbyist with one of the industry's most advanced techniques in monitoring the exciting UHF and VHF signals of police, fire, U.S. Weather, Civil Defense, etc. The Guardian 7000 can tune 3 POLICE BANDS—ULTRA HI FM/UHF 450 to 470 MHz, High FM/VHF 147 to 174 MHz, and Low FM/VHF 30-50 MHz. You can also listen to International Shortwave Broadcasts on the 4-12 MHz band, as well as Standard AM and FM broadcasts. The Guardian 7000 has been engineered for outstanding performance and dependability with excellent sensitivity. Completely portable, it can be operated on 4 "C" batteries, or from 117 Volt, 60 Hz AC with built-in AC line cord.

Delivery 12/1/71

OUTSTANDING FEATURES

- Squelch Control
- Signal Strength Tuning and Battery Condition Meter
- Individual Tuned Circuits
- Instant-on Solid-State Circuitry
- Battery or AC Operation
- 2 Telescoping Antennas

Other deluxe features include a combined tuning meter/battery condition indicator, adjustable telescoping whip antenna, one for UHF, the other for VHF, SW, and FM Bands (plus an external antenna jack), adjustable squelch to help eliminate background noise; output jacks for use with headphone or external speaker, station logging scale, continuous tone control, pushbutton dial light, output jacks for earphone and external speaker. Sturdy, built-in handle for ease of portability. Size: 11½W x 7¾H x 3½"D. Imported. Shpg. wt., 9 lbs. 99 R 35677W No Money Down" Net 89.95

99 R 62572 "Extra C" batteries (4 req.) Net ea. .16

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 163



**PORTABLE
TRANSISTORIZED
ELECTRONIC ORGAN
With Built-In Amplifier
and Speakers**

- Easy to Carry—Packs Like a Suitcase
- Perfect for Combo or Home Use

299⁹⁵

Portable organ has a built-in fully transistorized 10-watt amplifier and two oval speakers. Ready to play anywhere... Suitable for any entertainer, at home or school. 49-key keyboard spans 4 full octaves and produces a wide range of tonal variations. Three 16' voice tabs—bass bourdon; bourdon; and strings. Four 8' voice tabs—flute; diapason; strings; and trumpet. Trumpet tab simulates 4' effects to give an even wider variety of sounds. On-Off tab vibrato with rotary speed and intensity controls. Volume/On-Off switch with pilot light and separate volume control for bass octave. Photo-cell type expression pedal. Can also be played through an external amplifier. Comes in red and black trim. Size: 31" keyboard; height 32"; 18" deep. Operate on 117 VAC. Imported from Italy. Shpg. wt., 61½ lbs.

13 R 66343W Net 299.95

magnum Chord Organ Ensemble



- Complete With Bench and Hard Covered Music Book

39⁹⁵

Anyone can play this organ in minutes... without lessons. Features 37 full-size treble keys and 12 chord buttons. Handsomely designed walnut finish hi-impact polystyrene cabinet with decorator inspired front panel enhances any decor. Stands 32" high on 4 detachable legs. Matching hassock bench has deep foam cushion in color coordinated textured vinyl. Matching music rack with light, On/Off switch. Complete with hard-bound music book. Size: 9½x28¾x10 10/16"D. For 117 VAC, 60 Hz. Shpg. wt., 35 lbs.

12 R 58078W Net 39.95

Panorama of Living Music in Colored Lights

**4-COLOR SOUND ACTUATED
COLOR LIGHTS 34⁹⁵**



4-color solid-state sound actuated color lights. You can actually see every note and tone converted to a brilliantly moving panorama of colored, dancing images with each note and tone produced by the music. Flashing red, blue, green and yellow colors creates an entertaining display of multi-color, 3-dimensional spontaneity which varies to the amplitude of the sound source. Hi/lo input allows you to adjust for music power levels; Sensitivity control. Housed in walnut wood grained cabinet. Easily connects to speaker leads. Size: 24x12x10". Wt., 15 lbs. 21 R 25904W Net 34.95

**WIRELESS 4-COLOR
AUDIO LIGHTS**

Same as above except with built-in microphone. No speaker leads to connect.

21 R 26084W Net 39.95

Audio-Lites[®]



**PRISMATIC COLOR
AUDIO LIGHTS 24⁹⁵**

Add a new dimension to your musical enjoyment. Priced to fit your budget. One-piece prismatic lens produces a brilliantly moving panorama of colors that have a 3-dimensional effect. Dancing images are seen with each note, tone and pitch produced by the music. Solid-state electronic control transposes sound impulses into multicolor patterns. Will not affect amplifier operation. Easily connects to speaker leads. Attractive simulated walnut vinyl cabinet. For 117 VAC 60 Hz. Size: 18x11x7". Shpg. wt., 8½ lbs. 13 R 75526W Net 24.95

FREQ-LITE

19⁹⁵



Remote Control

- The Louder the Sound
the Brighter the Light!

Now, without complicated and costly stage production equipment, lighting can be as wild as voice or music! Connect to any amplifier, tape recorder, or record player, its brilliance changes from note-to-note, projecting fantastically fast and precise variations of lighting to match the intensity of sound. Use multiple units in a group with varied light colors in each unit to get sensational color blending with sound. Control unit can be placed virtually anywhere for remote operation of light sensitivity, or, to turn lights on and off. System can also be used as a constant light source. Uses 2-75W flood lamps. Operates on 110-125V., 60 Hz AC. Includes lamps. 10' AC line cord. 13 R 17759 Shpg. wt. 4½ lbs. Net 19.95

BIG

SOUND

Drums



OPTIONAL
16"x16" Floor Tom Tom

ONLY
89⁹⁵

No Money Down*

9-PC. "COMBO" DRUM OUTFIT

- 6-Ply Construction Thru-Out
- Double Lug—Separate Tension
- With 14" Cymbal—Cow Bell—Tone Block—Sticks—Brushes
- "Fast-Action" Bass Drum Pedal

Ideal for beginner or advanced musician. Outfit contains an 8" x 12" Tom Tom, a 14" x 20" bass drum, both with double lug separate tension rods, and a 5 1/2" x 14" separate tension snare drum. Bass drum features adjustable "fast-action" pedal and chrome plated streamlined hardware. All drums have professional plastic heads, feature triple flanged rims. Also high quality 14" cymbal with external mounted "L" spaced adjustable telescoping cymbal holder. Attachment of Tom Tom disassembles, a flat base snare drum stand and block, brushes, chrome plated cow bell and block. Bright Blue Sparkle finish. Imported. Shpg. wt., 45 lbs.

13 R 24680WX Net 89.95
15" x 16" FLOOR TOM TOM FOR ABOVE Chrome Plated Steel Rims, 9-Ply 13 R 24573WX Wt., 19 lbs. Net 48.95

A DRUMMERS THRONE

Drummer's throne, chrome plated. Padded seat, 11" dia. Adjustable height from 20" to 27". Folds easily. Shpg. wt., 6 1/2 lbs.

13 R 66293W Net 13.50

B HIGH-HAT OUTFIT

Two 14" Swiss brass cymbals on an adjustable, chrome plated flat base. Features a fast action foot pedal for added speed and comfort in playing. Base adjusts from 24" to 31". Shpg. wt., 7 1/2 lbs.

13 R 66285W Net 32.95

C SNARE DRUM SET

An exciting 14"x5 1/2" separate tension, 6 ply snare drum with metal snares, tone modulator, speedy throw-off, flanged hoops, rolled chrome plated rims, plastic head, and nickel plated hardware. Attractive celluloid sparkle finish. Complete with deluxe flat base chrome stand, 10" cymbal, sticks, and brushes. Imported. Shpg. wt., 10 1/2 lbs.

13 R 87089W Net 27.95



13⁵⁰

32⁹⁵

27⁹⁵

- Complete with Stand, 10" Cymbal, Brushes, Sticks

ONLY **199⁹⁵** No Money Down*

PROFESSIONAL 15-PC. DRUM OUTFIT

- 9-Ply Construction Thru-Out
- Double Lug—Double Tension
- Chrome Plated Triple Flange Hoops

Deluxe, professional quality drum outfit with all the most wanted accessories. Meets the demand for quality and sound in every way. Each drum has completely adjustable tension rods for quick and easy tuning. Set consists of 14"x20" Bass Drum with 8 separate beaver-tail tension lugs, spurs, cymbal holder, cassette tom tom, 8"x14" Snare Drum, 8-tension speedy throw-off and internal muffler. 16"x16" Floor Tom Tom—8-tension with internal muffler. One 8"x12" and one 9"x13" Tom Tom—6-tension with muffler. Drums have coated plastic heads, celluloid covered for bright finish. Includes deluxe, flat-base snare stand, floor cymbal stand, and a super deluxe, direct-action Hi-Hat stand with fast action pedal. Set also contains a 16" Ride Cymbal, a pair of 14" Hi-Hat Cymbals, and deluxe bass drum pedal, drum sticks and brushes, cowbell, wood block and holder. Imported. Shpg. wt., 91 lbs.

13 R 66231WX Bright Red Net 199.95
13 R 66269WX Bright Blue Net 195.95
5-Piece Vinyl Drum Cover Case 13 R 66277W Shpg. wt., 10 lbs. Net 34.95

*See Page 22 for Full Credit Details on Easy Pay Plan

SOLID BODY ELECTRIC GUITARS

SAVE UP TO \$16⁰⁰ when you buy an outfit

ONLY
39⁹⁵
2-Pick-Up

**(A) 2 PICK-UP CUTAWAY
SOLID BODY ELECTRIC GUITAR**

- With Tremolo Tailpiece
- Steel Reinforced Adjustable Neck
- Volume and Tone Controls

Electric solid body, double-cutaway guitar. Steel reinforced neck features fast fingering over rosewood fingerboard. 23 frets with 9 white inlaid position markers. Adjustable steel bridge guides strings over dual pickups, each with individual on/off switch and volume control; master tone control provided. Compression tremolo, mounted to slimline body, has large flat bar for convenient use. Black pickguard is beautifully inlaid with gold floral patterns. Lacquered, highly polished, body is finished in radiant yellow sunburst effect. 40½x13½x2" D. Imported.

13 R 24656W Shpg. wt., 8½ lbs. Net 39.95

Sturdy Lined Case for Above. Net 9.95

13 R 13261W Shpg. wt., 4¾ lbs. Net 9.95

**(B) DELUXE 4 PICK-UP SOLID BODY
ELECTRIC GUITAR**

- With Tremolo Tailpiece
- Modern, Double Cutaway Design
- Adjustable, Steel Reinforced Neck

Thin body, double cutaway design features a fast, slimline neck. An instrument with great flair that can be played with pride by all guitarists. Features a steel reinforced adjustable neck with variable string guides and an adjustable metal bridge. Includes tremolo with a large, flat bar for convenient use. Has attractive oval rosewood fingerboard and 20 new flat-type frets providing faster fingering. Separate on/off switch and volume control for each pick-up plus a master tone control. Richly designed, ebony pick guard with gold floral inlay. 9 mother-of-pearl inlaid position markers. Highly polished green sunburst finish. Imported. Shpg. wt., 9 lbs.

13 R 24599W Net 49.95

Sturdy lined case for above. Shpg. wt., 4¾ lbs.

13 R 13261W Net 9.95

ONLY
49⁹⁵
4 Pick-Up



MONEY SAVING GUITAR OUTFITS

All outfits include a guitar, guitar case, amplifier, remote foot switch, plus neck strap, pickup cord, extra set of strings, pitch pipe, 6 picks, instruction book and record.

2 Pick-Up Solid Body Guitar Outfit

Includes: 13-24656W Guitar, 99-92074W 20 watt Reverb/Tremolo Amplifier (see page 171), plus all of above accessories. Shpg. wt., 33 lbs.

13 R 91218WXM Net 99.95

4 Pick-Up Solid Body Guitar Outfit

Includes: 13-24599W Guitar, 99-92074W 20 watt Reverb/Tremolo Amplifier (see page 171), plus all of above accessories. Shpg. wt., 35½ lbs.

13 R 91226WXM Net 109.95

Deluxe 4 Pick-Up Solid Body Guitar Outfit Includes: 13-24599W Guitar, 40 watt Reverb/Tremolo amplifier (see page 170), plus all of above accessories. Shpg. wt., 48½ lbs.

13 R 91234WXM Net 134.95

HOLLOW BODY

ELECTRIC GUITAR OUTFIT with 5-WATT AMPLIFIER

66⁸⁸

No Money
Down*

Save
over
8.00

From Individual
Catalog Prices



- Includes: Guitar, 5-Watt Amplifier, Carry Case, Extra Strings, Neck Strap with Shoulder Pad

Big sounding outfit! Features an ultra-slim semi-acoustic, hollow body guitar; 2 powerful magnetic pickups with individual switches for each pickup plus adjustable sensitivity controls for each string. Tremolo tailpiece, adjustable neck and compensating bridge, plus individual Volume/Tone controls. Rosewood fingerboard has inlaid pearl position markers; body is lustrous sunburst acrylic finish, 5-watt amplifier features built-in 6" heavy-duty speaker, 2 instrument inputs, On/Off and Volume/Tone controls; in sturdy vinyl covered wood cabinet. (See Page 172 for complete description). Size: Guitar, 40L x 13 $\frac{3}{4}$ W x 1 $\frac{3}{4}$ "D. Amp, 16H x 14W x 6"D. Imported. Shpg. wt., 23 lbs.

13 R 91259 WM..... Net 66.88
Guitar Outfit less amplifier. Shpg. wt., 11 lbs.
13 R 24631W..... Net 49.95

*See Page 22 for Full Credit Details on Easy Pay Plan

DELUXE SOLID AND HOLLOW BODY

ELECTRIC GUITARS


A DELUXE 2 PICK-UP "SLIMLINE" HOLLOW BODY ELECTRIC GUITAR

- "Laminated"—Steel Reinforced Adjustable Neck
- Individual Volume and Tone Controls
- Custom Designed Tremolo Tailpiece

Custom crafted, professional quality instrument! Features 21 fret, oval rosewood fingerboard with mother-of-pearl inlaid position markers and triple bound edges. Has two ultra-sensitive, hum-free pickups with individual pole adjustments, height adjustments and individual volume and tone controls. 3-position lever switch selects bridge pickup for solo, and forward pickup for rhythm work; or, permits use of both pickups simultaneously. Large handsome celluloid bound body is shaped and contoured for optimum sound response. Beautifully flamed high-gloss polyester finish. 16W x 44H x 2"D. Imported. 13 R 66020W Shpg. wt., 15 lbs. Net 79.95
Sturdy Case with Plush Lining For Above. 13 R 66038W Shpg. wt., 7 $\frac{3}{4}$ lbs. Net 12.95

ONLY
79⁹⁵
EACH

No Money
Down*



B NEW! "CUSTOM" SOLID-BODY ELECTRIC GUITAR

- Black Acrylic Finished Body

A perfect guitar designed for the young professional. Features a finely crafted mahogany solid body cutaway with an ultra-slim fully adjustable steel reinforced neck. Powerful twin pickups with incredible tonal response and a 6-way adjustable bridge let you produce throbbing lows and shimmering highs. 3-position toggle switch and separate tone and volume controls for each pickup. Rosewood finger board and 8 large pearlized

- Hardware Finished in Rich Gold Tone

position markers. Finished in show-stopping highly polished acrylic ebony color with rich gold tone pickups, machines, tailpiece and bridge. Large handsome body has celluloid bound neck and top. Size: 40L x 12 $\frac{3}{4}$ W x 1 $\frac{3}{4}$ "D. Imported. Shpg. wt., 11 lbs. 13 R 24694W..... Net 79.95

STURDY LINED CASE FOR ABOVE. 13 R 24705W Shpg. wt., 7 lbs. Net 9.95

SOLID & HOLLOW BODY

ELECTRIC BASSES

A VIOLIN SHAPED 2-PICK-UP ELECTRIC BASS

Classic violin shape produces brilliant electric bass tones, with the rich accent of an acoustic guitar. Three position switch accentuates the highs, lows and mid-range. Delicately arched hollow body bound in decorative celluloid trim, features: a 4-piece laminated, fully adjustable, steel reinforced neck; bound rosewood fingerboard with heavy nickel silver frets and inlaid position markers; chrome plated trapeze tailpiece; adjustable bridge; fully enclosed tuning machines; sparkling sunburst finish with a celluloid pick guard, and mahogany finger rest, cord. 44 $\frac{1}{2}$ x13x2 $\frac{1}{4}$ ". Imported.

13 R 24532W Shpg. wt., 8 lbs. Net 59.95

13 R 24540W Sturdy case for above. Shpg. wt., 7 $\frac{1}{2}$ lbs. Net 9.95

B 2 PICK-UP SOLID BODY ELECTRIC BASS

Long neck, slimline electric bass guitar of selected woods for excellent speed and response and easy fingering. Hand rubbed, shaded sunburst body finished in durable acrylic lacquer. 46" steel reinforced adjustable neck has celluloid bound oval rosewood fingerboard, 20 frets, 8 pearl inlaid position markers, and large machines for fast accurate tuning. Sensitive pick-ups have adjustable pole pieces for precise balancing of individual strings. Two, feather-touch rocker standby switches for instant control of each pick-up. Includes separate volume and tone controls and compensation adjustable bridge. With cord. Imported. Size: 46Lx13 $\frac{1}{2}$ Wx1"D.

13 R 24615W Shpg. wt., 9 $\frac{1}{4}$ lbs. Net 49.95

Sturdy Case for above. Shpg. wt., 5 $\frac{3}{4}$ lbs.

13 R 24623W Net 9.95

C DELUXE 2 PICK-UP HOLLOW BODY ELECTRIC BASS

Produces deep bass tones with brilliant cadence! Features adjustable muting control; 2 perfectly balanced adjustable pickups; individual tone and volume controls for each pick-up; 3 position toggle switch for solo/rhythm; fully adjustable compensating bridge; individual chrome covered precision machines; and custom designed tailpiece. Hard maple, steel reinforced adjustable neck with a 20 fret, oval rosewood fingerboard. 9 mother-of-pearl inlaid position blocks, side position markers and triple bound edges. The beautiful, flame grained thin-line, double cutaway hardwood body is celluloid bound and protected by a pick guard. With cord. Imported. Size: 46Hx16Wx2"D. Shpg. wt., 13 lbs.

13 R 66087W Net 89.95

Sturdy case with plush lining for above.

13 R 66095W Shpg. wt., 11 lbs. Net 13.95

VIOLIN SHAPED
2 PICK-UP BASS

59⁹⁵

2 PICK-UP
SOLID BODY
BASS

49⁹⁵

Save

UP TO
30⁰⁰

ON COMPLETE OUTFITS

DELUXE 2 PICK-UP
HOLLOW BODY
ELECTRIC BASS

89⁹⁵

COMPLETE ELECTRIC BASS OUTFITS

SAVE UP TO \$30.00 from Individual Catalog Prices

Each Electric Bass Guitar Outfit consists of an Electric Bass, Amplifier, Case, Neck Strap, Pick-up Cord plus "Modern Electric Bass Guitar Method" book. See Page 171 for Amplifiers.

Outfit No.	Elec. Bass	Amplifier	Watts	Shpg. Wt.	Net
13 R 91192WXM	13 R 24615W	13 R 01548WX	60	62 $\frac{3}{4}$ lbs.	154.95
13 R 91135WXM	13 R 24532W	13 R 01548WX	60	63 lbs.	164.95
13 R 91242WXM	13 R 66087W	13 R 01654WX	170	113 $\frac{3}{4}$ lbs.	275.95

RICH TONE ACOUSTIC GUITARS



**Classic
Guitars**

AS LOW AS

A 29⁹⁵

**Folk
Guitars**

Only **B 69⁹⁵** Only **C 34⁹⁵**



(A) CONCERT SIZE CLASSIC GUITAR

Magnificent sounding classical guitar! Has 19 fret fingerboard for wide scaling. Sound hole features a beautifully engraved mosaic decoration. Attractive Spanish styled bridge is an authentic classical design. In addition, this concert size classical guitar has 6 precision tuning machines with plastic roller, slotted headpiece, and a steel reinforced neck. Back and sides are finished in highly polished mahogany—top is polished natural finish. Size 39¼L x 14¾W x 3¾"D. Nylon strings. Imported.

13 R 66137W Shpg. wt., 8 lbs. Net 29.95
Sturdy Case for Above Guitar
13 R 52913W Shpg. wt., 4 lbs. Net 9.95

(A) GRAND CONCERT SIZE CLASSIC GUITAR

Deluxe version of above. Size: 39½L x 14¾W x 3¾"D. 13 R 52905W Shpg. wt., 10 lbs. Imported. Net 34.95
Sturdy Case for Above Guitar
13 R 52913W Shpg. wt., 4 lbs. Net 9.95

(B) JUMBO COUNTRY AND WESTERN GUITAR

Rich deep bass and clear treble tones are built-in this jumbo size model. Made of carefully selected woods—resonant hand rubbed maple back and sides, and close grained, antique colored spruce top. Genuine "Nato" wood adjustable neck with celluloid bound rosewood fingerboard; inlaid pearl position markers; 20 nickel silver frets. Rosewood adjustable bridge, black pickguard with flowered design, individual tuning pegs. 40¾L x 16½W x 4¼"D. Steel Strings. Imported. Shpg. wt., 10 lbs.

13 R 52814W No Money Down* Net 69.95
13 R 52830WX Case for above guitars. Shpg. wt., 9¼ lbs. Net 12.95

(C) GRAND CONCERT SIZE FOLK GUITAR

Grand concert size folk guitar is made of beautiful, carefully selected natural white spruce top, mahogany sides, and highly polished light mahogany color back. Features adjustable thin neck reinforced double truss rod; all white celluloid-bound edges of neck, top, and back of body; mosaic inlay around soundhole; moderate celluloid-guard-plate; rosewood pin bridge and solid oval rosewood fingerboard. 6 inlaid square type larger position markers for easier finger placement. Size: 39¼L x 14¾W x 3¾"D. Imported.

13 R 24664W Shpg. wt., 6 lbs. No Money Down* Net 34.95
13 R 24672W Case for Above Guitar, Shpg. wt., 7¼ lbs. Net 9.95

7 Piece 'Beginners Outfit'

Complete Outfit
Only **24⁹⁵**



- Everything You Need Including
Beginners Record Course and Book

Nicely finished with open headpiece and pinless bridge. Can be used either as nylon string classic or steel string Folk guitar. Steel reinforced neck. Guitar has hardwood body with blonde top. Highly polished finish with design around sound hole. Comes complete with nylon and extra set of steel strings, Vinyl zippered carrying bag, neck cord, pick, instruction book and record course. Size: 36¼x13Wx3½"D. Imported. Shpg. wt., 6 lbs.

13 R 52921W Net 24.95



LAFAYETTE Deluxe Musical

140 Watt Solid State "Piggy Back" Amplifier with Reverb-Tremolo, 3-Speakers, 2-Channels

- For Guitar, Organ and Vocal Use
- Hammond Reverberation Unit
- Variable Tremolo
- 2-12" Special Design Heavy Duty Speakers plus High-Frequency Horn
- Extruded Aluminum Panel

Piggy back amplifier with 14 silicon transistors plus silicon rectifier and heavy-duty power and driver transformers provides 140 watts peak music power! Closed back speaker designed to project low end response. Two 12" Heavy-Duty speakers plus a high frequency horn results in tremendous reproduction of brilliant highs, deep lows and solid midrange. Excellent for lead or rhythm guitars. Two channels with high and low level inputs. Separate volume and tone controls for each channel. Depth control for reverb. Intensity control for tremolo circuit. Footswitch jacks for reverb and tremolo activation. Pilot light, fuse, and on-off switch. Sturdy wood cabinets covered in black textured scuff-resistant vinyl with metal corner protectors and heavy duty handles. Amplifier size: 7H x 22½L x 10¾"D. Speaker cabinet size: 27H x 23½ x 11½"D. For 117 VAC 50/60 Hz.

13 R 01647WX Shpg. wt., 68 lbs. Net 199.95
 Dual Foot Switch for Remote Control of Tremolo and Reverb.
 13 R 01506 Shpg. wt., 1½ lbs. Net 4.95
 Dolly for above Amplifier.
 13 R 01498W Wt. 6½ lbs. Net 11.95

140
WATT

199⁹⁵

No Money Down



75
WATT

129⁹⁵


No Money Down*

75 Watt Solid-State "Reverb-Tremolo" Twin Speaker Amplifier

- 2-10" Heavy Duty Special Design Speakers
- Pulsating "Tremolo" For "Go-Go" Effect
- Hammond "Reverb" Unit For Echo-Like Effect

Get faithful reproduction of every note. Excellent for guitar, organ and vocal use. Has special heavy-duty speakers. All Solid State 10 transistor circuitry provides excellent performance. 3 instrument inputs for guitar, microphone, and organ. Powerful 75 watt peak music power amplifier. Has a volume and 2 tone controls. Features remote control foot switch jacks for colorful tremolo and reverb operation plus 2 tremolo controls and 2 reverb controls; on/off switch; pilot light and carrying handle. Sturdy wood case covered in shimmering black vinyl. Size: 25"Hx18¾"Wx8½"D. Imported. For 117 Volts, 50/60 Hz. AC. Shpg. wt., 32 lbs.

13 R 01696W Net 129.95
 Dual Foot Switch for Remote Control of Tremolo and Reverb.
 13 R 01506 Shpg. wt., 1½ lbs. Net 4.95



40
WATT

79⁹⁵

No Money Down*

40 Watt Solid-State "Reverb-Tremolo" Amplifier

- "Reverb" For Echo-Like Effect
- Tremolo For Pulsating Sound
- 12" Special Design Speaker
- 3-Instrument Inputs
- Easy Reach "Slanted" Front Panel

Features a built-in heavy duty 12" speaker for clean reproduction of every musical note. Excellent for guitar, microphone, and accordion use. Three instrument inputs. Five controls: two for volume and tone; two for speed and intensity of tremolo, and one for "reverb" depth control. Footswitch jacks for remote control of tremolo and reverb. 40 watt peak, music power AC amplifier chassis utilizes 5 dual tubes equivalent to an 8 tube circuit, plus solid state rectifiers for reliable operation. Also has pilot light, on/off switch and fuse. Sturdy wood cabinet covered in black vinyl. Size: 22H x 17W x 8½"D. For 117 VAC 50-60 Hz.

13 R 01662W Shpg. wt., 29¼ lbs. Net 79.95
 Dual Foot Switch for remote control of tremolo and reverb.
 13 R 01506 Shpg. wt., 1½ lbs. Net 4.95

Instrument Amplifiers



60-Watt Solid State "Piggy Back" Bass Amplifier

- Heavy Duty 15" Special Design Speaker
- For Use With Electric Bass, Regular Guitar, Accordion and Combo-Organ
- 2-Instrument Inputs

Gives full bass and vibrant sound with a minimum of distortion. Powerful 60 watt peak music power amplifier is ideal for use with electric bass or standard guitars, and combo organs. All solid state circuitry (5-transistors and 4-silicon rectifiers) provides excellent sound. Features a specially designed 15" speaker with a wide range response. High and low gain inputs separate volume and tone controls allow complete operating flexibility. Has On-Off switch plus pilot light and fuse. Two units; speaker and amplifier in matching black vinyl covered wood enclosures with handles. Size: Amp. 4¾H x 14W x 8"D; Speaker, 22¾H x 18W x 11"D. For 117V 50/60 Hz AC.

13 R 01548WX Shpg. wt., 47 lbs. Net 109.95

Big Bass Sound

60
WATT

109⁹⁵

No Money Down*

170
WATT

199⁹⁵

No Money Down*



170-Watt "Piggy Back" Bass Amplifier

- Two Powerful 12" Special Design Heavy-Duty Speakers With 20 Ounce Alnico Magnets
- Projects "Big Bass Sound"
- Excellent For Use With Bass, Accordion and Combo-Organ
- "Easy Reach" Extruded Aluminum Control Panel

A real powerhouse! Fabulous, full bass sound with a minimum of distortion. Two powerful 12" speakers have a wide-range response. The amplifier features three inputs with deep and sharp selector switches, treble, bass, and volume controls and neon pilot lamps. Fuse and 3-position switch for power off/standby/on. Super 170-watt peak music power chassis uses 5 tubes, 2 dual purpose tubes for 7 tube performance, and all solid state rectifier power supply circuit. Heavy duty transformers provide greater output. Two units: Rugged acoustic wood amplifier/speaker cabinet, and a "piggy back" amplifier which sits neatly on top of speaker cabinet. Cabinets have attractive gray and silver acoustical cloth. Ribbed vinyl carrying handle. Speaker cabinet size: 30Hx22½Wx13½"D; Amplifier cabinet size: 9¼Hx22½Wx11"D. For 117VAC 50-60 Hz.

13 R 01654WX Shpg. wt., 88¼ lbs. Net 199.95

Additional Speaker System Unit (Less Amplifier)

13 R 01720WX Shpg. wt., 60 lbs. Net 99.95

20 Watt Solid-State "Tremolo-Reverb" Amplifier

- "Reverb" For Echo-Like Effect
- Tremolo For Pulsating Sound
- Tremolo Speed/Depth Reverb Controls
- Heavy-Duty 10" Speaker

Impressive, 20-watt solid state peak music power reverb and tremolo amplifier with self-contained 10" heavy-duty speaker. Slanted, front-mounted control panel features "easy-to-reach" controls for Volume, Tone, Reverb, Tremolo speed, Tremolo depth; two instrument inputs; reverb and tremolo foot switch input jack; bright-glow pilot light. Housed in an attractive sturdy vinyl covered wood cabinet with carry handle and grill cloth. Size: 19"H x 15"W x 6½"D. For 117V, 60 Hz AC. Imported. Shpg. wt., 16 lbs.

99 R 92074W Net 49.95

Dual Foot Switch for remote control of tremolo and reverb. Shpg. wt., 1½ lbs.

13 R 01506 Net 4.95

20
WATT

49⁹⁵

No Money Down*



Musical Instrument Amplifiers-Reverb Units



5 WATT SOLID-STATE STUDENT AMPLIFIER **24⁹⁵**

- Three Instrument Inputs
- Volume and Tone Controls

Great for the student or beginner! Features rugged, solid state circuitry for cool, instantaneous amplification and trouble-free operation. Provides 5-watts peak music power into a heavy-duty specially designed 6" speaker with excellent clarity and tonal response. Smartly styled control panel has on/off, Volume control and Tone control; and three instrument inputs. Attractively designed sturdy wood construction covered in water repellent, scuff-resistant black vinyl. With carrying handle. Size: 16Hx14Wx6"D. For 117V., 60 Hz AC operation. Shpg. wt., 13 lbs.

13 R 01704W Net 24.95



10 WATT SOLID-STATE 'TREMLO' AMPLIFIER **36⁹⁵**

- Tremolo Speed And Intensity Controls
- 3 Inputs—Foot Switch Jacks

Functional, attractive, all-transistor tremolo amplifier. Delivers 10-watts peak music power to a specially designed 8" speaker for full instrument range. Front mounted control panel has controls for Tone, Volume, Tremolo speed, Tremolo Intensity; three instrument inputs; tremolo foot switch input jack; and pilot light. Housed in a sturdy wood cabinet with jet black vinyl covering and harmonizing grill. Carrying handle. Size: 19Hx16Wx8 1/2"D. For 117 V., 60 Hz AC. Wt., 19 lbs. 13 R 01712W Net 36.95

Foot Switch For Remote Control of Tremolo. 13 R 01514 Shpg. wt., 1/2 lb. Net 2.99



12 WATT SOLID-STATE BASS AMPLIFIER **44⁹⁵**

- 10" Heavy Duty Speaker
- 3 Inputs—Volume/Tone Controls

Excellent choice for the student. 12-watt peak music power output. Rugged dependability with 10" heavy duty bass speaker; front mounted volume and tone controls for easy access. Inputs for three instruments! Solid state circuitry for instantaneous response and trouble-free operation. Pilot light. Cabinet is sturdily constructed of wood with a scuff-resistant, black vinyl covering. Handsome matching grill. Carrying handle; rubber feet. Size: 16"Hx19"Wx8"D. For 117V., 60 Hz AC operation. Shpg. wt., 17 lbs. 13 R 24649W No Money Down* Net 44.95

LAFAYETTE SOLID STATE "ECHOVERB" REVERBERATION UNIT



Only
19⁹⁵

- "Add-on" Reverb Unit for any Musical Instrument Amplifier or P.A. System
- Inputs for Mike and Instruments

Simulates the full sound top artists get! Compact, lightweight, transistorized reverberation unit creates a new dimension in audibility to overcome dull, flat ordinary sound. Can be used with any instrument amplifier, or P.A. system. Minutes to connect, the "Echo-Verb" may be used for sound effects. Has inputs for mike and/or instrument—plus a foot switch input to cut reverberation in or out from a remote location, pilot light and a reverb mix control that lets you select whatever intensity of reverberation you desire. With reverb mix control in the "Off" position, standard sound will be heard from the amplifier. With on/off switch. For 117 v., 50/60 Hz AC. Size 3 3/4"H x 11 1/2"W x 6 1/2"D. Imported. Shpg. wt., 4 lbs. 99 R 92025W Net 19.95

Foot switch for Remote Control of "Echo-Verb." Shpg. wt., 1/2 lb. 13 R 01514 Net 2.99

LAFAYETTE TWO-CHANNEL "ECHO-VERB 11" REVERBERATION UNIT



Only
29⁹⁵

- 4 Inputs Mix and Fade
- Master Reverb Intensity Control
- Separate Volume Controls For Each Channel

"Echo-Verb II" offers full, dynamic reverberation, comparable to professional sound, in a lightweight, transistorized compact unit. Has two inputs for microphones and two inputs for instruments, each with individual volume controls to permit mixing and fading. A separate, full-range Reverb Control adjusts from zero to maximum intensity, assuring you a desired level of reverberation. The "Echo-Verb II" also features a pilot light and a foot switch jack which allows you to cut reverberation in or out from anywhere in your room. Can be easily connected to an instrument amplifier, P.A. amplifier, or Hi-Fi amplifier/receiver. Simulated black pebble-grain leather enclosure with leather strap. Size: 3 3/4"H x 11 1/2"W x 6 1/2"D. For 117 VAC 50-60 Hz. Imported. Shpg. wt., 4 lbs. 99 R 92116W Net 29.95

Foot Switch for Remote Control of "Echo-Verb II". Shpg. wt., 1/2 lb. 13 R 01514 Net 2.99

LAFAYETTE SOLID-STATE 120-WATT PA and MUSICAL INSTRUMENT SOUND SYSTEM

A two piece portable sound system that is easy to handle and extremely versatile. Features a mono-stereo mixer control center and a separate solid-state amplifier-speaker system. Mixer can handle up to 4 amplifier-speaker (120 watts each) giving up to 480 watts of power and all the flexibility you will ever need. Amplifies voices as well as instruments.

Master Control Center Features:

- 4 Channels—8 Inputs
- Each Channel Has 2 Inputs (High and Low) with Individual Volume, Bass and Treble Controls
- 2-Slider-Type Master Volume Controls for Mono or Stereo
- Two 3" Illuminated VU Meters to Monitor Preamp or Power Amp with Selector Switch
- Solid State—All Silicon Transistors
- Drive Capacity for 4 Amplifier-Speaker Systems
- Control Center is Built Into A Carrying Case with Detachable Lid

Only
299⁹⁵
No Money Down*

Amplifier Speaker System Features:

- Solid State 120-Watt Power Amplifier with Four 10" Jensen Speakers

This unique portable sound system has exceptional performance for use with many instruments and voices. Control center features all of the above plus on-off switch, pilot light, fuse, 2 aux. AC receptacles and output connector with on-off switch for echo or reverb equipment. Amplifier-speaker systems and control center may be stacked. May be used for stereo with second amplifier-speaker system. Amplifier-speaker system size: 27Hx23W x11½"D. Control center size: 9Hx21Wx8"D. Sturdy black vinyl covered wood cabinets with handles. With cords and plugs. For 117VAC 60 Hz.

13 R 90756WXM Shpg. wt., 78½ lbs. Net 299.95

"Add On" 120 Watt Amplifier-Speaker System. Shpg. wt., 53½ lbs.

13 R 01597WX Net 149.95

Heavy Duty Aluminum Dolly for above system. Shpg. wt., 7 lbs.

13 R 01605W Net 21.95



GRAPHIC EQUALIZER AND REVERBERATION UNIT

- Corrects Acoustic Inadequacies Wherever you are Performing
- Balance your sound by adding or subtracting Highs or Lows

Every Group Needs An Audio Spectrum Equalizer—Easily Connects to any Amplifier. Eliminate "hisses," dead spots, flat spots, and acoustic feed back howling from your amplifier. Add bottom to a voice or instrument, or eliminate bottom and add highs. Convert your guitar or Bass amplifier to an acceptable P.A. amplifier. Seven individually calibrated slide controls for precise frequency selection from 100 Hz. to 7000 Hz., covers the spectrum for most voices or instruments. Features Hammond Reverberation unit with depth control which renders limitless color to your sound. Has on-off switch, volume and tone control, pilot light. Attractive simulated leather grained case with chrome trim. Vinyl cover included. Size: 19"W x 7¾"H x 7¾"D. For 117 volts 50/60 Hz. AC. Imported. Wt., 10 lbs. 13 R 66533W No Money Down* Net 169.95



169⁹⁵

LAFAYETTE ENTERTAINER MICROPHONES & STAND

A CARDIOID DYNAMIC MIKE

A superb dynamic microphone designed for applications where location of performer in relation to speakers causes feedback and reverb. Highly directional cardioid pattern. Dual impedance: 50K or 600 ohms, selectable by switch. Response: 100-10,000 Hz. Mylar diaphragm. On/off switch. Modern design, satin chrome finished die-cast case. For hand-held or stand use. Size: 8¼Lx1½"D head. With swivel stand adapter and 20 ft. detachable cord with phone plug at other end. Imported. Shpg. wt., 3 lbs.

99 R 46294 Net 12.95

A



12⁹⁵



20 ft. Cable with Phone Plug

B DELUXE BALL DYNAMIC MIKE

Modern design features dual impedance—High 50K ohms, or low 250 ohms. Omni-directional, 100-10,000 Hz. Has on/off switch. Ball screen insures against "pop" and wind blast. Die-cast, finished in satin aluminum. Size: 6¼" long, max. diam. of ball 2½". Complete with detachable 20 ft. cable and phone plug. Black metal desk stand and adapter for any 5/8"-27 floor stand. Imported.

99 R 46203 Shpg. wt., Net 16.95


B

16⁹⁵



C ATLAS MIKE FLOOR STAND

Model MS-10C Mike stand featuring "Full-Grip" clutch mechanism for fast quiet adjustments. Functionally designed base assures maximum stability plus 3 "anti-tip" points. Full chrome plated tube assembly. Terminates in a ¾"-27 thread. Base dia. 10", finished in gray shrivel. Height adj. 35 to 63". Shpg. wt., 10¾ lbs. 44 R 10031W Net 8.91



MUSICAL INSTRUMENT AUTOMATIC RHYTHMER



129⁹⁵

No Money
Down*

• 12 Exciting Rhythms

• A Versatile Electronic Instrument Producing a Wide Variety of Rhythms For Accompaniment


Solid-state portable rhythm. Ideal for teachers to produce a wide variety of rhythms and a steady beat for the students to follow. For students—a complete rhythm section to play along with. For single performers—bring along your own rhythm section! Works with any amplifier to produce 12 distinctive rhythm selections plus an infinite variety of accompaniments by mixing two or more rhythms. Variable tempo control can be set for accompaniment to a Waltz, Fox Trot, Rhumba, Samba, Mambo, Slow Rock, Fast Rock, Swing, Bossa Nova, Cha-Cha, Tango, or a March. Each rhythm is

made up of a variety of percussion sounds: Bass Drum, Snare Drum, High Hat, Cow Bell, Bass Conga, Tenor Conga, and Cymbal. Additional features include: Master Volume and On/Off control, Tone control, On/Off rocker switch for instant control or rhythmmer plus On/Off Remote Control Foot switch, pilot light and 12 pushbutton rhythm selectors. Circuitry: 32 transistors, 95 diodes. For 100-117 VAC. 50/60 Hz. Handsomely styled walnut finish case with brushed aluminum panel. Size: 17 3/4 x 4 1/4 x 9 1/2" D. Shpg. wt., 15 1/4 lbs. 13 R 24557W

Net 129.95

AUTOMATIC RHYTHMER

"SUPER" AUTOMATIC RHYTHMER



Only

99⁹⁵

No Money Down

• 10 Exciting Rhythms

- Complete with brackets for under keyboard mounting
- Mix sounds—Set tempos

A marvel of the micro transistor age. A compact electronic automatic rhythmmer, computer designed, to produce a selection of 10 exciting rhythms. 5 dual selector switches render distinctive popular rhythms: waltz, mambo, bossa-nova, rock 1, rock 2, fox trot, cha-cha, latin beat, polka, and ballad. Gives fantastic reproduction of actual rhythm instruments including brushes, claves, conga drums, snare drum, bass drum, and maracas. The compact control panel contains separate tempo and volume controls, on/off switch, down beat start switch, pilot light, fuse, and output connecting jack. Panel is designed to be operated from either the top of organ or under the keyboard. Brackets are provided for under keyboard mounting. Cabinet of walnut wood veneer. For 117 VAC 50/60 Hz. Size: 3H x 9W x 9 1/2" D. Shpg. wt., 5 lbs. 13 R 66541W

Net 99.95

169⁹⁵

No Money
Down*



- Produces background rhythms electronically

- Nineteen Automatic Rhythms
- Fox Trot/Swing Section with 36 Variations
- For teachers, students, performers

Become a one-man combo with this fully transistorized instrument—you'll never miss a beat! Provides nineteen computer programmed rhythms plus a special Fox Trot/Swing section with thirty-six variations. By mixing two or more rhythms, additional sounds can be added to create a myriad of accompaniments. The "Super" Automatic Rhythmmer gives you "true-to-life" sound, tonal variations and accurate tempo. Actual musical instrument sounds created include: Bass Drum, Large and Small Conga, Claves, Cowbell, Maracas, Snare Drum and Cymbal. Computer programmed rhythms include: Rock 1-2-3-4; Ballad; Western; Bossa Nova 1-2; Tango; Rhumba; Mambo; Cha-Cha; Samba; Beguine; Meringue; Waltz/Viennese Waltz; and thirty-six variations of Fox Trot/Swing. Controls: Tempo; Volume On/Off Switch; Pilot Light; Tone Downbeat Start Switch; Fuse; High-Low Impedance Outputs; and Foot Control. Vinyl carrying bag. For 117 VAC 50/60 Hz. Size: 4 1/2 H x 9 1/2 W x 14" L. Imported. 13 R 66509W Shpg. wt., 10 1/4 lbs.

Net 169.95

ACCESSORIES

ROTO-VIBE



79⁹⁵

A NEW DIMENSION IN SOUND

Finally an electronic instrument that can truly simulate the rotating speaker effect through any musical instrument amplifier! Not only produces the Fast or Slow rotating effect but, by the use of the remote speed control pedal, can vary the speed at any rate you desire. Enables the player to produce the various modern effects which are being used on the stage, in the studio, and with theater organs. Can be used with any of the following instruments: organ, bass guitar, rhythm and lead guitar, electric piano, accordion, & other electronic band instruments. Plus: Voice for vocal effects now being used by the top recording groups around the country. Easily connects between instrument and amplifier. Foot pedal has cancel switch to instantly cancel effect being produced. Also features a rocker switch for selecting either the rotating speaker effect or a true vibrato effect. Other controls include Volume, Chorus/Vibrato, Intensity, On/Off power switch, fuse, pilot light, inputs for 2 instruments, and an output for the amplifier. Unit is AC operated, fully transistorized, and has a rugged metal construction. Compact, only 10" Wx6 1/2" Dx3" H. Can be placed in any conveniently reached location. Imported. Shpg. wt., 7 3/4 lbs.

13 R 66400 No Money Down*

PRODUCE THE ROTATING SPEAKER EFFECT AND VIBRATO WITH YOUR OWN AMPLIFIER — ELECTRONICALLY!



14⁹⁵



• Make your guitar or bass produce the harmony of several wind instruments!

Add more instruments to your small combo with the "Fuzz" Sound! Create a wide variety of synthesized tones such as those produced by a baritone, or bass saxophone. Battery powered, it easily connects between your guitar, or bass and the amplifier and is operated by an On/Off foot switch. Has two variable control knobs; one for regulating the "fuzz" effect and one for volume and intensity. A supplementary On/Off switch is combined with the volume control to conserve battery life. Fully transistorized, the unit is built for heavy duty use and operates on a single penlight battery. A rugged metal case protects inside circuitry. Overall size: 5 1/2" L x 3 1/2" W x 2 1/4" over. H. Imported. Shpg. wt., 1 3/4 lbs.

99 R 91993

Net 14.95

99 R 62580 Battery for above Net .10

Net 79.95

SUPER-DRIVE FOOT PEDAL CONTROL

37⁹⁵

- Use on P.A., Guitar, Bass, Organ, Electric Piano, Etc.
- Built-In Volume Control Pedal
- 6-Step Calibrated Input Boost
- Volume "Leakage" Control
- Full Die-Cast Casing
- 100 Times Amplification Factor



Fully solid state Super Drive offers a new dimension in completely controlled sound. Set your amplifier for the tonal range desired and let Super Drive provide the volume you wish to play. This eliminates amplifier playing at full volume. Contains a calibrated attenuator which provides 6 ranges of boost, plus a built-in volume pedal which varies the boost selected. Super Drive provides "clean distortion", rich harmonics and is capable of endless sustain. In addition, Super Drive also contains a volume "leakage" control which will adjust the volume pedal to hold a desired leakage when the control is in the off position. Battery powered. Frequency Range: 20-30 kHz. Size: 11 3/4" L x 5 1/4" W x 3 1/2" H. Shpg. wt., 5 3/4 lbs.

13 R 66517 No Money Down*

Net 37.95

99 R 60212 9V Battery

Net ea. .29

WAH WAH SOUND and VOLUME CONTROL

- Produce A Wide Variety of Special Sound Effects
- Use With Any Electric Guitar or Bass



Only 29⁹⁵

Produce the Wah-Wah effect of a trumpet or trombone with your guitar or bass, electronically. Add extra instruments to your combo by creating the effect of synthesized tones identical to those of a trombone or trumpet when muted by hand or derby. No reaching down for controls. Large, 8 1/2" footpedal gives you the full range of Wah-Wah sounds plus operates as a volume control by depressing a built-in switch under the heel of the footpedal. Input jack contains a switch to turn the unit on or off. Operates on 3 "C" cells. Fully transistorized, rugged construction. Imported. Size: 10x3 1/4x3".

13 R 66301 Shpg. wt., 3 1/4 lbs.

Net 29.95

99 R 62572 Battery for above, 3 required.

Net ea. .16

DELUXE AC SUPER FUZZ

39⁹⁵

No Money Down*



- Remote Control Foot Switch for Ease of Operation

AC operated super fuzz. No more batteries to fuss with as in conventional units. No more bending to adjust controls; control unit is separate from foot switch. Can be placed on amplifier or speaker within easy reach of the performer. Controls include Balance, Expander, and Tone control for a complete, controlled range of sustained fuzz effects. Electronically creates a harmonic producing sustained sound, now being used by top recording artists. Connects easily between your guitar or bass and the amplifier. Includes remote control foot switch. Long-lasting, solid-state circuitry combined with rugged metal construction. Size: 7 3/4" W x 5" D x 2" H. For 117 VAC, 60 Hz. Imported. Shpg. wt., 2 1/4 lbs.

13 R 66418

Net 39.95

SUPER FUZZ

Today's "In-Sound"

Only 27⁹⁵

- Super Fuzz Can Produce an Expanded Dimension in Sound
- Full Control of Fuzz Sustain Effects
- Heavy Metal Casting For Long Life and Appearance



Solid-state Super Fuzz provides a complete range of controlled new sustained harmonic effects. Produces the wild new In-Sound widely used by the top recording groups. Balance control enables perfect blend of fuzz and normal tones. Expander control provides unlimited range of sustained fuzz effects. Tone switch permits choice of conventional fuzz or new harmonic sustained effects. Master foot control switches instantly to normal guitar operation. Rugged die-cast metal construction. Size: 6 1/2 x 3 1/4". With cord and battery. Imported. Shpg. wt., 2 1/4 lbs.

13 R 66525

Net 27.95

99 R 60212 Battery for Above

Net .29

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 175

Musical Instruments & Accessories



**"VU-PITCH"
6 STRING
GUITAR TUNER**

- Lets Anyone Professionally Tune a Guitar in Minutes
- Great For the Beginner


5²⁵

Tune your guitar visually! The easy-to-use VU-Pitch tuner with 6 precision tuned reeds works on the principle of sympathetic vibration. When the guitar string is exactly tuned, the vibration from the string will be transmitted to the associated reed and cause it to visibly vibrate thereby indicating proper pitch. Great for the beginner, the VU-Pitch tuner, will tune your guitar rapidly and precisely in a professional manner. Shpg. wt., 6 oz.

13 R 48507

Net 5.25

SEIKO KEYWOUND METRONOME WITH BELL



12⁷⁵

Streamlined, pleasant tone keywound metronome gives both a visual and audible beat timing from 40 to 208 beats per minute. Highly popular among professional musicians, an invaluable aid while practicing or giving instruction. When set on 40 scale will operate over an hour. Brown case with clear front. Imported. Shpg. wt., 1 1/2 lbs.

13 R 66558

Net 12.75

Seth Thomas

ELECTRONIC METRONOME

Precision instrument, contains 2 complete electronically calibrated beat systems; audible and visual, 40 to 208 beats per minute. Single knob control, calibrated radial dial plus neon light. Wooden cabinet, operates on 115 V AC 60 Hz. Walnut. Shpg. wt., 3 1/4 lbs.

13 R 44530

Net 21.95



As Low As

10⁹⁵

Hohner Melodicas



- With Case, Spare Mouthpiece—Instructions

Student Melodica—Ideal for the beginner. 20 chromatic keys from middle C to G, give it a range adequate for most music.

13 R 66319 Shpg. wt., 1 1/2 lbs.

Net 10.95

Soprano Melodica—Similar to above. 25 keys from middle c.

13 R 66327 Shpg. wt., 1 1/2 lbs.

Net 13.95

Alto Melodica—Similar to above, 25 keys from low F.

13 R 66335 Shpg. wt., 1 3/4 lbs.

Net 14.95

PROFESSIONAL TUNABLE BONGOS

16⁹⁵

- Fast, Unobstructed Hand-Playing



Pure white perfect calfskin heads for best rhythm effect and authentic tone. Sparkling color finish. Sturdy construction full flanged counter loops with heavy chrome plated hardware. Four tuning-lugs on each bongo. Head sizes: 7 3/4" and 6 1/2". Overall 7" deep. Complete with Tuning Key. Imported. Shpg. wt., 3 lbs.

13 R 87042W

Net 16.95

HOT SHOT POWER BOX

11⁹⁵ • Provides A Dramatic Expansion Of Power From Your Amp



Solid-state preamplifier that will boost the output of any electric instrument (guitar, bass, organ, microphone, etc.). Has 2-transistor circuit that provides 1 volt of power from a 50 millivolt input. Has emitter follower output and provides a high degree of boost with full fidelity. Boosts the power of an amplifier. Instant change switch allows instant change from regular instrument output to pre-set boosted output. Plugs into input jack of music amplifier. Increases guitar sustain. Improved performance of all fuzz tones and wah-wah pedals. Shpg. wt., 1 lb.

13 R 24714

Net 11.95

9 Volt Btry. for above

99 R 60212

Net .29



Average Shpg. wt., 8 oz.

- | | | |
|--|-------------------|----------|
| (A) Guitar Strings. Set of 6, plated copper wire wound. | 13 R 22536 | Net 1.69 |
| (A) Nylon Classic Guitar Strings. Set of 6. | 13 R 22544 | Net 1.69 |
| (A) Electric Guitar Strings. Flat wound, set of 6. | 13 R 22528 | Net 2.39 |
| (A) Deluxe Electric Guitar Strings. Gibson, flat wound hi-fi strings. High quality. Set of 6. | 13 R 52871 | Net 4.95 |
| (B) Guitar Picks—6 Flat, 2 Thumb | 13 R 22569 | Net .59 |
| (C) Adjustable Foam Padded Guitar Strap. | 13 R 22502 | Net 1.69 |
| (D) Guitar Pitch Pipe | 13 R 22510 | Net 1.69 |
| (E) Retractable Guitar Cords with Plugs | 13 R 52889 10 Ft. | Net 1.59 |
| | 13 R 52897 20 Ft. | Net 2.29 |
| Deluxe 20 ft. Noiseless Coiled Cord. Superior shielding minimizing feedback. | 13 R 65866 | Net 3.95 |
| (F) Deluxe Adjustable Bright Sparkle Vinyl Neck Strap for Guitar. Brass Plated Buckle. | 13 R 22585 | Net 3.19 |
| (G) Deluxe Adjustable Embroidered Hootenanny Neck Strap, colorful fabric and leather, brass plated buckle. | 13 R 88016 | Net 2.49 |

4 PIECE GUITAR ACCESSORY KIT



An ideal 4 piece set for the beginner—Consists of: 1 set of (6) Flatwound Guitar strings; guitar pitchpipe; adjustable foam padded guitar neck strap and 8 guitar picks—6 flat and two thumb picks.

13 R 22577 Shpg. wt. 1 lb. Net 4.95

GUITAR SELF-INSTRUCTOR FOR THE BEGINNER

- Book And Record

Book and instruction record for the beginner. Chord sounds and pictures plus "strum" along favorites. Shpg. wt., 6 oz.

12 R 67079

Net 1.50



SMITH'S MODERN ELECTRIC BASS BOOK

Authoritative 4 string electric bass guitar method book

12 R 67095 Shpg. wt., 8 oz.


Net 1.25

Famous Name Musical Instrument Speakers

SUPER POWER CADENCE MUSICAL INSTRUMENT SPEAKERS

- Provides Natural Reproduction of Amplified Instruments
- Full Rich Tonal Quality
- Aluminum Dust Cone and Rubberized Cone Edges for Prolonged Life

As Low As **975**



Improved musical instrument speakers with heat-proofed voice coils and reinforced steel chassis for long life at higher power levels. Specially designed to meet the rigid requirements for

replacement in electric organs, guitars, bass guitars, and accordions. All speakers have 8 ohm voice coils. All speakers are round except † which is oval.



Stock No.	Utah Model	Type	Mag. Structure Wt. Lbs.	V.C. Dia. (in.)	Peak Audio (watts)	For Use With	Depth (in.)	Shpg. Wt. (lbs.)	Net Ea.
32 R 49349	MH-8JC	8"	1 3/4	1	30	Organ, Guitar	3	3	9.95
32 R 49356	MH-10JC	10"	1 3/4	1	35	Organ, Guitar	3 1/4	4 1/4	10.95
32 R 49430	MH10PS	10"	4	1 1/2	50	Organ, Guitar, Bass Guitar, Accordion	3 3/4	7	13.95
32 R 49364	MH-12JC	12"	1 3/4	1	40	Organ, Guitar	4 1/4	6 1/4	11.95
32 R 49372W	MH-12PC	12"	4	1 1/2	60	Organ, Guitar, Bass Guitar Accordion	4 1/4	8 1/4	16.75
32 R 49380W	MH-12PXC	12"	6 1/2	1 1/2	70	Organ, Guitar, Bass Guitar Accordion	5 1/4	10	22.50
32 R 49398W	MH-12RC	12"	7 3/4	2	85	Organ, Bass Guitar	5 1/4	12	39.00
32 R 49505	MH-12R3RA	12"	15	3	120	Bass Guitar	6 3/4	18 1/2	64.50
32 R 49406W	MH-15PXC	15"	6 1/2	1 1/2	75	Organ, Guitar, Bass Guitar Accordion	6 1/2	11 1/4	27.00
32 R 49414W	MH-15RC	15"	7 3/4	2	90	Organ, Bass Guitar	6 1/4	13 3/4	44.50
32 R 49513	MH-15R3RA	15"	15	3	125	Bass Guitar	8 1/2	21	69.50
32 R 49422	MH-69JC†	6x9"	1 3/4	1	30	Guitar	3	3	9.75

ALTEC LANSING PROFESSIONAL INSTRUMENT SPEAKERS


- Upgrade Your Present Equipment
- Designed For String Bass Instruments, Electric Guitars, Electric Organs
- Reproduces Crisp Brilliant Highs, And Full Clean Lows
- Massive Magnet Structures Up To 17 1/2 Lbs.
- Rugged Heavy Cast Aluminum Frames
- 3" Aluminum Edge-Wound Voice Coils

417-8C

418B



421A



MODEL 41780—12" Professional Quality Instrument Speaker. Power: Will work with amplifiers rated up to 75 watts. Impedance: 8-ohms, Voice Coil: 3", Magnet Structure: 10 1/2 lbs., Diameter: 12 1/4", Depth: 5 1/4". Shpg. wt., 16 lbs.

32 R 38508W No Money Down* Net 85.00

MODEL 418B—15" Professional Quality Instrument Speaker. Power: Will work with amplifiers rated up to 100 watts. Impedance: 8-ohms, Voice Coil: 3", Magnet Structure: 10 1/2 lbs. Diameter: 15 1/4", Depth: 7". Shpg. wt., 14 1/4 lbs.


32 R 38516W No Money Down* Net 95.00

MODEL 421A—15" Professional Quality Instrument Speaker. Specifically designed for the BASS INSTRUMENTS... Bass Guitars and Organs. Power: Will work with amplifiers rated up to 100 watts. Impedance: 8-ohms, Voice Coil: 3", Magnet Structure: 17 1/2 lbs., Diameter: 15 1/4", Depth: 6 1/4". Shpg. wt., 25 lbs.

32 R 38524W No Money Down* Net 109.00

As Low As

85⁰⁰



INSTRUMENT AMPLIFIER HORN

Only **14⁹⁵**

- Complete With Crossover



Add exciting overtones to your amplified instrument music. Molded of strong, light weight fibre which is free of resonance. Only 3 1/2 x 8 x 8 1/2" deep. When used with the crossover supplied, handles the high frequencies of a 50 watt amplifier. With larger amps, use 2 horns per woofer. Response, 2,000/20,000 Hz. Use with 8 or 16 ohm speakers, 2.8 oz. ceramic magnet. Shpg. wt., 1 1/2 lbs.

32 R 49521 Net 14.95



BANSHEE VOICE SPEAKERS

As Low As

42¹⁵

- Designed To Boost Vocals Above Instrument Levels

Model CJ-40. Voice speaker. Attractive charcoal gray, molded fiberglass. Minimizes feedback, boom, and annoying harmonics to create performances that can be heard. 40 watts peak music power. Can be mounted on any mike stand (page 189) or with model SS-4 stand below. Quick connect-disconnect receptacle takes standard phone plug. Response: 150-14,000 Hz. Impedance 8 ohms. 6Hx14Wx 12 3/4"D. Shpg. wt., 9 lbs.

44 R 10361W No Money Down* Net 42.15

BIG BANSHEE MODEL CJ-125

Similar to above except 125 watts peak music power. Uses SS-4 Stand below. Response: 100-12,000 Hz. 13H x 23W x 19"D. Shpg. wt., 20 1/2 lbs.

44 R 10379W No Money Down* Net 83.10

Model SS-4 weighted base speaker stand. Black wrinkle finish base, chrome steel tubing extends to over 6 ft. Shpg. wt., 17 1/4 lbs.

44 R 10387W Net 19.59

LAFAYETTE 25-Watt Solid State P.A. Amplifier



Model PA-25

ONLY

59⁹⁵

Specifications

Power Output: 25 Watts (RMS) at less than 5% distortion (50 Watts Peak).
 Frequency Response: 100 to 10,000 Hz \pm 2db.
 Sensitivity: High Impedance Mike = 4mV, Low Impedance Mike = 0.3mV, Aux-1/Phono = 400mV, Aux-2 = 200mV.
 Inputs: Mike High = 100K ohms, Mike Low = 200 ohms; Aux-1 = 400K ohms, Aux-2 = 100K ohms.
 Hum and Noise: Mike Input = 45db; Aux Input = 60db.
 Outputs: 4, 8, 16 ohm speaker; 25V, 70V, Tape/Booster = 5V at rated output; Tape Recorder = 0.5V at rated output.
 Semi-conductors: 9 Silicon Transistors, 2 Silicon Diodes, 1 Zener Diode, 1 Thermistor.

- 25-Watts Continuous Power (RMS), 50 Watts Peak
- Microphone Precedence Switch
- Anti-Feedback Network
- Switchable High and Low Level Mike Input
- Tape Recorder and Booster Amplifier Outputs
- Master Volume Control
- Outputs for 4, 8 and 16 ohm Speakers and, 25 Volt and 70 Volt Constant Voltage Speaker Installations

Lafayette's PA-25, 25-Watt solid state PA amplifier will more than satisfy your requirements for dependable performance for medium size meeting rooms, classrooms, entertainment centers, etc. The PA-25 incorporates all the desirable PA features plus several other sophisticated characteristics found in much more expensive equipment, i.e.: Controls: Separate Bass and Treble, Master Volume, Microphone Volume, Auxiliary-1, Auxiliary-2, Anti-feedback for minimizing feedback and for protection of speakers, and Microphone Precedence for direct or remote muting of auxiliary inputs when only microphone input is desired. In the rear, the PA-25 features a tape record output jack plus a separate output jack for tape recorder or booster amplifier, 2 speaker output sockets and impedance matching terminals for 4, 8, 16-ohms and 25-Volt and 70-Volt constant outputs, an AC convenience outlet, and AC and DC fuses. Complete with microphone connector and 2 plug-in speaker connectors. For 105-125 Volts, 60 Hz. Size 15 $\frac{1}{2}$ "x8 $\frac{1}{2}$ "x4 $\frac{1}{2}$ "D. Shpg. wt., 27 lbs. Imported.
 99 R 46286W No Money Down* Net 59.95

25-WATT INDOOR P.A. SYSTEMS

with HEAVY DUTY 12" SPEAKER

Includes PA-625 25-watt P.A. amplifier; Rugged, specially designed hi-power 12" P.A. speaker; Polished walnut wooden wall baffle; Lafayette 99 R 45874 slim crystal microphone with on-off locking switch, desk stand, lavaliar cord, cable and removable type floor stand and desk stand adapter; 35 ft. speaker cable. Shpg. wt., 37 lbs.
 44 R 91965WXM No Money Down* Net 76.95

with COLUMN SPEAKERS

Same P.A. system as 44-91965WXM except with 30 $\frac{1}{2}$ "x7 $\frac{1}{4}$ " column speaker instead of 12" speaker and wall baffle. Attains extra efficient sound reproduction with 6 internal speakers. Shpg. wt., 43 lbs.
 44 R 91973WXM No Money Down* Net 90.95
 Above system with extra column speaker and cable. Shpg. wt., 57 lbs.
 44 R 91981WXM No Money Down* Net 119.95



99-45874

12" Speaker

As Low As
76⁹⁵

PA-25

Wall Baffle

Column Speakers

25-WATT PORTABLE P.A. SYSTEMS

A complete 25-watt P.A. portable system that in addition to Lafayette's fine 25-watt P.A. amplifier, includes a heavy duty 12" P.A. speaker; a rugged excellently constructed carrying case that serves as an efficient speaker baffle and housing for the amplifier, optional phonotop, microphone, cables and up to 2-12" speakers; Lafayette 99 R 45874 high impedance slim crystal microphone with on-off locking switch, with cable, desk stand, removable swivel type floor stand adapter, and lavaliar cord, and 35 ft. speaker cable. For 105-125 volts 60 Hz. AC. Shpg. wt., 52 $\frac{3}{4}$ lbs.
 44 R 91999WXM No Money Down* Net 91.95
 Same as 44 R 91999WXM except with 2-12" heavy duty 15 watt PA speakers plus 35' speaker cable. Shpg. wt., 57 $\frac{3}{4}$ lbs.
 44 R 92005WXM No Money Down* Net 99.95



As Low As
91⁹⁵


99-45874

Phono Turntable

4-speed (16, 33 $\frac{1}{3}$, 45, and 78 RPM) phonograph turntable. Used alongside of PA-25, PA-50 and PA-100. Takes records up to 12". High quality ceramic pickup—turnover type with dual synthetic sapphire stylus. Power requirements: 15 watts, 117 volts, 60 Hz AC. Durable finish. Size: 12 $\frac{3}{4}$ "x8 $\frac{1}{2}$ "x4". Shpg. wt., 6 $\frac{3}{4}$ lbs.
 44 R 01584 Net 18.95



LAFAYETTE 50-Watt Solid-State P.A. Amplifier



ONLY **84⁹⁵**
No Money Down*

- 50-Watts Continuous Power (RMS)
- Switchable High and Low Level Mike Inputs
- Microphone Precedence Switch
- Anti-Feedback Network
- Tape Recorder and Booster Amplifier Outputs
- Master Gain Control
- 25 Volt and 70 Volt Constant Voltage Outputs

PA-50

SPECIFICATIONS

Power Output: 50 Watts at less than 5% Distortion (Peak Power 100 Watts). Frequency Response: 100 to 10,000 Hz ± 2 db. Sensitivity: High Impedance Microphone—4 mV; Low Impedance Microphone—0.3 mV; Aux 1/Phono = 400 mV, Aux 2 = 200 mV. Inputs: Mic-1 High = 100 K ohms, Low = 200 ohms, Mic-2 High = 100 K ohms; Aux-1 = 400 K ohms; Aux-2 = 100 K ohms. Num and Noise: Mic. Input = 40 db; Aux Input = 55 db. Outputs: 4, 8, 16-ohm Speaker; 25V; 70V; Tape/Booster = 5V at rated output; Tape Record = 0.5V at rated output. Semi-Conductors: 10 Silicon Transistors, 4 Silicon Diodes, 1 Zener Diode, 1 Thermistor.

Lafayette's 50-watt solid state P.A. amplifier combines power with versatility for superb performance in indoor and outdoor applications. Features separate bass and treble controls, master gain control, 2 separate microphone volume controls, mixer control for both auxiliary inputs, and switchable anti-feedback network for minimizing feedback and for protection of speakers. The PA-50 also incorporates a microphone precedence switch and terminals for direct or remote muting of auxiliary inputs when only microphone input is desired; one tape record output jack plus a common tape record and booster amplifier output jack; 2 speaker output sockets for 4, 8 and 16-ohm speakers, and 25 volt and 70 volt constant voltage speaker outputs for a multiple speaker constant level sound system. The PA-50 also includes power-on light, AC convenience outlet, and push-to-reset circuit breaker. Complete with microphone connector and 2 plug-in speaker connectors. For 105-125 volts, 99 R 45684W

4 Speed Turntable for Above Amplifier.
44 R 01584 Shpg. wt., 6 3/4 lbs.

Net 84.95

Net 10.95

50-WATT INDOOR PA SYSTEMS

Excellent for Large Halls, Department Store Paging Systems, Auditoriums, Supermarkets, etc.

WITH 12" HEAVY DUTY SPEAKERS



12" Heavy Duty Speakers



As Low As **130⁹⁵**
No Money Down*

Consists of:

- Lafayette PA-50 50-WATT PA Amplifier
- 2-12" 30-Watt (60 watts peak) Heavy Duty Speakers. Each with Tough Industrial Type 1 1/2" Voice Coil and 1 1/4 lb. Ceramic Magnet for Excellent Efficiency.
- 2- Sturdy Attractive Walnut Wall Baffles for Speakers
- Choice of Deluxe Dynamic Mikes
- 2-35' Lengths of Speaker Cable

Above system with Lafayette 99-46039 dual impedance dynamic microphone and 99-45999 desk stand. Can also be hand held or used with standard floor stand. 110-130 VAC 50/60 Hz. Shpg. wt., 49 lbs.
44 R 92013WXM Net 130.95
Same as above with Shure Unisphere A dynamic "pop-proof" cardioid mike instead of Lafayette microphone. Shpg. wt., 47 1/4 lbs.
44 R 92011WXM Net 160.95



Wall Baffles



Lafayette 99-46039 Dynamic Mike with 99-45999 Desk Stand

Shure Unisphere A Dynamic Mike

WITH 8" SPEAKER-BAFFLE COMBINATIONS



8" Speaker Baffle Combinations



PA-50


As Low As **164⁹⁵**
No Money Down*

Consists of:

- Lafayette PA-50 50-Watt PA Amplifier
- 4-8" Speaker-Baffle Combinations; each with Matching Transformer for 25 and 70.7 Volt Constant Voltage Outputs, plus Volume Control.
- Choice of Deluxe Dynamic Microphones.
- 4-35' Lengths of Speaker Cable
44 R 91924WXM Net 164.95
Complete PA system as above with Lafayette 99-46039 dual impedance dynamic microphone and 99-45999 desk stand. Mike can also be hand-held or can be used with standard floor stand. Shpg. wt., 65 lbs.
44 R 91924WXM Net 164.95
Same as above except with Shure Unisphere A dynamic cardioid "pop-proof" microphone instead of Lafayette microphone. Shpg. wt., 64 lbs.
44 R 91932WXM Net 194.95

LAFAYETTE P.A. AMPLIFIER GUARANTEE

ONE Year Guarantee: All parts guaranteed against defects in material and workmanship for one year. Ship defective part to us prepaid for replacement or ship amplifier prepaid for repair



LAFAYETTE


PA SYSTEMS

50 WATT OUTDOOR PA SYSTEMS

For Airports, Loading Platforms, Railroad Stations, Country Clubs, Camps, etc. For up to 100,000 Square Ft. of Outdoor Area



Lafayette PA-50



E-V PA-30A Projectors



Lafayette 99-46039 Dynamic Mike with 99-45999 Desk Stand



Shure Unisphere A Dynamic Mike

AS Low AS **141⁹⁵**

No Money Down*

Consists of:


- Lafayette PA 50 Versatile 50 Watt PA Amplifier
- Choice of Deluxe Dynamic Microphones†
- Two E-V PA-30A 30 Watt Weatherproof Speakers

Above system with Lafayette 99-46039 deluxe dual impedance dynamic microphone with 99-45999 desk stand. Microphone can be hand held or used with standard floor stand. Includes 20 ft. of detachable mike cable and connector. SHPG. wt., 48 lbs.
44 R 92039WXM Net 141.95
 Same system as above except with Shure Unisphere A dynamic cardioid mike instead of Lafayette microphone. SHPG. wt., 45½ lbs.
44 R 92047WXM Net 171.95

50 WATT PORTABLE PA SYSTEMS

with Dual Speakers

For the Majority of Sound System Applications . . . School Auditoriums, Churches, Theatres, Dance Halls, Studios, Lecture Halls, etc.



Lafayette PA-50



Lafayette 99-46039 Dynamic Mike with 99-45999 Desk Stand



Shure Unisphere A Dynamic Mike

AS Low AS **140⁹⁵**

No Money Down*

Consists of:

- Lafayette PA-50 50 Watt P.A. Amplifier
- Two 30 Watt Heavy Duty 12" P.A. Speakers
- Lafayette 99-46039 Dual Impedance Dynamic Microphone & Desk Stand
- Attractive, Sturdy Carrying Case for Amplifiers, Speakers, & Accessories. Serves As Efficient Baffle
- Two 35' Speaker Cables

Complete System as above. SHPG. wt., 64¾ lbs.
44 R 91940WXM Net 140.95

Same as above system except with Shure Unisphere A Cardioid Dynamic Microphone instead of Lafayette microphone. SHPG. wt., 62¾ lbs.
44 R 91957WXM Net 170.95

50 WATT INDOOR PA SYSTEMS

with LAFAYETTE 6-Speaker Column Speakers

Excellent for: Auditoriums, Churches, Theatres, Studios, and Special Events.



Lafayette PA-50



Lafayette 99-46039 Dynamic Mike with 99-45999 Desk Stand



Shure Unisphere A Dynamic Mike



Column Speakers

AS Low AS **151⁹⁵** No Money Down*

Consists of:

- Lafayette PA-50 50 Watt PA Amplifier
- Two 30 Watt 6-Speaker Column Speakers
- Choice of Deluxe Dynamic Microphones†
- 2—35 Ft. Cables

Above system with Lafayette 99-46039 dual impedance dynamic microphone and 99-45999 desk stand. Can also be hand held or used with standard floor stand. Column speaker is 30¼"x7"x13¼" utilizing 6 speakers for efficient reproduction of program material. SHPG. wt. 61 lbs.
44 R 92054WXM Net 151.95

Same as above system except with Shure Unisphere A† Cardioid Dynamic Microphone instead of Lafayette microphone. SHPG. wt., 59¼ lbs.
44 R 92062WXM Net 181.95

Same system as 44 - 92054WXM except with 2 Deluxe 60 watt, 6-speaker sound column speakers instead of 30 watt speakers. SHPG. wt., 78½ lbs.
44 R 92070WXM Net 189.95

Same as 44 - 92070WXM except with Shure Unisphere A† Cardioid Dynamic Microphone instead of Lafayette microphone. SHPG. wt., 76¾ lbs.
44 R 92088WXM Net 219.95

LAFAYETTE 100-Watt Solid State P.A. Amplifier Model PA-100



Only **124⁹⁵**

- 100-Watts (RMS) at Less Than 5% Distortion (200-Watts Peak Power)
- Switchable High & Low Level Mike Inputs
- Microphone Precedence Switch
- Anti-Feedback Network
- Tape Recorder and Booster Amplifier Outputs
- Master Gain Control
- 25 Volt and 70 Volt Constant Voltage Outputs

SPECIFICATIONS

Power Output: 100 Watts at less than 5% Distortion (Peak Power 200 Watts)
 Frequency Response: 100 to 10,000 Hz \pm 2db.
 Sensitivity: High Impedance Microphone = 4mV. Aux 1/Phono=400 mV, Aux 2=200 mV.
 Inputs: Mic-1 High = 100K ohms; Mic.—2 Low = 200 ohms; Aux-1 = 400K ohms; Aux-2 = 100K ohms.
 Hum and Noise: Mic. Input=40db; Aux Input=55db.
 Outputs: 4, 8, 16 ohm Speaker. 25V; 70V; Tape/Booster=5V; Tape Record=0.5V.
 Semi-Conductors: 10 Silicon Transistors, 4 Silicon Diodes, 1 Zener Diode, 1 Thermistor.
 Power Requirements: 105 to 125V, 60 Hz AC; 190 VA.

Lafayettes' 100-watt solid-state P.A. amplifier features outstanding solid state circuitry design for truly dependable public address long life performance. Its high power and special features make it ideal for use in large meeting areas, factories, department stores, airports, churches, temples, outdoor areas, etc. where maximum coverage is essential. Some of its salient features are separate bass and treble controls, efficient master gain control, separate microphone volume controls for microphone 1 and microphone 2, mixer control for both auxiliary inputs (phono, tuner, etc.), 2 switchable high and low level microphone inputs, a switchable anti-feedback network to minimize feedback and to protect speakers against burnout. In addition the PA-100 incorporates a microphone precedence switch that permits muting of auxiliary inputs when only microphone input is desired, as well as separate mike precedence terminals to permit remote switchable microphone precedence with suitable microphone; one tape record output jack plus a common tape record and booster amplifier output jack; 2 speaker output sockets for 4, 8 and 16 ohm speakers, and 25 volt and 70 volt constant voltage speaker outputs for a constant level sound system. The PA-100 also includes power-on indicator light, AC convenience output and push-to-reset circuit breaker. It is professionally designed for attractive appearance as well as for exceptional utility. Complete with microphone connector and 2 plug-in speaker connectors. For 105-125 volts, 60 Hz, 190 VA. Size 15 $\frac{1}{4}$ "W x 5 $\frac{1}{4}$ "H x 10 $\frac{1}{2}$ "D. Shpg. wt., 28 lbs. 99 R 46138W No Money Down* Net 124.95
 Desk Type Dynamic Qu Impedance Press-to-Talk P.A. Microphone. Excellent For Standard and Mike Precedence Activation of PA-100. Shpg. Wt., 2 $\frac{1}{2}$ lbs. 99 R 46096 Net 12.95

LAFAYETTE P.A. AMPLIFIER GUARANTEE

ONE Year Guarantee: All parts guaranteed against defects in material and workmanship for one year. Ship defective part to us prepaid for replacement or ship amplifier prepaid for repair

100-Watt Indoor Public Address Systems

Excellent for: Department Stores, Auditoriums, Airports, Large Meeting Halls, Churches, Temples, etc.



99-45981



Model PA-100



E-V 664



with WALL-MOUNT SPEAKERS

As Low As

239⁹⁵

- Lafayette PA-100 100-Watt Solid State PA Amplifier
- 6 Lafayette Pre-wired Speaker Baffle Combination with 8" Speakers, Volume Controls, and Universal 25 Volt/70.7 Volt Constant Voltage Matching Transformers
- Choice of Deluxe Dynamic Microphones
- Six 35 ft. Speaker Cables

Wall-Mount Speaker Baffle Combinations with 25V/70.7V Transformers

with COLUMN SPEAKERS

As Low As

191⁹⁵

- Lafayette PA-100 100 Watt Solid State -PA Amplifier
- Two 30-Watt 6-Speaker Sound Column Speakers for Optimum Voice and Music Reproduction
- Choice of Deluxe Dynamic Microphones
- Two 35 ft. Speaker Cables

Above 100-watt PA system with Lafayette 99-45981 deluxe dual impedance dynamic "pop proof" microphone with on-off switch and desk stand. Column speakers are 30 $\frac{1}{4}$ " H x 7"-W x 3 $\frac{1}{4}$ "-D. Shpg. wt., 59 lbs. No Money Down*
 44 R 91841WXM Net 191.95

Column Speakers

Complete 100-watt indoor PA system as above with Lafayette 99-45981 deluxe dual impedance dynamic "pop-proof" microphone with on-off switch, desk stand and 6 ft. detachable cable. The microphone can also be hand held or mounts on any standard floor stand. Shpg. wt., 76 lbs. No Money Down*
 44 R 91825WXM Net 239.95


Same system as above except with 2 Lafayette deluxe 60-watt 6-speaker 41 $\frac{1}{2}$ "x7 $\frac{1}{4}$ "x5"D sound column speakers instead of 30-watt column speakers. Shpg. wt., 76 $\frac{1}{2}$ lbs. No Money Down*
 44 R 91858WXM Net 229.95

Same as above system except with famous Electro-Voice 664 dynamic cardioid microphone with 15 ft. of cable instead of 99-45981 microphone. Shpg. wt., 76 lbs.
 44 R 91833WXM No Money Down* Net 279.95

Same system as 44-91858WXM except with Electro-Voice 664 dynamic cardioid microphone with 15 ft. of cable instead of 99-45981 microphone. Shpg. wt., 76 $\frac{1}{2}$ lbs. No Money Down*
 44 R 91874WXM Net 269.95

LAFAYETTE P.A. AMPLIFIER GUARANTEE

ONE Year Guarantee: All parts guaranteed against defects in material and workmanship for one year. Ship defective part to us prepaid for replacement or ship amplifier prepaid for repair



100-Watt Hi-Power Outdoor P.A. Systems

Consists of: Ideal For Large Area Coverage

- Lafayette PA-100 100-Watt Solid State PA Amplifier
- 2 Electro-Voice PA30A 30-Watt Outdoor Speakers
- Choice of Deluxe Dynamic Microphones

This outstanding outdoor PA system with Lafayette 99-45981 deluxe dual-impedance dynamic "pop-proof" microphone with on-off switch, desk stand and 6-ft. detachable cable. Microphone can also be hand held or mounts on any standard floor stand. Shpg. wt., 46 lbs.

44 R 91882WXM No Money Down* Net 181.95

Same system as above plus 2 additional E-V PA30A projector speakers. Shpg. wt., 61 lbs.

44 R 91890WXM No Money Down* Net 229.95

Same system as 44-91882WXM except with famous Electro-Voice 664 dynamic cardioid microphone instead of 99-45981 microphone. Shpg. wt., 46 lbs.

44 R 91908WXM No Money Down* Net 221.95

Same system as 44-91890WXM except with Electro-Voice 664 dynamic cardioid microphone instead of 99-45981 microphone.

44 R 91916WXM Shpg. wt., 61 lbs. Net 269.95

Lafayette
99-45981



Model PA-100



E-V PA30A
Projectors

As Low As
181⁹⁵



E-V 664

100-Watt Portable P.A. Systems with Dual Speakers

FOR THE MAJORITY OF SOUND SYSTEM APPLICATIONS...
School Auditoriums, Churches, Theaters, Studios, Lecture Halls, etc.

Consists of:

- Lafayette PA-100 100-Watt PA Amplifier
- Two 30-Watt Heavy Duty 12" P.A. Speakers
- Choice of Deluxe Dynamic Microphones
- Attractive, Sturdy Carrying Case and Baffle for Amplifiers, Speakers, and Accessories.
- Two 35' Speaker Cables

Complete 100-Watt portable PA system as above with Lafayette 99-45981 deluxe dual-impedance dynamic "pop-proof" microphone with on-off switch, desk stand and 6 ft. detachable cable. The microphone can also be hand-held or mounts on any standard floor stand. Shpg. wt., 62 3/4 lbs.

44 R 91809WXM No Money Down* Net 179.95

Same as above system except with famous Electro-Voice 664 dynamic cardioid microphone with 15 ft. of cable instead of 99-45981 microphone. Shpg. wt., 62 3/4 lbs.

44 R 91817WXM No Money Down* Net 219.95



Lafayette
99-45981

As Low As
179⁹⁵



E-V
664


Lafayette Portable P.A. Case

- 2 Baffles In One Case
- Room For Two 12" Speakers

A sturdily constructed case for amplifier and two 12" speakers. Made of heavy plywood with reinforced metal corners. Case splits into 2 baffles, each with heavy duty plastic carrying handle. Covered with attractive grill cloth. Has 2 hooks in each half for carrying speaker cables and provisions for mike and mike base. 4 snap locks. In addition to room for two 12" speakers, there is ample space for any amplifier and phono top measuring up to 16 3/4" x 11 3/4" x 10" H. 17 3/4" x 12 3/4" O.D. Shpg. wt., 19 1/4 lbs.

44 R 01618WX Net 21.95

Only
21⁹⁵



Buy Any Complete P.A. System on This Page and SAVE MONEY

PA Sound Columns, Speakers, and Megaphones

LAFAYETTE 6 SPEAKER DIRECTIONAL SOUND COLUMNS



Ideal For
Auditoriums,
Schools,
Churches,
Meeting Rooms

As Low As **29⁹⁵**


- Reduces Reverberation and Feedback Problems
- Concentrates or "Focuses" Sound Where Needed

Specially designed, matched and balanced speakers stacked in a vertical array. By widely directing sound in a horizontal plane cover a large audience, and by narrowing the vertical plane they reduce normal acoustic feedback and reverberation from floor and ceiling reflections, resulting in crystal-clear voice and music reproduction.

A Lafayette 30 Watt Sound Column — Six 4 1/2" speakers handle up to 30 watts power. Frequency response 200-10,000 Hz. Dispersion 120° horizontal, 30° vertical. Impedance 16 ohms. Attractive vinyl covered wood cabinet. Dimensions 31"Hx7 1/4"Wx3 1/4"D. Imported. 99 R 46146W Shpg. wt., 1 1/2 lbs. Net 29.95

B Deluxe Lafayette 60 Watt Sound Column — Six powerful 6" speakers handle up to 60 watts power. Size: 41 1/2"Hx7 1/4"Wx5"D. Frequency response 70-10,000 Hz. Dispersion 120° horizontal, 30° vertical. Handsome vinyl covered wood cabinet. Impedance 8 ohms. Shpg. wt., 2 1/4 lbs. 99 R 46252WX No Money Down* Net 49.95

WEATHERPROOF OUTDOOR PUBLIC ADDRESS AND HI-FIDELITY SPEAKERS



(A) E-V SONOCASTER

(B) HI-FI SPEAKER

(C) UNIVERSITY MLC

24⁵⁰

34⁹⁵

46⁷⁶

(A) ELECTROVOICE SONOCASTER I Lightweight, rugged and weatherproof for extension or portable use anywhere. Special radax coaxial 8" speaker provides amazingly wide range response, 70-13,000 Hz. Ideal for use with existing stereo system. Improves performance of any portable radio, record player, recorder, etc. Black molded housing similar to fine air travel luggage; can't chip, fade or peel. Accessory hangup bracket included. Molded-in handle. 8 ohms. 30 watts peak. 16 1/4"Hx17Wx5 1/2"D. Wt. 6 1/2 lbs. Net 24.50

21 R 30300W Net 24.50

(B) DELUXE HIGH FIDELITY OUTDOOR WEATHERPROOF SPEAKER Designed to be used with outdoor home high fidelity and stereo music systems on patios, lawns, terraces, and around swimming pool areas. The magnificent projecting speaker consists of a special 6 1/2" full range speaker mounted in a totally sealed, infinite baffle-type compression chamber with the speaker diaphragm driving on one piece, fiberglass reinforced polyester, folded, front loaded horn. The woofer compression chamber is made of spun aluminum. Comes with adjustable and serrated "U" bracket which permits 180° variation in mounting position. Dispersion 120°. Response, 100-15,000 Hz. Power Handling 20 Watts. Impedance 8 ohms. Size: 12 1/4"Wx9 1/4"H. Finish —Light Grey. Shpg. wt., 10 lbs. 44 R 80307W No Money Down* Net 34.95

(C) UNIVERSITY MLC Ideal for coverage of moderate size areas or crowds—or for sound reinforcement where smooth, clean, wide range musical reproduction and even distribution are important. Fiberglass reinforced polyester housing with movable mounting bracket. Excellent reproduction from 150-15,000 Hz with a power rating of 15 watts. System has a 2000 Hz crossover. 120° dispersion; 8 ohms impedance. Dimensions: 12 1/4"Wx9 1/4"Hx15 1/2"D. Shpg. wt., 10 lbs. 44 R 80018W No Money Down* Net 46.76

44 R 80018W No Money Down* Net 46.76

LAFAYETTE 8" 10-WATT MULTI-TAP PA SPEAKER SYSTEM



17⁹⁵

- Built-in Volume Control

- 70 Volt and 25 Volt Line Matching Transformer with Taps for 10, 5, 2.5, 1.25, and .625 Watts

An 8" multi-tap PA speaker completely prewired in a finished wood baffle. Ideal for any type of indoor sound system. Heavy duty speaker has 4.64 oz. Alnico magnet. Power rating: 10-watts. Transformer is mounted directly on speaker frame. Taps are 10, 5, 2 1/2, 1 1/4, and 3/4 watts for connection to 70 volt and 25 volt amplifier output. Terminal board with screw terminals is provided at the rear of baffle for easy connections. Speaker has its own volume control for setting volume levels as desired at speaker location. Size: 11Wx9 1/2"Hx6 1/4"D. Imported. Shpg. wt., 6 1/2 lbs. 99 R 46310W Net 17.95

POWER MEGAPHONES

FANON MV-3 TRANSISTORIZED MEGAPHONE



31⁹⁵

- Range up to 600 Ft.
- 3 Watts Output.

Lightweight aluminum. Baked enamel finish for durability. Anti-howl damping element. Pistol grip. Hi/Lo volume switch. 5" reflex air column. 8 1/2" bell. Power output: 3 watts peak — 1.5 watts rated. Range: 200 yds. Batteries: Four "D" cells (not included) give over 6 hours continuous operation. Convenient carrying strap. Size: 9" x 13". Imported. Shpg. wt., 4 1/2 lbs. 44 R 30260W No Money Down* Net 31.95

99 R 63661W Long-Life "D" Batteries (4 req'd) Ea. .25

FETRO POWERHOUSE TRANSISTORIZED MEGAPHONE



44⁹⁵

- Rustproof • Waterproof
- Range Up to 1200 Feet

This land and sea megaphone features all aluminum construction, superb clarity and tonal quality, a durable handy carrying strap, instant battery loading, a noise-canceling microphone, fingertip volume control and power-packed amplification. It is capable of 5-watts output and operates off 4 optional flashlight "D" cells. The bell is protected and cushioned with a polyvinylchloride bumper rim. Finished in brilliant red and ebony black. Imported. Dim.: 7 1/4" Dia. x 12 1/4" L. 44 R 27027W Shpg. wt., 4 1/4 lbs. No Money Down* Net 44.95

99 R 63661 Long-Life "D" Batteries (4 Required) Ea. .25

UNIMETRICS 20-WATT PORTACALL POWER MEGAPHONE



74⁵⁰

No Money Down*

Less batteries

- Range 3600 ft.
- Red Emergency Light
- Blast Siren Signal

Extremely rugged and reliable. For long range voice communication. Water resistant and corrosion proof. Transistorized amplifier. Brilliant red emergency light. Powerful built-in emergency siren. Pistol grip, trigger operation with volume control. Built-in mike. Operates on 8 "C" Batteries (not included). With carrying strap. Imported. 40 R 69118W Shpg. wt., 6 lbs. Net 74.50

99 R 62572 "C" Batteries for above (8 required) Net ea. .16

PA Projectors, Trumpets, Paging Speakers and Drivers

LAFAYETTE MINIATURE HORN PAGING SPEAKER



8⁹⁵


- Mounts Easily
- 90° Dispersion
- Weatherproof

An excellent general purpose paging speaker of amazingly compact size. Ideal for portable PA systems, patios, etc. Long-throw projection of 90° dispersion offers maximum speech intelligibility in high noise areas. Compact size enables it to be mounted anywhere in almost any position. Frequency response 400-12,000 Hz. Impedance 8 ohms. Power handling capacity 5 watts, 8 watts maximum. Complete with mounting bracket, 2-conductor cable. Horn diameter 5 1/4" Depth 4 3/4". Imported, Shpg. wt., 1 1/2 lbs.

99 R 45080

Net 8.95

E-V PROJECTORS AND PAGING SPEAKERS



(A) Model 848A, COMPOUND DIFFRACTION PROJECTOR—a wide range horn and driver system using two way driver plus high and low frequency horns coupled to both sides of diaphragm. Delivers wide angle sound with extremely low distortion. Outer horn is fabricated of fiberglass and polyester resin for strength and resistance to corrosion. Rating: 52 db. Power handling capacity: 30 watts program. Response: 150-10,000 Hz. Impedance: 8 ohms. Dispersion: 120°. Universal U Mounting bracket. Dimensions: 10 1/2 x 20 1/2 x 20".

44 R 25641W Shpg. wt., 17 lbs. Net 60.75

(B) Model PA-12, 12-WATT PAGING SPEAKER. Fiber-polyester construction. Round reentrant design. Wide dispersion. Freq. Response: 325-14,000 Hz. Impedance: 8-ohms. Power Handling: 12-watts. Size: 7 1/2 x 6 3/8". Shpg. wt., 4 lbs.

44 R 25765 Net 17.40

(C) Model PA-30A, 30-WATT PAGING PROJECTOR. Rugged, high-impact horn. Rectangular horn design for maximum versatility, wide dispersion. Smooth response for both voice and music: 250-14,000 Hz. 30 watts, 8 ohms. Dispersion: 120° x 90° EIA sensitivity rating 59 db, 11H x 6 1/2 W x 8 1/2 D. Shpg. wt., 6 3/4 lbs.

44 R 25153 Net 25.50

UNIVERSITY PAGING/TALK BACK SPEAKERS



As Low As
21⁸⁰

Compact sized, weatherproof, highly efficient speakers for all PA fixed and mobile installations. With patented "Omni-Lok" swivel mount—quickly converts for fitting to 1/2" pipe.

Model MIL-AB—Response: 350-13,000 Hz. Impedance: 8 ohms. Ideal for low power systems requiring high efficiency. Handles 10 watts. Dispersion: 120°. Size: 7 1/8 x 6 3/8". Shpg. wt., 3 3/4 lbs.

44 R 80067 Net 21.80

Model IB-AB. Ideal for fill in applications in high power sound systems and as the main speaker in low to moderate power systems. Response: 250-13,000 Hz. Handles 30 watts. Impedance: 8 ohms. Dispersion: 90° Size: 10 x 9 3/4". Shpg. wt., 4 3/4 lbs.

44 R 80034 Net 26.40

Lafayette Supplies Public Address Equipment at Low Prices

LAFAYETTE PA DRIVER UNITS



25 Watt
Driver

11⁹⁵

40 Watt
Driver

16⁹⁵

Hermetically sealed weatherproof driver units. Recommended for all type of PA work and industrial requirements. Wide-range response of these drivers assure excellent reproduction of voice and music. Will fit all trumpets and projectors. Impedance 16 ohms.

Stock No.	Response (Hz)	Size	Watts	Shpg. Wt.	Net
99 R 45072	120-7100	4 x 3 3/4	25	2 3/4 lbs.	11.95
99 R 46260	80-12,000	4 1/2 x 4	40	3 3/4 lbs.	16.95

UNIVERSITY WEATHERPROOF REFLEX TRUMPETS



As Low As

26³⁰


GH
LH
PH
SMH

- Ideal for use with Lafayette PA Drivers

Highly efficient air column directional reproducer to give maximum intelligibility in areas of high noise level. Design of units listed below provide optimum sound distribution pattern, increases sound intensity along speaker axis dependent upon diameter of horn. Made of heavy gauge spun aluminum, weather proof, gray finish. With universal "U" type mounting bracket, less driver unit. Type GH: 85 Hz cut off for music. Types LH and PH: 120 and 150 Hz cut off for general use. Type SMH: 200 Hz cut off for voice only.

Stock No.	Model	Diam.	Lng.	Air Col.	Shpg. Wt.	Net
44 R 80125WX	GH	30 3/8"	27 3/8"	6 1/2"	23 1/4 lbs.	65.85
44 R 80133WX	LH	25 5/8"	19"	4 1/2"	19 3/4 lbs.	42.30
44 R 80141W	PH	20 3/4"	15 3/4"	3 1/2"	11 1/4 lbs.	30.63
44 R 80158W	SMH	16 3/4"	12"	2 1/2"	8 lbs.	26.30

ATLAS MOBILE PA MARINE AND CB SPEAKERS



As Low As

30⁸⁴
ea.

Model MO-1 Weatherproof speaker with special, rigid, one-piece cast bracket for fail-safe use on vehicles or boats. Concealed wiring and special one-piece horn discourage tampering. High efficiency for use with mobile radio transceivers. Ideal for shipboard cabin-top mounting. Power: 25 watts. Impedance: 8 ohms. Response: 300-13,000 Hz. Dispersion: 130°. Size: 7 1/4" bell diameter, 6 3/8" D. Shpg. wt., 6 lbs.

44 R 10346 No Money Down* Net 31.14

Model MO-2 Compact, weatherproof mobile communications speaker with welded steel bracket for concealed, limited space use in vehicles or on boats for bulkhead or cabin-top mounting. Power: 25 watts. Impedance: 8 ohms. Response: 300-13,000 Hz. Dispersion: 130°. Size: 6 5/8" W x 8 1/4" D. Shpg. wt., 5 1/2 lbs.

44 R 10353 No Money Down* Net 30.84

UNIVERSITY LINE MATCHING TRANSFORMERS

Model 5433—30 watt. Primary 45/165/200/250/1000/2000 ohms; secondary 4, 8 and 16 ohms; 70 volt line taps 30/25/20/10/5/2.5 watts. 1 3/4 x 2 1/8 x 1 1/4". 2 3/8" centers.

44 R 80166 Shpg. wt., 3 3/4 lbs. Net 6.68

Model 5434—15-watt. Primary 45/325/500/1000/2000/4000/8000 ohms; secondary 4/8/16 ohms; power taps with 70 volt line 15/10/5/2.5/1.25/.65 watts. 1 3/4 x 1 1/8 x 1 1/4". 2" centers.

44 R 80174 Shpg. wt., 1 1/4 lbs. Net 5.60

LAFAYETTE PA Speakers — Lowell Baffles

LAFAYETTE CEILING BAFFLE with SPEAKER

- Wide Range Hi-Fi Response
- Measures Only 2 1/4" Deep
- 12 oz. Magnet Structure

6⁹⁵




The perfect speaker to furnish music or paging throughout your home, office or factory, this unique ceiling and wall baffle speaker offers fine audio reproduction. Highly attractive mint cool green-beige color that blends harmoniously with any ceiling or enclosure. Only 2 1/4" deep with its own metal baffle plate, it easily mounts in any wall, ceiling, closet or ordinary wood enclosure. Two are perfect for stereo. Voice coil is 1" Diam. Frequency Response: 90-9,000 Hz. Impedance: 8 ohms. Overall size including metal baffle is 9 1/2". Requires 6 1/2" wall cutout. Imported. Shpg. wt., 3 lbs. 99 R 45056

Net 6.85

UTAH OM-10 OMNI-Directional 8" WALL/CEILING SPEAKER

- 8" Wide Range Speaker
- Radiates Sound For a Full 360°

15⁹⁵



Fasten to ceiling or hang on wall. Will not overpower people directly in front or under speaker. Handsome walnut grained baffle. Supplied L-Pad type control and all necessary hardware. Impedance: 8 ohm. Power 8 watts (15 watts peak). Size: 11 x 11 x 4 1/2". 44 R 20030W Shpg. wt., 4 lbs. Net 15.95

LAFAYETTE PA SPEAKERS

8" PA SPEAKER 5⁹⁵

- Handles 20 Watt Peaks

The 8" favorite of professional sound installers; with 5.5 oz. ceramic magnet and 3/4" voice coil. Magnet assembly bonded with RF-cured epoxy, can't shift. Internal magnet seal for added dependability. Handles 10-watts program, 20-watts peak. Impedance, 8-ohms. Only 2 1/4" deep, fits inside walls. A popular speaker at a popular price. 44 R 01030 Shpg. wt., 2 1/4 lbs. Net 5.95



12" PA SPEAKER 8⁹⁵

- Handles 36 Watts Peaks

Highly efficient magnet and voice coil combination for maximum sound output per watt; 10 oz. ceramic magnet and 1" voice coil. Magnet assembly bonded with RF-cured epoxy, can't shift. Internal magnet seal for added dependability. Handles 18-watts program, 36-watts peak. Impedance, 8-ohms. 4 1/4" deep. Shpg. wt., 5 lbs. 44 R 01022 W Net 8.95



DELUXE HEAVY DUTY 12" PA SPEAKER 12⁹⁵

- Handles 60 Watts Peak

High Power handling ability for large installations. Tough industrial type 1 1/2" voice coil. 20 oz. ceramic magnet for excellent efficiency. Accepts all popular line-to-voice coil transformers. Power handling 30 watts (60 watts peak). Imp. 8 ohm. Overall Diameter 12 1/2". Depth 4 1/2". Shpg. wt., 7 lbs. 44 R 01600W Net 12.95



LOWELL PA SPEAKER BAFFLES


FLUSH-MOUNTING PLASTIC BAFFLES



Decorative high impact Styrene plastic baffles: White finish. Lightweight and durable—will not fade, chip or mar—Model ADS80-P has full 360° dispersion. Self-tapping speaker mounting screws supplied.

Stock No.	Type	Description	Wt.	Net
44 R 50144	ADS80P	For 8" ceiling Spkr 10x10"	10 oz.	2.96
44 R 50151	CR80P	For 8" ceiling/wall Spkr 10x10"	8 oz.	1.43
44 R 50169	L35P	For 3 1/2" intercom Spkr 4 1/2x7"	5 oz.	.94

STEEL RECESSED BAFFLES



Popular steel style grills with enduring baked on white enamel finish. All grills have 4 studs on rear to mount speaker. For 8" speakers. All hardware is furnished.

Stock No.	Type	Description	Wt.	Net
44 R 50201	LK-8	For 8" Ceiling Speaker 13 1/4" dia.	1 1/4 lbs.	2.53
44 R 50219	CW-8	For 8" Ceiling Speaker 12" dia.	2 3/4 lbs.	6.21

FLAT TILE TYPE PANEL BAFFLE

Type M8—Square steel type. Designed to match and replace standard 12 x 12 x 1/2" acoustic tile blocks. Permits a completely hidden speaker system—for 8" speaker mounting hardware is furnished—Baffle is zinc chromate undercoated and finished in flat white lacquer 12 x 12 x 1/2". FOR PROPER ENCLOSURE SEE ENCLOSURE LISTING. 44 R 50193 Net 3.73



RECESSED ALUMINUM BAFFLES



RS and AL ceiling baffles are ideal for installation in homes, offices, restaurants, etc. Spin aluminum material has lacquer protected satin finish. Model AL features diffuser cone for full 360° sound dispersion. REQUIRE PROTECTIVE SPEAKER ENCLOSURES (TYPE CP AND XCP LISTED BELOW).

Stock No.	Type	Description	Lbs.	Net
44 R 50011	RS-6A	For 6" speaker 10 3/4" x 7 1/4"	3/4	2.53
44 R 50029	RS-8A	For 8" speaker 12 1/2" x 1 1/2"	1	2.50
44 R 50037	RS-8A	Same as above but wh. enam.	1	2.50
44 R 50045	RS-12A	For 12" speaker 16 1/2" x 1 1/2"	1 3/4	3.85
44 R 50052	AL6A	For 6" speaker 10 1/2" Dia.	3/4	5.06
44 R 50060	AL8A	For 8" speaker 12 1/2" Dia.	1	8.66
44 R 50078	AL12A	For 12" speaker 16 1/4" Dia.	2	10.95

PROTECTIVE MOUNTING ENCLOSURES

Protect against damage from falling mortar, dust, rodents, etc. 22 ga. steel welded construction. Exteriors are rust-proofed with zinc chromate; interiors are heavily undercoated to prevent resonance. CP series used for new construction, XCP for existing ones, P875X for either. Shpg. wt.: Types CP1012, XCP1012—8 lbs.; CP84, XCP84, P875X, CW-8—3 1/4 lbs.; CP-6, XCP-2 1/2 lbs.; P22X—1 lb.




Stock No.	Type	For	I.D.	O.D.	Depth	Net
44 R 50086	CP-6	AL6-A, RS6-A	7 1/2"	11 1/4"	4 1/4"	3.67
44 R 50094	CP84	AL8-A, RS8-A, M8	8 1/2"	13 1/2"	4 1/4"	4.21
44 R 50102	CP1012	AL12-A, RS12-A	12 1/2"	17 1/2"	7 1/4"	8.45
44 R 50110	XCP6	AL6-A, RS6-A	7 1/2"	10 1/4"	4 1/4"	3.68
44 R 50120	XCP84	AL8-A, RS8-A, M8	8 1/2"	11 1/4"	4 1/4"	4.07
44 R 50136	XCP1012	AL12-A, RS12-A	12 1/2"	16"	7 1/4"	9.32
44 R 50177	P875X*	AL8-A, RS8-A, M8, ADS80-P, CR80-P	—	—	3 1/2"	3.76
44 R 50185	P22X**	L35P	—	—	2"	3.05
44 R 50227	CP-200	CW-8	10"	13 1/2"	5"	5.71

*Size 8 3/4x8 3/4"

**Size 6 1/4x4"

Extension, Outdoor, and TV Remote Control Speakers

Deluxe LAFAYETTE "DECORATOR TYPE" EXTENSION SPEAKER SYSTEM



Only
10⁹⁵
ea.

- Powerful 6½" Wide-Range Speaker
- Handles Up To 6-Watts Music Power
- Handsome Oiled Walnut Wood Enclosure

Our finest quality extension speaker system. Powerful 6½" rich sounding wide-range speaker is housed in a handsomely styled oiled walnut wood enclosure with a decorative black grill cloth. You can enjoy fine hi-fi music everywhere in your home as well as enhance the decor of your home. Use 2 for stereo or place these systems in every room of your home. Also ideal for use in background music systems in offices and restaurants. Handles up to 6-watts. Impedance 8 ohms. Size: 7½" W x 9¾" H x 5¼" D. Wt., 5½ lbs. Imported. 99 R 02032W **10.95**

LAFAYETTE OUTDOOR 8" PATIO SPEAKERS

MISCO WEATHERPROOF SPEAKERS



As Low As **11⁹⁵**

- Weatherproof + Waterproof
- Freq. Response: 40-15,000 Hz
- 5.5 oz. Ceramic Magnet
- Peak Power 20 Watts

Relax with music outdoors at patio, porch or poolside. Prewired with 25' cable for easy connection to radio, phono or hi-fi system. Unaffected by dampness or rain. Durable steel enclosure with baked-on finish. Convenient, step-saving volume control. 8 ohms; 20 watts peak; 40-15,000 Hz.; 10½" x 10½" x 5¾" D. Shpg. wt., 7 lbs. **44 R 33058 W** Net **11.95**

DELUXE VERSION of above with heavy-duty speaker featuring 10 oz. ceramic magnet and co-axially mounted high-frequency cone for 35-19,000 Hz response. 15 watts normal, 30 watts peak. **44 R 33066 W** Shpg. wt., 7¼ lbs. Net **13.95**



As Low As **7⁷²**

- 3½" and 8" Models
- Gimbal Type Mounting Bracket
- For Patio, Paging, or Mobile Applications

Model MS-3-3BB. Compact, weatherproof, dustproof. Ideal for use in mobile communications, for intercom paging, and as an extension speaker. Can be immersed in water. Power rating 3-watts. Resp: 100 to 10,000 Hz; 8 ohms imp. 4½ x 4½ x 2½ with bracket. Wt., 1¼ lbs. **44 R 52017** Net **7.72**

Model MMS-8F. Similar to above but with 8" speaker. Power rating 8 watts. Resp: 70-13,000 Hz. 9 x 9 x 4¼". Shpg. wt., 7¼ lbs. **44 R 52025** Net **14.65**

LAFAYETTE EXTENSION SHELF SPEAKER SYSTEM

LAFAYETTE EXTENSION WALL SPEAKER SYSTEM

LAFAYETTE DESK TYPE EXTENSION SPEAKER SYSTEM



Only
7⁹⁵

- Attractive Walnut Finished Wood Cabinet

Ideal as an extension speaker for your den, basement, kitchen or bedroom. Use two for stereo or with your TV and Radio. Housed in a beautiful walnut finished wood cabinet. 5-watt 4 x 6" speaker is designed to work from either 4- or 8-ohm output. Supplied with 25 feet of cable. Size: 9½ x 7¾ x 3¼" D. Imported. Shpg. wt., 3 lbs. **99 R 45502** Net **7.95**



Only
8⁹⁵

- 6" Speaker
- Oiled Walnut Wood Finish
- Volume Control

Fine sounding and handsome looking extension speaker system with brackets for hanging on any wall. Outstanding tonal quality from a wide-range 6" speaker makes it ideal for hi-fi extension speaker use. Features volume control. Excellent for P.A. and paging. 9¾" H x 9¾" W x 4" D. Imp: 8 ohms. Imported. **99 R 45494** Shpg. wt., 3½ lbs. Net **8.95**



Only
6⁹⁵

- Walnut Decorator Baffle with Cane Grille

Versatile extension speaker suitable for desk or shelf use. Attractive tri-angular shaped, oiled walnut finished cabinet. Powerful 4 x 6" oval speaker provides fine tone. Complete with volume control and 22 ft. of wire. Impedance 8 ohms. Size: 7¾" W x 5¼" H x 5¼" D (at the base). Imported. Wt., 2 lbs. **99 R 01216** Net **6.95**

LAFAYETTE 4" PAGING SPEAKER SYSTEM

MINIATURE 2-WAY REMOTE CONTROL TV SPEAKER

DELUXE 2-WAY REMOTE CONTROL TV SPEAKER



4⁹⁵

- Includes 25-Ft. Speaker Cable With Plug

For use in multi-speaker low power paging systems, intercom systems, auxiliary bench speaker, etc. 4" PM speaker with heavy magnet. Mounted in 2-tone walnut and black wood baffle. The baffle has sloping-front and enclosed-back acoustic construction and has a built-in jack for plug-in connection of the 25' cable and plug supplied. Speaker voice coil is 4 ohms. Size: 5W x 5¾" H x 3¾" D. Imported. Shpg. wt., 1½ lbs. **99 R 45510** Net **4.95**



Only
3⁹⁵

- Control Both TV Set Speaker and Remote Speaker From Your Armchair

Fine quality built-in speaker makes it perfect for use as a remote TV speaker anywhere in your home or office. Dual controls for listening to TV speaker only, remote speaker only, or both speakers together. Attractive molded cabinet measures 4W x 2¾" H x 1¾" D. Complete with 20-ft. of 4-conductor cable. Imported. Wt., ¾ lb. **99 R 45486** Net **3.95**



Only
7⁹⁵

- Control Both TV Set Speaker and Remote Speaker From Your Armchair

A large 4 x 6" full-range speaker mounted in a larger cabinet for improved tonal quality. With 2 fader controls so that you may listen to either the TV speaker, this remote speaker, or both blended to the volume level you desire for each. You can turn off volume on both speakers without turning off the set. Attractive walnut finished cabinet which measures 9¾" L x 6¼" H x 3¾" D. Complete with 20' of cable. Imported. Shpg. wt., 3 lbs. **99 R 45965** Net **7.95**

MIXERS—PREAMPS—EQUALIZERS

LAFAYETTE TRANSISTORIZED STEREO/MONAUURAL MIKE MIXER



9⁹⁵
 • Up to 4 Input Channels
 • Matches High Impedance Mikes

In monaural position, can be used to control up to four different signals into a single output. In the Stereo position, it can be used to feed two separate signals into each of the left and right outputs. Each mike control independent of the other, permits fading of one input while increasing others. Controls high impedance microphones, recorders, phonographs or tuners. Output jack fits standard RCA type phono plugs. Inputs are standard 2-conductor phone plugs. Less battery. Size: 6W x 2 1/4H x 3 1/2"D. Imported.

99 R 45635 Shpg. Wt., 1 1/2 lbs. Net 9.95
 99 R 60212 Battery for above Net .29

LAFAYETTE SOLID STATE STEREO MIXER/PREAMP




16⁹⁵

"All-Transistor" stereo-mixer/preamp! For use with any power amplifier not incorporating low-level inputs for magnetic cartridges, tape heads and low-impedance microphones. Raises the output of any low level source without affecting the signal-to-noise ratio. Features: 2-mike, 2-phono, 2-tape inputs, volume controls for left/right channel; equalization switch; power off/on switch; mode switch; built-in 9V DC power supply, or operates off 117V 50/60 Hz AC. Input impedance: 50K ohms. Output impedance 5K ohms at max. vol. Size: 2 1/2Hx7Wx5 1/2"D. With battery. Imported.

99 R 01788 Shpg. wt., 2 1/2 lbs. Net 16.95
 99 R 60212 Replacement Battery Net .29

BOGEN MODEL MX6A-T MIXER — PREAMPLIFIER



52⁴⁵
 • 4 Mic and 2 Phono Inputs

FEATURES: Any 4 channels may be used simultaneously, each individually controlled for mixing and fading. Connects to high impedance radio/phono input of any amplifier, tape recorder or microphone. SPECIFICATIONS — OUTPUT VOLTAGE: 2 Volts and .04 volts at 0.5% distortion; FREQUENCY RESPONSE: 50-20,000 Hz \pm 2 db; GAIN: Mic —60 db, phono —20 db; HUM: —68 db below 5 volt; OUTPUT IMPEDANCE: 2200 ohms; CONTROLS: 2 Mic volume, 2 Mic or phono volume, on-off; SEMICONDUCTORS: 6 transistors, 2 diodes (all silicon); POWER CONSUMPTION 1.2W at 117 VAC, 50-60 Hz; DIMENSIONS: 9 1/4 x 6 x 2 3/4". Shpg. wt., 5 3/4 lbs.

44 R 12201 No Money Down* Net 52.45

SHURE LEVEL-LOC CONTROLLER




60⁰⁰

MODEL M62V "Level Loc" Audio Level Controller, now with a variable input level control. Automatically locks the volume level of a sound system, virtually eliminating annoying volume changes, blasting, fadeout, etc. Level is predetermined by setting a single switch. Frequency Response: 20-20,000 Hz \pm 2 db. Input Impedances: 100K and 500 ohms; output approximately 500 and 10 ohms. Cannon-type connectors. Gain: low Imped. input to low output is 0; to high output is +22; high Imp. input to low output is +22; to high output is 0. Battery operated, 2 1/2 x 1 1/4 x 5 1/4". Shpg. wt., 4 lbs. Complete with battery.

44 R 75976 No Money Down* Net 60.00
 99 R 60212 Extra 9 volt battery Net .29

LAFAYETTE TRANSISTORIZED MIKE MIXER



5⁶⁰

• Up to 4 Channels
 • Matches High Impedance Microphones
 • Modern Solid State Design

Mixer controls high impedance signals from mikes, phonos, recorders or tuners. Standard 2-conductor phone inputs, standard RCA type phono pin plug output, 9 volt battery. Imported.

99 R 45353 Monaural Mixer Shpg. Wt., 1 1/2 lbs. Net 5.60
 99 R 60212 Battery for above Net .29

SHURE MICROPHONE MIXER



84⁰⁰

The Shure M68 is a fully transistorized professional mixer providing for the utmost flexibility in use. It has four microphone channels plus an auxiliary channel. There are five gain controls (an individual one for each channel) plus a master gain control. There is instantaneous and independent selection of high or low impedance on each of the microphone inputs. Male Cannon-type input receptacles. Outputs to match high or low impedance microphone inputs or high imp., high level auxiliary input. Size: 2 1/2 x 1 1/4 x 5 3/4".

44 R 75588 No Money Down*. Shpg. wt., 5 3/4 lbs. Net 84.00
 MODEL M68FC. M68 above but with female Cannon-type receptacles.
 44 R 75851V No Money Down* Net 90.60

REVERBERATION MIXER

MODEL M68RM. Similar to M68FC above, except has built-in adjustable intensity reverb for special effects. Master volume control. Four inputs, and can be combined with M68 or M68FC for more inputs. Jack for use with remote reverb. 28 VDC jack. 40-20,000 Hz. Size: 2 1/2 x 1 1/4 x 5 3/4". For 105—130 volt AC, 50/60 Hz.
 44 R 75877Y No Money Down*. Shpg. wt., 8 lbs. Net 117.00

SHURE STEREO MICROPHONE MIXER



114⁰⁰

Model M688. Designed for use with stereo tape recorders and sound reinforcement systems. It has four dual impedance microphone inputs—three switchable to either left or right channel and the fourth with a pan control. Individual volume controls plus a stereo master volume control. Mono/Stereo switch. Stereo high impedance, high level outputs. 120 VAC or 30 VDC operation, Shpg. wt. 7 lbs.
 44 R 76115 No Money Down* Net 114.00

SHURE AUDIO MASTER




96⁰⁰

MODEL M63. For maximum control flexibility with any high level input source. Works in conjunction with the Shure M68 Series of mixers. Provides the means for correction of room acoustics, to reduce feedback, to provide special sound effects, for recording, to reduce stand and stage noise, etc. Has VU meter to monitor audio level. Five types of outputs: 600 ohm balanced line, high impedance high level, high and low impedance microphone levels, and headphone jack for monitoring. Variable high pass and low pass 6 db per octave filters. Bass and treble tone controls. Two 30 VDC jacks and an AC receptacle. Frequency Response: 20-20,000 Hz. Size: 2 1/2 x 1 1/4 x 5 3/4". For 105-130 volts, 50/60 Hz AC, or 30 VDC.
 44 R 75844 No Money Down*. Shpg. wt., 4 3/4 lbs. Net 96.00

Microphone Stands — Booms — Connectors

ATLAS MICROPHONE STANDS AND BOOMS



Model MS-10C Full Grip Mike Stand. Economical mike stand featuring "Full-Grip" clutch mechanism for fast quiet adjustments without slipping and wear. Functionally designed base assures maximum stability and includes self-leveling, shock-absorbing pads plus 3 "anti-tip" points. Full chrome plated tube assembly. Terminates in a $\frac{3}{8}$ "-27 thread. Base dia. 10", finished in gray shrivel. Height adj., 35 to 63". Shpg. wt., 10 $\frac{1}{4}$ lbs.

44 R 10031W Net 8.91

Model MS-12C. As above but heavier and tube extends to 62".

44 R 10049 Shpg. wt., 11 $\frac{1}{4}$ lbs. Net 9.50

Model MS-11C. As above but with full chrome finished base.

44 R 10056 Shpg. wt., 10 lbs. Net 11.58

MODEL CS-52. Handsome, slim, low profile 15" gray base with chrome tube. Height adjusts from 34 to 62". Shpg. wt., 10 lbs.

44 R 10312 Net 10.62

Model MS-12S "Sleeve-Action" Mike Stand. New mike stand featuring a fully automatic means of height adjustment. To lower the stand, just press on the "Sleeve Action" control. To raise the stand, any point on the tube can be grasped. Quiet and smooth action. Ht. 39 to 62". 10" dia. gray base, chrome tube. $\frac{3}{8}$ "-27 thread.

44 R 10064 Shpg. wt., 9 $\frac{1}{4}$ lbs. Net 19.20

Model CS-32 Demountable Stand. Revolutionary in design, this mike stand is fully collapsible to fit in amplifier or speaker-carrying case. No tools needed. Self-leveling legs are skid-proof. Features "Full-Grip" and "Velvet Action." Adjustable from 36 to 64 in. Fully chrome plated. $\frac{3}{8}$ "-27 thread. Shpg. wt., 5 $\frac{1}{4}$ lbs.

44 R 10072 Net 11.01

Model CS-33. As above but with ht. adj. of 26-64". Collapses to 22 $\frac{1}{2}$ ". Shpg. wt., 4 $\frac{3}{4}$ lbs.

44 R 10080 Net 12.98

MS-25—Professional stand, featuring "Safety Air Lock Cushion." Prevents accidental slippage of telescoping section, smoothly lowers on cushion of air. Grey and chrome base. Ft. adj. from 38" to 67". Oversize chrome tubing with $\frac{3}{8}$ "-27 adapter. Shpg. wt., 28 $\frac{1}{2}$ lbs.

44 R 10288 Net 24.00

DS-14—Contemporary motif desk stand. Slims elongated, slim mikes. Gun metal, shivel base with protective felt pads. 3" polished chrome upright tube with $\frac{3}{8}$ "-27 thread. Shpg. wt., 1 $\frac{3}{4}$ lbs.

44 R 10296 Net 3.68

Model DS-5. "Velvet Action" Desk Stand. Same quality as floor models. Base dia. 6". Gun metal shrivel finish. Fixed ht. 4".

44 R 10098 Shpg. wt., 2 $\frac{1}{2}$ lbs. Net 2.99

Model DS-7. Like DS-5 but with ht. adj. 8 to 13". Shpg. wt., 3 lbs.

44 R 10106 Net 4.92

Model TS-8. Adjustable Stand. A decorative and fine appearing stand suitable for use on a banquet table. Features quiet "Full Grip, Velvet Action" control. Adjustable from 14 $\frac{1}{2}$ " to 26". Base diameter 8". Fully chrome-finished base and tube assembly. Shpg. wt., 5 $\frac{3}{4}$ lbs.

44 R 10114 Net 9.15

Model BS-36. Professional boom stand. Has removable 62" boom with gyromatic swivel joint to keep mike positioned. "Safety Air-Lock Cushion" eliminates slippage. Super-chromed tubes adjust 48" to 72". Chrome and gun metal base. Shpg. wt., 29 lbs.

44 R 10122W No Money Down Net 59.85

Model BS-36W. Same as above but with swivel casters. Wt., 36 $\frac{1}{4}$ lbs.

44 R 10338W No Money Down Net 67.80

Model BS-7. Like BS-5 but with ht. adj. 8 to 13". Shpg. wt., 3 lbs.

44 R 10130 Net 6.92

FLEXO MIKESTER

Model 1. Versatile mike stand with an extremely flexible arm, providing wide range of adjustment. Swings out 36" in any direction. Ideal for use in radio broadcast or recording studios, offices, airport, switchboard, theatres, night clubs, schools, hotels. Handles any mike up to 4 lbs. in weight. Clamps or screws to any horizontal or angular surface up to 3" thick. Shpg. wt., 6 lbs.

44 R 10148 Net 19.95

FLEXIBLE GOOSE NECKS

Model GN-13 Goose Neck. 13" long for complete adjustment of mike $\frac{5}{8}$ "-27 thread. Chrome finish. Shpg. wt., 10 oz.

44 R 10262 Net 2.37

Model GN-19. As GN-13 but 19" long. Shpg. wt., 1 $\frac{1}{4}$ lbs.

44 R 10270 Net 3.35

PORTO-STAND • All-In-One Microphone Stand—Baby Boom—Cable Hanger—and Carrying Case

29.16

Professional portable microphone stand—boom combination eliminates time and trouble involved in assembling and disassembling. Once assembled, 2 lock-on connectors provide instant detachment of boom and microphone from stand. Complete stand and 31" baby boom fit into the rugged black vinyl carrying case. Stand has fully chromed tube section with a "full grip" clutch assembly for quick, silent height adjustments without slipping. Height range is 34"-62". Tip-proof 10"-12 lb. base assures excellent stability. Shpg. wt., 19 $\frac{1}{2}$ lbs.

44 R 10429W Net 29.16

ATLAS MICROPHONE ACCESSORIES

Mike Flanges And Extension Rods. For neat and permanent mounting. Fits $\frac{3}{8}$ "-27 mikes. Base dia., 1 $\frac{1}{4}$ "

Extension rods, male on both ends. Av. shpg. wt., 5 ozs.

44 R 10155 AD-12 Male Flange Net .92

44 R 10163 AD-11 Female Flange Net .90

44 R 10171 AD-8-6" Ext. Rod Net .83

Mike Adapters. For adapting special fittings, Wt., 10 oz.

AD-1 $\frac{3}{8}$ "-27 female to $\frac{1}{2}$ " male thread (RCA) Net .83

44 R 10189 AD-2 $\frac{1}{4}$ " female pipe to $\frac{3}{8}$ "-27 male Net .62

44 R 10197 AD-4 $\frac{3}{4}$ " long $\frac{3}{8}$ "-27 male running thread Net .50

44 R 10213 AD-5 $\frac{3}{8}$ "-27 female to $\frac{3}{8}$ "-27 female coupling Net .68

44 R 10221 **Model SW-1 Gyromatic Swivel.** Permits any mike to be locked at any angle. $\frac{3}{8}$ "-27 thread. 4 $\frac{1}{2}$ " long.

44 R 10247 Net 4.47

Model SO-1 "Snap-On" Mike Attachment. Quick and safe. For all mikes and stands. Two "Snap-On" sections.

44 R 10254 Net 2.66

Model LO-2 "Lock-On" for quick disconnect of mike from stand. Positive lock when on stand, pushbutton release.

44 R 10023 Net 3.15

Model CO-1. Connect-on 360° swivel attachment. Mounts instrument or second microphone to mike floor stand or to table or desk top. Shpg. wt., 8 oz.

44 R 10427 Net 3.51

Model TM-1. Twin microphone mount for installation of two or three microphones on mike stand, podium or lectern top. Shpg. wt., 8 oz.

44 R 10445 Net 6.00

AD-4 AD-5 AD-11 AD-12

AS-1 AS-2

AB-6

SO-1

SW-1

CO-1 LO-2

TM-1



LAFAYETTE


Microphones

Dynamic Microphones

LAFAYETTE'S REVOLUTIONARY "DCD" DUAL CARTRIDGE HI-FI DYNAMIC

- Wide-range Frequency Coverage by 2 Independent Cartridges
- Quick Adaption for Floor Stand or Hand-Held Use

Lafayette's "DCD" high impedance (50K ohms) dynamic incorporates a new engineering concept designed to overcome the limitations on high quality wide frequency response imposed by ordinary single cartridge microphones. The "DCD" has 2 independent cartridges, one each for the high and low frequency ranges in a carefully engineered acoustic design. Response is 50 to 15,000 Hz. Output is —55 db. Pattern is omnidirectional. Has non-inductive transformer to eliminate effects of external alternating fields. On-Off slide switch. Die cast body is finished in satin-black and gleaming chrome. Black metal desk stand. Comes with adapter for mtg. on desk stand or floor stand and 54" detachable cable. Sizes: mike 6 $\frac{1}{4}$ "x1 $\frac{1}{4}$ "O.D.; base 4 $\frac{1}{2}$ " diam. Imported. Shpg. wt. 2 lbs. Net 17.95




17⁹⁵

DCD

LAFAYETTE DUAL IMPEDANCE DYNAMIC MIKE

- Designed Specifically for High Quality PA Applications
- Omni-directional Pattern at all Frequencies

A superb dual impedance, omni-directional dynamic microphone. Designed for high quality PA applications. Superior anti-feedback properties. Allows close talking without boom or bass accentuation. Features pop-proof wire mesh grille. Special filler minimizes wind effect. Attractive chrome plated frame of modern design. Equipped with on-off switch. Freq. Response 100-10,000 Hz. Sensitivity: —58db at 30K. Mylar diaphragm for "pop" and "blast" proofing. Dual impedance: may be shifted from high impedance to 250 ohm low impedance by means of a cable connection. Mike tiltable thru 90° arc. For all standard $\frac{3}{8}$ "-27 stands. Size: 7 $\frac{3}{4}$ "x1 $\frac{1}{2}$ " Dia. With 20 ft. detachable cable with mike plug at one end. Imported. Net 12.95



12⁹⁵

Dual Impedance

LAFAYETTE MODERN DYNAMIC

- Dual Impedance
- Omni-directional

A lightweight non-directional dual impedance: (High 50K; Low 250 ohms) selectable at cable with a fine response of 100-10,000 hertz. Output —60 db. For use either as hand-held or on any standard $\frac{3}{8}$ "-27 desk or floor stand. Adapter supplied. Has 20 ft. detachable cable with mike plug. On-off slide switch. Tapered metal case finished in satin-black and aluminum. Size: 7 $\frac{1}{2}$ "x1 $\frac{3}{8}$ " diam. Wire mesh grille for protection against "pop" or wind blast. Net 10.95



10⁹⁵

Modern

LAFAYETTE DELUXE BALL DYNAMIC

- Dual Impedance
- For High Quality PA and Recording
- Complete with Stand

The most modern design features dual impedance: high (50K ohms) or low (250 ohms) selectable at cable end. Pattern is omnidirectional. Output at high impedance is —59 db. Frequency response is 100-10,000 Hz. Has on-off switch. Ball screen insures against "pop" and wind blast. Die cast case is 6 $\frac{1}{4}$ " long. Max. diam. of ball 2 $\frac{1}{8}$ ". Finished in satin aluminum. 6 ft. detachable cable with mike plug at one end. With black metal desk stand and adapter for any standard $\frac{3}{8}$ "-27 stand. An excellent general purpose mike. Net 14.95



14⁹⁵

Deluxe Ball

LAFAYETTE PA DYNAMIC MICROPHONE

- Press-to-Talk
- Integral Desk Stand
- Dual Impedance

Ideal for public address work. Integral desk stand has press-to-talk switch with optional locking feature. Dual impedance: 50K ohms and 250 ohms. Dynamic with omni-directional pattern, output of —60 db and frequency response of 50-9,000 Hz. Metallic green finish. 7 ft. cable. Size: 7 $\frac{7}{8}$ "H; base 5 $\frac{1}{2}$ "x3 $\frac{3}{8}$ "W. Imported. Shpg. wt., 2 $\frac{1}{2}$ lbs. Net 12.95



12⁹⁵

PA Dynamic

Dynamic Microphones

LAFAYETTE ENTERTAINERS MIKES

For Musical Instrument Amplifiers



A CARDIOID DYNAMIC MIKE

A superb dynamic microphone designed for applications where location of performer in relation to speakers causes feedback and reverberation. Highly directional cardioid pattern. Dual impedance: 50K or 600 ohms, selectable by switch. Response: 100-10,000 Hz. Mylar diaphragm. On/off switch. Modern design, satin chrome finished die-cast case. For hand-held or stand use. Size: 8 1/4" x 1 1/2" D head. With swivel stand adapter and 20 ft. detachable cord with phone plug at other end. Imported. Shpg. wt., 1 3/4 lbs.

99 R 46294

Net 12.95


B DELUXE BALL DYNAMIC MIKE

- For Hand and Stand Use

Modern design features dual impedance—High 50K ohms, or low 250 ohms. Omni-directional, 100-10,000 Hz. Has on-off switch. Ball screen insures against "pop" and wind blast. Die-cast, finished in satin aluminum. Size: 6 1/4" long, max. diam. of ball 2 1/4". Complete with detachable 20 ft. cable and phone plug. Black metal desk stand and adapter for any 3/8" -27 floor stand. Imported. Shpg. wt., 3 lbs.

99 R 46203

Net 16.95



LAFAYETTE PA DYNAMIC

An excellent general purpose dynamic microphone for PA and Paging, etc. Designed for flexibility in use, it may be hand-held, mounted on any 3/8"-27 stand. Frequency range 100-10,000 Hz. Output —58 db, high impedance (50K ohms). Omnidirectional pick-up pattern. Has on-off slide switch. Gleaming black body with chrome head. Tapered body size 6 3/4" long, max. O.D. 1 1/4". Complete with 4 1/2 ft. detachable cable with mike connector, adapter for stand mounting. Imported. Shpg. wt., 1 1/2 lbs.

99 R 46369

Net 7.95

LAFAYETTE DYNAMIC PA MICROPHONE W/SWITCH

The perfect companion microphone to the solid state mobile PA amplifier. Features a high impact styrol case, hang-up clip and flexible single conductor shielded cable. Omnidirectional pattern mike has output impedance of 300 ohms and output level of —73 db at 1000 cps. Frequency Response: 300-2500 cps. Grey and black case with push-to-talk switch. Imported. Shpg. wt., 3/4 lb.

99 R 45775

Net 4.95

LAFAYETTE 3-WAY DYNAMIC

Uni-directional microphone has cardioid pattern. Excellent for general use wherever feedback or unwanted pickup is a factor. May be hand-held, slipped into its own desk stand or used on lavalier cord. Frequency response 200-10,000 Hz., output —61 db. High impedance (50K ohms). Case is high impact plastic finished in blue and gray. Chrome plated desk stand. Really "fly-weight" mike measures only 3 3/8" x 1 1/2" max. diam. Complete with 5 ft. cord. stand and lavalier cord. Imported. Shpg. wt., 1/2 lb.

99 R 45866

Net 7.95

LAFAYETTE HEAVY DUTY DYNAMIC

12⁹⁵

- 100-10,000 Hz
- High Output

An especially rugged dynamic microphone featuring a wide response of 100-10,000 Hz. and output of —55 db. High impedance (50K ohms). Omnidirectional pattern. On-off slide switch. Very heavy die cast case. Finished in satin chrome. Mounts on any standard 3/8"-27 stand. Size: 4" H x 1". With 18 ft. detachable cable with mike plug on one end. Imported. Shpg. wt., 2 lbs.

99 R 45908

Net 12.95

LAFAYETTE VOICE-ACTUATED MICROPHONE

- Also Operates As Remote Control Dynamic Microphone

Allows a transistorized portable tape recorder to start automatically when sound is picked up by the microphone and stop a few seconds after the sound stops. Designed for recorders having a "Remote" jack for remote Start/Stop switch equipped microphone. Has electronically controlled relay, 3 position switch for voice Control-Off-Remote. Threshold sensitivity control adjustable for varying noise level locations. In "Remote" position, it operates as a dynamic microphone with remote control switch. Complete with cord, plugs, and instructions. With 9V battery. Imported. Shpg. wt., 3/4 lb.

99 R 46047

Net 14.95

9V Battery For Above

99 R 60212

Net 2.95

LAFAYETTE VERTICAL DYNAMIC MICROPHONE

6⁹⁵

- Ideal For Tape Recording and P.A.
- Smooth Omnidirectional Sound Pickup

A highly versatile studio-type dynamic microphone which is equally at home with the tape recorder and public address sound systems. Lightweight, and it can be mounted on any standard 3/8"-27 stand. Has omnidirectional polar pattern. Frequency response: 100-10,000 hertz. High output, —54 db. Impedance, 50,000 ohms. Smart, durable chrome finish, with silver grey screen. Complete with self-adjusting swivel, standard 3/8"-27 stand thread and non-detachable 5 ft. cable. Dimensions: 5" H x 1 1/2" W. Imported. Shpg. wt., 3/4 lb.

99 R 45933

Net 6.95



LAFAYETTE MICROPHONES

Economy Mikes and Miniature Mixers




4-WAY SLIM CRYSTAL MICROPHONE

Only **4⁹⁵**

- Complete With Desk Stand, Lavalier Cord and Bracket and Floor Stand Adapter.

Designed for every possible type of mounting, this slim mike may be hand-held, mounted on the desk stand, used as a chest mike with the lavalier cord and bracket, or mounted on any standard $\frac{3}{8}$ "-27 floor or desk stand with adapter supplied. Good clean reproduction. Frequency response 50-9,000 Hz. Output, —65 db. Equipped with on-off switch which may be used as press-to-talk or locked into "on" position. Brushed aluminum body is 5" long with 54" cord. Black oval base is $3\frac{3}{8}$ "x $2\frac{1}{2}$ " W. Imported.

99 R 45874 Shpg. wt., 1 lb. ... Net 4.95



TINY CRYSTAL MIKE



LAFAYETTE QUALITY CRYSTAL MICROPHONE

4⁵⁰

- Die Cast Case



response 50 to 10,000 Hertz. Output level —52 db provides ample output for use with low gain amplifiers. Uses quality moisture sealed crystal; Die cast case in rich green baked enamel finish, with chrome grill. Completely equipped with 5 feet of shielded cable. Mike may be used on any stand with $\frac{3}{8}$ "-27 thread. Grill diameter $2\frac{3}{4}$ ", depth $4\frac{1}{4}$ ". Height $4\frac{1}{2}$ ". Imported. Shpg. wt., 1 1/4 lbs.

99 R 45122 Net 4.50

- For Desk-Top, Hand-Held Use
- Full —55 DB Output Level
- Excellent Frequency Response

An attractive, specially engineered general purpose crystal mike for desk-top or hand-held use. Excellent frequency response. Output level —55db. Only $1\frac{3}{8}$ " in diameter. Includes 5-ft. of shielded cable for connection to tape recorders, public address amplifiers and radios. Chrome plated stand. Imported. Shpg. wt., 6 ozs.

99 R 45437 Net 2.49

LAFAYETTE MINIATURE MIKES & CARTRIDGES



1⁸⁹

(A) MINIATURE DYNAMIC MIKE

Rugged—metal encased—to resist mechanical shock and variations in heat and humidity. Measures only $1\frac{1}{4}$ " dia. x $5/16$ " thick. High sensitivity in the voice range. Frequency response 300 to 5000 Hz. 600 ohm impedance. Output —73 db. Includes 4" flexible lead terminals. Imported. 2 ozs.

99 R 45270 Net 1.89



1¹⁹

(B) SUBMINIATURE CRYSTAL MICROPHONE

An extremely sensitive and small crystal microphone similar to the round types but for replacement use in hearing aids where a rectangular shape is required. Measures: $1\frac{3}{8}$ "x $1\frac{3}{4}$ " deep. Imported. Shpg. wt., 2 ozs.

99 R 45189 Net 1.19



99^c

(C) CRYSTAL CARTRIDGE

Crystal microphone cartridge with heavy flexible rubber cushioned rim designed for speedy, economical repair. Replacement for Astatic, Shure, and many other popular microphones. Overall diameter 2", depth $1/2$ ". Output —52 db. Excellent frequency response. Imported. Shpg. wt., 3 ozs.

99 R 45130 Net .99



LAPEL MICROPHONE

1⁹⁵

A sensitive general purpose crystal microphone designed to attach to your lapel for situations requiring both mobility and the full use of both hands. Only $1\frac{1}{8}$ " in diameter. Excellent frequency response. Output level —55 db. Chrome plated case and clip for attaching to lapel. Includes 5 ft. shielded cable. Imported. Shpg. wt., 4 oz.

99 R 45106 Net 1.95

GENERAL PURPOSE MIKE

2⁹⁸



- May Be Hand-Held or Suspended By Lavalier Cord

A crystal microphone for use either as a hand-held or as a breast mike. Silver colored lavalier metal chain and holding bracket. Good frequency response with an output of —53 db. Aluminum alloy case with black baked finish and silver screen. 6' cord. $2\frac{3}{8}$ "x $1\frac{1}{8}$ " max. diam.; convenient to hold. Shpg. wt., $\frac{1}{2}$ lb. Imported.

99 R 45957 Net 2.98

LAFAYETTE MINIATURE AUDIO MIXERS



(A) Performs any mixing operation where 2 high impedance input channels are connected to a single, mixed high impedance input channel. Each input has its own level control. Momentary switch protects speaker while inserting into system. Shielded, chrome plated housing. Has 2 RCA-type female input jacks and an RCA-type male phone plug output. $2\frac{3}{4}$ "x $1\frac{3}{4}$ "x $\frac{7}{8}$ " overall. Imported. Shpg. wt., $\frac{1}{4}$ lb.

99 R 10134 Net 2.29

(B) Same as above except output is standard phone plug. $3\frac{1}{4}$ "x $1\frac{3}{8}$ "x $1\frac{1}{8}$ " overall. Imported. Shpg. wt., $\frac{1}{4}$ lb.

99 R 10142 Net 2.39



SWITCHCRAFT AUDIO MIXERS

2-input hi-impedance mixers. Record sound-on-sound. Record music direct and dub your voice at the same time. Record from 2 mikes at once. Separate gain controls for each channel allow fading. Shielded housing. Size: $2\frac{1}{2}$ "x $1\frac{1}{2}$ "x $1\frac{1}{4}$ ". Shpg. wt., 6 ozs.

Type 310. Two 2-cond. phone jack inputs to 2-cond. phone plug output.

24 R 88666 Net 5.88

Type 311. As above but has long output plug to fit recorders with recessed jacks.

24 R 88674 Net 5.88

Type 313. As above but with short Revere plugs and jacks for std. or short phone plugs. For all Revere/Wollensak recorders.


24 R 88518 Net 5.88

Type 320. Male mike connector inputs and female mike connector output.

24 R 88658 Net 5.88

RECORDING — MUSICAL INSTRUMENT — WIRELESS MIKES

LAFAYETTE RECORDING MICROPHONES



(A) LAFAYETTE PROFESSIONAL DYNAMIC

- Specially Designed for Transistorized Recorders

Recommended for all high quality recorders and particularly solid-state units. Has a wide frequency response of 80-15,000 Hz. High impedance (10K ohms) with an output of —65 db. Die cast satin-black body with aluminum trim. Slim tapering design. May be hand-held, used on desk stand supplied or mounted in any 3/4" x 27 stand. Black stand with aluminum trim. Mike is 5 1/2" x 1 1/4" dia. with 8 ft. attached cord and standard phone plug. Stand is 4 1/2" x 2 1/2". Imported. Shpg. wt., 1 1/4 lbs.

99 R 45882

Net 14.95

(B) LAFAYETTE DELUXE DYNAMIC

For fine recording and general use, this slim beauty may be hand-held, placed on its own desk stand, used as a lavalier mike or mounted on any standard 5/8" x 27 stand. Omnidirectional pattern gives wide coverage. Wide range response from 100 to 10,000 Hz. Dual impedance: 50K and 250 Ohms. Output —64db. All metal. Die case base and mike finished in handsome satin-chrome. 5 ft. cable. Mike only 3 7/8" L x 3/4" diam. Stand 3 3/4" x 2 1/4" with stand, lavalier cord and bracket and stand adapter. Imported. Shpg. wt., 1 lb.

99 R 45924

Net 8.50



(C) LAFAYETTE STANDARD DYNAMIC

An outstanding value, this featherweight dynamic microphone is attractively styled in a tapering design, and finished in handsomely contrasting black with aluminum trim. It may be hand-held or used on the small desk stand supplied. The omni-directional pattern picks up sounds from all sides. Assures wide coverage. Impedance is 10,000 ohms. Frequency Response is 70 to 9000 Hz ± 7 db and the output is —67 db. Has a built-in on-off switch. Comes complete with 6 ft. cord with standard phone plug. Size: 6 1/4" L x 7/8" diam. Imported

99 R 46161

Shpg. wt., 1 lb. Net 6.95

(D) LAFAYETTE TINY DYNAMIC MIKE

- For Solid State Recorders

This is an excellent quality dynamic microphone which may be set on table or desk top or hand held. Impedance is 600 ohms and is designed for use with solid-state recorders requiring relatively low impedance dynamic microphones. Used with many Lafayette recorders. Size is 3 1/4" L x 3/4" D. Supplied with 5 ft. of cable terminating in standard phone plug. Imported. Shpg. wt., 8 oz.

99 R 46302

Net 5.95

LAFAYETTE REMOTE CONTROL CASSETTE MIKE



3.95

Remote control dynamic microphone for table top or hand use. Impedance is 200 ohms for cassette recorders requiring low impedance mikes. Response: 100 to 9,000 Hz. Has on-off switch. Size: 4 1/2" L x 7/8" dia. With 5 ft. cable terminating in dual miniature plugs for mike and remote control. Miniature 1/4" and sub-miniature 3/8" plugs fit most cassette recorders. Complete with prop stand. Imported. Shpg. wt., 5 oz.

99 R 46344

Net 3.95

LAFAYETTE FM WIRELESS MICROPHONE

19.95

With FCC Type Approval

- Transmits Clearly up to 150 Feet
- Can Be Used With Any 88-108 MHz FM Tuner, FM Radio, FM Portable or FM Auto Radio
- Requires No Bothersome Connecting Cables
- Clear, Static-Free Performance

A transistorized FM transmitter and microphone which transmits up to 150 feet with perfect clarity to any 88-108 MHz FM receiver. Has hundreds of practical uses—for entertainers and theatrical productions, in-plant communications, baby sitting, inventory and survey situations and many other remote sound pick-up applications without interfering connecting cables. Has sensitive built-in microphone and is fully shielded against interference. Approved by FCC. Tunable from 88-108 MHz. Operates on inexpensive 9 V transistor battery (not supplied). Compact: 4 3/4" x 1" x 1". Lightweight: only 3 1/2 oz. Includes antenna, tuning tool and operating instructions. Imported.

Shpg. wt., 10 oz.

99 R 46393

99 R 60212 9V Battery—1 required

Net 19.95

Net .29

LAFAYETTE MUSICAL INSTRUMENT MICROPHONES

DELUXE GUITAR MICROPHONE

- Individual String Controls
- 2 Pickups Tone Control
- 2 Volume Controls

This unusual microphone gives the utmost in versatility of tonal effects. Each of the 2 sensitive magnetic pickups has 6 adjustable heads so you may vary the power of each individual string. Each pickup has its own separate volume control. Combining these with the overall tone control, makes available an almost infinite adjustment of sound for any requirement. Comes complete with 6 ft. removable cord with mike plug at one end and standard phone plug for amplifier at other. For F hole guitars. Size: 10 1/2" long. With bracket and mounting accessories. Imported. Shpg. wt., 3/4 lb.

99 R 45833

Net 8.95

ROUND HOLE GUITAR MICROPHONE

For use with Spanish guitar, ukuleles or other round hole instruments. Magnetic pickup with 6 adjustable heads so you may vary the power of each string. It has separate tone and volume controls. 7 ft. cable with standard phone plug for musical amplifier. Finished in black and gleaming nickel. Simple to mount, easily adjustable. Imported.

99 R 46351

Shpg. wt., 1 lb. Net 6.49

MUSICAL CONTACT MICROPHONES

Easily attached to all stringed instruments. Provides rich reproduction. Clamp slips under sounding board cutout. With 8 ft. cable. 1 3/4" long. Imported. Shpg. wt., 4 oz.

99 R 45767

With volume control. Net 1.99


HARMONICA CONTACT MICROPHONE

This is a fine quality, sensitive, crystal contact microphone with a high output that is especially designed to fit harmonicas. Installation is simple. It is sturdily built and measures only 1 5/8" L x 3/4" W x 3/8" D. Complete with 7 ft. shielded cable. Imported. Shpg. wt., 3 oz.

99 R 45163

Net 1.49

LAFAYETTE Top Performing CB Microphones



A DYNAMIC CB MICROPHONE

• For Use With Low Impedance Solid State Transceivers
 Super efficient low impedance dynamic microphone. Housed in attractive, professionally styled, gray and black, high-impact plastic case. Fits snugly in palm of hand. Top-performing coiled cord consists of 3 conductors plus shield and terminates in 4 prong miniature plug. Wired for relay switching. Mates directly with microphone input chassis socket of Lafayette HB-500, HB-500A, HB-555, HB-525, HB-525A, HB-525B, HB-525C, HB-625, HB-23, HE-20T, HE-20D, HA-450T, HB-600, and Telsat 23. Size: 3½x2¾x1¼". Imported.
 99 R 46187 Shpg. wt., ¾ lb. Net 6.95

B NOISE CANCELLING CB MIKE


A high output (-48 db) low noise cardioid pattern PTT ceramic mike excellent for mobile and base applications. Minimizes noise pickup from rear to avoid interference with audio input. Rugged, high-impact Cyclocac dark grey case with 3 conductors (one conductor shielded) coiled cord. Fits comfortably in palm of your hand. Frequency response 300-3000 Hz. For use with tube-type CB equipment. With hang-up clip. Less plug. Shpg. wt., ¾ lb.
 44 R 45011 Net 6.95

Miniature Microphone Plug. For connection to Comstat 19, 23, 25, 25A, 25B, HB-444, A, and Comstat 23 Mark V. Mark VI. Imported.
 99 R 62630 Net 1.49

MICROPHONE MOUNTING CLIP

Standard microphone mounting clip. Accommodates most stud mounting CB and Ham microphones. Attaches to metal case or dash board with 2 screws.
 Shpg. wt., 2 oz.
 99 R 31841 Net 50

RCA STARMAKER MICROPHONES



Model HK-96. An excellent cardioid dynamic microphone for stage, recording or broadcast use. Dual impedance 200 or 15,000 ohms; response: 50-15,000 Hz, 3 position bass roll-off switch reduces rumble. Complete with windscreen, slip-on holder, 20 ft. shielded cable and attaché case. Black and chrome finish. Size: 9¼ x 1.6" diameter. Shpg. wt., 3 lbs.
 44 R 21004 No Money Down* Net 37.00

Model HK-98. A ball-type, omnidirectional mike ideal for high quality music and voice applications. Dual impedance 200 or 15,000 ohms; response: 40-17,000 Hz with on-off switch. Black and satin chrome finish. Complete with windscreen, adjustable swivel mount, 20 ft. shielded cable and attaché carrying case. Size: 7½ x 1.9" diameter.
 44 R 21012 Shpg. wt., 2½ lbs. Net 30.00

C CB BASE STATION CERAMIC MICROPHONE

For tube-type CB transceivers. Efficient, attractive high impedance desk ceramic microphone. With convenient push-to-talk button plus lock-switch for prolonged transmission, 3-conductors plus shield for normal relay or electronic switching, 3¼x5¼x7¾". Imported. Shpg. wt., 1½ lbs.
 99 R 46070 Less plug. Net 11.95

Miniature Microphone Plug. For connection to Comstat 19, 23, 25, 25A, 25B, HB-444, A, and Comstat 23 Mark V, Mark VI. Imported.
 99 R 62630 Net 1.49

D BOOM MIKE/HEADSET

Free hands for safe driving. Perfect answer to your CB and Ham mobile needs. For use with VOX or foot switch for transmit-receive changerover. Lightweight and comfortable with 8-ohm earphone. Crystal mike for high output and full modulation. Boom and headband adjust to individual preference. Mike mounted on swivel. Finished in chrome and two tone plastic. With 5 ft., 4-conductor cable. Imported. Shpg. wt., ¾ lb.
 For tube transceivers
 99 R 25652 Net 5.99

MAGNETIC

MICROPHONE HOLDER 79¢

• For CB, Ham and Commercial Mobile Radios



Either clip to microphone for ready-to-use magnetic mike or attach to any steel surface and slip microphone in holder. Fits most microphones. Imported wt., 3 oz.
 99 R 45535 Net .79

E CB CRADLE HAND SET

Modernize your present fixed of mobile CB station with these telephone style handsets. Attaches to dashboard, side of unit or wall of fixed station. Switch in the cradle automatically disconnects the speaker when the handset is lifted. The microphone is activated by means of a push-bar, push-to-talk switch. Ideal for use in heavy traffic, loud background noise area, at home or in the office for privacy. Shpg. wt., 2 lbs.

For Solid State Transceivers
 42 R 65039 Net 24.95

For Tube-Type Transceivers
 42 R 65047 Net 24.95

Microphone plug for connection to solid state HB-500, A, HB-555, HB-600, A, HB-525, A, B, C, D, HB-625, HE-20T, HB23, Telsat 23, 50, 150, Micro 12.
 99 R 62838 Net .99

Speaker Plug for insertion into external phone/speaker jack.
 99 R 62101 Net .25

Microphone plug for connection to tube-type Comstat 19, 23, 25, 25A, 25B, HB-444, A, Comstat 23 Mark V, VI.
 99 R 62630 Net 1.49

Speaker Plug for insertion into external phone/speaker jack.
 99 R 62218 Net .30

F "MITY-MITE" CB CERAMIC MICROPHONE

Ceramic microphone expertly designed and professionally styled for real performance. Fits snugly in palm of hand for effortless operation. Features a "Long Life" ceramic element. Three conductors plus shield connected for electronic switching. Includes instruction sheet for conversion to relay switching. For all high impedance input CB transceivers (tube type). High impact plastic case and 4 foot coiled cord. 1½x¾x3¼".

99 R 45791 Wt., 8 oz. Imported Net 4.95
 Miniature Microphone Plug. For connection to Comstat 19, 23, 25, 25A, 25B, HB-444, A, and Comstat 23 Mark V, Mark VI. Imported.
 99 R 62630 Net 1.49

ASTATIC MICROPHONES



MODEL D-104 MICROPHONE

Used extensively by radio amateurs for its high intelligibility and "punch." Responds with rising characteristics from 500-4,000 Hz. High output sealed crystal element. Output level -46 db. Chrome finished mesh grille and body. With 5-ft. cable and adapter to ¼"-27 thread. Shpg. wt., 1¾ lbs.
 44 R 14017 Less Stand Net 18.60

MODEL GD-104. Same as D-104 except with grip-to-talk stand. SPST switch.
 44 R 14025 Shpg. wt., 3¼ lbs. Net 30.72



MODEL UG8-D104

The D-104 microphone with the UG8 grip-to-talk stand. Described below. DPDT switch.
 44 R 14033 Shpg. wt., 3¼ lbs. Net 37.72

MODEL UG8 STAND
 Die cast, all metal with bar activated DPDT leaf-switch for either momentary or "lock-on." Two switch sections. Noise free, silver contacts rated up to 3 amp DC, 8 terminals for connections, 6 ft., 4 conductor cable. Chrome and gray. 5¼" diam. x 8¼" H. Shpg. wt., 2½ lbs.
 44 R 14041 Net 17.97

Turner Microphones

MODEL "M + 2U" MOBILE MICROPHONE



- Built-in 2-transistor preamp.

"M+2/U" MOBILE MIKE increases signal strength and range. Frequency 300-3000 Hz. Preamp has volume control on rear to adjust modulation for best performance. Complete with battery, dash bracket and 5 ft. coiled cord. For sets with relay switching. 44 R 70183 Shpg. wt., 1 1/2 lbs. Net 30.00 Same for electronic switching. 44 R 70191 Net 30.00 Replacement 7V. mercury battery for above. 32 R 47699 Net 15.70

MODEL "+2" BASE STATION MICROPHONE



- Built-in 2-transistor preamp

"+2" BASE STATION MIKE increases signal strength and range! Frequency response of 300-3500 Hz. Push-to-talk bar with locking switch permits normal PTT operation or VOX. Works with all sets—Relay or Electronic switching! 3 conductor, 1 shield blue, coiled cord. Finished in blue and chrome. Output impedance 5000 ohms. Battery included. 44 R 70167 Shpg. wt., 2 3/4 lbs. Net 36.00 Replacement 9V long life battery for above. 95 R 63729 Net .45

Model "Plus-3" Base Station Microphone



- Transistorized Pre-amp Plus Modu-gard

The "Plus-3" ceramic microphone has a new transistorized pre-amp with volume control plus a new compression amplifier circuit which allows user to talk close or far from the mike without varying the output signal. This prevents mike sputter and sputter. Response: 300-3000Hz. 3 conductor (1 shielded) coiled cord. Touch-to-talk front bar switching with slide lock when desired. Wiring instructions for over 100 popular transceivers. Shpg. wt., 4 lbs. 44 R 70316 No Money Down* Net 45.00 Replacement 9V. long life battery for above. 99 R 63729 Net .45

MODEL NC3500

12⁶⁰



- Mobile Noise Cancelling Microphone

A new noise cancelling ceramic mobile microphone with all the most desired professional features. Peaked for SSB response from 200 to 4,000 Hz, to really cut through the QRM. Recommended by experts for today's new AM/SSB transceivers. The noise cancelling feature really cuts down on mobile background noise caused by passing or on-coming traffic, truck engine roar, etc. Professional all black case with soft rubber lip guard and neoprene coiled cord. Shpg. wt., 1 lb. 44 R 70373 Net 12.60

NEW! MODEL M + 3 MOBILE MICROPHONE



- Transistorized Mobile Microphone with Volume Control and Modu-Gard

A modern excitingly styled transistorized mobile microphone with a compression amplifier circuit which permits full modulation and guards against overmodulation. Slide-action control permits volume adjustment for up to 20 db gain. Modu-gard allows talking close to or far from the microphone without varying the output signal or over-modulating. Ceramic interior with frequency response of 300-4,000 Hz., peaked SSB (rising characteristics). Blue and white case with attractive blue coiled (three conductor, one shielded) cord. Comes with 7V battery and instructions. Shpg. wt., 1 lb. 44 R 70357 Net 33.00 Same as above for electronic switching. 44 R 70365 Shpg. wt., 1 lb. Net 33.00 Replacement 7V Mercury battery for above. 32 R 47699 Net 1.50

33⁰⁰



MODEL 254C

Attractive ceramic microphone with DPDT push-to-talk switch plus lock switch for fixed station operation—either relay or electronic switching. 7 foot 3 conductor (one shielded) straight cable. Response 80-7000 Hz. Output level —54 db. Gray hammertone finish with chrome trim. 7 3/4 x 3 7/8 x 5 1/4" base. Shpg. wt., 2 1/2 lbs. 44 R 70035 Net 21.00

MODEL 254X

Crystal version with output of —48 db. 44 R 70100 Net 21.00

MODEL 454C

Single sideband ceramic mike that is ideal for hams. Output level of —52 db. Frequency response 300-3000 Hz. Push-to-talk front bar plus locking switch gives choice of PTT or continuous VOX operation. For electronic or relay switching. Complete with coiled cord that extends to 5 ft. Size 7 3/4 x 5 1/4" deep. Shpg. wt., 2 1/2 lbs. 44 R 70019 Net 24.00

MODEL 454X

Same as above but crystal with output of —48 db. 44 R 70043 Net 24.00



454C

Ideal for CB use. A rugged push-to-talk ceramic microphone wired for relay operation. Extra-tough polystyrene case; hanger button and standard dash bracket are included. Also neoprene coiled cord, 11 inch retracted. 5-ft. extended. Output, —54 db. Response 80-7000 Hz. Dark grey finish. Shpg. wt., 1 1/4 lbs. 44 R 70027 Net 10.80

MODEL 355C


Mobile ceramic microphone with handy grip-to-talk switch. Comfortable to hold, comfortable to use. Features an output level of —50 db. Frequency response 80-7000 Hz. Tough plastic case. Complete with 5 ft. coiled cord. Shpg. wt., 1 lb. 44 R 70050 Net 12.00

MODEL 866 CARDIOID DYNAMIC

Cardioid dynamic type, high impedance. An excellent sounding mike for music and home recording. Minimum feedback. Response 100-13,000 Hz. 20 ft. cable and plug. With carrying case. Shpg. wt., 2 1/2 lbs. 44 R 70290 Net 24.00



355C



866



766

MODEL 766 BALLADIER MUSICIAN'S CARDIOID DYNAMIC

A ball screen styled cardioid dynamic microphone designed specifically to reproduce the high volume sound of today's musical groups. Excellent cardioid performance accommodates high levels without feedback. A high impedance microphone with 40-15,000 Hz. frequency range. Has on-off switch; built-in blast filter to eliminate "pop" "howl" or wind noise. Rugged stand adapter for in-hand on-stand use. Removable 20 ft. cable with phone plug. Heavy-duty chrome finish. Packaged in individual carrying case. Shpg. wt., 3 lbs. 44 R 70381 No Money Down* Net 45.00

REPLACEMENT CARTRIDGES

Ceramic for "+2" and 360 44 R 70324 Shpg. wt., 3 oz. Net 6.00 Ceramic for "M + 2/U" and "M + 2U" 44 R 70332 Shpg. wt., 4 oz. Net 6.00 Ceramic for 254C, 3500, etc. 44 R 70092 Shpg. wt., 4 oz. Net 6.00

*See Page 22 for Full Credit Details on Easy Pay Plan

SHURE

Microphones Broadcasting — PA



NEW SHURE 545SD "UNIDYNE III"

Slender dynamic unit with completely symmetrical unidirectional pattern. Performs in difficult applications without feedback and sound boom. Acclaimed for its natural reproduction of human voice. Features a new built-in long life magnetic reed "on-off" switch. 50 to 15,000 Hz. Dual impedance. Outputs: 50-250 ohms, —57 db; Hi-Z, —55 db. Chrome, black, swivel adapter, 15 ft. 3-cond. cable. 5/16" x 1 1/4" dia. Shpg. wt., 2 1/2 lbs.

- 44 R 75984 No Money Down* Net 61.20
- Model 545. As above, but, without "on-off" switch. Amphenol type connectors.
- 44 R 75059 No Money Down* Net 57.60
- Model 545S. As above, but with swivel mount contained "on-off" switch.
- 44 R 75042 No Money Down* Net 61.20
- Model 545SD-CM. Same as 545SD but with a prewired Cannon type male connector on the amplifier end of 20' cable.
- 44 R 76123 No Money Down* Net 64.20

"UNIDYNE IV"

Model 548SD. This member of the Unidyne family of feedback-free unidirectional dynamic microphones offers remarkable ruggedness and performance features such as a new long-life magnetic reed "on-off" switch incorporated into the case, improved shock mounting; wind, pop and blast filters; broadcast-type Cannon XLR-3-11c connector; high flexibility cable, etc. Frequency: 40-15,000 Hz. Dual (high and low) impedance with output of —55.5 db, swivel adapter chrome and black case, 15' 2-conductor detachable cable. 1 1/2" D x 1 1/4" L.

- 44 R 75992 Shpg. wt., 2 1/4 lbs. Net 72.00
- Model 548. Same as above but less "on-off" switch.
- 44 R 75653 No Money Down* Net 69.00
- Model 548S. Same as above but with swivel mount contained "on-off" switch.
- 44 R 75646 No Money Down* Net 72.00
- Model 548SD-CM. Same as 548SD but with a prewired Cannon type male connector on the amplifier end of 20' cable.
- 44 R 76131 No Money Down* Net 75.00

555W "UNIDYNE II"

A dependable rugged dynamic microphone for deluxe sound systems. 50 to 15,000 Hz response. Unidirectional pickup prevents feedback. Three-way impedance switch. Output levels: 35-50 ohms. —55db; 150-250 ohms, —56db; Hi-Z, —55 db. Complete with on-off switch, swivel mount. 15 ft., cable. 7/8" x 2 1/4" x 3 1/4". Wt. 3 3/4 lbs.

- 44 R 75018 No Money Down* Net 58.80
- Model 55S. Same as above, without on-off switch. Shpg. wt., 3 3/4 lbs.
- 44 R 75026 No Money Down* Net 57.00

"UNISPHERE I"

Model 565SD. Deluxe ball-type pop-proof unidirectional dynamic microphone. Features new long life magnetic reed "on-off" switch incorporated into the case, dual impedance; low imp. (50-250) ohms output —57 db, high imp. —55 db. Response: 50-15,000 Hz. With swivel adapter and 15 ft. 3 cond. detachable cable, with Cannon XLR-3-11c type connector. Size: 6 3/4" L x 2" D. Shpg. wt., 3 lbs.

- 44 R 76008 No Money Down* Net 67.80
- Model 56S. Same as above but without "on-off" switch. Amphenol type connectors.
- 44 R 75547 No Money Down* Net 64.80
- Model 565S. Same as above but with swivel mount contained "on-off" switch.
- 44 R 75620 No Money Down* Net 67.80
- Model 565SD-CM. Same as 565SD but with a 20' cable terminating in Cannon type male connector.
- 44 R 76149 No Money Down* Net 70.80

"UNISPHERE B"

Model 588SA. A dynamic unidirectional microphone with popular ball-type styling. Features feedback-free cardioid pickup pattern, shock-mounted cartridge, wind, pop and blast filters, lockable "On-Off" switch and a broadcast-type Cannon connector with 15' detachable cable. Includes swivel stand adapter. Response: 50-13,000 Hz. High Imp. Output: —58 db. Satin chrome. 6 1/2" x 2" dia.

- 44 R 75893 Shpg. wt., 2 lbs. Net 39.00
- Model 588SAC. Same as above but with prewired plug end assembly for use as MCIF, MCIM or phone plug.
- 44 R 75885 No Money Down* Net 40.20
- Model 588SB. Same as 588SA above, but with low impedance. Output: —59.5 db, 15' two-conductor cable.
- 44 R 75901 No Money Down* Net 39.00
- Model 588SB-CM. Same as 588SB but with a 20' cable terminating in Cannon type male connector.
- 44 R 76156 No Money Down* Net 42.00

"SPHER-O-DYNE"

Model 533SA. Omnidirectional dynamic probe type. Ideal for entertainers, lecturers. Spherical front with built-in wind, breath and "pop" filter 40-11,000 Hz. High Impedance. Output —55 db. On-off switch, swivel stand adapter and 15 ft. single conductor cable. Chrome case. 6 1/2" x 2 1/4" dia. 2 lbs.

- 44 R 75554 No Money Down* Net 34.20
- Model 533SAC. Same but with prewired plug assembly which can be used as MCIF, MCIM or phone plug.
- 44 R 75711 No Money Down* Net 35.40
- Model 533SAVC. Same as 533SAV above but volume control to regulate amplifier output at microphone.
- 44 R 75935 No Money Down* Net 40.20
- Model 533SAV. Same as 533SAV above but with plug assembly like 533SAC.
- 44 R 75943 No Money Down* Net 39.00

540S "SONODYNE II"

Modern design all-directional microphone. Fine for recording applications and sound systems. Has on-off switch. Adjustable response: 50-13,000 Hz for music, 400-6,000 Hz for speech. Dual impedance: 50-250 ohms and high impedance. Outputs: Hi-Z, —55 db; Low-Z, —56 db. Chrome and black. Swivel mount; 1/2" 27 thread, 15 ft. 2-cond. cable 3/8" x 1 1/4". Shpg. wt., 2 1/4 lbs.

- 44 R 75166 No Money Down* Net 33.60

"UNISPHERE A"

Model 585SA. Rugged dynamic unidirectional "pop"-proof unit with wire-mesh spherical screen. Feedback free. Response 50-13,000 Hz. High impedance. Output —57 db. Chrome and black case. Has on-off switch, adjustable swivel stand adapter and 15 ft. single conductor shielded cable. Size: 6 3/4" x 1 1/4" diam. 2 lbs.

- 44 R 75521 No Money Down* Net 45.00
- Model 585SAC. Same as above but with prewired plug end assembly which can be used as MCIF, MCIM or phone plug.
- 44 R 75687 No Money Down* Net 46.20
- Model 585SB. Same as 585SA except low impedance, output —59 db and 2 conductor cable.
- 44 R 75539 No Money Down* Net 45.00
- Model 585SAV. Similar to 585SA but instead of on-off switch has built-in volume control to change loudness without adjusting amplifier controls. Shpg. wt., 2 lbs.
- 44 R 75612 No Money Down* Net 49.80

Model 585SAVC. Same as above but with plug end assembly like 585SAC.

- 44 R 75695 No Money Down* Net 51.00

"VOCAL SPHERE"

Model 5795B. Omnidirectional dynamic microphone with natural and intelligible voice reproduction. Ideal choice for public-address, entertaining, recording, etc. Extremely rugged. Has built-in wind and breath noise filters. Lockable "On-Off" switch and a broadcast-type Cannon connector with 20' two conductor detachable cable. Includes swivel stand adapter. 50-15,000 Hz frequency response. Low impedance. Output: —59 db. Satin chrome and gray housing. 6 3/4" x 1 1/4" diameter.

- 44 R 75919 Wt., 2 lbs. Net 45.00

"UNIDYNE B"

Model 5155A. Very low priced unidirectional dynamic microphone with a highly effective cardioid pickup pattern which solves feedback and boominess. Ideal for low budget sound systems. Frequency: 80-13,000 Hz. High Impedance with output of —58 db. Has on-off switch and swivel adapter. 15 ft. single conductor non-detachable cable. Chrome and black case. Size: 1 1/2" D x 1 1/4" L.

- 44 R 75661 Shpg. wt., 2 lbs. Net 27.00
- Model 515SAC. Same but with prewired plug-end assembly for use as MCIF, MCIM, or phone plug.
- 44 R 75950 Net 28.20
- Model 5155B-G18. 18" gooseneck mounted low impedance version of Model 515SA. Ideal for language lab, paging and base station. Features a built-in "on-off" push-to-talk switch which controls microphone and relay circuit. 51" cable. Size: 1 1/2" x 25". Shpg. wt., 2 3/4 lbs.
- 44 R 76016 No Money Down* Net 31.80

SWIVEL ADAPTER


390



Model A25B SWIVEL ADAPTER. For Shure models 515, 545, 548, 565, 580, and 588 microphones. For use with standard desk or floor stands. Shpg. wt., 8 oz.

- 44 R 76164 Net 39.00

Electro-Voice Popular Microphones




**664 "VARIABLE D"®
CARDIOID DYNAMIC**

A cardioid "Variable D" (variable distance) microphone designed for top quality PA applications. Cardioid pattern provides a significant front-to-back signal ratio to suppress noise, reverberations and feedback. Allows close talking without booming bass, air blasts or distortion. Non-metallic diaphragm is shielded against dust and magnetic particles. Resistant to extreme conditions of humidity, temperature and vibration. Response 60-15,000 Hz. Output level—58db. High impedance easily lowered to 150 ohms without tools. Standard $\frac{3}{8}$ "-27 thread. Satin chrome finish die-cast case, with ON-OFF switch and 15 ft. 2 conductor shielded cable. 1 7/8" dia. 7 1/4" long. Shpg. wt., 3 1/4 lbs. 44 R 25328 No Money Down* Net 57.00 664G—Same as above but gold finish. 44 R 25336 No Money Down* Net 61.20 664A—Same as above but non-reflecting gray finish. 44 R 25351 No Money Down* Net 57.00

**644 "SOUND SPOT" UNI-DIRECTIONAL
LINE MICROPHONE**

A combination cardioid and distributed front opening makes this the most directional microphone ever. Has better than 2.5 times the working distance of pressure types. Cancellation from the rear and sides exceed 20 db giving virtually complete rejection of unwanted sound. High reduction of wind noise and low sensitivity to shock. Smooth response from 40 to 10,000 Hz, high output—53 db., dual high and low impedance selective. Rear diameter $\frac{23}{32}$ ", length 16". Cable is 16 ft. Shpg. wt., 3 1/4 lbs. 44 R 25476 No Money Down* Net 78.15

**E-V OMNIDIRECTIONAL
MICROPHONES**



631 HAND AND STAND DYNAMIC

High quality entertainers microphone. Omni-directional. Lightweight, rugged, shockproof. Effective 4-stage filter allows closeup use without blasting, pops, or distortion. Silent magnetic on-off switch with removable actuator button. Satin chrome case. Frequency Response: 80-13,000 Hz. Output: —55 db. 16 ft. cable. With stand clamp. Size: 6" L x 1 3/8" head dia., 3/4" shank dia. Shpg. wt., 2 lbs. No Money Down* 44 R 25732 Hi Impedance ... Net 38.70 44 R 25740 Lo Impedance ... Net 38.70

647A LAVALIER DYNAMIC

Tiny size with big performance 70-10,000 Hz. High impedance. Output level, —60 db. 18 ft. cable. Complete with neck cord. Size: 3 3/4" x 3/4" Dia. Shpg. wt., 1 1/2 lbs. 44 R 25195 No Money Down* Net 57.90

**676 CONTINUOUSLY "VARIABLE-D"®
CARDIOID DYNAMIC**

Radically new design brings professional quality to public address, recording, communications and other general purpose applications. Continuously "Variable-D" principle assures uniform, symmetrical cardioid pattern at all frequencies. Response 60 to 15,000 Hz. Highest discrimination against feedback and unwanted sound. Exclusive 3-position switch offers controlled low-frequency attenuation to overcome rumble and feedback when microphone is used at a distance. Slim design—full view of speaker. Use hand-held or with stand clamp supplied. Rugged diecast case. Acoustalloy diaphragm, 150 ohms or Hi-Z; impedance changed by new connector (no tools required). Output —57 db. Satin chrome finish. 16" cable. Size: 7 3/8" long. x 1 1/4" dia. Shpg. wt., 2 1/2 lbs. 44 R 25229 No Money Down* Net 61.35

**674 CONTINUOUSLY "VARIABLE D"®
CARDIOID MICROPHONE**

This professional microphone has the exact specifications and all of the features of Model 676 microphone above, except that it has an on-off switch and integral stand mounting stud instead of stand clamp adapter. Shpg. wt., 2 3/4 lbs. 44 R 25724 No Money Down* Net 61.35

**TYPE 502B MATCHING
TRANSFORMER**

Matches 150 ohm to Hi Z amplifier. Input 30-20,000 Hz ± 1 db. Size 3 7/8" x 1" dia. Shpg. wt. $\frac{3}{4}$ lb. 44 R 25666 ... Net 11.25

**SHURE MICROPHONE
ACCESSORIES**

LINE TRANSFORMERS

For connecting low impedance mikes to high impedance amplifiers. Preserves high frequencies and cuts hum pickup in long lines. Built-in MC1F and male Cannon type connectors. Type A95A.

44 R 75414 Shpg. wt., 14 oz. Net 12.60
Model A95F Transformer. Same as Model A95A except input is female Cannon type.
44 R 76099 Shpg. wt., 9 oz. Net 14.40
Type A95P Same as above but with phone plug output.
44 R 75968 Shpg. wt., 11 oz. Net 13.80
Model A95FP Transformer. Same as Model A95P above except input is female Cannon type.
44 R 76107 Shpg. wt., 10 oz. Net 15.60

ISOLATION MOUNT



Provides maximum isolation from mechanical vibrations (over 20 db) when used on floor stands, desk stands, conference tables, and lecture podiums. For Shure Models 545, 548, 565 and other microphones not having switches mounted in the handle. Swivel locks in tilted positions. Fits standard $\frac{3}{8}$ " x 27 thread. Shpg. wt., 1 1/4 lbs. 44 R 76172 ... Net 15.00

627A ENTERTAINER'S DYNAMIC

"Single-D" cardioid microphone ideal for vocalists and other close to mouth applications. Low frequency response is accentuated as working distance is reduced. Lightweight (8 oz.), rugged construction with built-in pop and dust filter. Response: 60-13,000 Hz. Output: —58 db. High impedance. With 15 ft. cable and stand adapter. Size: 6" long x 1 1/2" head dia. Shpg. wt., 2 lbs. 44 R 25773 No Money Down* Net 39.70

635A BROADCAST DYNAMIC

A popular design microphone. Omni-directional pick up pattern perfect for use by entertainers and vocalists. For desk or floor stand or hand held use. The rugged steel case is finished in fawn beige matte, lightweight, slim and attractively styled. 4 stage pop and dust filter eliminates need for external wind screen. Response: 80-13,000 Hz (rising), output —55 db. low impedance. Supplied with 18' 2 cond. cable. Convenient microphone size: 6" long x 1 3/8" diameter at head. Shpg wt., 3 lbs. 44 R 25591 No Money Down* Net 56.70

SHURE MICROPHONES



**MODEL 444T TRANSISTORIZED
BASE STATION MICROPHONE**

- Built-in 2 Transistor Preamp.
- Variable Output Level

Provides optimum performance for CB and other types of communications equipment including AM, FM, and single side-band. Built-in 2 transistor preamp increases signal strength. Controlled magnetic type with response of 200-6000 Hz. Semi-directional. Output level variable from 2 to 45 mv. Press-to-talk control bar for locking or non-locking operation. Height adjustable from 9 3/4" to 11 1/4". Base 5 1/4" x 4". Four ft. coiled cable. Battery Supplied. Shpg. wt., 2 1/4 lbs. 44 R 75604 No Money Down* Net 33.60 99 R 60212 Replacement battery ... Net .29

MODEL 575S "VERSADYNE"

Smooth response from 40-15,000 Hz—rugged, omnidirectional dynamic cartridge. High or low impedance models. Complete with switch, stand adapter and lavalier cord. For use in hand, on stand, or used as lavalier. Single cond. 7 ft. shielded cable. 4 3/4" l. x 1 1/4" dia. Wt., 1 lb. High impedance model. 44 R 75174 Less stand ... Net 16.50

MODEL 575SB "VERSADYNE" Similar to above, but impedance: 150-250 ohms. 44 R 75182 ... Net 15.00

TYPE 388B BEK STAND. Round black base for models 575S and 575SB above. 44 R 75208 Shpg. wt., 1 1/4 lbs. Net 3.00

LAFAYETTE Wireless Intercoms - Plug Into AC Outlets

"Mini" Solid State Wireless Intercom System

2-Stations
For Only


19⁹⁵

- Portable—Move From Room to Room or Between Houses—No wiring
- Push-to-Talk Button—Lock Button

A highly efficient wireless intercom system that simply plugs into standard 110V 60Hz AC outlets. Your voice is transmitted thru this electric power line. Talk-Lock button for monitoring baby's room or long time talking. Solid state circuitry for instant-on communication between any rooms in your home. Wide range speaker-microphone for fine tone quality. Operates on very low voltage for pennies a week. Each unit is a master so you can use as many intercoms as you need. High impact styrene cabinet. On/off switch—volume control. Pilot light. Size: 3⁷/₈"W x 5¹/₂"D x 1³/₄"H. Imported. For 110VAC, 60 Hz. Shpg. wt., 2¹/₂ lbs.

99 R 46278

Net 19.95



• No Installation Required Just Plug In and Talk

Quality Solid State Wireless Intercom System

2-Stations
For Only

27⁹⁵

- 4 Transistors—No Warm-Up
- Plugs Into Any 117V AC Outlet In Your Home
- Each Unit Is A "Master"—Use As-Many As You Need

Solid-State 2-station intercom system at an amazingly low, low price. Ideal for use in the home, office, factory, etc. — will connect any two places that are serviced by the same electric company power line transformer. No wiring required, simply plug each unit into any AC outlet and start talking — 4-transistor circuit means no warm-up time. Each unit is a "Master" with a Volume/On-Off control. Push-to-Talk Bar with a "lock-bar" feature for continuous talking, and a pilot light. 2-tone gray-colored plastic case has rubber-tipped base that will not scratch furniture. Overall size 6¹/₂" x 5" x 2¹/₂"H. For 110-120V 60 Hz. AC. Imported. Shpg. wt., 4¹/₂ lbs.


99 R 45734M 2-Station Intercom System

Net 27.95

Extra Station. Imported. Shpg. wt., 2¹/₄ lbs.

99 R 45726

Net 14.95



Deluxe 3 Channel Solid State Wireless Intercom

- For Up to 3 Simultaneous But Independent Communications Using Separate Channels
- Each Station A "Master"—Can Use As Many As Needed

Our finest and most versatile wireless intercom systems. No wiring to install, plug into AC outlets on the same electric line between offices, rooms and even between buildings. 3 channel design permits using up to 3 simultaneous but independent communications using separate channels. Units operating on channel 1 will not interfere with units operating on channel 2 or 3. Since each unit is a master, any number of stations can be set up to form a super-deluxe wireless intercom system. Controls: Press-to-talk bar with "lock-talk" feature for continuous monitoring, channel 1-2-3 selector. Powerful solid-state circuit provides instant-on operation and includes squelch for noise free operation, transformer power supply and pilot light. Handsome high impact plastic case. 5 Transistors, 3 diodes, 1 silicon rectifier, 1 thermistor. Size each station: 5x6¹/₂x3". For 117 VAC 60 Hz. Imported. Shpg. wt., 2¹/₂ lbs.

99 R 46104

Net ea. 19.95




19⁹⁵
EA.

No Wires to Attach—
Just Plug Into Any AC
Outlet and Talk. Use as
Many Stations as Required

LAFAYETTE'S Best-Selling Wired Intercom Systems

DELUXE LAFAYETTE SOLID STATE 6 STATION INTERMIX INTERCOM SYSTEM




XL-6 MASTER

29⁹⁵
ea.

R-6 REMOTE

11⁹⁵
ea.



3 Super Selective Systems Can be Hooked Up:

- (1) Master to Master
- (2) Master to Remote
- (3) Intermixed Master and Remote

Designed to fulfill virtually every office, industrial, commercial or home intercom need. Provides complete flexibility and versatility with 3 separate types of installations: (1) MASTER TO MASTER HOOK-UP: All Master Intercom System incorporates up to 6 separate master stations enabling 3 private conversations or 6 station conferences to be held. Master can initiate calls to any other Master. (2) MASTER TO REMOTE HOOKUP: Enables 1 Master station to communicate with up to 5 remotes either separately or in a six station conference. Remote can be hooked-up private or non private. Remotes can initiate call back to Master, but cannot talk directly to other remotes. (3) INTERMIX SYSTEM USING UP TO 12 MASTERS AND REMOTES: The number of units in this system may be as high as 12 depending on how many masters are used. For example if 3 Masters are used, each Master has 3 of its selector switches available to call 3 remotes, thus giving a total of 3 Masters and 9 remotes or 12 unit in the system. The maximum number of remotes associated with any 1 Master is 6 minus the number of Masters in the system. Solid-state circuitry for "instant on" operation. Incorporates a balanced 40 ohm

- Instant on Solid State Circuitry
- Balanced Input and Output to Virtually Eliminate Annoying Noise Interference

Input and output circuit design. The advantages of this type of design is that the entire system when operating is virtually not susceptible to noise interference. Master unit has 5 individual station selector slide switches, 2 position press to talk—talk/lock bar, and volume control. Remote unit has 2 position press to talk—talk/lock bar. Handsome walnut wood cabinet with brushed aluminum finish. Includes junction box for wiring.

WIRING INSTRUCTIONS: In a balanced input and output system both Master to Master or Master to Remote hook-ups use separate 4 conductor unshielded pairs for each master or remote used in the system. Dim.: Master & Remote 7 $\frac{1}{2}$ " L x 2 $\frac{1}{4}$ " H x 4 $\frac{3}{4}$ " D. For 117VAC, 60 Hz. Imported.


99 R 46112 Model XL-6 Master. Shpg. wt., 3 $\frac{1}{4}$ lbs. Net 29.95

99 R 46120 Model R-6 Remote. Shpg. wt., 2 $\frac{1}{4}$ lbs. Net ea. 11.95

100 FT. SPOOL OF CABLE FOR ABOVE SYSTEM

Beidon 8741—unshielded 4 conductor, vinyl insulated wire. Net 4.66
32 R 15787

LAFAYETTE SOLID STATE 2 STATION INTERCOM SYSTEM



Complete System **8⁹⁵**


- Battery-Operated
- Inter-Unit Tone Calling
- Simple Plug-in Connecting Cord

Battery operated solid-state 2-station intercom system. Especially useful where AC outlets are not readily available. Complete system includes 1-Master unit, 1-Remote unit, and 70' of interconnecting cable with molded plugs for easy installation. Master unit features On/Off/Volume control plus a Listen/Talk switch. "Beep" tone signaling from either Master or remote operates even when Master is "Off". Has simple provision for stationary wall mounting, or, can be conveniently placed on desk top. 9-volt battery included. Size: 2Hx3 $\frac{1}{2}$ Wx5"D. Shpg. wt., 1 $\frac{1}{4}$ lbs.

99 R 46245 2-Station System Net 8.95

99 R 60212 Extra 9-Volt Battery Net .29

LAFAYETTE 4-STATION SOLID-STATE INTERCOM SYSTEM



Complete System

18⁹⁵

Includes

- 1 Master Control Unit
- 3 Remote units
- 3—60 Ft. lengths of hook-up wire
- 1—9 volt battery

- Instant Communications—No Warm up, Heat or Hum
- 4-Way Selector Switch—3 Remote Stations
- Remote Tone Call
- 2-Wire Distribution System
- Battery Powered

Deluxe solid state 4-station intercom system that combines smart styling, and portability with high quality performance. All interstation calling is accomplished with one 4-way selector switch. Push-button listen-call on all units. Call signal operates even when master switch is "off". Simple coded interruption of buzzer signal lets master operator know which remote is calling. Cool, efficient solid state master unit runs on a single, economical 9-volt battery. With selector switch in "wait" position battery life is further extended. Master unit has its own volume control with "on-off" switch. Easy hook-up is facilitated by inclusion of three 60 foot lengths of 2-conductor wire with jacks at each end. Just plug in and talk. Additional wire is available at extra cost. See below. Complete set consists of, master control unit, 3-remote units, 9-volt battery and wire. Size: Master: 4 $\frac{1}{2}$ Wx3 $\frac{1}{2}$ "D; Remotes: 2Wx4"D. Imported. Shpg. wt., 2 $\frac{3}{4}$ lbs.

99 R 45551 Complete 4-station System Net 18.95

99 R 60212 Replacement 9-volt Battery (1 Req.) Net .21

32 R 30521 Additional wire. 100 Ft. Coil Net 1.49


Deluxe LAFAYETTE 10-Station Selective Ring Selective Talk Private Telephone Intercom System

Up to 5 Separate Simultaneous Conversations



27⁹⁵
PER PHONE

POWER SUPPLY **12⁹⁵**



- Immediate Operation—No Dialing
- Selective Ring—Selective Talk
- Battery or AC Operated

Completely private 10 station ultra-selective intercom system. Unit is styled like regular telephone, complete with coiled cord and junction box. Its functional design permits positioning on desk or hanging from the wall. No need to waste time dialing, simply set pointer to desired station, push ring button and speak. Interruptions or listening in by other stations is impossible. Handles up to 5 simultaneous conversations. Conference calls are available by one station calling another until all are on the line. Frees your regular telephone lines for outside calls. Power for all units in the system is obtained from a central location, either from a battery source or the AC power adapter listed below. Low power consumption on either AC or DC: 100 ma calling, 25 ma talking. Finished in beige plastic. Imported.

99 R 45601 10 Station Lafayette phone. Shpg. wt., 4¾ lbs. Net ea. 27.95
 99 R 45619 AC Power Supply for system Net 12.95
 32 R 48669 1½ V Battery for DC operation—6 required Shpg. wt. 2½ lbs. Net ea. 1.05

WIRING INSTRUCTIONS

The total number of unshielded conductors common to each phone is 2 more than the total number of phones in the system.

32 R 14988 100 ft. length, Belden 8456, 10 cond. unshielded. Shpg. wt., 5¾ lbs. Net 10.80
 32 R 14970 100 ft. length, Belden 8457, 12 cond. unshielded. Shpg. wt., 5¾ lbs. Net 12.15

In the above 10-station system, up to 5 separate conversations can be held simultaneously—or any station may converse with any other station.

Bogen Telephone Intercom Systems



AS LOW AS
29⁰⁵

(A) 6 & 12 STATION TQ SERIES—SELECTIVE RING—COMMON TALK



AS LOW AS
40⁷⁵

(B) 8 & 16 STATION TSL SERIES—SELECTIVE RING—SELECTIVE TALK

WIRE REQUIREMENTS FOR BOGEN PHONES

Use 3 more unshielded conductors than the total number of phones in the system. Those listed below may be used between phones.
 32 R 14525 3 conductor unshielded per 100' Shpg. wt. 2¼ lbs. 3.66
 32 R 14582 9 conductor unshielded per 100' Shpg. wt. 6½ lbs. 10.95
 32 R 14970 12 conductor unshielded per 100' Shpg. wt. 5¾ lbs. 12.15
 32 R 14954 25 conductor unshielded per 100' Shpg. wt. 11¾ lbs. 31.50
 Connect PRS-16 or PRS-1A power supplies to any junction box with a short 3 conductor cable.

(A) TQ SERIES—SELECTIVE RING—COMMON TALK

Allows only one conversation at a time. "Conference" feature lets you talk to as many stations at once as there are receivers in the system. Two separate models are available—to handle up to 6 or 12 stations. Each phone is furnished with a snarl-proof 4-ft. handset coil, and a 6-ft. master cable with junction box for simple and easy wiring. For desk or wall mounting. Phones are housed in impact resistant beige plastic. Each TQ system requires a PRS-1A Power Supply (117 VAC, 60 cycle). Shpg. wt., 4½ lbs. per unit.
 44 R 12045 TQ6A 6-Station Phone less wire Net ea. 29.05

44 R 12052 TQ-12A 12-Station Phone less wire Net ea. 32.65


PRS-1A Power Supply (1 req. per system) Shpg. wt. 2½ lbs.
 44 R 12060 Net ea. 25.00

(B) TSL SERIES—SELECTIVE RING—SELECTIVE TALK

Bogen TSL Phones will permit you to reach other individuals in their offices without depending upon an overburdened telephone switchboard. 100% trunkage permits as many as 8 separate conversations to take place at the same time with model TSL-16, and 4 separate conversations with the Model TSL-8. Select the station with which you wish to converse, press the ring button. When the called party lifts his handset, he is in direct communication with you. Phones may be desk or wall mounted. Each phone is furnished with a 4 ft. snarl-proof handset cord, and 6' master cable with junction box. Phones are housed in impact-resistant beige plastic. One PRS-16 Power Supply required to power each system. Shpg. wt., 3¾ lbs.
 44 R 12011 TSL-8 station phone, less wire Net 40.75
 44 R 12029 TSL-16 16-station phone, less wire Net 48.25

PRS-16 Power Supply (1 req. per system) Shpg. wt., 2¾ lbs.
 44 R 12037 No Money Down* Net 41.55

EMERSON-RITTENHOUSE SOLID-STATE AM/FM HOME RADIO-INTERCOM SYSTEM



Complete System

109⁹⁵

No Money Down*

COMPLETE SYSTEM INCLUDES


- 1—AM/FM Master Unit
- 3—Indoor Remote Stations
- 1—Entrance Remote Station
- 1—Installation Kit with Plaster Frames For Above Equipment, AM/FM Antenna, Low Voltage Transformer and 165 ft. 3-Wire Cable

- AM-FM Master Unit Features Powerful 17 Semi-Conductor Solid State Circuitry with Tuned RF Stage For Improved FM Performance
- Radio Is Silenced Automatically When Intercom Calls Are Made From Any Station

Handsomely styled FM/AM home radio intercom system fills your home with the pleasant sounds of music, entertainment and news. Intercom permits instant room-to-room communication, monitoring and door answering. Radio is silenced automatically when intercom calls are made from any station. Twelve transistors and 5 diodes with tuned RF stage for improved FM performance. Up to 8 remote stations may be connected to master. All stations are designed for built-in installation in walls of 2" or more thickness. Color coded wiring simplifies connections. Powered by U.L. listed low voltage transformer (supplied). Complete system includes 1 RM-16 master station with off-white finish and gold trim, 3 each RI-17 indoor stations, 1 RO-14 weatherproof door entrance station, AM and FM antenna, RT-28 low voltage transformer, plaster rings for above and 165 ft. coil of 3-wire intercom cable. Dimensions: Master Unit—14½ x 5"; RI-17: 7¾ x 4½"; RO-14: 3¾ x 5¾". Shpg. wt., 12½ lbs.

44 R 46019 w Net 109.95
ADDITIONAL STATIONS AND WIRE FOR ABOVE SYSTEM
 44 R 46027 RI-17 Indoor Remote. Shpg. wt., 1 ¼ lbs. Net 9.95
 44 R 46035 RO-14 Entrance Remote. Wt. 8 oz. 6.95
 32 R 14525 100' 3-cond. Cable. Shpg. wt., 2 ¼ lbs. Net 3.66

BOGEN IE SERIES SOLID-STATE 7 AND 13 STATION INTERCOMS



ALL MASTER SYSTEM: Consists of a Multiple-Conversation intercom system using up to 7 IE-7 masters or up to 13 IE-13 masters. Any master can call one or more stations. IE-7 and IE-13 masters have volume control, press-to-talk bar with dictate lock, rugged push-push selector switches, with identification strips. For 120 volt AC 50/60 Hz. Wiring instructions—use unshielded cable with at least one more conductor than total number stations in system.


SINGLE MASTER-MULTIPLE REMOTE SYSTEM: Consists of 1 IE-7 master and up to 6 RIE-1 remote stations, or 1 IE-13 master and up to 12 RIE-1 remote stations. Master can call one station—or several simultaneously. RIE-1 remote station can originate calls to master privately or non-privately. RIE-1 remote has press-to-talk bar and privacy switch. For 120VAC 50/60 Hz. Wiring requirements—use 3 conductor unshielded cable between master and each remote. Sizes of IE-7, IE-13, RIE-1 are 7 1/8" x 6 7/8" x 4 3/4". Shpg. wt., (IE-7 and IE-13) 3 1/2 lbs.; (RIE-1) 2 1/4 lbs. EACH IE-7 MASTER USED IN A SYSTEM REQUIRES A JBE JUNCTION BOX. EACH IE-13 MASTER USED IN A SYSTEM REQUIRES 2 JBE JUNCTION BOXES.

44 R 12318 Model IE-7	7 Station Master	37.45
44 R 12300 Model IE-13	13 Station Master	46.45
44 R 12292 Model RIE-1	1 Remote Station	11.95
44 R 12326	JBE Junction Box 13 oz.	Net 5.25

Stock No.	Length	Conductor	Weight	Net
32 R 14525	100 ft.	3 cond. unshielded	— 2¼ lbs.	3.66
32 R 14566	100 ft.	7 cond. unshielded	— 5 lbs.	9.60
32 R 14582	100 ft.	10 cond. unshielded	— 6¼ lbs.	10.95
32 R 14947	100 ft.	15 cond. unshielded	— 8¾ lbs.	20.55

*See Page 22 for Full Credit Details on Easy Pay Plan

NEW! FANON IN-404 SOLID STATE 3-STATION INTERCOM SYSTEM



Complete System: • Features Plug-in Wiring for Instant Installation
 • Comes with Two 50 ft. Cables and Plugs

32⁹⁵
 No Money Down*

Versatile system features the IN-400 Master Station, two IN-2 Indoor Remote Stations, two lengths of 50 ft. cable. Master accepts up to four remote stations, indoor, or outdoor. Master calls any or several rooms desired. Remotes have "beep call" signal. Ivory/brown with wood grain accents. Size: Master & Remotes, 7" x 3½" x 2". For 117V AC. Imported. Shpg. wt., 15 lbs.

44 R 30294W Net 32.95
 Extra indoor remote with 50 ft. cable and plug. 44 R 30302 Shpg. wt., 4 lbs. Net 8.50
 Outdoor remote with 50 ft. cable and plug. 44 R 30310 Shpg. wt., 4 lbs. Net 8.50
 Additional 100 ft. cable with plugs. 44 R 30328 Shpg. wt., 2 lbs. Net 3.75

FANON IN-600 ALL MASTER 5 STATION INTERCOM

Features plug-in wiring for "instant installation". Fully selective; any station can speak to one or more other stations. Up to five stations in a system. Permits conference calls. Two separate conversations may proceed simultaneously. Includes 50 ft. multi-conductor cable with plugs. Powerful IC circuitry allows distances of 500 ft. between first and last master station. Size: 7 x 3½ x 2". For 117V AC, 60 Hz. Imported. Shpg. wt., 3¾ lbs. (Not Illustrated.) 44 R 30278 Net 29.95

Additional 50 ft. length of 6-conductor cable with plugs. 44 R 30286 Shpg. wt., 1 ¼ lbs. Net 9.50

Telephones—New and Reconditioned for Private Systems

*Authentic Lafayette Reproduction of
a French Cradle Phone*



For Only
44⁹⁵

with 5 ft.
Cord and
Plug

**BRAND
NEW!**

An exquisite reproduction of the classic turn-of-the-century French Cradle Phone. Adds a touch of continental charm to your home—your phone will become a conversation piece. Simple hook-up. Ideal for private phone systems or as an extension to your present phone system. Ready to use . . . equipped with bell ringer, induction coil, dial, horn, mouthpiece handset, 5-ft. cord and plug. Finished in beautiful ivory with gold trim. Size: 8½" L x 8½" W x 8¾" H. Imported. Shpg. wt., 8¼ lbs.
99 R 46328 No Money Down* Net 44.95




**DIAL PHONE
Have Your Own
Private Intercom
9⁹⁵**

- Reconditioned
- For Telephone Systems, Intercoms, and Private Systems

Popular modern dial phone. Can be used to make complete private systems, or add to your present system. Equipment taken from service, reconditioned and ready to work. Simple 3-wire hook-up. Complete with handset, dial bell, induction coil and connecting cable. General appearance may vary slightly from catalog illustration. Shpg. wt., 5½ lbs.
44 R 18018 Net 9.95

**"PRINCESS-DUTCHESS" TYPE
DIAL TELEPHONE**

**BRAND NEW!
34⁹⁵**



With 6 Ft. Coiled
Cord, buzzer,
and Plug

Add a touch of elegance to your decor with the "Princess-Dutchess" type dial phone. Can be used to make complete private systems or add to your present phone system. Comes complete with built-in buzzer, metropolitan dial with numbers, ear piece, transmitter, and 6 ft. coiled cord with plug. Beautiful pearl white finish. 8½" L x 4" W x 4½" D. Imported. Shpg. wt., 3¾ lbs.
44 R 17010 No Money Down* Net 34.95

"BONNIE & CLYDE" EXTENSION TELEPHONE

As Low As **49⁹⁵** With 4½ Ft. Cord and Plug



**BRAND
NEW!**

- Handsome Styling in Black With Gold Trim
- Equipped With Electronic Components Compatible To Telephone Co. Systems

Magnificent reproduction of the early phones used in the twenties and thirties. Complete with dial, ringer, induction coil, 4½ ft. cord & plug. Size: 12" H Diameter of Base 6". Shpg. wt., 6 lbs.
44 R 24008 Net 49.95
Deluxe All-Brass Bonnie & Clyde Phone. Same as above, but all brass. Shpg. wt., 6¼ lbs.
44 R 24016 Net 54.95

GRILLO TEENAGER PHONE

BRAND NEW!

49⁹⁵
with 4½' cord,
buzzer, and
plug



The pocket mini telephone — closed it looks like a sculptured shell, opens into a modern one piece telephone. Ready to use. Comes complete with dial, buzzer, induction coil, 4½' cord and plug. Bisque white. Imported. Shpg. wt., 3 lbs.
44 R 24057 No Money Down* Net 49.95

MODERN DESK PHONE

As Low As
34⁹⁵

with 4½' cord,
plug, and
ringer



BRAND NEW!

Available in Blue,
Ivory, or Beige

Handsome, modern dial phone for the home or office. Add to your present phone system. Comes complete with bell, ringer, induction coil, 4½' cord and plug. Imported. Shpg. wt., 7 lbs.

44 R 19024 Black Net 34.95
44 R 19032 White Net 39.95
44 R 19040 Beige Net 39.95

ERICA PHONE

49⁹⁵ No Money Down*

with 4½' cord,
buzzer, and
plug

**BRAND
NEW!**



One of the most modern of all phones in use today. Add to your present phone system. Comes complete with dial, buzzer, induction coil, and 4½ ft. cord and plug. Beautiful pearl white finish. Size: 8½" H x 5½" L x 4" W. Imported. Shpg. wt., 2 lbs.
44 R 24040 Net 49.95

Telephone Amplifiers, Telephones and Accessories

DELUXE LAFAYETTE EASY-PHONE TELEPHONE AMPLIFIER


- 4 Transistors
- No Warm-up, Instant Operation
- No Pick-ups To Connect

The Easy-Phone amplifier is ideal for group conversation with one telephone in the room. Easy to operate: simply place the telephone on the amplifier, adjust the volume and everyone can listen through the separate matching speaker system, leaving both hands free for writing or typing. The Easy-Phone utilizes a 4-transistor battery powered amplifier and inductive pick-up, in an attractive plastic case. Features separate 3" speaker, volume control, on/off switch. Imported. Dimensions—Amplifier Section: 8W x 3 7/8H x 3 3/4"D. Speaker Section: 3 1/2W x 2 1/2H x 4 1/4"D. Supplied with batteries. Shpg. wt., 2 lbs.

99 R 92066 Net 12.95
Replacement "AA" Type Batteries (4 req.)
99 R 62580 Wt., 3 oz. Net ea. .10

12⁹⁵

With Batteries



- Amplifies Telephone To Room Volume

MINIATURE "SNAP-ON" LAFAYETTE SOLID-STATE TELEPHONE AMPLIFIER AND TELEPHONE HEARING AID

6⁹⁵

- Ideal For Hard Of Hearing
- Portable - Carry It In Your Pocket
- 4 Transistor Circuitry

Miniature portable, snap-on telephone amplifier because of its compact size can be carried in a pocket or purse. Designed to fit any modern telephone. Just insert battery (supplied) into battery holder. Attach amplifier to the receiver of the telephone you are using—and turn up the volume control of the amplifier. IDEAL FOR HARD-OF-HEARING. Specifications: 4 transistors, 2" dynamic speaker. Size 2 3/4" round, 1" in depth. With battery and snaparound band. Imported.

Shpg. wt., 1/2 lb.
99 R 92082 Net 6.95
Eveready E90 Replacement Alkaline Battery.
32 R 47541 Pkg. of 2 Net .79



WESTERN ELECTRIC TYPE SG-1 SOUND POWERED HANDSETS

Simple 2-way communications for miles. No batteries required. Just connect phone clips to two conductor wire. Excellent for Private Intercom System, Construction, TV Installer, Motels, or Camps, etc. Any number of handsets can be installed on one line. Complete with retractable cord and alligator clips. Shpg. wt., 1 1/2 lbs.

44 R 18034 Net ea. 9.95
Set of two Handsets with 300 ft. of 2 Conductor Inside-Outside Wire. Shpg. wt., 4 lbs.
44 R 18042 Net 18.95



9⁹⁵

NEW! DUAL PURPOSE TELEPHONE JACK-IN-A-PLUG

ONLY **1¹⁹**

- Connects Two Phones To One Jack




Unique telephone plug contains built-in jack. Enables 2 phones to be connected from a single existing jack. No reduction of power. Meets phone company regulations. Imported. Shpg. wt., 6 oz.

44 R 19016 Net 1.19

"LISTEN-IN" DUAL TELEPHONE DEVICE

- Snaps On To Your Phone... Instantly Two Persons Can Listen To Any Conversation On The Same Phone

1⁹⁹



Just snap "Listen-In" over earpiece, 2nd listener simply presses receiver of "Listen-In" next to his ear and he is ready to listen in on conversation. Teenagers can use Listen-in for extra "Party-Line" fun. Imported. Shpg. wt., 1/2 lb.
44 R 27019 Net 1.99

30 FT. TELEPHONE EXTENSION CORD

2⁴⁹



- Ideal Extension Cord for Use With Phones Listed on this Page

Add flexibility to your telephone intercom. Now be able to move your telephone intercom from room to room. 30 feet of telephone extension cord with standard 4-pin plug and jack. Color coded cord to match screw terminals on plug and socket. Imported. Wt., 3/4 lb.
99 R 45395 Net 2.49

TELEPHONE PLUGS AND JACKS

44 R 60036 Phone Plug (Imported) 3 oz. Net .59
44 R 60028 Phone Jack (Imported) 6 oz. Net .59
100 Feet 2-Conductor Twisted pair—unshielded telephone wire. 6 oz.
32 R 13030 Net 2.94

TELEPHONE OUTLET KIT

1⁴⁹



Complete telephone outlet kit with telephone jack, mounting bracket, and wall plate for standard outlet box. Flush mounted.

44 R 86007 Shpg. wt., 6 oz. Net 1.49

3 AND 4-CONDUCTOR COILED CORDS

As low as **1²⁹**



- Terminated with Spade Lugs on each End

4 conductor coiled cord extends to 5 feet, retracts to 10 inches. All four conductors are vinyl insulated and terminated with metal spade lugs at each end. Ideal for telephone, push-to-talk microphone, headphones and many other applications. Imported. Shpg. wt., 3 oz.
99 R 46005 Net 1.39
3 Conductor Coiled Cord. Same as above but only 3 conductors.
99 R 46013 Net 1.29

Telephone Recorders, Telephone Amplifiers, and Accessories

DELUXE CROWN CTA-4450 TELEPHONE ANSWERING AND RECORDING MACHINE

- Direct In-Line Coupling Facilities
- Built-in Cassette Recorder for Incoming Messages
- Incoming Recording Time Can Be Set At 30, 60, or 90 Seconds
- Outgoing Message Recording Time—23 seconds
- Can be used as an Outgoing Message Repeater

Crown's finest telephone answering and recording machine. Completely self-contained with built-in cassette recorder. Features direct in-line coupling—the 4450 can be plugged directly into the phone line, bypassing the phone itself. Or, you can have indirect connections with the phone itself by using the accessory phone cradle (included). Incoming Messages are recorded on 60 or 90 minute cassette Tapes. Recording Time per incoming call can be set, 30, 60, or 90 seconds. Beep tones will let the caller know his message is being recorded. Outgoing Messages are recorded on a separate 23 second tape (included). The 4450 is completely pushbutton operated and is mounted in a handsome wood grained cabinet. Other important features are: Automatic Record Level Control, and 3 digit tape counter with instant reset button. Size: 15 $\frac{1}{4}$ "x11 $\frac{1}{2}$ "x4 $\frac{1}{4}$ "H. For 117VAC 60 Hz. Imported.

27 R 72184W No Money Down* Shpg. wt., 18 lbs. Net 249.95
 27 R 72192 Extra 23 sec. outgoing Message Tapes... ea. 4.95
 Accessory Cassette Recording Tapes
 28 R 01223 Lafayette 60 Min. Cassette. Imported..... Net 1.19
 28 R 01207 Lafayette 90 Min. Cassette. Imported..... Net 1.99



ONLY **249⁹⁵**

with Dynamic Mike,
 Phone Cradle, 60 Minute Cassette Tape,
 and 23 second outgoing Message Tape

CROWN CAD-8 AUTOMATIC SOLID STATE TELEPHONE DIALER

ONLY
139⁹⁵



- Solid State Circuitry
- Built-in Telephone Amplifier For Incoming Calls
- Automatically Dials up to 26 numbers

A solid state automatic telephone dialing system using regular telephone sockets for easy installation to your telephone. The CAD-8 memorizes up to 26 telephone numbers (up to 13 digits for each number). Simply select the persons code number (1 to 26) and push a button. The CAD-8 automatically dials the number and connects with the person you are calling. For business discussions or family messages, a flip of a switch amplifies the call, allowing everyone to hear the conversation. Telephone operates normally for incoming calls, and for numbers not coded. Preset numbers can be changed simply. Easily operated by one hand. Housed in a low profile, decorator styled walnut cabinet which sits flat on any desk or table. A complement to any home or office. Size: 11"x5"x16". For 110 VAC 60 Hz. Imported. Shpg. wt., 11 $\frac{1}{2}$ lbs.

44 R 41002W Net 139.95

CROWN 4100 TELEPHONE ANSWERING AND RECORDING MACHINE

89⁹⁵
 No Money Down*



Records Incoming Messages
 Up To 1 Minute In Duration
 With Any Tape Recorder with
 a Remote Control Mike Input



Optional RC-4 Direct
 Line Adapter — 19.95

Use with phone cradle (included) or can be plugged directly into phone line using optional RC-4 Direct Line Adapter. Answers phone callers with up to 60 second prerecorded message. Incoming phone calls with optional recorder attached are recorded for up to 1-minute in duration. Can be played back at a later time at your leisure. Can also be used as message repeater. With AC/DC remote control terminal, recording switch, and built-in mike. For 110VAC, 60 Hz. Imported.

27 R 72143W Shpg. wt., 10 $\frac{3}{4}$ lbs. Net 89.95
 27 R 72150 Model RC-4 In-Line Adapter. Wt. 3/4 lb. Net 19.95
 27 R 72101 1-Minute Message Tape For 4100 Net 4.95
 Lafayette RK-65 Cassette Tape Recorder for Incoming calls Imported.
 99 R 15828L Shpg. wt., 4 lbs. Net 19.95

NEW! MESSAGE-MINDER TAPE RECORDER

Only **16⁹⁵**
 with batteries



- Leave Messages for Family Members
- Record Important Dates & Appointments
- Give Assignment to Secretary

Mini-Tape Recorder—one lever control for record or playback. Built-in continuous Loop Tape provides efficient method for recording messages. Ideal for businessmen, secretaries, housewives, and students. Records up to 30 seconds. Erases for over and over re-use. Reliable solid state circuitry. Built-in mike and speaker. Operates on 1 "9v" and 1 "C" battery (included). Size: 3 $\frac{1}{4}$ " oval by 6 $\frac{1}{2}$ "H. Imported. Shpg. wt. 1 $\frac{1}{2}$ lbs.

44 R 19008 Net 16.95
 99 R 62572 Extra "C" battery 1 req. Net ea. .16
 99 R 62012 Extra 9 Volt battery 1 req. Net ea. .29

CROWNSCRIBER CASSETTE DICTATING/TRANSCRIBING MACHINE

New Low
 Price
149⁹⁵




with foot pedal, head
 set, remote control
 mike, dust cover

- Seven Second Repeat Feature

Solid State Cassette dictating/transcribing machine with a 7 second repeat feature. Patented foot pedal control starts and stops the "Crownscriber." In stop position, the transcriber can repeat the last 7 seconds of the message. Pushbutton controls for record, rewind, forward, fast forward, stop. Uses standard size 30, 60, and 90 minute cassette tapes. For transcribing, a remote control start/stop mike controls the Crownscriber. Size: 11" x 11" x 5 $\frac{1}{8}$ ". Shpg. wt. 14 $\frac{1}{2}$ lbs. For 117 VAC 6 volts. Imported.

27 R 72176WX No Money Down* Net 149.95

Telex Headphones and Microphones



TELEX TELESET

(A) Lightweight (8 ounce) headsets tailored to the requirements of radio operators, and all general work. Fine stainless steel and plastic design delivers high sensitivity and faithful sound reproduction. Freq. Resp.; 50-10,000 Hz. 5-ft. durable vinyl-covered cord. Shpg. wt., 1 lb.
 40 R 59010 Imp. 2,000 ohms Net 18.50
 40 R 59028 Imp. 500-600 ohms Net 18.50
 Soft foam plastic cushions. Wt. 6 oz.
 40 R 59036 One pair ACT-2 Net 1.28

TELEX MONOSET

(B) An under-chin headset ideal for secretarial office dictating machine use and private listening to radio, TV and recordings. Anodized aluminum tone arms are fully adjustable and weigh only 1.2 ounces. Frequency response: 50-5,000 Hz. Single detachable 5 ft. cord with standard phone plug eliminates tangling. Shpg. wt., 7 oz.
 40 R 59044 125 ohm model HMV-2 Net 9.75
 40 R 59051 2000 ohm model HMY-2 Net 9.75

TELEX DYNASET

(C) This lightweight headset is excellent for every kind of communication use, including office equipment, radio, TV and commercial applications. A magnetic driver element provides clear reproduction. Sound travels through 5 ft. tubing. With phone plug. Frequency Response: 50-5,000 Hz. Shpg. wt., 7 oz.
 40 R 59069 Model HUP-01 Net 12.65

TELEX TWINSET

(D) Banishes bothersome ear pressure. Tubular sound arms pipe signal to ears. Only 1.6 oz. Complete with 5 ft. cord and standard phone plug. Shpg. wt., 7 oz.
 40 R 59085 500 ohms HTW-2 Net 15.65
 40 R 59093 1000 ohms HTX-2 Net 15.65

TELEX PERSONA-PHONE



- For Private Listening
- Individual Volume Control

34⁰⁰

Persona-Phone allows personal listening in churches, libraries, auditoriums, museums, exhibits, etc. Individual volume controls allow the listener to adjust to his own hearing without annoying nearby persons. Each unit has two shell type earsets which slip comfortably over the ear. Beige colored earsets weigh less than 1 1/2 oz. and are equipped with 5' cords. Units may be used with sound systems providing 70 volt, 25 volt or 8 ohm outputs. Size: 4 3/4" W x 3 3/8" H x 2 1/4" D. Shpg. wt., 4 lbs.
 40 R 59507Y No Money Down* Net 34.00

TELEX TELE-FI

(E) Fidelity "in depth" with only one speaker. The 1/2 ounce continuous piece tone arm delays the sound to the ear opposite the speaker for one millisecond. This delay creates greater depth and clarity. Unlimited applications. A perfect leisure listening set for individuals with a hearing loss. 5 ft. flexible cord included. Shpg. wt. 6 oz.
 40 R 59101 15 ohm HFR-91 Net 5.95
 40 R 59119 125 ohm HFV-91 Net 5.95
 40 R 59127 500 ohm HFW-91 Net 5.95
 40 R 591351,000 ohm HFX-91 Net 5.95
 40 R 591432,000 ohm HFY-91 Net 5.95

TELEX 600 SERIES MAGNETIC BOOM MIKE HEADSETS

(F) Dual magnetic headsets with removable ear cushions. Light in weight—yet very rugged. Choice of 600 or 2000 ohm headphone impedance. *With 250 ohm noise cancelling dynamic boom microphone. † With High Z ceramic boom microphone. All with 5 ft. cord and standard 1/4" Phone plugs. Average shpg. wt. 1 lb.

Stock No.	Type	Impedance	Net
40 R 59374	*600-1	600 ohm	19.95
40 R 59390	†600-3	600 ohm	21.95

TELEX MAGNETIC PILLOW SPEAKER

(G) Ideal for radio or TV. Enjoy private listening in bed or in a chair without disturbing others. Great for late listening. Only 2 1/4" diameter and 3/8" thick. Maroon waterproof plastic. Complete with 5 ft. cord and standard phone plug. Shpg. wt., 6 oz.
 40 R 59234 2000 ohms SMY-2A Net 8.85

FULL FIDELITY MUSIC HEADPHONES



Designed For Music
Appreciation Courses,
Electronic Instrument
Lessons & Libraries

Telex 820 Series Headphones offer outstanding versatility and value. Frequency response of 50-18,000 Hz. Light-weight and attractively styled in brown with white trim and vinyl protected spring steel headband. Monaural version has 4-ohm impedance, six foot white cord and two-circuit phone plug. Stereoversion has 8-ohm impedance, six foot brown cord and three circuit plug. Shpg. wt., 1 lb.
 40 R 59499 Monaural Net 9.95
 40 R 59481 Stereophonc Net 9.95

TELEX TV LISTENER

(H) Cord clips allow simple and safe attachment to any radio or TV. The control switches turn the radio or TV speaker on or off and control the volume through the earset. Listener complete with one earset, 15 ft. listener cord, and 4 ft. earset cord. Shpg. wt., 14 oz.
 40 R 59192LCP-90 Net 9.95
 Extra earpiece ELY-98. Allows two to listen at once. Shpg. wt., 4 oz.
 40 R 59333 Net 2.95

TELEX DYNAMIC PILLOW SPEAKER

(I) New dynamic miniature pillow speaker gives the ultimate in tonal quality without distortion. For individual and institutional use. Safe and no complicated wiring necessary. Stainless steel, moisture proof housing. Size: 3 3/4" D. 1 1/4" max. thickness. Complete with a 5 ft. cord and standard phone plug. Shpg. wt., 12 oz.
 40 R 59200 3.2 ohms SDN-2A Net 8.85
 40 R 59218 10,000 ohms SDM-2A Net 11.80

TELEX ACCESSORY CORDS



5' accessory cords with standard phone plug on one end and Telex connector on other. * May be used with illustrations D or I. † May be used with B or E. Shpg. wt., 4 oz.

Stock No.	Description	Net
40 R 59259 CCM-2	Coiled Cord	* 3.40
40 R 59267 CMM-2	Straight Cord	* 2.25
40 R 59275 CCT-2	Coiled Cord	† 3.25
40 R 59283 CMT-2	Straight Cord	† 2.25

TELEX 1200 FOR LANGUAGE LABS

33²⁵



- Meets All Language Institute & Governmental Specifications

Deluxe headset with boom mike designed for language laboratory use. Dynamic headphone response is 20-20,000 Hz. Dynamic boom noise-cancelling microphone response 100-8000 Hz. Headset impedance 600 ohms. With 1/4" phone plug. White with gray trim. Shpg. wt., 1 3/4 lbs.
 40 R 59457 Telex 1200-42 Net 33.25
 Headset only, less boom mike.
 40 R 59465 Telex 1210-04 Net 24.95

Hearing Aids, Headphones and Pillow Speaker

SUB-MINIATURE HEARING AID

Lightweight!



29⁹⁵

- 2½ Lx1½ Wx¾" D
Only 2 ounces!

A high quality, completely adjustable, hearing aid which weighs only 2 ounces. Features an advanced 4 transistor circuit, wide range volume control, crystal microphone, magnetic earphone, and a 4 position tone converter control. Three tiny ear plugs and a 3 ft. flexible cord are included. Supplied with leather carrying case, earphone, and battery. Shpg. wt., ½ lb. imported.

99 R 90680L	Net	29.95
32 R 4B754 Extra Battery, Burgess NE type	Net	.10
99 R 9069B Extra Plug in cord	Net	.69
99 R 90706 Extra Earphone	Net	1.89

BEHIND-THE-EAR HEARING AID



62⁹⁵

- Weighs Only 1/2 Oz.—No Cords
- Self-Contained Miniature Unit
- Complete with Battery Charger, 2 Rechargeable Nickel Cadmium Batteries and Case

A fine unit combining good performance and very small size. Designed as a light and compact "ear-lobe" hearing aid. All components are contained in the flesh-colored high impact case, which is worn behind the ear. Weighs only 1/2 of one ounce! Sound travels to the ear through a clear tube. Independent on-off switch and volume control. Operates 8-10 hours on a rechargeable nickel cadmium battery and 80-100 hours with a non-rechargeable mercury cell. Complete with a handy battery charger capable of charging cells overnight. Imported. Shpg. wt., 9 oz.

99 R 90722L No Money Down*	Net	62.95
32 R 47467 Rechargeable nickel cadmium cell for above	Net	1.44
32 R 46683 Pkg. of 6 Mercury cells for above	Net	1.95

PRIVATE RADIO-TV LISTENER

1⁹⁸


- Control Either Private Earphones or Remote Speakers



Simply installed unit allows normal use of TV or radio while adding controllable earphones or extension speakers. The hard of hearing may control their volume while others may listen at normal listening levels. May be operated up to 17 feet from set. Supplied complete with instructions, one earphone, and two earphone jacks. Imported. Shpg. wt., 5 oz.

99 R 91720	Net ea.	1.98
99 R 2548E Extra Earphone. Shpg. wt., 4 oz.	Net ea.	.59
99 R 25496 10 ft. extension cord. Shpg. wt., 3 oz.	Net	.59

REMOTE CONTROL FOR SILENT TV VIEWING



- Simple to Attach to any TV or Radio Set
- See and Hear—Noiselessly and Conveniently

FOR LATE LISTENERS. One or two people can both see and hear the program with the loudspeaker cut off. Tops for enjoying the late-late show without disturbing the rest of the household or the neighbors.

FOR HARD-OF-HEARING. Hear without turning the set volume so high that others can't stand the noise. It is possible to listen either with the loudspeaker cut off or, if the everyone wants to hear, with the speaker on.

FOR NOISY PROGRAMS view with the speaker off.

FOR NORMAL OPERATION it does not affect the regular use of the TV set. It does not have to be disconnected.

REMOTE CONTROL comes complete with 20 ft. of cable so it can be operated comfortably from a distance. Has its own volume control, speaker on-off switch, and two sets of jacks so either 1 or 2 earphones can be connected. Supplied with a miniature dynamic earphone. Highly sensitive and efficient. Complete with 1 earphone with 3 ft. of cord and plug and control box with 20 feet of cable. Only 3 7/8 x 2 1/2". Instructions included. Shpg. wt., 1 1/4 lbs.

13 R 09012	Net	6.50
EXTRA EARPHONE. Shpg. wt., 3 oz.		
99 R 2548B	Net	.59
10' EXTENSION CORD for above.		
99 R 25496 Shpg. wt., 3 oz.	Net	.59

"WHISPER" BONE-CONDUCTION PILLOW SPEAKER

- "Sonic Transducer" cannot be heard at a distance

2⁷⁹



Sound is actually conducted through your pillow and bone to the inner ear. No danger of disturbing others—even husband or wife asleep in the same bed! 2 1/4" diameter round ivory plastic case is only 5/8" thick. With 6 ft. cord, 1/8" plug and jack. Plugs into radio or TV. Imported. Shpg. wt., 8 oz.

99 R 90730	Net	2.79
99 R 25496 10 ft extension cord	Net	.59

CRYSTAL HEADSET

- Under-the-Chin Design
- Lightweight
- Sensitive Crystal Element



1³⁹

This lightweight, under-the-chin crystal headset provides the utmost in listening comfort wherever a headset is used. This unit is characterized by a high sensitivity and is ideal for all applications where a very high impedance unit is required. This headset offers fine reproduction and comfortable listening in a lightweight design. Complete with 3ft. cord. Imported. Shpg. wt., 3 oz.

99 R 25504	Net	1.39
------------	-----	------

SUPEREX AMATEUR PHONES

24⁴⁵



These earphones are made specially for the Ham and short wave listener. Comfortable, removable and replaceable vinyl foam ear cushions make long hours at the rig a real pleasure. Dual impedance, 600 and 4-16

ohms, can be changed at plug. High sensitivity and a crisp clear reproduction for that hard to read station. Shpg. wt., 2 1/4 lbs.

40 R 85015	Net	24.45
------------	-----	-------



LAFAYETTE HEADSET

2²⁹

- 4000 ohm DC Resistance
- Double Permanent Magnet

A real bargain—the convenience and advantages of earphone listening at an especially low price. This is an extremely efficient, double headset with adjustable headband, for private listening or for greater intelligibility when there are distracting sounds and external noise, 4,000 ohms DC resistance. Has durable permanent magnets, removable earpiece and 3 1/2 feet of extension cord terminated with standard headphone tips. Imported. Shpg. wt., 1/2 lb.

99 R 25041	Net	2.29
------------	-----	------

CLEVITE-BRUSH HEADPHONES

22⁰⁰



Model BA-200-1. Rugged, sensitive, impedance, 45,000 ohms. Response, 100-8,000 Hz. With 5' cord and headband and phone plug termination.

40 R 80016 Shpg. wt., 1 1/2 lbs.	Net	22.00
----------------------------------	-----	-------

Model BA200-S. Same as above but wired for stereo use. Impedance, 90,000 ohms. With eyelet terminals.

40 R 80024 Shpg. wt., 1 1/2 lbs.	Net	22.00
----------------------------------	-----	-------

Miniature Earphones & Headphones

Argonne

- Detachable Plug-in Cord
- Flexible Plastic Support
- Excellent Sound Reproduction

A sensitive dynamic earphone of exceptionally fine quality. Lightweight, convenient and comfortable to wear. A flexible polyethylene support holds the receiver securely in place for either ear. The practically invisible transparent cord is connected to the cased earpiece by means of a special plug. Provides clear reproduction with a pleasing tone quality. Complete with 3-ft. cord. Shpg. wt., 3 oz. Imported.

99 R 25421 3000-Ohm Impedance with phone tips Net 1.19
 6-Ohm Impedance with 1/4" diameter phone plug and phone jack, Net 1.29
 99 R 25413



SOUND SHELL EARPHONE WITH DYNAMIC SPEAKER

295

- Fits over the ear
- Less than 1 1/2 oz.

Unique, new listening device incorporates a wide range (30 to 14,000 Hz.) speaker in a specially designed plastic sound shield. Comfortably fits over either ear for maximum listening pleasure. Impedance 8 ohms. Complete with 4 1/2' cord and 1/8" dia. miniature plug. Imported. Shpg. wt., 1/4 lb.
 99 R 26148 Net ea. 2.95



EXTENSION CORD FOR MINIATURE EARPHONES

Perfect for extending earphone from transistor and portable radios. 10 ft. extension cord has 1/8" dia. miniature plug at one end and enclosed socket on the other which accepts 1/8" dia. plug. Cable comes in attractive light pink color. Imported. Shpg. wt., 3 oz.
 99 R 25496 Net .59




59c

SUPER POWER DYNAMIC EARPHONE FOR TRANSISTOR CIRCUITS

- Powerful Efficient Magnet

Extra efficient construction and a powerful magnet provides exceptional performance. Ideal solution to the problem of low output in transistor circuits. You'll be amazed at the difference in volume, as well as its quality of reproduction, when you use this dynamic earphone. AC impedance 6700 ohms. DC resistance 3000 ohms. Snap on ear-plug. Complete with 3 ft. detachable plug-in cord with miniature 1/8" diameter plug. Imported. Shpg. wt., 2 oz.
 40 R 78010 Net 2.95



C.F. CANNON HEADPHONES



"CANNON-BALL" DOUBLE HEADSET

Low-priced, lightweight, with powerful Alnico V magnets and double coils. Adjustable vinyl covered steel headband. 4 1/2 ft. cord. With pin tips. Type AM-15-2—2000 ohm DC, with standard phone plug.

40 R 81113 Shpg. wt., 1 lb. Net 3.80

"CANNON-BALL" SINGLE HEADSET

Single efficient phone with spring steel headband and 4 1/2 ft. cord. Shpg. wt., 6 oz.

40 R 81048 AM-15-1—1000 ohms DC Net 1.65

"CHIEF" HEADSET

Bakelite phones, double coils, alnico magnets and vinyl covered headband. Diaphragm diameter 2 1/4".

40 R 81063 CC11-11 ohms DC Net 3.70

BRANDES "ADMIRAL" HEADPHONES

"Matched-tone" headset, large diaphragms. Double coils, chrome steel magnets. Adjustable vinyl covered headband. 4 1/2 ft. cord. Shpg. wt., 3 1/4 lb.

40 R 81071 BA-2—2000 ohms Net 3.60

40 R 81097 BA-5—5000 ohms Net 4.37

REPLACEMENT CUSHIONS

Soft rubber cushion fits all above phones and most standard headphones. Shpg. wt., 5 oz.
 40 R 59325 Net .70



REPLACEMENT CORDS, & TIPS

Sturdy copper conductor replacement cords with cotton insulation, 4 1/2 feet long, with terminations indicated. Double phone cord, except * is single cord. Shpg. wt., 3 oz.

40 R 59291 Spade and pin tip Net .67

40 R 59309 Pin tip both ends Net .67

40 R 59317 *Pin tip both ends Net .50

Heavy plated tips. Takes up to No. 18 wire, 1" long, 2 oz.

32 R 85244 Pkg. of 10, Net .25

ECONOMY ALL-PURPOSE DYNAMIC EARPHONE

- For Transistor and Subminiature Receivers
- For Silent Radio and TV Listening

A sensitive all-purpose earphone which is ideal for use with TV and radio sets, amplifiers, and transistor receivers. Lightweight and equipped with a practically invisible support which is comfortable over either ear. Impedance 6 ohm, with a miniature 1/8" diameter phone plug and a 3 ft. cord. Shpg. wt., 3 oz. Imported.
 99 R 25488 1/8" dia. plug Net .59
 Same as above with 3/8" dia. plug Net .59
 40 R 79018



STETHOSCOPE TYPE STEROPHONIC HEADPHONES

- True Binaural Reproduction
- Lightweight—Less Than 2 Oz.

Binaural magnetic units are equipped with two separate transducers and cord sets for true dual-channel reproduction. Extremely sensitive, sound is carried through plastic tubes to earpieces. Hinge permits adjustment to desired spacing. Complete with 1/8" dia. plugs. Imported. Shpg. wt., 6 oz.

99 R 10027 5000 ohms Imped. Net 1.95



MONAURAL HEADPHONES

Single channel version of above FM Monaural listening. Single transducer is removable and may be used as earphone with a snap-on earpiece which is included. Complete with 1/8" dia. plug and jack. Imported. Shpg. wt., 5 oz.
 99 R 25462 6 ohms Impedance Net 1.75
 99 R 25470 5000 ohms Impedance Net 1.95



LAFAYETTE

Experimenter Kits

LAFAYETTE 150-in-1 ELECTRONIC EXPERIMENTERS KIT

Assemble 150 Interesting Electronic Projects

- 100% Reusable Components
- No High Voltage or Soldering
- Sturdy Compact Wooden Case
- Detailed Instruction Manual

Only

24⁹⁵

Featuring An Enlarged Visualized Integrated Circuit


Vivid enlarged representation clearly shows the functional components of a typical integrated circuit. Incorporates a capacitor, resistors, transistor and diode to form a remarkable educational unit.



Lafayette's 150-in-1 IC Electronic Experimenter's Kit supplies a variety of exciting projects dealing with measurement, radio broadcasting and receiving, communications, sound and musical instruments, physics, chemistry, amusement, and convenient living. Its quality components are attractively displayed in a functional, sturdy wooden storage case for ease in experimentation and long lasting protection. The enlarged visualized integrated circuit clearly shows the various devices that form a typical IC. Each experiment is wired using easy to connect spring tension terminals. This feature permits 100% reuse of all components and eliminates the bother and danger of soldering. Power is supplied from three standard low voltage batteries, thus eliminating the possibility of shock hazard. Simplified manual portrays each experiment in both visual and written forms. The visual representation permits convenient theoretical circuit reasoning and the instructions provide a short cut for speedy wiring. Geared to be educationally stimulating for youngsters as well as adults. Supplied with all components including batteries. Size: 3 1/2" H x 15 1/2" W x 8 1/2" D. Shpg. wt., 3 3/4 lbs.

99 R 35107 Net 24.95
 99 R 62572 Extra 1 1/2 V. "C" Cell (2 req.) Net ea. 16
 99 R 60212 Extra 9 volt battery Net .29

EDUCATIONAL-CREATIVE-NO TECHNICAL KNOWLEDGE NECESSARY! LEARN WHILE YOU BUILD!



Only

16⁹⁵

LAFAYETTE 80-in-1 ELECTRONIC PROJECT KIT BUILD 80 SAFE BATTERY OPERATED ELECTRONIC PROJECTS

- All Solid State Circuitry • No Soldering Required

The ideal introduction to the world of electronics for young or old experimenters. Build over 80 safe, battery operated, useful solid-state projects with this one kit. No soldering or tools required. Detailed, simplified instruction manual provides easy-to-follow instructions for each project. Point-to-point wiring between numbered parts using spring type connectors completely eliminates soldering. Each project can be assembled and disassembled in just minutes. This "breadboard" type kit is ideally suited to the design of as many additional circuit projects as your ingenuity and creativity can produce. Nothing else needed—kit includes all parts for these projects—galvanometer, solar cell, transistors, relay, baffled speaker, carphone, microphone, relay transformer, tuning capacitor, volume control, telegraph key, antenna, diode, resistors, capacitors, batteries and connecting wires—all packed in a fitted hardwood case. Size 15x8 3/4x4". Imported. Shpg. wt., 3 lbs.

99 R 35016 Complete 80-in-1 Kit Net 16.95
 99 R 62580 1 1/2V Replacement Battery (2-required) Net ea. .10
 99 R 60212 9V Replacement Battery (1-required) Net .29

SOME OF THE PROJECTS YOU CAN BUILD

The fascinating projects which can be assembled with these Lafayette kits cover a wide range of subjects such as home entertainment, wireless communications, telephony and telegraphy, music, public address, alarms and warning systems, electrical measurement, digital circuitry, physiology, weather, etc. You can build many different radio receivers, including a solar powered transistor radio. Also included are projects concerning computer type "AND" and "OR" circuits, many varieties of light and sound code signal com-

munications using Morse Code, several transistorized amplifiers and public address systems, continuity checkers and signal tracer, wireless microphone, metronomes, electric harmonica, photoelectric relay and burglar alarms. Some unusual projects include a sensitive photometer, rain alarm, auto headlight dimmer, cat sound simulator, muscle simulator, water level warning system and many others designed to provide fun for the entire family.

LAFAYETTE 20-in-1 ELECTRONIC PROJECT KIT

- ★ Absolutely Safe . . . No High Voltage or Soldering
- ★ Detailed Simplified Instruction Manuals
- Build 20 Interesting Electronic Projects
- Easy to Wire Spring Tension Terminals
- Pre-assembled Educational Wiring Block

Educationally stimulating kit utilizes separate building units that connect to form 20 interesting electronic devices. Spring tension terminals simplify wiring and eliminate the bother and danger of soldering. Incorporates one transistor, a tuner, diode, key, transformer, galvanometer, solar battery, two resistors, and three capacitors. Battery provides safe low voltage power. Projects are easily assembled in minutes. Attractively packaged in a convenient storage case. Supplied with all components including battery. Shpg. wt., 2 lbs.

99 R 35214 Net 9.95
99 R 62580 Extra 1½ volt "AA" battery Net .10

LAFAYETTE 10-in-1 ELECTRONIC PROJECT KIT




- ★ Absolutely Safe . . . No High Voltage or Soldering
- ★ No Technical Knowledge Necessary
- ★ Detailed Simplified Instruction Manuals
- Build 10 Educationally Stimulating Projects
- Enlarged Visualized Integrated Circuit

Lafayette's electronic project kit features an enlarged visualized integrated circuit which clearly shows the typical placement of a condenser, two resistors, transistor and diode in an IC. All connections are facilitated by spring tension terminals for easy wiring without soldering. Projects include circuit testers and communication sets. All components are reusable and mounted on an attractive wood molded panel. Supplied complete with manual and batteries. Size 11Wx1¾Hx8"D. Shpg. wt., 1½ lbs.

99 R 35099 Net 7.95
99 R 60212 Extra 9 volt battery Net .29

SHORTWAVE AND SUPERHET BROADCAST RADIO KIT



17⁹⁵

2 bands cover both standard broadcast 540-1620 kHz and shortwave 5.8-18 MHz which includes international broadcast, 40 and 20-meter ham bands and some of the aeronautical and marine bands. Superheterodyne circuit has high gain IF's, built-in broadcast band loop antenna. Comes complete with ivory cabinet 4" PM speaker, tubes (12BE6, 12BA6, 12AV6, 50C5, plus 35W4 Rectifier) and all parts. Easy to follow step-by-step instructions. Shortwave band requires external antenna (not supplied). Size: 8¾Wx5¾Hx5¼"D. For 110V AC or DC.

19 R 40071 Wt. 4¾ lbs. Net 17.95
Shortwave antenna kit for above.
32 R 30984 Wt., 1¼ lbs. Net 23.55

RAYTHEON-LECTRON EDUCATIONAL SETS

- Space-Age Magnetic Blocks Make Electronics Child's Play
- No wiring ● No tools No Electronics Knowledge Needed
- Match magnetic blocks with a schematic diagram in guidebook
- Series 2 Set Builds 43 Projects
- Series 3 Set Builds 56 Fascinating Projects



Set consists of domino-like see-thru magnetic connecting plastic blocks each self-contained with a transistor, capacitor, or other electronic component, etc., inside and the electronic symbol therefor engraved on the top; an 8" x 11" metal ground plate and an 80 page instruction manual. When a project is complete, circuit symbols on the blocks form a schematic diagram. Manual covers basic theory principles of the components and project diagrams and explanation. Easy! And Fun!


SERIES 2 LECTRON SET—make 43 working projects including transistor radio, electronic organ, rain moisture indicator, audio amplifiers, light modulated detector, Morse code transmitter, metronome, burglar alarm and more, plus your own ingenuity. Shpg. wt., 3 lbs.
19 R 18051 Net 17.95

SERIES 3 LECTRON SET—make a solid state radio with speaker in 2 minutes and 55 more projects—all of Series 2 plus Intercom, voice transmitter, public address and telephone amplifier, automatic night light, etc. Shpg. wt., 3¼ lbs.
19 R 18044 Net 24.95


To Speed Your Mail Order—Please Give Your Zip Code Number

Lafayette Cat. No. 720 209

LAFAYETTE
Experimenter Kits



Only 9⁹⁵



Only 7⁹⁵

Computer and Hobby Kits

GENIAC® COMPUTER KITS

For School,
For Science Fairs,
For Advanced Experimenters



- Over 800 Parts
- Computes, Reasons, Plays Games
- Composes Music, Forecasts Weather
- Design Your Own Computers

DOUBLE GENIAC

The newest kit in famous Geniac series! The "Double" Geniac contains over 800 parts. Two of everything in the Standard model. Offers the advanced experimenter a far wider range of activities. Perfect for school demonstration. Multiple setup is ideal for Science Fair projects—submit one or more designs. Build "electric brains" that test intelligence—code and decode—add, subtract, multiply and divide—solve puzzles—play games—forecast weather—reason in syllogisms—information and logic circuits. No soldering required. Easily assembled and operated. 64 page guide and reference book, beginners manual, wiring diagrams and many extra pamphlets outlining projects and methods. Complete with mounting rack and batteries. Shpg. wt., 9 lbs.

19 R 38034

Net 18.95

STANDARD GENIAC

You build up to 125 exciting "electric brain" machines. Has special circuits for forecasting weather. No soldering required. Comes complete with extra pamphlets including 64-page "Simple Electronic Brains and How To Make Them," "Symbolic Analysis of Relay and Switching Circuits," "Beginner's Manual," "Machine to Compose Music," wiring diagrams, etc. Complete with battery. 16½x11¾". Shpg. wt., 4¼ lbs.

19 R 38042

Net 11.95

MAGIC-GLO BLACK LIGHT KIT



12⁹⁵

- Learn Invisible Detection
- Write Secret Messages
- Educational—Scientific
- Enjoyable—Interesting

The Black Light Kit enables you to see the invisible. Guaranteed completely safe and harmless. This kit allows children to study the phenomena of fluorescence and phosphorescence. Set contains black light, socket and cord, laboratory lamp stand, 4 jars of fluorescent paint, invisible ink, invisible crayon, tracer powder, 3 fluorescent mineral specimens, phosphorogram, optical bleach, brushes and pen, and a pkg. of fluorescent materials. Enables the student to perform endless numbers of fascinating experiments. The amply illustrated 48 page booklet "The Story of Black Light — The Unseen World Around Us," explains the use of black light in fields such as mineralogy, electronics, crime detection, medicine, stamp collecting and many others. Shpg. wt., 2½ lbs.

19 R 13011

Net 12.95

19 R 13029 Replacement U.V. Bulb for above

Net 3.95

TRANSISTOR RADIO AND BROADCAST KIT



9⁹⁵

- Use It Either As An AM Wireless Broadcaster or AM Radio Receiver

Transmit your own radio program with this safe, battery-operated transistorized broadcaster or receive AM radio programs. Includes headphone, broadcast microphone for home broadcasts, Alnico loudspeaker, antenna, plus all other required parts. Big 18" plastic cabinet. Easy to assemble with instructions provided. Operates on 3 inexpensive "C" cells (not included). Shpg. wt., 2¾ lbs.

19 R 31096W Less batteries

Net 9.95

99 R 62572 C Batteries (3 required)

Net ea. .16

ANALOG COMPUTER KIT



14⁹⁵

- Ideal Introduction to Basic Elements of Analog Computers
- Work Over 50 Experiments
- Easy-to-Assemble with Screwdriver and Pliers
- Learn the Way to Sound Scientific Knowledge

Analog Computer Kit offering a basic introduction to computer theory—gives accurate answers to practical problems. Perform over 50 experiments—multiplication, division, powers, square roots, rocketry, interest, radio-active decay, light, kinetic energy, etc. Level of accuracy better than 5%. The computer consists of a masonite, solid instrument panel, kits, potentiometers, meter specially calibrated scales, guide and operating booklet. Easy-to-assemble.

19 R 38059 Shpg. wt., 4¼ lbs. Net 14.95

INFORMATION RETRIEVAL PORTABLE MEMORY CARD FILE SYSTEM



SALE Save 2.00 12⁹⁵

How to file a card in 25 places simultaneously.

For the busy scientist, engineer, teacher, businessman or student who must keep basic information on file. NOW the Geniac Portable Memory Unit, (PMU), a low cost information retrieval system can conservatively sort 400 cards per minute—using no electrical parts or gadgets. Sorting is by rods. Information is coded into the cards by matching prepunched holes around the edge of the card. No previous knowledge is necessary. Once coded the card is filed at random and will automatically appear during sorts. Includes a single hand punch, sorting rods and 200 cards. Shpg. wt., 3¾ lbs.

19 R 38018 Net 12.95

Double Punch: For use when more extensive coding requires punching of double rows.

Shpg. wt., ½ lb.

19 R 65011 Net 9.00

Additional Cards. Pkg. of 100

Shpg. wt., 3¼ lbs.

19 R 38026 Net 3.92

MASTER FILE

Includes same components as above plus filing cabinet and 1200 cards. Shpg. wt., 17 lbs.

19 R 38067W Net 49.95

Logix ELECTRONIC COMPUTER KIT

NEW!



29⁹⁵

- Absolutely Safe—No High Voltage
- No Soldering
- Over 425 Parts
- 39 Different Programs
- 112 Page Detailed Illustrated Instruction Manual

Provides an insight to the Complex World of the Computer

The Logix electronic computer provides an introduction to computer technology by means of numerous experiments and programs. Its fundamental principles correspond to those of infinitely larger computers systematically showing what makes them work and how they can be used. "Snap-In" type parts simplify assembly of the console. Once assembled its manual details 39 different programs, progressing from very simple to more and more complex ones. Setting up a program simply involves connecting wires on the top side of the console exactly as shown in a wiring scheme. With each program is learned the logic that goes with it. You can play computerized games with an opponent, or match wits with the computer. Computerized weather forecasting is obtained by use of weather

input. Similarly, the computer can diagnose illness and recommend therapy. You can program airline bookings, routing of long distance telephone calls, mixing of complex colors, translation of languages, detection of criminals and investigation of cybernetic problems. Nine advanced programs deal with the binary system, complex mathematical calculations, Venn diagrams and the law of sets as well as playing a game of computerized chess. In addition provisions are made for individuals own creative programming. Kit is complete with 112 page manual, less flashlight battery. Shpg. wt., 2½ lbs.

19 R 23002 Complete Kit (less battery) Net 29.95
99 R 62564 D Cell for above (2 Req.) Net .18

NEW!

MINILAB SCIENCE KITS

COMPLETE EASY-TO-BUILD SCIENCE PROJECTS

1⁹⁸



- Explains Scientific Principles Involved
- Instructions and Additional Experiments



ELECTRIC MOTOR KIT. Wind armature, construct motor, adjust speed running forward and backward. Illustrates electromagnetic principles. Less battery.

19 R 14027 Shpg. wt., 4 oz. Net 1.98
D Cell for above (1 Req.) Net .18

LENS AND LIGHT LAB. Convex and concave lenses are used to bend light, project and focus images, build a simple telescope and many other interesting lens activities.

19 R 14035 Shpg. wt., 4 oz. Net 1.98

HYDRAULIC PUMP KIT. Build working lift, force and compression pumps. Interior cylinder, piston valves and reservoir visible while pump is working. Shoots a stream of water 25 feet.

19 R 14043 Shpg. wt., 4 oz. Net 1.98

VISIBLE FLASHLIGHT KIT. Construct a rugged transparent flashlight and understand basics of electrical circuits and function of switches in controlling electricity. Less batteries.

19 R 14019 Shpg. wt., 4 oz. Net 1.98
D Cell for above (2 Req.) Net .18

WEIGHT MEASUREMENT KIT. Assemble an accurate double-platform scale using factory-accurate gram weights. Perform experiments in comparative weight measurement.

99 R 14050 Shpg. wt., 4 oz. Net 1.98

CAMERA AND PRISM LAB. Build a working pinhole camera. The prism, mirror and color filters permit experiments in bending and reflecting light and investigating the color spectrum.

19 R 14068 Shpg. wt., 4 oz. Net 1.98

ELECTRIC BELL KIT. Makes push-button bell, buzzer and telegraph key. Teaches how electricity and magnetism create sound. Morse Code. Less battery.

19 R 14001 Shpg. wt., 4 oz. Net 1.98
D Cell for above (1 Req.) Net ea. .18

SOLID-STATE TREASURE/METAL LOCATOR

• New Design Using Integrated Circuit

- Gives Positive Variable Audible Signal Indicating The Presence Of Buried Coins And Metal Objects
- Locates Both Ferrous Metals (Iron, Steel, Tin) And Non-Ferrous Metals (Gold, Silver, Copper)

Pays for itself many times over . . . opens up a new world of excitement and adventure. Electronically detects metal objects as small as a half-dollar up to 6 inches beneath the ground; gold, silver, coins, anything metallic. No meters or dials to check; solid-state integrated circuit gives positive audible low frequency beat heard through a built-in 2 1/4" speaker whenever a metal object is approached. Audible signal intensity increases when the treasure/metal locator draws nearer the object. Practical for home and public utilities (gas and telephone servicemen) too. Helps locate plumbing inside walls, or, find pipes in yard or garden before digging. Epoxied super-sensitive 5/2" coil is shock, heat and water resistant. Special shield increases sensitivity, prevents false indications. Lightweight and easy to use. 36" handle collapses to 20" for easy storage. Not a kit—electronics completely factory wired and tested—merely requires attachment of loop and handle. Uses single 9V., transistor battery (not supplied). Overall length: 40"; housing 4x5x2 3/4". Shpg. wt., 3 lbs.

19 R 67017 Treasure/Metal Locator—less battery. No Money Down* Net 29.95
99 R 60212 9V Battery. Shpg. wt., 3 oz. Net .29

Not a Kit—
Factory Wired

29⁹⁵



Find Buried
Coins and Metals

Locates Pipes
Inside

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 211



LAFAYETTE Solid State Modules

FOR HOBBYISTS, EXPERIMENTERS AND KIT BUILDERS



- All Solid State
- Completely Wired
- Compact Modular Circuitry

As Low As **1.49**

- Fully and Permanently Encapsulated
- Pre-Tested for Performance
- With Instructions and Parts List

Lafayette semiconductor modules are especially designed for many educational, enjoyable, and useful projects. Each permanent module encapsulates the complete solid state circuit required for each project, less accessories. With a few additional simple connections to

accessories below such as batteries, speaker, etc., you create an enjoyable and practical device. Every module is carefully checked for reliable performance. Supplied complete with instructions and parts list. Size: Approx. 1 3/4" x 1 1/4". Shpg. wt., 4 oz.

ELECTRONIC SIREN MODULE

Complete solid state electronic circuitry ready for immediate use as a modern efficient high volume siren. It will drive any 8 ohm P.M. speaker to a very high level of attention-getting volume with an upward scream and downward wail. Use with: A, H, I, J. See accessory list below. **Net 2.98**
19 R 55053

FM WIRELESS MICROPHONE MODULE

Ready for immediate use as an efficient wireless means of transmitting your voice over moderate distances within a home, from a high impedance microphone into any standard FM radio. Use with B, C, O, or P. **Net 2.98**
19 R 55277

BURGLAR ALARM MODULE WITH SIREN ALARM

Protect your home, car, boat, garage, etc., with this efficient burglar alarm module. Complete electronic circuitry with a built-in electronic high volume upward screaming siren as the alarm sounds. Use with: A, H, I, K. **Net 2.98**
19 R 55061

DUAL FLASHER MODULE

For Auto Road Warning Lights, Window and Counter Display, Attention Getters, Model Train Grade Crossings Flasher, Emergency Boat Flasher, Bicycle Rear Wheel Flasher, Alarm Indicator, etc. A complete solid state astable multivibrator with a cycling rate of about 100 times per minute. Use with: A, 2 ea. S, 2 ea. T. **Net 1.98**
19 R 55194

SIGNAL INJECTOR MODULE

For RF and AF Trouble Shooting. An efficient signal injector which generates a 2Kc audio frequency signal with modulated radio frequency harmonics up to 30 Mc. Enables isolation of defective electronic stages. Use with: D, E. **Net 2.98**
19 R 55269

CB MICROPHONE PREAMP MODULE

Effectively increases CB modulation for more dependable communications. More than doubles the sensitivity and output of your microphone when powered by a 1 1/2 volt battery. Use with: B, C, W, AA on accessory list. **Net 2.98**
19 R 55152

TELEPHONE AMPLIFIER MODULE

Compact module with complete solid state circuitry for use as a telephone amplifier. Permits group and conference listening to any phone conversation. Use with: A, H, Q, Y, DD. **Net 2.98**
19 R 55129

AM WIRELESS MICROPHONE MODULE

Transmit from your high impedance microphone (crystal, ceramic, high impedance dynamic) into any AM broadcast band radio in your home. Meets FCC regulations. No license or registration is required. Use with: D, E, O or P, BB. See accessory list. **Net 2.98**
19 R 55228

METRONOME MODULE

An excellent aid for keeping proper beat in music and dancing. Capable of reproducing beats at varying frequencies ranging from 40 cycles to over 300 cycles per minute. Use with: A, H, I, Z, DD. **Net 1.98**
19 R 55202

INTERCOM AMPLIFIER MODULE

A low cost highly efficient intercom module that facilitates conversations between two separate and remote points. Use with: A, L, U, CC and two H. **Net 2.98**
19 R 55137

PUBLIC ADDRESS AMPLIFIER MODULE

Complete solid state circuitry for immediate use as a public address amplifier and for use in portable high gain P.A. systems. Produces clear audio signal sufficient for large rooms. Ideal for small gatherings and business meeting. Use with: A, G, O or P, Y, DD. **Net 2.98**
19 R 55111

LAFAYETTE CONVERTER MODULES

LISTEN TO POLICE, FIRE, AIRCRAFT, AND SHORTWAVE ON YOUR PRESENT AM SET

VHF POLICE AND FIRE CONVERTER MODULE
Permits reception of police and fire calls in the 30-50 MHz band on your standard broadcast band AM radio. Use with D, E, BB. See accessory list below. **Net 5.00**
19 R 55205

SHORTWAVE CONVERTER MODULE

Same as above but tunes 25, 31, and 41 meter bands (7-12 MHz.). Use with D, E, BB. See accessory list below. **Net 5.00**
19 R 55301

FM VHF POLICE AND WEATHER CONVERTER MODULE

Permits reception of 150-164 MHz FM-VHF police, fire, emergency, marine and weather transmissions on a standard FM radio. Use with D, E, U, CC, BB. See accessory list below. **Net 5.00**
19 R 55368

AIRCRAFT CONVERTER MODULE

Same as above but for reception of 118 to 128 MHz. Band Use with D, E. See accessory list below. **Net 5.00**
19 R 55293

New you can have the thrill of listening to the exciting police broadcasts, the fire department calls, communications between planes and ground stations as well as international shortwave bands. Simple to connect to your present AM broadcast radio. Size: 1 3/4 x 3/4 x 1". Control extends 1 1/2". Shpg. wt., 4 oz.

ACCESSORIES FOR SOLID STATE MODULES ABOVE

Stock No.	Price	Description
A. 32 R 48184	1.13	Battery, 6 Volt Lantern
B. 99 R 62564	.18	Battery, 1 1/2 Volt "D"
C. 34 R 50137	.33	Holder for B
D. 99 R 60212	.29	Battery, 9 Volt
E. 99 R 62879	.29	Clips for D
F. 99 R 60329	.99	Speaker, PM, 8 ohm, 3"
G. 44 R 01030	5.95	Speaker, PM, 8 ohm, 8"
H. 32 R 22056	3.59	Speaker, PM, 8 ohm, 6"
I. 99 R 61509	.34	Switch, SPST, On-Off
J. 99 R 62184	.24	Switch, SPST, Push-Button, Momentary, NO.
K. 34 R 60029	.63	Switch, SPST, Momentary, NC
L. 30 R 41241	1.41	Switch, 4PDT
M. 99 R 25553	2.50	Telegraph Key
N. 99 R 45767	1.89	Microphone, Guitar Contact

Stock No.	Price	Description
O. 99 R 45106	1.95	Microphone, Lapel Crystal
P. 99 R 45437	2.49	Microphone, Hand Held/Desk Crystal
Q. 99 R 10340	1.49	Telephone Pickup Coil
S. 32 R 66194	.17	#47 Pilot Light Bulb
T. 32 R 28053	.29	Socket for #47 Bulb
U. 32 R 22510	.74	Potentiometer, 5,000 Ohm/SPST Switch
W. 32 R 22544	.74	Potentiometer, 1/2 Megohm with Switch
Y. 32 R 22551	.74	Potentiometer, 1 Megohm with Switch
Z. 33 R 11552	1.17	Potentiometer, 2 Megohm
AA. 32 R 13071	1.17	Microphone Cable, Shielded (Cut to 3 ft.)
BB. 32 R 31909	.49	Wire, Antenna (Cut to less than 10 ft.)
CC. 32 R 24052	.15	Knob, Miniature
DD. 32 R 24185	.17	Knob

BA Mod-u-Kits-Educational, Useful, And Fun to Build



A AM BROADCAST RADIO KIT
Learn as you build this fun-giving AM broadcast radio. Ingenious solid state circuitry uses a novel 2 transistor audio-reflex circuit with diode detection. Gives high gain at very low current drain. Complete with all parts, case, earphone and instructions. Supplied with matching transformer to permit use as an AM tuner. Powered by a single 9 volt battery. 3" x 2" x 1 1/4". Shpg. wt., 7 oz.
19 R 70029 less battery Net 4.95
99 R 60212 battery Net .29

B AIRCRAFT RECEIVER KIT
Listen to airplane to ground communications. Will pick up and amplify the strongest signals in its vicinity in the 100 to 200 MHz range. Has 3-stage high gain amplifier. Circuitry incorporates a passive detector that does not radiate signals. Does not interfere with aircraft navigational systems. Telescoping antenna. Supplied with earphone. Unplugging earphone disconnects power. Powered by a single 9 volt battery. DC Size: 3x2x1 1/4". Shpg., wt., 6 oz.
19 R70086 Less Battery Net 5.95
99 R 60212 Battery Net .29

C AM WIRELESS MIKE KIT
Transmits through any standard AM radio. Can be located up to 50-ft. away from set. Basic 2-transistor circuit. Frequency varied by tuneable coil. Complete with crystal mike and telescoping antenna. Size: 3x2x1 1/4". Shpg. wt., 6 oz.
19 R 70094 Less Battery Net 7.95
99 R 60212 9V Battery Net .29

E INTRUDER SOUND-LIGHT ALARM KIT
Novel security device detects intruders. Sounds picked up in room or house by microphone included and sensitive amplifier turns on light or sounds alarm. Sensitivity control sets noise threshold. Housed in walnut finished aluminum case. Size: 5x4x2 1/2".
19 R 70219 Shpg. wt., 1 lb. Net 19.95
Electric Alarm Bell 110 VAC for above.
99 R 70235 Shpg. wt., 1 lb. Net 2.95
Line cord for bell. Wt. 4 oz.
12 R 39011 Net .39

G PROXIMITY SWITCH KIT
An alarm at the touch of the hand! The Proximity Switch kit when properly built can be used as a special light alarm and night light. Can control devices using universal type motors up to 2 amps, and can

D 5-WATT UNIV. AMPLIFIER KIT
Excellent as a portable amplifier, guitar amplifier, etc. Complete with all parts, case, volume control, and instructions. Works on a 6-volt battery or power supply. Will accept almost any type of pickup device, i.e., phono cartridge, tuner, etc.; will work with any 3-ohm to 16-ohm PM speakers. 3" x 2" x 1 1/4".
19 R 70011 Shpg. wt., 7 oz. Net 5.95

F FM WIRELESS MIKE KIT
Transmits your voice to be picked up by any standard FM radio. 2-transistor circuit with an audio modulator, and R.F. oscillator. Frequency controlled by external trimmer condenser. Complete with mike and telescoping antenna. Size: 3x2x1 1/4".
Shpg. wt., 6 oz.
19 R 70102 Less Battery Net 8.95
99 R 60212 9V Battery Net .29

trigger off an alarm when used with a special transformer and AC supply. Touching a door knob or other chosen part switches circuit on! 4x3x1 7/8".
18 R 70045 Shpg. wt., 3/4 lb. Net 6.95

MOD-U-KIT PSYCHEDELIC LIGHT KITS

FREQUENCY CONTROLLED 3-CHANNEL PSYCHEDELIC CONTROL CENTER KIT
24⁹⁵
● Frequency Controlled 500 Watts Per Channel — 1500 Watts Total
A 3-channel sound to light control center providing frequency separation of the incoming sound into 3 parts: low frequencies — 60 Hz to 1 kHz, medium frequencies — 1 kHz to 3 kHz, high frequencies — 3 kHz to 15 kHz. Uses triacs to control 500 watts of light per channel for a total of 1500 watts. Each channel has its own sensitivity control and an AC outlet. On/off neon panel indicator. Size: 5x4 1/2 x 2 1/2".
19 R 70185 Shpg. wt., 1 1/2 lbs. Net 24.95

3-CHANNEL PSYCHEDELIC CONTROL CENTER KIT
12⁹⁵
● Responds to Intensity of Sound
● Provides 500 Watts Per Channel — 1500 Watts Total
Converts audio signals to 1500 watts of available external psychedelic lighting. The audio input signal is directly applied to 3 separate SCR's. Has 3 individual sensitivity controls for 3 separate channels each capable of accommodating 500 watts of external light. Housed in walnut finish aluminum case. Size 5x4x2 1/2".
19 R 70169 Shpg. wt., 1 1/2 lbs. Net 12.95

WIRELESS SOUND TO LIGHT CONVERTER KIT
NEW! 12⁹⁵
● Requires No Connection To Equipment
● Controls 500 Watts of External Psychedelic Lighting
Converts the rhythm and intensity of any sound, voice or music to psychedelic light keying signals. Extremely sensitive microphone included and high gain amplifier with sensitivity control, responds to all sounds anywhere in the vicinity. No wire hookup needed. Will modulate sound up to 500 watts of external lighting. Size: 5x4x2 1/2". Shpg. wt., 1 1/2 lbs.
19 R 70227 Net 12.95

SOUND TO LIGHT CONVERTER KIT
● Supplies 100 Watts Of Psychedelic Lighting!
5⁹⁵
Accepts sound from any radio, hi-fi, phono, or any amplifier and changes these direct audio signals to light keying signals. In addition to 4 colored pilot light indicators plugged into the unit, an AC socket supplies 100 watts of external psychedelic lighting which varies with the sound. Shpg. wt., 1 lb.
19 R 70151 Net 5.95

ELECTRONIC STROBE KIT
● 100 Watt Incandescent Lamp Strobe
9⁹⁵
This electronic strobe converts a 100 watt incandescent bulb into a strobe type lighting unit which gives eerie stopmotion and light-burst effects for light shows. An adjustable frequency audio oscillator and SCR circuit controls the lamp. The pulsations can be varied from fast to a one pulse per second slow rate.
19 R 70177 Wt., 1 lb. Net 9.95

9⁹⁵
19 R 70227

EICOCRAFT Solid-State Kits

- ★ EASY
- ★ FAST
- ★ EDUCATIONAL
- ★ USEFUL

NO TECHNICAL KNOWLEDGE OR EXPERIENCE NECESSARY

- Ideal For Science Fair Projects
- All Solid-State Circuitry
- Pre-Drilled, Copper-Plated Etched Printed Circuit Boards
- Comprehensive Step-By-Step Instructions

AS LOW AS
2.50



MINI COLOR ORGAN KIT

14.95

EC-3000. Converts your favorite music to an entertaining display of multicolor

3 dimensional patterns varying to the amplitude of the sound source. Molded plastic cabinet has 8 x 8" viewing screen. For 115 VAC 60 Hz. Shpg. wt., 1 1/2 lbs. For 115 VAC 60 Hz. Shpg. wt., 1 1/2 lbs. Net 14.95

ELECTRONIC STROBE-LIGHT KIT

NEW!
19.95



EC-3004 Xenon strobe light to provide the kaleidoscopic audio lighting now in use by combos, discotheques, etc. Has adjustable flash rate control. Ideal for home entertainment, decor and display use. Easy-to-build. For 115 VAC 60 Hz. Shpg. wt., 1 1/4 lbs. Net 19.95

"VARASPEED" MOTOR CONTROL KIT

13.95



EC-3600. Varies and controls the speed of power tools and appliances having AC/DC Motors. Handles up to 10 amps in a smooth continuous manner from 0 to full RPM. Has 3 position "Variable-Off-Full Speed" switch. Fused, with 3 wire receptacles and 3 ft. heavy-duty line cord. For 115 VAC 60 Hz. For 115 VAC 60 Hz. Shpg. wt., 12 oz. Net 13.95

TREASURE FINDER KIT

9.95



EC-1900 Battery operated beat-frequency locator can be used to locate both ferrous (iron, steel etc.) and non-ferrous (gold, silver, copper) metals. Has two RF oscillators and search loop. Distinctive audio variations in tone indicate the presence of buried metal objects over a wide area. Use with A. Shpg. wt., 6 oz. For 115 VAC 60 Hz. Shpg. wt., 6 oz. Net 9.95

FM WIRELESS MIKE KIT

9.95



EC-1100 Pocket size wireless FM microphone transmitter permits you to broadcast your voice or music through any FM standard broadcast radio or tuner, without any interconnecting cables. Broadcasts on vacant frequency in FM band. 90-100 MHz. No license or age requirements. Use with A. Shpg. wt., 6 oz. For 115 VAC 60 Hz. Shpg. wt., 6 oz. Net 9.95

ELECTRONIC ORGAN KIT

9.95



EC-2000 Battery operated one octave (8 tones) electronic organ. Supplied with a built-in preamplifier. Has outputs for mellow, bright or flute-like tones. Two or more can be played in-harmony to produce chords. An excellent multitone audio generator for testing. Use with A. Shpg. wt., 6 oz. For 115 VAC 60 Hz. Shpg. wt., 6 oz. Net 9.95

CODE OSCILLATOR KIT

EC-1000 Two transistor code practice oscillator produces strong, sharp tones. Can be used as monitor by paralleling an existing transmitter key. Other uses as bicycle horn, doorbell, entry signal, etc. Use with B, D and E. Shpg. wt., 4 oz. For 115 VAC 60 Hz. Shpg. wt., 4 oz. Net 2.50

ELECTRONIC BONGOS KIT

EC-1600. Electronically produces exciting percussive sounds of bongos, tomtoms, bass drum, marimba, gongs, etc. when used with amplifier and speaker. Ideal accessory for use with electronic guitars. Mounts on or near instrument. Use with B. Shpg. wt., 5 oz. For 115 VAC 60 Hz. Shpg. wt., 5 oz. Net 7.95

2 STATION INTERCOM KIT

EC-3100. Sensitive battery-operated 2-station intercom system for room-to-room and front-door communication. Master and remote stations have beep-tone call signal. Kit includes battery, 50-ft. wire, and plastic cabinets. For 115 VAC 60 Hz. Shpg. wt., 1 lb. Net 10.95

VOICE-OPERATED SWITCH KIT

EC-1300. An audio-activated relay amplifier for audio remote control of such devices as tape recorder, radio, TV, etc. Activated by music as well as voice. Provides variable time delay (adjustable). Use with B. Shpg. wt., 6 oz. For 115 VAC 60 Hz. Shpg. wt., 6 oz. Net 8.95

LOW BAND POLICE AND FIRE CONVERTER KIT

EC-2700. An RF converter operating in the 30-50 MHz VHF band which permits you to hear police, fire and emergency services on your standard AM radio. Inductively coupled without interconnecting wires. Use with A. Shpg. wt., 5 oz. For 115 VAC 60 Hz. Shpg. wt., 5 oz. Net 7.95

FM RADIO KIT

EC-1400. Receives the FM broadcast band from 88-100 MHz. May be used as a private listening personal radio with earphone supplied, or as an FM tuner when coupled with audio amplifier such as EC-300. Use with B. Shpg. wt., 6 oz. For 115 VAC 60 Hz. Shpg. wt., 6 oz. Net 9.95

FUZZBOX KIT

EC-2500. Creates a wide variety of synthesized tones consisting of multiple harmonics and square waves to produce the fuzz sound. Mounts on guitar amplifier with ON-OFF slide switch which mounts on guitar. Use with A. Shpg. wt., 6 oz. For 115 VAC 60 Hz. Shpg. wt., 6 oz. Net 8.95

AC POWER SUPPLY KIT

EC-900. Transformer operated full-wave bridge rectifier power supply converts house current (110-125 VAC) to 6V DC. It can power all Eicocraft kits using 6V batteries, eliminating battery operation and converting to AC use. Shpg. wt., 13 oz. For 115 VAC 60 Hz. Shpg. wt., 13 oz. Net 8.95

HI BAND POLICE AND FIRE CONVERTER KIT

EC-2900. Convert your standard (car or home) AM radio to receive police, fire, marine and weather broadcasts in the 152-174 MHz VHF band. Inductively coupled without interconnecting wires. Use with A. Shpg. wt., 5 oz. For 115 VAC 60 Hz. Shpg. wt., 5 oz. Net 7.95

AUDIO POWER AMPLIFIER KIT

EC-300. General purpose 2-watt audio amplifier. Accepts microphone, phono cartridge, radio, recorder and other high-level inputs. Two used for stereo. Handles one or more speakers for intercom, PA, or long distance calling. Use with B and E. Shpg. wt., 5 oz. For 115 VAC 60 Hz. Shpg. wt., 5 oz. Net 5.95

ELECTRONIC "MYSTIFIER" KIT

EC-700. A fascinating "do nothing" relaxation oscillator circuit of 6 blinking lights whose random geometric sequence of blinks you control. An ideal conversation piece for desk, den or mantle. Use with C. Shpg. wt., 5 oz. For 115 VAC 60 Hz. Shpg. wt., 5 oz. Net 4.95

EICOCRAFT KIT ACCESSORIES

A. 99 R 60212 Battery, 9 Volt Net .29
B. 99 R 48184 6V. Lantern Batt. Net 1.13
C. 99 R 48515 Battery, 90 Volt Net 2.98
D. 99 R 25546 Telegraph Key Net .79
E. 99 R 60394 3.2 Ohm, 2 1/2" spkr. Net .99

For Suitable Enclosures See page 295

Educational Science Specialties

GILBERT TRI-LAB-PAK 3 SCIENCE KITS IN 1!

- Over 95 Experiments in Microscope Observation, Chemistry and Geology
- Illuminated 75x Microscope
- Includes Chemicals, Specimens and Apparatus

10⁹⁹



Ideal for fascinating hours of microscope observation, chemical experimentation and geological exploration by the junior scientist. Complete instruction manual explains manufacture of inks, soaps, and dyes, chemical experiments, geological procedures and mineral identification and techniques of the microscope. Equipment for over 95 experiments includes: illuminated die-cast metal 75x microscope, slides, 9 bottles of chemicals, test tubes and rack, alcohol lamp with blowtorch, mineral specimens and identification wall chart, geologists hammer, and other associated lab testing apparatus and tools utilized in laboratory experimentation. Complete with detailed instruction manual. Shpg. wt., 5 lbs.

19 R 34090

Net 10.99

GILBERT WEATHERCRAFT METEOROLOGY LAB

- Build and Use Barometer, Wind Vane, Psychrometer and Rain Gauge
- Forecast Weather Accurately

9⁹⁹



Be your own meteorologist and simply forecast the weather. This deluxe weather laboratory kit contains every instrument necessary for extremely accurate weather prediction. Includes: a wind vane to show wind direction and an anemometer to give its speed; a compensated aneroid barometer provides barometric pressure; a psychrometer determines relative humidity; a set of graphs for charting air pressure and temperature; a detailed weather map and cloud chart. A gauge measures rainfall to 1/100th inch, and a detailed manual shows how to make accurate forecasts. Requires 2 "C" batteries, not supplied. Shpg. wt., 3 lbs.

19 R 34082 Less Batteries

Net 9.99

99 R 62572 1.5v C battery (2 required)

Net ea. .16

WEATHER STATION KIT



FOR ONLY 10⁹⁵

Fun to erect and fascinating to use, this weather station kit operates with flashing neon lights to show wind speed and direction on indoor indicator board. Includes a sensitive air tank barometer with 4-ft. indicator column, a sling psychrometer to measure relative humidity, rain gauge with scale calibrated to measure 1/100th of an inch rainfall, cloud chart, weather map and forecasting manual. 150 ft. wire supplied, enough for a 2-story house. Safety power cord. All connections safe to touch. Shpg. wt., 3 3/4 lbs.

19 R 30023

Net 10.95

NOVATRON

A SCIENTIFIC INSTRUMENT FOR THE EXPERIMENTER

- Miniature Atom Smasher
- Produces 75,000 Volts
- Absolutely Safe

Completely Wired (Not A Kit)



A scientific instrument capable of producing 75,000 volts—makes sparks up to 2" long—yet it is absolutely safe because the current is infinitesimal. The science-teacher—science lover—or hobbyist can perform experiments to astound students—friends—family. Makes smoke disappear—defy gravity—turns propellers at a distance—transforms atomic energy into light—makes artificial lightning—smashes atoms—demonstrates ionic space ship drive—and many other experiments. Includes an experimental kit and illustrated experiment manual. A fine research tool that will give years of beneficial service. 110 VAC. Imported. Assembled.

99 R 90086 Shpg. wt., 3 lbs. Net 13.95

ELECTROCAST MASTER ELECTRIC BUILD-IT SET



8⁹⁵

An advanced but completely safe educational kit in the field of electricity that enables the student to make any one of over 30 projects including motor driven hot rod, motor driven dune buggy, lamp, flashlight, electro-magnet, telegraph set, electric crane and many others. All projects are battery operated. Easy-to-read, illustrated 76-page instruction manual. Size: 2 1/2 x 1 3/4 x 2 1/4". Shpg. wt., 2 1/2 lbs.

19 R 64030 Less Batteries Net 8.95

Batteries For Above

99 R 62564 "D" 2 req. Net ea. .18

99 R 62580 "AA" 2 req. Net ea. .10

SKY ROVER CRYSTAL RADIO KIT



3⁰⁰

Easy to assemble, brings in loud, clear reception. Precision wound tuning coil, super-sensitive crystal, bakelite cabinet. No batteries or electricity required. Complete with earphone with plastic ear-holder, antenna lead-in wire, and hardware. Requires external antenna (not supplied).

19 R 58024 Shpg. wt., 1 lb. Net 3.00

Antenna kit. WL, 1 1/4 lbs. Net 2.35

32 R 30984

Net 2.35

ATOMIC ENERGY LAB



9⁹⁵

Ingenious kit for studying some basic nuclear physics by experimentation. See the vapor trails of alpha and beta particles, and of cosmic rays. Shows exploding atoms. Instruction book covers such experiments as detecting radioactivity with a cloud chamber, with a spintharoscope, and with radio-autographs; checking radioactivity with an electroscope, detecting ionization and others. Kit includes radioactive materials. Shpg. wt., 3 1/2 lbs.

19 R 30015 Net 9.95

MINERAL TEKNIKIT SET 1



As Low As

2⁵⁰

Contains 48 specimens of ore, organics, fossils, elements, plutonics, oxides, volcanics, hypabyssals, effusive crystals, common and uncommon minerals. Each specimen is tagged with name and classification. An excellent introduction to rock and mineral identification. Imported. Shpg. wt., 1 1/2 lbs.

99 R 71557 Net 2.50

SET II includes additional specimens of some of above plus carbonates, tantaline, phosphates, and gemstones. 48 specimens. Imported. Shpg. wt., 1 1/2 lbs.

99 R 71565 Net 2.95

Special Combination. Buy both sets and save. You get all 96 specimens. Shpg. wt., 2 3/4 lbs.

99 R 71573M Net 4.50


Depend on Lafayette For Complete Stocks, Lowest Prices, Fastest Service

Lafayette Cal. No. 720 215

Solid State Audio Amplifiers, Tuner and

5-TRANSISTOR PUSH-PULL AUDIO AMPLIFIER


• 360 MW. Output



A more powerful and sensitive version of the 4-transistor amplifier on right, this amplifier employs 3 stages of audio driving a push-pull output stage. Power output is 360 mw, designed for speakers with a voice coil impedance of 8-11 ohms. Low impedance input has sensitivity of 300 microvolts. Input transformer for matching high impedance to the amplifier input available as an accessory (see below). Comes with leads for low impedance input, speaker, volume control/on-off switch. Battery clips and leads supplied for 9 volt miniature battery (one required). Imported. Shpg. wt., 5 oz.
Use with accessories below. A, D, H, or I, and J.
99 R 90375 Net 5.85

4-TRANSISTOR SUBMINIATURE PUSH-PULL AUDIO AMPLIFIER


• 100 MW. Output



A tiny, transistorized push-pull audio amplifier with a multitude of applications. Only 3" x 1 1/4" x 1/4", it can be mounted inside other equipment to serve as a subminiature phono amplifier, tape recorder, amplifier, etc. Two stages of audio are followed by a push-pull output stage designed to deliver 100 mw to an 8-11 ohm impedance. Low impedances input, with a sensitivity of 0.9 mv. Input transformer for matching high impedances to the amplifier available as an accessory (see below). Includes leads for input, speaker, and volume control/on-off switch. Battery clips and leads supplied for 9-volt miniature battery (one required). Imported. Shpg. wt., 4 oz.
Use with accessories below. A, E, H, or I, and J.
99 R 90425 Net 4.95

1-WATT 4-TRANSISTOR PUSH-PULL AUDIO AMPLIFIER


- 1-Watt Power Output
- 4-Transistors plus Varistor
 - Completely Wired—Easy to Connect
 - Sturdy Printed Circuit Construction
 - Audio Output Transformer



One of our most powerful miniature amplifiers. It has many direct uses in audio frequency applications for tuners, test equipment, etc. Push-pull circuit is very sensitive and has an output of 1-watt! Using only 4 transistors, it requires a 12-volt source supplied by Standard 'D' cells in series. Outputs from record players with magnetic cartridge, tape heads, microphones, etc. (not exceeding 20 millivolts) can be connected directly. Higher output devices may be easily connected with a resistor in series. Components are neatly laid out on a printed circuit board with pre-drilled holes for mounting the entire unit in a vertical or horizontal position. Built-in leads are supplied for a volume control, on-off switch, battery and 8 ohm loudspeaker. Dimensions: 4 1/4" x 1 1/2" x 2 1/4". Imported. Shpg. wt., 5 oz.
99 R 90383 Use with accessories B and C below. Net 6.95

3-TRANSISTOR SUBMINIATURE AUDIO AMPLIFIER

3.75



- Printed Circuit
- Complete with Transistors

Here is an amazing little audio amplifier with a multitude of challenging applications; i.e., subminiature phono amplifier, tape recorder amplifier, hand-held public address amplifier, telephone pick-up amplifier, etc. Output sufficient for average listening. Has leads for any one of the following inputs: Tape recorder record/play-back heads, radio-tuner, crystal or ceramic phono cartridge, and crystal or ceramic microphone. Has lead terminations for ON-OFF switch, Volume Control, 4 to 10 ohm speaker, and leads terminating in clips for a 9-volt miniature battery. Size: 2 1/4" x 1 1/4" x 3/4". Can be readily mounted on chassis. Imported. Shpg. wt., 4 oz.
Use with accessories A, C, F, and G below.
99 R 90391 Net 3.75

CODE OSCILLATOR MODULE

98c



- Matchbook Size
- Drives Any PM Speaker

Transistorized code oscillator module ready to connect to your telegraph key, and 1 1/2 to 6 volt battery and any PM speaker. Provides clear tone—ideal for learning Morse code. Simple connecting instructions and schematic included. Shpg. wt., 3 oz.
19 R 15131 Net .98


ACCESSORIES FOR AMPLIFIERS AND TUNER ON THIS AND FACING PAGE

A.	99 R 60212* 9 Volt Battery 3 oz.	Net .29
B.	99 R 62564* "D" Cell Battery 5 oz.	Net .18
C.	5,000 Ohm Volume Control/Switch/Knob, 2 oz.	Net .59
D.	99 R 60196*	
	10,000 Ohm Volume Control/Switch	Net .74
	32 R 22528*	
E.	100,000 Ohm Volume Control/Switch, 3 oz.	Net .74
	32 R 22535*	Net .99
F.	99 R 45130* Crystal Microphone, 3 oz.	Net .99
G.	99 R 60972* 2 1/2" 10 Ohm Speaker, 5 ozs.	Net .99
H.	99 R 60329* 3" 8 Ohm Speaker, 2 oz.	Net .99
I.	99 R 60360* 2" 8 Ohm Speaker, 2 oz.	Net .99
J.	Matching transformer (high impedance to amp.)	
	99 R 60345* Wt., 2 oz.	Net .99

* Imported

..... Accessories For Experimenter and Hobbyist

1 WATT, 4 TRANSISTOR, DIRECT OUTPUT PUSH-PULL AUDIO AMPLIFIER



6⁹⁵

- 1 Watt Push-Pull Power Output
- 4 Transistors Plus Thermistor
- Completely Wired—Easy to Connect
- Direct Output—8 and 16 Ohms

Amazingly powerful miniature solid state audio amplifier with many direct uses in audio frequency applications for tuners, test equipment, as a phono amplifier, tape recorder amplifier, public address or telephone pick-up amplifier, etc. Push-pull circuit has an output of 1 watt. Using 4 transistors and a thermistor, it requires a single 9 volt battery. Direct output into 8 or 16 ohm speakers for minimum distortion. Can be readily mounted on chassis. Dimensions: 4 7/8" x 1 1/2" H x 2 1/4" W. Shpg. wt., 6 oz. Imported. Use with accessories A, E, and H. (See p. 216.)

99 R 90979

Net 6.95

3 WATT 4 TRANSISTOR PUSH-PULL AUDIO AMPLIFIER



7⁹⁵

- 3 Watt Push-Pull Power Output
- 4 Transistors Plus Thermistor
- Completely Wired—Easy to Connect

A mighty amplifier with 3 watt push-pull output which fits in the palm of your hand and weighs less than 6 oz! This versatile general purpose amplifier suitable for phono amplifier, public address, intercom, monitor modulation, test equipment and a host of other uses. Sensitive 4 transistor push-pull circuitry has 3 watt output, requiring a 9 volt DC source. Frequency response 150-10,000 cps; input impedance 2,000 ohms; Output impedance 8 and 16 ohm terminations. Components neatly laid out on printed circuit board with pre-drilled holes for horizontal or vertical mounting. Heat sink for power transistors. Dimensions: 3L x 2 3/8" W x 1 3/8" H. Imported. Shpg. wt., 8 oz. Use with accessories: D, and H. (See p. 216)

99 R 91324

Net 7.95



22⁹⁵

20 WATT STEREO SOLID STATE AMPLIFIER MODULE

- 2-IC's and 8-Transistors
- Separate Bass and Treble Controls
- Frequency Response 30 Hz to 40 kHz
- Includes Rectifier and Filter

This especially fine transistor stereo amplifier delivers 10 watts per channel continuous power (RMS) into any 8 ohm speaker. Has 2-IC's and 8-transistors. The separate bass and treble controls allow 20 db adjustment at 100 Hz and 10 kHz. The dual volume control allows simultaneous increase in volume of both channels, while the balance control allows compensation for program variations. The low noise preamp stage provides a sensitivity of 0.5 volts for use with a ceramic phono cartridge or a AM/FM tuner. The direct coupled complementary symmetry circuit gives a Hi-Fi frequency

response of 30 Hz to 40 kHz \pm 3 db. Includes the power supply components except a power transformer. Size: 7 3/8" x 1 3/8" x 4 3/8".

19 R 09159 Shpg. wt., 1 1/2 lbs.

Net 22.95

Same model as above but on two separate printed circuit boards for compact mounting. Control strip size: 7 3/8" x 1 1/2" x 1 1/8". Power amplifier size: 7 3/8" x 1 1/2" x 2 3/8" D. Shpg. wt., 1 1/2 lbs.

19 R 09167

Net 22.95

Power transformer for above amplifier modules. Shpg. wt., 1 3/4 lbs.


Net 2.95

19 R 09175

To Speed Your Mail Order—Please Give Your Zip Code Number

Lafayette Cat. No. 720 217

3-TRANSISTOR SUBMINIATURE AM BROADCAST TUNER



• 540 kHz to 1600 kHz

- 4 TRANSFORMERS: Exceptional Superhet Sensitivity and Selectivity

7⁹⁵

A deluxe 3-transistor subminiature AM broadcast tuner that features 3 dependable transistors, 3 IF plus 1 oscillator transformer, and ferrite antenna in an efficient, completely wired superheterodyne circuit on a sturdy printed-circuit board.

Now you can build your own highly efficient broadcast receiver by simply adding this exceptional tuner to any of the transistor audio amplifiers listed. The long tuner leads for connecting to external amplifier and/or to a separate 9-volt battery, makes this easy as pie. Also features a large clearly visible calibrated tuning dial. The printed circuit board layout permits either vertical or horizontal mounting. Supplied complete with mounting brackets and detailed instructions. Size: 4x1 3/4x2 1/2" H with brackets. Imported. Shpg. wt., 7 oz.

99 R 90409

Net 7.95

ADJUSTABLE POWER SUPPLY KIT



Only
12⁹⁵

- Simple To Build
- Variable 0-12VDC
- Up to 1 Ampere Current
- Ideal Power Supply For Modules On This and Facing Page

This simple-to-build power supply is ideal for any application requiring a low voltage DC source of power to be used as an alternative to batteries. Plugs into regular 110 volt AC current and delivers DC voltage which you can adjust from 0 to 12 volts at a current drain of up to 1 ampere. A neon indicator light is supplied to indicate if the 110 AC power is on. Uses a special transformer that supplies approximately 16 VAC to a full wave bridge circuit. The DC produced is fed into a special dual transistor filter and regulating circuit. The base voltage of the first transistor is made variable by means of a control. Size: 4x4x1 1/2". Shpg. wt., 1 3/4 lbs.

19 R 70110

Net 12.95


Rock Polisher & Specialty Items

GEM STONE TUMBLING AND JEWELRY MAKING KIT

- Grinds and Polishes Rocks and Gem Stones
- Complete Outfit, Nothing Else to Buy

Only
23⁹⁵

THUMLERS TUMBLER



Only
18⁹⁵

- Grinds and Polishes Rocks, and Gem Stones

A fascinating hobby-craft. You can polish all rocks to a sleek, gleaming gem-like finish. Use them for decoration, put in settings, etc. Tumbling machine has two side by side barrels with a total capacity of approx. 6 lbs. of stones. This is not a knock-down kit, but a completely assembled unit ready to run with powerful continuous duty motor that operates on standard 110 VAC current. Size: 7"x9"x11". Complete with cans, but less grit and can liner. See listing on left for additional accessories. Shpg. wt., 7 1/4 lbs.

15 R 44014 Net 18.95

Accessory pack. Ass't. of coarse and fine grits, pre-polish and polish, and liners for above drums. Shpg. wt., 2 1/2 lbs.

15 R 44022 Net 2.95

Extra Cans For Above Tumbler.

15 R 44048 Shpg. wt., 8 oz. Net ea. .39

Extra Rubber Liners For Above. (Pkg. of 2).

15 R 44055 Shpg. wt., 8 oz. Net .89

ACCESSORIES FOR TUMBLERS

Stones. 1 lb. pkg. of Oregon Beach Agate and Jasper. Shpg. wt., 1 1/2 lbs.
15 R 44030 Net 1.89

Deluxe Rough Stone Assortment. Approximately 200 agate and rose quartz, tiger eye, jasper, etc. Exotic colored rock is from all over the world; will polish to a jewelry like finish.
15 R 58014 Shpg. wt., 3 lbs. Net 2.95

Grit and Polish Assortment Kit. Provides everything needed to polish rocks. Packed in resealable plastic container. Each kit contains graded silicon carbide grit and fine polish compound for fast grinding and fine finishes. Each set will process 14 lbs. of rock.
15 R 58030 For Rough Rocks, 4 step. Shpg. wt., 5 lbs. Net 3.95

PROFESSIONAL 12 POUND HEXAGONAL TUMBLER

- Heavy Duty Motor With Overload Protection
- Nylon Bearings For Smooth Operation And Long Life
- Vinyl Covered Rollers For Quiet Rotation
- UL Listed

44⁹⁵ No Money Down*



This professional rock tumbler is ruggedly designed for long, hard wear. The heavy gauge steel hexagonal drum has a 12 pound (9 pints) capacity. Features an overload protected, continuous duty fan cooled motor . . . runs over 50° cooler. Shuts off automatically when motor overheats. Prevents burnt-out motor should power fail or circuits overload. Neoprene gasket and rubber double seal prevents leakage and gas build-up. Sturdy wood grained steel base covers protect motor from dirt and grit. Easy to clean. Shpg. wt., 21 lbs.
15 R 58055W Net 44.95

JEWELRY MAKING KIT

- Jewelry Blanks For Mounting Polished Stones




4⁹⁵

This high quality Hamilton gold plated 38 piece jewelry finding assortment enables you to mount your semi-precious stones that have been polished. Makes earrings, tie clasps, bracelets, cuff links, key ring, tie tack, necklaces, adjustable finger ring, etc. from these commercial findings. Kit also contains jump rings, bell caps and a tube of jewelers on-off cement—everything you need. Shpg. wt., 8 oz.

15 R 58063 Net 4.95

ALL-TRANSISTOR BULL HORN

Made in U.S.A.
Only **8⁹⁵**
NOT A KIT COMPLETELY PREASSEMBLED



- Range up to 400 feet
- Weighs only 2 1/2 lbs.
- For Hunting, Camping, Boating, Sports

A fully transistorized directional megaphone at Lafayette's low price. Lightweight, it carries your voice over 100 yards or above noise. Just press the trigger and talk. Features variable volume control and carrying strap. Uses 4-standard "D" cells (not supplied with unit). 11" long. Shpg. wt., 2 lbs.
44 R 15097 Net 8.95
1 1/2-volt D batteries, 4 required. Imported. Shpg. wt., 5 oz.
99 R 62564 Net ea. .18

PHILMORE DUAL BAND BROADCAST SHORTWAVE RADIO KIT

ONLY **14⁶⁵**

- 2 Bands 550-1650 kHz, 3-13 MHz



This radio covers the standard broadcast band from 550 to 1650 kHz and a shortwave band from 3 to 13 MHz. Modern circuitry with enough audio to drive a built-in 3/4 inch speaker. Be rewarded with the satisfaction of having built a radio which will actually pull in standard broadcast, amateur and other shortwave stations. Includes punched chassis, grey hammettone panel, 3 1/2" speaker, pictorial and schematic diagrams and easy-to-follow instructions. Complete with all hardware: less solder, wire and tubes. Tubes required: 1—50C5, 1—12AU6 plus 1—35W4 rectifier. For 105-125 volts, AC or DC. Shpg. wt., 3 3/4 lbs.


19 R 58016 MODEL 7001CR. Net 14.65

Shortwave antenna kit for above.

32 R 30984 Shpg. wt. 1 1/4 lbs. Net 2.35

Hobby Kits & Specialties

RENWAL VISIBLE V-8 ENGINE KIT



9⁹⁵

Looks And
Performs Like
The Real Thing

The Visible V-8 is a superb guide to the study of the internal combustion engine. Precise 1/4 scale "see-thru" model engine that simulates the power plant of V-8 autos. Parts molded in 4 colors, including "clear", so that functioning pistons, connecting rods, rocker arms and properly timed spark plugs can be observed. Powerful permag motor activates over 100 moving parts. Powered by two "C" batteries (not supplied). Complete with polystyrene cement, hardware, screwdriver, and illustrated instruction manual which details how an auto engine works. Shpg. wt., 5 lbs.

19 R 69005 Complete Kit Less Batteries Net 9.95
99 R 62572 1.5V "C" battery (2 required) Net ea. .16

GILBERT DELUXE CHEM-CRAFT KIT



- Full Range of Chemicals and Supplies
- File Cards for Over 700 Experiments
- Six Storage Modules in Metal Case

Ideal deluxe chemistry lab kit for experimenters, hobbyists, students. Conduct over 700 programmed experiments in chemical gardening, analytical testing, spectroscopy analysis, cold fuel rocketry and many more. 6 modular storage racks hold over 26 chemicals and supplies. Advanced equipment includes precision lab scale and weights, hydrometer, spectroscope, hydroponics tray, alcohol lamp and blow pipe, plus all basic lab equipment such as test tubes, etc. Detailed instructions and lab procedures. Shpg. wt., 12 lbs.

19 R 34074 Net 16.95

PHOTOGRAPHY DARKROOM LAB WITH ENLARGER

14⁹⁵




- Complete Darkroom Outfit
- Photo Enlarger, Contact Printer, 35mm Projector — All in One Kit

Photography lab kit enables you to print and develop your own photos, enlarge 35mm shots up to 8x10", and project your 35mm negatives. Kit includes developing chemicals, printing and enlarging paper, 3 trays, thermometer, neon safelight, print frame taking slides up to 3 1/2 x 4 1/4", twin condensing lenses and G.E. projection lamp. A complete photo lab in one kit. Shpg. wt., 4 1/4 lbs.

19 R 30031 Net 14.95

VASHON ROCKET AND ROCKET PLANE KITS



- As Low • Looks And Performs Like The Real Thing
- As • Safe, Non-Flammable Non-Toxic Propellant
- Altitude Capability Over 1000 Feet
- Reusable With Parachute Recovery

10⁹⁵

VALKYRIE-2 ROCKET KIT

- Launched Mechanically or Electrically

Here is an authentic, educational and yet entirely safe rocket kit for modelers and hobbyists which demonstrates the principles of rocket propulsion. The propellant releases no heat, is non-flammable, non-toxic and non-explosive. The 18 1/2 inch long Valkyrie-2 which blasts off to 1000 feet, can be safely held in hand. Uses durable polished aluminum rocket, engine and parts, with seal working valves, separator and parachute. At liftoff, the rocket starts slowly at 4 "G's," with acceleration at burnout about 10 "G's." A timer assures deployment of the parachute which returns the rocket for another launch. May be either mechanically or electrically launched with a battery (not supplied). Complete kit includes rocket, engine, timer, separator, parachute, balsa nose cone, fins, loading valve and hose, electric firing assembly, launch stand, one can of propellant, accessories and instructions. Size: 18 1/2" long x 1" dia.

19 R 75010 Complete Rocket kit. Shpg. wt., 2 3/4 lbs. Net 12.95
15 oz. can of propellant sufficient for 3 launchings.
19 R 75028 Shpg. wt., 1 1/2 lbs. Net 2.00
6-Volt battery for electrical launching.
32 R 48184 Shpg. wt., 1 3/4 lbs. Net 1.13
Replacement Ignitor wire for electrical launching.
19 R 75036 Shpg. wt., 3 oz. Net .35

VIKING TWO STAGE ROCKET KIT

The Viking is a complete, high performance, functioning two stage rocket with staging mechanism for in-flight separation. The first stage boosts the rocket to about 75 feet where a "burn-out" signal triggers the second stage engine. This accelerates to a velocity of 300 feet per second (200 miles per hour) while the first stage drops away. This velocity carries the second stage well over 1000 feet, where a parachute is automatically deployed to return it. All parts are recovered for future flights. Both engines are the same—reloadable, highly polished aluminum construction, pre-assembled and factory tested, each using 2 ounces of propellant per flight. The kit is complete including launcher, 15 ounce can of propellant, clear, concise instructions and a booklet on the principles of multi-staged rockets. Size 20" long x 1" dia.

19 R 75051 Complete Kit. Shpg. wt., 3 1/4 lbs. Net 14.95
15 oz. can of propellant, sufficient for 3 launchings.
19 R 75028 Shpg. wt., 1 1/2 lbs. Net 2.00

BARON ROCKET PLANE KIT

The bright red Baron Rocket Plane is a combination of a rocket and a plane. The rocket carries the plane up hundreds of feet, then catapults the plane free, at the height of its flight. While the Baron glides high in the sky, the booster rocket parachutes to earth. The aluminum booster rocket engine uses a non-flammable, non-explosive aerosol propellant and may be launched alone. The kit is complete with factory assembled and tested engine, fins, nose cone, parachute, 7 oz. can of propellant, decals, etc. and clear illustrated instructions. Size: 22 1/2" long x 1" dia. Shpg. wt., 2 1/2 lbs.

19 R 75069 Complete rocket plane kit Net 10.95
15 oz. can of propellant.
19 R 75028 Shpg. wt., 1 1/2 lbs. Net 2.00

To Speed Your Mail Order—Please Give Your Zip Code Number

Lafayette Cat. No. 720 219

FLY THE BIG SKYHAWK BY REMOTE CONTROL

COMPLETE OUTFIT:
Plane, Receiver, Transmitter,
Batteries and Charger for
Plane



TESTOR'S R/C SKYHAWK



Only **79⁹⁵**
No Money Down*

Simple snap in wing and ready to fly radio controlled plane which incorporates true (pulse) proportional control for smoother, more realistic flight control. This plane is so easy to fly that it is recommended for beginners—no electronic or mechanical skill is required. Aircraft fuselage constructed of virtually indestructible super-impact styrene. Wings and horizontal stabilizer are of super light styrofoam. Tricycle landing gear assures simple landings. High torque .049 cubic inch internal combustion engine has gas tank attached for 4 minutes of powered flight. Super sensitive 9 transistor superhet receiver combines with a powerful dual coil, twin magnet actuator

for superior reliability, 8 transistor 250 milliwatt transmitter provides up to one mile range control. Simple guidance controls include finger tip trim for basic in-flight stabilization. Transmitter powered by eight 1½V penlite cells (not supplied). Complete with R/C plane, transmitter, battery charger, and illustrated flying instruction book. Shpg. wt., 7 lbs.

42 R 73017W for 27.145 MHz	Net 79.95
42 R 73058W for 26.995 MHz	Net 79.95
42 R 73090W for 27.195 MHz	Net 79.95
99 R 62580 1½V Penlite cells — 8 required.	Net ea. .10

SKYHAWK SPECIFICATIONS

Length: Fuselage 27". Wing 44". Flying Weight: 23 ounces (approximately). Speed: 30 MPH True. Fuel Capacity: 4 Minutes powered

Flight: Transmitter: Single Tone AM Modulated Relayless Pulse. Receiver: Superheterodyne With Pulse Width Rate Decoders.

REMOTE CONTROL MUSTANG GT OUTFIT

No License Required



Testor's
R/C Mustang

COMPLETE OUTFIT:
Mustang, R/C Receiver,
R/C Transmitter, Car
Batteries, and Charger

79⁹⁵
No Money
Down*

- Completely Assembled—Ready To Use
- Twin High Torque Drive Motors
- Rechargeable Car Batteries with Charger
- Electronic "Relay-less" Drive Control

Authentic 1/11th scale model R/C Mustang GT. Fully-assembled. Car body of glossy polystyrene. Durable chassis is tempered aluminum. Twin high torque drive motors are coupled to rear wheels through an electronically controlled 4 transistor rear end... achieves true differential action! True (pulse) proportional circuitry permits feather-touch control. Guidance controls include steering (left-center-right), drive motor (start-stop) and speed (high-low). Super sensitive 9 transistor receiver combines with powerful dual coil, twin magnet actuator for superior reliability. 8 transistor 100 milliwatt transmitter provides convenient control board. Transmitter powered by eight 1.5V penlight cells, (not supplied). Complete with R/C model transmitter, and battery charger. Shpg. wt., 7½ lbs.

42 R 73033W for 27.095 MHz	Net 79.95
42 R 73108W for 26.995 MHz	Net 79.95
42 R 73124W for 27.195 MHz	Net 79.95
99 R 62580 1½V Penlight Cell, 8 req.	Net ea. .10

MUSTANG GT SPECIFICATIONS

Length: 16 inches. Width: 6 inches. Height: 4 inches. Weight: 2 lbs., 8 ounces. Speed: 100 MPH Scale. Turning Radius: 3 feet. Transmitter: Single Tone AM Modulated Relayless Pulse. Receiver: Superheterodyne With Pulse Width Rate Decoders.

220 Lafayette Cal. No. 720

Jerobee COMMANDO RADIO-CONTROL RACING CAR

NEW! **89⁹⁵**
No Money Down*



- Completely Assembled Racing Car, Engine, and Radio-Control System
- Races at Up to 240 Scale Miles per Hour
- Fully Proportional Steering and Throttle

Enjoy the unbeatable excitement of driving a 1/12 scale gas powered racing car with all the sound, action, speed, and thrills of the track... on any concrete or asphalt surface. The 'Commando' features independent front suspension, Ackerman steering, centrifugal clutch, heavy-duty rear axle and 'mag' type wheels. Rugged high-strength cyclac® body and molded frame. 100 milliwatt radio control system (No FCC license required) has fully proportional simultaneous dual-servos for separate steering and throttle control for a range of 200 feet. Car automatically stops when control range limit is reached. .049 Cox engine with recoil pull starter provides speed of 240 scale mph. Receiver powered by 4 AA penlite cells (not supplied), transmitter powered by 9V battery (not supplied). Overall length: 13¼"; turning radius: 4". Complete package supplied ready to race, less only fuel and batteries, including operating manual. Available in five frequencies. Shpg. wt., 40 lbs.

42 R 14003 For 26.995 MHz. Delivery from stock	Net 89.95
42 R 14011Z For 27.045 MHz. Delivery 4 weeks*	Net 89.95
42 R 14029Z For 27.095 MHz. Delivery 4 weeks*	Net 89.95
42 R 14037Z For 27.145 MHz. Delivery 4 weeks*	Net 89.95
42 R 14045Z For 27.195 MHz. Delivery 4 weeks*	Net 89.95
*Shipped freight collect, FOB. Redmond, Wash.	
99 R 62580 Receiver AA batteries, 4 required	Net .10
32 R 47053 Transmitter 9V. battery, 1 required	Net 1.67
32 R 46781 Engine starting battery, 1½V.	Net 1.06

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette® FIBER

OPTICS

Magic Wand

NEW!

EXCITING!

CHALLENGING!

Simple To Use—Safe—Educational

Explore The Phenomenon Of Cool Controlled Light


Enjoy exciting experimentation in transmitting cool controlled light resulting from internal reflection in glass and plastic fibers. You can literally tie light in knots. Fiber optics provide thousands of practical and decorative applications—limited only by your ingenuity and creativeness.



Aquarium Lights



Digital Readouts



Flexible Trouble Light

LAFAYETTE INTRODUCTORY FIBER OPTICS KIT

LAFAYETTE HOBBYIST FIBER OPTICS KIT



5⁹⁵
INCLUDES
LIGHT SOURCE



9⁹⁵

- Make Decorative Light Sprays and a Flexible Trouble-Shooting Light
- Bend Light Around Corners

- Includes Colored Plastic Fibers For Colorful Arrays
- Make A Fiber Optics Tree And Lamp

Let Lafayette introduce you to the magical world of plastic and glass fibers that transmit light energy from one end to the other—safely—even underwater. You can cut and bend these flexible strands to obtain a myriad of decorative effects. This is the ideal kit with which to get started. Kit includes a 2-cell penlite light source (batteries not supplied); two light hood adapters, a 12" vinyl covered flexible light pipe with polished ends (containing 225 glass microfibers), a rigid image pipe with attached ball magnifier, 12 20 mil diameter 1 foot long plastic fibers, a fiber optics image stone and a set of instructions. Shpg. wt., 7 oz.

19 R 32003 Complete kit, less batteries Net 5.95
99 R 62580 1½V Penlite cell (2 required) Net ea. .10

50 FT. COLORED PLASTIC FIBERS




- Add Color To Your Displays

Now you can add the touch of color to your customized fiber optics decorative displays. The 50 ft. package of fibers cut into 25—2 ft. lengths comes in five assorted colors which add immeasurably to the beauty of your lighting effects. Shpg. wt., 7 oz.

19 R 32026 Net 2.49

12 INCH GLASS FIBER LIGHT PIPE



Use additional light guides for multi-trunked light projects. Each 12" light pipe contains 225—1.8 mil diameter glass fibers bundled into a flexible vinyl covered jacket, with polished and eyeleted ends. Shpg. wt., 4 oz.

19 R 32037 Net 1.00

The perfect kit for the hobbyist and experimenter. Gives complete simplified information on handling, bundling, cutting, and terminating optic fibers as well as additional suggestions for projects and applications. Colored plastic fibers permit construction of beautiful decorative illumination. Kit contains a 2-cell penlite light source (batteries not included), light hood adapter, 12" vinyl covered glass light pipe (containing 225 glass microfibers), 20—1 ft. lengths of five assorted colored plastic fibers, 12" bundle of unjacketed 1.8 mil glass fibers (over 2,000 strands), 5 ft. vinyl jacketed glass light pipe, 1½" rigid image pipe, ½" square fiber optic image plate, ½" square glass plate, lens, rigid image pipe with attached ball magnifier, rigid and flexible heat shrink, "Introduction to Fiber Optics Manual" and an instruction manual. Shpg. wt., 13 oz.

19 R 32011 Complete kit, less batteries Net 9.95
99 R 62580 1½V Penlite cell (2 required) Net ea. .10

COLORED FLAME TIP KIT

- 25 Colored Flame Tips
- 25 Fibers

Achieve truly startling lighting effects with these unique colored flame-shaped tips in decorative illuminated displays. Kit consists of 25 assorted colored plastic fiber optic flame tips, 25 one foot lengths of 20 mil plastic fiber, and instructions for mounting the tips on the fibers. Shpg. wt., 8 oz.

19 R 32045 Net 1.95

BUNDLE OF 1200 GLASS FIBERS



Package of 12" unjacketed 1.8 mil diameter glass optic fibers. Can be used for experiments, or displays and bundled into light guides. Shpg. wt., 4 oz.

19 R 32052 Net 1.95

Experimenter, Semiconductor, IC Kits & Circuits

RCA INTEGRATED CIRCUIT PROJECT KITS



Requires only soldering iron. Project kits come complete with:

- Active and passive components
- Predrilled printed-circuit boards
- Assembly instructions

KC4000 Microphone Pre-amplifier. Build a high-gain, low noise, wideband preamplifier for both low and high impedance microphone inputs. Shpg. wt., 8 oz.
19 R 43752 Net 6.34

KC4001 Two-Channel Mixer. Combine two input signals into single output. Channel inputs from two microphones into a tape recorder or combine any other two phone, radio, or microphone signals into one output. 19 R 43760 Shpg. wt., 8 oz. Net 6.84

KC4002 Audio Oscillator. Use as code-practice oscillator or to test amateur radio transmitters or hi-fi and other audio equipment. 19 R 43778 Shpg. wt., 8 oz. Net 5.25

KC4003 Oscillator and Amplifier. Build a 500 mW audio amplifier or a variable-tone audio oscillator. Use in portable PA systems or in applications that require a low-power, portable amplifier.

19 R 43786 Shpg. wt., 8 oz. Net 9.44

KC4500 Kit Enclosure and Hardware Pack. A handsome, sturdy case with input and output jacks, switch and other hardware. Especially designed to provide the builder with a functional enclosure for their projects. Use with kits KC4000, KC4001 and KC4002.

19 R 43794 Shpg. wt., 8 oz. Net 5.09

KC4004 9-Volt Regulated Power Supply. Supplies 9 volts DC output with voltage regulation of 3% at a maximum current of 250mA.

19 R 43661 Shpg. wt., 3/4 lb. Net 10.59

KC4005 Intruder Alarm. A circuit that develops a "whopping" signal for security system.

19 R 43679 Shpg. wt., 8 oz. Net 7.94

KC4006 Fire Alarm. A low-melting point solder sets off this circuit for a warning device.

19 R 43687 Shpg. wt., 8 oz. Net 7.94

KC4007 I.C. Converter Kit. 118-136 MHz. Aircraft Band.

19 R 43695 Shpg. wt., 8 oz. Net 11.25

KC4008 I.C. Converter Kit. 135-150 MHz. Ham, Gov't, Space Band.

19 R 43703 Shpg. wt., 8 oz. Net 11.25


KC 4909 I.C. Converter Kit. 148-164 MHz. Maritime Mobile, Police, Fire Band.

19 R 43711 Shpg. wt., 8 oz. Net 11.25

KC 4010 I.C. Converter Kit. 160-174 MHz. Police, Fire Band.

19 R 43729 Shpg. wt., 8 oz. Net 11.25

5 PIECE HEAT SINK KIT



1.39

• Use as a Third Hand

Set of 5 spring loaded aluminum heat sinks to protect components while soldering. Includes 1 1/2" and 2 1/2" straight and bent jaws, and one 2 1/2" with magnetic base for use as a third "hand."

14 R 15017 Shpg. wt., 4 oz. Net 1.39

RCA EXPERIMENTER'S IC VARIETY PACK



KD-2117 Kit

Enables the engineer or experienced hobbyist to extend his knowledge of IC's. The pack contains 5 integrated circuits: two KD2114 transistor arrays, One KD-2115 audio amplifiers, and two KD-2116 transistor arrays. Included is a folder giving 12 useful circuits, their schematic diagrams, parts lists, and features. The KD-2114 can be used as a very wide-bandwidth video amplifier, as an RF amplifier for range between 2 and 100 MHz, an i.f. amplifier with 30 db gain at 1 MHz, or as a class B audio amplifier delivering almost 40 mW. The KD-2115 is a multi-function power amplifier designed for use in portable or fixed communication equipment as well as with a portable PA system, or phonograph amplifier. The KD-2116 is a 4 transistor IC connected to form two independent Darlington pairs for very low noise and a gain bandwidth of over 100 MHz.

19 R 53066 Shpg. wt., 3 oz. Net 4.92

RCA EXPERIMENTER'S KITS



One "basic" and two "add-on" kits contain most necessary components to build the fourteen different circuits shown in the RCA Experimenter's manual. Circuits include: Lamp Dimmer, motor speed control, electronic timer, time delay, flashers, two battery chargers, model train or racer speed control, heat controls and others.

KD2105 "Basic" kit contains one silicon control rectifier, two transistors and five rectifiers.

19 R 43000 Shpg. wt., 4 oz. Net 11.25

KD2106 "Add-on" Light Sensor Kit

19 R 43018 Shpg. wt., 2 oz. Net 2.92

KD2110 "Add-on" Heat Sensor Kit

19 R 43026 Shpg. wt., 2 oz. Net 2.50

FAIRCHILD INTEGRATED CIRCUITS

• For The Experimenter And Hobbyist

703 LOW POWER RF AMPLIFIER. Contains 3 transistors, 2 diodes and 2 transistors to be used as RF and IF amplifiers, harmonic mixer, oscillator, etc. useful frequencies in excess of 100MHz. Requires 12VDC supply. With 12 page instruction and applications booklet containing 12 circuit diagrams. Shpg. wt., 2 oz.

19 R 25015 Net 1.59

MOTOROLA HEP IC EXPERIMENTER KIT

Contains 5 popular RTL Integrated circuits that will function in many digital and linear applications i.e., one J-K Flip Flop, one Dual Buffer, one 4-Input Gate, and two Dual 2-Input Gates, a total of 34 transistors and 48 resistors. Also includes Integrated Circuit Cross Reference Substitution Guide, "Tips on Using IC's," and 8 IC Project Circuits. Shpg. wt., 3 oz

19 R 54528 Net 3.95

INTEGRATED CIRCUIT EXPERIMENTER KITS



COMPUTER CIRCUIT EXPERIMENT KIT

• With 3-Fairchild IC's

Ingenious new experiment kit dealing with fundamentals of digital computer circuitry and technology as well as application of integrated circuits in this area. Supplied with all necessary parts including 3 Fairchild μ L914 integrated circuits and comprehensive 18-page kit manual. Manual contains Instructions, circuit diagrams, pictorial diagrams, and thorough easy-to-follow discussion of Boolean algebra, lamp driver "truth meter", logic functions and circuitry (AND, OR, NAND, NOR, AND INVERTER), truth tables, adders, number system conversion (decimal to binary and binary to decimal), and three different types of flip-flops and their applications. Shpg. wt., 7 oz.

19 R 53025 Net 9.95

AUDIO CIRCUIT EXPERIMENTERS KIT

• With Three Fairchild IC's

Excellent experimenters kit for hobbyists, designers, technicians and students interested in solid state audio circuitry and applications of integrated circuits. Kit comes complete with illustrated instructions and discussion of transistor operation, common emitter class A and B amplifiers, phase splitter, 2 and 4 channel audio mixers, square wave audio signal generator, code practice oscillator, sine wave generator, complete audio amplifier, etc. With 4 PC boards and 16 page instruction and circuit manual. Shpg. wt., 6 oz.

19 R 53041 Net 9.95

INTEGRATED CIRCUIT EXPERIMENTER KIT

Excellent kit dealing with theory and applications of revolutionary new Integrated Circuits that offer major advantages over conventional solid state circuitry. Interesting experiments with Gates, Logic Circuits, Flip-Flops, Monostable Multivibrator, Square Wave Generator, Amplifiers, Triggers, Alarms and Counters. Includes 2 Fairchild μ L914 IC's.

19 R 53017 Shpg. wt., 4 oz. Net 6.95

DECIMAL TO BINARY CONVERTER MATRIX KIT



Only

4.95

Invaluable kit for electronic hobbyists, technicians, schools and students interested in digital computer circuitry and technology. Kit includes diodes, pilot lamps, pre-etched printed circuit board and instruction manual. Diode matrix computes the binary number equivalent of the decimal numbers 0 thru 9 and displays binary number on its own pilot lamp readout. Manual contains instructions, circuit and pictorial diagrams and discussion of the binary number system.

19 R 53033 Shpg. wt., 5 oz. Net 4.95

Hobbyist and Experimenter Semiconductor Specialties



FOR HOBBYIST EXPERIMENTER

WITH APPLICATION SCHEMATICS

GE-X1 Silicon Controlled Rectifier. For plug-in speed control for tools, etc. 117 VAC, 4.7 amps max. 200 PIV. Wt., 2 oz. **19 R 27045** Net 2.60

GE-X2A Light Activated Silicon Controlled Rectifier. For "slave" photoflash for flash-bulbs, etc. 25 PIV, 1.6 amps max. Wt., 2 oz. **19 R 27052** Net 2.80

GE-X3 Silicon Controlled Rectifier. For 12V regulated battery charger. Up to 13 amps and 50 PIV. Wt. 2 oz. **19 R 27060** Net 4.00

GE-X4 Silicon Rectifier. For high-low-off control for motor, lamp, heater, etc. 20 amps, 200 PIV. Wt., 3 oz. **19 R 27078** Net 1.60

GE-X5 Silicon Controlled Rectifier. For enlarger photo-timer. Also for simple remote controls, 2 amps, 50 PIV. Wt., 2 oz. **19 R 27086** Net 2.30

GE-X6 Photocell. For light flasher, or night light control. 250V peak AC or DC. 250 mw. Wt., 2 oz. **19 R 27094** Net 1.40

GE-X7 Reed Switch. For light flasher, and burglar alarm. 15 W max, on contacts 500 max. breakdown volts. Wt., 2 oz. **19 R 27102** Net .80

GE-X8 NPN Transistor. For light flasher, light target triggered light source. Also for bi-stable lamp drivers. Wt., 2 oz. **19 R 27110** Net .70

GE-X9 Transistor. For light flasher, light target or triggered light source, low frequency switching. Wt., 2 oz. **19 R 27128** Net .70

GE-X10 Unijunction Transistor. For high precision tachometer with 12 volt neg. ground. For timing circuits. Wt., 2 oz. **19 R 27136** Net 1.35

GE-X11 Zener Diode. For high precision tachometer with 12V neg. grd. Wt., 2 oz. **19 R 27144** Net 1.80

GE-X12 Triac. For remote control for lamps and appliances. Wt., 2 oz. **19 R 27151** Net 4.50

GE-X13 Diac. For full-wave lamp dimmer, lamp sentine, and AC motor control. **19 R 27169** Wt., 2 oz. Net 1.60

GE-X14 Thyrector. For dual-voltage power supply; 100 watt output. Wt., 3 oz. **19 R 27177** Net 1.15

GE-X16 Silicon Controlled Rectifier. For battery operated fluorescent light. Excellent for mobile lighting in trucks, boats, buses, camp trailers and aircraft. 400 PIV, 7.4 amps max. 117 VAC. Wt., 2 oz. **19 R 28142** Net 3.45

GE-X17 PN PN Silicon Programmable Unijunction Transistor. Wt., 2 oz. **19 R 28191** Net 1.20

GE-X18. NPN Silicon Power Transistor. **19 R 28209** Wt., 3 oz. Net 1.50

GE-X19 NPN Silicon Photo-Darlington Amplifier-Light Sensor. Wt., 3 oz. **19 R 28217** Net 1.10

GE1C-1 2-Watt Audio Amplifier—Integrated Circuit. Wt., 8 oz. **19 R 28225** Net 5.45

2N5308A NPN Silicon Monolithic Darlington Amplifier. Wt., 3 oz. **19 R 28233** Net .75

TRANSISTOR ZS SILICONE GREASE WITH INJECTOR



Easily dispenses compound to hard to reach areas when replacing transistors. **13 R 61096** Wt., 4 oz. Net 2.39

PRINTED CIRCUIT TRANSISTOR COMPONENT BOARDS



ONLY

99c


Pkge. of 3 Boards

PACKAGE OF 3 BOARDS CONTAIN ...

TOP BRAND TRANSISTORS MANY 1% TOLERANCE RESISTORS ... MANY 5% TOLERANCE RESISTORS ... GLASS AND MOLDED DIODES ... plus

TOP QUALITY, PRECISION CAPACITORS Each package contains 3 assorted boards. **19 R 49023** Shpg. wt., 5 oz. Net .99

EXPERIMENTERS SEMICONDUCTOR KIT



Assortment of 38 Semiconductors

4 ea.—PNP General Purpose Transistors. 4 ea.—NPN General Purpose Transistors. 2 ea.—Power Transistor—10-3 case. 4 ea.—Stud Mount Silicon Rectifiers; 2 amp, 200 PIV. 20 ea.—General Purpose Germanium Diodes. 4 ea.—3/4 Watt Zener Diodes **19 R 15347** Shpg. wt., 4 oz. Net 2.49

EXPERIMENTER'S ADVANCED SEMICONDUCTOR ASSORTMENT

50 Assorted Semiconductors Transistors, Diodes, Zeners, Rectifiers Excellent assortment consisting of 50 desirable semiconductors for experimenters, hobbyists and for replacement. Consists of:

- 5 ea. MADT 50 MHz. HI Frequency Transistors
 - 5 ea. ZENER DIODES—400mw.
 - 2 ea. 3 Ampere DAP Transistors—PNP Germanium TO-5 Case
 - 5 ea. 1N82A HI-Frequency Germanium Diodes
 - 2 ea. SCR 2 Ampere Low Voltage
 - 2 ea. NPN TO-3 Transistors—Silicon Mesa
 - 2 ea. PNP TO-3 Transistors—Germanium Power
 - 27 ea. Silicon Rectifiers—400 mw. Over 25 PIV
- 19 R 15362** Shpg. wt., 5 oz. Net 2.49

THE ELECTRONIC EXPERIMENTER CIRCUIT MANUAL

ONLY **2 00**

Takes 50 pages to describe the function and operation of various components. Then supplies the diagrams and information needed for 44 projects geared for audio, automotive, marine, game, hobby, home, farm, camp and workshop application. 252 pages. Shpg. wt., 13 oz. **10 R 36078** Net 2.00



SILICON RECTIFIERS

As Low As **49c** ea.




Top hat lead type silicon rectifiers, for TV, Radio, and power supplies as halfwave, full wave rectifiers and voltage doublers
Type A: 750 Ma, 400 PIV @ 25°C. 500 Ma, 400 PIV @ 90°C. **19 R 42093** Shpg. wt., 2 oz. Net .59 100 for 48.25

Type B: 750 Ma, 200 PIV @ 25°C. 500 Ma, 200 PIV @ 90°C. **19 R 42101** Shpg. wt., 2 oz. Net .49 100 for 39.50

Type C: 750 Ma, 700 PIV @ 25°C. 500 Ma, 700 PIV @ 90°C. **19 R 5009E** Shpg. wt., 2 oz. Net .79 100 for 62.50

STUD-MOUNT SILICON POWER RECTIFIERS



All popular models, 7/16" hexagonal mounting studs. Shpg. wt., 3 oz. per package. 2 Ampere Rectifiers

Stock No.	PIV	Pkg. of	Net
19 R 50070	50	4	.49
19 R 50088	100	2	.39
19 R 50054	200	2	.59
19 R 50062	400	2	.97

12 Ampere Rectifiers

19 R 50039	50	2	1.19
19 R 50047	100	1	.77
19 R 42077	200	1	.98
19 R 42085	400	1	1.69

50 Ampere Rectifiers 1 1/2" Hex

19 R 15149	50	1	2.49
19 R 15214	100	1	3.25
19 R 15222	200	1	4.25

TRANSISTOR AND RECTIFIER HEAT SINKS


As Low As

59c



For 1 TO-3 transistor. 22.8 sq. in.† **19 R 15271** Shpg. wt., 4 oz. Net .69
For 1 TO-36 transistor. 27.85 sq. in.† **19 R 15255** Shpg. wt., 4 oz. Net .79
For 7/16" Hex. rectifiers. 16.71 sq. in.† **19 R 15263** Shpg. wt., 4 oz. Net .59
For 1 1/16" Hex. rectifiers. 22.28 sq. in.† **19 R 15230** Shpg. wt., 4 oz. Net .69
For 1 1/2" Hex. rectifiers. 27.85 sq. in.† **19 R 15248** Shpg. wt., 4 oz. Net .79
For 2 TO-36 transistors. 70.28 sq. in.† **19 R 15339** Net 1.60
† Radiating Surface.

RCA SOLID-STATE HOBBY CIRCUIT MANUAL



ONLY **1 95**

Complete construction information on 62 circuits of general interest to experimenters. Theory, operation, testing, trouble shooting. Construction and operation of each circuit, schematic diagrams, parts lists, and photographs of actual circuit boards. 368 pages. Shpg. wt., 2 lbs. **10 R 47109** Net 1.95

Semiconductors for Hobbyist and Experimenter



FIG. (A)



FIG. (B)



FIG. (C)



FIG. (D)



FIG. (E)



FIG. (F)



FIG. (G)



FIG. (H)

(A) 2-10-WATT POWER TRANSISTORS

Package of 2 PNP 10-Watt germanium power transistors in popular TO-3 case. Shpg., 3 oz. 19 R 15016 Pkg. of 2 Net .89

(A) POPULAR POWER TRANSISTORS

MEDIUM POWER TRANSISTORS

Beta=30; BV_{cer}=36 Volts.
19 R 15073 Shpg. wt., 3 oz. Net ea. .59

HIGH POWER TRANSISTORS

Beta=50; BV_{cer}=36 Volts Min.
19 R 42051 Shpg. wt., 3 oz. Net ea. .69

(A) PHOTO-MULTIPLIER

POWER TRANSISTOR

Complete with Instructions, Data and Diagrams for photo control systems, photo-electronic amplifiers; Relays, Alarms, etc. Shpg. wt., 3 oz.
19 R 15065 Ea. Net 1.79

(B) 4 PNP GERMANIUM TRANSISTORS

Package of 4 PNP General Purpose Type Transistors similar in performance to: 2N107, 2N218, 2N1265, CK722, GT-222, TR722, 2N1191, etc. Wt., 2 oz.
19 R 15024 Pkg. of 4 Net .89

(B) 2 NPN TRANSISTORS

Package of 2 NPN germanium transistors similar to 2N170 for Audio & RF. Beta 20 minimum. Shpg. wt., 2 oz.
19 R 27029 Pkg. of 2 Net .49

TRANSISTOR MOUNTING KITS

19 R 15313 For TO-3 Type Net .30
19 R 15321 For TO-36 "Door Knob" Type Net .30

(C) 2 TOP HAT SILICON RECTIFIERS

750 MIL-400 PIV

Pkg. of 2 top hat type silicon rectifiers rated at 750 millamps, 400 PIV. Shpg. wt., 2 oz.
19 R 42028 Pkg. of 2 Net .89

(E) 750 MIL EPOXY SILICON RECTIFIERS

750 mil 400 PIV Epoxy Silicon Rectifier
19 R 50013 Shpg. wt., 3 oz. Net ea. .37;
10 for 3.45; 100 for 29.95
750 Mil 700 PIV Epoxy Silicon Rectifier
19 R 50021 Net ea. .59; 10 for 4.95
100 for 42.50

(H) GE-509 UNIVERSAL SILICON

RECTIFIER

1 amp., 1000 PIV, 60 amp. max. surge.
19 R 28019 Net .79

(F) 40-WATT HIGH POWER TRANSISTOR

Excellent for power supplies, auto replacement, audio output, etc. Bolt mounted.
19 R 15032 Shpg. wt., 3 oz. Net .89

(G) GENERAL PURPOSE DIODES

Excellent Detector for Transistor and Vacuum Tube Radio Receivers

EQUIVALENT TO: 100 for
IN34 IN34A IN38A 8.50
IN48 IN56 IN69
19 R 49015 Net .10 each; 10 for .90

(D) 10 GERMANIUM DIODES

Pkg. of 10 germanium diodes that replace IN34, IN34A, IN46, IN48, IN51, IN60, IN64, IN64A, IN87, IN105, IN109, IN147, IN267, IN268, IN295, etc. Shpg. wt., 2 oz.
19 R 15057 Pkg. of 10 Net .79

(D) 10 SILICON DIODES

Package of 10 silicon diodes. Replaces IN34, IN34A, IN46, IN48, IN51, IN60, IN87, IN295, etc. Wt., 2 oz.
19 R 60012 Pkg. of 10 Net .89

RECTIFIER MOUNTING KITS

19 R 15081 For 7/16" Hex Base Net .17
10 for 1.59
19 R 15156 For 1/16" Hex Base
Net .27; 10 for 2.49
19 R 15164 For 1/4" Hex Base Net .35
10 for 3.15



MOTOROLA EXPERIMENTER AND UNIVERSAL REPLACEMENT SEMICONDUCTORS



STOCK NO.	HEP No.	NET	STOCK NO.	HEP No.	NET
19 R 54585	HEP1	.89	19 R54700	HEP101	.95
19 R 54247	HEP2	1.25	19 R 54718	HEP102	1.20
19 R 54544	HEP50	.79	19 R 54726	HEP103	1.20
19 R 54536	HEP3	1.25	19 R 54734	HEP105	1.20
19 R 54031	HEP53	1.15	19 R 54742	HEP134	.26
19 R 54270	HEP64	1.08	19 R 54759	HEP135	.26
19 R 54593	HEP56	1.44	19 R 54767	HEP153	2.45
19 R 54114	HEP30	1.25	19 R 54775	HEP156	.41
19 R 54122	HEP231	1.99	19 R 54783	HEP157	.45
19 R 54601	HEP245	1.99	19 R 54791	HEP158	.54
19 R 54619	HEP247	2.80	19 R 54809	HEP161	1.09
19 R 54627	HEP251	.89	19 R 54817	HEP165	.62
19 R 54353	HEP254	1.13	19 R 54825	HEP232	2.34
19 R 54171	HEP310	1.49	19 R 54833	HEP233	4.20
19 R 54221	HEP801	1.59	19 R 54841	HEP235	4.50
19 R 54361	HEP802	1.59	19 R 54858	HEP240	2.05
19 R 54635	HEP803	3.39	19 R 54866	HEP242	2.40
19 R 54239	HEP451	1.49	19 R 54874	HEP243	1.79
19 R 54205	HEP556	3.89	19 R 54882	HEP253	1.20
19 R 54213	HEP558	4.39	19 R 54890	HEP311	.99
19 R 54372	HEP572	3.90	19 R 54908	HEP320	.99
19 R 54445	HEP580	.95	19 R 54916	HEP340	4.49
19 R 54452	HEP581	.95	19 R 54924	HEP632	1.67
19 R 54478	HEP583	1.49	19 R 54932	HEP633	1.84
19 R 54508	HEP592	3.25	19 R 54940	HEP636	1.12
19 R 54052	HEP104	1.20	19 R 54957	HEP639	1.50
19 R 54551	HEP151	1.90	19 R 54965	HEP640	1.73
19 R 54379	HEP154	.36	19 R 54973	HEP641	1.32
19 R 54072	HEP159	.60	19 R 54981	HEP642	1.95
19 R 54569	HEP160	.75	19 R 54999	HEP643	1.95
19 R 54403	HEP162	1.25	19 R 55005	HEP700	2.49
19 R 54643	HEP170	.82	19 R 55013	HEP710	2.49
19 R 54080	HEP175	1.49	19 R 55021	HEP702	5.25
19 R 54650	HEP176	2.05	19 R 55029	HEP703	2.75
19 R 54577	HEP302	2.69	19 R 55037	HEP704	2.67
19 R 54023	HEP51	1.29	19 R 55044	HEP707	8.80
19 R 54130	HEP250	.79	19 R 55052	HEP712	3.30
19 R 54288	HEP55	1.20	19 R 55060	HEP715	.95
19 R 54429	HEP570	2.10	19 R 55068	HEP721	1.55
19 R 54460	HEP582	1.49	19 R 55076	HEP723	.95
19 R 54486	HEP590	3.99	19 R 55084	HEP724	.95
19 R 54494	HEP591	3.60	19 R 55092	HEP725	1.05
19 R 54676	HEP52	.95	19 R 55100	HEP726	1.15
19 R 54684	HEP57	1.20	19 R 55108	HEP728	1.10
19 R 54692	HEP75	2.95	19 R 55116	HEP729	1.35

FREE

Motorola HEP Semiconductor cross-reference guide and catalog

An excellent cross-reference and guide for the hobbyist, experimenter and professional service technician. Contains packaging index, outline dimensions, and minimum ratings and characteristics of HEP semiconductors as well as complete cross-reference of over 25,000 domestic and imported germanium and silicon semiconductor devices to HEP semiconductors. Shpg. wt., 8 oz.
10, R 64047 **FREE**

HEP PROJECT MANUALS

HEP No. 400—General Hobby/Experimenter Solid State Projects Manual. Fundamentals from interesting projects; i.e., Panic Button, Deluxe Code Oscillator, Audio Generator, Min-Fi Amplifier, Intercom System, Motor Speed Control and Six Meter Converter.
10 R 64013 Net .50

HEP No. 407—Interesting IC theory & applications in such projects as Binary Computer, Organ, Square Wave Generator, Glidestone, Electronic Guitar and Code Oscillator.
10 R 64021 Net 1.00

HEP No. 408—Learn theory and applications of FET's. Interesting projects such as Vibrato, Audio Mixer, Timer, Crystal Oscillator, Preampifier and D.C. Voltmeter.
10 R 64039 Net 1.00

MOTOROLA FET EXPERIMENTER'S KIT

Contains 2 Field Effect Transistors, 2 bipolar transistors, brochure on FET's including a project circuit and FET Cross-Reference Guide.
19 R 54668 Shpg. wt., 4 oz. Net 3.95

RCA "TOP OF THE LINE" UNIVERSAL Replacement Semiconductors

REPLACE: More Than 10,000 Transistors and Integrated Circuits—More Than 3,600 Rectifiers!

Top quality semiconductors for replacement of transistors, IC's, selenium and silicon rectifiers used in AC and battery-operated

portable and auto radios, phonographs, tape recorders, TV receivers, AF amplifiers, etc. Shpg. wt., 3 oz.

"TOP-OF-THE-LINE"

Solid State Replacement Guide . Domestic and foreign transistors, IC's and rectifiers cross-referenced against RCA "Top-of-the-Line" SK semiconductors. Includes diagrams. Shpg. wt., 8 oz.

10 R 47125

Net .35

Stock No.	RCA Type	Net Each
19 R 43133	SK 3003	.99
19 R 43141	SK 3004	1.14
19 R 43158	SK 3005	1.17
19 R 43166	SK 3006	1.41
19 R 43174	SK 3007	1.26
19 R 43182	SK 3008	1.23
19 R 43190	SK 3009	2.34
19 R 43208	SK 3010	1.26
19 R 43216	SK 3011	1.62
19 R 43224	SK 3012	4.77
19 R 43232	SK 3013	4.68
19 R 43240	SK 3014	3.15
19 R 43257	SK 3015	6.30
19 R 43265	SK 3016	.57
19 R 43273	SK 3017A	.80
19 R 43281	SK 3018	1.35
19 R 43289	SK 3019	1.47
19 R 43297	SK 3020	1.32
19 R 43305	SK 3021	1.95
19 R 43313	SK 3022	3.96
19 R 43321	SK 3023	3.96
19 R 43329	SK 3024	1.98

Stock No.	RCA Type	Net Each
19 R 43042	SK 3025	2.70
19 R 43058	SK 3026	1.80
19 R 43067	SK 3027	3.15
19 R 43075	SK 3028	3.60
19 R 43083	SK 3029	6.30
19 R 43091	SK 3030	.42
19 R 43109	SK 3031	.51
19 R 43117	SK 3032	.81
19 R 43125	SK 3033	.81
19 R 43133	SK 3034	4.50
19 R 43141	SK 3035	5.49
19 R 43149	SK 3036	5.85
19 R 43157	SK 3037	11.70
19 R 43165	SK 3038	1.44
19 R 43173	SK 3039	1.98
19 R 43181	SK 3040	2.25
19 R 43189	SK 3041	2.52
19 R 43197	SK 3042	3.96
19 R 43205	SK 3043	1.80
19 R 43213	SK 3044	5.49
19 R 43221	SK 3045	5.67
19 R 43229	SK 3046	1.98

Stock No.	RCA Type	Net Each
19 R 43538	SK 3047	2.88
19 R 43547	SK 3048	5.58
19 R 43554	SK 3049	8.10
19 R 43802	SK 3050	3.78
19 R 43810	SK 3051	1.08
19 R 43828	SK 3052	2.35
19 R 43836	SK 3053	4.68
19 R 43944	SK 3054	2.70
19 R 43851	SK 3055	1.08
19 R 43869	SK 3056	1.08
19 R 43877	SK 3057	1.08
19 R 43885	SK 3058	1.08
19 R 43893	SK 3059	1.08
19 R 43901	SK 3060	1.08
19 R 43919	SK 3061	1.08
19 R 43927	SK 3062	1.08
19 R 43935	SK 3063	1.08
19 R 43943	SK 3064	1.08
19 R 43950	SK 3065	4.15
19 R 43968	SK 3066	3.15
19 R 43976	SK 3067	4.68
19 R 43984	SK 3068	5.04
19 R 43992	SK 3069	13.65



REPLACEMENT ENTERTAINMENT TRANSISTORS AND SEMI-CONDUCTORS

General Electric Universal Replacement Entertainment Transistors replace most types of transistors used in radios, TV, tape recorders, phonographs and other applications where normal voltages exist. Shpg. wt., 3 oz. *Matched Pairs.

ENTERTAINMENT SEMICONDUCTOR ALMANAC

Replace over 12,000 Transistors, Over 5,000 Diodes, color rectifiers, 3.5 MHz crystals used in the major popular TV sets and maintenance industrial semiconductors. Wt., 8 oz.

Stock No.	GE Type	Net Each
19 R 27268	GE-1	1.20
19 R 27276	GE-2	1.02
19 R 27284	GE-3	1.78
19 R 27292	GE-4	2.94
19 R 27300	GE-5	1.68
19 R 27318	GE-6	1.83
19 R 27326	GE-7	1.77
19 R 27334	GE-8	1.29
19 R 27714	GE-9	1.26
19 R 27358	GE-10	1.20
19 R 27367	GE-11	1.53
19 R 27722	GE-12	2.34
19 R 27730	GE-13*	3.56
19 R 27748	GE-14	3.51
19 R 27756	GE-15*	7.02
19 R 27763	GE-16	1.15
19 R 27771	GE-17*	1.42
19 R 27789	GE-18	1.46
19 R 27797	GE-19	3.06
19 R 27805	GE-20	1.10
19 R 27813	GE-21	1.12
19 R 27821	GE-22	1.03
19 R 27839	GE-23	2.52
19 R 27847	GE-24*	5.04
19 R 27854	GE-25	7.50
19 R 28134	GE-26	3.10
19 R 28159	GE-27	2.18
19 R 28167	GE-28	2.15
19 R 28241	GE-30	2.20
19 R 28258	GE-31*	4.40
19 R 28266	GE-32	2.79
19 R 28274	GE-53	1.02
19 R 28282	GE-62	.81
19 R 28290	GE-63	1.80
19 R 28308	GE-64	.96
19 R 28316	GE-66	2.49
19 R 28324	GE-67	1.80
19 R 28332	GE-69	2.76
19 R 28340	GE-90	.81
19 R 28357	GE-300	.81
19 R 27862	GE-FET-1	2.25
19 R 28365	GE-FET-2	1.44
19 R 27474	2N107	.75
19 R 27482	2N170	1.02
19 R 27490	2N188A	1.83
19 R 27870	2N190	.84
19 R 27888	2N324	.72
19 R 27896	2N404	.54
19 R 27904	2N508	.78
19 R 27920	2N2160	1.65

Stock No.	GE Type	Net Each
G.E. VAC-U-SEL® DUAL DIODES		
19 R 27441	6GC1	.55
19 R 27458	6GD1	.55
19 R 27466	6GX1	.55
CRYSTAL DIODES		
19 R 27938	1N34AS	.33
19 R 27946	1N60	.33
19 R 27953	1N82A	.87
19 R 27979	1N295	.33

Stock No.	GE Type	Net Each
COLOR TV RECTIFIERS		
19 R 27417	GECR-1 Focus Rect.	2.25
19 R 27425	GECR-2 Boosted Boost	.39
19 R 27433	GECR-3 Convergence	.86

Thermalloy

SEMICONDUCTOR ACCESSORIES

Neatly pre-packaged heat sinks, mounting and insulating kits and heat sink compound.

2 Heat Sinks for TO-5 transistor. Cools to 1.9 watts of heat. Net .59

1 Heat Sink for TO-5 transistor. Cools to 3 watts of heat. Net .44

2 Piece Heat Sink for TO-66 transistor. Cools up to 10 watts of heat. Net .64

19 R 56323 Shpg. wt., 8 oz. Net .64

2 Piece Heat Sink for TO-3 transistor. Cools up to 12 watts of heat. Net .70

19 R 56331 Shpg. wt., 8 oz. Net .70

1 Heat Sink for TO-3 transistor. Cools up to 20 watts of heat. Net 1.08

19 R 56549 Shpg. wt., 8 oz. Net 1.08

Universal Heat Sink for TO-3, TO-36 or TO-66 transistors. Cools up to 40 watts of heat. Net 1.72

19 R 56556 Shpg. wt., 12 oz. Net 1.72

Thermacote Semiconductor silicone heat transfer compound. 1 1/2 x 1 1/2" roll tube. 19 R 56606 Shpg. wt., 4 oz. Net .65

Mounting and Insulating Kits. Wt. 4 oz.

19 R 56614 for TO-3 Transistor Net .38

19 R 56622 for TO-36 Transistor Net .34

19 R 56630 for TO-66 Transistor Net .38

10 R 36243 Net .28

G-E COLOR TV CRYSTALS

GE-41 3579.545KC GE only		
19 R 27375		3.36
GE-42 3579.545KC other sets		
19 R 27383		2.28

ZENER DIODES, 1 watt; * = 400 Milliwatt

Stock No.	Type	Volts	Net
19 R 28027	GEZD-10.4*	10	.90
19 R 28035	GEZD-3.6	3.6	1.20
19 R 28043	GEZD-5.1	5.1	1.20
19 R 28050	GEZD-5.6	5.6	1.20
19 R 28068	GEZD-6.2	6.2	1.20
19 R 28076	GEZD-9.1	9.1	1.20
19 R 28084	GEZD-12	12	1.20
19 R 28092	GEZD-15	15	1.20
19 R 28100	GEZD-18	18	1.20
19 R 28118	GEZD-20	20	1.20
19 R 28126	GEZD-27	27	1.20
19 R 28373	GEZD-33	33	1.20
19 R 28381	GEZD-39	39	1.20
19 R 28399	GEZD-47	47	1.20

RECTIFIERS

Stock No.	Type	PIV	MAX Ipc MA	Net
19 R 27987	1N91	100	150	.94
19 R 27995	GE-504A	600	1 Amp	.66
19 R 28019	GE-509	1000	1 Amp	.79
19 R 28183	GE-BR600	600	1.5 Amp	3.05

(Full Wave Bridge)

EXPERIMENTER'S MANUAL

KM-71. 136 page book on the theory and applications of solid state electronic devices with particular emphasis on the silicon-controlled rectifier. Includes construction details, circuits for the hobbyist or experimenters plus 24 complete circuits for dozens of SCR applications with schematic and pictorial diagrams. Shpg. wt., 1 lb.

10 R 47067 Net .95

Printed Circuit Components-Experimenters Items

PERFORATED COPPER-CLAD AND UNCLAD BOARDS

- Ideal for Transistor and Subminiature Circuitry

These sturdy perforated boards are the ideal base for builders, experimenters, and labs to mount miniaturized components. Two available; either high grade bakelite for wired circuits, or one side copper-clad for "printed" circuitry. Holes are $\frac{1}{16}$ " diameter with $\frac{1}{16}$ " between hole centers. All boards are $\frac{1}{8}$ " thick. For contacts, the flea clips listed on this page are ideal. Avg. shpg. wt., 9 oz.

PERFORATED CLAD				PERFORATED UNCLAD					
Stock No.	Net	Each	Lots of	No. of	Stock No.	Net	Each	Lots of	
		1	100	Holes			1	100	250
19 R 36012	.35	30	24	2 $\frac{1}{2}$ "x3 $\frac{3}{4}$ "	17x12	19 R 36053	.25	.20	.18
19 R 36020	.64	.52	.47	3 $\frac{1}{2}$ "x6 $\frac{3}{4}$ "	35x19	19 R 36061	.45	.40	.35
19 R 36038	1.15	.96	.87	7 $\frac{1}{2}$ "x6 $\frac{3}{4}$ "	39x35	19 R 36079	.75	.65	.60
19 R 36046	1.99	1.58	1.42	10 $\frac{1}{2}$ "x7 $\frac{3}{4}$ "	56x38	19 R 36087	1.20	1.08	.97
				18x7 $\frac{3}{4}$ "	95x38	19 R 36095	1.99	1.79	1.65

UNPERFORATED COPPER CLAD LAMINATE

Unperforated, finest quality XXXP bakelite and G-10 epoxy glass bases one side copper laminate clad boards for printed circuit work. Avg. shpg. wt., 10 oz.

Stock No.	XXXX Bakelite	Net	Stock No.	Epoxy Glass	Net
19 R 71019	9" x 12"	1.50	19 R 37044	9" x 12"	4.20
19 R 71027	6" x 4 $\frac{1}{2}$ "	.49	19 R 37051	6" x 4 $\frac{1}{2}$ "	1.24
19 R 71035	3" x 4 $\frac{1}{2}$ "	.30	19 R 37069	3" x 4 $\frac{1}{2}$ "	.61
19 R 71043	2" x 4 $\frac{1}{2}$ "	.25	19 R 37077	2" x 4 $\frac{1}{2}$ "	.40
19 R 71050	3" x 2 $\frac{1}{4}$ "	.24	19 R 37085	3" x 2 $\frac{1}{4}$ "	.34

"TECHNIQUES" PRINTED CIRCUIT KITS AND SUPPLIES

- For The Builder—Experimenter—Student—Technician



FLEA CLIPS FOR TRANSISTOR AND SUBMINIATURE CONTACTS

"Flea" clips are specially designed for sub-miniature work. Fit perfectly in holes in perforated copper-clad and unclad boards with $\frac{1}{16}$ " dia. holes. Made of beryllium copper, silver plated finish. Simply insert wire thru hole for positive grip contact.

19 R 33019 Package of 12 Net .35
19 R 33027 Package of 1000 Net 15.75



G-C CHEMICALS FOR PRINTED CIRCUITS

PRINT-KOTE SILVER PRINT. Pure silver compound. Air drying. Used to repair printed circuit "wires" and touch up connections. $\frac{1}{2}$ Troy oz. Shpg. wt., 4 ozs.

13 R 60106 GC-21-1 Net 4.75

PRINT-KOTE COPPER PRINT. A high conductive, fast drying compound to touch up and repair printed circuits. With brush-cap in 2 oz. bottles. Shpg. wt., 7 oz.

13 R 61146 Net 1.95



SCREEN PRINTING KIT NO. 5006 FIG. A

This Screen Printing Kit provides an accurate and rapid means for making larger sample quantities or even short production runs of printed circuits. Frame measures 8"x12". It comes with silk already stretched and its hinge mounted on durable formica covered plywood base. Neoprene squeegee is mounted in sturdy all wood handle. Photo stencil film and all chemicals necessary for making stencils. Complete with screen process etch resistant ink, blockout medium, tape masking, solvent, spare bottle and complete instructions. Shpg. wt., 12 $\frac{1}{2}$ lbs.

19 R 68247W Net 29.95

1:1 NEGATIVE ARTWORK KIT FIG. B

Photo reversing kit converts black line artwork to "clear" line artwork for exposing presensitized panels. Kit contains pressure sensitive, actual size pattern of transistor pads, IC pads, fingers, lines, dots, etc. Press desired pattern onto mylar, connect dots with tape, add fingers, etc., place in contact with reverse film and expose to bright light. Swab developer onto film and the result is an accurate 1:1 negative ready to use to expose any number of presensitized P.C. boards. No darkroom (subdued light only), camera, tanks or trays needed. All supplies to make two (or more if smaller size) 4 $\frac{1}{2}$ " x 6" negatives.

19 R 68502 Shpg. wt., 3 lbs. Net 12.95

Extra Developer and 4 sheets of film. Net 6.50

19 R 68510 Shpg. wt., 2 lbs. Net 6.50

Extra Patterns, Tape and Dots Net 7.95

BALL POINT TUBES

Make resist patterns directly on copper clad boards. As easy to use as a ball point pen. Deposits line $\frac{1}{16}$ " wide. No need to "lay-out" colors of resist for color coding circuitry.

Stock No.	Type	Color	Net ea.
19 R 68395	PRLT	Red	1.25
19 R 68403	PRLT	Black	1.25
19 R 68411	PRLT	Blue	1.25
19 R 68429	PRLT	Green	1.25
19 R 68437	PRLT	Yellow	1.25



TECHNICIANS KIT NO. 5003 FIG. C

Contains 10 assorted single and double clad XXXP and epoxy glass boards from 4 $\frac{1}{2}$ "x6" to 3x2 $\frac{1}{4}$ ". 1 tape resist; 1 liquid resist; eyelets; 1 drill, etching solution and directions. In plastic box size: 7 $\frac{1}{8}$ "x5"x2"

19 R 68064 Shpg. wt., 4 lbs. Net 9.75

EXPERIMENTERS KIT NO. 5002



A good kit to start off learning the technique of etched circuitry. Contains 6 copper clad boards from 4 $\frac{1}{2}$ "x6" to 3x2 $\frac{1}{4}$ ". 1 pack etchant; 1 tape resist; eyelet assortment; drill and directions. In plastic box size: 7 $\frac{1}{8}$ "x5"x1 $\frac{1}{8}$ ".

19 R 68072 Shpg. wt., 1 $\frac{3}{4}$ lbs. Net 4.75

PRESENSITIZED COPPER CLAD PANELS

All are $\frac{1}{16}$ " thick copper clad one side. Except \ddagger is both sides. \ddagger are XXXP laminate. \ddagger are G10 epoxy-glass laminate.

Stock No.	Type	Size	Net Ea.
19 R 68031	PXC-F \ddagger	6"x9"	2.00
19 R 68049	PXC-B \ddagger	6"x4 $\frac{1}{2}$ "	1.00
19 R 68056	PXC-C \ddagger	3"x4 $\frac{1}{2}$ "	.75
19 R 68254	PXE-F \ddagger	6"x9"	4.00
19 R 68270	PXE-B \ddagger	6"x4 $\frac{1}{2}$ "	2.00
19 R 68282	PXE-C \ddagger	3"x4 $\frac{1}{2}$ "	1.00
19 R 68445	PXC-FF \ddagger	6"x9"	3.00
19 R 68452	PXC-BB \ddagger	6"x4 $\frac{1}{2}$ "	1.50
19 R 68460	PXC-CC \ddagger	3"x4 $\frac{1}{2}$ "	1.00
19 R 68478	PXE-FF \ddagger	6"x9"	5.00
19 R 68486	PXE-BB \ddagger	6"x4 $\frac{1}{2}$ "	2.50
19 R 68494	PXE-CC \ddagger	3"x4 $\frac{1}{2}$ "	1.25

PROCESSING MATERIALS

Type PXD-8 eight ounce developer Net ea. 1.00

19 R 68023

Type PXY-1 one ounce dye, Net ea. 75

19 R 68288



INDUSTRIAL LABORATORY KIT NO. 5100 FIG. D

Ready to use presensitized copper clad laminate cuts time to make prototype printed circuits. Kit contains 20-pieces single and double clad XXX-P and epoxy fiberglass laminates in assorted convenient sizes, presensitized and uncoated, 20 assorted printed circuit tube and transistor sockets, 2 rolls tape resist strip $\frac{1}{16}$ " and $\frac{1}{8}$ " wide, 200 die-cut tape resist circles $\frac{1}{16}$ " and $\frac{1}{8}$ " diameter. Bottle liquid resist and brush. Ball-point resist pen. Package of printed circuit eyelets and terminals. #51 drill, layout paper, exposure clamp, developing and etching solutions with trays. Full instructions and technical bulletins.

19 R 68015W Shpg. wt., 9 lbs. Net 29.95

PRINTED CIRCUIT ACCESSORIES

Basic components for the experimenter-designer-lab-limited production-etc. in printed circuit construction. Highest quality materials—indispensable for prototype work.

TAPE RESIST

320" Rolls of Tape Resist (Black) Average Shpg. wt., 2 oz.

Stock No.	Type	Width	Net Ea.
19 R 68122	PRT1	$\frac{1}{16}$ "	.85
19 R 68130	PRT2	$\frac{1}{8}$ "	.75
19 R 68148	PRT3	$\frac{1}{4}$ "	.90
19 R 68155	PRT4	$\frac{3}{8}$ "	.90
19 R 68296	PRT8	$\frac{1}{4}$ "	1.00

RESIST CIRCLES Pkg. of 100 ea.

19 R 68163 PRD-6 $\frac{1}{16}$ " dia. .75
19 R 68304 PRD-8 $\frac{1}{8}$ " diam. .75

TOUCH-UP RESIST

19 R 68171 PRL one ounce jar50

EYELETS

19 R 68114 PEY12 125 Ass't. Eyelets60

PRINTED CIRCUIT TERMINALS

19 R 68312 PTE10 Pkg. of 1040

ECHANTS

19 R 68098 PE16 Pint 1.25

19 R 68106 PE32 Quart 2.25

VECTOR BOARDS, TERMINALS & KITS

VECTOR "Plug Boards" and Receptacles

Ready to wire plugboards are ideal for prototypes and short runs. Made from Grade EXXXP 1/16" thick epoxy paper per MIL-P-22324. Made from FR-4 epoxy glass type GEE per MIL-P-18177C. Overall .062" holes located on alternate .1" centers speed component mounting. Elco Varicon contacts provided on "types". Other boards have copper. .156" spaced etched contact fingers or nickel gold plated contacts on "GN" types.

Stock No.	Mfgs. Type	Size	No. Contacts	Net Each
19 R 83238	837"+	3"x4 1/2"	12	2.33 2.10 1.96
19 R 83246	837WE*G	3"x4 1/2"	12	2.58 2.32 2.17
19 R 83253	812"+	4 1/2"x6 1/2"	16	2.98 2.68 2.50
19 R 83626	812WE*G	4 1/2"x6 1/2"	16	3.53 3.18 2.97
19 R 83303	848WE*G	4 1/2"x6 1/2"	35	6.09 5.48 5.12
19 R 83279	838A-1	4 1/2"x6 1/2"	22	2.81 2.53 2.36
19 R 83634	838AWE-1G	4 1/2"x6 1/2"	22	3.17 2.85 2.66
19 R 83642	838AWE-1GN	4 1/2"x6 1/2"	43	4.70 4.23 3.95
19 R 83659	838WE-1GN	4 1/2"x6 1/2"	43	5.81 5.23 4.88

Receptacles have solder tabs and mounting holes.

Stock No.	Mfrs. Type	No. Contacts	Used With	Net Each
19 R 83329	R612-1	12	837, 837WE	2.08
19 R 83337	R616-1	16	812, 812WE	2.60
19 R 83345	R635	35	848WE	5.35
19 R 83352	R644	44	838A, 838AWE, 838WE, 1GN, 3474, 3474-2, 3677-2, 3662	2.97

VECTOR INTEGRATED CIRCUIT KITS

Vector's hardware kits provide maximum flexibility for hooking up all kinds of IC circuits as well as discrete components. Kits are built around pre-punched epoxy paper Micro-Vectorboard* chassis which has .042" holes on 1" x 1" centers plus solder type push-in Micro-Klip terminals and various accessories, such as Micro bus strip, wire wrap terminals, chassis supports, etc. KIT 30XA Micro-Vectorboard chassis 4 1/2 x 8 1/2 x 1/16", wooden chassis supports, 100 T42-1 terminals.

19 R 83691 Net 4.50

KIT 30X Micro-Vectorboard chassis 4 1/2 x 8 1/2 x 1/16", 2" high extruded aluminum chassis rails (which can form box with addition of cover plates), 100 T42-1 terminals and installing tool, bare and solder thru hookup wire, layout paper.

19 R 83709 Net 10.75

KIT 31X Same as 30X, with addition of Micro bus strip, wire wrap terminals and inboard pins, pot and switch brackets.

19 R 83717 Net 17.50

KIT 29X Professional sized version with 4 1/2" x 13.9" chassis and extruded aluminum supporting rails, solderless daisy chain contacts, solderable and wire wrap terminals and inserting tools, solderless contacts for pins, Micro bus strip, DIP extractor tool, 14 and 16 pin dual-in-line sockets, 4 lead transistor sockets, 8 and 10 lead round TO-5 IC sockets, mounting pads for 12 lead IC's flat pack, I.C. adapter plates, etc.

19 R 83725 Net 59.75



VECTOR PRE-PUNCHED BREADBOARDS

Pre-punched terminal boards for prototypes and production Ivory Epoxy Paper grade EXXXP per MIL-P-22324 Natural Tan Phenolic Grade EXXXP per Mil-A-31153 Tan or green epoxy glass NEMA grade FR-4 per MIL-P-18177C. All 1/16" thick except #3/32" Patterns: "A", .093" holes, .265" centers, "F", .062" hole, .2" centers, "G", .062" holes alter .1" centers, "P", .042" hole, .1" centers.

PHENOLIC BOARDS

Stock No.	L and W	Pat.	No. of Holes	1-19	20-99
19 R 83071	17"x4.8"	A	64A18	1.30	1.17
19 R 83089	17"x4.8"	F	85x24x2	1.30	1.17
19 R 83097	19"x8.6"	G	95x43x2	2.41	2.17
19 R 83105	19"x8.75"	A	72x32	2.33	2.10
19 R 83113	8.5"x4.8"	A	32x18	.86	.77
19 R 83121	17"x4.8"	A	64x18	1.30	1.17
19 R 83139	8.5"x2.41"	A	*32x9	.62	.56
19 R 83147	17"x8.51"	A	*64A32	2.86	2.57


EPoxy PAPER BOARDS

19 R 83154	17"x4.8"	F	85x23	2.28	2.05
19 R 83162	17"x4.8"	G	185x23 x2	2.28	2.05
19 R 83584	6.5"x4.5"	P	64x44	1.89	1.52
19 R 83592	17"x4.8"	P	169x47	3.98	3.58

EPoxy GLASS BOARDS

19 R 83428	17"x4.8"	A	64x18	3.87	3.48
19 R 83436	17"x4.8"	G	85x23 x2	3.96	3.56
19 R 83733	6 1/2"x4 1/2"	P	64x44	1.79	1.61
19 R 83741	17"x4 1/2"	P	169x44	4.36	3.92

PUSH-IN TERMINALS AND INSERTION TOOLS



Type T9.4, Brass, tin plated with serrated slots, fits .093" hole.

19 R 83014 Pkg. of 100 1.44

19 R 83402 Pkg. of 1000 10.18

Type P122B Insertion tool T9.4 terminals.

19 R 83410 Net ea. 1.40

Type T28 terminal beryllium copper, tin plated, fits hole size .062"

19 R 83022 Pkg. of 100 1.61

19 R 83396 Pkg. of 1000 11.44

Type T28S, Same as T-28 except silver plated.

19 R 83618 Pkg. of 100 1.72

19 R 83600 Pkg. of 1000 13.51

Type P91, Insertion tool for T28 and T28S terminals.

19 R 83063 .59

Type T30N-2 Springclip terminal holds up to six wires without soldering. Nickel plated brass body with nickel plated steel wire spring, fits hole size .093".

19 R 83048 Pkg. of 10 7.99

19 R 83030 Pkg. of 100 9.23

19 R 83394 Pkg. of 1000 50.44

P92A Insertion tool for T30N-2 terminals

19 R 83055 .50

Type T42-1 Micro-Klip Push-in terminal for .042" holes, beryllium copper, tin plated.

19 R 83758 Pkg. of 100 1.82

19 R 83766 Pkg. of 1000 11.70

Type K24C Inboard Pin, Push-in for .042" diameter holes, Phosphor bronze tin plated.

19 R 83774 Pkg. of 50 .86

19 R 83782 Pkg. of 1000 11.21

Type T44 .025" square wire wrap pin with slotted top fits .042" diameter holes.

19 R 83790 Pkg. of 100 2.96

19 R 83808 A13 insertion tool for T44 1.69

E. F. JOHNSON INSULATORS AND LEAD-IN BUSHINGS



THRU PANEL STEATITE INSULATORS. Compression mounted by means of a stud. Flat mounting surfaces with cushion washer. Hardware: *10-32, #6-32. Average shgp. wt., 4 oz.

Stock No.	Mfrs. Type	Fig.	Ht.	Hole	Net Ea.
33 R 32012	40	A	1 1/4"	3/8"	.55
33 R 32053	44	A	1 1/2"	3/8"	.39

STAND OFF INSULATORS. Type 65 and 68 are ribbed and have drain and etched aluminum bases. Type 66 has smooth surfaces and drawn bases. * similar to fig. E, but with square base. Avg. wt., 6 oz.

STEATITE

Stock No.	Mfrs. Type	Fig.	Ht.	Wd.	Net Ea.
33 R 32178	20	C	1 1/4"	10-32	.43
33 R 32194	22	C	1"	8-32	.26
33 R 32210	24	C	3/8"	6-32	.21

PORCELAIN

33 R 32244	65	D	1 3/8"	10-32	.44
33 R 32269	66	E	2 3/4"	1/4-20	.99
33 R 32293	68	E	2"	10-32	.67

Insulated bushings ideal for use in transmitter and antenna installations. Type 50, and 55 are steatite, supplied with cushion washers and hardware. Type 54 is porcelain less all hardware except cushion washer. Maximum diameter: Type 50 3/4", Type 54 3 1/2", and Type 55 3/4".

Stock No.	Mfrs. Type	Shgp.	Fig.	Wt.	Hole	Net Ea.
33 R 32319	50	M	2 oz.	4 1/2"	1 1/2"	.46
33 R 32350	54	J	1 lb.	4"	2 1/4"	1.56
33 R 32368	55	L	2 oz.	3/4"	1 1/2"	.37

Fig. N. ANTENNA STRAIN INSULATOR. Porcelain, heavily glazed, nickel-plated brass hardware, 400 lbs. breaking strength.

Stock No.	Mfrs. Type	Size	Shgp.	Net Ea.
33 R 32376	104	4x3/4" sq.	4 oz.	.36

Fig. D. STEATITE CONE INSULATORS. Complete with 2 machine screws, washers, and a cork cushion washer. Avg. shgp. wt., 2 oz.

Stock No.	Mfrs. Type	Ht.	Width	Net Ea.
33 R 32129	500	3/8"	3/8"	.26
33 R 32137	501	1"	3/4"	.35
33 R 32145	502	1 1/2"	1"	.65

Fig. P. FEEDER SPREADERS. Silicone impregnated, 3/8" x 1/2" cross section. Avg. shgp. wt., 3 oz.

Stock No.	Mfrs. Type	Length	Net Ea.
33 R 32400	136-122	2"	.20
33 R 32418	136-124	4"	.34
33 R 32426	136-126	6"	.50

Antenna Coils—Photoconductive & Photoelectric Cells

INTERNATIONAL RECTIFIER 83M SELENIUM SOLAR CELL



Ratings (in full sunlight). Output 0.2 to 0.4 volts, 1 1/2 to 2 1/2 milliamps. Plastic case with adhesive disc. Size: 1 1/2 x 1 1/2 x 3/8". Shpg. wt., 2 oz.

19 R 29033 Net 2.30

INTERNATIONAL RECTIFIER 82M SUN BATTERY



Average sunlight generates 2 ma. current under 10-ohm load. With MILIL ammeter can be used to measure light. In series or series-parallel will drive transistorized equipment. 60 microamps @ 100 foot candles with 55 ohm load. .5 volt in average sunlight, .25 volt at 100 foot candles. Shpg. wt., 2 oz.

19 R 29017 Net ea. 2.00



PHOTO CELL AND SUN BATTERY ASSORTMENT

This interesting special package contains 4 selenium photo-cells with outputs from 1/2 to 1 1/2 volt and 0.5 ma to 3 ma. in bright sunlight. Complete with 24-page instruction and project manual. Shpg. wt., 4 oz.

19 R 29108 Net .99

INTERNATIONAL RECTIFIER

51M SILICON SOLAR CELL

Output rating 0.3 to 0.4 volts and 10 to 16 milliamps in full sunlight. Plastic case with pressure sensitive adhesive disc. Size: 1 1/2 x 1 1/2 x 3/8". Shpg. wt., 2 oz.


19 R 29041 Net 2.40

54M SILICON SOLAR CELL

High efficiency version of above 51M. Same output voltage of .3 to .4 volt with output current of 25 to 40 ma. Shpg. wt., 4 oz.

19 R 29124 Net ea. 4.40

INTERNATIONAL RECTIFIER



SOLAR DRIVE MOTOR

Precision motor with anti-friction bearings. Ideal for the experimenter and science project enthusiast. Direct operation from power supplies utilizing solar cells. Recommended driving cell is type 54M or two 51M's in parallel (see listing immediately above). Operation from 0.35 to 1.5 Volt. Shpg. wt., 4 oz.

19 R 29132 Net ea. 3.95

LAFAYETTE

PHOTO CONDUCTIVE CELLS



Conductivity of these sensitive cells varies with intensity of light. All rated at 20 ma at 200 volts. Wave length 4000 to 8000 angstroms. Resistance at 0 ft. candle is 10 meg for type A, 5 meg for type B. Other chart ratings approx. ± 50%. Imported. Shpg. wt., 2 oz.

Stock No.	Fig.	Resistance in ohms at	1FC	10FC	100FC	Net
99 R 63208	A	1.5 meg	150,000	25,000	25,000	.99
99 R 63216	B	25,000	4,500	700	700	.99



LAFAYETTE SELF GENERATING SELENIUM CELLS

• No external power needed

Sensitive to a wide spectrum including white, colored or ultra-violet light. All unmounted; complete with leads. Outputs of 100 µa taken at 100 foot candle illumination with 100 ohm load. Shpg. wt., 2 oz. Size: 1 1/2" x 3/4". Imported.

99 R 62432 Net .59



PIONEER CDS CELLS

FIG. A (700 Series) FIG. B (900 Series)
Hermetically sealed high sensitivity cadmium sulphide cells. Types ending in 01 thru 04 are suggested for use with slowly changing daylight; types ending in 10 thru 13 especially suited for industrial photo-control operations depending on interruption of an incandescent source. Maximum dissipation on 700 series is 1/4 watt continuous or 1-watt intermittent (1 min. periods); 900 series is 1/2 watt continuous, 2-watts intermittent. Mean output is photo-current at 50 V AC and simulated daylight of 1 FC; range varying ±33% of mean. Maximum dark current measured at 100V, 5 seconds after 50FC light extinguished. Photosensitive area of 700 series is .1 sq. in. 900 series is .44 sq. in. Average Shpg. wt., 3 oz.

DAYLIGHT TYPES

Stock No.	Type	Mean Output	Max. Dark Curr.	Max. Dark Volt Ea.
19 R 47027	701	1.5 ma.	25 µa.	500 1.40
19 R 47035	702	3 ma.	25 µa.	500 1.40
19 R 47043	703	6 ma.	40 µa.	350 1.40
19 R 47050	901	1.5 ma.	25 µa.	1000 1.25
19 R 47068	902	3 ma.	25 µa.	1000 1.25
19 R 47076	903	6 ma.	40 µa.	700 1.25
19 R 47084	904	12 ma.	200 µa.	500 1.25

INCANDESCENT TYPES

Stock No.	Type	Nom. Res. Ohms	Min. Res	Max. Dark Volt Ea.
19 R 47092	710	1330	4 meg.	500 1.40
19 R 47100	711	670	4 meg.	500 1.40
19 R 47118	712	330	2.5 meg.	350 1.40
19 R 47126	910	1330	4 meg.	1000 1.25
19 R 47134	911	670	4 meg.	1000 1.25
19 R 47142	912	330	2.5 meg.	700 1.25
19 R 47159	913	165	5 meg.	500 1.25

HIGH-GAIN LOOPSTICK ANTENNA



Give high gain across complete AM broadcast band from 540 to 1600 kHz when used with standard 365 pF tuning condenser.

A. VARIABLE TYPE. An extremely small yet very powerful replacement antenna with a "Q" of 240-275. Boosts sensitivity and signal to noise ratio. With adjustable ferrite core for maximum peaking efficiency and precise tracking on entire broadcast band. Single, hole snap-mounting, plus bracket. Efficient at any angle. 2 1/4" x 1/4".

32 R 41064 Shpg. wt., 2 oz. Net .59

B. ENERGIZED FERRI-LOOPSTICK. New 5" ferrite rod loopstick antenna with a "Q" of up to 350. Extremely high gain brings in even distant stations not normally received. Adjustable coil with self-locking vinyl collar permits peaking antenna for super sensitive results. 3/8" x 5". Shpg. wt., 3 oz.

32 R 82019 Net .98

C. 7" SUPER LOOP. Super sensitive ferrite loopstick antenna with a "Q" of up to 425. Excellent for replacement of old style loops. Brings in even hard to get stations. Adjustable for maximum sensitivity over length of 7 in. Complete with mount.

32 R 82027 Shpg. wt., 3 oz. Net 1.35

TRANSISTOR TAPPED VARIABLE ANTENNA COIL



- Boosts Signal Pickup
- Super-Selective!

Specially designed for matching the low input impedance of transistors. Maximum transfer of signal energy from tuning stage when used with 365 to 420 pF variable capacitors, as well as in minimum loading by first transistor stage for sharper tuning and greater selectivity. Highly sensitive with a "Q" of up to 250. With adjustable ferrite core for maximum peaking. Single-hole snap-in mounting, plus bracket. Efficient at all angles. Size: 2 3/8" diam.

32 R 41080 Shpg. wt., 2 oz. Net .99

FERRITE ANTENNA KIT

- 3 Antennas for All 3 Transistor Radios
- High "Q" for Top Reception

for **79¢**



Three sizes of flat ferrite antennas. Each has a high inductance of 480 microhenries. Tapped leads are color coded. Designed to match most AM transistor radios. Matches tuning condenser sect. 167.5—8pF, osc. sect. 75.5—8pF. Sizes: (1) 1 1/4 x 3/8 x 1/8" (2) 2 1/4 x 3/8 x 1/8" (3) 2 3/8 x 3/8 x 1/8". Imported.

99 R 62275 Wt., 3 oz. Net 79¢

RESISTOR PHOTOCELL 109



A cadmium-sulphide light-activated resistor used to actuate door openers, burglar alarms, relays, light controls, production counters, etc. Resistance varies from 75 ohms at approx. 93 foot-candles to over 10 megohms in total darkness. Maximum volts: 110VAC (peak) 110VDC; maximum dissipation: .2 watt @ 40°C, .1 watt @ 50°C, 0 @ 60°C. Capacity approx. 6pF. 1/2" diam. x 3/8" thick. Imported. Shpg. wt., 2 oz.

19 R 21014 Net 1.09

Terminal Strips - Poly Rods & Sheets

BEAU BARRIER STRIPS



Sturdy closed back Barrier strips moulded in black Bakelite are ideal for permanent installations, as well as breadboard and experimental work. Sturdy barriers between terminal strips insure against accidental shorts. Two mounting holes on each end of strip insure ease of installation. See headings about each series for size specifications. Avg. wt., is 5 oz.

TYPE 14000 — 15 AMP

Leakage path between terminals is 3/8". Base is 7/8" wide x 13/32" high.

Stock No.	No. of Contacts	1-49	50-99	Net Each
33 R 86018	1	.16	.13	
33 R 86026	2	.17	.15	
33 R 86034	3	.20	.17	
33 R 86042	4	.25	.21	
33 R 86059	5	.31	.26	
33 R 86067	6	.36	.30	
33 R 86075	7	.41	.35	
33 R 86083	8	.47	.40	
33 R 86091	9	.52	.44	
33 R 86109	10	.59	.50	
33 R 86117	11	.63	.53	
33 R 86125	12	.70	.59	
33 R 86133	13	.74	.62	
33 R 86141	14	.80	.67	
33 R 86158	15	.86	.72	
33 R 86166	16	.91	.76	
33 R 86174	17	.97	.81	
33 R 86182	18	1.02	.85	
33 R 86190	19	1.07	.90	
33 R 86208	20	1.13	.95	
33 R 86216	21	1.20	1.00	

BAKELITE MOUNTING STRIPS



Cadmium plated steel lugs spaced 3/8" on centers. Bakelite strip is 3/8" wide x .062 in. thick. Ideal for supporting and joining electrical components. Type marked * have grounding lugs in addition to the number of terminals indicated below. Mount with No. 6 screw. Avg. wt., 3 oz. 5 per pkg.

Stock No.	Term.	Fig.	Net Per Pk. of 5
32 R 12057	1	A	.18
32 R 12065	2	B	.20
32 R 12073	2*	C	.20
32 R 12081	3	D	.28
32 R 12099	3*	E	.30
32 R 12107	4	F	.31
32 R 12115	4*	G	.33
32 R 12123	5	H	.35
32 R 12131	5*	J	.38
32 R 12149	6	K	.39
32 R 12156	6*	L	.40

KIT OF 48 SOLDER LUG STRIPS

139



Handy assortment of 48 solder lug terminal strips with 8 of each type from 1 thru 6 lugs. Shpg. wt., 8 oz. Imported. Net 1.39

Make Lafayette Your One Dependable Source for Everything in Electronics

TYPE 18000 — 20 AMP

Leakage path between terminals is 7/16". Base is 1 1/4" wide x 1/2" high.

Stock No.	Contacts	No. of	1-49	50-99	Net Each
33 R 86265	1	.19	.16		
33 R 86273	2	.20	.17		
33 R 86281	3	.26	.22		
33 R 86299	4	.34	.28		
33 R 86307	5	.41	.34		
33 R 86315	6	.47	.39		
33 R 86323	7	.55	.46		
33 R 86331	8	.62	.52		
33 R 86349	9	.68	.57		
33 R 86356	10	.76	.64		
33 R 86364	11	.82	.69		
33 R 86372	12	.89	.74		
33 R 86380	13	.96	.80		
33 R 86398	14	1.03	.86		
33 R 86406	15	1.10	.92		
33 R 86414	16	1.18	.99		
33 R 86422	17	1.24	1.04		
33 R 86430	18	1.31	1.10		
33 R 86448	19	1.39	1.16		
33 R 86455	20	1.46	1.22		

TYPE 21000 — 30 AMP

Leakage path between terminals is 9/16". Base is 1 1/4" wide x 5/8" High.

Stock No.	Contacts	No. of	1-49	50-99	Net Each
33 R 86513	1	.22	.18		
33 R 86521	2	.23	.20		
33 R 86539	3	.32	.27		
33 R 86547	4	.40	.34		
33 R 86554	5	.49	.41		
33 R 86562	6	.58	.48		
33 R 86570	7	.67	.56		
33 R 86588	8	.75	.63		
33 R 86596	9	.83	.70		
33 R 86604	10	.93	.78		
33 R 86612	11	1.01	.84		
33 R 86620	12	1.10	.92		
33 R 86638	13	1.19	.99		
33 R 86646	14	1.28	1.07		
33 R 86653	15	1.37	1.14		

HEAVY DUTY SCREW COLLAR STRIPS



3/8" bakelite, 7/8" wide Nickel Plated Brass Screw Terminals, tinned solder lugs. Avg. shpg. wt., 3 oz.

Stock No.	Term.	1-9	10-99	100	NET EACH
32 R 64488	2	.20	.18	.16	
32 R 64496	3	.25	.22	.20	
32 R 64504	4	.30	.27	.24	
32 R 64512	5	.36	.32	.29	
32 R 64520	6	.41	.37	.33	
32 R 64538	7	.46	.41	.37	
32 R 64546	8	.52	.47	.42	
32 R 64553	9	.60	.54	.49	
32 R 64561	10	.63	.57	.51	

TERMINAL STRIPS



High quality bakelite terminal strips. Solder lugs mounted on 3/8" thick insulation. Available with 2 thru 10 solder lugs and screw terminals. Mounting holes for 6-32 screws. Avg. shpg. wt., 5 oz. 5 per Package.

Stock No.	Term.	Pkg. of 5
32 R 12164	2	.45
32 R 12172	3	.63
32 R 12180	4	.78
32 R 12198	5	.93
32 R 12206	6	1.10
32 R 12214	7	1.28
32 R 12222	8	1.45
32 R 12230	9	1.65
32 R 12248	10	1.85

POLYSTYRENE RODS, TUBES AND SHEETS



Feature high dielectric strength, dimensional stability Low loss, arc-resistance, and insulating properties. Moisture proof. Easily sawed, drilled and tapped. Sheets and rods are transparent, tubing satin finish

POLYSTYRENE SHEETS

Stock No	Size Inch	Thick Inch	Shpg. Wt.	Net Each
13 R S1014	12x12	1/4	9 oz.	4.07
13 R S1022	12x12	3/8	9 oz.	4.70
13 R S1030	12x12	1/2	9 oz.	5.39
13 R S1048	12x12	3/4	10 oz.	7.01
13 R S1055	12x12	1/4	1 1/2 lbs.	7.99
13 R S1063	12x24	1/4	14 oz.	7.84
13 R S1071	12x24	3/8	1 1/2 lbs.	8.97
13 R S1089	12x24	1/2	1 1/2 lbs.	10.29
13 R S1097	12x24	3/4	2 1/2 lbs.	12.89
13 R S1105	12x24	1/4	3 1/2 lbs.	15.34

12" POLYSTYRENE ROOS

Stock No.	Size L x Diam.	Shpg. Wt.	Net Each
13 R S1113	12" x 1/2"	3 oz.	.15
13 R S1121	12" x 3/8"	3 oz.	.17
13 R S1139	12" x 1/4"	3 oz.	.20
13 R S1147	12" x 3/4"	3 oz.	.21
13 R S1154	12" x 3/8"	4 oz.	.32
13 R S1162	12" x 1/2"	4 oz.	.47
13 R S1170	12" x 5/8"	5 oz.	.71
13 R S1188	12" x 3/4"	6 oz.	.98
13 R S1196	12" x 7/8"	8 oz.	1.39
13 R S1204	12" x 1"	9 oz.	1.86

12" POLYSTYRENE TUBES

Stock No.	O.D.	I.D.	Shpg. Wt.	Net Each
13 R S1212	1/4"	1/8"	3 oz.	.20
13 R S1220	3/8"	3/16"	3 oz.	.23
13 R S1238	1/2"	1/4"	3 oz.	.28
13 R S1246	5/8"	3/8"	3 oz.	.33
13 R S1253	3/4"	1/2"	3 oz.	.39
13 R S1261	7/8"	3/4"	3 oz.	.44
13 R S1279	1"	3/4"	4 oz.	.60

POLYSTYRENE CEMENT AND COIL DOPE



Pure polystyrene dissolved in thinner. For coating, doping, sealing coils, and for cementing polystyrene to polystyrene. 2 oz. bottle. Shpg. wt., 7 oz.

13 R 60031	Net .55
THINNER FOR ABOVE, 6 oz.	
13 R 60049	Net .59

MASONITE BREADBOARD



● Ideal for Kit Builders

Tempered masonite board with holes spaced 1/2" apart to facilitate mounting of parts. Size 7 1/2" x 11 1/2" x 1/8" thick. Holes 1/4" diam. Shpg. wt., 8 oz.

19 R 17012 Net .29

SPACER ASSORTMENTS




BRASS SPACERS
Package of 16 cadmium plated brass spacers 4 each of 1/4", 1/2", 3/4" & 1" length. All accommodate #6 screw. 1/4" O.D. Shpg. wt., 10 oz.

32 R 12263 Net per pkg. 1.39

FIBRE SPACERS
Assortment of 12 fibre spacers. 4 each of 1/4"—1/2" & 1" lengths. All have 1/4" outer diameter and accommodate #6 screw. Shpg. wt., 3 oz.

32 R 12255 Net per pkg. 1.10

Dials-Variable Condensers



VERNIER LOGGING DIALS

Precision planetary drive vernier dials with approximately 7 to 1 ratio. Ideal for test equipment, calibration instruments, amateur equipment, etc. $\frac{1}{4}$ " diam. shaft extending from rear may be easily coupled to another drive shaft. Type A has framed wire hair line, type B has pointer. All with 1 log scale and blank scales. Fluted knob. Imported.

Stock No.	Fig.	Scale width	Log Scales	Blank Scales	Size Overall	Shp. wt.	Net Each
99 R 25660	B	4 $\frac{1}{4}$ "	0-180	5	5x3x1 $\frac{1}{2}$	10 oz.	2.59
99 R 25678	A	6"	0-200	6	6 $\frac{7}{8}$ x4 $\frac{1}{2}$ x2	1 lb.	2.99
99 R 25686	A	7 $\frac{1}{4}$ "	0-200	6	8 $\frac{1}{2}$ x5 $\frac{3}{4}$ x2 $\frac{1}{4}$	1 $\frac{1}{2}$ lbs.	3.95



COUPLERS AND EXTENDERS

Brass couplings (A) and extenders (B). Diameter of extender or coupling may be equal to, greater than, or less than diameter of shaft extended. Extender shaft length, $\frac{3}{8}$ "; over-all length $\frac{1}{4}$ " Average shpg. wt., 3 oz. All are couplers except * which are extenders.

Stock No.	Size	Each
32 R 64124	$\frac{1}{4}$ x $\frac{1}{4}$ "	.30
32 R 64132	$\frac{1}{4}$ x $\frac{3}{8}$ "	.30
32 R 64140	$\frac{3}{8}$ x $\frac{3}{8}$ "	.30
32 R 64157*	$\frac{1}{4}$ x $\frac{1}{4}$ "	.40
32 R 64165*	$\frac{3}{8}$ x $\frac{1}{4}$ "	.40



PANEL BEARING ASSEMBLY

Use with rigid or flexible coupling when mounting. For up to $\frac{3}{16}$ " panels. Av. shpg. wt., 4 oz.

32 R 64050	3" long, $\frac{1}{4}$ " shaft	.40
32 R 64066	6" long, $\frac{1}{4}$ " shaft	.60
32 R 64074	Bearing only	.15

EXTENSION RODS

For $\frac{1}{4}$ " dia. extensions. Av. shpg. wt., 4 oz.

32 R 64082	6" Nickel Plated	.35
32 R 64090	6" Fibre	.15
32 R 64108	12" Nickel Plated	.70
32 R 64116	12" Fibre	.30





MICA TRIMMERS AND PADDERS

Base of low-loss ceramic. Capacity ranges derived from 3 turns open to tight setting. Av. shpg. wt., 2 oz.

Stock No.	pF	Each	Each
34 R 68386	1.5-15	.35	.32
34 R 68295	2.7-40	.35	.32
34 R 68303	5 -80	.35	.32
34 R 68311	10 -180	.40	.36
34 R 68329	25 -280	.48	.43
34 R 68337	50 -380	.54	.49
34 R 68345	75 -480	.60	.54
34 R 68352	105 -580	.68	.61

PRECISION VERNIER DIALS



AS LOW AS
99¢

Precision planetary drive vernier dials with approximately 8 to 1 ratio. Mounts on panel surface and has accurately centered metal inserts for $\frac{1}{4}$ " shafts. Metal dials are brushed silver finish with deeply etched and black filled engraving to provide maximum legibility even under poor lighting conditions. Reads counter-clockwise 0 to 100 in 180°. Uses tough scratch resistant fluted molded knob and housing for sure grip. Phosphor bronze and brass utilized for internal parts. Imported. Average Shpg. wt., 5 ozs.

Fig. E. 36MM (1 $\frac{1}{2}$ ") Diameter Vernier Dial, $\frac{1}{4}$ " from front to back

99 R 60311

Fig. D 50MM (2") Diameter Vernier Dial, 1" from front to back

99 R 60303

Fig. C 70MM (2 $\frac{7}{8}$ ") Diameter Vernier, 1 $\frac{1}{4}$ " from front to back

99 R 60295

Net .99

Net 1.39

Net 1.69

TINY TUNING CONDENSER—with DIAL

• For Transistor and Miniature Circuits • Only 1" Square, $\frac{1}{8}$ " Deep • 385 pF • Polyethylene Dielectric

A new "Poly-Vari-Con" model for use in TRF broadcast-band and experimental receivers. Complete with good-looking clear plastic tuning dial with calibrations from 530 to 1600 kHz. Capacity variable from 10 to 365 pF. Knurled dial is $\frac{1}{4}$ " diam.; rotation is 180°. Dial is mounted to condenser shaft by $\frac{1}{8}$ " diam. chrome-plated threaded retainer. Imported.

99 R 62176 Shpg. wt., 3 oz.

Net .79



HAMMARLUND MINIATURE VARIABLE CONDENSERS



TYPE HF

Single section tuning employing "APC" rotor and stator design—ideal for critical high freq. circuits. Isolantite insulation. Air gap is 0.015" nominal. Shpg. wt., 4 oz.

Stock No.	Mfg's Type	Max. Min.		Net
		pF	pF	
40 R 28617	HF15	17.5	2.8	1.45
40 R 28625	HF35	36.	3.2	1.55
40 R 28633	HF50	42.	3.7	1.75
40 R 28641	HF100	102.	5.3	2.00
40 R 28658	HF140	142.	6.3	2.15

TYPE HFA

Similar to "HF" except very desirable for high frequency low-power applications. Single hole or base mounting. $\frac{3}{16}$ " x $\frac{1}{4}$ " round shaft. $\frac{3}{16}$ -32 thread x $\frac{3}{16}$ " L bushing. Wt., 8 oz.

40 R 28411	HFA-15-B+	16	2.8	2.20
40 R 28429	HFA-25-B**	25	3.0	2.30
40 R 28437	HFA-50-B+	50	4.3	2.50
40 R 28445	HFA-100-B+	100	7.5	4.35



TYPE APC

Compact, high quality. Has high leakage resistance and resistant to temperature, moisture, and vibration effects. Straight line capacitance. Hex collar on slotted shaft for rotor and screw-driver adjustment. Air gap is 0.015" nominal. Shpg. wt., 4 oz.

Series APS (Screwdriver Slot)

Stock No.	Mfrs. Type	Max. Min.		Net
		pF	pF	
40 R 28460	APC-25	25	3.0	1.25
40 R 28478	APC-50	50	3.9	1.35
40 R 28486	APC-75	75	4.6	1.45
40 R 28494	APC-100	100	5.5	1.60
40 R 28502	APC-140	140	6.7	1.80

Series APC-B ($\frac{1}{2}$ " Shaft)

40 R 28528	APC-25B	25	3.0	1.35
40 R 28536	APC-50B	50	3.9	1.45
40 R 28544	APC-75B	75	4.6	1.55
40 R 28551	APC-100B	100	5.5	1.80
40 R 28569	APC-140B	140	6.7	2.00



TYPE MAPC

About half the weight and size of the APC, but with the same quality and performance. Excellent for VHF use. Slotted shaft for screwdriver or hex wrench adjust. Nom. air gap 0.0135". Size $\frac{3}{16}$ " x $\frac{1}{4}$ " H. Shpg. wt., 3 oz.

Series MAPC (Screwdriver Slot)

Stock No.	Mfrs. Type	Max. Min.		Net
		pF	pF	
40 R 28635	MAPC-15	15	2.3	1.10
40 R 28643	MAPC-25	25	2.6	1.15
40 R 28650	MAPC-35	35	2.9	1.20
40 R 28668	MAPC-50	50	3.2	1.25
40 R 28676	MAPC-75	75	3.9	1.35
40 R 28684	MAPC-100	100	4.5	1.45

Series MAPC-B ($\frac{1}{2}$ " Shaft)

40 R 28692	MAPC-15B	15	2.3	1.10
40 R 28700	MAPC-25B	25	2.6	1.15
40 R 28718	MAPC-35B	35	2.9	1.20
40 R 28726	MAPC-50B	50	3.2	1.25
40 R 28734	MAPC-75B	75	3.9	1.35
40 R 28742	MAPC-100B	100	4.5	1.45

Knobs—Dial Cord and Coils

LAFAYETTE
455 kHz UNIVERSAL I.F.
TRANSFORMER FOR
BROADCAST AND
CITIZENS BAND

As Low As

79^c

● Only 3/4" Square



The most popular replacement I.F. Ideal for experimenters. Exceptionally high gain powdered iron core, compression tuned 455 kHz midget I.F.—only 3/4" square by 1 1/2" high. For both input and output circuits. Supplied with mounting clip and adapter plate to replace both midget and larger size cans. Shpg. wt., 4 ozs.
32 R 09467 Singly, each .89
Lots of 10 each .79


LAFAYETTE
MINIATURE I.F. TRANSFORMERS
AND OSCILLATOR COILS





NET
EACH
59^c


Slug-tuned printed circuit mounted miniature I.F. transformers. All have 455 kHz intermediate frequency. Each with schematic and pin contacts. Ideal replacements for Japanese transistor radios. Shpg. wt., 2 oz. Imported. All Units only 3/4" Sq. and 3/4" High.
99 R 63000 Oscillator coil Inductance 270µh.
99 R 63018 1st IF; pri. 70,000 ohms, sec. 1500 ohms.
99 R 63026 2nd IF; pri. 50,000 ohms, sec. 1000 ohms.
99 R 63034 3rd IF; pri. 30,000 ohms, sec. 5000 ohms.
Any of above Net ea. .59

MILLER TRANSISTOR
ANTENNAS

STANDARD 
Has a fixed inductance of 240µh and covers a band of 540-1650 kHz. Large pickup area and high Q. Maximum tuning capacity 365 mmf. Q @ 790 kHz. 450. Shpg. wt., 3 oz.
34 R 88194 Type 2000 Net 2.58

MINIATURE 
Has an inductance of 240µh and is designed for use with a standard variable condenser having a maximum capacity of 365 mmf. Freq. range 540-1650 kHz. Q @ 790 kHz, 550. Shpg. wt., 4 oz.
34 R 87485 Type 2001 Net 2.28

SUB MINIATURE 
Adjustable antenna coil with high Q ferrite cores. Inductance range for 2002 is 40-300µh, for 2007, 150-1000µh. Freq. range 540-1650 kHz. Q @ 790 kHz for 2002, 250; for 2007, 220. Tuning capacity 2002, 250-450 mmf; 2007, 100-250 mmf. Wt., 4 oz.
34 R 87493 Type 2002 Net 1.80
34 R 88210 Type 2007 Net 2.25

FERRITE STRIP 
Has an inductance of 240µh and is to be used with a condenser having a maximum capacity of 365 mmf. Freq. range 540-1650 kHz. Q @ 790 kHz, 500. Shpg. wt., 3 oz.
34 R 88202 Type 2004 Net 2.55

POINTER, BAR AND
LEVER KNOBS



Black knobs molded of high quality plastic. All have set screw for 1/4" round or flatted shaft, and white indicator lines. Items marked * have brass insert. Size shown is length. Av. shpg. wt., 2 oz.

Stock No.	Fig.	Size	Net Each	
			1-24	25-99
32 R 24110	A	2"	.22	.20
32 R 24128	C	1 1/4"	.14	.12
32 R 24136*	C	1 1/4"	.20	.18
32 R 24144	D	1 1/4"	.16	.14
32 R 24151*	B	1 1/2"	.29	.26
32 R 24169	E	1 1/4"	.16	.14

MINIATURE
KNOBS



Plastic knob, only 5/8" diameter fits 1/4" shafts, for miniature components such as Ferri-loop-stick, sub-miniature pots, etc. Avg. shpg. wt., 2 oz.
32 R 24052 Walnut Net .15
32 R 24011 Ivory Net .16

PROFESSIONAL
KNOBS



Add professional appearance to any equipment. Professional black-matte finish with concave top. To fit 1/4" round shaft. All knobs come with set screw. Skirt dimen. 3/4" dia. x 3/4" H. Imported. Shpg. wt., 2 ozs.
99 R 61087 Net .34

FLUTED KNOBS



Black fluted knobs, with and without skirt. Made of thermosetting plastic with high gloss finish. All have recessed brass insert and set screw. Mount on 1/4" round or flatted shaft. Shpg. wt., 2 ozs.

Stock No.	Fig.	Diam.	Hght.	Net Each	
				1-24	25-99
32 R 24060	A	1 1/4"	3/8"	.31	.29
32 R 24078	A	1 3/8"	3/4"	.34	.31
32 R 24086	A	1 5/8"	3/4"	.37	.34
32 R 24094	B	1 1/2"	1 1/4"	.68	.61
32 R 24102	B	2 1/8"	1 3/4"	.75	.68

STANDARD PLASTIC KNOBS



Plastic knobs with knurled bodies for general application. All have molded hole with set screw for mounting 1/4" round or flatted shafts. Fig. C has white indicator lines. Av. shpg. wt., 2 ozs.

Stock No.	Fig.	Diam.	Color	Net Each	
				1-24	25-99
32 R 24177	A	1"	Walnut	.18	.16
32 R 24185	A	1"	Black	.17	.15
32 R 24201	C	1 1/2"	Black	.22	.19
32 R 24219	C	1 3/4"	Black	.20	.17
32 R 24227	B	3/4"	Maroon	.14	.10

MATCHED KNOB KITS

- Molded From Hi-Impact Plastic
- Brass Screw and Shaft Insert
- For 1/4" Round or Flat Shaft



KIT OF 5
as low as

89^c

Trim distinctive, functionally styled knobs. Finished in an attractive steel gray and molded from tough hi-impact plastic, the knob is of cylinder design with sure-grip fluted sides and an aluminum ring-set in a recessed face. Rugged brass screw and mounting shaft insert will accept 1/4" round or flat shaft. Each kit contains 5 knobs—all same size. Imported. Shpg. wt., 5 oz. 1 7/8" Diam., 7/8" Deep Kit of 5.

99 R 61145 Net .89
1 3/8" Diam., 1 1/4" Deep Kit of 5
99 R 61152 Net .89
1" Diam., 1 1/4" Deep Kit of 5
99 R 61160 Net .89

METAL KNOB KIT



Set of 3 attractive, tapered aluminum knobs. Set-screw type, fit 1/4" shaft. Polished concave top, 3/4" long, diameter tapers from 1/4" to 1/8". Imported.
99 R 62606 Shpg. wt., 4 oz. Net 1.29

COMMUNICATION
RECEIVER
KNOBS



Molded of Tenite with easy grip knurling. These knobs are 1 1/4" over-all diameter with chrome-plated bevel skirts. Depressed numerals are black enameled on chrome plate. Designed to fit 1/2" shafts. Numbered 0-10 through an arc of 300° clockwise. Imported. Shpg. wt., 3 oz.
99 R 61053 Net ea. .36

DIAL CORD



Handy spools of pre-stretched nylon dial cord in sizes that cover almost all replacement needs. Breaking strength medium is 35 lbs., standard 20 lbs., thin 15 lbs. Average shpg. wt., 4 oz.

100 Foot Spools

Stock No.	Type	Diameter	Net.
32 R 80187	Medium	.040"	2.60
32 R 80195	Standard	.028"	2.60
32 R 80203	Thin	.025"	2.60

25 Foot Spools

32 R 80211	Medium	.040"	.83
32 R 80229	Standard	.028"	.83
32 R 80237	Thin	.025"	.83

NATIONAL BALL REDUCTION
DRIVE FOR PRECISE TUNING

Efficient drive in ratios of 5:1 and 10:1. Shaft set screw for mounting 1/4" round shaft. Shaft size 1/4"; = female coupling one end, ↑ male shafts both ends. Shpg. wt., 4 to 8 oz.



Stock No.	Type	Reduction	Net Ea.
32 R 51352	NBD1-1 ↑	5:1	4.28
32 R 51360	NBD1-2 ↑	5:1	4.81
32 R 51378	NBD2-1 ↑	10:1	4.93
32 R 51386	NBD2-2 ↑	10:1	5.43

Antennas Are Available On Easy Pay Plan—No Money Down

Lafayette Cat. No. 720 231

Coils - Coil Forms - Coil Winder



UNSHIELDED MINIATURE TRANSISTOR OSCILLATORS

(Fig. A.) The 34 R 88012 oscillator coil (Revised 5-lug) is designed for use in a converter oscillator circuit. The 34 R 87022 oscillator coil (6-lug) is for use where a separate transistor is used for the oscillator and another transistor for the mixer. I.F. Freq. 455 kHz. Avg. Shpg. wt., 3 oz. Dimensions: 3/8" x 1" high

Stock No.	Miller	Capacity	Net
34 R 88012	2020	365 mmf.	2.10
34 R 87014	2022	78-100 mmf.	2.10
34 R 87022	2023	365 mmf.	2.10

MILLER WIDE RANGE ADJUSTABLE INDUCTORS



For immediate application in many prototype designs where the exact value of the required inductance is not known. Induction measured at 1000 KHz. Dimensions: max. dia. 3/4" x 1 1/4" long. Specifications for tapped are identical to untapped of reference types shown. Column headed "Ratio" refers to the total number of turns on the coil to the number of turns to the tap. Shpg. wt., 3 oz.

Untapped				
Stock No.	Type	L Min.	L Max.	Net
34 R 89846	9001	40μh	.240 MH	1.59
34 R 89853	9002	.180 MH	.800 MH	1.80
34 R 89861	9003	.570 MH	2.80 MH	2.16
34 R 89887	9005	6.00 MH	16.0 MH	2.88
34 R 89895	9006	12.0 MH	40.0 MH	3.27
34 R 89911	9008	78.0 MH	240. MH	3.39
34 R 89511	9009	180. MH	750. MH	3.54

Tapped Ref.				
Stock No.	Type	Type	Ratio	Net
34 R 89937	9012	9002	204/68	2.16
34 R 89945	9013	9003	376/128	2.52
34 R 89978	9016	9006	1480/493	3.27
34 R 89994	9018	9008	3860/1286	3.78
34 R 86529	9019	9009	6100/2030	3.95

STANDARD ADJUSTABLE CERAMIC FORM AND R.F. COILS

Permeability tuned coils wound on silicone impregnated ceramic forms. Hardware necessary for assembly is supplied. Dimensions (form): 3/8" diameter x 1 1/4" long. Shpg. wt., 3 oz.

Stock No.	Type	Microhenries	Net
34 R 89515	4400	Form Only	2.15
34 R 87535	4404	1.6-3.1	2.66
34 R 87543	4405	3.3-6.5	2.70
34 R 87550	4406	7.3-14	2.77
34 R 87558	4407	16-29	2.84
34 R 87575	4408	33-66	3.02
34 R 87584	4409	74-124	3.10
34 R 87592	4410	139-238	3.13
34 R 87600	4411	270-451	3.17
34 R 87618	4412	495-760	3.20
34 R 87626	4413	825-1300	3.24
34 R 87634	4414	1400-2000	3.24

COILMASTER DELUXE ACCURATE COIL WINDER



Latest redesigned model gives even greater accuracy than ever to meet modern requirements. Easy-to-use set winds honeycomb, spiderweb and solenoid coils of various widths and diameters—equal in appearance to a factory job. Also suitable for winding chokes, transformers and filter inductors. Indicator counts number of turns on coil. Uses #22 to #40 wire. Supplied with accessories including wood spools, metal pegholders and extension for making long solenoid coils. Instructions included, but less coil form and pegs. Shpg. wt., 2 lbs. 32 R 87018 Net 8.25

UNIVERSAL ADJUSTABLE OSC. COIL

(Fig. D.) Adjustable iron core oscillator coil for general replacement use. RF freq. 500-1800 kHz, IF freq. 100-500 kHz. Dimensions 1 1/2" x 1 1/2" high. Shpg. wt., 3 oz. 34 R 87048 Miller Type 71-OSC Net 3.36



MILLER R.F. COIL FORMS

Fine grade quality coil forms. Frequency range of core is 1-20 MHz. Types 20A000-2, 21A000-2, 22A000-2 are constructed of a phenol impregnated tubing which could be certified to MIL-P-79B, type PBG. Type 4200-2 is strong nylon. Types 4300-2, 4400-2, 4500-2 are made of silicone-impregnated ceramic. In accordance with JAN 1-10, grade L5. Hardware is included. Shpg. wt., 3 oz.

Stock No.	Type No.	Dia.	Lgth.	Hole	Net Ea.
34 R 89432	20A000-2	1/4"	1 3/4"	1/4"	1.24
34 R 89135	21A000-2	3/8"	1 1/4"	1/4"	1.24
34 R 89432	22A000-2	1/2"	7/4"	1/4"	1.81
34 R 89507	4200-2	.289	1 1/4"	3/16"	.98
34 R 87725	4300-2	3/8"	5/8"	1/4"	1.43
34 R 89515	4400-2	3/8"	1 1/4"	1/4"	2.15
34 R 89523	4500-2	1/4"	7/8"	3/16"	1.52



PHENOLIC FORM 3-SECTION R.F. CHOKES

A new series of R.F. Chokes taking advantage of the high permeability of ferrite cores. These chokes combine high inductance and low D.C. resistance.

Stock No.	Miller	mh	Ohms	Max. ma	Net
34 R 88277	4646	0.24	8.16	125	.89
34 R 88285	4649	0.55	13.2	125	.95
34 R 88293	4652	1.0	19.8	125	.95

RESINITE ADJUSTABLE R.F. COILS

Resinite is a phenolic impregnated tubing which can be certified to MIL-P-79B type PBG. Combines good mechanical and electrical characteristics. Dimensions: 1/4" dia. x 1 1/4" long. Avg. shpg. wt., 3 oz.

MINIATURE ADJUSTABLE R.F. COILS

Stock No.	Miller	Type	20A-	Min. μh.	Max. μh.	Net
34 R 89440	107RB1			.088	1.20	1.68
34 R 89416	157RB1			.108	1.80	1.58
34 R 89408	477RB1			.356	5.64	1.76
34 R 89374	687RB1			.508	8.16	1.76
34 R 89382	827RB1			.735	9.84	1.76
34 R 89358	106RB1			.885	1.20	1.76
34 R 89366	156RB1			1.08	1.80	1.76
34 R 89333	226RB1			1.62	2.64	1.76
34 R 89341	336RB1			2.38	3.96	1.76
34 R 89325	686RB1			5.08	8.16	1.76
34 R 89291	826RB1			7.35	9.84	1.76
34 R 89275	155RB1			10.8	18.0	1.99
34 R 89259	335RB1			23.8	39.6	1.99
34 R 89226	154RB1			108.	180.	1.99

HIGH-Q R.F. COILS

(Fig. E.) A complete line of unshielded permeability tuned coils for replacement use or as the front end components in new receiver design. Ranges shown are for use with a 365 mmfd variable tuning condenser. Dimensions: 3/8" x 2". Avg. shpg. wt., 3 oz.

Stock No.	Miller No.	Use
LONG-WAVE COILS (140-420 kHz)		
34 R 87063	A-5495-A	Antenna Stage
34 R 87071	X-5495-RF	RF Stage
34 R 87089	X-5495-C	Standard Osc. 455 kHz
34 R 87097	X-5496-C	Tapped Osc. 455 kHz
Any of above Net ea. 3.42		

BROADCAST BAND COILS (540-1700 kHz)		
34 R 87105	A-5495-A	Antenna Stage
34 R 87113	A-5495-RF	RF Stage
34 R 87121	A-5495-C	Standard Osc. 455 kHz
34 R 87139	A-5496-C	Tapped Osc. 455 kHz

MEDIUM WAVE COILS (1.75-5 MHz)		
34 R 87147	B-5495-A	Antenna Stage
34 R 87154	B-5495-RF	RF Stage
34 R 87162	B-5495-C	Standard Osc. 455 kHz
34 R 88186	B-5496-C	Tapped Osc. 455 kHz

SHORT WAVE BROADCAST COILS (5-18 MHz)		
34 R 87519	C-5495-A	Antenna Stage
34 R 87170	C-5495-RF	RF Stage
34 R 87188	C-5495-C	Standard Osc. 455 kHz
34 R 87196	C-5496-C	Tapped Osc. 455 kHz

HIGH FREQUENCY COILS (12-36 MHz)		
34 R 87204	D-5495-A	Antenna Stage
34 R 87212	D-5495-RF	RF Stage
34 R 87220	D-5495-C	Standard Osc. 455 kHz
34 R 87238	D-5496-C	Tapped Osc. 455 kHz
Any of above Net ea. 2.85		

HIGH-Q FERRITE ANT. COIL

(Fig. G.) Highly efficient broadcast band antenna coil for use in small receivers where no external antenna is desired. High-permeability low loss ferrite tuning core. Freq. range, 540-1700kHz. Supplied with mounting bracket and 18" polyethylene insulated antenna wire. Size: 3/8" x 2 1/4". Wt., 3 oz. 34 R 87055 Miller 6300 Net 1.52

10.7 MHz TRANSISTOR I.F.'S

(Fig. F.) A complete series of IF Transformers specifically designed for operation with transistors. Single tuned IF's and double tuned ratio detector. Size: 1F—1/2" sq. x 3/4" high—Size: ratio detector—1/2" x 3/4" x 1/2" high. Shpg. wt., 3 oz. Net Ea.

34 R	Miller	Type	1st IF	2nd IF	3rd IF	Ratio Det.	Net Ea.
34 R 88145	2070		3.42				
34 R 88152	2071			3.42			
34 R 88160	2072				3.42		
34 R 88178	2073					4.07	

3/4" PERMEABILITY TUNED I.F. COILS

Tuned top and bottom, powdered iron cores. Silvered mica condensers, molded plastic bases, etched aluminum cans. 3/4" x 1/2" x 1/2" With mounting clip and plate. *Spade bolt mtg. with leads. †—with diode condenser. Shpg. wt., 3 oz.

Stock No.	Meissner	Type	Function	Net
32 R 55320	16-6758		455 kHz Input	2.18
32 R 55346	16-6752		262 kHz Input	1.86
32 R 55361	16-3487		10.7 MHz FM Input	3.72
32 R 55379	16-6678*		455 kHz AC-DC	3.83

HORIZONTAL LINEARITY AND WIDTH CONTROLS

Iron core variable inductance coils for linearity and width adjustment. Wound on a bakelite form 3/8" in diameter. Mtg. clip fits 3/8" hole. 6300's—phenolic form. Avg. shpg. wt., 3 oz.

Stock No.	Miller	Millichenries	Net
34 R 88384	6196-A	054-.50 Tapped	2.12
34 R 88442	6314	2.0-18	1.75
34 R 88459	6315	4.0-30	1.75
34 R 88483	6318	20-3.0	1.59
34 R 88491	6319	15-60	2.16
34 R 88517	6321	1.0-5.0 Tapped	2.03
34 R 88525	6322	1.5-10	1.69
34 R 88533	6323	5.0-5.0 Tapped	2.03
34 R 88541	6324	60-130 Tapped	2.16
34 R 88487	6329	2.2-10 Tapped	2.16
34 R 88495	6330	45-215	2.39

Coils and Chokes

MILLER COMMUNICATIONS I.F. TRANSFORMERS



Designed for experimental use in communications equipment where selectivity and stability are important. The 100 kHz I.F. transformer and BFO coil are intended for tube application, while the 455 kHz crystal filter I.F. transformers have taps on the winding to allow for use with both tubes and transistors. The 1800 kHz I.F. transformer offers the best possible "Q" with stability to give a degree of selectivity that compares with lower frequency I.F. transformers. This transformer is for use with tubes only. Type number 1770 is a double-tuned I.F. transformer having taps on both Primary and Secondary windings. Dimensions: 3/4" by 3/4" by 2" high. Average shpg. wt., 4 oz.

Stock No.	Type	Description	Net
34 R 86404	1709	100 kHz I.F.—2.5 kHz Bandwidth	3.82
34 R 87840	1710	100 kHz I.F.—3 kHz Bandwidth	3.17
34 R 87857	1711	100 kHz B.F.O.	2.95
34 R 87865	1725	455 kHz Crystal Filter I.F. Input	3.31
34 R 87873	1726	455 kHz Crystal Filter I.F. Output	2.95
34 R 87881	1727	455 kHz B.F.O.	2.74
34 R 87899	1730	1800 kHz I.F.—25 kHz Bandwidth	3.17
34 R 87915	1731	455 kHz Double Tuned Transistor I.F.—30K:1K	3.82
34 R 86412	1732	1650 kHz Link Coupling Coil Unshielded	3.60
34 R 86420	1733	1650 kHz I.F. (Citizens Band Transceivers)	3.17
34 R 86438	1740	9 MHz S.S.B. Input Trans.	3.17
34 R 86396	1741	9 MHz S.S.B. Output Trans.	3.17

FERRITE CORE R.F. CHOKES



A new series of R.F. Chokes taking advantage of the high permeability of ferrite cores. These chokes combine high inductance and low D.C. resistance. Size: 1/4" diameter x 7/8" long. 1 1/2" axial leads.

Stock No.	Miller Type	Mh	Ohms Max.	MA.	Net
34 R 87923	6302	2.5	9	160	1.24
34 R 87931	6304	5	14	160	1.43
34 R 87949	6306	10	31	100	1.59
34 R 87956	6308	25	82	65	1.59
34 R 87964	6310	50	127	65	1.91

FREQUENCY SELECTIVE R.F. CHOKES



Designed for maximum efficiency and highest impedance at specific operating frequencies, this group of R.F. chokes eliminates the designers task of attempting to choose the best coil for a particular application. Designed to cover the major

Amateur, Industrial, and Citizens bands. Shpg. wt., 3 oz.

Stock No.	Miller Type No.	L	Freq. MHz	Fig.	Net
34 R 89697	RFC-14	84 μ h	7-20	1	1.49
34 R 89705	RFC-21	38.5 μ h	15-30	1	1.21
34 R 89713	RFC-28	24 μ h	25-40	2	1.34
34 R 89721	RFC-50	8.2 μ h	30-90	2	1.15
34 R 89739	RFC-144	1.72 μ h	75-180	2	.80
34 R 89747	RFC-220	.82 μ h	160-340	2	.80
34 R 89754	RFC-420	.22 μ h	325-500	2	.98

ECONOMY ADJUSTABLE R.F. CHOKES



A recently developed nylon molding process makes possible an inexpensive line of adjustable chokes. They are adjustable from either the top or the bottom, giving you design flexibility. Mounting is achieved by way of a metal clip in a 3/4" hole. Dimensions: 3/4x1 3/4" long. Shpg. wt., 3 oz.

Stock No.	Miller Type	Microhenries	Net
34 R 89507	4200	Form only	.88
34 R 89762	4202	1-2.5	1.30
34 R 89770	4203	2-5.5	1.34
34 R 89788	4204	5-15	1.37
34 R 89796	4205	10-25	1.40
34 R 89804	4206	20-55	1.49
34 R 89812	4207	50-140	1.52
34 R 89820	4208	120-330	1.56
34 R 89838	4209	310-860	1.59

MILLER FM STEREO MULTIPLEX INDUCTORS

For use in FM Stereo Multiplex tuners and receivers, both standard and printed circuit. Size: 3/4" sq. x 1 1/2" high. Shpg. wt., 3 oz.

Stock No.	Type	Description	Net
34 R 88749	1351	Low Pass Filter	2.99
34 R 88756	1352	Band Pass Filter Series Element	2.74
34 R 88764	1353	Band Pass Filter Shunt Element	2.74
34 R 88772	1354	Locked Oscillator 19 kHz	3.89
34 R 88780	1355	Output Transformer 38 kHz	3.60

PRINTED CIRCUIT

Stock No.	Type	Description	Net
34 R 88798	1351-PC	Low Pass Filter	2.99
34 R 88805	1352-PC	Band Pass Filter Series Element	2.74
34 R 88814	1353-PC	Band Pass Filter Shunt Element	2.99
34 R 88822	1354-PC	Locked Oscillator, 19 kHz	3.46
34 R 88830	1355-PC	Output Transformer, 38 kHz	3.46

For use in a newly designed circuit that eliminates the 19 kHz Oscillator and resulting synchronizing problems. In conjunction with an improved low pass filter and detecting system. Improved separation can be achieved. Shpg. wt., 3 oz.

Stock No.	Type	Description	Net
34 R 87816	1356	19 kHz Output	3.49
34 R 87824	1357	38 kHz Input	3.46
34 R 87832	1358	Low Pass Filter	3.60

SUBMINIATURE ADJUSTABLE R.F. COILS



These compact adjustable coils offer a minimum two-to-one inductance range with relatively small changes in Q. The tuning adjustment is accessible from either the top or bottom of the coil assembly. Magnetic and electrostatic shielding. Printed circuit terminals. Size: 1/4" sq. x 3/8" high. Avg. shpg. wt., 3 oz.

Stock No.	Miller Type	L Min.	L Max.	Cap (pf)	Net
34 R 89572	9054	28.0 μ h	60.0 μ h	11.0	2.77
34 R 89598	9056	120.0 μ h	280.0 μ h	9.0	2.77
34 R 89614	9058	650.0 μ h	1.3Mh	8.0	2.84
34 R 89622	9059	1.3Mh	3.0Mh	7.0	3.13
34 R 89630	9060	3.0Mh	10.0Mh	7.0	3.13
34 R 89648	9061	8.0Mh	20.0Mh	7.0	3.13
34 R 89655	9062	15.0Mh	40.0Mh	7.0	3.13
34 R 89663	9063	20.0Mh	60.0Mh	10.0	3.24

MILLER HEAVY DUTY HASH CHOKES



Molded powdered iron form offer a series of relatively high inductance, high current hash filter chokes.

Stock No.	Part	Uh.	Ohms Max.	Amp.	Net
34 R 86586	5218	3.35	.010	13	1.85
34 R 86594	5220	8.8	.021	5	1.85
34 R 86610	5240	40.0	.082	2	1.32
34 R 86602	5248	68.0	.054	5	1.50
34 R 86628	5250	100.0	.216	2	1.50

NATIONAL RF CHOKES

Wound on ceramic form except R33, R50 and R60 series on bakelite. All have fungus resistant varnish coat. Type R33 is 2 section, R50 are 3 and 4 section. Types with \dagger mounted on fixed standoff insulator. Types ending in U have removable standoff. Shpg. wt., 1 oz. All others, 2 oz. \ddagger = Millihenries μ = Microhenries

Stock No.	Mfr. Type	Fig.	MH \ddagger	Ma	Ohms	NET EACH
32 R 51014	R-100	A	2.5	115	44	.84
32 R 51022	R-100	A	5	70	90	1.15
32 R 51030	R-100	A	10	60	130	1.35
32 R 51063	R-100U \ddagger	B	10	60	130	1.80
32 R 51121	R-300	A	1	400	11	.80
32 R 51154	R-300ST	C	2.5	375	17	1.00
32 R 51162	R-50	D	.5	150	15	.60
32 R 51170	R-50	D	1	135	23	.80
32 R 51196	R-50	D	10	115	36	.85
32 R 51212	R-154U	F	1	600	6	4.00
32 R 51238	R-33	D	1*	850	.06	.48
32 R 51246	R-33	D	11*	350	1.8	.45
32 R 51253	R-33	D	50*	225	3.5	.45
32 R 51261	R-33	D	100*	200	5	.48
32 R 51279	R-33	D	750*	125	16	.48
32 R 51287	R-60	E	2*	1500	.06	.51
32 R 51295	R-40-3.3	G	3.3	125	15.7	.82

STANDARD ANTENNA AND R.F. COILS




Designed to cover the broadcast band from 545 to 1580 kHz (190-550 meters) with a 365 mfd. tuning condenser. High impedance primaries, wound with Litz wire. Shielded coils are in black crackle finish, non magnetic can. 1 1/2" in diameter, 2 1/2" high. *unshielded \ddagger shielded. Average shpg. wt., 4 oz.

Stock No.	Meissner	Description	Net
32 R 55205	14-1010*	Ant. Coil	3.72
32 R 55213	14-1004*	Ant. Coil	3.72
32 R 55221	14-1011*	RF Coil	2.79
32 R 55239	14-1005*	RF Coil	3.72

SUB-MINIATURE TRANSISTOR I.F.'s AND OSCILLATOR

Cup core construction permits the use of extremely small shields without adversely affecting transformer operation. A high impedance, tapped primary winding coupled to a low impedance secondary provides optimum energy transfer between stages. Dimensions: 3/8" sq. x 3/8" high.


Stock No.	Miller Type	Freq.	Imp.	Item	Net
34 R 86081	9-C1	455kHz	25K	Input 300 ohms	3.00
34 R 86131	9-C2	455kHz	25K	Output 1000 ohms	3.00
34 R 87030	2021	Oscillator	(Tuning Cap. 78 pF Max.)		2.67



Depend on Lafayette For Complete Stocks, Lowest Prices, Fastest Service

RELAYS — RELAY TOOLS — COUNTERS

SENSITIVE MINIATURE RELAY



ONLY
\$2.95 ea.




Extremely small, sensitive relay—weighs only 1/2 oz.! Double-pole double-throw, with silver and silver-gold-platinum alloy contacts. Contact handle up to 100 volts at 300 ma. (30 watts). Coil measures 5,300 ohms DC resistance-rated at 4.1 ma, DC pull-in current, 0.95 ma. DC, drop-out. Enclosed in transparent plastic dust cover; Operating time 2.8 milliseconds; release time about 1.5 msec. Breakdown voltage rating: coil to frame, 500V; contacts to frame 350V. Measures 1 1/2 x 1 1/2 x 7/8". Ideal for model control, photocell relay, carrier-current control and dozens of other miniature applications. Imported. Shpg. wt., 4 oz.

OPDT Miniature OC Relay
99 R 60931

Net 2.95

HAND TALLY REGISTER



249


- 4 Digit Capacity
- Counts 0-9999
- Single Turn Reset Knob

Registers 0 to 9999. Highly polished chromium plated brass case. Attached finger-ring and compact shape for comfort in holding. Plunger operated for smooth, easy action. Large, clearly read numerals. Knurled reset knob sets register to zero in one turn. Precision accuracy for lab, school and industrial users. Invaluable for inventory control—gate checking—traffic, etc. Small size, approximately 1 1/2 x 1 1/2 x 7/8". Permits concealed operation. Imported. Wt. 5 oz.

99 R 90300

Net 2.49

5-DIGIT STROKE-ACTUATED RESET COUNTER



349

Easy-to-mount rugged counter for counting machine operations. One count per stroke. Drilled mounting flange; actuating arm and spring. May be manually or solenoid actuated. Reads up to 99,999; side knob easily resets to zero from any number. Overall size: 2 1/2 x 1 1/2 x 1 1/2". Imported. Wt., 1/2 lb.

99 R 90292

Net 3.49

6-DIGIT ELECTRIC COUNTER



1295

- Registers from 1 to 999,999

May be actuated by any switch, relay, etc. Operates in any position. White figures on a black background read up to 999,999. Built-in selenium rectifier. DC operated solenoid, chrome-plated. 6" leads, 110V, AC, 50/60 Hz. Size: 2 1/2 x 2 x 1 3/4". Removable front plate: 3 3/8 x 2". Imported. Shpg. wt., 1 lb.

99 R 90110

Net 12.95

JONARD RELAY TOOLS

POCKET CLEANER-BURNISHERS



Compact penfile for cleaning and burnishing relay contacts. Replaceable steel blades leave no residue. Plastic cap permits working on "live" contacts. Chromed barrel with pocket clip. With 12 blades. Size: 3/8 x 5 1/2". Shpg. wt., 3 oz.

- P-4, Penfile with 12 RB-4, 1/4 x 1 1/4" blades. 12 R 22058 Net 4.82
- P-6, Penfile with 12 B-6, 3/8 x 1 3/4" blades. 12 R 22066 Net 4.82
- RB-4, Replacement blades for P-4, pkg. 25. 12 R 22074 Shpg. wt., 3 oz. Net 5.02
- RB-6 Replacement blades for P-6, pkg. 25. 12 R 22082 Shpg. wt., 4 oz. Net 5.02

SPRING TENSION GAUGES



Precision gauges for determining tension of relay and other electronic springs. Engraved scale, front and back for indicating horizontally or vertically. Center-to-left or center-to-right reading. 1 1/2 x 5". Shpg. wt., 1/4 lb. G-10, 0-10 gram gauge in 1 gram steps. 12 R 22108 Net 9.15

- G-50, 0-50 gram gauge in 5 gram steps. 12 R 22116 Shpg. wt., 5 oz. Net 9.15



LAFAYETTE HIGH SENSITIVITY METER RELAY

- Meter Movement
- Closes Circuit at 2 Mils

Extremely sensitive meter type relay. Normally open. Ideal suited for uses with model railroad, photoelectric relay circuit, baby-tenders, remote control toys, remote control boats, fire alarm, and many other practical applications. Precision-built meter movement provides virtually friction-free movement. Contact will close at 2 milliamperes. Internal resistance 100 ohms. Meter movement rated 5 ma continuous, 10 ma momentary; contacts rated 500 ma continuous, momentary 1 amp at 3v and 250 ma at 6v with resistive load. Sensitivity: 2.5-6 mw. Internally adjustable. Relay is enclosed entirely and transparent cover permits observation. Solder pins are placed externally for easy connections. SPST. Size: 1 3/4 x 1 3/4 x 1 3/4". Imported. Shpg. wt., 5 oz.

99 R 61996

Net 4.39

LITTLE "JEWEL"



REMOTE CONTROL RELAY 229

A natural for remote control receivers, it is highly sensitive, and built to withstand severe crashes. The smallest commercial job available, it weighs less than 1/2 oz. Factory adjusted to pull in at 1.4 MA drop out at 1.2 MA D.C. Single pole, double throw. Used in many R/C receivers. 5,000 ohm coil. Imported.

99 R 60915

Net 2.29

ALCO ISOLATION CONTROL RELAYS



As Low As
385

- No More Hot AC Line Dangers in Your Equipment Switches and Controls!

Permits any on-off power switch or control circuit to be isolated from the dangerous AC line voltage and to be operated safely. Excellent for remote operation of vacuum cleaners, TV sets, electric lawn mowers, floor scrubbers, heating systems, burglar alarms, slide projectors, attic fans, stereo hi-fi, machine control, etc. Handle up to 600 Watts of power and may be operated from remote switches up to several hundred feet away. With 6 inch leads and two 8/32 thread mounting holes. Size: Model FR-105 = 1.770" L x 1.319" W x 1.385" H; Model FR-102 = 2.130" L x 1.733" W x 1.531" H; Model FR-103 = 2.800" L x 2.000" W x 1.440" H. Shpg. wt., 8 oz.

Stock No. Model Contacts Circuit Resist. Net
30 R 12036 FR-105 SPST 50 ohms 3.85
30 R 12010 FR-102 SPDT 300 ohms 4.45
30 R 12028 FR-103 SPDT 400 ohms 4.95
† = AC Outlet Plug-In type. Has side jack for plug-in of remote switch or sensor.

DOW KEY 60 SERIES COAXIAL RELAYS



Heavy-duty SPDT coaxial relays rated 1 KW. Impedance, 50 ohms. Life, over 1,000,000 operations. VSWR, less than 1.15:1 from 0 to 500 MHz. Features patented automatic receiver-protecting connector for positive isolation of RF from receiver. Greater than 100 db isolation between receiver and transmitter lines from 0 to 500 MHz. With UHF coaxial connectors and 2 Form C Aux. Contacts. Size: 3.00" x 0.88" x 0.88". Shpg. wt., 12 oz.

Stock No. Type Coil Volts Net Ea.
40 R 52015 60-262842 115VAC 21.78

5-CHANNEL RESONANT REED



HOBBY RELAY

- For R/C Hobby and CB Tone Receivers
- For High Stability Oscillator Control

Frequency tolerance $\pm 1\%$. Features low tuning error, good temperature stability, low driving requirements. SPECIFICATIONS: (at 25°C): Frequency stability: $\pm 0.025\%$ per degree C over the range of -40 to $+85^\circ\text{C}$; Coil resistance: 600 Ohms DC $\pm 10\%$; Threshold Sensitivity: 1.0 V rms to 2.0 V rms at resonant frequency; Operating level: 6.0 vrms. Design frequencies: (Hz) $\pm 1.0\%$: REEDS: A=266.0, B=280.8, C=313.0, D=349.0, E=389.0 Hz. Constant rating 100 ma peak at 48 vdc (resistance load, contacts (-) in relation to reeds). Weight 2.5 oz. Mounts with 2-6/32" tapped holes on back. Size: 1 3/4 x 1 3/4 x 1 1/4". Shpg. wt., 9 oz.

42 R 61012

Net 10.95

MULTI-COUNTER 5-POSITION TALLY REGISTER



Five plunger operated tally registers in a single highly polished chromium plated case. Ideal for (1) laboratory use (2) time & motion studies (3) production control. Each 3-digit register counts up to 999. Easy-to-read numerals. Large knurled reset knob on side returns all 5 positions to zero simultaneously. Overall size: 5 3/4 x 1 1/2 x 1 1/4" D. Imported. Shpg. wt., 1 lb.

99 R 90318

Net 12.95

Now — from Columbia — at great savings...

Any 7 tapes or any 7 records FOR ONLY \$3.98

plus processing and postage

if you join now and agree to buy as few as 7 selections during the coming year



202523



195727




203372




205377



203539 *




201145



196c44



202960



191825



202705



202135



203471 *



199992



198911 *



202176 *



201806



191309



204321 *




199828



201905



201830 *



204347/204354

Counts as 2 selections



204230/204248

Counts as 2 selections

Take your pick



8-TRACK CARTRIDGES




OR

TAPE CASSETTES



OR

7" REEL-TO-REEL TAPES



OR

12" STEREO RECORDS

More selections and complete details on the other side...

Send no money
Just mail this post-paid card

FIRST CLASS
Permit No. 1050
Terre Haute, Ind.

BUSINESS REPLY MAIL
No Postage Stamp Necessary if Mailed in the United States

Postage will be paid by
COLUMBIA HOUSE
Terre Haute, Indiana
47808



Columbia House

ANY 7 tapes or records

FOR ONLY **\$3.98** plus processing and postage

if you join now and agree to buy just 7 selections during the coming year



Just look at this great selection of recorded entertainment—available in your choice of 8-Track Cartridges OR Tape Cassettes OR Reel-to-Reel Tapes OR 12" Stereo Records!

To receive your 7 tapes or records for \$3.98, just fill in and mail the postpaid card provided. Indicate which type of recorded music you prefer . . . cartridges, cassettes, reel tapes or records . . . and your seven selections will be sent upon enrollment.

As a member you will receive, every four weeks, an informative music magazine—describing the regular selection for the month, and scores of alternate selections from every field of music.

If you do not want any selection in any month—merely return the special card by the date specified. If you want only the regular selection, do nothing—it will be shipped to you automatically. Or use the card to order any of the alternate selections offered. And from time to time, we will offer some special selections which you may reject by returning the dated form provided—or accept by simply doing nothing.

Your own charge account will be opened upon enrollment . . . and selections will be mailed and billed to you at our regular prices: cartridges and cassettes, \$6.98; reel-to-reel tapes, \$7.98; records, \$4.98 or \$5.98 . . . plus a processing and postage charge. (Occasional special selections may be somewhat higher.)

Fantastic bonus plan. Your only obligation is to buy seven selections (at regular Club prices) during the coming year. After doing so, you have no further obligation—and you may cancel membership at any time. If you decide to continue, you will be eligible for our generous bonus plan—which can save you at least 33% on all your future purchases!

Please accept my membership in the Club. I am interested in the following type of recorded entertainment:

- Be sure to check one box only**
- 8-Track Cartridges (AN-W) 941
 - Tape Cassettes (AO-X)
 - Reel-to-Reel Tapes (BX-Y)
 - 12" Stereo Records (7Z-Z)

Send me the seven selections indicated, and bill me only \$3.98, plus processing and postage. I agree to buy seven more selections (at regular Club prices) during the coming year, and may cancel membership any time thereafter. If I continue, I'll be eligible for your bonus plan.

All selections will be described in advance in the Club magazine, sent every four weeks. If I do not want any selection, I'll return the selection card by the date specified—or use it to order any selection I do want. If I want only the regular selection for my musical interest, I need do nothing—it will be sent automatically. And from time to time, I'll be offered special selections which I may accept or reject by using the dated form always provided.

MY MAIN MUSICAL INTEREST IS (check one box only)

- Easy Listening Young Sounds Country

- Mr.
 Mrs.
 Miss

(Please Print) First Name Initial Last Name

Address

City State Zip

Do you have a telephone? (check one) YES NO

APO, FPO addressees: write for special offer

B16/F71

SEND ME THESE 7 SELECTIONS FOR ONLY \$3.98

DOUBLE SELECTIONS

2-record sets or twin-pack tapes—yet each double selection counts as only one!



199133



196725



195685

* Selections marked with a star are not available in reel tapes

Amperite... Hart-Advance... Hillburn Relays

AMPERITE THERMOSTATIC DELAY RELAYS

Heater-actuated time-delay relays. Operate on AC, DC or pulsating current. Hermetically sealed in glass envelope with act base. SPST, normally open, closed by heater after delay (in sec.). Heater draws only 2 watts. Contacts rated 3 amp. at 115V AC or 1.0 amp. at 220V AC. Shpg. wt., 5 oz. Size 2 3/4" x 1 1/4" diameter.



Delay Sec.	Normally Open		Normally Closed	
	6.3V AC-DC	115V AC-DC	6.3V AC-DC	115V AC-DC
2	33 R 35015	33 R 35148	33 R 35254	33 R 35387
5	33 R 35023	33 R 35155	33 R 35262	33 R 35395
10	33 R 35031	33 R 35163	33 R 35270	33 R 35403
15	33 R 35049	33 R 35171	33 R 35288	33 R 35411
20	33 R 35056	33 R 35189	33 R 35296	33 R 35429
30	33 R 35064	33 R 35197	33 R 35304	33 R 35437
45	33 R 35072	33 R 35205	33 R 35312	33 R 35445
60	33 R 35080	33 R 35213	33 R 35320	33 R 35452
75	33 R 35098	33 R 35221	33 R 35338	33 R 35460
90	33 R 35109	33 R 35239	33 R 35346	33 R 35478
120	33 R 35114	33 R 35247	33 R 35353	33 R 35486
150	33 R 35122		33 R 35361	
180	33 R 35130		33 R 35379	

Any of above Net ea. 2.40

Miniature Relays. Same type delay relays as above, available in miniature size, with delays from 2 to 120 Sec. Contacts rated 2 Amps. at 115 VAC or 1 Amp. at 220 VAC. Has 9 pin miniature base. Size 2 1/2 x 7/8 dia. Shpg. wt., 4 oz.

Delay Sec.	Normally Open		Normally Closed	
	6.3V AC-DC	115V AC-DC	6.3V AC-DC	115V AC-DC
2	33 R 35494	33 R 35601	33 R 35718	33 R 35825
5	33 R 35502	33 R 35619	33 R 35726	33 R 35833
10	33 R 35510	33 R 35627	33 R 35734	33 R 35841
15	33 R 35528	33 R 35635	33 R 35742	33 R 35858
20	33 R 35536	33 R 35643	33 R 35750	33 R 35866
30	33 R 35544	33 R 35650	33 R 35757	33 R 35874
45	33 R 35551	33 R 35658	33 R 35765	33 R 35882
60	33 R 35569	33 R 35678	33 R 35783	33 R 35890
75	33 R 35577	33 R 35684	33 R 35791	33 R 35908
90	33 R 35585	33 R 35692	33 R 35809	33 R 35916
120	33 R 35593	33 R 35700	33 R 35817	33 R 35924

Any of above Net ea. 2.40

HILLBURN RELAYS

MG POWER RELAYS are most effective for power transfer or control of multiple circuits. Used for motor controls, lighting, automation, mobile, air-conditioning, elevators, etc. Completely insulated from mounting bracket and grounded by insulated washers and barrier strip which meets UL requirements for over air and over surface spacing. Insulation tested at 1250 VAC. Contacts: heavy duty, positive action 1/4" fine silver rated 15 amperes. Mounts by two #6-32NC-28 thread holes in 2" mounting centers. Size: 2 1/2 x 1 1/2 x 1 1/2". Shpg. wt., 8 oz.



Stock No.	Catalog No.	Volts	Nominal Power	Resistance (ohms)	Contacts	Net
30 R 20286	MG-1C-115A	115 VAC	5.3 VA	585	SPDT 4.31	
30 R 20294	MG-2C-115A	115 VAC	5.3 VA	585	DPDT 6.33	

PSJ SENSITIVE CIRCUIT RELAY

A highly sensitive compact relay adaptable for single and multiple circuit control where reliability and low operating powers are indicated. Terminal board and armature assembly molded with black general purpose phenolic for excellent insulating properties. Contacts: 5A-3/16" silver cadmium oxide-gold plated. Sensitivity: 100 MW per pole. Mounts by two 5-32NC-28HD holes on 1.437" centers. Size: 1 1/2 x 1 1/2 x 1 1/2". Shpg. wt., 8 oz.



Stock No.	Catalog No.	Resistance (ohms)	Nominal Power	Contacts	Net
30 R 20302	PSJ-1C-2500	2.5K	.1W	SPDT	4.13
30 R 20310	PSJ-2C-2500	2.5K	.2W	DPDT	4.69

HART-ADVANCE RELAYS

General Purpose Relays



Types GHUB-GHUM. Available as an open relay (GHUB) or with a dustite plastic enclosure (GHUM). Enclosed types with SPDT and DPDT contacts have 8 pin octal plug-in bases while the 3PDT types use 11 pin plug-in bases. Open relays supplied with axial type solder lugs. Size: GHUB—1 1/4" x 1 1/4" x 1 1/4"; GHUM—2 1/2" x 1 1/4" x 1 1/4". Last part of type No.—Volts and AC or DC, i.e., /24VA=24 volts AC. UL Recognized. Wt., 5 oz.



Stock No.	Type	Coil Ohms	Contacts Form	Amps	Net
30 R 20005	GHUB/1C/24VA	96	SPDT 10	3.23	
30 R 20013	GHUB/1C/12VD	120	SPDT 10	3.10	
30 R 20021	GHUB/2C/24VA	96	DPDT 10	3.95	
30 R 20039	GHUB/2C/115VA	2,200	DPDT 10	3.95	
30 R 20047	GHUB/2C/12VD	120	DPDT 10	3.54	
30 R 20054	GHUB/3C/6VD	30	3PDT 10	4.00	
30 R 20062	GHUB/3C/24VD	480	3PDT 10	4.00	
30 R 20070	GHUB/1C/115VA	2,200	SPDT 10	5.53	
30 R 20088	GHUB/2C/115VA	2,200	DPDT 10	8.14	
30 R 20096	GHUB/3C/115VA	2,200	3PDT 10	7.89	

TYPE 12

Multiple contacts. Used widely in industrial controls, communications equipment, and automatic vending machines. Coil dissipation, 3 watts maximum. Size: 1 3/8" W x 1 1/2". Mounting: 4 6-32 tapped holes on 3/4" x 7/8" centers. Standard Contacts: 3/16" silver. Rated 10 amperes resistive at 115 VAC. Shpg. wt., 8 oz.



Stock No.	Type	Coil Volts	Contacts Form	Amps	Length ("L")	Net
30 R 20104	12DC-12-2C-10	12VDC	DPDT	10	1 1/2"	3.95
30 R 20112	12AC-12-2C-10	12VAC	DPDT	10	1 1/2"	3.95
30 R 20120	12AC-24-2C-10	24VAC	DPDT	10	1 1/2"	3.95
30 R 20138	12AC-115-2C-10	115VAC	DPDT	10	1 1/2"	3.95
30 R 20146	12AC-115-3C-10	115VAC	3PDT	10	1 1/2"	4.90

TYPE MK

Type MK DC relays require less than 1/2 cubic inch mounting space. Beryllium copper armature hinges assure stable performance under vibration and shock. Mounting Data: Relay supplied w/ single 2-56 NC-2 machine screw. Size: 1" x 6L x 51/64H x 5/8" D. Shpg. wt., 6 oz. Last part of type no.—Volts, i.e., /6VD=6 Volts DC.



Stock No.	Type	Coil Ohms	Contacts Form	Amps	Net
30 R 20153	MK/1C/6VD	50	SPDT	1	5.85
30 R 20181	MK/1C/12VD	200	SPDT	1	5.85
30 R 20179	MK/2C/12VD	120	DPDT	1	7.50

POWER RELAYS

Type PC Compact and positive acting relays for either AC or DC. Contacts rated at 35 Amps resistive, 5 Amps inductive at 115 VAC or 26.5 VDC. Size: 2 1/2" L x 1 3/4" W x 1 1/2" H.

Last part of type no.—Volts and AC or DC, i.e., /24VA = 24 Volt AC; /6VD = 6 Volts DC. Shpg. wt., 8 oz.



Stock No.	Type	Coil Ohms	Contacts Form	Amps	Net
30 R 20187	PC/1C/24VA	16	SPDT	15	9.60
30 R 20195	PC/1C/115VA	450	SPDT	15	9.60
30 R 20205	PC/1C/6VD	16	SPDT	15	9.60
30 R 20211	PC/1C/12VD	63	SPDT	15	9.60
30 R 20229	PC/2C/115VA	450	DPDT	15	12.25
30 R 20237	PC/2C/6VD	16	DPDT	15	12.25
30 R 20245	PC/2C/12VD	63	DPDT	15	12.25
30 R 20252	PC/3C/12VD	63	3PDT	15	12.25

TIME DELAY

TYPE DT Used with relays for time delay of 5 to 60 seconds. Adjustable with a range of 8 to 20 cycles per minute.

Mounting Data: 2 holes .154 dia. for 6-32 NC-2 screws; 1 3/8" centers. Size: 1 1/2" L x 1 1/2" W x 1 3/16" H. Shpg. wt., 2 oz.

Stock	Type	Coil Volt	Contacts Form	Amps	Net
30 R 20260	DT/1A/115VA	115VAC	SPST-NO	2 3.60	
30 R 20278	DT/1B/115VA	115VAC	SPST-NC	2 3.60	



Depend on Lafayette For Complete Stocks, Lowest Prices, Fastest Service

Pilot Light Assemblies

E. F. JOHNSON PILOT LIGHTS

ONE-INCH ENCLOSED ASSEMBLIES

Attractive, enclosed, candelabra screw base types for 115 V. 56 Jamps. Chrome plated threaded jewel permits replacement of lamp from front panel. Mounts in 1" hole; may be used on panels up to 3/8" thick. Binding screw terminals. UL listed. Series 147-1209 have faceted jewel; 23/4" behind panel. Series 147-1600 have dome for wide angle visibility; 2 1/4" behind panel. With mounting nut and washer, less lamp. Shpg. wt., 4 oz.



1/2 INCH HORIZONTAL OPEN ASSEMBLIES

(C) For low voltage miniature bayonet (Series 147-403) and screw base (Series 147-400) lamps. 1/2" faceted lens. Easy lamp replacement. 1/4" mounting hole. Solder terminals. Less lamp. Shpg. wt., 2 oz.

Stock No.	Mfg. No.	Fig.	Jewel	Net Ea.
33 R 32467	1209-2	A	Red	2.40
33 R 32475	1209-3	A	Green	2.40
33 R 32483	1209-3	A	Amber	2.40
33 R 32491	1600-2	B	Red	2.45
33 R 32509	1600-3	B	Green	2.45
33 R 32517	1600-4	B	Amber	2.45

Stock No.	Mfg. No.	Socket Color	Net ea.
33 R 32525	147-403-2	bayonet Red	.80
33 R 32533	147-403-3	bayonet Green	.80
33 R 32541	147-403-4	bayonet Amber	.80
33 R 32558	147-400-2	screw Red	.80
33 R 32566	147-400-3	screw Green	.80
33 R 32574	147-400-4	screw Amber	.80

LINE-O-LITE PILOT LIGHTS

Rectangular pilot light, lamp is high intensity neon, and unit has internal resistor. White nylon housing, chrome plated bezel. Plastic lens size 1/4 x 1 1/2". Mounts in hole 1 1/2 x 1/2", with speed nut supplied. Operates on 95-125 VAC. Shpg. wt., 2 oz.



34 R 52190	Red Lens	
34 R 52208	Amber Lens	
34 R 52455	White Lens	Net ea. .74

1/2 INCH VERTICAL OPEN ASSEMBLIES

Space saving inexpensive pilot light for low, voltage incandescent bulbs with miniature screw or miniature bayonet bases. Faceted colored jewels. Solder terminals; 3/8" mounting hole. Less lamp. Shpg. wt., 3 oz.



Stock No.	Socket	Color	Net ea.
34 R 70069	min. screw	Red	.40
34 R 70077	min. screw	Green	.40
34 R 70085	min. screw	Yellow	.40
34 R 70093	min. bayonet	Red	.47
34 R 70101	min. bayonet	Green	.47
34 R 70119	min. bayonet	Yellow	.47

INDUSTRIAL DEVICES PILOT LIGHTS

PILOT LIGHT ASSEMBLIES WITH SLIDE BASE LAMPS



As
Low
As
1.19

Bright, highly visible pilot lights utilizing long-lived miniature slide base incandescent lamps rated 5,000 hours. Easy front panel lamp replacement.

K. Dome Lens
Dome screw-in lens has stainless steel bezel, nylon non-strip self-locking fastening nut and mounts in 1/4" hole. Square lens has snap-on lens, spring steel mounting speednut and mounts in 1/2" hole. UL listed. Available complete with lamps, in voltages and color lenses shown. Shpg. wt., 2 oz.

K. Dome Lens			
Volts	Red Lens	Amber Lens	Green Lens
6	34 R 52240	34 R 52257	34 R 52265
12	34 R 52273	34 R 52281	34 R 52299
24	34 R 52307	34 R 52315	34 R 52323
120	34 R 52216	34 R 52224	34 R 52232
Any of the above			Net ea. 1.49


L. Square Lens			
Volts	Red Lens	Amber Lens	Green Lens
6	34 R 52489	34 R 52497	34 R 52505
12	34 R 52513	34 R 52521	34 R 52539
120	34 R 52547	34 R 52554	34 R 52562
Any of the above			Net ea. 1.19

SLIDE BASE LAMPS



Stock No.	Lamp No.	Volts Watts	End Foot Candles	Net Each
34 R 51085	6 PSB	6 .8	800	.62 .53
34 R 51093	12 PSB	12 2.0	2400	.62 .53
34 R 51101	24 PSB	24 1.7	2200	.62 .53
34 R 51143	120 PSB	120 3.0	1600	.62 .53

OMNI-GLOW NEON PILOT LIGHTS



For use on instrument panels, etc. Will last in excess of 10-25,000 hours. Built in NE-2H neon glow lamp and current limiting resistor. Mounts in 1/2" hole with speed nut (supplied). Complete with 4 1/2" leads. Operates on 95-125 VAC. Available with rounded, cylindrical or square lens, with chrome bezel. Shpg. wt., 2 oz.

(A) ROUNDED LENS	34 R 52083 Red lens	34 R 52091 Amber lens
	34 R 52018 Clear lens	34 R 52026 White lens Net ea. .69
(B) CYLINDRICAL LENS	34 R 52109 Red lens	34 R 52125 White lens Net ea. .69
	34 R 52117 Amber lens	
(C) SQUARE LENS	34 R 52133 Red lens	34 R 52158 White lens Net ea. .69
	34 R 52141 Amber lens	
(D) BUTTON TYPE LENS (Mounts in 7/8" hole)	34 R 52422 Red lens	34 R 52448 White lens Net ea. .69
	34 R 52430 Amber lens	

GLO-DOT NEON PILOT LIGHTS

As
Low
As
67c

Especially made for tight spots. Mounts in 3/4" hole with speed nut supplied. High brilliance NE-2H lamp with built-in resistor assures long life. UL and CSA listed. Complete with two 4 1/2" leads. Operates on 95-125VAC. Shpg. wt., 2 oz.

(A) MEDIUM LENS	34 R 52034 Red lens	34 R 52042 Clear lens
	34 R 52059 Amber lens	34 R 52067 White lens Net ea. .67
(B) HIGH HAT LENS	34 R 52166 Red lens	34 R 52182 White lens Net ea. .69
	34 R 52174 Amber lens	

LAFAYETTE PILOT LIGHTS



LAFAYETTE SPECIAL NEON ASSEMBLY

For operation on 110 volts AC. Requires 100k resistor in series. When used with 200 v. use 250k resistor in series. AC starting voltage 60v. Servicing life, 5000 to 10,000 operating hours. Chrome finish. Imported. Shpg. wt., 2 oz.

Stock No.	Color	Net ea.	Lots of 10 ea.
99 R 62242	Yellow	.45	.35
99 R 62259	Amber	.45	.35
99 R 62267	Red	.45	.35

LAFAYETTE HOBBYIST PILOT LIGHT ASSEMBLIES

• Ideal for the Builder and Experimenter



For both miniature screw and miniature bayonet lamps. Bulb replaceable from front of panel. Transparent plastic dome for 180° visibility except * = opaque. Front mounting with nickel finish nut and lock-washer. Solder terminals. 5/8" mounting hole. Less lamp. Imported. Shpg. wt., 2 oz.

Screw Stock No.	Color	Bayonet Stock No.	Color	Net Lots of 10 Ea.
99 R 63323	Red	99 R 63398	Red	.45 .39
99 R 63331	Clear	99 R 63406	Clear	.45 .39
99 R 63349	Amber	99 R 63414	Amber	.45 .39
99 R 63356*	Green	99 R 63422*	Green	.45 .39

Miniature Pilot Lamps and Sockets

AC-DC PILOT LAMPS



Rated at 115-125V. 1500 hours average use. All are Candelabra Screw base except * are Double Contact Bayonet Candelabra and † is miniature bayonet. All clear except * is white. Average shpg. wt., 2 oz. each.

Stock No.	Type	Fig.	Watts	10 For
32 R 66840	3S6	L	3 .55	.45
32 R 66857	6S6	L	6 .74	.20
32 R 66885	6S6DC†	M	6 .40	.33
32 R 66873	7C7/C	N	7 .21	.17
32 R 66881	7C7/W*	N	7 .34	.31
32 R 66899	10C7/DC†	R	10 .40	.33
32 R 66787	T-4A4	Q	4 .75	.47
34 R 51077	120M‡	K	3 .82	.53

PILOT LIGHT SOCKETS



Cadmium plated brackets with tension brass lugs. Bayonet type with coil spring construction for positive contact. For miniature screw, bayonet, and candelabra base. Avg. shpg. wt., 2 oz.

MINIATURE SCREW TYPE

Stock No.	Fig.	Watts	10 For
32 R 28004	1		
32 R 28012	2	.35	2.80
32 R 28020	3		
32 R 28038	4		

MINIATURE BAYONET TYPE

Stock No.	Fig.	Watts	10 For
32 R 28046	1		
32 R 28053	2	.30	2.80
32 R 28081	3		
32 R 28079	4		

CANDELABRA TYPE, 115 VOLT

Stock No.	Fig.	Watts	10 For
32 R 28087	1		
32 R 28096	2	.40	2.60
32 R 28183	3		
32 R 28111	4		

SOCKETS FOR NEON, ARGON AND PILOT LAMPS



- (5) Clear Receptacle with Edison Socket. 13 R 81278 Shpg. wt., 4 oz. Net .28
- (5) Receptacle with miniature screw socket. 13 R 81284 Shpg. wt., 3 oz. Net .22
- (5) Receptacle with candelabra socket. 13 R 81292 Shpg. wt., 3 oz. Net .22
- (6) Recessed receptacle with double contact bayonet socket. Top mounting. 13 R 34010 Shpg. wt., 3 oz. Net .82
- (7) Double contact bayonet candelabra socket 13 R 34028 Shpg. wt., 3 oz. Net 1.62
- (7) Single contact bayonet candelabra socket 13 R 34036 Shpg. wt., 3 oz. Net 1.49

PILOT LAMPS—FLASHLIGHT BULBS



For radio and T.V. pilot lights, panels, flashlights, toys, appliances, coin machines, autos, etc. Base code: 1-single contact flanged, 2-miniature screw, 3-double contact index, 5-single contact midjet, 6-single contact bayonet, 7-double contact bayonet, 8-midget screw, 9-miniature bayonet, 10-two pin. Under AMPS, CP means candlepower. †—25,000 hour sub-miniature lamp. Shpg. wt., box 10 in 4 oz., 1 lamp, 2 oz.

Stock No.	Type	Voigt	Amp.Fig.	Base	Net Ea.	10 For	Stock No.	Type	Voigt	Amp.Fig.	Base	Net Ea.	10 For	
32 R 66012	PR-2	2.4	0.50	A	1	.24	32 R 66156	257	14	0.27	G	9	.42	2.52
32 R 66020	PR-3	3.6	0.50	A	1	.24	32 R 66384	313	28	0.17	C	9	.42	2.53
32 R 66036	PR-4	2.3	0.27	A	1	.25	32 R 66392	327	28	0.04	P	5	.83	4.99
32 R 66046	PR-6	2.5	0.30	A	1	.24	32 R 66400	328	6	0.20	P	5	.66	3.94
32 R 66053	PR-12	5.95	0.50	A	1	.25	32 R 66913	330	14	0.08	P	5	1.11	6.68
32 R 66061	PR-13	4.75	0.50	A	1	.24	32 R 66954	387†	4	0.04	P	5	.94	5.62
32 R 66079	12	6.3	0.15	O	10	.33	32 R 66863	407	28	0.30	H	2	.28	1.66
32 R 66087	13	3.7	0.30	H	2	.21	32 R 66418	425	5	0.50	H	2	.27	1.60
32 R 66095	14	2.5	0.30	H	2	.21	32 R 66426	428	12.5	0.25	H	2	.32	1.91
32 R 66103	27	4.9	0.30	H	2	.25	32 R 66434	432	18	0.25	H	2	.37	2.73
32 R 66111	31	6.2	0.30	H	2	.31	32 R 66442	433	18	0.25	G	9	.39	2.31
32 R 66129	40	6.8	0.15	B	2	.17	32 R 66459	502	5.1	0.15	H	2	.22	1.11
32 R 66137	41	2.5	0.50	B	2	.33	32 R 66467	605	6.1	0.50	H	2	.31	1.81
32 R 66145	42	3.2	0.35	B	2	.43	32 R 69032	755	6.3	0.15	C	9	4.1	2.46
32 R 66152	43	2.5	0.50	C	9	.30	32 R 69040	756	14	0.08	C	9	.55	3.27
32 R 66160	44	6.8	0.25	C	9	.17	32 R 69057	757	28	0.08	C	9	.60	3.60
32 R 66178	45	3.2	0.35	C	9	.20	32 R 69172	1034	12.8	1.8	F	3	.54	3.25
32 R 66186	46	6.8	0.25	B	2	.17	32 R 66475	1125	6.8	21C.P.	F	6	4.0	2.41
32 R 66194	47	6.8	0.15	C	9	.17	32 R 66489	1133	6-8	32C.P.	F	6	7.0	4.19
32 R 66202	48	2.0	0.06	B	2	.33	32 R 66715	1156	12	32C.P.	F	6	.57	3.40
32 R 66210	49	2.0	0.06	C	9	.28	32 R 69180	1157	12.8	2.1	F	3	.54	3.25
32 R 66228	50	6.8	1C.P.	H	2	.20	32 R 66491	1446	12	0.20	H	2	.38	2.30
32 R 66236	51	6.8	1C.P.	G	9	.18	32 R 66509	1447	18	0.15	H	2	.26	1.57
32 R 66244	53	14.4	0.12	G	9	.20	32 R 66517	1449	14	0.20	H	2	.21	1.27
32 R 66259	55	6.8	2C.P.	G	9	.20	32 R 66533	1477	24	0.17	B	2	.84	5.06
32 R 66269	57	12-16	2C.P.	G	9	.20	32 R 66549	1487	12-16	0.20	B	2	.33	1.97
32 R 66277	63	6-8	3C.P.	G	6	.23	32 R 66558	1488	14	0.15	C	9	.35	2.11
32 R 66184	67	13.5	0.59	G	6	.28	32 R 66566	1490	3.2	0.16	C	9	.27	1.63
32 R 66285	81	6-8	6C.P.	G	6	.30	32 R 66574	1493	6.5	2.75	F	7	1.59	9.56
32 R 66293	82	6-8	6C.P.	G	7	.30	32 R 66889	1700	6	5.5	J	6	1.43	8.57
32 R 66846	93	12	15C.P.	F	6	.40	32 R 66582	1763	6	0.20	B	8	1.18	7.87
32 R 66301	112	1.2	0.22	D	2	.21	32 R 66590	1815	12-16	0.20	C	9	.30	1.79
32 R 66319	123	1.25	0.30	H	2	.32	32 R 66595	1819	28	0.04	C	9	.43	2.59
32 R 66327	136	1.3	0.60	H	2	.29	32 R 66608	1823	28	0.10	C	9	.48	2.87
32 R 66335	222	2.2	0.25	D	2	.21	32 R 69065	1825	37.5	0.05	C	9	.87	5.24
32 R 66340	223	2.2	0.25	E	4	.33	32 R 66618	1829	28	0.07	C	9	.46	2.74
32 R 66358	224	2.15	0.22	E	4	.28	32 R 66624	1847	6.3	0.15	C	9	.23	1.40
32 R 66368	233	2.2	0.27	H	2	.30	32 R 66632	1898	12	0.24	C	9	.21	1.26
32 R 66107	239	6.3	0.36	C	9	.39	32 R 69099	1893	14	0.33	C	9	.24	1.43
32 R 66378	248	2.5	0.80	H	2	.44	32 R 69198	1895	14	0.27	G	9	.28	1.71

METER ILLUMINATING PILOT LAMP

For Illuminating Meters Internally Used in Lafayette "S" and Modulation panel meters. Operates on 6 volts AC or DC. Can operate on 12 volts with 2 lamps in series. Shpg. wt., 2 oz. Net .34



Channel Selector Dial Indicator Lamp. Used in Lafayette Citizens Band and communications equipment. Operates on 6 volts AC or DC. Can operate on 12 volts with series voltage dropping resistor, imported. Shpg. wt., 2 oz. Net .29

NEON GLOW LAMPS

For 105-125 VAC operation. Screw types have resistor in base for 105-125 v others require external resistor. AC starting voltage shown. DC starting voltage 40% higher. Shpg. wt., 2 oz.



Stock No.	Type	Watts	Start Volt	Base Type	Each	10-Up Each	
32 R 66731	ABA	NE-2E	1/10	65	Wire Term	.20	1.19
32 R 66830	C2A	NE-2, NE-2H	1/4	95	Wire Term	.20	1.19
32 R 66739	B7A	NE-45	1/4	65	Cand. Screw	1.53	9.17
32 R 66808	B9A	NE-48	1/4	65	S.C. Bay.	1.25	7.47
32 R 66814	B1A	NE-51	1/25	65	S.C. Bay, Min	.44	2.65
32 R 66822	B2A	NE-51H	1/4	95	S.C. Bay, Min	.44	2.85
32 R 66871	5AC	NE-68	—	60	Wire Term.	.80	3.58
32 R 66887	5AH	NE-83	—	60	Wire Term.	.43	2.55

General Electric and RCA Picture Tubes


ONE-YEAR GUARANTEE

Tubes failing in normal use within 1 year will be replaced. You pay only transportation. Black & white tubes are made of entirely new materials except the glass which may be re-used after test inspection and refurbishing to meet new glass standards. Color tubes may contain used materials which, prior to re-use have been carefully inspected and tested.

YOUR OLD TUBE IS WORTH MONEY
If you return your old picture tube (Dud) when you purchase a new one, we will credit you for its value as shown in the column headed "Dud Value." Duds must be brought or shipped prepaid to us and must be intact, under vacuum and without scratches. Do not bring in tubes for which no value is shown.



RCA



AVERAGE SHIPPING WEIGHTS FOR PICTURE TUBES

Tube Prefix	Shpg Wt	Tube Prefix	Shpg Wt	Tube Prefix	Shpg Wt
8	5 lbs.	13	8 lbs.	20	20 lbs.
9	5 lbs.	14	9 lbs.	21	30 lbs.
10	7 lbs.	16	11 lbs.	23	40 lbs.
12	8 lbs.	17	13 lbs.	24	42 lbs.
		19	15 lbs.	27	45 lbs.

The prefix of the picture tube is determined by the first two digits in the Type No.

NOTE: WE WILL FILL YOUR ORDER WITH EITHER A G.E. OR AN RCA TUBE DEPENDING UPON STOCK AVAILABILITY.

STOCK NO.	TUBE TYPE	NET EA.	DUD VALUE	Stock No.	TUBE TYPE	Net Each	Dud Value	Stock No.	TUBE TYPE	Net Each	Dud Value
36 R 80055WX	8DP4	32.65	—	36 R 82192WX	17EMP4	38.00	—	36 R 82234WX	21FMP4	38.80	—
36 R 80063WX	8XP4	36.90	—	36 R 82325WX	17WP4	38.00	—	36 R 81566WX	21VP4	44.05	—
36 R 80071WX	8YP4	48.75	1.00	36 R 80477WX	17HP4C	23.35	—	36 R 81962WX	21GP4	46.65	1.75
36 R 82374WX	9AEP4	24.15	—	36 R 80485WX	17LP4B	24.15	—	36 R 80899WX	21VP4B	29.55	—
36 R 82382WX	9AGP4	27.75	1.75	36 R 80493WX	17QP4B	24.15	—	36 R 82556WX	21XP4B	29.95	—
36 R 40174WX	9VP4	28.10	1.75	36 R 80519WX	18VAUP4	39.05	—	36 R 80915WX	21YP4B	24.50	—
36 R 81640WX	9WP4	26.95	—	36 R 80527WX	19AFP4	35.50	4.00	36 R 80923WX	21ZP4	24.50	—
36 R 82283WX	10ARP4	25.35	1.75	36 R 80543WX	19AJP4	34.30	4.00	36 R 80949WX	22VABP4	44.65	—
36 R 82390WX	10ATP4	28.40	—	36 R 80568WX	19AVP4	34.30	4.00	36 R 81574WX	23ARP4	45.65	6.50
36 R 82606WX	10AVP4	26.95	—	36 R 80576WX	19AYP4	34.30	4.00	36 R 81582WX	23BGP4	46.25	6.50
36 R 81665WX	11GP4	29.30	—	36 R 80584WX	19BDP4	34.30	4.00	36 R 80972WX	23BJP4	41.70	6.50
36 R 82291WX	11HP4	29.30	—	36 R 81509WX	19CHP4	34.30	4.00	36 R 80988WX	23BKP4	46.15	6.50
36 R 81673WX	11UP4	21.30	—	36 R 81517WX	19CMP4	34.30	4.75	36 R 81020WX	23BP4	46.25	6.50
36 R 81681WX	12BEP4	25.95	—	36 R 81780WX	19QVP4	39.60	4.00	36 R 81038WX	23BTP4	39.15	6.50
36 R 82408WX	12BGP4	25.95	—	36 R 81525WX	19CXP4	34.30	4.00	36 R 81053WX	23CP4A	46.25	6.50
36 R 82135WX	12BKP4	25.60	—	36 R 82473WX	19CZP4	38.30	4.00	36 R 81590WX	23CQP4	41.30	6.75
36 R 81442WX	12BNP4A	23.35	—	36 R 82481WX	19DAP4	38.30	4.00	36 R 81061WX	23DQP4	41.70	6.75
36 R 81699WX	12BP4	26.50	—	36 R 81798WX	19DBP4	39.50	4.00	36 R 81079WX	23DAP4	48.55	6.75
36 R 81624WX	12CP4	26.50	—	36 R 81806WX	19DKP4	38.30	4.00	36 R 81087WX	23DBP4	45.85	4.00
36 R 81707WX	12DP4	28.40	—	36 R 40059WX	19DQP4	36.65	1.00	36 R 81098WX	23DKP4	44.95	4.00
36 R 82143WX	12CWP4	26.50	—	36 R 81541WX	19DRP4	36.65	1.00	36 R 82564WX	23DLP4	44.95	4.00
36 R 82317WX	12DFP4	32.15	—	36 R 81558WX	19DSP4	36.65	1.00	36 R 81970WX	23DNP4	46.65	6.50
36 R 82416WX	12DGP4	22.40	—	36 R 81350WX	19DUP4	36.65	1.00	36 R 82572WX	23DSP4	51.60	4.00
36 R 82424WX	12DSP4	28.40	—	36 R 81368WX	19DVP4	38.50	4.00	36 R 82259WX	23DWP4	51.60	4.00
36 R 82614WX	12VAGP4	30.00	—	36 R 81384WX	19ECP4	38.30	4.00	36 R 81152WX	23EP4	46.25	6.75
36 R 81715WX	13AP4	31.95	—	36 R 81822WX	19ECP4	37.95	1.00	36 R 81988WX	23ECP4	46.65	6.50
36 R 82622WX	15VACP4	34.05	—	36 R 82200WX	19EKP4	38.10	4.00	36 R 81995WX	23EDP4	46.65	6.50
36 R 80212WX	16ATP4	29.00	—	36 R 81871WX	19GAP4	37.95	1.00	36 R 40216WX	23EKP4	46.30	4.00
36 R 82150WX	16AUP4	32.70	—	36 R 82333WX	19GEP4A	34.30	—	36 R 40083WX	23ENP4	46.30	4.00
36 R 82440WX	16AYP4	32.70	—	36 R 82515WX	19GJP4	36.30	4.00	36 R 81608WX	23EQP4	41.50	—
36 R 81723WX	16BCP4	37.50	—	36 R 82523WX	19VAHP4	39.25	—	36 R 81676WX	23ETP4	49.15	6.75
36 R 81475WX	16BGP4	31.90	—	36 R 82531WX	19VAJP4	39.25	—	36 R 82267WX	23EYP4	48.80	4.00
36 R 82168WX	16BUP4	22.60	—	36 R 82341WX	20AHP4	39.95	—	36 R 82580WX	23EZP4	43.80	—
36 R 81731WX	16BXP4	35.40	—	36 R 82549WX	20RPA	37.40	—	36 R 81178WX	23FPA4	41.70	6.50
36 R 82457WX	16CNP4	31.95	—	36 R 82218WX	20SP4	36.30	—	36 R 82028WX	23FNP4	41.70	4.00
36 R 81749WX	16CHP4A	36.05	—	36 R 82226WX	20TP4	38.30	—	36 F 82036WX	23RPA	50.40	6.50
36 R 81832WX	16CQP4	29.30	—	36 R 82655WX	20VAP4	45.40	—	36 R 82044WX	23RSP4	50.40	6.50
36 R 82176WX	16CWP4	30.60	—	36 R 81897WX	21AMP4B	25.70	—	36 R 82598WX	23CWP4	48.15	6.50
36 R 81764WX	16RP4B	20.70	—	36 R 80717WX	21AUP4C	26.35	—	36 R 40224WX	23HP4	49.15	6.50
36 R 81772WX	16TP4	28.25	—	36 R 81905WX	21CBP4C	21.85	—	36 R 82101WX	23HWP4	50.40	6.50
36 R 80295WX	17BP4D	22.55	—	36 R 80741WX	21CQP4	30.15	—	36 R 81186WX	23JP4	46.25	6.50
36 R 80287WX	17BJP4	26.95	—	36 R 80782WX	21DLP4	28.75	—	36 R 81202WX	23NP4	41.70	6.50
36 R 80303WX	17BWP4	22.55	—	36 R 81921WX	21DSP4	30.50	—	36 R 81236WX	24AEP4	32.95	—
36 R 82465WX	17CFP4	24.60	—	36 R 80790WX	21EP4C	31.65	—	36 R 81244WX	24AHP4	46.50	4.00
36 R 82630WX	17DKP4	26.55	—	36 R 82359WX	21EMP4/EQP4	31.65	—	36 R 81277WX	24AUP4	39.25	—
36 R 80410WX	17DQP4	26.55	—	36 R 80873WX	21FP4D	21.85	—	36 R 81301WX	24CP4B	32.95	—
36 R 80428WX	17DRP4	30.10	—	36 R 80840WX	21FDP4	38.92	—	36 R 81343WX	27XP4	96.85	16.50
36 R 80436WX	17DSP4	28.45	—					36 R 82127WX	27ZP4	101.85	16.50

CROSS-REFERENCE FOR TUBE TYPES NOT SHOWN ABOVE

Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With
9UP4	9VP4	16BW4	16BG4	17JP4	17BP4D	19DCP4	19DRP4	19FWP4	19AYP4	21CWP4	21CBP4A
11AP4	11HP4A	16CAP4	16CBP4	17RP4	17HP4C	19DFP4	19CHP4	19GCP4	19CZP4	21CX4	21DS4
11BP4	11HP4A	16CEP4	16CMP4A	17VP4	17LP4B	19DHP4	19DSP4	19GFP4	19GEP4	21CZP4	21EMP4
12BLP4	12BK4	16CFP4	16CQP4	19ACP4	19CHP4	19DLP4	19CWP4	19GJP4	19DQP4	21DAP4	21EMP4
12BMP4	12CDP4	16CJP4	16CMP4A	19ADP4	19AVP4	19DNP4	19DKP4	19GNP4	19DRP4	21DEP4	21EMP4
12BQP4	12BK4	16CUP4	16ATP4	19AMP4	19AYP4	19DWP4	19DQP4	19GRP4	19DQP4	21DFP4	21EMP4
12BUP4	12BK4	16CVP4	16ATP4	19AKP4	19AVP4	19DYP4	19CVP4	19GTP4	19DUP4	21DMP4	21EMP4
12CQP4	12BK4	16KP4	16RP4B	19ANP4	19AYP4	19DZP4	19DVP4	19KPA	19AVP4	21DRP4	21CBP4A
12DHP4	12BK4	17ATP4	17BJP4	19ARP4	19AFP4	19EDP4	19DRP4	19ZP4	19AVP4	21DQP4	21DL4
12CFP4	12CNP4	17AVP4	17BJP4	19AUP4	19AFP4	19EP4	19SP4	20KP4	20TP4	21EDP4	21EMP4
12GCP4	12BHP4A	17BP4	17DSP4	19AP4	19AYP4	19EP4	19DRP4	21ACP4	21AMP4B	21EQP4	21EMP4
16ASP4	16ATP4	17BP4	17BJP4	19AZP4	19AVP4	19EP4	19DUP4	21AVP4	21AUP4C	21ESP4	21EMP4
16AVP4	16BCP4	17BP4	17BWP4	19BHP4	19AVP4	19ELP4	19AVP4	21AYP4	21XP4B	21ETP4	21EMP4
16AYP4	16BGP4	17BZP4	17DSP4	19BP4	19AVP4	19ERP4	19DRP4	21BAP4	21CBP4A	21FAP4	21EMP4
16BDP4	16AUP4	17CAP4	17DSP4	19BWP4	19AYP4	19ESP4	19DSP4	21BDP4	21AUP4C	21FLP4	21CBP4
16BFP4	16AYP4	17CBP4	17BJP4	19CDP4	19CXP4	19EUP4	19DVP4	21BNP4	21CBP4C	21FWP4	21VP4
16BG4	16ATP4	17CKP4	17DSP4	19CJP4	19AVP4	19EVP4	19DQP4	21BSP4	21AMP4B	21FZP4	21VP4
16BK4	16CHP4A	17CSP4	17BWP4	19CLP4	19BDP4	19EWP4	19DQP4	21BTP4	21CBP4A	21GAP4	21CBP4
16BMP4	16AYP4	17CWP4	17DSP4	19CQP4	19CXP4	19FBP4	19EGP4	21CEP4	21EMP4	23ACP4	23BT4
16BQP4	16CMP4A	17CZP4	17BJP4	19CRP4	19BDP4	19FCP4	19DQP4	21CMP4	21CBP4A	23AFP4	23BT4
16BS4	16ATP4	17DLP4	17DSP4	19CSP4	19CHP4	19FDP4	19DQP4	21CUP4	21AMP4B	23ALP4	23CQP4
16BV4	16ATP4	17FP4	17HP4C	19CUP4	19CMP4	19FJP4	19DQP4	21CVP4	21CBP4A	23ANP4	23BK4

PICTURE TUBE CROSS-REFERENCE (Cont'd.)

Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With	Orig. Type	Replace With
23ASP4	23AHP4	23CEP4	23ARP4	23FCP4	23GJPA4	23HP4	23CP4A	23YP4	23CP4A	23YP4	23BTP4
23ATP4	23BKP4	23GZP4	23AHP4	23FDP4	23GJPA4	23HL4	23GSP4	23ZP4	23GSP4	23ZP4	23BTP4
23AUP4	23AHP4	23DNP4	23BKP4	23EP4	23ENP4	23HRP4	23HWP4	24ADP4	23HRP4	24ADP4	24CP4B
23BDP4	23BTP4	23DTP4	23DKP4	23FHP4	23GJPA4	23JHP4	23JHP4	24ALP4	23JHP4	24ALP4	24AHP4
23BHP4	23BGP4	23DXP4	23CP4A	23FLP4	23EK4	23JCP4	23FRP4	24ANP4	23JCP4	23FRP4	24EP4
23BLP4	23BKP4	23ZTP4	23EP4	23FMP4	23HF4	23JHP4	23HF4	24OP4	23JHP4	23HF4	24EP4
23BMP4	23BTP4	23FF4	23GWP4	23VP4	23HP4	23LP4	23TP4	24TP4	23LP4	23TP4	24CP4B
23BNP4	23CP4A	23EM4	23EK4	23GP4	23CP4A	23MP4	23FA4	24VP4	23MP4	23FA4	24CP4B
23BVP4	23BTP4	23ELP4	23EK4	23GBP4	23HF4	23QP4	23CP4	24YP4	23QP4	23CP4	24EP4
23BWP4	23BTP4	23MP4	23EK4	23GEP4	23ENP4	23TP4	23BTP4	24ZP4	23TP4	23BTP4	24EP4
23BXP4	23EDP4	23SP4	23HF4	23GTP4	23ET4	23UP4	23BQP4	27SP4	23UP4	23BQP4	27XP4
23BZP4	23GCP4	23WP4	23QP4	23GUP4	23FRP4	23WP4	23FA4	27VP4	23WP4	23FA4	27XP4
23CBP4	23BQP4	23FBP4	23EMP4	23GXP4	23GSP4	23XP4	23BTP4				

COLOR PICTURE TUBES

Stock No.	Tube Type	Net Ea.	Dud Value	Stock No.	Tube Type	Net Ea.	Dud Value	Stock No.	Tube Type	Net Ea.	Dud Value
36 R 40356WX	11SP22	71.00	4.00	36 R 40471WX	19GWP22/EYP22	95.85	4.00	36 R 40299WX	21GFP22	123.35	9.00
36 R 40455WX	11WP22	95.40	4.00	36 R 40604WX	19MCP22/19HKP22	95.40	4.00	36 R 40414WX	22JP22	104.00	9.00
36 R 40547WX	15ACP22	79.35	—					36 R 40422WX	23GEP22	115.95	4.00
36 R 40554WX	15AEP22	82.05	—	36 R 40630WX	19HNP22	95.40	4.00	36 R 40638WX	25BEP22	119.30	16.50
36 R 40562WX	15MP22	82.00	—	36 R 40612WX	19HXK22	84.55	4.00	36 R 40513WX	25CP22	113.15	16.50
36 R 40570WX	15YP22	79.35	—	36 R 40620WX	19JWP22	93.40	4.00	36 R 40331WX	25UP22	128.35	1.00
36 R 40588WX	17EXP22	102.65	9.00	36 R 40117WX	21CYP22A	60.00	—	36 R 40521WX	25AP22/25AP22A	93.30	16.50
36 R 40596WX	17EZP22	89.65	4.00	36 R 40398WX	21FBP22	73.85	4.00	36 R 40539WX	25YP22/25BP22A	93.30	16.50
36 R 40463WX	19GVP22/EXP22	80.40	4.00	36 R 40406WX	21FJP22	60.00	4.00				

COLOR TUBE CROSS-REFERENCE

Original Type	Replace With	Original Type	Replace With	Original Type	Replace With
19YPP22	Use 19GWP22/EYP22	21GUP22	Use 21FBP22	25AP22A	Use 25XP22/AP22A
19FMP22	Use 19GWP22/EYP22	21GVP22	Use 21FJP22	25BP22A	Use 25YP22/BP22A
19FXP22	Use 19GWP22/EYP22	22ABP22	Use 22JP22	25CP22	Use 25YP22/BP22
19GLP22	Use 19GWP22/EYP22	22LP22	Use 22IP22	25GP22	Use 25XP22/AP22A
19GXP22	Use 19GWP22/EXP22	22QP22	Use 22JP22	25RP22	Use 25YP22/BP22A
19GYP22	Use 19GWP22/EXP22	22SP22	Use 22JP22	25SP22	Use 25XP22/AP22A
19GZP22	Use 19GWP22/EYP22	22YP22	Use 22JP22	25TP22	Use 25XP22/AP22A
19HBP22	Use 19GWP22/EYP22	25AFP22	Use 25XP22/AP22A	25UP22	Use 25XP22/AP22A
19FKP22	Use 21FJP22			25ZP22	Use 25XP22/AP22A

RCA-GE-RAYTHEON


The tubes shown in this listing will be supplied from brand new factory boxed stock manufactured by RCA, GE or Raytheon. Type shown with * is Victoreen Mfg. Quantity users please contact our

SPECIAL PURPOSE TUBES

Industrial Division for quotation on quantities of five or more of any type required. Many types other than shown here are available.

RCA-GE-RAYTHEON

Stock No.	Tube Type	Net Ea.	Stock No.	Tube Type	Net Ea.	Stock No.	Tube Type	Net Ea.	Stock No.	Tube Type	Net Ea.
36 R 41008	OA2	1.45	36 R 41727	6A5E	3.90	36 R 42675	5642	3.55	36 R 43773	6417	3.53
36 R 41024	OA3	1.75	36 R 41735	6A57GA	5.25	36 R 42683	5651A	1.95	36 R 43806	6550	6.00
36 R 41032	OA4G	2.30	36 R 41743	6A6WB	3.22	36 R 42709	5653	6.05	36 R 43863	6669/6AQUA	1.76
36 R 41040	OB2	1.60	36 R 41768	6D18/ECC68	1.90	36 R 42808	5686	4.00	36 R 43871	6677/6CL6	2.46
36 R 41065	OB3	2.35	36 R 41834	12A6	3.75	36 R 42857	5696	2.36	36 R 43887	6679/12AT7	1.83
36 R 41073	OC2	1.75	36 R 41842	12AT7WB	3.03	36 R 42931	5726/GAL5W	2.20	36 R 43905	6680/12AU7A	1.61
36 R 41081	OC3	1.66	36 R 41933	83	2.31	36 R 42956	5727	3.05	36 R 43813	6681/12AX7A	1.44
36 R 41099	OD3	1.65	36 R 41990	807	5.50	36 R 43012	5751	3.00	36 R 43947	6683	4.95
36 R 41123	1B85*	19.75	36 R 42006	811A	9.25	36 R 43046	5763	2.70	36 R 43954	6922/E88CC	4.90
36 R 41131	1C21	4.85				36 R 43061	5814A	2.80	36 R 43988	7054	1.70
36 R 41172	1L4	1.67	36 R 42014	812A	7.60	36 R 43095	5823	1.85	36 R 44001	7056	1.02
36 R 41240	1P40	7.15	36 R 42048	816	4.75	36 R 43194	5881	3.10	36 R 44010	7059	1.68
36 R 41362	2D21	1.50	36 R 42121	866A	4.45	36 R 43269	5915	1.99	36 R 44028	7060	2.10
36 R 41396	2E26	4.65	36 R 42139	868	7.75	36 R 43277	5963	1.50	36 R 44036	7061	1.56
36 R 41438	2X2A	4.90	36 R 42154	884	2.90	36 R 43293	5965	2.25	36 R 44093	7360	3.77
36 R 41446	3A4	2.16	36 R 42212	922	4.90	36 R 43327	6012	8.21	36 R 44011	7551	3.67
36 R 41453	3A5	2.31	36 R 42253	927	9.10	36 R 43426	6080	5.50	36 R 44127	7558	3.68
36 R 41487	3B28	9.55	36 R 42261	929	5.35	36 R 43442	6082	5.84	36 R 44150	7587	5.50
36 R 41560	3KP1	35.70	36 R 42279	930	6.55						
36 R 41570	3RP1	21.00	36 R 42303	934	8.60	36 R 43509	6136	3.25	36 R 44200	7905	4.05
36 R 41644	5B1PA	47.20	36 R 42329	955	7.05	36 R 43517	6146A	4.45	36 R 44218	7984	5.35
36 R 41669	5R4GYB	2.40	36 R 42428	1614	5.84	36 R 43525	6146B/8298A	9.45	36 R 44317	8077/7054	1.54
36 R 41677	5UP1	22.40	36 R 42493	1625	6.60	36 R 43580	6201	3.30	8298A	Use 6146B/8298A	
36 R 41693	6AG7Y	3.11	36 R 42501	1629	2.86	36 R 43632	6211A	2.70	36 R 44374	9005	8.05
36 R 41701	6AK6	1.40	36 R 42527	2050A	2.30	36 R 43699	6366A	4.95	36 R 44382	9006	2.70
						36 R 43707	6386	9.50			



(A) TUBE PIN STRAIGHTENER

A 6" plastic ruler combination tube pin straightener. Accommodates Noval, Nuvsitor, and Compactron large 7 pin, 9 pin and 10 pin tubes.

13 R 61229 Net .59

(B) TUBE AND PARTS EXTRACTOR

This handy tube extractor is skillfully constructed of spring steel, nickel plated. Has rubber cushion on the prongs.

13 R 61211 Net .98


SERVICEMAN'S TUBE CADDY

12⁹⁵

- All Wood Reinforced Construction
- Easy To Carry

Light, compact caddy capable of holding up to 143 tubes. One fold-out compartment has snap fastened cover, other has built-in separator. Extremely convenient caddy for carrying tools, new, vinyl covering. Size 15 3/4 x 12 1/2 x 8". Shpg. wt., 7 1/4 lbs.

12 R 18015W Net 12.95



RCA TUBE RECEIVING MANUAL


RC-28. The brand new edition of RCA's enormously popular RCA receiving tube manual. A big 672 pages long, the manual includes: complete technical data on all current tubes. Features tube theory written for the layman, application information and a useful circuits section. Tuner, receiver, amplifier, intercom and other circuit diagrams, socket diagrams, tube dimension drawings, resistance-coupled amplifier data. Shpg. wt., 1 3/4 lbs.

10 R 47019 Net 2.00



LAFAYETTE Receiving Tubes

with the 2-YEAR GUARANTEE



Lafayette tubes are made to rigid quality standards which assure you of efficient performance and long life. We will replace without charge any tube which due to defects in material or workmanship, fails in

normal use within 2 years from date of purchase. Simply bring or return the tube postpaid to the store from which you purchased it along with your original sales slip or order. Some types imported.

ASSORTMENT PRIVILEGE: TUBES MAY BE ASSORTED FOR QUANTITY PRICE

STOCK NO.	TUBE TYPE	NET EA.		25 1-5 6-24 & UP	STOCK NO.	TUBE TYPE	NET EA.		25 1-5 6-24 & UP	STOCK NO.	TUBE TYPE	NET EA.		25 1-5 6-24 & UP	
		1-5	6-24				1-5	6-24				1-5	6-24		
36 R 30001	074	2.15	1.94	1.72	36 R 30852	6CB6A/6CF6	1.80	1.62	1.44	36 R 31587	6K28	2.25	2.03	1.80	
36 R 32460	1B2C	1.63	1.47	1.30	36 R 30853	6CG7 USE 6F07/6CG7				36 R 31595	6L6CC	3.33	3.00	2.66	
36 R 30019	1B3/1G3GT	2.10	1.89	1.68	36 R 30854	6C6U USE 6B06GTB/6C6U				36 R 32684	6LE8	3.33	3.00	2.66	
36 R 30027	1K3/1J3	2.10	1.89	1.68	36 R 30886	6CC8A	2.40	2.16	1.92	36 R 32692	6LM8	2.68	2.41	2.14	
36 R 30035	1R5	2.95	2.66	2.36	36 R 32395	6CJ3/6DW4B/6CL3				36 R 32700	6L06/6JEGC	4.40	3.96	3.52	
36 R 30043	1U4	2.30	2.07	1.84			2.05	1.85	1.64	36 R 32718	6L6U	2.85	2.57	2.28	
36 R 30050	1U5	2.25	2.03	1.80	36 R 30894	6CL6	2.60	2.34	2.08	36 R 32726	6M0D	2.90	2.61	2.32	
36 R 30068	1V2	1.28	1.15	1.02	36 R 30902	6CL8A	2.45	2.21	1.96	36 R 32734	6ME8	3.10	2.79	2.48	
36 R 30076	1X2B	2.05	1.85	1.64	36 R 30910	6CM7	2.28	2.05	1.82	36 R 31629	6SA4	1.85	1.67	1.48	
36 R 30084	2AF4B	2.45	2.21	1.96	36 R 30936	6CQ8	2.53	2.28	2.02	36 R 31652	6SL7GT	2.70	2.43	2.16	
36 R 32305	2A52	1.95	1.76	1.56	36 R 30944	6CS6	2.05	1.85	1.64	36 R 31650	6SN7GTB	2.20	1.98	1.74	
36 R 30082	2AV2	1.73	1.56	1.38	36 R 30951	6CS7	2.23	2.01	1.78	36 R 31678	6T8	2.68	2.41	2.16	
36 R 30118	2C V5	2.43	2.19	1.94	36 R 30969	6CUS	2.20	1.98	1.76	36 R 31702	6T10	2.95	2.66	2.36	
36 R 32312	2K5/2FQ5A	2.10	1.89	1.68	36 R 30985	6CW4/6DS4	2.95	2.66	2.36	36 R 31694	6UBA/6K08	1.95	1.76	1.56	
36 R 30126	3A3B/3AW3	2.13	1.92	1.70	36 R 32544	6CWS/EL86	1.38	1.24	1.10	36 R 32742	6U10	2.23	2.01	1.78	
36 R 30134	3AT2	2.13	1.92	1.70	36 R 30993	6CX8	2.80	2.52	2.24	36 R 31710	6V6GTA	2.45	2.21	1.96	
36 R 30159	3BN6	2.75	2.48	2.20	36 R 31009	6CY5	2.68	2.41	2.14	36 R 31728	6W4GTA	1.65	1.49	1.32	
36 R 30167	3B26	2.05	1.85	1.64	36 R 31025	6CZ5	2.60	2.34	2.08	36 R 31744	6X4	1.88	1.69	1.50	
36 R 30175	3CB6/3CF6	1.48	1.33	1.18	36 R 31041	6DE4	2.08	1.87	1.66	36 R 31751	6XS5GT	1.98	1.78	1.58	
36 R 30183	3C V5	1.95	1.76	1.56	36 R 31058	6DE6	1.88	1.69	1.50	36 R 31789	6X8A	2.23	2.01	1.78	
36 R 32320	3D76A	1.85	1.67	1.48	36 R 31066	6DE7	2.78	2.50	2.22	36 R 31789	6Z10/6J10	3.33	3.00	2.66	
36 R 30209	3GK5	2.10	1.89	1.68	36 R 31074	6DM6	1.78	1.60	1.42	36 R 31777	7AU7	1.55	1.40	1.24	
36 R 32338	3HQ5	3.13	2.82	2.50	36 R 31086	6DD5	4.20	3.78	3.36	36 R31705	8AW8A	2.93	2.64	2.34	
36 R 30217	3K4	2.23	2.01	1.78	36 R 31089	6DQB/6GW6	2.93	2.64	2.34	36 R 32767	8B10	2.43	2.19	1.94	
36 R 30233	3B26	2.05	1.85	1.64	36 R 31108	6DR7	2.13	1.92	1.70	36 R 31793	8T8/8CG7	1.63	1.50	1.36	
36 R 32346	4CB6	1.55	1.40	1.24			6DS4 USE 6CW4/6DS4			36 R 32437	8L5	2.33	2.10	1.86	
36 R 32353	4DT6A	2.15	1.94	1.72	36 R 31116	6DT6A	1.78	1.60	1.42	36 R 31801	10DE7	2.70	2.43	2.16	
36 R 32361	4E7J/LF184	2.13	1.92	1.70			6DW4B USE 6CJ3/6DW4B/6CL3			36 R 32783	10K6	2.25	2.03	1.80	
36 R 30258	5A05	2.05	1.85	1.64	36 R 31132	6DZ4/6FA4A	2.45	2.21	1.96	36 R 32445	10GN8	2.75	2.48	2.20	
36 R 32478	5AR4/GZ34	2.13	1.92	1.70			6EA7 USE 6EM7/6EA7			36 R 31819	12AD6/12GA6	2.03	1.83	1.62	
36 R 30282	5C6L8	2.28	2.05	1.82	36 R 31157	6E8	2.15	1.94	1.72	36 R 31827	12AT6	1.63	1.47	1.30	
36 R 30290	5CL8A	2.98	2.68	2.38	36 R 31165	6E8B	2.83	2.55	2.26	36 R 31835	12AT7/ECC81	1.78	1.60	1.42	
36 R 32379	5K8	3.53	3.18	2.82	36 R 31173	6E7/EF183	1.93	1.74	1.54	36 R 31843	12AU6	1.93	1.74	1.54	
36 R 32494	5LJ8	2.63	2.37	2.10	36 R 31181	6E7/EF184	1.78	1.60	1.42	36 R 31850	12AU7A/ECC82				
36 R 30316	5U4GB	1.73	1.56	1.38			6EL4A USE 6BK4C/6EL4A					1.55	1.40	1.24	
36 R 30324	5U8	2.78	2.50	2.22	36 R 31199	6EM5	2.45	2.21	1.96	36 R 31876	12AV6	1.35	1.22	1.08	
36 R 30332	5Y3GT	1.70	1.53	1.36	36 R 31207	6EM7/6EA7	3.05	2.75	2.44	36 R 31884	12AV7	2.68	2.41	2.14	
36 R 30340	6B4	2.00	1.80	1.60	36 R 31215	6E7	2.20	1.98	1.76	36 R 31892	12AX4GTB	1.85	1.67	1.48	
36 R 30357	6AF3/6BR3	2.03	1.83	1.62	36 R 31223	6E V5	2.13	1.92	1.70	36 R 31900	12AX7A/ECC83				
	6AF4A USE 6D24/6AF4A				36 R 31231	6E W6	1.93	1.74	1.54			1.53	1.38	1.22	
36 R 30381	6AH4GT	1.63	1.47	1.30	36 R 31249	6F7	2.53	2.28	2.02	36 R 31918	12AZ7A	2.23	2.01	1.78	
36 R 30399	6AH6	2.90	2.61	2.32	36 R 31264	6FM7	2.78	2.50	2.22	36 R 31926	12B4A	2.30	2.07	1.84	
36 R 30407	6AK5/EF95	2.38	2.14	1.90			6FQ5A USE 6GK5/6FQ5A			36 R 31934	12BA6	1.55	1.40	1.24	
36 R 30415	6AL5	1.48	1.33	1.18	36 R 31280	6FQ7/6CG7	1.63	1.47	1.30	36 R 31942	12BE6	1.70	1.53	1.36	
36 R 30423	6AM8A	2.53	2.28	2.02			6FV8A USE 6BR8A/6FV8A			36 R 31959	12BH7A	2.15	1.94	1.72	
36 R 30431	6AN8A	2.75	2.48	2.20	36 R 31298	6GE5	3.15	2.84	2.52	36 R 31975	12BY7A/12BV7				
36 R 30449	6AQ5A/6HG5	1.85	1.67	1.48	36 R 31306	6GF7A	2.83	2.55	2.26			2.08	1.87	1.66	
36 R 30456	6AS5	2.23	2.01	1.78	36 R 31314	6GH8A	1.68	1.51	1.34	36 R 31983	12C5/12CU5	2.38	2.14	1.90	
36 R 30498	6AU4GTA	2.60	2.34	2.08	36 R 32569	6GJ7/ECF801	3.08	2.77	2.46	36 R 32007	12DQ6B	2.68	2.41	2.14	
36 R 30506	6AU8A	1.63	1.47	1.30	36 R 31322	6GK5/6FQ5A	2.53	2.28	2.02			12GA6 USE 12AD6/12GA6			
36 R 30514	6AU8A	3.15	2.84	2.52	36 R 31330	6GM6	2.13	1.92	1.70	36 R 32015	12GN7A	2.95	2.66	2.36	
36 R 30530	6AV6	1.48	1.33	1.18	36 R 32577	6GN8	2.83	2.55	2.26	36 R 32809	12HL7	2.68	2.41	2.14	
36 R 30548	6AW8A	2.45	2.21	1.96	36 R 31348	6GU7	2.23	2.01	1.78	36 R 32817	13DR7	2.95	2.57	2.28	
36 R 30563	6AX4GTB	2.10	1.89	1.68	36 R 32585	6GV5	2.45	2.21	1.96	36 R 32825	13EM7/15EA7	3.23	2.91	2.58	
36 R 30571	6AY3B/6BS3A	2.10	1.89	1.68			6GW6 USE 6DQ6B/6GW6					15EA7 USE 13EM7/15EA7			
36 R 32387	6B10	2.65	2.39	2.12	36 R 31355	6GW8/ECL86	1.53	1.38	1.22	36 R 32452	15KY8A	3.48	3.13	2.78	
36 R 30589	6BA6/EF93	1.88	1.69	1.50	36 R 32593	6GX7	2.95	2.66	2.36	36 R 32072	17AX4GTA	1.85	1.67	1.48	
36 R 30597	6BA8A	2.60	2.34	2.08	36 R 31363	6GY6/6CX6	1.75	1.58	1.40	36 R 32833	17BE3	2.10	1.89	1.68	
36 R 30605	6BA11	2.80	2.52	2.24	36 R 32429	6HA5/6HM5	1.93	1.74	1.54	36 R 32098	17D4A	2.23	2.01	1.78	
36 R 30621	6BC8/6BZ8	2.68	2.41	2.14	36 R 31371	6HB7	2.38	2.14	1.90	36 R 32106	17DQ6B/17GW6				
36 R 30639	6BE6	1.90	1.71	1.52	36 R 31389	6HE5	2.78	2.50	2.22			3.03	2.73	2.42	
36 R 30647	6BGG6A	3.58	3.22	2.86	36 R 31397	6HF8	2.95	2.66	2.36	36 R 32858	17JM6A	3.33	3.03	2.66	
36 R 30654	6BH6	2.23	2.01	1.78			6HG5 USE 6AQ5A/6HG5			36 R 32868	17JN6	2.95	2.66	2.36	
36 R 30659	6B9B	2.83	2.52	2.24			6HM5 USE 6HA5/6HM5			36 R 32114	17L7	2.13	1.92	1.70	
36 R 30670	6B16	2.23	2.01	1.78	36 R 32601	6H55	4.30	3.87	3.44	36 R 32122	19AU4GTA	2.78	2.50	2.22	
36 R 30688	6BK4C/6EL4A	3.93	3.54	3.14	36 R 31413	6H58	2.60	2.34	2.08	36 R 32130	21CY5	2.78	2.50	2.22	
36 R 30696	6BK7B	2.60	2.34	2.08	36 R 31421	6HZ6	1.83	1.65	1.46	36 R 32148	22DE4	2.38	2.14	1.90	
36 R 30712	6BL8/ECF80	1.35	1.22	1.08	36 R 31447	6J6A	2.45	2.21	1.96	36 R 32155	22J6A	3.38	3.04	2.70	
36 R 30720	6BM8/ELC82	1.45	1.31	1.16	36 R 31454	6J86	3.60	3.24	2.88	36 R 32163	23Z9				
36 R 30738	6BN4A	2.00	1.80	1.60	36 R 31462	6JCG6A	2.38	2.14	1.90			2.75	2.48	2.20	
36 R 30746	6BN6/6KS6	2.70	2.43	2.16	36 R 32619	6JD6	2.30	2.07	1.84			2.20	1.98	1.76	
36 R 30753	6BN8	2.15	1.94	1.72			6JEGC USE 6LQ6/6JEGC			36 R 32189	25CD6GB	3.20	2.88	2.56	
36 R 30761	6B05/EL84	2.13	1.92	1.70	36 R 31488	6JH6	3.15	2.84	2.52	36 R 32205	25L6GT	2.60	2.34	2.08	
36 R 30779	6B06GTB/6C6U				36 R 31504	6JMG6A	2.93	2.64	2.34	36 R 32213	33GY7A	3.48	3.13	2.78	
		3.03	2.73	2.42	36 R 31512	6JN6	3.93	3.54	3.14	36 R 32221	35C5	1.93	1.74	1.54	
36 R 30787	6B07A/6BZ7	2.68	2.41	2.14	36 R 31520	6J56C	2.38	2.14	1.90	36 R 32239	35L6GT	2.45	2.21	1.96	
36 R 30795	6BR3 USE 6AF3/6BR3				36 R 31548	6JH8A	2.23	2.01	1.78	36 R 32247	35W4	1.13	1.02	.80	

RCA — GE — Raytheon Receiving Tubes

12 MONTH GUARANTEE

All receiving tubes are guaranteed for 12 months from date of purchase. We will replace any tube that does not give efficient performance for a full 12 month's period. This of course does not apply to burned out or broken tubes.

BRANDS: RCA—GE—RAYTHEON. We will supply one of these famous national brands depending on our stock availability. Some types imported.

ASSORTMENT PRIVILEGE: TUBES MAY BE ASSORTED FOR QUANTITY PRICE



Stock No.	Tube Type	25 & Up		
		1-5	6-24	Up
36 R 10003	OZ4/OZ4A	2.32	2.15	1.94
36 R 10029	1A3	3.59	3.33	3.00
36 R 10037	1A5GT	2.16	2.00	1.80
36 R 10045	1A7GT	2.92	2.70	2.43
36 R 10052	1A2D/A			
	1B2A	2.30	2.13	1.92
36 R 10060	1A2YA	2.19	2.03	1.83
	1B3GT USE 1G3GT/1F3GT			
36 R 10078	1B2C	2.13	1.98	1.78
36 R 19749	1B2C	1.81	1.40	1.26
	1B2X USE 1X2C/1B2X			
36 R 10086	1B2H	2.11	1.95	1.76
	1B2YA USE 1A2D/1B2YA			
36 R 21000	1D3G	2.43	2.25	2.03
36 R 20515	1D1K	1.73	1.60	1.44
36 R 20523	1D1K27	2.19	2.03	1.83
36 R 20531	1D1K29	1.51	1.40	1.26
36 R 10094	1D1N5	2.38	2.20	1.98
36 R 10102	1G3GT/1B3GT			
	1B3GT	2.27	2.10	1.89
36 R 10110	1H2	2.13	1.98	1.78
36 R 10136	1K3/J19	2.27	2.19	1.89
36 R 10151	1L6	6.78	6.28	5.65
36 R 10169	1H4	4.10	3.80	3.42
36 R 10177	1N2A	2.38	2.20	1.98
36 R 10185	1N5GT	2.65	2.45	2.21
36 R 10193	1R5	3.19	2.95	2.66
	1R2K3 USE 1S2A/DY87			
36 R 10201	1S2A/DY87	1.38	1.28	1.15
36 R 10219	1S4	2.21	2.05	1.85
36 R 10227	1S5	1.84	1.70	1.53
36 R 10235	1T4	2.40	2.23	2.01
36 R 10243	1U4	2.48	2.30	2.07
36 R 10250	1U5	2.43	2.25	2.01
36 R 10268	1R5	1.38	1.28	1.15
36 R 10276	1X2C/1B2X	2.21	2.05	1.85
36 R 10284	2A3	5.81	5.38	4.83
36 R 10292	2AF4B/2D24	2.65	2.45	2.21
	2AH2 USE 2BU2			
	2AS2 USE 2BU2/2AS2A			
36 R 10326	2AV2	1.86	1.73	1.56
36 R 10334	2B2J	2.48	2.30	2.07
36 R 10359	2BN4A	2.32	2.15	1.94
36 R 20069	2BU2/2AS2/2AH2			
	2CN3A/B	2.57	2.38	2.14
36 R 10367	2C6	2.43	2.25	2.01
36 R 10375	2C5	2.89	2.68	2.41
36 R 10383	2D54	3.16	2.93	2.64
36 R 10391	2D4V	4.00	3.70	3.33
	2D24 USE 2AF4B/2D24			
36 R 10409	2EG4	3.67	3.40	3.06
36 R 10417	2EN5	1.73	1.60	1.44
36 R 10425	2ER5	2.00	1.85	1.67
36 R 10433	2FH5	2.00	1.85	1.67
	2FQ5A USE 2GK5/2FQ5A			
36 R 10441	2F5S	2.86	2.65	2.39
36 R 10458	2G4S/2FQ5A	2.27	2.10	1.89
36 R 10466	2H4	2.43	2.25	2.03
36 R 10474	2HA5	2.08	1.93	1.74
36 R 10482	2HK5	2.08	1.93	1.74
36 R 10490	2HQ5	2.08	1.93	1.74
36 R 10508	3A2	3.00	2.75	2.48
36 R 10516	3AC3/3AW3/3B2	2.30	2.13	1.92
36 R 10524	3AF4B/3D24	2.57	2.38	2.14
36 R 10532	3AL5	1.73	1.60	1.44
36 R 10540	3AT2B	2.30	2.13	1.92
36 R 10557	3AU6	1.84	1.70	1.53
36 R 10565	3AV6	1.59	1.48	1.33
36 R 10573	3AW2A	2.40	2.23	2.01
	3AW3 USE 3A3C/3AW3			
	3B2 USE 3A3C/3AW3			
36 R 10581	3BA6	1.27	1.18	1.06
36 R 10599	3BC5/3CE5	1.84	1.70	1.53
36 R 10607	3BE6	1.46	1.35	1.22
36 R 10615	3BL2A	2.43	2.25	2.03
36 R 20077	3BM2	2.40	2.23	2.01
36 R 10623	3BN2	2.16	2.00	1.80
36 R 10631	3BN4A	1.84	1.70	1.53
36 R 10649	3BN6	3.00	2.75	2.48
	3BS2A USE 3BW2/3BS2A			
	3BT2 USE 3BW2/3BS2A			
36 R 10664	3BU8/3GS8	2.81	2.60	2.34
36 R 20085	3BW2/3BS2A/3BT2	2.65	2.45	2.21

Stock No.	Tube Type	25 & Up		
		1-5	6-24	Up
36 R 10672	3BY6	1.62	1.50	1.35
36 R 10680	3BZ6	2.21	2.05	1.85
36 R 10698	3CA3	2.35	2.18	1.96
36 R 10706	3CB6/3CF6	1.59	1.48	1.33
	3CE5 USE 3BC5/3CE5			
	3CF6 USE 3CB6/3CF6			
36 R 10714	3CN3B	2.48	2.30	2.07
36 R 10722	3CS3A	2.54	2.35	2.12
36 R 19988	3CU3A	3.13	2.90	2.61
	3CX3 USE 3DA3/3CX3			
	3CY3 USE 3DB3/3CY3			
36 R 10730	3CY5	2.35	2.18	1.96
36 R 20408	3CZ3	2.81	2.60	2.34
36 R 20416	3DA3/3CX3	2.27	2.10	1.89
36 R 20101	3DB3/3CY3	2.57	2.38	2.14
36 R 20424	3DC3	3.16	2.93	2.64
36 R 20549	3DF3	2.51	2.33	2.10
36 R 10748	3DG4	3.43	3.18	2.86
36 R 21372	3DH3	2.30	2.13	1.92
36 R 50025	3DHH13	3.86	3.58	3.22
36 R 21018	3DJ3	2.48	2.30	2.07
36 R 10755	3DG6	1.52	1.48	1.32
36 R 10763	3DT6A	2.90	1.85	1.67
	3DZ4 USE 3AF4B/3DZ4			
36 R 10789	3EH7/XF182	1.38	1.28	1.15
36 R 10797	3EJ7/XF184	1.38	1.28	1.15
36 R 10805	3ER5	2.81	2.60	2.34
36 R 10813	3FH5	1.76	1.63	1.47
36 R 10821	3FS5	2.57	2.38	2.14
36 R 10839	3GK5	2.27	2.10	1.89
	3GS8 USE 3BU8/3GS8			
36 R 10847	3HM5/3HA5	2.08	1.93	1.74
36 R 10854	3HQ5	3.38	3.13	2.82
36 R 21026	3H6	2.32	2.15	1.94
36 R 10862	3JG6A	2.19	2.05	1.86
36 R 10870	3KT6	2.24	2.08	1.87
36 R 50033	3MP26	2.32	2.15	1.94
36 R 10896	3Q4	1.81	1.68	1.51
36 R 10904	3Q5GT	3.16	2.93	2.64
36 R 10912	3S4	1.84	1.70	1.53
36 R 10920	3V4	2.40	2.23	2.01
36 R 10938	4AU6	2.08	1.93	1.74
36 R 10946	4AV6	1.59	1.48	1.33
	4BC5 USE 4CE5/4BC5			
36 R 10953	4BC8	2.65	2.45	2.21
36 R 10961	4BL8/XCF80	1.30	1.20	1.08
36 R 10979	4BN6	2.19	2.03	1.83
36 R 10987	4B7A/4B7	2.65	2.45	2.21
36 R 10995	4B8A	2.30	2.13	1.92
36 R 11001	4BU8/4GS8	2.62	2.43	2.19
36 R 11019	4BZ6	2.21	2.05	1.85
	4BZ7 USE 4BQ7A/4BZ7			
36 R 11027	4CB6	1.67	1.55	1.40
36 R 11035	4CE5/4BC5	1.53	1.38	1.22
36 R 11043	4CS6	2.08	1.93	1.74
36 R 11050	4CY5	1.35	1.22	1.08
36 R 11068	4D6	1.59	1.48	1.33
36 R 11076	4D6K	2.16	2.00	1.80
36 R 11084	4DT6A	2.32	2.15	1.94
36 R 11092	4FW7/LF183	2.30	2.13	1.92
36 R 11100	4E7/LF184	2.30	2.13	1.92
36 R 11118	4ES8	3.00	2.78	2.50
36 R 11126	4EW6	2.65	2.45	2.21
36 R 21380	4GJ7	2.08	1.93	1.74
36 R 11134	4GK5	2.11	1.95	1.76
36 R 11142	4GM6	1.19	1.10	.99
	4GS8 USE 4BU8/4GS8			
36 R 11159	4GX7	3.19	2.95	2.66
36 R 11175	4HA5/PC90	1.27	1.18	1.06
36 R 11183	4HA7/4HC7	2.30	2.13	1.92
	4HC7 USE 4HA7/4HC7			
36 R 11191	4HM6	2.16	2.00	1.80
36 R 11209	4HQ5	2.81	2.60	2.34
36 R 11217	4HS8	2.70	2.50	2.25
36 R 11233	4JC6A	3.00	2.75	2.48
36 R 11241	4JD6	2.72	2.53	2.28
36 R 11258	4JH6	2.16	2.00	1.80
36 R 11266	4KE8	3.81	3.53	3.18
36 R 20556	4KN8/4RHH8	4.06	3.70	3.33
36 R 20432	4KT6	2.81	2.60	2.34
36 R 11274	4LJ8	3.16	2.93	2.64
36 R 21034	4LU6	1.84	1.70	1.53
	4RH2 USE 4BG7A			
	4RHH USE 4KN8/4RHH8			
36 R 50041	4MP12	2.32	2.15	1.94
36 R 50058	4MP26	2.32	2.15	1.94

Stock No.	Tube Type	25 & Up		
		1-5	6-24	Up
36 R 11282	5AM8	3.05	2.83	2.55
36 R 11290	5AN8	3.13	2.90	2.61
36 R 11308	5AQ5	2.21	2.05	1.85
36 R 11316	5AR4/GZ34	2.30	2.13	1.92
	5AS4A USE 5U4GB/5AS4A			
36 R 11324	5AT8	2.48	2.20	1.98
36 R 11332	5AT8	2.59	2.40	2.16
	5AU4 USE 5V3A/5AU4			
36 R 11357	5AV8	2.19	2.03	1.83
36 R 11365	5AZ4	2.86	2.65	2.39
36 R 11373	5B8	3.00	2.75	2.48
36 R 11381	5BC3A	2.16	2.00	1.80
36 R 11399	5BE8	1.67	1.55	1.40
36 R 11407	5BK7A	2.24	2.08	1.87
	5BQ7A USE 5BZ7/5BQ7A			
36 R 11423	5BR8/5FV8	3.05	2.83	2.55
36 R 11431	5BT8	1.67	1.55	1.40
36 R 11449	5BW8	2.43	2.25	2.03
36 R 20119	5BZ7/5BQ7A	2.72	2.53	2.26
36 R 11456	5CG8	3.21	2.98	2.68
36 R 11464	5CL8A	1.78	1.60	1.42
36 R 11472	5CM8	2.21	2.05	1.85
36 R 11480	5CQ8	2.20	2.05	1.85
36 R 11498	5CZ5	2.40	2.23	2.01
36 R 11506	5D0H8	3.00	2.75	2.48
	5DK8 USE 6UBA/6AX8			
36 R 11514	5DJ4	1.92	1.78	1.60
36 R 11522	5EA8	3.05	2.83	2.55
36 R 11530	5E8A/YCC189	3.00	2.75	2.48
36 R 11548	5EU8	2.83	2.63	2.37
36 R 11555	5EW6	2.16	2.00	1.80
36 R 11563	5FG7	2.72	2.50	2.07
	5FV8 USE 5BR8/5FV8			
36 R 11589	5GH8A	2.72	2.53	2.23
36 R 11597	5GJ7	1.59	1.48	1.33
36 R 11605	5GM6	2.00	1.85	1.67
36 R 20564	5GS7	1.97	1.83	1.65
	5GX6 USE 5H26			
36 R 11621	5GX7	3.19	2.95	2.66
36 R 11639	5HA7	2.30	2.13	1.92
36 R 11647	5HB7	1.84	1.70	1.53
36 R 11654	5HG8/LCF86	2.00	1.85	1.67
36 R 11662	5HZ6/5GX6	2.00	1.85	1.67
36 R 11670	5J6	2.00	1.85	1.67
36 R 11688	5JK6	2.27	2.10	1.89
36 R 11696	5JL6	2.27	2.10	1.89
	5KD8 USE 6UBA/6KD8			
36 R 11704	5KE8	3.81	3.53	3.18
36 R 11712	5KZ8	2.30	2.13	1.92
36 R 11720	5LJ8	2.83	2.63	2.37
36 R 20127	5M8B	1.97	1.83	1.65
	5MMH3 USE 5J6			
36 R 501				

RCA-GE-RAYTHEON RECEIVING TUBES (Cont.)

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 12058	6AK5/EF95	2.57	2.38	2.14
36 R 19764	6AK6	1.65	1.53	1.38
36 R 20135	6AK8/ EBC80	1.78	1.65	1.49
36 R 20440	6AK10	3.00	2.78	2.50
36 R 12066	GAL3/EY88	1.40	1.30	1.17
36 R 12074	6AL5	1.59	1.48	1.33
36 R 12082	6AL7GT	3.75	3.45	3.13
36 R 12090	6ALL1	3.59	3.33	3.00
36 R 12108	6AM4	3.89	3.60	3.24
36 R 12116	6AM8A	2.72	2.55	2.28
36 R 12124	6AN4	3.32	3.08	2.77
36 R 12132	6AN8A	3.00	2.75	2.48
36 R 12140	6AQ5A/6HG5	2.00	1.85	1.67
36 R 12157	6AQ6	2.08	1.93	1.74
36 R 12165	6AQ7GT	2.54	2.35	2.12
36 R 12173	6AQ8/ECC85	1.62	1.50	1.35
36 R 12181	6AR5	2.35	2.18	1.96
36 R 12199	6ARB	3.19	2.95	2.66
36 R 12207	6AR11	3.02	2.80	2.52
36 R 12215	6AS5	2.40	2.23	2.01
36 R 12223	6AS8	2.89	2.68	2.41
36 R 12231	6AS11	3.27	3.03	2.73
36 R 12249	6AT6	1.30	1.20	1.08
36 R 12256	6AT8A	3.05	2.83	2.55
36 R 12264	6AU4GT	2.81	2.60	2.34
36 R 12272	6AU5GT	3.13	2.90	2.61
36 R 12280	6AU6A	1.76	1.63	1.47
36 R 12298	6AU8A	3.40	3.15	2.84
36 R 12306	6AV5GA	3.51	3.25	2.93
36 R 12314	6AV6	1.59	1.48	1.33
36 R 12322	6AV11	2.87	2.48	2.23
36 R 12330	6AW8A	2.65	2.45	2.21
36 R 12348	6AX3	2.03	1.88	1.69
36 R 12355	6AX5GTB	2.27	2.10	1.89
36 R 12363	6AX5GT	2.35	2.18	1.96
36 R 12389	6AX8 USE GUBA/6AX8			
36 R 12397	6AY3B/ 6BS3A	2.27	2.10	1.89
36 R 12405	6AZ8	3.19	2.95	2.66
36 R 12413	6B8	3.70	3.43	3.09
36 R 12421	6B10	2.86	2.65	2.39
36 R 12439	6BA3	1.65	1.53	1.38
36 R 12447	6BA6/EF93	2.03	1.88	1.69
36 R 12454	6BA7	3.19	2.95	2.66
36 R 12462	6BABA	2.81	2.60	2.34
36 R 12470	6BA1A	3.02	2.80	2.52
36 R 12488	6BC4	3.19	2.95	2.66
36 R 12496	6BC5/6CE5	2.03	1.88	1.69
36 R 12504	6BC7	1.94	1.80	1.62
36 R 19772	6BC8/6BZ8	2.89	2.68	2.41
36 R 12520	6BD6	1.27	1.18	1.06
36 R 12538	6BD11	3.32	3.08	2.77
36 R 12546	6BE3/6BZ3	2.86	2.65	2.39
36 R 12553	6BF4	2.05	1.90	1.71
36 R 12561	6BF5	1.81	1.68	1.51
36 R 12579	6BF6	1.76	1.63	1.47
36 R 12587	6BF11	3.11	2.88	2.59
36 R 12595	6BG6GA	3.86	3.58	3.22
36 R 12603	6BH3A	1.51	1.40	1.26
36 R 12611	6BH6	2.40	2.23	2.01
36 R 12629	6BH8	3.16	2.93	2.64
36 R 12637	6BH11	3.05	2.83	2.55
36 R 12645	6BJ3	1.76	1.63	1.47
36 R 12652	6BR6A	2.40	2.23	2.01
36 R 12660	6B7	1.59	1.48	1.33
36 R 12678	6BJ8	2.57	2.38	2.14
36 R 12686	6BK4C/ 6EL4A	4.24	3.93	3.54
36 R 12694	6BK5	1.89	1.75	1.58
36 R 12702	6BK7B	2.81	2.60	2.34
36 R 12710	6BL7GT	3.27	3.03	2.73
36 R 12728	6BL8/ECF80	1.46	1.35	1.22
36 R 12736	6BM8/ECL82	1.57	1.45	1.31
36 R 12744	6BN4	2.16	2.00	1.80
36 R 12751	6BN6/6KS6	2.32	2.10	1.94
36 R 12769	6BN8	2.89	2.65	2.41
36 R 12777	6BN11	2.89	2.68	2.41
36 R 12785	6BQ5/EL84	2.30	2.13	1.92
36 R 12793	6BQ6GA/ 6CU6	3.27	3.03	2.73
36 R 12801	6BQ6GTB	3.27	3.03	2.73
36 R 12819	6BQ7A/ 6BZ7/6BS8	2.89	2.68	2.41
36 R 20580	6BR3/6RK19	2.46	2.28	2.05
36 R 12827	6BR4/ 6FV8A	2.81	2.60	2.34
36 R 12834	6BS3A USE 6BAY3B/6BS3A			
36 R 12842	6BS8 USE 6BQ7A/6BZ7			
36 R 12850	6BUB	3.00	2.78	2.50
36 R 12868	6BV8	2.13	1.98	1.78
36 R 19996	6BV11 6BW3 USE 6CG3/6CE3	3.24	2.92	2.70
36 R 12876	6BW4	1.49	1.38	1.24
36 R 12884	6BWS	2.81	2.60	2.34
36 R 12892	6BX11	2.37	2.15	1.94
36 R 12900	6BX7GT	3.59	3.33	3.00

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 12918	6BY5GA	2.59	2.40	2.16
36 R 12926	6BY6	2.38	2.20	1.98
36 R 12934	6BY8	1.48	1.35	1.22
36 R 21364	6BY11	2.70	2.50	2.25
36 R 12959	6BZ3 USE 6BE3/6BZ3			
36 R 12959	6BZ7 USE 6BQ7A/6BZ7			
36 R 12959	6BZ8 USE 6BC8/6BZ8			
36 R 12975	6C4	2.24	2.08	1.87
36 R 12983	6C5	3.19	2.95	2.66
36 R 12991	6C6	4.24	3.93	3.54
36 R 13007	6C9	2.97	2.75	2.48
36 R 13015	6C10	2.40	2.23	2.01
36 R 13023	6CA4	2.03	1.88	1.69
36 R 13031	6CA5	1.62	1.50	1.35
36 R 13049	6CA7/EL34	3.19	2.95	2.66
36 R 13056	6CBSA	5.35	4.95	4.46
36 R 13064	6CBB/6CF6	1.94	1.80	1.62
36 R 13072	6CD3 USE 6CG3			
36 R 13072	6CD6GA	4.10	3.80	3.42
36 R 13072	6CE3 USE 6CG3/6CE3			
36 R 13072	6CE5 USE 6BC5/6CE5			
36 R 13072	6CF6 USE 6CBA/6CF6			
36 R 13080	6CG3/6CE3/6CD3/ 6BW3	2.32	2.15	1.94
36 R 13080	6CG7 USE 6FQ7/6CG7			
36 R 13098	6CGBA	2.58	2.40	2.16
36 R 13106	6CH8	3.05	2.83	2.55
36 R 13114	6CJ3/6DW4B	2.21	2.05	1.85
36 R 13122	6CK3	2.21	2.05	1.85
36 R 13130	6CK4	1.92	1.78	1.60
36 R 21398	6CL3	2.21	2.05	1.85
36 R 13155	6CL6	2.81	2.60	2.34
36 R 13163	6CL8A	2.65	2.45	2.21
36 R 19780	6CM3	2.83	2.63	2.37
36 R 13171	6CM6	2.54	2.35	2.12
36 R 13189	6CM8	2.46	2.28	2.05
36 R 13197	6CM8	2.19	2.03	1.83
36 R 13205	6CN7	2.92	2.70	2.43
36 R 13221	6CQ8	2.72	2.53	2.28
36 R 13239	6CR6	1.59	1.48	1.33
36 R 13247	6CS6	2.21	2.05	1.85
36 R 13254	6CS7	2.40	2.23	2.01
36 R 13262	6CUS	2.38	2.20	1.98
36 R 13270	6CUB	3.02	2.80	2.52
36 R 13288	6CW4	3.19	2.95	2.66
36 R 13296	6CW5/EL86	1.49	1.38	1.24
36 R 13304	6CX8	3.02	2.80	2.52
36 R 13312	6CY5	2.89	2.68	2.41
36 R 13320	6CY7	1.65	1.53	1.38
36 R 13338	6CZ5	2.81	2.60	2.34
36 R 13346	6D10	3.00	2.78	2.50
36 R 13353	6DA4A/ 6DM4A	2.27	2.10	1.89
36 R 13379	6DB5	2.70	2.50	2.25
36 R 13387	6DB6	2.38	2.20	1.98
36 R 13395	6DC8/EBF89	1.65	1.53	1.38
36 R 13403	6DE4/6CQ4	2.24	2.08	1.87
36 R 13411	6DE6	2.03	1.88	1.67
36 R 13429	6DE7	3.00	2.78	2.50
36 R 50116	6DGGGT USE 6W6GT			
36 R 13445	6DHH13	3.94	3.65	3.27
36 R 13445	6DK6	1.92	1.78	1.60
36 R 21406	6DL3	2.81	2.60	2.34
36 R 20382	6DL4/ ECC88	4.29	3.98	3.56
36 R 13452	6DLS/EL95	1.59	1.48	1.33
36 R 21042	6DM4A USE 6DA4A/6DM4A			
36 R 13478	6DN3	2.21	2.05	1.85
36 R 13478	6DN6	3.78	3.50	3.15
36 R 13486	6DN7	3.11	2.88	2.59
36 R 13494	6DQ5	4.54	4.20	3.78
36 R 13502	6DQ6B/6GW6	3.16	2.93	2.64
36 R 13510	6DR7	3.16	2.93	2.64
36 R 13528	6DS4	3.19	2.95	2.66
36 R 13536	6DS5	1.97	1.83	1.65
36 R 13544	6DT5	1.92	1.78	1.60
36 R 13551	6DT6A	1.92	1.78	1.60
36 R 13569	6DT8	2.40	2.23	2.01
36 R 13577	6DV4	3.67	3.40	3.06
36 R 13593	6DW4B USE 6CJ3			
36 R 13593	6DX8/ECL84	1.59	1.48	1.33
36 R 11994	6DZ4/6FA4	2.65	2.45	2.21
36 R 13601	6DZ7	5.59	5.18	4.66
36 R 13619	6E5	3.46	3.20	2.88
36 R 13619	6E4A USE 6EH4A			
36 R 13619	6E4S USE 6CY3			
36 R 13619	6E4T USE 6EM7/6EA7			
36 R 13635	6E8	2.32	2.15	1.94
36 R 13635	6E8B USE 6GN8/6E8B			
36 R 13635	6EF4 USE 6EJ4A			
36 R 13668	6EH4A	4.64	4.30	3.87
36 R 13676	6EH5	2.24	2.08	1.87
36 R 13684	6EH7/EF183	2.88	1.93	1.74
36 R 13692	6EH8	1.89	1.75	1.58

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 13700	6EJ4A	5.05	4.68	4.21
36 R 13718	6EJ7/EF184	1.92	1.78	1.60
36 R 13726	6EL4 USE 6BK4C/6EL4			
36 R 13726	6EM5	2.65	2.45	2.21
36 R 13734	6EM7/6EA7	3.29	3.05	2.75
36 R 13751	6EN4	4.56	4.23	3.81
36 R 13752	6EN4	1.59	1.48	1.33
36 R 13759	6ES5	2.51	2.33	2.10
36 R 13767	6ES5	1.54	1.43	1.29
36 R 13775	6ES8/ ECC189	2.94	2.73	2.46
36 R 13783	6ET7	2.16	2.00	1.80
36 R 13791	6EU7	2.38	2.20	1.98
36 R 13809	6EUB	2.38	2.20	1.98
36 R 13817	6EV5	2.30	2.13	1.92
36 R 13825	6EV7	1.76	1.63	1.47
36 R 13833	6EW6	2.08	1.93	1.74
36 R 13841	6EY7	3.51	3.25	2.93
36 R 13866	6EY6	2.70	2.50	2.25
36 R 13874	6EZ5	3.13	2.90	2.61
36 R 13882	6EZ8	1.92	1.78	1.60
36 R 13890	6F5	3.51	3.25	2.93
36 R 13908	6F6/6F6GT	3.62	3.35	3.02
36 R 13924	6F8G	4.56	4.23	3.81
36 R 13932	6F97	1.65	1.53	1.38
36 R 13940	6FD6	1.92	1.78	1.60
36 R 13957	6FD7	3.35	3.10	2.79
36 R 13965	6FE5	1.84	1.70	1.53
36 R 13973	6FG5	2.72	2.53	2.28
36 R 13981	6FG6/EM84	1.81	1.68	1.51
36 R 13999	6FG7	2.72	2.53	2.28
36 R 14005	6FH5	2.70	2.50	2.25
36 R 14013	6FH8	2.38	2.20	1.98
36 R 14021	6EJ7	2.65	2.45	2.21
36 R 14039	6FM7	3.00	2.78	2.50
36 R 14047	6FN8	2.64	2.48	1.87
36 R 14054	6FQ5A USE 6GK5/6FQ5A			
36 R 14054	6FQ7/6CG7	1.76	1.63	1.47
36 R 14062	6FS5	2.46	2.28	2.05
36 R 14070</				

RCA-GE-RAYTHEON RECEIVING TUBES (Cont.)

Stock No.	Tube Type	1-5	6-24	25 & Up	Stock No.	Tube Type	1-5	6-24	25 & Up	Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 14534	6HM6	1.59	1.48	1.33	36 R 15218	6LUB	3.08	2.85	2.57	36 R 15960	8BQ5	2.38	2.20	1.98
36 R 14542	6HQ5	3.00	2.78	2.50	36 R 21463	6LX6	5.13	4.75	4.28	36 R 15978	8BQ11	2.57	2.38	2.14
36 R 14559	6HR6	2.38	1.28	1.15	36 R 15226	6LX8/				36 R 15986	8BU11	2.97	2.75	2.48
36 R 14567	6HR6	2.00	1.83	1.67		LCF802	1.40	1.30	1.17	36 R 20473	8CB11	3.02	2.80	2.52
36 R 14575	6HS5	4.64	4.36	3.87	36 R 15234	6LY8	2.40	2.23	2.01		8C7G USE 8FQ7/8C7G			
36 R 14583	6HS6	2.00	1.85	1.67	36 R 15242	6M11	3.43	3.18	2.86	36 R 15994	8CM7	1.46	1.35	1.22
36 R 14591	6HS8	2.81	2.60	2.34	36 R 20200	6MB8	1.97	1.83	1.65	36 R 16000	8CN7	1.65	1.53	1.38
36 R 20143	6HU6/EM87	2.62	2.43	2.19	36 R 15259	6MD8	3.13	2.90	2.61	36 R 16018	8CS7	2.16	2.00	1.80
36 R 20598	6HUB/ELL803	3.32	3.08	2.77	36 R 15267	6ME8	3.35	3.10	2.79	36 R 16026	8CW5/XL86	1.38	1.25	1.13
36 R 20150	6HV5A	5.37	4.98	4.48	36 R 19806	6MF8	2.57	2.38	2.14	36 R 16034	8CX8	2.38	2.20	1.98
36 R 21414	6HZ5/6JD5	4.19	3.88	3.47	36 R 20457	6MG8	1.32	1.23	1.11		8EB8 USE 8GN8/8EB8			
36 R 14609	6HZ6	1.97	1.83	1.65	36 R 50173	6MMH3	1.45	1.31	1.16	36 R 16042	8EM5	2.21	2.05	1.85
36 R 14625	6J5	2.72	2.53	2.28	36 R 20218	6MJ8	2.72	2.53	2.28	36 R 16059	8ET7	2.24	2.08	1.87
36 R 14633	6J5GT	2.72	2.53	2.28	36 R 19814	6MK8A	2.65	2.45	2.21	36 R 16067	8FQ7/8CG7	1.76	1.63	1.47
36 R 14641	6J6A	2.65	2.45	2.21	36 R 20622	6MN8	2.86	2.65	2.39	36 R 16075	8GJ7	1.76	1.63	1.47
36 R 14658	6J7	4.10	3.80	3.42	36 R 20226	6MQ8	2.40	2.23	2.01	36 R 16083	8GN8/8EB8	2.24	2.08	1.87
	6J10 USE 6Z10/6J10				36 R 21091	6MU8	3.19	2.95	2.66	36 R 16091	8JU7	1.73	1.60	1.44
36 R 14666	6J11	3.11	2.88	2.59	36 R 21109	6MV8	2.92	2.70	2.43	36 R 16103	8JU8A	2.00	1.85	1.67
36 R 21075	6JB5/6HE5	3.00	2.78	2.50	36 R 15275	6N7	3.27	3.03	2.73	36 R 16117	8JVB	2.72	2.53	2.28
36 R 14673	6JBCA	3.89	3.60	3.24	36 R 15283	6N7GT	3.19	2.95	2.66	36 R 16125	8KAB	2.89	2.68	2.41
36 R 14682	6JCA	2.57	2.38	2.14	36 R 15291	6Q1	3.19	2.95	2.66	36 R 20689	8KR8	3.35	3.10	2.79
36 R 14690	6JCB	2.13	1.98	1.78		6Q11 USE 6K11/6Q11				36 R 16133	8LC8	3.08	2.85	2.57
	6JD5 USE 6HZ5/6JD5					GRMH8 USE 6BC8/6BRH8				36 R 16141	8LT8	2.51	2.33	2.10
36 R 14708	6JD6	2.48	2.30	2.07		GRMH8 USE 6KN8/6RRH8				36 R 16158	9AB/8AB/PCF80			
	6JEGA USE 6LQ6/6JEGC				36 R 50207	6RP15	2.51	2.33	2.10	36 R 21125	9AH9	1.43	1.33	1.20
36 R 14724	6JE8	2.00	1.85	1.67	36 R 20663	6RP22	5.37	4.98	4.48	36 R 21471	9AK10	2.72	2.53	2.28
36 R 14732	6JF6	3.92	3.63	3.27	36 R 15309	6SA4	2.00	1.85	1.67	36 R 20697	9A08/PC085	3.86	3.58	3.20
36 R 21422	6JG5	1.73	1.60	1.44	36 R 15325	6SA7	3.19	2.95	2.66	36 R 16166	9AU7	1.59	1.48	1.33
36 R 14740	6JG6A	4.00	3.70	3.33	36 R 15333	6SA7GT	2.38	2.20	1.98	36 R 16174	9BJ11	1.70	1.58	1.42
36 R 21430	6JH5	4.27	3.95	3.56	36 R 15341	6SB7Y	3.21	2.98	2.68	36 R 16190	9CL8	1.59	1.48	1.33
36 R 14757	6JH6	2.24	2.08	1.87	36 R 15358	6SC7	3.19	2.95	2.66	36 R 20259	9CGH8A	2.21	2.05	1.85
36 R 14765	6JH8	3.19	2.95	2.66	36 R 15374	6SF7	3.40	3.15	2.84	36 R 16216	9GV8/XCL85	1.84	1.70	1.53
36 R 21448	6JK5	5.29	4.90	4.41	36 R 15382	6SG7	3.02	2.80	2.52	36 R 21133	9JWB	2.11	1.95	1.76
36 R 20165	6JK6	2.27	2.10	1.89	36 R 15390	6SH7	3.32	3.08	2.77	36 R 16224	9KC6	2.35	2.18	1.96
36 R 14773	6JK8	3.40	3.15	2.84	36 R 15408	6S17	3.16	2.93	2.64	36 R 16232	9KX6	2.24	2.08	1.87
36 R 14781	6JMA6	3.16	2.93	2.64	36 R 15424	6SK7	3.19	2.95	2.66	36 R 16240	9KZ8	1.59	1.48	1.33
36 R 14799	6JN6	2.57	2.38	2.14	36 R 15432	6SK7GT	2.97	2.75	2.48	36 R 20267	9LA6	2.27	2.10	1.89
36 R 14807	6JN8	2.57	2.38	2.14	36 R 15440	6SL7GT	2.92	2.70	2.43	36 R 50264	9MMH3	2.24	2.08	1.87
36 R 20010	6JQ6	2.81	2.60	2.34	36 R 15465	6SQ7	3.21	2.98	2.68	36 R 21141	9MM8	2.40	2.23	2.01
36 R 20028	6JR6	3.43	3.18	2.86	36 R 15475	6SN7GTB	2.36	2.20	1.98	36 R 50272	9MP12	2.32	2.15	1.94
36 R 14815	6JS6C	4.24	3.93	3.54	36 R 15481	6SR7	2.65	2.45	2.21	36 R 50280	9RA6	4.13	3.83	3.45
36 R 14823	6JTG6A	3.16	2.93	2.64	36 R 15499	6T4	2.78	2.58	2.32		9RA11 USE 10DE7			
36 R 14831	6JT8	2.72	2.53	2.28	36 R 15507	6T8A	2.89	2.68	2.41	36 R 20713	9RH2	2.65	2.45	2.21
36 R 20036	6JUGA	2.38	2.20	1.98	36 R 15515	6T9	2.38	2.20	1.98	36 R 16257	9UBA	1.67	1.55	1.40
36 R 14849	6JUBA	2.57	2.38	2.14	36 R 15523	6T10	3.19	2.95	2.66	36 R 16265	10AL11	2.46	2.28	2.05
36 R 14856	6JVB	2.72	2.53	2.28	36 R 15531	6U5	4.00	3.70	3.33	36 R 16273	10BQ5	1.49	1.38	1.24
36 R 14864	6JWB				36 R 19822	6UBA/6AX8/6KDB/5KDB	2.11	1.95	1.76	36 R 16281	10C8	3.27	3.03	2.73
	ECF802*	1.67	1.55	1.40	36 R 15549	6U9/ECF201	1.57	1.45	1.31	36 R 16299	10CW5/LL86	1.38	1.28	1.15
36 R 50165	6JY8	3.29	3.05	2.75	36 R 15556	6U10	2.48	2.23	2.01	36 R 16307	10DE7	2.92	2.70	2.43
36 R 14872	6JZ6	2.91	2.73	2.40	36 R 15564	6V3A	2.48	2.28	2.05	36 R 16315	10DR7	2.40	2.23	2.01
36 R 14880	6JZ8	2.40	2.23	2.01	36 R 15572	6V4/EZ80	4.81	4.51	4.23	36 R 16323	10DX8	1.49	1.38	1.24
36 R 14898	6KG7	3.75	3.45	3.13	36 R 15580	6V6	4.00	3.70	3.33	36 R 16331	10EG7	2.38	2.20	1.98
36 R 14906	6K7	3.75	3.45	3.13	36 R 15598	6V6GTA	2.65	2.45	2.21	36 R 16349	10EM7	2.65	2.45	2.21
36 R 14914	6K8	4.16	3.85	3.47	36 R 15606	6W4GTA	1.78	1.65	1.49	36 R 16356	10CF7A	2.94	2.73	2.46
36 R 14922	6K11/6Q11	2.40	2.23	2.01	36 R 15614	6W6GT/6DG6GT	2.48	2.30	2.07	36 R 16372	10GK6	2.65	2.45	2.21
36 R 14930	6KA8	2.89	2.68	2.41					36 R 16389	10GN8	2.97	2.75	2.48	
36 R 14948	6KD6	5.27	4.88	4.39	36 R 15622	6X4	2.03	1.88	1.67	36 R 21489	10GV8	3.32	3.15	2.94
	6KD8 USE 6UBA/6AXB				36 R 15630	6X5GT	2.13	1.98	1.78	36 R 16398	10HF8	3.19	2.95	2.66
36 R 14955	6KE8	3.62	3.35	3.02	36 R 15648	6X8A	2.40	2.23	2.01	36 R 21497	10JA5	2.72	2.53	2.28
36 R 21455	6KG6A/				36 R 15655	6X9/ECF200	1.59	1.48	1.33		10JAB USE 10LZ8/10JAB			
	EL509	5.27	4.88	4.39	36 R 15671	6Y6GT/6YF200	1.92	1.78	1.60	36 R 16406	10JT8	2.54	2.35	2.12
36 R 14963	6L8	1.55	1.48	1.33	36 R 15689	6Y9/EFL200	1.67	1.55	1.40	36 R 16414	10JY8	2.35	2.18	1.96
36 R 14971	6KM6	4.78	4.43	3.99		6Z4 USE 84/6Z4				36 R 16422	10KR8	2.54	2.35	2.12
36 R 14989	6KM8	1.86	1.73	1.58	36 R 15697	6Z10/6J10	3.59	3.33	3.00	36 R 16430	10KU8	2.62	2.43	2.19
36 R 20176	6KN6	4.32	4.00	3.60	36 R 15721	7A7	3.86	3.58	3.22	36 R 16448	10LB8	2.54	2.35	2.12
36 R 20606	6KNB/				36 R 15747	7AU7	1.67	1.55	1.40	36 R 16455	10LC8	3.19	2.95	2.66
	6KRH8	4.00	3.70	3.33	36 R 15754	7B5	4.51	4.18	3.76	36 R 16463	10LV8	3.29	3.05	2.75
36 R 14997	6RR8	2.30	2.13	1.92	36 R 15770	7C5	2.54	2.35	2.12	36 R 16471	10LZ8/10JAB	2.11	1.95	1.76
	6KS6 USE 6BN6/6KS6				36 R 15788	7C7	1.84	1.70	1.53	36 R 21158	10T10	3.16	2.93	2.64
36 R 15002	6KT6	2.65	2.45	2.21	36 R 15796	7EY6	2.38	2.20	1.98	36 R 21166	10Z10	3.32	3.08	2.77
36 R 15010	6KT8	3.19	2.95	2.66	36 R 15804	7F7	4.05	3.75	3.38	36 R 20275	11AF9	1.67	1.55	1.40
36 R 15028	6KUB	2.59	2.40	2.16	36 R 15812	7F8	4.46	4.13	3.72	36 R 16489	11AR11	2.89	2.68	2.41
36 R 21083	6KV6A	3.94	3.65	3.27	36 R 15820	7G7	2.94</							

RCA-GE-RAYTHEON RECEIVING TUBES (Cont.)

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 16638	12AE6A	1.67	1.55	1.40
36 R 16646	12AE10	3.27	3.03	2.73
36 R 16653	12AF3/12BR3/ 12RK19	2.30	2.13	1.92
36 R 16661	12AF6	1.70	1.58	1.42
36 R 16687	12AL5	1.89	1.75	1.58
36 R 16695	12AL8	3.35	3.10	2.79
36 R 16703	12AL11	3.05	2.83	2.55
36 R 16711	12AQ5	2.08	1.93	1.74
36 R 16729	12AT6	1.76	1.63	1.47
36 R 16737	12AT7/ ECC88	1.92	1.78	1.60
36 R 16745	12AU5	2.08	1.93	1.74
36 R 16752	12AU7A/ ECC82	1.67	1.55	1.40
36 R 16760	12AV5GA	2.94	2.73	2.46
36 R 16778	12AV6	1.46	1.35	1.22
36 R 16786	12AV7	2.89	2.66	2.41
36 R 16794	12AW6	1.92	1.78	1.60
36 R 16802	12AX3	2.00	1.85	1.67
36 R 16810	12AX4CCTB	2.00	1.85	1.67
36 R 16828	12AX7/ECC83	1.65	1.53	1.38
36 R 19855	12AX7A/ 7025	1.67	1.55	1.40
36 R 16836	12AY3A/ 12B3	1.57	1.45	1.31
36 R 16844	12AY7	3.48	3.23	2.91
36 R 16851	12AZ7A	2.40	2.23	2.01
36 R 16869	12B4A	2.48	2.30	2.07
36 R 16877	12B4E	1.67	1.55	1.40
36 R 16885	12B47	3.19	2.95	2.66
36 R 16893	12B46	1.27	1.18	1.06
36 R 16901	12BE3	2.27	2.10	1.89
36 R 16919	12BE6	1.84	1.70	1.53
36 R 16927	12BF6	1.27	1.18	1.06
36 R 16935	12BF11	3.59	3.33	3.00
36 R 16943	12BH7A	2.32	2.15	1.94
36 R 16950	12BK5	2.03	1.88	1.69
36 R 16968	12BL6	2.30	2.13	1.92
36 R 16976	12BN6	2.48	2.30	2.07
36 R 16984	12BQ6CA	2.27	2.10	1.89
33 R 16992	12BQ6GTB/ 12CU6	2.40	2.23	2.01
36 R 17008	12BR3 USE 12AF3/12BR3	1.65	1.53	1.38
36 R 17024	12BR7	1.86	1.73	1.56
36 R 20291	12BV11	2.59	2.40	2.16
36 R 17040	12BW4	1.81	1.68	1.51
36 R 17057	12BY7/12DQ7	2.24	2.08	1.87
36 R 17065	12BZ6	1.30	1.20	1.08
36 R 17073	12BZ7	2.24	2.08	1.87
36 R 17081	12CA5	2.48	2.30	2.07
36 R 19863	12CL3	1.92	1.78	1.60
36 R 17099	12CN5	1.76	1.63	1.47
36 R 17107	12CR6	1.59	1.48	1.33
36 R 21208	12CT3	1.76	1.63	1.47
36 R 17115	12CT8	3.46	3.20	2.88
36 R 17123	12CU5/12CS5	2.57	2.38	2.14
36 R 17131	12CV6 USE 12BQ6GTB	1.49	1.38	1.24
36 R 17148	12D4	1.65	1.53	1.38
36 R 17156	12D05	1.40	1.30	1.17
36 R 17164	12D08	1.67	1.55	1.40
36 R 17172	12D0K6	1.24	1.15	1.04
36 R 17206	12DQ6B/12GW6	2.89	2.68	2.41
36 R 17222	12DQ7 USE 12BY7A/12BV7	2.92	2.70	2.43
36 R 17230	12DT5	1.84	1.70	1.53
36 R 17248	12DT8	2.16	2.00	1.80
36 R 20747	12DW4A	2.34	2.13	1.92
36 R 17271	12E7	1.65	1.53	1.38
36 R 17289	12DY8	4.29	3.98	3.58
36 R 17305	12DZ6 USE 12EK6/ 12DZ6/12EA6	1.49	1.38	1.24
36 R 17313	12ED5	1.46	1.35	1.22
36 R 17318	12EG6	1.86	1.73	1.56
36 R 17321	12EK6/12DZ6/12EA6	1.94	1.80	1.62
36 R 17347	12EQ7	1.49	1.38	1.24
36 R 17354	12E26	1.92	1.78	1.60
36 R 17362	12F6	1.76	1.63	1.47
36 R 17370	12FK6	1.36	1.28	1.15
36 R 17388	12FM6	1.40	1.30	1.17
36 R 21216	12FQ7	2.00	1.85	1.67
36 R 17396	12FQ8	2.81	2.60	2.34
36 R 17404	12FV7	1.84	1.70	1.53
36 R 17412	12FX5	2.00	1.85	1.67
36 R 21224	12FX8A	2.08	1.93	1.74
36 R 17438	12GA6	1.46	1.35	1.22
36 R 20754	12GB3	5.05	4.68	4.21
36 R 17458	12GB6 USE 12GW6			

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 17446	12GC6	2.81	2.60	2.34
36 R 17453	12GE5	3.19	2.95	2.66
36 R 17461	12GJ5A	2.65	2.45	2.21
36 R 17479	12GN7/ 12HG7	3.19	2.95	2.68
36 R 17487	12GT5A	2.89	2.68	2.41
36 R 17495	12H6	2.40	2.23	2.01
36 R 17503	12HE7	3.67	3.40	3.06
36 R 17529	12HG7 USE 12GN7/12HG/ 12HL7	2.89	2.68	2.41
36 R 17537	12I5	2.21	2.05	1.85
36 R 17545	12I5GT	2.59	2.40	2.16
36 R 17552	12J8	2.35	2.18	1.96
36 R 17560	12JB6A	3.75	3.45	3.13
36 R 21521	12JF5	2.97	2.75	2.48
36 R 17578	12JN6	2.11	1.95	1.76
36 R 17586	12JN8	2.00	1.85	1.67
36 R 20309	12JQ6	2.40	2.23	2.01
36 R 17594	12JT6A	2.67	2.48	2.23
36 R 17602	12K5	1.86	1.73	1.56
36 R 17628	12KL8	1.32	1.23	1.11
36 R 17636	12LG6T	1.92	1.78	1.60
36 R 17644	12MD8	2.62	2.43	2.19
36 R 17651	12M5	1.81	1.68	1.51
36 R 17669	12SA7 USE 12AF3/ 12R19 USE 12AF3	3.19	2.95	2.66
36 R 17685	12SC7	2.81	2.60	2.34
36 R 17693	12SF5	2.13	1.98	1.78
36 R 17701	12SF7	3.35	3.10	2.79
36 R 17719	12SG7	2.54	2.35	2.12
36 R 17727	12SH7	2.92	2.70	2.43
36 R 17735	12SJ7	2.78	2.58	2.32
36 R 17743	12SK7	3.13	2.90	2.61
36 R 17750	12SK7GT	2.40	2.23	2.01
36 R 17768	12SL7GT	2.67	2.48	2.23
36 R 17776	12SN7GTA	2.65	2.45	2.21
36 R 17784	12R5	2.97	2.75	2.48
36 R 17800	12T10	3.19	2.95	2.66
36 R 17818	12V6GT	2.81	2.60	2.34
36 R 17826	12W6GT	3.05	2.83	2.55
36 R 17834	12X4	1.22	1.13	1.02
36 R 17842	13CW4	3.19	2.95	2.66
36 R 17859	13DE7	3.19	2.95	2.66
36 R 17867	13DR7	3.08	2.85	2.57
36 R 17875	13EM7/ 15EA7	3.48	3.23	2.91
36 R 17883	13F07	3.19	2.95	2.66
36 R 17891	13FM7 USE 15FM7/13FM7	2.35	2.18	1.96
36 R 17909	13GF7A	3.08	2.85	2.57
36 R 20317	13JZ8	2.72	2.53	2.28
36 R 17917	13V10	3.59	3.33	3.00
36 R 17925	13Z10/13J10	3.83	3.55	3.20
36 R 17941	14BL11	4.34	4.03	3.63
36 R 17958	14BR11	3.46	3.20	2.88
36 R 17966	14GT8	1.89	1.75	1.58
36 R 17974	14JG8	2.16	2.00	1.80
36 R 17982	15AF11	2.83	2.63	2.37
36 R 17990	15BD11A	3.27	3.03	2.73
36 R 18006	15CW5/PL841.32	1.23	1.11	
36 R 18014	15DQ8/ PCL84	1.92	1.78	1.60
36 R 18030	15EA7 USE 13EM7/15EA7	3.48	3.23	2.91
36 R 18048	15FM7/ 13FM7	2.40	2.23	2.01
36 R 18063	15FY7	2.11	1.95	1.76
36 R 18071	15KY8A	3.75	3.45	3.13
36 R 18079	15LE8	4.13	3.83	3.45
36 R 21539	15MF8	2.75	2.55	2.30
36 R 18089	16A8/PCL82	1.86	1.73	1.56
36 R 19871	16AK9	3.67	3.40	3.06
36 R 18097	16C03/YX88	1.46	1.35	1.22
36 R 19889	16CB11	2.89	2.68	2.41
36 R 19897	16BX11	3.35	3.10	2.79
36 R 18105	16GK6	1.65	1.53	1.38
36 R 18113	16GY5	2.62	2.43	2.19
36 R 18121	16KA6	3.38	3.13	2.82
36 R 20499	16LUBA	4.32	4.00	3.60
36 R 21240	17A8	3.19	2.95	2.66
36 R 20762	17A89	3.27	3.03	2.73
36 R 18139	17AB10 USE 17X10	1.40	1.30	1.17
36 R 18147	17AX3	2.00	1.85	1.67
36 R 18154	17AY3/ 17BS3	2.27	2.10	1.89
36 R 20770	17BL14	5.64	5.23	4.70
36 R 18162	17BE3/ 17BZ3	2.27	2.10	1.89
36 R 18170	17BF11	3.59	3.33	3.00
36 R 18188	17BH3	1.54	1.43	1.29
36 R 18196	17BQ6GTB	2.81	2.60	2.34
36 R 20788	17BR3/ 17RK19	2.00	1.85	1.67
36 R 20887	17BS3A/ 17DWA4	2.27	2.10	1.89

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 20051	17BW3	1.73	1.60	1.44
36 R 18212	17BZ3 USE 17BE3/17BZ3			
36 R 18220	17C9	3.86	3.58	3.22
36 R 18238	17C9/17CS5/17CS	2.00	1.85	1.67
36 R 18246	17D4/17DM44.2	2.23	2.01	1.89
36 R 18253	17DE4	1.97	1.83	1.65
36 R 18279	17DQ6B/ 17GW6	3.27	3.03	2.73
36 R 18287	17DWA4 USE 17BS3A			
36 R 18295	17EW8/ HCC85	1.49	1.38	1.24
36 R 18303	17G5 USE 17BQ6GTB			
36 R 18311	17GE5	2.35	2.18	1.96
36 R 18329	17G5A	3.59	3.33	3.00
36 R 18337	17GT5A	3.59	3.33	3.00
36 R 20796	17HV5 USE 17DQ8			
36 R 18345	17H23	2.00	1.85	1.67
36 R 18353	17H85	4.33	4.03	3.69
36 R 18361	17J6A	3.48	3.23	2.91
36 R 18369	17J6	4.00	3.70	3.33
36 R 18377	17J6A	3.40	3.15	2.84
36 R 18385	17J6A	3.40	3.15	2.84
36 R 18393	17J6A	3.40	3.15	2.84
36 R 18401	17J6A	3.40	3.15	2.84
36 R 18409	17J6A	3.40	3.15	2.84
36 R 18417	17J6A	3.40	3.15	2.84
36 R 18425	17J6A	3.40	3.15	2.84
36 R 18433	17J6A	3.40	3.15	2.84
36 R 18441	17J6A	3.40	3.15	2.84
36 R 18449	17J6A	3.40	3.15	2.84
36 R 18457	17J6A	3.40	3.15	2.84
36 R 18465	17J6A	3.40	3.15	2.84
36 R 18473	17J6A	3.40	3.15	2.84
36 R 18481	17J6A	3.40	3.15	2.84
36 R 18489	17J6A	3.40	3.15	2.84
36 R 18497	17J6A	3.40	3.15	2.84
36 R 18505	17J6A	3.40	3.15	2.84
36 R 18513	17J6A	3.40	3.15	2.84
36 R 18521	17J6A	3.40	3.15	2.84
36 R 18529	17J6A	3.40	3.15	2.84
36 R 18537	17J6A	3.40	3.15	2.84
36 R 18545	17J6A	3.40	3.15	2.84
36 R 18553	17J6A	3.40	3.15	2.84
36 R 18561	17J6A	3.40	3.15	2.84
36 R 18569	17J6A	3.40	3.15	2.84
36 R 18577	17J6A	3.40	3.15	2.84
36 R 18585	17J6A	3.40	3.15	2.84
36 R 18593	17J6A	3.40	3.15	2.84
36 R 18601	17J6A	3.40	3.15	2.84
36 R 18609	17J6A	3.40	3.15	2.84
36 R 18617	17J			

RCA-GE-RAYTHEON RECEIVING TUBES (Cont.)

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 18816	25AV5GA	3.05	2.83	2.55
36 R 18824	25AX4GT	1.65	1.51	1.49
36 R 50421	25BB14	5.67	5.25	4.72
36 R 18832	25BK5	1.64	1.70	1.53
36 R 18840	25BQ6GA/25CU6	2.35	2.18	1.96
36 R 18857	25BQ6GTB/25CU6	2.26	2.20	1.98
36 R 18865	25C5	2.24	2.08	1.87
36 R 18873	25CA5	1.54	1.80	1.62
36 R 18881	25CD6GB	3.46	3.20	2.88
36 R 18899	25CG3	1.84	1.70	1.53
36 R 20838	25CK3	1.84	1.70	1.53
36 R 21570	25CT3	1.59	1.48	1.33
36 R 18907	25DK4 USE 25BQ6GTB	1.19	1.10	.99
36 R 21596	25DL3	3.51	2.75	2.48
36 R 18915	25DN6	3.56	3.30	2.97
36 R 20846	25E5/PL36	3.59	3.33	3.00
36 R 18923	25EC6	3.75	3.45	3.13
36 R 18931	25EH5	2.40	2.23	2.01
36 R 18949	25F5A	2.08	1.93	1.74
36 R 21604	25HX5	2.81	2.60	2.34
36 R 21612	25J28	3.73	2.90	2.61
36 R 18956	25L6GT/25W6GT	2.81	2.60	2.34
36 R 18964	25W4GT/25W6GT USE 25L6GT	2.80	1.85	1.67
36 R 18980	25Z6GT	2.08	1.93	1.74
36 R 20358	26HU5	5.51	6.05	5.42
36 R 21307	26LX6	5.13	4.75	4.28
36 R 18998	27	2.75	2.55	2.30
36 R 19004	27GB5	2.00	1.85	1.67
36 R 19012	29GK6	1.94	1.80	1.62
36 R 20853	29PK6	6.35	5.87	5.29
36 R 21620	29LE6	3.19	2.95	2.66
36 R 21315	30AE3/PY81	3.81	1.68	1.51
36 R 19200	30AG11	3.48	3.23	2.91
36 R 20861	30JZ6	3.32	3.08	2.77
36 R 20879	30KC6	4.37	4.05	3.85

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 19954	31AL10	3.75	3.45	3.13
36 R 19038	31JS6C	4.13	3.83	3.45
36 R 21323	31LQ6	4.59	4.25	3.85
36 R 21638	31LR8	5.43	5.02	4.52
36 R 21646	31LZ6	5.27	4.88	4.39
36 R 19046	32ET5A	1.30	1.20	1.08
36 R 19962	32HQ7	4.16	3.85	3.47
36 R 19053	33G7	4.00	3.70	3.33
36 R 19061	33GY7A	3.75	3.45	3.13
36 R 21653	33JR6	3.35	2.10	2.79
36 R 19970	33JV6	2.51	2.33	2.10
36 R 19028	34CE3/34CD3	2.40	2.23	2.01
36 R 19095	34GD5A	1.59	1.48	1.33
36 R 21331	34R3	3.78	3.50	3.15
36 R 19111	35B5	1.73	1.60	1.44
36 R 19129	35C5	2.08	1.93	1.74
36 R 19145	35EH5	2.40	2.23	2.01
36 R 19160	35L6GT	2.65	2.45	2.21
36 R 20507	35LR6	4.78	4.43	3.99
36 R 19178	35W4	1.22	1.13	1.02
36 R 19186	35Y4	2.43	2.25	2.03
36 R 19202	35Z4GT	1.38	1.28	1.15
36 R 19210	35Z5GT	1.84	1.70	1.53
36 R 19228	36AM3B/40KD6	1.76	1.63	1.47
36 R 19236	38HE7	4.32	4.00	3.60
36 R 19244	38HK7	4.32	4.00	3.60
36 R 21661	40KD6 USE 36KD6/40KD6	5.43	5.02	4.52
36 R 19289	42	2.62	2.43	2.19
36 R 21679	42EC4A	2.65	2.45	2.21
36 R 19277	42KN6	4.32	4.00	3.60
36 R 19285	43	3.89	3.60	3.24
36 R 19293	45B5/ULB4	1.51	1.40	1.26
36 R 19301	50A5	3.16	2.93	2.64
36 R 19319	50B5	1.59	1.48	1.33
36 R 20374	50BM8/ UCL82	2.35	2.18	1.96

Stock No.	Tube Type	1-5	6-24	25 & Up
36 R 19327	50C5	1.89	1.75	1.58
36 R 19335	50DC4	1.30	1.20	1.08
36 R 19343	50EH5	2.11	1.95	1.76
36 R 19350	50FH5	2.40	2.23	2.01
36 R 19368	50FK5	1.19	1.10	.99
36 R 21349	50GY7A	5.35	4.95	4.46
36 R 19376	50HC6	2.24	2.08	1.87
36 R 19384	50HK6	1.16	1.08	.97
36 R 19392	50HN5	1.49	1.36	1.24
36 R 21356	50JV6	3.78	3.50	3.15
36 R 19400	50L6GT	3.05	2.83	2.55
36 R 19426	50Y6GT	2.35	2.18	1.96
36 R 19442	53HK7	4.51	4.18	3.76
36 R 19459	60FX5	1.59	1.48	1.33
36 R 19467	75	3.20	2.88	2.56
36 R 19475	80	2.59	2.40	2.16
36 R 19491	117L7	7.96	7.39	6.65
36 R 19509	117N7GT	6.94	6.43	5.79
36 R 19525	117Z3	4.23	2.25	2.03
36 R 19541	5879	2.89	2.68	2.41
36 R 19558	6267	1.51	1.40	1.26
36 R 19561	63N1	1.84	1.70	1.53
36 R 19574	6973	2.72	2.53	2.28
36 R 19590	7025 USE 12AX7A/7025	4.02	3.73	3.36
36 R 19608	7189A	2.38	2.20	1.98
36 R 19616	7199	3.05	2.83	2.55
36 R 19624	7247	2.54	2.35	2.12
36 R 19632	7355	2.38	2.20	1.98
36 R 19640	7408	1.81	1.68	1.51
36 R 19657	7543	1.76	1.63	1.47
36 R 19665	7581A/KT66	3.32	3.08	2.77
36 R 19673	7591A	1.51	1.40	1.26
36 R 19681	7695	2.38	2.20	1.98
36 R 19699	7868	3.05	2.83	2.55
36 R 19715	8417	3.05	2.83	2.55
36 R 19723	825A/6A6A	1.76	1.63	1.47
36 R 19731	8426A/12AU6	2.03	1.88	1.69



MULLARD HIGH FIDELITY TUBES

Premium quality tubes widely used by Hi-Fi TUBE TUBES are directly interchangeable listed. Imported from England. Shpg. wt., 1/2 lb.

equipment manufacturer with equivalent types

Matched Pairs (Types Ending in MP) Consists of 2 of the type, measured and tested to be within close tolerance of each other to assure maximum balanced output. Wt. 1 lb.

Stock No.	Tube Type	Eqv. Type	Net
36 R 53862	EABC80	6AK3	1.65
36 R 53870	EB91	6AL5	1.48
36 R 53888	EB8C1	6B07A	2.70
36 R 53896	EB91	6AV5	1.35
36 R 53904	EBF89	6DC3	1.53
36 R 54530	EC88	6DL3	3.98
36 R 53912	EC92	6BA8	1.80
36 R 54548	EC900	6HA5	1.93
36 R 53920	EC97	6FY3	1.38
36 R 53938	EC81	12AX7	1.78
36 R 53946	EC82	12AU7	1.58
36 R 53953	EC83	12AX7	1.40
36 R 53961	EC85	6AQ8	1.50
36 R 53979	EC88	6DL3	2.48
36 R 53987	ECF80	6BL8	1.35
36 R 53995	ECF82	6U8	1.73
36 R 54555	ECF801	6EJ7/6GJ7	1.55
36 R 54019	EC81	6AJ3	2.00
36 R 54027	ECL80	6A6B	3.75
36 R 54035	ECL82	6BM8	1.45
36 R 54043	ECL86	6CW8	1.53
36 R 54050	EF80	6DB6	1.53
36 R 54068	EF85	6B7	2.75
36 R 54076	EF86	6E7	2.25
36 R 54084	EF89	6DA6	1.43
36 R 54092	EF93	6BA6	1.63
36 R 54100	EF94	6AL6A	1.48
36 R 54118	EF95	6AK5	2.38

Stock No.	Tube Type	Eqv. Type	Net
36 R 54126	EF183	6EJ7	1.93
36 R 54134	EF184	6EJ7	1.78
36 R 54142	EK90	6BE6	1.47
36 R 54159	EL34	6CA7	3.13
36 R 54175	EL84	6BQ5	1.95
36 R 54183	EL86	6CW5	1.38
36 R 54191	EL90	6AQ5A/6HG5	1.70
36 R 54209	EL95	6DL5	1.48
36 R 54217	EM34	6C07	4.75
36 R 54225	EM84	6FG6	1.68
36 R 54233	EZ80	6V4	1.80
36 R 54241	EZ81	6CA4	.88
36 R 54258	EZ90	6X4	1.70
36 R 54266	GZ34	5AR4	2.50
36 R 54274	HCC85	17EW8	1.38
36 R 54282	KT66		9.75
36 R 54290	KT77		8.75
36 R 54308	KT88		14.75
36 R 54563	LC900	3HA5	1.93
36 R 54571	LCF801	5GJ7	1.48
36 R 54589	LL86	10CW5	1.28
36 R 54597	LY88	20AQ3	1.63
36 R 54605	PC900	4HA5	1.93
36 R 54613	PC85	9AQ8	3.58
36 R 54621	PCF80	9AB7	1.33
36 R 54738	PCF801	8G17	1.45
36 R 54639	PCL82	16A8	1.70
36 R 54647	PCL84	150Q8	1.70

Stock No.	Tube Type	Eqv. Type	Net
36 R 54654	PCL85	18GV8	2.33
36 R 54662	PL36	25E5	3.35
36 R 54670	PY81	12X7	2.20
36 R 54688	PY88	30AE3	1.63
36 R 54316	UCL82	50BM8	1.48
36 R 54332	UL84	45B5	2.10
36 R 54696	YX88	16A23	1.35
36 R 54357	7025A		1.55
36 R 54365	7189A		1.93
36 R 54373	7247	12DW7	1.53

MATCHED-PAIRS

Stock No.	Tube Type	Eqv. Type	Net
36 R 54381	ECL82MP	6BM8MP	5.85
36 R 54399	ECL86MP	6CW8MP	6.90
36 R 54407	ECL84MP	6CA7MP	9.50
36 R 54423	EL84MP	6GQ5MP	6.25
36 R 54431	EL86MP	6GQ5MP	6.25
36 R 54449	EL90MP	6CW8MP	5.70
36 R 54456	EL95MP	6DL5MP	6.00
36 R 54464	KT66MP		19.75
36 R 54472	KT77MP		17.50
36 R 54480	KT88MP		31.25
36 R 54498	ECL82MP	50BM8MP	5.75
36 R 54506	UL84MP	45B5MP	5.25
36 R 54514	7189MP		3.93

IEC MULLARD MASTER 10M SERIES

This selected series of individually lab-tested tubes features tube-to-tube uniformity section-to-section uniformity to the most stringent specifications. Hum, noise, microphonics and distortion kept to absolute minimum (Rf to the maximum, individual plastic

foam cushion packing. Any tube failing to give 10,000 hours of effective performance within 2 years from purchase may be returned for no charge replacement. Avg. shpg. wt., 5 oz.

Stock No.	10M Type	Net
36 R 54704	6CY5	4.20
36 R 53276	6EU7	2.60
36 R 54712	6EV5	4.20
36 R 53282	6GK5	2.65
36 R 53334	6T8A	3.10
36 R 54720	12BY7A	5.00
36 R 54522	5654/6AK5W	4.50
36 R 53458	7025	2.60
36 R 53425	7247/12DW7	2.85
36 R 53474	ABC80/6AK8	3.05
36 R 53482	EB91/6AL5	2.15

Stock No.	10M Type	Net
36 R 53490	EB90/6AT6	2.15
36 R 53508	EB91/6AV6	2.15
36 R 53516	EBF89/6DC8	2.95
36 R 53524	EC90/5CA	3.15
36 R 53532	EC95/6ER5	2.65
36 R 53540	EC97/6FY5	2.60
36 R 53557	ECC81/12AT7	2.85
36 R 53565	ECC82/12AU7	2.45
36 R 53573	ECC83/12AX7	2.45
36 R 53581	ECC85/6AQ8	2.65
36 R 53589	ECC88/6D18	3.45

Stock No.	10M Type	Net
36 R 53607	ECC91/616	2.80
36 R 53615	ECC189/6ES8	3.85
36 R 53623	ECF80/6BL8	3.40
36 R 53631	ECF86/6BH8	3.40
36 R 53649	ECH81/6A18	2.92
36 R 53656	ECL80/6AB8	3.05
36 R 53664	ECL84/6DX8	3.15
36 R 53672	EF86/6267	2.75
36 R 53680	EF89/6DA6	2.80
36 R 53698	EF93/6BA6	2.8

Batteries-Burgess, Eveready, RCA, Mallory

POPULAR 1.5 V. GENERAL PURPOSE AND 9 V. TRANSISTOR BATTERIES

The most popular 1.5 volt D, C, and AA flashlight, general purpose batteries and 9-volt transistor radio batteries. Available in: standard zinc-carbon; alkaline types featuring up to 10 times longer life;

mercury types characterized by excellent voltage stability throughout long operating life plus extremely long shelf life; rechargeable nickel-cadmium types which may be recharged hundreds of times



Stock No.	Type	Chemical Composition	Replaces Manufacturer's Type				Volts	Wt. oz.	Net	
			Eveready	Burgess	RCA	Mallory				
32 R 47491	D	Carbon-Zinc	950	2	VS036	M13F	1.5	8.0	Pkg. of 2	.39
32 R 48846	D	Alkaline	E95	AL2	VS1336	MN1300	1.5	7.0	Each	.65
32 R 47590	D	Mercury	—	—	—	RM42R	1.35	8.0	Each	3.25
32 R 48895	D	Nicad	CH4	CD10	—	—	1.25	7.0	Each	6.64
32 R 47509	C	Carbon-Zinc	935	1	VS035A	M14F	1.5	5.0	Pkg. of 2	.39
32 R 48879	C	Alkaline	E93	AL1	VS1335	MN1400	1.5	4.0	Each	.52
32 R 48887	C	Nicad	—	CD14	—	—	1.25	5.0	Each	3.90
32 R 47757	AA	Carbon-Zinc	915	910	VS034A	M15F	1.5	3.0	Pkg. of 2	.34
32 R 47525	AA	Alkaline	E91	AL9	VS1334	MN1500	1.5	4.0	Pkg. of 2	.32
32 R 48857	AA	Mercury	E9	Hg9	VS9	ZM	1.4	4.0	Pkg. of 2	1.31
32 R 47490	AA	Nicad	C450	CD6	—	—	1.25	3.0	Each	1.65
32 R 48077	Radio 9V	Carbon-Zinc	216	206	VS323	M1604	9.0	3.0	Each	.54
32 R 47533	Radio 9V	Alkaline	—	—	VS1323	MN1604	9.0	4.0	Each	.90
32 R 47673	Radio 8.4V	Mercury	E146X	H146X	VS146X	TR146X	8.4	1.9	Each	1.28

MALLORY DURACELL MERCURY BATTERIES

Types with * have snap connections. Shipping weight varies from 2 oz. to 10 oz. max.

Stock No.	Type No.	Volts	Net Per Package
32 R 47566	RM1	1.4	pkg. of 4 2.68
32 R 47574	RM1R	1.35	pkg. of 4 3.26
32 R 47582	RM4R	1.35	pkg. of 4 6.48
32 R 46550	RM12	1.4	pkg. of 2 2.28
32 R 47590 (D)	RM42	1.4	Each 3.25
32 R 47608	RM312	1.4	pkg. of 6 3.00
32 R 47616	RM400	1.4	pkg. of 6 3.00
32 R 47620	RM401	1.4	Each 3.67
32 R 46618	RM502R	1.35	pkg. of 2 2.20
32 R 47632	RM520	1.4	pkg. of 6 1.02
32 R 47640	RM625R	1.35	pkg. of 4 2.92
32 R 47657	RM630	1.4	pkg. of 4 2.52
32 R 46675	RM640	1.4	pkg. of 2 1.26
32 R 46683	RM675	1.4	pkg. of 6 3.00
32 R 46709	TR115R	6.75	pkg. of 2 4.88
32 R 47665	TR126	8.4	Each 1.67
32 R 46725	TR132R	2.7	pkg. of 2 2.94
32 R 46733	TR133R	4.05	pkg. of 2 3.74
32 R 46741	TR134R	5.4	pkg. of 2 4.54
32 R 46750	TR135R	6.75	pkg. of 2 5.34
32 R 47656	TR136	8.4	pkg. of 2 4.54
32 R 47673	TR146X*	8.4	Each 1.28
32 R 46782	TR163	4.2	pkg. of 2 3.68
32 R 47681	TR164	5.6	Each 1.67
32 R 46800	TR165	7.0	pkg. of 2 4.34
32 R 46816	TR169	12.6	Each 3.67
32 R 47699	TR175	7.0	Each 1.50
32 R 47707	TR177*	9.8	Each 1.67
32 R 47715	TR233	4.2	Each 3.00
32 R 46857 (AA)	ZM9	1.4	pkg. of 2 1.31
32 R 46965	ZM12	1.4	pkg. of 2 2.54
32 R 47723	PX1	1.35	pkg. of 4 3.26
32 R 47731	PX13	1.35	pkg. of 4 2.68
32 R 46864	PX23	5.6	pkg. of 4 2.68
32 R 46823	PX29	4.05	pkg. of 2 2.54

SILVER OXIDE BATTERIES

32 R 46956	MS13	1.5	pkg. of 6 2.19
32 R 46931	MS41	1.5	pkg. of 6 2.19
32 R 46849	MS76	1.5	pkg. of 6 3.00
32 R 47749	PX26	6.0	pkg. of 2 3.34

RECORDER BATTERIES

Stock No.	Type	Volts	Shpg. Wt.	Net
32 R 39035	2X7	10½	½ lb.	4.80
32 R 39050	2V18	12	½ lb.	2.00

INDUSTRIAL BATTERY TYPES

Lafayette Stock No.	Eveready	Replaces Burgess	Mfr's. Type R.C.A.	Voltage	Wt. lbs.	Net
32 R 39019	711	2FH	VS101	1½	¾	1.06
32 R 47137	W356	2F2H	VS136	3	1½	2.70
32 R 47160	750	422	VS134	¾	¾	1.20
32 R 47178	703	532	VS346	4½	¾	1.63
32 R 47202	781	5360	VS028	4½	¾	1.79
32 R 47228	773	5540	VS029	7½	½	2.50
32 R 47236	763	4156	VS102	2½	1	1.88
32 R 47444	778	5156SC	VS131	2½	1¾	5.45
32 R 47251	W350	Z30NC	VS114	2½	1¾	3.42
32 R 47293	7625	5308	VS112	45	¾	3.77

PORTABLE A TYPES

Lafayette Stock No.	"Eveready" No.	Burgess	R.C.A.	Replaces Manufacturer's Type	Dimen. in inches L x W x H	Voltage	Shpg. Wt. Lbs.	Net
32 R 48192	1050	230	VS336	1½ diam. x 2½	1½	½	.23	
32 R 48218	742	4F	VS004	2½ x 2½ x 3½	1½	½	1.15	
32 R 48226	964	—	VS236	1½ diam. x 4½	1½	½	.65	
32 R 48234	206	L6	VS327	4½ x 1½ x 2½	9	¾	.70	
32 R 48242	736	F3	VS067	3½ x 1½ x 5½	4½	1¼	2.50	
32 R 48267	718	ZF4	—	3½ x 2½ x 5½	6	3	3.22	
32 R 48275	724	24	VS068	1½ x 1½ x 2½	6	¾	1.34	
32 R 48283	744	F4P1	VS345	2½ x 2½ x 3½	6	1½	1.15	
32 R 48291	707	O5	VS315	2½ x 2½ x 2½	7½	1	2.50	
32 R 48309	713	85	VS129	3½ x 1½ x 2½	7½	½	2.85	
32 R 48317	717	C5	VS065	2½ x 1½ x 3½	7½	1	1.35	

PORTABLE B TYPES

32 R 48333	411	U10	VS083	1½ x 1½	15	¾	1.03
32 R 48341	417	K10	—	1½ x 1½	15	¾	1.67
32 R 48358	504	U10	VS704	1½ x 1½	15	¾	1.03
32 R 48366	412	U15	VS084	1½ x 2½	22½	¼	1.17
32 R 48374	420	K15	—	1½ x 2½	22½	¼	2.02
32 R 48382	505	V15	VS705	1½ x 1½	22½	¼	1.17
32 R 48390	413	U20	VS085	1½ x 2½	30	¾	1.30
32 R 48408	506	Y20	—	1½ x 2½	30	¾	2.53
32 R 48051	415	U30	VS086	1½ x 3½	45	¾	2.85
32 R 48424	455	UX30	VS055	2½ x 1½ x 3½	45	¾	1.46
32 R 48101	482	M30	VS013	3½ x 2½ x 5½	45	2¼	3.27
32 R 48432	484	B30	VS344	3½ x 2½ x 5½	45	3¾	3.77
32 R 48465	416	UX45	VS118	1½ x 1½ x 3½	67½	½	2.23
32 R 48473	457	K45	VS082	2½ x 1½ x 2½	67½	¾	2.97
32 R 48481	467	UX45	VS016	2½ x 1½ x 3½	67½	1	2.70
32 R 48489	477	P45	VS218	1½ x 1½ x 5½	67½	¾	3.05
32 R 48507	437	XX50	VS217	1½ x 1½ x 7½	75	1¼	3.77
32 R 48515	479	PC0	VS219	1½ x 1½ x 7½	90	1¼	2.98
32 R 48176	490	V60	VS090	3½ x 1½ x 3½	90	1½	3.40
32 R 48556	W361	XX69	—	1½ x 1½ x 11½	103½	1¾	5.44

PHOTOFLASH AND HIGH VOLTAGE TYPES

Stock No.	Eveready	Burgess	R.C.A.	Replaces Manufacturer's Type	Capacity	Wt.	Net
32 R 48564	493	U200	VS093	2½ x 2½ x 3¾	300	1¾	9.75
32 R 48804	497	U370	—	3 x 1½ x 5¾	510	2	13.00
32 R 48820	491	U160	—	2½ x 1½ x 4½	240	1	7.20

NICKEL CADMIUM RECHARGEABLE BATTERIES

Hermetically sealed steel nickel cadmium cells. High energy, long lasting, unaffected by idle periods. May be recharged many times. All are 1.25 average discharge voltage. All capacities rated in milliampere-ohm except † rated in ampere-hours.

Lafayette Stock No.	"Eveready" No.	Burgess	Manufacturer's Type	Cap.	Wt. In Oz.	Net
32 R 47467	B20	CD1	20B	20	3	1.44
32 R 47301	B50	CD2	50B	50	2	1.00
32 R 47327	*B100†	*CD8L	*100BL	100	2	1.29
32 R 47350	B225	CD4	225B	225	2	1.33
32 R 47368	*B25†	*CD4L	*225BL	225	3	1.48
32 R 47384	*B450†	*CD5L	*450BL	450	3	2.08
32 R 47392	*C450†	*CD6L	*475SCL	450	3	2.44
32 R 47400 (AA)	C450	CD6	475SCB	450	3	1.65
32 R 47418	CH1.2	—	1.25CB	1200	4	2.89
32 R 48887 (C)	CH1.5	CD14	2.05CB	1.5 †	5	3.90
32 R 48895 (D)	CH4	CD10	4.05CB	4 †	7	6.64

*Types with "†" or "L" identification have Tabs for Soldering to Cells

Popular Batteries at Popular Prices

Constructed To Lafayette's Rigid Specifications



- Fresh Stocks
- Extra Dependability
- Available in
- Standard Carbon-Zinc
- Extra Long Life
- Alkaline
- Nickel Cadmium

STANDARD BATTERIES

Stock No.	Volt-age	Net	Lots of 10	RCA	Replaces Mfr's Type	Bur- gess ready	Ever- ready	Shpg. wt.
99 R 62564	1½(D)	.18	1 50	VS036	2 950	5 oz. ea.		
99 R 62572	1½(C)	.16	1 30	VS035	1 935	4 oz. ea.		
99 R 62580	1½(AA)	.10	80	VS034	2 915	3 oz. ea.		

STANDARD 9-VOLT TRANSISTOR BATTERY

99 R 60212	9	.29	2 60	VS323	2U6 216	3 oz. ea.		
99 R 62796 Pkg. of 2 batteries Net per pkg. .55								

ALKALINE BATTERIES

These high energy Alkaline batteries provide up to 10 times longer life than ordinary zinc-carbon types in heavy and/or continuous drains, at all temperatures. Especially good for toys, photo, radios, tape recorders, record players and heavy-duty flashlights. Imported.

Stock No.	Volt-age	Net ea.	Mallory	Bur-gess	Ever-ready	Shpg. wt.
99 R 63786	1-½ (D)	.60	MN1300	AL2	E95	5 oz.
99 R 63802	1-½ (C)	.48	MN1400	AL1	E93	3 oz.
99 R 63828	1-½ (AA)	.42	MN1500	AL9	E91	2 oz.

MANGANESE ALKALINE BATTERIES

Up to 10 times longer life. Do not require rest period, operate with same efficiency in continuous or intermittent service.

Stock No.	Ever-ready	Mallory	R.C.A.	Bur-gess	Volt-age	Wt. Oz.	Per Pkg.	Net
32 R 46972	EPX825	PX-825	—	APX825	1.5	2	2	.99
32 R 48466(D)	E95	MN1300	VS1336	AL2	1.5	7	1	.85
32 R 47525(AA)	E91	MN1500	VS1334	AL9	1.5	4	2	.92
32 R 48879(C)	E93	MN1400	VS1335	AL1	1.5	4	1	.52
32 R 47541	E90	MN9100	VS1073	ALN	1.5	3	2	.79
32 R 4893(AAA)	E92	MN2400	VS1074	AL7	1.5	3	1	.86
32 R 46451	523	MN1306	VS1149	AL133	4.5	3	1	1.27
32 R 47426	563	—	VS1563	—	4.5	2	1	3.00
32 R 47434	564	—	VS1564	—	13.5	7	1	10.99
32 R 47533	—	MN1604	VS1323	—	9.0	4	1	.98

TRANSISTOR AND HEARING AID BATTERIES

Lafayette Stock No.	"Ever-ready"	Bur-gess	Replaces R.C.A.	Mfr's Type	Volt-age	Wt. Lbs.	Net
32 R 48192 (D)	1050	230	VS336	M13R	1.5	½	.23
32 R 47012 (C)	1035	13C	VS335	M14R	1.5	¼	.23
32 R 47020 (AA)	1015	930	VS334	M15R	1.5	¼	.19
32 R 47038	243	—	VS324	—	4½	¾	2.05
32 R 48077	216	2U6	VS323	M1604	9.0	¾	.54
32 R 47046	246	2NB	VS305	M1602	9.0	¾	1.50
32 R 48886	266	M6	VS322	M1605	9.0	¾	1.36
32 R 47053	276	D6	VS306	M1603	9.0	¼	1.67
32 R 47061	2506	D6P1	VS301	—	9.0	1¾	2.40
32 R 47079	239	KX9	VS304	—	13½	¼	2.40
32 R 47095	2356N	C6K	VS330	—	9.0	1	2.40
32 R 47129	226	P6	VS300A	M1600	9	¾	.79

FLASHLIGHT & LANTERN BATTERIES

32 R 48655 (AAA)	912	7	VS074	1½	¼	.16
32 R 47757 (AA)	915	910	VS034A	1½	¼	2 for .34
32 R 47509 (C)	935	1	VS035A	1½	¾	2 for .39
32 R 47491 (D)	950	2	VS036	1½	½	2 for .39
32 R 48671	735	410	VS106	1½	¼	1.06
32 R 48689	#6 Ign.	6 Ign.	VS006S	1½	2¾	1.13
32 R 48697	509	F4M	VS040C	6	1¾	1.13
32 R 48184	510S	F4BP	VS040S	6	1¾	1.13
32 R 48705	731	TW1	VS317	6	3¼	2.30
32 R 48713	706	4F4H	VS103	6	6¾	4.34
32 R 47772	732	TW2	VS342	12	3½	2.30
32 R 48754	904	NE	VS073	1½	¼	.10
32 R 48786	715	415H	VS139	7½	¾	5.30
32 R 47764	—	Z46HD	—	69	3¼	2 for 7.66

EXTRA LONG LIFE BATTERIES

Lafayette's extra long life batteries reduce the frequency of necessary replacement. They use a special chemical formulation which provides more than 50% longer useful life without either diminishing their shelf life or increasing battery weight.

Stock No.	Volts	Net.	Lots of 10	RCA	Bur- gess ready	Ever- ready	Shpg. wt.
99 R 63661	1½(D)	.25	2 80	VS036	2 950	5 oz. ea.	
99 R 63687	1½(C)	.22	1 80	VS035	1 935	4 oz. ea.	
99 R 63703	1½(AA)	.15	1 20	VS034	2 915	3 oz. ea.	

EXTRA LONG LIFE 9-VOLT TRANSISTOR BATTERY

99 R 63729	9	.45	3 60	VS323	2U6 216	4 oz. ea.	
------------	---	-----	------	-------	---------	-----------	--

AA NICKEL CADMIUM BATTERY

This Lafayette penlite nickel cadmium cell is manufactured to Lafayette's rigid specifications by one of America's best known manufacturers. Provides up to 500 charge-discharge cycles and the economies resulting from such recharging.

32 R 47400	1¼ (AA)	1.65	—	CD6	C450	3 oz. ea.	
------------	---------	------	---	-----	------	-----------	--

MALLORY EMERGENCY RESERVE DURACELL ALKALINE BATTERY

• 10 Year Emergency D Cell

These unique D size batteries hold their full power in reserve until activated, even 10 years from now. Ideal emergency power for auto, home, boat, schools, industry, etc. Easily activated by removal of clip which provides a brand new alkaline D cell. Shpg. wt., 13 oz.



KEYSTONE BATTERY HOLDERS


Battery Holders are made of Aluminum Alloy, sturdy construction with insulated, nickel plated Brass eyelets. All multiple holders mount batteries side by side except items marked *mount end to end. Av. shpg. wt., 3 ozs.



Stock No.	Holds	Burgess	Eveready	RCA	Mallory	Net Ea.
34 R 50012	1	—	—	VS074	—	.25
34 R 50020	2	7, AL7	912, E92	VS1074	MN2400	.62
34 R 50038	3	—	—	—	—	.41
34 R 50053	1	Z, 9R,	E9, E12,	—	RM12R,	.25
34 R 50061	2	Y15	E133, E502	VS034	TR133R,	.40
34 R 50087	3	CD6	505, 915	VS9	ZM-9,	.55
34 R 50095	4	—	1015E, C450	—	TR233R	.70
34 R 50103	1	—	—	VS035	MN1300	.33
34 R 50111	2	—	—	—	—	.40
34 R 50137	1	2, D,	935, E93	—	—	.33
34 R 50145	2	Z4	950, E95,	VS036	RM42R	.40
34 R 50152*	2	CD10	CH4	VS1336	—	.51

BATTERY CLIPS

Stock No.	Fig.	Avg. Shpg. Weight 2 oz.	For Burgess	Net Ea.
34 R 10016	A	—	P6, D5, P6M, M6, XX45, XX30, XX50	.07
34 R 10024	B	—	K45, P45, P45M, P60, D6, 4D4, N60X, C6X	.07
99 R 62879*	C	—	2U6, U30, 2N6	.29
99 R 62887*	C	—	same, pkg. of 5	.69
34 R 10040	D	—	XX50, P45, P60, N60X	.27



*Imported

Prices and Specifications are Subject to Change Without Notice

Battery Eliminators—Chargers

"STORAGE CELL" for TRANSISTOR RADIOS 9V BATTERY PLUS CHARGER


ONE CHARGEABLE BATTERY
OUTLASTS DOZENS OF
CONVENTIONAL BATTERIES

- Replaces Z06, Z16, and BL-006P
- Fluid Storage Type
- Plays About 15 Hours on One Charging
- Battery Recharges Overnight
- Complete—Battery Plus Charger



9V Battery complete with charger. Battery 1 1/2x1 1/4"; charger 3 3/4x 1 1/2x 7/8". Imported. Shpg. wt., 5 oz.
99 R 90169 Battery and Charger Net 2.89
99 R 60261 Battery Replacement for above Net 1.49

LAFAYETTE 9-VOLT TRANSISTOR RADIO BATTERY CHARGER AND ELIMINATOR



- Charge Battery, Operate Set On AC, or Both
- Isolation Transformer — Shock-Proof

3⁹⁹

Just plug into any 117-volt AC receptacle and recharge your old 9-volt battery for many hours of extra use, or operate your set indoors without using the battery at all, or you can both charge battery and operate set at the same time. Has 4-position switch for above functions plus off position and pilot light. Size 4Wx1 1/4xHx 2 1/4"D. Imported. Shpg. wt., 3/4 lb.
99 R 90219 Net 3.99

LAFAYETTE MULTI-PURPOSE BATTERY CHARGER



- Recharge All Popular Batteries—9V Transistor, AA Penlight, C And D Cells ... Up to 3 At One Time!
- Just Plug-In And Use

Designed to charge regular carbon zinc, nickel cadmium and alkaline batteries. Charges up to 3 batteries in a relatively short time for less than a penny. Two compartments automatically adjust to size of battery inserted, plus 2 snaps are provided for 9V... transistor radio batteries. Red light indicates charger is operating. For 110-120 volts 50/60 Hz AC. Imported. Shpg. wt., 3/4 lb.
99 R 92058 Net 2.95

UNIVERSAL 6 and 9 VOLT ADAPTER



- 6V 300Ma and 9V 250 Ma Outputs
- Reverse Polarity Connector
- Four Popular Terminations

3⁹⁰

This switchable 6 and 9 volt battery eliminator substitutes for batteries in nearly all radios, cassettes, phonos, recorders and other battery operated equipment when used with 117 V 50-60 Hz input. Reverse polarity connector (+ or — ground) assures proper function of equipment. Selector switch for choice of 6 or 9 V DC. Terminates in miniature plug, sub-miniature plug, and the two popular coaxial power jacks to fit nearly all equipment. Compact: 2 1/2x1 1/4x1 1/2". Imported. Shpg. wt., 12 oz.
34 R 27002 Net 3.90

UNIVERSAL 6, 7.5 AND 9 VOLT ADAPTER

This battery eliminator is same as above but has three-way switch to provide 7.5 volts in addition to 6 and 9 volts. Imported. Shpg. wt., 12 oz.
34 R 27010 Net 5.25

POWERHOUSE HOME BATTERY CHARGER



4⁷⁵

- Recharge Batteries Up to 15 Times
- Built-in Battery Tester
- "D" - "C" - "AA" and 9V Transistor Sizes

Recharge from one to five batteries at one time. Safely is assured since charger is in operation only when lid is closed. Plugs into standard 110-120 volt, 60 Hz AC outlet. Imported.
34 R 24017 Shpg. wt., 1 1/4 lbs., 5 oz. Net 4.75

BATTERY CHARGER WITH TWO RECHARGEABLE BATTERIES



**QUANTITIES
LIMITED 2⁹⁵**

- 2 D Type Batteries Included
- Recharges Batteries Overnight
- For Flashlights, Transistor Radios, Toys ...

Recharges any type D battery overnight. No longer must toys, transistor radios and flashlights be without "live" batteries. White plastic case with 2 rechargeable type D batteries. Replaces VS036, VS036, 2, 950 etc. Imported. Shpg. wt., 1 1/4 lbs.
99 R 91001 Charger and 2 Batteries Net 2.95

CHART CHARGE NICKEL-CADMIUM BATTERY CHARGER



- Charges 1 to 10 Cells in Series Up to 250 MA

Meets the demands of Nickel-cadmium cells in industrial and hobby use. Continuously variable from 10 to 250 MA to charge 1 to 10 cells in series. Use of isolation transformer eliminates shock hazard. Full wave silicon diode rectification. No meter is required for accurate calibration. Pilot light on-off indicator, UL listed. Cord. 6 1/2x3 3/4x2". Shpg. wt., 2 1/4 lbs.
34 R 41011 Net 10.50

AUTOMATIC DRY CELL BATTERY CHARGER



7⁵⁰

- Charge Up To 14 Batteries At A Time
- Uses AC Or DC Power Source
- Will Not Overcharge
- Built-in Battery Tester

Recharges all "D", "C", and 9-volt transistor carbon-zinc, alkaline, mercury, and nickel cadmium batteries. Charging receptacles for 4 "D" cells, 4 "C" cells, 6 "AA" cells and one 9V battery permits recharging up to 14 batteries at one time. Transformer circuitry operates on a demand principle and automatically prevents overcharging. Has built-in battery tester-indicator light. Shock-proof since low voltage charging occurs only when lid is closed. Attractive, decorator styled hi-impact plastic case. For 110-120 volt DC or AC 60 Hz. Size: 7 1/2x4 3/4x2 3/4". Shpg. wt., 1 1/2 lbs.
34 R 25006 Net 7.50

BATTERY HOLDERS



A. Ultra-compact bakelite battery case. Holds 8—1 1/2 volt (AA) penlight cells. 2 1/2" holes, 1 1/4" on centers for mounting. Size: 2 1/2x2 1/4x1 1/4". Imported. Shpg. wt., 1 1/2 oz.
99 R 63232 Net .69

Same as above except holds 10—1 1/2 volt (AA) penlight cells. Size: 2 1/2x2 3/4x1 1/4". Imported. Shpg. wt., 2 oz.
99 R 31353 Net .79



B. Battery holder for 4—1 1/2 volt (AA) penlight cells. Has snap-on battery clip and leads. Size: 1 1/2x1 1/4x2 1/4". Imported.
99 R 63315 Shpg. wt., 2 oz. Net .45

Resistors and Resistor Assortments

FIXED COMPOSITION RESISTORS

Moulded carbon resistors in 1/2 to 2 watt ratings, 5% & 10% tolerance. Made by leading American manufacturers such as Allen Bradley, Speer and IRC to high industry standards. Moulded bodies are insulated to have high breakdown resistance. All have E.I.A. color coded bands for positive identification of ohmage and tolerance. All are brand new factory fresh stock with full length leads.



HOW TO ORDER

Specify Stock Number from the price line, code number and ohmage from the tolerance chart.

EXAMPLE: For a 1/2 watt, 3900 ohm 10% resistor; order as 52 R 3087, 3900 ohms. For the same resistor with 5% tolerance; order as 52 R 8087, 3900 ohms.

10% RESISTORS — SELECT FROM CHART BELOW

STOCK NO.	WATTS	RANGE SEE CHART BELOW	Net Each				MAY BE ASSORTED			
			1-9	10-49	50-99	100 up	1-9	10-49	50-99	100 up
52 R 1	1/2	10 ohms to 22 meg	.24	.20	.16	.14				
52 R 2	1/4	2.7 ohms to 22 meg	.13	.11	.07	.05				
52 R 3	1/2	1 ohm to 22 meg	.12	.10	.08	.07				
52 R 4	1	2.7 ohms to 22 meg	.18	.15	.09	.08				
52 R 5	2	10 ohms to 22 meg	.24	.20	.15	.11				

CHART OF AVAILABLE 10% RESISTORS AND ORDERING CODE

Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Megs Code
1.0 001	10 025	120 051	1500 077	18K 103	220K 129	2.2 153		
1.2 003	12 027	150 053	1800 079	22K 105	270K 131	2.7 155		
1.5 005	15 029	180 055	2200 081	27K 107	330K 133	3.3 157		
1.8 007	18 031	220 057	2700 083	33K 109	390K 135	3.9 159		
2.2 009	22 033	270 059	3300 085	39K 111	470K 137	4.7 161		
2.7 011	27 035	330 061	3900 087	47K 113	560K 139	5.6 163		
3.3 013	33 037	390 063	4700 089	56K 115	680K 141	6.8 165		
3.9 015	39 039	470 065	5600 091	68K 117	820K 143	8.2 167		
4.7 017	47 041	560 067	6800 093	82K 119		10 169		
5.6 019	56 043	680 069	8200 095	100K 121	1.0 145	12 171		
6.8 021	68 045	820 071	10K 097	120K 123	1.2 147	15 173		
8.2 023	82 047	1000 073	12K 099	150K 125	1.5 149	18 175		
	100 049	1200 075	15K 101	180K 127	1.8 151	22 177		

5% RESISTORS — SELECT FROM CHART BELOW

STOCK NO.	WATTS	RANGE SEE CHART BELOW	Net Each				MAY BE ASSORTED			
			1-9	10-49	50-99	100 up	1-9	10-49	50-99	100 up
52 R 7	1/4	2.7 ohms to 22 meg	.26	.22	.14	.10				
52 R 8	1/2	1 ohm to 22 meg	.24	.20	.12	.09				
52 R 9	1	2.7 ohms to 22 meg	.36	.30	.18	.13				
53 R 1	2	10 ohms to 22 meg	.48	.40	.24	.19				

CHART OF AVAILABLE 5% RESISTORS AND ORDERING CODE

Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Ohms Code	Megs Code
1.0 001	11 026	20 051	1300 076	15K 101	180K 127	2.0 152		
1.1 002	12 027	130 052	1500 077	16K 102	200K 128	2.2 154		
1.2 003	13 028	150 053	1600 078	18K 103	220K 129	2.4 156		
1.3 004	15 029	160 054	1800 079	20K 104	240K 130	2.7 158		
1.5 005	16 030	180 055	2000 080	22K 105	270K 131	3.0 156		
1.6 006	18 031	200 056	2200 081	24K 106	300K 132	3.3 157		
1.8 007	20 032	220 057	2400 082	27K 107	330K 133	3.6 158		
2.0 008	22 033	240 058	2700 083	30K 108	360K 134	3.9 159		
2.2 009	24 034	270 059	3000 084	33K 109	390K 135	4.3 160		
2.4 010	27 035	300 060	3300 085	36K 110	430K 136	4.7 161		
2.7 011	30 036	330 061	3600 086	39K 111	470K 137	5.1 162		
3.0 012	33 037	360 062	3900 087	43K 112	510K 138	5.6 163		
3.3 013	36 038	390 063	4300 088	47K 113	560K 139	6.2 164		
3.6 014	39 039	430 064	4700 089	51K 114	620K 140	6.8 165		
3.9 015	43 040	470 065	5100 090	56K 115	680K 141	7.5 166		
4.3 016	47 041	510 066	5600 091	62K 116	750K 142	8.2 167		
4.7 017	51 042	560 067	6200 092	68K 117	820K 143	9.1 168		
5.1 018	56 043	620 068	6800 093	75K 118	910K 144	10 169		
5.6 019	62 044	680 069	7500 094	82K 119		11 170		
6.2 020	68 045	750 070	8200 095	91K 120	1.0 145	12 171		
6.8 021	75 046	820 071	9100 096	100K 121	1.1 146	13 172		
7.5 022	82 047	910 072	10K 097	110K 122	1.2 147	15 173		
8.2 023	91 048	1000 073	11K 098	120K 123	1.3 148	16 174		
9.1 024	100 049	1100 074	12K 099	130K 124	1.5 149	18 175		
10 025	110 050	1200 075	13K 100	150K 125	1.6 150	20 176		
				160K 126	1.8 151	22 177		

Prices and Specifications are Subject to Change Without Notice

MOST POPULAR KIT OF 100 CARBON RESISTORS 1/2 WATT — 10%

2⁹⁸



Designed especially for the serviceman. Here is a selection of 100 resistors of the most popular values used in general service work. All brand-new 1/2 watt 10%, full lead length resistors. Color coded. This is no random assortment. You get 3 each: 100, 470, 2200 ohms; 4 each: 1K, 4.7K, 22K, 27K, 33K, 47K, 15 meg, 27 meg, 2.2 meg, 5—10K; 10 each: 1 meg, 47 meg, 1 meg, plus 20 other popular values. Shpg. wt., 4 oz.

32 R 99047

Net 2.98

1/2 & 1 WATT CARBON RESISTOR ASSORTMENT




1⁹⁸

A value packed assortment of carbon resistors. Kit of 100 resistors consists of 75 1/2-watt and 25 1-watt resistors. Wide range of resistance value in varied tolerances. All have the standard RMA color code and normal length axial leads. Shpg. wt., 6 oz.

32 R 60007

Net 1.98

1 WATT CARBON RESISTOR KIT



1⁹⁸


- 50 Pieces
- Selected Values

Contains 2 each of the following selected values: 22 - 68 - 82 - 120 - 180 - 330 - 390 - 820 - 1500 - 2700 - 3000 - 4700 - 7500 - 8200 - 12K - 18K - 39K - 68K - 120K - 180K - 330K - 390K - 560K - 820K - 3.3 Meg.

32 R 60049

Shpg. wt., 5 oz. Net 1.98

1/4 WATT CARBON RESISTOR KIT



100 piece kit of 1/4 watt carbon resistors. Assortment of 33 selected values. Body size approx. 1/4" long x 3/16" dia. All ±10% tolerance. Shpg. wt., 3 oz.

32 R 60031

Net 1.98

OHMITE OHM'S LAW CALCULATOR



Solves Ohm's Law problems with just one setting of the slide. Has parallel resistance computing scales. Covers range from 0.01 ohm to 100 megohms. Current scale in amperes and milliamperes. Handy pocket size 9x3". Shpg. wt., 2 oz.

34 R 63023

Net .25



IRC RESISTOR O-GUIDE

Pocket size guide, identifies resistance

values and color code. Simply dial the colors or resistance values; corresponding data comes up automatically. MIL, EIA, and standard values listed on reverse side.

33 R 45436

Shpg. wt., 2 oz. Net ea. .20

Power Resistors—Variable Transformers

IRC PW-10 POWER RESISTORS



10 Watt wire wound resistors with axial leads. Rectangular ceramic body. 10% tolerance. Body size 1 1/8" Long x 3/8" square.

MALLORY ADJUSTABLE POWER RESISTORS



Same fine quality and construction as the fixed types, but with an exposed section of winding to provide tapping-off of resistance values from 0 to the max. value of the resistor. All with lug terminals, tolerance $\pm 10\%$, each supplied with 2 mg. feet and one adjustable clip. Type 2AV $3/4"$ dia. x 2" long, wt. 3 oz. Type 5AV $3/4"$ dia. x 4" long, wt. 4 oz. Type 10AV $3/4"$ dia. x 6 1/2" long, wt. 7 oz.

Stock No.	Ohms	Stock No.	Ohms	Stock No.	Ohms
33 R 46004	1	33 R 46202	300	33 R 46392	3300
33 R 46012	2	33 R 46210	350	33 R 46400	3500
33 R 46020	3	33 R 46228	400	33 R 46418	3900
33 R 46038	4	33 R 46236	500	33 R 46426	4000
33 R 46046	5	33 R 46244	600	33 R 46434	4500
33 R 46053	7.5	33 R 46251	700	33 R 46442	5000
33 R 46061	10	33 R 46269	750	33 R 46459	6000
33 R 46079	15	33 R 46277	800	33 R 46467	7000
33 R 46087	20	33 R 46285	820	33 R 46475	7500
33 R 46095	25	33 R 46293	900	33 R 46483	8000
33 R 46103	30	33 R 46301	1000	33 R 46491	8200
33 R 46111	40	33 R 46319	1200	33 R 46509	8500
33 R 46129	50	33 R 46327	1250	33 R 46517	9000
33 R 46137	75	33 R 46335	1500	33 R 46525	10K
33 R 46145	100	33 R 46343	1750	33 R 46533	12K
33 R 46152	120	33 R 46350	2000	33 R 46541	12.5K
33 R 46160	125	33 R 46368	2250	33 R 46558	15K
33 R 46178	150	33 R 46376	2500	33 R 46566	20K
33 R 46186	200	33 R 46384	3000	33 R 46574	25K
33 R 46194	250				

Shipping wt., 2 oz. Net ea. .36

TYPE 2AV—25 WATT ADJUSTABLE

Stock No.	Ohms	Net Ea.	Stock No.	Ohms	Net Ea.
30 R 43148	1	1.34	30 R 43288	500	1.34
30 R 43155	3	1.34	30 R 43304	1000	1.34
30 R 43163	5	1.34	30 R 43320	1500	1.39
30 R 43171	10	1.34	30 R 43338	2000	1.39
30 R 43189	15	1.34	30 R 43346	2500	1.39
30 R 43197	25	1.34	30 R 43387	5000	1.39
30 R 43205	50	1.34	30 R 43395	6000	1.49
30 R 43221	100	1.34	30 R 43403	7500	1.49
30 R 43239	150	1.34	30 R 43411	10K	1.49
30 R 43247	200	1.34	30 R 43429	12K	1.55
30 R 43254	250	1.34	30 R 43437	15K	1.55
30 R 43262	300	1.34	30 R 43445	20K	1.55
30 R 43270	400	1.34	30 R 43452	25K	1.63

TYPE 5AV—50 WATT ADJUSTABLE

Stock No.	Ohms	Net Ea.	Stock No.	Ohms	Net Ea.
30 R 43460	1	2.32	30 R 43585	500	1.81
30 R 43478	2	2.32	30 R 43601	1000	1.81
30 R 43486	5	2.32	30 R 43619	1500	1.86
30 R 43494	10	1.81	30 R 43635	2500	1.86
30 R 43502	25	1.81	30 R 43668	5000	1.86
30 R 43510	50	1.81	30 R 43684	10K	1.91
30 R 43528	75	1.81	30 R 43700	20K	2.01
30 R 43536	100	1.81	30 R 43718	25K	2.21
30 R 43551	200	1.81	30 R 43726	30K	2.21
30 R 43569	250	1.81	30 R 43742	50K	2.42
30 R 43577	400	1.81			

TYPE 2.5HJ—25 WATT FIXED

Stock No.	Ohms	Net Ea.	Stock No.	Ohms	Net Ea.
30 R 53683	1	.75	30 R 53840	1000	.75
30 R 53691	2	.75	30 R 53857	1500	.78
30 R 53709	3	.75	30 R 53865	2000	.78
30 R 53717	5	.75	30 R 53873	2500	.78
30 R 53725	7.5	.75	30 R 53899	3500	.78
30 R 53733	10	.75	30 R 53915	5000	.78
30 R 53741	15	.75	30 R 53949	10K	.93
30 R 53758	25	.75	30 R 53956	12.5K	.98
30 R 53766	50	.75	30 R 53964	15K	.98
30 R 53782	100	.75	30 R 53972	20K	.98
30 R 53808	200	.75	30 R 53980	25K	1.03
30 R 53816	250	.75	30 R 54004	40K	1.03
30 R 53824	500	.75	30 R 54012	50K	1.29
30 R 53832	750	.75	30 R 54038	100K	1.67

TYPE 10AV—100 WATT ADJUSTABLE

Stock No.	Ohms	Net Ea.	Stock No.	Ohms	Net Ea.
30 R 44021	1	2.28	30 R 44146	500	2.28
30 R 44039	2	2.28	30 R 44153	750	2.28
30 R 44047	5	2.28	30 R 44161	1000	2.28
30 R 44054	10	2.28	30 R 44187	2000	2.34
30 R 44062	25	2.28	30 R 44203	3000	2.34
30 R 44070	50	2.28	30 R 44245	10K	2.49
30 R 44088	100	2.28	30 R 44252	15K	2.62
30 R 44096	150	2.28	30 R 44278	25K	2.90
30 R 44104	200	2.28	30 R 44310	50K	3.24

Extra Feet		Extra Sliders	
Stock No.	Net ea.	For Use With	Stock No. Net ea.
30 R 48352	.06	25 and 50 Watt	30 R 49087 .18
30 R 48360	.10	100 Watt	30 R 49095 .18

STACO INC. VARIABLE AUTO-TRANSFORMERS



Made of a single-layer winding and high grade toroidal core. Sliding brush taps transformer to permit selection of output voltage. Brush is always in contact with at least

one turn of wire. †Deluxe types have circuit breaker, pilot light, banana jacks, on-off switch and 3 prong plug and receptacle. °Bench types are fused with pilot light & switch.

Stock No.	Mtg. No.	Fig.	Input			Output			Description	Size	Wgt.	
			Volts	Hz	Volts	Amps.	Lbs.	Net				
33 R 70343	171	F	120	50/60, 60	0-120, 0-132	1.75		For mounting in panels up to 1/4"	2 1/4" Dia. x 2 1/4" D.	2 1/2	12.00	
33 R 70335	251	F	120	50/60, 60	0-120, 0-132	2.50		For Mounting in Panels up to 1/2"	2 1/4" Dia. x 3 1/4" D.	3 1/4	13.00	
33 R 70327	371	J	120	50/60, 60	0-120, 0-140	3.75		For Mounting in Panels up to 1/2"	3 1/4" Sq. x 3 1/4" D.	6 1/4	18.00	
33 R 70319	501	J	120	50/60	0-120, 0-140	5.00		For Mounting in Panels up to 1/2"	4 3/4 x 3 3/4 x 3 3/4 D.	6 3/4	19.00	
33 R 70301	1010	J	120	50/60	0-120, 0-140	10.00		For Mounting in Panels up to 1/2"	5 3/4 x 5 x 4 1/4" D.	10 1/4	25.00	
33 R 70293X	1510	B	120	50/60	0-120, 0-140	15.00		For Mounting in Panels up to 1/2"	8 1/4 x 8 x 5 1/4" D.	20 3/4	48.00	
33 R 70285	1020	J	240	50/60	0-240, 0-280	3.5		For Mounting in Panels up to 1/2"	5 3/4 x 5 x 4 1/4" D.	10 3/4	30.00	
33 R 70277X	1520	B	240	50/60	0-240, 0-280	9.5		For Mounting in Panels up to 1/2"	8 1/4 x 8 x 5 1/4" D.	20	48.00	
33 R 70269	2PF171°	G	120	60	0-132	1.75		w/2 Cond., Cord., Plug & Socket	3 3/4 Sq. x 2 1/2	3 3/4	23.00	
33 R 70251	2PF501°	H	120	50/60	0-120, 0-140	5.0		w/2 Cond., Cord., Plug & Socket	6 1/4 x 5 3/4 x 4 1/2	10 1/4	28.00	
33 R 70244	3PN501°	H	120	50/60	0-120, 0-140	5.0		w/3 Cond., Cord., Plug & Socket	6 1/4 x 5 3/4 x 4 1/2	9 3/4	30.00	
33 R 70236	2PF1010°	C	120	50/60	0-120, 0-140	10.0		w/2 Cond., Cord., Plug & Socket	6 1/4 x 5 x 4 1/2	12 3/4	34.00	
33 R 70228	3PN1010°	C	120	50/60	0-120, 0-140	10.0		w/3 Cond., Cord., Plug & Socket	6 1/4 x 5 x 4 1/2	12	40.00	
33 R 70210X	3PN1510°	D	120	50/60	0-140	15.0		w/3 Cond., Cord., Plug & Socket	9 x 6 1/4 x 5 1/2	22	62.00	
33 R 70202W	EJ201V†	E	120	50/60	0-140	2.0 AC/DC	Deluxe	Isolated Type w/0-140 V. Meter	7 3/4 x 15 1/4 x 5 1/2	19 1/2	85.00	
33 R 70194W	EJ401V†	A	120	50/60	0-140	4.0 AC/DC	Deluxe	Isolated Type w/0-150 V. Meter	9 1/2 x 12 1/4 x 6 1/4	31	110.00	
33 R 70186W	EJ901V†	A	120	50/60	0-140	9.0 AC/DC	Deluxe	Isolated Type w/0-150 V. Meter	11 1/4 x 14 1/4 x 6 1/4	51	155.00	

Argonne®



- Nickel-Steel Laminations
- Mylar Outer Wrap
- Wound on Nylon Bobbins
- Color Coded Leads

Efficiently designed to meet the needs of miniaturization and engineered to provide excellent power handling capacity and frequency response with minimum distortion. All are nickel-steel laminations. Applications under "TYPE" show typical use. UBC is unbalanced current. Many units may be used for other applications as well. Average net weight 1 1/4 oz.: average shgp. wt., 4 oz. MADE IN U.S.A.

The Quality Line of Transistor Transformers

Singly EACH

298

PRICE SCHEDULE

QUANTITY BUYERS

- Lots of 10 Assorted 2.75
- Lots of 25 Assorted 2.50
- Lots of 50 Assorted 2.35
- Lots of 100 Assorted 2.20

WRITE FOR PRICES ON LARGER QUANTITIES

Applies to all units on this page except 33 R 85762, 33 R 85770, 99 R 60287.

ARGONNE HI-FI TRANSISTOR TRANSFORMERS



495

- Designed For Wide Range Transistor Audio Amplifiers
- 20-20,000 Hz ± 0.25 DB

Completely encased transformers specifically designed for use in transistorized, wide range, high fidelity audio amplifiers. Both driver and output have a frequency response of 20,000 Hz ± 0.25 db when used in properly designed circuits. At full power rating of 1.5 watts the same response may be achieved at ± 2 db. Size 1 1/2" x 1 1/2" x 1 3/4". Threaded mounting studs. Color coded leads. Shgp. wt., 6 ozs.

DRIVER TRANSFORMER

Primary impedance 5000 ohms, 3000 ohm center tapped secondary, DC resistance of primary 50 ohms, of secondary 75 ohms. Unbalanced primary current 20 ma DC.

33 R 85762 (Argonne AR-500) Net 4.95

OUTPUT TRANSFORMER

Primary impedance, 125 ohms center tapped. Secondary impedance, 8 ohms. DC resistance of primary is 4 ohms, of secondary, 0.8 ohms. Unbalanced primary current 50 ma DC.

33 R 85770 (Argonne AR-501) Net 4.95

LAFAYETTE 500-WATT VARIABLE VOLTAGE CONTROL

1595



- Input—115 Volts
- Output—0 to 130 Volts—Fused
- Linear Output from "No-Load" to "Full-Load"
- Excellent Regulation—Smooth Control

Precision, toroidal-wound core delivers full, rated output from 0 to 130 volts. Voltage variation is negligible from "no-load" to "full-load". Continuous, smooth, well regulated from zero to above input line voltage. Suitable for many industrial and laboratory applications, class room demonstrations, light dimming, motor control, model railroad and other hobby fields. Measures 5 1/2" x 5 1/2" overall. With 2-cond. outlet (fused at 5 amps), on-off switch and 6-ft. 2-cond. cord, tabs for bench or wall mounting. Shgp. wt., 10 lbs. Imported.

99 R 60287 Net 15.95

Replacement 5A fuse for above, (Pkg. 5 fuses)

13 R 10184 Net 5.4

Stock No.	Arg. No.	Type	IMPEDANCE		UBC*		Pwr		DC Ohms		Overall Size
			Pri.	Sec.	Pri.	DC	MA	M.W.	Pri.	Sec.	
33 R 85242	AR-141	Input	500,000	1,500 CT	.3	350	3600	60	1" x 3/4" x 3/4"		
33 R 85259	AR-142	Input	500,000	200 CT	.3	350	3500	20	1" x 3/4" x 3/4"		
33 R 85267	AR-143	Input	250,000	200 CT	.5	350	3600	20	1" x 3/4" x 3/4"		
33 R 85275	AR-144	Input	200,000	1,500 CT	.5	350	3000	65	1" x 3/4" x 3/4"		
33 R 85283	AR-100	Input	200,000	7,000	.5	100	3850	90	1" x 3/4" x 3/4"		
33 R 85291	AR-126	Input	150,000	1,500 CT	2.	100	3700	55	1" x 3/4" x 3/4"		
33 R 85309	AR-101	Input	100,000	3,000 CT	.5	100	3600	60	1" x 3/4" x 3/4"		
33 R 85317	AR-145	Input	100,000	2,000 CT	.5	350	3000	50	1" x 3/4" x 3/4"		
33 R 85325	AR-102	Input	100,000	1,500 CT	.5	100	3600	40	1" x 3/4" x 3/4"		
33 R 85333	AR-146	Input	100,000	50	.5	350	3000	1.6	1" x 3/4" x 3/4"		
33 R 85341	AR-127	Input	50,000	3,000 CT	1.	100	2000	50	1" x 3/4" x 3/4"		
33 R 85358	AR-128	Input	50,000	1,500 CT	2.	100	3000	50	1" x 3/4" x 3/4"		
33 R 85366	AR-129	Input	50,000	1,000	2.	100	2500	20	1" x 3/4" x 3/4"		
33 R 85374	AR-148	Input	50,000	500 CT	1.	175	1300	20	3/4" x 3/8" x 3/8"		
33 R 85382	AR-149	Input	50,000	200 CT	1.	175	1300	10	3/4" x 3/8" x 3/8"		
33 R 85390	AR-147	Input	50,000	30 CT	1.	175	1300	1.5	3/4" x 3/8" x 3/8"		
33 R 85408	AR-150	Input	40,000	100	1.	175	850	6	3/4" x 3/8" x 3/8"		
33 R 85416	AR-103	Driver	20,000	2,000 CT	1.	100	400	50	1" x 3/4" x 3/4"		
33 R 85424	AR-104	Driver	20,000	1,000	1.	100	400	50	3/4" x 3/8" x 3/8"		
33 R 85432	AR-151	Driver	20,000	800 CT	1.5	175	600	60	3/4" x 3/8" x 3/8"		
33 R 85440	AR-105	Driver	20,000	400	1.	100	600	30	1" x 3/4" x 3/4"		
33 R 85457	AR-130	Output	20,000	8	.5	100	400	0.6	3/4" x 3/8" x 3/8"		
33 R 85465	AR-131	Output	20,000	3.2	.5	100	400	0.3	3/4" x 3/8" x 3/8"		
33 R 85010	AR-106	Driver	16,000	4,000	1.	100	620	350	3/4" x 3/8" x 3/8"		
33 R 85028	AR-152	Driver	15,000	200 CT	1.5	175	550	10	3/4" x 3/8" x 3/8"		
33 R 85035	AR-107	Driver	15,000	200	1.5	250	1000	20	1" x 3/4" x 3/4"		
33 R 85044	AR-108	Driver	10,000	3,000 CT	1.5	100	200	100	3/4" x 3/8" x 3/8"		
33 R 85051	AR-109	Driver	10,000	2,000 CT	1.5	100	500	50	3/4" x 3/8" x 3/8"		
33 R 85069	AR-153	Driver	10,000	200 CT	2.	175	400	10	3/4" x 3/8" x 3/8"		
33 R 85077	AR-110	Output	10,000	16	2.	150	600	2.5	3/4" x 3/8" x 3/8"		
33 R 85085	AR-132	Output	10,000	8	1.	100	600	.6	3/4" x 3/8" x 3/8"		
33 R 85093	AR-133	Output	10,000	3.2	1.	100	600	.3	3/4" x 3/8" x 3/8"		
33 R 85101	AR-154	Input	5,000 CT	80,000	2.	175	350	1800	3/4" x 3/8" x 3/8"		
33 R 85119	AR-157	Input	5,000	45,000	2.	175	250	1600	3/4" x 3/8" x 3/8"		
33 R 85127	AR-156	Input	5,000	30,000	2.	175	150	1300	3/4" x 3/8" x 3/8"		
33 R 85135	AR-155	Input	5,000	10,000	2.	175	150	450	3/4" x 3/8" x 3/8"		
33 R 85143	AR-154	Input	5,000 CT	7,500 CT	2.	175	150	400	3/4" x 3/8" x 3/8"		
33 R 85150	AR-173	Driver	5,000	3,000 CT	2.	350	200	90	1" x 3/4" x 3/4"		
33 R 85168	AR-111	Output	5,000	100	1.	100	600	10	3/4" x 3/8" x 3/8"		
33 R 85176	AR-134	Output	4,000 CT	8	4.	250	150	.8	1" x 3/4" x 3/4"		
33 R 85184	AR-135	Output	4,000 CT	3.2	4.	250	150	.3	1" x 3/4" x 3/4"		
33 R 85192	AR-112	Output	3,500	200	1.	150	120	25	1" x 3/4" x 3/4"		
33 R 85200	AR-113	Driver	3,000 CT	1,000	9.	150	100	60	3/4" x 3/8" x 3/8"		
33 R 85278	AR-114	Output	2,500	11	10.	150	50	1.1	3/4" x 3/8" x 3/8"		
33 R 85226	AR-115	Input	2,000 CT	8	2.	150	150	660	1" x 3/4" x 3/4"		
33 R 85234	AR-116	Output	2,000	200	4.	250	120	20	1" x 3/4" x 3/4"		
33 R 85473	AR-175	Driver	2,000	1,500 CT	2.	350	150	60	1" x 3/4" x 3/4"		
33 R 85481	AR-159	Driver	1,500	500 CT	4.	175	100	20	3/4" x 3/8" x 3/8"		
33 R 85499	AR-136	Output	1,000 CT	100	4.	250	120	10	1" x 3/4" x 3/4"		
33 R 85507	AR-137	Output	1,000 CT	8	4.	250	120	.9	1" x 3/4" x 3/4"		
33 R 85515	AR-138	Output	1,000 CT	3.2	4.	250	120	.3	1" x 3/4" x 3/4"		
33 R 85523	AR-160	Output	800 CT	3.2	5.	175	40	.3	3/4" x 3/8" x 3/8"		
33 R 85531	AR-162	Output	500 CT	500 CT	5.	350	18	18	1" x 3/4" x 3/4"		
33 R 85549	AR-163	Output	500 CT	150 CT	5.	175	18	8	3/4" x 3/8" x 3/8"		
33 R 85556	AR-165	Output	500 CT	50	5.	175	18	4	3/4" x 3/8" x 3/8"		
33 R 85564	AR-118	Output	500 CT	16	5.	100	20	1.5	3/4" x 3/8" x 3/8"		
33 R 85572	AR-164	Output	500 CT	8	5.	175	18	.8	3/4" x 3/8" x 3/8"		
33 R 85580	AR-119	Output	500 CT	3.2	5.	100	20	.3	3/4" x 3/8" x 3/8"		
33 R 85598	AR-166	Output	400 CT	16	5.	175	16	1.3	3/4" x 3/8" x 3/8"		
33 R 85606	AR-120	Output	400 CT	11	1.	150	20	.9	3/4" x 3/8" x 3/8"		
33 R 85614	AR-167	Output	400 CT	8 or 3.2	5.	175	16	.6/3	3/4" x 3/8" x 3/8"		
33 R 85622	AR-168	Output	300 CT	16	6.	175	12	1.4	3/4" x 3/8" x 3/8"		
33 R 85630	AR-121	Output	300 CT	3.2	6.	150	20	.25	3/4" x 3/8" x 3/8"		
33 R 85648	AR-139	Output	250 CT	8	2.	250	15	.7	1" x 3/4" x 3/4"		
33 R 85655	AR-122	Output	250 CT	3.2	2.	150	11	.3	1" x 3/4" x 3/4"		
33 R 85663	AR-123	Output	200	2,000 CT	2.	150	11	50	1" x 3/4" x 3/4"		
33 R 85671	AR-124	Output	200 CT	16	2.	250	20	1.3	3/4" x 3/8" x 3/8"		
33 R 85689	AR-169	Output	200 CT	8 or 3.2	7.	175	9	.6/3	3/4" x 3/8" x 3/8"		
33 R 85697	AR-140	Output	200 CT	3.2	2.	100	10	.3	3/4" x 3/8" x 3/8"		
33 R 85705	AR-170	Output	160 CT	8 or 3.2	8.	350	10	.6/3	1" x 3/4" x 3/4"		
33 R 85713	AR-176	Output	125 CT	8	8.	350	4	.7	1" x 3/4" x 3/4"		
33 R 85721	AR-174	Output	100 CT	3.2	8.	350	6	.3	1" x 3/4" x 3/4"		
33 R 85739	AR-171	Output	100 CT	10 CT	10	175	4	.8	3/4" x 3/8" x 3/8"		
33 R 85747	AR-172	Output	48 CT	8 or 3.2	15.	350	2.3	.6/3	1" x 3/4" x 3/4"		
33 R 85754	AR-125	Input	3	4,000	15.	250	14	50	3/4" x 3/8" x 3/8"		

Prices and Specifications are Subject to Change Without Notice

Lafayette Cat. No. 720 251



Stancor Transformers

POWER TRANSFORMERS

All primaries 117 V 60 Hz. All 6.3V secondaries are C.T. except * and PC-8414 which has extra 6.3V 3.0A. winding Types with † are for selenium or silicon rectifier circuits or tubes such as 6AX5, 6X4, 6X5, etc. † Plate V. not center tapped. ♦ For half wave circuits. ◆ For full wave C.T. circuits.

Stock No.	Stan. No.	Plate YCT	MA	5V Amp	6.3V AMP	12.6V AMP	Size	Mtg. Type	Wt. lbs.	Net Each
33 R 80946*	PS-8415	125†	15	—	0.6	—	2x2½x1¾	S	¾	3.64
33 R 84633	P8624	125†	15	—	0.3	—	1½x2½x1½	A	½	3.64
33 R 84641	P8626	125†	50	—	0.1	—	2½x3½x2½	S	1½	5.69
33 R 84658	P8627	150†	25	—	0.3	—	2x2½x1¾	VE	½	5.37
33 R 80953*	PA-8421	125†	50	—	2.0	—	2½x3½x2½	A	2	5.69
33 R 80961*	PS-8416	250†	25	—	1.0	—	2½x2½x1¾	S	1½	4.66
33 R 84666	P8625	250♦	25	—	0.5	—	2½x2½x1¾	S	1	4.66
33 R 80979*	PC-8418	460†	50	—	2.5	—	3½x2½x2½	C	2½	7.61
33 R 81027	PM-8402	480	55	2.0	2.0	—	2½x2½x2½	M	2¾	9.71
33 R 81050*	PC-8419	480†	70	—	3.0	—	2½x2½x2½	C	3	8.94
33 R 81134	PC-8405	540	120	3.0	3.5	—	4x3½x3½	C	3½	12.47
33 R 80722	PC-8407	650	55	2.0	2.0	—	3½x2½x3½	C	3½	9.62
33 R 80763	PC-8409	700	90	2.0	3.0	—	3½x3x3½	C	4¾	13.15
33 R 80821	PC-8412	800	200	3.0	5.0	—	4½x4x4	C	9¾	19.03
33 R 80939	PC-8414	1200	200	3.0	3.0	—	4½x3¾x4	C	10½	22.80

FILAMENT/CONTROL/RECTIFIER TRANSFORMERS

All primaries are 117 volt 50-60 Hz AC except † which have a 117/107V and ‡ which have 230V. 50-60Hz.

Stock No.	Stan. No.	Volts	Secondary I Amperes	Insul.	Mtg. Type	Shpg. Wt. In Lbs.	Net Each
33 R 80847	P-6133	2.5 CT	5.0	7,500	S	1¾	6.64
33 R 84674	P-8628	2.5 CT	0.3	1,500	A	¼	2.37
33 R 84682	P-8629	2.5 CT	1.0	1,500	A	¼	2.30
33 R 80888	P-6467	5.0 CT	3.0	2,500	A	3	5.09
33 R 80490	P-6465	6.3 CT	.6	1,500	A	½	3.10
33 R 84690	P-8705#	6.3 CT	.6	1,500	A	½	3.10
33 R 80508	P-6134	6.3 CT	1.2	3,000	A	½	3.14
33 R 80516	P-8130	6.3	1.2	5,000	A	1¼	4.75
33 R 80557	P-6466	6.3 CT	3.0	2,500	A	1½	4.67
33 R 80615	P-3064	6.3 CT	6.0	2,500	BV	2¾	8.59
33 R 80631	P-6456†	6.3 CT	6.0	2,000	A	2	7.31
33 R 80649	P-6464	6.3 CT	10.0	2,000	C	3¾	9.47
33 R 80664	P-6309†	6.3 CT	20.0	2,500	BV	7¾	13.83
33 R 80698	P-6458†	10.0 CT	5.0	2,000	BV	3	9.16
33 R 81191	P-8130	12.6 CT	2.0	1,500	A	1½	4.84
33 R 84708	P-8715#	12.6 CT	2.0	1,500	A	1½	4.84
33 R 84716	P-8604	20.0 CT	1.0	1,500	A	1¼	4.00
33 R 81209	P-6469	25.2	1.0	1,500	A	1½	4.27
33 R 84724	P-8614	30.0	3.0	2,500	C	4¼	9.14

DRIVER TRANSFORMERS

All type A mtg, 10,000 ohm primary, single plate to push-pull grids. Use between first audio and push-pull output. Ratio is pri. to ½ Sec. *

Stock No.	Stan. No.	Max MA Pri. DC	Pri. Ohms	Ratio**	Size	Shpg. Wt.	Net Each
33 R 81217	A-4713	30	10,000	2:1	1½x2½x1½	½	4.02
33 R 81225	A-4723	30	10,000	3:1	1½x2½x1½	¾	3.77

ISOLATION TRANSFORMERS

All have 1500V Insul. † Pri. tapped for 125, 115 and 105V with 115V. Sec. * 117. Pri. and tapped sec. with sockets for 105, 115 and 125V. ‡ 115 V Pri. to 115V sec.

Stock No.	Stan. No.	Fig.	Size	Watts	Wt. Lbs.	Net Each
33 R 84807	P6413‡	A	1½x2½x1½	0.6	¼	2.40
33 R 82413	P-6410‡	K	3½x2½x2½	50	3¾	11.61
33 R 82421	P-6415*	KC	5¾x4½x5¾	350	18¾	38.20

CONTROL/RECTIFIER TRANSFORMERS

Automation-type transformer designed for high speed automatic equip. Adapted to relays and pilot lamps. Two secondary windings permit series or parallel operation. Primary 115 or 230V 50-60 Hz.

Stock No.	Mfr. No.	Fig.	Secondary		Size	Mtg. Ctr.	Wt. Lbs.	Net Ea.
			Parallel	Series				
33 R 82454	P-6377	J	12V at 4A	24V at 2A	3½x5½x2¾	3¼	2¾	7.76
33 R 82462	P-6378	BV	12V at 8A	24V at 4A	3½x2¾x3	2½x2½	4¾	12.66
33 R 82470	P-6379	BV	12V at 16A	24V at 8A	4½x3¾x3¾	3x2¾	5¾	22.92

MINIATURIZED CONTROL/RECTIFIER TRANSFORMERS

Primary 230V., 50-60 Hz.; Secondary 24V. CT Except * Is 36V. CT.

Stock No.	Stan. No.	Rms	Full-wave		Bridge	Mtg Type	Size	Wt. lbs.	Net Each
			.085	.135DC					
33 R 84732	P-8720	.085	.135DC	.055DC	A	2½x1½x1¼	¼	3.38	
33 R 84740	P-8722	.400	.550DC	.270DC	A	2½x1½x1½	½	3.55	
33 R 84757	P-8728*	.065	.075DC	.045DC	A	2½x1½x1¼	¼	2.85	

RECTIFIER TRANSFORMERS

Designed to operate in full-wave center-tapped or bridge type circuits. Each transformer has a tapped primary and a tapped additional winding permitting a wide range of output voltages. All are BV mtg. type. Primaries are for 117V 50/60 Hz AC operation. Supplied with wiring chart.

Stock No.	Stan. No.	Range of AV Volts		Max. D.C. Resistive		Output Lead Capacitive		Size	Wt. Lbs.	Net Ea.
		11.7 to 29.4	11.1 to 28.5	11.2V at 2.0A	23.0V at 1.25A	13.8V at 2.0A	30.0V at 1.25A			
33 R 82306	RT-201	11.7 to 29.4	11.1 to 28.5	11.2V at 2.0A	23.0V at 1.25A	13.8V at 2.0A	30.0V at 1.25A	3½x2½x2½	4½	9.74
33 R 82322	RT-204	11.7 to 29.2	11.6 to 29.2	12.0V at 8.0A	24.0V at 4.0A	14.5 at 8.0A	32.4V at 4.0A	3½x3¾x3¾	7½	16.51



Transformers-Voltage Regulators

STANCOR UNIVERSAL OUTPUT TRANSFORMERS

Match single or push pull plates to voice coil. All type A mtg.

Stock No.	Stan. No.	Primary	Watts	Size, Inch	Wt. Lbs.	Net Each
33 R 01258	A3822	7-10K	4	1 3/4x2 3/4x1 3/4	1/2	3.50
33 R 01274	A3825	1.5-4.5K	8	2x3 1/4x1 1/2	1	4.25
33 R 01308	A3830	3-10K CT	20	2 1/2x3 3/4x2 1/4	2	6.10
33 R 01324	A3849	1.5-10K	10	1 3/4x2 3/4x1 1/2	3/4	5.35
33 R 01332	A3852	4-14K CT	18	2 1/2x2 3/4x2	1 1/4	7.12
33 R 01360	A3855	4-14K CT	4	1 3/4x2 3/4x1 3/4	3/4	4.54
33 R 01360	A3870	4-14K CT	18	2x3 1/4x2	1 1/4	6.91

STANCOR FIXED OUTPUT TRANSFORMERS

All are type A mtg. except * is G. A3337 is type S mtg.

Stock No.	Stan. No.	Primary	Secondary	Watts	In Mtg. Centers	Wt. Lbs.	Net Each
33 R 01391	A2313	7,000	8	10	2 1/4"	1 3/4	3.87
33 R 01407	A3311*	10K CT	500/16/8/4	25	2 1/4x2	3 3/4	10.31
33 R 01415	A3327	25K	4	5	2	1/2	2.74
33 R 01423	A3328	4,000	3.5	3	1 3/4	1/2	2.24
33 R 01431	A3329	8,000	3.5	3	1 3/4	1/2	2.24
33 R 01449	A3332	2,000	3.2	3	1 3/4	1/2	2.65
33 R 01456	A3337	5K	6-8	10	2 3/4	1 1/2	3.85
33 R 01477	A3801*	6,500 CT	500/250/15/8/4	35	2 1/2x2 3/4	5 3/4	12.34
33 R 01480	A3831	10K CT	8/4/2	5	2 3/4	3/4	4.66
33 R 01490	A3857	25K CT	4	5	2	1/2	3.52
33 R 01506	A3876	2,000	4	5	2	1/2	2.37
33 R 01514	A3877	5,000	4	5	2	1/2	2.55
33 R 01522	A3878	7,000	4	5	2	1/2	2.72
33 R 01530	A3879	10,000	4	5	2	1/2	3.67
33 R 01548	A8093	10,000 CT	3-4	10	2 3/4	3/4	

STANCOR FILTER CHOKES

All rated 1500 V. ins. except * is 3000 V. ■ 2500 V. All type A mtg. except † are C and ▲ are BH.

Stock No.	Stan. No.	Hgs.	Ma	Ohms	Size	Wt. Lbs.	Net Each
33 R 01597	C-1003	16.0	50	580	2x3 1/4x1 3/4	1 3/4	3.86
33 R 01605	C-1080	8.5	50	200	1 3/4x1 1/2x2 3/4	3/4	2.97
33 R 01621	C-1279	8.5	50	400	1 3/4x2 3/4x1 1/2	3/4	3.30
33 R 01639	C-1325	5.0	50	250	1 3/4x2 3/4x1 1/2	3/4	2.97
33 R 01654	C-1411†	4.5	200	80	3 3/4x3 3/4	3 3/4	9.49
33 R 01686	C-1515	20	15	900	1 3/4x2 3/4x1 1/2	3/4	3.67
33 R 01704	C-1706	4.5	50	300	1 3/4x2 3/4x1 1/2	3/4	2.42
33 R 01712	C-1707	7.0	50	550	1 3/4x2 3/4x1 3/4	3/4	3.30
33 R 01738	C-1709	8.0	85	250	2x3 1/4x2	1 1/4	3.42
33 R 01829	C-2325	2.0	200	60	2 1/4x3 3/4x2 1/4	2	3.06
33 R 01870	C-2343	.75	300	32	1 3/4x2 3/4x1 1/2	3/4	3.15
33 R 01886	C-2344	1.5	10	85	1 1/4x2 1/4x1 1/2	1/2	2.58
33 R 01910	C-2685▲	.035	2A	.75	2 3/4x2 3/4x2 3/4	2 1/4	5.84

STANCOR LINE TO VOICE COIL TRANSFORMER

All are J type Mtg. except † 25V Type. ‡ 70.7V type § power steps in watts.

Stock No.	Stan. No.	Impedance	Sec.	Watts	Mtg. Ctrs.	Wt. Lbs.	Net Each
33 R 80060	A8101	500	6-8/3.2	5	2	1/2	2.90
33 R 80066	A8103‡	16/8/4/2/1/0.5§	4/8/16	16	2 1/4"	2	7.19

CONTROL/RECTIFIER TRANSFORMERS

Automation-type transformers designed for high speed automatic equipment. Primary 115 or 230V. 50-60Hz. Two secondary windings for series or parallel use.

Stock No.	Stancor No.	Mtg. Type	Secondary Parallel	Secondary Series	Watts	Wt. Lbs.	Net Each
33 R 04765	P-0615	J	24V./1.5A	48V./1.25A	2 1/2x2 1/4x1 3/4	2 3/4"	1
33 R 04773	P-0616	J	24V./1.1A	48V./1.5A	2 1/2x3 1/4x2	2 3/4"	1 1/2
33 R 04781	P-0617	J	24V./1.2A	48V./1.1A	3 1/4x3 3/4x2 1/4	3 1/4"	2 1/2
33 R 04789	P-0618	8V	24V./4.4A	48V./2.2A	3 3/4x2 3/4x2 3/4	2 1/4"	4 1/4

STEP DOWN AUTO TRANSFORMERS

230 to 115V. All supplied with 6 Heavy duty line Cord and built in receptacle.

Stock No.	Fig.	Wattage	Primary	Secondary	Wt. Lbs.	Net Each
33 R 80097	A	20	230V	115V	1 3/4	5.95
33 R 80105	A	40	230V	115V	2	6.50
33 R 80118	A	60	230V	115V	2 1/4	7.50
33 R 80014	A	100	230V	115V	3	8.85
33 F 80022	B	150	230V	115V	4 1/4	8.69
33 R 80030	B	250	230V	115V	6 1/4	12.55
33 R 80048	B	350	230V	115V	8 1/4	13.83
33 R 80055	B	500	230V	115V	10 1/4	17.23
33 R 80063	B	750	230V	115V	13 1/4	21.71
33 R 80071W	B	1000	230V	115V	16 1/2	28.49
33 R 80089W	B	1500	230V	115V	21 3/4	31.87

PERMA-POWER AUTOMATIC VOLTAGE REGULATOR

Completely automatic voltage control for color TV or appliances rated up to 400 watts. Simple plug-in installation. Automatically shuts off when set or appliance is not in use. Eliminates picture flutter, shrinking, brilliance loss, and other problems caused by line voltage drops. Shpg. wt. 4 1/4 lbs.

32 R 40058 Net 14.95
Similar to above 300 watts
32 R 40025 Net 9.95



AIR CONDITIONER AUTOTRANSFORMERS

STANCOR PSU3000. Especially designed for use with 1 to 2 ton home air conditioners having 1 to 2 HP. motors. Converts 208 volt unit to 230 volts or 230 volt units to 208 volt. Size: 4 x 6 x 4 1/2". Shpg. wt. 12 1/4 lbs. Net Ea. 33.43

33 R 82066 Wt., 12 1/4 lbs. Net Ea. 33.43



T.V. POWER TRANSFORMER

TYPE P-0356. Plate voltage 540 V.C.T. at 260 ma; filament windings 5 volt at 3 amp. 6.3 V at 8.8 amp. 117 V. 60 cycle AC input. Type C mtg. Size: 3 3/4x3 3/4x3 1/4".

33 R 82298 Wt., 6 1/2 lbs. Net 20.33

POLYPEDANCE MODULATION TRANSFORMERS

Fig. A. for transmitters to match class B modulators to class C load impedance. Primaries and secondaries multi-tapped to match loads from 2,000 to 20,000 ohms. Type A-3893. Rated 60 watts, primary and secondary 180 ma. Size: 4x3 1/4x4 1/4".

33 R 82074 Wt., 7 1/4 lbs. Net 26.99

Type A-3894. Rated 126 watts with 125 ma. windings. Size: 4 3/4x4 1/4x4 1/4".

33 R 82082 Wt., 10 3/4 lbs. Net 29.39

MICROPHONE TRANSFORMERS

A-4350. Fig. Q. For mike or line to line. Dual primary 500 and 200 ohm sections. C-T. pri. imp. 500/333/125/50. Sec. 500/333/200/125/50. Mtg. Centers 2 1/4". Size: 2x3 1/4x1 3/4".

33 R 81953 Wt., 1 1/4 lbs. Net ea. 6.86

A-4351. Fig. TD. For Mike or line to single grid. Dual primary 500 and 200 ohm sections. Pri. imp. 500/333/200/124/50. Sec. imp. 89000. Turns ratio 1:13.3. Mtg. Ctrs. 2 1/4x1 1/2". Size: 2 1/4x2 3/4x2 3/4".

33 R 82017 Wt., 1 3/4 lbs. Net ea. 7.47

A-4705. Fig. A. For single button mike to single grid. Pri. imp. 200/70. Sec. imp. 80,000. Turns ratio 1:20 Mtg. center. 2". Size: 1 3/4x2 1/4x1 3/4".

33 R 82033 Wt., 1/2 lb. Net ea. 4.59

ACME T8394M VARIABLE VOLTAGE ADJUSTER



300 W. continuous duty variable transformer. Adjusted by rotary tap sw. Used as step up or step down. Voltmeter shows sec. voltage. Pri. 95/100/105/110/120/125 volts at 50/60 Hz. Sec. out 115 V. 8" cord and plug. Size: 4 1/4x4 1/2".

33 R 80015 Wt., 6 1/4 lbs. Net 13.40

Transformers-Rectifiers

POWER/ISOLATION TRANSFORMER

- Ideal For Amplifiers, Intercoms and Receivers



249

Here is a versatile power transformer that is ideal for experimenters, hobbyists and constructors. Primary 117 volts and secondary 105 volts no-load—82 volts with 150 ma filament load. Literally hundreds of uses for this versatile unit. Minimizes the danger of shock by isolating circuits from the power line. Size: 2 1/4 x 2 x 1 1/2". Shpg. wt., 1 1/4 lbs. 33 R 75029 Net 2.49

UNIVERSAL POWER TRANSISTOR OUTPUT TRANSFORMER

- Designed For The Experimenter

- Pri. Tapped At 8-12-16-24-32 And 48 ohms

Rated 10 Watts

Engineered for construction projects using the increasingly popular power transistors. Will also serve as a general replacement for many transistorized auto radios. Rated at 10 watts for push-pull operation. Primary tapped at 8, 12, 16, 24, 32 and 48 ohms. Secondary tapped at 4, 8 and 16 ohms. Sizes: 3 1/2" x 2 1/4" x 2 1/4". Shpg. wt., 2 3/4 lbs. 33 R 75011 Type TR 94 Net 4.59

LINE-TO-VOICE COIL TRANSFORMERS

25 VOLT, 16 WATT LINE-TO-VOICE COIL

May be used with either 8 or 16 ohm speakers. 8 ohm speakers have choice of 4, 8 or 16 watt taps. 16 ohm speakers use 2, 4, 8 or 16 watt taps. Imported. Size: 2 3/4 x 2 1/4 x 2". Shpg. wt., 1 3/4 lbs. 99 R 63430 Net ea. 2.49

70 VOLTS, 10 WATT LINE-TO-VOICE COIL

70 volt line-to-voice coil matching transformer. Primary tapped 10, 5, 2.5, 1.25 and .625 watts. Secondary tapped 5, 8 and 16 ohms. Size: 2 1/2 x 1 1/2". Mtg. Centers 2 3/8". Imported. Shpg. wt., 3/4 lb. 99 R 62846 Net 1.99

Lots of 3 Ea., 1.89, Lots of 6 Ea., 1.50

POWER TRANSFORMER for SELENIUM RECTIFIER CIRCUITS

249

Most popular replacement power transformer for circuits using selenium rectifiers of rectifier tubes such as 6AX5, 6X4, 6X5. Primary is 117V 60 Hz A.C. Plate supply is 125 VAC 1/2 wave at 15 ma with 6.3V 0.6 amp filament winding. Size 2 x 2 3/8 x 1 1/8"; mounting centers 2". Shpg. wt., 3/4 lb. 33 R 34059 Net 2.49

SUBMINIATURE TRANSISTOR AUDIO TRANSFORMERS

ONLY 1/2" x 1/2" x 1/2"

A new series of miniature transformers for transistor and experimental miniature circuits. Ideal for miniature radio receivers, amplifiers, hearing aids, etc. using standard transistors. Incorporate special heat-treated high permeability magnetic cores treated to resist corrosion. Designed for improved frequency response with low distortion. 3" color-coded leads. Average shpg. wt., 2 oz. Imported



99c

Stock No.	Type No.	Circuit	Impedance Pri. Ohms	Sec. Ohms	D.C. Resistance Pri Ohms	Sec. Ohms	Net
99 R 61251	TR 97	INPUT	100,000	1000	1000	1000	.99
99 R 61269	TR 98	DRIVER	10,000	2000 C.T.	240	60 C.T.	.99
99 R 61277	TR 99	OUTPUT	500 C.T.	3.2	40 C.T.	0.7	.99
99 R 60345	TR 120	INPUT	200,000	1000	1400	50.5	.99
99 R 61293	TR 116	OUTPUT	500 C.T.	8	50 C.T.	1.7	.99

UNIVERSAL POWER TRANSISTOR OUTPUT TRANSFORMER

- Designed For High Output Transistors
- Used In Auto Radios PA Systems — Intercoms — Etc.



6 WATT OUTPUT TRANSFORMER

Rated 6 watts. Frequency response 70 to 20,000 Hz \pm 2 db. Primary Impedance 48 ohms center tapped. Secondary, 3.2 ohms; Primary DC resistance 1.1 ohms, secondary 0.3 ohms. Unbalanced primary current 500 ma DC. Size 1 1/2 x 1 1/2 x 1 1/2". Shpg. wt., 3/4 lb. 33 R 85788 Type AR-503 Net 1.95

INPUT TRANSFORMER

165



Rated 2 watts. Frequency response 70 to 20,000 Hz \pm 2 db. Primary Impedance 100 ohms. Secondary impedance 200 ohms CT. Primary DC resistance 1.8 ohms, secondary 2.7 ohms. Unbalanced primary current, 200 ma DC. Size: 1 1/2 x 1 1/2 x 1 1/2". Wt., 7 oz. 33 R 85796 Net 1.65

24-VOLT FILAMENT TRANSFORMER

219



Primary 117-Volt, secondary 24 Volts at 1 amp. Mounting centers 2 1/4". Size 2 1/4 x 1 1/2 x 1 1/2". Imported. Shipping wt., 1 1/2 lbs. 99 R 62663 Net 2.19

HIGH DENSITY SELENIUM RECTIFIERS

Replacements for radios, TV sets, Hi-Fi etc. 130 VAC input; 380 max. peak inverse volts. All have solder lugs. Avg. shpg. wt., 4 oz.



Stock No.	Ma	Net Each
33 R 45378	0-75	.59
33 R 45386	75-150	.75
33 R 45394	150-300	.92
33 R 45410	400-500	1.25
33 R 45345	750	1.86

TRANSISTOR OUTPUT TRANSFORMER



Only 3/8 x 1/2 x 1/4". 2000 ohm primary to 10 ohm voice coil.

Matches most transistor outputs. Shpg. wt., 3 oz. Imported. 99 R 61012 Net .79

MODULATION & AUDIO OUTPUT TRANSFORMER



Subminiature 3/4 x 3/8 x 5/8". Center-tapped primary; 2 secondary windings. Impedance: Primary—500 ohms C.T., secondary—8 ohms and 3K ohms. With schematic. Shpg. wt., 3 oz. 99 R 61327 imported Net .89

OUTPUT TRANSFORMER



Fig. A



Fig. B

50L6 OUTPUT

Fig. B. Matches 50L6, 35L6, 25L6, etc. to 3-4 ohm voice coil. Size: 1 1/2 x 1 1/4 x 1 1/8" with 1 3/4" mounting ctr. Shpg. wt., 5 oz. 33 R 37011 Net ea. .89

UNIVERSAL OUTPUTS

Fig. A. Match any single or push-pull output tubes to any voice coil. Shpg. wt., 3/4 lb. 33 R 75037 4-Watt Net ea. 2.54
33 R 75045 8-Watt Net ea. 3.06

6.3 VOLT FILAMENT TRANSFORMER

139



Primary 115 VAC. Secondary 6.3V. at 1 amp. Size: 1 3/4 x 1 1/2 x 1 1/2" with 2 1/4" mounting ctg. Shpg. wt. 1/2 lb. 33 R 37029 Net ea. 1.39

SARKS TARZIAN SILICON RECTIFIERS

RECTIFIERS

Stock No.	Fig.	Type	Shpg. wt., 2 oz.	Max DC	Max. Input PIV	Net VAC Ea.
33 R 59098	A	F-4	1 amp.	400	130	.56
33 R 59106	A	F-6	1 amp.	600	195	.60
33 R 59056	B	M-500	1 amp.	400	130	.96



HOLDERS FOR TYPE M500

13 R 62045	Single Holder	ea.	.22
13 R 62052	Dual Holder	ea.	.40

Mueller Clips and Insulators



MINI-GATOR CLIP (A)
*Cad. plated steel. †Solid copper. Length 1½", alligator jaws open ¾". #20 or smaller wire. Avg. shgp. wt., 2 oz.

Stock No.	No.	Each	Lots 10 Each	Lots 100 Each
32 R 35069	30*	.09	.06	.053
32 R 35389	30C†	.11	.08	.065

MICRO-GATOR CLIP (J)
Smallest made alligator clip for use on P.C. boards, tiny terminals, and other crowded spots. *Cad. plated steel. †Solid copper. #20 or smaller wire. Avg. shgp. wt., 2 oz.

Stock No.	No.	Size	Open	Net Each	Lots 10 Each	Lots 100 Each
32 R 35330	34*	15-	½"	.07	.05	.041
32 R 35340	34C†	15-	½"	.09	.06	.053

TEST CLIP WITH MESH TEETH (B)
Pee-Wee clip for general test purposes. Cad. plated steel except *C is solid copper. Avg. shgp. wt., 2 oz.

Stock No.	No.	Amp.	Size	Net Each	Lots 10 Each	Lots 100 Each
32 R 35017	48	5	1½"	.10	.07	.058
32 R 35025	48C*	10	1½"	.17	.12	.103

TWIN CLIPS (C)
Jaws of both ends operate independently. Cad. plated steel 2" long, jaws open ½". Shgp. wt., 2 oz.

Stock No.	No.	Each	Lots 10 Each	Lots 100 Each
32 R 35223	22	.15	.10	.087

FLEXIBLE INSULATORS

Avg. Shgp. wt., 4 oz.

Stock No.	Ins. No.	Color	Fits Clip Series	Net Each	Lots 10 Each	Lots 100 Each
32 R 35462	13	Red	11	.06	.60	.52
32 R 35470	13	Black	11	.06	.60	.52
32 R 35488	23	Red	21	.47	.33	.28
32 R 35496	23	Black	21	.47	.33	.28
32 R 35504	26	Red	24A & 25	.29	.20	.172
32 R 35512	26	Black	24A & 25	.29	.20	.172
32 R 35520	29	Red	27	.19	13	.115
32 R 35538	29	Black	27	.19	13	.115
32 R 35546	32	Red	30	.05	.03	.029
32 R 35553	32	Black	30	.05	03	.029
32 R 35561	36	Red	34	.05	03	.029
32 R 35579	36	Black	34	.05	03	.029
32 R 35587	47	Red	45	.08	05	.045
32 R 35595	47	Black	45	.08	05	.045
32 R 35603	49	Red	48 & 50	.12	.09	.073
32 R 35611	49	Black	48 & 50	.12	.09	.073
32 R 35629	62	Red	60	.06	.04	.035
32 R 35637	62	Black	60	.06	.04	.035
32 R 35645	87	Red	85	.08	05	.045
32 R 35652	87	Black	85	.08	05	.045

LAFAYETTE KIT OF 20 INSULATED ALLIGATOR CLIPS


Two kits of insulated alligator clips. Kit A consists of 20 large size clips, kit B consists of 20 small size clips. All have sturdy nickel-plated jaws with strong spring and hard bite. Each kit contains 10 red and 10 black alligator clips, carded and bagged. Imported. Shgp. wt., 8 oz.
 99 R 62356 Kit B (1½") Net 1.19
 99 R 62366 Kit A (2½") Net 1.59

KIT OF 10 JUMPER LEADS

10 handy 14" leads with miniature insulated alligator clips attached to each end. Clips and leads color coded. 5 pairs each a different color. Ideal for serviceman or experimenter. Imported. 99 R 00572 Shgp. wt., 5 oz. Net 1.19

KIT OF HEAVY DUTY JUMPER LEADS

Kit of 5 jumper leads each 48" long with battery clip terminations. Clip insulators and leads are color coded for easy identification. Imported. Shgp. wt., 8 oz. Net ea. 1.49



CROCOIL CLIPS (O)
*Copper, others cad. plated. † Has standard phone tip to one jaw. Avg. shgp. wt., 2 oz.

Stock No.	No.	Size	Conn.	Each	Lots 10 Each	Lots 100 Each
32 R 35140	65	2½"	Screw	.12	.08	.072
32 R 35157	65C*	2½"	Screw	.24	.17	.142
32 R 35165	65T†	2½"	Tip	.31	.22	.184

ALLIGATOR CLIPS (E)
*Copper, others steel. All fit banana plugs. Avg. shgp. wt., 2 oz.

Stock No.	No.	Size	Open	Conn.	Each	Lots 10 Each	Lots 100 Each
32 R 35173	80	2"	¾"	Std. Screw	.10	.07	.061
32 R 35181	80S*	2"	¾"	Screw	.12	.08	.070
32 R 35199	80CS*†	2"	¾"	Screw	.10	.13	.108

INSULATED ALLIGATOR CLIPS (F)
*Copper, others cad. plated steel. Size: 2½"-screw connections. Avg. shgp. wt., 2 oz.

Stock No.	No.	Color	Each	Lots 10 Each	Lots 100 Each
32 R 35421	60WS	Red	.16	.12	.098
32 R 35439	60NS	Black	.16	.12	.098
32 R 35447	60CS*†	Red	.22	.16	.134
32 R 35454	60CNS*†	Black	.22	.16	.134

BATTERY CLIPS STEEL AND COPPER (B)
*Are solid copper, all others are lead plated. Avg. shgp. wt., 8 oz.

Stock No.	No.	Amp.	Size	Net Each	Lots 10 Each	Lots 100 Each
32 R 35066	24A	25	2½"	.20	.20	.174
32 R 35074	21A	50	4"	.52	.36	.31
32 R 35082	11A	100	6"	1.44	1.01	.86
32 R 35371*	29C*	75	3"	.91	.36	.304
32 R 35059	21C*	100	4½"	1.34	.94	.80
32 R 35108	11C*	200	6"	2.65	1.85	1.59

3 SIDED MESH TEETH CLIPS
All steel cadmium plated except * is solid copper, † has insulation piercing needle in jaw. Avg. shgp. wt., 3 oz.

Stock No.	No.	Amp.	Size	Each	Lots 10 Each	Lots 100 Each
32 R 35033	48B	10	2"	.15	.10	.085
32 R 35041	48C*	20	2"	.22	.15	.13
32 R 35055	50C*†	30	2½"	.36	.25	.213
32 R 35116	27	20	2½"	.10	.12	.104
32 R 35124	27C*	40	2½"	.31	.22	.187

FULLY INSULATED ALLIGATOR CLIPS (K)
*Copper, †Cad. plated steel, 2½" long, shgp. wt., 1 oz.

Stock No.	No.	Color	Each	Lots 10 Each	Lots 100 Each
32 R 35660	63†	Red	.23	.16	.136
32 R 35678	63†	Black	.23	.16	.136
32 R 35686	63C*	Red	.27	.19	.162
32 R 35694	63C*	Black	.27	.19	.162

INSULATED ALLIGATOR TEST CLIPS WITH 6 FT. LEAD

Handy for quick connections. Plated brass alligator clip with insulated handles and 6 ft. of No. 22 stranded wire attached. Clip is 1½" overall. Imported. Shgp. wt., 2 oz.
 99 R 62317 Red Net ea. .19
 99 R 62325 Black 10 for 1.35

INSULATED ALLIGATOR CLIP

Sturdy nickel-plated brass jaws with plastic insulated thumb rest and insulated barrel. Strong spring with hard bite. Solder lug connection. Overall length 2½". Imported. Shgp. wt., 2 oz. Supplied in Red and Black.
 99 R 62192 Red Net ea. .12
 99 R 62208 Black 10 for .79

FAHNSTOCK CLIPS

Brass clips that assure good electrical contact without injury to wire. ¾" wide except * which are ½". Packages of 10. Shgp. wt., 4 oz.

Stock No.	Fig.	Lgth.	Max. Wire	Mfg. Note	Pkg. of 10
33 R 71010	B	1"	No. 10	No. 8	.30
32 R 76011	C	1½"	No. 10	No. 8	.32
32 R 64595	A	1½"	No. 10	No. 8	1.16
33 R 71028*	B	¾"	No. 14	No. 6	1.30

Sockets, Connectors, Test Adapters



BEAU PLUG CONNECTORS

Beauchaine Versatile 3300 plugs and sockets are reliable, versatile connectors for chassis or cable use. The cable type have scuff-resistant, insulated bakelite made of polypropylene plastic. (UL & CSA listed). Supplied complete with cable clamps. The recessed types have black wrinkle paint

over plated steel shell. All hardware is electroplated. Female contacts are cadmium plated phosphor bronze. Male contacts are cadmium plated brass. Contacts rated voltage 750 V RMS and a current capacity of 10 amp. Average shpg. wt., 4 oz.

SET OF 10 TRANSISTOR SOCKETS



only
98¢

A set of ten universal transistor sockets at a low Lafayette price. Ideal for experimenters, hobbyists and kit builders. For 3-pin transistors in-line or 4-pin types. Includes saddle mounts. Size: $9 \times 1 \frac{1}{4}$ ". 99 R 62614 Shpg. wt., 2 oz. Net .98

TRANSISTOR SOCKETS

Miniature transistor sockets of low loss mica filled phenolic. Contacts are of Beryllium copper, gold flashed over silver plate.



Stock No.	Fig.	Contacts	Net
32 R 42252	A	4	.11
32 R 42161	B	3	.12
32 R 42179	B	4	.12
32 R 42278	C	Ring for Fig. A	.02

ENCLOSED PLUG WITH CLAMP (FIG. A)

Stock No.	Mfg. No.	No. of Contacts	Net 1-24	Each 25-49
34 R 20015	P-3302-CCT	2	.65	.516
34 R 20023	P-3303-CCT	3	.68	.546
34 R 20031	P-3304-CCT	4	.70	.558
34 R 20049	P-3306-CCT	6	.78	.624
34 R 20056	P-3308-CCT	8	.83	.666
34 R 20064	P-3310-CCT	10	.94	.75
34 R 20072	P-3312-CCT	12	1.03	.822
34 R 20080	P-3315-CCT	15	1.35	1.08
34 R 20098	P-3318-CCT	18	1.59	1.272

ENCLOSED SOCKET WITH CLAMP (FIG. B)

Stock No.	Mfg. No.	No. of Contacts	Net 1-24	Each 25-49
34 R 20163	S-3302-CCT	2	.67	.534
34 R 20171	S-3303-CCT	3	.69	.552
34 R 20189	S-3304-CCT	4	.71	.564
34 R 20197	S-3306-CCT	6	.80	.642
34 R 20205	S-3308-CCT	8	.94	.75
34 R 20213	S-3310-CCT	10	1.04	.828
34 R 20221	S-3312-CCT	12	1.19	.954
34 R 20239	S-3315-CCT	15	1.49	1.194
34 R 20247	S-3318-CCT	18	1.73	1.386

ANGLE BRACKET PLUGS (FIG. C)

Stock No.	Mfg. No.	No. of Contacts	Net 1-24	Each 25-49
34 R 20312	P-3302-AB	2	.29	.234
34 R 20320	P-3303-AB	3	.35	.276
34 R 20338	P-3304-AB	4	.35	.282
34 R 20346	P-3306-AB	6	.44	.348
34 R 20353	P-3308-AB	8	.51	.408
34 R 20361	P-3310-AB	10	.58	.462
34 R 20379	P-3312-AB	12	.65	.522
34 R 20387	P-3315-AB	15	.91	.726
34 R 20395	P-3318-AB	18	1.10	.882

ANGLE BRACKET SOCKETS (FIG. D)

Stock No.	Mfg. No.	No. of Contacts	Net 1-24	Each 25-49
34 R 20460	S-3302-AB	2	.32	.252
34 R 20478	S-3303-AB	3	.36	.288
34 R 20486	S-3304-AB	4	.37	.294
34 R 20494	S-3306-AB	6	.47	.372
34 R 20502	S-3308-AB	8	.58	.462
34 R 20510	S-3310-AB	10	.69	.552
34 R 20528	S-3312-AB	12	.80	.642
34 R 20536	S-3315-AB	15	1.04	.834
34 R 20544	S-3318-AB	18	1.24	.99

DEEP BRACKET PLUGS (FIG. E)

Stock No.	Mfg. No.	No. of Contacts	Net 1-24	Each 25-49
34 R 20619	P-3302-DB	2	.72	.576
34 R 20627	P-3303-DB	3	.74	.588
34 R 20635	P-3304-DB	4	.75	.60
34 R 20643	P-3306-DB	6	.84	.672
34 R 20650	P-3308-DB	8	.91	.726
34 R 20676	P-3312-DB	12	1.10	.882
34 R 20684	P-3315-DB	15	1.34	1.074
34 R 20692	P-3318-DB	18	1.61	1.29

DEEP BRACKET SOCKETS (FIG. F)

Stock No.	Mfg. No.	No. of Contacts	Net 1-24	Each 25-49
34 R 20767	S-3302-DB	2	.72	.576
34 R 20775	S-3303-DB	3	.78	.624
34 R 20783	S-3304-DB	4	.80	.636
34 R 20791	S-3306-DB	6	.89	.714
34 R 20809	S-3308-DB	8	1.01	.804
34 R 20825	S-3312-DB	12	1.27	1.014
34 R 20833	S-3315-DB	15	1.51	1.206
34 R 20841	S-3318-DB	18	1.78	1.41

POMONA TEST ADAPTERS



Ideal for in-circuit checking of voltage, resistance, audio and video from above chassis. † for use in sockets having captive shields. Shpg. wt., 3 oz.

Stock No.	Type	Pins	Description	Each
33 R 57019	TVS-7	7	Miniature Octal	1.85
33 R 57027	TVS-8	8	Miniature Octal	2.15
33 R 57035	TVS-9	9	Miniature	1.95
33 R 57076	1779	9	Novar	2.25
33 R 57118	2497	9	Magnoval	2.75
33 R 57126	2610	10	Decal	2.55
33 R 57084	1710	10	Miniature	2.95
33 R 57043	TVS-12	12	Compaction	2.95
33 R 57050	1447	17	Miniature	1.95
33 R 57068	1449	17	Miniature	2.15

HORIZONTAL OUTPUT COLOR TEST ADAPTERS



For 6JE6, 6KM6. Test adapter with No. 3 Pin interrupted allows you to measure and adjust the cathode current of output tubes without removing chassis. Shpg. wt., 3 oz.
33 R 57092 Net 3.75
 For 6J6E, 6JM6. Similar to unit above, but with number 2 pin interrupted. WL 3 oz.
33 R 57100 Net 3.95

COMPACTRON SOCKET



Mica filled 12 pin tube saddle type socket with four ground lugs. Shpg. wt., 2 oz.
33 R 87016 Net .33

NOVAR SOCKET



Nine Pin (Novar) Socket with bottom mount saddle plate. Shpg. wt., 2 oz.
33 R 87255 Net ea. .20.

TV PICTURE TUBE SOCKETS




MOLDED: New all molded duo-decal socket for std. CRT's. Complete with back plate, contacts, hardware. Less leads.

18 R 27138	Shpg. wt., 4 oz.	Net .33
18 R 27153	Shpg. wt., 4 oz.	Net 1.05
110° Sylvania CRT Socket.	Wired for easy replacement with 18 inch leads.	
18 R 27161	Shpg. wt., 5 oz.	Net .99
110° RCA CRT Socket.	Wired for easy replacement, with 18 inch leads.	
18 R 27179	Shpg. wt., 5 oz.	Net .75
Color CRT Socket.	for 70° color tubes, wired with 18" leads. Shpg. wt., 7 oz.	
18 R 27203		Net 2.25
Color CRT Socket.	for 90° color tubes will accept either RCA or Motorola tubes. Wired with 18" leads. Shpg. wt., 9 oz.	
18 R 27195		Net 2.25

LOW LOSS TRANSISTOR SOCKETS

Transistor sockets with mounting ears for top mounting. Shpg. wt., 2 oz.
 3 Pin
33 R 87271 Net .60
 4 Pin
33 R 87289 Net .60



INTEGRATED CIRCUIT SOCKETS

For 14 and 16 pin in-line hybrid packages having .100"x.300" grid spacing. For round or flat pins, Phenolic body. Brass electroplated contacts. Shpg. wt., 2 oz.


Stock No.	Pins	Body	Net
32 R 65162	14	P.C.	.50
32 R 65170	16	P.C.	.50

NUVISTOR SOCKETS

5 and 7 pin sockets for nuvistor tubes. *are general purpose bakelite, † is mica-filled bakelite. Shpg. wt., 2 oz.

33 R 87198	† 5 Pin	Net ea. .27
33 R 87206	* 7 Pin	Net ea. .29

PRINTED CIRCUIT SOCKETS



MOLDED TYPE (A). All molded printed circuit socket. With mounting tabs for individual hole insertion.

33 R 87164	7 Pin	Net .16
33 R 87172	9 Pin	Net .20

TOP MOUNTING TYPE (B). Molded with tabs for top board mounting.

33 R 87123	7 Pin	Net .20
33 R 87131	9 Pin	Net .24
33 R 87149	octal	Net .48


TEST POINT ADAPTERS

FOR BLACK & WHITE TV Test socket adapter for black and white CRT's. Except 110°. Permits in-circuit checks from readily accessible lugs.

33 R 87248	Shpg. wt., 3 oz.	Net 1.20
110° test adapter for 8 pin TV picture tubes.		
33 R 57134	Shpg. wt., 3 oz.	Net 2.95
110° test adapter for 7 pin TV picture tubes.		
33 R 57142	Shpg. wt., 3 oz.	Net 2.95

ROBINS Sockets and Connectors

XLP AND XL CANNON AUDIO AND ELECTRONIC CONNECTORS



Dependable rugged construction. Features push-action Latch-Lock for locking mated fittings together securely, interchangeable and mates with Cannon XLR Connectors. Connectors have zinc alloy shell, phenolic insulator, and satin nickel finish. Avg. Shpg. wt., 5 oz.

PANEL AND WALL MOUNT RECEPTACLES

Stock No.	Mfr's. No.	Fig.	Contacts, Type Mount	Net Ea.
33 R 29174	XL-3-13	D	3-Socket, Wall or Panel	1.82
33 R 29463	XL-3-14	E	3-Pin, Wall or Panel	1.15
33 R 29208	XL-4-14	E	3-Pin, Wall or Panel	1.50
33 R 29215	XL-3-13H	F	3-Socket, Panel	2.37
33 R 29224	XL-3-14H	G	3-Pin, Panel	1.80
33 R 29240	XL-3-31	H	4-Socket, Wall	1.80
33 R 29257	XL-4-31	H	4-Socket, Wall	2.12
33 R 29265	XL-3-32	I	3-Pin, Wall or Panel	1.20
33 R 29471	XL-4-32	I	4-Pin, Wall or Panel	1.52
33 R 29281	XL-3-35	J	3-Socket, Wall, single gang	3.84
33 R 29289	XL-3-36	J	3-Pin, Wall, single gang	3.73
33 R 29307	XL-4-36	J	4-Pin, Wall, single gang	4.23
33 R 29315	XL-3-35-2G	K	3-Socket, Wall, two gang	7.42
33 R 29323	XL-3-36-2G	K	3-Pin, Wall, two gang	7.17

STRAIGHT CORD PLUGS AND SOCKETS

Stock No.	Mfr's. No.	Fig.	Contacts, Type Mount	Net Ea.
33 R 29050	XLP-3-11	A	3-Socket	1.70
33 R 29067	XLP-4-11	A	4-Socket	2.12
33 R 29075	XLP-3-12	B	3-Pin	1.62
33 R 29083	XLP-4-12	B	4-Pin	1.97
33 R 29448	XLP-3-15	C	3-Socket, Right Angle	4.15
33 R 29455	XLP-4-15	C	4-Socket, Right Angle	4.50

AMPHENOL RELAY SOCKETS

OCTAL TYPE Rugged, melamine sockets with high insulation barriers with long creepage paths. Rated 5 amp. 125OV RMS. *Has 4 molded-in threaded inserts for tie points. 103-104 are top mounted, 203 is bottom mounted. Shpg. wt., 4 oz.



Stock No.	Mfg. Type	Net Each
32 R 19045	146-103	1.64
32 R 19912	146-104*	2.04
32 R 19920	146-203	1.64

AMPHENOL OCTAL SADDLE SOCKET

No. 168-015. Steel mounting plate molded in black bakelite. Uses 1" mounting hole with 1 1/4" centers. Shpg. wt., 3 oz. 32 R 20951 Net ea. .32



AMPHENOL "FLOATING" SOCKET

Type 77-MIP8FK. Octal Socket with live rubber grommets fit into mtg. holes for vibration-free operation. Mounts above or below chassis in 1 1/4" dia. holes on 1 1/2" centers. With hardware. Shpg. wt., 3 oz. 32 R 19429 Net ea. .41



AMPHENOL "MIP" SOCKETS



Molded high dielectric black phenolic, with molded-in plate for 1 1/2" mounting centers. T type is mica-filled, 1 1/4" mounting hole except * 1 1/4" mtg. hole. 1 1/4" mtg. ctrs. † 1 1/4" mtg. hole. ‡ Octal socket. Avg. shpg. wt., 3 oz.

Stock No.	Mfg. No.	Prongs	Net Each
32 R 29415	77-MIP-4	4	.24
32 R 29423	77-MIP-5	5	.27
32 R 29431	77-MIP-6	6	.29
32 R 29456	77-MIP-7S	7S	.31
32 R 29464	77-MIP-8	8	.26
32 R 29472	77-MIP-8T	8	.28
32 R 29480	98-8	8	.28
32 R 29494	88-8X†	8	.44
32 R 29506	77-MIP-9	9	.30
32 R 19852	77-MIP-11	11	.31
32 R 20522	77-MIP-12	12	.36
32 R 29530	77-MIP-20‡	20	.70

AMPHENOL COAXIAL CONNECTORS



Series 83 UHF coaxial connectors for all RF applications. All connectors single contact except * are dual. Connectors mate by 3/4-24 thrd. couplings. Avg. shpg. wt., 3 oz.

Stock No.	Mfg. No.	Fig.	Military Number	Description	Net Each
32 R 19961	83-1AP	A	UG-646/U.M-359, 49192	Adapter, Right Angle	1.77
32 R 19987	83-1F	C	UG-363/U.PL-274, 491049	Adapter, Bulkhead	2.87
32 R 19995	83-1H	B	UG-106/U.M-360, 49193	Hood	.54
32 R 20019	83-1HP	B	UG-372/U.M-360, 49193	Hood	.50
32 R 20027	83-1J	C	PL-258, 49191	Adapter, Straight	1.21
32 R 20035	83-1R	D	SO-239, 49194	Receptacle	.58
32 R 20043	83-1SP	E	PL-259, 49190	Plug (Mica-Filled Bake)	1.19
32 R 20050	83-1SPN	E	PL-259A, 49195	Adapter, Tee	3.18
32 R 20068	83-1T	F	M-358, 49199	Adapter, Tee Receptacle*	4.50
32 R 20076	83-2R	—	UG1057	Plug	5.52
32 R 20084	83-21SP	E	UG-358/U	Adapter, Strt. Bulk*	4.17
32 R 20100	83-2F	—	PL-275	Receptacle*	1.30
32 R 20126	83-22R	—	UG-103/U.SO-264	Adapter, Right Angle	2.41
32 R 20159	83-58	A	M-359A, 49192A	Adapter, Reducing	.20
32 R 20167	83-168	—	UG-176/U	Adapter, Reducing	.19
32 R 20175	83-185	—	UG-175/U	Adapter, Reducing	.20
32 R 20183	83-750	E	UG-111/U	Plug (Teflon)	1.12
32 R 20191	83-756	E	PL-259A, 49195	Plug (Teflon)	1.73
32 R 20217	83-776	E	UG-203/U, 49482	Plug	1.76
32 R 20225	83-786	B	UG-203/U, 49482	Hood and Gang Nut	1.06
32 R 20233	83-798	D	SO-239A	Receptacle	1.47
32 R 20241	83-821	E	—	Plug*	2.42
32 R 20250	83-822	E	PL-259	Plug (Teflon)	.87

AMPHENOL TYPE BNC CONNECTORS

BNC SERIES. Compact "Quick-Connect-Disconnect" single contact bayonet type locking connectors. All are low voltage and weatherproof. *Resolite inserts †Teflon inserts.

Receptacle springs are made of beryllium copper. All other metallic parts are silver plated brass. Shpg. wt., 2 oz.

Stock No.	Mfg. No.	Fig.	Mfr. No.	Description	For RG Cable	Net Each
32 R 21101	31-003	A	UG-290/U	*Receptacle		.87
32 R 21199	31-203	A	UG-390A/U	*Receptacle		.93
32 R 21207	5575	B	UC625	*Receptacle		.83
32 R 21215	31-236	B	UG-258/U	*Receptacle		.86
32 R 21223	31-102	B	UG-657/U	*Receptacle		1.32
32 R 21231	31-221	B	UG1094/U	*Receptacle		.74
32 R 21249	31-002	C	UG-8/U	†Plug	55U, 58U	.74
32 R 21256	31-202	C	UG-8C/U	†Plug	55U, 58U	.80
32 R 21264	31-3202	C	UG-88C/U	†Plug	55U, 58U, 223	1.06
32 R 21272	31-012	C	UG-60U	*Plug	59U, 62U, 71U	.83



AMPHENOL 7 & 9 PIN SOCKETS



Amphenol sockets for TV, FM, auto radios, etc. 147-series connectors on 3/4" chassis hole. 59-series mounts in 3/4" hole with 1 1/4" mtg. ctrs., .095" rivet holes. †.125" rivet hole. ‡ Black Bakelite. † Mica-filled bakelite. Avg., 3 oz.

BOTTOM MOUNTING TYPE—FIG. (A)

Stock No.	Mfg. No.	No. of Cont.	Net Ea.
32 R 20787	147-500‡	7	.38
32 R 20795	147-505†	7	.39
32 R 20803	59-409†	9	.44
32 R 20811	59-410†	9	1.03

TOP MOUNTING TYPE—FIG. (B)

Socket with tube shield base to fit shields listed below.

Stock No.	Mfg. No.	Cont.	Net Ea.
32 R 20829	147-905‡	7	.46
32 R 20837	147-913‡	7	.46
32 R 20845	59-403‡	9	.72
32 R 20852	59-407†	9	.51
32 R 20860	59-406†	9	.53

TUBE SHIELDS—FIG. (C)

For 7-Contact Bases.	For 9-Contact Bases.		
32 R 20878	5-401	1 1/4"	.21
32 R 20886	5-402	1 1/4"	.22
32 R 20894	5-405	1 1/2"	.21
32 R 20902	5-408	1 1/4"	.25
32 R 20910	5-409	2 1/4"	.31

Amphenol Microphone and Audio Connectors



SERIES 75. PRESSURE TYPE — SINGLE CONTACT
Polished chrome plated brass fittings with $\frac{1}{8}$ "-27 thread, wt., 3 oz.

Stock No.	Type	Fig.	Description	Net Ea.
32 R 19060	75-MC1F	A	Cable plug	.70
32 R 19078	75-MC1M	B	Cable Jack Fits Above	.48
32 R 19086	75-PC1M	C	Receptacle, open	.48
32 R 19094	75-CL-PC1M	D	Receptacle, shorting	.68
32 R 19102	75-MC1F-A	E	90° cable jack	1.48
32 R 19110	75-MC1P	F	Phone plug Adapter	.68
32 R 19128	75-1	A	Min. Straight cable plug	.76
32 R 19136	75-2	B	Min. Cable Jack Fits Above	.90
32 R 19144	75-3	C	Min. Locknut receptacle	.93

SERIES 80. SINGLE AND DOUBLE CONTACT TYPES
For concentric lines, shielded mike cables, etc. Center contacts are pin and socket type. *Single-contact type. †Double-contact type. Av. shpg. wt., 3 oz.

Stock No.	Type	Fig.	Description	Net Ea.
32 R 19151	*80F	G	Female cable jack	.77
32 R 19159	*80C	H	Female chassis receptacle	.60
32 R 19177	*80M	I	Male cable plug	.76
32 R 19185	†80-MC2F	G	Female cable jack	.85
32 R 19193	†80-PC2F	H	Female chassis receptacle	.68
32 R 19201	†80-MC2M	I	Male cable plug	.80
32 R 19219	*80-F1	I	Female cable plug	.70
32 R 19227	*80-M1	G	Male cable jack	.76
32 R 19235	*80-C1	H	Male receptacle	.61
32 R 19243	†80-MC2F1	I	Female cable plug	.85
32 R 19250	†80-MC2M1	G	Male cable jack	.80
32 R 19268	†80-PC2M	H	Male receptacle	.66

75-CCC1—Cap and chain, used for 75 and 80 series seals open chassis against dirt and dust. Shpg. wt., 3 oz.
32 R 19276 1-49 ea. .47 50-99 ea. .40

MINIATURE PLUGS AND SOCKETS



Usable with 91-MPM, 91-MPF and 78-PCG miniature connectors. Supplied with push-on retainer rings. Need $\frac{3}{16}$ " hole. Av. T Type is MICA filled. Shpg. wt., 3 oz.

Stock No.	Socket Type	No. Contacts	Net Ea.
32 R 19631	78-S3S	3	.15
32 R 19649	78-S4S	4	.22
32 R 19656	78-S5S	5	.23
32 R 19664	78-S6S	6	.24


Stock No.	Plug Type	No. Contacts	Net Ea.
32 R 19698	71-3S	3	.16
32 R 19706	71-4S	4	.19
32 R 19714	71-5S	5	.20
32 R 19722	71-6S	6	.24

LAFAYETTE MINIATURE MICROPHONE CONNECTORS



(A) Microphone plug for CB and Amateur uses. Precision engineered and sturdily constructed. Plug takes any 4 conductor (or 3 conductor with shield) coiled cord or straight cable. Features threaded retaining ring for positive locking. Integral cable retaining clamp eliminates shorts and open connections due to cable strain. Polarizing keyway insures easy, properly orientated fit. May be used for any low voltage plug-in circuitry applications. Imported. Sizes: $\frac{1}{4}$ " x $\frac{1}{4}$ " Dia. Shpg. wt., 3 oz. Net 1.49
99 R 62630

(B) Microphone Chassis Socket. Mounts on equipment chassis or panel and mates with 99-62630 plug (shown above). Size $\frac{3}{4}$ " x $\frac{1}{4}$ " Dia. Requires $\frac{3}{16}$ " mounting hole. Imported. Shpg. wt., 3 oz. Net .89
99 R 62648



SERIES 91. 3- AND 4- CONTACT TYPES
Polarized microphone connectors for portable equipment. Strain-relieving clamps. *3-contact type. †4-contact type. Shpg. wt., 3 oz.

Stock No.	Type	Fig.	Description	Net Ea.
32 R 19284	*91-MC3F	J	Female cable jack	1.13
32 R 19292	*91-PC3F	K	Female chassis receptacle	.80
32 R 19300	*91-MC3M	L	Male cable plug	1.11
32 R 19318	†91-MC4F	J	Female cable jack	1.17
32 R 19326	†91-PC4F	K	Female chassis receptacle	.76
32 R 19334	†91-MC4M	L	Male cable plug	1.16
32 R 19342	*91-MC3F1	L	Female cable plug	1.18
32 R 19359	*91-MC3M1	J	Male cable jack	1.06
32 R 19367	*91-PC3M	K	Male receptacle	.72
32 R 19375	†91-MC4F1	L	Female cable plug	1.23
32 R 19383	†91-MC4M1	J	Male cable jack	1.11
32 R 19391	†91-PC4M	K	Male receptacle	.73

"QWIK" SERIES 91. 3- AND 4- CONTACT TYPES
New design. Simply pushed together; released by thumb pressure on lock button while pulling outward. Polarized contacts. Nickel plated shells. *3-contact type. †4-contact type. Av. shpg. wt., 4 oz.

Stock No.	Type	Fig.	Description	Net Ea.
32 R 19409	*91-853	M	Male cable plug	1.89
32 R 19417	*91-854	N	Female cable plug	2.31
32 R 19425	*91-855	D	Male chassis receptacle	1.47
32 R 19433	*91-856	P	Female chassis receptacle	3.48
32 R 19441	†91-857	M	Male cable plug	2.02
32 R 19458	†91-858	N	Female cable plug	2.85
32 R 19466	†91-859	D	Male chassis receptacle	1.59
32 R 19474	†91-860	P	Female chassis receptacle	3.75

91-CC3 Cap and chain. Used for the 91 series, seals open chassis units against dirt and dust.
32 R 19482 1-49 ea. .50 50-99 ea. .43

CABLE CONNECTORS

Shielded cap and rubber grommet-end opening. Consist of "S" type tube sockets and "CP" plugs with hoods. Avg. shpg. wt., 3 oz.

Stock No.	Female		
	Type	Cont.	Net Ea.
32 R 19730	78-PF4	4	.50
32 R 19748	78-PF5	5	.52
32 R 19755	78-PF6	6	.54
32 R 19763	78-PF7S	7S	.56
32 R 19771	78-PF8	8	.50
32 R 19789	78-PF9	9	.53
32 R 19797	78-PF11	11	.58

Stock No.	Male		
	Type	Cont.	Net Ea.
32 R 19805	86-PM4	4	.55
32 R 19813	86-PM5	5	.55
32 R 19821	86-PM6	6	.57
32 R 19839	86-PM7S	7S	.58
32 R 19847	86-PM8	8	.57
32 R 19854	86-PM9	9	.58
32 R 19862	86-PM11	11	.59
32 R 19870	86-PM12	12	.60

AMPHENOL TYPE 79-CC4 Cable-clamp used with above connectors to relieve strain on soldered connections. Wt., 2 oz.


Stock No.	Mfg. No.	Net Ea.
32 R 19896	79-CC4	.09

POPULAR MIKE CONNECTORS



Standard single contact, cord mounted, nickel plated brass, knurl grips. $\frac{5}{16}$ "-27 thread. Shpg. wt., 3 oz.
32 R 64173 Female connector Fig. A Net .39
32 R 64181 Male connector Fig. B Net .30

MINIATURE SHIELDED CONNECTORS



Molded bakelite cad. plated brass shells, for cables up to $\frac{1}{4}$ " Diam. PCG series take $\frac{7}{16}$ " hole. Suffix "L" indicates long— $\frac{1}{16}$ "; "S" indicates short— $\frac{1}{16}$ ". Shpg. wt., 3 oz.

Fig. A — Male			
Stock No.	Type	Cont.	Net Ea.
32 R 19490	91-MPM3L	3	.42
32 R 19508	91-MPM3S	3	.42
32 R 19516	91-MPM4L	4	.47
32 R 19524	91-MPM4S	4	.47
32 R 19532	91-MPM5L	5	.49
32 R 19540	91-MPM6L	6	.48

Fig. B Female			
Stock No.	Type	Cont.	Net Ea.
32 R 19557	91-MPF3L	3	.51
32 R 19565	91-MPF3S	3	.50
32 R 19573	91-MPF4L	4	.55
32 R 19581	91-MPF4S	4	.53

Fig. C Chassis Connectors for Above

Net Ea.			
32 R 19599	78-PCG-3	3	.50
32 R 19607	78-PCG-4	4	.59
32 R 19615	78-PCG-5	5	.62
32 R 19623	78-PCG-6	6	.63

MIKE ACCESSORIES



329 Switchcraft Microphone Volume Control Adapter. Reduce or Increase volume at the mike. For high impedance circuits using shielded single conductor cable only.
34 R 60078 Shpg. wt., 2 oz. Net 4.29
Amphenol Mike Switch. Attach between male and female of 75 series connectors. Push-to-talk with lock. Shpg. wt., 3 oz.
Amphenol 75-MC1S, Net 2.49
"T" Connector. Has 2 males and 1 female.
33 R 89012 Shpg. wt., 3 oz. Net 1.26

Plugs — Jacks — Binding Posts



INSULATED PLUGS

- Fig. A. Insulated Tip Plug. Heavy duty. Solder type. 1" handle. 2 1/4" overall.
- | | |
|------------------|-------------|
| 32 R 64645 Red | Net Ea. .17 |
| 32 R 64652 Black | 10 For 1.61 |
- Fig. B. Insulated Solderless Tip Plug. 1" handle. 2" length overall.
- | | |
|------------------|-------------|
| 32 R 64660 Red | Net Ea. .17 |
| 32 R 64678 Black | 10 For 1.61 |
- Fig. C. Insulated Short Tip Plug. Solder type. 1" handle. 1 1/4" overall length.
- | | |
|------------------|-------------|
| 32 R 64686 Red | Net Ea. .13 |
| 32 R 64694 Black | 10 For 1.23 |
- Fig. D. Insulated Banana Plug. Spring type. Internal set screw for soldering. 1" handle. 1 1/4" length overall. Phosphorbronze.
- | | |
|------------------|-------------|
| 32 R 64702 Red | Net Ea. .30 |
| 32 R 64710 Black | 10 For 2.85 |
- Fig. E. Solderless Insulated Banana Plug. Spring type. 1" handle. 1 1/4" overall.
- | | |
|------------------|-------------|
| 32 R 64728 Red | Net Ea. .25 |
| 32 R 64736 Black | 10 For 2.37 |
- Fig. F. Solderless Insulated Banana Plug. Split type. 1" handle. 1 1/4" overall.
- | | |
|------------------|-------------|
| 32 R 64744 Red | Net Ea. .20 |
| 32 R 64754 Black | 10 For 1.90 |
- Fig. G. Insulated Banana Plug. Spring type. 1" handle. 1 3/4" overall. Solder type.
- | | |
|------------------|-------------|
| 32 R 64769 Red | Net Ea. .25 |
| 32 R 64777 Black | 10 For 2.37 |
- Fig. H. Molded Meter Banana Plug.
- | | |
|------------------|-------------|
| 32 R 64785 Red | Net Ea. .40 |
| 32 R 64793 Black | 10 For 3.80 |
- Fig. J. Molded Meter Tip Plug.
- | | |
|------------------|-------------|
| 32 R 64801 Red | Net Ea. .30 |
| 32 R 64819 Black | 10 For 2.85 |
- Fig. K. Insulated Spade Lug. 3/4" handle. 1 1/2" length overall.
- | | |
|------------------|-------------|
| 32 R 64827 Red | Net Ea. .18 |
| 32 R 64835 Black | 10 For 1.71 |

INSULATED JACKS

- Fig. L. Phone Tip or Banana Plug. Mounts in 5/16" hole.
- | | |
|------------------|-------------|
| 32 R 64843 Red | Net Ea. .20 |
| 32 R 64850 Black | 10 For 1.90 |
- Fig. M. 5-way Binding Post. Takes phone tips, banana plugs, spade lugs, alligator clip, wire. All Insulated type.
- | | |
|------------------|-------------|
| 32 R 64868 Red | Net Ea. .45 |
| 32 R 64876 Black | 10 For 4.27 |
- Fig. N. Nylon All Insulated Tip Jack. 1" overall. Mounts in 3/8" hole.
- | | |
|------------------|-------------|
| 32 R 64884 Red | Net Ea. .20 |
| 32 R 64892 Black | 10 For 1.90 |
- Fig. P. Insulated Tip Jack. 1 1/4" overall length. Mounts in 5/16" hole.
- | | |
|------------------|-------------|
| 32 R 64900 Red | Net Ea. .15 |
| 32 R 64918 Black | 10 For 1.42 |
- Fig. Q. Nylon Insulated Tip Jack. With nylon washer. 1" overall length. Mounts in 5/16" hole.
- | | |
|------------------|-------------|
| 32 R 64926 Red | Net Ea. .27 |
| 32 R 64934 Black | 10 For 2.56 |
- Fig. R. Insulated Banana Jack. 21/32" overall length. Mounts in 5/16" hole.
- | | |
|------------------|-------------|
| 32 R 64942 Red | Net Ea. .15 |
| 32 R 64959 Black | 10 For 1.42 |
- Fig. S. Instrument Banana Jack. 27/32" overall length. Mounts in 5/16" hole.
- | | |
|------------------|-------------|
| 32 R 64967 Red | Net Ea. .18 |
| 32 R 64975 Black | 10 For 1.71 |
- Fig. T. Nylon Insulated Banana Jack. With nylon washer. Overall length 53/64". Mounts in 5/16" hole.
- | | |
|------------------|-------------|
| 32 R 64983 Red | Net Ea. .25 |
| 32 R 64991 Black | 10 For 2.37 |

METAL JACKS

- Fig. U. Metal Tip Jack. Mounts in 1/4" hole.
- | | |
|-------------|---------------|
| 32 R 64371 | Net ea. .15 |
| 10 for 1.35 | 100 For 12.50 |
- Fig. V. Metal Banana Jack. Mounts in 1/4" hole.
- | | |
|-------------|---------------|
| 32 R 64389 | Net ea. .15 |
| 10 for 1.35 | 100 For 12.50 |
- Fig. W. Metal Banana Jack. Mounts in 1/4" hole.
- | | |
|-------------|---------------|
| 32 R 64397 | Net ea. .15 |
| 10 for 1.35 | 100 For 12.50 |
- Fig. X. Solderless Phone Tip. Sr. 1 1/2" long.
- | | |
|-------------|---------------|
| 32 R 64405 | Net ea. .15 |
| 10 for 1.35 | 100 For 12.50 |

NON-INSULATED PLUGS

- Fig. Y. Solderless Phone Tip. Jr. 1 1/4" long.
- | | |
|-------------|---------------|
| 32 R 64413 | Net ea. .15 |
| 10 for 1.35 | 100 For 12.50 |
- Fig. Z. Banana Plug. Spring type. 1 1/2" overall. 6-32 x 1/2" stud.
- | | |
|-------------|---------------|
| 32 R 64421 | Net ea. .25 |
| 10 for 2.37 | 100 For 22.00 |
- Fig. AA. Banana Plug. Spring type. Screw in head. 1 1/2" overall.
- | | |
|-------------|---------------|
| 32 R 64439 | Net ea. .25 |
| 10 for 2.37 | 100 For 22.00 |
- Fig. BB. Banana Plug. Spring type. 1 1/4" overall. 6-31/32" stud.
- | | |
|-------------|---------------|
| 32 R 64447 | Net ea. .25 |
| 10 for 2.37 | 100 For 22.00 |
- Fig. CC. Banana Plug. Split Type. 1 1/4" overall. 6-32 x 1/2" stud.
- | | |
|-------------|---------------|
| 32 R 64454 | Net ea. .17 |
| 10 for 1.61 | 100 For 15.30 |

SMITH DUAL BANANA PLUG



No. 210 moulded polystyrene dual binding post with brass nickel plated plugs on 3/4" centers. Mates with standard binding posts. Polarity indicated on top and side. Wire held by internal set screw. May be stacked. Shpg. wt., 3 oz.

32 R 65048 Black	Net .72
32 R 65055 Red	Net .72

SMITH TEST PRODS

Brass, nickel plated plugs mounted in 4" molded butyrate handles. Shpg. wt., 2 oz.



- | | |
|-----------------------------------|---------|
| No. 302 Solderless Test Prod Type | |
| 32 R 65063 Red | Net .30 |
| 32 R 65071 Black | Net .30 |

- | | |
|--------------------------------|---------|
| No. 317 Phono Needle Test Prod | |
| 32 R 65089 Red | Net .33 |
| 32 R 65097 Black | Net .33 |

SMITH "SPEEDI-MOUNT" JACKS



Unusual dished lockwasher permits fast assembly. Teeth embed into jack and panels, prevents pulling out and turning. Mounts in 3/8" hole in panels up to 3/8" thick. Shpg. wt. 2 oz.

- | | |
|------------------------------|---------|
| No. 279 Accepts Tip Jacks | |
| 32 R 65105 Red | Net .08 |
| 32 R 65113 Black | Net .08 |
| No. 398 Accepts Banana Jacks | |
| 32 R 65121 Red | Net .08 |
| 32 R 65139 Black | Net .08 |

LAFAYETTE KIT OF 10 5-WAY BINDING POSTS

- For Banana Plug
- For Phone Tip Plug
- For Spade Lug
- For Alligator Clip
- For Strand of Wire

For panels 3/8" to 1/4" thick. Assortment of 10 pieces. 5 Red and 5 Black. Imported. Shpg. wt., 4 oz.

99 R 62333 Binding Post Kit	Net 1.09
-----------------------------	----------



ULTRA MINIATURE PLUG & JACK



Plug is 1/4" overall. Pin Dia. 3/32". Jack mounts on panels up to 3/32" thick. Requires 3/32" mtg. hole. Extends 1/2" behind panel, circuit jack can be used open or closed. Shpg. wt., 2 oz. Imported.

- | | |
|------------|---------|
| 99 R 63141 | Net .30 |
|------------|---------|

LAFAYETTE JUMBO 5-WAY BINDING POSTS

29^c




This versatile binding post is designed to accept spade lugs, phone tip lugs or wire which is held firmly in place by tightening down the head. Adequate room is allowed for connections with alligator plugs. Banana plugs will firmly seat in the top mounting hole. May be mounted in panels from 1/4" to 1/2" thickness. Sturdily made with non-movable head piece. Imported. Shpg. wt., 2 oz.

- | | |
|------------------|---------|
| 99 R 61202 Black | Net .29 |
| 99 R 61210 Red | Net .29 |

Make Lafayette Your One Dependable Source for Everything in Electronics

LAFAYETTE Plugs And Jacks

STANDARD LAFAYETTE 2-CONDUCTOR PHONE PLUGS




Phone plugs for a wide variety of applications with choice of handle sizes and materials. All sleeves fit standard 1/4" phone jacks. Avg. shpg. wt., 3 oz.
FIG. A. SLIM PHONE PLUG Smooth bakelite handle. Solder terminals with cable clamp. Imported.
 99 R 62218 Net .30 ea. — 10 for 2.50
FIG. B. BARREL PHONE PLUG Ribbed plastic barrel handle. Screw terminals. Imported.
 99 R 62234 Net .35 ea. — 10 for 2.89
FIG. C. SHIELD SLIM PHONE PLUG Ribbed chromed metal handle. Solder terminal with cable clamp. Imported.
 99 R 62150 Net .49 ea. — 10 for 4.19
FIG. D. PHONE TO PHONO PLUG ADAPTER. Adapts from standard phone plug to RCA type phono plug. Overall length 2 1/4 x 1/2" diameter. Imported.
 99 R 62168 Net .69

STANDARD LAFAYETTE PHONE JACKS FOR 1/4" PLUGS




FIG. E. OPEN CIRCUIT JACK Standard open circuit phone jack. 3/4" bushing. 1/2" long. Complete with mounting hardware. Imported.
 99 R 62135 Net .30 ea. — 5 for 1.29
FIG. E. CLOSED CIRCUIT JACK Same as above but closed-circuit phone jack. Imported.
 99 R 62226 Net .30 ea. — 5 for 1.29
FIG. F. EXTENSION CABLE JACK Fit standard 1/4" phone plug. Screw terminals. Barrel plastic handle matches Barrel plug above. Imported. Shpg. wt., 3 oz.
 99 R 62143 Net .39 ea. — 3 for .99

PHONO PLUGS AND JACKS



(A) Single Prong Shielded Plug—RCA type, used extensively for mike, phono, etc. Shpg. wt., 3 oz.
 32 R 64579 10 for .56 singly, ea. .07
(B) Phone Jack—Accepts RCA type phono plug. Mounts in rear of panel. Shpg. wt., 3 oz.
 32 R 64587 10 for .79 singly, ea. .09
(C) Finger grip plug—Phone plug with finger grip. Wt., 2 oz.
 32 R 78173 10 for .90 singly, ea. .10
(D) Feed Thru—Accepts male phono plug at both ends. Shpg. wt., 3 oz.
 32 R 52012 Ea. .49

LAFAYETTE FLAT PHONE PLUG



Two conductor all metal phone plug for standard 1/4" jack, body only 3/8" thick. Shielding crimps to body, center lead to solder terminal. Imported. Shpg. wt., 2 oz.
 99 R 62708 Net ea. .45

PHONO PIN JACK SINGLE HOLE MOUNTING



RCA type female input jack. Mounts securely in single 1/4" hole by means of locknut on jack. Screws, nuts and washers unnecessary. Imported. Shpg. wt., 3 oz.
 99 R 62341 4 for .88 Singly ea. .25

ULTRA MINIATURE PLUG & JACK



Plug is 3/16" overall. Pin Dia. 3/32". Jack mounts on panels up to 3/32" thick. Requires 3/32" mtg. hole. Extends 1 1/2" behind panel. 3 circuit jack can be used open or closed. Shpg. wt., 2 oz. Imported.
 99 R 63141 Net .30

SUB-MINIATURE PLUG ADAPTER



Provides Extra Earphone Jack for Transistor Radios

79¢

A sub-miniature combination plug and jack designed for most transistor radios with earphone jacks. Just plug it in and you have 2 jacks for earphones, speakers, etc.—can be used in instruments provided with 1/8" Dia. earphone jack. Overall size: 2 1/4 x 1/4 x 3/4" D. Shpg. wt., 2 oz. Imported.
 99 R 63109 Net .79

SUBMINIATURE PHONE PLUG AND JACK



Sub-miniature "phone plug" and Jack. Only 1" long x 1/4" diameter, overall. Pin Dia. 1/8". Excellent for transistor and subminiature applications. Plug has removable sleeve. Jack can be mounted on panel up to 3/8" thick. Jack can be used for both open and closed circuits. Imported. 3 oz.
 99 R 62101 Plug Net .25
 99 R 62119 Jack Net .23

PHONE PLUG TO PHONO JACK ADAPTER



79¢

Brass, nickel-plated adapter. Has standard phone jack on one end to take regular phone plug, and RCA-type phono plug on other end. Has threaded bushing with nut and washer so can be panel mounted if desired. Imported. Shpg. wt., 3 oz.
 99 R 62309 Net .79

HEAVY SHIELDED PHONE PLUGS AND JACKS



(A) Sturdy, heavy brass, nickel-plated phone plug with screw terminal connections. Threaded insulated cable outlet may be removed for larger cables to pass through. Body dia. 3/4". Pin Dia. 1/4", overall length 3 1/4". Shpg. wt., 3 oz. Imported.
 99 R 62291 Plug Net ea. .64 10 for 5.50
(B) Matching in-line phone Jack, same construction as plug. Overall length 2". Imported.
 99 R 62283 Jack Net ea. .59 10 for 5.30

ALL SHIELDED PHONO PLUG AND JACK



(A) Removable Shell for easy soldering of wires. Positive ground connection through unique ground lug reduces hum to a minimum. Extra long handle makes removal from amplifier a snap. Completely shielded in bright nickel plate on brass body and shell. Fits all RCA type jacks. 1 1/4" long. Imported. Shpg. wt., 2 oz.
 99 R 62390 Net .25
(B) Extension Cable Jack for use with above or any other type phono plug. Imported. Shpg. wt., 2 oz.
 99 R 62408 Net .25

3 CONDUCTOR PHONE PLUG & JACK



(A) 3 Conductor Phone Plug 1/4" Dia. Black Bakelite Handle. Solder lugs. Imported.
 99 R 61194 Shpg. wt., 2 oz. Net .44
(B) 3 Conductor Phone Jack, Open Circuit. Imported.
 99 R 61186 Shpg. wt., 2 oz. Net .44


3-CONDUCTOR PLUG AND JACK SET



69¢

A finely built 3-conductor plug and jack set. Uniquely made so that jack can be used as normally open although one circuit may be used as normally closed. Heavy gauge construction. Plug 1 1/4" overall. Jack mounts in 3/8" hole in panels up to 3/8" thick. Pin Dia. 3/32". Imported. Shpg. wt., 2 oz.
 99 R 63281 Net .69


KIT OF 10 COLOR CODED PHONO PLUGS



99¢

Kit contains 10 RCA-type phono plugs in assorted colors—Black, Red, Yellow, Blue, and White. Plastic shell with finger grip. Plugs are semi-solderless type—need only spot solder at tip. Fit standard RCA type phono jacks. Imported. Shpg. wt., 3 oz.
 99 R 63273 Net .99


DOUBLE PHONO JACK AND PLUG SET



Set consists of two phono male plugs and a dual female socket. Excellent for such dual signal applications as stereo equipment. Sturdy solder contacts are used throughout construction. Shpg. wt., 3 oz.
 99 R 63307 Net .39

Plugs — Jacks — Connectors



SWITCHCRAFT 3 CONDUCTOR FLAT PHONE PLUGS



$\frac{3}{4}$ " flat phone plugs with removable plastic cap for easy connection of wire leads. Ideal for use where space is limited. Tip rods are $1\frac{3}{4}$ " long. All metallic parts are of nickel plated brass. All plugs have screw type terminals except #238 which is solder type. Shpg. wt., 3 oz.

Stock No.	Mfr. No.	Fig.	Color	Net Each
34 R 60391	230	A	Black	1.02
34 R 60409	S-230	A	Black	1.29
34 R 60417	235	A	Red	1.02
34 R 60425	238	B	Metal	1.08

SWITCHCRAFT "LITTEL PLUGS" AND JACKS



"LITTEL-PLUGS" PHONE PLUGS—Compact quality plugs. Fits standard $\frac{3}{4}$ " phone jacks except # with .206 diam. sleeve and † with short sleeve for Revere recorders. In plastic handle or with brass nickel plated shells for shielding. Solder terminal has built-in cable clamp. Handle $1\frac{1}{4}$ " long, $\frac{1}{2}$ " diam. Av. shpg. wt., 3 oz.

Stock No.	Type	Fig.	Cond.	Handle	Terminals	Net
34 R 60128	240	A	2	Black	Screw	.57
34 R 60136	245	A	2	Red	Screw	.57
34 R 60144	250	A	2	Black	Solder	.54
34 R 60151	S-250*	A	2	Black	Solder	.57
34 R 60169	255	A	2	Red	Solder	.54
34 R 60177	260	A	3	Black	Screw	.90
34 R 60185	267	A	3	Black	Solder	.81
34 R 60193	280	B	2	Metal	Solder	.78
34 R 60201	S-280*	B	2	Metal	Solder	.78
34 R 60219	R-280†	B	2	Metal	Solder	.99
34 R 60227	297	B	3	Metal	Solder	.99

"LITTEL-JAX" PHONE JACKS (Fig. C) Accept standard $\frac{3}{4}$ " phone plugs, except # with .210" I.D. sleeve and † mates with 480 Mil type "Littel-Plug." Abbrs.: SCC—single closed ckt.; OC—open ckt. $\frac{3}{4}$ " dia., $1\frac{1}{2}$ " overall; $\frac{3}{8}$ " dia. threaded shank, $\frac{1}{2}$ " long. Av. shpg. wt., 2 oz.

Stock No.	Type	Schematic	Cond.	CKT.	Jan Type	Net
34 R 60235	11	I	2	OC	—	.33
34 R 60243	C-11	I	2	OC	JJ-034	.48
34 R 60250	S-11*	I	2	OC	—	.36
34 R 60268	12A	II	2	SCC	—	.36
34 R 60276	C-12A	II	2	SCC	JJ-089	.57
34 R 60284	12B	III	3	OC	—	.42
34 R 60292	C-12B†	III	3	OC	JJ-033	.57
34 R 60300	13B	IV	3	SCC	—	.60

"TINI-PLUGS" SUBMINIATURE PHONE PLUGS, 2-conductor phone plugs for use with "Tini-Jax." Only $\frac{1}{32}$ " in length. In plastic or metal shielded handles. Pin Dia. $\frac{1}{16}$ ". Shpg. wt., 2 oz.

Stock No.	Type	Fig.	Handle	Terminals	Net
34 R 60318	740	A	Black	Screw	.57
34 R 60326	745	A	Red	Screw	.57
34 R 60334	750	A	Black	Solder	.54
34 R 60342	755	B	Red	Solder	.54
34 R 60359	770	B	Metal	Screw	.78
34 R 60367	780	B	Metal	Solder	.75


"TINI-JAX" SUBMINIATURE PHONE JACKS (Fig. D) 2-conductor jacks for "Tini-Plugs." Only $\frac{1}{32}$ " long. Abbrs.: OC—open Ckt.; CC—closed Ckt. Av. shpg. wt., 2 oz.

Stock No.	Type	Schematic	CKT.	Net
34 R 60375	41	I	OC	.33
34 R 60383	42A	II	CC	.36

"TINI-EXTENSION JAX" (Fig. E) An extension or cable jack to mate with "Tini-Plugs." Two conductor with metal housing for ruggedness and electrical shielding. Solder lug terminals. Shpg. wt., 2 oz.

Stock No.	Type	Fig.	Cond.	Terminals	Net
34 R 60458	125	E	2	Solder	.90

SWITCHCRAFT PLUGS AND JACKS



MIL TYPE PLUGS AND EXTENSION JACK
All meet industrial and military requirements. Plugs are made to MIL-P-642A Specs. The extension Jack type 820 meets MIL-J-641A specs. Best quality material and workmanship assure positive internal interlock. Parts will not shift in position. Black plastic handle. Extension Jack fits type 430 "Littel-Plug." All have screw terminals. Av. shpg. wt., 2 oz.

Stock No.	Type	Cond.	Old S.C. No.	Jan. Type	Net Each
34 R 60066	430	2	PL-55	PJ-054B	.90
34 R 60094	440	2	PL-55	PJ-055B	.90
34 R 60102	480	3	PL-68	PJ-068	2.16
34 R 60110	820	2	JK-26	JJ-026	1.26

SWITCHCRAFT "MICRO PLUGS AND JAX"

(A) A miniaturized 2-conductor plug for use with cables of up to $\frac{1}{4}$ " O.D. Nylon insulation is used between tip and sleeve. Pin Dia. $\frac{3}{32}$ ". Shpg. wt., 2 oz.
(B) Ultra-miniaturized jack is designed for above plugs. Features solder lugs and positive tip spring grip.

34 R 60433 (A) Black handle (No. 850)	Net .51
34 R 60441 (A) Red handle (No. 855)	Net .51
34 R 60490 (A) Natural Al. handle (No. 880)	Net .51
34 R 60508 (B) Jax (No. TR-2A) Shpg. wt., 2 oz.	Net .39

SWITCHCRAFT "THICK PANEL JAX"

A long bushing allows mounting in panels of up to $1\frac{1}{4}$ " in thickness with a $15/32$ " diameter hole. Features shielding and solder terminals. No. 151 is 2-conductor and mates with 240, 245, 250, 255, 270, and 280 plugs. No. 152B is 3-conductor and mates with 260, 267, 269, and 297 plugs. Shpg. wt., 3 oz.

Stock No.	Description	Net
34 R 60474	Switchcraft No. 151	.99
34 R 60482	Switchcraft No. 152B	1.08

SWITCHCRAFT STEREO "LITTEL-JAX"

A three conductor jack specially designed for switching out speakers when connecting stereo headphones. Recommended for such stereo applications as record players and multiplex tuners. Dual, normally-closed switch contacts, open both stereo circuits independently when a three conductor plug is inserted. Mounts in single $\frac{3}{4}$ " diameter hole. Shpg. wt., 2 oz.

34 R 60466	Switchcraft No. 14B	Net .78
------------	---------------------	---------

LAFAYETTE STEREO PHONE JACK

For Insertion of standard $\frac{3}{4}$ " Dia. three conductor plug. Will switch out speakers and allow operation of only headphones or extension speakers. Many uses. Imported. Shpg. wt., 2 oz.

99 R 62739	Net ea. .59
------------	-------------

EUROPEAN AUDIO CONNECTORS

Made to European DIN engineering specs. Fully shielded in plastic snap-on shells. Will mate with sockets on Norelco, Grundig, Telefunken, Uher, etc. imported.


3 PIN AUDIO PLUG—Fig. A	Net .89
34 R 31012 Shpg. wt., 2 oz.	
5 PIN AUDIO PLUG—Fig. B	Net .99
34 R 31020 Shpg. wt., 2 oz.	
5 PIN AUDIO PLUG—Fig. C	Net .99
34 R 31038 Shpg. wt., 2 oz.	

TELEX MINIATURE PHONE PLUG AND JACK

Precision made plugs and jacks. Plug is $1\frac{1}{2}$ " long (overall), body is $1/4$ " diameter, prod is $1/8$ " Dia. Jack can be mounted on any panel up to $1/8$ ". Shpg. wt., 2 oz.

32 R 83017 PM-01 Plug	Net .93
TELEX No. JMP-01 Jack (Closed Circuit)	Net .50
32 R 83025	Net .50
TELEX No. JMP-02 Jack (Open Circuit)	Net .50
32 R 83033	Net .50

Replacement Speakers and Baffles




LAFAYETTE ECONOMY-LINE PM SPEAKER

Top quality replacement speakers. Selected for universal application rugged construction-standard configurations. All have 3.2 ohm voice coils. Made in U.S.A. except 99 Series are imported.

Stock No.	Size	Shape	Mag. Wt.	Peak Watts	Shpg. Wt.	Net Ea.
99 R 62688	4"	Square	.60 oz.	3.0	1/2	1.49
99 R 62697	5"	P.C.	.68 oz.	4.0	3/4	1.79
32 R 01092	5x7"	Oval	1.0 oz.	5.0	1	2.69
32 R 01078	6x9"	Oval	1.47 oz.	7.0	1 1/2	3.19
32 R 01043	6x9"	Oval	2.15 oz.	8.0	1 3/4	3.69

utah MICROGAP PM SPEAKERS



Features famous MICROGAP precision in centering of voice coil, giving increased and uniform sensitivity. All heavily cadmium plated rust proof construction. All with alnico V magnets. All voice coils 3-4 ohms except 12" is 8 ohms. † With provisions for mounting transformer.

Stock No.	Size-Shape	Program Power Watts	Mag. Oz.	Fig.	Shpg. Wt. Lbs.	Net Ea.
32 R 49141	5x3 OVAL	4	.55	D	3/4	2.34
32 R 49018	3 1/2" SQUARE	3	.68	A	1/2	2.31
32 R 49026†	4" SQUARE	5	1.2	A	1/2	2.70
32 R 48034	4x6 OVAL	5	1.2	D	3/4	3.25
32 R 49042†	5" P.C.	5.5	1.2	B	3/4	2.99
32 R 49455	6" P.C.	6	.68	B	1	3.15
32 R 49471†	6" P.C.	5.5	1.0	B	1 3/4	4.41
32 R 49067	6x9 OVAL	10	3.16	D	1 3/4	5.42
32 R 49463	8" P.C.	8	1.47	B	1 1/2	3.81
32 R 49079†	8" ROUND	10	3.36	C	1 3/4	5.75
32 R 49083†	12" ROUND	14	6.8	C	5 3/4	8.75

UTAH TAPE RECORDER SPEAKER

5x3" oval. Rated 4 watts Program 3.2 ohm voice coil. Net 2.34

UTAH INTERCOM SPEAKERS

High sensitivity, especially designed for "talk-back" circuits. Ideal for selective paging systems. Use as speaker and microphone. All 45 ohm voice coil impedance.

Stock No.	Size-Shape	Mag. Wt.	Peak Watts	Fig.	O.D.	Depth	Shpg. Wt.	Net
32 R 49125	3 1/2" SQUARE	.68	4	A	3 1/2"	1 1/2	1/2	3.15
32 R 49133	4" SQUARE	.68	4	A	4 1/2"	1 1/2	1/2	3.02


MODERN SPEAKER BAFFLES



AS LOW AS **3⁰⁵**

Well built plywood speaker baffles for indoor public address and paging systems, intercoms, extension speakers, etc. Prieze-design grille cloth, modern walnut finish. Baffle for 5" speaker is 7 3/4" square; Depth at top 4 3/4", at bottom 4". For 8" speaker 13" square; Depth at top 6 1/4", at bottom 4". For 12" speaker, 13" square; Depth at top 8 1/2", at bottom 4 1/2".

Stock No.	Description	Wt. lbs.	Singly Each	Lots of 3 Each
20 R 13068	For 5" or 6"	1 1/2	3.59	3.23
20 R 13076	For 8"	1 3/4	3.95	3.53
20 R 13084	For 12"	3	3.69	5.19



EXACT REPLACEMENT MINIATURE SPEAKERS

Quality Alnico PM speakers for replacement in transistor portable sets. Ideal for the experimenter. * have mtg. holes on 2" centers; † on 1 1/2" centers; OHMS is Voice coil impedance. Dimensions given are overall. Imported.

Stock No.	Fig.	Diam.	Depth	Ohms	Wt.	Net
99 R 60352†	A	1 1/2"	1 3/4"	10	5 oz.	.99
99 R 60360	C	2"	1 3/4"	8	3 oz.	.99
99 R 60370	C	2 1/4"	1 3/4"	8	3 oz.	.99
99 R 60972*	B	2 1/4"	1 1/2"	10	5 oz.	.99
99 R 60329	E	3"	1 3/4"	8	3 oz.	.99

LAFAYETTE SPEAKERS FOR CAR RADIOS AND TAPE PLAYERS


SET OF 2 UNDER-DASH 3x5" MATCHING SPEAKER SYSTEMS

2-3x5" wide-range ceramic speakers mounted in plastic housings will mount under dash, under seats, on kick panels, doors, or rear package shelf. Includes all necessary cables and mounting hardware. Imported. Imp., 8 ohms. Shpg. wt., 2 1/2 lbs. Net 6.95



CUSTOM IN-DOOR SET OF 4 SPEAKERS

Get that full, rich stereo sound from your car tape player. Ready for quick installation. Improves the sound and performance of any car tape player. Kit includes: Four 4 3/4" extended range 8-ohm PM speakers; four round custom mount plastic speaker grills; all necessary hookup wire with solderless connectors; mounting hardware and easy-to-follow instructions. Imported. Imp., 8 ohms. Wt., 3 1/2 lbs. Net 8.95



SET OF 2 DELUXE REAR DECK MATCHING SPEAKER SYSTEMS

Set of two powerful 4" speakers mounted in handsome ebony plastic cabinets with silver trim. Specially designed to mount on car's rear deck. Can also be surface mounted anywhere. Provides outstanding sound reproduction. Includes all necessary cables and mounting hardware. Imported. Imp., 8 ohms. 99 R 62988 Shpg. wt., 3 lbs. Net 9.95



CORNER BAFFLES

Frames constructed of plywood, front panels of acoustically correct particle board. Locked corners for maximum strength. Attractive recessed front, beautiful walnut wood-grain fabric covering. Complete with speaker mounting hardware.

Stock No.	Utah No.	Fig.	For Spkr.	Size InWxD"	Shpg. Wt.	Net
20 R 48122	SSB-W	A	8"	14x15 1/2x8 1/4	4 1/4	9.39
20 R 48148	CSB-W	B	8"	9 1/2x9 1/2x6 1/4	2	6.30
20 R 48195	CS12-W	B	12"	13 1/2x13 1/2x8 3/4	3 3/4	8.25

Mallory Controls

EXPLANATION OF MALLORY TAPERS

Taper No. 1—For audio or antenna shunt circuits.
Taper No. 2—For Series circuits or cathode voltage controls.
Taper No. 4—Linear taper for voltage divider circuits.

MALLORY MIDGETROL



Carbon element Midgetrols are rated 1 watt linear or 1/2 watt audio. Size 3/8" dia. with 2 3/4" long x 1/4" dia. round shafts. Shaft can be easily cut to any required length. Supplied with two shafts and knob adaptors for knurled and push-on-knobs, one Paint and instruction sheet. Shpg. wt., 4 oz.

Stock No.	Mfg. No.	Ohms	Tpr.	Stock No.	Mfg. No.	Ohms	Tpr.
33 R 11107	U-1	100	4	33 R 11370	U-36	75K	1
33 R 11115	U-2	500	4	33 R 11388	U-39	100K	1
33 R 11511	U-52R	500	2	33 R 11396	U-40	100K	2
33 R 11123	U-751R	750	2	33 R 11404	U-41	100K	4
33 R 11131	U-3	1K	2	33 R 11412	U-45	125K	4
33 R 11149	U-4	1K	4	33 R 11420	U-42	150K	1
33 R 11156	U-5	1500	2	33 R 11438	U-43	200K	4
33 R 11164	U-5L	1500	4	33 R 11446	U-44	250K	1
33 R 11172	U-6	2K	4	33 R 11453	U-45	250K	2
33 R 11180	U-7	250K	2	33 R 11461	U-46	250K	4
33 R 11198	U-8	3K	4	33 R 11479	U-48	500K	1
33 R 11206	U-9	3K	2	33 R 11487	U-50	500K	4
33 R 11214	U-12	5K	1	33 R 11495	U-51	750K	1
33 R 11222	U-14	5K	4	33 R 11503	U-52	1 Meg.	2
33 R 11230	U-18	10K	1	33 R 11529	U-53	1 Meg.	1
33 R 11248	U-19	10K	2	33 R 11537	U-54	1 Meg.	4
33 R 11255	U-20	10K	4	33 R 11545	U-55	1.5 Meg.	4
33 R 11263	U-21	15K	1	33 R 11552	U-55	2 Meg.	4
33 R 11271	U-22	15K	2	33 R 11560	U-56	2 Meg.	4
33 R 11289	U-24	20K	1	33 R 11578	U-255	2.5 Meg.	4
33 R 11297	U-26	20K	4	33 R 11586	U-57	3 Meg.	1
33 R 11305	U-28	25K	2	33 R 11594	U-59	3 Meg.	4
33 R 11313	U-28A	25K	1	33 R 11602	U-63	5 Meg.	2
33 R 11321	U-29	25K	4	33 R 11610	U-65	5 Meg.	1
33 R 11339	U-30	30K	4	33 R 11628	U-67	5 Meg.	4
33 R 11347	U-33	50K	1	33 R 11636	U-82	10 Meg.	4
33 R 11354	U-34	50K	2				
33 R 11362	U-35	50K	4				

Any of above Singly Ea. 1.02

SINGLE TAPPED MIDGETROLS

Shpg. wt., 4 oz.

Stock No.	Mfg. No.	Ohms	Tap At	Stock No.	Mfg. No.	Ohms	Tap At
33 R 11644	UT-153	15K	10K	33 R 11743	UT-438	1 Meg.	300K
33 R 11651	UT-415	30K	25K	33 R 11750	UT-443	1 Meg.	450K
33 R 11669	UT-420	250K	50K	33 R 11768	UT-450	2 Meg.	125K
33 R 11677	UT-421	250K	150K	33 R 11776	UT-448	2 Meg.	250K
33 R 11685	UT-425	300K	70K	33 R 11784	UT-454	2 Meg.	400K
33 R 11693	UT-429	500K	50K	33 R 11792	UT-449	2 Meg.	600K
33 R 11701	UT-427	500K	100K	33 R 11800	UT-451	2 Meg.	900K
33 R 11719	UT-430	500K	150K	33 R 11818	UT-457	3 Meg.	900K
33 R 11727	UT-431	500K	225K	33 R 11826	UT-461	3.25 M.	300K
33 R 11735	UT-440	1 Meg.	200K				

Any of above Singly ea. Net 1.26

DOUBLE TAPPED MIDGETROLS

Shpg. wt., 4 oz.

Stock No.	Mfg. No.	Overall Resistances	Tap Resistances	
			Tap 1	Tap 2
33 R 11834	UDT-283	500K	100K	200K
33 R 11842	UDT-289	1 Meg.	250K	500K
33 R 11859	UDT-291	1.5 Meg.	225K	500K
33 R 11867	UDT-295	2.25 Meg.	250K	500K
33 R 11875	UDT-296	2.25 Meg.	500K	1 Meg.
33 R 11883	UDT-303	3.3 Meg.	300K	1.5 Meg.

Any of above Singly ea. 1.26

SU INSULATED SHAFT MIDGETROLS FOR TV



3/8" dia. carbon controls with 1/4" dia. fixed knurled and slotted phenolic shafts. Shaft protrudes 1/4" beyond bushing. Linear taper. With hex nut. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	Ohms	Stock No.	Mfg. No.	Ohms
33 R 12089	SU-6	1500	33 R 12154	SU-46	250K
33 R 12097	SU-8	3K	33 R 12162	SU-50	500K
33 R 12105	SU-14	5K	33 R 12170	SU-54	1 Meg.
33 R 12113	SU-20	10K	33 R 12188	SU-56	2 Meg.
33 R 12121	SU-29	25K	33 R 12196	SU-565	2.5 Meg.
33 R 12139	SU-35	50K	33 R 12204	SU-59	3 Meg.
33 R 12147	SU-41	100K	33 R 12212	SU-67	5 Meg.
			33 R 12220	SU-69	7.5 Meg.


Any of the above Singly ea. .93

ATTACHABLE MIDGETROL SWITCHES



Midgetrol types U, UT and UDT—with dummy terminal 1 with built-in switch/circuit breaker. Breaks at 2.5 amps, resets by turning to "off" position. ST types rated 6 amps/125V. DT types rated 3 amps/125V. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	Description	1-24	25-49
33 R 11891	US-26	S.P.S.T.	.42	.30
33 R 14804	USB-29	S.P.S.T.†	.90	.46
33 R 11909	US-267	S.P.S.T.*	.31	.48
33 R 11917	US-27	D.P.S.T.	.51	.48
33 R 11925	US-28	S.P.D.T.	.53	.46



EXTENSION SHAFTS

DS-37

DS-36 Extension Shaft 2 1/8" long x 1/4" dia. For tubular shaft Mid and 2-watt wire-wound controls. Shpg. wt., 3 oz.

33 R 11933(DS-36) Net .55

DS-37 3/8" diameter shaft. For use with round-shaft Midgetrols to accommodate knobs requiring 3/8" shaft. Shpg. wt., 3 oz.

33 R 11941(DS-37) Net .95

PUSH-PULL CONTROLS



Carbon element controls with a Push-Pull type SPST switch permanently attached. Switch rated 6 amps/125V. UL listed. Rated 1 watt linear or 1/2 watt audio. Size 3/8" dia. with 2" long x 1/4" dia. shaft. No assortment for quantity prices. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	Ohms	Taper	Net Each	
				1-24	25-49
33 R 12808	PP-13R	1K	1	1.35	1.22
33 R 14820	PP-252R	2.5K	1	1.35	1.22
33 R 14838	PP-253R	25K	1	1.35	1.22
33 R 14846	PP-15L	100K	4	1.35	1.22
33 R 12816	PP-15A	100K	1	1.35	1.22
33 R 12824	PP-25L	200K	4	1.35	1.22
33 R 12832	PP-25A4	250K	1	1.35	1.22
33 R 12840	PP-55A	500K	1	1.35	1.22
33 R 12857	PP-55L	500K	4	1.35	1.22
33 R 12865	PP-16A	1 Meg.	1	1.35	1.22
33 R 12873	PP-16L	1 Meg.	4	1.35	1.22
33 R 12881	PP-155L	1.5 Meg.	4	1.35	1.22
33 R 12899	PP-26A	2 Meg.	1	1.35	1.22
33 R 14853	PP-36L	3 Meg.	4	1.35	1.22
33 R 12907	PP-56L	5 Meg.	4	1.35	1.22

Any of above Singly ea. Net 1.26

Stock No.	Ohms	Tapped @	Taper	Net Each	
				1-24	25-49
33 R 12915	250K	100K-150K	4	1.59	1.43
33 R 12923	500K	200K	4	1.59	1.43
33 R 12931	500K	78K-168K	4	1.59	1.43
33 R 12949	500K	250K	1	1.59	1.43
33 R 12956	1 Meg.	500K	2	1.59	1.43
33 R 12964	1 Meg.	100K	1	1.59	1.43
33 R 12972	1 Meg.	200K	2	1.59	1.43
33 R 12980	1 Meg.	250K-500K	4	1.59	1.43
33 R 12998	2 Meg.	500K-1 Meg.	1	1.59	1.43
33 R 13012	2 Meg.	1 Meg.	4	1.59	1.43
33 R 13020	3 Meg.	1 Meg.-2 Meg.	4	1.59	1.43
33 R 13038	4 Meg.	2 Meg.	4	1.59	1.43

Mallory Controls

MALLORY PRINTED CIRCUIT MINITROLS



Carbon transistor controls, all linear taper, rated 1/4 watt. Diameter 1/2". No shaft, all open screwdriver slot adjustment. 1/4"-32 bushing. Choice of horizontal or vertical mount. Shpg. wt., 3 oz.



Type MTC-1

Res. Ohm	Stock No. Vert. Mt.	Stock No. Horiz. Mt.
100	33 R 16379	33 R 16450
200	33 R 16387	33 R 16458
250	33 R 16395	33 R 16476
300	33 R 16403	33 R 16484
500	33 R 16411	33 R 16482
750	33 R 16429	33 R 16700
1000	33 R 16437	33 R 16718
1500	33 R 16445	33 R 16726
2000	33 R 16452	33 R 16734
3000	33 R 16460	33 R 16742
5000	33 R 16478	33 R 16759
6000	33 R 16486	33 R 16767
6800	33 R 16494	33 R 16775
10000	33 R 16502	33 R 16783

Type MTC-4

Res. Ohm	Stock No. Vert. Mt.	Stock No. Horiz. Mt.
15K	33 R 16510	33 R 16791
20K	33 R 16528	33 R 16809
25K	33 R 16536	33 R 16817
50K	33 R 16544	33 R 16825
100K	33 R 16551	33 R 16833
120K	33 R 16569	33 R 16841
180K	33 R 16577	33 R 16858
250K	33 R 16585	33 R 16866
325K	33 R 16593	33 R 16874
450K	33 R 16601	33 R 16882
500K	33 R 16619	33 R 16890
1 MEG	33 R 16627	33 R 16908
2 MEG	33 R 16635	33 R 16916
3.5 MEG	33 R 16643	33 R 16924

Any of above

Net each .39

WIRE WOUND SENSITIVITY CONTROLS



For AGC, hum-balancing, linearity, etc. 3/4" diam. For conversion from cross-slot adjustment to shaft, use shafts listed below. Shpg. wt., 3 oz.

MR-F 3-WATT FLANGE MOUNT

Mounting ears with .130" dia. holes on 1" center. Cross-slot adjustment, front and rear.

Stock No.	Mfr. No.	Ohms	Stock No.	Mfr. No.	Ohms
33 R 16007	MRF6	6	33 R 16098	MR600F	600
33 R 16015	MR15F	15	33 R 16106	MR750F	750
33 R 16023	MR40F	40	33 R 16114	MR1000F	1000
33 R 16031	MR75F	75	33 R 16122	MR1500F	1500
33 R 16049	MR100F	100	33 R 16130	MR2000F	2000
33 R 16056	MR150F	150	33 R 16148	MR2500F	2500
33 R 16064	MR200F	200	33 R 16155	MR3000F	3000
33 R 16072	MR250F	250	33 R 16163	MR4000F	4000
33 R 16080	MR500F	500	33 R 16171	MR5000F	5000

Any of above

Net ea. .66

MR-P 3-WATT PC MOUNT

Printed circuit board mounting with cross-slot adjustment, front and rear.

Stock No.	Mfr. No.	Ohms	Stock No.	Mfr. No.	Ohms
33 R 16189	MR15P	1.5	33 R 16247	MR1000P	1000
33 R 16197	MR15P	15	33 R 16254	MR1500P	1500
33 R 16205	MR100P	100	33 R 16262	MR3000P	3000
33 R 16213	MR175SP	*175	33 R 16270	MR4000P	4000
33 R 16221	MR200SP	1260	33 R 16288	MR5000P	5000
33 R 16239	MR600P	600			

*Stop at 60 ohms. †Stop at 100 ohms.

Any of above

Net ea. .66

MRC-P 1/2-WATT PC MOUNT

Convergence controls with printed circuit board mounting and permanent knob.

Stock No.	Mfr. No.	Ohms	Stock No.	Mfr. No.	Ohms
33 R 16296	MRC10P	10	33 R 16320	MRC100P	100
33 R 16304	MRC30P	30	33 R 16338	MRC120P	120
33 R 16312	MRC60P	60	33 R 16346	MRC150P	150

Any of above

Net ea. .66

MR-T 3-WATT TAB MOUNT

With twist-tabs for mounting on PC board or chassis. Slot adjust.

Stock No.	Mfg. No.	Ohms	Ea.	Stock No.	Mfg. No.	Ohms	Ea.
33 R 14861	MR10-T	10	.66	33 R 14945	MR2500-T	2500	.70
33 R 14887	MR50-T	50	.66	33 R 14952	MR3000-T	3000	.70
33 R 14895	MR100-T	100	.66	33 R 14960	MR4000-T	4000	.70
33 R 14903	MR250-T	250	.66	33 R 14978	MR5000-T	5000	.76
33 R 14911	MR500-T	500	.66	33 R 14986	MR8000-T	8000	.76
33 R 14929	MR850-T	850	.66	33 R 14994	MR10K-T	10K	.83
33 R 14937	MR1000-T	1000	.66	33 R 14978	MR15K-T	15K	.93

SHAFTS FOR MR CONTROLS

Mallory No. MRS1250—1/4" dia. x 1/4" FMS knurled and slotted nylon. Plugs into either end of MR control.

33 F 16353

Net ea. .12

CARBON TRANSISTOR CONTROLS

Linear taper (4) rated 1/4 Watt; Audio taper (1) rated 1/4 Watt Diam. 1/2" Universal 1/4" steel shaft 1" long with 1/4"-32 bushing and screwdriver slot except * has 5/8" long nylon shaft. Shpg. wt., 3 oz.



Stock No.	Mfg. No.	Ohms Tpr.	Stock No.	Mfg. No.	Ohms Tpr.
33 R 12534	MLC13L	1K 4	33 R 12659	MLC15L	100K 4
33 R 12592	MLC25A	2500 1	33 R 12667	MLC25L	200K 4
33 R 12600	MLC53A	5K 4	33 R 12675	MLC25L	250K 4
33 R 12618	MLC53L	5K 4	33 R 14812	MLC55A	500K 1
33 R 12626	MLC14L	10K 4	33 R 12683	MLCN55L*	500K 4
33 R 12634	MLC54L	50K 4	33 R 12691	MLCN16A*	1 Meg 1
33 R 12642	MLC15A	100K 1	33 R 12709	MLCN16L*	1 Meg 4

Any of above

Singly Ea. 1.14

MALLORY 3-WATT WIREWOUND TV & INDUSTRIAL POTS



Dust-proof phenolic case 1 1/2" diameter. Insulated contact arm type 300 V. AC insulation. All have linear taper. Knurled screwdriver slotted stub shaft with 3/8" standard bushing. With nut. Shpg. wt., 3 oz.

Stock No.	Type	Ohms	Stock No.	Type	Ohms
33 R 13061	R2L	2	33 R 13657	R50L	50
33 R 13079	R3L	3	33 R 13665	R100L	100
33 R 13087	R5L	5	33 R 13673	R250L	250
33 R 13095	R6L	6	33 R 13681	R500L	500
33 R 13103	R8L	8	33 R 13699	R750L	750
33 R 13111	R10L	10	33 R 13707	R1000L	1K
33 R 13129	R15L	15	33 R 13715	R1500L	1500
33 R 13137	R20L	20	33 R 13723	R2500L	2500
33 R 13145	R25L	25	33 R 13731	R3000L	3000
33 R 13152	R30L	30	33 R 13749	R5000L	5000

Any of above

Net ea. .93

Stock No.	Type	Ohms	Stock No.	Type	Ohms
33 R 13160	R7500L	7500	33 R 13186	R15ML	15K
33 R 13178	R10ML	10K	33 R 13194	R20ML	20K

Any of above

Net ea. 1.08

CENTER TAPPED CONTROLS

Stock No.	Type	Ohms	Stock No.	Type	Ohms
33 R 13202	R10CT	10	33 R 13228	R30CT	30
33 R 13210	R20CT	20	33 R 13236	R50CT	50

Any of above


Net ea. 1.32

SWITCH FOR ABOVE 3-WATT CONTROLS

Stock No.	Mfg.	Type	Net Each	10-49
33 R 13244	US30	SPST	.19	.38

MALLORY VW SERIES SUBMINIATURE 5-WATT WIRE WOUND

Wire wound control rated at 5 watts. Break down voltage 900VAC RMS. Linear taper ±10% tol. Dim. 3/4" dia. x 7/8" depth. 1/4" shaft dia. Bushing dia. 3/8" with 32 x 3/8" thread. Shpg. wt., 3 oz. No assortment for quantity prices.



Stock No.	Ohms	1-9	10-49	Stock No.	Ohms	Each 1-9	10-49
33 R 13269	1	1.38	1.24	33 R 13442	300	1.38	1.24
33 R 13277	2	1.38	1.24	33 R 13459	400	1.38	1.24
33 R 13285	3	1.38	1.24	33 R 13467	500	1.38	1.24
33 R 13293	5	1.38	1.24	33 R 13475	600	1.38	1.24
33 R 13301	6	1.38	1.24	33 R 13483	750	1.38	1.24
33 R 13319	8	1.38	1.24	33 R 13491	1K	1.38	1.24
33 R 13327	10	1.38	1.24	33 R 13509	1500	1.44	1.30
33 R 13335	15	1.38	1.24	33 R 13517	2K	1.44	1.30
33 R 13343	20	1.38	1.24	33 R 13525	2500	1.44	1.30
33 R 13350	25	1.38	1.24	33 R 13533	3K	1.44	1.30
33 R 13368	30	1.38	1.24	33 R 13541	4K	1.44	1.30
33 R 13376	40	1.38	1.24	33 R 13558	5K	1.44	1.30
33 R 13384	50	1.38	1.24	33 R 13566	7500	1.50	1.35
33 R 13392	60	1.38	1.24	33 R 13574	10K	1.50	1.35
33 R 13400	75	1.38	1.24	33 R 13582	15K	1.56	1.40
33 R 13418	100	1.38	1.24	33 R 13590	20K	1.56	1.40
33 R 13426	200	1.38	1.24	33 R 13608	25K	1.65	1.49
33 R 13434	250	1.38	1.24				

Volume Controls-T & L Pads—Rheostats

LAFAYETTE 1/2 WATT AUDIO TAPER CONTROLS WITH SWITCH



Popular Universal Replacement Controls

59¢

1 1/4" dia. control with 1/4" dia., 2 1/2" L, round shaft. Control rated 1/2 watt audio; switch rated 3 amp. — 125V. (AC/DC). Bushing: 3/16" — 32x3/4". Complete with hardware. Imported. Shpg. wt., 2 oz.
 99 R 83521 1 meg. ea. .58
 99 R 83513 1/2 meg. ea. .59

REPLACEMENT 5,000 OHM VOLUME CONTROL FOR JAPANESE TRANSISTOR RADIOS



59¢

A volume control with the proper resistance, dimensions and mounting for replacement in thousands of Japanese transistor radios. A 5,000 ohms potentiometer with S.P.S.T. switch. Only 3/8" dia., 1/2" total depth. Easily installed in printed circuits. Comes with 1/8" dia. knob. Shpg. wt., 2 ozs. imported.
 99 R 80198 Net .59

SUB-MINIATURE VARIABLE CONTROLS



39¢

SIZE—3/8" Dia. 1/8" Thick

Carbon composition potentiometers built for the most compact installations. Ideal for printed circuits. Shpg. wt., 2 oz. Imported

Stock No.	Ohmage	Net Ea.
99 R 81426	1,000	.39
99 R 81434	5,000	.39
99 R 81442	10,000	.39
99 R 81459	50,000	.39

VOLUME CONTROL ACCESSORIES



Shpg. wt., 3 oz.

Stock No.	Fig.	Description	Net
33 R 11974	A	Extends control body 3/8" from surface	.22
33 R 11982	D	Wrench for 1/2-3/8" V.C. hex nuts	.85
33 R 11990	E	Ext. shaft 4x1/4, 1/2" flat	.95
33 R 12014	E	Ext. shaft 4x1/4, 3/8" flat	.95
33 R 12022	E	Ext. shaft 4x3/8, 1/2" flat	.95
33 R 12030	E	Ext. shaft 2x1/4 with 3/8" slot	.81
33 R 12048	B	Couples 1/4" shaft to 1/4", 3/8" shafts	.72
33 R 12055	C	Bushing for panel mounting	.20
33 R 12063	F	Mtg. Bkt. 2 1/2" Mtg. centers	.05
33 R 12071	F	Mtg. Bkt. 1 3/4" Mtg. centers	.05

MINIATURE VOLUME CONTROLS



Audio Taper controls with D.P.S.T. switches. Mount in 3/8" holes in panels up to 1/4" thick. 1/4" flattened shaft is 3/8" long. Dimensions: 1/2" W x 1 1/8" x 1" Deep. Mounting nut and washer supplied. Imported. Shpg. wt., 3 oz.

32 R 22510	5K ohm	32 R 22544	1/2 Meg.
32 R 22528	10K ohm	32 R 22551	1 Meg.
32 R 22536	100K ohm		

Any of Above Net Each .74

MALLORY OUTDOOR SPEAKER CONTROLS



Engineered for outdoor movie speakers. Rated 8 watts, audio. Bushing 3/8" — 32x3/8". Shaft 1/4" dia., x 3/8" long. Supplied with nut. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	Ohms	Net
33 R 12238	TSA-10	4-ohm-L Pad	1.35
33 R 12246	TSA-35	35	1.35
33 R 12253	TSA-6	6	1.14

OHMITE WIRE-WOUND RHEOSTATS



Vitreous enamel rheostat with copper graphite control brush except "S" silver-graphite contact brush. Ohmage above 5000 have silicone ceramic coating. Rating indicated are at full setting. Less knob. Avg. shpg. wt., 5 oz.

For Level Control of low impedance audio circuits. Rated at 15 watts peak audio, 4 watts DC. Accessories furnished: one bar knob, one dial plate, with matched rotation, one nut, one lock washer. Bushing 3/8" — 32x3/8", shaft 1/4" x 2" long. Shpg. wt., 6 oz.

L-PADS

Stock No.	Mfg. No.	Ohms	Stock No.	Mfg. No.	Ohms
33 R 13756	L2	2	33 R 13830	L250	250
33 R 13764	L4	4	33 R 13848	L500	500
33 R 13772	L6	6	33 R 13855	L600	600
33 R 13780	L8	8	33 R 13863	L1000	1K
33 R 13798	L15	15	33 R 13871	L2000	2K
33 R 13806	L50	50	33 R 13889	L3000	3K
33 R 13814	L100	100	33 R 13897	L4000	4K
33 R 13822	L200	200			

Singly Each 2.73

LA-PADS

Same as above with a 3/8" — 32x1" Bushing. 2 nuts, 2 lock washers, 1 1/2x1 1/2" dial plate. Shpg. wt., 6 oz.

Stock No.	Mfg. No.	Ohms	Stock No.	Mfg. No.	Ohms
33 R 13895	L8A	8	33 R 13913	L16A	16

Singly Each 2.85

DUAL L-PADS

Ganged pads for stereo use. Same specifications as single L Pads bushing 3/8" — 32x1" Shpg. wt., 8 oz.

Stock No.	Mfg. No.	Ohms	Stock No.	Mfg. No.	Ohms
33 R 13921	LL8	8	33 R 13947	LL50	50

Singly Each 5.70

T-PADS

Stock No.	Mfg. No.	Ohms	Stock No.	Mfg. No.	Ohms
33 R 13954	T2	2	33 R 14036	T200	200
33 R 13962	T4	4	33 R 14044	T250	250
33 R 13970	T6	6	33 R 14051	T500	500
33 R 13988	T8	8	33 R 14069	T600	600
33 R 13996	T15	15	33 R 14077	T1000	1K
33 R 14010	T50	50	33 R 14085	T2000	2K
33 R 14028	T100	100	33 R 14093	T3000	3K

Singly Each Shpg. wt., 1/2 lb. 3.54

MODEL E-1 1/2 WATT 3/8" dia. 1/4" deep		MODEL H-25 WATT 1 1/2" dia. 1 3/8" deep		Net Each	
Stock No.	Mfg. No.	Ohms	Stock No.	Mfg. No.	
30 R 81114	0101*	1	30 R 81395	0140*	6.30 5.36
30 R 81122	0102*	2	30 R 81403	0141*	6.30 5.36
30 R 81130	0103	3	30 R 81411	0142*	6.30 5.36
30 R 81148	0104	6	30 R 81429	0143*	6.30 5.36
30 R 81155	0105	8	30 R 81437	0144*	6.30 5.36
30 R 81163	0106	10	30 R 81445	0145*	6.30 5.36
30 R 81171	0107	15	30 R 81452	0146	5.50 4.68
30 R 81189	0108	25	30 R 81460	0147	5.50 4.68
30 R 81197	0109	35	30 R 81478	0148	5.50 4.68
30 R 81205	0110	50	30 R 81486	0149	5.50 4.68
30 R 81213	0111	75	30 R 81494	0150	5.50 4.68
30 R 81221	0112	100	30 R 81510	0151	5.50 4.68
30 R 81239	0113	125	30 R 81528	0152	5.50 4.68
30 R 81247	0114	175	30 R 81536	0153	5.50 4.68
30 R 81254	0115	250	30 R 81544	0154	5.50 4.68
30 R 81262	0116	350	30 R 81551	0155	5.50 4.68
30 R 81270	0117	500	30 R 81559	0156	5.50 4.68
30 R 81288	0118	750	30 R 81577	0157	5.50 4.68
30 R 81296	0119	1000	30 R 81585	0158	6.30 5.36
30 R 81304	0120	1500	30 R 81593	0159	6.30 5.36
30 R 81312	0121	2500	30 R 81601	0160	6.30 5.36
30 R 81320	0122	3500	30 R 81619	0161	7.50 6.46
30 R 81338	0123	5000	30 R 81627	0162	7.50 6.46
30 R 81346	4190	7500	30 R 81635	4200	7.90 6.72
30 R 81353	4191	10,000	30 R 81643	4201	7.90 6.72
30 R 81361	4192	12,500	—	—	0.60 7.31
30 R 81379	4193	15,000	30 R 81650	4202	8.60 7.31
—	—	20,000	30 R 81668	4203	8.40 7.14
—	—	25,000	30 R 81676	4204	9.20 7.82

5151 Knob for Model E Net ea. .33 5150 Knob for Model H Net ea. .33

LAFAYETTE T & L Pads - Faders - Switches

STEREO LEVEL BALANCE CONTROL

- Dual Concentric 8 ohm L Pads
- Logarithmic Curve



Provides individual level control for stereo speakers. Varies "brilliance" or "presence." Controls stereo extensions without mismatching. Dual control mounted on concentric shaft. Gold-finished brass plate and attractive black knobs with gold trimming. L pad for 8 ohm circuits. Plate is 2 1/2" across; overall depth 3/4". Imported. Shpg. wt., 7 oz.

99 R 61400 Level Control Net 3.19

DELUXE STEREO LEVEL BALANCE CONTROL

- Dual Concentric 8 ohm L Pads
- Logarithmic Curve



Two phone jacks enable you to plug in extension or monitoring speakers from the front. Screw terminals in the rear provide for a simple, permanent hookup. Control mounted on concentric shaft. Brushed brass plate with attractive black with gold-trim knobs. Concentric 8 ohm L pads. Use it to control volume on a second set of speakers. Plate is 4 1/2 x 2 3/4"; from front of knob to plate 1". Overall depths 3 3/8". Imported. Shpg. wt., 10 oz.

99 R 61418 Deluxe Level Control Net 4.40

LAFAYETTE L PADS

L pads for use as "brilliance" controls to vary tweeter level, or as "presence" controls to vary midrange speaker level. Both wire-wound elements are concentrically mounted within one plastic housing. With gold-finished metal escutcheon plate, mtg. screws, and attractive black knob. Size: 1 1/4" dia., 7/8" deep (less shaft), 2 1/2" deep overall. Imported. Shpg. wt., 5 oz.



L pad for 8 ohm circuits. 99 R 61343 Net 1.89

L pad for 16 ohm circuits. 99 R 61350 Net 1.89

LAFAYETTE T PADS

Constant impedance control to adjust speaker volume. With brass satin plate for wall mounting. Impedance, 8 ohms. With all parts and instructions. Imported. Shpg. wt., 9 oz.



99 R 61368 Net 4.89

LAFAYETTE REMOTE SPEAKER FADERS

As Low
As

89¢



Remote Speaker Fader Provides adjustable volume level for Radio, TV, Hi-Fi and remote speaker. Gradually increases volume on one speaker while diminishing volume on the other. May also be used to adjust volume for 1 speaker. Gold plate for front panel mounting. With instructions. Imported. Shpg. wt., 3 oz.

99 R 61384 Net .89

Remote Speaker Fader. Same as above except for wall mounting. Imported. Shpg. wt., 4 oz.

99 R 61392 Net 1.09

MULTI-INPUT SELECTOR CONTROL

1 99



An all purpose selector control... connects any one of 5 inputs to one output. For AM, FM radio, phono, tape recorder or other auxiliary. Unit is completely shielded to prevent hum. Comes complete with all necessary mounting hardware and 5 input phono jacks and one output phono jack. An inexpensive addition to any multi-component system. Imported. Shpg. wt., 6 oz.

99 R 10290 Net 1.99

LAFAYETTE STEREO LEVEL CONTROL

3 98

- Logarithmic Curve



Two precision 8-ohm level controls concentrically mounted for stereo. Ideal for controlling individual volume of stereo extension speakers without fear of mismatch or affecting volume of main speakers. Also may be used to vary "brilliance" or "presence." Screw terminals. Handsome cream finish with gold panel plate. Overall size 3 1/4" x 4 1/2" x 2 3/8". Imported. Shpg. wt., 10 oz.

99 R 61475 Net 3.98

STEREO SELECTOR SWITCHES



(Fig. A)

(Fig. B)

- Permits Remote Selection of any 3 Pairs of Speakers

Recommended only for Hi-Fi Systems Using Vacuum Tube Circuitry

(Fig. A) A constant impedance speaker selector switch for multiple-speaker Stereo Hi-Fi. Selects 3 sets of speakers in any combination, with up to 60 watts of audio power. Mounted on an attractive, gold-finished, steel, electric outlet plate. 2 3/4 x 4 1/2". Imported. Shpg. wt., 8 oz.

Stereo Speaker Selector Switch 99 R 00986 Net 2.09

(Fig. B) As above in enclosed case 2Hx4Wx 3"D. Shpg. wt., 10 oz.

99 R 01018 Net 3.19

VOLUME CONTROL ADAPTER



Built in volume control permits high volume signals to be fed into the high gain input of tape recorders without overloading. Phono jack input to a 2-conductor standard phone plug output. Completely shielded. Designed for use in unbalanced stereo channels; use in pairs for dual stereo channel control. Imported. Shpg. wt., 4 oz.

99 R 00994 Net 1.59

STEREO SELECTOR SWITCHES FOR SOLID STATE HI-FI SYSTEMS



Speaker selector switch for solid state stereo systems. Allows choice of one of three pairs of speakers. High quality, non-shorting contacts capable of handling up to 60 watts audio. Imported. Shpg. wt., 7 oz.

Wall Box Selector. 99 R 01745 Net 2.19

Enclosed Case Selector. 99 R 01752 Net 3.19

LAFAYETTE MULTIPLE 6 SPEAKER SWITCHES



(A)

(B)

- Recommended only for Hi-Fi Systems Using Vacuum Tube Circuitry

Multiple Speaker Switch Constant impedance device for controlling any 6 remote speakers; up to 63 different combinations. Wall mounting with brass plate. With instructions and hardware. Shpg. wt., 5 oz.

99 R 00548 Imported. Fig. A Net 2.69

Multiple Speaker Switch Identical to above but mounted on flat, gold-embossed plate for mounting on flat panel. 3 1/2 x 2 3/8". Imported. Shpg. wt., 4 oz.

99 R 00663 Fig. B Net 2.29

LAFAYETTE REMOTE SPEAKER SWITCHES



(Fig. A)

(Fig. B)

- Recommended only for Hi-Fi Systems Using Vacuum Tube Circuitry

(Fig. A) For manual use. Selects any one of 3, or any combination of 2 or 3 speakers with up to 60 watts of audio power. A constant impedance device. On gold finished steel electric outlet plate with black and ivory knob. 2 3/4 x 4 1/2". Imported. Shpg. wt. 8 oz.


99 R 00531 Net 1.59

(Fig. B) Same as above in enclosed case 3 1/4 x 4 1/2". Imported. Shpg. wt., 11 oz.

99 R 00838 Net 1.98

STEREO SPEAKER WALL JACK KIT

1 49



A handsome ivory-finish wall stereo jack kit designed to be mounted in a standard outlet box. Ideal for remote amplifiers or for added stereo pleasure in the den, play room, etc. Contains two standard 1/4" phone plugs and two standard 1/4" phone jacks. Size: 4 1/4" x 2 1/4". 1" back clearance required. Imported. Shpg. wt., 6 oz.

99 R 01364 Net 1.49

Cutler Hammer Switches

AC - DC TOGGLE SWITCHES LIGHT DUTY — 3 to 6 AMPS

For use on small motor-driven tools and appliances where a sturdy switch is required. Long life and high arc resistant. $\frac{1}{2}$ " dia. threaded stem. Length of stem $\frac{1}{2}$ ", except $\frac{1}{4}$ " and $\frac{3}{8}$ " $\frac{1}{4}$ ". All have solder lug terminals except # 6" wire leads, $\frac{1}{2}$ " screw terminals. All 3 amps at 250V except $\frac{1}{2}$ " amp. U.L. listed. Avg. shgp. wt., 3 oz.

Stock No.	Mfr's. Type	Con-tacts	Fig.	Amps Net Each		
				125V	1-24	25-49
34 R 33026	8280-K-14*	SPST	A	3	.77	.71
34 R 33034	8280-K15†	SPST	A	3	.77	.71
34 R 33042	8280-K16	SPST	A	3	.77	.71
34 R 33059	8282-K13††	SPDT	G	3	.97	.89
34 R 33067	8282-K14†	SPDT	G	3	.97	.89
34 R 33091	8290-K15†#	SPST	B	3	.92	.85
34 R 33109	8290-K16#	SPST	B	3	.92	.85
34 R 33117	8295-K7††	SPST	C	3	.92	.85
34 R 33125	8295-K8†	SPST	C	3	.92	.85
34 R 33133	8360-K6*	DPST	G	3	1.40	1.27
34 R 33141	8360-K7	DPST	G	3	1.40	1.27
34 R 33166	8363-K6*	DPDT	E	3	1.59	1.46
34 R 33174	8363-K7	DPDT	E	3	1.59	1.46
34 R 33182	8363-K8†	DPDT	E	3	1.59	1.46
34 R 33208	8370-K7	DPST	G	6	1.48	1.37
34 R 33224	8372-K7†	DPST	D	6	1.81	1.67
34 R 33257	8375-K7†	DPDT	D	6	2.19	2.02
34 R 33281	8391-K7††	SPST	B	6	1.04	.96
34 R 33299	8391-K8#	SPST	B	6	1.04	.96

AC TOGGLE SWITCHES LIGHT DUTY — 6 AMPS

For use in radios, appliances and other equipment which use snap action mechanism. All rated 6 amps at 125V and 3 amps at 250V. * Center-off position. Threaded stems are $\frac{1}{2}$ " in. dia., stem length $\frac{1}{2}$ ". U.L. listed. Avg. shgp. wt., 3 oz. † indicates screw terminals, †† indicates solder terminals.

Stock No.	Mfr's. Type	Contacts	Fig.	Amps Net Each		
				125V	1-24	25-49
34 R 33430	7580-K4†	SPST	K	.81	.74	
34 R 33448	7580-K6†	SPST	K	.70	.64	
34 R 33455	7581-K4†*	SPDT	K	.92	.85	
34 R 33463	7581-K6†*	SPDT	K	.75	.70	
34 R 33513	7582-K6†	SPDT	K	.75	.70	
34 R 33521	7590-K4†	DPST	F	1.23	1.13	
34 R 33539	7590-K6†	DPST	F	1.00	.92	
34 R 33547	7591-K4†*	DPDT	F	1.46	1.34	
34 R 33554	7591-K6†*	DPDT	F	1.12	1.04	
34 R 33562	7592-K4†	DPDT	F	1.46	1.34	
34 R 33570	7592-K6†	DPDT	F	1.12	1.04	

"ROCKETTE" SWITCHES

Modern design, dependable, with nylon rocker type actuator. Fast connect .250" terminals. Requires $\frac{1}{4}$ " x $\frac{1}{4}$ " hole. U.L. and CSA listed. Shgp. wt., 3 oz.

Stock No.	Mfg. Type	Amperes	125V	250V	Cont.	Net Each	
						1-24	25-49
34 R 34164	8134K21A1M52	6	3	SPST	.72	.66	
34 R 34107	8144K20A1M52	15	10	SPDT	.91	.84	
34 R 34115	8142K21E6M52	15	10	DPST	1.24	1.15	

ON-OFF PLATE FOR TOGGLES

34 R 33935	Shgp. wt., 3 oz.	1-9	.06
		10-99	.05

LAFAYETTE FOOT SWITCH



Only **2⁹⁹**

Keeps Your Hands Free!

The ideal switch for safe, hand free control of bench tools, appliances or other electrical devices. Rated at 10 amps, 125 Volt A.C. Merely step on the switch and constant power is supplied until foot is removed. Supplied with six foot cord and plug. Plug unit into the wall and appliance into the back of plug. Steel housing is finished in gray crackle and has a skid-proof base. Size: 2 $\frac{3}{4}$ " square x 1" high. Imported. Shgp. wt., 1 lb. 99 R 80707 Net Ea. 2.99

STANDARD DUTY — 10 to 15 AMPS

Slow make, slow break mechanism. All have 15/32 diameter threaded stem. 15/32 long except $\frac{1}{2}$ " 11/32 long, and * center off, all rated 10 amps at 250 V AC and 15 amps at 125V AC. U.L. listed. Avg. shgp. wt., 4 oz. † indicates screw terminal, †† indicates solder terminals.

Stock No.	Mfr's. Type	Contacts	Fig.	Amps Net Each		
				1-24	25-49	
34 R 33588	7500-K13††	SPST	K	.84	.77	
34 R 33596	7500-K14†	SPST	K	.84	.77	
34 R 33612	7501-K13†	SPST	K	.73	.68	
34 R 33638	7502-K13†	SPDT	K	.99	.91	
34 R 33653	7503-K13†*	SPDT	K	.84	.77	
34 R 33679	7504-K4†	SPDT	K	.99	.91	
34 R 33695	7505-K4†	SPDT	K	.84	.77	
34 R 33703	7500-K5†	DPST	F	1.33	1.22	
34 R 33729	7561-K4†	DPST	F	1.12	1.03	
34 R 33745	7562-K4†*	DPDT	F	1.63	1.50	
34 R 33778	7563-K5††*	DPDT	F	1.33	1.22	
34 R 33786	7564-K6†	DPDT	F	1.63	1.50	
34 R 33802	7565-K5†	DPDT	F	1.33	1.22	
34 R 33810	7565-K6†	DPDT	F	1.33	1.22	
34 R 33844	7610-K2†	DPST	F	2.54	2.35	
34 R 33851	7611-K2†	3PST	L	2.18	2.01	
34 R 33877	7613-K2†*	3PDT	L	2.68	2.48	
34 R 33893	7615-K2†	3PDT	L	2.68	2.48	

HEAVY DUTY — 15 to 20 AMPS

Switches contain heavy parts, larger clearances and higher ratings. Handle large motors and heavier loads. Longer life on lighter loads. All bakelite bodies, screw terminals and quick make and break contacts. $\frac{1}{2}$ " threaded stem $\frac{1}{2}$ " long except * $\frac{1}{2}$ " stem. U.L. listed. All 10 amps at 250V except † 20 amps. Shgp. wt., 4 oz.

Stock No.	Mfr's. Type	Con-tacts	Fig.	Amps Net Each		
				125V	1-24	25-49
34 R 33356	7360-K7*	DPST	H	20	2.41	2.23
34 R 33364	7360-K8	DPST	H	20	2.41	2.23
34 R 33372	7361-K5	SPST	H	20	2.52	2.33
34 R 33406	7402-K4†	DPST	H	20	3.24	2.99

STANDARD DUTY — 8 to 16 AMPS

Quick make, quick break contact mechanism eliminates pitting caused by high arcing. These long life switches are primarily designed for use on small motors and similar equipment. All in bakelite case with screw terminals. $\frac{1}{2}$ " threaded stem x 15/32 long except † 11/32 stem length. U.L. listed. All 8 amp at 250V and 16 amp at 125V, except † 5 amps at 250V. Avg. shgp. wt., 3 oz.

Stock No.	Mfr's. Type	Con-tacts	Fig.	Amps Net Each		
				125V	1-24	25-49
34 R 33323	7320-K2†	DPST	H	16	1.40	1.29
34 R 33943	7320-K3	DPST	H	16	1.40	1.29
34 R 33331	7321-K2†	SPST	H	16	1.50	1.39
34 R 33360	7321-K3	SPST	H	16	1.50	1.39
34 R 33349	8680-K1††	DPDT	H	5	4.17	3.85

SPST MIDGET SWITCH

Type 8097-K3. Bat handle $\frac{1}{4}$ " from end of threaded stem. 3 Amps at 125V AC. .75 at 250V DC. Screw terminals. Threaded stem dia. $\frac{1}{8}$ ", stem length $\frac{1}{2}$ ". Shgp. wt., 2 oz.

Stock No.	Fig.	Net Each	
		1-24	25-49
34 R 33018	M	.59	.54

LAFAYETTE

SUBMINIATURE SWITCHES

TOGGLE SWITCH Industrial quality, subminiature, D.P.D.T., AC toggle switch. Rated at 10 amps, 125 volts A.C. Life tested through 100,000 cycles. Contact resistance, 0.01 ohms. Insulation resistance 100 meg-ohms at 500 V.A.C. Maximum breakdown voltage 1000 V.A.C. Body size $\frac{1}{2}$ " x $\frac{1}{2}$ " x $\frac{1}{4}$ ". Bushing $\frac{1}{4}$ " Dia. Handle $\frac{3}{16}$ " L. Behind panel depth, including lugs, $\frac{3}{16}$ ". Includes slip-on insulator for handle, mounting hardware and "on-off" plate. Shgp. wt., 2 oz. Net ea. 1.49
99 R 61624 Imported
Lots of 100 ea. 1.19 Lots of 10 ea. 1.35
SUBMINIATURE MOMENTARY PUSH-BUTTON SWITCH. All dimensions and specifications exactly the same as above except momentary push-button action, imported.
99 R 61830 Shgp. wt., 2 oz. Net ea. 1.89
Lots of 100 ea. 1.56 Lots of 10 ea. 1.70



MALLORY Switches and Dial Plates

CERAMIC SELECTOR SWITCHES



Ideal for RF circuits. All non-shorting. Ceramic insulation, silver plated contacts. 1/2" spacing between gangs except 1" on 3 gang. Voltage breakdown 500V AC or DC. Max. non-breaking resistive load is 10 amps, 1" mtg. radius. Notched shaft 2 1/4" diameter with 3/8" bushing. Adjustable stop. Type with * have added "OFF" position preceding others. With knob, nut and lockwasher. Shpg. wt., 5 oz.

SINGLE GANG

Stock No.	Mfg. No.	Poles Pos.		1-4 Each	5-9 Each
		Gang	Pole		
30 R 40573	172C	1	11	2.77	2.31
30 R 40581	173C*	2	5	2.77	2.31
30 R 40599	174C*	3	3	2.77	2.31

Shpg. wt., 8 oz. THREE GANG

Stock No.	Mfg. No.	Poles Pos.		1-4 Each	5-9 Each
		Gang	Pole		
30 R 40631	180C	1	11	5.04	4.21

ALL PURPOSE SWITCHES



Single section phenolic type 2" long by 1/4" dia. shaft with 3/8" bushing. Supplied with knob lockwasher and nut except † uses knurled shaft, no knob furnished. Shpg. wt., 4 oz.

SHORTING TYPES

Stock No.	Mallory No.	Cir. Pos.	1-4 Each	5-9 Each	
					30 R 49202
30 R 49210	5M1113	1	3	1.19	.99
30 R 49228	5M1113K†	1	3	1.19	.99

DIAL PLATES



Silver markings on black background. 30° spacing plates for all Mallory 1200 L and 1300 L series switches and for 1 1/4" base. 3100 J and 3200 J series. Shpg. wt., 2 oz.

Stock No.	Marking	Stock No.	Marking
30 R 40664	1 to 2	30 R 40771	Off 1 to 3
30 R 40672	1 to 3	30 R 40789	Off 1 to 4
30 R 40680	1 to 4	30 R 40797	Off 1 to 5
30 R 40698	1 to 5	30 R 40805	Off 1 to 6
30 R 40706	1 to 6	30 R 40813	Off 1 to 7
30 R 40748	1 to 10	30 R 40821	Off 1 to 8
30 R 40755	1 to 11	30 R 40839	Off 1 to 9
30 R 40763	1 to 12	30 R 40847	Off 1 to 10

ANY OF ABOVE NET EACH 20

MALLORY SINGLE GANG ROTARY SWITCHES

Single gang, phenolic wafer. 1 1/4" diameter and 30° indexing except * are 1 1/2", and have 20° indexing and adjustable stop. Voltage breakdown 300 V AC or DC. 2" notched shaft with 3/8" threaded bushing. 3/8" long. With bar knob, nut and lockwasher. Shpg. wt., 5 oz.

Shorting Type		Non Shorting		Poles	Posi- tions	Net Each
Stock No.	Mfg. No.	Stock No.	Mfg. No.			
30 R 40011	3115J	30 R 40136	3215J	1	5	1.20
30 R 40029	3112J	30 R 40144	3212J	1	12	1.20
30 R 40037	3122J	30 R 40151	3222J	2	2	1.20
30 R 40045	3123J	30 R 40169	3223J	2	3	1.20
30 R 40052	3126J	30 R 40177	3226J	2	6	1.20
30 R 40060	3134J	30 R 40185	3234J	3	4	1.24
30 R 40078	3142J	30 R 40193	3242J	4	2	1.24
30 R 40086	3143J	30 R 40201	3243J	4	3	1.24
30 R 40110	3136*	30 R 40235	3236*	3	6	1.93
30 R 40128	3163*	30 R 40243	3263*	6	3	1.93

LEVER ACTION SWITCHES



Positive action, phenolic sections. 6000 series have mtg. brackets with round holes 1 3/8" apart; 5000 series have elongated holes in bracket with 2 3/8" centers. Voltage rating 500 VAC-DC. Max. non-breaking current resistive load, 6 amp. at 5 VAC. 20° indexing with knob and hardware. Shpg. wt., 5 oz.

Stock No.	Mfg. No.	Poles Pos.		1-4 Each	5-9 Each
		Gang	Pole		
30 R 41209	5124	2	4	1.62	1.35
30 R 41217	5142	4	2	1.41	1.17
30 R 41229	5143	4	3	1.41	1.17

Non-Shorting

30 R 41239	5224	2	4	1.62	1.35
30 R 41241	6242	4	2	1.41	1.17
30 R 41250	6243	4	3	1.41	1.17

MINIATURE PUSH-BUTTON SWITCHES



Non-locking type, contact made only when depressed. Silver contacts, cadmium plated frame. Mount in 1/4" hole on up to 1/4" panels. Mtg. radius 1/4". Mtg. depth 3/8" min to 7/8" max. Circuit codes: M=make, B=break, MBB =make before break. Voltage breakdown 500 V DC. With hardware. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	Circuit	Net Ea.
30 R 41118	1011	SPST-M	.82
30 R 41126	1012	SPST-B	.82
30 R 41134	1013	SPDT	.90
30 R 41142	1014	DPST-M2	1.03
30 R 41159	1015	DPST-B2	1.03
30 R 41167	1016	DPDT	1.24

DECADE SWITCHES



Type 154L resistor switch for simple construction of decade boxes (up to 10 positions). Phenolic insulation. The number of positions is adjustable for use as a single decade or with more switches as a multiple decade. Requires only 4 resistors for full decade operation. Depth behind panel is 1". Lateral space 2". Voltage breakdown rating 500V DC or AC. Shaft 2" long x 1/4" diameter. With knob and hardware. Shpg. wt., 5 oz.

Stock No.	Type	1-4 Each	5-9 Each
30 R 41274	154L	3.44	2.88

Type 389 Dial Plate for above
30 R 40839 Net .12

MINIATURE LEVER SWITCHES



Phenolic type all are single section type. Contact rating is 350 MA at 500 volts RMS resistive load. 30° indexing. Mtg. holes 1 1/4" apart. * are spring action and spring return. † are spring return. Supplied with lever knob. Shpg. wt., 3 oz.

SHORTING TYPES

Stock No.	Mfr. No.	Cir. Pos.	1-4 Ea.	5-9 Ea.	
					30 R 41472
30 R 41498	6M1213U*	2	3	1.82	1.52
30 R 41506	6M14125†	4	2	1.98	1.63

NON-SHORTING TYPES

30 R 41514	6M2213	2	3	1.39	1.16
30 R 41922	6M2213S†	2	3	1.58	1.32
30 R 41530	6M2213U†	2	3	1.82	1.52
30 R 41548	6M24125†	4	2	1.92	1.60

MULTIGANG ROTARY SWITCHES



Phenolic wafers. 1/2" spacing between gangs except 3 and 4 gang is 1". Indexing is 30°. Have 1 fixed and 1 adjustable stop. Voltage breakdown 1000V AC or DC. Contacting members silver coated 2" notched shaft requires 3/8" mtg. hole. Types with * have additional off position with all circuits open. With bar knob, nut and lock washer. Avg. shpg. wt., 8 oz.

Non-Shorting Stock No.	Mfg. No.	Gang	Pos.	Total Per Pole		NET Each
				Pole	NET	
30 R 40417	1311L	1	11	2.46	2.46	
30 R 40425	1315L*	1	2	5	2.46	
30 R 40435	1313L*	1	3	3	2.46	
30 R 40445	1312L*	1	4	2	2.46	
30 R 40458	1321L	2	2	11	3.00	
30 R 40466	1325L*	2	4	5	3.00	
30 R 40482	1322L*	2	8	2	3.00	
30 R 40498	1331L	3	3	11	3.78	
30 R 40508	1335L*	3	6	5	3.78	
30 R 42686	1333L*	3	9	3	3.78	
30 R 42694	1332L*	3	12	2	3.78	
30 R 40518	1341L	4	4	11	4.45	
30 R 40524	1345L*	4	8	5	4.45	
30 R 42678	1342L*	4	16	2	4.45	
30 R 40532	1351L	5	5	11	4.81	
30 R 40540	1356L*	5	10	5	5.29	
30 R 40557	1361L*	6	6	11	5.65	
30 R 40565	1366L*	6	12	5	6.45	

UNIVERSAL MOUNTING BRACKET

"L" shape. For rear support of switches. Shpg. wt., 2 oz.
30 R 41100 Type RB254 Net .09

PHENOLIC MINIATURE ROTARY SWITCHES



Stators and rotors use Richardson T725 grade phenolic. Has common contact on same side as the switching contacts. Commercial equivalent to MIL-S-3786. Resistor voltage between contacts, and contacts and frames is 1700 V R.M.S., 60 cycles. Contact rating is 350 MA at 500 volts R.M.S. resistive load. Shaft is 2" long by 1/4" dia. with 1/2" spacing between wafers. Wafers are 1 1/4" dia. and 30° indexing. Overall dia. 1 1/4". Supplied with knob, adjustable stop, lock washer and nut. Shpg. wt., 5 oz.

Non-Shorting Stock No.	Mfr. No.	Cir. Per Sec.	Pos.	1-4 Ea.		5-9 Ea.
				Pos.	NET	
30 R 41720	4M21111	1	1	11	1.98	1.65
30 R 41738	4M2215	2	1	5	1.98	1.65
30 R 41746	4M21211	1	2	11	2.84	2.37
30 R 41787	4M2225	2	2	5	2.84	2.37
30 R 41803	4M21511	1	5	11	4.83	4.11
30 R 41811	4M2323	3	3	11	2.84	2.37
30 R 41837	4M21611	1	6	11	5.54	4.63
30 R 41852	4M2245	2	4	5	4.20	3.51

Switches—Toggle, Push-Button, Slide & Telephone

TOGGLE SWITCHES

1 SPST BAT HANDLE
 Rated 3 amps—125V. Body size 1 1/4 x 3/4 x 1/2" behind panel. Bushing 7/16" diam. 7/16" long. Bat handle 1/2" long. Shpg. wt., 3 oz. Imported.
 99 R 61509 Net ea. .34
 In lots of 10, ea. .29

2 HEAVY DUTY 6 AMP DPDT
 Rated 250V at 3 Amps or 125V at 6 amps. Switch body 1 1/4 x 3/4 x 7/8" behind panel including terminals. Bushings 15/32" Dia. 7/16" long. Bat handle 1/2" long. Shpg. wt., 3 oz. Imported.
 99 R 61517 Net ea. .44
 In lots of 10, ea. .40

3 6 AMP. DPDT CENTER OFF
 Rated 6 amps, 125 V.A.C. 1 1/4 x 3/4 x 1" behind panel including screw terminals. Bushing 7/16 x 7/16". 5/8" bat handle. Shpg. wt., 3 oz. Imported.
 99 R 61483 Net ea. .55
 In lots of 10, ea. .50

4 10 AMP. SPDT CENTER OFF
 Rated 10 amps at 125V. Silvered lugs for low loss connections. Body size 1 1/4 x 9/16 x 5/8" depth behind panel. Bushings 3/8" Dia., 7/16" long. Bat handle 1/2" long. Shpg. wt., 3 oz. Imported.
 99 R 61558 Net ea. .44
 Lots of 10, ea. .40

PUSH-BUTTON SWITCHES

5 MINIATURE MOMENTARY
 Momentary contact push-button switch ideal for all miniaturized applications. Single pole two circuit push-to-make type. Beryllium copper leaf contacts. Overall diameter 1/2", overall depth 11/16", protrudes 3/8" behind panel. Bushing 1/4" dia., 3/16" long. Supplied with washer and mounting nut. Shpg. wt., 3 oz. Imported.
 Miniature Push-Button Switch.
 99 R 62184 Net ea. .24
 In lots of 10, ea. .21

7 SUB-MINIATURE MOMENTARY
 Momentary contact push button switch. SPST, non-snap action. Rated 115V AC at 100 ma. Overall dimensions 3/8 x 3/4 x 1/4". Bushing 1/4" long. Shpg. wt., 2 oz. Imported.
 99 R 61590 Net ea. .26
 5 for .23

6 ILLUMINATED P.B. SWITCH
 A compact illuminated switch which will indicate mode of operation at a glance. Button lights in "ON" position. Takes no more space than conventional switches. Lamp is built into push handle. SPST Type. Current capacity, 10 Amps at 125VAC, 6A at 250V AC; insulation resistance, 100 meg ohms or more at 500V DC. Solder terminals. Single-hole mtg. Mount in 13/64 hole, 1 1/2" behind panel. Shpg. wt., 3 oz. Imported.
 99 R 61921 Net 1.75

8 MINIATURE 4 PDT SPRING RETURN
 Push button switch. Ideal for ham or citizens band. Rated at 800 milliamp for 100V AC. Ideal for transistor application. Heavy duty spring. Two circuit operation. Measures 1 1/2 x 5/16 x 1/2" plus 1/2" plunger. Shpg. wt., 2 oz. Imported.
 99 R 61756 Net ea. .49

RUGGED TELEPHONE TYPE 4PDT LEVER SWITCH

CHROME PLATED CAM

79[¢]
 Telephone Type 4 PDT. Lever switch: 3 position lever action switch of non induction construction. Has 4 sets of SPDT contacts—Has 3 locking positions—Heavy insulated rollers. Panel mount, 15/16" mounting centers. Size: 2 1/2" long behind panel, 5/8 x 1 1/4" H. Shpg. wt., 3 oz. Imported.
 99 R 61491 Net ea. .79
 In lots of 5, 69

MINIATURE DPDT SLIDE SWITCH

29[¢]
 Perfect for ultra-small switch applications. Rated current capacity, 3 amps at 125 volts. Can withstand up to 1000V AC. Solder lug terminals. Measures 15/16L x 1/4W x 3/8" D. Mounting centers: 13/16". Shpg. wt., 2 oz. Imported.
 99 R 61863 Net .29

3PDT AC-DC SLIDE SWITCH

29[¢]
 3 PDT AC-DC Slide Switch: Rated at 500 microamps at 100V. Solder lug terminals. Measures 3/4" W x 1 3/8" L x 7/8" D. Overall including 5/16" trigger. Mounting centers 1 1/4". Shpg. wt., 4 oz. Imported.
 99 R 61665 Net ea. .29
 In lots of 10, ea. .25

DELAY ACTION SWITCHES FOR HOME AND CAR

(A) (B)
 • Keeps light on for 60 seconds after turning off switch

For the home. Install in regular wall outlet. Keeps outside lights on for 60 seconds while you go to car. Rated 10 amps 125V (Fig. A) Shpg. wt., 5 oz.
 34 R 38058 Net 2.39

For the car. Keeps car lights on for 60 seconds while you walk to house then turns them off automatically. Easy to install in any 6 or 12 Volt car. 3/4 x 1 1/4" diam. (Fig. B) Shpg. wt., 6 oz.
 34 R 46010 Net 2.39

SLIDE SWITCHES AT LOW PRICES

 Compact slide switches in cadmium steel housings. All rated 3 amp at 125 volts AC. 1 1/4" mounting centers. Shpg. wt., 3 oz.

Stock No.	Circuit	Net Each	Lots 10 Each
34 R 37035	SPST	.19	1.65
34 R 37043	SPDT	.22	1.95
34 R 39114	DPST	.24	2.15
34 R 39122	DPDT	.26	2.35

ULTRAMINIATURE SPDT SLIDE SWITCH

29[¢]
 Exceptionally shallow design—only 1/8" deep for panel mounting. Contact resistance: 1/20 ohm or less; Insul. res., 20 megohms at 500V DC., max. AC current 0.5 amps. Withstands 600V AC. Size 5/8 x 1/8 x 5/16". Size of switch body, mounting ears add 1/2" to overall length. Mfg. centers 1". Shpg. wt., 2 oz. Imported.
 99 R 61897 Net .29

MIDGET-BAKELITE KNIFE SWITCHES

 Complete switches mounted on black bakelite base with insulated knob handle of black bakelite. Plated brass contacts provide positive low-resistance connection. Imported.

SPDT KNIFE SWITCH
 Overall size 1 1/4 x 2 3/4". Shpg. wt., 2 oz.
 99 R 61525 Net .19 ea.—10 for 1.69

DPDT KNIFE SWITCH
 Overall size 1 5/8 x 2 3/4". Shpg. wt., 3 oz.
 99 R 61533 Net ea. .29
 In Lots of 10 .25 ea.

MASTER DISCONNECT SWITCH

 • Disconnects Battery & Generator Circuits With A Single Switch

With a flip of a single lever protect cars, boats against fires resulting from shorts, battery run down due to appliances unknowingly left on, theft by ignition "jumping" (when mounted in concealed position). Perfect for cars, boats, heavy equipment. All steel construction, operates on ball bearings for quick, easy operation and rapid reset. Fits 6 or 12 volts. Shpg. wt., 1 1/4 lb.
 11 R 87012 Net 6.75

Switches for Industry and Experimenters

MAGNETIC PROXIMITY SWITCH



- Magnet Switch—Circuit Closes When Magnet Approaches Switch
- Activating Magnet Supplied
- Hermetically Sealed

An ingenious little device that has untold uses in the home—in a burglar alarm system, electric trains, "magic tricks," and many more. As the magnet approaches the switch, the circuit closes. Hermetically sealed; precious metal contacts: 1 millisecond actuation. 15 watts resistive max. up to 1 amp to 250 volts. Size: 2 1/4" with leads. 34 R 44015 Shpg. wt., 3 oz. Net 1.89


MERCURY SWITCH KIT

- Silent—Swift
- Positive Action
- Hermetically Sealed In Glass



This kit of five mercury wetted switches is ideally suited to the needs of hobbyists and experimenters. Tilt activated switches come in varying shapes and current carrying capacities. With recommended maximum load at 115V AC resistive, the largest switch is rated at 5 amps., 115V. AC with smaller types rated down to 1 amp., 115V AC or less. 19 R 21253 Shpg. wt., 4 oz. Net ea. 2.98

LINEMASTER FOOT SWITCHES



Model B-2-S "Executive." Two momentary SPDT switches side by side. Interlock prevents both circuits from being operated at same time. Both sides normally off when not in use. 15 amps, 125 VAC. 4 1/2"x4 1/2". Shpg. wt., 1 1/2 lbs. 34 R 36086 Net ea. 7.50

Model T51-S "Treadlite". Compact, rugged, SPDT momentary contacts rated 7 amps at 125-250V. AC. 1/2 H.P. at 115V. AC. Rubber tread and skid-proof base 3 1/2"x2 1/2"x1". Shpg. wt. 10oz. 34 R 36011 Net ea. 2.90

Model T51-SC—Same with a six ft. cord and two prong series plug. U.L. Listed. Shpg. wt., 1 lb. 34 R 36029 Net ea. 4.35

Model T-51-SC-3—Same as above but with 3 conductor cord and 3 prong grounded series plug. U.L. Listed. Shpg. wt., 1 1/4 lb. 34 R 36078 Net ea. 5.60

Model 491-S "Compact"—SPDT momentary contacts rated 10 amps 125V. AC, 1/2 HP at 115V. AC. Steel housing, black wrinkle finish, skid-proof base. 2 7/8"x2 1/2"x2 1/4". Wt. 9 oz. 34 R 36037 Net ea. 3.50

Model 491-SC3—Same with eight foot cord and three prong grounded series plug. Shpg. wt., 1 1/4 lbs. U.L. Listed. 34 R 36094 Net ea. 6.45

HEAVY DUTY LOCK SWITCH



- For Burglar Alarm Systems
- Hidden Auto Disconnect

Heavy duty bakelite construction insures minimum internal resistance and greater current carrying capacity. Extra heavy contacts. Terminals set for simple installation—well recessed to prevent shorting. Installs in any hole from 3/4" to 1 1/4" in dia., in any panel up to 3/4" thick. Two terminal single throw. Key can be removed in both "on" and "off" position. Prevents tampering with automotive equipment. Activates alarm systems—only key can shut off. Suitable for marine equipment. With 2 keys. Wt., 5 oz. 33 R 64015 Net 1.59

ILLUMINATED "SEE-SAW" SWITCH

109



SPST. Flip action, rocker arm type equipment type, rated at 125V AC, 10 amp, illuminated. Fully enclosed. Mounts flush in panels up to 1/8" thick. Requires mounting hole 1 1/2"x5/8". Mtg. centers 1 1/4". Imported. Shpg. wt., 1/4 lb. 99 R 62598 Net ea. 1.09 Lots of 10 ea. .99

DPDT "SEE-SAW" SWITCH

59c



Flip action, rocker arm type equipment switch. Mounts flush in panel up to 1/8" thick. Requires rectangular mounting hole 1/2" x 1 1/4" long. Mtg. centers 1 3/8". Rated 4 amps at 125V AC. Imported. Wt. 1/4 lb. 99 R 61574 Net ea. .59 Lots of 10 ea. .54

4 POLE-3 POSITION

59c



Four pole rotary selector switch, 3 positions per pole. Useful in hi-fi preamps and stereo applications. Spring loaded, positive detent action. Shorting type. Over-all diameter 1 1/4". Depth behind panel, including lugs, 3/4". Bushing 3/8" x 3/8" 1/4" knurled shaft, 1 1/4" long. Shpg. wt., 3 oz. Imported. 99 R 61566 Net ea. .59 Lots of 10 ea. .53

RUGGED LEVER SWITCH FOR AUDIO AND INTERCOMS

109



4PDT Audio Lever Switch: Has 2 dual sets of single pole, double throw contacts. One set is momentary contact-spring return, (press-to-talk). In the reverse position of the lever (dictate), the second set of contacts remain in the positive position until released. Panel mounting, mtg. centers 1" apart. Size 2 1/4" long behind panel. 1 1/4"W x 1"H. Imported. Shpg. wt., 4 oz. 99 R 61582 Net ea. 1.09

HART AND HEGEMAN MOMENTARY PUSH BUTTON SWITCHES



Metal base push switches with laminated phenolic sections, slotted sleeve 15/32 diam., 7/16" long. All have solder lug terminal, and plain tops. Complete with mounting ring and nut. Rated 1A 125 VAC. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	1-Net Each	24-25-Up
2 CIRCUIT—ONE N.O., ONE N.C.			
34 R 34503	3392E	1.05	.97

Identical to the above switches except slotted sleeve is 1/2" by 1/4" long. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	1-Net Each	24-25-Up
2 CIRCUIT—ONE N.O., ONE N.C.			
34 R 34537	3392	1.05	.97
NORMALLY CLOSED—SPST			
34 R 34560	3391	.82	.75
NORMALLY OPEN—SPST			
34 R 34594	3391E	.82	.75

Type 3391-194 Snap-On Insulator Buttons for any of the above switches. Wt. 2 oz. 34 R 34628 Red Net ea. .24 34 R 34636 Black Net ea. .24

SWITCHCRAFT TINI-SWITCH

Subminiature push-button switch for use in limited space applications. Specially useful in miniaturized-transistor devices, microphones, intercoms or wherever an extra small switch is desired. One-piece plastic shaft available in red or black. Suitable for low level circuits only. No—normally open. NC—normally closed. Threaded 1/4" bushing. 11/16" long, requires 3/8" behind panel. Shpg. wt., 2 oz.




Black Type

Stock No.	Mfg. No.	Contracts	Net ea.
34 R 60011	961	SPST-NO	.63
34 R 60029	962	SPST-NC	.63
34 R 60037	963	SPDT	.75

Red Type

34 R 60045	951	SPST-NO	.63
34 R 60052	952	SPST-NC	.63
34 R 60060	953	SPDT	.75

REAR SEAT SPEAKER CONTROLS



Controls come completely mounted on black and silver metal plate with ivory pointer knob plus attached wiring for connections to both speakers. With mounting hardware and instructions. Imported. Shpg. wt., 3 oz.

FADER TYPE (Fig. A)

Controls the volume of both front and rear speakers. Gradually reduces the volume on one while increasing volume on the other. 32 R 22505 Net ea. .89

SWITCH TYPE (Fig. A)

Gives choice of front speaker alone, rear speaker alone, or both together. 32 R 22577 Net ea. .89

PUSH-BUTTON TYPE (Fig. B)

Just push a button to select front speaker alone, rear speaker alone, or both together. 32 R 22569 Net ea. 1.24

Selected Replacement Capacitors

SPRAGUE 500D MINIATURE METAL-CASE ALUMINUM ELECTROLYTIC CAPACITORS




- Hermetically Sealed
- With Plastic Sleeves

reliable, miniature aluminum electrolytic capacitors suitable for miniature electronic circuitry. Excellent replacement for transistorized equipment. Dia. varies from 1/8" to 3/4", lengths vary from 3/4" to 1 1/2". Shpg. wt., 2 oz.


ECONOMY TUBULAR ELECTROLYTICS

These electrolytic capacitors are specifically designed for service replacement applications. All single electrolytics are hermetically sealed in aluminum cans with outer cardboard insulating sleeves and have solid tinned copper leads. Dual and triple section electrolytics have wax impregnated cardboard tubes with mounting strap, and color coded insulated flexible leads. Avg. shpg. wt., 4 oz.



Stock No.	µF	Net Each 1-99 100 Up	Stock No.	µF	Net Each 1-99 100 Up	Stock No.	Mfd.	W.V.	Net Each	Net Each in Lots of 10		
6 Volt												
34 R 85273	1	.48 .315	34 R 85588	1	.48 .315	32 R 01100	10	25	.40	.36		
34 R 85281	2	.48 .315	34 R 85596	2	.45 .30	32 R 01118	25	25	.42	.38		
34 R 85299	3	.48 .315	34 R 85604	5	.48 .33	32 R 01126	20	150	.48	.43		
34 R 85307	5	.48 .315	34 R 85612	6	.48 .33	32 R 01134	40	150	.54	.49		
34 R 85315	10	.48 .33	34 R 85620	10	.48 .33	32 R 01365	150	150	.76	.68		
34 R 85323	15	.48 .33	34 R 85638	15	.51 .345	32 R 01142	8	450	.50	.45		
34 R 85331	20	.48 .315	34 R 85646	25	.54 .36	32 R 01159	20	450	.66	.59		
34 R 85349	25	.51 .345	34 R 85653	35	.57 .39	32 R 01167	40	450	.76	.68		
34 R 85356	100	.57 .39	34 R 85661	50	.60 .405	32 R 01373	80	450	1.17	1.05		
34 R 85364	150	.60 .405	34 R 85679	75	.63 .42	32 R 01381	100	450	1.28	1.15		
34 R 85372	200	.57 .39	34 R 85687	100	.63 .42	Dual Section Tubular Electrolytic						
34 R 85380	250	.60 .405	34 R 85695	150	.66 .45	32 R 01175	20-20	150	.55	.49		
34 R 85398	300	.69 .465	34 R 85703	200	.72 .495	32 R 01183	30-30	150	.58	.52		
34 R 85406	400	.66 .45	50 Volt					32 R 01191	40-40	150	.62	.56
16 Volt												
34 R 85414	1	.48 .315	34 R 85711	1	.45 .30	32 R 01209	50-30	150	.60	.54		
34 R 85422	2	.48 .315	34 R 85729	2	.48 .33	32 R 01217	50-50	150	.73	.66		
34 R 85430	5	.45 .30	34 R 85737	3	.48 .315	32 R 01399	80-50	150	.79	.71		
34 R 85448	6	.48 .33	34 R 85745	5	.51 .345	32 R 01407	100-50	150	.86	.77		
34 R 85455	8	.48 .33	34 R 85752	10	.45 .30	Triple Section Tubular Electrolytic						
34 R 85463	10	.48 .315	34 R 85760	20	.54 .375	32 R 01415	40-40-20	150	.86	.77		
34 R 85471	15	.51 .345	34 R 85778	35	.57 .39	32 R 01423	50-30-20	150	.86	.77		
34 R 85489	20	.48 .33	34 R 85786	50	.63 .42	32 R 01431	80-40-20	150	.93	.84		
34 R 85497	25	.54 .36	34 R 85810	2	.57 .39	WIDE RANGE ELECTROLYTIC CAPACITOR						
34 R 85505	30	.51 .345	34 R 85828	4	.63 .435	Replaces A Host of Popular Combinations						
34 R 85513	35	.54 .375	34 R 85836	5	.66 .45	Compact unit which provides exact electrical replacement for 8 original standard 150 VDC capacitors used principally in printed circuit home radio receivers. 1" dia. x 2 1/2" L. Shpg. wt., 3 oz.						
34 R 85521	50	.54 .36	34 R 85844	10	.72 .485	Replaces all of the following:						
34 R 85539	75	.54 .375	34 R 85851	20	.78 .525	50-30 mfd.	70-30 mfd.	75-30 mfd.	60-40 mfd.			
34 R 85547	100	.57 .39	150 Volt					80-40 mfd.	50-50 mfd.	70-50 mfd.	80-50 mfd.	
34 R 85554	150	.60 .405	34 R 85869	2	.54 .375	32 R 56300				Net 1.32		
34 R 85562	200	.66 .45	34 R 85877	5	.63 .435							
34 R 85570	350	.78 .525	34 R 85885	10	.72 .48							

CERAMIC DISC CAPACITORS



RATED
1000
DCWV

Stock No.	Cap.	Stock no.	Cap.
32 R 01472	5µf	32 R 01720	250µf
32 R 01480	6.8µf	32 R 01738	270µf
32 R 01498	10µf	32 R 01746	300µf
32 R 01506	12µf	32 R 01753	330µf
32 R 01514	15µf	32 R 01761	390µf
32 R 01522	18µf	32 R 01779	470µf
32 R 01530	20µf	32 R 01787	500µf
32 R 01548	22µf	32 R 01795	560µf
32 R 01555	25µf	32 R 01803	680µf
32 R 01563	27µf	32 R 01811	750µf
32 R 01571	30µf	32 R 01829	0.01µf
32 R 01589	33µf	32 R 01837	0.012µf
32 R 01597	39µf	32 R 01845	0.015µf
32 R 01605	47µf	32 R 01852	0.018µf
32 R 01613	50µf	32 R 01860	0.02µf
32 R 01621	56µf	32 R 01878	0.022µf
32 R 01639	68µf	32 R 01886	0.025µf
32 R 01647	75µf	32 R 01894	0.027µf
32 R 01654	82µf	32 R 01902	0.03µf
32 R 01662	100µf	32 R 01910	0.033µf
32 R 01670	120µf	32 R 01936	0.047µf
32 R 01688	150µf	32 R 01944	0.05µf
32 R 01696	180µf	32 R 01951	0.068µf
32 R 01704	200µf	32 R 01959	.01µf
32 R 01712	220µf		

Assort any of above for quantity price
10 for .90; Singly, each .10.

HIGH CAPACITY DISCS

.015 µf Shpg. wt., 2 oz.	
32 R 09483	10 far 1.26 Singly, ea. .14
.02 µf. Shpg. wt., 2 oz.	
32 R 09491	10 for 1.44 Singly, ea. .16

LAFAYETTE SUBMINIATURE SQUARE CERAMIC CAPACITORS



Shpg. wt., 2 oz.

75 VOLT MICROMINIATURE

Dependable conservatively rated ceramic capacitors designed for greatest capacitance in the smallest size.

Type	Cap. µF	Size LxWxThick.	Net Each	Lots of 10, Each
33 R 69014	.0005	1/8x 1/8x 1/8"	.20	.18
33 R 69022	.001	1/8x 1/8x 1/8"	.20	.18
33 R 69030	.002	1/8x 1/8x 1/8"	.20	.18
33 R 69048	.005	1/8x 1/8x 1/8"	.20	.18
33 R 69055	.01	1/8x 1/8x 1/8"	.27	.24
33 R 69063	.02	1/8x 1/8x 1/8"	.29	.26
33 R 69071	.05	1/8x 1/8x 1/8"	.32	.29
33 R 69089	.1	1/8x 1/8x 1/8"	.57	.51
33 R 69097	.2	1/8x 1/8x 1/8"	.76	.68

CERAMIC DISC KIT 48 VALUES



98¢

A fine selection of 48 ceramic disc type capacitors. Values included range from .001 mfd to 2 mfd. Voltage ratings range from 50 to 5000 volts DC. Ideal selection for servicemen, builders and experimenters. Shpg. wt., 3 oz.
32 R 60023 Net .98

SPRAGUE HYPASS CAPACITORS

Three terminal network feed-thru capacitors. Bypass VHF currents (up to 150Mc). Suppress TVI from shortwave transmitters, diathermy machines, etc.



Reduce vibrator hash, harmonic radiation generator and regulator noise. Wt. 4 oz.
• Have female screw terminals; + Bulkhead mounting.

Stock No.	Type No.	µF	Amps	WVDC	Net
34 R 83336	48P18*	.5	40	50	3.03
34 R 83344	48P8*	1	20	600	1.98
34 R 83351	46P12	.002	15	600	1.62
34 R 83369	80P3*+	1	20	600	2.16
34 R 83377	47P16	.002	20	5000	3.00

KIT OF 50 ASSORTED MICA CAPS.

AS LOW AS

99¢



A kit of popular mica capacitors for service-men. Contains 50 popular sizes. A handy assortment for any service shop or experiment. Shpg. wt., 1/2 lb.
34 R 72016 Net 1.19
Lots of 3 Ea. .99

Cornell-Mallory-Sprague-Aerovox



TUBULAR ELECTROLYTIC CAPACITORS



CORNELL BLUE BEAVER

Cornell Dubilier types BR and BBRD are dry electrolytics in compact aluminum cases. Highest quality for TV general replacement with extra safety for high surge voltages in power supplies. Very low leakage. Operating temperature up to 85°C.

MALLORY TC

Mallory type TC dry electrolytic capacitors are housed in aluminum containers. These compact units are of the highest quality and are ideal for use in TV radio and general replacement in electronic circuitry. Low leakage and built-in safety factors against high voltage surges. Operating temperature up to 85°C.

SPRAGUE "ATOMS"

Sprague types TVA and TV are dry electrolytics in extremely compact metal cases. They are designed to withstand high surge voltages and high ripple currents making them ideal for TV replacements, power supplies, etc. Leakage is very low. Efficient at temperatures up to 85°C.

AEROVOX DANDEE

Aerovox type PRS are dry electrolytic in compact aluminum cases. Dependable replacements for TV and all electronic equipment when a quality unit is required. Feature low leakage high voltage surge protection and operating temperature up to 85°C.

STANDARD BRANDS

Because no one manufacturer offers all sizes, we have made this integrated list. Your order will be filled with one of the 4 famous brands illustrated. We will supply any particular manufacturers brand specified, if available in the size desired. Avg. shpg. wt., 4 ozs.

SINGLE SECTION

NET EACH IN LOTS OF					NET EACH IN LOTS OF				
Stock No.	Cap. MFD.	W.V.	1-24	25-49	Stock No.	Cap. MFD.	W.V.	1-24	25-49
33 R 15082	1000	3	1.05	.82	34 R 55409	40	150	.81	.64
34 R 84011	50	6	.57	.45	34 R 55417	50	150	.84	.66
34 R 55102	100	6	.72	.56	34 R 55425	60	150	.90	.70
34 R 55110	250	6	.81	.64	34 R 55433	80	150	.96	.76
34 R 55128	500	6	.93	.74	34 R 55441	100	150	1.05	.83
34 R 55136	1000	6	1.14	.90	34 R 55458	150	150	1.14	.90
34 R 75027	1500	6	1.26	.99	34 R 75134	200	150	1.35	1.03
34 R 75035	2000	6	1.38	1.09	34 R 75373	300	150	1.68	1.30
34 R 75043	100	12	.72	.57	33 R 15421*	200	200	1.70	1.27
34 R 75050	250	12	.87	.69	34 R 75381	4	250	.66	.52
34 R 75068	500	12	1.02	.80	33 R 15124	5	250	.75	.54
34 R 75076	1000	12	1.35	1.07	34 R 75142	8	250	.69	.54
34 R 55144	100	15	.75	.58	33 R 15132	10	250	.72	.57
33 R 15090	200	15	.90	.67	34 R 55466	12	250	.75	.59
34 R 55151	250	15	.93	.74	34 R 55474	16	250	.78	.61
34 R 55169	500	15	1.05	.83	34 R 55482	20	250	.81	.64
34 R 55177	1000	15	1.38	1.09	34 R 55490	30	250	.87	.69
34 R 55185	2000	15	1.92	1.43	34 R 55508	40	250	.93	.74
34 R 56225	3000	15	2.37	1.82	34 R 55516	50	250	1.02	.81
34 R 56233	4000	15	3.00	2.25	34 R 55524	60	250	1.08	.85
34 R 56241	5000	15	3.27	2.45	33 R 15439*	140	300	1.85	1.38
34 R 84029	2	25	.54	.43	34 R 55532	4	350	.63	.50
34 R 84110	5	25	.60	.46	33 R 15140	5	350	.63	.50
34 R 75084	10	25	.60	.47	34 R 75159	10	350	.75	.60
34 R 75092	16	25	.60	.43	34 R 55565	16	350	.84	.67
34 R 55193	20	25	.60	.48	34 R 55573	20	350	.87	.69
34 R 55201	25	25	.60	.46	34 R 75167	24	350	.93	—
34 R 55219	50	25	.66	.52	34 R 55581	30	350	.99	.78
34 R 55227	100	25	.81	.64	34 R 55599	40	350	1.05	.82
34 R 55235	250	25	1.02	.80	34 R 55607	50	350	1.11	.87
34 R 55243	500	25	1.38	1.09	34 R 75399	60	350	1.17	.93
34 R 56258	1000	25	2.37	1.39	33 R 15447*	150	400	2.38	1.77
34 R 56266	2000	25	2.91	2.19	34 R 55615	1	450	.66	.52
33 R 15108	1	50	.54	.43	34 R 55623	2	450	.66	.53
34 R 75100	2	50	.54	.43	34 R 55631	4	450	.69	.54
34 R 55250	5	50	.60	.46	33 R 15157	5	450	.72	.62
34 R 55268	10	50	.60	.47	34 R 55649	8	450	.75	.60
34 R 75118	20	50	.60	.48	34 R 55656	10	450	.78	.61
34 R 55276	25	50	.63	.49	34 R 55672	16	450	.84	.66
34 R 75126	50	50	.72	.57	34 R 55680	20	450	.93	.74
34 R 55284	100	50	.84	.66	34 R 55698	30	450	1.02	.81
34 R 55292	150	50	.93	.73	34 R 55706	40	450	1.08	.85
34 R 55300	250	50	1.05	.83	34 R 75175	50	450	1.26	.99
34 R 55318	500	50	1.44	1.13	34 R 55714	60	450	1.41	1.12
34 R 56274	1000	50	2.34	1.81	34 R 55722	80	450	1.95	1.51
34 R 58189	1500	50	2.28	1.02	34 R 75183	100	450	1.92	1.53
34 R 58197	2000	50	3.48	2.60	34 R 55730	4	500	.72	.56
34 R 55326	4	150	.60	.47	34 R 55748	8	500	.78	.62
33 R 15116	5	150	.60	.48	34 R 75191	10	500	.81	.64
34 R 55334	8	150	.63	.49	34 R 55771	20	500	.96	.83
34 R 55342	10	150	.63	.48	34 R 55789	30	500	1.05	.79
34 R 55359	12	150	.66	.52	34 R 55797	8	600	1.83	1.42
34 R 55367	16	150	.69	.54	34 R 55805	10	600	2.19	1.70
34 R 55375	20	150	.72	.56	34 R 55821	16	600	2.49	1.93
34 R 55383	25	150	.75	.59	34 R 75209	20	600	2.58	2.00
34 R 55391	30	150	.78	.61	34 R 55839	8	700	1.74	1.33
					34 R 55862	16	700	2.25	1.69

DUAL SECTION—COMMON NEGATIVE

NET EACH IN LOTS OF				
Stock No.	Cap. MFD.	W.V.	1-24	25-49
33 R 15165	25-25	25	1.00	.77
34 R 55896	10-10	50	.96	.75
34 R 55912	20-20	150	1.05	.80
34 R 55920	20-20	150	1.02	—
34 R 55938	30-30	150	1.08	.86
34 R 55946	40-20	150	1.14	.88
34 R 55961	40-40	150	1.11	.88
34 R 55979	50-30	150	1.17	.91
34 R 55987	50-50	150	1.26	.96
34 R 84078	80-30	150	1.32	1.05
34 R 55995	80-40	150	1.32	1.01
34 R 75241	80-50	150	1.41	1.09
33 R 15470*	100-50	150	1.62	1.21
34 R 56015	100-100	150	1.92	1.47
34 R 75290	10-10	250	1.07	.85
34 R 56050	20-20	250	1.11	.88
34 R 56084	8-8	450	1.17	.91
34 R 75308	10-10	450	1.23	.98
34 R 56100	16-16	450	1.35	—
34 R 56118	20-20	450	1.50	1.18
34 R 56126	30-30	450	1.95	1.51

DUAL UNITS—SEPARATE SECTIONS

34 R 56142	15-15	150	1.37	1.14
34 R 56183	40-40	150	1.63	1.36
33 R 15413	70-70	175	2.00	1.68

TRIPLE SECTION

NET EACH IN LOTS OF				
Stock No.	Cap. MFD.	W.V.	1-24	25-49
34 R 56324	30-25-20	150	1.80	1.40
34 R 56340	40-20-20	150	1.80	1.40
34 R 56357	40-30-20	150	1.86	1.44
34 R 56365	40-40-20	150	1.86	1.45
34 R 75456	50-30-20	150	1.89	1.50
34 R 56381	80-40-20	150	1.98	1.54
33 R 15280	80-50-50	150	2.10	1.63
34 R 56464	50-30-20	150/25	1.86	1.43


QUADRUPLE UNITS

NET EACH IN LOTS OF				
Stock No.	Cap. MFD.	W.V.	1-24	25-49
34 R 56647	50-50-50-20	150/25	2.07	1.63
34 R 83385	80-10-40-1000	400/400/300/50	3.27	2.50

*Cardboard Tubular Wax-Filled Electrolytics

Prices and Specifications are Subject to Change Without Notice

Twist Prong Capacitors



**CORNELL
DUBILIER
TYPES
AA-BB-CC-DD**


**AEROVOX
TYPE
AFH**

CAPACITORS SIZE CHART

Average shpg. wt. 8 oz.

Code	Dia. x H	Code	Dia. x H	Code	Dia. x H
A	3/8" x 2"	F	1" x 3 3/8"	J	1 3/8" x 3 1/2"
B	1" x 2"	G	1 3/8" x 2 1/2"	K	1 3/8" x 3 3/8"
C	1" x 2 1/2"	H	1 3/8" x 2 1/2"	L	1 3/8" x 4"
D	1" x 3"	I	1 3/8" x 3"	M	1 3/8" x 4 1/8"
E	1" x 3 1/2"				

**SPRAGUE
TYPE
TVL**



**MALLORY
TYPES
FP-WP**



STANDARD BRANDS:

Because no one manufacturer makes all sizes, we have made this comprehensive integrated list. Orders will be filled with

one of the famous brands listed above. Ideal for high ripple selenium rectifier circuits. Average shpg. wt., 5 oz.

SINGLE SECTION TWIST PRONG

Stock No.	Mfd.	DCWV	Size	NET EACH 1-24 25-49		Stock No.	Mfd.	DCWV	Size	NET EACH 1-24 25-49		Stock No.	Mfd.	DCWV	Size	NET EACH 1-24 25-49	
34 R 84771	4000	15	J	3.33	2.40	34 R 57991	120	200	G	1.57	1.06	34 R 76371	80	450	I	2.10	1.45
34 R 76025	5000	50	G	1.83	1.20	34 R 76199	100	250	E	1.85	.98	34 R 76389	100	450	I	2.37	1.61
34 R 76033	1000	50	K	2.58	1.61	34 R 76207	150	250	H	2.13	1.15	34 R 76397	125	450	M	2.64	1.83
34 R 76041	1500	50	G	3.03	1.01	34 R 83278	160	250	H	2.13	1.29	34 R 76413	10	500	B	1.17	.75
34 R 76082	100	150	C	1.38	.82	34 R 58015	200	250	I	2.52	1.46	34 R 76439	30	500	D	1.38	.98
34 R 76108	120	150	C	1.50	1.01	34 R 76306	150	350	K	2.73	1.60	34 R 76447	40	500	F	1.71	1.09
34 R 76116	140	150	D	1.50	.90	34 R 76314	10	450	B	1.02	.72	34 R 76454	80	500	K	2.49	1.69
34 R 76157	300	150	I	1.95	1.33	34 R 76348	40	450	D	1.41	.97	34 R 76462	90	500	K	2.40	1.80

DUAL SECTION TWIST PRONG

Stock No.	Cap.	Mfd.	DCWV	Size	NET EACH 1-24 25-49		Stock No.	Cap.	Mfd.	DCWV	Size	NET EACH 1-24 25-49		Stock No.	Cap.	Mfd.	DCWV	Size	NET EACH 1-24 25-49				
34 R 76702	20-20	150	B	1.17	1.05	34 R 76587	100-100	350	M	4.23	1.99	34 R 77023	50-50	450	I	2.64	1.73	34 R 77072	80-40	450	K	3.48	1.91
34 R 76751	40-40	150	B	1.32	.88	34 R 76611	80-80	400	M	3.42	2.09	34 R 77148	20-20	500	H	1.95	1.34	34 R 77155	30-10	500	H	1.71	—
34 R 76769	50-30	150	B	1.38	.88	34 R 83286	80-2	450-350	M	2.31	1.57	34 R 77148	20-20	500	H	1.95	1.34	34 R 77155	30-10	500	H	1.71	—
34 R 76777	50-50	150	C	1.50	.91	34 R 76942	10-10	450	B	1.32	.90	34 R 77155	30-10	500	H	1.71	—	34 R 77155	30-10	500	H	1.71	—
34 R 76793	70-30	150	C	1.53	.91	34 R 76967	20-20	450	D	1.77	1.06	34 R 77155	30-10	500	H	1.71	—	34 R 77155	30-10	500	H	1.71	—
34 R 76819	80-40	150	C	1.59	1.11	34 R 76975	30-10	450	D	1.65	1.06	34 R 77163	40-40	500	I	2.25	1.56	34 R 77163	40-40	500	I	2.25	1.56
34 R 15371	80-50	150	C	1.65	.97	34 R 77015	40-40	450	I	2.37	1.56	34 R 77171	60-40	500	K	3.18	2.04	34 R 77171	60-40	500	K	3.18	2.04

TRIPLE SECTION TWIST PRONG

Stock No.	Cap.	Mfd.	WVDC	Size	Eq.	Stock No.	Cap.	Mfd.	WVDC	Size	Eq.	Stock No.	Cap.	Mfd.	WVDC	Size	Eq.
34 R 79581	80-60-250	150-150-10	H	2.04		34 R 79938	80-40-100	350-350-200	I	4.48		33 R 15405	20-10-10		450	D	2.01
34 R 79649	80-40-20	150-150-25	C	1.92		34 R 74046	100-10-80	400-400-350	M	4.20		34 R 74236	20-20-20		450	H	2.49
34 R 79698	40-40-40	150	C	1.80		34 R 74087	10-10-20	450-450-25	B	1.65		34 R 74285	40-30-20		450	I	2.97
34 R 79730	80-40-20	150	D	2.01		34 R 74095	20-20-20	450-450-35	D	2.10		34 R 74301	40-40-20		450	K	3.06
34 R 79821	140-100-60	300-300-50	M	4.17		34 R 74111	40-40-20	450-450-25	I	2.70		34 R 74319	40-40-40		450	K	3.39
34 R 79847	80-40-40	350	I	3.27		34 R 74178	80-20-100	450-450-50	M	3.30		34 R 74350	80-40-20		450	M	3.72
34 R 79870	125-5-100	350-200-75	K	3.26		34 R 74228	10-10-10	450	C	1.80		34 R 74392	30-20-20		500	I	2.91

QUADRUPE SECTION TWIST PRONG

Stock No.	Cap.	Mfd.	WVDC	Size	NET EACH 1-24 25-49 50-99		Stock No.	Cap.	Mfd.	WVDC	Size	NET EACH 1-24 25-49 50-99		
34 R 74418	50-40-160-40	150-150-25-25	G	2.46	2.21	5.05	34 R 83310	80-50-20-50		450-450-250-50	L	4.14	2.79	1.84
34 R 74426	60-40-20-200	150-150-150-10	G	2.37	1.36	1.09	34 R 83328	80-50-10-20		450-450-450-25	L	3.99	2.29	1.83
34 R 58106	60-100-60-60	350-350-200-75	M	4.10	2.43	2.05	34 R 74848	40-30-10-20		450-450-450-25	I	3.09	1.76	1.41
34 R 74632	40-40-40-40	350-350-350-25	I	3.60	1.75	1.40	34 R 84953	80-40-40-40		450-450-450-25	L	4.44	2.46	1.97
34 R 84912	70-40-10-50	350-350-350-50	I	3.63	1.77	1.42	34 R 74921	10-10-10-10		450	G	2.31	1.39	1.11
34 R 84904	100-20-10-20	350-350-350-50	J	3.72	1.80	1.44	34 R 74939	20-20-20-20		450	I	3.24	1.73	1.39
34 R 74574	40-40-40-40	350	K	3.84	1.99	1.80	34 R 74947	30-30-20-20		450	K	3.60	1.91	1.53
34 R 74699	100-10-30-20	400-400-50-50	K	3.84	1.99	1.80	34 R 74970	40-20-10-10		450	I	2.67	1.57	1.22
34 R 74723	80-40-10-100	400-400-400-200	M	4.38	2.30	1.84	34 R 73014	40-40-20-20		450	M	3.84	2.04	1.63
34 R 83302	30-20-160-40	450-450-250-150	L	4.08	2.15	1.72	34 R 73030	40-40-40-40		450	L	4.44	2.41	1.93
							34 R 73113	20-20-10-10		475	H	3.00	1.66	1.33

Centralab Ceramic Capacitors

Low Voltage Capacitors for Transistor Circuits

TYPE DM MIN KAPS

1/2 x 3/8 x 3/16" thick; Durez Coated 150 WVDC; Tolerance: + is +50%, -20%; all others are +80-20%. Shpg. wt., 2 oz.

Stock No.	Mfrs. Type	Cap mfd	1-99	100 up
33 R 21734	101*	.0001	.90	.72
33 R 21742	201*	.0002	.90	.72
33 R 21759	301*	.0003	.90	.72
33 R 21767	501*	.0005	.90	.72
33 R 21775	102*	.001	.90	.72
33 R 21783	202	.002	.90	.72
33 R 21791	302	.003	.90	.72
33 R 21809	502	.005	.90	.72
33 R 21817	103	.01	.90	.72
33 R 21825	2-502	2K.005	.90	.72

TYPE DA PLATE CAPACITORS

Size: 1/2 x 1/4 x 1/16" thick. Tolerance -20% to +100% 30 WVDC. Shpg. wt., 2 oz.

Stock No.	Mfrs. Type	Cap mfd	1-99	100 up
33 R 21171	203	.02	.36	.28
33 R 21189	503	.05	.81	.64
33 R 21197	104	.10	1.35	1.07



**DD60 6000 WVDC
DISC CERAMICS**

Tolerance ±20%. Avg. shpg. wt., 2 oz.

Stock No.	CRL No.	Cap	Stock No.	CRL No.	Cap
33 R 24084	4R7	4.7	33 F 24282	151	150
33 R 24118	100	100	33 F 24290	181	180
33 R 24134	150	150	33 F 24308	201	200
33 R 24175	300	300	33 F 24332	271	270
33 R 24183	330	330	33 F 24340	301	300
33 R 24191	390	390	33 F 24357	331	330
33 R 24209	470	470	33 F 24381	411	410
33 R 24217	500	500	33 F 24390	501	500
33 R 24233	680	680	33 F 24423	751	750
33 R 24266	101	100	33 F 24431	821	820

NET EACH ANY OF ABOVE IN LOTS OF

1-49 .36 50 UP .285

33 R 24449	102	1000	100 up .60 ea. 1-99 up .475 ea.
33 R 24456	122	1200	
33 R 24464	152	1500	
33 R 24472	202	2000	
33 R 24480	222	2200	

DA

DM UK



TYPE UK AND UK-10 ULTRA-KAPS

UK rated 3 WVDC, tolerance GMV; UK-10 rated 10WVDC; tol. +80%, -20%. Shpg. wt., 2 oz.

TYPE UK

Stock No.	Mfrs. Type	Cap. mfd.	1-99	100 up	Net Price
33 R 21221	UK104	.1	.42	.33	
33 R 21239	UK224	.22	.30	.24	
33 R 21247	UK474	.47	.30	.24	
33 R 21254	UK105	1.0	.36	.29	
33 R 21262	UK225	2.2	.42	.33	

TYPE UK-10

33 R 21270	UK10-503	.05	.18	.14
33 R 21288	UK10-104	.1	.18	.14
33 R 21296	UK10-204	.2	.30	.24
33 R 21304	UK10-474	.47	.42	.33

ELMENDO—SANGAMO—CENTRALAB

TYPE DM-10 (CM04) DIPPED SILVERED MICA CAPACITORS

Meets all the electrical requirements of military spec. #MIL-C-5C and EIA specification RS-153. All are 5% tolerance except * = min tolerance ± 1.0 pF. All 500 WVDC except † is 300 WVDC and ‡ is 100 WVDC. Wt., 2 oz.

Stock No.	Cap. pF	NET EACH	
		DM10- Type	1-9 99
30 R 35011 1*	010*	15	.12
30 R 35029 2*	020*	15	.12
30 R 35037 3*	030*	15	.12
30 R 35045 5*	050**	15	.12
30 R 35052 10	100	.23	.20
30 R 35062 12	120	.23	.20
30 R 35078 15	150	.23	.20
30 R 35086 18	180	.23	.20
30 R 35094 20	200	.18	.15
30 R 35102 22	220	.18	.15
30 R 35110 24	240	.18	.15
30 R 35128 27	270	.18	.15
30 R 35136 30	300	.18	.15
30 R 35144 33	330	.18	.15
30 R 35151 36	360	.20	.17
30 R 35169 39	390	.20	.17
30 R 35177 43	430	.20	.17
30 R 35185 47	470	.20	.17
30 R 35193 50	500	.18	.15
30 R 35201 51	510	.20	.17
30 R 35219 56	560	.20	.17

Stock No.	Cap. pF	NET EACH	
		DM10- Type	1-9 99
30 R 35227 62	620	.23	.17
30 R 35235 68	680	.23	.17
30 R 35243 75	750	.23	.17
30 R 35250 82	820	.23	.17
30 R 35268 91	910	.22	.18
30 R 35276 100	101	.22	.18
30 R 35284 110	111	.22	.18
30 R 35292 120	121	.23	.20
30 R 35300 130	131	.22	.18
30 R 35318 150	151	.23	.20
30 R 35326 160	161	.25	.21
30 R 35334 180	181	.25	.21
30 R 35342 200	201	.23	.24
30 R 35359 220	221	.30	.26
30 R 35367 240	241	.32	.27
30 R 35375 250	251	.30	.26
30 R 35383 270†	271	.30	.26
30 R 35391 300‡	301	.34	.29
30 R 35409 330‡	331	.32	.27
30 R 35417 360‡	361	.34	.29
30 R 35938 390‡	391	.35	.30



TYPE DM-19 (CM06) DIPPED SILVER MICA CAPACITORS

TYPE DM-19 (C Style CM06) Operate from -55 to 150°C. Meets all electrical requirements of mil spec MIL-C-5C and EIA spec RS-153. Capacitance values 430-4700 pF bear CM06 type designations. All have $\pm 5\%$ tolerance. All 500 DCWV except * 300 WV and † 180 WV. Shpg. wt., 2 oz.

Stock No.	Cap. MMF	NET EACH	
		DM19 Type	1-9 99
30 R 35425 100	101	.15	.12
30 R 35433 110	111	.15	.12
30 R 35441 120	121	.15	.12
30 R 35458 130	131	.15	.12
30 R 35466 150	151	.15	.12
30 R 35474 160	161	.15	.12
30 R 35482 180	181	.15	.12
30 R 35490 200	201	.15	.12
30 R 35508 220	221	.15	.12
30 R 35516 240	241	.15	.12
30 R 35524 250	251	.15	.12
30 R 35532 270	271	.16	.14
30 R 35540 300	301	.16	.14
30 R 35557 330	331	.16	.14
30 R 35565 360	361	.18	.15
30 R 35573 390	391	.18	.15
30 R 35581 430	431	.18	.15
30 R 35599 470	471	.22	.18
30 R 35607 500	501	.22	.18
30 R 35615 510	511	.22	.18

Stock No.	Cap. MMF	NET EACH	
		DM19 Type	1-9 99
30 R 35722 1500	152	.39	.33
30 R 35730 1600	162	.39	.33
30 R 35748 1800	182	.43	.36
30 R 35755 2000	202	.48	.41
30 R 35763 2200	222	.51	.44
30 R 35771 2400	242	.53	.45
30 R 35789 2500	252	.55	.47
30 R 35797 2700	272	.58	.50
30 R 35805 3000	302	.65	.56
30 R 35813 3300	332	.69	.59
30 R 35821 3600	362	.76	.65
30 R 35839 3900	392	.79	.68
30 R 35847 4300	432	.66	.74
30 R 35854 4700	472	.53	.80
30 R 35862 5000	502	.59	.84
30 R 35870 5100	512	1.00	.86
30 R 35888 5600*	562	.95	.81
30 R 35904 6800†	682	.92	.78
30 R 35912 7500‡	752	1.00	.86
30 R 35920 8200‡	822	1.09	.93

30 R 35623 560	561	.22	.18
30 R 35631 620	621	.23	.20
30 R 35649 680	681	.23	.20
30 R 35656 750	751	.25	.21
30 R 35664 820	821	.27	.23
30 R 35672 910	911	.27	.23
30 R 35680 1000	102	.29	.24
30 R 35698 1100	112	.30	.26
30 R 35706 1200	122	.32	.27
30 R 35714 1300	132	.36	.30



CENTRALAB CERAMIC TRANSMITTING CAPACITORS

Designed primarily for transmitter, induction heaters, X-Rays, etc. Tolerance 850 type $\pm 10\%$, 858 type $\pm 20\%$. Mounting $\frac{1}{8}$ " long hex studs tapped 6/32 thread. All 7500 DCWV except *5000 v. Temp. Coefficient types ending in Z NPO, ending in N N750. Avg. shpg. wt., 2 oz.

Stock No.	CRL No.	Cap. MMF.	Price Schedule
33 R 24498	850S-252	25	
33 R 24506	850S-502	50	
33 R 24514	850S-50N	50	1-4 2.70 ea.
33 R 24522	850S-75N	75	5-29 2.43 ea.
33 R 24530	850S-100N*	100	30-100 2.14 ea.
33 R 24548	858S-500*	500	
33 R 24556	858S-1000*	1000	

Depend on Lafayette For Everything in Electronics



CENTRALAB TYPE DD 1000 WVDC CERAMIC DISCS

Ideal for by-pass coupling in high frequency circuits. 1000 VDC working except DD-153, DD-203, DD-303, DD-403, DD-503 which are 600 VDC working. Tolerance all $\pm 10\%$ except * $\pm 20\%$, † ± 5 MMF, ‡ GMV. ** +80-20%. Avg. shpg. wt., 2 oz.

Stock No.	DD- mmf	Stock No.	DD- mmf
33 R 22580	3R3† 3.3	33 R 22989	391 39C
33 R 22591	5R0 5	33 R 24977	401 40C
33 R 22617	6R8 6.8	33 R 22997	471 47C
33 R 22625	7R5 7.5	33 R 23011	471G† 47C
33 R 22641	100 10	33 R 23029	501 50C
33 R 22658	120 12	33 R 23045	561 56C
33 R 22666	150 15	33 R 23052	601 60C
33 R 22674	180 18	33 R 23060	681 68C
33 R 22682	200 20	33 R 23078	751 75C
33 R 22690	220 22	33 R 23086	801‡ 80C
33 R 22708	240 24	33 R 23094	821 82C
33 R 22716	250 25	33 R 23102	911 91C
33 R 22724	270 27	33 R 23110	102‡ 100C
33 R 22732	300 30	33 R 23128	102G† 100C
33 R 22740	330 33	33 R 23136	122 120C
33 R 22757	390 39	33 R 23144	122G† 120C
33 R 22765	470 47	33 R 23169	152 150C
33 R 22773	500 50	33 R 23177	152G† 150C
33 R 22789	560 56	33 R 23193	182 180C
33 R 22807	680 68	33 R 23201	202 200C
33 R 22815	750 75	33 R 23219	222‡ 220C
33 R 22823	820 82	33 R 23227	252‡ 250C
33 R 22849	101 100	33 R 23235	272‡ 270C
33 R 22856	121 120	33 R 23243	302‡ 300C
33 R 22864	131 130	33 R 23250	332‡ 330C
33 R 22872	151 150	33 R 23268	392‡ 390C
33 R 22880	181 180		
33 R 22898	201 200	33 R 23284	432‡ 430C
33 R 22906	221 220	33 R 23292	472‡ 470C
33 R 22914	241 240	33 R 23300	472G† 470C
33 R 22922	251 250	33 R 23318	502‡ 500C
33 R 22930	271 270	33 R 23326	502‡ 500C
33 R 22948	301 300	33 R 23334	562‡ 560C
33 R 22956	331 330	33 R 23342	682‡ 680C
33 R 22963	351 350	33 R 23359	752‡ 750C
33 R 22971	361 360	33 R 23367	822‡ 820C

NET EACH ANY OF ABOVE IN LOTS OF 1-99 .15 100 UP .119

Stock No.	CRL No. DD-	Cap. MFD	1-99	100
33 R 23375	103‡	.01	.24	.19
33 R 23383	103‡*	.01	.24	.19
33 R 23391	153**	.015	.24	.19
33 R 23409	203**	.02	.45	.356
33 R 23417	303**	.03	.45	.356
33 R 23425	403**	.04	.45	.356
33 R 23433	503**	.05	.45	.356

CENTRALAB TYPE DD3 600 WVDC DUAL SECTION DISCS

Two individually shielded capacitors in one small case. All 600 WVDC. Tolerance GMV. Avg. shpg. wt., 2 oz.

Stock No.	DD3- MFD	Price Schedule
33 R 2344†	102 2X .001	
33 R 23458	152 2X .0015	1-99 .30 ea.
33 R 23466	202 2X .002	100 up .238 ea.
33 R 23474	502 2X .005	
33 R 23482	103 2X .01	

CRL DD-16 1600 WVDC CERAMIC DISCS

All tolerance GMV. Avg. shpg. wt., 2 oz.

Stock No.	CRL No. DD16-	Cap. MFD	1-99	Net Each in Lots of 100
33 R 23490	302	.003	.27	.21
33 R 23508	402	.004	.27	.21
33 R 23516	502	.005	.27	.21
33 R 23524	602	.006	.27	.21
33 R 23532	752	.0075	.27	.21
33 R 23547	802	.008	.27	.21
33 R 23565	103	.01	.27	.21

CENTRALAB DD-30 3000 WVDC DISC CERAMICS

Shpg. wt., 2 oz.

Stock No. DD30- mmf	Stock No. DD30- mmf
33 R 23581	4R7 4.7
33 R 23589	100 10
33 R 23596	220 22
33 R 23664	250 25
33 R 23680	300 30
33 R 23706	390 39
33 R 23714	470 47
33 R 23722	500 50
33 R 23730	560 56
33 R 23748	680 68
33 R 23755	750 75
33 R 23763	820 82
33 R 23771	101 100
33 R 23789	121 120
33 R 23813	201 200
33 R 23821	221 220
33 R 23854	301 300
33 R 23862	331 330
33 R 23870	391 390
33 R 23896	471 470
33 R 23904	501 500
33 R 23929	681 680
33 R 23938	751 750
33 R 23946	821 820

NET EACH ANY OF ABOVE IN LOTS OF 1-49 .24 50 up .19

Stock No. DD30- mmf	Stock No. DD30- mmf
33 R 23953	102 1000
33 R 23979	152 1500
33 R 23987	202 2000
33 R 24019	252 2500
33 R 24035	302 3000
33 R 24042	332 3300
33 R 24068	472 4700
33 R 24075	502 5000

NET EACH ANY OF ABOVE IN LOTS OF 1-49 .30 50 UP .238

Dipped Mylar - Paper Capacitors And Filters

STANDARD BRAND DIPPED MYLAR-PAPER CAPACITORS

CORNELL DUBILIER
"QUIETONE" FILTERS



**SPRAGUE
ORANGE DROP**



ELMENCO DP



MALLORY PVC

Shpg. wt., 2 oz.

100 WVDC

600 WVDC (Cont.)

Stock No.	CAP. MFD.	NET EACH IN LOTS OF		
		1-24	25-49	50-99
34 R 67016	.005	.16	.14	.12
34 R 67024	.006	.16	.14	.12
34 R 67032	.0068	.16	.14	.12
34 R 67040	.0075	.16	.14	.12
34 R 67057	.01	.16	.14	.12
34 R 67065	.015	.16	.14	.12
34 R 67073	.02	.16	.14	.12
34 R 67081	.022	.16	.14	.12
34 R 67099	.025	.16	.14	.12
34 R 67107	.03	.16	.14	.12
34 R 67115	.033	.16	.14	.12
34 R 67123	.04	.16	.14	.12
34 R 67131	.047	.20	.17	.14
34 R 67149	.05	.20	.17	.14
34 R 67156	.056	.20	.17	.14
34 R 67164	.068	.20	.17	.14
34 R 67172	.075	.20	.17	.14
34 R 67180	.1	.22	.19	.16
34 R 67198	.15	.26	.23	.19
34 R 67206	.2	.30	.26	.21
34 R 67214	.22	.30	.26	.21
34 R 67222	.25	.32	.28	.23
34 R 67230	.33	.34	.29	.24
34 R 67248	.47	.38	.34	.27
34 R 67255	.5	.40	.35	.29
34 R 67263	.68	.50	.43	.31
34 R 67271	1.0	.60	.52	.43

Stock No.	CAP. MFD.	NET EACH IN LOTS OF		
		1-24	25-49	50-99
34 R 82411	.0039	.18	.12	.09
34 R 82429	.004	.18	.12	.09
34 R 82437	.0047	.18	.12	.09
34 R 82445	.005	.18	.12	.09
34 R 82452	.0056	.18	.12	.10
34 R 82460	.006	.18	.12	.10
34 R 82478	.0068	.18	.12	.10
34 R 82486	.0075	.18	.12	.10
34 R 82494	.008	.18	.12	.10
34 R 82502	.0082	.18	.12	.10
34 F 82510	.01	.18	.12	.10
34 R 82528	.012	.21	.14	.11
34 R 82536	.015	.21	.14	.11
34 R 82544	.02	.21	.15	.12
34 R 82551	.022	.21	.15	.12
34 R 82569	.025	.24	.16	.13
34 R 82577	.027	.24	.16	.13
34 R 82585	.03	.24	.16	.13
34 R 82593	.033	.24	.16	.13
34 R 82601	.035	.24	.16	.13
34 R 82619	.039	.24	.18	.14
34 R 82627	.04	.24	.18	.14
34 R 82635	.047	.24	.18	.14
34 R 82643	.05	.24	.18	.14
34 R 82650	.056	.27	.20	.15
34 R 82668	.06	.27	.20	.15
34 R 82676	.068	.27	.20	.15
34 R 82684	.075	.27	.20	.15
34 R 82692	.082	.33	.23	.18
34 R 82700	.1	.33	.23	.18
34 R 82718	.15	.48	.35	.27
34 R 82726	.2	.72	.53	.41
34 R 82734	.22	.72	.53	.41
34 R 82742	.25	.87	.64	.50
34 R 82821	.33	.48	.36	.28
34 R 82829	.47	.57	.42	.33
34 R 82837	.5	.86	.74	.61

200 WVDC

Stock No.	CAP. MFD.	NET EACH IN LOTS OF		
		1-24	25-49	50-99
34 R 82015	.02	.21	.14	.11
34 R 82023	.022	.21	.14	.11
34 R 82031	.047	.21	.15	.12
34 R 82049	.05	.21	.15	.12
34 R 82056	.1	.24	.18	.14
34 R 82064	.15	.33	.23	.18
34 R 82072	.2	.39	.29	.22
34 R 82080	.22	.39	.29	.22
34 R 82098	.25	.54	.40	.31
34 R 82106	.33	.54	.40	.31
34 R 82114	.47	.72	.53	.41
34 R 82122	.5	.72	.53	.41

400 WVDC

Stock No.	CAP. MFD.	NET EACH IN LOTS OF		
		1-24	25-49	50-99
34 R 82130	.01	.18	.12	.10
34 R 82148	.015	.21	.14	.11
34 R 82155	.02	.21	.15	.12
34 R 82163	.022	.21	.15	.12
34 R 82171	.025	.24	.16	.13
34 R 82189	.03	.24	.16	.13
34 R 82197	.033	.24	.16	.13
34 R 82205	.04	.24	.16	.13
34 R 82213	.047	.24	.16	.13
34 R 82221	.05	.24	.16	.13
34 R 82239	.056	.24	.18	.14
34 R 82247	.068	.24	.18	.14
34 R 82254	.075	.33	.23	.18
34 R 82262	.1	.33	.23	.18
34 R 82270	.15	.39	.29	.22
34 R 82288	.2	.54	.40	.31
34 R 82296	.22	.54	.40	.31
34 R 82304	.25	.72	.53	.41
34 R 82312	.27	.72	.53	.41
34 R 82320	.25	.72	.53	.41
34 R 82328	.33	.46	.39	.33
34 R 82336	.33	.46	.39	.33
34 R 82344	.47	.54	.46	.33
34 R 82352	.5	.60	.52	.43

600 WVDC

Stock No.	CAP. MFD.	NET EACH IN LOTS OF		
		1-24	25-49	50-99
34 R 82312	.001	.18	.12	.09
34 R 82320	.0012	.18	.12	.09
34 R 82338	.0015	.18	.12	.09
34 R 82346	.0018	.18	.12	.09
34 R 82353	.002	.18	.12	.09
34 R 82361	.0022	.18	.12	.09
34 R 82379	.0025	.18	.12	.09
34 R 82387	.0027	.18	.12	.09
34 R 82395	.003	.18	.12	.09
34 R 82403	.0033	.18	.12	.09

1600 WVDC

Stock No.	CAP. MFD.	NET EACH IN LOTS OF		
		1-24	25-49	50-99
34 R 82833	.0005	.72	.53	.41
34 R 82841	.001	.24	.18	.14
34 R 82858	.0015	.27	.20	.15
34 R 82866	.002	.27	.20	.15
34 R 82874	.0022	.27	.20	.15
34 R 82882	.003	.33	.23	.18
34 R 82890	.0033	.33	.23	.18
34 R 82908	.004	.33	.25	.20
34 R 82916	.0047	.33	.25	.20
34 R 82924	.005	.33	.25	.20
34 R 82932	.006	.39	.29	.22
34 R 82940	.0068	.39	.29	.22
34 R 82957	.007	.39	.29	.22
34 R 82965	.0075	.39	.29	.22
34 R 82973	.008	.45	.33	.26
34 R 82981	.01	.45	.33	.26
34 R 82999	.015	.54	.40	.31
34 R 83013	.02	.72	.53	.41
34 R 83021	.022	.72	.53	.41
34 R 83039	.03	.87	.64	.50
34 R 83047	.04	1.05	.77	.60
34 R 83054	.05	1.05	.77	.60

2000 WVDC

Stock No.	CAP. MFD.	NET EACH IN LOTS OF		
		1-24	25-49	50-99
34 R 83260	.001	.27	.20	.15


.001 MFD—400 VOLT SPECIAL



25 for 89¢

QUANTITIES LIMITED

Twenty-five .001 mfd. 400 volt molded plastic capacitors. Shpg. wt., 4 oz.
32 R 01282 Net .89



PLUG-IN TYPE

Type IF-18, Fig. A. An effective all-wave capacitive-inductive type filter for use with all types of electrical appliances causing severe radio and TV interference, such as air conditioning and ventilating units, machine tools, washing machines, etc. In bakelite case, 6x3 1/2x2 1/2", with line cord and plug, receptacle and ground terminal. Binding post for attachment of ground wire. Rated at 115V AC-DC, 5 amperes.
34 R 58114 Shpg. wt., 2 lbs. ... Net 10.17

Type IF-19, Fig. B. An effective capacitive-inductive type filter, smaller than above, yet having the same degree of attenuation of severe interference. For elimination of interference from food mixers, diathermy machines, electric fans, neon signs, washing machines, business machines, etc. Has line cord, plug, receptacle and terminal for ground connection. Rated 115V AC-DC, 5 amperes. In bakelite case 4x2 1/2x2 1/2".
34 R 58122 Shpg. wt., 2 lbs. ... Net 9.10

Type IF-4, Fig. C. A cylindrical filter for use with small radios and portable TV sets for reduction of low or medium intensity interference caused by small portable electrical appliances such as electric shavers, fans, adding machines, etc. Rated 110V AC-DC, 5 amps. Connects to power line between radio plug and outlet.
34 R 58130 Shpg. wt., 4 oz. ... Net 1.54

Type IF-6, Fig. D. A plug-in cylindrical filter for elimination of moderate interference. Suppresses interference of fluorescent lighting, electric shavers, etc. Connects between power line and appliance or between power line and radio. Has binding post terminal for grounding. Rated 110V AC-DC, 10 amperes. 1 1/2" dia., 2" long.
34 R 58148 Shpg. wt., 5 oz. ... Net 2.40

WIRED IN TYPE

Type IF-24, Fig. E. FLUORESCENT NOISE FILTER. Dual capacitive type filter for eliminating fluorescent noise. Easily connected by means of flexible leads, in addition has bracket for mounting. For 110V AC-DC. Cylindrical metal case 7/8" dia., 1 1/2" long.
34 R 58163 Shpg. wt., 4 oz. ... Net 1.48

Type IF-34, Fig. F. A capacitive-inductive filter with greater efficiency than that above. Rated 110-220V AC-DC, 2 amperes. Has flexible leads for simple connection, with additional lead for ground. Rectangular metal case 2x2 1/4", w/tabs for mounting.
34 R 58171 Shpg. wt., 8 oz. ... Net 4.00

Littelfuse Fuses and Fuse Holders



TYPE 3AG STANDARD FUSES

Series 312000. Quick acting for low time-lag applications such as amplifiers—auto radios. U.L. listed. 1 1/4x1/4" diam. All rated 250 volt except 8 amp is 125V. 5 fuses per package. Shpg. wt. 3 oz.

Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.	Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.
13 R 10085	1/4	.63	.53	13 R 10143	1 1/2	.45	.38
13 R 10101	3/8	.63	.53	13 R 10150	2	.45	.38
13 R 10119	1/2	.63	.53	13 R 10160	3	.45	.38
13 R 10127	3/4	.63	.53	13 R 10176	4	.54	.45
13 R 10135	1	.45	.38	13 R 10184	5	.54	.45
13 R 12503	1 1/4	.45	.38	13 R 10192	6	.54	.45

3AG STANDARD PIGTAIL FUSES

Series 318000. Same as series 312000 above but with pigtails. 5 fuses per pkg. Shpg. wt. 3 oz.

Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.	Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.
13 R 11521	3/4	.99	.83	13 R 11554	2	.81	.68
13 R 11539	1	.81	.68	13 R 11562	3	.81	.68
13 R 11547	1 1/2	.81	.68	13 R 11588	5	.84	.70

TYPE 3AG SLOW BLOW FUSES

Series 313000. High time-lag to withstand heavy surges, blows quickly on shorts. Units through 5 amps are rated 125 volts and are UL listed, above 5 amp rated 32 volt. 5 fuses per pkg. 1 1/4x1/4" diam. Shpg. wt. 5 oz.

Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.	Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.
13 R 10258	1/8	1.38	1.15	13 R 10416	1 1/2	1.29	1.08
13 R 10309	1/4	1.38	1.15	13 R 10432	2	1.29	1.08
13 R 10317	3/10	1.38	1.15	13 R 10440	2 1/2	.99	.83
13 R 10325	3/8	1.38	1.15	13 R 10457	3	.99	.83
13 R 10341	1/2	1.38	1.15	13 R 10465	3.2	.99	.83
13 R 10358	6/10	1.38	1.15	13 R 10473	4	.99	.83
13 R 10366	7/10	1.38	1.15	13 R 10481	5	.99	.83
13 R 10374	3/4	1.38	1.15	13 R 10507	7	.99	.83
13 R 10382	8/10	1.38	1.15	13 R 10523	10	.99	.83
13 R 10390	1	1.38	1.15	13 R 10531	15	.99	.83
13 R 10408	1 1/4	1.29	1.08	13 R 10549	20	.99	.83

TYPE 8AG INSTRUMENT FUSES

Series 361000. Designed for high speed action to protect delicate electrical equipment. All rated at 250 volts, except 5 amp rated 32 volt. 5 fuses per pkg. 1 1/4x1/4" diam. Shpg. wt. 3 oz.

Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.	Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.
13 R 11356	1/100	2.49	2.08	13 R 11430	1	.45	.38
13 R 11364	1/32	2.19	1.83	13 R 11448	1 1/2	.45	.38
13 R 11398	1/4	.63	.53	13 R 11455	2	.45	.38
13 R 11414	1/2	.63	.53	13 R 11463	3	.45	.38
13 R 11422	3/4	.63	.53	13 R 11471	5	.45	.38

TYPE 3AB FUSES

Series 314000. Steatlite enclosed, ARC-Quenching Powder filled fuses. Will not shatter against quick shorts. Medium time-lag, types through 15 Amp. UL listed. All 250 volt except 30 amps 125 volt. 1 1/4x1/4" diam. 5 fuses per pkg. Shpg. wt. 3 oz.

Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.	Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.
13 R 11612	2	.87	.73	13 R 11653	10	.78	.65
13 R 11638	5	.78	.65	13 R 11679	15	.87	.73
13 R 11646	8	.78	.65	13 R 11687	20	.87	.73

LITTELFUSE AUTO FUSES

307000 Series Medium acting fuses designed for auto use. Length according to current to guard against over fusing. All 1/4" diam. 5 fuses per pkg. Shpg. wt. 3 oz.

Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.	Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.
13 R 12263	4	.33	.28				
13 R 12289	7.5	.33	.28				
13 R 12297	9	.33	.28				
13 R 12305	14	.33	.28				
13 R 12313	20	.33	.28				

AUTO FUSE ASSORTMENT



Universal auto fuse assortment easily stored in glove compartment for emergency use. Fuses for radio, heater, lights, cigar lighter, air conditioner, windshield wipers, etc. packed in plastic case, 10 fuses. Assorted value. Shpg. wt. 3 oz.

13 R 11745	Universal auto fuse assortment easily stored in glove compartment for emergency use. Fuses for radio, heater, lights, cigar lighter, air conditioner, windshield wipers, etc. packed in plastic case, 10 fuses. Assorted value. Shpg. wt. 3 oz.	Net 1.13
13 R 11752	Shpg. wt. 3 oz.	Net .46


LITTELFUSE EUROPEAN EQUIPMENT FUSES

Used in European instruments, tape recorders, radios, Hi-Fi equipment and Mickok test equipment, 5x20 mm. Rated at 250V. 5 fuses per pkg. Shpg. wt. 3 oz.

Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.	Stock No.	Amps	Per Pkg.	20 Pkgs. Per Pkg.			
Type 271 Standard Fuse				Type F212 Standard Fuse						
13 R 12107	1/2	1.50	1.25	13 R 12131	1/2	1.50	1.25			
13 R 12198	1 1/2	1.20	1.00	13 R 12149	8/10	1.50	1.25			
Type T213 Slow Blow Fuse				13 R 12206				1 1/4	1.20	1.00
13 R 12180	1	1.53	1.28	13 R 12214	2	1.20	1.00			
13 R 12248	2	1.53	1.28							
13 R 12255	4	1.53	1.28							

SNAP-ON FUSE HOLDER

For fast replacement of pigtail fuses. One side of dual holder clips on to blown fuses. New fuse fits into other side.



13 F 12388 wt., 4 oz. Each .20 10 for 1.75

LITTELFUSE MOUNTINGS AND EXTRACTOR POSTS

Mounts and fuse holders for every application. *Includes fuse. Fig. N is 3AG indicating fuse post. Avg. Shpg. wt., 3 oz.

Stock No.	Fig.	For Fuses	Description	Net Ea.
13 R 11760	A	3AG, 3AB	Panel mount, screw slot	.64
13 R 11778	B	3AG, 3AB	Panel mount, finer knob	.64
13 R 11786	A	8AG	Panel mount, screw slot	.64
13 R 11810	C	8AG	Single fuse, lug terminal	.22
13 R 11828	C	3AG, 3AB	Single fuse screw terminal	.42
13 R 11844	D	8AG	Double fuse, lug terminal	.40
13 R 11851	E	8AG	Meter-back mtg.	.43
13 R 11869	F	3AG, 3AB	Below panel mtg.	.64
13 R 11877	F	3AG, 3AB	Below panel mtg.	.64
13 R 11885	G*	SFE(9A)	Auto inline fuse retainer	.46
13 R 11893	G*	SFE(14A)	Auto inline fuse retainer	.46
13 R 11901	G*	SFE(20A)	Auto inline fuse retainer	.46
13 R 11984	N	3AG 90-125V	#34125 indicating fuse post	2.02

MINIATURE 3AG FUSE EXTRACTOR POSTS

Shortest 3AG fuse posts. Test Post hole in knobs. UL listed. Body and knob meet MIL-P-14F type CFG. Rated at 15 amp, 250 volts. Fig. K has straight bottom terminals, behind panel length 1 1/4". Fig. L, M has right angle bottom terminal behind panel length 1 1/4". Fig. L has knurled knobs. Fig. K, M has fluted knobs. Shpg. wt., 3 oz.

Stock No.	Mfg. No.	Fig.	1-99	NET EACH 100-499	500 Up
13 R 11927	342014	K	.46	.38	.30
13 R 11935	342022	L	.53	.45	.36
13 R 11943	342004	M	.53	.45	.36

BUSS FUSE MOUNTINGS




Convenient methods for mounting fuses on equipment, radio, TV, instruments, etc. Fuses easily replaced. Shpg. wt., 3 oz.

Stock No.	Buss	For	Net Ea.	Stock No.	Buss	For	Net Ea.
13 R 62029	HKP	3AG	.46	13 R 62045	4405	3AG	.22
13 R 62037	HJM	8AG	.46	13 R 62052	4408	3AG	.40

As Low As 15¢ DUAL FUSE HOLDER WITH CLEAR PLASTIC COVER

LOTS OF 10
Dual fuse holder for popular 3AG, 3AB, and 8AG fuses with durable, clear plastic, protective cover. Rated 250 volts 3 amps. Has right angle bottom solder terminals. Imported.
99 R 63372 Shpg. wt., 2 oz. Net Each .18
Lots of 10, Net Each .15



Prices and Specifications are Subject to Change Without Notice

PREMIER Metal Products

TABLE TYPE RELAY RACKS

Rigidly constructed of #16 gauge steel finished in blue-gray. Base constructed of one piece, similar to a chassis. Panel mounted holes are tapped for 10-32 machine screws. Shipped knocked down.

Stock No.	Mfr. Type	HxWxD"	Space	Lbs.	Net
12 R 85923W	TR-2119	25x21x12"	21x19"	18½	12.50
12 R 85972W	TR-2819	32x21x12"	28x19"	21	15.00

TELEPHONE TYPE RELAY RACKS

Open type racks constructed of #12 gauge steel finished in blue-gray. Vertical members and top crossbars are included together. Panel mounting holes are tapped for 10-32 machine screws. Racks shipped knocked down with all necessary bolts for easy assembly. Base punched to accommodate type CA-4 casters.

Stock No.	Mfr. Type	HxWxD"	Panel Space	Lbs.	Net
12 R 85699W	RR-800	39½x20x18¾"	36¾x19"	40	28.30
12 R 85907W	RR-801	74½x20x20¾"	71¾x19"	50½	33.65
12 R 85915W	RR-802	79½x20x20¾"	77 x19"	52	38.99

ALUMINUM PANELS

Aluminum panels, type MAP, bright aluminum protected both sides by peelable masking paper. Type ARP painted gray both sides. 19" wide, ¼" thick.

"MAP" Masked Aluminum				"ARP" Gray Hammertone			
Stock No.	Type	Each	Mgt.	Lbs.	Stock No.	Type	Each
12 R 85477	319	2.06	3½"	1¼	12 R 86830	319	2.25
12 R 85485	519	2.87	5¼"	1¾	12 R 86848	519	3.00
12 R 85493	719	3.42	7"	2	12 R 86855	719	3.83
12 R 85501	819	4.13	8¾"	2½	12 R 86863	819	5.40
12 R 85519	1019	5.17	10½"	2¾	12 R 86871	1019	5.42
12 R 85527	1219	5.88	12¼"	3¼	12 R 86889	1219	6.25
12 R 85535	1419	6.77	14"	3¾	12 R 86897	1419	7.17

STANDARD AMPLIFIER FOUNDATIONS

Consists of regular chassis with ruggedly constructed metal covers. Top cover has perforations, rounded corners; 8" high, 1 pc. chassis with corners spot-welded; Gray Hammertone Finish.

Stock No.	Type	Chassis DxDxH	Lbs.	1-24
12 R 85303	AF-510	5x10x3	4¾	8.85
12 R 85311	AF-615	6x14x3	6¾	9.83
12 R 85329	AF-1017	10x17x3	10¾	12.37
12 R 85337	AF-1317	13x17x3	12¾	13.92

METAL UTILITY CABINETS

Have two removable sides for easy accessibility. Have flanged edges and spot-welded corners. No. 20 ga. steel, attractively finished. No. 16 ga. (.051) aluminum in natural aluminum finish. Av. shpg. wt. of steel cabinets 6¼ lbs.

BLACK WRINKLE STEEL			NATURAL ALUMINUM		
Stock No.	Net	HxWxD"	Stock No.	Net	HxWxD"
12 R 83399	1.85	4x4x2	12 R 83480	1.78	4x4x2
12 R 83407	1.73	4x5x3	12 R 83498	1.88	4x5x3
12 R 83415	1.95	5x6x4	12 R 83506	2.17	5x6x4
12 R 83423	3.00	5x9x6	12 R 83514	3.67	6x6x6
12 R 83431	2.63	6x6x6	12 R 83522	2.87	6x6x6
12 R 83449	3.05	6x9x5	12 R 83530	3.52	7x5x3
12 R 83456	2.52	7x5x3	—	—	—
12 R 83464	5.40	8x10x10	—	—	—
12 R 83472	4.20	12x7x6	12 R 83548	5.02	12x7x6
—	—	15x9x7	12 R 83555	6.92	15x9x7

SLOPING PANEL CABINETS

These handy cabinets have rounded top corners and a removable front panel. Back of cabinet is perforated and has opening for leads. Constructed of #20 gauge steel. Finished in gray hammertone.

Stock No.	HxWxD"	Use Chassis"	Lbs.	Net
12 R 85840	8x8x8	7x7x2	4¾	7.00
12 R 85857	8x10x8	7x9x2	5¾	7.88
12 R 85865	8x14x8	7x13x2	7	8.40
12 R 85873	9x18x8	7x17x3	8¾	11.07
12 R 85881	12x18x12	10x17x3	12	14.17

ALUMINUM CHASSIS

Chassis are of one piece construction with gussets spot-welded to the bottom flanges for additional strength. Made of No. 18 gauge (.040) aluminum except for No. 14 gauge (.064) in natural aluminum finish. Bottom plates have holes to match chassis and have 4 pressed dimples. Av. shpg. wt. 3¼ lbs.

CHASSIS				BOTTOM PLATES	
Stock No.	Size Inches	Lbs.	Net	Stock No.	Net
12 R 81906	4x6x1½	¼	1.62	12 R 82870	1.05
12 R 81914	4x6x2	¼	1.73	12 R 82870	1.05
12 R 81922	4x6x3	¼	2.00	12 R 82870	1.05
12 R 81930	4x8x2	¾	1.68	12 R 82888	1.16
12 R 81948	4x17x3	1	3.40	12 R 82896	1.21
12 R 81955	5x7x2	¼	1.78	12 R 82904	1.05
12 R 81963	5x7x3	¼	2.05	12 R 82904	1.05
12 R 81971	5x10x3	¾	2.27	12 R 82912	1.05
12 R 81989	5x13x3	¾	2.60	12 R 82920	1.21
12 R 81997	5½x9½x1½	¾	1.78	12 R 82938	1.05
12 R 82037	7x7x2	½	2.05	12 R 82961	1.05
12 R 82045	7x9x2	½	2.17	12 R 82979	1.05
12 R 82052	7x11x2	¾	2.32	12 R 82987	1.21
12 R 82060	7x13x3	¾	2.87	12 R 82987	1.21
12 R 82078	7x12x3	¾	2.87	12 R 82995	1.42
12 R 82102	7x17x3	1½	3.95	12 R 83035	1.68
12 R 82110	8x10x2½	1	2.87	12 R 83043	1.31
12 R 82128	8x12x3	1	3.35	12 R 83050	1.58
12 R 82177	10x14x3	1¼	4.22	12 R 83092	1.84
12 R 82193	10x17x3	1¾	4.70	12 R 83100	2.00
12 R 82250	12x17x3	2¼	5.93	12 R 83134	2.52
12 R 82284	13x17x3	2¼	6.10	12 R 83142	2.78
12 R 82300	17x17x4	3	12.53	12 R 83159	3.14

ALUMINUM MINIBOXES

Two piece case made of #16 gauge (.051) aluminum. Each section forms 3 sides. Flanges assure proper shielding. Available in variety of sizes for popular electronic devices and construction projects. Available in natural finish or grey hammertone.

NATURAL ALUMINUM			GREY HAMMERTONE		
Stock No.	Net	Size—LxWxD"	Lbs.	Stock No.	Net
12 R 83670	.80	2¾x2¼x1½	¼	12 R 83845	.95
12 R 83688	.83	3¼x2¼x1½	¼	12 R 83852	1.00
12 R 83696	.88	4x2¼x1½	¼	12 R 83860	1.07
12 R 83704	1.00	4x2¼x2¼	¾	12 R 83878	1.15
12 R 83712	1.08	5x2¼x2¼	¾	12 R 83886	1.28
12 R 83720	1.17	5x4x3	¾	12 R 83894	1.57
12 R 83738	1.17	5¼x3x2¼	½	12 R 83902	1.35
12 R 83746	1.50	6x5x4	1	12 R 83910	2.00
12 R 83753	1.92	7x5x3	1	12 R 83928	2.30
12 R 83761	2.50	8x6x3½	1½	12 R 83936	2.83
12 R 83779	2.67	10x6x3½	1½	12 R 83944	3.35
12 R 83787	3.67	12x7x4	2	12 R 83951	4.00
12 R 83795	4.00	17x5x4	2¼	12 R 83969	4.50
12 R 83803	1.42	10x2x1¾	¾	12 R 83977	2.00
12 R 83811	1.75	12x2½x2¼	1	12 R 83985	2.33
12 R 83829	1.08	4x2x2¼	½	12 R 83993	1.17
12 R 83837	1.08	4¼x2¼x1½	½	12 R 84017	1.17

SLOPING PANEL UTILITY BOXES

Steel and aluminum sloping panel cabinets with round top corners and sloping front. For installations that require opening in rear of box. No. 20 gauge attractively finished steel. No. 18 gauge (.040) aluminum—natural aluminum finish. 4½"x4¼"D.

STOCK NO.	WIDTH	TYPE	LBS.	Net
12 R 80650	4¾"	BLACK WRINKLE SPC-1200	1	2.47
12 R 80676	6¾"	SPC-1202	1½	2.78
12 R 80700	5¾"	ALUMINUM ASPC-1201	½	2.63
12 R 80726	7¾"	ASPC-1203	¾	3.00

CASTERS FOR RACKS AND CABINETS

Made of Plaskite non-marking composition wheel with Ball Bearing Swivel Plate. Packed one set of 4 in box.

Stock No.	Lbs.	Size	Net
12 R 83373	2¼"	2" Diam.	Per Set 4.90
12 R 83381	7¼"	3" Diam.	Per Set 11.60

Experimenter Boxes — Electrical Accessories

UNIVERSAL METER CASES

A meter case that can accommodate either a 2" or 3" meter. Center hole for 2" meter increases to 3" meter hole by simply removing a knock-out. 4 3/4" x 4 1/2" x 1 1/4". Supplied with two 1/2" dia. knockouts for feed-through insulators or Volume Controls. Type SPC-23 #20 gauge steel. Type ASPC-23 #18 gauge (.040) Aluminum—Natural Finish. Average shpg. wt., 1 lbs.



Stock No.	Type	Net
12 R 83167	SPC-23	2.37
12 R 83175	ASPC-23	2.37

BAKELITE CASES AND PANELS

Ideal for building test equipment and small electronic devices. All black bakelite with rounded corners and recessed threaded inserts for mounting panels. Walls 1/4". Panels are 3/8" thick. Avg. shpg. wt., 1 1/2 lbs.




Stock No.	Size	Lbs.	Net
19 R 20016	6 1/4 x 3 3/4 x 2"	1/2	.89
19 R 37010	Panel for above	1/4	.45
19 R 20024	6 3/4 x 5 1/4 x 2 1/4"	1	1.39
19 R 37028	Panel for above	1/2	.61
19 R 20032	8 3/4 x 7 3/4 x 3"	1 1/4	2.39
19 R 37036	Panel for above	1/2	.75

MINI-COOL BOXES

Integrated Enclosure And Heat Sink

Made of aircraft alloy aluminum. Patented lock-joint corners tighten under stress. The six sides assemble easily with screw-driver. 2 finned sides have .100" max. wall for use as heat sink; 2 plain sides have .040" wall. Strong and rigid. Avg. Shpg. wt. 3/4 lb.



Stock No.	L x W x H	Net
19 R 22004	2" x 2.6" x 2"	.90
19 R 22012	3" x 2.6" x 2"	1.15
19 R 22020	4 1/2" x 2.6" x 2"	1.50
19 R 22038	6" x 2.6" x 2"	2.00

PLAIN TYPES

Identical to above but with all sides plain, none finned.

19 R 22046	2" x 2.6" x 2.6"	.90
19 R 22053	3" x 2.6" x 2.6"	1.15
19 R 22061	4 1/2" x 2.6" x 2.6"	1.50
19 R 22079	6" x 2.6" x 2.6"	2.00

CUSTOM CABINETS



Fast, Easy, Push-Together, Stay Together Assembly

Designer styled Flexi-Cab brown vinyl clad steel cabinets. Front panels are brass finished. All sides link together with mar-resistant plastic bindings. All kits supplied with package of 40 pressure sensitive function identifying labels.

Stock No.	Size	Lbs.	Net ea.
19 R 22558	3 1/4 x 4"	1/4	3.49
19 R 22517	3 1/4 x 6"	1	3.99
19 R 22533	3 1/4 x 9"	1 3/4	4.69

COMPACT CABINETS

Body made of 20 gauge steel with .064 aluminum front panel. Top four corners are rounded. Sides are perforated for ventilation. Top handle is recessed. Panel fits into 1/2" recess. Two inch opening in rear for leads. Welded construction. Base has rubber feet. Attractive two-tone enamel finish. With hardware for assembly. Ideal for instrumentation.



Stock No.	Size D x W x H"	Use Chassis lbs.	Wt. Net lbs. Ea.
12 R 84355	8x6 1/8x8	5x7x2	4
12 R 84363	8x8 1/8x8	7x7x2	4 1/2
12 R 84371	8x10 1/8x8	7x9x2	5 1/2
12 R 84389	12x8 1/8x8	7x11x2	7
12 R 84397	18x11 1/8x11	10x17x3	10
12 R 84405	18x14 1/8x12	13x17x3	15

BAKELITE UTILITY CASE WITH ALUMINUM PANEL

Ideal for housing small electronic devices. Sturdy bakelite box features smooth rounded corners and recessed brass inserts for screw mounting of aluminum panel. Complete with hardware. Imported. Avg. Shpg. wt., 1/2 lb.



Stock No.	Size	Net ea.
99 R 80772	3 1/4" x 2 1/4" x 1 1/4"	.69
99 R 80780	4" x 2 1/4" x 1 1/4"	.79
99 R 80756	5 1/4" x 2 1/4" x 1 1/4"	.89
99 R 62721	6 3/8" x 3 3/4" x 1 7/8"	1.09
99 R 80764	7 3/4" x 4 1/4" x 2 3/8"	1.59

BUILDER'S PANEL KIT

Ideal set of 5 panels for the experimenter. Consists of 1 plain black bakelite panel, 3 perforated boards with holes on 3/8" centers, and 1 aluminum panel with perforated circular pattern for speaker outlet. All panels are sized and have mounting holes to fit 99-62721 case above. Shpg. wt., 1/2 lb.



99 R 63380 Net 1.49

MINIATURE ALUMINUM OPEN-END CHASSIS

Ideal for small amplifiers, oscillators, and miniature assemblies. Made of 18 gauge (.040) aluminum natural finish. Avg. shpg. wt., 5 oz.



Stock No.	Size D x W x H"	ACH Type	NET
12 R 83183	2 5/8 x 2 3/4 x 1 1/4"	1350	.63
12 R 83191	1 3/4 x 3 1/4 x 1"	1351	.63
12 R 83209	3 3/4 x 4 1/2 x 2"	1352	.75
12 R 83217	2 3/4 x 4 1/4 x 1"	1353	.75
12 R 83225	3 3/4 x 4 1/4 x 1 1/2"	1354	.75
12 R 83233	3 1/4 x 4 1/4 x 1"	1355	.87
12 R 83241	5 3/4 x 4 7/8 x 1 1/2"	1356	.92
12 R 83258	4 3/4 x 4 1"	1357	.75
12 R 83266	4 3/4 x 4 1"	1358	.87
12 R 83274	4 3/4 x 4 1"	1359	.87
12 R 83282	4 6/8 x 4 1"	1360	.92

SLOPING COMPACT CABINETS

Two piece unit made of #20 cold rolled steel. Front, bottom and back form one "U" shaped unit which screws to one piece cover and sides. Attractive two-tone finish.



Stock No.	H.W.D.	Lbs.	Net
12 R 85931	6x10x7"	4 1/4	7.93
12 R 85949	7x12x8"	6 1/4	8.68
12 R 85956	3x8x5"	2 1/4	4.48
12 R 85964	5x5x5"	2 1/4	4.83


PLASTIC CASES for MINIATURE ELECTRIC GEAR



Clean, polystyrene cases. Ideal for miniature assemblies. All have ball type hinged covers. Avg. shpg. wt., 3 oz.

Stock No.	Size L x W x H"	Net
13 R 38011	1 5/8 x 2 1/4 x 1"	.25
13 R 38029	2 7/8 x 1 3/4 x 1"	.27
13 R 38037	2 7/8 x 2 1/2 x 1"	.29
13 R 38045	3 3/4 x 2 3/8 x 1"	.32

ELECTRICAL ACCESSORIES



A. E-Z WIRE PARALLEL GROUND DUPLEX WALL OUTLET. Breakoff terminals for 2 separate 3-wire circuits. Easily wired by pressure terminals or screws. UL listed. 15 amps; 125 V.

B. E-Z WIRE QUIET SWITCH. Ultra-quiet action switch with no clicking noise. Has screw, and E-Z wire pressure terminals. 15 amps; 120V. UL listed. AC only.

C. CHASSIS AC RECEPTACLE. Mounts from top or bottom. Mtg. cents 1 1/4". U.L. Listed. 15A. 125VAC/DC. Solder terminals.

D. JIFFY PUSH-PULL PLUG. Attaches in 5 seconds without any tools. Spring prongs. Brown. U.L. Listed.

13 R 81136 Ea. 15; 10 for 1.35

E. CUBE TAP EXTENSION. Trio tap, 9 ft. rubber cord. AC plug. Brown. U.L. Listed.

13 R 81110 Net .72

F. PARALLEL GROUND ADAPTER. Adapts 3 wire tools and appliances to 2 wire AC outlets. 15A., 125V. 3/4" ground lead and lug. U.L. Listed.

13 R 81151 Net .28; 10 for 2.52

G. RUBBER CUBE TAP. 3 outlets. Unbreakable one piece soft rubber construction.

13 R 81102 U.L. Listed Net .37

H. PARALLEL GROUND RUBBER PLUG. With cord clamp. U ground Dia. 1 1/2". 15 amps; 125V. U.L. Listed.

13 R 81219 Net .64

J. FLEXIBLE RUBBER HANDLE PLUG. Can be used for heavy duty work. 15A. 125V.

13 R 81078 Ea. .12; 10 for 1.08

K. RUBBER CORD CONNECTOR. With pull handle for extension cords. 1 1/4" diameter. With cord clamp. 2 wire. U.L. listed.

13 R 81144 Net .48

Belden Wire For Microphones-Intercom-P.A. Sound



SINGLE CONDUCTOR HIGH IMPEDANCE MIKE CABLE

Shielded single conductor cables. No. 25 tinned stranded wire; 3x33 copper and 4x33 copper-weld tinned, cellulose yarn braid, polyethylene insulated, tinned copper braid shield, chrome-vinyl jacket. Type 8410 has rubber insulation and black rubber jacket. Available only in lengths listed below.

Beld. No.	Out Diam.	Wt. 100'	15 Ft. Spool		25 Ft. Spool		50 Ft. Spool		100 Ft. Spool	
			Stock No.	Net	Stock No.	Net	Stock No.	Net	Stock No.	Net
8411	.144"	2 lb.	32 R 13071	1.17	32 R 13089	1.65	32 R 13097	2.61	32 R 13105	4.95
8401	.200"	3 lb.	32 R 13113	1.44	32 R 13121	1.92	32 R 13139	3.39	32 R 13147	6.30
8410	.245"	4 1/4 lb.	—	—	32 R 13162	3.60	32 R 13170	6.39	32 R 13188	11.90

3-CONDUCTOR CABLES FOR PA AND INTERCOM



SHIELDED CABLES

All have 3 conductors. Type 8771 has cable No. 22 stranded tinned copper conductors with polyethylene insulation, aluminum-polyester shield, stranded tinned copper No. 22 ground drain wire and overall chrome vinyl jacket. O.D. is .175". Type 8791 is same but with 18 gauge conductors, vinyl insulation, tinned copper wrapped shield and no ground wire. O.D. is .236".

Stock No.	Beld. No.	Gauge	Feet	Wt.	
				Lbs.	Net
32 R 15647	8771	22	250	6 1/4	11.05
32 R 15688	8791	18	100	6	9.36
32 R 15696	8791	18	500	24 1/4	41.80

2-CONDUCTOR LOW-IMPEDANCE MINIATURE AND STD. MIKE CABLES

All cables shielded. Miniature types 8420 and 8413 both No. 24 stranded tinned, 8420 has polyethylene insulation and chrome vinyl jacket, 8413 rubber insulation and black rubber jacket. Stranded types: 8422 is 22 stranded tinned, poly insulation and chrome vinyl jacket; 8412 No. 20 stranded tinned, rubber insulation and black rubber jacket; 8402 same as 8412 but brown hypalon jacket; 8428 is heavy duty No. 18 stranded tinned, black Neoprene jacket for studio use. Available only in length listed below.

Beld. No.	Out Diam.	Wt. 100'	15 Ft. Spool		25 Ft. Spool		50 Ft. Spool		100 Ft. Spool	
			Stock No.	Net	Stock No.	Net	Stock No.	Net	Stock No.	Net
8420	.185"	2 1/4 lb.	32 R 13196	2.04	32 R 13204	3.06	32 R 13212	4.65	32 R 13220	8.65
8413	.190"	3 lb.	32 R 13228	2.46	32 R 13246	3.69	32 R 13253	6.90	32 R 13261	12.75
8422	.231"	4 1/4 lb.	32 R 13279	1.80	32 R 13287	2.76	32 R 13295	5.10	32 R 13303	8.95
8412	.268"	5 3/4 lb.	—	—	32 R 13329	3.07	32 R 13337	7.05	32 R 13345	13.35
8402	.268"	6 1/4 lb.	—	—	—	—	—	—	32 R 13359	14.40
8428	.295"	7 3/4 lb.	—	—	—	—	—	—	32 R 13386	17.25

UNSHIELDED CABLES

All are 3-conductor solid #19 copper, vinyl insulated and cabled, 8487 has chrome vinyl outer jacket. 8483 has no jacket. Shpg. wt., 2 1/2 lbs. per 100 ft.

Stock No.	Beld. No.	O.D.	Feet	Net
32 R 15704	8487	.180	500	19.50
32 R 15712	8483	.132	100	3.90
32 R 15720	8483	.132	500	15.75



SPECIAL INTERCOM AND P.A. CABLES

BELDEN 8734. 3 conductor No. 22 stranded tinned copper with vinyl insulation, 1 conductor with tinned copper braid shield, 2 unshielded, cabled with overall chrome vinyl jacket. O.D. .194". Shpg. wt., per 100', 3 lbs. 32 R 13972 100 ft. spool Net 6.15 32 R 15738 500 ft. spool Net 25.75

BELDEN 8732. 4 conductors No. 22 stranded tinned copper with polyethylene insulation, 2 conductors with tinned copper braid shield, 2 unshielded. Chrome vinyl jacket overall. Oval shape O.D. .188" x .296". Shpg. wt., 100', 3 1/2 lbs. 32 R 13998 100 ft. spool Net 7.73 32 R 15753 500 ft. spool Net 32.65

SHIELDED PHONO PICKUP CABLE

BELDEN TYPE 8431. Extremely limp and flexible. No. 24 stranded (16x36) tinned copper, rubber covered, tinned copper braid shield, brown cotton braid jacket. Only in lengths listed below. Shpg. wt., 100 ft., 3/4 lb. 32 R 14020 15 ft. coil Net each 1.26 32 R 14038 25 ft. coil Net each 1.65 32 R 14046 100 ft. coil Net each 5.25

HIGH VOLTAGE LEAD



BELDEN 8866 high voltage lead with No. 18 stranded tinned copper polyethylene insulation. Reduces corona. Long life construction. Vinyl jacket. O.D. .208". Working voltage. 40KV. Only in lengths listed below. Shpg. wt., 2 1/2 lbs. 100 ft. 32 R 17064 25 ft. spool Net 2.31 32 R 17072 100 ft. spool Net 6.53

TINNED BUS BAR WIRE

Solid tinned copper bus-bar wire. Especially for use where high current conductor is needed as in power plants, ground wire, switchboards and point to point wiring.

Belden No.	AWG	O.D.	100 Ft. Spool	
			Stock No.	Net
8022	24	.020	32 R 15183	4 .98
8021	22	.025	32 R 15208	6 1.01
8020	20	.032	32 R 15225	8 1.19
8019	18	.040	32 R 15241	10 1.59
8013	16	.050	32 R 15266	15 2.24
8012	14	.064	32 R 15282	26 3.36
8011	12	.080	32 R 15308	40 5.04



SHIELDED CABLES FOR PA AND INTERCOM

2 CONDUCTOR-TWISTED PAIR-SHIELDED CABLES

All have stranded tinned copper conductors except No. 8739 is solid. Each conductor has vinyl insulation except * has polyethylene. Shielding: types marked * have aluminum-polyester shield with stranded tinned ground wire; types marked # have tinned copper braided shield; types marked Δ have tinned copper spiral wrapped shield. All have overall chrome vinyl jacket except # have no outer jacket over shield.

Beld. No.	Gauge	D.O."	Lbs. 100 Ft.	100 Ft. Spool		250 Ft. Spool		500 Ft. Spool	
				Stock No.	Net	Stock No.	Net	Stock No.	Net
8739Δ	22	.160	2 1/2	32 R 13519	4.56	—	—	32 R 15407	19.35
8737Δ	22	.170	2 3/4	32 R 13527	4.80	32 R 15415	10.65	32 R 15423	21.25
8759Δ	20	.195	3	32 R 13535	6.00	—	—	32 R 15431	25.00
8790Δ	18	.231	4 1/4	32 R 13543	7.65	32 R 15449	16.50	32 R 15456	33.00
8780Δ	16	.266	5 1/4	32 R 13559	9.60	—	—	32 R 15464	42.75
8761*	22	.167	2	—	—	—	—	32 R 15472	17.55
8762*	20	.196	3	32 R 13576	5.33	32 R 15480	11.05	32 R 15488	22.10
8760*	18	.222	3	—	—	32 R 15506	13.30	32 R 15514	26.60
8758#	20	.165	1 3/4	32 R 13600	5.85	—	—	32 R 15522	23.80
8789#	18	.204	3 1/4	—	—	—	—	32 R 15530	34.65
8779#	16	.225	4	—	—	—	—	32 R 15548	44.65

VINYL COVERED MULTIPLE UNPAIRED CABLE

All conductors No. 22 unshielded stranded tinned copper except * include two No. 18 conductors. Each conductor vinyl insulated cabled. Chrome vinyl jacket overall. Available only in sizes listed below.

Belden No. Conds.	O.D."	Lbs. 100 Ft.	15 Ft. Spool		25 Ft. Spool		100 Ft. Spool		250 Ft. Spool	
			Stk. No.	Net	Stk. No.	Net	Stk. No.	Net	Stk. No.	Net
8443	3 .150	2 1/4	—	—	32 R 14244	1.40	32 R 14525	3.66	32 R 15902	7.31
8444	4 .168	2 3/4	—	—	32 R 14251	1.59	32 R 14531	4.03	32 R 15910	9.98
8445	5 .180	3	—	—	32 R 14269	1.83	32 R 14541	4.58	32 R 15928	11.90
8446*	6 .222	4 1/4	32 R 14277	1.83	—	—	32 R 14558	5.30	32 R 15936	18.30
8447*	7 .246	5	—	—	—	—	32 R 14566	9.60	32 R 15944	21.20
8448*	8 .250	5 3/4	32 R 14285	2.07	—	—	32 R 14574	10.26	32 R 15951	23.25
8449*	9 .261	6 1/4	32 R 14293	2.25	—	—	32 R 14582	10.95	32 R 15969	25.10
8456	10 .260	5 3/4	—	—	—	—	32 R 14988	10.80	—	—
8457	12 .260	5 3/4	—	—	—	—	32 R 14970	12.15	—	—
8458	15 .320	8 3/4	—	—	—	—	32 R 14947	20.55	—	—
8459	25 .370	11 3/4	—	—	—	—	32 R 14954	31.50	—	—

SHIELDED SOUND-PA-INTERCOM CABLE



BELDEN 8208. 2 conductor No. 18 tinned stranded copper, twisted pair, rubber insulated, braided tinned copper shield, chrome vinyl jacket overall. O.D. .255". Shpg. wt., 100', 4 lbs. BELDEN 8735. 3 conductor No. 22 tinned stranded copper vinyl insulated, cabled, tinned copper braid shield chrome vinyl jacket overall. O.D. .199". Shpg. wt., 100', 5 lbs.

Belden No.	15 Ft. Spool		50 Ft. Spool		100 Ft. Spool		500 Ft. Spool	
	Stock No.	Net	Stock No.	Net	Stock No.	Net	Stock No.	Net
8208	—	—	—	—	32 R 13808	9.90	32 R 15621	43.90
8735	32 R 13865	1.47	32 R 13873	3.90	32 R 13881	6.75	32 R 15629	28.90

Belden TV, Intercom and P. A. Wire


DUOFOIL

BELDEN DUOFOIL 75 OHM COAX

Belden 8228. Low loss 100% shielded, 75 ohm, 100% sweep tested coaxial cable for 82 channel VHF/UHF color or black and white TV reception. No. 18 solid bare copper conductor with low loss polyethylene insulation. Shielding is polyester film with aluminum lamination on both surfaces. Has 4 No. 28 solid tinned copper-weld drain wires spirally wrapped. Overall PVC black all weather jacket is only .242" OD. Only in lengths listed below.

32 R 17411 100' Shpg. wt., 3 3/4 lbs. Net 6.75
32 R 17403 500' Shpg. wt., 15 3/4 lbs. Net 22.40

COILED MICROPHONE AND TELEPHONE CORDS



Have insulated cadmium bronze conductors except * has 5 strands tinned copperweld and 16 strands tinned copper. Microphone cables have black neoprene jacket except # has gray vinyl; telephone cables, black vinyl jacket. Type 8499 and 8605 shielded; type 8497, 1 shielded and 2 unshielded conductors, all others unshielded. Telephone cables have spade terminals and strain relief. Shpg. wt., 1/2 lb.

Stock No.	Belden No.	Cond.	Type	Extens		Net
				From	To	
32 R 14236	8415*	4	Mic	11 1/2"	6'	1.84
32 R 15084	8497*	3	Mic	11 1/2"	6'	1.77
32 R 15092	8499	1	Mic	7 1/2"	4'	1.20
32 R 17395	8605**	1	Mic	21 1/2"	12'	1.80
32 R 15118	8495	3	Tel	10"	4 1/2'	1.65

BELDEN TEST PRO WIRE

Extremely flexible, limp rubber covered hi-voltage lead. No. 18 stranded, tinned, cotton wrap, 8899 for 5000 working volts, 8898 for 10,000 working volts. In red or black. Shpg. wt., 100 ft., 4 1/4 lbs.

Belden No.	10 Ft.	Net	25 Ft.	Net	100 Ft.	Net
8899 Bld	32 R 17239	.87	32 R 17254	1.38	32 R 17270	4.41
8898 Bld	32 R 17247	.87	32 R 17262	1.38	32 R 17288	4.41
8898 Bld	32 R 17296	1.23	32 R 17312	2.28	32 R 17338	5.97
8898 Bld	32 R 17304	1.23	32 R 17320	2.28	32 R 17346	5.97

VINYL COVERED MULTIPLE PAIRED CABLE



For balanced line intercom system and telephone wiring. Unshielded #22 solid tinned copper conductors, vinyl insulated, cabled in pairs, chrome vinyl outer jacket. Available only in lengths listed below.

Belden No.	No. Conds.	O.D. In.	bs. 100'	100 Ft. Spool Stock No.	Net
8740	2	.150	2	32 R 15741	2.82
8741	4	.201	3	32 R 15787	4.68
8742	6	.240	3 3/4	32 R 15803	6.12
8743	12	.305	6 3/4	32 R 15829	10.05
8744	18	.354	8 3/4	32 R 15845	14.85
8754	26	.409	11 1/4	32 R 15860	21.00
8745	30	.420	13 1/4	32 R 15886	25.80

UNSHIELDED 2 CONDUCTOR TWISTED PAIR SPEAKER AND INTERCOM CABLE



BELDEN 8205. 2 conductor No. 20 stranded tinned copper, vinyl insulated, cabled with overall chrome vinyl jacket. O.D., .190" Shpg. wt., 100', 2 lbs Lengths available only in sizes listed below.

32 R 14202 100 ft. spool Net 3.83
32 R 17056 500 ft. Spool Net 14.10

2-CONDUCTOR-TWISTED PAIR-UNSHIELDED



All have tinned stranded copper conductors except * are solid copper. Types with † have chrome vinyl jacket overall, others without jacket. All conductors have vinyl insulation. Available only in lengths listed below.

Beld. No.	Gauge	O.D."	Lbs.	100 Ft. Spool Stock No.	Net	500 Ft. Spool Stock No.	Net
8481	22*	.112	1 1/4	32 R 13717	2.25	32 R 15555	7.35
8482	19*	.130	1 3/4	32 R 13030	2.94	32 R 15563	10.95
8460	18	.175	2 1/2	32 R 13725	4.29	32 R 15571	16.90
8470	16	.195	2 1/2	—	—	32 R 15589	21.55
8740†	22	.150	2	32 R 13741	2.82	32 R 15597	10.05
8461†	18	.226	3 3/4	32 R 13766	5.07	32 R 15605	20.85
8471†	16	.256	4	—	—	32 R 15613	28.35

BELDEN 9090 METRO COLOR AND 9085 MAXI COLOR TV LEAD-IN WIRE

9090

NEW!

9085

9090 METRO COLOR Shielded lead-in wire provides finest color, black/white, and FM reception in high interference metropolitan areas. Eliminates ghost signals, electrical and automotive ignition noises and assures sharper, more pleasing color viewing. Shpg. wt., 3 1/2 lbs. per 100 ft.

32 R 17429 50 ft. Net 4.95
32 R 17437 75 ft. Net 6.30


32 R 17445 100 ft. Net 7.80
32 R 17452 500 ft. Net 34.90

9085 MAXI COLOR Delivers superior color, black/white, and FM reception in low-interference suburban areas. Provides more signal to the receiver under adverse environmental conditions. Shpg. wt., 4 1/2 lbs. per 100 ft.

32 R 17460 50 ft. Net 2.18
32 R 17478 75 ft. Net 2.80

32 R 17486 100 ft. Net 3.50
32 R 17494 500 ft. Net 14.65

BELDEN 8290 SHIELDED PERMOHM 300 OHM COLOR TV LEAD-IN



Designed for 82 channel color TV reception, 8290 PermoHM combines the strong signal strength of twin-line with the clean signal of shielded cable. Shielded to eliminate ignition and other interference caused by line pick-up. Weatherproof. Shpg. wt., 6 lbs. per 100 ft. Available only in lengths listed below.

32 R 15357 50 ft. Net 6.10
32 R 15365 75 ft. Net 8.25

32 R 15373 100 ft. Net 10.40
32 R 15977 500 ft. Net 49.10

BELDEN 300 OHM TWIN LEAD



Type 8225, Fig. A. for TV and FM antennas. Low loss polyethylene insulation. Stranded No. 20 (7x28). Shpg. wt., 100 ft. 2 lbs.

32 R 14061 (50 ft.) 1.34
32 R 14067 (75 ft.) 1.76
32 R 14067 (100 ft.) 2.18
32 R 15965 (250 ft.) 5.37

Type 8235, Fig. B. Low loss 300 ohm line for UHF or VHF TV antennas and for amateur transmitting and receiving—Twin lead rated 1KW(RF). Resists oxidation and sun; made with 100% virgin polyethylene web, 18 gauge (7x26) stranded.

32 R 14193 (100 ft.) Shpg. wt., 4 3/4 lbs. 5.94

Type 8230, Fig. A. "Weldohm" copper coated steel wire. Polyethylene insulation. Almost twice as strong as plain copper. Perfect for long runs. Stranded No. 20 (7x28). Shpg. wt., 100 ft. 2 lbs.

32 R 14129 (50 ft.) 1.43
32 R 14145 (100 ft.) 2.37

32 R 14137 (75 ft.) 1.85
32 R 15993 (250 ft.) 5.85

Type 8285, Fig. C. Encapsulated in low loss cellular polyethylene. Delivers a strong signal on all channels VHF or UHF. A must for color TV. 2 Conductor #22 (7x30) stranded copper weld conductors. Shpg. wt., 4 lbs. per 100 ft.

32 R 14160 (50 ft.) 3.08
32 R 14186 (100 ft.) 5.25

32 R 14178 (75 ft.) 4.08
32 R 17015 (250 ft.) 12.45

CONSOLIDATED 3-WAY ANTENNA SYSTEM




- Makes Any Of 3 Marconi And Doublet Systems

Uniquely designed set of parts for construction of any of 3 types of short and long wave antennas. All parts supplied for either a doublet, double doublet, or inverted L antenna system. Contains 100 ft. bare aerial wire, 50 ft. twisted insulated transmission line, 4 insulators, 2 screw eyes, doublet lightning arrester, window lead-in strip, ground clamp and complete instructions. Shpg. wt., 3 1/4 lbs. Net 5.95

CONSOLIDATED ANTENNA KIT

2.35



Ideal for small crystal, diode and transistor broadcast, and short-wave sets. 50 ft. 7 x 26 bare copper aerial wire, 25 ft. rubber covered lead-in wire, 10-in. window lead-in strip, 2 antenna and 2 stand-off insulators. Simple printed instructions. Shpg. wt., 1 1/4 lbs. Net 2.35

Coaxial and Special-Purpose Cable

RG LOW-LOSS COAXIAL CABLES

Excellent for RF, amateur and citizens band applications. All branded with standard type numbers and meet requirements of RG cables on qualified products list of U.S. Government. O.D.: RG-8/8U, RG-11/U, RG-11A/U .405"; RG-58/U, RG-58A/U .195"; RG-59/U .242. MMF/FT:

RG-8/U 29.5; RG-11/U 20.5; RG-11A/U 20.5; RG-58/U 28.5; RG-58A/U 29.5. RG-59/U 21. Available only in lengths listed below. Average shpg. wt., per 100 ft., 12 lbs.

RG Type	Imp. Ohms	50 Ft. Length		100 Ft. Length		250 Ft. Lengths		500 Ft. Lengths	
		Stock No.	Net	Stock No.	Net	Stock No.	Net	Stock No.	Net
RG-8/U	52	32 R 17080	8.70	32 R 30315	16.30	32 R 17096	34.80	32 R 30323WX	64.80
RG-11/U	75		—	32 R 30349	14.10	32 R 17114	31.00	32 R 30356WX	55.65
RG-58/U	53.5	32 R 17122	3.21	32 R 30364	5.64	32 R 17130	12.15	32 R 30372WX	20.70
RG-58A/U	50	32 R 17148	3.51	32 R 30324	6.60			32 R 30327WX	23.70
RG-59/U	73	32 R 17155	3.90	32 R 30398	6.90	32 R 17163	15.45	32 R 30406WX	28.90

STEREO PHONO PICKUP WIRE



Extremely flexible, lightweight wire for all stereo cartridges and tone arms. No. 32 stranded 2, 3 and 4 conductor twisted miniature color coded cables. Low hum and noise pickup for best stereo performance. Shpg. wt., 10 SF. 1/2, 3 oz.; 25 FT., 5 oz.

UNSHIELDED WIRE

Cond.	Stk. No.	Net	25 Ft. Spool Stk. No.	Net
2	32 R 31263	.63	32 R 31271	.61
3	32 R 31289	.72	32 R 31297	.61
4	32 R 31305	.90	32 R 31313	1.68


SHIELDED WIRE

*Individually shielded conductors

2	32 R 31321	.86	32 R 31339	1.61
3	32 R 31347	1.00	32 R 31354	1.79
4	32 R 31362	1.43	32 R 31370	2.32
2*	32 R 31388	1.08	32 R 31396	2.18

MAGNET WIRE

Finest quality. Available in plain enamel or heavy FORMVAR insulation. See FORMVAR listing for approx. footage per lb. Available in 1/2 lb. spools only. Shpg. wt., 3/4 lb.



PLAIN ENAMELED 1/2 LB. SPOOLS

B & S Size	Stock No.	Net	B & S Size	Stock No.	Net
14	32 R 31586	1.32	28	32 R 30711	1.86
16	32 R 30596	1.37	30	32 R 30737	1.93
18	32 R 30612	1.50	32	32 R 30752	2.00
20	32 R 30638	1.55	34	32 R 30778	2.20
22	32 R 30653	1.60	36	32 R 30794	2.55
24	32 R 30679	1.67	38	32 R 30810	2.99
26	32 R 30695	1.76	40	32 R 31602	3.51

HEAVY FORMVAR IN 1 LB. SPOOLS

Stock No.	B&S Size	Feet	Net
32 R 30828	14	78	2.20
32 R 30836	16	124	2.23
32 R 30844	18	198	2.32
32 R 30851	20	313	2.43
32 R 30869	22	501	2.53
32 R 30877	24	798	2.71
32 R 30885	26	1200	2.86
32 R 30893	28	1999	3.20
32 R 30901	30	3200	3.39
32 R 30919	32	4900	3.93
32 R 30927	34	7950	4.13
32 R 30935	36	12,800	4.78
32 R 30943	38	20,000	6.15
32 R 30950	40	31,700	9.39

Shpg. wt., 1 1/2 lbs.

BARE NICKEL CHROMIUM WIRE



For electrical heating appliances and devices whose operating temperatures do not exceed 1850°F. Ideal for compact resistance required of heavy duty rheostats and controls. 1/4 lb. spools. Shpg. wt., 7 oz.

Stk. No.	Size	Net	Stk. No.	Size	Net
32 R 31404	14	3.44	32 R 31479	28	5.04
32 R 31412	16	3.53	32 R 31487	30	5.41
32 R 31420	18	3.64	32 R 31495	32	5.79
32 R 31438	20	3.74	32 R 31503	34	6.09
32 R 31446	22	3.95	32 R 31511	36	6.75
32 R 31453	24	4.30	32 R 31529	38	7.62
32 R 31461	26	4.69	32 R 31537	40	12.46

LOW LOSS POLYFOAM COAX

These polyfoam coax cables have basically similar constructional and physical specifications as the standard cables bearing the same RG number. Lower attenuation and capacitance result in signal strength increases up to 35%. 75 ohm cables are for TV and FM use while 50 ohm cables are ideal for amateur radio and CB. Available only in lengths listed.

RG-11/U 75 ohm coax feeder with non-peaking attenuation characteristics. Ideal for distribution lead-in. Shpg. wt., 10 1/4 lbs.

32 R 31248 100 ft. coil Net 16.25
 RG-59/U 72 ohm coax cable for improved FM and TV reception. Minimizes noise, ghosts and color smears. Recommended for color TV. Shpg. wt., 3 1/4 lbs.
 32 R 31248 100 ft. coil Net 6.50

RG 8/U 50 ohm impedance cable with minimum signal loss and stray radiation for increased antenna system efficiency. Shpg. wt., 5 3/4 lbs.

32 R 30463 100 ft. coil Net 16.30
 RG-58/U 53.5 ohm impedance cable with low loss and increased operation range for use in CB and amateur radio. Shpg. wt., 2 3/4 lbs.
 32 R 31180 100 ft. coil Net 6.00

RUBBER JACKETED SERVICE CORDS

U.L. listed, rubber sheathed service cord. Each stranded copper conductor has color coded rubber insulation, cotton wrapped with tough outer rubber jacket. Ideal for electronics equipment, household appliances, garden and power tools. SV for light appliances; SJ for medium appliances. Rated 300 volts maximum. Available only in lengths shown below. Average wt., per 100 ft., 8 3/4 lb.



U.L. Type	No. Size	Con. O.D.	25 Ft. Spool Amps	Stock No.	Net	50 Ft. Spool Stock No.	Net	100 Ft. Spool Stock No.	Net	
SV	10	2	250"	5	32 R 30992	1.76	32 R 31008	3.29	32 R 31016	5.99
SJ	10	2	340"	7	32 R 31024	2.81	32 R 31032	5.09	32 R 31040	8.99
SJ	10	3	345"	5	32 R 31057	2.99	32 R 31065	5.27	32 R 31073	10.00
SJ	10	3	375"	7	32 R 31081	4.04	32 R 31099	7.72	32 R 31107	13.99

THERMOPLASTIC HOOK-UP WIRE

Convenient spools of plastic insulated wire. Shpg. wt., 25'-5 oz.; 100'-3/4 lb.



Stock No.	Description	Net	Stock No.	Description	Net
32 R 31891	#20 Solid-25 ft. Red	.49	32 R 89444	#20 Stranded-100 ft. Red	1.35
32 R 31909	#20 Solid-25 ft. Black	.49	32 R 89451	#20 Stranded-100 ft. Black	1.35
32 R 31917	#20 Solid-25 ft. Blue	.49	32 R 89469	#20 Stranded-100 ft. Blue	1.35
32 R 31925	#20 Solid-25 ft. Green	.49	32 R 89477	#20 Stranded-100 ft. Green	1.35
32 R 31933	#20 Solid-100 ft. Red	1.25	32 R 89485	#22 Stranded-25 ft. Red	.49
32 R 31941	#20 Solid-100 ft. Black	1.25	32 R 89493	#22 Stranded-25 ft. Black	.49
32 R 31959	#20 Solid-100 ft. Blue	1.25	32 R 89519	#22 Stranded-25 ft. Blue	.49
32 R 31966	#20 Solid-100 ft. Green	1.25	32 R 89527	#22 Stranded-25 ft. Green	.49
32 R 89482	#20 Stranded-25 ft. Red	.58	32 R 89535	#22 Stranded-100 ft. Red	1.25
32 R 89410	#20 Stranded-25 ft. Black	.58	32 R 89543	#22 Stranded-100 ft. Black	1.25
32 R 89428	#20 Stranded-25 ft. Blue	.58	32 R 89550	#22 Stranded-100 ft. Blue	1.25
32 R 89436	#20 Stranded-25 ft. Green	.58	32 R 89568	#22 Stranded-100 ft. Green	1.25

BELL WIRE



No. 18 solid. 2 conductor twisted pair. Plastic insulated. Shpg. wt., 1 1/4 lb. per 100'.

32 R 30288 100 ft. coil Net 2.90
 32 R 36296 500 ft. coil Net 17.75

HI-FI SPEAKER CABLES



Set of 2—15 ft. speaker cables, each with spade lugs on all ends. Clear plastic covered polarized conductors. 24 gauge copper conductors. Shpg. wt., 5 oz.

32 R 36486 Per Set Net .98
 Same as above, but set of 2 30-ft. cables with 22 gauge conductors.
 32 R 36528 Shpg. wt., 14 oz. Net 1.69

BELDEN COPPER BRAID



Flexible tinned copper braiding. Size is oval I.D. except * is flat width. Shpg. wt., per 50 ft., is 2 lbs.

Size ID"	10 Ft. Spool Stock No.	Net	50 Ft. Special Stock No.	Net
3/16"	32 R 14301	.96	32 R 14368	2.88
1/8"	32 R 14319	1.34	32 R 14376	3.96
5/16"	32 R 14327	1.44	32 R 14384	4.89
1/2"	32 R 14335	1.32	32 R 14392	4.56
3/4"	32 R 14343	2.31	32 R 14400	9.84
1"	32 R 14350	3.15	32 R 14418	13.90

HOOK-UP WIRE



ASSORTMENTS

Various colors, gauges and insulation.
 KIT OF SIX 25-FOOT COILS
 Convenient kit of six 25' coils.
 Shpg. wt. 3/4 lb. Net per kit 1.49
 KIT OF FIVE 100-FOOT COILS
 Shpg. wt., 1 1/2 lbs. Net per kit 3.49

Antenna Wire - Guy Wire - Speaker and Zip Cord



UHF-VHF OPEN LINE

300 OHM. Attenuation averages only 1.9 db over entire UHF band. No. 18 copperweld wire—pure polyethylene separators spaced at 6". Spaced only 1/2" between conductors. Shpg. wt., 2 lbs. per 100'. Available only in lengths listed below.

32 R 36106 100 ft. coil Net 4.05
32 R 36114 250 ft. coil Net 9.79
32 R 36122 500 ft. spool Net 18.95

450 OHM. Similar to above. 1" spacing between conductors.

32 R 36130 100 ft. coil Net 3.99
32 R 36148 250 ft. spool Net 9.65
32 R 36155 500 ft. spool Net 18.78



LIFELINE COPPERWELD TWIN LEAD

• Guaranteed for Life of Your Antenna

Guarantee: If this deluxe 300 ohm line fails to last the life of your antenna we will replace it at no charge. 20 Gauge Copperweld (copper clad steel) conductors with finest brown polyethylene insulation. Chemically protected against deterioration. Special "waste free" dispenser package. Shpg. wt., 2 1/4 lbs. per 100 ft.

32 R 36163 100 ft. package Net 2.65
32 R 36460 1000 ft. Net 24.40



FOAM-TV TWIN LEAD

• For UHF-VHF and Color TV

A flat 300 ohm twin lead with the conductors totally encased in and surrounded by polyethylene foam with an outer black polyethylene jacket. Has high resistance to ultraviolet rays, oil, fumes, moisture, salt air and abrasion. 20-gauge stranded copper conductors. Available only in lengths listed below. Shpg. wt., 3/4 lbs. per 100 ft.

32 R 36031 50-ft. Coil Net 2.29
32 R 36049 100-ft. Coil Net 4.19
32 R 36015 500-ft. Coil Net 18.60
32 R 36023W 1000-ft. Coil Net 36.85



300 OHM TWIN LEAD

BROWN. High quality, low-loss lead-in for all TV and FM installations. 55 mil polyethylene dielectric—22 gauge copper leads. Only in lengths listed below. Shpg. wt., 1 lb. per 100 ft.

32 R 89121 100 ft. coil Net 1.59
32 R 89139 500 ft. coil Net 6.85
32 R 89147 1,000 ft. coil Net 12.81


CLEAR. Same as above but clear for a better blend with base boards.

32 R 89154 100 ft. spool Net 1.68
32 R 89162 500 ft. spool Net 7.51
32 R 89170 1,000 ft. spool Net 14.11

HEAVY DUTY

300 ohm brown twin lead with 80 mil thick polyethylene insulation and 20 gauge copper conductors. Shpg. wt., 1 3/4 lbs. per 100 ft.

32 R 89188 100 ft. coil Net 1.99
32 R 36452 1,000 ft. coil Net 16.95



ROTATOR CABLES

4 CONDUCTOR FLAT. Flexible stranded No. 20 copper encased in tough plastic insulation. Shpg. wt., 2 1/2 lbs. per 100' coil.

32 R 89105 100 ft. coil Net 3.40

4 CONDUCTOR ROUND HEAVY DUTY. Belden 8489. All 18 gauge stranded flexible conductors, plastic insulated and jacketed. 5 3/4 lbs. 32 R 17108 100 ft. coil Net 8.76

5 CONDUCTOR FLAT. Same construction as 4-cond. flat. Shpg. wt., 2 3/4 lbs. 32 R 36312 per 100 ft. Net 4.72

6 CONDUCTOR ROUND. Belden 8488. No. 22 stranded copper conductors. Vinyl insulated, vinyl jacket. In 100 ft. coils only. 32 R 14863 Shpg. wt., 3 3/4 lbs. Net 6.75

8 CONDUCTOR ROUND HEAVY DUTY. Belden 8448. Similar to above but 2 conductors are 18 gauge. 100 ft. coil. 32 R 14574 Shpg. wt., 5 3/4 lbs. Net 10.26



MINIATURE ZIP-CORD PARALLEL CABLE

Multi purpose miniature zip cord. 2 conductor, 24 gauge stranded. Extremely flexible for Hi-Fi installations, auto speakers, low voltage control, etc. Available in white, brown, gray, clear.

Average shpg. wt., 1 lb. per 100 ft.


32 R 89238 25 ft. white Net .50
32 R 89246 25 ft. brown Net .50
32 R 89253 25 ft. gray Net .50
32 R 89261 25 ft. clear Net .50
32 R 89279 50 ft. white Net .80
32 R 89287 50 ft. brown Net .80
32 R 89295 50 ft. gray Net .80
32 R 89303 50 ft. clear Net .80
32 R 89311 100 ft. white Net 1.25
32 R 89329 100 ft. brown Net 1.25
32 R 89337 100 ft. gray Net 1.25
32 R 89345 100 ft. clear Net 1.25



SPEAKER-LAMP CORD

U.L. listed 2 conductor zipcord for lamps, speaker leads, etc. All No. 18 Gauge except * is 16 Gauge. Shpg. wt., 4 1/4 lbs. per 100 ft. Only in lengths shown below.

PLASTIC INSULATION POT
32 R 31743 Black 25' Net 1.40
32 R 31768 Brown 25' Net 1.40
32 R 31776 *Brown 25' Net 2.50
32 R 31800 Black 100' Net 3.75
32 R 31826 Brown 100' Net 3.75
32 R 31826 *Brown 100' Net 6.75
32 R 31834 Gray 100' Net 3.75
32 R 31842 White 100' Net 3.75
32 R 30497 Brown 250' Net 8.95



INDIVIDUALLY SHIELDED ZIP CORD

Two conductors No. 24 (7 x 32) individually shielded in spiral wrap. Gray plastic jacket over each conductor. Ideally suited for audio, hi-fi, stereo and laboratory use. Shpg. wt., 1 lb. per 25'.

32 R 31693 25' spool Net 2.00
32 R 31701 50' spool Net 3.39

GUY WIRE

Available in Fiberglass, Steel, Vinyl Covered Steel and Aluminum

FIBERGLAS GUY WIRE

Non-metallic, non-conductive, non-radiating guy line for minimum loss. 1000 pounds tensile strength. Will not rot, shrink, stretch or sag. Shpg. wt. 3 1/2 lbs. per 100 ft.

32 R 45016 100 ft. 6.50
32 R 45024 600 ft. 37.75

STEEL GUY WIRE

Six strands of no. 20 high tensile strength galvanized steel wire.

33 R 31014 50 ft. roll Wt., 1 lb. .55
33 R 31022 100 ft. roll Wt., 2 lbs. .95
33 R 31030 500 ft. roll Wt., 10 lbs. 4.59

VINYL COVERED GUY WIRE

Steel guy wire as above with translucent green vinyl. Covering; weatherproof, non-stretch, long lasting.

32 R 36494 50 ft. roll Wt., 1 1/2 lbs. 1.05
32 R 36502 100 ft. roll Wt., 2 1/2 lbs. 2.00
32 R 36510 250 ft. roll Wt., 6 1/4 lbs. 4.89

ALUMINUM GUY WIRE

7-18 gauge stranded wires. Breaking strength 500 lbs. Shpg. wt., 1 1/4 lbs. 34 R 46275 100 ft. roll. Net 2.65

ALUMINUM GROUND WIRE

No. 8 gauge solid conductor.
33 R 31048 50 ft. coil, Wt., 1 lb. 1.00
33 R 31055 100 ft. coil, Wt., 1 3/4 lbs. 1.93
33 R 31063 500 ft. coil, Wt., 9 lb. 9.15

ANTENNA STRAIN INSULATORS



Fig. A. Brown glazed porcelain. Shpg. wt., 3 oz.
32 R 30083 lots of 10 ea., 10 Singly 23
Fig. B. Johnson 136-32. 1 1/2" Long. Dry glazed porcelain.
33 R 32459 Wt., 2 oz. Net ea. 20



ANTENNA WIRE

Finest grade high tensile strength copper for all antenna requirements. Avg. shpg. wt., 2 1/2 lb. Only in lengths listed below.

32 R 30189 75 ft. 7/22 bare Net 2.59
32 R 36197 100 ft. 7/22 bare Net 3.25
32 R 36221 75 ft. 7/26 bare Net 1.39
32 R 36239 100 ft. 7/26 bare Net 1.69
32 R 30091 100 ft. 12 solid enamel Net 4.85
32 R 30109 100 ft. 14 solid enamel Net 3.35

COPPERWELD. Copper outside conductor bonded to steel core. For ham antennas, commercial installations. Non-stretch, hard drawn high conductivity copperweld wire.

32 R 36247 75 ft. 12 solid Net 3.33
32 R 36254 100 ft. 12 solid Net 4.20
32 R 36262 75 ft. 14 solid Net 2.64
32 R 36270 100 ft. 14 solid Net 3.49

INTERCOM WIRE



2-conductor Twisted; Flexible, tinned copper with plastic insulation over each conductor.

Shpg. wt., 2 lbs. per 100 ft. Available only in lengths listed below.


32 R 30521 100 ft. coil Net 1.49
32 R 30539 250 ft. spool Net 3.39

3 conductor twisted. Same construction as above. Shpg. wt., 1 lb. per 100 ft.

32 R 30547 100 ft. coil Net 2.09
32 R 30554 250 ft. spool Net 4.70

3 conductor twisted. Same construction as above but with outer plastic jacket overall.

Shpg. wt., 2 lbs. per 100 ft.
32 R 30552 100 ft. coil Net 3.65
32 R 30570 250 ft. spool Net 8.60



SHIELDED "CONCO-FOAM"

• All Channel Color TV and FM Cable


Assures excellent VHF, UHF, COLOR and B/W T.V. and FM reception in crowded areas where reception is critical. Mylar-aluminum shielding provides strong and clean signals, eliminating electrical noise and ghost signals. 22 gauge, solid copperweld conductors, foam insulation, mylar-aluminum foil shield, stranded tin copper down wire, black polyethylene outer jacket. Spade terminals included. 4 1/4 lbs. per 100 ft. Only in lengths listed below.

32 R 31067 50 ft. coil Net 4.39
32 R 31875 75 ft. coil Net 5.98
32 R 31883 100 ft. coil Net 7.95

LVL-UV Log-Periodic Antennas


FOR VHF-UHF-FM/STEREO

COLOR
Approved




A
34⁹⁵

VHF to 175 Miles
UHF to 90 Miles
FM to 95 Miles




B
21⁹⁵

VHF to 125 Miles
UHF to 65 Miles
FM to 70 Miles



C
15⁹⁵


VHF to 85 Miles
UHF to 50 Miles
FM to 55 Miles



D
11⁹⁵

VHF to 60 Miles
UHF to 30 Miles
FM to 35 Miles

3 ANTENNAS IN 1
UHF-VHF-FM CHANNELS 2-83



Complete with
VHF-UHF-FM
Signal Splitter

NO EXTRA CHARGE!

- For Color or Black-White Pictures Plus FM
- One Down Lead for All 3 Signals
- Powerful Log Periodic Design
- High Front-to-Back Ratio—High Gain
- Goldenized Finish For Long Lasting Protection
- More Picture Power On Channels 2 To 83

Super color-engineered antennas of famous log periodic design for color TV and stereo FM. Now you can easily install one antenna instead of three to obtain superb reception on VHF channels 2-13, UHF channels 14-83 and the FM band with one downlead. Ends unsightly roof clutter while providing strong, clear signals to improve the performance of any TV or FM set. All antennas are preassembled. VHF elements are reinforced with triple-strength sleeves at pivot points. The goldenized finish provides weather protection. Larger model features boom brace supports for greater rigidity. Supplied with a 3-way splitter for good isolation and low signal loss. Less Mast.


A 41 ELEMENT "EXTREME FRINGE" ANTENNA
Range in miles up to: VHF to 175, UHF to 90, FM to 95. 41 Individual elements, 26 for VHF/FM, 15 for UHF. Has 1" square 15 ft. boom with brace boom supports. Shpg. wt., 13 lbs.
18 R 01802WX No Money Down* Net 34.95

B 25 ELEMENT "FRINGE" ANTENNA
Range in miles up to: VHF to 125, UHF to 65, FM to 70. 25 Individual elements, 14 for VHF/FM, 11 for UHF. Has 1" square 10'1" boom.
18 R 01826WX Shpg. wt., 9 lbs. Net 21.95

C 17 ELEMENT "SUBURBAN" ANTENNA
Range in miles up to: VHF to 85, UHF to 50, FM to 55. 17 Individual elements, 10 for VHF/FM, 7 for UHF. Has 1" square 4'8" boom. Shpg. wt., 6 1/2 lbs.
18 R 01836WX Net 15.95

D 13 ELEMENT "METROPOLITAN" ANTENNA
Range in miles up to: VHF to 60, UHF to 30, FM to 35. 13 Individual elements, 6 for VHF/FM, 7 for UHF. Has 1" square 30" boom. WL, 4 1/2 lbs.
18 R 01844W Net 11.95

35 ELEMENT
VHF to 150 MILES
UHF to 90 MILES
FM to 75 MILES
29⁹⁵



COLOR
Approved

23 ELEMENT
VHF to 100 MILES
UHF to 60 MILES
FM to 60 MILES
17⁹⁵

LAFAYETTE "TECHNI-POWER" COLOR TV ANTENNAS UHF-VHF-FM CHANNELS 2-83

- Complete With VHF-UHF-FM Signal Splitter
- One Down Lead For All Three Signals
- For Color or Black and White Plus FM

Powerful combination VHF, UHF TV and FM-FM/Stereo antennas for near or deep fringe reception. The corner reflector yagi combination brings in uniform gain on VHF-UHF plus FM. The corner reflector doubles as a reflector system on UHF and as a director system on VHF. Built of high tensile strength aluminum with a gleaming goldenized finish for lasting protection. Factory pre-assembled for simple installation. Includes 3-way signal splitter for good isolation and low loss. Less Mast

35 ELEMENT "DEEP FRINGE" ANTENNA
Boom length, 120 inches. Shpg. wt., 11 1/2 lbs.
18 R 02107WX Net 29.95

23 ELEMENT "NEAR FRINGE" ANTENNA
Boom length, 81 inches. Shpg. wt., 7 lbs.
18 R 02115WX Net 17.95

TWIN-BOOM VHF-UHF-FM/Stereo Log-Periodic Antennas



3 ANTENNAS IN 1
UHF-VHF-FM
CHANNELS 2-83

Complete with
VHF-UHF-FM
Signal Splitter

NO EXTRA CHARGE!

- One Down Lead Required
- Extra Long Super Sensitive Capacitor-Coupled VHF Elements
- Multiple Directors and UHF Driven Elements for Maximum Picture Power
- Twin-Boom Construction for Extra Strength
- Goldenized Finish for Long Lasting Protection

Lafayette deluxe all-purpose twin boom three-in-one antenna for VHF, UHF, FM/STEREO. New frequency independent design permits all elements to work together on both low and high bands for maximum front-to-back ratio and high db gain. Extra long up to 55" reinforced aluminum VHF elements with wide band "cap-electronic" elements operate on both fundamental and harmonic modes. The result is an increased number of working elements producing maximum gain and directivity to bring sharpness and color brilliance to your screen. Disc-on-Rod UHF director system reinforces performance of surface wave UHF driver on low end of UHF band. Improved impedance match obtained by unique twin boom construction which combines mechanical rigidity with superior electrical performance. This superior construction virtually does away with interference caused by wind and vibrations. Features heavy duty insulators, rust resistant hardware and lasting goldenized finish. Complete with splitter to separate VHF, UHF, and FM signals. Less mast.

- A 63 ELEMENT "ULTRA-FRINGE" ANTENNA**
Range in miles up to: VHF to 200, UHF to 100, FM to 110. 63 individual elements, 22 for VHF/FM, 41 for UHF. Has heavy-duty 3/4" square "twin-boom" and boom brace support. Boom Length 15'2". Shpg. wt., 16 lbs.
18 R 02172WX No Money Down* Net 44.95
- B 45 ELEMENT "DEEP-FRINGE" ANTENNA**
Range in miles up to: VHF to 150, UHF to 80, FM to 85, 45 individual elements, 16 for VHF/FM, 29 for UHF. Has heavy-duty 3/4" square "Twin-Boom" and boom brace support. Boom Length 11'2". Shpg. wt., 12 3/4 lbs.
18 R 02180WX Net 29.95
- C 27 ELEMENT "NEAR FRINGE" ANTENNA**
Range in miles up to: VHF to 100, UHF to 60, FM to 65, 27 individual elements, 12 for VHF/FM, 15 for UHF. Has heavy-duty 3/4" square "Twin Boom." Boom Length 7'10". Shpg. wt., 9 lbs.
18 R 02198WX Net 19.95

A 44⁹⁵
VHF—To 200 Miles
UHF—To 100 Miles
FM To 110 Miles

B 29⁹⁵
VHF—To 150 Miles
UHF—To 80 Miles
FM —To 85 Miles

C 19⁹⁵
VHF to 100 Miles
UHF to 60 Miles
FM to 65 Miles

LAFAYETTE "TECHNI-COLOR" HIGH GAIN COLOR TV ANTENNA FOR VHF-UHF-FM/STEREO CHANNEL 2 TO 83

- One Down Lead Required
- With VHF-UHF-FM Signal Splitter
- Designed for "Deep-Fringe" Reception
- Rugged Goldenized Construction

Powerful High Gain 58-Element 82-Channel Antenna of new expanded design, increases capture area, gain, and front-to-back ratio. Improves impedance match and ghost rejection. Staggered tuned design on both the VHF and UHF bands insures flat-broad band performance on all 82 channels plus FM. This antenna provides the ultimate for color and black and white. Convenient behind-the-set splitter separates VHF-UHF-FM signals to individual terminations. Phasing harness integrated with boom, eliminates need for separate harness. Triangulated design makes it mechanically rugged. Boom length 11'5". Less Mast. Shpg. wt., 13 lbs.
18 R 02206WX No Money Down* Net 49.95

49⁹⁵ **COLOR Approved**

58 Element
VHF to 225 Miles
UHF to 110 Miles
FM to 120 Miles


*See Page 22 for Full Credit Details on Easy Pay Plan

COLOR
Approved

LVL Log-Periodic Antennas

FOR VHF-AND-FM/STEREO


LAFAYETTE "HIGH POWER" "VECTOR-LOG"[®]
SWEEP-ELEMENT ANTENNAS
DESIGNED FOR VHF-TV CHANNELS(2- 13)
AND FOR DYNAMIC FM



31⁹⁵
36 ELEMENTS

- Intensifies Color or Black-White Pictures . . . Plus FM
- Excellent Front-to-Back Ratio . . . High db Gain
- Sharp-Narrow Directivity and Selectivity
- Flat TV Color Response — Plus FM Signal
- Protective Goldenized Finish

Lafayette's powerful, revolutionary LVL—designed specifically for (VHF) true-to-life color reception plus black and white. Also reaches out to pull in static-free FM and stereo FM signals. Five models to choose from for ideal performance. Offers such exceptional quality features as: Heavy aluminum reinforced insulator cups—heavy duty insulators—special back-up brackets and square boom! Triple thick combination sleeved elements assure great ruggedness. Double contact drive line and air-insulated spacers provide maximum signal delivery to set. Less mast and twin lead.* With boom brace support.



10⁹⁵
10
ELEMENTS

Stock No.	Range	Elements	Boom Length	Shpg. Wt.	Net
18 R 01851W	up to 75 miles	10	4' 8"	6 lbs.	10.95
18 R 01869WX	up to 100 miles	14	6'11"	8 lbs.	14.95
18 R 01877WX	up to 140 miles	20	9' 5"	10 lbs.	19.95
18 R 01885WX	up to 175 miles	30*	12' 5"	12½ lbs.	27.95
18 R 01893WX	up to 200 miles	36*	14' 4"	13 lbs.	31.95


LAFAYETTE SUPER COLOR 'TENNA

FOR VHF - UHF - AND FM/STEREO
COMPLETE WITH VHF/UHF/FM SIGNAL SPLITTER

- For Color and Black and White
- Protected Goldenized Finish
- Easy To Install, Just One Down Lead


26 Element super color antenna with high gain providing fringe area reception on all VHF/UHF/FM channels. High front-to-back ratio minimizes co-channel interference. Rugged aluminum harness, with rust-proof clips deliver maximum signal to set. Includes VHF/UHF/FM signal splitter. Requires only one down-lead. Range: 26 element, up to 140 miles VHF, 90 miles FM, 60 miles UHF. Boom length 105" with aluminum boom support.

18 R 01638WX Shpg. wt., 9 lbs. Net 24.95



24⁹⁵

FAMOUS VHF-FM COLOR 'TENNA




14⁹⁵

- For VHF-FM Reception
- Range: Up To 125 Miles
- For Color and Black-White

Twelve twin-driven elements work with carefully tuned, phased and spaced directors and reflectors to extend flat high gain response across entire VHF band. Cuts out ghosts and unwanted signals. Rugged reinforced aluminum elements and brackets stand up under most severe wind and ice loading. 100% pre-assembled for easy installation. Less mast, lead in. Shpg. wt. 7 lbs.

18 R 01018WX Net 14.95

LAFAYETTE "Star Fire"[™] COLOR ANTENNA



10⁹⁵



- For VHF-UHF-FM Reception
- With VHF-UHF Signal Splitter
- Range Up To: VHF—50 Miles, UHF—25 Miles, FM—30 Miles

Eleven element high gain antenna provides VHF-UHF & FM reception with one downlead. Separate folded dipoles on low and high bands assure greatest power with constant 300 ohm impedance match. Sturdily constructed 68" boom. Completely pre-assembled—just snap open to install. Goldenized finish resists corrosion.

18 R 01976WX Shpg. wt., 5 lbs. Net 10.95

LAFAYETTE "Fringe Area" Antenna Outfits

• 20-40 FT. MAST • WITH OR WITHOUT FAMOUS ALLIANCE ROTATOR • FINEST COMPONENTS



SAVE WHEN YOU BUY COMPLETE ANTENNA OUTFIT


Nothing else to buy. Available with or without automatic rotor. Buying a kit gives you substantial savings over the total catalog price of individual components if purchased separately.

INSTALLATION ACCESSORIES

Antenna Outfits feature Lafayette "Deep-Fringe" Log-Periodic Antennas. (See pages 284 to 286 for antennas). Each kit contains pre-selected high-gain antenna, telescoping mast of heavy gauge galvanized steel, plus all components in kit "A" which includes a universal base mount, lightning arrester, 50' ground wire, 3-3/4" mast standoffs, 5-3/4" wood screw standoffs, 5-guy hooks, 5-turnbuckles, ground rod, 200' guy wire supplied with 20' outfits; 500' supplied with 40 outfits. 100' twin lead supplied with all outfits. Optional Automatic Rotor package (Kit "B") includes—Alliance U-100 Automatic Rotor, thrust bearing additional 10' antenna mast, 100' of rotor cable. Kits shipped express only.

Stock No.	Antenna	Mast	Kit	Wt.	Net
"ULTRA-FRINGE" VHF-UHF-FM ANTENNA OUTFITS					
18 R 90383WXM	18-02172WX	20 Ft.	A	39 3/4 lbs.	57.50
18 R 90375WXM	See Page 285	20 Ft.	A&B	57 3/4 lbs.	96.50
18 R 90367WXM	285	40 Ft.	A	58 lbs.	66.95
18 R 90391WXM		40 Ft.	A&B	75 3/4 lbs.	105.95
"EXTREME-FRINGE" VHF-UHF-FM ANTENNA OUTFITS					
18 R 90193WXM	18-01802WX	20 Ft.	A	36 3/4 lbs.	48.50
18 R 90201WXM	See Page 284	20 Ft.	A&B	54 1/4 lbs.	86.00
18 R 90219WXM		40 Ft.	A	55 lbs.	58.00
18 R 90227WXM		40 Ft.	A&B	72 3/4 lbs.	94.95
"ULTR-FRINGE" VHF-FM ANTENNA OUTFITS					
18 R 90235WXM	18-01893WX	20 Ft.	A	38 lbs.	43.50
18 R 90243WXM	See Page 286	20 Ft.	A&B	54 1/4 lbs.	81.95
18 R 90250WXM		40 Ft.	A	54 1/4 lbs.	53.00
18 R 90268WXM		40 Ft.	A&B	72 lbs.	92.50

CONICAL WINDOW ANTENNA



- Ideal for Apartments
- All Aluminum Construction

(A) VHF MODEL

Contains 4 full-sized elements plus 2 high frequency dipoles. Ideal for apartment building, hotels, etc., or wherever roof-top installations are impractical but necessary for the greater gain which is provided by a good outdoor antenna. Complete with all mounting hardware, less 300 ohm twin lead. Base spans up to 44". Shpg. wt. 3 1/2 lbs.

18 R 01380W Net 6.50

(B) VHF/UHF MODEL


Same as VHF model plus 8 element UHF section.

18 R 01646W Net 9.95

18 R 01398 Extension bar to 60" 1.69

18 R 01406 Extension bar to 72" 2.29

POWER BEAM VHF ANTENNA




- For VHF-FM Reception
- Range To 60 Miles
- Goldenized Finish

7.95

The ideal metropolitan and suburban VHF TV antenna. For Ch. 2-13, Broad-band, sharply directive. Full length elements, all aluminum construction, famous in-line design, 300-ohm impedance match reduces stray reflections and ghosts. Less mast. Shpg. wt. 4 1/2 lbs.

18 R 01026W Net 7.95

LAFAYETTE "PRIME AREA" VHF-UHF-FM ANTENNA




- 9 Elements
- Range Up To 30 Miles
- Complete with VHF-UHF Signal Splitter

Receives sharp, clear pictures on all VHF-UHF channels 2 to 83, plus FM/Stereo. Features 5 VHF and 4 UHF elements for crisp clean pictures in color or black and white. Gold colored alodized all aluminum construction, famous in-line design, 300-ohm impedance match reduces stray reflections and ghosts. Only one download needed to set. Deluxe square boom for extra stability. Less mast. Shpg. wt. 2 1/2 lbs.

18 R 02236W Net 5.95

Improve Your Color TV Reception With Lafayette Antennas

JFD LPV-CTC CAPACITOR - COUPLED LOG - PERIODIC TV ANTENNAS



Model LPV CTC 639

Color Tuned Capacitor-Coupled

54⁷⁵

FOR CHANNELS 2-83 AND FM STEREO


3 ANTENNAS IN 1
VHF/UHF/FM

Complete with VHF-UHF-FM Splitter
NO EXTRA CHARGE!



- Delivers Powerful 82-Channel TV Performance—COLOR or Black/White and FM/Stereo
- Only One Downlead Into Your Home
- Utilizes Capacitor-Coupled "Cap-Electronic" Dipoles for Extra High Gain
- Features Twin-Boom Construction

Unmatched picture power and FM/Stereo from one powerful antenna! New improved Log periodic trapezoid driver provides sharper UHF pictures, broader response. "Cap Electronic" dipoles work on both first and third harmonic modes to develop higher gain, narrower beam widths, and higher front-to-back ratios to achieve brilliant color and black and white on channels 2-83—plus FM stereo. New staggered disc director system aids in trapping "tricky" stratified UHF signals. Simplified installation: single antenna covers entire VHF-UHF TV range, plus the FM band, with a single down lead. Model LPV-CTC639 reinforced by powerful U-boom. Protective, gold anodized aluminum construction. Less mast.




Model LPV CTC 220

21⁴⁰

Stock No.	Model No.	Active Elements	Max. Range VHF	Max. Range UHF	In Miles	Boom Length	Shpg. wt. lb.	Net
18 R 39224WX	LPV-CTC639	39	185	90	100	163"	17	54.75
18 R 39232WX	LPV-CTC426	26	125	75	85	108"	10	36.45
18 R 39240WX	LPV-CTC220	20	90	55	60	83"	6	21.40

JFD LPV-TV COLOR LOG PERIODIC VHF/FM ANTENNAS FOR CHANNELS 2-13 AND FM STEREO

As Low As **21²⁵**



Color Tuned Capacitor-Coupled


- Color Capacitor Electric Dipoles To Assure Fine Performance On All VHF Channels
- Highest Gain For Deep, Rich Full Color
- Dual Boom Ruggedized Construction

Pulls in extra true color and sharp black/white pictures—plus true-fidelity FM through patented frequency-independent, log periodic design with cap-electronic dipoles. Maximum gain and directivity on all VHF channels and especially channels 7-13. High S/N ratio eliminates snow. Ghost and interference rejected by sharp directivity, narrow beamwidth and high f/b ratio. "Flip-Quick" construction for quick easy assembly. Models LPV-TV130 and LPV-TV190 reinforced by powerful U-boom. All models gold colored alodized for protection against weather and corrosion. Less mast.

Stock No.	Model No.	Active Elements	Max. Range in Miles	Boom Length	Shpg. wt.	Net
18 R 38846WX	LPV-TV190	19	VHF up to 225	205"	17 lbs.	68.95
18 R 38820WX	LPV-TV130	13	VHF up to 175	143"	14 lbs.	44.40
18 R 38804WX	LPV-TV80	8	VHF up to 115	81"	9 1/2 lbs.	28.20
18 R 38796WX	LPV-TV60	6	VHF up to 90	70 3/4"	6 1/2 lbs.	21.25

JFD LPL-FM LOG PERIODIC FM/STEREO ANTENNAS

- Designed for L-O-N-G Distance Reception
- Uniform Gain Across Entire FM Band
- Directional Sensitivity for Highest Interference Rejection
- Super-Rugged Triple Square Boom Construction



As Low As **15⁶⁵**

Log periodic array of L-dipoles pull in superior gain—provides extra high signal strength for FM and FM Stereo-multiplex tuner circuits. Offers maximum rejection of reflected or multipath signals that cause stereo distortion. Elements provide a backfire radiation for superior f/b ratio. Frequency independent wideband response permits unvarying gain across the entire FM band. Low VSWR transfers maximum signal from the antenna to the set. Easy to assemble. Gold alodized colored construction protects against weather and corrosion. Less mast.

Stock No.	Model	Elements	Range in Miles	Shpg. wt. lb.	Net
18 R 38275WX	LPL-FM10A	10	to 175	17	39.10
18 R 38291WX	LPL-FM6A	6	to 125	8	23.50
18 R 38309WX	LPL-FM4A	4	to 75	6	15.65

Prices and Specifications are Subject to Change Without Notice

Super Colortron Antennas by Winegard

COLOR
Approved


"COLOR-WEDGE"
FOR SUPER POWER COLOR
CH 2-83 AND FM STEREO

Complete With
VHF/UHF/FM Signal Splitter



- Delivers Superb Color Fidelity and Perfect Black and White
- Exclusive Built-In Cartridge Housing
- Optional Solid State Preamplifier Loads Instantly Into Housing
- Single Downlead Into House
- Gold Anodized Throughout
- Super Rugged Truss Construction

Winegard Color-Wedge high gain, 82 channel antennas provide superb color fidelity, perfect black and white pictures and excellent FM stereo reception even in deep fringe areas. Extremely high front-to-back ratio and sharp directivity insure ghost-free reception. Narrow vertical reception lobe prevents antenna from picking up such interferences as airplane flutter, ignition noise, and harmonic radiations from citizens band or amateur transmitters. Antennas feature perfect, no-loss coupling between VHF and UHF sections and precise impedance match to downlead terminals for excellent signal transfer to TV set. Wedge design of VHF elements provide maximum VHF capture area for increased gain... up to 50% shorter than most all-channel antennas with comparable gain. Antenna is gold anodized and performance is not affected by moisture. Super-rugged truss construction holds elements in perfect alignment and withstands the most severe weather conditions. Completely pre-assembled, easy to install. For extra power, use Super Colortron Cartridge Amplifier. See listing below.



Model
CW-1000



Built-in 300/75 ohm
Cartridge Housing



Optional
Solid State
Preamplifier
Loads Instantly
Into Housing

As Low As
41²⁷
No Money Down*

Model
CW-96

Stock No.	Model No.	Elements	Max. Range in Miles			Boom Length	Shpg. Wt.	Net
			VHF	UHF	FM			
10 R 60782WX	CW-1000	56	225	100	120	135"	21½	69.97
10 R 60840WX	CW-98	38	185	90	100	114"	18	52.15
10 R 60857WX	CW-96	27	125	75	85	77"	13½	41.27

Solid State Amplifier For Above Antennas See Listing Below

HIGH GAIN 82-CHANNEL SUPER COLORTRON ANTENNAS FOR VHF-UHF-FM

Extremely high uniform gain for VHF-UHF-FM reception. Three models with pin-point directivity. High front-to-back ratio for sharp, clear color and black and white reception. Exclusive impedance correlators allow each model to be much more compact for easier installation and less wind resistance. Features vertical resonant UHF reflectors for very high UHF gain. FM control elements allow user to peak antenna for extra long distance FM and FM stereo. Exclusive built-in cartridge housing holds 300/75 ohm terminal board (included) for weather-tight down-lead connection. For extra power, use Super Colortron Cartridge amplifier listed below.

Stock No.	Model No.	Elements	Max. Range in Miles			Boom Length	Shpg. Wt.	Net
			VHF	UHF	FM			
10 R 60618WX	SC-81	23	90	60	85	81"	9½ lbs.	29.25
10 R 60626W	SC-80	18	75	50	70	64"	8 lbs.	23.69
10 R 60634W	SC-79	13	50	40	55	44"	6½ lbs.	18.63

- Exclusive Winegard Built-In Cartridge Housing
- One Downlead

As Low As **18⁶³**

Model
SC-81

Complete with
VHF-UHF-FM
Signal Splitter

SOLID STATE CARTRIDGE AMPLIFIER FOR ALL SUPER-COLORTRON ANTENNAS ABOVE

- Amplifies VHF-UHF & FM Signal
- Signal Booster Extends Reception Range, Strengthens Weak Channels and Lets You Operate Several Sets At The Same Time

Model AC-823B Adds greater range to your Super-Colortron antenna with this solid state cartridge amplifier. Printed circuit design with long-life overlay silicon transistors, adds big signal boost right at point of reception. Helps pull in weak distant channels and delivers strong clean signals to TV set for crisp, clear, snow-free color and black and white. Slides perfectly into Super-Colortron cartridge housing on antenna. Includes power supply that mounts on back of TV set. For 300 ohm lines. For 117 VAC, 60 Hz. Shpg. wt., 1 lb. 18 R 60659 No Money Down* Net 31.24

ONLY
31²⁴



*See Page 23 for Full Credit Details on Easy Pay Plan

UHF TV Antennas for Channels 14-83

LAFAYETTE PARABOLIC UHF ANTENNA

• Ultimate In Directivity— Rugged Construction

As Low As
22⁹⁵

7-FT. DEEP FRINGE PARABOLIC ANTENNA

• For Deep Fringe Areas

Advanced 7 ft. diameter antenna utilizes a parabolic design to achieve the highest performance characteristics attainable. Multiple element construction has extremely high front-to-back ratio with narrow beam width to help eliminate ghost reflections— especially in fringe areas. All aluminum thick-wall assembly is fitted with vibration dampers for quiet high wind operation. For channels 14 to 83. Impedance: 300 ohms. Shpg. wt., 13¼ lbs.


18 R 01927WX Net 36.95

5-FT. PARABOLIC UHF ANTENNA

• For Fringe Areas

A 5 foot parabolic antenna which utilizes a signal drive broadband driver unit. The high front-to-back ratio eliminates the necessity of reflectors which shadow the center of the field. Signals reaching any part of the parabola are concentrated on the driver mounted at the exact focal point. This selective design provides up to 18.6 db gain. Back of reflector acts as a shield to reduce unwanted and reflected signals. Preassembled for easy installation. Small diameter, rugged elements with vibration dampers limit ice loading. All aluminum with protective Gold Corodized finish. Shpg. wt., 7¾ lbs.

18 R 01901W Net 22.95



LAFAYETTE UHF CORNER REFLECTOR

4⁹⁵

- Range Up to 50 Miles
- Goldenized

For quality UHF reception even in fringe areas. High gain, sharp horizontal and vertical directivity eliminates "ghosts" and "snow." Rugged construction, large reflector screen made of highest grade aluminum tubing. "Fold-open" assembly. "Goldenized" finish for protection against weather and salt-air deterioration. Shpg. wt., 3 lbs.

18 R 01448W Net 4.95



JERROLD PARA-PRO 27 ELEMENT UHF ANTENNA

- Add On To Present VHF Antenna—No Antenna Coupler Required
- Range Up To 75 Miles

Only **6⁹⁵**

Low silhouette, high-gain periodic design requiring little space and offering a minimum of wind resistance. Has 11 driven elements plus 16 parasitic directors for perfect, sharp color reception across entire UHF band. Comes assembled with all hardware for quick, easy mounting to existing mast. Shpg. wt. 3½ lbs.

18 R 36113W Net 6.95




4-BAY BOW-TIE UHF ANTENNA

- Completely Preassembled
- Excellent Directivity
- Flat Response Across Each Channel
- Range Up To 60 Miles

5⁹⁵

Four bay, UHF bow-tie antenna. Exceptionally high (12db) gain—relatively flat across the entire spectrum. Fully factory assembled. Quickest and easiest to install. High efficiency screen grid reflector boosts front to back ratio. Unique "cross-over" phasing bars—open V elements, rugged—rigid—corrosion resistant construction. Shpg. wt., 5 lbs.

18 R 01422W Net 5.95



BLONDER-TONGUE "GOLDEN DART" UHF ANTENNA

- Range Up to 50 Miles
- 4⁹⁵**

No matter what UHF channels serve your area—from 14 to 83—the Dart delivers a sharp, clean pattern on every channel. Utilizes the logarithmic—periodic principle which is the modern approach to UHF TV antenna design. Maintains an excellent front-to-back ratio (more than 20 db). An extremely low VSWR prevents ghosts and smears. Completely pre-assembled, nothing to snap out, no screws to tighten. Rugged, unitized welded construction. Shpg. wt., 2¾ lbs.

18 R 18012 Net 4.95



UHF INDOOR ANTENNA

3⁹⁵

- Attractive "Bow-Tie" Design

Decorator designed to blend perfectly with any interior. Black "bow-ties" are sharply set off by the attractive golden grid. Provides excellent UHF reception; minimizes snow and ghosts; attaches to back of any TV set; uses 300-ohm lead-in wire. Shpg. wt., 2½ lbs.

18 R 63240 Net 3.95



ATTACHABLE UHF-TV ANTENNA LOOP

- Fits all Television Sets


UHF indoor antenna has omni-directional pick-up for stronger signal reception. Simple to install, universal mounting lugs will fit twin lead terminals on any UHF converter or TV set. Shpg. wt., 5 oz.

FM TWIN LINE ANTENNA

Folded dipole type for indoor use. Six foot lead-in with spade lugs. Install behind cabinet, under rug, or any concealed place. Imported. Wt., 4 oz.

99 R 40297 Net. 99

.99



UNIVERSAL PORTABLE TV REPLACEMENT ANTENNA RODS

As Low As

1²⁹

Exact replacement telescoping antenna rods for all indoor TV antennas. Easily replaces existing 4, 5 or 6 section broken or bent antenna rods. Heavy gauge—chrome finished. Easily installed with a screw-driver. Shpg. wt., 4 oz.

4 section 38" long Net 1.29

18 R 54009 Net 1.59

5 section 38" long Net 1.59


18 R 54017 Net 1.59

6 section 40" long Net 1.99

18 R 54025 Net 1.99

FM Antennas for Superior Performance

"DOUBLE-DRIVEN" 5 ELEMENT FM ANTENNA




- For Fringe Area
- GOLDENIZED**

6⁹⁵

High gain antenna design for the audiophile who seeks perfection in FM reception. Ideally suited for FM-stereo reception. Trouble free operation even under severe weather conditions. The fully automatic snap-lock brackets insure easy, rapid and secure installation. Boom length: 72". Shpg. wt., 5 lbs.
18 R 01497WX

Net 6.95

"DOUBLE-DRIVEN" 10 ELEMENT FM ANTENNA



- For Deep Fringe Areas
- GOLDENIZED**

11⁹⁵

Ideally suited for FM-stereo reception. This 10-element double-driven, yagi array has the necessary added gain, sensitivity and directivity to compensate for the lack of signal strength. All-aluminum goldenized construction. Fiberglass Insulators, Torsion lock hardware sure-lock mast clamp. Boom length: 128". Shpg. wt., 8 lbs.
18 R 01281 WX

Net 11.95

FM ALL DIRECTIONAL ANTENNA KIT

- Attaches To Existing TV Mast
- All Directional
- 40 Mile Range

6⁵⁰



Provides excellent gain for areas up to 40 miles from the station. Gold alodized aluminum. Complete with 50 ft. of 300-ohm twin lead, mast standoff, screw eye standoffs, mast mount.

18 R 01323W Shpg. wt., 3 1/4 lbs.

Net 6.50

FM ANTENNA ONLY. Shpg. wt., 2 lbs.

18 R 01331W

Net 4.29


FM STEREO-PLEX ANTENNA

- Receives up to 50 Miles In Any Direction

9⁹⁵

Model FML Seven-Element Stereo Plex FM antenna is designed specifically for Multiplex Stereo FM. An omnidirectional antenna with high gain and sensitivity. Goldenized for long lasting protection. All aluminum construction. Receives from any direction at distances up to 50 miles from the station. Shpg. wt., 4 1/2 lbs.
18 R 24028W


Net 9.95



FINCO

HIGH GAIN BROAD BAND FM ANTENNAS

ALL DIRECTION FMT-A KIT



9²⁰

- Receives Stations from All Directions
- Gold Corodized

Model FMT-A Mounts on present T.V. mast. An All Direction FM Antenna designed for reception over the entire FM band. Two folded dipoles are matched with a special quarter wave phasing stub for optimum gain and "all direction" radiation pickup pattern. Kit supplied with 50 ft. of 300 ohm twin lead, two mast stand-off insulators, 3 Wood screw-eye stand-off insulators. Gold Corodized. Shpg. wt., 3 3/4 lbs.
18 R 30280W

Net 9.20

FM STEREO MODEL FM-4G




16³⁵

- For Fringe Areas
- Gold Corodized

Receive clear, strong signals with this 6 element FM antenna. Geometrically designed to provide 9.6 db gain with twin driven element and impedance control stubs. Extra wide spacing of the six elements results in high front to back ratio (22.5). Square boom for rigid support with locking brackets for no-tilt elements. Pre-assembled. Shpg. wt., 8 lbs.
18 R 30249WX

Net 16.35

FM STEREO MODEL FM-5



23⁹⁰

- For Deep Fringe Areas

10 Element deluxe FM antenna using twin drive elements with impedance control "T" match stubs. Db gain of 9.6 for maximum reception throughout 88-108 MHz band. Patented fidelity phasing provides 27.1 front to back ratio with 1.25 SWR. Corrosion resistant with gold corodized finish. Sturdy saddle mounting of elements and "box girder" snap out, self aligning brackets are pre-assembled for easy installation. Braced square boom, 10 ft. long. Shpg. wt., 8 lbs.
18 R 30231WX

Net 23.90


FINCO

WINDOW MOUNTED FM ANTENNA

- Ideal For Apartments, Buildings, etc.

Only

10⁴⁵



Model FM-WT. The ideal answer to FM/FM Stereo reception problems in apartment buildings, etc., wherever a rooftop antenna is impractical but an outside antenna is needed for improved reception. The antenna is FINCO's famous omnidirectional FMT, ingeniously mounted on a highly adaptable window mount. Mounting can be either horizontal or vertical. The sturdy extendable window frame mount will fit any window up to 42 inches wide. Shpg. wt., 4 1/2 lbs.
18 R 30462W

Net 10.45

FINCO

INDOOR 2-SET FM SIGNAL BOOSTER

17⁴⁵

- High Gain 20db
- Ideal For Stereo And Monaural FM



Model 65-7, high gain, 20 db (nominal), low noise transistorized FM amplifier, designed to reject any strong signals outside the FM band to improve reception of weak FM signals in deep or medium fringe areas, even where strong local signals are present. Shock hazard is eliminated through the use of an isolation transformer. 300-ohm input and unique output board will drive 1 or 2, 300-ohm sets. Compact, and easily mounted on set, baseboard, or wherever desirable. Complete unit measures: 1 3/4 x 4 x 4 1/2".
18 R 30421 Shpg. wt., 1 1/2 lbs.

Net 17.45

Depend on Lafayette For Quality Communications Equipment

Lafayette Cat. No. 720 291

Rembrandt

IMPERIAL-COLOR
UHF/VHF ANTENNA

24⁹⁵




- Electroplated 24 Karat Gold Loops
- Superior on Color and Black and White

For clearer and sharper color and black and white pictures, the Imperial antenna has specially designed 6-section all brass elements with exclusive "High Inductance Grid" and "Loading Coil". You can actually pinpoint signal pickup with the combined action of the special "Signal", "Picture", and "Color" controls provided. Five gears remotely control two sensitive color tuning loops which allow you to easily achieve more precise color adjustment on any set. Special 12-position signal level control reduces overloading of signals. Walnut decorator styling. 18 R 12429 Shpg. wt., 4½ lbs. Net 24.95

Color VHF/UHF Indoor Antennas

COLOR CHAMPION
UHF/VHF ANTENNA

19⁹⁵




- Features Color Tuning Loops and Power Boosters
- VHF-UHF Isolation Network Switch

Get clearer, sharper pictures on all VHF/UHF channels 2 thru 83, in color and black and white, plus FM stereo. Combined action of color tuning loops, power boosters, and 5 section 46" solid brass elements give superb reception. 12 position picture correction control clears up ghosts, snow and color fading in most difficult areas. Separate VHF/UHF isolation network switch allows consistent true color levels and sharper color register. Attractive styling with walnut finish. Range up to 30 miles. Shpg. wt., 4¼ lbs. 18 R 12411 Net 19.95

"COLOR KING"
VHF/UHF ANTENNA

12⁹⁵



- Clear, Sharp Color/B&W Pictures
- Special Color Phasing Loops and Color Filter Control

Deluxe indoor antenna for color and black and white reception on all VHF and UHF channels. Perfect pictures insured by color phasing loops and color filter coupled with 46" solid brass telescoping arms. 12 position picture correction control with silver plated contacts to clear up annoying "ghosts" and "snow" even in the most difficult reception areas. Separate VHF and UHF transmission lines provide low-loss matched impedance. Attractive styling in walnut or mahogany. Shpg. wt. 3½ lbs. 18 R 12221 Walnut Net 12.95
18 R 12239 Mahogany Net 12.95

9⁹⁵

"DELUXE" VHF/UHF ANTENNA

- For Channels 2-83
- For Color, Black and White TV

Indoor TV antenna with 46" telescoping arms coupled with adjustable radar loops for extra efficient operation in difficult reception areas. 12-position dual control to reject ghosts and orient antenna to direction of strongest signal. Solid brass tip balls on telescoping arms eliminate signal losses and static discharge interference. Radar loop principle makes possible clearer and sharper pictures on all channels. Matched impedance with separate leads for VHF and UHF. Attractive, durable plastic base. Shpg. wt., 3¼ lbs. 18 R 12080 Walnut Net 9.95
18 R 12072 Mahogany Net 9.95

6⁹⁵

"RADARCOIL" VHF/UHF ANTENNA

- For Color and Black & White

Wherever an indoor antenna is necessary for both color and black-and-white all-channel TV reception, the "Radar Coil" will bring you clearer and sharper pictures. Powerful indoor antenna utilizes 46" long solid-brass 4-section telescoping arms to provide efficient reception, plus 12-position switch helps to eliminate ghosts and snow. A real beauty to grace any decor. Includes separate leads for VHF and UHF. Available in mahogany, or walnut finish base. Shpg. wt., 2¼ lbs. 18 R 12122 Walnut Net 6.95
18 R 12114 Mahogany Net 6.95

6⁹⁵

FM STEREO/MULTIPLEX ANTENNA

- Reduces Drift, Hum and Noise

Assures virtually drift and distortion-free FM reception. Strengthens weak stations and helps block out reflected signals and background noise. Features ¼ wave 4-section precision arms; ¾ wave induction coil; 12 position station direction control and a special noise filtering circuit for extremely effective performance. Provides strong reception over entire 88-108 MHz FM band. Low silhouette slim-line styling. Shpg. wt., 2¼ lbs. 18 R 12197 Walnut Net 6.95
18 R 12171 Mahogany Net 6.95

4⁹⁸

"POWER-KING" VHF/UHF ANTENNA

- 12-Position Switch

Designed for both color and black-and-white; all channels VHF/UHF 2 thru 83, plus FM stereo 88-108 MHz. Combined action of unique concentric rings and long 39" telescoping arms help to eliminate ghosts, snow and interference for clear sharp black-and-white plus true-to-life color reception. 12-position station direction control effectively matches the antenna to channel frequency for optimum gain and all-directional pickup pattern. Slimline styling. Includes separate leads for VHF and UHF. Shpg. wt., 2 lbs. 18 R 12155 Walnut Net 4.98
18 R 12148 Mahogany Net 4.98

Add Channels 14-83 To Your 12 Channel TV Set

**BLONDER-TONGUE UHF
CONVERTER/AMPLIFIER**

BLONDER-TONGUE UHF CONVERTER

FINCO UHF CONVERTER



30⁹⁰



20¹⁵



14⁹⁵

Model BTX-11A Now you can enjoy additional educational and regular UHF programming. This attractive solid-state converter adds all UHF channels (14-83) to your present TV, anywhere within the range of a UHF station. Features a new dual speed 100 to 1 fine vernier and illuminated dial for easy tuning; 3 times amplification; double tuned UHF input circuits and shielded oscillator section for interference-free reception. AC convenience outlet. Complete with UHF loop antenna, connecting cable. Reliable patented tuner; spliceless, stripless terminals. For 110-120VAC/60Hz, UL listed. Shpg. wt., 2 lbs. **18 R 18319** Net **30.90**

Model BTX-999 Keep abreast with the new look in TV programming. If your present television has been dated by modern UHF reception, modernize your TV and allow for future expansion. Adds all UHF channels (14-83) to your B&W or color TV set. Ideal for prime signal areas up to 20 miles from the station, and in many areas can perform well using only an indoor antenna. Low noise, solid state circuit is virtually drift-free. Rugged, reliable patented tuner. Fine vernier illuminated dial for easy tuning. Spliceless, stripless terminals. Complete with UHF loop antenna, connecting cable. For 110-120 V. 60 Hz, AC. UL listed. Shpg. wt., 2 lbs. **18 R 18301** Net **20.15**

Model U-VERT 100 All-transistor UHF converter provides clear, all-channel reception in metropolitan areas where you receive a strong television signal. Adds all the UHF channels (14-83) to your present TV set. Unit is housed in a sturdy, plastic, streamlined cabinet that looks like expensive furniture... will actually enhance the appearance of any room as it sits on top of the TV set. Easy to install—all you need is a screwdriver and a few minutes of your time; extremely simple to operate. Meets all FCC specifications. Overall cabinet size 8x5x3 3/4". Operates with 110-120 volts. 60 Hz., AC. U.L. listed. Shpg. wt., 2 1/4 lbs. **18 R 30314** Net **14.95**

JFD "MONTEGO" COLOR VHF/UHF TV ANTENNA

- All Angle Ball Sockets For Easy Positioning
- Features Color-Accented Dipoles
- 14-Position Picture Clarifier Control

7⁹⁵



Just flick the knob of this advanced indoor TV antenna and eliminate ghosts, snow and smears. Interacting impedance matching circuits work together with phased-intersecting loops and adjustable ball-pivoted 45° telescoping dipoles to pull in true-to-life color, and sharper black and white on channels 2 to 83. Color accented dipoles. High quality polished chromated brass elements. Handsomely styled walnut colored tilt-proof base. Separate VHF and UHF twin leads. Shpg. wt., 3 lbs. **18 R 39208** Net **7.95**


JFD "LE MANS" COLOR VHF/UHF TV ANTENNA

- Features Color-Accented Dipoles
- 14-Position Picture Clarifier Control
- Clears-up Color, Black/White and FM Stereo

12⁹⁵



Deluxe indoor TV antenna for color, black and white reception. 14-position picture tuning control clears-up snow, ghosts and smears. Interacting impedance matching circuits and adjustable ball-pivoted 45° telescoping color-accented dipoles deliver brighter, crisper pictures in color or black and white on channels 2 to 83. High quality polished chromated brass elements. Elegant walnut colored tilt-proof base with walnut wood grain inlay. Separate VHF and UHF twin leads. Shpg. wt., 4 lbs. **18 R 39216** Net **12.95**



(A) 4-SECTION DIPOLE ANTENNA

Tip proof base. 4-section aluminum dipoles adjust for best picture on all VHF channels and FM. Handsome mahogany base. Tip-proof felt padded base design safeguards TV cabinet. Complete with 300-ohm twin line. Shpg. wt., 1 1/4 lbs. **18 R 38408** Net **1.69**

(B) ASTRO-JET SWITCH-TYPE ANTENNA


Dual direction-finding loops pull in stronger signals on UHF spectrum. 4-section, 38 inch, telescoping dipoles provide VHF reception. Multi-position channel-selector switch rejects ghosts, interference. Separate leads for VHF and UHF. Cushioned, tip-proof mahogany base. Shpg. wt. 1 1/4 lbs. **18 R 38853** Net **3.95**

Similar to above for VHF/FM only. **18 R 38390** Net **2.95**

(C) UNIVERSAL BEHIND-SET TV ANTENNA

For portable and console TV's. Excellent replacement. 5-section, highly polished dipoles extend to 38" and have a 360° swivel. Collapses behind set. With mounting screws. **18 R 71011** Shpg. wt., 3/4 lb. Net **2.39**

EXACT REPLACEMENT ANTENNAS FOR SONY AND PANASONIC TV SETS



Avg. shpg. wt., 8 oz.

Stock No.	Fig.	Panasonic Model No.	Net
18 R 39265	1	AN 109, AN 209	3.49
18 R 39273	2	AN 29, AN 52	4.15
		AN 32, AN 59	

Stock No.	Fig.	Sony Model No.	Net
18 R 39281	3	500U, 900U, 920U	3.27
18 R 39299	3	700U, 710U	4.57

Make Lafayette Your One Dependable Source for Everything in Electronics

Lafayette Cat. No. 720 293

Winegard Color TV-FM Boosters

VHF-UHF-FM SOLID STATE BOOSTER-COUPLER



30⁴⁸

- 4-300 Ohm Outputs
- Perfect For Ch. 2-83 and FM Home System
- Excellent For Color Because Of Uniform Gain


Model BC-382 highly efficient TV-FM signal amplifier with overlay silicon transistors and printed circuitry. Delivers full gain on all 82 channels (5 db for VHF, 4.5 for UHF), enough to operate 1, 2, 3, or 4 sets. 15 db isolation between outputs. Low noise (6.2 db avg., VHF, 11.7 db avg., UHF), cuts snow even in deep fringe areas. Uses existing 300-ohm downlead to the input and has 4-300 ohm outputs with "no-strip" connections. In enamel steel case with connectors and instructions. 117 VAC. Shpg. wt., 2 1/4 lbs.

18 R 60733 Net 30.48

Model BC-782. Similar to above except for 75 ohms; gain 6.5 db per output. Shpg. wt., 2 1/4 lbs.

18 R 60741 Net 33.04

SOLID STATE VHF-FM 4-SET BOOSTER-COUPLER



29¹⁰

- +7.1db Gain To Each Of 4-300 Ohm Outputs
- Recommended For Color and Black and White—
- Improves FM Reception
- 75 and 300-ohm Inputs


Model BC-234 makes a good home TV and FM system amplifier, or an amplified 4-set coupler. Gain is +7.1 db at each of the 4-300 ohm outputs or +14 db at the single 75 ohm output. Uses temperature stable overlay silicon transistors—long life, low cost operation. Flat response for perfect color reception. No interaction between sets. All metal housing. Includes connectors. 117VAC.

18 R 60758 Shpg. wt., 2 1/4 lbs. Net 29.10

Model BC-274 As above, except with 4-75 ohm outputs. Avg., gain 4 db per output. With connectors. Shpg. wt., 2 1/2 lbs.

18 R 60766 Net 29.37

+25 db VHF-UHF-FM SOLID-STATE COLOR SYSTEM AMPLIFIER



44⁹⁰

- Will Drive 10 TV/FM Units
- Use In Motels, Apartments, Hospitals, Homes


Model DA-825A. 75-ohm, 82-channel high quality color and black and white amplifier with 25 db gain. Rugged transistor circuitry features silicon transistors in a unique grounded emitter circuit for excellent stability, sensitivity, and ultra-low noise figure (5.1 db VHF, 7 db UHF.) Provides 35 db mV per channel UHF output with 4-channel input operating at 60% maximum input level. Ideal for home and commercial MATV systems with up to 10 line tap offs. May be used with a single 82 channel antenna or separate VHF-UHF antennas. Has separate inputs for VHF and UHF. Model CS-775 separator-joiner recommended for separating VHF-UHF signal from a single downlead of a 82 channel antenna. Compactly designed in a cabinet unit. Complete with coaxial connectors, hardware and built-in 117VAC power supply. Shpg. wt., 2 1/4 lbs.

18 R 60709 No Money Down* Net 44.90

Model CS-775 Separator-Joiner to attach single downlead to separate VHF-UHF inputs of DA-825A above. Shpg. wt., 1/2 lb.

18 R 60824 Net 5.96

SUGGESTED DISTRIBUTION SYSTEM FOR ABOVE



82 CHANNEL 2-TRANSISTOR VHF-UHF-FM SOLID-STATE AMPLIFIER

24²⁵



Mast Mounted Unit



Indoor Power Supply

- 20db Gain On VHF-FM
- 10db Gain On UHF
- For Color and Black and White
- Use With Any VHF-UHF-FM Antenna

Model RD-830 Twin-transistor antenna preamplifier gives big signal boost to any 82 channel antenna for beautiful color and black and white reception. No extra wires needed; connects to existing downlead. High signal input assures snow-free reception of weak and distant stations. AC isolation transformer—no shock hazard. Protected against lightning, static discharges, or power line surges. Built-in hi-pass filter. Has single 300 ohm input and output. With AC power supply, mtg. hardware. 117 VAC. 60 Hz. Shpg. wt., 1 1/2 lbs.

18 R 60873 Net 24.25

Model RD-870 Same as above but 75-ohm output.

18 R 60881 Net 24.71

VHF-UHF-FM SOLID-STATE 2 SET BOOSTER-COUPLER



14³²

- Doubles Input Signal
- Perfect For Color and Black and White
- High Isolation Between Sets

Model BC-830. Boosts signals on all channels 2 thru 83, plus FM; operates two TV sets or TV and FM set from single 300 ohm antenna downlead. Unique lightning protected circuit overcomes loss of splitting signals. Average gain of 5.25 db to each output, provides a healthy boost for snow-free pictures. High input level prevents overload in mixed signal area. 300 ohm input and output thru handy "no strip" screw terminals. Operates on 117VAC. 60 Hz. Shpg., 3/4 lb.

18 R 60717 Net 14.32

Model BC-870. Similar to above, except with 2-75 ohm outputs. Average gain. 4.5 db to each output. Shpg. wt., 3/4 lb.

18 R 60725 Net 16.25

FM SUPERCHARGER



14²⁰

- Transistorized
- Gives You 8 Times More FM Signal
- Ideal for Stereo and Monaural FM
- Easy to Install

Model FM-340. Greatly improves FM and FM stereo reception. Transistorized booster-amplifier adds +17 db gain (8 times more signal) to incoming signal. Ideal for fringe and deep fringe areas. 300 ohm input and output. Bandpass: 88-108 MHz. Operates on 110-120 VAC 60 Hz.

18 R 60642 Shpg. wt., 3/4 lbs. Net 14.20

ACCESSORIES FOR DISTRIBUTION SYSTEM



Model VTF-73A—Flush mounting 82 channel variable line tap. Matches 75 ohm input to 300 ohm output. Fits standard wall box with plug.

18 R 60774 Shpg. wt., 7 oz. Net 3.78

Model SB-1—Rugged plastic, surface mounting wall box for outlets or line tap-offs. Shpg. wt., 6 oz.

18 R 60907 Net .60

Model T-28—82-channel molded matching transformer for attaching 75 ohm coaxial cable to 300 ohm antenna terminals of TV set. Features very low insertion loss with F-59 connector. Shpg. wt., 7 oz.

18 R 60204 Net 2.19

Model T-28M—Mast mounted 82 channel. Matching Transformer matches 300 ohm antenna to 75 ohm coaxial cable. Complete with mounting clip, weatherproof boot, and F-59 connector. Wt., 8 oz.

18 R 60816 Net 2.30

Model CS-285—Behind set VHF-UHF signal splitter.

18 R 60584 Shpg. wt., 4 oz. Net 2.25

Model CS-175—Behind set VHF-UHF signal splitter and 75-300 ohm matching transformer with F-59 connector.

18 R 60675 Shpg. wt., 4 oz. Net 3.96

COLOR
Approved

Color TV-FM Boosters

COLOR
Approved

LAFAYETTE COLOR-BOOST TRANSISTORIZED VHF-FM ANTENNA BOOSTER FOR CHANNEL 2-13 & FM/STEREO

15⁵⁰

Made in U.S.A.



- Gain +14.6 db — Supplies TV set Up To 5 Times More Signal — Low Noise High Gain Transistorized Circuit — Use With Any VHF (Ch. 2-13) Or FM Antenna

Solid-state antenna preamplifier for superb fringe area reception. Gives sharp color and clean black and white pictures without snow and interference plus provides a healthy boost to FM. Features exclusive lightning protection circuit, highest quality components, and latest RF circuit techniques. Weatherproof outdoor housing has handy five-way mounting bracket and "no-strip" screw terminals. Separate power supply plugs into any 117 VAC, 60 Hz outlet. AC Isolation transformer in the power supply eliminates shock hazard. Has single 300 ohm input and output. 18 R 02131 Shpg. wt., 1½ lbs. Net 15.50

LAFAYETTE COLOR-AMP. TRANSISTORIZED VHF-UHF-FM ANTENNA BOOSTER FOR CHANNEL 2 — 83 & FM/STEREO

21⁹⁵

Made in U.S.A.




- Gain 20 db VHF-FM — 10 db UHF — Uses Low Noise 2-Transistor Solid-State Circuit
- Use With Any Outdoor TV or FM Antenna — AC Isolation Transformer — No Shock Hazard

Enjoy vivid color and crisp black and white pictures; instantly improve your FM reception. 2-transistor solid-state mast-mounted preamplifier overcomes download losses and rejects interference, matching your roof antenna to your TV or FM set under all atmospheric and weather conditions. Gives 20 db boost to VHF and FM; 10 db to UHF. Designed for moderate to fringe area signals. Weatherproof outdoor housing mounts easily on an antenna boom or mast. Complete with 117 VAC indoor power-supply and hardware. Has single 300-ohm input and output thru "no-strip" screw terminals. Shpg. wt., 1½ lbs. 18 R 02149 Net 21.95

LAFAYETTE TRANSISTORIZED 4-SET VHF-TV/FM ANTENNA BOOSTER FOR CHANNEL 2-13 & FM/STEREO

14⁹⁵



- 300 ohm Input— 4 - 300 ohm Outputs
- Amplifies Signals for Up to 4 Sets
- Easy to Connect and Economical to Operate

If your antenna isn't pulling in signals of sufficient strength then this Lafayette Booster Amplifier is just what you need. Screw-on terminals make wire connections easy, no cutting is necessary. Transistor circuit runs cool, draws little current. Signal strength is boosted 3 to 5 times. Will operate up to 4 TV and/or FM sets on the same antenna. Input impedance is matched to antenna impedance. Needs no adjustment. Isolated outputs insure maximum set separation. Can be mounted in any convenient location where adequate ventilation is provided. Size 4¾Wx1¼Hx3¼D. For 117 volts, 60 Hz AC. Imported. Shpg. wt., 1 lb. 99 R 40115 Net 14.95

LAFAYETTE TRANSISTORIZED 4-SET VHF-UHF-FM ANTENNA BOOSTER FOR CHANNEL 2 — 83 & FM/STEREO

27⁹⁵



- 300 ohm Input— 4 - 300 ohm Outputs
- Ideal For Home TV/FM Entertainment Systems
- Perfect For Color And Black and White

Highly efficient 3 transistor Indoor amplifier boosts and distributes VHF/UHF/FM signals to as many as four TV and/or FM receivers. Three Noverload® silicon overlay transistor circuitry provides 6 db VHF gain and 6.5 db UHF gain at each of four 300-ohm outputs. Flat response across each channel for excellent color. 15 db gain isolation between outputs. High Input signal capability boosts weak signals but will not overload from other strong signals in area. Pilot light. Amplifier and power supply are combined into one perforated steel cabinet. Size: 2Hx4Dx6¼W. For 117 VAC, 60 Hz. Imported. Shpg. wt., 2 lbs. 18 R 02214 Net 27.95

JFD MAST MOUNTED VHF-UHF-FM COLOR AMPLIFIER

44⁰⁷



Model SP-2382CD VHF/UHF/FM Mast Mounted 3 Transistor Amplifier. 12 db gain on VHF and FM, 14 db gain on UHF. Clears up ghosts, snow and interference. For color, black and white and FM reception. 300 ohm input and outputs. Weather and lightning protected amplifier unit mounts on mast for high signal to noise ratio. Compact power supply. Needs only one download from VHF/UHF/FM antenna. For 110-120 VAC, 60 Hz. Shpg. wt., 2¼ lbs. 18 R 39158 No Money Down* Net 44.07
Model SP-2300CD Similar to above except for VHF—Ch. 2-13 and FM only. Power supply has built-in coupler to operate two sets. Gain/VHF—One set, 14 db, 2 sets 8.5 db at each output. 18 R 39182 Net 35.65

JFD INDOOR VHF-UHF-FM COLOR AMPLIFIER

31⁹⁵




- Intensifies Color
- 4—300 ohm Outputs
- Clears Up "Ghosts" & "Snow"

Model PC-4382CD VHF/UHF/FM Director 3 Transistor Amplifier. Improves performance of any VHF/UHF/FM combination antenna using one download. Broadband design. 300 ohm input splits to four 300 ohm outputs with 6.5 db gain per output. Network completely isolates each output and prevents interaction. Ultralow noise silicon "Noverload" transistor circuitry. Improves color reception. Easily mounts in any position on any surface. For 110-120 VAC, 60 Hz. Size: 5x3½x1¾". Shpg. wt., 2 lbs. 18 R 39166 Net 31.95
Model PC-4312CD Similar to above except for VHF—Ch. 2-13 and FM, 8 db gain per output. 18 R 39174 Net 22.50

BLONDER-TONGUE TV and FM Boosters

4-SET VHF-FM TRANSISTOR AMPLIFIER-COUPLER



Only **19¹⁵**

- For Color and Black and White
- For Up To 4-TV Or FM Sets

Model DA-4V-300 indoor 300-ohm amplifier for channels 2-13 plus FM. All solid-state transistor amplifier can supply up to 4 sets. Gain: At each of 4 outputs—VHF (ch. 2-13) 6.2 db. Maximum signal-to-noise ratio for clear pictures. Excellent isolation between outputs prevents interaction between sets. Use in home and small 300-ohm systems. Stripless screw terminals. Self-contained power supply. 8 $\frac{1}{4}$ x3 $\frac{1}{2}$ x1 $\frac{1}{8}$ " 110-120VAC, 60 Hz. 18 R 18335 Shpg. wt., 1 $\frac{1}{4}$ lbs. Net 19.15

4 SET VHF-FM 75-OHM AMPLIFIER-COUPLER

Model DA-4V-75—Similar to above except with 75-ohm input and 4-75 ohm outputs. Average gain to each output 5 db. Shpg. wt., 1 $\frac{1}{2}$ lbs.

18 R 18434 Net 23.40

4-SET VHF/UHF/FM AMPLIFIER

Model DA-4UV-300. Similar to above except for channels 2-83 plus FM. 3-transistor silicon circuitry. Gain: At each of 4 outputs—VHF (ch. 2-13) 5 db; UHF (ch. 14-83) 7db. 110-120 VAC, 60 Hz. 18 R 18343 No Money Down* Shpg. wt., 11 oz. Net 31.15

MAST-MOUNTING VHF-UHF-FM AMPLIFIER

35²⁵

No Money Down*

- 4 Silicon Transistors
- For Color and Black and White
- Built-In FM Filter



Mast Mounted Unit



Indoor Power Supply 18 R 18095 Shpg. wt., 2 lbs. Net 35.25

MAST-MOUNTING 2-TRANSISTOR VHF/FM AMPLIFIER

Horizon solid-state, mast-mounted home TV amplifier with remote power supply. 2-transistor circuit brings in distant and local stations with sparkling clarity and no overloading. Built-in 2 set coupler. Gain: At each of 2 outputs—VHF (ch. 2-6) 9.5 db; (ch. 7-13) 11 db. Hardware provided. 117VAC. Size: 2 $\frac{1}{2}$ x3 $\frac{1}{2}$ x3 $\frac{3}{8}$ ". Power supply, 4 $\frac{7}{8}$ x3 $\frac{1}{2}$ x3 $\frac{3}{8}$ ". Similar appearance to above.

18 R 18103 Shpg. wt., 1 $\frac{1}{2}$ lbs. Net 26.35


AMECO NUVISTOR FM PREAMPLIFIER

34⁹⁵



Nuvistor Cascade FM Preamplifier is the ideal solution for weak, fading, and noisy FM reception. Extremely easy to install and operate; just connect between your existing FM antenna and tuner or receiver with 300 ohm twin-lead wire. Contains its own power supply and ON/OFF indicator light and may be placed anywhere near the FM tuner. Once desired station is tuned on FM tuner, the control is also tuned to that station for optimum reception. Greatly helps to eliminate fading and background noise especially inherent in weak FM multiplex signals. Features two 6D54 nuvistors in cascade circuit. Size 5 $\frac{3}{4}$ x4 x 3 $\frac{1}{2}$ x 3 $\frac{3}{8}$ ". Power requirements 120 VAC, 60 Hz. Shpg. wt., 2 $\frac{1}{2}$ lbs. 21 R 20012 Net 34.55

4-Set VHF/UHF/FM AMPLIFIER/COUPLER



As Low As **14⁹⁵**

- 4-300 Ohm Outputs
- For Channels 2-83 Plus FM

Homer 300 U/V Indoor, solid state, 4-output, 300-ohm VHF/UHF/FM indoor powered amplifier/coupler for VHF/UHF channels 2-83 plus FM. Low noise transistorized circuitry. Excellent isolation between outputs prevents interaction between sets. 300-ohm balanced input/output impedance. Gain: At each of 4 outputs—VHF (ch. 2-6) 7.5 db. (ch. 7-13) 6.5 db; UHF (ch. 14-83) 1.0 db. All terminals with stripless screws. Size: 3 $\frac{1}{4}$ x4x1 $\frac{1}{8}$ ". For 110-120VAC, 60 Hz. 18 R 18392 Shpg. wt., $\frac{3}{4}$ lb. Net 14.95

MAST-MOUNTED HIGH GAIN VHF-FM AMPLIFIER



Mast Mounted Unit **44⁹⁵**

No Money Down*

- 30db Minimum on VHF/FM
- Solid-State
- For Deep-Fringe

Indoor Power Supply



Model AB-30

Deluxe two-piece mast mounted amplifier for use in the most difficult reception areas. One of the most powerful units available for the home. May be used in small hotels, appliance stores, etc. Will drive up to 50 sets in a properly designed distribution system. May be used as a preamplifier for an HAB or other distribution amplifier. Power is duplexed onto lead connecting amplifier and its remote power supply. (Power supply is included with unit). Mast mounted amplifier has 300 ohm input and 75 ohm output. Specs.: 30 db gain on all VHF and FM frequencies. Remote Amplifier/Power supply mounts anywhere—indoors. Single 75-ohm input and output. Supplied with coaxial connectors. Size: Mast Mounted Unit—5 $\frac{1}{4}$ x3 $\frac{3}{4}$ x3 $\frac{3}{8}$ "; Indoor Amplifier/Power Supply—8 $\frac{1}{4}$ x3 $\frac{1}{2}$ x2 $\frac{1}{4}$ ". For 117 volts AC, 60 Hz.

18 R 18376 Shpg. wt., 2 $\frac{3}{4}$ lbs. Net 44.95

BLONDER-TONGUE PRISM-MATIC AUTOMATIC ANTENNA ROTATOR



35⁹⁵

No Money Down*

- Solid State Control Box
- Will Handle Largest Color TV Antenna
- Heavy Duty Thrust Bearings

Control Box

Model PM-1. Just set the dial and the Prism-Matic automatically aims your antenna to the direction indicated. Complete solid state control unit assures precise synchronization throughout the full 360° rotation. High-power DC motor allows low current to pass thru the leads. Has automatic shut-off, positive braking and illuminated dial. Off-center loading ensures non-breakage, at 1300 ft.-lbs. Accepts masts up to 1 $\frac{1}{2}$ " diameter. In addition, unit is short circuit proof, burn-out proof and lightning protected. Operates at temperature extremes from -30°F to +140°F and 100% humidity. Factory lubricated for life. Supplied with corrosion resistant mounting hardware. Control unit is hi-impact beige and brown polystyrene cabinet with brushed compass face. 2 $\frac{7}{8}$ x5 $\frac{1}{4}$ x 7". 105-130 VAC. Uses 4 conductor cables. Shpg. wt., 7 $\frac{1}{2}$ lbs.

18 R 18418W Net 35.95

For cable listing see page 297.



Rotator

*See Page 22 for Full Credit Details on Easy Pay Plan.



Alliance Tenna-Rotor® Systems



Rotator For Control Units

35⁹⁷

No Money Down*



28⁷⁸

24⁰³



19³⁷



2⁹⁷

- Factory Lubricated for Life
- Reinforced Housing Weather Protected
- External Hardware of Corrosion Resistant Materials
- Full 360° Rotation

- Will Handle the Largest Color TV Antenna In Winds In Excess of 90 M.P.H. Rotation Speed 1 R.P.M.
- Magnetic Brake for Instant Stops with No Drift

A Model C-225 Automatic Rotor System with Transistorized Control Box. Enables you to receive the brightest, clearest picture possible and eliminate interference with pin-point accuracy. You can bring in more stations and in addition, you have the sensitive tuning required for Color TV viewing, CB, & Amateur Radio. Accepts masts to 1 3/4" O.D. Guy wire accesses provide secure installation. Has patented offset feed thru design for greater strength-to-weight ratio. Control Case is solid-state, featuring a patented phase-sensing bridge circuit from scientific laboratory test equipment. Completely silent operation and accurate repeatability. Size: Rotator: 7 3/4 x 4 1/2 x 8", Control Case: 6 1/2 x 4 1/4 x 5". 115V. 60Hz AC, 80 Watts. Uses 5 Cond. Cable. Shpg. wt., 9 1/2 lbs.

18 R 14011W

Net 35.97

B Model U-100 Automatic Rotor System. Accepts masts to 1 3/4" O.D. Guy wire accesses provide secure installation. Control Box fully automatic, just set control knob and antenna rotates to desired position and stops automatically. Indicator shows position of antenna. Has positive mechanical stop at the end of rotation. Sizes: Rotator 7 3/4 x 4 1/2 x 8", Control Case 7 x 4 1/2 x 4". 115 V, 60 Hz AC at 65 Watts. Uses 4 Cond. Cable. Shpg. wt., 9 1/2 lbs.

18 R 14037W

Net 28.78

C Model T-45 Manual Rotor System. Slight pressure on the control bar rotates antenna through its full 360° cycle and stops at any point by releasing the bar. New patented 5-wire circuit provides a precision system that is unaffected by motor current, cable length and line voltage variations. Improved electrical system with expanded meter scale, assures pin-point accuracy and easy-to-read antenna direction indication. 115 V, 60 Hz at 70 Watts. Size: Rotator 7 3/4 x 4 1/2 x 8". Control Case 6 1/2 x 4 1/2 x 2 1/2". Uses 5 Cond. Cable.

18 R 14029W Shpg. wt., 10 lbs.

Net 24.03

D Model K-22 Manual Rotor System. Economy model—provides instant fingertip control of rotation. Push on end of bar and antenna turns clockwise. Push down on other end and antenna turns counter-clockwise. Automatic signal light indicates when limit of travel in either direction has been reached. Size: Rotator 7 3/4 x 4 1/2 x 8". Case 5 x 5 x 4". 115 V, 60 Hz. AC at 50 watts. Uses 4 Cond. Cable.

18 R 14045W Shpg. wt., 8 3/4 lbs.

Net 19.37

E Thrust Bearing Bracket, Recommended for stacking antennas. Withstands winds up to 90 M.P.H. Prevents buckling and bending. Shpg. wt., 2 lbs.

18 R 14052

Net 2.97

CORNELL DUBILIER ROTORS

AR-22R AUTOMATIC ROTOR SYSTEM (units 1 & 2)

Heavy duty rotor will handle antennas up to 150 lbs. Developed from years of experience in the amateur radio field. Completely weather-proof and life lubricated. Simple automatic operation. Set the edge-lit dial at the desired position and the rotor will automatically rotate to this position and firmly brake in place. Reversible clamps will accommodate masts from 3/8" to 2" O.D. Control unit is marked in compass points. Housed in attractive Black Vinyl steel clad cabinet, dial edge illuminated. Complete with rotor, control unit and instructions. Uses 4 wire cable. For 110/120 volt, 50-60 Hz. A.C. Wt., 15 lbs. 42 R 86076W No Money Down*

Net 36.95

AR-33 SOLID STATE AUTOROTOR™ (units 1 & 3)

- Fully Automatic Pushbutton Antenna Rotor For 5 Specific Stations

Advanced design, heavy-duty antenna rotor. Control unit; features an exclusive CDE patented circuit with five station pushbutton automatic control function, plus 360° compass dial operation; pushbutton feature can be pre-set to select any five antenna positions automatically. Quiet operating solid state circuitry includes rugged silicon transistors protected by an RF bypass provision, heavy duty relay contacts, and thermally protected transformer. Unit controls the famous CDE heavy-duty "Bell" rotor. Uses five conductor cable. For 110/120V., 50/60 Hz AC. Shpg. wt., 16 lbs.

42 R 86100W No Money Down*

Net 49.95



As Low As

36⁹⁵

No Money Down*



CABLES FOR ALLIANCE AND CDE ROTATORS

4 Conductor flat cable. Shpg. wt., 2 1/4 lbs. per 100 ft.

32 R 89105 Per 100 ft.

Net 3.40

5 Conductor Cable. Shpg. wt., 2 3/4 lbs. per 100 ft.

32 R 36312 Per 100 ft.

Net 4.72

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 297

TV Couplers—Splitters—Filters

LAFAYETTE 2-SET VHF-UHF-FM COUPLER



- 149**
- Up To 2 TV or FM Sets From One Antenna
 - Low Signal Loss

Couples 2 TV or FM sets from a single TV/FM Antenna. Low insertion loss and high isolation between sets. Ideal for color or black and white installations. Easy to install, no-strip 300-ohm input and output terminals and mounting hardware. When used with 82 channel (VHF-UHF) TV sets. 99-40339 signal splitter required (see this page). Imported. Shpg. wt., 5 oz.

Net 1.49
99 R 40333

LAFAYETTE 4-SET VHF-UHF-FM COUPLER



- 199**
- Up To 4 TV or FM Sets From One Antenna
 - Low Signal Loss

Couples up to 4 TV or FM sets from a single TV/FM antenna. Excellent design gives high isolation between sets and low insertion loss. For color and black & white. Easy to install, no-strip 300-ohm input and output terminals, and mounting hardware, when used with 82 channel (VHF-UHF) TV sets. 99-40339 signal splitter required (see this page). Imported. Shpg. wt., 5 oz.

99 R 40321

Net 1.99

BLONDER-TONGUE 2-SET UHF-VHF-FM COUPLER



- Excellent Isolation
- No Strip Terminals

Model A-102U/V. Couples 2 TV or FM sets from one TV/FM Antenna. Low loss design and excellent isolation between sets prevents interaction. No strip terminals for use with 300-ohm line. When used with 82-channel TV set, with separate VHF-UHF antenna input terminals. Behind set signal splitter required (see 99-40339 this page). Sturdy, non-breakable case. Shpg. wt., 5 oz.

10 R 18327

Net 2.19

LAFAYETTE INDOOR VHF-UHF SIGNAL SPLITTER



- Separate VHF And UHF Signal From A 82 Channel Single Line Installation

Back of set, VHF-UHF signal splitter. Adapts a single all-channel 300-ohm twinlead to a 82 channel TV set with separate VHF and UHF 300-ohm input terminals. Low insertion loss and high isolation between VHF and UHF bands insures sharp pictures on color and black & white. No-strip input terminals—includes pre-attached VHF-UHF leads. Imported. Shpg. wt., 3 oz.

99 R 40339

Net 1.49

LAFAYETTE LO-PASS LINE FILTER



- 329**
- Dual Ferrite Core Coils

Exceptionally efficient line noise eliminator. Utilizing dual ferrite core coils, heavily wound. Eliminates line noises caused by motors, industrial RF, neons, appliances, etc. Particularly useful on TV and FM sets, radios, tuners, record players. Automatic attenuation of unwanted disturbances. For 110-125 VAC, 60 Hz; 350 watts max. Imported. Shpg. wt., 1 lb.

99 R 40057

Net 3.29

LAFAYETTE TV FILTERIZER




- 349**
- Eliminates Most Television Interference

Easily adjusted to remove any antenna-fed interference causing picture distortion: FM, diathermy, SW, ignition, amateur/CB, adjacent channel, etc. Does not attenuate signal. Actually tunes out unwanted signal. Matches any antenna. Metal case finished in black enamel. Easily installed. Size 4x2 3/4 x 1 1/2". Imported. Shpg. wt., 1 lb.

99 R 40172

Net 3.49

LAFAYETTE HIGH PASS FILTER



239

A high pass filter for use at the antenna terminals of a TV set to block interfering signals from radio amateurs, police and taxicab transmitters, paging systems, X-ray machines, passing automobile ignition noise, etc. Attenuation more than 25 db at 47 MHz. Only .5 db insertion loss. Imported.

99 R 40214 Shpg. wt., 5 oz. Net 2.39

SUPEREX CLEAR PIX



139

- 27 MHz Citizens Band Interference Filter

Clear Pix by-passes most sources of TV interference before they have a chance to enter your receiver. Picture and sound enter stripped of common types of man-made interference. Designed for maximum interference elimination at 27 MHz (citizens band). Requires just a screwdriver to install.

18 R 51080 Shpg. wt., 3 oz. Net 1.39

JFD HIGH PASS FILTER



330

- For Outdoor—Indoor Use

Model HP50. Hi-pass wavetrap that eliminates ham, citizens' band, police, fire, marine interference. Low phase shift ideal for color TV indoor or outdoor mounting. No-strip terminals eliminate wire-stripping, splicing or cutting. Low insertion loss—300 ohm impedance. Shpg. wt., 4 oz.

18 R 38200 Net 3.30

FINCO FM BAND PASS FILTER



MODEL 3007. Eliminates interference from citizen band, amateur operators, electric motors, aircraft, fluorescent lamps and auto ignition. Provides up to 40 db attenuation of all interfering signals outside the FM band. Less than 1 db insertion loss in 88 to 108 MHz band. Recommended to be mounted at FM radio set for maximum effectiveness but may be mounted anywhere in line for less serious applications.

18 R 30165 Shpg. wt., 5 oz. Net 4.80

VIDAIRE COLOR GHOST ELIMINATOR



399

- Reduce Color Fringing

Get true color reception with this color ghost eliminator. Reduces or eliminates multiple images (ghosts) in a picture. Reduce the effects of intermitting caused by strong signals of radio and TV transmitters in nearby areas. L-pad attenuator keeps constant 300-ohm impedance. Adjustable for all channels.

18 R 80020 Shpg. wt., 5 oz. Net 3.99

VHF-UHF SEPARATOR AND GHOST ELIMINATOR



395

Separate UHF and VHF signals at set while it helps eliminate ghost and picture tear due to overloading in strong signal areas. Built-in attenuating control eliminates poor sync., multiple images, buzz, beats in picture, etc. Slide switch to VHF or UHF depending on channel selected. To help eliminate a VHF ghost, throw switch to UHF and vice versa. Connects to back of set. Shpg. wt., 5 oz.

18 R 12387 Net 3.95

THESE 2 FREE BOOKS

CAN GET YOU STARTED ON A HIGH- PAYING CAREER IN ELECTRONICS...The Science of the Seventies

Trained electronics technicians are needed in such fast-growing fields as radio and TV broadcasting, air transportation, crime prevention, pollution control, industrial systems engineering and manufacturing.

Cleveland Institute of Electronics — one of America's leading Electronics home study schools — can prepare you for high-paying opportunities in these growth industries. CIE AUTO-PROGRAMMED® Lessons help you *understand* electronics theories and principles by building your knowledge one piece at a time. You learn quickly and easily at home in your spare time . . . at your own pace. CIE training prepares you for a career . . . not just a better job. TURN THE PAGE FOR DETAILS!



MAIL THIS CARD TODAY FOR TWO FREE BOOKS



APPROVED UNDER THE G. I. BILL

All CIE courses are approved for full tuition refund under the new revised G.I. Bill. If you are a veteran or serviceman with more than 180 days of creditable service, check the box on the reply card for latest G.I. Bill Information.

MAIL CARD TODAY
NO STAMP REQUIRED

CIE Cleveland Institute of Electronics
1776 East 17th Street, Cleveland, Ohio 44114

Please send me 2 FREE books describing the opportunities in Electronics and how to prepare for them.

I am especially interested in: Electronics Technology

- | | |
|---|--|
| <input type="checkbox"/> Electronics Technology with Laboratory | <input type="checkbox"/> Broadcast Engineering |
| <input type="checkbox"/> First Class FCC License | <input type="checkbox"/> Electronic Communications |
| <input type="checkbox"/> Industrial Electronics | <input type="checkbox"/> Electronics Engineering |

Print Name _____

Address _____

City _____


State _____ Zip _____ Age _____

Veterans and Servicemen: Check here for G.I. Bill information.

Accredited Member National Home Study Council.

LF-01

CIE IS LIGHT YEARS AHEAD WITH THIS NEW ELECTRONICS LABORATORY COURSE



CIE STUDENTS MOVE UP FAST

"I worked in the engine room of a tugboat when I started my CIE training. Before finishing I landed a job as



broadcast engineer at KFDM-TV. Got two raises in the first year."— Richard Kihn, Anahuac, Texas.

"Only six months into my CIE training course, I got a 20% increase in pay and was promoted. Since then, I've completed the course, bought a



new home and a camper."— David Ferriera, San Diego, California.

TEAR OUT & MAIL POSTPAID CARD TODAY

FIRST CLASS
PERMIT NO. 8685
CLEVELAND, OHIO

BUSINESS REPLY MAIL

No Postage Stamp Necessary if mailed in the United States

POSTAGE WILL BE PAID BY

**Cleveland Institute
of Electronics**

**1776 East 17th Street
Cleveland, Ohio 44114**

SEND FOR TWO FREE BOOKS

CIE offers seven career courses including five which prepare you for a Government FCC License. CIE promises full refund of tuition if you fail to pass the FCC exam after completing a CIE licensing course. Don't delay. Send the postpaid reply card today or write: CIE, 1776 East 17th Street, Cleveland, O. 44114.

JFD

TV-FM SPLITTERS - COUPLERS - COMBINERS



(1)




(2)



(3)



(4)



(5)

Maximum Signal Transfer • Crisp, Rich Color—Sharp Black/White—True Fidelity FM • No-Strip Terminals

(2) 2-SET VHF/UHF/FM COUPLER
Model SC42 Couples 2 TV or FM sets from one TV or FM antenna. Low insertion loss and high inter-set isolation makes this unit ideal for use on COLOR or BLACK & WHITE installations. No-strip terminals provided for quick connections. 300-ohms input and output. Supplied with wood screws for indoor use and insta-mount adhesive. When used with 82-channel (VHF-UHF) TV set either Model SS-21 or SS-83 signal splitter required at your set.
18 R 38135 Shpg. wt., 5 oz. Net 2.40

(2) 3-SET VHF/UHF/TV COUPLER
Model SC-62 Similar to above except couples up to 3 TV or FM sets from one TV or FM antenna.
18 R 38143 Shpg. wt., 6 oz. Net 2.97

(2) 4-SET VHF/UHF/FM COUPLER
Model SC72 similar to above except couples up to 4 TV or FM sets from one TV or FM antenna. Shpg. wt., 6 oz.
18 R 38150 Net 3.30

(1 & 2) 2-ANTENNA COUPLER (VHF/UHF)
Model SC20 combines separate VHF and UHF antennas so that only one 300-ohm download is needed. High insulation for crisp clear color. No-strip terminals. Mast mounting hardware supplied.
18 R 38127 Shpg. wt., 5 oz. Net 2.85

(4) INDOOR VHF/UHF SIGNAL/SPLITTER
Model SS21 splits VHF/UHF signal from all-channel 300-ohm single download into separate VHF-UHF outputs. For feeding into 82-channel TV set with separate VHF-UHF antenna input terminals. High and low pass filter networks insure sharp, clear pictures. Color or black/white. No interaction because UHF and VHF lines are completely isolated from each other. No-Strip terminals. Includes wire lead. Mounts quickly with insta-mount adhesive.
18 R 39083 Shpg. wt., 3 oz. Net 2.40

(4) INDOOR VHF/UHF/FM SIGNAL SPLITTER
Model SS83 similar to above except splits VHF/UHF/FM signal into separate VHF/UHF and FM outputs. Shpg. wt., 5 oz.
18 R 39291 Net 2.97

(3) VHF/UHF SPLITTER 75-300 OHM MATCHING TRANSFORMER
Model MT-56 2-way 75 to 300-ohm matching transformer. Plus splits VHF/UHF signal from all-channel, single 75 ohm download into separate VHF/UHF outputs. For feeding into 82-channel TV set with separate VHF-UHF antenna input terminals. With coaxial cable fitting.
18 R 39133 Shpg. wt., 6 oz. Net 2.97

(5) VHF/UHF/FM SPLITTER 75-300 OHM MATCHING TRANSFORMER
Model MT-58 similar to Model MT-56 except splits VHF/UHF/FM signal into VHF/UHF and FM outputs. Shpg. wt., 4 oz.
18 R 39190 Net 4.17

2-WAY VHF/UHF/FM 75-OHM LINE SPLITTER
(3) Model SC72-75 splits one 75-ohm VHF/UHF/FM line into two 75-ohm outputs. Also combines two 75-ohm lines into one line. 3 mating plugs supplied.
18 R 39109 Shpg. wt., 5 oz. Net 6.50

4-WAY VHF/UHF/FM 75 OHM LINE SPLITTER
(3) Model SC72-75 splits one 75-ohm VHF/UHF/FM line into four 75-ohm lines. Excellent for use in home or master antenna TV system. May be combined with an (SC42-75) to provide any number of lines. 5 mating plugs supplied.
18 R 39117 Shpg. wt., 8 oz. Net 8.70

(1 & 2) TV/FM SPLITTER-COUPLED FM FILTER
Model SSTV/FM splits FM signal from TV/FM signal to FM set—and TV signal to TV set. Ideal for stereo—prevents interference. Can also be used as FM bandpass which will admit clean FM signals only through to the FM tuner. Can also combine TV and FM antennas into a single system. Eliminates all TV, amateur and citizens band signal pickup by antenna or transmission line. 300-ohm impedance. With hardware.
18 R 39125 Shpg. wt., 10 oz. Net 3.30

JFD VHF-UHF-FM COAXIAL CABLE MATCHING TRANSFORMER KIT

- 75-300 Ohm Impedance Match
- Includes Outdoor and Indoor Units
- Ideal for COLOR TV

Model MT-51 Complete kit of matching transformers for installing TV & FM antennas. For use with noise-free 75-ohm coax cable. Weather-proof outdoor transformer matches any 300-ohm antenna to 75-ohm coaxial cable. Indoor transformer at set matches the 75-ohm coax to the 300-ohm TV or FM set. Includes coaxial cable fittings. Shpg. wt., 1/2 lb.
18 R 38995 Net 4.20



LAFAYETTE INDOOR/OUTDOOR VHF-UHF-FM 75-300 MATCHING TRANSFORMER


- Rugged Weather-Proof Housing with Weather Boot
- Ideal for Color TV

82-channel VHF-UHF matching transformer efficiently matches 300-ohm antenna or TV set to 75-ohm coaxial cable. Weatherproof unit has leads which attach directly to either antenna terminals on set. With connector. Shpg. wt., 4 oz. Imported.
99 R 40347 Net 1.79



MATCHING TRANSFORMER KIT WITH VHF-UHF-FM SPLITTER

Model MT-59 similar to above except indoor unit has separate VHF/UHF and FM outputs. For feeding into 82-channel TV set with separate VHF-UHF antenna input terminals plus FM set. With fittings. Shpg. wt., 1/2 lb.
18 R 39141 Net 6.27



LAFAYETTE OUTDOOR VHF-FM 300-75 OHM MATCHING TRANSFORMER

- With Coaxial Fitting
- Ideal for Color

Coaxial cable matching transformer for installing VHF-TV and FM antennas. For use with noise-free 75-ohm coax cable. Matches 300-ohm antenna to 75-ohm coax. With mounting bracket and fitting. Imported.
99 R 40271 Shpg. wt., 6 oz. Net 1.49



BLONDER-TONGUE INDOOR VHF-UHF CABLEMATCH

- 75-Ohm Coax to 300-Ohm Impedance

Model 3413 cablematch VHF/UHF indoor matching transformer, especially suited for matching TV set inputs to a coax distribution system. Match 75-ohm coaxial cable to 300-ohm input. Connectors: Two spade lugs (300-ohms) and a solderless Type F plug supplied. For RG-59 type cable. Shpg. wt., 4 oz.
18 R 18384 Net 1.65



VIDAIRE SIGNAL ATTENUATOR

May be used with all TV sets troubled with excessive signal. Eliminates poor sync., multiple images, buzz, beats in picture, etc., when caused by signal overloading. Produces 100% to 1 change in signal reaching set. Reduces most cross-modulation effects. Adjustable for all signal areas. Simple to mount—simple to install. Shpg. wt., 4 oz.
18 R 80012 Net 3.50



COAXIAL SHIELDED CABLE KITS

High quality 75-ohm RG-59U low loss coaxial cable with connectors on both ends to fit all above matching Transformers. Shpg. wt., 3 1/2 lbs.
18 R 58075 50' with connectors Net 4.85
18 R 58083 75' with connectors Net 6.95
18 R 58091 100' with connectors Net 8.95




NOISE FILTER

- Stop Radio & TV Noises

Eliminate radio and TV noise caused by household appliances, oil burners, motors, neon signs, etc. Just plug filter in any wall outlet and TV or radio into filter and enjoy noise-free entertainment; or plug noise producing appliance into filter and eliminate noise throughout house. Shpg. wt., 4 oz.
18 R 19010 Net 1.19





South River
**HEAVY-DUTY
SUPER MOUNT**
850

Model CMA500SS super-heavy pair of chimney mounts made of cast aluminum alloy. Extra strong and durable. Will withstand the most severe weather conditions. Two 12 ft. stainless steel 3/4" straps and stainless steel seals. Six aluminum corner brackets to protect chimney bricks. The most ideal and permanent installation for those who want quality and durability. Will hold masts up to 2" O.D.

18 R 56012 Shpg. wt., 3 3/4 lbs. Net 8.50
Same as above with 18" straps.
18 R 56277 Net 9.50



South River
**GOLD VINYL
COATED 'Y' TYPE
CHIMNEY MOUNT**
650
• Snap-in Mast
Sockets

Model V-SN-ST. Heavy-duty steel riveted brackets with gold colored vinyl protective sheath that will not peel, chip, or crack. All remaining hardware and components of stainless steel for a completely rustproof installation. Eliminates rust streaks. Snap-in feature eliminates holding mast while applying hardware. Shpg. wt., 3 3/4 lbs.

18 R 56368 Net 6.50



**RATCHET TYPE
CHIMNEY MOUNT**
495

Fastens easily with an ordinary wrench. Two 12" heavy-duty stainless steel straps assembled at one end. Two heavy-gauge brackets per set with serrated U-bolts. Easily assembled. Rainbow gold color rustproof finish. Accepts masts up to 1 1/2" O.D. Shpg. wt., 3 3/4 lbs.

18 R 63315 Net 4.95




**'Z' TYPE CHIMNEY
MOUNT**
295

"Z-MOUNT" design provides simple installation and sturdy support. Heavy gauge steel construction with gold color rustproof finish. Takes up to 1 1/2" O.D. masts. With

2-10 ft. stainless steel 3/8" straps and seals.
18 R 01653 Shpg. wt., 2 1/4 lbs. Net 2.95
Heavy Duty 'Z' Mount. Similar to above with 2-12" 3/4" stainless steel straps. Shpg. wt., 2 1/2 lbs.

18 R 02222 Net 3.99

**STAINLESS STEEL STRAP
REPLACEMENT KIT**



Consists of 2-12 ft. 3/4" stainless steel straps, stainless steel seals, triangular eye-bolts, lockwashers, hexnuts. Puts an end to rust and corrosion. Shpg. wt., 1 1/2 lbs.

18 R 63091 Net ea 1.99

TV Antenna Mounts-Towers

HEAVY-DUTY 12" WALL MOUNT



- RIGID TRIPOD
LEG SUPPORT

329

Completely constructed of steel, using extra heavy gauge steel tubing which will not bind. Protected against corrosion by the ALCOATE finish. Special "sure grip" U-bolts. Holds mast up to 1 1/2" O.D. tripod leg for one section. (Set of 2.)

18 R 63059 Shpg. wt., 2 1/2 lbs. Net 3.29

ADJUSTABLE 18" WALL MOUNT

(Set of 2) Wt., 4 1/4 lbs. Net 6.50
18R63067

4" WALL BRACKETS



4" STAINLESS STEEL WALL BRACKET. All stainless steel construction for extremely long life. Provides 4" clearance from wall. With special shaped U-bolt to hold masts up to 1 1/2" O.D. (Set of 2.) Shpg. wt., 1 lb.

18 R 01968 Net 2.39

4" WALL BRACKET. Securely grips all masts from 1" to 1 1/2" O.D. Made of rust resistant steel. With hardware. (Set of 2.)
18 R 01661 Shpg. Wt. 1/4 lb. Net 1.09



**SNAP-IN VENT
PIPE MOUNT**

239

6" Snap in feature eliminates holding of mast while applying hardware. Single front locking carriage bolt for easy one hand tightening. Fits vent pipes up to 6". Heavy gauge mount resists corrosion. (Set of 2.)

18 R 63349 Shpg. wt., 1 lb. Net 2.39



**PEAK AND FLAT
ROOF MOUNT**

A heavy gauge steel roof mount. Heavily plated to resist corrosion. Will accommodate masts up to 1 1/2" diameter. Fully adjustable, can be easily rotated. Complete with all necessary hardware. Shpg. wt., 2 lbs.


18 R 63083 Net 1.99



ALL-ANGLE MOUNT
• Accepts 1/2" to 1 1/4" Masts

All-angle mount permits setting of 1/2" to 1 1/4" masts at most suitable angle for maximum reception. Rust-resistant steel. With mounting hardware. Ship. wt., 10 oz.

18 R 01992 Net .89



ANTENNA MOUNTS

**GOLD VINYL COATED 6"
SNAP-IN WALL BRACKETS**



- With
Stainless
Steel
Screws

295

Model V-SM-6 Gold, vinyl coated antenna mounts are ruggedly constructed of heavy-duty steel riveted steel. Vinyl coating prevents corrosion and eliminates rust streaks; will not peel, chip, or crack in bad weather or when exposed to direct sun. Brackets come two to a set. Stainless steel screws supplied. Shpg. wt., 3 lbs.

18 R 56350 Net 2.95

UNDER-EAVE MOUNT



- For Modern
Overhanging
Eaves

549

Model YE-1 Permits mounting antenna to the underside of over-hanging eave. Can also be used as a sturdy self-supporting flat roof mount. Heavy gauge steel and Hot-Dip galvanized for maximum corrosion resistance. One piece mounting of welded construction with a heavy gauge embossed steel diagonal support. Complete with installation hardware. Shpg. wt., 5 3/4 lbs.

18 R 56038 Net 5.49

**HEAVY-DUTY TRIPOD
ROOF TOWERS**



- No Guy Wires Needed
- One Man Installation
- Roof Sealing Patches
- Completely Adjustable to Roof Rafter

As Low As **695**

Heavy-duty, self-supporting tripod tower eliminates guying. Constructed of heavy (1 1/4" O.D.) components embossed for extra strength and rigidity. Designed for convenient mounting of all peak or flat rooftops. Exclusive adjustable slide permits mounting to randomly spaced roof rafters. Hot-dipped galvanized to provide utmost protection against corrosion or rust. Roof sealing watertight pitch patches supplied. Recommended for color TV installation where heavy multi-element antennas are used. Complete with pitch patches and hardware. Model HDT-3 For 6' tower. Use with 5" mast. Shpg. wt., 8 1/4 lbs.

18 R 56285W Net 6.95

Model HDT-5 for 12' tower. Use with 10" mast. Shpg. wt., 13 1/4 lbs.

18 R 56293W Net 10.95

UNIVERSAL ALL-POSITION MOUNT

A strong self-supporting mount which adjusts to any position on peak, slope, flat, corner, or sidewall of building. Positive locking braces eliminate need for guy wires in most installations. Two plane adjustment for true vertical alignment of mast. Made of heavy gauge hot dipped galvanized steel.

Model-APM Standard model for masts up to 1 1/2" O.D. Net 4.50
18 R 56319 Shpg. wt., 5 1/2 lbs.

Model-APM-LM Large model for masts up to 2 1/2" O.D. Net 5.50
18 R 56327 Shpg. wt., 5 1/2 lbs.

TV Antenna—Towers—Masts—Accessories

ROHN: SPAULDING "STRATO TOWERS" "EP SERIES" INSTALL ON GROUND OR ROOF



"XCB"
TOWERS

High quality beaded channel construction. All riveted, no welds to rust. Rugged, zinc plated steel. More strength—less wind resistance at tower top. Top sections accept any rotator. All sections factory assembled. Each tower consists of one or more 8' sections plus an 8' mast, base plate, house bracket and mast kit assembly. Free standing installations require guying every 16'. Roof mount, and guy stations are extra.

Stock No.	Type	Hgt.	Sect.	Weight	Net
18 R 73025XZ	EP-2	22'	2	51 lbs.	37.95
18 R 73033XZ	EP-3	30'	3	71 lbs.	46.95
18 R 73041XZ	EP-4	38'	4	90 lbs.	56.95
18 R 73059XZ	EP-5	46'	5	109 lbs.	66.95
18 R 73074XZ	EPR-1	Roof Mount Base		2 lbs.	4.95
18 R 73082XZ	GS-12	Guy Station		3½ lbs.	4.19

"XCB SERIES"—CYLINDER BASE

NO CONCRETE REQUIRED

Extreme high strength, self-supporting towers. Self-aligning hinge base for quick easy installation. Can be assembled on the ground and hinged up or built vertically, section upon section. All riveted 100% galvanized steel construction prevents rust. With 4 ft. base, hinged feet, 8' mast, mast kit 8' tower sections.

Stock No.	Type	Hgt.	Sect.	Weight	Net
18 R 73090XZ	X-16CB	23'	2	89 lbs.	57.95
18 R 73108XZ	X-24CB	31'	3	120 lbs.	69.95
18 R 73116XZ	X-32CB	39'	4	155 lbs.	89.95
18 R 73124XZ	X-40CB	47'	5	184 lbs.	114.95
18 R 73132XZ	X-48CB	55'	6	272 lbs.	139.95

*Height includes antenna mast. Shipped F.O.B. Frankfurt, Ind. No C.O.D. Send full remittance or use LAFAYETTE'S Easy Pay Plan. Shipping charges collected on delivery.



"EP"
TOWERS

ALUMINUM ANTENNA MASTS

- Gold Alodized



Gold alodized aluminum mast; rust and corrosion proof. Made of extra strong, drawn aluminum alloy. Two or more masts may be telescoped together. 19 Gauge. 1¼" O.D.
18 R 38176W 5', Wt., 1¼ lbs. Net 1.49
18 R 56145WX 10', Wt., 2 lbs. Net 2.79

HEAVY DUTY ALUMINUM MAST

Heavy-Duty 16 Gauge gold alodized aluminum mast, recommended for larger color antennas. Shpg. wt., 3 lbs.

18 R 39257WX 10 feet Net 3.49

SUPER HEAVY-DUTY ALUMINUM MAST

Made of high strength aluminum alloy. Recommended for use with rotors and large antenna installations. Length 10 ft. 1¼" O.D. Wall thickness full ¼". Shpg. wt., 5¼ lbs.

18 R 56202WX Net 6.95

18 R 56269WX 10', 1½" O.D. Net 7.95

GOLD KOTE STEEL MAST

- Gold Colored to Match Most Antennas

Corrosion resistant steel mast sections made to fit all antennas. Made of rigid steel tubing with rugged high tensile strength. Highly protective gold colored baked enamel finish for lasting beauty and endurance. "Jam Fit" construction. 1¼" O.D.

Stock No.	Hgt.	Gauge	Wt. Lbs.	Net
18 R 63257W	5'	20	2	1.19
18 R 63265WX	10'	20	4	1.99
18 R 63273W	5'	16	4	1.89
18 R 63281WX	10'	16	4	3.19

INSULATED NAILS

Single head wiring nails excellent for fastening 300 Ohm twin lead antenna wire to woodwork, baseboard, etc. Does not affect signal.
#14x¾" brown. Shpg. wt., .09
#18 R 02032 Box of 50 Net .89



STEEL GUY WIRE

Six strands of No. 20 high tensile strength galvanized steel wire.

33 R 31014	50 ft. roll. Wt., 1 lb.	.55
33 R 31022	100 ft. roll. Wt., 2 lbs.	.95
33 R 31030	500 ft. roll. Wt., 10¼ lbs.	4.59

VINYL COVERED GUY WIRE

6 strands of No. 20-gauge high tensile strength galvanized wire. Weatherproof, non-stretch, long lasting. Ideal for TV guy wire, clothesline, and numerous garden uses. Translucent aqua green color.

32 R 36494	50 ft. roll. Wt., 1½ lbs.	1.05
32 R 36502	100 ft. roll. Wt., 3 lbs.	2.00
32 R 36510	250 ft. roll. Wt., 7½ lbs.	4.89

ALUMINUM GUY WIRE

7-18 gauge stranded wires. Breaking strength 500 lbs.

34 R 46275	100 ft. roll. Wt., 2 lbs.	2.65
------------	---------------------------	------

ALUMINUM GROUND WIRE

33 R 31048	50 ft. coil. Wt., 1½ lbs.	1.00
33 R 31055	100 ft. coil. Wt., 2¼ lbs.	1.93
33 R 31063	500 ft. coil. Wt., 13 lbs.	9.15

STEEL A TURNBUCKLES



(A) Takes up guy-wire slack. Rustproof galvanized steel. Size 7¾" open, 5½" closed. Shpg. wt., 5 oz.

18 R 72175 29

(B) Hook and eye type used where quick removal is required. Shpg. wt., 5 oz.
18 R 72183 29

DOUBLE HEAD INSULATED NAILS

Same as nails on left, but with double head. Recommended for all tubular and shielded 300 Ohm twin lead. #3x¾" brown. Shpg. wt., 5 oz.
18 R 02040 Box of 50 Net .89



TELESCOPING TV MASTS

Heavy duty telescoping masts. Ideal for any TV antenna array. Hotdip zinc galvanizing inside and outside provides unusual ruggedness and impervious corrosion resistance. Designed for easy installation and assembly. Husky bolts lock sections automatically. No slipping, no twisting. Precision fitting assures lasting service. 18 and 20 gauge walls. Supplied complete with all guy rings, clamps and necessary hardware. Total 5 10-ft. sections for height up to 50 ft.: O.D. #1 (1¼"). #2 (1½"). #3 (1¾"). #4 (2"). #5 (2¼"). Shipped express only.

50-FT. MAST—Consists of all 5 sections listed above: Nos. 1, 2, 3, 4 and 5. Height 50 feet. Shpg. wt., 35½ lbs.
18 R 56095WX Net 19.95

40-FT. MAST—Consists of 4 sections, Nos. 1, 2, 3 and 4. Height 40 feet. Shpg. wt., 26½ lbs.
18 R 56103WX Net 15.95

30-FT. MAST—Consists of 3 sections, Nos. 1, 2 and 3. Height 30 feet. Shpg. wt., 18½ lbs.
18 R 56111WX Net 11.95

20-FT. MAST—Consists of 2 sections, Nos. 1 and 2. Height 20 feet. Shpg. wt., 13 lbs.
18 R 56129WX Net 7.95

HEAVY DUTY PEAK AND FLAT ROOF MOUNT

Swivel base mounts on any surface—flat, slant, peak or wall. Heavy gauge weather-proofed steel. Takes any mast up to 2¼" O.D. Complete with hardware. Wt., 3 lbs.

18 R 56186 Net 1.95

Exact Roof

HEAVY DUTY 5' WALL BRACKET MOUNT

Model GU-5. Made of heavy steel bar stock. Fits large masts up to 3¾" O.D. Mast holder swivels 360° permitting bracket to be mounted in any position. Ideal for heavy ground-up mast installations. Shpg. wt., 1½ lbs.
18 R 56376 Net 2.49

¾" PLATED GROUND ROD




For use where pipe ground is not available. Heavy steel yoke for head, 4 ft.
18 R 72159W Shpg. wt., 1½ lbs. 1.09

TV SERVICE LITE

Keep your hands free. Spring clamp with rubber covered ends attaches anywhere in TV cabinet. 4¼" highly polished aluminum reflector uses standard 25 watt bulb. Complete with 5 ft. cord and plug, less bulb.
18 R 17014 Shpg. wt., ¾ lbs. Net 2.19



TV Installation Accessories



(1) "GRIP" GROUND CLAMP. Makes vise-like grip on pipe. Sharp pointed screw makes perfect contact. Shpg. wt., 3 oz.
18 R 82018 Net .29

(2) GUY WIRE RING & COLLAR. Economy free-floating guy ring and support collar. Mast can be rotated freely after guying to orient antenna. Fits masts up to 1 1/4" O.D.
18 R 63356 Net .79

(3) DELUXE GUY WIRE RING & COLLAR. Cast aluminum floating guy wire ring and collar permits complete orientation of the mast. Will fit masts up to 1 3/8". Shpg. wt., 7 oz.
18 R 81051 Net 1.99
 Same as above but will take masts up to 1 3/4".
18 R 56079 Net 2.09

(4) LAG SCREWS & EXPANSION SHIELDS. Lead expansion shield for easy fastening to masonry, brick, stone, etc. Lag bolt 1/4" dia. Shank by 1 1/2" long. Pkg. of 4 bolts and shields. Shpg. wt., 4 oz.
18 R 63346 Net .89

(5) MAST GUY CLAMP. Has 6 guying points. A handy thing to keep in the tool kit. Will accommodate masts up to one and one-half inches in dia. Shpg. wt., 9 oz.
18 R 63216 Net .39

(6) 3-WAY GUY WIRE CLAMP. Fits masts up to 2 1/4" diameter. Features 3 eye bolts for guy wire attachment. Made of heavy gauge steel. Shpg. wt., 10 oz.
18 R 63208 Net .59

(7) BALL-TYPE GUY WIRE TIGHTENER. Simply draw guy wire through the "grip-lite"; loop wire back, and twist once. Provides easy method for adjusting and tightening guy wire. Cast zinc housing. Shpg. wt., 6 oz.
18 R 01935 Net 1.09

(8) CLOSED EYE BOLT. For anchoring guy wires. Size: 1/4 x 5". Shpr. wt., 5 oz.
18 R 63224 Net .12

(9) CABLE CLAMP. Strong aluminum alloy body construction with plated steel U-bolt. Fits cables up to 3/8" dia. Provides solderless and spliceless cable-loop termination. Shpg. wt., 3 oz. pkg. of 2.
18 R 67126 Net per pkg. .45


(10) MAST CLAMP. Notched retaining clamp holds 2 masts firmly in sturdy U-bolts. Galvanized steel. Wt., 5 oz.
18 R 01950 Net .39

(11) U BOLTS. Made of galvanized steel. Supplied with nuts and washers in place. Shpg. wt., 5 oz.
18 R 02024 2 pieces per pkg. Pkg. .35

(12) QUICK CLIP. For speedy, simple attachment of antenna lead-in to TV set. Can't short out. Shpg. wt., 4 oz.
18 R 02057 Pkg. of 2 Ea. .45

(13) GUY WIRE HOOK EYE. Strong and permanent anchoring. Made of galvanized steel. Av. shpg. wt., 6 oz.
18 R 02016 5 pieces per pkg. Pkg. .49

UNIVERSAL STANDOFF INSULATORS



Latest polyethylene insert will accommodate twin-lead, open line, hollow and tubular lines, round lines, oval lines double lines, etc.

(1) SCREW-EYE STANDOFF. First choice for fast secure anchoring. Shpg. wt., 7 oz.
 3 1/2" 4 pieces per pkg. PKG. .29
18 R 01679
 5" 4 pieces per pkg. PKG. .39
18 R 01687
 7 1/2" 4 pieces per pkg. PKG. .49
18 R 01695
18 R 01703 4 pieces per pkg. PKG. .69

(2) DRIVE-IN STANDOFF. Made of galvanized steel. Av. shpg. wt., 4 oz.
18 R 01711 2 pieces per pkg. PKG. .29

(3) ADJUSTABLE STRAP-TYPE STANDOFF. Fits any size mast. Av. shpg. wt., 6 oz.
18 R 01729 7 1/2" 2 pieces per pkg. PKG. .49
18 R 01737 3 1/2" 2 pieces per pkg. PKG. .39

(4) "CLIP-ON" STANDOFF. Attach to mast instantly—"Click" and they're on 3 1/2" long. Av. shpg. wt., 4 oz. For 1 1/4" mast.
18 R 01745 2 pieces per pkg. PKG. .35

(5) SUPER NAIL INSULATOR. Takes flat twin-lead or coaxial cables. Easily drives in brick, mortar, wood and even most concrete. Secure connection. 3 3/8" long. Shpr. wt., 4 oz.
18 R 01752 2 pieces per pkg. PKG. .35

(6) COLOR VHF/UHF SCREW-EYE STANDOFF. For all UHF/VHF lines. 3 pcs. per pkg. 5 1/2" long. Shpg. wt., 5 oz.
18 R 01760 PKG. .59

(7) OPEN LINE STANDOFF. Designed especially for use with open line transmission wire installations. Ideal for use as anchor point, spacer, etc. Polystyrene block and galvanized steel hardware. 5 1/2" nail type. Shpg. wt., 8 oz.
18 R 58067 5 pieces per pkg. PKG. .89

(8) STAND-OFF SUPPORT. Break resistant plastic-adhesive base. Attaches firmly to aluminum, brick, concrete—all surfaces. Use with any machine or wood screw-eye.
18 R 37012 Shpg. wt., 2 oz. Net ea. .22

(9) COLOR INSULATORS. Converts most existing standoffs for color. Pkg. of 6. Wt., 4 oz.
18 R 01778 PKG. .29


South River LIGHTNING PROTECTION KIT



• Complete!
 Nothing Else To Buy
395

Model GND-ANT. Do-it-yourself kit to minimize lightning strikes to your antenna. Directs and discharges excess to ground. Kit contains: 50 ft. heavy-duty electrical-conductor type, aluminum ground wire, coppered-steel ground rod and clamp. U.L. listed lightning arrester, 6 ground wire nail fasteners, ground wire warning tag and complete detailed instruction sheet.
18 R 56194 Shpg. wt., 2 3/4 lbs. Net 3.95

JFD LIGHTNING ARRESTERS



• Protects Home and Antenna Installation Against Damage From Lightning and Static Discharge

• With Stainless Steel Strap and Hardware For Mounting Indoors or Outdoors, UL Listed

(A) ECONOMY VHF/UHF ARRESTER
 Model AT131S. Designed for flat, tubular, oval twin lead or open transmission lines. Saw tooth washers grip line securely without stripping or cutting of wire. Low loss material construction reduces capacity and inductance, results in maximum TV signal transfer to set. Complete with strap and hardware listed at top.
18 R 38010 Shpg. wt., 6 oz. Net .99

(B) LITTLE GIANT VHF/UHF ARRESTER
 Model AT105S. Fits any flat, tubular, or oval twin lead or open transmission line. Saw tooth washers make positive contact with line—no wire stripping or cutting necessary. High dielectric construction maintains excellent signal transmission to set. Complete with strap and hardware listed at top.
18 R 39307 Shpg. wt., 9 oz. Net 1.89

(C) DELUXE VHF/UHF ARRESTER
 Model AT110S. Takes any flat, tubular, or oval twin lead or open transmission line. Saw tooth washers make positive contact with line—eliminating need for wire cutting or stripping. Low loss high dielectric construction maintains high signal transfer. Complete with strap and hardware listed at top.
18 R 38051 Shpg. wt., 5 oz. Net 2.49


(D) 4-WIRE ROTATOR ARRESTER
 Model AT104S. For 4-wire rotator lead-ins. No wire stripping or cutting. Simply tighten cover that makes automatic and positive contact with lines. Shpg. wt., 1/2 lb.
18 R 38069 Net 2.39

(E) 5-WIRE ROTATOR ARRESTER
 Model AT106S. Protects 5-wire automatic rotator antenna installations. No wire cutting or stripping necessary. Just place wire in slot and tighten cover over it for quick, sure electrical contact. Complete with strap and hardware listed at top.
18 R 38911 Shpg. wt., 1/2 lb. Net 3.29

TV-FM Installation Accessories

UNIVERSAL TV-FM PLUG & SOCKET

39^c



Compact low loss—300 ohm plug and socket. Surface mounting socket—low loss polystyrene plug. Solderless screw terminals. Imported. Shpg. wt., 3 oz.
99 R 40065 Plug & Socket
Lots of 3



Net .39
Net ea. .33

SURFACE OUTLET AND PLUG



- Complete With Solderless Plug

Surface mounting outlet and plug for TV-FM and loudspeakers. A neat baseboard mounted outlet with plug. Fits 300-ohm twin lead or speaker wire. Nickel plated brass hardware with set screw connectors. Unbreakable ivory plastic, with mounting screws. Shpg. wt., 3 oz.
18 R 57259

Net .79

SOLDERLESS TWIN-LEAD CONNECTORS



Plug fits transmission line socket below. Shpg. wt., 2 oz.
99 R 40073

Net ea. .29

Solderless socket for above. Shpg. wt., 2 oz.
99 R 40081

Net ea. .29

MOSLEY SHIELDED TWIN-LEAD SPLICER

- Permits Splicing of Shielded 300-Ohm Twin-Lead



No need for twisting or soldering.
18 R 42061 Shpg. wt., 3 oz. Net .99

TWIN LEAD SPLICE

Speeds splicing without need for twisting or soldering. Shpg. wt., 2 oz.
18 R 70096

Net .20

TV LINE CORD



6 ft., brown replacement cord. It has regular molded plug on one end and special rubber plug on the other to fit TV sets. UL listed. Shpg. wt., 4 oz.
18 R 41014
Net .39
Same as above but with polarized terminals at both ends.
18 R 74015 Shpg. wt., 3 oz. Net .49


INTERLOCK TV LINE SOCKET



Conventional male interlock socket. Standard type used on all television receivers. Heavily plated contact pins. 1 1/4" mounting centers. Shpg. wt., 3 oz.
18 R 27187

Net .19

AC-TV RECEPTACLE AND WALL PLATE



Duplex AC receptacle and duplex TV receptacle on one 2 gang wall plate. Puts both outlets in one location. Use with standard wall box. Ivory only. Shpg. wt., 6 ozs.
18 R 70062

Net 1.69

Molded 2 contact plug for 300 ohm lead.
18 R 70138

Net .22

4 wire rotor combination plates. Similar to above except includes 4 conductor rotor outlet in place of one 2-wire outlet.
18 R 70039 Shpg. wt., 6 oz. Net 1.95

Molded 4 contact plug for rotor lead.
18 R 70054

Net .42

5 wire rotor combination plate. Similar to above except includes 5 conductor rotor outlet in place of one 2-wire outlet.
18 R 70161 Shpg. wt., 6 oz. Net 2.09

18 R 70179

Net .59

MOSLEY WALL-PLATE FOR HEAVY-DUTY TWIN LEAD

- Complete With Plug, Wall Bracket, Hardware
- Excellent For All 300-Ohm Shielded Cable and Tubular Cable



For TV installation where heavy-duty twin-lead cable is used—shielded or unshielded. Low loss socket with solderless plug for easy installation, may be mounted with wall mounting bracket or in standard outlet box. With polarized plug and wall mounting bracket. Shpg. wt., 6 oz.
18 R 42020

Net 1.69

MOSLEY TV-FM COAXIAL WALL PLATES

• For 75 Ohm Antenna Installation
Ivory coaxial outlets, flush mounting especially designed for superior color and black/white reception, provides a constant impedance match with 72 ohm RG 59U coaxial cable. Complete with all connector, plug, mounting brackets. Fit all standard wall outlet boxes. Shpg. wt., 7 oz.

Stock No.	Description	Net
18 R 42087	1 TV-FM Coax Outlet	2.69
18 R 42095	1 TV-FM Coax Outlet With 4- or 5-wire rotor	3.69

MOSLEY UNIVERSAL ROOF-THRU/WALL THRU



Weatherproof entrance accessory for all types of antenna and rotor lead-in line. Mounts on any sloped roof or on the wall of any non-brick structure with hardware included. Insect-proof housing molded of black cyclac for break-resistant strength. Easy to install with built on flange and rubber gasket. No roof cement needed. Shpg. wt., 5 oz.
18 R 42079


Net 1.19

UNIVERSAL BUSHING



Fits all types of coaxial or twin-lead wires. Fits walls up to 1 1/2" thick. Requires 3/4" hole. Shpg. wt., 4 oz.
18 R 72019

Net ea. 1.19



LAFAYETTE TV/FM WALL PLATES

- Fits Standard Outlet Box
- Complete with Plugs and Mounting Bracket

SINGLE TV/FM WALL PLATE

(1) Single TV/FM wall plate which can be used to neatly custom install an antenna system. Plug is polarized and designed to accept a 300-ohm twin lead line. Ivory finish.
99 R 40131 Shpg. wt., 4 oz. Net .89

DUPLEX TV/FM WALL PLATE

(2) A dual TV/FM wall plate designed to supply two signal sources. Can be used for two different TV antennas each oriented in a different direction of a TV and FM antenna. Plugs are slotted for 300-ohm twin lead. Ivory finish.
99 R 40149 Shpg. wt., 4 oz. Net 1.09

TV-FM ROTOR WALL PLATE

(3) Wall plate has 5-wire outlet for 4- or 5-conductor rotor leads and 2 twin-lead outlets. Flexible design allows easy installation. Includes 1 plug for TV twin lead and 1 plug for rotor cable. Ivory finish. Wt., 5 oz.
99 R 40305

Net 1.39

SURFACE MOUNTING WALL BOX

- Accepts Standard TV/FM Wall Plates



Sturdy plastic housing for surface mounting with any standard 300-ohm or 75-ohm wall receptacle. Knock-outs on all four sides for ease of installation. No special tools required. Ivory color. Supplied with instructions and mounting hardware. Imported. Shpg. wt., 6 oz.
99 R 40024

Net .49

BAKELITE WALL BOX



Necessary for terminating TV lines in old or new work. Knockouts top and bottom. Sturdy construction with steel ears. Black standard size; U.L. Listed. Shpg. wt., 4 ozs.
18 R 70013

Net .89

"OPEN-HOLE" WALL BRACKET



Permits attaching any wall plate to wall openings without the use of a wall box in up to 3/4" wall board or plaster. Shpg. wt., 4 ozs.
18 R 70021

Net .49

ANTENNA CONNECTOR

For quick solderless connection of lead-in to TV antenna terminal. Fits 99-40081 socket. Low-loss polystyrene and non-ferrous metal. Standard 1/2" spacing. Shpg. wt., 3 oz.
18 R 42012



Net .29

Picture Tube Brighteners — Service Aids

COLOR PICTURE TUBE BRIGHTENER

- Boost Fading Color Picture Tubes
- No Wiring Necessary—Plugs Right In

Bring out the lost sharpness and detail of fading color picture tubes. Electron emission is increased by boosting the filament voltage, thereby returning full contrast and color quality to the set. Plugs in between picture tube and socket. No wiring or switching is necessary. For round tubes (12 pin base).

18 R 46070 Shpg. wt., 1 lb. Net 4.95
For rectangular tubes (12 pin base).
18 R 46088 Shpg. wt., 1 lb. Net 5.50



FIG. (A)



FIG. (B)



FIG. (C)

UNIVERSAL TV TUBE "BRITENER"

Restores brightness to dim TV picture tubes. Operates on all types—magnetic or electrostatic—and in all circuits—parallel or series. For Duodecal Base. Shpg. wt., 8 oz.
18 R 46005 FIG. (A) Net 1.75

UNIVERSAL 110° CRT "BRITENER"

A single heavy-duty unit which performs four ways. A simple adjustment adapts it for either series or parallel wired filaments and it can be used on electromagnetic or electrostatic focus tubes. Shpg. wt., 8 oz.
For Sylvania Type 110° Tubes, 18 R 46013 FIG. (C) Net 1.99
For RCA Type 110° Tubes, 18 R 46021 FIG. (B) Net 1.99

ACME T8394M VARIABLE VOLTAGE ADJUSTER



300 W. continuous duty variable transformer. Adjusted by rotary tap sw. Used as step-up or step-down. Voltmeter shows sec. voltage. Pri. 95/100/105/110/120/125 volts at 50/60 Hz. Sec. out 115 V. 8' cord and plug. Size: 4 3/4" x 4 5/8". Shpg. wt., 6 1/4 lbs.
33 R 40015 Net 13.40

TERADO VARIABLE VOLTAGE ADJUSTER



- 500 Watt Capacity
- AC Voltmeter

The Saturn Voltage Adjuster gives TV lifelike color and improves clarity and brightness by correcting low or high AC line voltages to normal. Can be installed on television sets in seconds, and the easy-to-read highly accurate edgeview voltmeter and 6-position switch allow the viewer fingertip control of AC line voltage resulting in a clearer, sharper, and fuller picture. It turns "on" and "off" automatically with the equipment. Can also be used with Hi-Fi, CB, Ham, etc. equipment.
11 R 63286 Shpg. wt., 3 1/4 lbs. Net 18.77

TV SERVICE EXTENSION HARNESS KIT

Makes possible testing sets with picture tube electrically connected in circuit, but removed from chassis. Reduced danger of contact with high voltage terminals and tube breakage. Consists of anode extension harness, yoke extension harness, tube socket extension harness and CRT extension is for both electrostatic and electromagnetic tubes.

18 R 27088 Shpg. wt., 1 lb. Net 5.50
Color Extension Harness Kit. Similar to above but designed for color TV. Shpg. wt., 1 1/4 lbs.
18 R 27211 Net 11.95

AUTOMATIC TV VOLTAGE REGULATOR

AS LOW AS
995



- Compensates For Low Line Voltage

For color or black and white TV. Returns full height and width of TV picture affected by low line voltage. Boosts 10-volts automatically when line is below 110 volts. Increases set sensitivity. Reduces low line hazards. Simple plug-in installation. Turns on and off with the TV set. Shpg. wt., 4 lbs. Perma-Power model D-210, 400 watts.

32 R 40058 Net 14.95
Perma-Power model D-200, 300 watts.
32 R 40025 Net 9.95



TUBE GUARD

- Stop Voltage Surge
- Adds Life To

TV-Radio and Hi-Fi Tubes

The "Tube Guard" will pay for itself many times over by greatly reducing costly vacuum tube replacements. The Tube Guard checks surge of current, reduces filament damages and increases tube life. Just plug "Tube Guard" into outlet, and appliance into it. 600 watts. UL listed. Shpg. wt., 4 oz.
18 R 31106 Net 1.99




HORIZONTAL BAR GENERATOR

Provides Horizontal Lines On Any T.V. Set—Quick—Accurate Alignment

Simplifies precise setting of yoke. Makes possible accurate positioning of focus coil or magnet. Quick adjustment of vertical linearity, height and centering. Plugs onto picture tube. Shpg. wt., 4 oz.

18 R 27013

Net 1.95



FUSIBLE RESISTOR KIT

Kit includes 1 each of the following values—4.7, 5.6, 7.5, 9.0 and 22 OHMS. Shpg. wt., 1/4 lb.
18 R 79048 Net .80

MALLORY RESET CIRCUIT BREAKERS



- Just Reset
- Not A Fuse—A True Circuit Breaker

Exact replacement circuit breakers for television and industrial applications. Button must be pressed to reset. Tripping mechanism is temperature compensating for constant protection. Normal tripping time is 10 seconds or less. All values above 31 amps have special heavy-duty contacts to withstand heavy surge currents. Twist tab mounting lugs. Adapter for bushing mount listed below. Shpg. wt., 3 oz.

Stock No.	Mfrs. Type	Break Curr. Amps	Oper. Curr. Amps	Surge Curr. Amps	Net Each
33 R 14606	CBT050	0.5	0.325	2	.81
33 R 14614	CBT075	0.75	0.49	3	.81
33 R 14622	CBT100	1.0	0.65	5	.81
33 R 14630	CBT150	1.5	0.975	12	.81
33 R 14648	CBT175	1.75	1.14	12	.81
33 R 14655	CBT200	2.0	1.3	12	.81
33 R 14663	CBT225	2.25	1.46	12	.81
33 R 14671	CBT250	2.5	1.63	12	.81
33 R 14689	CBT275	2.75	1.79	12	.81
33 R 14697	CBT300	3.0	1.95	12	.81
33 R 14705	CBT310	3.1	2.1	25	.88
33 R 14713	CBT325	3.25	2.11	25	.88
33 R 14721	CBT350	3.5	2.2	25	.88
33 R 14739	CBT375	3.75	2.44	25	.88
33 R 14747	CBT400	4.0	2.6	25	.88
33 R 14754	CBT450	4.5	2.92	25	.88
33 R 14762	CBT500	5.0	3.25	25	.88
33 R 14770	CBT600	6.0	3.9	25	.88
33 R 14788	CBT700	7.0	4.14	25	.88

Type CBB adapter for bushing mount. Bushing 3/4"—32x1/4" with nut.
33 R 14796 Net .16

CIRCUIT BREAKER REPLACEMENT FOR TV FUSES

- Stop Fuse Replacement



Circuit breaker replacement for TV color-coded TV fuses used in many TV sets. Circuit breaker can be reset as often as needed. When ordering, order same color as fuse removed from TV set. Shpg. wt., 4 oz.

Stock No.	Color	Stock No.	Color
18 R 31130	Red	18 R 31187	White
18 R 31148	Dark Green	18 R 31205	Light Green
18 R 31155	Blue	18 R 31213	Grey
18 R 31163	Pink	18 R 31221	Yellow
18 R 31171	Black	18 R 31239	Maroon
18 R 31189	Turquoise	18 R 31247	Brown

Net each 1.39

TV Accessories • Service Aids

LAFAYETTE COLOR TV TUNER CLEANER - LUBRICANT

- For Color and Black and White
- With Spray-Aid Needle

Non-flammable, non-toxic, easy to use. Can be applied without removing chassis from the cabinet. Will not harm plastics or electrical insulation or detune the tuner. Excellent for both color and black and white sets. 6 oz. spray can.

18 R 01984 Shpg. wt., 11 oz. Net .99
16 oz. economy size spray can with spray-aid needle. Shpg. wt., 1 3/4 lbs. Net 1.99



LAFAYETTE 7" COLOR TV PURIFIER

- For Sharp and Clear Color Reception

Sharpens color reception through demagnetization of the picture tube. Simply turn on the set, plug in the purifier, and with switch depressed rotate unit in front of the TV screen. Use regularly to keep your color reception sharp and clear. Convenient clip for hanging on back of set when not in use. Imported. Shpg. wt., 1 lb.

99 R 40248 Wt., 3/4 lb. Net 2.95



INJECTOR TUNER CLEANER-LUBRICANT

- With Injector Needle
- For Color—Black and White

Super 100. Fast drying, will not harm plastics or electrical insulation. Non-toxic, non-flammable. Can be sprayed on without removing chassis from cabinet. Contains "anti-static" agent. Will not cause drift or detune tuners.

3 oz. spray can. With plastic injector needle. 18 R 34043 Shpg. wt., 8 oz. Net .99
6 oz. spray can. With steel injector needle. 18 R 34050 Shpg. wt., 12 oz. Net 2.10
16 oz. spray can with steel injector needle. 18 R 34068 Shpg. wt., 1 3/4 lbs. Net 2.99



WALSCO 7" COLOR TV PURIFIER

- Portable Tube Kaddy Size
- For In-The-Home Servicing
- Color TV Degaussing Coil

Improve the quality of color TV with this portable 7" DEGAUSSER. Easily demagnetizes tube shield and accessories to eliminate stray colors and purify the picture. Momentary push button switch simplifies operation. You don't need to be a technician to use this little marvel. U.L. listed. For 110-120 VAC. 60 Hz. Shpg. wt., 3/4 lb.

18 R 84022 Net 6.25



"No Noise" & CONTACT CLEANER

- Cleans and Lubricates
- Will Not Harm Plastics

For color and black and white TV, radios, volume controls, band switches, pushbutton assemblies, relays, and electrical contacts. Restores, lubricates, protects, and cleans. Non-toxic and non-flammable. Prevents gumming. Does not change capacities. 6 oz. spray can with 5" extender (needle). Wt., 11 oz.

18 R 43010 Net 1.99



PROFESSIONAL COLOR TV PURIFIER

- For Color TV Receivers
- Large 13" Diameter Coil

Well suited for the serviceman or set owner. Heavy-duty degaussing coil demagnetizes and removes stray magnetic flux from color TV chassis and picture tube to achieve color purity. Contains momentary switch to de-energize coil without pulling plug. With 9 ft. cord. For 110-120 VAC, 60 Hz.

18 R 84055 Wt., 4 1/2 lbs. Net 19.95



CHEMTRONICS "FROST AID"

- Components Cooler
- With Pin-Point Spray Needle

Pinpoints bad capacitors and transistors, oxidized joints by cooling components. Leaves no residue. With spray needle for hard to reach places. Non-flammable. 8 oz. spray can, Shpg. wt., 1 lb.

18 R 52011 Net 1.49



BAKELITE KNIFE SWITCH

As Low As

25c

Excellent for TV antenna switching. Heavy metal parts mounted on bakelite base. Double pole, double throw. Shpg. wt., 4 oz.

99 R 61533 Net Ea. .29

In lots of 10 ea. Net .25



50 PIECE TV KNOB KIT

Selection contains 50 assorted TV knobs including such types as channel selector, fine tuning, volume, etc. Useful and attractive. Many with gold lettering or gold inserts. Shpg. wt., 1 lb.

32 R 99021 Net 1.99



Rembrandt

TV GHOST ELIMINATOR

5⁹⁵

- Improves Color Reception
- Receives From All Directions
- Filters Out Interference

Electrically rotates the polar-receiving pattern of your existing antenna and phases the ground wave picked up by the electrical wiring system with the sky wave picked up by the antenna. Improves any existing antenna; indoor, outdoor, master or built-in. Boosts pick-up power of any antenna—old or new. Just a flick of the selector control tunes out ghosts—filters out interference—tunes in those "hard-to-get" problem channels. Automatically amplifies TV signal strength for "snow" free, brighter, clearer pictures. Works on every channel—in any location—with any antenna—for any TV set. No installation problem—simply attach to antenna terminals in back of TV set—and plug into 117V AC/DC socket. UL Listed. Shpg. wt., 1 3/4 lbs.

18 R 12064 Net 5.95




STANDARD KOLLSMAN "ARBOR" PRESET TUNERS


16⁹⁵

- Replacements for over 1500 Different Models

Latest advances in tuner design result in maximum performance with outstanding frequency stability and precise tuning. With 13 position detents. IF Video: 45.75 MHz. IF Sound: 41.25 MHz. B+-125—145 VDC. Antenna input: 300Ω balanced to ground. With mounting brackets. Shpg. wt., 3 lbs.



Stock No.	Model No.	Heater	Net
18 R 20109	SBR-250	6.3V	16.95
18 R 20117	SBR5-252	600ma	16.95
18 R 20125	SBR4S-251	450ma	16.95



MARK VI LABEL MAKER KIT

Embosses Both $3/8"$ and $1/4"$ Tape

7⁵⁰

- You Get: Tool, Horizontal Character Wheel and Vertical Character Wheel, Case, and 5-12" Magazines of Tape
- Convenient Tape Cut-Off Lever
- Space Letters in Narrow or Wide Widths

Low-Cost tapewriter kit for home, office, store or workshop. Makes raised-letter labels that are self-adhesive, permanent and waterproof. Set dial to letter, number, or symbol and squeeze the handle. When label is completed, squeeze trigger to snap off tape. Kit includes: High-impact plastic embossing tool, two wheels, three $3/8"$ and two $1/4"$ magazines of tape plus rugged carrying case. Shpg. wt., $1\frac{3}{4}$ lbs. 14 R 41484 Net 7.50

DYMO $1/4"$ and $3/8"$ SLIMLINE TAPEWRITER KIT




- Flat Easy to Store Design
- Lightweight But Extremely Rugged

18⁹⁵

Model 1450-01. The Dymo SLIMLINE, compact, only $1\frac{1}{4}"$ thick, $2\frac{1}{2}"$ wide, and $8\frac{3}{4}"$ long, lies flat, stores conveniently almost anywhere. Embosses new easier-to-read "Designer" extended letters in both $1/4"$ and $3/8"$ vinyl tape. Features automatic pull-tab tape cut off. Set includes SLIMLINE embossing tool with 2 different size horizontal letter and one vertical letter embossing wheels. PLUS one roll $3/8"$ and one roll $1/4"$ tape. PLUS molded carrying case. Shpg. wt., 2 lbs. 14 R 41542 Net 18.95

DYMO $1/2"$ AND $3/8"$ TAPEWRITER KIT



- 2 Horizontal and 1 Vertical Letter Embossing Wheels

22⁹⁵

Model 1570-01 Exclusive "Touch Action" helps you make permanent, self-sticking Dymo labels, without effort. Great for organizing the office, store, stockroom, or workshop. Embosses easier-to-read "Designer" extended letters in both $1/2"$ and $3/8"$ vinyl tape. Set includes rugged chrome plated zinc embossing tool, $9\frac{1}{2}"$ long. PLUS 2 different size horizontal letter and one vertical letter embossing wheels. PLUS one roll $1/2"$ tape and one magazine $3/8"$ tape. Shpg. wt., $1\frac{1}{4}$ lbs. 14 R 41609 Net 22.95

DYMO $1/4"$ AND $3/8"$ LABELMAKER



ONLY 4⁵⁰

- Space Letters in Narrow or Wide Widths
- Convenient Tape Cut-Off Lever

Handy, labelmaker for home, school or office, Embosses both $3/8"$ and $1/4"$ self-adhesive vinyl tape to make permanent, waterproof raised labels. Lightweight Cyclocat® tool, only $7\frac{1}{2}"$ x $3"$, has wide or narrow letter spacing, and a convenient tape cut-off lever. Comes with interchangeable horizontal and vertical letter wheels PLUS 12" magazine of $3/8"$ tape. Shpg. wt., $5\frac{1}{2}$ oz. 14 R 41492 Net 4.50

$1/4"$ OR $3/8"$ LABELMAKERS

- Handy Tape Cut-Off

Home labelmaker embosses raised characters on vinyl tape. Just dial the letters, numbers, or symbols and squeeze the handle. Has pull tab cut-off and rugged plastic body. Size: $6\frac{1}{2}"$ x $6"$ H. Choice of model with $1/4"$ or $3/8"$ wheel. Wt., 2 lbs. 14 R 41534 $3/8"$ Model Net 2.75 14 R 41013 $1/4"$ Model Net 2.75 $3/8"$ Labelmaker complete with 3-12" rolls of vinyl tape. Shpg. wt., $3/4$ lb. 14 R 41583 Net 3.95

DYMO EMBOSSING TAPES

1/4 INCH
Each contains 144" of $1/4"$ glossy vinyl tape with adhesive backing. Shpg. wt., $1/4$ lb. Net ea. .79

Stock No.	Color	Stock No.	Color
14 R 41021	Blue	14 R 41062	Brown
14 R 41039	Green	14 R 41070	Black
14 R 41047	Red	14 R 41302	Orange
14 R 41054	Clear	14 R 41310	Yellow
14 R 41518	Wal. Grain	14 R 41328	Gold


3/8 INCH
Contains 144" of $3/8"$ dirt/moisture resistant vinyl tape with adhesive backing. Shpg. wt., $1/4$ lb. Net ea. .99

Stock No.	Color	Stock No.	Color
14 R 41112	Blue	14 R 41153	Blue
14 R 41120	Black	14 R 41161	Green
14 R 41138	Red	14 R 41278	Orange
14 R 41146	Clear	14 R 41286	Yellow
14 R 41526	Wal. Grain	14 R 41294	Gold

1/2 INCH
Contains 144" of $1/2"$ glossy vinyl tape with adhesive backing. Shpg. wt., $1/4$ lb. Net ea. 1.39

Stock No.	Color	Stock No.	Color
14 R 41187	Black	14 R 41229	Green
14 R 41195	Yellow	14 R 41237	Brown
14 R 41203	Red	14 R 41245	Gold
14 R 41211	Blue	14 R 41252	Clear

Engine Divided Slide Rules



As Low As
8⁹⁵

(A) 13 1/4" VECTORLOG® SLIDE RULE

For Communications Engineers and Physicists

- Laminated Bamboo Construction • P, P', and Q Scales • For Direct Vector Addition • Hyperbolic Sine and Tangent Scales. Two Sine Scales—One Marked in Degrees, One Marked in Radians. • 5 Log Log Scales Plus a Voltage DB Scale • Complete with Belt Carrying Loop and Leather Case • With 10" Scale

The Lafayette VECTORLOG Slide Rule provides a new concept in scientific calculation, incorporating scales and arrangement designed for quick-easy-manipulation. Twenty-seven (27) scales incorporate the many problems encountered in Electrical Engineering and Physics. The unique P, P', and Q scales allow direct right angle vector addition. No longer are several settings required to obtain right angle vector sums—these scales work in the same manner as the C and D for multiplication. The two Hyperbolic Sine and one Hyperbolic Tangent Scale, the voltage db scale, and the five Log Log scales, provide maximum coverage of these dynamic fields. VECTORLOG is the result of extensive tests for ease of manipulation. Several of these features are: C and D scales on both the front and back of the rule; Sine scales in both degrees and radians, removing the necessity of both scale conversion of units; a problem-tested location of scales; and adjustable screws to allow variable tension on the slide. Scales include: (FRONT) Tr-1, TR-2, P, P', Q, ST, S-1, S-D, C, D, LL01, LL02, LL03, LL1'; (REAR) Sh-1, Sh-2, DF, A, B, C, CF, Th, C, D, LL3, LL2, db. With instruction book, leather carrying case, and belt carrying loop. Imported. Shpg. wt., 1 1/4 lbs.

99 R 71029

Net 17.95

(B) 13 3/4" DELUXE LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE

- With 11" Scale • 25 Scales with 8 Log Log Scales
- Extended Range Avoids "Going Off Scale"
- Extra P Scale Simplifies Computations • Two Color Scales

A log log dupli decimal trigonometric slide rule contains 25 scales including 8 Log Log Scales. Troublesome end-for-end resetting is eliminated by extensions of C and D scales. Twin set of Log Log scales run from 1.001 to 100,000 and .999 to .00001, enlarging the scale by one scale length each compared with ordinary log slide rules. Extra features include P scale which enables direct "readout" of cosine value. Scales include LL01, LL02, LL03, DF, CF, CIF, CI, C, LL3, LL2, LL1, LL00, L, K, A, B, S, ST, T, C, D, DI, P, and LL0. With instruction books, saddle leather case. Imported. Shpg. wt., 1 1/4 lbs.

99 R 70559

Net 16.95

(C) DECIMALOG™ 6 1/2" LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE

- P Scale (Pythagorean) permits direct "readout" of Cosine Values
- 24 Scales including 8 Log Log Scales • With 5" Scale

A pocket version of our 13 3/4" Log Log Dupli Decimal Trigonometric slide rule. Contains all the scales of the 13 3/4" rule except the "ST" scale. Two color scales—positioned for each in use and rapid calculations. "C" and "D" scales on both sides of the rule. "P" scale for direct, cursor line reading of cosines of angles. Scales—front face: LL1, LL2, LL3, DF, CF, CIF, CI, C, D, LL3, LL2, LL1. Back face: LL0, L, K, A, B, S, T, C, D, DI, LL0. Engine divided rule of laminated, non-hygroscopic bamboo. Complete with instruction book and leather case with pocket clip. Imported. Shpg. wt., 8 oz.

99 R 70997

Net 8.95

(D) 12 1/2" LOG LOG DUPLI TRIG SLIDE RULE

- With 10" Scale

Specially selected, laminated, non-hygroscopic bamboo. Scales machine engraved on white plastic in permanently accurate calibrations. Adjusting screws permit varying tension on slide. 21 scales including C, D and CI on both sides. LL0 and LL00 scales refer to B scale. All other scales coordinate and refer to D scale. Scales are L, LL1, DF, CF, CIF, CI, C, D, LL3, LL2, LL0, LL00, A, B, K, CI, C, D, S, ST and T. Scale characteristics permit multiplication, division, proportion, inverse proportion, reciprocals, cotangents, squares, square roots, cubes, cube roots, logarithms, tangents, sines, Pi factor multiplication and division, powers and roots of numbers less than 1, powers and roots of numbers greater than 1, logarithms to base "e." Shpg. wt., 1 lb. Imported.

99 R 70310

Net 12.95

5" POCKET SLIDE RULE



- Extremely Accurate
- Has Standard S, L and T Scales

Convenient pocket sized slide rule of specially selected and treated bamboo. Will not warp, shrink or lengthen under varying atmospheric conditions. A, B, CI, C, D and K scales engraved on white plastic surface. Reverse side of slide has standard S, L, and T scales. The upper beveled edge of the rule is graduated in mm to 13 cm. Other edge is divided into 5 inches by 32nds. Only 5 3/4," long over all. Carried easily in any pocket. Wt., 6 oz. Imported.

99 R 70302

Net 3.95

USING THE SLIDE RULE IN ELECTRONIC TECHNOLOGY

by Charles Alvarez

2⁹⁵

Written for electronic students, both beginners and advanced. It can also serve as auxiliary text in math theory. All scales are discussed separately with detailed examples, graded in difficulty to develop speed and accuracy in use of the slide rule. 120 pp. 5 1/2 x 8 1/2 paperback. Shpg. wt., 8 oz.

10 R 11626

Net 2.95



4" CIRCULAR SLIDE RULE

3⁴⁹

A versatile calculating instrument specially constructed with special chemical resistant, 1/4" thick, plastic, it will not shrink or expand under varying climatic conditions. 12 scales to solve problems involving multiplication, division, proportions, squares, cubes, and all trigonometric functions. Special scales allow direct conversions of angles from radians to degrees. Ideal for quick calculations. With leatherette case.

99 R 71276 Wt., 4 oz. Imported Net 3.49

FRACTION ADDING MACHINE

2⁹⁵

Continuous adding or subtracting of fractions, decimal equivalents, or mixed fractions and decimals. Answers shown instantly. Invaluable for the shop and technical school, office, factory, machinists, designers, draftsmen, and engineers. Made of satin-finished aluminum—only one moving part—numbers and lines etched and filled for years of trouble-free service. Complete with plastic case and instructions.

13 R 17015 Shpg. wt., 4 oz. Net 2.95

Drafting & Drawing Supplies

PRECISION DRAWING SET




10⁹⁵

TECHNICAL DRAFTING SET

- Center Wheel Adjustment
- Professional Quality
- Made in W/Germany of Nickel Plated Brass

Contains 6 1/4" self-centering compass, one leg knuckle joint with divider, pencil, pen parts and lengthening bar; 6 1/4" self-centering divider; spring bow divider 4 1/4", center wheel adjustment with interchangeable needle points; spring bow pencil and spring bow pen, both 4 1/4" with center wheel adjustment and interchangeable needle point; two 5/4" ruling pens; extra handle for pen and pencil parts; adjustment tool; lead case and leads; and spare parts kit, all in fitted lined case. Shpg. wt., 1 1/2 lbs.

99 R 76039 Net. 10.95



6⁹⁵

UTILITY DRAFTING SET

- Side Wheel Adjustment
- Made in W/Germany of Nickel Plated Brass
- Professional Quality

Made in Germany of hard rolled, nickel plated brass. All instruments are nested in a fitted, lined case. Contains three side wheel 3 3/4" bow instruments—one a divider, one a pencil and one a pen. All have reversible needle point. 5 1/4" compass with pen and pencil parts—and lengthening bar. 5 1/4" divider with straightening device. 5" ruling pen. Extra handle for use with pen and pencil parts. Capsule with extra leads. Perfect for school, labs, industrials. Shpg. wt., 1 lb.

15 R 21046 Net. 6.95



5⁹⁵

PROFESSIONAL GIANT BOW

- 6" Size with Center Wheel Adjustment
- Finely Balanced—Professional Type
- Made in W/Germany of Nickel Plated Brass

Professional quality utility set in a fitted lined case. Made in Western Germany of nickel plated brass. 6" giant bow has preferred center wheel adjustment. Makes circles from 1/8" to over 10" in diameter. Set includes 6" giant bow, interchangeable pen and pencil parts, extra needle for using bow as divider, handle for use with pen and pencil parts, lead, lead box and repair parts. Shpg. wt., 9 oz.

15 R 21053 Net 5.95

draftette PORTABLE DRAFTING MACHINE



16⁹⁵

- Precision Instrument

Model 9-B—sketch draft, design, draw diagrams and schematics like a professional. A new DRAFTETTE which gives you all the advantages of a T-square, triangle and protractor in a compact, easy to operate portable drafting machine. Constructed of anodized aluminum, features tubular arms, 360° protractor, one-piece 6" x 9" scale calibrated in 16ths-1/8-1/4. Mounted on a 16" x 21" drawing board, completely assembled ready to use. Shpg. wt., 5 1/2 lbs.

15 R 74011 Net 16.95

PRECISION DRAWING SET



13⁹⁵

- Includes 14 Drawing Aids plus 13" x 19" Basswood Board

An attractively designed drawing set. Consists of 14 drawing aids: 13" x 19" Basswood Drawing Board, T square, Protractor, French curve, 30/60° and 45/90° triangles, Architect's scale, slide rule, bow compass, 12" ruler, erasing shield, lettering guide, architect's scalemaster, eraser and lead holder. Shpg. wt., 3 3/4 lbs.

15 R 14504 Net 13.95

PORTABLE DRAWING KIT



3⁵⁰

- Can Be Carried or Stored

A folding portfolio conveniently carried or stored. Includes a 12-inch T-square, a 180° protractor, a 6-inch French curve, a 4-inch 45/90° and a 4-inch 30/60°, a 50-sheet drawing pad and drawing pencil. Plastic portfolio is 9x13 1/2 x 1 1/2". Tools housed in separate pockets. Shpg. wt., 2 lbs.

15 R 14330 Net 3.50

HARD MAPLE PANTOGRAPH

For Enlarging, Reducing, Reproducing



5⁹⁵

- "Quick-Change" Feature Allows Setting to Any Ratio

A 21" adjustable pantograph with 21 different ratios from 1 1/4 to 8. Enlarges, reduces or reproduces drawings, etc. Most rapid, accurate means of reducing or enlarging to scale. Lacquered highly finished bars are 21" long and 3/4" wide. Heavy ball bearing standard. Chrome plated hardware, ratio thumb screws and nuts. Complete with lead, accessories and detailed instructions. Shpg. wt., 1 lb.

15 R 56026 Net 5.95

31" PANTOGRAPH

Similar to above except 31" long, with 32 ratios. Complete with accessories and instructions. Shpg. wt., 1 lb. 3 oz.

15 R 56067 Net 7.95

draftette PORTABLE DRAFTING MACHINE



9⁹⁵

- Mounted on 11 x 17" Hardboard

Model #117 portable drafting machine with interchangeable one-piece aluminum 4 x 6" scale, calibrated in 16th, 1/4 and 1/8 or 10/50ths (eng.) and Metric. Full 360° protractor. Precision all-aluminum construction gives you a rugged and accurate machine. Ideal for schematics, layouts, etc. 15 R 74060 Shpg. wt., 2 1/4 lbs. Net 9.95

draftette SKETCH KIT



9⁹⁵

Model #68 portable drafting drawing machine permanently mounted in a Vinyl binder (self-locking). Can be used for sketching, designing, drawing, and drafting. Great for traveling. Contains a precision portable drafting instrument with a 4 x 6" scale, 360° protractor, pad of 50 sheets, drawing-tracing paper 8 1/2 x 11", pencil, all in one compact binder. Does not require tape or tacks to hold paper in place for use. Binder 9 1/2 x 13 1". Shpg. wt., 2 1/4 lbs.

15 R 74029 Net 9.95


Drafting & Drawing Supplies

DATAK

INSTANT LETTERING KITS

As Low As **3⁰⁰**

Sharply defined 1/8" high, Gothic typeface, letters, numerals, and most often used electronic terms. Transfer easily and cleanly onto any smooth, dry surface—paper, metal, plastic, wood, or glass. Not a decal, goes on instantly without water or tapes. Leaves no background haze or film. Looks like it was printed on! Hundreds of characters on 3 x 5" sheets in each set. Shpg. wt., 4 oz.



Stock No.	Mfg. No.	No. of Sheets	Kit Includes	Color	Net
32 R 75047	9581	24	Letters, words	Black	5.95
32 R 75054	9591	24	Numerals	White	5.95
32 R 75088	9601	12	Letters, Words	Black	3.00
32 R 75096	9611	12	Numerals	White	3.00
32 R 75104	9621	12	Alphabets Only	Black	3.00
32 R 75112	9631	12	Alphabets Only	White	3.00

METER AND DIAL MARKING KIT

Contains 12 5" x 7" sheets—4 different sheets in 3 colors, black, white and red. Sheets have switch patterns, arcs, graduation lines, letters and numerals etc. for marking rotary and standard switches and dials, etc.

32 R 75013 per package Net 5.95

DATAK-OAT PROTECTIVE COATINGS. Maximum protection for instant lettering. 7 oz.

32 R 75002 Protective Coating Kit Net .99

32 R 75076 Protective Coating Kit (16 oz. spray can) Net 2.95

RUBBER TYPE SET

An easy to use printing kit that comes complete with 14-point (1/4") rubber type, 22 numerals, over 100 capital letters, punctuation marks, ink pad and tweezers. Print anything from one to four lines long. Special "base-lock" type for perfect alignment. Neat, clean, and clear results. Many printing uses in the home or business. Instructions included. Shpg. wt., 3/4 lb.



15 R 60010 Net 3.50

Extra set of (1/5") rubber type, 22 numerals, over 100 capital letters, punctuation marks. Net 2.39

15 R 60002 Net 2.39

20 CAMEL HAIR BRUSHES

99^c



Imported camel hair brushes. Sizes #1 through #6. Each brush is 6 1/2" long with different color handles. Excellent for cleaning tuners and precision parts. Perfect for water color, cabinet touch-up, and sign lettering. Shpg. wt. 4 oz.

15 R 78509 Net 99

ELECTRONIC DRAFTING TEMPLATE



ELECTRONIC TEMPLATE. Exceptionally accurate! Made to J.I.C. standards. All elements of electronic and CR tubes are provided for—plus tube bases for 7, 8 and 9 prong tubes. Includes transistors, diodes, rectifiers, plugs, etc. Covers all symbols. Size: 7x5". Thickness: .030". Shpg. wt., 4 ozs.

15 R 43016 Net 2.79



Made of crystal clear plastic .090" thick. Set consists of eight French curves. Excellent for perspective, three dimensional drawing and general applications. wt., 3/4 lb.

15 R 14256 Net 3.19

TACIRO TACROGRAPH SET

5⁹⁵

• with Three Nibs



A top quality drawing pen for all lettering and drawing work. Uses both India and drawing inks. Precision point for constant flow lines. Slim, easy to hold pen comes with 3 color coded nibs. Fine (Size 0, Grey nib), Light Medium (Size 1 Yellow nib), Very Broad (Size 3, Blue nib). Ideal for your every artistic and mechanical need. Shpg. wt., 4 oz.

15 R 80026L Net 5.95

TACIRO TACROGRAPH SET

11⁹⁵

Complete with (7) Nibs



Professional quality Tacrograph pen set. Uses both drawing and India inks. 7 precision crafted points. With rubber sleeve for easy removal of nib. In attractive velveteen lined leatherette pigskin case. Nibs: White-00-very fine; grey-0-fine; yellow-1-light med.; beige-2-heavy med.; green-2 1/2-brd; blue-3-very broad; red-4-extra broad. Shpg. wt., 8 oz.

15 R 80034L Net 11.95

LETTERING GUIDE SET



Made of transparent plastic. Use with either sharp pencil or ink. Each has complete alphabet, numbers and commonly used signs. Set consists of six guides. Sizes 1/8, 3/16, 1/4, 5/16, 3/8, and 1/2". Shpg. wt., 1 lb.

15 R 14322 Complete Set Net 4.95


LETTERING PEN

Reservoir type drawing pen. Designed for use with lettering guides from 1/8" to 1/2". Shpg. wt., 3 oz.

15 R 14074 Net 1.79

ELECTRIX® THE EXECUTIVE PERSONAL FAN

10⁹⁵



- Powerful Compact
- Whisper Quiet
- Use Anyplace You Relax

Cools like fans several times its size. Set it on a desk, alongside your bed, or in the kitchen . . . wherever a breath of fresh air is needed without blowing up a storm, or disturbing papers. The Executive is so whisper quiet and efficient you can use it any place you relax or work. Durable, high impact Cyclocol® base adjusts to direct a concentrated, cooling, even stream of air. Beautiful off-white/walnut finish. For 117 VAC, 60 Hz. Size: 8Wx4Hx4D.

15 R 51019 Shpg. wt., 2 3/4 lbs. Net 10.95

AUTOMATIC ELECTRIC PENCIL SHARPENER

11⁹⁵



- Automatic Stopper When Pencil Is Sharpened
- Heavy Duty Electric Motor

Model 660—Ideal for student, artist, draftsman, business firms . . . gives a needle point instantly. Unit even sharpens charcoal and pastel pencils. Sensitive micro switch automatically stops motor when pencil is sharpened. Carefully machined precision ground cutters last indefinitely. Easy cleaning with convenient push out receptacle drawer. Safe for even a child to use. Sturdy die cast metal with heavy duty 115 volt AC motor. U.I. Listed. Imported.

15 R 17051 Shpg. wt., 4 3/4 lbs. Net 11.95

Make Lafayette Your One Dependable Source for Everything in Electronics

Lafayette Cat. No. 720 309

brother CHARGER 11
ALL STEEL
PORTABLE TYPEWRITER



- Two Color Ribbon
- Console Type Case Cover

39⁹⁵

No Money Down*

Charger 11. Rugged, lightweight portable typewriter, ideal for students and home use. All steel construction ensures years of solid performance and dependability. Compact design features a full size 84 character keyboard. Additional features include: jam release key, 2 color ribbon, stencil position, half-space ratchet, line drawing aperture, measuring scale and card holder. Comes with console type case cover. Pica type. Size: 14½ x 15 x 5½". Imported. Shpg. wt., 13½ lbs.

15 R 17119W Net 39.95

brother ECHELON 89
ALL STEEL COMPACT
PORTABLE TYPEWRITER



- With Key Set Tabulator
- Automatic Repeat Space Key
- Attractive Case With Lock

64⁹⁵

No Money Down*

Echelon 89. Space-age engineering comes to popular priced typewriters... automatic spacing at the touch of a button without electricity. Other features include full 88 character keyboard, jam release key, touch adjustment, half space ratchet, key-set tabulator, variable line spacer, measuring scale and card holder, 2 color ribbon and stencil selector and line drawing aperture. Comes with attractive luggage type carrying case with lock and key. Pica type. Size: 16 x 18 x 8". Imported. Shpg. wt., 19 lbs.

15 R 17143W Net 64.95



99⁹⁵

No Money Down*

brother ELECTRIC PORTABLE TYPEWRITER

**With Fully Electric Repeat Keys
Plus Automatic Repeat Spacer!**

MODEL 3000 Features a full 88 character office keyboard including the +, =, 1, !... four more than standard. Has 3 repeat keys... 6 electric repeat characters: - , _ , , X , . , x. Equipped with automatic repeat spacer, tabulator, half-space ratchet, 2-color ribbon and stencil selector, line drawing aperture, paper meter and scale. Comfort sloped keyboard, eraser table, and paper support. Comes with lid cover. Pica type. Size: 5¼H x 14L x 13½"W. Imported. Shpg. wt., 20 lbs.

15 R 17150W Net 99.95

Smith-Corona® CORONA 70 ELECTRIC
PORTABLE TYPEWRITER

- Precision Electric Keyboard
- Key Set Tabulator

Student-priced—styled for the 70's. Precision portable electric typewriter with big machine features. Has push-variable platen, repeating space bar, electric segment shift, removable easy-to-clean platen, key set tabulator (more than 80 stops) and quick-set visible margins. Also features a forward glide deck and high performance motor. All steel construction. Genuine Naughahyde carrying case. Smartly styled in Aztec blue. Pica type only. For 110-120V AC. U.L. listed.

15 R 40178W Shpg. wt., 24 lbs. Net 129.95.



Smith-Corona® CORONET AUTOMATIC 12
ELECTRIC PORTABLE

- Big 12" Carriage
- Fully Powered Carriage—Tabulation—Keys

The Coronet Automatic 12 meets the most exacting needs of office, home or school—yet travels with filite-lite ease. Full sized keyboard, full length tabulator key sets, clears. Repeat action for dashes, dots, X's, underlines. Repeat spacing; copy-set dial; 3-position ribbon selectors. 12" carriage automatically returns and advances to next line. Copy set dial—makes up to 10 carbons. Aztec blue body w/Seamist keyboard. Pica type. All steel construction. Carrying case incl. 110-120V 60 Hz, AC. Shpg. wt., 30 lbs.

15 R 40194 Net 184.95

184⁹⁵

- With Deluxe, Vinyl Coated Steel Case

No Money Down*

Bohn COMPACT ELECTRIC ADDING MACHINE

With Direct Credit Balance



89⁹⁵
No Money Down*

- Fully Automatic Two-Color Ribbon
- Larger Capacity: Totals 11 Columns Up To \$999,999,999.99

Model 10/11 Short stroke 10-key keyboard. Automatic operation—add, multiply, subtract, total, subtotal and true credit balance. Two-color ribbon prints credit balance and minus factors in red. Clearly marked single-use function keys. Raised PLUS bar makes "sure target." "Ezy-Lock" multiplication key simplifies and speeds up all repeat operations. New non-add key prints reference numbers. All-steel frame and steel mechanism. Two-tone high impact styrene housing. 15 R 55002W Shpg. wt., 10 lbs. Net 89.95

Contour-fitted Statesman Carry Case with zipper and handles. 15 R 55010 Shpg. wt., 13½ lbs. Net 6.95

SMITH-CORONA "FIGUREMATIC" PORTABLE ELECTRIC ADDING MACHINE

• Totals 8 columns to \$999,999.99



74⁹⁵
No Money Down*

A fast-figuring electric portable that adds, subtracts and multiplies. Full-featured construction with 10 keys. Add-Subtotal, Subtract-Total, and Repeat. "Clear" and digital indicator are combined. Lists 7 columns of figures. New, easy-load-ribbon cartridge gives thousands of extra prints. Easy to carry—the cord tucks in, stylish dust cover snaps on, built-in retractable carrying handle comes out, and away it goes. Ideal for everyone who figures—at work, home, in-between. Overall 7x9x13". For 110-115 volts. 60 Hz, AC. Shpg. wt., 10½ lbs. Shpg. wt., 10½ lbs. Net 74.95

Adding tape for above 2½" wide. 15 R 40061 Shpg. wt., 10 oz. Net ea. .39



COPYMATE III DRY COPIER


- Makes Crisp, Black-on White Copies
- No Messy Liquids, Powders, Sprays or Inks
- Copy Letters, Photographs, Pages Bound in Books

49⁹⁵

Easy to use and economical dry copier for home and office. Anyone can make permanent black-on white copies of documents, recipes, etc. in less than 30 seconds, regardless of color or thickness up to size 8½ x 11". No messy chemicals, inks, powders or sprays; uses two ordinary 150 watt frosted bulbs and "Copymate" paper. Features a built-in automatic timer that determines proper exposure and also indicates when copies are ready. Compact, handsome two-tone grained finish case with carrying handle has a convenient built-in paper storage compartment. Easy front panel controls and pilot light. For 110-120 VAC, 60 Hz, UL listed. Size: 22¼ x 17½ x 6¼". Shpg. wt., 9 lbs.

15 R 46043W Net 49.95

"Copymate" Paper. 33 sheets per pkg. Shpg. wt., 1½ lbs. Net 3.25



Decorative 2 Drawer Desk

IDEAL FOR STUDYING AND HOME OFFICE

- Permaneer Finish Resists Heat, Stains, and Scratches
- Easy to Clean

29⁹⁵

CHAIR OPTIONAL

Finely crafted chrome and walnut desk is designed to blend with any decor. Perfect for the home study or office. Two storage drawers and a large extended desk top provide plenty of functional work space. Constructed of durable pressed-wood Permaneer. Walnut-grained finish has the look and feel of rich, lustrous hardwood and is stain, heat, and scratch resistant. Easily wipes clean with a damp cloth. Keeps its beautiful woodlike finish with no special polishing care. Desk stands 29" high on 4 sturdy chrome-plated legs. Desk measures 48" wide x 20" deep. Easily assembled with just a screwdriver. Shpg. wt., 50 lbs.

20 R 16020WX Net 29.95

OPTIONAL CHAIR, has contour back with black vinyl fully padded seat. Walnut wood finish matches above desk.

20 R 23059W Shpg. wt., 12½ lbs. Net 12.95



*See Page 22 for Full Credit Details on Easy Pay Plan

Desk Lamps for Home & Office



HIGH INTENSITY DESK LAMP

- All Angle
- Spring
- Control Arm For Perfect Balance
- Extra-Wide Shade For Glare Free Light

only
15⁹⁵

Now you can have pure white concentrated light exactly where you want it. Decorator styled to fit any decor in your home or office. The glare-free bulb supplied with the lamp is equal to 200 watts of illumination. An oversize shade provides a greater light area than ordinary high intensity lamps and does not retain heat. A steel spring gives you complete mobility in all directions with perfect balance. Arm reach is 24". Lamp is black with a heavy chrome and black vinyl finish base. Shpg. wt., 7 $\frac{3}{4}$ lbs.

12 R 33501 Net 15.95

5-WAY HIGH INTENSITY LAMP

- Hi-Lo-Off Selector Switch
- Adjustable Telescoping Arm




ONLY
4⁹⁵

Beautifully designed, transformer powered telescoping Hi-Intensity lamp featuring HIGH and LOW switch. Telescopes from 3 $\frac{1}{2}$ " to 12". May be used as a desk and wall light, spot and TV lamp. Use as a night light when closed. Shade swivels 360° with an arc of 180°. Shade and base are richly finished in black. Uses #93 bulb, supplied. Overall height 13". 117V, 60 Hz. Imported.

12 R 28535 Shpg. wt., 2 lbs. Net 4.95

FLUORESCENT DESK LAMP



6⁹⁵

14⁹⁵

Fig. A. An attractive all metal fluorescent lamp with combination solid/gooseneck support finished in chrome. Brown metal base with push button light control perfect for study, office or den. Translucent white plastic diffuser for maximum light dispersal. Includes 15-watt, 18" cool fluorescent bulb. Streamline design complements any room decor, 14 inches high by 15 inches wide. Provides illumination anywhere on your work or reading surface. 117V, 60 Hz. Imported. Shpg. wt., 5 $\frac{1}{4}$ lbs.

12 R 16027 Net 6.95

Fig. B. Attractive, all metal desk lamp with two 15-watt fluorescent bulbs for maximum light. Contemporary design matches any decor. Dual, polished chrome goosenecks and black finish base. 18 $\frac{1}{2}$ " metal shade with plastic light diffuser for high light dispersion and reduced eye fatigue. Great for students, office work, or reading. Pushbutton starter and off switch on base. Height: 17" With two bulbs. 117V, 60 Hz.

12 R 16043 Shpg. wt., 5 $\frac{1}{4}$ lbs. Net 14.95



DIAL-A-LITE HIGH INTENSITY LAMP

- Dials Any Degree of Light From Night Light to Bright Light.

11⁹⁵

Now you can vary your light continuously from a soft glow that is dimmer than a night light to a brilliant, glare-free, white light equivalent to 150 watts of illumination. Slide switch turns light on or off without disturbing dial setting. Telescoping arm extends to 15"; shade swivels 360°. The lamp can be hung on a wall by using keyhole slot on base. Unit folds down to only 3 $\frac{1}{4}$ x9 $\frac{1}{4}$ ". Sand finish. For 120v, 60 Hz, AC, Uses GE No. 1129 bulb (included). U.L. listed. Shpg. wt., 2 $\frac{1}{2}$ lbs.

13 R 81318 Net 11.95

"NIGHT-WATCH" HIGH INTENSITY LAMP

Only **9⁹⁵**

- Hi-Lo-Off Selector Switch
- Rosewood Inlay on Shade and Base



Richly styled high intensity lamp with rosewood inlay on both base and shade. Tip-proof base is of high impact polypropylene which cannot crack, chip, or mar. May be used as a night light in "lo" position when shade is rested on base. Chrome plated steel folding arm directs light in any direction. Equal to 150-watts of illumination with G.E. 1141 bulb supplied. Charcoal finished sides. U.L. listed. 117V, 60 Hz. Imported.

12 R 17504 Shpg. wt. 2 $\frac{1}{4}$ lbs. Net 9.95

TYPE-LITER TYPEWRITER LAMP



12⁹⁵

- Fits Any Typewriter

Useful addition to your office or study. Type-Liter attaches snugly to the back of any typewriter or office machine to provide light where it is needed. Prevents eye strain. No nuts, or bolts necessary. Uses 15-watt fluorescent bulb for cool, non-glare illumination. Swivel action shade with flexible arm. Neutral color to blend with any decor. U.L. listed. Shpg. wt., 4 lbs.

12 R 10095 Net 12.95


T-8 15-Watt Cool White Lamp, Shpg. wt., 5 oz.

12 R 10020 Net 1.39

REPLACEMENT HIGH INTENSITY BULBS

Popular replacement bulbs for most high intensity lamps. Avg. shpg. wt. 3 oz.

Stock No.	Type No.	Qty	Net
32 R 66848	93	1	.40
12 R 75536	40S11N	1	.79
32 R 66475	1129	1	.40
32 R 69206	1141	1	.30



Home - Office - Shop Lamps



A DELUXE INCANDESCENT LAMP
 Model LB-1A. Designed for use wherever work areas must be well illuminated. Non-friction, spring-balanced design permits easy positioning, and keeps lamp permanently in place. Can be raised or lowered, swivels 360°, and has 45" reach. Dual-shade construction reduces heat and maintains new lamp performance. Easily clamps to edge of table or desk. Dove gray finish. Accepts standard bulb. U.L. listed. Less bulb.
 12 R 69554W Shpg. wt., 5 lbs. Net 19.95

B DELUXE COMBINATION INCANDESCENT and FLUORESCENT
 Model LC-1A. Ideal for use in any office or home where maximum lighting efficiency is necessary. Separate switches independently control each light. Spring-controlled, counter balanced arms "finger-touch", "stay put" positioning; can be raised or lowered, rotates 360°, extends 45". "C" clamp mtg. Handsome dove gray finish. U.L. listed. Less bulbs.
 12 R 69562W Shpg. wt., 7 3/4 lbs. Net 27.95
 12 R 75015 22 watt, cool white fluorescent lamp. Net 3.49


C DELUXE FLUORESCENT MAGNIFIER LAMP
 Model LFM-1A. Designed for assembly and inspection of miniature parts, reading numbers and fine print. Spring balanced design; the lightest touch guides the light to any fixed position; users hands are left completely free. 5" magnifier; 360° swivel; reaches 25 to 45". Constructed with precision ground lens and die cast aluminum shade. Dove gray. "C" clamp mtg. U.L. listed.
 12 R 69570W Less Bulb. Shpg. wt., 8 lbs. Net 39.95
 12 R 75015 22 watt, cool white fluorescent lamp. Net 3.49

D DELUXE FLUORESCENT DESK LAMP
 Model FL-1A Dual-light fluorescent desk lamp with uniquely designed shade and inner reflector to produce maximum, non-glare, lighting. Spring-balanced extension arms permit smooth, easy adjustment. Has two button starter switch, and top quality ballast for quiet operation. 45" reach, 360° sweep. Includes "C" clamp mtg. bracket. Beautiful desert tan. U.L. listed.
 12 R 69588W Less bulbs. Shpg. wt., 10 lbs. Net 29.95
 12 R 10020 15 watt, cool white lamp. (2-required) Net ea. 1.39

FLUORESCENT MAGNIFYING LAMP

As Low As **22.95**

Designed for precision work. features a 5" diameter magnifying glass with a powerful 13" focus, surrounded by a 22 watt shadow-free fluorescent tube. A custom-engineered arm permits complete directional mobility—special adjustment knobs insure the proper tension and steadiness for any desired position. 45" arm reach. Ideal for assembly, laboratory, quality control and other detail work. In kit or assembled form. Shpg. wt., 7 lbs.
 12 R 69521W Kit, less lamp Net 22.95
 12 R 69539W Assembled less lamp Net 26.95
 T9, 22-watt, cool white lamp. Shpg. wt., 11 oz.
 12 R 75015 Net ea. 3.49




ALL PURPOSE LAMP

24.95

- Universal Joints
- Light at Any Angle
- Extends to 36"

Ideal for factory benches, tables and drafting boards. Two bolts clamp base securely to any surface up to 3" thick. Spring-controlled swivel joints and double arm action give you light in any desired position. Arm extends 36". Uses two T8, 15-W lamps. For 110-125V., 60 Hz. AC. Bronze finish. Shpg. wt., 9 1/2 lbs.
 12 R 10012W Less lamps. Shpg. wt., 9 lbs. Net 24.95
 T8, 15-watt, cool white lamp. Shpg. wt., 5 oz.
 12 R 10020 Net ea. 1.39



FLUORESCENT MAGNIFYING LAMP

24.95

- Flexible Gooseneck
- 5" Lens with 13" Focus

The perfect lamp for the hobbyist who needs plenty of light and magnification for close precision work. The flexible, goose-neck arm adjusts and holds the lamp in the position you want. Five inch diameter magnifying glass; overall length about 2 1/2 feet. Sturdy, clamp-mount base. Uses 22-watt circline fluorescent lamp.
 Less Lamp, Shpg. wt., 8 lbs.,
 12 R 10046 Net 24.95
 T9, 22-watt, cool white lamp. Shpg. wt., 11 oz.
 12 R 75015 Net 3.49




STUDY-LYTE CLAMP ON LAMP

As Low As **11.95**

- Spring Control
- Extends to 45"

Perfect illumination where you need it—moves up, down, sideways at your lightest touch, and stays exactly where you put it. From a central position, the 45" arm reach can swing to illuminate any area on a desk or table, six feet long and four feet wide. Sleek all-metal construction with versatile 3" throat edge clamp. Uses standard bulb (not included). Available in easy-to-assemble kit form or completely assembled. Kit. Shpg. wt., 4 lbs.
 12 R 69505W Net 11.95
 12 R 69513W Assembled Net 13.95



CLAMP-ON ALL PURPOSE LAMP

6.95

- 18" Flexible Arm
- 3-Way Mounting Clamp

Most adaptable clamp-on all purpose lamp with 18" flex arm with parabolic shade. Ideal for drafting, hobbies, machine tools and work bench. The entire lamp traverses an entire 360° with lock nut to maintain it in any fixed position. Reverse the clamp and you can screw it to the wall. The lamp shade on the inside is painted white enamel to give full reflection and a concentrated source of light where needed. For 75 watt lamp. Green color finish. Shpg. wt., 3 lbs.
 12 R 10087 Net 6.53




LAFAYETTE Wireless Remote Control

For Lamps, T.V., Hi-Fi, Household Appliances

- Turns Lights and Appliances On and Off From Anywhere In Your Home—By Remote Control!
- Simply Plug In and Operate! • A Lafayette Exclusive!



Only
14⁹⁵




Now you may turn on or off any electrical device from anywhere in your home or shop. The Lafayette wireless remote control requires no additional wires. Simply plug in your transmitter wherever you choose in the house, and the appliance, TV, hi-fi system or lights that are plugged in to the receiver will be turned off or on by pressing the button on the transmitter. Perfect for viewing TV or listening to hi-fi in bed. When you get sleepy press the switch and turn everything off. Safe! Simple remote switch of lights, lamps, radios, TV and appliances. Transmitter and Receiver operate on ordinary house current, receiver accepts any 105 to 120 volt device up to 300 watts. Imported. Shpg. wt., 1/2 lb.

Complete Transmitter & Receiving Unit	
99 R 91183	Net 14.95
Extra Transmitter Shpg. wt., 1/4 lbs.	
99 R 91787	Net 5.95
Extra Receiver Shpg. wt., 1/4 lbs.	
99 R 91225	Net 9.95

WIRELESS REMOTE CONTROL SWITCH



Teleswitch



ONLY
21⁹⁵

- Turn On and Off Lamps, Hi-Fi, TV, And Radios From Chair or Bed



Telewand

"Microsonic Beam" switches On/Off any appliance in the home. A touch of the button on the wireless transmitter switches TV, hi-fi, lamps, radios, fans or other electrical devices On/Off up to 40 feet away. Consists of a Teleswitch (miniature receiver), and a Telewand (miniature transmitter). Installs in seconds . . . just plug the AC cord from the appliance you wish to control into the Teleswitch socket, then plug the AC cord from the Teleswitch into any 110-120V., 60 Hz AC wall outlet. For use with up to 7.5 Amps. 860 Watts. Telewand operates on 9V battery. Shpg. wt., 14 oz.

12 R 87010	Net 21.95
99 R 60212 Battery for above.	Net .29
Extra Telewand for above less battery.	
12 R 87028 Shpg. wt., 1/4 lb.	Net 5.95

WHISTLE SWITCH

ONLY **13⁹⁵**


- The Amazing Electro-Sonic Switch That Turns Anything Electrical On or Off With a Whistle



Let Sound Command do the work. Turns radios, televisions, Hi-Fi, Lamps, outdoor light, On or Off while you relax in your chair or bed. No need to walk in darkness . . . turn on lights in a different room before you get there. Just blow the whistle and appliance immediately goes On or Off. WHISTLE SWITCH is plugged into any standard household outlet, then electrical appliance is plugged into WHISTLE SWITCH. Nothing further is required. 350-watt capacity. For 110 v 60 Hz AC.

12 R 78506 Shpg. wt., 10 oz.	Net 13.95
Extra Whistle for above	
12 R 78514	Net .89

AUTOMATIC PHOTO-ELECTRIC LIGHT CONTROL



ONLY **3⁹⁵**

- Automatic Light Switch
- Turns Lights On At Sunset Off At Sunrise

Automatically turns lights on at dusk and off at dawn. Helps to prevent burglary, vandalism, and accidents. Just attach to lamp cord and plug into wall socket for automatic light control. Responsive only to daylight . . . car lights, flashlights, or lightning will not operate unit. For 117V AC. 300 Watts. UL Listed. Shpg. wt., 3/4 lb.

12 R 28519	Net 3.95
------------	----------

LAFAYETTE 1000 WATT PHOTO-ELECTRIC LIGHT CONTROL

- Turns Lights On At Sunset Off At Sunrise
- Automatic Light Switch



Only **7⁵⁰**

Automatically switches on house, office, or store lights at sunset and off at sunrise. Great for vacation time, or daily use. No need to come home to a dark house at night. Helps keep burglars away. No special wiring necessary—just plug into wall socket and plug lamp into jack. 1000 watt capability permits use of several standard lights—will brilliantly light an entire house. Brass finish illuminator measures only 3" in diameter. Supplied with a 6 ft. cord. Wt., 3/4 lb.

12 R 01029	Net 7.50
------------	----------

AUTOMATIC OUTDOOR LIGHT CONTROL



- Turns Lights On At Dusk/Off At Dawn Automatically
- Easily Screws Into Fixture Socket

Helps prevent burglary . . . vandalism . . . accident by turning on all your outdoor lights at home, store, office, factory, signs, etc. Screws into any standard or floodlight socket. Compact, requires only 1 1/2" of additional clearance in fixture. Weather resistant. 300 watts. U.L. listed. Shpg. wt., 1 lb.

Only
3⁹⁵

12 R 28527	Net 3.95
------------	----------

PHOTO-ELECTRIC LIGHT CONTROL

- Easily Installs In Light Fixtures—Post Lanterns—Etc.

5⁹⁵



Now! Electronically protect your home in minutes . . . photo electronic "Lamp Litter" automatically turns lights On at dusk, Off at dawn. Easily installs in driveway post lanterns; yard lights around swimming pools, patios, and gardens; or, in expose mounted knockout type switch boxes. Built-in time delay prevents accidental switching from auto headlamps or fishing lights. UL component listed for 120 volts 800 watts maximum. Size: 1Hx1Wx2 1/4"D. Shpg. wt., 6 oz.

13 R 64504	Net 5.95
------------	----------

Electronic Dimmers—Electrical Accessories

ELECTRIC OUTLET CONTROL




- For Use in Home, Office, Industry
- Mount on Bench or Walls, or Keep Portable

5⁹⁵

If you need extra outlets, you need this Electric Outlet Control Center. Has six individual outlets with its own built-in fuse box. Finger-touch control on-off rocker switch with jeweled on-off indicator panel light. Heavy duty line cord for use in the home, office and industry too. Complete with mounting screws for permanent installation on wall or bench, or use it as a portable control center. For 110/120 VAC. 1500 watts, 15 amps. Less fuse. Imported. Shpg. wt., 1 1/4 lb.

14 R 21031 Net 5.95
Box of 5 15-amp fuses
13 R 11711 Net .55

DELUXE 6-STATION ELECTRIC OUTLET CONTROL CENTER



- 7 Individual Finger-Touch Rocker Power Switches
- 7 Individual "Signal-Glo" On/Off Indicator Lights

Provides six isolated, fused three prong "U" type grounded outlets. Convenient for home workshops, counter tops, etc. Mounts on wall, bench, floor, or remains portable. Each outlet utilizes a switch and indicator light. Built-in fuse compartment gives complete equipment protection. Entire fuse panel pulls out for easy, safe fuse changing. Rating: 15 amperes at 100-120 volts AC (1800 Watts). 6 ft. 3 cond. heavy-duty cord. Size: 10L x 6W x 1 1/4"D.

14 R 21106 Shpg. wt., 2 1/2 lbs. Net 15.95
13 R 11679 Pkg. of 5 Fuses Net .87

3 WAY POWER CONTROL



2⁹⁹

- Individually Switched Outlets With Indicator Lights

Switchable power outlet box for wall or bench mounting. Three individually controlled outlets, each with its own indicator light. Measures 4 x 2 1/2 x 1 1/4". Equipped with 3 polarized receptacles, 3 toggle switches, 3 indicator lights, 6 #L line cord. Rated 5 amps at 125 volts AC/DC. Imported. Shpg. wt., 1 lb.

99 R 90079 Net 2.99

FUSED POWER CONVENIENCE CENTER

ONLY

3⁹⁵

- Mounts Anywhere—Bench, Walls, Floor
- 6 Fused Outlets Anywhere



Lafayette's power control center adds six, fused convenient outlets anywhere you choose. Designed to mount on walls, floor, benches, counter tops or for portable use. On/Off rocker switches and panel mounted On/Off indicator light. Built-in fused holder with replaceable 15 amp. fuse. Heavy duty 8-foot line cord. For 120 volts AC, 1500 watts, 15 amps. With Fuse. Imported.

99 R 92890 Shpg. wt., 1 lb. Net 3.95
Pkg. of 5 fuses for above
13 R 11679 Net .87

POWER CONTROL OUTLET BOX



- Protective Circuit Breaker
- Six 3-Wire Outlets

Only
8⁵⁰

Designed to safely and conveniently deliver power to appliances, tools, lights, office equipment, etc. Easily mounted on wall, bench, floor, or kept portable. Six 3-wire "U" type grounded outlets controlled by one switch. Built-in circuit breaker protects equipment. Pilot light indicates when power is on. Rugged steel case. Rating: 100-120 V AC/DC @ 15 amperes. Size: 13 1/2 x 2 1/4 x 2".

12 R 15508 Shpg. wt., 2 lbs. Net 8.50

LAFAYETTE ELECTRIC BELL

2⁹⁵



Ideal as a fire alarm, burglar alarm warning bell. Gives a clear, loud ring to overcome high level background noise. Gleaming chrome-plated bell on a sturdy plastic base. 110 volts AC. Overall size, 4 1/4" across and 2 1/4" deep. Imported. Shpg. wt., 1 lb.

99 R 90235 Net 2.95

LAMP DIMMER

4⁹⁵

- Easily Screws Into Standard Lamp Socket



Solid-state lamp dimmer eliminates special wiring. Provides variable brightness to set a mood, TV viewing, etc. Turning lower section of dimmer selects light level from darkness to full bright. Lower intensity levels increase bulb life and reduce electricity cost. For 1 or 3-way bulbs up to 250 watts.

12 R 16506 Shpg. wt., 1/4 lb. Net 4.95

LAFAYETTE ELECTRONIC LIGHT DIMMER CONTROL

5⁹⁵

2 Year Guarantee




- Push-On—Push-Off Dial
- Full Range—Total Darkness To Full Brightness

Enjoy modern lighting in any room in your home or office. Soft light for TV viewing, bright light for reading or working. Easy to use, dimming is continuous from off to full illumination. Push on or off at any light level. Fits into standard single gang wall box without rewiring. Ivory plastic knob has brass finish insert. For 120 volts, 60 cycles AC. Operates incandescent lamps to 600 watt capacity. Highest quality—we will repair any defect due to material or workmanship within 2 years without charge. Simply ship to Lafayette prepaid. Shpg. wt., 1/2 lb.

12 R 01011 Net 5.95

600 WATT LIGHT DIMMER CONTROL

3⁹⁵



- Continuous Light Control From Dim To Full Brightness
- Replaces Any Ordinary Switch in Minutes

Convenient on/off dimmer control for use in living room, dining room, bedroom, family room, etc. Soft lighting for TV viewing and relaxing, bright light for reading and working. Easy to install in any standard wall box without complicated rewiring. Operates incandescent lamps to 600 watt capacity. Ivory plastic knob with brass finish insert. For 115 VAC, 60 Hz, Shpg. wt., 1 lb.

12 R 26513 Net 3.95

PORTABLE LAMP DIMMER

9⁹⁵

- Use With Any Incandescent Lamp



Dial the exact intensity of light desired. Create a light mood in any room in your home. Full-wave feature allows continuous dimming of any light load up to 350-watts. Efficient electronic circuit saves you money—pay only for the light you use. With cord and special plug/receptacle. For 120 VAC, Gold Color.

13 R 27568 Shpg. wt., 1 1/2 lbs. Net 9.95

Electrical Accessories

UNOER-CABINET FLUORESCENT LAMP



Only
4.95

• Complete with Bulb • Convenient AC Outlet
Ideal for shop or kitchen work centers. Can be mounted on the wall or under a shelf. Has white plastic diffuser, pushbutton switch, convenience outlet, cord and plug. With 15-watt bulb. White enamel finish. Size: 18 1/4 x 3 3/4 x 1 1/4" H. 2 3/4 lbs.

12 R 16050 Net 4.95
12 R 10020 Replacement Bulb. Shpg. wt., 5 oz. Net 1.39

MINI BREAKER




- UL Listed—Not A Fuse
- A True Circuit Breaker
- Don't Replace—Just Reset

Complete circuit protection—fits in standard Edison base fuse receptacle! Time delay for starting surges. Never needs replacing—just reset! Shpg. wt., 4 oz.


Stock No.	Amps	Net Each
12 R 70016	5	1.59
12 R 70024	10	1.59
12 R 70032	15	1.59
12 R 70040	20	1.59
12 R 70057	30	1.59

AC LINE CORD



6-ft. replacement for worn line cords in lamps, radios, small appliances, etc. Plug at one end; other end stripped and tinned. Shpg. wt., 4 oz.
12 R 39011 Net each .39

"THE WELCOME" ELECTRIC DOOR CHIME



Provincial White with Gold Leaf Trim

5.49

Contemporary design, blends well with any decor. Rich resonant tones; two-notes front door, one-note rear. Provincial white case, brushed brass plate and gold leaf trim. Installation instructions included. 4 3/4 x 7 1/4 x 2 3/8" D. Shpg. wt., 1 3/4 lbs.
12 R 48509 Net 5.49

CHIME ACCESSORIES



- (A) POLISHED BRASS LIGHTED PUSH BUTTON. Surface mount, equipped with miniature electric bulb. No special wiring required. 12 R 48525 For 6 to 16V. Wt., 4 oz. Net 1.69
- (B) "COLONIAL" LIGHTED PUSH BUTTON. Solid polished cast brass with lighted push button center. No special wiring required. 12 R 48533 Wt. 3 oz. Net 2.39
- (C) "QUICK MOUNT" SIGNAL TRANSFORMER for bells, buzzers, chimes. Thermal Switch prevents overload. Rated 16v., 10-W. 12 R 48541 UL listed. Wt., 13 oz. Net 3.19

PROGRESS CEILING or WALL FAN



Only
11.95 • Ideal for Bathroom, Utility or Recreation Room
• Attractive Aluminum Grille

Utility ventilating fan of compact design. Fits in "problem" areas such as shallow ceilings and partitions. Quiet operation with a big 6", four blade fan with 60 cfm capacity. Vents to standard 3" round duct, built-in plaster frame and outlet box. Has removable aluminum grille and automatic back-draft damper. Fits between 2"x4" studding. Size: 4x7 3/4 x 9". Shpg. wt., 6 3/4 lbs. UL Listed.

12 R 75551 Net 11.95

CORDOMATIC HANDY LIGHT

As Low As
9.95



- Retracts automatically

Provides light and power up to 20 feet from installation. Swivels 180° when wall mounted—360° when ceiling mounted. Detaches easily to change location. U.L. listed.

13 R 83025 Shpg. wt., 5 3/4 lbs. Net 9.95

3-Wire Lite. As above but with 3-wire cord and plug. Shpg. wt., 5 lbs.

13 R 83041 Net 11.95

CORDOMATIC PORTABLE OUTLET REEL



9.95

Cord pulls out to any desired length up to 15 feet... locks into position... automatically retracts when the reel is not in use. 3-way outlet operates several appliances at once. Case: 6 1/2" dia., 1 3/4" thick. 10 amps. Shpg. wt., 3 1/2 lbs.
13 R 83033 Net 9.95

INDOOR-OUTDOOR EXTENSION CORDS



- 2-Wire and 3-Wire, 16 Gauge 10 Amp
- Heavy-Duty Round Cord With Molded Connectors

Use indoors and out, with power tools, refrigerators, mowers, fans, etc. All are 16-gauge, 3 cond. cords have 3 prong plug. * 2-conductor † 3-conductor.

Stock No.	Feet	Shpg. Wt.	Net
12 R 25010*	25 ft.	2 lbs.	1.95
12 R 15011*	50 ft.	3 3/4 lbs.	3.29
12 R 34020*	100 ft.	6 3/4 lbs.	5.95
12 R 34038†	25 ft.	2 lbs.	3.19
12 R 25028†	50 ft.	3 3/4 lbs.	5.49
12 R 34046†	100 ft.	7 1/4 lbs.	8.95

TAP-A-LINE

As Low As **1.95**



A must for use in areas having a limited number of outlets. Permits the use of as many as 8 different appliances at one time. Easy to install or use unmounted. Rated at 1000 watts. Ivory colored tough plastic 12" long by 1" square. Four foot heavy cord and plug. Shpg. wt., 1/2 lb.
12 R 47014 Net 1.95
Same as above but 2 feet long.
12 R 47022 Net 3.19

VINYL PLASTIC ELECTRICAL TAPE



79c

- UL Listed
- 60 Ft. x 3/4"
- .008 in. Thick
- 10,000 V. Breakdown

First quality, pressure sensitive polyvinyl chloride tape. Extremely high dielectric strength of 10,000 breakdown. Insulation resistance of one million megohms. Over 150% elongation at break. Excellent resistance against acids, alkalis, oils, salt water, etc. Tensile strength of 15 lbs. per in. High conformability. Forms tight, smooth protective wrap. Imported. Shpg. wt., 6 oz.
99 R 80152 Net .79

LARGE PLASTIC TAPE KIT:

10 rolls of vinyl plastic tape. Each roll 33 ft. by 3/4". 1 ea. of Red, white, sky blue, blue, grey, yellow, brown, green, black and orange. Shpg. wt., 1 1/2 lbs.
99 R 80301 Net 2.89

DEARBORN CIRCUIT MONITOR



• A Must for Maintenance Men, Homeowners, Trailer Users, etc.
Detects faults instantly. Checks proper wiring of 3-wire outlets. Prevents dangerous shocks from the beginning, at your wall outlet. Indispensable for safe operation of appliances, power tools and office machines. Easily used by homeowners, service men and electricians, no meters necessary. Detects whether or not proper ground and AC polarity are available. Just plug into outlet, coded lights tell exactly what circuit condition is present: circuit OK, improper ground, improper neutral, reversed polarity, reversed ground and power, and power off.
12 R 73002 Shpg. wt., 1/2 lb. Net 5.95

REMOTE CONTROL

- For TV, Hi-Fi, Lamps, etc.



1.95

Turn any 110 volt appliance on and off without getting up from your chair or bed. Control your TV, radio, hi-fi, lamp, fan, appliance, movie projector, tape recorder, phonograph, etc. Nothing to connect—just plug it in. Easy fingertip control with handy in-out push switch. Long 15-foot cord makes it ideal for TV viewing when you're confined to bed. Imported. Capacity—750 watts. Shpg. wt., 1/2 lb.
14 R 21114 Net 1.95

Flashlights-Lanterns-Fire Extinguishers


BURGESS SAFARI LITE FLUORESCENT LIGHT SAFE—BRIGHT—

- AC or Battery Operation
- Hi-Lo Switch with batteries.

23⁹⁵

Efficient battery powered—weighs only a compact 9 lbs. yet delivers plenty of bright light for use in tents, trailers, boats, patios, etc. Especially useful during emergencies. Two light levels are provided for brilliant or low intensity illumination. Operates on batteries for only pennies per hour. Built-in 110 volt circuit permits use with standard AC current. Attractive polystyrene case and handle complemented with gleaming stainless steel trim. Size: 12 $\frac{3}{4}$ "x4 $\frac{1}{2}$ "x7 $\frac{3}{4}$ "D.

13 R 80567 Shpg. wt., 1 $\frac{1}{4}$ lbs. Net 23.95
Extra batteries for above (2 required). Wt., 3 $\frac{3}{4}$ lbs.
32 R 47764 Net 1.55
12 R 10079 FBT5CW Replacement Bulb



GARLAND RECHARGEABLE DELUXE SPORTSTER LANTERN

26⁹⁵

- Sealed Beam Light
- Powerful 13,000 Candle Power



Never buy batteries again with this smartly styled rechargeable sportsman's lantern. Portable sealed beam rechargeable lantern for camping, boating, car or home use. 13,000 candle power. Adjustable carrying handle also converts to stand. For easy recharging, cord plugs into 110V AC outlet or lantern charges on 12V car or boat battery. Features an adjustable handle that locks in any position. Handsomely finished in navy blue with silver trim. Operates on nickel cadmium batteries with 110 VAC built-in charger. Size: 3 $\frac{3}{4}$ "x5 $\frac{1}{4}$ "x4 $\frac{1}{2}$ "

Shpg. wt., 2 lbs. Net 26.95
14 R 14531

KIODE 2 $\frac{1}{4}$ LB. DRY CHEMICAL FIRE EXTINGUISHER

- Rated 6 B:C Coast Guard, ICC, and UL Listed

9⁹⁵

Extinguishes flammable liquids, grease and electrical fires. Powerful 2 $\frac{1}{4}$ lb. pressurized extinguisher meets marine and other requirements; Easy one-hand operation. Built-in pressure indicator can be read at a glance. Non-toxic dry chemical won't injure fabrics, etc. Tamper-proof lock. Meets Coast Guard and ICC specifications. UL listed. Rated 6 B.C. Corrosion resistant construction. 14H x 3" diam. Shpg. wt., 5 lbs.

13 R 45040 Net 9.95
DISPOSABLE RECHARGE CYLINDER: Recharges extinguisher in minutes. Shpg. wt., 4 $\frac{3}{4}$ lbs.
13 R 45057 Net 5.95



DELUXE RECHARGEABLE FLASHLIGHT

Slim, handsomely styled, flashlight with strong spotlight beam. Never needs batteries. Works on two long-lasting nickel cadmium power cells. Just remove cap and plug into any 110V AC wall outlet for a few hours. Smartly sized, tapered body fits in purse, travel bag or brief case. Length 5 $\frac{1}{2}$ "; lens diameter 2 $\frac{1}{4}$ ". Shpg. wt., 8 oz.

12 R 64043 Net 6.95
32 R 66038 PR-4 Repl. Bulb Net 2.5

"SUPER POWER"

SEALED BEAM SEARCHLIGHT

- For Campers, Truckers, Hunters

Deluxe, all purpose searchlight with long range GE 4546 sealed beam. Penetrates heavy fog and the darkest nights. Operates on 4 "D" batteries. Chrome finish. Shpg. wt., 1 $\frac{1}{2}$ lbs.

12 R 64084 Net 4.95
Batteries for above. (4 required.)
99 R 62564 Net ea. 1.8

DELUXE POWERHEAD LANTERN WITH EVEREADY BATTERY

Extra large power beam from huge bright chrome 4 $\frac{3}{4}$ " head. For motorists, home owners, sportsmen, campers. 6-position warning blinker arm telescopes into contour handle. Separate switches; gleaming chrome, sturdy steel construction. With bulbs and 6 volt battery. Shpg. wt., 5 $\frac{3}{4}$ lbs.

12 R 64092 Net 6.95

GARLAND "STANDBY" LIGHT

Plugs into any ordinary AC outlet. When electricity fails the "standby" goes on illuminating its area with a powerful beam. Eliminates many problems encountered because of sudden darkness. Powered by rechargeable nickel-cadmium batteries. "Standby" incorporates its own built-in recharger. Always ready for emergencies. You never buy batteries again. May be used as an extra powerful flashlight when and where you need it. Shpg. wt. $\frac{3}{4}$ lb.

14 R 14515 Net 13.95

FLEXIBLE NECK INSPECTION LIGHT

For use in any position. Perfect for hard to see areas in servicing TV's, Hi-Fi's, Auto and household appliances. Battery powered, with flexible chrome-plated neck and high intensity light beam, that puts the light where you want it. Durable plastic case with handy metal loop for hanging. Uses 2 "C" cells. Complete with extra bulb. Imported. Shpg. wt., $\frac{1}{2}$ lb.

13 R 27501 Net 3.29

Batteries for above (2 Req.)
99 R 62572 Net 1.15



JET ACTION HYDRO-PUMP FIRE EXTINGUISHER

- For Auto, Home, Boat
- With Wall Bracket



Extinguishes oil and grease fires, chemical fires electrical fires, wood, paper, and plastic fires. Chemically smothers fires in seconds that water cannot control. Just aim and pump. Put a unit wherever a fire is likely to start. Keep one ready in your kitchen, basement, bedrooms, and car. Complete with "Quick-Disengage" wall mounting bracket and hardware. Imported. Shpg. wt., 1 $\frac{3}{4}$ lbs.

14 R 21064 Net 2.95

2⁹⁵



SMOKE AND HEAT DETECTOR


29⁹⁵

- Photo-Electric Cell Operates as a Radar Beam to "See" and Detect 2% to 4% Smoke Obscurity
- A Powerful Buzzer Built-in Unit

The Model SM-5 Smoke and Heat Detector contains an automatic smoke detector, automatic fire alarm sensor, and a powerful buzzer. Ideal for home, business, office. This alarm unit protects by "seeing" smoke and "feeling" heat or fire in its earliest stages and sounding the powerful buzzer. Completely transistorized. Indicator light has a 70,000 hour life. It "feels" (senses) heat at 135°F. Operates on less than 3 cents of electricity per month. Size: 4 $\frac{1}{4}$ " x 4 $\frac{3}{4}$ " x 2 $\frac{1}{2}$ ". For 110-120 VAC or 220-240 VAC. Shpg. wt., 1 $\frac{1}{4}$ lbs.
14 R 13517 No Money Down* Net 29.95



LAFAYETTE Techni-Timer



ONLY
7⁹⁵

- Makes Any Lamp or Appliance Completely Automatic
- Turns Lights On and Off When You're Away—Discourage Prowlers
- No Special Wiring—Just Plug In
- Handles Loads Up To 1875 Watts
- Can Be Set To Skip-A-Day • 1 Year Guarantee

The Lafayette Techni-Timer makes practically everything electrical automatic. Turns radios on and off. Does not have to be reset each night. Defrosts refrigerator, controls roaster, electric blanket, fans, coffee-makers, phonographs, etc. Turns your home lights on and off automatically while you're away. Repeats cycle every 24 hours—no need to reset. Minimum ON time 15 minutes, maximum ON time, 23-hours. Minimum OFF time 1-hour, max. OFF time, 23-hours 45 minutes. Easy-to read- 24-hour dial. Can be set to skip-a-

day operation and, controlled manually without automatic reset. Attractive design. For shelf, table or wall mounting. With 6 ft. cord, plug and receptacle for equipment to be controlled. Highest quality—we will repair any defect due to material or workmanship within 1 year without charge. Simply ship timer to Lafayette prepaid. 5Wx4Hz2 1/4"D. Capacity 15 amps., 1875 watts, 125v., 60Hz. UL/CSA listed. Shpg. wt., 1 1/4 lbs.

13 R 01407 Net ea. 7.95

LAFAYETTE PLUG-IN 24-HOUR TIMER

Automatically Turns Lights On and Off When You Are Away



Only **5⁹⁵**

- Handles Up To 875 Watts
- Gives Your Home A "Lived-In" Look . . .
- Discourages Prowlers
- No Wiring Required

A compact cordless convenience . . . plugs directly into wall socket. Finger-tip control allows you to set and forget it. Once desired "on and off" times are set, plug in lamp, radio, or fan, etc.—up to 875 Watts and the automatic timer takes over. Resets automatically. Maximum "on" time—2 1/2 hours; minimum "on" time—2 1/2 hours. Highest

quality—we will repair any defect due to material or workmanship within 1 year without charge. Simply ship timer to Lafayette prepaid. Capacity: 7 Amps, 875 Watts—125V, 60 Hz. AC. UL/CSA Listed. Size: 2 3/4" x 3 3/4" x 1 1/4". Shpg. wt., 2 lbs.

13 R 01688 Net 5.95

Intermatic TIME-ALL

- Turn Lights and Appliances On and Off Automatically

Finger-tip control plus angled face for easy access and viewing. Attractive, walnut grain panel with champagne white case goes with any decor. Wake up with music, TV, or even fresh coffee, start air-conditioners before you arrive home. Can also be used to defrost refrigerator. Does not have to be reset each night. Easy-to-read AM and PM dial for full 24 hour period. Can be controlled manually. Plug-in receptacle for equipment to be controlled. Minimum "ON" time: 15 min. Maximum "OFF" time: 23 hr. 45 min. Capacity: 15 Amps, 1875 Watts. For 125V, 60 Hz with 5 ft. cord, plug and instructions. Size: 3 1/2" x 4 1/2" x 3 1/2". UL listed and CSA approved. Shpg. wt., 1 1/2 lbs.

• 1875 Watt Model

13 R 27584 Net 9.77

13 R 27584

Intermatic IN-WALL TIME-ALL®

9⁹⁵

- Fits into Existing Wall Outlet or Wall Switch Box

Smartly styled wall timer with finger-tip control. Installs easily in standard, single outlet wall box. Automatically controls air conditioners, lamps, radios, coffee makers, and any other plug-in appliance. Can also be used for wall switch operation to control porch and post lights. Resets automatically, 1 timed AC outlet and 1 AC outlet completely independent of timer. May also be used manually. Minimum "ON" time: 15 min. Maximum "OFF" time: 23 hr. 45 min. Capacity: 15 amps. 125 volts, 60 Hz. Compact, only 1 1/4" above wall.

13 R 27576 Pearl white housing. Shpg. wt., 1 1/2 lbs. Net 9.95

WESTCLOX 24 HOUR CLOCK AND SWITCH TIMER

12⁹⁵

- Turns Lights, Appliances On and Off

Beautiful electric clock/timer makes any appliance completely automatic while serving as a timepiece, complete with a sweep second hand. Just plug the appliance into the timer and plug the timer into the wall outlet for instant operation. Will repeat one on-off cycle per day without resetting or may be manually switched. Unlimited applications! Handsomely styled wood tone case with gold color spun aluminum dial. Handles appliances up to 1800 watts (15 amperes). For 117 VAC. UL Listed. Shpg. wt., 2 lbs.

13 R 56500

Net 12.95

PARAGON® TIMITE® MINIATURE 24-HOUR TIMER

- Installs in Wall Switch box.
- Automatically Turns on Night Lights—Yard Lights, etc.

9⁹⁵

MODEL 101 compact time control ideal for window displays, night lights, yard lights, etc. Provides one on-off operation per day with minimum setting of two hours. Has manual trip lever. 24-hour dial is divided into 30 minute segments for easy, accurate setting. Fits over a U.S. standard single gang handy box. Size 4 1/2" x 2 3/4" x 3 1/4" D. Capacity: 15 amp. non-ind., 1800W, 1 HP. 12 am., full load. For 120V., 60 Hz. UL and CSA Listed.

13 R 17510 Shpg. wt., 1 1/4 lbs. Net 9.95



Precision Timers for Home and Industry

LAFAYETTE TV TIMER CONTROL



Only **4⁹⁵**

- Simple to Use—Just Plug In
- 500 Watt Capacity with 15' Cord

Now you can fall asleep while TV is still on! No need to wake up and turn it off—the TV Timer Control turns off your TV set automatically. Simply plug the TV into the Timer Control, and the Timer Control into the wall outlet. Then turn the dial to choose the automatic "turn-off" time—from 5 minutes to one hour. The 500-watt capacity makes it ideal for use with most other household appliances—radio, hi-fi, tape recorder, lamp, patio light, electric blanket, heating pad, hair dryer, etc. With 15' cord. Imported. Shpg. wt., 1 lb.

99 R 80798

Net 4.95

AUTOMATIC PORTABLE AIR CONDITIONER TIME SWITCH



- Come Home to Cool Comfort
- With 5 ft. 3-wire Cord and Ground Receptacle

Turns air conditioners ON and OFF automatically without costly installation. 24 hour cycle with minimum setting of 2 hours between ON and OFF operation. Capacity: 12 amps full load at 120VAC. Beige case. Size: 2½x4½x2¾" D.

13 R 17577 Model AC1-0, 120V Wt., 2¼ lbs. Net 10.95

13 R 17585 Model AC-4-20, 208-240 V Net 11.95

5-HOUR "RINGER TIMER"



6⁵⁰

- Portable "Alarm Type" Timer
- Rings From 1 Minute to 5 Hours

An indispensable aid for your everyday timing needs—cooking, photography, phone calls, etc. Loud long-ringing bell signals the end of the preset time period. Has an easy-to-read, crystal covered black dial with bold white numerals, gold hour dividers, and a red dial window to show the hours from 1 to 5. Housed in an attractively styled high-impact white plastic case. From England. Shpg. wt., ¾ lb. 13 R 13501 Net 6.50

SWISS POCKET TIMER

- Set It and Forget It
- Buzzes at Any Pre-Set Time up to 120 Minutes



Avoid parking tickets, late appointments, etc. Also use as a timer on phone calls, cooking, photography, etc. The 120-minute dial is marked in 5 minute intervals. To operate, just set the dial to the time wanted and the buzzer will sound off when the pre-selected time has elapsed. With handy key chain. Shpg. wt., ¼ lb.

13 R 31115L

Net 5.95

INTERMATIC TIMING MOTOR



Self-starting synchronous motor with lifetime lubrication. Geared to 4 clockwise revolutions per hour. Will retain constant speed even under fine voltage variations of 25%. Torque load 5 oz. in. maximum. Shaft ¼" x ½" dia. For 110-120 volt 60 Hz AC. Shpg. wt., 7 oz.

13 R 27246 Intermatic W-160 Net 4.50

RHODES MARK-TIME SWITCHES

A TIMED EXTENSION CORD

- For Hi-Fi TV, Fan

And Other Small Appliances

An automatic time switch, extension cord, convenient outlet. Timing range up to 4 hours, with manual "Hold" feature. Easy to operate—plug it into any wall outlet, connect one, two or three devices to be controlled, and turn the knob to the time period desired. At the end of time period, the electricity is turned off automatically. 6-foot cord. 10 amps.-120 VAC, U.L. listed, wt., 1 lb.

13 R 85012

Net 5.99

B FOR WALL BOX INSTALLATION

A dependable and versatile time switch to automatically turn off attic fans, porch and garage lights, window lights, heating units, etc. at any preset time. Has special HOLD feature! turn of knob cuts out timing mechanism and allows unit to be used as a regular toggle switch. Capacity 20 amps, 125 volts AC, U.L., CSA listed, Satin-chrome dial 4½x3" W; switch 2½x1¼x1¼" D. Fits any standard rectangular wall box. wt., 1 lb.

MODEL 90024—time range up to 1 hr.

13 R 85020 Net 5.99

Model 90015—to 12 hours, wt. ¾ lb.

13 R 85038 Net 5.99

C PHOTOGRAPHIC TIME SWITCH

It's easy to control accurate timing on photographic developers, enlargers, and photo copy equipment by plugging them into the convenience outlet on this inexpensive unit. Adjustable stop makes repeated settings—even in total darkness—easy and foolproof. Times up to 60 seconds, then automatically shuts off current. May also be used as "on-off" switch when timing is unnecessary. Rated 15 amps—125 volts—A.C. UL and CSA listed. Shpg. wt., 1½ lbs.

13 R 85046 Model 78174 Net 7.88



D BUILT-IN INDUSTRIAL TIME SWITCH

Easily panel mounted or installed in a 4" octagon switch box using the adapter plate. May be used in conjunction with thermostats to time control zone heated areas. Versatile SPDT construction permits switch to be wired for either "on" or "off" type operation. Rated at 20 amps, 125V/240V AC. UL and CSA listed. ¾ lb.

13 R 85079 15 min. Net 6.56

13 R 85087 30 min. Net 6.56

13 R 85103 60 min. Net 6.56

ADAPTER FOR 4" Octagon Switch Box

13 R 85095 Shpg. wt., 8 oz. Net .39

E 2-SPEED PRECISION TIMER

- For Precise 1 Second To 1 Hour Timing In The Home, Office and Laboratory

Indispensable for timing precise, short operations such as boiling eggs, pressure cooking, heat and sun lamp treatment, home permanents, photo developing and printing, long distance calls, etc. Times up to 6 minutes in seconds and up to 1 hour in minutes. Exclusive 2-speed feature permits instant timing speed change by flick of a lever. A bell sounds at end of timing period. Smartly styled in white with dial face a rich copper tone. 4 x 2½". Shpg. wt., 1 lb.

13 R 85053 Model 2130 Net 5.33

F UTILITY HOUSEHOLD TIMER

This reliable, low-priced timer in a neat durable white plastic case, has innumerable household timing uses, i.e., cooking, baking, home permanents, games, remembering appointments, TV and radio programs, etc. Times any interval up to one hour accurately and gives resonant bell signal at end of period. 3½ x 3 x 1½". Shpg. wt., ¾ lb.

13 R 85061 Model 29001 Net 3.25

To Speed Your Mail Order—Please Give Your Zip Code Number

Lafayette Cat. No. 720 319

Intermatic

Time Controls — Clock Timer



PORTABLE INTERVAL TIMER

- Control Operating Time of Household Appliances
- Time Range: 0-60 Minutes
- Minimum Setting: 1 Minute

MODEL PT-301 Easy-to-use—just plug timer into outlet, connect appliance and set the large easy-to-read dial to the desired operating time. Appliance begins operation immediately and stops at pre-set time. White case with walnut trim. For 120 volts 60 Hz, AC only, 1875 watts max. UL listed. Size: 5W x 4H x 3"D. 13 R 27535 Shpg. wt., 1 lb. Net 7.95

MODEL PT-304 Similar to above but 0-24 hours. Minimum setting 1/2 hour. 13 R 27543 Shpg. wt., 1 lb. Net 7.95




ELECTRIC CLOCK AND APPLIANCE TIMER

9 95

- Tells time and turns appliances on and off

Model A-401-4 not only tells time, but turns appliances both on and off automatically for periods of 15 minutes to 5 1/2 hours. Cooks dinner while you're away, wakes you to music, controls electric fans, heaters, radios, TV sets, etc. No installation problem—just plug it in and set. Capacity 1875 watts. Special alloy "T." Plaskon case 4 3/4x4 1/2x2 1/4"D. 6 ft. cord. For 110V 60 Hz. U/L Listed. Shpg. wt., 2 1/4 lbs. 13 R 27170 Net 9.95



TYPE T101 TIME SWITCH

Turns equipment "on" and "off" once in 24 hours, or from 1-12 "on" and "off" operations a day can be obtained by use of extra trippers—can be added without removing dial. Min. on or off time 1 hr., max. 23 hours. Can be turned on or off manually with reset SPST switch rated at 40 amps, 4375 watt capacity. Mounting holes and knockouts. Gray steel case. U/L Listed. Operates on 110 volt 60 Hz AC. 7 3/4x5Wx3"D. Shpg. wt., 3 1/4 lbs. 13 R 27022 Net 11.34
 TYPE T103. Same as above, but with DPST switch. 13 R 27600 Net 12.64

TYPE P101. Similar to T101 except but with 6 ft. cord set and receptacle. Capacity 1250 watts. Shpg. wt., 3 1/2 lbs. 13 R 27030 Net 12.64

TYPE P101-300. Same as P101 but with 3-wire cord set and receptacle. Recommended for Air Conditioners. Shpg. wt., 3 3/4 lbs. 13 R 27295 Net ea. 13.94

"SKIPPER" TIME SWITCH

Automatically turns equipment on or off skips operations on any selected days. Ideal where offices or factories are closed on Saturdays, Sundays or Holidays. Turns "on and off" once every 24 hours with single set of trippers supplied, but up to 11 on and off operations can be had by adding extra trippers below. With 3 skipping screws; more can be added. 1 cut out tripper advances day dial automatically. Min. on or off time 1 hour, maximum 23 hours. Cap. 4000 watts. 7 3/4x5x3". U/L Listed. Shpg. wt., 4 lbs. For 110-120V 60 Hz AC. SPST—Skips "ON" operation. Shpg. wt., 3 3/4 lbs. 13 R 27063 Net 14.59
 Type T175 — SPDT. Opens one circuit and closes another. Skips either "ON" or "OFF" operation. Shpg. wt., 3 3/4 lbs. 13 R 27071 Net 15.89
 Type P171 — Portable Plug-in version of Type T171. Capacity 1250 watts (contacts 10 amps). Shpg. wt., 3 3/4 lbs. 13 R 27089 Net 15.89

TYPE C-8301-S CYCLER TIMER

Up to 12 sets of ON-OFF trippers provide repeated operations. ON operations may range from 10 sec. to 11 min., 10 sec.; OFF from 50 sec. to 11 min., 50 sec. Dial makes complete revolution every 12 minutes. Ideal for ventilating fans, pumps, process timings, etc. SPST, rated at 15 amp. For 110-125V, 60 Hz AC. U/L Listed. Case 6 1/2x5x3" with 2 comb knockouts on bottom. 13 R 27188 Shpg. wt., 2 3/4 lbs. Net 11.67
 EXTRA SET ON-OFF TRIPPERS FOR C-8301-S 13 R 27196 Shpg. wt., 2 oz. Net .72

PROGRAM TIMERS

1-96 OPERATIONS EVERY 24 HOURS

TYPE T-1905. Designed for applications requiring many ON-OFF operations. Can be set for as many as 48 ON and 48 OFF operations during any 24-hour period. Minimum "ON" or "OFF" period is 15 minutes; maximum is 23 hours 45 minutes. Ideal for control of heating, air-conditioning, ventilating, etc. Has SPDT switch. Contacts rated to handle 20 amps at 125 volts; For 105-125 V; 60 Hz AC. U/L Listed. 7 3/4x5x3". Shpg. wt., 3 3/4 lbs. 13 R 27139 Net 22.07
 TYPE T1975. Same as T1905 above, but has "Skipper" feature for omitting operations on selected days. Shpg. wt., 3 3/4 lbs. 13 R 27360 Net ea. 25.32
 TYPE P1971. Portable Plug-in version of Type 1975. Contacts rated 10 amps at 125 volts — 60 Hz AC. Shpg. wt., 3 1/2 lbs. 13 R 27147 Net 27.59

7 DAY PROGRAM TIMER

Provides a different program each day of the week, with up to 4 on-off operations per day. 3-hour minimum between operations. 4PST rated 20 amps. per pole. 110-125V 60 Hz AC. Steel case, 10 7/8x7 3/8x3 3/8". Grey finish. 1/2" 3/4" knockouts. 7 sets of trippers. U/L Listed. Shpg. wt., 6 3/4 lbs. Type V26001. 13 R 27337 Net ea. 25.64
 TYPE V26003. As above, but 4P; 2NO-2NC. Rated 40 amps. per pole. 13 R 27345 Net ea. 25.64
 Set ON-OFF (1 ea.) trippers for either above. 13 R 27352 Shpg. wt., 2 oz. Net .50

TYPE T185 TIME SWITCH

For applications where multiple "on-off" cycles of 5 to 60 minutes are required in a 24 hr. period. A minute selector on each specially designed tripper sets the number of minutes, (5 to 60), the "on-off" cycle will operate. Up to 12 combinations can be used at the same time. Minimum interval between start of each cycle, 1 3/4 hrs. rated 40 amps, 4375 watts, 125 volts, AC. 7 3/4x5x3". With 3 trippers (for 2 "on-off" Hz). For 110-125 volts, 60 Hz AC. U/L Listed. Shpg. wt., 3 3/4 lbs. 13 R 27048 Net 14.92
 Extra Trippers for above. One Tripper for each additional "on-off" cycles. Wt., 4 oz. 13 R 27055 Net 1.95

"SKIPPER" 3 CIRCUIT SPRINKLER TIMER

THE INTERMATIC lawn sprinkling system time controls permit completely automatic pre-programmed watering of up to 3 zones. A 24 hour time dial can be set to initiate sprinkling any time during the day while skipper wheels serve to eliminate watering on selected days. Time durations per area are adjustable from 5 to 60 minutes. May be manually operated. Rated at 120 volts. 60 Hz, 5 amps. Gray hammertone case measuring 7 3/4x5x3". U/L Listed. Shpg. wt., 3 3/4 lbs. TYPE LS-7041 14 DAY SKIPPER 13 R 27592 Net 18.17

SWITCH ACCESSORIES

TRIPPERS—Set of ON-OFF units (one for each) for all models except T185, C8301S, T1905, P1971, T1975 and Sprinkler Timer. Shpg. wt., 3 oz. 13 R 27097 per set Net .50
 COMB. ON-CUTOUT TRIPPER. For "Skipper" types only. 13 R 27105 Shpg. wt., 3 oz. Net .50
 SKIPPING SCREW. For "Skipper" types only. 13 R 27113 Shpg. wt., 2 oz. Net .08

MINI-CYCLE and FUNKART

Fun For The Whole Family

DELUXE 3 HP MINI-CYCLE †

- A Breakthrough in Minibike Design
- Features Variable Speed Torque Converter

A new concept in minibikes. Features 3 H.P. Tecumseh engine, single loop heavy gauge 1½" steel frame, chrome plated handlebars, rear shock absorbers, remote gas tank, Chrome wire wheels with sealed ball bearings and 17" diameter "motorcycle" knobby tires. A rugged, variable speed torque converter transmission with 13:1 to 4:1 ratio and new "cyclocat" torque converter protective cover; motorcycle roller chain. Rear internal expansion brake system with 5" aluminum drum. "Motorcycle" type twist throttle control; full kickstand and footrest. Handlebar mounted engine "stop" button. Metallic paint finish with oversized seat, 41" Wheel Base, 56" Overall, 25" Width; 7½" Ground Clearance. Shpg. wt., 105 lbs.

- 13 R 68596XZ see note below Net 239.95
 4 H.P. MINICYCLE—SIMILAR TO ABOVE. Shpg. wt., 110 lbs.
 13 R 68604XZ see note below Net 279.95

"FUNKART" WITH 3 HP SILVER STREAK ENGINE †

This "Funkart" is where it's at! Heavy gauge cold-rolled steel tubular frame—Argon Sigma welded. All steel full width hub wheels with sealed ball bearings and all steel fully automatic clutch. Vinyl coated control cable clamps and aircraft type vibration-proof hardware assure lasting performance. Tecumseh Silver Streak industrial engine is rated at 3 H.P. Rack steering with chrome steel "mag" steering wheel, control pedals, control rods, "nerf bars", and tie rods. Steel mini chainguard. Adjustable dual friction brakes. 62" Overall, 49½" Wheelbase, 36½" Width, 4" Road Clearance. Bright Metallic Blue with Vinyl Upholstery. Shpg. wt., 135 lbs.
 13 R 68612XZ see note below. No Money Down*..... Net 219.95

AS LOW AS
239⁹⁵
 No Money Down*



219⁹⁵

**NOT FOR USE ON
 PUBLIC ROADS,
 STREETS, OR
 HIGHWAYS**

MINICYCLE AND FUNKART SHIPPED F.O.B. HACKENSACK, N. J.
 NO C.O.D. SHIPPING CHARGES COLLECTED ON DELIVERY
 SEND FULL REMITTANCE, OR USE LAFAYETTE'S EASY PAY PLAN*

FRIDGETTE COMPACT REFRIGERATORS



119⁹⁵

5.5 CU. FT. REFRIGERATOR

MODEL BAR-5F small refrigerator for apartment, home, or office. Walnut grain laminate plastic top and front, copper-tone sides and chrome trim. Deluxe features: 2 removable, adjustable chrome shelves, 1 heavy duty chrome trimmed glass shelf, full sized across-the-top freezer, adjustable thermostat, large tinted crispers, in-door storage racks, magnetic door catch. Hermetically sealed compressor unit. Interior light. Imported. For 110 VAC, 60 Hz, 34Hx20Wx23"D.

- 13 R 32790XZ Wt., 115 lbs. Net 119.95
 Similar to above, laminated top only standard interior, white finish. Shpg. wt., 115 lbs.
 13 R 32800XZ No Money Down* Net 104.95
 MODEL FRZ-55 5.5 CU. FT. FREEZER ONLY Holds up to 195 lbs. frozen food. Appearance similar to BAR-5F above.
 13 R 32824XZ Wt., 87 lbs. Net 149.95



74⁹⁵

2.2 CU. FT. COMPACT REFRIGERATOR

Compact refrigerator holds 2.2 cu. ft. (including freezer). Ideal for small apartments, campers, or boats. Freezer accommodates 2 ice cube trays. Features in-door storage rack and egg holder; 2 deep, removable adjustable shelves; hermetically sealed compressor unit; and 7-position thermostat and magnetic door catch. White finish. Operates on 110 VAC, 60 Hz. Imported. Size: 18Hx19½Wx18"D. Shpg. wt., 65 lbs.
 No Money Down*

- 13 R 32766XZ Net 74.95
 Similar to above in copper-tone finish.
 13 R 32774XZ Net 79.95
 14" walnut legs for both of above (4).
 13 R 32782XZ Shpg. wt., 2 lbs. Net 4.95



74⁹⁵

COMPACT PORTABLE REFRIGERATOR

- Works On Both 110 Volts AC and 12 Volts DC

Lightweight .62 cubic foot portable refrigerator perfect for use in autos, trailers, boats, or on picnics. Interior measures 12"x6"x10" and features an all white porcelain body. Plugs into cigarette lighter or AC outlet. Stores all types of food with the convenience of a home refrigerator. Ice tray for making ice on AC. Quiet operating absorption system, no disturbing compressors or motors. Fits almost anywhere. Outside dimensions are 14½Wx12½Dx13"H. High Impact housing, complementary blue top. With AC and DC power cords and ice tray. Shpg. wt., 23 lbs.
 13 R 32816W No Money Down* Net 74.95

2.2 and 5.5 Cu. Ft. Models Shipped FOB Newark, N.J. No C.O.D. Send Full Remittance Or Use LAFAYETTE'S EASY PAY PLAN*. Shipping Charges Collected On Delivery.

*See Page 22 for Full Credit Details on Easy Pay Plan

SPECIALTY SWISS WATCHES



Digital Calendar Wrist Watch

- Gives You The Hour, Minute And Date At A Glance
- Sweep Second Hand
- Shock Resistant

Digital watch shows hour, minute, and date in large, easy-to-read red and blue numerals. Great for anyone who must account for time at a glance . . . pilots, rally drivers, etc. Striking dial features sweep second hand and incorporates an automatic calendar. Precision anti-magnetic Swiss movement has unbreakable mainspring. Beautiful gold tone finish case with genuine lizard strap. Imported. Shpg. wt., 14 oz.
13 R 31362L Net 14.95

14⁹⁵



Self Winding 17 Jewel Day and Date Calendar Watch

- Shows The Day And Date At A Glance
- Shock Resistant

Deluxe self winding Swiss crafted watch automatically indicates the day of the week and the date. Precision 17 jewel movement is water resistant, anti-magnetic and features an unbreakable main spring. Handsome 10 micron gold filled case with stainless steel back. Complete with a genuine lizard band. Raised gilt numerals on white face dial with sweep second hand. Shpg. wt., 8 oz.
13 R 31412L Net 29.95

29⁹⁵

Double Button Chronograph Watch

- Shock Resistant

Superb Swiss made chronograph serves six timing functions in addition to telling time. Can be used as a tachometer for measuring speed, a telemeter for measuring the distance of sound, an elapsed timer for sports events and scientific experiments, a parking timer, a production timer, and a stop watch with a 30 minute register. Precision movement is shock resistant, water resistant, anti-magnetic, and has an unbreakable mainspring. Sweep second hand. Luminous dial and hands. Chrome case with stainless steel back. Complete with stainless steel band. Shpg. wt., 13 oz.
13 R 31420L Net 17.95



17⁹⁵

Deluxe 17 Jewel Double-Button Chronograph Watch

- Shock Resistant

Precision made 17 jewel Swiss chronograph is ideally suited for accurate elapsed timing of sporting events, scientific experiments, etc. Features a tachometer for measuring speed, a telemeter for measuring the distance of sound and a stop watch with a 45 minute register and a sweep second hand. Accurate, dependable movement features an unbreakable mainspring. Water resistant, dustproof and anti-magnetic. Bright chrome case with a stainless steel back, raised numerals, and a genuine leather strap. Shpg. wt., 13 oz.
13 R 31131L Net 36.95



36⁹⁵
 No Money Down*



Wrist Alarm Watch

- Automatic Reminder Anytime—Anywhere
- Shock Resistant

Handy Swiss made wrist alarm watch that never lets you forget appointments, parking meters, cooking, etc. Features an unbreakable mainspring for long trouble-free wear. Anti-magnetic. Smartly styled gold tone case, with stainless steel back, has a luminous dial and hands for easy night reading. Sweep second hand on attractive dial face with gilt numerals and markings. Complete with a genuine lizard strap. Shpg. wt., 8 oz.
13 R 31438L Net 14.95

14⁹⁵




Deluxe 17 Jewel Calendar Wrist Alarm Watch

- Automatic Reminder Anytime—Anywhere
- Shock Resistant


Swiss made wrist alarm serves as an automatic reminder and daily calendar. 17 jewel movement is water resistant, anti-magnetic and features an unbreakable mainspring. Radium dial. Dial has raised gilt numerals on a white face with a sweep second hand. Gold filled case with stainless back or all stainless steel. Genuine lizard band. Shpg. wt., 14 oz.
Stainless Steel Case
13 R 31396L Net 37.95
Gold Tone Case
13 R 31404L Net 37.95

37⁹⁵
 No Money Down*

PRECISION SWISS STOP WATCHES



As low as
11⁹⁵



As low as
13⁹⁵

- Accurate Jeweled Movements
- Anti-Magnetic Hair Spring
- Unbreakable Main Spring

A 1/10 SECOND TIMER

Designed for close timing. Large hand registers 1/10 of a second, up to 30 seconds; small hand reads minutes, up to 15. Start, stop, and continue from crown; instant zero, 7 jewel movement. Chromium plated case. Shpg. wt., 6 oz. Imported.

13 R 31032L Net 12.95

Same as 13 R 31032 (above) except 1 jewel. Net 11.95

13 R 31024L Shpg. wt., 6 oz. Net 11.95

B 1/5 SECOND TIMER • Ideal for Sports

Second hand registers 1/5 of a second and completes turn in 60 seconds. Small hand indicates up to 30 minutes. Side slide starts and stops hands. Fast resetting dependable 7-jewel movement. Shpg. wt., 6 oz. Imported.

13 R 31040L Net 12.95

Same as 13 R 31040 (above) except 1 jewel. Net 11.95

13 R 31057L Net 11.95

C TRACK TIMER 1/10 SECOND

Excellent for athletics. The second hand indicates tenths of a second and seconds, and completes one turn in 10 seconds. The small hand registers up to 10 minutes. Start, stop, and reset by successive depression of the crown. 7-jewel movement. Shpg. wt., 5 oz. Imported.

13 R 31065L Net 16.95

D DECIMAL TIMER

Ideal for industrial time-studies. Easy-to-read outer dial divided in 1/100 of a minute registering up to one minute. Inner dial graduated in minutes and registers up to 30 minutes. Push button, for timing out, brings both hands back to zero. Pressures on the crown will consecutively start, stop and again start the timer. Dependable 7-jewel movement. Swiss made. Shpg. wt., 6 oz.

13 R 31016L Net 13.95

24-HOUR ELECTRIC WORLD CLOCK



- Adjustable for Various Time Zones
- South Polar Projection

Self starting, accurate electric clock. Tells world-wide and local time. Calibrated in hours—1 to 24, minutes and seconds—1 to 60. Black dial with white graduations, 8" overall diameter. Chrome plated case. UL listed, 110V, 60 Hz, AC. Shpg. wt., 2 lbs.
13 R 26024 Net 10.95

Sportsman's Calendar Watch WITH WORLD TIMER

Tells Time In 12 World Wide Cities

11⁹⁵

An Underwater Watch That Indicates Elapsed Diving Time

- Pressurized Water-Resistant Case
- Automatic Daily Calendar
- Parking Meter Time
- Luminous Marker and Hands



Swiss Precision Crafted

Handsome wristwatch especially designed for the sportsman who is apt to get his watch wet—fishermen, hunters, or skin divers. Hermetically sealed pressurized case provides maximum protection to 5 atmospheres. Movable outer bezel determines time in 12 major cities around the world. Swiss crafted anti-magnetic movement features automatic daily calendar, unbreakable mainspring, and sweep second hand. Luminous hour markers and hands for high visibility. Polished chrome case, stainless back, and comfortable waterproof strap. Imported. Shpg. wt., 7 oz.
13 R 31461L Net 11.95

Automatic Self-Winding Sportsman's Calendar Watch

An Automatic Underwater Watch That Indicates Elapsed Diving Time



16⁹⁵

Swiss Precision Crafted

- Pressurized Water-Resistant Case
- Parking Meter Time
- Luminous Marker and Hands
- Stainless Steel Band

Designed for the active sportsman! Tell the time and the date at a glance. Has a revolving outer bezel for determination of elapsed time up to 60 minutes. Perfect for skin diving, flying, racing; even keeps time on sports rentals. Automatic self winding; no need to wind watch every day. Calendar date changes automatically. Features a sweep second hand and luminous hands and dial markers. Rugged Swiss crafted timepiece is water resistant, antimagnetic and has an unbreakable mainspring. Hermetically sealed, pressurized case provides protection to 5 atmospheres. Case is finished in bright chrome with a stainless steel back and a matching stainless steel band. Shpg. wt., 9 oz.
13 R 31446L Net 16.95

Man's Deluxe Automatic Sportsman's Watch. Similar to above except with 17 jewel movement and all stainless steel case.

13 R 31453L No Money Down* Net 32.95

PEDOMETER

6⁹⁵

- Range 0-25 Miles
- Ideal For Hikers, etc.
- Clips To Belt

Fine quality pedometer accurately registers distance you have walked in quarter mile increments from 0 to 25 miles. Large easy to read dial. This precision instrument comes with clip for wearing on belt. Easily set, simple to use. A must for those who want to know their distance traveled. Shpg. wt., 6 oz.
13 R 31123L Net 6.95



*See Page 22 for Full Credit Details on Easy Pay Plan

SELECTED CLOCKS AND WEATHER INSTRUMENTS

CORDLESS ELECTRIC DECORATOR CLOCKS

AMERICAN TRADITIONAL CORDLESS ELECTRIC PENDULUM CLOCK



Only **16⁹⁵**

Charming replica of an old favorite expertly reproduced in Time-wood and carefully accented in walnut tones. Mottled parchment dial is in striking contrast to the large Roman Numerals. The graceful motion of its swinging pendulum completes the authenticity of this ageless favorite. Runs up to one year on a single "D" cell. Size: 14" H x 9" W x 2" D. Shpg. wt., 2 lbs.

13 R 30547W Net 16.95
Battery for above.
99 R 63661 Net .25




"GRANDFATHER" CORDLESS ELECTRIC PENDULUM CLOCK

Only **29⁹⁵**

Warm walnut American styling for a charming blend of accuracy and handsome traditional design. Beautifully accented handsome spun gold and ivory dial with smoked antique Federal mirror complements the graceful motion of the golden swinging pendulum. Carved walnut raised trim is crowned with an eagle to complete this elegant timepiece. Runs up to one year on a single "D" cell. Size: 25" H x 11" W. Shpg. wt., 6 lbs.

13 R 30521W Net 29.95
Battery for above.
99 R 63661 Net .25

DECORATIVE HOME WEATHER STATIONS



Thermometer—Barometer—Humidity Meter

(A) HOME WEATHER STATION. Three accurate dial-type instruments report barometric pressure, temperature and humidity. Finely etched precision calibrated 2 1/2" spun metal dials for easy reading. Heavy metalized finish has the warm glow of polished brass. Mounted on walnut grained panel in an ebony-grained and gold accented frame with a brass antiqued metal finish 17"x7". For horizontal or vertical mounting.

13 R 40041 Shpg. wt., 2 1/2 lbs. Net 11.95

(B) DELUXE HOME WEATHER STATION. Beautiful three instrument home weather station incorporates a precise and sharply calibrated thermometer, barometer and humidity meter. Rich hand-rubbed, wood-grained finished case houses instruments and beautifully sets off spun golden, extra large, easy-to-read dials. Calibrations and markings are etched in black to stand out clearly. 20" tall case may be mounted vertically or horizontally.

13 R 40066 Shpg. wt., 3 1/4 lbs. Net 15.95

(C) ELEGANTLY STYLED HOME WEATHER STATION. Decorator inspired home weather station. Contains 3 precision weather instruments to accurately measure the temperature, barometric pressure, and humidity. Reset index on barometer for easy discernment of pressure tendencies. Distinctive hand-rubbed case of antique black and walnut finish with gold inlay accents. Recessed dials with gold numerals. Size: 28 x 8".

13 R 16108 Shpg. wt., 3 1/4 lbs. Net 19.95

INDOOR-OUTDOOR THERMOMETER AND HUMIDITY METER

- Indoor As Well As Outdoor Temperatures
- Richly Grained, Deep Luster Finish

9⁹⁵

Handsome wood-grained case mounts three precise instruments that accurately report the most important outdoor as well as indoor weather conditions. Indoor and outdoor temperatures are read side-by-side on attractive gold-colored, easy-to-read metal scales. Humidity can be seen at a glance on large dial below. Comes complete with 4' of capillary tubing. 14" tall. Shpg. wt., 2 lbs.

13 R 40033 Net 9.95

DIGITAL TELE-VISION LAMP CLOCK

12⁹⁵

- Takes Guesswork Out Of Telling Time
- Relieves TV Eye Strain




Time comes to life... with beautiful decorator colors for tuning in on the "now" way to tell "time at a glance." Ideal for use on a TV cabinet, in the kitchen or nursery. Provides soft illumination and precise time in hours, minutes, and seconds. Big easy-to-read numerals in three colors. UL and CSA listed. For 110-120V AC, 60 Hz. Size: 4 1/4" H x 7" W x 3 3/4" D. Shpg. wt., 3 lbs.

14 R 60039 Charcoal Brown Case/White Face/Gold Trim Net 12.95
14 R 60047 White Case/Ebony Face/Silver Trim Net 12.95

ELECTRIC DIGITAL TIME-ALARM CLOCK

Compact digital time-alarm clock has large, easy-to-read numerals. Unique AM-PM alarm lets you set alarm to ring only once in a 24 hr. period. Set in the morning—it won't ring until next morning. Illuminated numerals, for easy night reading. White plastic case, brushed chrome face, black trim. Size: 4 7/8 x 3 3/4". For 110VAC. Wt., 1 1/2 lbs.

13 R 78504 Net 14.95



Precision Weather Forecasting Instruments

WINDSCOPE® WIND SPEED AND DIRECTION INDICATOR

Taylor

WEATHER HAWK RECORDING THERMOMETER OR BAROMETER



99⁹⁵

- Easy to Install
- Self-contained
- 60 Ft. Lead-in Wire

Tells wind speed or direction by 2-position knob. Self contained, no outside power source needed. Easy to install and maintain. Outdoor parts corrosion-resistant. Attractive mahogany-finished indoor indicating unit 6½"x5" Boxed with battery, 60 feet of lead-in wire and instructions. Shpg. wt., 7 lbs. **13 R 74511W No Money Down* Net 99.95**

WEATHERSCOPE WEATHER STATION



- Outdoor Thermometer—Barometer—Wind Speed Indicator and Direction Indicator

Complete weather information center including wind speed and direction, barometric pressure and maximum-minimum outdoor temperature. Handsome 17" x 12". Walnut panel with brass bezels ready for wall mounting. Includes wind speed and direction roof unit with 60' of lead-in wire for outdoor mounting. 20' of capillary tubing for thermometer. With battery and instructions. Shpg. wt., 15¾ lbs. **13 R 74503W No Money Down* Net 199.95**



Only **59⁹⁵**


7-DAY RECORDING THERMOMETER
Records outdoor temperatures on 7-day chart. 110 volt, 60 cycle. Range minus 40° to +120° F. Eight feet capillary tubing. Black plastic base with clear cover. 13"x7". Boxed, with 13 charts, ink and instructions. Shpg. wt., 8½ lbs. **13 R 74529W No Money Down* Net 59.95**

7-DAY RECORDING BAROMETER
Records barometric pressure changes on 7-day chart, range 29-31 inches. Uni/Mag movement for maximum pen motion. 110 volt 60 cycle. For altitudes 0-10,000 feet. With 13 charts, ink and instructions. Shpg. wt., 5 lbs. **13 R 74537W No Money Down* Net 59.95**

RAIN GAUGE

- Keep Record of Total Rainfall

Precision rain gauge designed to give accurate rainfall records. Unique "chisel" shape permits recording of minute quantities. Easily operated cumulative rainfall indicator. Scale graduated up to 5½ inches. Scale in black numerals. With instructions for mounting and use, to obtain weather-station accuracy to 1/10th of an inch. Overall length 10¾", width 2½". Shpg. wt., 6 oz. **13 R 16017 Net 1.95**




Dwyer WIND SPEED INDICATOR

24⁹⁵

- For All Sportsmen, Yacht Clubs, Gun Clubs, Fishing and Hunting Camps
- Great For Pilots

Wind velocity registered by liquid filled tube. Calibrated in both MPH and Beaufort Scale. No calculations, reads just like a thermometer. Vane-type external fittings must be mounted on outside elevated point.



Attractive gray indicator features jet black calibrations. Supplied with 50 ft. tubing to connect outer unit to gauge. Gauge Size: 7¾x5¾x1" **13 R 62508 Shpg. wt., 3½ lbs. Net 24.95**

MAXIMUM-MINIMUM THERMOMETER




- READ: Present, High, Low Temp.

For weather enthusiasts gardeners-farmers, etc. Gives three readings at a glance—maximum, minimum and present temperatures. Self-registering—no knobs—magnets—or push buttons needed for reset. Magnifying lens case for ease of reading. Maintains automatic check on temperature variations. Makes you the local weather expert. Shpg. wt., 11 oz. **13 R 16033 Net 6.50**

REMOTE READING THERMOMETER. Same as above but with remote "sensor" for comfortable indoor reading of outdoor temperature. Includes mounting bracket and instructions. Shpg. wt., 11 oz. **13 R 16041 Net 7.95**

INDOOR-OUTDOOR THERMOMETER

Shows inside and outside temperature from the comfort of your room. Inside location ideal for quick easy reading. Single scale for instant comparison. Modern plastic case. 8x2½" L. 48" long copper capillary tube and bulb. Large numerals for easy reading. Shpg. wt., 7 oz. **13 R 16025 Net 3.95**



POCKET THERMOMETER




Ideal for the laboratory, factory, etc. Mercury type—total immersion. White scale with black numerals. Sub-divided by 2° F. Polished nickel-plated case; tube length 5½". Shpg. wt. 4 oz. **15 R 48015 Range, -30° to 120°F Net 2.95**
15 R 48023 Range: 0° to 220°F Net 3.19

"SLIDE RULE" HUMIDICATOR


- Slide Rule Readings
- No Computing
- No Conversion

3 95

Fastest and easiest method of determining relative humidity. With the cursor (slide) set on the temperature, the relating humidity is read directly off the humidity graph. The "humidicator" graph is calibrated in increments of 2%. Both thermometers are calibrated in increments of 2° from 20°F to 120°F. Background colors chosen for easily readability. Overall size, including cylinder is 13½x3¾". Mounted on mahogany board with provisions for hanging. Imported. **99 R 90050 Shpg. wt., 1 lb. Net 3.95**



*See Page 22 for Full Credit Details on Easy Pay Plan



POWER ZOOM MOVIE OUTFIT with DUAL 8 PROJECTOR



SAVE WHEN YOU BUY THE COMPLETE OUTFIT Only **159⁹⁵**

CAMERA FEATURES

- 3-1 Power Zoom & Reflex Viewing
- Thru-the-Lens CdS Electric Eye
- Drop-in Film Cartridge Loading

Outfit includes everything you need for movie making and showing fun, Deluxe super 8 power zoom reflex camera features thru-the-lens CdS automatic exposure control, fast f/1.8 3-to-1 manual or power zoom, insufficient light indicator, electric film drive, built-in type A filter, focusing eyepiece, and drop-in loading. Fully automatic 500 watt brilliance dual 8 projector has f/1.5 lens, automatic reel-to-reel thru gate threading, single knob control for forward, reverse, still, fast forward and automatic rapid rewind. 400 foot capacity projector

PROJECTOR FEATURES

- Dual—For Both Super and Regular 8
- Automatic Reel-to-Reel Threading
- 400 Foot Film Reel Capacity

includes self-contained case, film trimmer and room light outlet. Outfit also includes camera case, roll of GAF color movie film with processing, 650 watt sealed beam movie light, batteries, and "Guide To Better Home Movies" book. Shpg. wt., 22 lbs.
15 R 78228 W No Money Down* Net 159.95

15 R 78236L Camera Only. Shpg. wt., 2 1/2 lbs. Net 79.95
15 R 78244W Projector Only. Shpg. wt., 10 lbs. Net 79.95

YASHICA

SUPER 600 ELECTRO 6-1 POWER ZOOM



- 8-48mm f/1.8 Automatic Zoom Lens
- Motorized—3-Speeds
- With Ultra-Modern Servomatic CdS Thru-the-Lens Exposure Control
- Reflex Viewing

Only **159⁹⁵**
No Money Down*

Deluxe electric drive Super 600 Electronic reflex camera with fast electric f/1.8 lens zooms from 8 to 48 mm. Automatic CdS through-the-lens exposure system and micro-split focusing. Super 8 drop-in cartridge loading, no threading. Shoot 50 ft. without rewinding. Other features include film type indicator window, parallax free reflex viewing, shutter trigger with continuous run button, spotlight and backlight lighting control, automatic film ASA speed selector, insufficient light indicator, remote control, single frame, adjustable eyepiece, and cable release sockets, 85A filter, battery checker, footage counter, and movie light slot. ASA Speeds: 25-400. Film Speeds: 12, 18, 24 fps. Imported. Shpg. wt., 3 lbs.
15 R 36770L Net 159.95
99 R 63703 Batteries for above. (4 req.) Net ea. .15

YASHICA

SUPER-50 5-1 POWER ZOOM



- 5 to 1 Power Zoom (8-40mm f/1.8)
- Fully Automatic Thru-the-Lens CdS Electric Eye
- Thru-the-Lens Reflex Viewing
- 2-Speeds and Single Frame

Only **99⁹⁵**
No Money Down*

Slim and neatly designed, the Super 50 permits you to power zoom your movies from wide angle vistas to intimate close-ups at the press of a button. Sharp Yashinon electric zoom 8-40mm f/1.8 12 element lens delivers crisp pictures. Thru-the lens CdS exposure control automatically selects the proper exposure. Bright reflex viewfinder has exposure setting indicator. Provides the convenience of power film drive and threadless cartridge film loading. Features battery tester, footage counter, remote control socket, filter control dial, film type window and movie light slot. Film speeds: 18 and 24 fps.; single framing. Fold away pistol grip. Uses 4 penlight batteries. Imported.
15 R 36788L No Money Down* Shpg. wt., 2 1/4 lbs. Net 99.95
99 R 63703 Batteries for above. (4 req.) Net ea. .15

Deluxe Dual 8 MM Movie Projectors & Editors

gaf

DUAL 8mm PROJECTOR FOR BOTH SUPER AND STANDARD 8



- Instant Switch from Standard to Super 8 MM Film
- Automatic Reel-to-Reel Threading

59⁹⁵


No Money Down*

Model 1388. Standard/super 8 mm projector combines 500-watt brilliance and a fast f/1.6 color-corrected, coated lens for vivid screen viewing. Automatic threading design features Adjusto-Matic control for proper feed onto take-up reel. Accepts reels to 400 ft. capacity. Quiet, cool operation. Automatic rewind, framing control, elevation adjustment, focus control, film trimmer and automatic tensioning. Handsome, self-contained carrying case with handle. Supplied with 400 ft. empty film reel. For 117 VAC, 60 Hz. Shpg. wt., 10 lbs.

15 R 78202W

Net 59.95

Bell & Howell DELUXE DUAL 8mm Zoom PROJECTOR FOR BOTH SUPER AND STANDARD 8



- Multi-Motion Feature
- Forward/Reverse Operation
- Rugged Die-Cast Case


154⁹⁵

No Money Down*

Automatic reel to reel threading and variable film speed control. Brilliant f/1.6, 18-30 mm Filmovara zoom lens assures crisp full screen viewing. Incorporates spindle adapters for super 8 reels, dial focusing, framing dial, tilt control, reverse and rapid rewind, film cutter for both super and standard 8 film, auto-load 400 ft. reel, and cord storage compartment. Motor fan cooling switch permits after show cooling for fast safe storage. Rugged die-cast construction. Self contained carrying case. For 117 volts 60 Hz. AC.

15 R 65134W Shpg. wt., 17½ lbs. Net 154.95

baia DUAL 8mm EDITOR



- For Both Standard and Super 8
- 3¼ x 2¼ Viewing Screen


15⁹⁵

Compact Dual 8 Reviewer for both Regular and Super 8mm film. With Dual Track Dual 8 system and Dual Uniflex splicer, splicing tape, plus big 7 sq. in. picture area, built-in focusing and framing controls, frame marker and lamp switch. Has film protecting heat filter, geared 400' capacity rewinds. UL listed.

15 R 62008 Shpg. wt., 4 lbs.

Net 15.95

DeJUR DUAL 8mm Zoom PROJECTOR FOR BOTH SUPER AND STANDARD 8



- A Movie Projector That Thinks It's A Slide Projector
- Self-Enclosed Case

79⁹⁵


No Money Down*

Eldorado 84-AZ. Designed to run for extended periods in 100% illuminated "still" position without burning film. Handles standard and super-8 mm film. Even splice the two together and run them on the same reel. Sharp, f/1.5 zoom lens assures full screen brilliance. Features quiet, automatic reel-to-reel threading, built-in film trimmer, 400 ft. reel capacity, fast rewind, lifetime lubrication, die cast aluminum body and self-enclosed carrying case with handle. For 117 VAC, 60 Hz. Shpg. wt., 10½ lbs.

15 R 52132W

Net 79.95

DeJUR DELUXE DUAL 8mm Zoom PROJECTOR FOR BOTH SUPER AND STANDARD 8



- A Movie Projector That Thinks It's A Slide Projector
- Forward And Reverse
- Slow Motion Plus Variable Speed

109⁹⁵

No Money Down*

Eldorado 86-AZ movie projector with the advanced features of variable speed control, true slow motion and forward or reverse projection-100% illumination for extended "still" projection and cool, quiet operation. With sturdy diecast aluminum case, 400 ft. reel capacity, built-in automatic room light receptacle, automatic reel-to-reel threading, fast rewind, built-in film trimmer lifetime lubrication and a self enclosed carrying case with handle. Sharp f/1.5 zoom lens for excellent sharpness. For 117 VAC, 60 Hz.

15 R 52140W Shpg. wt., 12½ lbs. Net 109.95

ATLAS-WARNER DUAL 8mm EDITOR



- For Both Standard and Super 8

26⁹⁵

- Over 17 Sq. In. Viewing Screen
- Die-cast Metal Construction

17 sq. in. viewing area. Film notches in exact frame that is being viewed. Takes reels up to 400 ft. Smooth and rapid geared rewind. Adjustment knobs for focusing and framing. Foldaway arms. Includes splicer and splicing tape. Size: 9½x7x6½". UL listed.

15 R 84093 Shpg. wt., 8½ lbs.

Net 26.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 327

MIRANDA AUTO "SENSOREX EE" 35MM SLR



- Automatic Thru The Lens CdS Meter
- No Needles To Match

269⁹⁵
with case

Designed to provide the creative flexibility demanded by professional photographers yet have the operational simplicity needed by the novice. Fully automatic or manual Miranda Sensorex EE offers a host of refined useful features including a built-in CdS exposure circuit which automatically selects the correct lens opening for either average or spot lighting conditions. Sharp 50mm f/1.8, 4 group, 6 element lens delivers superb resolving power. Features include an interchangeable pentaprism viewfinder, universal bayonet lens mount, variable delay self-timer, depth-of-field preview, focusing down to 17" and FP & X synchronized hot shoe. Focal Plane shutter speeds: B, 1-1/1,000 sec. EE coupling range: EV3-18, ASA 25-1600. Imported. Shpg. wt., 4 lbs.

15 R 37588L No Money Down* Net 269.95

MIRANDA "SENSOREX" 35MM SLR



- Behind-The-Lens CdS Meter
- Variable Delay Self-Timer

199⁹⁵
with case

Fully automated SLR camera utilizes cross-coupled behind-the-lens CdS meter (ASA range 25-1600 and EV 3-18) and ultrasharp Auto Miranda lens. Match needle is set with the lens wide open. Built-in shoe provided for wide range of accessories. Multi split-grid resolves into perfect clarity when pin point focus is achieved. Features interchangeable lens mount, built-in self timer, instant return mirror, interchangeable viewfinder, and rapid advance geared 150° cocking lever. Complete with built-in variable delay self-timer. Includes case and strap. Specifications: 50mm f/1.8 lens. Speeds: B, 1-1/1000th sec. FP & X Synch. Imported. Shpg. wt., 4 lbs.

15 R 37455L No Money Down* Net 199.95
"SENSOREX" with 50mm f/1.4 lens. Net 239.95
15 R 37463L No Money Down*

Minolta SR-T 101 35MM SLR



- Cross Coupled CdS Thru-The-Lens Exposure System
- F/1.7 55 MM Lens

224⁹⁵
with case

A quality SLR featuring Minolta's "contrast light compensator" thru-the-lens CdS metering system. Exposure "match-needles" in viewfinder respond to change in aperture and/or shutter speeds. Exposure readings not affected by light entering viewfinder. Shutter speed scale visible in viewfinder. Readings are taken with lens wide open. ASA range is 6-6400. Features an instant return mirror; a focal plane shutter with speeds from 1-1/1000th plus B; FP&X synch.; auto-reset frame counter; self-timer, mirror lock, depth of field preview, and built-in accessory shoe. Includes a 55 mm f/1.7 lens, case and strap. Imported. Shpg. wt., 4 1/4 lbs.

15 R 34551L No Money Down* Net 224.95

MIRANDA "SENSOMAT" RE 35MM SLR



- Thru-The-Lens CdS Meter
- Sharp 50 MM F/1.8 Lens

169⁹⁵
with case

"Sensomat" is a truly versatile 35 mm SLR featuring a thru-the-lens CdS metering system with a narrow angle of acceptance for easier, more perfect picture taking. Match needle in the viewfinder can be centered for proper exposure by rotating the diaphragm and/or the shutter speed dial. ASA range: 25-1600. Other features include rapid loading spool, fully interchangeable finder and lens systems, shutter speeds of 1-1/1000th plus B & X synch., automatic reset film counter with a magnifying lens, and a front and top shutter release for greater convenience. Focus from 17". Camera includes 50 mm f/1.8 auto lens, case and strap. Imported. Shpg. wt., 4 lbs.

15 R 37471L No Money Down* Net 169.95



Kowa SR 35MM SLR

119⁹⁵
with case

Fully coupled, behind-the-lens, CdS exposure meter system measures illumination at full aperture. Match needles visible in viewfinder. ASA range 10-800. Finder uses a microprism dot at the center for more accurate focusing and a fresnel screen for bright, edge-to-edge viewing. Fast f:1.9, 50 mm lens features bayonet mounting and fully automatic diaphragm. Camera accepts full range of Kowa lenses. Features easy-loading, leaf shutter, 1-1/500th plus B, rapid film advance, auto-reset film counter, self-timer, M or X sync. Imported. 15 R 63055L Shpg. wt., 3 lbs. No Money Down* Net 119.95



DELUXE PIGGY-BACK SLR BAG

Only **27⁹⁵**

- Fine Top Grain Cowhide
- Holds SLR Camera —Extra Lenses & Accessories

Includes extra thick foam rubber protection, fully lined interior with a woven velvete green fabric, patented locking mechanism, thick rubber cut-outs for maximum protection for two supplementary lenses. Velcro belt to lock camera in place, and an expandable band in lid to hold accessories. May be carried in combination or separated into two bags. Size: 13 x 8 x 5 1/2; piggy-back 9 x 5 x 3". Shpg. wt., 4 lbs.

15 R 16194 Net 27.95

YASHICA ELECTRO-35 GS 35MM

109⁹⁵
with case



- Sensitive CdS Sensor
- Electronic Exposure Control: 30 Sec. to 1/500 Sec.

MODEL ELECTRO-35GS. Advanced 35 mm rangefinder camera with the "electronic brain". Sensitive solid-state circuit reads the existing lighting conditions and automatically sets the proper shutter speed at a preselected aperture. Continuously variable range of shutter speeds from 30 sec. to 1/500 sec. For maximum reliability when shooting flash, contacts are finished in gold providing very low resistance and long life. Also features coupled range/viewfinder focusing with automatic parallax correction, built-in self timer, shutter release lock, accessory shoe for flash or other accessories, battery checker. ASA: 12-500, X sync. Sharp f/1.7, 45 mm color corrected lens. Imported.

15 R 36754L Shpg. wt., 3 lbs. No Money Down* Net 109.95

KONICA AUTO S2 35MM

109⁹⁵
with case



- Range/Viewfinder With Parallax and Field Compensation
- Fully Automatic, Match Needle or Manual Option—CdS Meter

Just set the shutter and shoot with this fully automatic 35 mm camera. Features a CdS electric eye built into the lens for accurate exposure even when using filters. Shutter automatically locks under extreme lighting conditions. Uses Insta-Grip-Loading for quick, easy film loading. Other features include rangefinder focusing with automatic parallax correction and field compensation, short stroke film advance, shutter speeds from 1-1/500th and B, M & X synch., self-timer, and an auto-reset film counter. Can be used automatically, semi-automatically or manually. Includes a fast 45 mm f/1.8 lens with a built-in collapsible lens shade, case and strap. Imported. Shpg. wt., 3 1/4 lbs.

15 R 76065L No Money Down* Net 109.95

AIREQUIPT

SEMI-AUTOMATIC SLIDE PROJECTOR



39⁹⁵ • With Circular Magazine For 100 Slides
• Panel Focusing and Controls.

Model 125. Semiautomatic slide projector with 500-watt lamp and a 4", 3-element color-corrected lens for bright, clear viewing pleasure. Features an efficient blower for long lamp life, cool, quiet operation and low slide temperature. Slide pre-heat to assure immediate focus. Also includes a 3-way on/off switch, panel focus control and elevation control. Handsomely styled housing and cover are of unbreakable, lightweight Cyclocac. Complete with circular slide magazine. Shpg. wt., 10 lbs.

15 R 36531W No Money Down* Net 39.95

REMOTE CONTROL SLIDE PROJECTOR



59⁹⁵ • Remote Control-Forward/Reverse and Micro Focus
• With Circular Magazine For 100 Slides

Model 135. Fully remote controlled, jam-proof projector with a sharp, 4" color-corrected lens and a 500-watt lamp for brilliant screen viewing. Features a highly efficient blower for cool, quiet operation, slide pre-heat to insure immediate focus, elevation control, 3-way on/off switch, panel focus control, remote control for forward/reverse and micro-focus. Smartly designed, self-contained, unbreakable case. Complete with circular slide magazine. Shpg. wt., 12 lbs.

15 R 36473W No Money Down* Net 59.95

ELECTRONIC FOCUS SLIDE PROJECTOR



89⁹⁵ • Remote Control for Forward/Reverse and Micro-focus
• Automatic, Electronic Focusing

Model 660. A combination of functional design and precision engineering. Features solid-state electronic focusing, brilliant 4" f/3.5 color-corrected lens. Remote controlled forward/reverse as well as remote controlled focusing. 3-way on/off switch, 500-watt lamp, elevation and leveling controls. Whisper-quiet cooling system provides long lamp life and low slide temperatures. Attractive cover and housing of lightweight Cyclocac for durability. Complete with one circular and one metal magazine. Shpg. wt., 15 R 36762W Wt., 15 1/2 lbs. Net 89.95

15 R 36499 36-Slide Metal Magazine. Wt., 1/2 lb. Net 2.39 15 R 36481 100-Slide Circular Magazine. Wt., 1 1/2 lbs. Net 2.95

35MM SLIDE SORTER

The illuminated 11" x 15" inspection screen is large enough to see a whole tray full of slides (35) at one time. Folds flat in a jiffy for compact storage, built-in illumination with on-off switch, 6 ft. line cord; can be used with 110 or 120 volts, AC or DC. Size: 15 x 8 1/2 x 8 1/2". Shpg. wt., 1 3/4 lbs.

15 R 36168 Net 3.29



AIREQUIPT SLIDE STACKER

- For All Airequipt Slide Projectors

Permits viewing of slides without magazines. Holds up to 40 slides at a time. You can now view/edit your slides prior to storage in magazines.

15 R 36796 Wt., 1 lb. Net 8.95



8⁹⁵

*See Page 22 for Full Credit Details on Easy Pay Plan

LAFAYETTE CdS EXPOSURE METER

Only **14⁹⁵**

- High Quality, Ultra-Sensitive—Measures Moonlight, Candlelight, Bouncelight
- With Padded Vinyl Carrying Strap Case and Neck Strap

Achieve correctly exposed photographs and slides from the light of a single candle with this versatile low cost Lafayette meter. Ultra-sensitive CdS photocell meter utilizes dual light ranges to accurately measure light intensity including extremely low light levels for night and available light photography plus bright beach and snow scenes. Operates comfortably with one hand. A single rocker switch controls light range and turns meter "on" or "off." Measures both reflected and incident light with built-in hemispheric diffuser. 50° angle of coverage provides good averaging of subjects for proper exposure. Has battery test switch for maintaining accurate readings. Provision for zero adjustment. Long life mercury battery (included) assures accuracy over continuous use. Precision jeweled mechanism in high impact case. Size: 3 3/4 x 2 1/2 x 1 1/4". With padded vinyl carrying case and neck cord. Imported. Shpg. wt., 1 lb.

99 R 71961L

Net 14.95

SPECIFICATIONS

Sensitivity: Low Range, 0.275 to 444 footcandles; High Range, 444 to 36,674 footcandles. ASA Film Speed Range: 6 to 12,000. DIN: 9 to 42. Diaphragm Stops: f/1 to f/32. Shutter Speeds: 1/8000 to 8 minutes. Movie Scale: 8 to 128 frames per second. EV Scale: -3 to +22. Acceptance Angle: 50°. Color Response: 6,200 Angstroms (peak). Photocell Type: cadmium sulphide. Battery: 1 mercury, RM-625 or equivalent.




**SOLIGOR "SELECTOR"
DUAL RANGE CdS METER**



11⁹⁵

**LAFAYETTE "35" CLIP-ON
EXPOSURE METER**

5⁹⁵



- ASA Scale 10 to 1000
- Weighs 1 Oz.

Exceptionally convenient exposure meter. Clips right on camera—quick easy reading. Gives better, more accurate exposed pictures with a minimum of effort. Speeds 1/1000 to 1 second. Lens aperture f/1.4 to f/22. Mounts on camera or may be hand held. Complete with leather case and instructions. Imported.

99 R 70344 Shpg. wt., 1/2 lb. Net 5.95

**STROBE ADAPTER FOR KODAK
INSTAMATIC "X" CAMERAS**




**FITS
MODELS**
X-15
X-25
X-35
X-45

7⁵⁰

Now you can adapt your Instamatic "X" camera to use an Electronic Flash. No more flashcubes to carry about or run out of when that unexpected picture comes along. Flash pictures will seem sharper—the fast speed of the flash seemingly eliminates camera movement which can blur pictures. Simple to install. Synchronized to "X" model cameras. Has "hot shoe" and PC connection. Imported.

15 R 49633 Shpg. wt., 8 oz. Net 7.50

**LAFAYETTE ELECTRONIC
STROBE FLASH**



- Fully Transistorized
- Use Horizontally Or Vertically

9⁹⁵


Lightweight strobe weighs under 7 oz. with batteries. Small size: 3 1/4 x 2 3/8 x 1 3/8". Hot shoe adapter allows vertical or horizontal use for best flash coverage. Recycles in 7-10 seconds on 2 easily replaceable penlight batteries. Kodachrome II (ASA 25) guide no. of 28. Flash duration: 1/2000 sec. Color temperature: 6000 K. On/Off switch to prolong battery life. Neon lamp signals when strobe is ready to fire. Built-in PC cord prevents loss. Imported.

99 R 71128 Shpg. wt., 3/4 lb. Net 9.95

"AA" Alkaline Batteries for above (2 req.)

99 R 63828 Net ea. .42

**SOLIGOR MK-6
ELECTRONIC STROBE FLASH**



- Features Compact Design And Transistorized Circuitry
- "Golden" Flash Tube

17⁹⁵

Compactness and versatility make this unit a natural companion for all cameras. Features AC-DC operation. Has new color-corrected "Golden" Flash tube for sharp, perfectly balanced color pictures. Guide No. 28 for ASA 25. 150 flashes with Alkaline batteries. "Redi-light". Flash duration 1/2000th sec. Coverage: 60° Horizontal, 55° Vertical. Recycling time: 8 sec. on batteries, 5sec. on AC. Color temperature 5700° K. Extra long AC power cord. Requires 2 penlight batteries for DC operation. Size: 1 1/2 x 4 3/4".

15 R 37570 Shpg. wt., 1 lb. Net 17.95

"AA" Alkaline Batteries for above (2 req.)

99 R 63828 Net ea. .42

**HI-BEAM II
ELECTRONIC STROBE FLASH**



- With Built-in Rechargeable Nickel Cadmium Batteries and Charger

29⁹⁵

Compact, powerful flash no larger than a cigarette pack and weighing only 8 1/2 oz. gives you light where and when you need it. Guide No. 40 for ASA 25 films. 1/3000-sec. flash duration. Operates on 110 VAC with built-in cord or its self-contained rechargeable nickel cadmium batteries. Shoot every 10 seconds with up to 60 flashes per charge. Reflector coverage is 55°; color temperature is balanced for all daylight and B & W and/or color films. Size: 3 3/4 x 2 1/2 x 1 1/4". Imported.

15 R 36390 Shpg. wt., 1 lb. Net 29.95

Telephoto and Close-Up Lenses

SOLIGOR LENSES FOR TELEPHOTO OR WIDEANGLE SHOTS

Interchangeable lenses designed for use with single lens reflex cameras. Each precision lens is hard coated and fully color corrected. Shipped Prepaid Directly From Factory. No C.O.D. Send Full Remittance or Use Lafayette's Easy Pay Plan.

AS LOW AS

29⁹⁵



AUTOMATIC LENSES

High quality, fully automatic lenses for many SLR cameras including Canon FL; Exakta, Minolta SR series, SRT 101; Miranda F, FV, G, Sensomat, Sensomat "RE" Sensors; Nikon; Pentax and Topcon. Lenses have click stops, depth of field scale and manual diaphragm control when needed. Full lens versatility. Specify make and model of camera.

Stock No.	Auto Lens	Closest Focus	Net
15 R 37281Z	28mm f/2.8 W.A.	18"	69.95
15 R 37489Z	35mm f/2.8 W.A.	2'	51.95
15 R 37299Z	135mm f/2.8 Tele.	6'	64.95
15 R 37497Z	135mm f/3.5 Tele.	6'	49.95
15 R 37307Z	200mm f/3.5 Tele.	10'	84.95
15 R 37315Z	300mm f/5.5 Tele.	20'	99.95
15 R 37313Z	400mm f/6.3 Tele.	30'	119.95
15 R 37323Z	90-230mm f/4.5 Tele. Zoom	8'	149.95

PRESET LENSES

Low cost preset lenses for limited budgets. Compact, precision optics for most SLR cameras. Full range of focal lengths from wide angle to long telephotos to make previously "impossible" shots a reality. Specify make and model of camera.

Stock No.	Auto Lens	Closest Focus	Net
15 R 37331Z	28mm f/2.8 W.A.	18"	54.95
15 R 37349Z	35mm f/3.5 W.A.	2'	29.95
15 R 37521Z	105mm f/2.8 Tele.	4'	39.95
15 R 37539Z	135mm f/2.8 Tele.	5'	44.95
15 R 37364Z	135mm f/3.5 Tele.	5'	31.95
15 R 37372Z	180mm f/3.5 Tele.	7.5'	44.95
15 R 37547Z	450mm f/8 Tele.	25'	69.95
15 R 37554Z	90-230mm f/4.5 Tele. Zoom	8'	114.95

LENS SET FOR POLAROID CAMERAS

- Wide Angle & Telephoto Lens
- View Finder



Telephoto lens increases the focal length of the lens and results in a 3 times area magnification. Wide Angle lens provides a 75% increase of subject area. Each lens has a "conversion base scale." Supplied with slip-on adapter ring, view finder and case with shoulder strap. Imported. Wt. 1 1/4 lbs. For Polaroid Models 100, 101, 103, 230, 240, 250, 340, 350, 360 and 400 series.

15 R 49237 Net 34.95

VARI-CLOSE-UP LENS FOR SLR CAMERAS

- Sharp Focus From 3 Feet to 1 Inch Without Distortion



Variable magnification (+1 to +10 diopters), close-up lens for use on normal and medium telephoto lenses. Can be used with any single lens reflex, focusing camera either still or movie. Attaches easily to front of lens with series VII adapter ring. Does not interfere with automatic diaphragm and does not interfere with built-in meter systems of most cameras. No exposure compensation needed. Shpg. wt., 3/4 lb.

15 R 36523 Net 22.95

CLOSE-UP ATTACHMENT FOR KODAK INSTAMATIC CAMERAS

249



Add to the versatility of your Instamatic camera with this handy close-up attachment. Slips easily onto the front of the lens. For use with all black and white, and color films. Shpg. wt., 4 oz.

For Instamatic 100, 104, 124, 134, 150, 154, 174, X-10, X-15
15 R 36507 Net 2.49
For Instamatic 300, 304, 314, 400, 404, 414, X-25, X-35, X-45
15 R 36515 Net 2.49

WIDE ANGLE AND TELEPHOTO LENSES for KODAK INSTAMATIC CAMERAS

As Low As **5⁹⁵**

Increase your cameras' versatility with a wide angle or telephoto lens. No adjustments necessary. Just slip on the lens and shoot. The telephoto increases the focal length and results in a magnification of about 2 times the image size as compared with the normal lens. The wide-angle lens decreases the focal length and results in an increased subject area of about 75%. Each lens includes a built-in viewfinder. Shpg. wt., 4 oz.

For Instamatic Models—184, 154, 100, 150, 124R, 174R Hawk-eye 50.
15 R 49351 Wide Angle Lens Net 5.95
15 R 49369 Telephoto Lens Net 5.95
For Instamatic Models—304, 404, 300, 400.
15 R 49377 Wide Angle Lens Net 5.95
15 R 49385 Telephoto Lens Net 5.95



Complete Lens Set of Wide Angle, Telephoto, Viewfinder with Case. (Not Illustrated) Shpg. wt., 3/4 lb.

For Instamatic Models—S-10, S-20
15 R 49393 Net 18.95
For Instamatic Models—314, 414
15 R 49575 Net 18.95
For Instamatic Models—714, 814, X-90
15 R 49583 Net 18.95
For Instamatic Models—704, 804, 700, 800
15 R 49401 Net 18.95
For Instamatic Models—X-15, X-25
15 R 49617 Net 18.95
For Instamatic Models—X-35, X-45
15 R 49625 Net 18.95

DELUXE PHOTO COPIER FOR POLAROID CAMERAS

- With Built-In, Glare-Free, High Intensity Flood-lights



17⁹⁵

Copy photographs, magazine articles without damaging the original by using your present Polaroid camera. Deluxe photo copier with its own miniature 120-watt lights allows you to copy any time of day or night. Diffused light does not produce glare on prints. Fast exposure time assures a blur-free picture. Quickly installed or removed. With built-in linecord switch and glare-free lamps. CSA and UL listed. Shpg. wt., 1 1/2 lbs.
For Polaroid Series 100, 200, 300, 400 Color-pack Cameras.
15 R 16160 Net 17.95

PHOTO COPIER FOR POLAROID CAMERAS

As Low As **7⁹⁵**



- No Waiting—Make Extra Prints

Want copies of your Polaroid snapshots? Make them yourself on the spot in as little as 15 seconds using your present Polaroid. It's easy! Imported. Shpg. wt., 3/4 lb.
For Polaroid Series 100, 200, 300, 400 Color-pack Cameras.
15 R 49500 Net 8.95
FOR POLAROID COLOR PACK II, III, IV CAMERA
15 R 49559 Net 8.95
FOR BIG SWINGER
15 R 49526 Net 7.95

Minolta



35⁹⁵
each

No Money Down*

A "16 II" SUBMINIATURE CAMERA

An extremely easy-to-operate, palm-size camera. Sliding camera in and out of built-in case advances film, cocks shutter, counts exposure and prevents double exposure—all automatically. 6 shutter speeds from 1/30 to 1/500 sec. plus "B". Takes B & W pictures, color prints or color slides that fit any 35mm projector. Direct viewfinder shows picture exactly as it will appear on film. Lens opening from f/2.8 to f/16. With Case. Imported. Shpg. wt., 1 lb.

- 15 R 34163L Net 35.95
- MINOLTA 16 II Accessories. Av. Shpg. wt. 6 oz.
- 15 R 34213 Duo Fit Flash Gun Net 7.95
- 15 R 34221 Bracket for Flash and Tripod Mtg. Net 2.95
- 15 R 34239 Aux. Lens Set—

- 2 closeup, 1 distance, 1 Y filter Net 4.95
- 15 R 34247 Color Filter Set—1 ea. 1A, 80A, B1B Net 4.95
- FILM FOR "16 II"—All are 20-exposure magazines. Shpg. wt. 3 oz.
- 15 R 34171L Kodak Plus-X ASA 100 Net 1.19
- 15 R 34197L Ektachrome MS ASA 50 Net 1.80
- 15 R 34189L Kodak Double-X ASA 320 Net 1.19
- 15 R 34502L Ektacolor Neg. (color prints) ASA 100 Net 1.80

B MINI-"16" COLOR SLIDE PROJECTOR

Compact, lightweight projector to match Minolta and other 16 mm sub-miniature cameras. Sharp 40 mm Rokkor f/2.5 lens. Includes deluxe vinyl carrying case, standard slide carrier and 75 watt projector lamp. For 110-120 volts AC-DC. Imported.

- 15 R 34353 Shpg. wt., 3½ lbs. Net 35.95

YASHICA atoron

ULTRAMINIATURE CAMERA KIT



COMPLETE WITH CASE, FILTERS, FLASHGUN, CHAIN STRAP, AND BUILT-IN MATCH-NEEDLE EXPOSURE METER. **Only 89⁹⁵**
No Money Down*

Ultraminiature, lightweight camera accepts Minox-type film cartridges. Features drop-in loading—no film threading—no double exposures—no rewinding. Advanced, programmed shutter with speeds from 1/45 to 1/250 sec. plus bulb. Match-needle exposure system with ASA range from 25-400. Yashinon f/2.8, 18 mm lens gives detailed black and white, color prints and color slides. Bright, optical viewfinder can be used even in dimly lit surroundings. Parallax correction frame, visible in viewfinder, allows accurate framing when shooting closeup. Camera has built-in UV and Y2 filters. Includes camera and case, additional ND4X and 80B filters, cordless AG flashgun, and chain strap. Imported. Shpg. wt., 1½ lbs.

- 15 R 36259L No Money Down* Net 89.95
- PRELOAD CARTRIDGE FILM FOR ATORON. Av. shpg. wt. 3 oz.
- 15 R 36267L 40 exposure ASA 125 B & W Net 2.19
- 15 R 36275L 40 exposure XT-Pan ASA 25 B & W Net 2.19
- 15 R 36283L 40 exposure Kodachrome II Slides Net 2.59
- 15 R 36291L 40 exposure Ektacolor S Prints Net 3.19
- 32 R 47541 Batteries for above. Pkg. of 2 Net .79

DEVELOPMENT TIMER FOR POLAROID

- 10 to 120 Seconds

Now you don't have to count to develop your Polaroid film. Get top notch pictures every time. Can be set for up to 120 seconds in 10 second intervals. For all Color Pack cameras. Bell rings when time is up. Imported.

- 15 R 49534 Shpg. wt., ½ lb. Net 5.95



KODAK

INSTAMATIC CAMERA COLOR OUTFITS



As Low As
21⁵⁰

• Uses Pop-on Magicubes

Model AX-15R Outfit. Simple-to-operate camera with Lumenized f/11 prefocused lens for quality pictures. Bright, large viewfinder for realistic viewing. Quick film advance. Uses self-powered Magicube flashcube which requires no batteries. Automatically adjusts for outdoor or flash shooting. Warning lamp shows in viewfinder when new Magicube required. Outfit: camera with wriststrap, Kodacolor-X film cartridge, Magicube, and instructions.

- 15 R 26375L Shpg. wt., 1¼ lbs. Net 21.50

Model AX-25R Outfit. Features automatic film advance for up to 12 pictures in 12 sec. Uses self-powered Magicube flashcube which requires no batteries. "Used Lamp" shows in viewfinder when new Magicube required. Bright, large viewfinder for true-to-life viewing. f/11 Lumenized prefocused lens. Automatically adjusts for flash or outdoor operation. Outfit: camera with wriststrap, Kodacolor-X film cartridge, Magicube, and instructions.

- 15 R 26383L Shpg. wt., 1½ lbs. Net 31.50

INSTA-LOAD CAMERA OUTFIT



6⁹⁵

Instant loading lightweight cartridge camera that's perfect for recording your family fun. Simple to use—just drop in a Kodak 126 cartridge, close the back and snap excellent color or black and white pictures. Choose from slides or prints. No focusing, no settings. Flashcube automatically rotated and synchronized with each shot. Precision lens. Outfit includes permanent carrying case, wrist strap, color film cartridge, batteries and flashcubes. Shpg. wt., 1½ lbs.

- 15 R 53007 Net 6.95

KODAK FILM WITH PROCESSING INCLUDED



- Slides Returned Mounted, Ready for Viewing or Showing; • Convenient, direct-mail "mailers" in every roll.

After the complete roll has been filmed, put it into the mailer, drop into a mailbox and in a few days your finished films are delivered postpaid to your door. You get 3½" square prints with cx-126 color snapshots and 3½"x5" giant prints with cx-135 color snapshots. Should you get less than the full number of prints or printable negatives per roll you will receive coupon for additional FREE prints. DO NOT MAIL FILM TO LAFAYETTE RADIO. Av. shpg. wt., 8 oz.

KODAPAK KODACHROME MOVIE FILM FOR SUPER 8MM

- 15 R 47056L KA-464 Super 8mm 50-ft. Cartridge, Indoor/Outdoor Net 4.29

KODACHROME 35MM, TYPE X FOR COLOR SLIDES

Type X ASA index 64

- 15 R 47082L KX 135-20 35mm, Type X, 20 Exp. Net 3.29
- 15 R 47090L KX 135-36 35mm, Type X, 36 Exp. Net 4.79
- 15 R 47108L KX 126 Instamatic Cartridge, 20 Exp. Net 3.29

FOR COLOR SNAPSHOTS

- 15 R 47140L CX-126 Instamatic cartridge, 12 Exp. Net 3.89
- 15 R 47348L CX-135 35mm Indoor/Outdoor, 20 Exp. Net 5.99

FLASHCUBES

For use with standard flashcube cameras. 4 flash pictures without changing bulbs. Pkg. of 3 cubes takes 12 pictures.

- 15 R 26326L Shpg. wt., 3 oz. Net 1.29

New Magicube Type X used with new Kodak series "X" cameras only. Pkg. of 3 cubes, takes 12 snapshots.

- 15 R 47330L Shpg. wt., 3 oz. Net 1.99



ACCESSORIES FOR MOVIE and STILL CAMERAS

MOTORIZED PROJECTOR-VIEWER FOR SUPER 8 MOVIES

Only
39⁹⁵

- No Screen or Dark Room Needed
- Automatic Rewind



Delivers sharp, clear pictures with even corner to corner brightness. Great for individual or small group use. Needs only 8 inches of space yet provides a 3½ x 4" picture. Operation is simple enough for children to view alone. Film automatically rewinds at the press of a button. View film in motion or in still life frame by frame. Features focus control. Projects with brilliant detail under normal lighting conditions. No need to set up a screen or darken the room. Handles reels up to 50 feet. Imported. Shpg. wt., 5 lbs.
15 R 71009 No Money Down* Net 39.95

DELUXE LENTICULAR SCREENS

- Automatic Lever-Type Handle Permits Smooth Easy Adjustment



Specially-designed, optically-correct lenticular screen is free of glare, sheen and hot spots. Amazing sharpness and color rendition. Durable vinyl fabric resists fire and fungus. Sturdy, secure tripod legs. Screen is 40 x 40". Shpg. wt., 10 lbs.
15 R 50052W Net 12.95
Same as above. Extra Large 50" x 50" Super Screen—Ideal for New Super 8 Movies. Shpg. wt., 12¼ lbs.
15 R 50219W Net 16.95


TABLE TOP SCREEN

22" x 30" Lenticular. Shpg. wt., 2 lbs.
15 R 87021W Net 2.95

DELUXE ELEVATOR TRIPOD

12⁹⁵

- 3-Sections Extend to 60"



Stability and minimum weight make for easy portability. Suitable for both still and movie cameras. Quick column lift allows you to raise camera in a jiffy and lock it at desired height. Reversible pan-tilt handle permits right or left handed operation at varying heights. 3-section non-binding aluminum tubular legs have grip-life internal lock and non-slip, protective feet. Constructed of sturdy lightweight die-castings and cycloc. Overall extended height: 64". Closed length: 22". Shpg. wt., 3¼ lbs.
15 R 68021 Net 12.95

2 x 2 SLIDE FILE

1⁹⁹



For 35mm, Instamatic slides—holds 300 2 x 2 cardboard slides or 150 aluminum, metal or glass mounts. Index card and permanent, molded-in numbering system. Made of polystyrene. Shpg. wt., 1¾ lbs.
15 R 59227 Net 1.99

G.E. OR SYLVANIA PROJECTION LAMPS

Exact replacement projection lamps for most movie and slide projectors. We will fill your order with either G.E. or Sylvania depending on stock availability. Imported. Shpg. wt., 6 oz.

Stock No.	ASA Code	Watts	Net Ea.
15 R 36713	BCK	500	13.40
15 R 36721	CBA	500	13.95
15 R 36564	CLS/CLG	300	4.60
15 R 36572	CYC	300	4.70
15 R 36580	CZA/CZB	500	6.80
15 R 36739	CZX/DAB	500	6.50
15 R 36598	DAK	500	6.10
15 R 36606	DCA	150	7.05
15 R 36614	DDB/DJA	150	6.50
15 R 36622	DDB	500	6.70
15 R 36630	DEF	150	8.10
15 R 49450	DET†	750	2.95
15 R 36648	DEK/DFW	500	6.95
15 R 36655	DFA/DJL	150	7.05
15 R 36663	DFC/DFN	150	6.50
15 R 36671	DFG	150	6.50
15 R 36677	DLS/DHX	150	7.80
99 R 71219	EDK ‡	500	1.99
15 R 36747	EGH	500	13.00

DUAL 8 AUTO-THREAD METAL REEL AND CAN

As Low As

79^c



A fully automatic self-threading take up reel. Designed for all standard 8 and super 8 projectors. Quality constructed with a precision diecast hub and sturdy flanges. Shpg. wt., 6 oz.
15 R 16178 400' Capacity Net .99
15 R 16186 200' Capacity Net .79

SEALED-BEAM MOVIE LIGHT

7⁵⁰

- Head Tilts for Bounce Lighting



Compact, powerful 650 watt tungsten sealed beam will provide sparkling, bright indoor movies. Features top mounting and convenient on-off switch. Will fit all new super 8mm cameras plus all standard 8mm cameras with tripod socket on top, with 6 ft. cord and exposure guide.
15 R 68013 Shpg. wt., 2 lbs. Net 7.50

DELUXE 650 WATT QUARTZ MOVIE LIGHT

- Head Tilts for Bounce Lighting
- For All Super-8 Cameras

11⁹⁵



Shoot brilliant movies indoors. Long life, quartz-bromine movie light for maximum output. Small, all metal unbreakable housing with built-in on/off switch. UL listed. With 6¼ ft. cord. Shpg. wt., 1 lb.
15 R 68005 Net 11.95

DELUXE ZOOM MOVIE CAMERA CASE

- Adjustable Shoulder Strap
- Nickel Plated Hardware

6⁹⁵



Holds substantially any super 8 camera with attached hand grip. Made of exquisite black vinyl material, firm core and fully lined, with French stitching. Ample space also provided for camera accessories; film, lens filters. Size 11 x 10¼ x 3¾. Shpg. wt., 2 lbs.
15 R 16053 Net 6.95

Microscopes For Beginners & Intermediate Students

900X 'ZOOM' STUDENT LABORATORY

Complete Outfit
For Only

24⁹⁵



- Zoom from 50 to 900 Power
- All Metal Construction
- All Dissecting and Mounting Materials
- Includes AC/DC Substage Illuminator
- With Attache Type Carrying Case

A complete microscope laboratory for the student and enthusiast. Provides all necessary material to explore the interesting field of microscopic research. Achieves magnification from 50X to 900X with combinations of the 3 objective lenses (5X, 20X, and 45X), and the fine ocular which zooms from 10X to 20X. Rack and pinion focusing assures clear, sharp images. The 900X scope features an optical condenser, plano mirror, and built-in 3-volt light powered by the AC adapter or 2 penlight batteries. Laboratory includes a complete dissecting kit with hand lens, blunt-end scissors, probe, scalpel, spatula, tweezers, and eyedropper, plus glassware, including: 11 blank slides, 12 cover glasses, 3 test tubes and beaker. Also includes: prepared slides, 2 bottled specimens, 4 slide preparation chemicals, 2 spare light bulbs, mounting balsam, and instructions. Less batteries. Imported.

Shpg. wt., 5 lbs. Net 24.95
99 R 70252 Replacement Bulb Net .22
99 R 71060 Replacement Bulb Net .22
99 R 62580 Battery (2 req.) Net ea. .10

80X TO 1200X 'ZOOM' MICROSCOPE SET

29⁹⁵



- 80X-1200X Magnification
- Complete Set of Dissection Instruments
- 4 Achromatic Objective Lenses
- All Metal Construction
- With Built-in Plano Mirror and Illuminator

Constantly variable magnification of 80, 100, 160, 200, 400, 600, 800 and 1200 times. Zoom eyepiece for less specimen adjustment and controlled detail magnification. Excellent dual knob rack and pinion coarse focus control, plus fine focus control. Stage includes optical condenser and aperture diaphragm. Spring loaded rack prevents damaging objective. Sub-stage illuminator-mirror combination for direct, incandescent, or reflected illumination. Includes 2 prepared slides, 4 blank slides, spatula, scalpel, probe, scissors, tweezers, and magnifying glass. Wooden case with carrying handle. Illuminator operates on penlight cells or house current, by means of an optional transformer. Less batteries. Imported. Shpg. wt., 5 1/2 lbs.

99 R 71409 Zoom Microscope Net 29.95
99 R 71060 Replacement Bulb Net .22
99 R 62580 Battery (2 required) Net ea. .10
TRANSFORMER—Permits use of house current for illumination of zoom microscope.
99 R 71102 Shpg. wt., 9 oz. Net 1.99

750X 'ZOOM' MICROSCOPE SET

13⁹⁵



- Variable Magnification
- 50X to 750X
- All Metal Construction
- Built-in Substage Illuminator
- 3 Coated Objectives

Ideal for student or hobbyist. Features advanced zoom type micro-optics. Zoom action permits smooth, vibration-free, variable magnification without disturbing stage or specimen. Three hard coated objectives set in a revolving "click stop" turret give magnifications of 50X, 75X, 200X, 300X, 500X and 750X. Zoom action permits choosing multiple magnifications without changing eyepiece or objectives. The eyepiece zooms smoothly from 10X to 15X. Illuminator operates with batteries or on ordinary house current with transformer supplied. Includes instructions, sample slides, 5 piece dissecting kit and wooden carrying case. Less batteries. Imported.

99 R 70450 Wt., 3 1/4 lbs. Net 13.95
99 R 71060 Replacement bulb Net .22
99 R 62580 Battery (2-Req'd.) Net .10

600X MICROSCOPE SET

7⁹⁵



- With Sub-Stage Light
- 75X-300X-600X
- Triple Revolving Turret

For the student—hobbyists—or budding scientist! Features built-in sub-stage light and three achromatic objective lenses giving magnification of 75X, 300X and 600X. Complete with 3 glass slides, 5-piece dissecting set and hardwood cabinet. All metal. Less batteries. Imported. Shpg. wt., 2 1/2 lbs.

15 R 64020 Net 7.95
99 R 62580 Battery (2-req'd.) Net ea. .10

Microscopes and Accessories



"MICRO'DAPTER"™



- Micro-photography!
- Astro-photography!
- Use Any Camera!

14⁹⁵

Microscope or Camera/Telescope Setup

Permits the use of any camera—even movie cameras—with practically all microscopes and telescopes. No need to remove the camera lens. Cross hairs are super-imposed on the image for centering. The image is automatically in focus for the camera when viewed in focus through the MICRO'DAPTER. Accessory sleeves permit the MICRO'DAPTER to be used with other than Society size microscopes. The MICRO'DAPTER may be used with any telescope by attaching to eyepieces of 29 mm (1 1/8") maximum diameter. Imported. Shpg. wt., 2 1/4 lbs.

99 R 70807 Net 14.95

DELUXE 1200X RESEARCHER MICROSCOPE SET

- 25X to 1200X in 12 Ranges
- Full Range Fine Focus Adjustment
- Integral Mechanical Stage
- Rotating Diaphragm
- All Metal Construction

Closely parallels the "Society" grade microscope. Four Huyghenian eyepieces: 5X, 10X, 15X P20X combine with four achromatic objectives: 5X, 10X, 40X, 50X to yield 12 combinations: 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 800X, 900X, 1200X. Dual knob rack and pinion coarse focusing with tension adjustment for slow motion. Micro-motion fine focusing adjustment. Spring loaded to prevent objective from driving through slide. 85mm x 85mm stage can be moved in any direction, with slide by 2 knurled screws while looking through the eyepiece. Sub-stage has rotating, 5-position diaphragm and 35mm plano/concave reflecting mirror. Stable horseshoe base. Complete with set of 5 basic dissecting instruments, 10 slides, pack of cover slips, tube of mounting fluid. All in a dovetailed wooden carrying case with handle and four rubber feet. Imported. Shpg. wt., 7 lbs.

99 R 70419 Net 44.95



44⁹⁵
No Money Down*

MICROSCOPE LIGHT

- Use with any Microscope
- Furnishes Bright, Even Light

350



Provides a bright, evenly lighted field of view. Height 4 1/2" Lamp may be raised or lowered to any desired height. Inclination and elevation joint permit swinging through 360° in both horizontal and vertical plane. Fully adjustable for transparent or opaque specimens, direct or indirect illumination. Invaluable where oblique light is necessary. Operates on 110-120 volts AC/DC. Self-contained cord and plug. With extra bulb. Imported.

15 R 64103 Shpg. wt. 1 1/4 lbs. Net 3.50

MICROSCOPE MECHANICAL STAGE

- With Graduated Scale • Vernier to 1/10th mm
- Attaches to Any Square Microscope Stage

Attaches to any square microscope stage 70 mm x 80 mm or larger. Accommodates slides up to 75 mm x 50 mm. Both lateral and front-to-back movement by rack and pinion. Adjustment scales are graduated in single millimeters with verniers reading to 1/10th mm. Essential accessory for all high magnification examination. Permits relocating any portion of a slide or charting the entire slide. Spring clip automatically accommodates slides of varying dimensions. Imported. Shpg. wt., 12 ozs.

15 R 64087 Net 9.95



MICRO-STANDARD MECHANICAL STAGE



24⁹⁵

- Locates Any Spot On A Slide, "On the Nose."
- Smooth Action—Horizontal and Vertical
- Foolproof Co-ordinate System

Graduated mechanical stage attaches to any "Society" size microscope stage such as Medica, Micro-Plex and Micro-Standard. Adjustable holder takes any slide up to 90 mm x 50 mm. Essential for methodical examinations such as is required under an oil immersion lens or in blood counting. Locates and relocates portion of the slide quickly and easily. Vertical movement by rack and pinion—horizontal movement by worm gear. Machine engineered scales, graduated in single millimeters with vernier reading to 1/10th mm. All slides can be charted by means of the co-ordinates of these scales. Spring clip automatically fits the slide into proper position. Imported. Shpg. wt., 1 1/2 lbs.

99 R 70385L Net 24.95

A HUNTING WITH THE MICROSCOPE.

How to prepare and study cultures—set up a microscope zoo and garden—grow micro organism—perform micro surgery. Illustrated with photographs and drawings.

10 R 60029 Shpg. wt., 8 oz. Net 1.50

B HOW TO DISSECT.

Tips on dissecting the digestive, reproductive, nervous, circulatory and structural systems of the earthworm, crayfish, grasshopper, starfish, squid, shark, frog, gladiolus, perch, lobster, octopus, snail, moths, barnacles, etc. Special projects: behavior of earthworms, food and oxygen in space ships, regeneration, micro-dissection, camouflage, etc. 128 pages, 82 photos.

10 R 60011 Shpg. wt., 8 oz. Net 1.50

C SLIDE PREPARATION KIT.


30 glass slides, 3" x 1", in a fitted, sturdy, cardboard container. Slotted guides hold slides upright for easy indexing. Includes slide covers and vial of mounting fluid. Imported.

15 R 21020 Shpg. wt., 3/4 lb. Net 2.19

D DISSECTING AND SLIDE MOUNTING SET.

All the necessary implements for dissecting, staining, mounting micro-subjects on slides: Seven dissecting instruments; 5 well slides, 20 blank slides; 50 cover glasses; 50 blank labels; blue stain; mounting fluid. All in a fitted wood case. Imported.

15 R 42067 Shpg. wt., 1 1/4 lbs. Net 5.95





LAFAYETTE

Microscopes

Research Equipment




The "Micro-Standard Mark II" 1500X SOCIETY STANDARD MICROSCOPE



CLINICAL AND
ADVANCED
ACADEMIC MODEL

99⁹⁵
No Money
Down*



- 25X to 1500X in 12 RANGES
- 4 ACHROMATIC OBJECTIVES IN ROTATING TURRET
- VARIABLE SUBSTAGE CONDENSER WITH IRIS DIAPHRAGM
- STANDARD SOCIETY OPTICS, BOTH OBJECTIVES AND EYEPIECES
- RIGID QUALITY CONTROL STANDARDS
- PAR FOCAL WITHIN 0.1mm

An unusually fine optical instrument designed especially for precision viewing requiring high magnification with an oil immersion lens. The outstanding features of great range and engineered versatility, optimum clarity and great magnification are usually found in microscopes costing much more.

OPTICAL SPECIFICATIONS: Three Huygenian eyepieces—5x, 10x, 15x, Four achromatic objectives—5x, 10x, 40x, 100x (oil immersion). FOCAL LENGTH: 170 mm. Monocular. FOCUSING: Coarse focus with adjustable tension. Fine focus vernier adjustment. Par-Focal within 1/2 rotation of fine focus control (0.1 mm.). Spring loaded safety device prevents objective going through slide. STAGE: Square stage: 95 mm x 95 mm. Integral mechanical stage, adjustable in any direction. Stage clips. SUBSTAGE: Focusing condenser with variable iris, diaphragm. 41 mm plano/concave mirror. Tilting Base. Black and chrome finish. Overall 12" high, 6 1/2" deep, 4 1/2" wide. Includes fitted wood cabinet with lock and key, 3 slides, bottle of cedar oil. Imported. Shpg. wt., 5 1/2 lbs.
99 R 71342W

Net 99.95

Micro-Plex —BINOCULAR-MONOCULAR RESEARCH MICROSCOPE

- 20X to 2000X • Interchangeable Binocular/Monocular Tubes
- Quadruple revolving nosepiece • Eight paired eyepieces
- Vernier calibrated mechanical stage



339⁹⁵
No Money Down*

An outstanding instrument with features of construction and design that will, without reservation, be appreciated by competent experts.

OPTICAL SPECIFICATIONS: Four achromatic, coated objectives 4X/0.15 n.a., 10X/0.25 n.a., 40X/0.65 n.a., oil immersion 100X/1.25 n.a. Eight paired eyepieces. Two each 5X Huygenian, 10X Huygenian, 15X peri-planatic, 20X Kellner. Dust proof quadruple revolving nosepiece.

FIELD SIZE: Field is 4.7 to 2.0mm for the 20X to 80X range, 1.88mm—0.8mm for 50X—200X, 4.7mm—2.0mm for 200X—800X, 1.88mm—0.8mm for 500X—2000X. Taken at 170mm focal length.

BODY: Interchangeable Binocular tube inclined 45°, graduated interpupillary adjustment, left eyetube adjusts for refractive difference between eyes. Monocular is extendable, graduated from 140 mm to 190mm. Parfocal at 170mm.

STAGE: Square stage 125mm x 130mm. Mechanical stage with 30 mm x 70mm range of movement with vernier accurate to 0.1mm. Slides of practically every shape and size, including petri dishes, can be used.


FOCUSING: Coarse focus by means of coaxial rack and pinion drive on dovetail slide. Fine focus by coaxial micrometer slow motion Meyer's type adjust. Graduated 1 division equals .002mm (2 micron intervals).

SUBSTAGE: Rack and pinion drive. Double lens bright field condenser (interchangeable) 1.2 n.a. iris diaphragm. Filter holder, stop against over-wind, 50mm plano-concave mirror. Satin black enamel finish. Chrome trim. 13 1/4 x 8 1/2 x 5 1/4" overall. Net weight 22 lbs. Includes fitted cabinet of fine grained oak with lock and key, 5cc of cedar oil, spring clips, spanner, blue filter. Imported. Shpg. wt., 26 lbs.
99 R 70401W

Net 339.95

Medica II —MEDICAL-BACTERIOLOGICAL MICROSCOPE

- Standard Society Size
- 20X to 1500X
- Vernier Calibrated Mechanical Stage
- Extendable Monocular Tube
- Par-focal at 170mm Tube Length



189⁹⁵
No Money Down*

Outstanding design—features unexcelled optically and mechanically—and priced far below any equivalent instrument.

OPTICAL SPECIFICATIONS: Four coated achromatic objectives. 4X/0.10 n.a., 10X/0.25 n.a., 40X/0.65 n.a., oil immersion 100X/1.25 n.a. Three eyepieces, 5X Huygenian, 10X Huygenian, and 15X peri-planatic.

BODY: Extendable, monocular tube. Graduated from 155 mm to 200 mm. Parfocal at 170 mm.

STAGE: Square stage 120mm x 125mm. Graduated mechanical stage with 50mm x 80mm range. Vernier accurate to 0.1 mm.

FOCUSING: Coarse focus by means of rack and pinion drive on dovetail slide. Fine focus by coaxial, lever type, micro-motion. Full 16 revolutions for 3mm travel. Spring loaded safety device prevents driving through subject. Focusing tension adjustable.

SUBSTAGE: Ring type, rack and pinion drive. Double lens bright field condenser (interchangeable) 1.2 n.a., iris diaphragm, filter holder, stop against over-wind, 50mm plano-concave mirror. 12 1/2 x 8 1/2 x 5 1/4" overall. Net weight 16 lbs. Includes fitted cabinet, 5cc of cedar oil, spanner, spring clips, blue filter. Imported. Shpg. wt., 19 1/2 lbs.
99 R 70393W

Net 189.95

LAFAYETTE TRU-ZOOM™

Wide Angle • Not a "Vari-Power"

One Control Zooms both barrels!

- 7X to 12X—or any Power in Between
- Center Focus—Right Eye Adjust—Plus Single Synchronous Zoom Control!


Sensational Zoom action holds even fast-moving subjects in perfect view. Sight in at 7-power—then Zoom up to 12-power (or any power in between) for closeup viewing. Full 40mm, objective lenses, hard coated achromats. Field of view is 323 feet at 1000 yds., at 7 power (6"), 289 feet at 1000 yds. at 12 power (5.5"). Prisms clamped in shock-resistant mounts. Lightweight alloy frame and body. Sealed against dust and moisture. Includes plush-lined, hard case and straps. Imported. Shpg. wt., 4¾ lbs.

99 R 71086

Net 49.95



49⁹⁵ No Money Down*



29⁹⁵



As Low As 18⁹⁵

DELUXE 7X35 WIDE-ANGLE BINOCULARS

- Doubles the Field of Ordinary Binoculars
- 578 FT. Field Of View at 1000 Yards
- Oversize Oculars • Exceptional Quality

A multi-purpose, precise 7x35mm binocular that is particularly adept for field studies. Wide-angle hard coated prisms permit brilliant and close-up details of sporting events, without sacrificing the image, as is the case with regular narrow angle binoculars. Field of view at 1000 yards is 578 feet! Center focus and right eye adjustment insure perfect focus. All optics are sealed against moisture and are properly collimated and aligned. Hard lined case for protective storage when not in use. Complete with neck strap. Imported. Shpg. wt., 3 lbs.

99 R 70195

Net 29.95

BINOCULAR MOUNTING CLAMP

Tripod adapter fits all binoculars by clamping around center post. Binocular can be stored in case with mount attached. Fits onto any standard camera tripod. Especially adapted for high powered binoculars. Imported. Shpg. wt., 6 oz.

15 R 42059

Net 3.50

MAGNI-BOOSTER

Converts Binoculars Into High-Powered Scope

- Magnifies Binocular power 2½ Times (7 Power becomes 17½ Power!)

Instantly converts standard binoculars into a high-powered all-purpose spotting scope with crystal clear magnification! Performs the function of usually bulky telescopes. Increases the power of your binoculars 2½ times making it possible to spot details

which cannot be seen with the binoculars alone. Ideal for slipping onto your binoculars when spotting game, checking target hits, or other uses where critical viewing is necessary. Easily slips off for standard binocular viewing. Fits over front lens of binocular with appropriate locking adapter (see below). Focuses with binocular controls or with its own focusing ring. Shpg. wt., 1 lb.

15 R 42018

Net 18.95

MOUNTING ADAPTERS

Stock No.	For Binocular Objective Rim Dia.	Net
15 R 42026	1¾" to 2" O.D. Shpg. wt., 5 oz.	3.29
15 R 42034	2" to 2¼" O.D. Shpg. wt., 5 oz.	3.29
15 R 42042	2¼" to 2¾" O.D. Shpg. wt., 6 oz.	3.29

VERSATILE BINOCULARS

Precise design—quality material—and expert workmanship. All lenses are hard coated—prisms clamped in lightweight alloy frame and body—sealed against dust and moisture—properly collimated and aligned. All are center focus with adjustable right eyepiece. Hard lined case and neckstraps included.

7x35 POPULAR, VERSATILE, ALL PURPOSE BINOCULARS. For the sportsmen—hunter—bird watcher—vacationer. High luminosity. Compact design. Field of view 367" at 1000 yards. Imported.

99 R 70187 Shpg. wt., 2¾ lbs.

Net 16.95

7x50 NAVY STYLE NIGHT GLASSES. Favored for marine use. The choice of professionals because of exceptionally high light gathering power. Superior image brightness. Field of view 372" at 1000 yards.

99 R 70161 Shpg. wt., 3¾ lbs. Imported.

Net 24.95

20x50 KING OF THE LONG RANGE. Hunters, mountain climbers, plane spotters, forest rangers—any long distance viewing and observation requirement. Field of view 157" at 1000 yards. Shpg. wt., 3¾ lbs.

99 R 70203 Imported.

Net 29.95

LAFAYETTE 8x24 MINI-SCOPE

- Includes 6x Super Wide-Angle (11°) Objective
- Fits in Palm of Hand
- Use as Close-up Magnifying Glasses



Only 13⁹⁵



Versatile, precision pocket telescope provides powerful 8-power optics, yet slips into your pocket. Ideal for travel, hiking or nature study. For a larger field, quick-change to the 6x extra-wide view 18mm lens. Pulls in the action at football, hockey, and shows. 24mm coated lens provides 435 ft. viewing area at 1000 yds., 18mm coated lens gives 575 ft. viewing area. With soft zippered case, wrist strap. Imported. Shpg. wt., 10 oz.

99 R 72159

Net 13.95

Arcturus

ARCTURUS 4 1/2" D. EQUATORIAL REFLECTOR

- 450X with Barlow Lens



89⁹⁵

No Money Down*

- Eyepieces and Barlow Lens For 450X, 300X, 225X, 150X, 90X and 45X • 900mm Focal Length • Micromotion Controls For Horizontal, Polar, Declination • 4 1/2" (114mm) F/8 Spherical Aluminized Quartz Mirror • Barlow Lens Included

4 1/2" spherical, aluminized quartz mirror gives wide, flat field of view and outstanding color definition. Three coated eyepieces provide magnifications of 45X, 150X, 225X; (with Barlow lens 90X, 300X and 450X). Fast resolving power of 1.5 seconds and 900mm focal length permits detailed viewing up to twelfth magnitude. 5X24mm right-angle, prismatic finder scope with cross hairs easily locates objects to be viewed. Micro-motion controls and equatorial mount with hour and declination circles provides complete control for tracking. Heavy-duty hardwood tripod with accessory tray adjusts from 33 to 60". Complete with lenses. Sun glass. Moon glass, Barlow lens. Scope size: 4 1/2" Dia., 36" long. Imported. Shpg. wt., 30 lbs. 99 R 72183WX Net 89.95

LAFAYETTE

Telescopes

Meteor 4" Reflector

- 264X with Optional Barlow Lens



39⁹⁵

No Money Down*

- Eyepieces for 132, 64X and 32X
- 4" (100mm) f/8
- Aluminized First Surface Secondary Mirror

A fine, compact professionally designed 4" reflecting telescope with carefully aluminized optics for exceptionally low light loss. Primary mirror is aluminized and quartz overlaid. Highly achromatic optical system features very low chromatic aberration. Adjustable wooden 48" tripod with tray brace and convenient optical sight permit easy field use on uneven surfaces. Rack and pinion drive assures smooth focusing. Lightweight aluminum body has white baked enameloid finish: Specs.: Mirror Dia.: 4" (100mm). Focal Length: 800 mm. Eyepieces: 6; 12.5; and 25 mm Huygenian. Resolving Power: 1.4 seconds. Supplied with stand, sun filter and three eyepieces. Imported. 99 R 72126W Shpg. wt., 10 1/2 lbs. Net 39.95
99 R 70542 Barlow lens for double power. Wt., 6 oz. Net 4.95

250x Astronomical Telescope



49⁹⁵

- Magnification up to 250x
- Fully coated 60 mm achromatic objective lens
- 700 mm focal length
- 5 x 24 mm view finder with crosshairs
- 2 Huygenian eyepieces plus a 2x Barlow lens

Achieve magnification from 55x to 250x with the use of the 2x Barlow lens included. Fully coated 60 mm achromatic objective lens provides exceptional light gathering power and very low chromatic aberration. 5 x 24 mm view finder with crosshairs for locating objects quickly. Star diagonal prism for right angle viewing. Sun lens for solar observation. Includes 2 Huygenian eyepieces, 55x H 12.5 mm and 125x H 5.5 mm. Mounted on sturdy wooden extension tripod with declination rod for vertical fine adjustment. Size 34"L x 60"H. Imported. Shpg. wt., 12 lbs.

15 R 21061W No Money Down*

Net 48.95

45x Terrestrial Telescope



14⁹⁵

- Fully coated 40 mm objective lens
- Adjustable focal length for 15x-30x and 45x
- View finder for locating quickly

Easy to use terrestrial telescope. Ideal for amateur astronomers, students, hobbyists. Built-in erecting system for righting stars. Fully coated 40 mm objective lens for high light gathering power. Adjustable focal length for 15x-30x and 45x magnification. View finder for locating quickly. Rack and pinion gear for easy focusing. Mounted on metal table tripod with rubber tips. Size: 27"L x 12"H. Imported. Shpg. wt., 4 lbs.

15 R 21079

Net 14.95

PEN-SCOPE

2¹⁹



- 8 Power Telescope
- 30 Power Microscope

The 8 power telescope with adjustable sliding focus barrel that extends to over 8 inches, collapses to 5 1/2" and fits easily in pocket. Barrel slips off to convert to a 30 power microscope. Nickel-plated metal case with pocket clip. Dia. only 5/16". Imported.

99 R 71987L Shpg. wt., 5 oz. Net 2.19

2X BARLOW LENS

4⁹⁵



Provides greater eye relief even on short focal length eyepieces. Sharpens definition and reduces image deterioration by permitting use of lowpower eyepieces to achieve high magnification. This also provides for greater illumination and a wider field. Accepts eyepieces of 24.5-mm (.97") O.D. and fits draw tubes of that size. Imported.

99 R 70542 Shpg. wt., 6 oz.

Net 4.95

Selected Scopes—Optical Accessories

LAFAYETTE 8-25X 30-mm ZOOM SPOTTING SCOPE

- Zoom Any Power From 8X to 25X
- Quick Focusing With Table Top Tripod

An outstanding varipower spotting scope that is ideal for any "spotting" need in field or general use...shooters, bird watchers, etc. Features 30 mm coated lens for brilliant viewing. Fingertip controls for quick zooming and focusing. Has a built-in camera tripod socket. Includes a table-top tripod with rubber-tipped legs that prevent scratching of furniture. Compact, lightweight and portable...ideal for taking it everywhere you go. Complete with black, zippered carrying case with convenient belt loop. Overall length of scope is 12". Imported. Shpg. wt., 3 lbs. Net 15.95



8-25X
15⁹⁵

DELUXE 13-40X 40-mm ZOOM SPOTTING SCOPE

• Zoom From 13x to 40x Power • 40 mm Objective
Same unique design as above but with extra power and larger 40-mm objective. With tripod less case. Overall Length 16". 15 R 64038 Shpg. wt., 2 3/4 lbs. Net 21.95

13-40X
21⁹⁵

15-30X ZOOM SPOTTING SCOPE



46⁹⁵
No Money
Down*

- Full Size 50mm Objective

Any power from 15X to 30X! Ideal for any "Spotting" Need. Pan-head, elevator tripod mount included. Perfect all round scope. Powerful, small lightweight, brilliant viewing. Minimum focusing distance 82 ft. All aluminum and chromed brass. Imported. Shpg. wt., 4 1/4 lbs. Net 46.95

30X, 60mm SPOTTING SCOPE



17⁹⁵

- With Case Tripod

The perfect companion for shooting, hunting and nature fans. Field of view is 85 feet at 1000 yds.! High relative brilliance due to 60mm objective lens. All optics are coated. Equipped with a 1 1/2" tripod and zippered leather carrying case. Minimum focusing distance 60 ft. Imported. Shpg. wt., 2 3/4 lbs. Net 17.95

10X30mm TELESCOPE with TRIPOD



8⁹⁵

- Portable-Compact-Lightweight

A 10 power, 30mm internal (front) focus telescope that is compact, lightweight and portable—ideal for taking it everywhere you go. Features coated achromatic lenses. Has built-in camera tripod socket. Sturdy tripod supplied with rubber-tipped legs. Minimum focusing distance 14 ft. 15 R 64046 Shpg. wt., 1 3/4 lbs. Net 8.95

LAFAYETTE BINOCULAR MAGNIFIER

- Leaves Hands Free
- Reduces Eyestrain

Only
8⁹⁵



- With 3 Lenses

Ideal for technicians, inspectors and hobbyists. Precision ground and polished lenses for very close work without eyestrain. Headband adjusts to any head size. Lenses can be changed with pushbutton ease for three magnifying powers. Flip up viewer may be worn over eyeglasses. Supplied complete with 3 lenses—2X, for 9" working distance; 2.5X for 5 1/2" working distance and 3X for 4 1/2" working distance. Imported. Shpg. wt., 1 lb. Net 8.95

9 R 72069

MAGNA SIGHT-MASTER 3-D BINOCULAR MAGNIFIER

- Leaves Hands Free
- Reduces Eyestrain
- 3-Dimensional
- Can be Worn With or Without Glasses

As Low
As
4⁹⁵



A precision optical instrument enabling anyone to do very close work and see it clearly in 3 dimensions. Adjusts to any head size comfortably. No moving parts to replace. Ideal for hobbyists, repairmen, inspectors and technicians. Available in 4 sizes. Imported. Shpg. wt., 9 oz.

15 R 20055 1.75X, 14" Working Distance Net 4.95
15 R 20063 2.25X, 10" Working Distance Net 4.95
15 R 20071 2.75X, 8" Working Distance Net 5.75
15 R 20089 3.5X, 4" Working Distance Net 6.50

LAFAYETTE OPTICAL MICROMETER

- Direct measurements to .005"
- Measures Diameters - Radii - Angles
- Linear scale in inches

High quality optical micrometer using a triplet lens system of approximately 7 power. Triplet system affords a wide flat field of view. Extremely accurate reticle of etched glass. 0.5 inch linear scale calibrated to .005 inch. 10 mm scale calibrated to .2 mm. Hole diameters from 1/4" to 1/2" and from .005 to .05". Thickness scales from 1/4" to 1/2". Radii from 1/4" to 3/8" and angles from 0 to 90°. Accurate to edge of 1" field. Adjustable focus. Complete with leather case. Imported. Shpg. wt., 8 oz. Net 7.95

99 R 70757L

Net 7.95



PROJECT-A-SCOPE

- Projects Giant Pictures in Color or Black and White
- Films or Negatives Not Needed

Handsome projector molded of heat and abuse resistant, hi-impact plastic for long life. Casts sharp, giant-size enlargements on any white wall or screen in brilliant color or black and white. Simple to operate. Can be used by students, artists, lecturers and demonstrators. Children can project comics or story books to amuse themselves and their friends. Uses ordinary household bulbs. U/L listed 110 volts, AC-DC. Shpg. wt., 2 1/2 lbs. Net 6.50

15 R 50011

Net 6.50



*See Page 22 for Full Credit Details on Easy Pay Plan

Lab and Field Research Equipment

80-WATT ULTRASONIC CLEANER



- High Capacity— $\frac{1}{2}$ -Gallon Tank
- 80-watt Average Output Generator

A new standard of time-saving, immaculate cleaning. A special transducer located in the solvent tank is excited by an ultrasonic generator (at 90,000cps). It sets the solvent in agitation, producing microscopic bubbles (cavitation) which disintegrate dirt particles. Soil can be removed from the finest crevices without damage to delicate parts. Ultrasonic Cleaner consists of a 80-watt pulse generator and a $\frac{1}{2}$ -gallon cleaning tank. Tank constructed of stainless steel with 4A grade polish. Specifications: Input 110-117V, 50/60 cycles; Output 90 kc—80 watts, avg., 320 watts peak. Tank, inside dim., 5 $\frac{1}{4}$ " x 5 $\frac{1}{4}$ " x 4". Complete with 4' connecting cable. Exterior of Tank and generator finished in baked enamel gray. See listing below for solvents. Shpg. wt., 20 $\frac{1}{2}$ lbs.

15 R 85017W No Money Down* Net 149.95

30-WATT ULTRASONIC CLEANER

For cleaning small manufactured parts — electrical contacts, contact lenses, dentures, bearings, jewelry, etc. Generator output 30 watts average, 120 watts peak. Inside tank dimensions: 3 $\frac{3}{4}$ " x 3 $\frac{3}{4}$ " x 3" deep, 1-pint capacity. See listing below for solvents.

15 R 85025W No Money Down* Shpg. wt., 24 lbs. Net 99.95

120-WATT ULTRASONIC CLEANER

An extra high capacity cleaner widely used in electronics, automotive and other precision instrument fields. Valuable in all areas of applied medicine. $\frac{1}{2}$ gallon polished stainless steel tank size (inside): 12" x 6" W x 6" H. Generator output: 90 KHz @ 120 watts average. 480 watts peak. With illustrated reference manual. See listing below for solvents.

15 R 85033W No Money Down* Net 259.95



40-WATT ULTRASONIC CLEANER

69⁹⁵

Model LP-1MD. Completely self-contained easy-to-handle ultrasonic cleaner capable of serving a variety of cleaning applications. Automatic 5-minute time switch turns unit off when cleaning cycle is finished. Control dial for Low and High Power Operation. Stainless Steel worktop and sides protect unit against spills and splashes. One-Pint Stainless Steel cleaning tank cannot be marred or harmed by any normal cleaning agent or solvent, warm or cold. Ideal for removing grease, tar, wax, sulphides, fluxes, and fingerprints from components, miniature mechanisms and a variety of other precision parts. Generator Freq.: 90 KHz., RF input power: 40 watts. Uses no tubes or transistors. Dimensions 9 $\frac{1}{2}$ " x 5 $\frac{1}{4}$ " x 6". See listing below for solvents. Shpg. wt., 7 $\frac{1}{2}$ lbs.

15 R 23026 No Money Down* Net 69.95

ELECTROMATION SOLID STATE ULTRASONIC CLEANER

29⁹⁵

High frequency ultrasonic cleaner vibrates 77,000 Hz., per second. Ideal for hobbyist, artist, draftsman. Cleans jewelry, coins, contact lens by disintegrating and dissolving dirt particles. Transistorized, all metal unit with stainless steel cleaning cup 2 $\frac{1}{4}$ " dia. x 1 $\frac{1}{2}$ " deep. Sample cleansers, jewelry brush and tweezers included. 115 volts, 60 Hz. Shpg. wt., 3 lbs.

15 R 23042 Net 29.95

Ultrasonic Cleaning Chemicals, Shpg. wt., 10 $\frac{1}{2}$ lbs. per gal.	
15 R 85041 Ammoniated Detergent, 1 gal.	Net 6.35
15 R 85058 Detergent Concentrate, 1 gal.	Net 6.50
15 R 85066 Zero Residue Fast Dry Solvent, 1 gal.	Net 5.70

SUGAR REFRACTOMETER



- A Modified Abbe Design—Reads Percentage of Sugar in Solution
- Completely Portable—Fits in Pocket
- Accuracy $\pm 0.2\%$ for Low Range Instruments— $\pm 0.5\%$ for High Range

An accurate hand sugar refractometer. Designed for accurate measurements of the percentage of sucrose or dissolved solids in solution. Particularly suited to the sugar industry. Permits accurate measurements, in the field, of sugar percentage in fruits and vegetables. Equally suitable for use in the "juice" industry, in canning plant lab, candy, chocolate and jelly industries, soft drink plants, breweries, agricultural as well as in other phases of chemistry and clinical pathology. Simple in operation—no moving parts except the focusing eyepiece. Completely color corrected optical train, perfectly clear field. Range of 0-32%, reads directly to 0.2%, easily estimated reading to 0.1%. Accuracy $\pm 0.2\%$. Includes adjusting screw driver, temperature correcting tables, leather carrying case, and straps. Imported. Shpg. wt., 1 $\frac{1}{4}$ lbs.

99 R 70369L No Money Down* Net 39.95

DIRECT VISION SPECTROSCOPE



- Focusable Field

A simple accurate instrument for the spectroscopic analysis of emission spectra from light sources, vaporized chemical salts, solids, liquids and the Solar Spectrum. Convenient for experimental and student use. A broad dispersion field of high intensity is obtained from several dispersing prisms of matched glass, while a high grade optical system yields good resolution, sufficient to separate 5769.6Å from 5790.6Å in the spectrum of a fluorescent lamp. The slit is preset and can be focused sharply by means of an eye piece draw-tube, assuring easy viewing and establishment of Fraunhofer lines of the Solar spectrum or bright lines of the emission spectra. Metal parts are made of chrome-plated, corrosion-proof brass. Supplied in fitted case. Imported. Shpg. wt., 10 oz.

99 R 70773L Net 21.75

ULTRA-VIOLET HAND LAMP



An economical, compact, self-contained source of both short wave and long wave ultra-violet light of medium intensity. For lab, home and field use where high intensity is not required. Operates from either AC house current or batteries. Easily carried—weighs only 1 lb., 14 oz. Portability extends its uses. Typical applications: fluorescence demonstrations, mineral determination, prospecting. Special circuit has been designed for high efficiency, low drain operation. Tubes are easily replaced. Separate, extra large filters for short wave and long wave and switch for independent operation of each source. Includes 6 identified mineral samples and a 12-page book which describes some of the many uses of ultra-violet radiation. Comes complete ready for use—for 110-120 volts 50/60 cps. AC. Less batteries (2-45V "B" batteries required for portable use). Battery adapter case optional. Size: 5 $\frac{1}{2}$ " x 2 x 8 $\frac{1}{2}$ ". Shpg. wt. 4 $\frac{1}{2}$ lbs.

15 R 45045 Net 39.75

Battery Adapter Case with adjustable shoulder strap. Shpg. wt., 1 $\frac{3}{4}$ lbs.

15 R 45052 Net 8.50

45-Volt "B" Battery (2 required for battery operation).

32 R 48101 Shpg. wt., 2 $\frac{1}{4}$ lbs. Net ea. 3.27

U/V FLUORESCENCE ACCESSORY SET

Contains 16 different items including: invisible water paint (4 colors), invisible tracer powder, invisible writing ink, phosphogram, UV transmitting and absorbing clear plastic, invisible dye, 10 yds. fluorescent elastic cord. 48-page "Story of Black Light" book of experiments. (Not illustrated). Shpg. wt., 2 $\frac{1}{2}$ lbs.

15 R 45060 Net 8.95

Trindl

ARC Welding Outfits

WITH CONTINUOUS MANUAL DUTY CYCLE



Complete
80 AMP
Outfit
No Money Down®

79⁹⁵



Complete
135 AMP
Outfit
No Money Down®

124⁹⁵

80 AMP ARC WELDING OUTFIT

- Continuous Manual Duty Cycle
- 9 Heat Ranges, 20-80 Amps.

Model 80A hardworking portable welder, industrial type. Built for continuous welding on a wide variety of jobs for maintenance men, plumbers, steam-fitters. Repair-money-saver for farm, home, garage, shop. Dual coil construction. Primary amps. 29. Power factor, 80%. Arc volts, 25. Welded

HEAVY-DUTY 125 AMP ARC WELDING OUTFIT

Model 125A above, but super-industrial type for fast production and maintenance, featuring 16 instant heat stages ranging from 20 to 125 amps; handles 1/8" to 3/8" rods on

- Handles 1/8" to 3/8" Rods on Work up to 1/4" thick

metal cabinet 9 1/4"x12 1/2"x9 1/4". Complete with head shield, ground, power and welding cables, assorted electrodes, electrode holder, 3-prong plug, ground clamp and easy instructions. Plugs into a 115-volt line fused for 30 amps 50/60 Hz AC. Shpg. wt., 36 1/4 lbs. 13 R 20514W Net 79.95

HEAVY-DUTY 125 AMP ARC WELDING OUTFIT

metal up to 1/2" thick. Plugs into 115 volts line fused for 35 Amps. Shpg. wt., 79 lbs. 13 R 20522WX Net 124.95

CARBON ARC TORCH

Increases versatility of any arc welder, AC or DC. Welds, solders, cuts, etc., all metals. Handles up to 1/4" carbons; use in heat ranges up to 125 amps. Two 5 ft. cables, lugs, four 1/4" cored carbons. Shpg. wt., 2 lbs. 13 R 20530 Net 9.95

MINI-TORCH BLOW TORCH AND SOLDERING KIT

- Pencil Size With Pinpoint Flame-Solder-Brazes
- Kit Includes 2 Chargers

Complete
Kit

3⁹⁵



An extremely useful and highly efficient miniature blow torch. A high heat, 3500°F, pin point flame delivers instant power. Unit is less than 7" long from end to end. Charged by a butane cartridge which gives 30 minutes of continuous service. May be turned on or off at any time. Economical throw-away cartridges can be stored indefinitely. Entire unit weighs approximately 4 oz. A true portable high heat torch. Ideal for repairs on wiring—radio—TV installations—appliances—pipes and plumbing. Wonderful for making putty soft and workable. Supplied complete with 2 chargers, soldering tip and coil of rosin core solder. Shpg. wt., 8 oz. 13 R 45016 Net 3.95

13 R 45073 Extra-chargers. Pkg. of 4. Shpg. wt., 7 oz. Net 1.39

MICROFLAME BRAZING ROD KIT

- For Hobbyist, Model Maker, Technician, etc.



Deluxe Brazing Kit enables you to securely join together all the various metals found in the home or shop. Includes 18 silver and 6 aluminum solder rods, silver and aluminum flux, sandpaper, "Fiberfax" board, and instruction manual. Shpg. wt., 1/2 lb. 14 R 42540 Net 4.95

BRAZING RODS

Silver Solder Brazing Rods (Pkg. of 12—6" long) 14 R 42557 Shpg. wt., 4 oz. Net per Pkg. 2.59
Aluminum Brazing Rods (Pkg. of 6—6" long) 14 R 42565 Shpg. wt., 2 oz. Net per Pkg. .99

DYNAMIC

MARK
35

PORTABLE ELECTRIC ARC WELDER



No Home Workshop
Should Be Without One

Complete
Ready To Use

19⁹⁵

- Weld-Brace-Solder-Cut
- Produces 11,000° Heat Operation on 110 Volt Line


Practical, dependable unit that produces professional welding—Save time, money by making your own repairs. Cuts and welds up 1/4" metals with 1/8" welding rods and 1/4" carbons. Completely portable. Simple instructions explain how to make spot repairs. Weld-brace-solder-cut on most metals. Ideal for use around home-shop-farm-even repair auto bodies. Includes welding and carbon rods. Protective mask, holders, 10 ft. H.D. cables, ground clamp, brazing rods, flux, solder and instruction manual. For 115V AC or DC. Fused for 30 amps. Shpg. wt., 7 1/4 lbs. 13 R 20548 Net 19.95

MICROFLAME®

GAS WELDING TORCH SETS

as low as

17⁹⁵



WELDS, BRAZES,
CUTS MOST METALS



Completely Self-Contained Torch Produces 5000°F Pin-Point Flame

(A) Miniature Torch Set

Miniature gas welding torch for precision welding, brazing and cutting jobs. Pin-point flame produces high heat in a very selective area. Many uses in printed circuit repair, jewelry repair, shop, dental lab, tool and model making. Hand-held, lightweight torch has self-contained oxygen and LP cylinders which are easily replaced. Up to 20 minutes of continuous heat. Cylinders last indefinitely when not in use. Complete torch with 3 tip sizes, 1 cylinder butane, 1 cylinder oxygen, gaskets and instructions. Overall size: 5 1/4" L x 2 1/4" W x 1 1/4" thick. See additional accessories at left.

14 R 42508 Shpg. wt., 1 1/4 lbs. Net 17.95
14 R 42516 Butane Cylinder (Pk. of 2) Net .99
14 R 42524 Oxygen Cylinder (Pk. of 2) Net 1.49

(B) Deluxe Miniature Torch Set

Deluxe miniature torch set is similar to basic torch set above but includes 6 oxygen cylinders, 3 LP gas cylinders, spark igniter, welding tips, 10 Silver Solder Brazing rods, a two-way bench bracket for mounting on bench or pegboard, Jar of Flux plus booklet on "How to Weld" properly. Comes with storage case. Shpg. wt., 2 1/2 lbs.

14 R 42532 Net 26.95
14 R 42516 Butane Cylinder (Pk. of 2) Net .99
14 R 42524 Oxygen Cylinder (Pk. of 2) Net 1.49

*See Page 22 for Full Credit Details on Easy Pay Plan

Weller

Dual-Heat Soldering Guns-Irons



A

As Low As

6²⁵

B



D

As Low As

145/210
WATTS

9⁷⁵

A 100/140 WATT "EXPERT" SOLDERING KIT

- Includes Gun, 3 Tips, Wrench, Flux Brush, Aid Tool, Solder, Sturdy Carry Case Plus Instructions
- Prefocused Spot-Light Illuminates Work
- Dual Heat Gun — UL Listed

MODEL 8200-PK. Just the thing for the novice or professional. Compact design and built-in prefocused spotlight eliminates maneuvering difficulties. Break-proof plastic utility case can be used to hold other parts or tools. Weller Expert Soldering Kit features the 8200 gun with exclusive tip Grip which assures constant heat. Dual heat feature gives choice of 100 or 140 watts with the pull of the trigger. Accessories include 3 durable soldering tips, tip changing wrench, nylon flux brush, soldering aid to facilitate difficult connections and all purpose solder. All the items you need for first-class solder connections are packed in a high impact plastic case. UL listed.

13 R 39159 Shpg. wt., 4 1/4 lbs. Net ea. 8.95
Lots of 3 Net ea. 7.65

B 100/140 WATT DUAL-HEAT GUN

Model 8200. Dual heat solder gun only, featured in above kit. Includes tip, instruction book. 120VAC 60 Hz. UL listed.

13 R 39142 Shpg. wt., 3 lbs. Net ea. 7.25
Lots of 3 Net ea. 6.25

PROFESSIONAL SOLDERING IRONS



Professional lightweight soldering iron designed for miniature soldering, kit building and production work. Extremely rugged stainless steel barrel construction. Long life industrial grade double coated tips. High efficiency. Popular pencil styling. Only 7 7/8" long; 1 3/4 oz. Complete with tip and 2 wire cord. For 120 Volts, 60 Hz AC. Shpg. wt., 7 oz.

Stock No.	Mfg. No.	Description	Net Each	1-11	12+
13 R 39415	WP-25	25 watt iron, with 1/8" tip	4.95	4.45	
13 R 39597	WP-40	40 watt iron, with 1/8" tip	5.80	5.25	

WELLER AUTOMATIC GLUE GUN KIT

Complete with 7 Sticks of Glue, Caulk, Stand and Case



Only **9¹⁵**

- 30 Second Setting

The automatic electric glue and caulk gun features rapid heat up, indicator and work light, automatic glue feed, drip proof with automatic flow control valve. The glue sets by cooling—instead of drying—in about 20 seconds. Firm bond in just 30 seconds. Includes 7 sticks of glue, caulk, stand and a handy case. Capacity 150 W., for 120 VAC, 2 wire cord. Shpg. wt., 2 1/2 lbs.

13 R 39605			Net 9.15
13 R 39613	Pkg. of 20 Glue Sticks	Shpg. wt., 6 oz.	Net 1.20
13 R 39621	Pkg. of 20 Caulk Sticks	Shpg. wt., 6 oz.	Net 1.20

C 240/325 WATT HEAVY DUTY SOLDERING KIT

MODEL D-550 PK. A Professional Heavy Duty soldering Kit featuring the dual-heat 240/325 watt Weller gun. Everything needed for hundreds of applications in Hobbies, Shopwork, Household repairs. Case can be used as tool kit lunch box or tackle box. Kit contains D-550 Solder gun. All purpose solder, Cutting Tip, Soldering Tip, Smoothing Tip, Tip Changing Wrench and Instruction Booklet. Replacement and accessory tips are available at low cost to fit special applications. Entire kit is enclosed in a high impact plastic case with carrying handle. UL listed. Shpg. wt., 4 1/2 lbs.

13 R 39183 Net ea. 14.15

Lots of 3 Net ea. 12.75

Model D-550 240/325-Watt Heavy Duty Soldering Gun, UL listed Shpg. wt., 3 3/4 lbs.

13 R 39175 Net ea. 11.65

Lots of 3 Net ea. 10.45

D 145/210 WATT PROFESSIONAL SOLDERING GUN

MODEL D-440. New High Wattage. Guns—these latest professional Model Soldering guns have everything! Increased wattage—dual spot-lights—rugged plastic case—featherweight balance. Come equipped with cord, plug and one tip. For 110-120 volts, 60 Hz, AC. Model D-440. Dual-heat type. 145/210 watts. UL listed. Shpg. wt., 3 3/4 lbs.

13 R 39167 Net ea. 10.80

Lots of 3 Net ea. 9.75

WELLER REPLACEMENT TIPS & PARTS

Stock No.	Type	Description	Avg. shpg. wt., 3 oz.	Net
13 R 39191	7300	Copper Tip, pkg. of 2, for B, S-107, D-207		.79
13 R 39209	8125	Plated Tip, pkg. of 2, for 8200, 8100B		.79
13 R 39217	8125N	Tip Nuts with Tip for 8200, 8100B		.79
13 R 39225	7135	Copper Tip, pkg. of 2, S-400, D-440, 8100		.79
13 R 39233	7135N	Tip Nuts with Tip for S-400, D-440, 8100		.79
13 R 39258	7250N	Tip Nuts, Tip, S-500, D-550, 8250A		.79
13 R 39274	6110	Cutting Tip for D-440, 8100, 8200, 8100B		.79
13 R 39282	6120	Smoothing Tip for D-440, 8100, 88200		.79
13 R 39290	6130	Cutting Tip for D-550, 8250A		.79
13 R 39308	6140	Smoothing Tip for D-550, 8250A		.79
13 R 39316	7323	Switch for all Single-Heat Models		1.20
13 R 39324	7324	Switch for all Dual-Heat Models		1.20
13 R 39423	ST-1	1/4" Screwdriver Tip for WPS		1.00
13 R 39431	ST-2	3/8" Screwdriver Tip for WPS		1.00
13 R 39449	ST-3	1/2" Screwdriver Tip for WPS		1.00
13 R 39530	ST-4	3/4" Screwdriver Tip for WPS		1.00

SOLDERING IRON KIT



4¹⁵

- Develops 750°
Tip Temperature

Model SP-23-K perfect iron for hobbyist and professional. Pencil tips permit accurate soldering of connections or joints. Kit contains: 25 watt iron; 5 ft. 60/40 Rosin core solder; 3 pre-tinned plated copper tips; solder aid tool and instructions.

13 R 39456 Shpg. wt., 3/4 lb. Net 4.15

Model SP-23 25 Watt Soldering Pencil.

13 R 39464 Shpg. wt., 1/2 lb. Net 2.75

Cone shape tips for SP-23 Iron.

13 R 39548 (pk. of 2) Net .79

Soldering Guns—Irons and Aids

LAFAYETTE SOLDERING GUN

- Easy-To-Handle Pistol Grip
- Ideal for Printed Circuits and Miniature Work

2¹⁹



Comfortable, contoured grip offers long periods of use without strain. 30-watt ventilated element is just right for working on printed circuits and miniature electronic equipment. Designed for extra long life and dependable service. Easily replaceable tip. Imported. 115 VAC. Shpg. wt., ¾ lb.

99 R 80814 Net 2.19
99 R 80285 Replacement Tip. Shpg. wt., 2 oz. Net .39

LAFAYETTE 30-WATT SOLDERING PENCIL

- Lightweight
- Exceptionally Cool Running!

1⁷⁹



Nine inches long—weighing a mere 2 oz. less the cord—for reaching easily into “parts-packed” chassis. Especially suited for precision electronic wiring. Highly stable heating assures long life. Replaceable screw-in, nickel plated copper tip. 110-120v AC/DC.

Imported. Shpg. wt., ½ lb.
99 R 80277 Net 1.79
99 R 80285 Replacement Tip Net .39

ORYX-TELVAC — 15 W. MINIATURE PLUG-IN SOLDERING IRON



- No Transformer
- Weighs Only 1 oz.

8⁹⁵

Model 115-15J. 15 watt miniature plug-in iron for light production, laboratory, and service use. Furnished with 4½' cord. No transformer. Heats quickly in about one minute to 725°F. Supplied with ⅜" J tip. Ready to plug in. For 110 V AC.

13 R 78181 Shpg. wt., 6 oz. Net 8.95

Turner BLOW-TORCH KIT

Model MT-99 Everything the home handyman needs to sweat fittings, solder and bend metal. All brass torch with improved pencil point burner assembly, heavy duty burner tip for larger flame, chisel point solder tip, brass flame spread, spark lighter and tank of fuel. Durable steel chest. UL listed. 6x 10¼x13". Wt., 5 lbs.
13 R 26503 Net 8.95
Super capacity fuel tank. Fits all standard propane torches, stoves, lanterns, etc. Shpg. wt., 2¼ lbs.
13 R 26511 Net 1.49



8⁹⁵

LOCKING FORCEPS



All stainless steel 5½" long. They have unusual holding qualities necessary in many servicing situations. Shpg. wt., 4 oz.
14 R 23011 Straight Nose Net 2.89
14 R 23029 Curved Nose Net 2.99

5 PIECE HEAT SINK KIT



1³⁹

- Use as a Third Hand

Set of 5 spring loaded aluminum heat sinks to protect components while soldering. Includes 1½" and 2½" straight and bent jaws, and one 2½" with magnetic base for use as a third “hand.”
14 R 15317 Shpg. wt., 4 oz. Net 1.39

25/450 WATT HEAVY-DUTY SOLDERING KIT



13⁹⁵

- Features Automatic Thermal Regulation

Model 450K4. Complete soldering kit designed to handle every soldering job from the most delicate printed circuit to rugged sheet metal work. Kit contains Model 450 25/450 watt gun that automatically regulates heat to suit the job and three interchangeable tips for 25 to 450 watts of heat power. Complete with solder and convenient carrying-case. UL listed. Shpg. wt., 4 lbs.
13 R 65360 Net 13.95

LIGHTWEIGHT SOLDERING PISTOL



4⁷⁵


- Instant Heat—Fast Cooling
- Spotlight Focuses on Work
- Trigger On/Off Switch

WEN 75. A finely balanced soldering pistol for delicate and heavy jobs. Draws only enough current necessary with ATR—50w surge and 30w operating produces 100w heat. Transformer voltage is low for cool handling. 120V AC. UL listed. Shpg. wt., 1¾ lbs.
13 R 65279 Net 4.75

WEN REPLACEMENT TIPS

Shpg. wt., 3 oz.		WEN REPLACEMENT TIPS	
Stock No.	Type	Description	Net
13 R 65220	45F7	25-100w Tip for 222,450	1.39
13 R 65238	45M7	100-200w Tip for 222,450	1.39
13 R 65246	45A7	200-450w Tip for 450	1.39
13 R 65204	75A7	Std. Tip for 75	1.09
13 R 65212	75B7	Fine Tip for 75	1.09
13 R 65295	1984	Repl Tip for 100	.49
13 R 65253	45S7	Plastic Cutter Attachment for 222 and 450	.69
13 R 65267	45P57	Flat Iron Attachment for 222 and 450	.69

BEAU-TECH SOLDERING AIDS



Hard-chrome plated tips to shed solder with both ends insulated from one another. Spade end for scraping joints, connections or reaming out lug holes. Shpg. wt., 3 oz.

Stock No.	Net ea.
14 R 24019 Printed Circuit-Straight Tip	.99
14 R 24027 Printed Circuit-Angled Tip	.99
14 R 24035 Printed Circuit-Scraper Tip	.99
14 R 24043 Straight Tip	1.19
14 R 24050 Angled Tip	1.19

You Can Depend On Lafayette For Quality Tools—Low Prices

Lafayette Cat. No. 720 343

Ungar Standard Line Soldering Tools

777 CLEAN-ROOM SOLDERING HANDLE



2⁰²

- Fatigue-free, Pastel Colored
- Convection Cooled Polypropylene Grip

777 pencil-type irons sport a cool-to-hold grip! Spring sockets accept a wide range of thread-in elements, tips and tiplets, give you the right tip and the right temperature. For exacting work on miniature, sub-miniature and printed circuits. Full length insulated cord. UL listed. 5" long. Shpg. wt., 5 oz.

Stock No.	1-0	Net ea. 10-49	50 and up
13 R 21868	2.02	1.66	1.51

HEATING UNITS



For 777 and 776 Handles

For use interchangeably with any tipletp except * for 800 and † for 100 series only iron base, silver plated. Av. shpg. wt., 4 oz. For 115V, AC-DC.

No.	Type	Description	Fig.	Net Each		
				1-9	10-49	50 UP
13R21405	4045*	Super Hi-Heat 850° 47½ W	1	3.67	3.01	2.75
13R21413	4035	Super Hi-Heat 850° 47½ W	13	3.67	3.01	2.75
13R21421	4037†	High-Speed 900° 47½ W	23	3.67	3.01	2.75
13R21439	1235	Hi-Heat 750° 37½ W	1	2.53	2.08	1.90
13R21447	535	Standard 650° 23½ W	1	1.75	1.44	1.31
13R21454	1237†	Hi-Speed 900° 37½ W	22	2.53	2.08	1.90

SOLID STATE SOLDERING GUN

Only 10⁹⁵



- Hi-Lo Switch, Instant Selection of 500° or 900° F

Model 6760 Solid state soldering gun with easy-to-set dual heat control for fast 500° or 900° heat at the flick of a switch. No changing elements necessary. Designed for solid state kit construction, servicing and the professional. No bulky, heavy transformers to cause fatigue and get in the way. Electrically isolated tip for safe, damage-free soldering of IC's and FET's. With pyramid tip. For 117 VAC. Grounded cord set. UL listed. Shpg. wt., 1¼ lbs.

	1-3	4-11	12-up
13 R 20829	Net ea. 10.95	9.95	8.95
13 R 20837	Replacement Tip 6755 (long chisel)	Net .43	
13 R 20845	Replacement Tip 6753 (short chisel)	Net .43	
13 R 20852	Replacement Tip 6754 (pyramid)	Net .43	

344 Lafayette Cat. No. 720

7070 TECHNICIANS SOLDERING KIT




- Interchangeable Tips & Heating Units
- Complete with Handle. 37½W Heating Unit, 3 Tips,

5⁹⁸

Worthy soldering package for electronic assembly and service. Features perfect balance handle with "Clean-Cool" grip. #1237 heating unit. 3 interchangeable thread-on-copper tips. UL listed. Shpg. wt., 8 oz.
13 R 21900 1-5, Net each 5.98
6-up 4.92


TIPLETS and MINI-TIPS



Thread-in and thread-on soldering tips. Made of super tough copper alloy. The PL series is iron clad and silver plated. Others are unplated. The 100 series Mini-Tips, ¼Lx½" O.D., are used with 1237 and 4037 units only. The 300 series tiplets, 1¼Lx½" O.D., are used with heating units 535, 1235, 4035 and with the Princess soldering irons. The 800 series Tiplets, ¾" O.D. for high heat transfer, are used with the 4045 unit. 833 and 834 1¼"L, 823 and 824 are 1"L. Avg. Shpg. wt., 3 oz.

Stock No.	Model	Fig.	Type	Net Each		
				1-9	10-49	50 UP
13 R 21629	PL 111	A	Pencil	.93	.77	.70
13 R 21637	PL 113	B	Chisel	.93	.77	.70
13 R 21645	PL 331	C	Pencil	.72	.59	.54
13 R 21652	PL 332	D	Offset	.72	.59	.54
13 R 21660	PL 333	E	Chisel	.72	.59	.54
13 R 21678	PL 338	F	Needle	.72	.59	.54
13 R 21686	PL 340	G	Micro	.72	.59	.54
13 R 21694	PL 823	H	Pyramid	.82	.67	.61
13 R 21702	PL 824	E	Chisel	.82	.67	.61
13 R 21710	PL 833	E	Chisel	1.17	.96	.88
13 R 21728	PL 834	D	Offset	1.17	.96	.88
13 R 21736	111	A	Pencil	.48	.40	.36
13 R 21744	113	B	Chisel	.48	.40	.36
13 R 21751	331	C	Pencil	.30	.25	.23
13 R 21769	332	D	Offset	.30	.25	.23
13 R 21777	333	E	Chisel	.30	.25	.23
13 R 21785	823	H	Pyramid	.35	.29	.26
13 R 21793	824	E	Chisel	.35	.29	.26

ELEMENT UNITS with TIPS



For 776 and 777 Handle

4000 Series, Super Hi-Heat. 900°-1000°F tip temperature. 47½ watts for heavy duty use. Teliurium copper base, plated with iron and pure silver. For 115V, AC-DC. Av. Shpg. wt., 4 oz.

Stock No.	Type	Descrip.	Fig.	Net Each		
				1-10	10-49	50 UP
13 R 21462	4033	¼" Chisel J	3.67	3.01	2.75	
13 R 21470	4036	Pyramid K	3.67	3.01	2.75	
13 R 21488	4039	¾" Chisel L	3.67	3.01	2.75	

1200 Series, Hi-Heat. 750°-800°F tip temperature. 37½ watts for medium duty use. Silver-plated solid Armo pure iron. *Copper tip. For 115V, AC-DC. Av. shpg. wt., 4 oz.

Stock No.	Type	Descrip.	Fig.	Net Each		
				1-10	10-49	50 UP
13 R 21496	1233	¼" Chisel J	2.53	2.08	1.90	
13 R 21504	1236	Pyramid K	2.53	2.08	1.90	
13 R 21512	1239	¾" Chisel L	2.53	2.08	1.90	

800 Series, Standard. 650°-750°F tip temperature. 23½ watts for general purpose use. Teliurium copper tip. For 115V, AC-DC. Av. shpg. wt., 4 oz.

Stock No.	Type	Descrip.	Fig.	Net Each		
				1-10	10-49	50 UP
13 R 21520	533	¼" Chisel J	1.75	1.44	1.31	
13 R 21538	536	Pyramid K	1.75	1.44	1.31	
13 R 21546	539	¾" Chisel L	1.75	1.44	1.31	

Ungar

HOT-VAC DE-SOLDERING TOOL

13.95



- One-hand Operation
- Hot-Vac Melts, Removes Solder
- De-solders, Cleans Printed Circuits

Vacuum action lifts solder from board for easy removal of components. Special tip coating prevents solder from sticking. Handle stays cool. Wt., 10 oz.

Stock No.	1-5	6-11	12-Up
13 R 21850	Net ea. 13.95	11.47	10.45
13 R 21959	Replacement tip for above		Net 1.29

1³²

UNGAR KLEEN TIP #400



Effective for removing oxidation and cleaning soldering tips. Clean tips last twice as long! With phenolic tray, two specially processed sponges and bracket for attaching to work bench. Shpg. wt., 4 oz.

13 R 21819	Net 1.32
Refill sponge for above.	
13 R 21975	Net .53

You Can Depend On Lafayette For Quality Tools—Low Prices

Ungar

SOLDERING IRON HOLDER

Attaches easily to top or underside of bench, or to wall. Angle adjusts to your convenience. Shpg. wt., 10 oz.

13 R 21157	#8000	Imperial Line
13 R 21165	#8000	For Standard Line

Net	1-9	10-49	50 up
Each	2.30	1.86	1.73



Soldering Irons-Solder


Ungar

IMPERIAL 6010 40-WATT SOLDERING KIT

- High Quality Components
- Includes: Handle, Cord, Heat Cartridge, and 3 Tips

Slim designed "Perma-Cool" handle uses a heat-sink and a double cushion of air to keep handle cool. Handy octagonal shape prevents rolling. Perfectly balanced for easy finger tip control. Package includes 40-watt heat cartridge that delivers up to 950°F tip temperature. UL listed. Shpg. wt., 8 oz.

13 R 21991	Net ea. 9.95	7.95	7.50
13 R 21223 (Repl. tip) Taper chisel	Net ea.	1.99	1.00
		1.58	



Ungar

PRINCESS MINIATURE SOLDERING IRON KITS

- Featherweight only 3 oz.
- Operates on 120 Volts AC/DC
- Complete with 10 Watt Capsule, 3 Copper Tips

998

Model 6975 Pencil light, high heat iron for critical miniature soldering, provides flexibility in tip shapes. Heat capsules and soldering nibs thread into turquoise handle with fingertip ease. Shpg. wt., 5 oz.

Stack No.	1-9	10-49	50-up
13 R 21876	9.90	8.65	7.69

PRINCESS SOLDERING STATION, Model 6900. Same as kit above but with deluxe soldering iron holder equipped with sponge. 7 oz.

Stack No.	1-9	10-49	50-up
13 R 21884	13.64	11.89	10.49

Replacement sponge for Model 6900. 13 R 20795 Net .60



PRINCESS DE-SOLDERETTE

Ungar

For Removal of Microminiature Components... Ideal for I.C. Chip Re-Work and Repair.

Fast... Safe... Efficient.

MODEL 6992, 18 watt Heat Capsule melts solder fast. Vacuum tip rated at 5.5 oz. per sq. in. draws melted solder from board for easy removal of microminiature components. "Ungarized" white coating inside and outside of collector prevents molten solder from sticking. Stainless steel tip with .033 aperture prevents clogging. Shpg. wt., 1/2 lb.

1-9	10-49	50 up
13 R 21919	Net Ea. 17.75	15.42
		13.65



KESTER SOLDER AND FLUX

Uniform compound of 40% tin and 60% lead with evenly distributed and free-flowing flux. Shpg. wt., 1 lb. spools 1 1/2 lbs.; 5 lb. spools 6 3/4 lbs.



Kester "44" Resin Core Solder

14 R 32012	1/4" Dia.	3 oz. Box	Net .39
14 R 32020	3/8" Dia.	1 1/2 lb. Sp. Net	2.09
14 R 32038	3/8" Dia.	6 3/4 lb. Sp. Net	9.95
14 R 32046	1/2" Dia.	1 1/2 lb. Sp. Net	2.19
14 R 32053	1/2" Dia.	6 3/4 lb. Sp. Net	10.50

Acid Core Solder

14 R 32061	1/4" Dia.	4 oz. Box	Net .39
14 R 32079	3/8" Dia.	1 1/2 lb. Sp. Net	2.09
14 R 32087	3/8" Dia.	6 3/4 lb. Sp. Net	9.95

KESTER "44" RESIN CORE SOLDER

Very active resin core flux. Non-corrosive and non-conductive. Easily solders zinc, brass, nickel plate and ferrous metals. 50% tin and 50% lead.

14 R 32095	3/8" Dia.	1 1/2 lb. Sp. Net	2.49
14 R 32103	3/8" Dia.	6 3/4 lb. Sp. Net	11.30
14 R 32111	1/2" Dia.	1 1/2 lb. Sp. Net	2.59
14 R 32129	1/2" Dia.	6 3/4 lb. Sp. Net	11.80

KESTER PASTE FLUX

14 R 32137	2 oz. can	Net .29
------------	-----------	---------

"SAL-MET" FLUX

129

• Non-corrosive

A non-corrosive flux that will solder all metals cleanly and permanently—copper to aluminum; aluminum to aluminum, copper to steel, etc. No special treatment of metal required. Packed in 1 oz. tubes. Shpg. wt., 3 oz.

14 R 49016	Net 1.29
------------	----------



ERSIN MULTICORE SOLDER

5-core construction assures constant maximum flux. Fast melting, non-corrosive, non-sticky, non-toxic, 1-lb. packs in carton and skin wrap for utmost protection, non-oxidation. Shpg. wt., 1 lb spools 1 1/2 lbs.—7 lb. spools, 8 1/4 lbs.



40% TIN, 60% LEAD #16 GAUGE

14 R 35015	1 1/2 lb. spool	Net 2.99
14 R 35023	3 1/2 lb. spool	Net 18.95

60% TIN, 40% LEAD #16 GAUGE

14 R 35031	1 1/2 lb. spool	Net 3.74
14 R 35049	8 1/4 lb. spool	Net 23.95

60% TIN, 40% LEAD #18 GAUGE

14 R 35056	1 1/2 lb. spool	Net 3.81
14 R 35064	8 1/4 lb. spool	Net 24.25

DISPENSER PAKS: In flameproof aluminum tubes. 60% Tin, 40% Lead. Shpg. wt., 4 oz.

14 R 35072	18 gauge, 14 Ft.	Net .69
Extra Thin 22 Gauge, 21 Ft.		
14 R 35080		Net .69

G. C. SERVICE TWEEZERS



Made of polished nickel-plated spring steel. Self-Closing Type. 6 1/2" long, with blunt points. Shpg. wt., 3 oz.

13 R 60858 (A)	Net .99
Heavy-Duty Type. 6 1/2" long, with slide lock and blunt points.	
13 R 60866 (B)	Net 1.10
Precision Type. 4 1/2" L. Pointed.	
13 R 60874 (C)	Net .75
All 3 above in leatherette case.	
13 R 60882	Net 2.84

SPYRALINE SOLDER



• 60% TIN—40% LEAD

11 ft. of high quality, 3/32" 60/40 activated resin core solder in handy dispenser. Container is non-flammable—affords insulation when working on a "hot" circuit. Eliminates waste—pull out only what you need. Keeps solder clean and unwarmed. Shpg. wt., 3/4 lb.

14 R 39058	Singly, Ea. .69
	Lots of 3 .59 ea.


SPYRALINE PRINTED CIRCUIT TOUCH UP SOLDER designed for a fast bond without overheating. Melting range of 240°-320°F, for low wattage soldering iron. Safe for silver, ceramics and transistors. Shpg. wt., 4 oz.

14 R 39066	Net ea. .85	Lots of 3 .75 ea.
------------	-------------	-------------------

PRINT-KOTE SOLDER. Non-corrosive flux with low melting solder combined with pure silver. 4 oz. coll. Shpg. wt., 4 oz.

13 R 60098	GC 9131	Net .69
------------	---------	---------

CHEMALLOY FLUXLESS ALUMINUM SOLDER




• No Flux Needed—Easy To Use

New, improved, 500° fluxless aluminum solder will solder, braze, or weld aluminum, zinc, potmetals, copper, brass, galvanized metals, aluminumized—copperized—tinned surfaces. Solders and "fills" die cast parts.

Package of two 2 oz. Bars	
14 R 34018	Shpg. wt., 7 oz. Net 1.19
1 lb. Package of Assorted Bars	
14 R 34034	Shpg. wt., 1 1/2 lbs. Net 2.69

G. C. Alignment Tools And Service Aids



Average Shipping Weight of all below: 3 Ozs.

Stock No.	TYPE	Fig.	DESCRIPTION	Net
13 R 60502	5000	A	Metal Tip Alignment Screwdriver	.46
13 R 60510	5066	B	Short Alignment Screwdriver	.40
13 R 60536	8195	C	Channel Tuning Tool with 1/2" blade	.78
13 R 60619	8282	D	Zenith TV Wrench & Aligner	.37
13 R 60627	8606	E	Zenith Nylon Hex Wrench	.48
13 R 60635	9087	F	Slug Tuner Adjusting Tool	.75
13 R 60668	8273	G	TV All-Purpose Aligner, recessed blade	.99
13 R 60700	8987	H	K-57 Long Slim Screwdriver 7"	.69
13 R 60718	8988	H	K-57 Long Slim Screwdriver 12"	.99
13 R 60726	8728A	I	7" Delrin Screwdriver	.47
13 R 60734	8728	I	12" Long Delrin Screwdriver	.58
13 R 60742	9440	J	Transistor I.F. core alignment tool	.63
13 R 60759	9298	K	Recessed Driver with 1/4" Blade	.48
13 R 60767	9091	L	5" .125 Hex Double End Iron Core Tool	.48



6²⁶ G. C. STANDARD T.V. ALIGNMENT TOOL KIT

Model 8455. Contains nine essential tools roll-type case: TV K-tran, TV channel tool, TV short tool for RF and IF, TV core aligner, TV universal aligner, TV oscillator tool, TV long reach aligner, TV duplex aligner, TV flex, tuning wand. A quality kit—made to last and wear. Complete with case.

13 R 60817 Shpg. wt., 8 oz. Net 6.26

COLOR T.V. ALIGNMENT TOOL KIT



Model 8454 Five different alignment tools for all standard adjustments in color TV. Made of natural Delrin® for extra durability. Includes "Extend-It" which makes each tool a long reach aligner. Each tool is color coded for easy identification. Packed in vinyl pocket saver.

13 R 61203 Shpg. wt., 4 oz. Net 2.49


CB ALIGNMENT TOOL KIT

• A Must For Every CB Owner Or Repairman

Model 9210 Nine precision adjustment tools for tuning IF transformers, RF coils, antennas, oscillator coils plus countless other fine intricate adjustments. Packaged in a durable plastic carrying case. Shpg. wt., 4 oz.

13 R 61237 Net 4.89

UNIVERSAL ALIGNMENT TOOL KIT



A handy, all-purpose kit in a convenient vinyl pouch. Kit contains 6 basic essential tools from 4 1/4" to 7", with 12 serviceable sides that will service the majority of TV sets. FM, AM CB, HAM Instruments, etc. Shpg. wt., 3 oz. 12 R 30028 Net 2.39

WIRE BENDING JIG



Handi-Bender forms wire sizes up to 1/4" dia. Steel slots and steel bending pins make basic bends such as eyes, angles, curves, circles, and for straightening wire. Makes dozens of useful and decorative articles. Complete instructions included.

14 R 70103 Shpg. wt., 1/2 lb. Net 1.19

SEVEN PIECE LUBRICANT KIT FOR HOME AND SHOP



Seven different lubricants in a colorful kit for home and shop. Kit stands or hangs. The right lubricant for every job. White Grease—All-Purpose Oil—Graphite Powder—Dry White Lubricant—Liquid Graphite—Penetrating Oil—Silicone Grease Stick. Shpg. wt., 1 lb. Net 2.69

346 Lafayette Cat. No. 720

REPAIR CRADLE

5⁴⁵



G.C. "Quick-Rig" makes radio repair work quick and easy. Complete 360° rotation permits you to lock the chassis at the best working angle, clamps chassis securely and eliminates make shift setups. All metal, sturdy construction. Adjustable width for different sizes of turntables, etc. Shpg. wt., 4 lbs.

13 R 60890 Net 5.45

ILLUMINATED MIRROR



Battery powered, inspecting tool with insulated shaft. Locking switch for on-off and one-hand operation. With bulb but less batteries. 12 1/4" long. Shpg. wt., 5 oz.

13 R 60825 Net 2.02

Batteries for above. (2 Required.) Net ea. .10

99 R 62580 Net ea. .10

INSPECTION MIRROR

Made of metal shaft with 1" dia. glass mirror and plastic handle. Length 7 7/8". Shpg. wt., 3 oz.

13 R 60148 Net .49

CHEMICALS

As Low As 60¢

Pilobond Cement. Sticks anything to anything. Dries rapidly—waterproof—very high strength. Shpg. wt., 7 oz.

13 R 60973 2 ozs. Net .60

Red-X Corona Dope. Prevents corona shorts in Hi-Voltage circuits. Flexible—fast drying.

13 R 60981 2 ozs. Shpg. wt., 7 oz. Net .70

Electronic Contact Cleaner. New red cleaner, made with DE-OX-ID. Fast drying—universal contact cleaner. Shpg. wt., 7 oz.

13 R 61013 2 ozs. Net .60

Service Cement. For repairing speakers and general radio work. Vibration-proof, waterproof—fast drying.

13 R 61062 2 ozs. Shpg. wt., 7 oz. Net .60



KRYLON CRYSTAL CLEAR ACRYLIC SPRAY

1^{69EA}

Dry in minutes, goes on clear—stays clear, tough, pliable, lasting. Prevents deterioration and moisture breakdown of insulation. Preserves and protects.

1 Pint Can. 13 R 14673 Net 1.69

Lots of 3 1.49 ea.

ECCOBOND 26 EPOXY ADHESIVE



• Sticks Anything to Anything

Handiest bonding agent ever for the lab bench or production line. Repairs tools, hardware, furniture, boats. Features permanent adhesion to metals, plastics, paper, ceramics, etc. Cures in four hours at room temperature—in minutes at 150 F. Can be sanded or worked—takes paint readily. White color. Mixes easily. Shpg. wt., 8 ozs.

14 R 51053 Net 1.95

CORD STRAIN RELIEFS

Package of 5 rubber cord strain reliefs prevents all standard line cords from pulling loose. Fits 3/8" holes for permanent or temporary installations. Imported. Shpg. wt., 2 oz.

99 R 62747 Net .39

24" PICK-UP TOOL



Has mechanical fingers that will pick-up and hold screws, nuts, and bolts. Just press button to open, release button to close. Flexible shaft. Shpg wt., 7 oz.

13 R 55551 Net .99

Waldom Solderless Terminals and Connectors

**SOLDERLESS TERMINALS,
CONNECTOR ASSORTMENT
WITH CRIMPING TOOLS**

Highest quality terminals made of pure copper, electroplated. Insulated types have permanently attached rigid vinyl sleeves. Crimp on rapidly and make positive, uniformly reliable connections. Column headed "type"; RT is Ring Tongue; BC is Butt Connector (length of non-insulated $\frac{3}{8}$ ", insulated $\frac{1}{2}$ "); QDM is Quick Disconnect Male; QDF is Quick Disconnect Female; NI is Nylon Insulated Closed End Connector. Avg. shpg. wt., 4 oz.



As Low As
10⁸⁵

**Non-Insulated Type
Terminal Assortment**

215 Non-insulated Types indicated by asterisk (*) right, plus Universal Crimping Tool. In handy compartmented plastic box. Shpg. wt., 2 3/4 lbs.


13 R 43011 Net 10.85

Insulated Type Terminal Assortment

138 Insulated Types indicated by (†) right plus Universal Crimping Tool. In handy compartmented plastic box with hinged cover. Shpg. wt., 2 1/2 lbs.

13 R 43029 Net 13.90

Wire		Stud Size	NON-INSULATED TYPES		INSULATED TYPES		
Type	Fig. Range		Qty.	Stock No.	Net Qty.	Stock No.	
ST	A 22-18	5-6	40	13 R 73604	1.09	18 13 R 73794	1.89
ST	A —	8	40	13 R 73612	1.09	18 13 R 73802	1.89
ST	A —	10	40	13 R 73620	1.09	18 13 R 73810	1.89
ST	A 16-14	5-6	40	14 R 73638*	1.09	18 13 R 73828	1.89
ST	A 16-14	8	40	13 R 73646	1.09	18 13 R 73836	1.89
ST	A 16-14	10	40	13 R 73653*	1.09	18 13 R 73844	1.89
HT	B 22-18	5-6	—	13 R 73661*	1.09	18 13 R 73851	1.89
FS	A 22-18	5-6	40	13 R 73679*	1.09	18 13 R 73869	1.89
FS	A 16-14	5-6	40	13 R 73687	1.09	18 13 R 73950	1.89
RT	B 22-18	5-6	40	13 R 73695*	1.09	18 13 R 73877	1.89
RT	D 22-18	8	40	13 R 73703	1.09	18 13 R 73893	1.89
RT	D 22-18	10	40	13 R 73711	1.09	18 13 R 73885	1.89
RT	D 16-14	5-6	40	13 R 73729*	1.09	18 13 R 73901	1.89
RT	D 16-14	10	40	13 R 73737*	1.09	18 13 R 73919	1.89
RT	D 12-10	10	40	13 R 73745*	1.09	16 13 R 73925	1.89
BC	E 22-18	—	40	13 R 73752*	1.09	10 13 R 73927	1.09
BC	E 16-14	—	40	13 R 73760	1.09	16 13 R 73943	1.09
QD	F 18-14 1/4" Male	—	40	13 R 73778*	1.09	10 13 R 73968	1.09
QD	F 18-14 1/4" Female	—	40	13 R 73786*	1.09	16 13 R 73992	1.09
NI	G 22-14 O.D. 3/8", I.D. 1/4", Lgth. 3/4"	—	—	—	—	20 13 R 73976	1.89
NI	G 16-10 O.D. 3/8", I.D. 1/4", Lgth. 3/4"	—	—	—	—	15 13 R 73984	1.89



Waldom Radio and TV Hardware



Fig. 1—Vinyl Grommets

Stock No.	Size	Qty.	Net
13 R 43912	1/8"	25	.59
13 R 43920	3/8"	20	.59
13 R 43938	1/4"	18	.59
13 R 43946	3/8"	15	.59
13 R 43953	3/8"	15	.59
13 R 43961	1/2"	10	.59
13 R 43979	5/8"	4	.59

Fig. 5—Metal Washers, Nickel Plated

Stock No.	Qty.	Net
13 R 42534 Assortment	100	.59

Fig. 6—"C" Washers

Stock No.	Qty.	Net
13 R 42583 Assortment	35	.59

Fig. 7—Extruded Fibre Washers

Stock No.	Qty.	Net
13 R 42609 Assortment	40	.59

Fig. 2-3—Solder Lugs—Hot Tin Dipped

Stock No.	Fig.	Size	Hole Qty.	Net
13 R 43987	2	#6	45	.59
13 R 43995	2	#8	46	.59
13 R 43417	3	#6	45	.59
13 R 43425	3	#8	45	.59

Fig. 8—Tension Springs

Stock No.	Size	Qty.	Net
13 R 42625	Assorted Large	15	.59
13 R 42633	Assorted Small	15	.59

Fig. 4—Knob Set Screws

Stock No.	Qty.	Net
13 R 42518 Assortment	20	.59

Fig. 9—Rubber Feet

Stock No.	Size	Qty.	Net
13 R 42674	3/8" O.D.	10	.59
13 R 42682	1/2" O.D.	10	.59

Waldom CRIMPING TOOL WITH BOLT CUTTER




- Crimps Insulated and Non-Insulated Terminals
- Cuts and Strips Wire, and Cuts Bolts

Make connections fast without soldering. Cuts and strips wire 22 to 10 gauge. Wire cutter at tip for close work. Crimps both insulated and non-insulated terminals. Bolt slicer accommodates 6 sizes of bolts, 4-40, 5-40, 6-32, 8-32, 10-32 and 10-24. Black oxide finish for beauty and durability. Insulated handles. 13 R 44001 Shpg. wt., 3/4 lb. Net 5.25

CRIMPING TOOLS AND TERMINALS

249



- Wire Cutter, Wire Stripper
- Includes Assortment of Terminals

Solderless terminal crimp tool cuts any size wire up to 10 gauge, strip wire easily. Crimps terminals quickly. Easy to use with insulated handles. With assorted solderless terminals and connectors. Imported. 13 R 70006 Shpg. wt., 3/4 lb. Net 2.49

PRECISION OILER



99^c

Instrument for precision oiling. Spout is only .003" dia. Made of stainless steel and butyrate. Filled with clear, non-staining machine oil. Can be refilled. Hypo action prevents messy, harmful over-oiling. 14 R 83106 Shpg. wt., 3 oz. Net .99

WALDOM HARDWARE KITS

195



SELF-TAPPING SHEET METAL KIT
Contains balanced assortment of plated self-tapping, slotted hex head sheet metal screws in sizes: #4 x 3/8", #6 x 1/2", #8 x 1/2", #6 x 3/4", #8 x 1/4", #8 x 3/8", #8 x 1/2", and #8 x 3/4". Total of 165 pieces in handy compartmented plastic box with hinged cover. 13 R 73190 Shpg. wt., 3/4 lb. Net 1.95


MACHINE SCREWS, NUTS AND SHEET METAL SCREW KIT
Pocket as above. Contains round-head steel plated machine screws in sizes: 4-40 x 1/2, 6/32 x 1/4, 6/32 x 3/4, 8/32 x 1/2, sheet metal screws, #6 x 1/2 and assortment of nuts. Total of 265 pieces. Shpg. wt. 3/4 lb. 13 R 73208 Net 1.95

BINDER HEAD ASST.
Same as above but machine screws have binder heads. 13 R 73216 Shpg. wt., 3/4 lb. Net 1.95

WOOD SCREW KIT
In same handy box. Contains assortment of 131 round head and flat head plated wood screws in 8 sizes for #4, 6 and 8 holes. 13 R 73224 Shpg. wt., 3/4 lb. Net 1.95

1-lb. MIXED HARDWARE ASSORTMENT

• In Handy Sturdy Plastic Box
An excellent assortment of popular hardware items for serviceman, hobbyist, or any homeowner. Provides the parts for an unlimited number of repair jobs. Packaged in a handy plastic box. 13 R 61245 Shpg. wt., 1 1/2 lbs. Net 1.39



You Can Depend On Lafayette For Quality Tools—Low Prices


Lafayette Cat. No. 720 347

Hobby—Tool Kits

DREMEL MOTO-TOOL KITS



- Grinds—Polishes—Engraves—Sands—Drills
- Precision High-Speed Steel Cutters and Wheel Points



- Model 261—Kit. Rugged, compact machine shop with an assortment of fine accessories in a molded polyethylene case. 30,000 rpm for peak performance with small, abrasive wheel points and both high-speed and carbide cutters. Kit contains: No. 260 Moto-Tool with high speed steel cutters, grinding wheels, wire and bristle brushes, rubber polishing tip, sanding discs, drum sander and sanding bands, mandrels, dressing stone, finger grip extension, collet wrench, 1/8", 3/32", 1/16", and 1/32" collets. 117 VAC, .5 amp motor. UL listed.
- 14 R 43043 Shpg. wt., 2 3/4 lbs. Net 29.95
- Model 260 Moto-Tool only—
- 14 R 43126 Shpg. wt., 1 3/4 lbs. Net 22.95
- Model 271—Heavy Duty Moto-Tool Kit. Similar to above but with heavy duty .8 amp. No. 270 Moto-Tool.
- 14 R 43050 Shpg. wt., 3 lbs. No. Money Down* Net 34.95
- Model 270 Heavy-Duty Moto-Tool only—
- 14 R 43134 Shpg. wt., 2 lbs. Net 26.95



FLEXIBLE SHAFT ATTACHMENT

- With 1/4" Chuck
- 2.95**

Operates off any fixed or portable power drill; enables you to drill at any angle anywhere. Capacity up to 1/4" size drills; 36" overall length, with chuck. Operates on speeds up to 6000 rpm. Imported, W.L. 1 1/2 lbs.

- 13 R 56112 Net 2.95
Coupler to use with motor below.
32 R 64124 Net .30



7.50

HOBBY MOTOR

For motorizing hobby tools, dental and jewelers lathes, sewing machines. 1/15 h.p. motor—5000 RPM full load and 15,000 RPM no load speed. CCW rotation facing shaft end. Steel housing—3 1/2" long, less shaft, x 2 1/4" H x 2 3/4" W. Two tapped 10-32 mounting holes on 2 1/8" centers, 1/4" shaft, 3/4" long. Fan cooled, permanent oilite bearings, and external brush openings. 12" cord lead. For 117V AC or DC.

- 19 R 24109 Shpg. wt., 2 lbs. Net 7.50

8-PC. BRUSH AND STONE SET



8-assorted pieces mounted on 1/8" or 3/16" shanks. Consists of 3 mounted grinding stones, 2 bristle brushes, 2 wire wheels, and 1 steel bun. Ideal for hobby tools. In handy plastic box. Shpg. wt. 4 oz.

- 13 R 50024 Net 2.29

VARIABLE SPEED FOOT CONTROL



- 3.95** • Speed Variable from 0 to Max. Speed of Motor

Regulate the speed of the motor in your sewing machine, hobby tool, etc. Handles up to 110 watts, 10-ft. cord with 2-way outlet—for motor and light. 1 amp.

- 12 R 54010 Shpg. wt., 2 lbs. Net 3.95



DREMEL MOTO-TOOL ACCESSORIES

(A) Model 223 Universal Stand. Leaves both hands free for holding the work. Adjusts to hold Moto-Tool at any angle. Quick action clamp for receiving and releasing Moto-Tool. Heavy cast iron base.

- 14 R 43092 Shpg. wt., 3 1/4 lbs. Net 7.95

(B)—Model 229 Router Attachment. Easily mounted on Moto-Tool. Has calibrated depth control adjustment for precision routing and shaping. Removable edge guide for free hand and surface routing. Instruction included.

- 14 R 43159 Shpg. wt., 1 1/2 lbs. Net 8.95

HIGH SPEED STEEL ROUTER BITS

- No. 650 1/8" Straight Cutter Bit
14 R 43167 Shpg. wt., 3 oz. Net 2.95
- No. 652 3/16" Straight Cutter Bit
14 R 43175 Shpg. wt., 3 oz. Net 2.95
- No. 654 1/4" Straight Cutter Bit
14 R 43183 Shpg. wt., 3 oz. Net 2.95
- No. 610 Convex Edger For Beading
14 R 43191 Shpg. wt., 3 oz. Net 2.95
- No. 632 Veneing Bit For Line Work
14 R 43209 Shpg. wt., 3 oz. Net 2.95
- No. 640 "V" Grooving Bit For Lettering
14 R 43217 Shpg. wt., 3 oz. Net 2.95




12-PC. ROTARY STEEL CUTTER SET



Selected assortment of 12 steel burrs of different shapes. Tempered tool steel for use on metal, plastic or wood. 1/8" and 3/16" shanks, in handy plastic box. Ideal for hobby tools. Shpg. wt. 3 oz.

- 13 R 50032 Net 2.49

6-PC. MOUNTED STONE SET



1.95

Six assorted grinding stones and wheels. Set of mounted grinding points, stones, and wheels. Mounted on 1/8" and 3/16" shafts. An ideal accessory for hobby tools. Shpg. wt., 4 oz.

- 13 R 50016 Net 1.95

DREMEL DELUXE MULTI-PURPOSE MOTO-SHOP


49.95

No Money Down*

- 5 Basic Powertools In One Compact Unit
- Jig Saw—Disc Sander—Bench Grinder—Buffing Wheel—Flexible Shaft
- Powered By Ball-Bearing 3450 RPM Rotary Motor

Model 572 Lightweight, compact portable multi-purpose workshop with 15" jig saw. Flexible accessory shaft attaches directly to power takeoff from motor for drilling, grinding, routing, sharpening, deburring and carving; has oilless bronze bearing, instant action wrenchless chuck, and neoprene cover. Accessories include: 3-sanding discs, grinding wheel, cloth buffing wheel, wire brush wheel, wheel guard, mounting bracket, 12-piece set, and 4-saw blades. U.L. Listed. 117V, 60 Hz AC. Shpg. wt., 17 lbs.

- 14 R 43068W Net 49.95



UNIMAT Miniature Machine Shop

The ALL-PURPOSE 5-in-1
METAL-MACHINING WORKSHOP

- Precision Metal-Working Lathe
- 11-Speed Ball-Bearing Spindle, Accurate to 1/2 Thousandths
- Converts to Vertical Mill or Drill in Seconds
- Turn, Mill, Bore, Saw, Buff, Sand, Polish, Grind—Steel, Aluminum, Brass, Plastic or Wood
- Ideal for R&D Labs, Model Shops, Electronic and Home Workshops

SPECIFICATIONS: Complete 5-in-1 machine shop small enough to use on a radio serviceman's bench. Designed as a multi-functional power tool. Converts from horizontal lathe to vertical drill press. The changeover causes no wear or loss of accuracy in precision fit parts. The motor-headstock detaches for use as a portable hand drill, power grinder or buffer. Extra attachments available include a very accurate circular saw, saber and jig saw, flexible shaft, lathe bed power feed, threading attachment, precision collets and cutting tools. Belt drive provides 11 speeds ranging from 900 to 7,200 RPM. Motor can also be controlled by rheostat foot switch or SCR power supply.

Includes 1/10 HP Brush Type fan cooled motor, drill press arm, column and hand lever, face plate, lathe dog, grindstone arbor, tool post, 2 dead centers, 1/4" Jacobs chuck and key. Allen wrench roughing tool bit, and a spindle return spring. 17 1/2 x 10 1/2 x 5 3/4" wood chest. 40-page manual. For 115V AC/DC operation. Imported. Shpg. wt., 2 1/4 lbs.
14 R 10141W Net 149.50


ONLY **149⁵⁰** No Money Down*



UNIMAT ATTACHMENTS AND ACCESSORIES

- Model DB-1001 3 jaw universal lathe chuck with reversing jaws, key and back plate. Shpg. wt., 1 lb.
14 R 10133 Net 29.95
- Model DB-1210 Milling Table: 5" x 3" with clamps. Shpg. wt. 2 1/4 lbs.
14 R 10026 Net 19.95
- Model DB-1010 Machine Vise: jaws open 1 1/4". Mounts cross slide or mill table. Shpg. wt., 1 lb.
14 R 10034 Net 11.50
- Model DB-2820: Set of 6 Lathe Tool Bits.
14 R 10059 Net 12.95
- Model DB-2860 Tool Kit: 2 tool bits, 4 drills, 2 grind wheels, 2 milling cutters, center drill and countersink bits, 2 chisels, boxed.
14 R 10042 Shpg. wt., 1 lb. Net 19.95
- Model DB-1290 Power Feed Attach: 1:50 reduction, feeds .0008" per revolution. Shpg. wt. 4 3/4 lbs. Net 29.95
- Model DB-1002 4-Jaw Independent Chuck; capacity 2 1/4".
14 R 10075 Net 29.95
- Model DB-1080 Jig Saw Attach. Cuts to center of 16" circle. 12 blades incl. Shpg. wt., 5 lbs.
14 R 10117 Net 24.95

Sabre-Lathe Multi-Purpose Shop Tool



Only
31⁹⁵

It's a . . .

- Wood Turning Lathe
- Sabre Jig Saw
- Bench Grinder
- Disc or Drum Sander
- Buffing or Polishing
- Horizontal Drill

A home shop tool that will excite the interest of every home craftsman! Powerful, 3-speed motor provides plenty of drive for every operation. . . unit changes for any purpose in just seconds. Complete with wood turning chisel, sanding discs, sanding drum discs, 3 sabre saw blades, 45° adjustable sanding table. Entire unit is mounted on wooden base for easy portability and stability. Lathe has 18" bed, 4" throat, can be used for spindle or face plate turning. 115 volt, approximately 1/5 h.p. motor, AC only. Output speeds 3,700, 3,300 and 3,100 rpm. With illustrated instruction booklet. Mounted on 32" x 6" board. Shpg. wt., 17 1/2 lbs.
13 R 36502W No Money Down* Net 31.95

KNIFE AND TOOL SET

- Precision Knives

Model 84 knife and tool set. Contains handles #1 (3/8 x 5" aluminum) for light work; #2 (3/8 x 5" alum.) for med. work; #5 (1 1/8 x 4 3/4" plastic) for heavy work. Plus 4 assorted routers, 2 different punches, plane, 1" sander, spoke shave, balsa stripper, 11 assorted blades and 4 assorted gouges. A complete wood carving workshop. In wood case with clear plastic cover. Shpg. wt. 2 1/2 lbs.
13 R 74230 Net 10.95

KNIFE CHEST

Model #2, Handy knife chest. Perfect for model building, photo retouching, shaping templates, cutting insulation, or cutting gaskets. Contains handles #1 for light cutting, #2 for medium work and #5 for heavy cutting plus 11 assorted blades including trimming, double edged and fine cutting. Complete with wood case. Shpg. wt., 3/4 lb.
13 R 74164 Net 4.50

4⁵⁰



X-acto CORDLESS POWER DRILL SET

5⁹⁵

- Drills Wood, Metal, Plastics
- Grinds, Drills, Carves, Polishes



Model 376. Powerful, versatile, efficient. Polish-deburr-carve-grind-drill, with new ease! Complete with center punch, grinder, drill bit and 3 precision collets. Drills plastic, wood, light metal. In handy styro foam holder. Embossed case. Less batteries.
13 R 74248 Shpg. wt., 3/4 lbs. Net 5.95
99 R 62572 "C" Batteries for above; 2 req. Net ea. .16

Replacement blades that fit all X-ACTO tools. Avg. shpg. wt., 3 oz.

SMALL BLADES

- No. 11 for fine angle cutting: deep cuts, narrow spots.
13 R 74073 #11, pkg. of 5 Net .58
- No. 24 for close corner cuts: templates, mats, trimming.
13 R 74123 #24, pkg. of 5 Net .59



*See Page 22 for Full Credit Details on Easy Pay Plan

Electric Tools For the Gardener and Hobbyist

GRASS EDGER-TRIMMER



19⁹⁵

- Powerful 3 AMP 4500 RPM with Rugged Reduction Gears
- Easily Adjustable Trimming Height
- Die Cast Aluminum Housing



URNS ON SIDE FOR USE AS EDGER


Lightweight Edger-Trimmer easily trims close-up to trees, foundations, and fences. Turning handle converts unit into a powerful edger. Features 6" tempered spring steel blade, diecast aluminum housing, side grip, finger tip push button switch on handle, fully adjustable trimming height, and oiled-for-life bronze bearings. Requires 115 volt 50/60 Hz 3 amp. AC motor. Shpg. wt., 9½ lbs. Ul listed. 13 R 36544W

Net 19.95



Black & Decker DOUBLE-EDGED BLADE SHRUB AND HEDGE TRIMMER

- Large 13" Double-Edge Blade



17⁹⁹

- Front 'Wrap-Around' Handle for Easy Balance

Model 8810 (U-175). Cuts smooth and fast with perfect control at any angle. Deep blade pockets grip and cut foliage fast, efficiently. Adjustable 'Wrap-Around' handle for steady, accurate control, plus 'Sure-Grip' handle with convenient fingertip switch. Strong lightweight die-cast aluminum housing. Durable orange enamel finish. 3600 strokes per min., 120 VAC, 60 Hz. 2.2 amps. Shpg. wt., 6½ lbs.

12 R 68721

Net 17.99



BVI ELECTRIC PENCIL ENGRAVER

- Writes On Metal—Wood—Plastic
- No Heat—Vibrating Point Engraves Keys—Tools—Toys—Jewelry

6⁵⁰



Handy, useful... mark, identify and engrave names, design decorator effects on luggage tags, toys, sporting goods, tools and kitchenware. Automatic with built-in mercury switch. You pick it up—it turns on. Put it down and it turns off. Easy as a pencil. Marks won't erase, smear or rub off. Tough hardened steel point vibrates 7200 strokes a minute. Lightweight 7x3x2". 110 VAC, 50/60 Hz motor. 13 R 80542 Shpg. wt., 10 oz.

Net 6.50

DREMEL ELECTRIC ENGRAVER

- Writes Like A Pencil
- Calibrated Stroke Adjustment

12⁹⁵

Model 290 heavy duty engraver provides a fast permanent method of marking all types of materials. High speed reciprocating motor delivers 7,200 strokes a minute with a calibrated adjustment that regulates the depth of engraving from fine lines to deep marks. Engrave steel, brass, aluminum, copper, silver, plastic, ceramic, glass, pewter. Identify dies and molds, shop and garden tools, production parts, sporting goods, camera equipment, jewelry, etc. Minimize inventory mix-ups, theft, and loss. Complete with solid carbide engraving point.

14 R 43142 Shpg. wt., 1½ lbs. Net 12.95



PLANER ATTACHMENT

- Fits Any Electric Drill

A professional tool with hardened and ground carbon alloy steel cutter. Perfect balance and comfortable handle for easy use. Instant, positive depth adjustment and 1¾" wide cut. Diagonal shearing action planes easily with or across grain. For 1/4" or 3/8" drill. Shpg. wt., 2 lbs.

14 R 62530

Net 4.95



SANDER ATTACHMENT

- Fits Any Electric Drill

Sand in minutes! For use with all 1/4" or 3/8" drills. Orbital action, ball bearing construction. Complete with three standard size no-load, jewel-hard abrasive sandpaper sheets in coarse, medium and fine grit. Top handle for easy handling.

14 R 62522 Wt., 3¼ lbs. Net 4.95



BURGESS VIBRO-TOOL KIT

- Versatile Multi-purpose Tool
- Files—Saws—Cleans—Carves De-burrs—Engraves—Cuts Grooves
- Complete With 8 Accessories

19⁹⁵



Performs many operations on nearly any kind of material with its accessories. Features motor control switch plus dial setting for engraving depth. Heavy-duty 2-speed motor delivers 3600 and 7200 strokes per minute. Rugged nylon housing. Molded plastic case with accessory storage area. Complete with accessories: Carbide tipped engraving point, knife blade, saw blade, half round chisel ½ inch tool, half round chisel ¼", V-shape chisel, flat edge chisel and abrasive point. Shpg. wt., 2½ lbs.


13 R 80575

Net 19.95

WHIZZ-DISC

2⁵⁰

- Will Cut or Shape Anything Including Steel



Cuts through the thickest materials—steel, brick, plastics. Super-hard silicon carbide particles embedded in tough resilient fabric form a shatter-proof, safe-to-use disc. No teeth to catch work and bind or kickback. Also removes paint, rust, shapes stone, metal, wood and plastic. Can be used on hand drill for close quarters. Complete with instructions, 7" Whizz Disc, 5" backing pad, ¼" arbor and flange washers. Shpg. wt., ¾ lb.

14 R 14358

Net 2.50

WHIZZ-DISC for Portable & Bench Saws, 7" dia. Shpg. wt., 4 oz.

14 R 14366 ½" bore


Net 1.79

14 R 14374 ¾" bore

Net 1.79

Power Sanders Grinder Planer Router

HEAVY DUTY 4" BELT SANDER



- Powerful 7.5 Amp motor

34⁹⁵

Model 72510. A powerful belt sander for every sanding job. Rugged gear drive moves 1500 surface feet per minute. Unique snap-lock on front roller for easy belt changing, vacuum cleaner hook-up provided for dust pick-up. Die cast aluminum housing, locking trigger switch. Uses standard 4x21 3/4" belt. AC motor with life-time lubricated bearings. 3-cond. cord. For 120 V 60 Hz AC. UL listed.

13 R 36601 Shpg. wt., 12 3/4 lbs.	Net 34.95
Sanding Belts For Above Shpg. wt., 4 oz.	
13 R 36619 40 Grit, Coarse	Net .99
13 R 36627 60 Grit, Medium	Net .99
13 R 36635 80 Grit, Fine	Net .99

TWO-WAY ELECTRIC SANDER



- Orbital or Straight Line
- Positive Slide Switch
- 3/8" Stroke Orbital or Straight

19⁹⁵

Heavy-duty electric sander with 3/8" orbital or straight line stroke. Features 2.0 amp, universal series wound motor. Heavy-duty ball bearing and self-lubricating sleeve bearings. Pad size: 3 1/2 x 7 1/4"; sand-paper size: 3 1/2 x 9". Assorted grit paper included. Industrial mirror finish. 6 ft. 3-cond cord. For 120 V. 60 Hz. AC. UL listed.

13 R 71020 Shpg. wt., 5 1/2 lbs. Net 19.95



1/4 H.P. ROUTER

31⁹⁵



- With Cutting Guide

Model R60: For hobbyists, home repairmen. Easy-to-make smooth cuts with or against the grain for fine inlaying, cabinetry, corncing. Does beading, grooving, routing, fluting, cove-cutting, dove tailing.

Features threading base with positive lever-locking depth of cut adjustment; veneer cutting guide and wrench included. 1/4" chuck uses standard router bits. Weight 8". For 120V, 60 Hz AC, 20,000 RPM cutting speed. UL listed. Shpg. wt., 6 lbs.

13 R 71087 No Money Down	Net 31.95
4-Pc. Router Bit Set, Includes 1/4" & 1/2" straight bits, 1/4" core bit, and 3/8" groove bit, Shpg. wt., 3 oz.	
13 R 71137	Net 9.95



2-SPEED SANDER POLISHER

37⁹⁵

- Powerful 1/2 H.P. Motor
- Burnout-Proof Armature
- Sands Metal and Plastics

Model 940: Combines two handy tools — a sander operating at 3400 RPM and an efficient out-isher at 1800 RPM. As a sander, you get the right combination of high speed and oversize sanding discs. Has perfect balance... auxiliary grip handle for right or left hand use. Tool rest. Extra large wood polishing bonnet permits working around and over edges. UL and CSA listed. For 117 VAC.

13 R 65168 No Money Down* Shpg. wt., 9 3/4 lbs. Net 37.95



ARCO QUICK-SAND VERTICAL PORTABLE SANDER POLISHER

- Sands, Grinds, Polishes, Sharpens: Metal, Steel, Wood, Plastics
- Portable
- For Any 1/4-1/2 H.P. Motor; With 1/2" Shaft

21⁹⁵



Safe, Versatile. Sharpens everything — from razors to plow-shares. Belt falls harmlessly to bench if it snaps. 19" high. With 1" x 42" abrasive belt, 50 grit. Shpg. wt., 11 1/4 lbs.

12 R 18502 Less Motor	Net 21.95
Sanding Belts For Above	
12 R 18510 50, Grit Heavy	Net .89
12 R 18528 120 Grit, Medium	Net .89
12 R 18536 220 Grit, Fine	Net .89

Black & Decker 5" BENCH GRINDER



- Sharpens All Your Household Tools

26⁸⁸

Versatile bench grinder for every home workshop need. Sharpens knives, hatchets, lawn mower blades, chisels, drill bits, etc. Balanced vitrified aluminum oxide grinding wheels give smooth performance. 8 1/2" wide wheel spread permits side grinding of longer objects. Self-aligning oil-impregnated bearings. Includes: 1/2" wide 5" medium grit and 5" coarse grit wheels, tool rests, guard covers, eye shields, rubber feet. 3400 rpm, 2.2 amps, 120 VAC. Shpg. wt., 10 1/4 lbs.

12 R 68713W



ELECTRIC PLANER

27⁹⁵

- Adjustable Guide Permits Planing At Any Desired Angle

Does a professional job of planing! Easily adjustable planing depths of 1/4" and 1/2". 2 hardened steel, adjustable cutting blades may be removed for sharpening, adjustable fence and angle guide may be removed for planing flush into corner. Burn-out protection. Motor develops 3/8 hp. (Industrial rating). Spindle speed 14,000 rpm with double race ball bearings. Die-cast aluminum housing. With 3-cond. cord. For 115V 50/60 Hz AC. Shpg. wt., 7 1/4 lbs.

13 R 36585

*See Page 22 for Full Credit Details on Easy Pay Plan



SKIL

7 1/4" BUILDER'S SAW

- 1 1/2 HP Burnout Protected Motor
- 5200 RPM No Load Speed 10 Amp Motor
- UL Listed

Model 574 Tackle the "big" jobs, with this dependable 7 1/4" builders' saw. Reinforced die-cast housing that really stands up. Cuts 2x4's with ease, at 45° angle. Easy set bevel and depth adjustments. Safe non-binding blade guard with vari-torque safety clutch. Sawdust ejector keeps your work clean, lets you see what you are doing. 7 1/4" combination blade and blade wrench. Powerful 1 1/2" HP motor is designed to be trouble free. Cutting depth: 90° 2 3/8", 45° 1 7/8", 10 amps. UL listed. 120 volts AC, 3 wire cord and plug. Shpg. wt., 11 1/2 lbs. See rip fence below.

13 R 69263 Net 29.99
 13 R 69123 Rip Fence Net 2.25
 Carrying Case for Above Saw
 13 R 69370 Shpg. wt., 5 1/4 lbs. Net 11.95

29⁹⁹

7 1/2" POWER SAW WITH 1 1/2 HP MOTOR


22⁹⁵

- UL and CSA Listed
- 10 Amp. 5400 RPM Universal Motor

Dependable power saw provides reserve power to cut thru 2x4's with ease. Powerful 10 amp., 5400 RPM motor. Cuts up to 2 1/4" vertically and 2 1/4" at 45°. Balanced for one hand operation. Features heavy-duty bronze bearings, floating blade guard, and easily set depth and angle adjustments. With combination blade included. For 120 VAC, 60 Hz. 3-cond. power cord. UL listed. Shpg. wt., 13 lbs.

13 R 71376W Net 22.95

RAM 670



fury

Black & Decker 2-HP 8" RADIAL ARM SAW

SPECIAL CUT 22.95

99⁹⁵
with leg stand

- Performs All Woodworking Saw Cuts
- Cuts Full 2 7/8" Depth
- Powerful 2 HP Roller Bearing Motor

Model 7700. Precision built for superb cutting accuracy . . . makes rip cuts, crosscuts, bevel and miter cuts. Roller head rides on ball bearings for accurate cutting every time. Anti-kickback lever holds board to prevent chatter. Large (22"x32") warp resistant work table allows out-ripping with blade located over table. Up-front bevel adjustment with easy-to-read scale and automatic 45° setting plus up-front elevation control permits fast, simple set-ups. Automatic positive locking position for 0° to 45° bevel; 0° and 45° miter, and 90° ripping position. Maximum depth of cut 2 7/8"; maximum depth of cut at 45° 1 7/8"; features miter and bevel scales, rocker type, up-front on/off switch with key lock for added safety. Constructed of extra-strong one piece tubular steel column mounted directly to base for rigidity. 120VAC; 2 HP max.; 5200 RPM; 10 amps.; 8" blade with leg stand. Shpg. wt., 90 lbs.

12 R 90022WXM No Money Down* Net 99.95

Model R-6024. 6" DADO HEAD SET. FLAT GROUND. (2 Blades, 4 Chippers 1/8". 1 Chipper 1/4" 3/8" Bore.

12 R 68705 Shpg. wt., 3 1/4 lbs. Net 22.99



HEAVY-DUTY 10" POWER CHAIN SAW

59⁹⁵

- 2 HP—10 Amps.
- With Oregon "Omark" Chain and Bar

A powerful top quality chain saw designed for professional or industrial use. This rugged, multi-purpose tool will also do dozens of jobs for the home craftsman, carpenter, contractor, or on the

farm. Positive chain adjustment eliminates slack. Chain travels at 2650 feet p/minute for fast, true cuts up to 10 inches deep. Cool running quiet helical cut gears in a sealed grease chamber. Self lubricating bearings. Beautifully balanced, weighs only 12 lbs. 10 Amp. 2 HP motor. 120 VAC. UL and CSA listed. Shpg. wt., 15 lbs.

14 R 48042W No Money Down* Net 59.95



"ARCO-SAW" ATTACHMENT

9⁹⁵

with "DADO-ARBOR" To Cut Any Groove



Attaches to any 1/4 and 3/8" drill in seconds! "Dado-Arbor" swivels sawblade to cut grooves up to 1/2"x1"D., in one cut; "Dado-Arbor" is easily removed for straight or angle cuts . . . cuts 2x4's in one cut with 5" blade. Graduated depth and bevel gages allow cuts up to 1 3/4"D; bevels to 45°. Has adjustable rip gage and visual guide, self-lubricating lifetime bearings, strong safety-

bracket and clamp. Fully assembled with instructions.

14 R 14275 Shpg. wt., 1 lb. Net 9.95

14 R 14283 5" Hycarbon Combination Blade Net 1.75

Selected Jig and Sabre Saws

**RAM
60**

fury

**SABRE
SAW**

12⁹⁵

• Heavy-Duty 2.9 Amp ¼ HP Motor

Model F-8: A rugged, multi-purpose sabre saw. Can be used as a rip, crosscut, jig saw, hack saw, band, coping, keyhole and scroll saw. Easily cuts 2x4's, plywood, plastic, composition board, aluminum and a host of other materials. Powerful 3 amp, ¼ H.P. motor with a built-in cooling system, produces 3500 ¼" long strokes per minute. Adjustable base. Bevel cuts from 0° to 45°. "On/Off" slide-switch. With wood cutting blade. For 120V., 60 Hz AC. UL listed.

13 R 71160 Shpg. wt., 4 ¼ lbs. Net 12.95
Wood Cutting Blades, Pkg. of 6.
13 R 71170 Shpg. wt., 4 ozs. Net 1.75
Metal Cutting Blades, Pkg. of 3.
13 R 71186 Shpg. wt., 2 ozs. Net 1.39

WEN

**DELUXE 2-SPEED
JIG SAW**



19⁹⁵

• Double Insulated For Extra Safety
• Powerful 2.6 Amp ½ HP Motor

Model 501 double insulated jig saw with 2 speeds, 3000 and 2400 ¾" strokes per minute. Husky shoeplate adjusts 45° left and right; forward for plunge cuts and backward for close to wall cuts. Fully enclosed handle. Includes 3-blades and rip guide. 2.6 amp. motor, 120 VAC. Shpg. wt., 3¾ lbs.
13 R 65394 Net 19.95

**HEAVY-DUTY VARIABLE
SPEED SABRE-JIG SAW**




29⁹⁵

• "Dial Control" Any Speed From 0-5200 S.P.M.
• Cuts Thru Wood 6" Thick

Electronic dial variable speed control lets you use this one tool for any cutting job. Cuts through 6" logs, 6 x 6" lumber, metal pipe, masonite—practically any material. Makes its own starting hole. Low speed for steel and plastics, medium for non-ferrous metals, high for rip or cross-cut. Bevel cuts to 45°. Features 5 amp, ½ HP General Electric motor. With 6' 3-cond. cord. 5 assorted blades and rip gauge. For 120 VAC, 25-60 HZ. UL listed. Shpg. wt., 6¾ lbs.
14 R 48059 Net 29.95

WEN

2-SPEED ALL-SAW




39⁹⁵ • Heavy-Duty ½ HP Motor
No Money Down*

Model 909D, "Souped-up" heavy duty-fast cutting—½ HP saw for every kind of sawing. Cuts metals up to ½". Cuts pipe and thin-wall up to 2". Cuts curves, circles, and straight lines. Cuts 2x4's, 4x4's and 6x6's. Makes its own starting holes. Motor fan blows air stream over work to keep the guide free of sawdust. Complete with 7 blades designed for all sorts of regular and special cutting. Powerful 6 amp 120 VAC motor, 3400 1" SPM. UL listed.
13 R 65014 Shpg. wt., 9¾ lbs. Net 39.95

SAW TABLE FOR WEN "909" & "909D". Heavy duty table for straight, circle, curve, bevel, and angle cuts. Size: 18 x 18 x 8½".
13 R 65055 Shpg. wt., 16¼ lbs. Net 11.95
EXTRA BLADES FOR WEN Models "909" & "909D"—"521". Pkg. of 3. Shpg. wt., 5 oz.
#81 7¼"—Very fast rough cuts.
13 R 65063 Net 1.95
#92 3½"—Fast rough cuts.
13 R 65071 Net 1.59
#93 2¾"—Medium cuts.
13 R 65089 Net 1.39
#94 2½"—Fine scroll cuts.
13 R 65097 Net 1.39
#95 3¼"—High-speed steel.
13 R 65113 Net 1.95
#97 3¾"—High-speed, extra fine.
13 R 65121 Net 1.95
#900. One each of above blades plus knife blade. Pkg. of 7.
13 R 65139 Net 3.59

**DREMEL
ELECTRIC
SCROLL SAW**



11⁹⁵


• Cuts Intricate Scroll Work
• No Sanding Required

Easily cuts intricate scroll work . . . saws wood up to ¾" thick, asphalt, rubber and plastic floor or wall tiles, aluminum and light metals. Ideal for hobbyists, carpenters, and craftsmen. The thin, fast cutting blade saws so smoothly, no sanding is required. High-speed reciprocating motor produces 7,200 strokes per minute. For 120V. AC 60 Hz. UL listed. Shpg. wt., 3 lbs.

14 R 43027 Net 11.95
Pkg. of 10 replacement blades for above.
14 R 43035 Shpg. wt., 3 ozs. Net .79

"JIG SAW" ATTACHMENT

• Fits Any Electric Drill



450

Pkg. of 6 blades (2-coarse, 2-medium, 2-fine). Shpg. wt., 4 oz.
14 R 14267 Net 1.75

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 353

Drills

RAM

fury



1/4" DRILL

8⁹⁵

- 2.5-Amp UL Listed Motor
- Jacobs Geared Chuck & Key
- Multiple Thrust Bearings

Model F-11 popular drill or all-around home and hobby use. 1/4" geared chuck drill rated at full 2.5 amps, UL listed. 1/4" capacity in steel, 1/2" in hardwood. 1200 RPM speed under full load; 2000 RPM no-load speed. Precision anti-friction bearings. Automatic trigger switch. Specially designed gear train for maximum torque transfer. For 115 volts, AC/DC. Shpg. wt., 3 1/2 lbs.

13 R 71012

Net 8.95



**McGRAW
EDISON**

HUSKY 3/8" DRILL

12⁹⁵

- 3 AMP UL Listed
- Auxiliary Left or Right Handle
- Double Reduction of Gears

A rugged, powerful 3/8" drill for tough drilling jobs around the house and shop. Features double reduction gears for maximum torque. No load speed 1000 rpm. Capacity 3/8" in steel, 1" in wood. Ball thrust bearing takes the full drilling load. Welded commutator leads prevent motor burnout. Geared key chuck, 3-conductor power cord. Bright finish. For 120 VAC, 50-60 Hz.

13 R 36551 Shpg. wt., 4 1/2 lbs.

Net 12.95

RAM

fury

50 Piece Power Workshop

WITH 3/8" VARIABLE TRIGGER SPEED CONTROL DRILL

29⁹⁵



Powerful! Efficient! Flexible! Rugged 3/8" variable speed power drill with 3/8 HP 3 Amp universal motor is capable of performing most any job around workshop and home. Squeeze the trigger for any speed you desire from 0 to 1,000 RPM. Complete assortment of attachments includes: Jacobs geared chuck and key, tilting top saw attachment, crosscut and rip saw blade, horizontal bench stand, lambswool polishing bonnet, 13 pc. drill kit, rubber backing pad, steel paint mixer, grinding wheel, 6 pc. adapter set, steel saw table with protractor and mounting post, drill press with mounting post and stand, and 15 pc. sanding disc set (5 fine, 5 med., 5 coarse). Drill features multiple thrust bearings and locking button on handle for constant speed without holding trigger. With instruction book. Drill UL listed. For 115 volts AC, 60 Hz.

13 R 71293W Shpg. wt., 12 lbs.

Net 29.95

DELUXE VARIABLE MOTOR SPEED CONTROL

12⁹⁵

- Varies Speed on AC-DC Motors from 0 to Full RPM
- Up to 8-Amps.
- 3-Position Switch: Variable—OFF—Full Speed



Perfect for all workshop power tools and home appliances. Use with drills to start holes, saws to extend blade life, polishing at low speeds etc. 3-position switch. Variable, OFF and Full permits maximum speed control, with Universal (AC-DC) or DC motors rated to 8 amps. Has automatic breaker surge protection. Input 120V AC only, 3 wire line cord. Black aluminum case, 4 1/2 x 2 1/2 x 1 1/2" D. Shpg. wt., 1 1/4 lbs.

13 R 27014

Net 12.95

"JIFFY" VARIABLE MOTOR SPEED CONTROL

9⁹⁵

- Varies Speed on AC-DC Motors From 0 RPM To Full Speed
- Ideal For Electric Drills, Saws, Polishers



Dependable motor speed control ideal for workshop power tools using universal AC-DC and series DC motors. Assures constant speed variation from zero to maximum speed. Has built-in circuit breaker, 5 amp load rating. Input: 120 volts 50-60 Hz AC. 3-wire receptacle and detachable line cord. 3 x 2 1/2 x 1 1/2" D. Shpg. wt., 1 lb.

13 R 27006

Net 9.95



15⁹⁹

Black & Decker

HEAVY-DUTY 3/8" DRILL

- 1/4 HP 1000 RPM
- Uses Double Reduction Gear System

Model 7110 Heavy duty capacity 3/8" drill incorporates a double reduction gear that permits a wide range of drilling needs. Perfect for grinding, buffing, mixing and all types of heavy and light drilling chores. Heavy duty UL listed 25 amp motor and precision gears combine to give maximum torque at all drilling speeds. "Cycloc" handle provides positive grip at all times. Jacobs geared chuck and key for quick change of bits. Handy trigger switch, with locking button, permits use in awkward places. 3 wire cord plug. Uses 120V AC. UL Listed. Shpg. wt., 4 lbs.

12 R 68507

Net 15.99



22⁸⁸

Black & Decker

3/8" VARIABLE SPEED DRILL WITH SPEED LOCK

- Drill Locks At Any Speed From 0-1000 RPM

Model 7120 heavy duty drill features double reduction gear system for full torque drilling action. Gearing and chuck able to handle bigger, tougher jobs. Lets you lock trigger at any selected speed suited to the job. Ideal for driving screws. Improved 1/4 hp 2.5 amp. burn-out protected motor. Capacity: 3/4" steel, 3/4" hardwood. Polished aluminum housing with rugged Man-Grip handle for greater comfort and control. For 120 VAC. UL listed. Shpg. wt., 3 1/2 lbs.

12 R 68739

Net 22.88

SKIL



1/2"

Drive-R-Drill

- Adjustable Trigger Speed Control
- Operates from 0 to 500 RPM—Forward or Reverse
- Pre-set Maximum Speed You Desire
- Drill Locks at Any Speed

49⁹⁵

Model 598 deluxe heavy duty 1/2" drill that can tackle most any drilling job with precision and accuracy. Squeeze the trigger for any drilling speed from 0 to 500 RPM plus reverse speed. Double reduction gears for extra torque; high torque helical gears and geared key chuck. Locking trigger switch. Powerful, 3 amp, super burnout protected motor. Capacity 1/2" in steel, 1 1/4" in wood. Removable handle. Lightweight aluminum housing. 3-wire cord and plug. For 120 VAC 60 Hz. Shpg. wt., 5 lbs. UL listed.

13 R 69339 No Money Down*

Net 49.95

HEAVY-DUTY 4-SPEED 1/2" REVERSIBLE DRILL

WEN



- 6 Amp 1/2 HP Burnout-Proof Motor
- Double Reduction Gears for Super Torque

39⁹⁵

Model 950 is designed for the big jobs! a rugged heavy duty 1/2" drill where greater power is required. Simple, easy to use two-lever control for electronic gear reduction and speed changes for precise and accurate drilling of any type of material. Reversing on all 4-speeds permits you to back out from extremely dense materials. Welded armature. Double reduction gears deliver hi-torque for heavy jobs. Trigger switch locks in place for extended operation. Precision Jacobs geared chuck and key. Polished die-cast aluminum housing. 120 V. AC with 3 wire cord. UL and CSA listed. Size: 11 x 8 1/2 x 3 1/2". Shpg. wt., 9 3/4 lbs.

13 R 65337

Net 39.95

*See Page 22 for Full Credit Details on Easy Pay Plan

SKIL



3/8"

Drive-R-Drill

- With Adjustable Trigger Speed Control
- Pre-set Maximum Speed You Desire—Forward or Reverse
- Drill Locks At Any Speed From 0-1000 RPM

36⁹⁹

No Money Down*

Model 457 double insulated Drive-R-Drill for safety—Two-prong plug eliminates the need for any adapter. Squeeze the trigger for more speed and torque. Lock it for any desired constant speed without pressure. Powerful, 3 amp, super burnout protected motor; large Chuck capacity for drilling, driving, and removing applications. Double reduction high torque helical gears give extra torque, steady power. Removable side handle. Heavy duty geared chuck with key. 6 ft. 2-wire cord and plug. For 120 VAC, 60 Hz. UL listed.

13 R 69396 Shpg. wt., 4 1/2 lbs.

Net 36.99

3/8" VARIABLE SPEED



DOUBLE INSULATED COMPACT DRILL

- Solid-State Magnetic Motor—Diode Circuitry
- Double-Reduction Gears

31⁹⁵

No Money Down*

A power drill that is so light, rugged and powerful... so comfortable! Revolutionary fast-back design features balanced power and lightweight materials. Weighs only 1 1/2 lbs.! Ingenious use of polycarbonate housing makes this drill virtually indestructible and is double insulated for safety. Unique magnetic motor offers variable speeds from 0-1200 r.p.m. 4-diode circuitry is solid-state, full wave rectifier with highly efficient energy transfer. Additional quality features include life-time lubricated spherical bearings, and industrial quality commutator, 18-blade wind tunnel fan, double reduction gears, plus induction-hardened armature pinion. For 120 VAC., 60 Hz.


13 R 53242 Shpg. wt., 3 1/4 lbs.

Net 31.95

Lafayette Cat. No. 720 355

Popular Power Drill Accessories

14 Pc. HIGH SPEED DRILL SET with CENTER PUNCH



Century

11.95

- 13 Sizes
 $\frac{1}{16}$ "- $\frac{1}{2}$ "
Plus Center Punch
- Hang on Pegboard
Mount on wall or
Stand on Workbench

Top quality, high speed drill set contains sizes $\frac{1}{16}$ ", $\frac{1}{8}$ ", $\frac{3}{16}$ ", $\frac{1}{4}$ ", $\frac{5}{16}$ ", $\frac{3}{8}$ ", $\frac{1}{2}$ " and $\frac{1}{4}$ " $\frac{3}{8}$ ", $\frac{3}{8}$ " and $\frac{1}{2}$ " with $\frac{1}{4}$ " shanks. Also contains center punch for accurate placement of drill. Convenient, high impact plastic case stands on workbench or mounts easily on wall or pegboard. Has built-in shelf for holding pencils or additional drill bits, chuck keys, etc. Shpg. wt., 1 1/4 lbs.

13 R 18112

Net 11.95



Century

5.95

13 PC. HIGH SPEED DRILL SET WITH CENTER PUNCH

Made in U.S.A.

- 12 Sizes: 1/16"-1/4"

Precision ground high speed drills and center punch placed in unbreakable flexible plastic case which opens and closes like a book! Drill Sizes: $\frac{1}{16}$ "- $\frac{1}{4}$ ". Handy center punch assures exact position of drill bit.

13 R 18500 Shpg. wt., 8 oz.

Net 5.95



10-PIECE HIGH SPEED DRILL SET

High quality, high speed tool steel "hot-twisted" for perfect-uniformity, "isoperm" heat treated for remarkable toughness. These twist drills keep cutting much longer than conventional drills. Made in Italy. Sizes $\frac{1}{16}$ " to $\frac{1}{4}$ ". In Plastic Indexed Case. Shpg. wt., 6 oz.

12 R 47501

Net 3.50

29-PIECE DRILL SET WITH STAND

- Sizes $\frac{1}{16}$ " to $\frac{1}{2}$ "


Precision ground chrome alloy steel twist drills with indexed stand. Gun black finish. Sizes $\frac{1}{16}$ " to $\frac{1}{2}$ " by 64th. Sizes larger than $\frac{1}{4}$ " have turned down shanks, imported. Shpg. wt., 2 1/2 lbs.

13 R 55775

Net 9.95



COMPASS CIRCLE CUTTER



- Simple and safe to use
- Uses special bit with side-cutting Action

5.95

Simple and safe to use, makes perfect circles in wood in seconds. Use with any electric drill to cut speaker holes, vents, pipes, ceiling lights, etc. Can also be used to make discs, rings and fancy shapes. Cuts circles $1\frac{1}{2}$ " to 12" in diameter. Has special bit for smooth side cutting. Shpg. wt., 1/2 lb.

12 R 41009

Net 5.95

HEAVY-DUTY INDUSTRIAL COMPASS CUTTER. As above except cuts up to 18 inch circular holes in Fiberglas, 2" wood plank, sheet metal, $\frac{1}{4}$ " aluminum and laminated plastics. Special router bit has drill point allowing you to bore center and radius hole. Shpg. wt., 1 lb.

12 R 41017

Net 7.95

TWIST DRILL SHARPENER

- Sharpens Drills from $\frac{1}{16}$ " to $\frac{1}{2}$ "

Fits any $\frac{1}{4}$ " or larger electric drill. 3" aluminum oxide grinding wheel. Sharpens any bit up to $\frac{1}{2}$ " dia. Also has adjustable tool rest for sharpening chisels, knives, scissors, etc.

14 R 14093 Shpg. wt., 3/4 lb.

Net 8.99



Black & Decker

AUTOMATIC DRILL BIT SHARPENER

- Operates Like a Pencil Sharpener

15.99



Automatically precision sharpens dull or broken high speed steel twist drill bits (not carbide tipped). Bits need no oil or lubricants. Accepts 11 sizes: $\frac{1}{16}$ ", $\frac{1}{8}$ ", $\frac{3}{16}$ ", $\frac{1}{4}$ ", $\frac{5}{16}$ ", $\frac{3}{8}$ ", $\frac{1}{2}$ ", $\frac{5}{8}$ ", $\frac{3}{4}$ ", $\frac{7}{8}$ " and $1\frac{1}{2}$ ". Double-insulated for maximum user safety. 1/7 H.P., 1.9 amps., 120 VAC, 50/60 Hz. Shpg. wt., 5 1/2 lbs.

12 R 68747

Net 15.99

UNIVERSAL DRILL PRESS STAND

12.95



- Adjustable Depth Stop
- Adjustable Cradle
- Spring Return Tension
- Adjustable Depth Gauge Dial

Drill stand can be used with any $\frac{1}{4}$ " or $\frac{3}{8}$ " drill or $\frac{1}{2}$ " compact. Converts hand drill to powerful lever operated drill press. Rack and pinion gear feed and spring return mechanism plus depth adjustment. Base drilled for bench or truck mounting. $2\frac{1}{2}$ " stroke, 5 to 1 leverage. Overall height: 20". Base size: $5\frac{1}{2}$ "x6". Shpg. wt., 8 lbs.

14 R 62555

Net 12.95



6-PC. SCREWDRIVER BIT SET

2.99

- Fits All Electric Screwdriver And Variable Speed Drills

Versatile set provides a variety of bits and finders to speed-up assembly and service work. For slotted and Phillips head screws. Kit includes 3-slotted bits and finders for screw sizes 6-8, 8-10, & 10-12; 3-Phillips bits No.'s 1, 2, & 3. All have $\frac{1}{4}$ " Hex shank. Shpg. wt., 5 ozs.

14 R 79047

Net 2.99



7 PIECE SOCKET SET

1.69

- Fits All Electric Screwdriver Drills

Drills $\frac{1}{4}$ " hex shank fits all power screwdrivers and drills. Fits directly into chuck for driving and removing bolts and nuts. Set contains socket adapter and 6 sockets — $\frac{3}{16}$ ", $\frac{1}{4}$ ", $\frac{5}{16}$ ", $\frac{3}{8}$ ", $\frac{1}{2}$ ", $\frac{5}{8}$ ".


14 R 79054 Shpg. wt., 5 ozs.

Net 1.69

DRILL-MATE

- Portable Organizer For Drill And Accessories

3.95



- Portable Organizer - For Drill And Accessories

Keep your drill and accessories organized and ready to use with Drill-Mate, the portable organizer. Holds any $\frac{1}{4}$ " or $\frac{3}{8}$ " drill. Handy and convenient to use, the Drill-Mate has a 25 hole drill bit index— $\frac{1}{16}$ " to $\frac{1}{2}$ ", a retractable handle for easy access, handy pockets for tools, discs and accessories, and two utility drawers. Hi-impact polystyrene construction.

13 R 76268W Shpg. wt., 2 3/4 lb.

Net 3.95

Selected Accessories For Power Drills

SCREWDRIVER RESTORER

6.50



- Refinish Phillips, Yankee, Sets, Chisels, Punches

At last! An attachment to grind Phillips or regular (Yankee) screw drivers to their original shape. Chuck in any drill. Will grind all Phillips drivers up to 1/16" and all Yankee type drivers up to 1/2" as easily as sharpening a pencil. Use for chisels, punches too. Shpg. wt., 3/4 lb.

13 R 25513

Net 6.50

ADJUSTABLE BEVEL CUTTER



Fits any electric drill. Makes fast, clean 45° corner bevels. Adjusts from 1/32" to 5/16" wide. Cuts wood, plastics and soft metal. Made of hardened, tempered manganese alloy tool steel. Shpg. wt., 4 oz.

14 R 14166

Net 1.79

3 PC. CORNER FINISHING CUTTER SET



Use with any electric drill, drill press, etc. Consists of fancy cove-cutter, Roman ogee-cutter and rabbit-cutter for cutting 3/16" contours. Dual guides assure accurate cuts in wood, plastic, soft metals. Made of fully hardened and tempered steel. Shpg. wt., 1/2 lb.

14 R 14333

Net 3.19

ADJUSTABLE 82° COUNTERSINK

Adjusts to exact depth with automatic stop... single flute, chatter-free design assures round, clean cuts. Tempered and hardened manganese tool steel construction. Countersinks in steel, wood, plastic. 1/4" shank. Shpg. wt., 4 oz.

14 R 14143

Net 1.49



5-PC. ROTARY FILE SET



For electric drill, drill press, flexible shaft. Milled from solid tool steel, hardened and tempered. Cuts steel and other metals, wood, plastic, wallboard, etc. For hole enlarging, routing, shaping, finishing. With 1/4" shank. Shpg. wt., 1/2 lb.

13 R 50180

Net 3.95

5-PC. SCREW EXTRACTOR SET



Chrome vanadium set. Removes broken and mutilated screws—bolts—studs, even 1/8" and 1/4" pipe. Simply drill damaged screw-twist extractor in—and back screw out. With plastic pouch. Imported. Shpg. wt., 6 oz.

13 R 55452

Net .99

ARCO SCREW & NUT DRIVER DRILL ATTACHMENT

4.95



- Complete 11 Piece Screw and Nut Driver

For rapid fastening of both screws (slotted and Phillips) and nuts (hex and square head). Has non-slip industrial type clutch for fast easy driving. Bit holder prevents screw head slippage. Includes flat bits and bit holders for #6-14 slotted screws, #2 Phillips head bit, 6 hex socket wrenches (1/4", 3/8", 1/2", 3/8", 1/2"), and socket wrench holder with ball lock. Shpg. wt., 1 lb.

14 R 14218

Net 4.95

7-BLADE DEEP HOLE SAW

1.39



- Cuts holes in 2 x 4's

Fits any electric drill or drill press. Cylindrical saw blades cut holes from 1" to 2 1/2" in diameter in any stock up to 2". Hole sizes are 1", 1 1/4", 1 1/2", 1 3/4", 2", 2 1/4", 2 1/2". Cut wood, plastic, metal, sheetrock, wallboard, masonite, formica, etc. Has guide bit and automatic slug ejector. Imported.

13 R 55262 Shpg. wt., 1 lb. Net 1.39

RIGHT ANGLE DRIVE

3.95



- Runs Drill At 1/2 or Double Speed

Close coupled—right angle attachment for working in confined spaces. 2 to 1 gear ratio permits halving or doubling drill speed. High speed for drilling and sanding—slow speed for polishing—large hole drilling—masonry drilling, etc. Fits 1/4" chuck or may be screwed directly to drill spindle. Includes 3/8-24 male and female adapters— and 1/4" plain shaft adapter.

14 R 36939 Shpg. wt., 1 1/2 lbs. Net 3.95

10-PC. MOUNTED STONE SET



A complete set of 10 individually mounted stones perfect for use on metal, wood, plastics, etc. Can be used for chamfering, grinding, polishing, burnishing, and honing. For use with electric drill, flexible shafts and motor arbors with 1/4" or larger chuck.

14 R 61243 Shpg. wt., 1 lb. Net 2.19

AUTOMATIC CENTER PUNCH



Speedy, automatic, and adjustable—a single-hand operated punch gives light or heavy impressions with just the turn of a screw. Spring pressure adjusts from 5-30 lbs. Imported from England. Shpg. wt. 4 oz.

14 R 33200

Net 2.99

REVERSE-A-DRIVE SPEED REDUCER SCREWDRIVER



- Includes 2 Bits and 1/4" Socket Adapter

Reversible speed reducer can be fitted to any electric drill or drill press quickly and easily. Forward speed reduction of 11 to 1, and reverse of 4 to 1 develops high torque. Ideal for nut running, and heavy duty screw-driving. Easy stop-start action with hand clutch control. Accessories include 1/4" slotted bit with finder—#2 Phillips bit and 1/4" socket adapter. Shpg. wt., 3/4 lb.

14 R 79021

Net 5.25

Speed reducer similar to above but less reversing feature. 11 to 1 speed reduction through the use of a planetary gear system. Easy stop-start action with hand clutch control. Includes slotted bit with finder, #2 Phillips and 1/4" socket adapter. Shpg. wt. 3/4 lb.

14 R 79039

Net 3.95

TOOL STEEL TAPERED REAMER



Enlarges holes to 1/2". Tapers down to 1/8" point. Machined edges. Overall length 5". Sliding "T" handle. Imported. Shpg. wt., 1/2 lb.

14 R 61029

Net 1.19

ARCO DRILL STAND

- Fits All 1/4" or 3/8" Electric Drills

Attaches to workbench. Is ideal for buffing, sanding, grinding. Fits all electric drills, 6 oz.

14 R 14200

Net 1.59

LAWN MOWER SHARPENER

- Sharpens All Rotary Mowers

Quickly and easily sharpens any flat blade—rotaries, hoes, scythes, etc. 1/4" shank fits any electric drill. Reversible grinding wheel. Wt., 1/2 lb.

14 R 14226

Net 1.19

KNIFE & SCISSOR SHARPENER

Converts any electric drill or bench motor to a knife or scissors grinding machine. Consists of rugged, specially designed grindstone with 1/4" shank arbor attached. Shpg. wt., 1/2 lb.

14 R 14234

Net 1.19

1/2" CHUCK FOR 1/4" DRILLS

1.19



• Add 1/2" Capacity to 1/4" Drill
Converts 1/4" electric drill to 1/2" capacity. Properly machined to insure correct balance. May also be used on standard 1/2x24 motor arbor or shaft. Imported. Shpg. wt., 3/4 lb.

13 R 55270

Net 1.19



(A)



(B)



(C)



(D)

Complete labeling kit included with each cabinet . . . all models set-up with welded steel frame, ready to use

ALL "MODULAR," CABINETS CAN BE STACKED—ADDED TO—CHANGED—ARRANGED—REARRANGED

CHARCOAL GRAY HAMMERTONE FINISH

FOR THE HOME-HOBBY-BUSINESS

(A) MODEL 17-136, 36 compact drawers:

(D) MODEL 17-416, 16 long wide drawers.

Drawer size: 1 $\frac{1}{4}$ "x2 $\frac{3}{4}$ "x5 $\frac{3}{4}$ "
Cabinet size: 17 $\frac{7}{8}$ "x6Dx11 $\frac{1}{2}$ "H. Cabinet, "See-Thru" drawers, dividers, and index labels. Shpg. wt., 12 $\frac{1}{2}$ lbs.
13 R 76102W Net 14.99

Drawer size: 2Hx4Wx11"
Cabinet size: 17 $\frac{7}{8}$ "x11Dx10 $\frac{1}{2}$ "H. Cabinet, "See-Thru" drawers, dividers and index labels. Shpg. wt., 21 $\frac{1}{2}$ lbs.
13 R 76128W Net 22.99

(B) MODEL 17-024, 24 deep compact drawers.

MODEL 18-416. Above but with unbreakable opaque drawers.
13 R 76052W Net 22.99

Drawer size: 2Hx2 $\frac{3}{4}$ "x5 $\frac{3}{4}$ "
Cabinet size: 17 $\frac{7}{8}$ "x6Dx10 $\frac{1}{2}$ "H. Cabinet, "See-Thru" drawers, dividers, and index labels. Shpg. wt., 10 $\frac{1}{2}$ lbs.
13 R 76110W Net 14.99

(C) MODEL 17-320, 20 long drawers.


Drawer size: 2Hx3Wx11"
Cabinet size: 17 $\frac{7}{8}$ "x6Dx10 $\frac{1}{2}$ "H. Cabinet, "See-Thru" drawers, dividers, and index labels. Shpg. wt., 21 $\frac{1}{2}$ lbs.
13 R 76037W Net 22.99

Drawer size: 3 $\frac{1}{2}$ "x5 $\frac{1}{2}$ "x11"
Cabinet size: 17 $\frac{7}{8}$ "x11Dx10 $\frac{1}{2}$ "H. Cabinet, "See-Thru" drawers, dividers, and index labels. Shpg. wt., 20 $\frac{1}{2}$ lbs.
13 R 76086W Not illustrated Net 22.99

MODEL 18-320. Above, but with unbreakable opaque drawers.
13 R 76045W Net 22.99

MODEL 18-909. Above but with unbreakable opaque drawers.
13 R 76094W Not illustrated. Shpg. wt., 9 lbs. Net 22.99


AKRO-MILS PORTABLE 15 DRAWER STORAGE CABINET



• All Steel Frame

Ideal storage unit for hobbyist or handyman. All steel unutilized frame 10"x8"x6". Compact yet holds many items in easy to locate fashion in 15 "see-thru" drawers. 2 $\frac{3}{4}$ "x1 $\frac{1}{4}$ "x5 $\frac{3}{4}$ ". Unbreakable tote handle. Metallic blue baked enamel finish. With drawer dividers and labels. Shpg. wt., 4 $\frac{1}{2}$ lbs.
13 R 76250 Net 3.59


AKRO-MILS 16 DRAWER STEEL UTILITY CABINET



• Deep Drawers

Model 11-266. Charcoal hammertone welded steel heavy duty 9"x13"x6" D frame with 16 extra deep 2 $\frac{3}{4}$ "x2 $\frac{3}{4}$ "x5 $\frac{3}{4}$ " "see-thru" drawers. Baked enamel finish cannot chip or peel. Can be stacked for more compact arrangement. Adjustable dividers and labels included. Suitable anywhere from office desk to workbench. Shpg. wt., 6 $\frac{3}{4}$ lbs.
13 R 76193W Net 5.95

AKRO-MILS PORTABLE LOCKING CABINET




Model 11-463 For secure storage of medicines, tools, small easily lost parts. Chip-proof welded steel frame provides for safe storage and transport. Locking steel door prevents theft and spilling. Key-hole slots for hanging. 12 drawers 1 $\frac{1}{4}$ "x2 $\frac{3}{4}$ "x5 $\frac{3}{4}$ " 1 jumbo drawer 2 $\frac{1}{2}$ "x8 $\frac{3}{4}$ ". Overall size 10"x9"x6". With carrying handle. Adjustable dividers and labels. Shpg. wt., 5 $\frac{1}{2}$ lbs.
13 R 76219W Net 5.95



25 DRAWER PARTS CABINET



For home, office, shop. Heavy gauge welded steel frame cabinet holds dozens of items. Rugged cabinet can be stacked or wall mounted. Plastic feet prevent scratching. Drawers have easy-grip handle, dividers, labels, and label holders. Baked-on hammertone finish. Drawer size: 2W x1 $\frac{1}{2}$ Dx5 $\frac{1}{2}$ "L. Cabinet size: 9 $\frac{1}{2}$ "x12 $\frac{1}{2}$ "x6 $\frac{1}{2}$ "D. Shpg. wt., 6 lbs.
13 R 77027W Net 4.95



48 DRAWER PARTS CABINET

10⁹⁵

- With Dividers and Index Cards
- Heavy Gauge Welded Steel Frame

Extra large cabinet 21 $\frac{1}{2}$ "x12 $\frac{1}{2}$ "W x 6 $\frac{1}{2}$ "D, holds hundreds of items. Modular construction permits arrangement in single or multiple units, on walls, workbenches, shelves, or shop floors. Rigid steel frame and full metal shelf support any load in drawers. Plastic feet prevent scratches when standing, and secure multiple stacking. Inside drawer size: 1 $\frac{3}{8}$ "x2 $\frac{1}{2}$ "x5 $\frac{3}{4}$ ". Crystal-clear drawers. Feature safety stop and safe-grip-handle comes with 1 divider per drawer and index cards. Baked enamel finish. Imported. Shpg. wt., 11 $\frac{1}{2}$ lbs.
13 R 77506W Net 10.95

AKRO-MILS 30 DRAWER PARTS CABINET



- For Home-Office-Shop
- Sturdy Steel Frame
- With Dividers and Labels

6⁹⁵

Versatile 30 drawer steel frame cabinet. Has carrying handle for easy portability or can be stacked when more drawers are needed. Cabinet tilts and has safety tabs to prevent accidental spilling. Easily wall-mounted for saving workbench space. See-thru drawers measure 5 $\frac{3}{4}$ "x2 $\frac{3}{4}$ "x1 $\frac{1}{4}$ ", perfect for small parts, electrical components, screws, etc. Sturdily built with steel sides and back wall. Complete with labels and dividers. Size: 14Hx10Wx6 $\frac{1}{2}$ "D. Shpg. wt., 10 lbs.
13 R 76276W Net 6.95

Vacuum Cleaners...Staple Guns

SHOP-VAC® ALL PURPOSE VACUUM CLEANERS


- Heavy Steel Drum—Excellent for the Home, Garage, Patio, School or Workshop
- Powerful 1 HP Motor, 6 Ft. 2 1/2" Dia. Hose

As Low As
34⁹⁵

Deluxe Shop-Vac 10 Gallon Vacuum Cleaner outfit. Excellent for picking up pebbles, wood chips, sawdust and other debris. Also attaches to woodworking machines for chip and sawdust removal. Reversible air flow—use it as a blower too. Perfect for winter oil burner cleaning. Complete with two-way 4-wheel dollie, 6 ft. 2 1/2" dia. hose, 6" nozzle, 2 1/2" to 1 1/4" adapter, 2-pc. 45" extension wand, right angle elbow, cloth filter bag and pkg. of 5 paper filters. UL listed. Shpg. wt. 23 lbs.
13 R 35652W No Money Down* Net 39.95

5 Gallon Shop-Vac Vacuum Cleaner. Same as above, including all accessories, except for 5 gallon vacuum capacity. UL listed. Shpg. wt., 17 lbs.
13 R 35702W |No Money Down*..... Net 34.95

Paper Filter Bags: For extra dirty jobs, slips over cloth bag.
13 R 35561 Pkg. of 5. Shpg. wL, 4 oz. Net .99
13 R 35579 Replacement Cloth Bag. wL 4 oz. Net 1.49




"HOPPY" SPLIT-IMAGE TRANSIT

Only **8⁵⁰**

- Plate Glass Mirrors

Amazingly accurate instrument that will indicate level and measure a minimum of 1/8" rise or fall at 25'. Makes present day bubble and string type levels obsolete. It not only indicates level but shows exactly how much correction is needed. One man can perform any leveling or incline measuring job quickly, easily, and accurately. Makes any complicated measuring/leveling job simple. Use it for patio layout, bricklaying, flooring, surveying, terracing, fencing, plumbing, shelving, guttering, drainage, irrigation, indispensable as a leveling and grading tool for model railway pike. Shpg. wt., 1 1/4 lbs.

14 R 18011 Net 8.50
14 R 18029 case—Shpg. wt., 3/4 lbs. Net 4.95



HIPPO POWERFUL VACUUM CLEANER

34⁹⁵



Powerful, portable vacuum for general household cleaning or use in the garage or garden. Rugged Lexan housing. Only 15" long and 7" dia. Equipped with 3' hose, 9" crevice tool, 2 1/4" round dusting brush, 5" upholstery nozzle, 9" floor nozzle with brush and 2-pc. 40" extension wand—all 1 1/2" diameter. Weighs 6 1/2 lbs. 1 HP motor. UL and CSA listed. Comes with 2 1/4" to 1 1/2" adapter for use of standard vacuum accessories. Supplied with 18 ft. cord and shoulder strap. Shpg. wt., 13 lbs.

13 R 35637W No Money Down* Net 34.95
Disposable Paper Bags for Hippo. Pkg. of 5. Net .99
13 R 35645

MULTI-PURPOSE GUN TACKER KIT



Only **14⁹⁵**

- Includes: Gun, Case—Wiring, Screening, And Window Shade Attachments—Staple Lifter

Professional staple gun with a powerful action that drives 6 heavy duty staple sizes, 1/4", 3/8", 1/2", 5/8", 3/4" and Cellitile®—especially designed for ceiling tile. Kit contains: staple gun; multi-staple pak of 2000 1/4", and 1000 ea. 3/8", 1/2" and Cellitile® staples, and attachments.

13 R 5750W Shpg. wt., 4 3/4 lbs. Net 14.95
STAPLES FOR THE MODEL T-50 GUN
Shpg. wt., 8 oz.
1/4" PKG. OF 5000

13 R 5752A Net 2.75
MULTI-PAK—ASSORTMENT OF 5000
2000 - 1/4", 1000 ea. OF 3/8", 1/2" & CEIL TILE®
13 R 57557 Net 2.75

Swingline® STAPLE GUNS

(A) HEAVY DUTY STAPLE GUN

- Built-In Staple Extractor
 - Easy Loading of 5 Staple Sizes
- Model 800 drives 5 sizes of staples. Snap open load. Exclusive power dot and tandem springing deliver super power. Loading takes only a moment. Built in extractor. Accepts 1/4" to 3/8" staples including special loktile staples for firm holding of ceiling tiles.
13 R 58126 Shpg. wt., 2 lbs. Net 8.95
1000 staples for #800 staple guns.

Stock No.	Leg Length	Shpg. wL	Net
13 R 58134	1/4"	7 oz.	.55
13 R 58142	3/8"	7 oz.	.60
13 R 58159	1/2"	8 oz.	.60
13 R 58167	5/8"	9 oz.	.70
13 R 58183†	3/4"	8 oz.	.80

†Special Loktile Staples

(B) CABLE TACKER

- Fast-action
- Reaches Into Tight Places

Model 300 Swingline fast-action staple gun for fastening low voltage electric and telephone wire, cable, rods, barbed wire, etc. Fires arched crown staples, 1/4"x3/8". Narrow width permits reaching into tight places.
13 R 58092 Shpg. wt., 2 1/2 lbs. Net 12.95
13 R 58100 Shpg. wt., 8 oz. Net 1.59



(A)
MODEL 800
8⁹⁵

(B)
MODEL 300
12⁹⁵

*See Page 22 for Full Credit Details on Easy Pay Plan

Vises and Metal Working Tools

PORTABLE VACUUM VISE

WITH 2 JAWS, 1½" AND 2½"

5⁹⁵

No clamps, no screws! Vacuum power holds vise securely on any non-porous surface. Use it on formica, linoleum, metal, porcelain or any painted smooth finish surface. Anvil back, 2 jaws, 1½" and 2½" open to 2¼ inches. 360° rotation swivelhead. Easy to use vacuum action and jaw controls. For hobbyist, repairman. Imported.
13 R 55916 Shpg. wt., 5¼ lbs. Net 5.95



3" MACHINIST VISE SWIVEL-BASE

6⁵⁰

A sturdy, reliable, swivel base vise for tool room, home or shop jobs. Three inch jaws; 3" opening. Swivel base permits 280° degree revolution. Locks in any position. Anvil back. Well made of malleable iron castings. Hardened tool steel jaw faces. Ideal for carpentry, sanding, sawing, tool sharpening, carving. Complete with fixed pipe jaws. Imported. Shpg. wt., 10¼ lbs.
13 R 55908 Net 6.50



HEAVY DUTY 4" SWIVEL BASE VISE

10⁹⁵

This favorite machinist vise swivels full 280° Width of Jaw: 4". Geared bolt and base plate give positive lock against slippage. Removable hardened pipe jaws open to 4¾"; plated screw bar. Steel handle balls forged from handle stock. Precision machined malleable iron castings. Self-lubricating graphite bronze bearing. Imported. Shpg. wt., 18¾ lbs.
13 R 55890 Net 10.95



HEAVY DUTY 6" MODEL. Similar to above: Width of Jaws: 6" opens to 6¼". Shpg. wt., 26¼ lbs.
13 R 56120W Net 16.95

WILTON

ELECTRONIC VISE WITH POSITIONER

17⁹⁵

For small sub-assemblies and intricate electronic work including printed circuits. Rubber protected jaws are 2¼" W with a 6¼" opening. PowRarm positioner offers superior positive lock and fast on-off action with horizontal handle. Shpg. wt., 2¼ lbs.
14 R 80029 Net 17.95



6⁹⁵

DOUBLE POWER GRINDER

• With 2 Grinding Wheels

Equipped with double tool rests — will accommodate 4" or 5" grindstone. Nylon bearings require little or no lubrication, and have outstanding abrasion resistant characteristics. Furnished complete with one coarse, one fine grinding wheel. Shpg. wt., 10¼ lbs.
14 R 76043 Net 6.95



BERNZCUTTER

CUTTING TOOL KIT

Cuts Anything
Metal or Plastic

ONLY 5⁹⁵

BernzCutter cleanly and easily cuts plastics and laminates up to ¼", floor tile, sheet metals (steel up to .040"), pegboard or paneling. Eliminates the danger of tearing or cracking delicate materials as with ordinary cutting tools. Hand operated BernzCutter is compact, can be used in confined areas. No limit to length of cut. Form fitting handles provide a comfortable grip for continuous use. With 1 metal cutting, 1 plastic cutting and 1 shaper blade for circles and curves plus die-instruction book. Shpg. wt., 1 lb.
14 R 31501 Net 5.95


4 TOOLS IN ONE

Complete Metal Workshop

FOR INDUSTRIALS, EXPERIMENTERS, REPAIR SHOPS,
MODEL WORKERS, SCHOOL SHOPS, HOME WORK SHOPS

• Punches • Shears • Rivets • Forms

An ideal tool for plant, shop or home use. Used extensively in industrial plants on small jobs. Handles stock up to 1" wide to 16 gauge. Punches clean, sharp, smooth, burr-free holes — up to 1" from edge — ¾" and ¼" round. Forms bend up to 90° in rod or bar stock. Cleanly shears metals up to 1" wide. 16 gauge, without distortion. Rivets easily with any type solid or hollow rivet. Rivets up to a maximum combined thickness of ¾". Shpg. wt., 5½ lbs.
14 R 11016 Net 11.95



EXTRA PUNCH SETS.

Avg. shpg. wt., 3 oz.
14 R 11024 Hex—3¼", ½" and ¼" Net 2.59
11 R 11032 Square—½" and ¾" Net 1.79
14 R 11040 Rectangular—½" x ¾" and ¼" x ¼" Net 1.79
14 R 11057 Round—¼", ⅜", ½" Net 2.59

HEAVY DUTY 18" BENDING AND FORMING BRAKE

• For Experimenters—
Servicemen—Shops
• Clean Smooth Bends
• Forms Up To 90°

• Handles Up To 18"
Width In Up To 16
Gauge Thickness

12⁹⁵

Rugged heavy-duty all steel construction and unique design permits forming chassis, boxes, covers, trays, etc. by means of 1" deep slots in brake-bar which allows corners to fold in. Provides flange edges up to 1" high. Easy to adjust for thickness, accuracy, angle of bend. Features built-in clamps. Imported. Shpg. wt., 16 lbs.
99 R 80640W Net 12.95



ADEL HAND "NIBBLING" TOOL

4⁵⁰ • Cuts Sheet Metal Like
a Punch and Die


Easily operated hand nibbler" cuts any shape hole in sheet steel—aluminum—copper—or plastic. Metal remains flat and straight after cutting. Does not add strain or distortion to edges. Cuts holes in preformed sheet metal without distorting original form. Cuts in all directions. Any design—angle—radius. Follows scribe lines easily. Best possible tool for cutting template and model parts.
14 R 12055 Shpg. wt., 10 oz. Net 4.50



Replacement punch for above
14 R 12063 Net 2.50

3" MITRE CORNER CLAMP

Portable clamp fully exposes both sides of the joint — allows you to put fastenings wherever you wish. Handy for clamping, cutting, gluing, nailing, etc. Sturdy die-cast aluminum. Chrome plated T-slide bars. Imported. Shpg. wt., ¾ lb.
14 R 70111 Net 1.39



1³⁹

HAND VISE

The only practical way to grip and hold small parts. 1¼" die cast jaws open to 7/8". Mounted on a 4" comfortable ferried-workman handle. Holds work for drilling, marking, filing, sawing, etc. Endless uses in handiwork. Imported. Shpg. wt., 8 oz.
13 R 55346 Net .99



Precision Metal Working Tools

GREENLEE CHASSIS PUNCHES



Type 730 Round Table Punches

Cut holes in metals up to 16 gauge thick with the turn of an ordinary wrench. No sawing, reaming or filing. TYPE 730, Round Holes, AVG. Shpg. wt., 7 lbs. ea.

Stock No.	Size	Net ea.	Stock No.	Size	Net ea.
13 R 29010	1/2"	3.05	13 R 29267	1 1/4"	3.60
13 R 29028	3/8"	3.05	13 R 29432	1 3/4"	4.45
13 R 29036	5/8"	3.05	13 R 29275	1 3/8"	4.45
13 R 29044	1 1/8"	3.05	13 R 29283	1 1/2"	4.90
13 R 29051	3/4"	3.05	13 R 29291	1 3/8"	5.95
13 R 29069	1 1/4"	3.05	13 R 29309	1 3/4"	6.80
13 R 29077	7/8"	3.05	13 R 29317	1 7/8"	8.40
13 R 29085	1"	3.45	13 R 29325	2"	9.00
13 R 29093	1 1/4"	3.45	13 R 29333	2 1/8"	9.70
13 R 29101	1 1/2"	3.50	13 R 29341	2 1/4"	10.00
13 R 29119	1 3/4"	3.50	13 R 29358	2 1/2"	16.30
13 R 29127	1 3/2"	3.50	13 R 29366	2 3/4"	22.65
13 R 29135	1 3/4"	3.50	13 R 29382	3"	31.30

TYPE 731, Square Holes, Punches.

Stock No.	Size	Net ea.
13 R 29143	1/2"	8.10
13 R 29150	3/8"	8.70
13 R 29168	3/4"	8.80
13 R 29390	7/8"	10.20
13 R 29408	1"	10.70

TYPE 732, Keyed Sockets, Punches.

Stock No.	Size	Net ea.
13 R 29176	1 1/2"	7.45
13 R 29184	1 3/4"	7.85
13 R 29192	1 7/8"	8.50
13 R 29416	1 3/4"	10.00
13 R 29424	1 3/4"	11.00

Replacement cap screws for 730, round hole, punches above. Shpg. wt., 1 1/4 ozs.

13 R 29200	For 1/2", 3/8", 5/8"	Net .35
13 R 29218	For 1 1/4" through 7/8"	Net .35
13 R 29226	For 1" through 1 1/2"	Net .50
13 R 29234	For 1 3/8" through 1 3/4"	Net .60
13 R 29242	For 1 7/8" through 2 1/2"	Net .70
13 R 29259	For 2 3/4" and 3"	Net .75

LAFAYETTE CHASSIS PUNCH SET

- Easy-smooth holes in sheet metal
- 5 Sizes: 1/2", 3/8", 3/4", 1", 1 1/8"

6.95



Five most often needed round hole punches. Easily cuts smooth accurate holes for sockets, plugs, controls, panel lights, switches, terminals, and most radio parts. Drive with any wrench or with included T-handle. Punch sizes included are 1/2", 3/8", 3/4", 1", 1 1/8". Complete with punches, dies, T drive handle, tapered reamer, fitted case, and instructions. Shpg. wt., 2 lbs. Imported. 99 R 80244 Net 6.95

DELUXE 40-PIECE TAP AND DIE SET

9.95

- National Coarse & Fine Thread



40-pc. set for mechanics, machinists, engineers. One tap and die in each of following: 4-36, 12-24, 3/8-16, 3/4-24, 6-32, 1/4-20, 5/16-20, 1/2-20, 8-32, 1/4-28, 3/16-14, 1/2-13, 10-32, 3/4-18, 3/4-24, 1/2-Pipe Tap; plus long handle adjustable tap wrench, "T" handle tap wrench, die handle, screwdriver, screw pitch gauge. Hinged metal box with moulded rubber inlay tray. Imported. 13 R 55882 Shpg. wt., 3 1/2 lbs. Net 9.95

20-PIECE TAP AND DIE SET

- National Coarse Sizes 4.95



Twenty of the most often needed tapes and dies. Sizes popularly used in radio, hobby, home, shop and light industry. Contains one tap and one die in each of the following sizes: 6-32, 8-32, 10-24, 12-24, 1/4-20, 3/8-16, 3/8-14, and 1/2-13. Including die stock and adjustable tap wrench. Entire set contained in a fitted metal case. Imported. Shpg. wt., 2 1/4 lbs. 13 R 55106 Net 4.95

12 NEEDLE FILES

- Swiss Pattern

All files are double cut for sharper, faster cutting. For hobbyist, jewelers, watchmakers, etc. all over the world. Consists of 12 assorted flat, oval, round, triangular and edge files to fit every need. Imported. Shpg. wt., 1/2 lb.



14 R 64536 Net 4.95

NUT SPLITTER

5.95



- Handy For Removing Frozen Nuts
- Easy to Use

Nut splitter, a handy, compact time-saver only 4 3/4" long, this tool will split nuts up to 3/4" across flats. A few turns with any 3/4" hand wrench cuts the nut for easy removal.

14 R 52869 Shpg. wt., 1 lb. Net 5.95

HANDY WARDING FILE SET

1.19

- 5 Individual Files



Perfect for shop—home—hobby work. Kit consists of flat, half round, triangular, square, round and taper files. All with individual hard plastic handles. Sturdy plastic pocket case included. Imported.

13 R 55122 Shpg. wt., 5 oz. Net 1.19

18-PC. HEX KEY WRENCH SET

89¢



9 short arm wrenches from .050" through 1/4", and 9 long arm wrenches 3/8" through 3/4". Quality tool steel. Bright plated—in plastic roll up kit, imported.

14 R 76019 Shpg. wt., 3/4 lb. Net .89

PATTERN MAKER AND CONTOUR GAUGE

1.59



- Match and Outline Any Irregular Shape
- For home, shop and industry. Simplifies measurement and copying of irregular shapes. Easy to use, just press the gauge's steel teeth against any irregular surface to exactly match and hold the shape taken. Uses include: measuring pillar contour, fitting, floor tile, carpeting, wood mouldings, linoleum. 6" long. Imported.

14 R 52051 Shpg. wt., 3/4 lb. Net 1.59

REMINGTON 10" TUNGSTEN CARBIDE ROD SAW

1.79



- Cuts Like a Diamond
- Super abrasive
- Fits Any Hacksaw Frame

Cuts materials that an ordinary hacksaw can't cut; ceramic tile, glass, masonry materials, tough plastics, welds, steel alloys... virtually anything hard or tough. Cuts curves and angles in any direction. No teeth to blunt, break, set or sharpen. Fits common hacksaw frame. Shpg. wt., 3 oz.

13 R 38508 Net 1.79

10" Flat Tungsten Carbide Hacksaw Blade. Net 1.95

13 R 38516 Similar to Above. Net 1.95

VERNIER SLIDING CALIPER

1.49



Sharp pointed projection for accurate dividing, scribing, etc. Lock nut insures against errors caused by sliding gauge. Rule graduated in 16th and 32nds plus 5" depth gauge. Precision made. Imported. Shpg. wt., 6 oz. 14 R 61128 Net 1.49

SAFETY EYE GUARD

Made in USA. Meets Fed. Spec. for impact and piercing. Optically clear plastic. Non-fogging. Well ventilated. Undistorted vision. Fits any size corrective eyeglasses. Shpg. wt. 5 ozs. 13 R 55353 Net 1.19



High Quality Pliers—Cutters for Electronics

KRAEUTER "INDUSTRIAL" PLIERS


CHAN NEL LOCK LITTLE CHAMP PRECISION PLIERS



• All With Cushion Grip Handles

Fine quality—hammer-forged from high grade tool steel. Individually fitted, tempered and adjusted. Fully polished heads. Rust-resistant cushion grip handles. Ave. Shpg. wt., 1 lb.


Stock No.	Type	Fig.	Description	Net
13 R 28012	35015	1	5" Diagonal Cutters	3.29
13 R 28020	35016	1	5" Diagonal Cutters	3.29
13 R 28038	37015	2	5" Needle Point Diagonals	3.69
13 R 28046	36616	2	6" Needle Nose with Cutter	3.39
13 R 28079	27510	4	10" Joint Pliers	3.09
13 R 28202	36535	5	5" Radio & Ignition Long Nose Cutting Pliers (Cross-Coil Springs)	3.99
13 R 28095	36107	6	7" Heavy Duty Diag.	3.39



• Top Quality Precision Pliers

Fine quality small pliers, ruggedly designed for bench work that requires delicate handling. Drop forged from high grade steel. Precision made and polished to jewelers finish with plastic cushion grip handles. Avg. shpg. wt., 5 ozs.

Stock No.	Type	Fig.	Description	Net
13 R 30059	41-G	A	4 1/4" Diagonal Cutter	3.39
13 R 30067	42-G	B	4" End Cutter Nipper	3.39
13 R 30075	43-G	C	4 1/4" Needle Nose	2.89
13 R 30083	44-G	D	4 1/4" Flat Nose	2.89
13 R 30091	45-G	E	4 1/2" Round Nose	3.19
13 R 30109	47-G	F	4 1/2" Needle Nose Cutter	3.39
13 R 30117	48-G	G	4 3/4" Transverse End Cutter	3.49
13 R 30125	49-G	H	4 1/2" Curved Needle Nose	3.39



CHAN NEL LOCK ELECTRONIC PLIERS

(A) 6 1/4" LONG NOSE PLIERS. Durable drop forged steel pliers with hardened and tempered side cutting edges. Insulated handles for protection and comfort. Thin nose reaches into any space. Completely polished and lacquered finish to prevent rusting. Imported. Shpg. wt., 7 oz.
13 R 55783 Net 1.69

(B) 6 1/4" DIAGONAL CUTTING PLIERS. Fully drop forged steel construction. Hardened and tempered cutting edges... thin nose for hard to reach places. Shockproof handles are insulated for comfort and protection. Rust-proof finish is completely polished and lacquered. Imported. Shpg. wt., 9 oz.
13 R 55791 Net 1.69

(C) 7" LINESMAN'S CUTTING PLIERS. Large strong holding grip. Rugged drop forged construction... tempered steel edges. Comfort design handles are shock insulated. Nose and handles protected by polished and lacquered finish—prevents rusting. Imported. Shpg. wt., 14 oz.
13 R 55809 Net 1.95


(D) 8" SLIP JOINT PLIERS. Rugged, efficient... adjust to a variety of positions, reach into any area. Strong gripping head with insulated cushion-grip handles. Long-lasting drop forged steel with attractive and protective chrome plated finish. Imported. Shpg. wt., 12 oz.
13 R 55817 Net 1.39

(E) 6 1/2" CURVE NOSE PLIERS. Versatile long-nose pliers bent 45° at midpoint of jaws. Forged from special heat treated alloy steel. Hand honed side cutters. Insulated grips.
13 R 55205 Shpg. wt., 7 oz. Net 1.39

(F) LIGHTWEIGHT LONG NOSE PLIERS. Ideal for all types of delicate work and for reaching into hard-to-get at places. Spring closing—holds wires, nuts, screws, etc. Handy for mechanics, assemblers, hobbyists. 8 3/4" long, with soft plastic colored handles. Shpg. wt., 5 oz.
14 R 26014 Net 1.39


(G) 9 1/2" HEAVY DUTY WATER PUMP PLIERS. Drop forged arc joint slip-groove for big leverage on work you can't get with other gripping tools. Fully chromed and polished pliers offer maximum leverage and strength. 5 adjustments. 1" parallel opening. Deep milled jaws made of chrome vanadium steel. Insulated handles. Imported. Shpg. wt., 1 1/4 lbs.
14 R 55211 Net 2.29

(H) 10" PLI-GRIP WRENCH WITH QUICK RELEASE. Made of high quality chrome molybdenum steel. All purpose drop-forged steel jaw for flat, round, or hex work. Quick flingerlip release lever permits convenient one hand operation. Has spring tension adjustment and bright plated finish. Imported.
13 R 55999 Shpg. wt., 1 1/4 lbs. Net 2.39



Forged from high grade steel, precision machined. Specially designed for fine electronics work. Long slender reach... precision-matched jaws... hand-honed, specially hardened cutting edges. The 738G long reach, round nose will pick up a human hair with its precision machined parts. The 728G-long reach diagonal cutters have a patented wire stripper that really works. With dipped plastic grips. Shpg. wt., 10 oz.
738G Round Nose 8" Long Net 3.39
728G Diagonal Cutter 7 1/2" Long Net 3.59
13 R 30034

REVOLVING LEATHER PUNCH



Has 6 standard punching tubes. Made of long-lasting tempered steel. Imported.
14 R 61144 Shpg. wt., 13 ozs. Net 1.69

ELECTRICIAN'S KNIFE



For handymen and electricians. Two-blade knife with safety lock. Features a knife, wire scraper and screwdriver. Non slip handle. Overall size: 3 5/8". With belt loop.
14 R 16510L Net 1.59

WIRE STRIPPER AND CUTTER

1.49 • Self Opening
• Strips Wire From 10-24 Gauge

For any size wire, stranded or solid. Adjustable arm for varying wire size. Made of hardened tool steel finely ground cutting edges. Built-in spring holds cutter open. Has ring-latch to hold blades in closed position. Shpg. wt., 6 oz.
14 R 16502 Net 1.49

AUTOMATIC WIRE STRIPPER AND CUTTER

ONLY 4.95 • Automatic Stay-Open Feature

Precision tool automatically cuts, strips all types of electrical insulated wire. Works on all standard gauges from 12 through 24. Complete with wire guide. Insulated handles. Imported. Shpg. wt., 3/4 lbs.
14 R 61250 Net 4.95

Professional Screwdrivers-Nutdrivers



(A) SERVICE MASTER TOOL KIT

- Versatile — 23 Piece Set — Quick-Change Tools
- Durable, Roll-Up Vinyl Canvas Case

Model 99SM—Valuable kit has: pliers—6" long nose and 5" diagonal; 6" adjustable wrench; 9 regular nutdrivers 3/16" through 1/2"; 3 stubby nutdrivers, 1/4", 3/16" and 3/8"; Phillips screwdriver; 2 slotted screwdrivers, 3/16" and 1/4"; 2 reamers; extension. Shpg. wt., 3 3/4 lbs. Net 27.90

13 R 46436



(B) "TRAY BIEN" NUT DRIVER SET

- Solid Shaft 7 Color Coded Nut Drivers
- Carrying Case for Bench Caddy or Wall Mounting

Model 127TB molded plastic bench tray has fold away stand. Holds tools securely yet permits easy removal. Hex sizes 3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8". Net 6.75

13 R 46469 Shpg. wt., 1 3/4 lbs.



(C) NUT DRIVER SCREWDRIVER SET

- 14 Piece Nut and Screwdriver Set
- Durable Plastic Roll Kit

Model 99PR—Thirteen interchangeable nut drivers and screwdrivers. Nine nutdrivers, 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2". Slotted screwdriver 3/16" and 1/4". Phillips screwdrivers #1 and #2. Handle. Roll up kit. Shpg. wt., 1 3/4 lbs. Net 9.60

13 R 46212



(D) "TRAY BIEN" NUT DRIVER SET

- Hollow Shaft—7 Color Coded Nut Drivers
- Carrying Case for Bench, Caddy or Wall Mounting

Model 147TB contains 7 hollow shaft color coded nut drivers. (Hex sizes 1/4", 9/32", 5/16", 11/32", 3/8", 7/16", 1/2".) Housed in attractive "snap lock" case for secure holding and easy removal. 13 R 4677 Shpg. wt., 2 lbs. Net 8.94

13 R 4677

COMPACT DOUBLE DUTY TOOL SETS

(E) PS-120 COMPACT NUTDRIVER SET—10 nutdrivers, 3 1/2" pocket-size, Piggy-back "torque amplifier" handle slips over pocket tool handles, gives grip and power of standard drivers. See-thru plastic case, slimmest to fit your pocket; stands on flat base. 3/8, 1/2, 5/8, 3/4, 7/8, 1, 1 1/8, 1 1/4, 1 1/2, 1 3/4, 2. Shpg. wt., 3/4 lb. Net 6.15

13 R 46022

(F) PS 7 DOUBLE DUTY TOOL SET—Saves bench space. Gives grip, reach and power of standard drivers with remarkable "torque amplifier" handle. Set includes: (all 3 1/2") 2 color coded nutdrivers, 1/4" and 3/8"; 2 slot tip screwdrivers, 2 Phillips screwdrivers, #0 and #1. Slim, pocket-fitting see-thru plastic case. Net 4.28

13 R 46220 Shpg. wt., 1/2 lb.

(G) PS 88 SCREWDRIVER SET—Compact, for bench and pocket. Set has 5 slot tip screwdrivers: 3/8, 1/2, 5/8, 3/4, 1/2"; 3 Phillips screwdrivers: #0, #1, #2. All 3 1/2" pocket size plus 1x3 1/4" hollow handle. See thru plastic case, stand-up base. Shpg. wt., 9 oz. Net 4.47

13 R 46444

(H) 99PS-50 SET OF SCREWDRIVERS-NUTDRIVERS—Contains seven nutdrivers: 3/8, 1/2, 5/8, 3/4, 1/2, 3/8, 1/4, and 3/16"; two slotted screwdrivers: #0 and #1 and #2 Phillips screwdrivers; an extension blade (adds 4" reach to single end blades) regular handle 1 1/4x4 1/8". Easy to work with in space-saving, convenient see-thru plastic case with flat base that stands up on work bench. Shpg. wt., 1 1/2 lbs. Net 9.15

13 R 46451



XCELITE POPULAR 6 PIECE SCREWDRIVER SET

- In Handy See-Thru Plastic Case

Only
5⁵⁰



Assorted popular sizes to meet the requirements of a great variety of service, production and maintenance applications. High quality chrome vanadium blades with tough shockproof plastic (UL) handles. Set includes 4 slotted blade screwdrivers 1/4", 3/8", 1/2" and 5/8", and 2 Phillips Type #1, #2, and #2-1/4", overall lengths 6 3/8" to 10 1/4". Shpg. wt., 2 1/4 lbs. Net 5.50

13 R 46550

HIGH QUALITY CHROME VANADIUM SHAFTS—UL HANDLES



SLOTTED BLADE SCREWDRIVERS

Stock No.	Type #	Shaft Size	Overall	Net
13 R 46246	R144	4"x1/4"	8"	1.11
13 R 46253	R146	6"x1/4"	10"	1.22
13 R 46261	R148	8"x1/4"	12"	1.28
13 R 46279	R182	2"x3/8"	2 1/2"	.47
13 R 46287	R183	3"x3/8"	5"	.44
13 R 46295	R184	4"x3/8"	6 1/2"	.54
13 R 46311	R188	8"x3/8"	10 1/2"	.71
SET-SCREW TYPE—with pocket clip				
13 R 46329	R184 1/2	4"x3/8"	6"	.47
13 R 46337	R3223	3"x3/8"	5"	.44
PHILLIPS SCREWDRIVERS—alloy steel				
13 R 46345	X101	3" #1 pt.	6 1/2"	.91
13 R 46352	X102	4" #2 pt.	7 3/4"	1.11
13 R 46360	X103	6" #3 pt.	10"	1.62
13 R 46378	X108	6" #1 pt.	10"	1.08

HOLLOW SHAFT NUT DRIVERS

Stock No.	Type #	Shaft Size	Overall	Net
13 R 46485	HS-6	3/8"	6 1/4"	1.15
13 R 46493	HS-7	3/8"	6 1/4"	1.15
13 R 46113	HS-8	1/2"	7"	1.15
13 R 46501	HS-9	3/4"	7"	1.15
13 R 46121	HS-10	3/4"	7"	1.15
13 R 46139	HS-11	1/2"	7"	1.15
13 R 46147	HS-12	3/8"	7"	1.15
13 R 46519	HS-13	1/2"	7 1/4"	1.32
13 R 46154	HS-14	3/4"	7 1/4"	1.32
13 R 46527	HS-15	1/2"	7 1/4"	1.32
13 R 46162	HS-16	1/2"	7 1/4"	1.32
13 R 46170	HS-18	3/4"	7 1/4"	1.38
13 R 46188	HS-20	5/8"	7 5/8"	1.55
13 R 46535	HS-22	1/2"	7 5/8"	2.36
13 R 46543	HS-24	3/4"	7 5/8"	2.36

Shpg. wt., 6 oz.

Extremely handy tool for assembling and disassembling. It's a 1/4 and 3/8" nut driver, a no. 1 Phillips screwdriver, and a 3/8" slotted screwdriver. Shpg. wt., 5 oz. Net 1.92

13 R 46238

4-WAY POCKET TOOL



SELECTED TOOLS for The Hobbyist

Electric Glue Gun

Swingline



- Automatic Feed Trigger
- Finger Tip Control Thermostat

750

Features exclusive automatic feed trigger and finger tip thermostat control, handy "on-off" switch plus contoured handle. You get 60 second bonding for wood, tile, leather, fabrics, metals, masonry, or caulking. Thermostat control has three heat ranges for "idling," "normal operation" and "extra flow." "Open/Close" nozzle control valve wrench included. Rated 70 watts at 120V., AC/DC. UL listed. Size: 6 3/4" x 4 1/2". Made of black heat-resistant phenolics.
 13 R 58217 Shpg. wt., 1 1/4 lbs. Net 7.50
 Pkg. of 8 Hot Melt Glue Sticks. Net .49
 13 R 58225 Shpg. wt., 4 oz. Net .49
 Pkg. of 8 Hot Melt Caulk. Net .49
 13 R 58233 Shpg. wt., 4 oz. Net .49

Moody

Miniature Tool Set



- In Handsome Leatherette Case

24⁹⁵

Here's a practical set of 6 individual small tool sets each with chuck-type handles for the sportsman, hobbyist, do-it-yourselfer, TV, and hi-fi enthusiast. SC-5 Tiny Screw Driver & Awl Set (Sizes: .055", .070", .080", .100", .125", .150", .175", .200", .250", .300", .350", .400", .450", .500", .550", .600", .650", .700", .750", .800", .850", .900", .950", 1.000", 1.100", 1.200", 1.300", 1.400", 1.500", 1.600", 1.700", 1.800", 1.900", 2.000", 2.100", 2.200", 2.300", 2.400", 2.500", 2.600", 2.700", 2.800", 2.900", 3.000", 3.100", 3.200", 3.300", 3.400", 3.500", 3.600", 3.700", 3.800", 3.900", 4.000", 4.100", 4.200", 4.300", 4.400", 4.500", 4.600", 4.700", 4.800", 4.900", 5.000", 5.100", 5.200", 5.300", 5.400", 5.500", 5.600", 5.700", 5.800", 5.900", 6.000", 6.100", 6.200", 6.300", 6.400", 6.500", 6.600", 6.700", 6.800", 6.900", 7.000", 7.100", 7.200", 7.300", 7.400", 7.500, 7.600, 7.700, 7.800, 7.900, 8.000, 8.100, 8.200, 8.300, 8.400, 8.500, 8.600, 8.700, 8.800, 8.900, 9.000, 9.100, 9.200, 9.300, 9.400, 9.500, 9.600, 9.700, 9.800, 9.900, 10.000, 10.100, 10.200, 10.300, 10.400, 10.500, 10.600, 10.700, 10.800, 10.900, 11.000, 11.100, 11.200, 11.300, 11.400, 11.500, 11.600, 11.700, 11.800, 11.900, 12.000, 12.100, 12.200, 12.300, 12.400, 12.500, 12.600, 12.700, 12.800, 12.900, 13.000, 13.100, 13.200, 13.300, 13.400, 13.500, 13.600, 13.700, 13.800, 13.900, 14.000, 14.100, 14.200, 14.300, 14.400, 14.500, 14.600, 14.700, 14.800, 14.900, 15.000, 15.100, 15.200, 15.300, 15.400, 15.500, 15.600, 15.700, 15.800, 15.900, 16.000, 16.100, 16.200, 16.300, 16.400, 16.500, 16.600, 16.700, 16.800, 16.900, 17.000, 17.100, 17.200, 17.300, 17.400, 17.500, 17.600, 17.700, 17.800, 17.900, 18.000, 18.100, 18.200, 18.300, 18.400, 18.500, 18.600, 18.700, 18.800, 18.900, 19.000, 19.100, 19.200, 19.300, 19.400, 19.500, 19.600, 19.700, 19.800, 19.900, 20.000, 20.100, 20.200, 20.300, 20.400, 20.500, 20.600, 20.700, 20.800, 20.900, 21.000, 21.100, 21.200, 21.300, 21.400, 21.500, 21.600, 21.700, 21.800, 21.900, 22.000, 22.100, 22.200, 22.300, 22.400, 22.500, 22.600, 22.700, 22.800, 22.900, 23.000, 23.100, 23.200, 23.300, 23.400, 23.500, 23.600, 23.700, 23.800, 23.900, 24.000, 24.100, 24.200, 24.300, 24.400, 24.500, 24.600, 24.700, 24.800, 24.900, 25.000, 25.100, 25.200, 25.300, 25.400, 25.500, 25.600, 25.700, 25.800, 25.900, 26.000, 26.100, 26.200, 26.300, 26.400, 26.500, 26.600, 26.700, 26.800, 26.900, 27.000, 27.100, 27.200, 27.300, 27.400, 27.500, 27.600, 27.700, 27.800, 27.900, 28.000, 28.100, 28.200, 28.300, 28.400, 28.500, 28.600, 28.700, 28.800, 28.900, 29.000, 29.100, 29.200, 29.300, 29.400, 29.500, 29.600, 29.700, 29.800, 29.900, 30.000, 30.100, 30.200, 30.300, 30.400, 30.500, 30.600, 30.700, 30.800, 30.900, 31.000, 31.100, 31.200, 31.300, 31.400, 31.500, 31.600, 31.700, 31.800, 31.900, 32.000, 32.100, 32.200, 32.300, 32.400, 32.500, 32.600, 32.700, 32.800, 32.900, 33.000, 33.100, 33.200, 33.300, 33.400, 33.500, 33.600, 33.700, 33.800, 33.900, 34.000, 34.100, 34.200, 34.300, 34.400, 34.500, 34.600, 34.700, 34.800, 34.900, 35.000, 35.100, 35.200, 35.300, 35.400, 35.500, 35.600, 35.700, 35.800, 35.900, 36.000, 36.100, 36.200, 36.300, 36.400, 36.500, 36.600, 36.700, 36.800, 36.900, 37.000, 37.100, 37.200, 37.300, 37.400, 37.500, 37.600, 37.700, 37.800, 37.900, 38.000, 38.100, 38.200, 38.300, 38.400, 38.500, 38.600, 38.700, 38.800, 38.900, 39.000, 39.100, 39.200, 39.300, 39.400, 39.500, 39.600, 39.700, 39.800, 39.900, 40.000, 40.100, 40.200, 40.300, 40.400, 40.500, 40.600, 40.700, 40.800, 40.900, 41.000, 41.100, 41.200, 41.300, 41.400, 41.500, 41.600, 41.700, 41.800, 41.900, 42.000, 42.100, 42.200, 42.300, 42.400, 42.500, 42.600, 42.700, 42.800, 42.900, 43.000, 43.100, 43.200, 43.300, 43.400, 43.500, 43.600, 43.700, 43.800, 43.900, 44.000, 44.100, 44.200, 44.300, 44.400, 44.500, 44.600, 44.700, 44.800, 44.900, 45.000, 45.100, 45.200, 45.300, 45.400, 45.500, 45.600, 45.700, 45.800, 45.900, 46.000, 46.100, 46.200, 46.300, 46.400, 46.500, 46.600, 46.700, 46.800, 46.900, 47.000, 47.100, 47.200, 47.300, 47.400, 47.500, 47.600, 47.700, 47.800, 47.900, 48.000, 48.100, 48.200, 48.300, 48.400, 48.500, 48.600, 48.700, 48.800, 48.900, 49.000, 49.100, 49.200, 49.300, 49.400, 49.500, 49.600, 49.700, 49.800, 49.900, 50.000, 50.100, 50.200, 50.300, 50.400, 50.500, 50.600, 50.700, 50.800, 50.900, 51.000, 51.100, 51.200, 51.300, 51.400, 51.500, 51.600, 51.700, 51.800, 51.900, 52.000, 52.100, 52.200, 52.300, 52.400, 52.500, 52.600, 52.700, 52.800, 52.900, 53.000, 53.100, 53.200, 53.300, 53.400, 53.500, 53.600, 53.700, 53.800, 53.900, 54.000, 54.100, 54.200, 54.300, 54.400, 54.500, 54.600, 54.700, 54.800, 54.900, 55.000, 55.100, 55.200, 55.300, 55.400, 55.500, 55.600, 55.700, 55.800, 55.900, 56.000, 56.100, 56.200, 56.300, 56.400, 56.500, 56.600, 56.700, 56.800, 56.900, 57.000, 57.100, 57.200, 57.300, 57.400, 57.500, 57.600, 57.700, 57.800, 57.900, 58.000, 58.100, 58.200, 58.300, 58.400, 58.500, 58.600, 58.700, 58.800, 58.900, 59.000, 59.100, 59.200, 59.300, 59.400, 59.500, 59.600, 59.700, 59.800, 59.900, 60.000, 60.100, 60.200, 60.300, 60.400, 60.500, 60.600, 60.700, 60.800, 60.900, 61.000, 61.100, 61.200, 61.300, 61.400, 61.500, 61.600, 61.700, 61.800, 61.900, 62.000, 62.100, 62.200, 62.300, 62.400, 62.500, 62.600, 62.700, 62.800, 62.900, 63.000, 63.100, 63.200, 63.300, 63.400, 63.500, 63.600, 63.700, 63.800, 63.900, 64.000, 64.100, 64.200, 64.300, 64.400, 64.500, 64.600, 64.700, 64.800, 64.900, 65.000, 65.100, 65.200, 65.300, 65.400, 65.500, 65.600, 65.700, 65.800, 65.900, 66.000, 66.100, 66.200, 66.300, 66.400, 66.500, 66.600, 66.700, 66.800, 66.900, 67.000, 67.100, 67.200, 67.300, 67.400, 67.500, 67.600, 67.700, 67.800, 67.900, 68.000, 68.100, 68.200, 68.300, 68.400, 68.500, 68.600, 68.700, 68.800, 68.900, 69.000, 69.100, 69.200, 69.300, 69.400, 69.500, 69.600, 69.700, 69.800, 69.900, 70.000, 70.100, 70.200, 70.300, 70.400, 70.500, 70.600, 70.700, 70.800, 70.900, 71.000, 71.100, 71.200, 71.300, 71.400, 71.500, 71.600, 71.700, 71.800, 71.900, 72.000, 72.100, 72.200, 72.300, 72.400, 72.500, 72.600, 72.700, 72.800, 72.900, 73.000, 73.100, 73.200, 73.300, 73.400, 73.500, 73.600, 73.700, 73.800, 73.900, 74.000, 74.100, 74.200, 74.300, 74.400, 74.500, 74.600, 74.700, 74.800, 74.900, 75.000, 75.100, 75.200, 75.300, 75.400, 75.500, 75.600, 75.700, 75.800, 75.900, 76.000, 76.100, 76.200, 76.300, 76.400, 76.500, 76.600, 76.700, 76.800, 76.900, 77.000, 77.100, 77.200, 77.300, 77.400, 77.500, 77.600, 77.700, 77.800, 77.900, 78.000, 78.100, 78.200, 78.300, 78.400, 78.500, 78.600, 78.700, 78.800, 78.900, 79.000, 79.100, 79.200, 79.300, 79.400, 79.500, 79.600, 79.700, 79.800, 79.900, 80.000, 80.100, 80.200, 80.300, 80.400, 80.500, 80.600, 80.700, 80.800, 80.900, 81.000, 81.100, 81.200, 81.300, 81.400, 81.500, 81.600, 81.700, 81.800, 81.900, 82.000, 82.100, 82.200, 82.300, 82.400, 82.500, 82.600, 82.700, 82.800, 82.900, 83.000, 83.100, 83.200, 83.300, 83.400, 83.500, 83.600, 83.700, 83.800, 83.900, 84.000, 84.100, 84.200, 84.300, 84.400, 84.500, 84.600, 84.700, 84.800, 84.900, 85.000, 85.100, 85.200, 85.300, 85.400, 85.500, 85.600, 85.700, 85.800, 85.900, 86.000, 86.100, 86.200, 86.300, 86.400, 86.500, 86.600, 86.700, 86.800, 86.900, 87.000, 87.100, 87.200, 87.300, 87.400, 87.500, 87.600, 87.700, 87.800, 87.900, 88.000, 88.100, 88.200, 88.300, 88.400, 88.500, 88.600, 88.700, 88.800, 88.900, 89.000, 89.100, 89.200, 89.300, 89.400, 89.500, 89.600, 89.700, 89.800, 89.900, 90.000, 90.100, 90.200, 90.300, 90.400, 90.500, 90.600, 90.700, 90.800, 90.900, 91.000, 91.100, 91.200, 91.300, 91.400, 91.500, 91.600, 91.700, 91.800, 91.900, 92.000, 92.100, 92.200, 92.300, 92.400, 92.500, 92.600, 92.700, 92.800, 92.900, 93.000, 93.100, 93.200, 93.300, 93.400, 93.500, 93.600, 93.700, 93.800, 93.900, 94.000, 94.100, 94.200, 94.300, 94.400, 94.500, 94.600, 94.700, 94.800, 94.900, 95.000, 95.100, 95.200, 95.300, 95.400, 95.500, 95.600, 95.700, 95.800, 95.900, 96.000, 96.100, 96.200, 96.300, 96.400, 96.500, 96.600, 96.700, 96.800, 96.900, 97.000, 97.100, 97.200, 97.300, 97.400, 97.500, 97.600, 97.700, 97.800, 97.900, 98.000, 98.100, 98.200, 98.300, 98.400, 98.500, 98.600, 98.700, 98.800, 98.900, 99.000, 99.100, 99.200, 99.300, 99.400, 99.500, 99.600, 99.700, 99.800, 99.900, 100.000, 100.100, 100.200, 100.300, 100.400, 100.500, 100.600, 100.700, 100.800, 100.900, 101.000, 101.100, 101.200, 101.300, 101.400, 101.500, 101.600, 101.700, 101.800, 101.900, 102.000, 102.100, 102.200, 102.300, 102.400, 102.500, 102.600, 102.700, 102.800, 102.900, 103.000, 103.100, 103.200, 103.300, 103.400, 103.500, 103.600, 103.700, 103.800, 103.900, 104.000, 104.100, 104.200, 104.300, 104.400, 104.500, 104.600, 104.700, 104.800, 104.900, 105.000, 105.100, 105.200, 105.300, 105.400, 105.500, 105.600, 105.700, 105.800, 105.900, 106.000, 106.100, 106.200, 106.300, 106.400, 106.500, 106.600, 106.700, 106.800, 106.900, 107.000, 107.100, 107.200, 107.300, 107.400, 107.500, 107.600, 107.700, 107.800, 107.900, 108.000, 108.100, 108.200, 108.300, 108.400, 108.500, 108.600, 108.700, 108.800, 108.900, 109.000, 109.100, 109.200, 109.300, 109.400, 109.500, 109.600, 109.700, 109.800, 109.900, 110.000, 110.100, 110.200, 110.300, 110.400, 110.500, 110.600, 110.700, 110.800, 110.900, 111.000, 111.100, 111.200, 111.300, 111.400, 111.500, 111.600, 111.700, 111.800, 111.900, 112.000, 112.100, 112.200, 112.300, 112.400, 112.500, 112.600, 112.700, 112.800, 112.900, 113.000, 113.100, 113.200, 113.300, 113.400, 113.500, 113.600, 113.700, 113.800, 113.900, 114.000, 114.100, 114.200, 114.300, 114.400, 114.500, 114.600, 114.700, 114.800, 114.900, 115.000, 115.100, 115.200, 115.300, 115.400, 115.500, 115.600, 115.700, 115.800, 115.900, 116.000, 116.100, 116.200, 116.300, 116.400, 116.500, 116.600, 116.700, 116.800, 116.900, 117.000, 117.100, 117.200, 117.300, 117.400, 117.500, 117.600, 117.700, 117.800, 117.900, 118.000, 118.100, 118.200, 118.300, 118.400, 118.500, 118.600, 118.700, 118.800, 118.900, 119.000, 119.100, 119.200, 119.300, 119.400, 119.500, 119.600, 119.700, 119.800, 119.900, 120.000, 120.100, 120.200, 120.300, 120.400, 120.500, 120.600, 120.700, 120.800, 120.900, 121.000, 121.100, 121.200, 121.300, 121.400, 121.500, 121.600, 121.700, 121.800, 121.900, 122.000, 122.100, 122.200, 122.300, 122.400, 122.500, 122.600, 122.700, 122.800, 122.900, 123.000, 123.100, 123.200, 123.300, 123.400, 123.500, 123.600, 123.700, 123.800, 123.900, 124.000, 124.100, 124.200, 124.300, 124.400, 124.500, 124.600, 124.700, 124.800, 124.900, 125.000, 125.100, 125.200, 125.300, 125.400, 125.500, 125.600, 125.700, 125.800, 125.900, 126.000, 126.100, 126.200, 126.300, 126.400, 126.500, 126.600, 126.700, 126.800, 126.900, 127.000, 127.100, 127.200, 127.300, 127.400, 127.500, 127.600, 127.700, 127.800, 127.900, 128.000, 128.100, 128.200, 128.300, 128.400, 128.500, 128.600, 128.700, 128.800, 128.900, 129.000, 129.100, 129.200, 129.300, 129.400, 129.500, 129.600, 129.700, 129.800, 129.900, 130.000, 130.100, 130.200, 130.300, 130.400, 130.500, 130.600, 130.700, 130.800, 130.900, 131.000, 131.100, 131.200, 131.300, 131.400, 131.500, 131.600, 131.700, 131.800, 131.900, 132.000, 132.100, 132.200, 132.300, 132.400, 132.500, 132.600, 132.700, 132.800, 132.900, 133.000, 133.100, 133.200, 133.300, 133.400, 133.500, 133.600, 133.700, 133.800, 133.900, 134.000, 134.100, 134.200, 134.300, 134.400, 134.500, 134.600, 134.700, 134.800, 134.900, 135.000, 135.100, 135.200, 135.300, 135.400, 135.500, 135.600, 135.700, 135.800, 135.900, 136.000, 136.100, 136.200, 136.300, 136.400, 136.500, 136.600, 136.700, 136.800, 136.900, 137.000, 137.100, 137.200, 137.300, 137.400, 137.500, 137.600, 137.700, 137.800, 137.900, 138.000, 138.100, 138.200, 138.300, 138.400, 138.500, 138.600, 138.700, 138.800, 138.900, 139.000, 139.100, 139.200, 139.300,

High Quality Drop-Forged Steel Socket Sets



• CHROME PLATED **5⁹⁵**
17 PIECE 1/4" DRIVE SOCKET SET

Heavy chrome plated socket set. Contains 6 Pt. socket; 3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8", 7/16", 1/2", 11/16", 3/4", 1". Plus 2" extension, 6" extension, 5 1/4" flex handle, 4 1/2" crossbar, 5 1/2" reversible ratchet. Each set packed in heavy gauge lacquered metal box. Imported, Shpg. wt., 2 1/4 lbs.

13 R 55643

Net 5.95



• CHROME PLATED **14⁹⁵**
21 PIECE 3/8" DRIVE

Precision quality socket set. Contains: 12 Pt. socket sizes: 3/8", 7/8", 1 1/2", 1 3/4", 2", 2 1/4", 2 1/2", 3", 3 1/4", 3 1/2", 4", 4 1/2", 5", 5 1/2", 6", 6 1/2", 7", 7 1/2", 8", 8 1/2", 9", 9 1/2", 10", 10 1/2", 11", 11 1/2", 12", 12 1/2", 13", 13 1/2", 14", 14 1/2", 15", 15 1/2", 16", 16 1/2", 17", 17 1/2", 18", 18 1/2", 19", 19 1/2", 20", 20 1/2", 21", 21 1/2", 22", 22 1/2", 23", 23 1/2", 24", 24 1/2", 25", 25 1/2", 26", 26 1/2", 27", 27 1/2", 28", 28 1/2", 29", 29 1/2", 30", 30 1/2", 31", 31 1/2", 32", 32 1/2", 33", 33 1/2", 34", 34 1/2", 35", 35 1/2", 36", 36 1/2", 37", 37 1/2", 38", 38 1/2", 39", 39 1/2", 40", 40 1/2", 41", 41 1/2", 42", 42 1/2", 43", 43 1/2", 44", 44 1/2", 45", 45 1/2", 46", 46 1/2", 47", 47 1/2", 48", 48 1/2", 49", 49 1/2", 50", 50 1/2, 51", 51 1/2, 52", 52 1/2, 53", 53 1/2, 54", 54 1/2, 55", 55 1/2, 56", 56 1/2, 57", 57 1/2, 58", 58 1/2, 59", 59 1/2, 60", 60 1/2, 61", 61 1/2, 62", 62 1/2, 63", 63 1/2, 64", 64 1/2, 65", 65 1/2, 66", 66 1/2, 67", 67 1/2, 68", 68 1/2, 69", 69 1/2, 70", 70 1/2, 71", 71 1/2, 72", 72 1/2, 73", 73 1/2, 74", 74 1/2, 75", 75 1/2, 76", 76 1/2, 77", 77 1/2, 78", 78 1/2, 79", 79 1/2, 80", 80 1/2, 81", 81 1/2, 82", 82 1/2, 83", 83 1/2, 84", 84 1/2, 85", 85 1/2, 86", 86 1/2, 87", 87 1/2, 88", 88 1/2, 89", 89 1/2, 90", 90 1/2, 91", 91 1/2, 92", 92 1/2, 93", 93 1/2, 94", 94 1/2, 95", 95 1/2, 96", 96 1/2, 97", 97 1/2, 98", 98 1/2, 99", 99 1/2, 100", 100 1/2, 101", 101 1/2, 102", 102 1/2, 103", 103 1/2, 104", 104 1/2, 105", 105 1/2, 106", 106 1/2, 107", 107 1/2, 108", 108 1/2, 109", 109 1/2, 110", 110 1/2, 111", 111 1/2, 112", 112 1/2, 113", 113 1/2, 114", 114 1/2, 115", 115 1/2, 116", 116 1/2, 117", 117 1/2, 118", 118 1/2, 119", 119 1/2, 120", 120 1/2, 121", 121 1/2, 122", 122 1/2, 123", 123 1/2, 124", 124 1/2, 125", 125 1/2, 126", 126 1/2, 127", 127 1/2, 128", 128 1/2, 129", 129 1/2, 130", 130 1/2, 131", 131 1/2, 132", 132 1/2, 133", 133 1/2, 134", 134 1/2, 135", 135 1/2, 136", 136 1/2, 137", 137 1/2, 138", 138 1/2, 139", 139 1/2, 140", 140 1/2, 141", 141 1/2, 142", 142 1/2, 143", 143 1/2, 144", 144 1/2, 145", 145 1/2, 146", 146 1/2, 147", 147 1/2, 148", 148 1/2, 149", 149 1/2, 150", 150 1/2, 151", 151 1/2, 152", 152 1/2, 153", 153 1/2, 154", 154 1/2, 155", 155 1/2, 156", 156 1/2, 157", 157 1/2, 158", 158 1/2, 159", 159 1/2, 160", 160 1/2, 161", 161 1/2, 162", 162 1/2, 163", 163 1/2, 164", 164 1/2, 165", 165 1/2, 166", 166 1/2, 167", 167 1/2, 168", 168 1/2, 169", 169 1/2, 170", 170 1/2, 171", 171 1/2, 172", 172 1/2, 173", 173 1/2, 174", 174 1/2, 175", 175 1/2, 176", 176 1/2, 177", 177 1/2, 178", 178 1/2, 179", 179 1/2, 180", 180 1/2, 181", 181 1/2, 182", 182 1/2, 183", 183 1/2, 184", 184 1/2, 185", 185 1/2, 186", 186 1/2, 187", 187 1/2, 188", 188 1/2, 189", 189 1/2, 190", 190 1/2, 191", 191 1/2, 192", 192 1/2, 193", 193 1/2, 194", 194 1/2, 195", 195 1/2, 196", 196 1/2, 197", 197 1/2, 198", 198 1/2, 199", 199 1/2, 200", 200 1/2, 201", 201 1/2, 202", 202 1/2, 203", 203 1/2, 204", 204 1/2, 205", 205 1/2, 206", 206 1/2, 207", 207 1/2, 208", 208 1/2, 209", 209 1/2, 210", 210 1/2, 211", 211 1/2, 212", 212 1/2, 213", 213 1/2, 214", 214 1/2, 215", 215 1/2, 216", 216 1/2, 217", 217 1/2, 218", 218 1/2, 219", 219 1/2, 220", 220 1/2, 221", 221 1/2, 222", 222 1/2, 223", 223 1/2, 224", 224 1/2, 225", 225 1/2, 226", 226 1/2, 227", 227 1/2, 228", 228 1/2, 229", 229 1/2, 230", 230 1/2, 231", 231 1/2, 232", 232 1/2, 233", 233 1/2, 234", 234 1/2, 235", 235 1/2, 236", 236 1/2, 237", 237 1/2, 238", 238 1/2, 239", 239 1/2, 240", 240 1/2, 241", 241 1/2, 242", 242 1/2, 243", 243 1/2, 244", 244 1/2, 245", 245 1/2, 246", 246 1/2, 247", 247 1/2, 248", 248 1/2, 249", 249 1/2, 250", 250 1/2, 251", 251 1/2, 252", 252 1/2, 253", 253 1/2, 254", 254 1/2, 255", 255 1/2, 256", 256 1/2, 257", 257 1/2, 258", 258 1/2, 259", 259 1/2, 260", 260 1/2, 261", 261 1/2, 262", 262 1/2, 263", 263 1/2, 264", 264 1/2, 265", 265 1/2, 266", 266 1/2, 267", 267 1/2, 268", 268 1/2, 269", 269 1/2, 270", 270 1/2, 271", 271 1/2, 272", 272 1/2, 273", 273 1/2, 274", 274 1/2, 275", 275 1/2, 276", 276 1/2, 277", 277 1/2, 278", 278 1/2, 279", 279 1/2, 280", 280 1/2, 281", 281 1/2, 282", 282 1/2, 283", 283 1/2, 284", 284 1/2, 285", 285 1/2, 286", 286 1/2, 287", 287 1/2, 288", 288 1/2, 289", 289 1/2, 290", 290 1/2, 291", 291 1/2, 292", 292 1/2, 293", 293 1/2, 294", 294 1/2, 295", 295 1/2, 296", 296 1/2, 297", 297 1/2, 298", 298 1/2, 299", 299 1/2, 300", 300 1/2, 301", 301 1/2, 302", 302 1/2, 303", 303 1/2, 304", 304 1/2, 305", 305 1/2, 306", 306 1/2, 307", 307 1/2, 308", 308 1/2, 309", 309 1/2, 310", 310 1/2, 311", 311 1/2, 312", 312 1/2, 313", 313 1/2, 314", 314 1/2, 315", 315 1/2, 316", 316 1/2, 317", 317 1/2, 318", 318 1/2, 319", 319 1/2, 320", 320 1/2, 321", 321 1/2, 322", 322 1/2, 323", 323 1/2, 324", 324 1/2, 325", 325 1/2, 326", 326 1/2, 327", 327 1/2, 328", 328 1/2, 329", 329 1/2, 330", 330 1/2, 331", 331 1/2, 332", 332 1/2, 333", 333 1/2, 334", 334 1/2, 335", 335 1/2, 336", 336 1/2, 337", 337 1/2, 338", 338 1/2, 339", 339 1/2, 340", 340 1/2, 341", 341 1/2, 342", 342 1/2, 343", 343 1/2, 344", 344 1/2, 345", 345 1/2, 346", 346 1/2, 347", 347 1/2, 348", 348 1/2, 349", 349 1/2, 350", 350 1/2, 351", 351 1/2, 352", 352 1/2, 353", 353 1/2, 354", 354 1/2, 355", 355 1/2, 356", 356 1/2, 357", 357 1/2, 358", 358 1/2, 359", 359 1/2, 360", 360 1/2, 361", 361 1/2, 362", 362 1/2, 363", 363 1/2, 364", 364 1/2, 365", 365 1/2, 366", 366 1/2, 367", 367 1/2, 368", 368 1/2, 369", 369 1/2, 370", 370 1/2, 371", 371 1/2, 372", 372 1/2, 373", 373 1/2, 374", 374 1/2, 375", 375 1/2, 376", 376 1/2, 377", 377 1/2, 378", 378 1/2, 379", 379 1/2, 380", 380 1/2, 381", 381 1/2, 382", 382 1/2, 383", 383 1/2, 384", 384 1/2, 385", 385 1/2, 386", 386 1/2, 387", 387 1/2, 388", 388 1/2, 389", 389 1/2, 390", 390 1/2, 391", 391 1/2, 392", 392 1/2, 393", 393 1/2, 394", 394 1/2, 395", 395 1/2, 396", 396 1/2, 397", 397 1/2, 398", 398 1/2, 399", 399 1/2, 400", 400 1/2, 401", 401 1/2, 402", 402 1/2, 403", 403 1/2, 404", 404 1/2, 405", 405 1/2, 406", 406 1/2, 407", 407 1/2, 408", 408 1/2, 409", 409 1/2, 410", 410 1/2, 411", 411 1/2, 412", 412 1/2, 413", 413 1/2, 414", 414 1/2, 415", 415 1/2, 416", 416 1/2, 417", 417 1/2, 418", 418 1/2, 419", 419 1/2, 420", 420 1/2, 421", 421 1/2, 422", 422 1/2, 423", 423 1/2, 424", 424 1/2, 425", 425 1/2, 426", 426 1/2, 427", 427 1/2, 428", 428 1/2, 429", 429 1/2, 430", 430 1/2, 431", 431 1/2, 432", 432 1/2, 433", 433 1/2, 434", 434 1/2, 435", 435 1/2, 436", 436 1/2, 437", 437 1/2, 438", 438 1/2, 439", 439 1/2, 440", 440 1/2, 441", 441 1/2, 442", 442 1/2, 443", 443 1/2, 444", 444 1/2, 445", 445 1/2, 446", 446 1/2, 447", 447 1/2, 448", 448 1/2, 449", 449 1/2, 450", 450 1/2, 451", 451 1/2, 452", 452 1/2, 453", 453 1/2, 454", 454 1/2, 455", 455 1/2, 456", 456 1/2, 457", 457 1/2, 458", 458 1/2, 459", 459 1/2, 460", 460 1/2, 461", 461 1/2, 462", 462 1/2, 463", 463 1/2, 464", 464 1/2, 465", 465 1/2, 466", 466 1/2, 467", 467 1/2, 468", 468 1/2, 469", 469 1/2, 470", 470 1/2, 471", 471 1/2, 472", 472 1/2, 473", 473 1/2, 474", 474 1/2, 475", 475 1/2, 476", 476 1/2, 477", 477 1/2, 478", 478 1/2, 479", 479 1/2, 480", 480 1/2, 481", 481 1/2, 482", 482 1/2, 483", 483 1/2, 484", 484 1/2, 485", 485 1/2, 486", 486 1/2, 487", 487 1/2, 488", 488 1/2, 489", 489 1/2, 490", 490 1/2, 491", 491 1/2, 492", 492 1/2, 493", 493 1/2, 494", 494 1/2, 495", 495 1/2, 496", 496 1/2, 497", 497 1/2, 498", 498 1/2, 499", 499 1/2, 500", 500 1/2, 501", 501 1/2, 502", 502 1/2, 503", 503 1/2, 504", 504 1/2, 505", 505 1/2, 506", 506 1/2, 507", 507 1/2, 508", 508 1/2, 509", 509 1/2, 510", 510 1/2, 511", 511 1/2, 512", 512 1/2, 513", 513 1/2, 514", 514 1/2, 515", 515 1/2, 516", 516 1/2, 517", 517 1/2, 518", 518 1/2, 519", 519 1/2, 520", 520 1/2, 521", 521 1/2, 522", 522 1/2, 523", 523 1/2, 524", 524 1/2, 525", 525 1/2, 526", 526 1/2, 527", 527 1/2, 528", 528 1/2, 529", 529 1/2, 530", 530 1/2, 531", 531 1/2, 532", 532 1/2, 533", 533 1/2, 534", 534 1/2, 535", 535 1/2, 536", 536 1/2, 537", 537 1/2, 538", 538 1/2, 539", 539 1/2, 540", 540 1/2, 541", 541 1/2, 542", 542 1/2, 543", 543 1/2, 544", 544 1/2, 545", 545 1/2, 546", 546 1/2, 547", 547 1/2, 548", 548 1/2, 549", 549 1/2, 550", 550 1/2, 551", 551 1/2, 552", 552 1/2, 553", 553 1/2, 554", 554 1/2, 555", 555 1/2, 556", 556 1/2, 557", 557 1/2, 558", 558 1/2, 559", 559 1/2, 560", 560 1/2, 561", 561 1/2, 562", 562 1/2, 563", 563 1/2, 564", 564 1/2, 565", 565 1/2, 566", 566 1/2, 567", 567 1/2, 568", 568 1/2, 569", 569 1/2, 570", 570 1/2, 571", 571 1/2, 572", 572 1/2, 573", 573 1/2, 574", 574 1/2, 575", 575 1/2, 576", 576 1/2, 577", 577 1/2, 578", 578 1/2, 579", 579 1/2, 580", 580 1/2, 581", 581 1/2, 582", 582 1/2, 583", 583 1/2, 584", 584 1/2, 585", 585 1/2, 586", 586 1/2, 587", 587 1/2, 588", 588 1/2, 589", 589 1/2, 590", 590 1/2, 591", 591 1/2, 592", 592 1/2, 593", 593 1/2, 594", 594 1/2, 595", 595 1/2, 596", 596 1/2, 597", 597 1/2, 598", 598 1/2, 599", 599 1/2, 600", 600 1/2, 601", 601 1/2, 602", 602 1/2, 603", 603 1/2, 604", 604 1/2, 605", 605 1/2, 606", 606 1/2, 607", 607 1/2, 608", 608 1/2, 609", 609 1/2, 610", 610 1/2, 611", 611 1/2, 612", 612 1/2, 613", 613 1/2, 614", 614 1/2, 615", 615 1/2, 616", 616 1/2, 617", 617 1/2, 618", 618 1/2, 619", 619 1/2, 620", 620 1/2, 621", 621 1/2, 622", 622 1/2, 623", 623 1/2, 624", 624 1/2, 625", 625 1/2, 626", 626 1/2, 627", 627 1/2, 628", 628 1/2, 629", 629 1/2, 630", 630 1/2, 631", 631 1/2, 632", 632 1/2, 633", 633 1/2, 634", 634 1/2, 635", 635 1/2, 636", 636 1/2, 637", 637 1/2, 638", 638 1/2, 639", 639 1/2, 640", 640 1/2, 641", 641 1/2, 642", 642 1/2, 643", 643 1/2, 644", 644 1/2, 645", 645 1/2, 646", 646 1/2, 647", 647 1/2, 648", 648 1/2, 649", 649 1/2, 650", 650 1/2, 651", 651 1/2, 652", 652 1/2, 653", 653 1/2, 654", 654 1/2, 655", 655 1/2, 656", 656 1/2, 657", 657 1/2, 658", 658 1/2, 659", 659 1/2, 660", 660 1/2, 661", 661 1/2, 662", 662 1/2, 663", 663 1/2, 664", 664 1/2, 665", 665 1/2, 666", 666 1/2, 667", 667 1/2, 668", 668 1/2, 669", 669 1/2, 670", 670 1/2, 671", 671 1/2, 672", 672 1/2, 673", 673 1/2, 674", 674 1/2, 675", 675 1/2, 676", 676 1/2, 677", 677 1/2, 678", 678 1/2, 679", 679 1/2, 680", 680 1/2, 681", 681 1/2, 682", 682 1/2, 683", 683 1/2, 684", 684 1/2, 685", 685 1/2, 686", 686 1/2, 687", 687 1/2, 688", 688 1/2, 689", 689 1/2, 690", 690 1/2, 691", 691 1/2, 692", 692 1/2, 693", 693 1/2, 694", 694 1/2, 695", 695 1/2, 696", 696 1/2, 697", 697 1/2, 698", 698 1/2, 699", 699 1/2, 700", 700 1/2, 701", 701 1/2, 702", 702 1/2, 703", 703 1/2, 704", 704 1/2, 705", 705 1/2, 706", 706 1/2, 707", 707 1/2, 708", 708 1/2, 709", 709 1/2, 710", 710 1/2, 711", 711 1/2, 712", 712 1/2, 713", 713 1/2, 714", 714 1/2, 715", 715 1/2, 716", 716 1/2, 717", 717 1/2, 718", 718 1/2, 719", 719 1/2, 720", 720 1/2, 721", 721 1/2, 722", 722 1/2, 723", 723 1/2, 724", 724 1/2, 725", 725 1/2, 726", 726 1/2, 727", 727 1/2, 728", 728 1/2, 729", 729 1/2, 730", 730 1/2, 731", 731 1/2, 732", 732 1/2, 733", 733 1/2, 734", 734 1/2, 735", 735 1/2, 736", 736 1/2, 737", 737 1/2, 738", 738 1/2, 739", 739 1/2, 740", 740 1/2, 741", 741 1/2, 742", 742 1/2, 743", 743 1/2, 744", 744 1/2, 745", 745 1/2, 746", 746 1/2, 747", 747 1/2, 748", 748 1/2, 749", 749 1/2, 750", 750 1/2, 751", 751 1/2, 752", 752 1/2, 753", 753 1/2, 754", 754 1/2, 755", 755 1/2, 756", 756 1/2, 757", 757 1/2, 758", 758 1/2, 759", 759 1/2, 760", 760 1/2, 761", 761 1/2, 762", 762 1/2, 763", 763 1/2, 764", 764 1/2, 765", 765 1/2, 766", 766 1/2, 767", 767 1/2, 768", 768 1/2, 769", 769 1/2, 770", 770 1/2, 771", 771 1/2, 772", 772 1/2, 773", 773 1/2, 774", 774 1/2, 775", 775 1/2, 776", 776 1/2, 777", 777 1/2, 778", 778 1/2, 779", 779 1/2, 780", 780 1/2, 781", 781 1/2, 782", 782 1/2, 783", 783 1/2, 784", 784 1/2, 785", 785 1/2, 786", 786 1/2, 787", 787 1/2, 788", 788 1/2, 789", 789 1/2, 790", 790 1/2, 791", 791 1/2, 792", 792 1/2, 793", 793 1/2, 794", 794 1/2, 795", 795 1/2, 796", 796 1/2, 797", 797 1/2, 798", 798 1/2, 799", 799 1/2, 800", 800 1/2, 801", 801 1/2, 802", 802 1/2, 803", 803 1/2, 804", 804 1/2, 805", 805 1/2, 806", 806 1/2, 807", 807 1/2, 808", 808 1/2, 809", 809 1/2, 810", 810 1/2, 811", 811 1/2, 812", 812 1/2, 813", 813 1/2, 814", 814 1/2, 815", 815 1/2, 816", 816 1/2, 817", 817 1/2, 818", 818 1/2, 819", 819 1/2, 820", 820 1/2, 821", 821 1/2, 822", 822 1/2, 823", 823 1/2, 824", 824 1/2, 825", 825 1/2, 826", 826 1/2, 827", 827 1/2, 828", 828 1/2, 829", 829 1/2, 830", 830 1/2, 831", 831 1/2, 832", 832 1/2, 833", 833 1/2, 834", 834 1/2, 835", 835 1/2, 836", 836 1/2, 837", 837 1/2, 838", 838 1/2, 839", 839 1/2, 840", 840 1/2, 841", 841 1/2, 842", 842 1/2, 843", 843 1/2, 844", 844 1/2, 845", 845 1/2, 846", 846 1/2, 847", 847 1/2, 848", 848 1/2, 849", 849 1/2, 850", 850 1/2, 851", 851 1/2, 852", 852 1/2, 853", 853 1/2, 8

Tools and Tool Boxes

MECHANICS' FOUR TRAY CANTILEVER TOOL BOX

- Full Size Storage Compartment — PLUS — Four Easy-Glide Cantilever Trays



9⁹⁵

Professional quality tool box. Ideal for machinists, electronics and automotive repairmen. Double cover swings out for easy access to each compartment. Bottom compartment large enough to store bulky tools. Extra-heavy gauge steel. Heavy-duty round handles and padlock eyes for locking. Handsome baked blue enamel finish. Overall size: 17" Lx8"Wx8 1/4"H. Shpg. wt., 16 lbs.

13 R 56104W

Net 9.95

HEAVY DUTY MACHINIST'S CHESTS

- Electrically Welded Heavy Duty Steel
- Ten Felt-Lined Drawers
- Pin-Tumbler Chest Lock



10 Drawer Machinist Chest with 10 felt lined drawers for storage and protection of tools. Rugged construction with integral full length hinges, and full suspension drawer slides for full extension of each drawer. Removable front panel locks when cover is closed and stores below drawers in a fitted compartment when open. Overall size: 8 1/2x17 1/2x20" Tilt in top 8 1/2x4x20". 6 drawers 7 1/2x1x8 3/8". Others 7 1/2x2x8 3/8", 7 1/2x1 1/2x18 1/4", 7 1/2x2 3/4x18 1/4", 7 1/2x3x18 1/4".

13 R 19540W No Money Down* Shpg. wt., 36 1/4 lbs. Net 41.95

HIP-ROOF TOOL BOX

With Lift-Out Tray

4⁹⁵

Long lasting, electrically welded heavy gauge steel construction with full-length hinge. Perfect for the home-owner, mechanic, or handyman. Plated handle will not break or pull out. Lift-out tray for smaller tools. Large storage area for bigger tools. 19Lx7Wx7 1/4"D. Shpg. wt., 6 1/2 lbs.

13 R 42500W

Net 4.95




STEEL TOOL AND UTILITY BOX

13 1/2" long tool box. Cantilever tray with four compartments. Room enough for soldering iron, pliers, screw drivers, wrenches, etc. Pushbutton catch with hasp for lock. Full grip handle. Baked enamel in glossy finish. 13 1/2 Lx 6 1/2 W x 5" D. Shpg. wt., 4 lbs.

14 R 86067

Net 2.95




MINIATURE IMPROVED HOIST

- 2000 lb. Capacity

Simple, reliable hoist enables you to lift as much as 2000 lbs., yet weighs only 1 1/2 lbs.! Ideal for hunters to hoist heavy game for cleaning, or boat owners to mount outboard engines with ease; can also be used to stretch a chain link fence. Has rust resistant cadmium plated housings, heavy duty welded ring, double grip safety hooks, nylon rollers, and locking device to eliminate slack. Includes high tensile-strength 65' nylon rope for long life. Shpg. wt., 2 lbs.

13 R 19060

Net 5.95



5⁹⁵

BADGER HOBBY & TOUCH-UP AIR BRUSH KIT

- Complete with Air Brush, Vinyl Hose, Air Valve, Mixing Jar, Thinner, 4 Jars Paint, and Instructions

7⁹⁵



One of the handiest tools for the handyman, craftsman, hobbyist, and homemaker. For professional refinishing or invisible touch-up on appliances, furniture, boats, cars, etc. Easy to use, air brush features high impact Delrin body, adjustable paint tip for fine or heavy spray, 15 oz. aerosol power pack with vinyl hose and on-off air valve, metal controls. Comes with 4 Jars of paint—RED, YELLOW, BLUE, BLACK. Easy-to-follow instructions.

13 R 45537 Shpg. wt., 3 lbs.

Net 7.95

REPLACEMENT POWER PACK

13 R 45529 Shpg. wt., 1 1/2 lbs.

Net 1.69

3 DRAWER TOOL CHEST

Only 16⁹⁵

An all purpose ruggedly constructed 3 drawer carrying type chest. Drawers have full suspension slides. Drawers may be locked in place even if cover is closed. Features electrically welded heavy gauge steel and baked enamel silicone treated finish. Dimensions: Box 8 1/2"Dx10 1/4"Hx20" long; 3 drawers — 7 1/2"Dx1 1/2"Hx18 1/4"L.

13 R 19508W Shpg. wt., 28 lbs.


Net 16.95



11 PIECE COMBINATION WRENCH SET

10⁹⁵

- Full Professional Size
- Handy Vinyl Roll-Up Kit



11 Piece Combination Box and Open End Wrench Kit. Drop forged alloy steel with bright chrome plated finish. Sizes: 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1 1/8", 1 1/4", 1 1/2", 1 3/4", 2", and 2 1/4". Length of wrenches 6" to 13" long. Imported. Shpg. wt., 5 3/4 lbs.

13 R 56130

Net 10.95

14 Piece Wrench Set similar to above plus addition of 1 1/2", 1 3/4", and 1 1/2" length of wrenches 6" to 16 1/2" long. Shpg. wt., 11 lbs.


13 R 56245

Net 19.95

ADJUSTABLE END WRENCHES

Fully Drop Forged

AS LOW AS



1⁷⁹

Adjusts jaws with a flick of your thumb... oversized knurl speeds opening and closing. Entire wrench is made of drop forged steel and fully polished. This head gets into tight places easily. Extra long for better leverage.

Stock No.	Size	Max. Jaw Open.	Shpg. Wt.	Net
13 R 55668	6"	3/4"	8 oz.	1.79
13 R 55676	8"	1"	11 oz.	2.39
13 R 55684	10"	1 1/8"	1 lb.	3.19
13 R 55692	12"	1 3/8"	1 3/4 lbs.	3.95

Work Benches • Shelves • Insect Killer

Hirsch STEEL STORAGE SHELVES

- Combines Strength and Beauty
- Unlimited Arrangements For All Storage Needs



Here's the bright, modern look in steel storage shelving ideal for offices, garages, stores—anyplace where both strength and beauty dictate your storage needs. New exclusive keyhole shelf clip is an easier and quicker method of shelf attachment. Split posts permit alternate arrangements of a single unit and an unlimited number of multiple unit arrangements to meet every storage and space requirement. Textured silver shelf finish resists flaking, peeling, rusting; grey posts.

- 4 shelf Unit: 60" Hx30" Wx12" D.
Shpg. wt., 14 lbs.
13 R 18567W Net 6.95
- 5 shelf Unit: 72" Hx36" Wx12" D.
Shpg. wt., 23 lbs.
13 R 18575W Net 9.95
- 6 shelf Unit: 72" Hx36" Wx18" D.
Shpg. wt., 36 lbs.
13 R 18583W Net 12.95

12V. AIR PUMP AND EXHAUSTER

- Plugs Into Cigarette Lighter Receptacle
- Inflates And Deflates Objects Effortlessly

This powerful and compact rotary air compressor is sure to be one of the handiest devices you'll ever own!! No more "huffing and puffing" the next time you wish to inflate air mattresses, pools, toys, blow-up furniture, etc. Deflating is just as easy: your compressor will exhaust all the air making the folding and storage of your inflatable items a cinch! With nozzle and 10' cord, 2.7 psi air pressure. 12V DC. Imported. Shpg. wt., 1 lb.

13 R 52004 Net 6.95



POWER MAGNET


Made of Alcomax—a material with 12 times the magnetic energy of tungsten steel. Designed for efficient performance/weight ratio—will lift up to 50 times its own weight. Horseshoe shape with plated keeper. Ideal for such applications as magnetic clutch, work holding, etc. Size 1½" Hx1½" Dx1¾" W. Distance between poles is ¾". Imported from England.

14 R 33028 Shpg. wt., ¾ lb. Net 3.29

A special "Alnico" button carefully designed to produce a highly efficient magnetic field. Attachable to any non-ferrous material by non-magnetic screws. Ideal for use most everywhere as magnetic fasteners. Supplied with plated keeper, imported from England. Avg. shpg. wt., 4 oz.



BUTTON MAGNETS



STOCK NO.	HEIGHT	DIA.	HOLE DIA.	MTG. EA.	NET
14 R 33093	¾"	1½"	1¼"	.69	
14 R 33101	½"	¾"	¾"	.99	
14 R 33119	5/8"	1"	¾"	1.49	

POW-O-MATIC STEEL TAPE

- Push Button ¾ In. x 12 Ft.



Power push-button 12' yellow steel measuring tape. Easy to read, red and black, Ft. and inch markings, ¼" and ½" graduations, with zip belt clip

14 R 16056 Shpg. wt., 1 lb. Net 2.79

STEEL FRAME WORK BENCH




19⁹⁵

Includes Tool Rack, Peg Board Back Panel and Bottom Shelf

A new all-steel frame work bench that is the ultimate in convenience and serviceability. The rigid, all steel frame is the core of this complete workshop that will last for years. Features a big 24x48" work top of special, heavy-duty, compressed high-impact board to withstand the roughest use. Matching bottom shelf offers handy storage space. Convenient tool rack with peg board back panel. Base on each leg gives extra support and can be bolted down if desired. Easy-to-assemble 34½" high. (Tools not included.) Shpg. wt., 54½ lbs.

13 R 35041WX Net 19.95

ALL-PURPOSE BENCH FRAME



It's easy to make a bench for every purpose—in the garage, store, house, laundry room, playroom, etc. Heavy gauge steel, completely pre-drilled, ready-to-assemble—just add the top. For larger benches, combine 2 or more. Overall: 22½x47½x34" high. Shpg. wt., 19 lbs.

13 R 35017W Net 5.95
TOOL RACK. Prepunched to fit frame. 46" L. 4½" H.
13 R 35025W Shpg. wt., 3 lbs. Net 2.29

"ADD-A-DRAWER"

In only seconds you get a permanent drawer under any flat surface—table, bench, cabinet, shelf, desk, etc. Completely assembled—comes with 2 brackets and 4 screws for easy installation. All-steel drawer with handy knob. Gray—can be repainted any color of your choice. Drawer size: 12 x 12 x 3¼". Shpg. wd., 3½ lbs.



13 R 36023 Net 3.95

ELECTRONIC INSECT KILLER

- Easy To Use Just Plug In
- Ideal For Patios
- No Chemicals—No Sprays—No Fumes



Only
3⁹⁵

An efficient, economical and safe insect control system with INSECT-O-MATIC™ electronic bug killer. Helps kill gnats, mosquitoes, moths, bees, and flies in your home, porch, garden, or pool area without the use of messy insecticides. Completely electronic system produces no disagreeable odors or harmful fumes. Operates indoors or out for pennies a day. Attractive white and black finish. Size: 10½" Hx4¾" Wx4½" D. For 117 VAC 60 Hz. Shpg. wt., 2 lbs.

14 R 21130 Net 3.95
Replacement bulb for above (pk. of 2) wt., 6 oz.
14 R 21122 Net 1.99

SELF LOCKING HASP-LOC

2⁹⁵



Self contained, no need to purchase a separate padlock. No keys required to lock; keys used for opening only. Heavy duty and rust proof. Size 4½" with 2 keys.

13 R 75054 Shpg. wt., 1 lb. Net 2.95

Lafayette Cat. No. 720 367

(A) POP RIVET TOOL KIT

Rivet metal to metal, plastic to wood, fabric to fabric. Easy to operate, just insert rivet into tool, place in pre-drilled hole and squeeze—you have a strong rivet joint. Ideal for hobbyists, electronics, household and auto repairs. Kit includes riveter, and supply of rivets of various sizes. Uses ¼" rivets. Shpg. wt., 1½ lbs.

13 R 54018 Net 2.95

(B) DUAL RIVET TOOL KIT

Contains the new "Pop" rivet tool with two interchangeable nosepieces to set ½" steel and aluminum and ¾" aluminum "Pop" rivets. Includes ¼" and ¾" rivets in assorted lengths, and backup plates. Shpg. wt., 1½ lbs.

13 R 54083 Net 4.95

RIVETS FOR ABOVE KITS

¾" Rivets Steel Av. Shpg. wt., 4 oz.

Stock No.	Qty.	Work Thickness	Net
13 R 54026	25	3/8"	.49
13 R 54034	20	¼"	.49
13 R 54042	15	½"	.49

Stock No.	Qty.	Work Thickness	Net
13 R 54091	15	¼"	.49
13 R 54109	12	½"	.49
13 R 54117	10	5/8"	.49

Stock No.	Qty.	Rivet Size	Net
13 R 54059	40	1/8"	.49
13 R 54125	30	3/16"	.49

Prices and Specifications are Subject to Change Without Notice

Sprayers for Handyman-Professional-Hobbyist

SPRAYIT 120 HANDYMAN SPRAYER



29⁹⁵

- Convenient Self-Contained Sprayer
- Sprays Oils, Paints, Insecticides, Liquid Wax
- Designed for Home Owner or Hobbyist

This economy priced portable sprayer is one of the most convenient self-contained sprayers built. It combines portability with high performance, making it perfect for spraying fences, screens, furniture, insecticides etc. It features an oil-less heavy duty diaphragm type compressor. A lightweight constant air flow pressure-feed gun gives excellent results with all sprayable materials. Includes 8 ft. rubber air hose and 6' electric cord. For 117V AC. Shpg. wt., 10½ lbs. 14 R 84153W Net 29.95

HEAVY DUTY TYPE SPRAYER



39⁹⁵

- Sprays Oils, Paints, Insecticides, Liquid Wax
- Quiet-running diaphragm type compressor
- 1 qt. aluminum canister

Economy priced portable sprayer designed for the homeowner and hobbyist. Precision engineered throughout to give professional results. Compact, lightweight, versatile... perfect for those dozens of small jobs around the house, wherever and whenever spraying is needed. The spray gun easily handles paint and other types of sprayable material. Sprayer unit features an internal mix spray gun, adjustable spray pattern, quart aluminum canister with a delrin thread insert to prevent fouling and 8' air hose. Easy to operate. Just plug in any 115 v. outlet. Develops maximum pressure of 40 psi. 7 ft. power cord. Shpg. wt., 13¼ lbs. 14 R 67539 No Money Down* Net 39.95

SPRAYIT. PRESSURE FLOW PAINT ROLLER KIT

- No Dip—No Drip—Feed Paint Directly From Can to Roller



Saves time and steps. Boils to any standard 1 gallon can. Has 15 ft. supply hose for easy reach. Use with compressors above or any compressor with range from .65 cfm at 20 psi to 3 cfm at 40 psi. Shpg. wt., 8¼ lbs.


- 14 R 84096 Net 23.95
- ¾" Hi-Pile Roller for rough surfaces. 14 R 84104 Shpg. wt., 5 oz. Net 3.79
- ¾" Pile Roller for smooth surfaces. 14 R 84112 Shpg. wt., 5 oz. Net 2.75

Only 23⁹⁵

PORTABLE ELECTRIC SPRAYERS-COMPRESSORS

MAXIMUM 100 PSI

- Tire Inflation
- Spray Painting
- Operating Air Tools, etc.



1/2 H.P.
119⁹⁵

3/4 H.P.
139⁹⁵

1 H.P.
199⁹⁵

SHIPPED PREPAID FROM FACTORY WITHIN CONTINENTAL UNITED STATES—NO C.O.D. SEND FULL REMITTANCE OR USE LAFAYETTE'S EASY PAY PLAN *

1/2 H.P. SINGLE CYLINDER—Displaces 3.2 CFM

All purpose ½ H.P. portable electric sprayer for use in your home, garden, workshop or garage. Great for spraying paint, insecticides, moth proofing, and fumigating as well as painting. Cylinder has 2¾" bore x 1½" stroke, aluminum head, Swedish steel valves and Torrington needle roller bearings. Delivers 2.0 CFM at 40 PSI and 1.4 CFM at 100 PSI. Automatic pressure switch charges the 12 gallon reserve tank at 70 PSI and turns off at 100 PSI. Lightweight aluminum 1 quart pistol grip spray gun has adjustable spray controls and regulator with gauge. Other features include: safety valve, reserve gauge, shut-off. Fan type flywheel, 15" hose assembly and 8" wheels for easy mobility. For 117 VAC 60 Hz. Shpg. wt., 95 lbs. 14 R 67505WXZ No Money Down* Net 119.95

3/4 H.P. SINGLE CYLINDER—Displaces 3.7 CFM

Similar to above but with increased air delivery (2.4 CFM at 40 PSI, 1.7 CFM at 100 PSI) and 15 gallon reserve tank. Shpg. wt., 97 lbs. 14 R 67513WXZ No Money Down* Net 139.95

1 H.P. TWO CYLINDER—Displaces 8.2 CFM

Similar to above but with larger 2" stroke for more air (6.1 CFM at 40 PSI, 5.1 CFM at 100 PSI), 15 gallon reserve tank for reduced air supply pulsation and bigger 10" wheels for greater mobility over lawns as well as indoors. Reserve tank pressure adjusted to 80 PSI compressor restart. Shpg. wt., 165 lbs. 14 R 67521WXZ No Money Down* Net 199.95

"spray-all" ELECTRIC SPRAYER

- 5 Position Nozzle Adjustment
- Includes Viscosimeter-Strainer

11⁹⁵



All purpose spray-gun for auto touch-up and refinishing, outdoor and household furniture, shutters, walls, siding, fences, etc. For use with water-base paints, enamels, acrylics, lacquers, and varnishes as well as spray insecticides for mothproofing. "Sprayall" comes in shatter-proof polypropylene housing with unbreakable graduated 28 oz. jar plus genuine sapphire jeweled nozzle and 5-position spray control lever for adjustment to any job. For 117V AC. Shpg. wt., 2 lbs. 12 R 43518 Net 11.95

PORTABLE POWER GENERATOR WITH PERMANENT MAGNET ALTERNATOR

- Produces 115 Volts AC
- 3 H.P. Lauson Engine
- Choice of 1000 Watt or 1250 Watt Models —Continuous Duty



as low as **229⁹⁵**
No Money Down*

A compact, portable electric power plant for on-the-spot electricity anytime, anywhere. Features a permanent magnet alternator that gives you more power and trouble-free operation — no brushes, armature windings, belts, slip rings or commutators. Dependable Lauson 3 H.P., 4 cycle engine gives easy-to-start, long-life service hour after hour. 1 1/2

qt. capacity fuel-tank. Standard equipment includes: visual fuel gauge, visual oil level indicator, Duplex receptacle, rubber shock absorbing feet, recoil starter and carrying handle. Portable. Compact. 115 VAC.

Stock No.	Continuous Duty	Shpg. wt.	Net
13 R 49018WX	1000 Watts	63 1/2 lbs.	229.95
13 R 49026WX	1250 Watts	69 lbs.	244.95

SUBMERSIBLE POW-R-PAK PUMPS



- Corrosion Resistant
- Hermetically Sealed Motor
- For Circulating And Dispensing Water

All-new Pow-R-Pak trouble free pumps for underwater use. Circulates and dispenses water and mild acid solutions for fountains, beverage dispensers, aquariums, photo developing, air conditioning, etc. Permalubed. Corrosion resistant stainless steel and plastic unit. Overload protection, threaded inlet and outlet. Outlet: E-200 has 1/4" std. pipe thread, E-400, 700 has 3/8" std. pipe thread. Comes with 6 ft. cord. For 110 Volts, 60 Hz. AC. Average size: 2 1/2x4x4".

Gals. per Hr. At

Stock No.	Model	Max. Hl. Amps.				Shpg. Lbs.	Net
		1 Ft.	3 Ft.	6 Ft.	Hi.		
13 R 89048	E-200	220	155	80	7.40	3	11.95
13 R 89055	E-400	400	320	220	11.91	4 1/2	15.95
13 R 89063	E-700	700	540	430	13.19	5	25.95



44⁹⁵
No Money Down*

1300 GPH SUBMERSIBLE PUMP

- Standard Hose Connection Outlet
- Operates at Depths up to 40 ft.
- Double Epoxy Coating—Will not Corrode

Heavy-duty sump pump or basement baller. Has long life carbon ceramic seal, thermo-overload protection, and leaf strainer. Standard garden hose outlet. 3/4" std. pipe thread inlet. Ideal for many underwater applications, such as in pools, fountains, etc. Pumps gallons per hour: 1300 @ 2 ft., 1030 @ 5 ft., 810 @ 10 ft., 600 @ 15 ft., 300 @ 25 ft. Shut off @ 40 ft. 4.5 amps load. 4 3/4"Hx7"D. 110V 60 cy. AC. With cord, Shpg. wt., 5 1/4 lbs.

13 R 89030 Net 44.95

MINIATURE PUMP AND MOTOR

- Powerful—Raises Liquid up to 12 Feet
- High Capacity—1 1/2 Gallons per Minute
- Waterproof, Lightweight Construction
- Industrial Quality

4⁴⁹



A motorized, miniature pump for the hobbyist and "Do-It-Yourselfer." Pumps liquids from container to container at the rate of up to 1 1/2 gallons per minute and raises liquids up to 12 feet. Ideal for fountains, water house plants, aquariums, science projects, waterfalls, etc. Pumps water, chemicals, viscous liquids. Requires just 3 to 12 volts DC. Shpg. wt., 4 oz.

13 R 19037 Net 4.49

*See Page 22 for Full Credit Details on Easy Pay Plan

TINY TIGER "HUSH TONE" PORTABLE GENERATOR

114⁹⁵



- Economical Gas Driven Motor
- 115 A.C. 350 Watts Electric Power 12V D.C. 12 Amps.
- Only 14 lbs.
- Automatic Overload Relief—for Tools, Appliances, Boats
- 12V D.C. for Battery Charging
- 1 H.P. Motor

Model 5001-1—Lightweight, rugged metal construction! Features a 1 hp, 2 cycle Ohlsson & Rice air cooled engine with a high capacity magneto ignition, 6 pint, premixed (2:1 parts gas—1 part oil) fuel capacity allows operation at full power (6,300 rpm) for 2 1/2 hours. Also features built-in quietness with a larger "Hush Tone" spark arrester muffler. Dual voltage, direct drive Tiny Tiger generator produces up to 350 watts of 115V., AC, and 12 amps of 12V., DC simultaneously for charging batteries, for starting cars, boats and trucks. Constant voltage within 110-120 volts with an automatic overload relief system. Light enough to carry anywhere (14 lbs.)... small enough to carry in one hand (8 1/2"H x 8 1/2"W x 10 1/4"L). Shpg. wt., 16 1/2 lbs.

12 R 35522 No Money Down* Net 114.95
HANDY CARRYING CASE

12 R 35514 Shpg. wt., 6 lbs. Net 10.95

Only **13⁹⁵**




12 VOLT DC SUBMERSIBLE PUMP

- Operates In Any Position—Submerged or in Open Air When Primed
- Ideal For Marine Use

Small enough to fit under marine engine stringers and duckboards, recreational vehicles and mobile homes. Pump delivers up to 400 gal./hr. (direct discharge) or pumps to 11' heights. Lifts water more than 6' below when primed. Draws 1.5 amp. at 12 volts. Port Connections: Beige inlet plate and strainer, and 1/2" female pipe threaded inlet plate. Outlet is 3/8" N.P.T. male and will accept 3/8" I.D. hose. Stainless steel shaft and high impact cyolac case. Size: 2 1/4 x 2 1/2 x 5 1/2".

13 R 89071 Shpg. wt., 1 1/4 lbs. Net 13.95



WATERFALL KIT

Enhancing waterfall of cascading water constantly recirculated by electric pump. Gallons per hour delivery: 180 at 1 ft., 140 at 3 ft., 100 at 5 ft., shut off at 10 ft. Outlet 3/4" Inlet 1/2" pipe O.D. Load: 65 amps; 43 watts. No concrete needed; complete with instructions. Kit consists of pump, 8-ft. plastic hose, 7 ft. sealing poly. pump filter. Shpg. wt., 6 1/4 lbs.

13 R 89022 Net 17.95

POWERFUL SELF-PRIMING PUMP

- Easily Connects To Standard Garden Hose



6⁹⁵

WORKS OFF ANY ELECTRIC DRILL

Now you can pump water, lubricants, solutions, and other liquids up to 10 feet vertically or prime a maximum horizontal distance of 50 feet. Compact and economical self priming pump handles up to 200 gallons per hour with 2,000 RPM 1/4" drill at temperatures from 40° to 180° F. Perfect for home, farm, or industry, to pump out basements, fill or empty tanks, or transfer chemical solutions. Lightweight, rugged phenolic plastic construction resists chemical corrosion. Fits electric drills like a "bit" and takes ordinary garden hose. Shpg. wt., 1 lb.

13 R 33756 Net 6.95

Battery Chargers And Booster Chargers



- LAFAYETTE
BOOSTER CHARGER**
- 50 Amp. Battery Boost Power
 - 10 Amp. Battery Charger
 - For 6, 8 or 12 Volts

Only **29⁹⁵**

Starts cars fast in the coldest weather with automatic 50 amp. boost. Perfect for 6, 8, or 12 volt batteries used in trucks, cars, boats, tractors and other vehicles. Operates as a booster and as a 10 amp. charger. Features include: color coded meter indicates battery condition, charging and booster rate, and correct polarity. Full wave charging circuit, triple density selenium rectifiers, isolated and fully impregnated transformer, and an auto-reset circuit breaker; heavy duty 8' input cord, and heavy duty 6' cables with soldered clamps for full output; acid resistant front panel and baked enamel back and sides. All internal components are plated for protection against corrosion. UL listed. Size: 8Hx5³/₄Wx6"0.

11 R 01062 Shpg. wt., 11³/₄ lbs. Net 29.95

SCHAUER

10-AMP BATTERY CHARGER



- For 6 & 12 Volts
- With Meter
- Automatic Circuit Breaker

19⁹⁵

Model C-6612. Heavy-duty 10-amp charger for 6 or 12 volt battery, which will bring the battery to full charge in 2 to 6 hours or less. Equipped with an automatic circuit breaker for overload protection. Selector switch for changing voltage. Accurate ammeter shows rate of charge entering battery. Rugged steel case with gold colored finish and two-tone brushed aluminum. Complete with cables. 117 VAC, 60 Hz. U.L. listed Shpg. wt., 12¹/₂ lbs. 11 R 55191 Net 19.95

SCHAUER

6-AMP BATTERY CHARGER



- Automatic Circuit Breaker
- For 6 & 12 Volts
- Built-in Meter

14⁹⁵

Model B-6612 charges both 6 and 12 volt batteries at a 6-amp rate. Will recharge the average battery in from 3 to 7 hours. Charger is equipped with an automatic circuit breaker for overload protection. Selector switch changes operation from one voltage to another, and an accurate numerical dial ammeter shows the exact rate of charge. Case is of rugged steel. Complete with battery cables 117 VAC, 60 Hz. UL listed. 9³/₈Wx6¹/₂". 11 R 55183 Shpg. wt., 9 lbs. Net 14.95

SURE-FIRE 3-AMP BATTERY CHARGER

10⁹⁵

- For Both 6 & 12 Volts
- Built-in Meter
- Automatic Reset Breaker

Full 3-amp battery charger for quick starts in all weather. Edge view colored meter shows actual battery condition. Reset circuit breaker gives automatic overload protection. Has 6 and 12 volt selector switch. Delivers tapering charge. Vented steel case; may be wall mounted. 6 ft. battery leads with 50 amp clips. Size: 6 x 4¹/₂ x 5³/₄". For operation from 105-125 Volt. 60 Hz AC. UL Listed.

11 R 76049 Shpg. wt., 5 lbs. Net 10.95



- SURE-FIRE
BOOSTER CHARGER**
- 100-Amp. Battery Boost Power 6, 8 or 12-Volts,
 - 10 Amp. Battery Charger
 - Trickle Charger
- As Low As

44⁹⁵ No Money Down*

Model WS-100-10. Get that extra "punch" needed to get your battery started in cold weather!

Provides 100 amp. booster power, 10 amp. and trickle charging for 6, 8 or 12-volt batteries. Ammeter indicates changing current. Features full wave rectifiers, heavy-duty transformers and an automatic reset circuit breaker. Push-button control panel with reverse polarity indicator light is enclosed in a rugged steel case with a baked wrinkle finish. Steel carrying handle also stores the heavy-duty input cord. U.L. Listed. Size: 12x7x9". Shpg. wt., 22³/₄ lbs. 11 R 76098 Net 44.95

Model WS-100-20 similar to above but with extra heavy-duty 200 amp. boost power, 20 amp. charger with trickle charge. For 6, 8 or 12 volts. Size: 12x9x9". Shpg. wt., 32³/₄ lbs. 11 R 76106W No Money Down* Net 64.95

SURE-FIRE 8-AMP AUTOMATIC BATTERY CHARGER WITH 6-HOUR TIMER



- For 6 & 12 Volts
- Colored Meter — Automatic 6-Hour Timer
- Trickle Charge

24⁹⁵

Automatic timer can be set from 5-min. to 6-hrs. After timer shuts-off, charger automatically into a trickle charge cycle which keeps battery fully charged. Uses selenium rectifiers and features automatic circuit breakers. Color meter shows rate of charge. With 6' power cord, 50-amp clips attached to battery cables. 117 VAC. 10x6¹/₂x7¹/₂". UL Listed. Shpg. wt., 11³/₄ lbs. 11 R 76072 Net 24.95

HY-CHARGE® 2-IN-1 BATTERY CHARGER



- For 6 & 12 Volts
- Automatic Circuit Breakers

6⁹⁵

The Hy-charge battery charger keeps all 6 and 12 volt batteries fully charged for peak performance even at 40° below freezing. Full 1 amp. "safe" charge rate prevents flaking and plate buckling. Has automatic circuit breakers to prevent overloading. Easy to use—plug the line cord into any 110V outlet, connect the two terminals to battery. Can't overcharge—automatically tapers off. With handle and wall bracket. Size: 5x3¹/₂x3". Shpg. wt., 3 lbs. 11 R 76023 Net 6.95



10⁹⁵

- For Both 6 & 12 Volts
- Built-in Meter
- Automatic Reset Breaker

Full 3-amp battery charger for quick starts in all weather. Edge view colored meter shows actual battery condition. Reset circuit breaker gives automatic overload protection. Has 6 and 12 volt selector switch. Delivers tapering charge. Vented steel case; may be wall mounted. 6 ft. battery leads with 50 amp clips. Size: 6 x 4¹/₂ x 5³/₄". For operation from 105-125 Volt. 60 Hz AC. UL Listed.

11 R 76049 Shpg. wt., 5 lbs. Net 10.95

terado TRAV-ELECTRIC **78⁷⁹**

Self-Contained Power Supply with Battery and Automatic Recharger

- Delivers 117 Volts 60 Hz A.C.
- At 125 Watts Continuous
- 3 to 4 hours of Portable T.V. Operation on One Charge

Hundreds of uses: Operates TV's, power tools, barbecue motors, lights, hedge clippers, or appliances using 117V, 60 Hz AC. Has self-contained 30 amp. rechargeable wet storage battery. Frequency stable within 1/2 cycle with load changes. Plugs into AC outlet, or, car cigarette lighter to recharge battery. Has automatic overcharge protection. Meter shows charge rate and hours of anticipated output. Size: 12x5¹/₂x8". Shpg. wt., 36³/₄ lbs. 11 R 63161W No Money Down* Net 78.79

terado - C - D - **TRIPP LITE** Inverters

TERADO SOLID-STATE DC-to-AC INVERTERS

AS
LOW AS
45⁹⁵

- Transistorized
- 110 Volt AC Electricity From Your 12 Volt Battery

NO MONEY DOWN*



Compact and convenient power inverters. Converts 12VDC to 110V 60 cycles AC. † Features frequency regulation $\pm 1/2$ cycle with changing input load and voltage. Ideal for tape recorders. Complete with battery cables. ‡

Stock No.	Mfr. No.	Watts	Cont. Interm.	Size	Shpg. Wt. Lbs.	Net
11 R 83013	50170	125	150	10 3/4 x 6 x 6	11 3/4	45.45
11 R 83153	50205	140	175	10 3/4 x 6 x 6	11 3/4	51.50
11 R 83203	50128	450	500	6 x 6 x 12 1/2	19 3/4	97.17
11 R 83237W†	50201	150	175	10 3/4 x 6 x 6	16 1/2	100.51

TERADO "SENIOR" DC TO AC INVERTER

Vibrator type inverter. Has automatic frequency control. Converts 12 volts DC to 110 volts, 60 cycles AC. Frequency regulation $\pm 1/2$ cycle. Filtered. Plugs into cigarette lighter. With battery cables. Size 2 1/2 x 2 1/2 x 4 1/2". Output 40 W. constant, 50 intermittent. 11 R 63062 Shpg. wt., 2 1/4 lbs. Net 20.16



TERADO "DYNAMO" DC TO AC INVERTER

Operate any small radio in any 12 volt car, truck, boat or trailer. No installation—just plug into cigar lighter. Operate electric shaver or any electric appliance up to 25 watts. With generator condenser and ignition noise suppressor. Size: 2 x 2 x 3 3/4". 11 R 63179 Shpg. wt., 2 lbs. Net 16.47



TRAV-ELECTRIC "AUTO-SHAVER"

Operates all electric shavers. Plugs into cigarette lighter. Polyethylene non-breakable case. Size: 3 3/4" W x 2 1/4" D x 4 1/4" H. 12 volts 15-20 watts. Shpg. wt., 2 lbs. 11 R 63047 12 Volt Net 11.85



TERADO SOLID-STATE INVERTER-CHARGER

- It's A Battery Charger
- It's An Inverter



Mark I, portable, transistorized 450 to 500 watt inverter/charger. Converts 12 volts DC to 117V., AC household current. Designed for use in cars, mobile homes, and boats to operate radios, recorders, televisions, lights, electric tools, and test equipment from any 12V., DC power source. Also serves as a battery charger with charging rate of 20, and 10 amps plus low trickle charge. Complete with amp meter, 12V., DC input poles, front panel mounted fuses, and 117V., AC standard outlet. 12 1/2 x 6 x 6". Shpg. wt., 20 1/2 lbs. 11 R 63260W No Money Down* Net 108.50

CORNELL DUBILIER DC TO AC INVERTER

42⁹⁵ No Money Down*

- Delivers 125 Watts Continuously
- Features "Hash Free" Filtering For Interference-Free Reception



Ideal for cars, boats, house trailers, campers, etc., as a source of AC power independent of power lines. Converts 12 volts DC to 110-120 volts AC at 60 Hz. Designed primarily for television receivers, tape recorders, phonographs and other frequency sensitive devices. Specifications: Input: 12 volts @ 12 amperes (full load); Output: 120 watts continuous, 140 watts intermittent; RF Filtering: both input and output; Size: 8 3/4 L x 7 1/2 W x 3 3/4" H. Shpg. wt., 15 1/4 lbs. 11 R 18256W Net 42.95
Model MK-3544-4 Mounting Kit—Heavy flanged plate for bulkhead or floor mounting. Includes hardware and instructions. 11 R 18264 Shpg. wt., 2 1/4 lbs. Net 3.60

*See Page 22 for Full Credit Details on Easy Pay Plan

TRIPP LITE 150-WATT TRANSISTORIZED INVERTER

39⁹⁵

- Delivers 150 Watts Continuously
- Fused to Protect Battery
- Provides Household Current Anywhere Model PV-150



A low-cost transistorized inverter which changes 12-volt DC to 115-volt 60 Hz AC. Delivers 150-watts continuously; 175-watts intermittently for shavers, recorders, radios, TV and many other appliances. Has on-off switch and replaceable fuse. Rugged construction. Size: 5 x 5 x 3 1/2". Shpg. wt., 3 3/4 lbs. 11 R 89505 No Money Down* Net 39.95

TRIPP LITE 100 WATT TRANSISTORIZED INVERTER

29⁹⁵

- Converts 12 Volt DC to 115 Volt AC
- Delivers 100 Watts Continuously
- Plugs Into Lighter

MODEL PV-100 Designed to give instant AC power where fast emergency service is needed. Lightweight, low-cost inverter converts 12 volts DC to 115V., 60 cycles AC; delivers 100 watts continuously. Specifically engineered to power televisions, and tape recorders in cars, boats, planes, or mobile homes. Incorporates 2-power switching transistors. Complete with cigarette lighter plug, and standard AC outlet. Size: 4 3/4 x 4 3/4 x 3". Shpg. wt., 1 3/4 lbs. 11 R 89547 Net 29.95



TRIPP LITE 350 WATT TRANSISTORIZED INVERTER

69⁹⁵

- Use It In Your Car, Boat, Trailer, Plane

Model PV-350. Converts 12-Volt D.C. current into 115-Volt A.C. Enables you to operate your house appliances and tools in your car, trailer, boat, plane, etc. Delivers 350 watts continuously, 385 intermittently. 8 power transistor circuitry for power boost. Advanced design has no moving parts to wear out. Inverter puts less strain on your battery, allowing your tool or appliance to do a quicker, better job. Mounts easily on any flat surface. Size: 3 1/2 H x 6 1/2 W x 9" D. Shpg. wt., 10 lbs. 11 R 89570W No Money Down* Net 69.95



TRIPP LITE ALL SOLID STATE POWERVERTERS



Model PV-200-B



Model PV-500-B

- Combination Power Inverters and Battery Chargers

MODEL PV-200-B—200-WATT INVERTER, 5 AMP BATTERY CHARGER. Converts 12-volt DC to 115-volt 60 cycle AC, delivers 200 watts continuously, 220 watts intermittently. 4 power transistor circuitry for power boost. Battery charger is rated 5 amp, has automatic control which tapers current down to prevent overcharging. Size: 3 1/2 x 5 x 5 1/4". Shpg. wt., 7 1/4 lbs. 11 R 89513 No Money Down* Net 54.95

MODEL PV-500-B—500 WATT INVERTER, 10 AMP BATTERY CHARGER. Rugged, heavy-duty inverter with 500 watt continuous output, 550 watt intermittent. 10 power transistors; hash-free TV, AM-FM reception. Battery charger rated at 10 amp, polarity protection in case of incorrect hook-up. Pilot light warns against overloading. Built-in rack handles. Size: 5 1/4 x 9 1/4 x 9". 11 R 89562 No Money Down* Shpg. wt., 19 1/4 lbs. Net 109.95

LAFAYETTE Automotive Test Equipment



6 1/2" DWELL TACHOMETER

28⁹⁵

- Tunes up Electronically, Any Car Ever Made
- Three Dwell Scales
- Low And High Range Tachometer Scales
- Giant 6 1/2" Easy-to-Read Scale

Made In U.S.A.

A complete ready-to-use Dwell Meter and Tachometer which will operate on any car ever made. Tests cam Dwell angle and engine RPM on 4, 6 or 8 cylinder cars, 6 or 12 volt right on the engine. Giant 6 1/2 easy-to-read meter makes it simple for anyone to adjust points and carburetors to insure maximum gas economy and quiet engine running. RPM readings are also essential to properly service automatic transmissions. Three dwell angle scales are provided: 0 to 45 degrees, 0-60 degrees, and 0 to 90 degrees. This instrument is suitable for dwell angle adjustment on all foreign and domestic cars. Dual range tachometer 0 to 1000 rpm for precise carburetor adjustments. 0 to 5000 rpm, suitable for making all other tests at high engine speeds. Complete with instruction manual. Shpg. wt., 3 1/2 lbs.

11 R 01013W

Net 28.95



3 1/2" DWELL TACHOMETER

16⁹⁵

- Tune Up Electronically Any Car Ever Made
- 3 1/2" Double Jeweled D'Arsonval Meter
- For 4, 6 or 8 Cylinder Engines
- For 6 or 12 Volt Systems
- Point Resistance Check


Made in U.S.A.

Electronically tune your car! This Dwell-Tachometer permits setting the carburetor for maximum efficiency, gas economy and greater power; indicates the correct point gap setting electrically (even if the points are pitted or corroded); permits setting points with the distributor cap off and engine cranking, and permits setting points on "Window" distributors with engine running. It also locates defective spark plugs; permits correct engine RPM setting for automatic transmission adjustments, throttle linkage and idle adjustment. RPM scale: 0-3000; 8-cylinder dwell: 5-45°; 6 cylinder dwell: 20°-60°; 4 cylinder reading obtained by doubling 8 cylinder scale reading. Two-color scale. Small and compact—measures only 6 1/4 x 3 3/4 x 2". Complete with instruction manual. Shpg. wt., 1 3/4 lbs.

11 R 01054

Net 16.95

DELUXE AC OR DC—POWER TIMING LIGHTS



DC WIRED
22⁹⁵

- Ultra-Brite Xenon Strobe Tube

DC POWER TIMING LIGHT

Chrome finished DC-power timing light. The ultimate in a mechanics light. Ultra-brilliant blue white xenon strobe tube gives bright light for day or night use. Rugged case, designed for operator to reach inaccessible timing marks. Simple replacement of xenon bulb. For 6 and 12 volt battery. On/Off Switch. Shpg. wt., 1 3/4 lbs.

11 R 42405

Net 22.95

Same as above in kit form

11 R 42470

Net 16.95

DC KIT
16⁹⁵

AC WIRED
12⁹⁵

AC KIT
10⁹⁵

- Available in Wired or Kit Form

AC POWER TIMING LIGHT

Deluxe 110 volt AC power timing light. Uses ultra-brilliant white xenon strobe tube. For day or night use. Plugs into any 110 volt AC line, insures maximum light regardless of condition of vehicles battery. Rugged black case with power cord and On/Off switch. Shpg. wt., 1 1/2 lbs.

11 R 42397

Net 12.95

Same as above in kit form

11 R 42488

Net 10.95



PROFESSIONAL D.C. POWER TIMING LIGHT




- Rugged Chrome Die-Cast Metal Case
- Super Brilliant Blue-White Xenon Tube

A professional tool in every respect. Gives ample flash intensity to overcome any surrounding light conditions. Connects directly to the car battery with shock-mounted internal components to take constant use without damage. Features: trigger actuated for longer bulb life, prefocused, unbreakable lens, burn-out proof and shock protected, heavy-duty clips electronically bonded to leads, grease and oil resistant leads, Flex-Guard strain-relief bushing at base of handle. Operates on 6 & 12 volt batteries to service domestic and foreign cars, universal spark plug adapter. Tests: Engine timing/ Vacuum advance/Mechanical advance/High-tension circuits.

11 R 43502 Shpg. wt., 3 1/2 lbs. Net 26.95

26⁹⁵

TIMING LIGHT WITH REMOTE STARTER



5⁹⁵

Deluxe neon prefocusing light. Cranks engine from the outside—checks points, bearings, and tappets. The remote starter is also useful in testing the fuel pump, generator, compression and electrical system. For 6, 12 or 24 volt systems. Shpg. wt., 1 1/4 lbs.

Net 5.95

DELUXE SOLID-STATE ENGINE ANALYZER

For All Electrical Systems 6, 12, 24 or 32 Volt
—Regular, Transistorized or Magneto Ignition,
8, 6 or 4 Cylinder 4 or 2 Cycle Engines.

ONLY
49⁹⁵

No Money Down*

- Large 6" D'Arsonval Double Jeweled Meter
- Do-It-Yourself Instruction Book



Performs "FIFTEEN" authoritative tests under actual operating conditions; Tests output voltages in three separate ranges: 0-3.2, 0-16, 0-32 VDC. Determines the condition of batteries, battery cables, spark plug wires, coil wire, solenoids and starter motors. Permits precise setting of distributor points (cam-dwell angle) and test centrifugal advance mechanism on three scales: 0-45° for 8-cylinder, 0-60° for 6-cylinder, and 0-90° for 4 cylinder. RPM scales allow precise setting of carburetor air/fuel mixture and engine RPM in four separate scales: 8 or 6-cylinder (low) 0-1,200, (high) 0-6000; 4-cylinder (low) 0-2400, (high) 0-12,000. Measures amps from —5 to +90. Resistance scale from 0-100,000 ohms. Operates on single "D" cell battery. Complete simple operating instructions. Detailed information supplied by make and model. Rugged steel case finished in baked enamel. Rear storage compartment holds 5½' leads, clamps, plug jacks and connectors. Size: 12 x 6½" x 6". Shpg. wt., 7¾ lbs.

11 R 24502 Net 49.95
99 R 63661 Battery For Above Net .25

Solid-State Engine Analyzer Will Test:

- Dwell or Cam Angle
- Measure Engine Speed
- Adjust Carburetors
- Adjust Points
- Check Condensers
- Check Coil Resistance
- Measure Carbon Suppressor Spark Plug Cables
- Check Batteries
- Test Alternators, Generators & Regulators
- Check Shorts & Opens in Wiring
- Checks All Lamps, Fuses, Relays & Switches
- Check Alternator Diodes

SOLID-STATE ENGINE ANALYZER

Only **39⁹⁵**

- Large 6" D'Arsonval Double Jeweled Meter
- Tunes Up Electronically, Any Car Made

For diagnosis & repair of electrical systems & carburetion in modern automatic engines. Analyzer will test: Dwell or cam angle, & Engine speed, Aids in adjusting carburetors, points, condensers. Ranges: Tach., Features: High and Low scales. 8 cyl., 0-1200 RPM, 0-4500 RPM. 6 cyl., 0-1600 RPM, 0-6000 RPM. 4 cyl., 0-2400 RPM, 0-9000 RPM. Dwell—8 cyl., 0-45°, 6 cyl., 0-60°, 4 cyl., 0-90°. Analyzer will also check: coil resistance, batteries, shorts & openings in wiring, all lamps, fuses, relays, switches and diodes, including alternator and protector diodes. Measures Carbon suppressor spark plug cables and it can be used to test alternators, generators, & regulators. Special Scales: Voltmeter, 0-16 Volts with charging ranges for both 6 & 12 Volt automotive systems, Amperes, —5 to +90. Ohms, 0-100,000. Operates on a single (AA) cell Shpg. wt., 6 lbs.

11 R 24528 No Money Down* Net 39.95
99 R 63703 Battery for Above Net .15




For All Electrical Systems 6, 12, 24 or 32 Volt
—Regular, Transistorized or Magneto Ignition,
8, 6 or 4 Cylinder 4 or 2 Cycle Engines.

DUAL-RANGE TACH-DWELL POINTS TESTER

24⁹⁵

- Large 6" D'Arsonval Double Jeweled Meter
- Electronically Tune Any Car

Hand-held mechanics quality Dual Range Tach/Dwell for 4, 6, or 8 cyl. engines, 6 or 12 Volt ignition systems. With high & low Tach scales: 0-1200 RPM, 0-6000 RPM. Used to adjust idle, eliminate creeping, or stalling, spot weak plugs, cylinders, valves, & distributor advance. Dwell Meter: has 0-45° & 0-60° range. Giant 6" Vista-Dial scale permits accurate setting + or —1°. Point resistance, calibrated to indicate if new points required, correct hard starting, improve high speed operation. Features: Simple hook-up color-coded scales for easy reading, with complete instructions. Shpg. wt., 3 lbs. 11 R 43510 Net 24.95



KARCHECK


AUTOMATIC TACH-N-DWELL

29⁹⁵

- Dual Meter Lets You Read Engine Speed & Dwell Angle Simultaneously

Now! In seconds detect problems in the primary ignition circuit that cause slow starting, rough idling, excessive gasoline consumption, poor acceleration and sluggish high speed passing. Makes simultaneous tests of dwell and RPM; lets you perform professional electronic tune-ups on both 2 and 4 cycle engines. Operates on 6, 12 or 24 volt systems. Front panel features two (one for Dwell; one for RPM) large 4½" double jeweled D'Arsonval meters with color-coded meter faces for easy, accurate readings—three tach ranges, plus three dwell ranges provide all the necessary ranges for virtually every engine. Self-contained solid-state circuitry eliminates adjustment and burn-out. Complete with carrying handle, color-coded test leads. Housed in sturdy steel cabinet with baked enamel finish. Size: 12¾ x 6½ x 4¾".

11 R 24510 Shpg. wt., 6¾ lbs. Net 29.95



*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 373

AUTO GAUGES AND TEST EQUIPMENT

**DELUXE 3/4" GAUGE AMMETER
-WATER-OIL PRESSURE**



19⁹⁵

• All Electric—No Tubing

End guess work and space problems with this beautiful three-in-one gauge. Illuminated dial face gives accurate individual readings of oil pressure, amperage, and water temperature. Amp. gauge reads —60 to +60, oil pressure registers 0 to 80 lbs., and water temperature is indicated from 100° to 220°.

Fits all 12 volt negative or positive ground alternator or generator electrical systems. Handy 360° universal mount and durable chrome zinc die cast case. Supplied with wire, adjustable mounting ring, and senders.

11 R 42033 Shpg. wt., 2 1/2 lbs. Net 19.95
OIL AND AMMETER GAUGE—Similar to above, less water temp. gauge.
11 R 42041 Shpg. wt., 2 1/4 lbs. Net 16.95

GAS SAVER VACUUM GAUGE



Only
12⁹⁵

- Automatically Shows Miles Per Gallon
- Chrome Die Cast Case

DELUXE 3/4" TWIN VACUUM GAUGE. Automatically shows miles per gallon. Saves up to 40% of your gasoline dollars by showing you how to drive for the best economy or power. Checks your engine constantly by measuring its manifold pressure on a clear, four color illuminated dial. With 360° universal mounting, zinc die cast case, T-connector, 6 ft. vacuum tubing, steering column mount ring and instructions. Fits any car.

11 R 42058 Shpg. wt., 1 1/4 lbs. Net 12.95



32⁹⁵

- 0-1600 and 0-8000 R.P.M. 0-60° Dwell, 0-16 Volts
- Positive or Negative Ground, 4-6-8 Cyl., 6 or 12 Volt Systems

Uni-Tach Dual Purpose Tachometer

• Can be Dash Mounted or Used as a Tune-up Tester
Use it as a mounted instrument on your dash or console, or as an engine tune-up tester. As an engine monitor, the tach gives you instant readings, critical for top performance. As a tune-up tester, the tach gives you the necessary instrumentation to do your own money saving tune-ups. Jeweled D'Arsonval movement provides pinpoint accuracy. Comes with all accessories including cable, hardware, test leads, operating instructions, and Tune-Up Guide and Test Log. Easy to install—only three simple connections to make. No tools required. Shock mounting for in-car use. Black dial face has white numerals and red pointer. Size: 6 1/4 x 3 1/4 x 2". Shpg. wt., 3 lbs.

11 R 66511 No Money Down* Net 32.95

TUNE UP KIT



10⁹⁵

- Tunes Engine for Maximum Efficiency
- For Accurate Ignition Timing Of Any Engine

Tune up the important systems of your car, truck or marine engine. Kit includes compression

tester, vacuum fuel pump tester and timing light with remote starter switch. Compression tester locates valve, ring, piston and cylinder troubles. Big 2 1/2" dial is calibrated 0-300 lbs. pressure. Vacuum and fuel pump tester checks pressure and suction of fuel pump and vacuum system. 2 1/2" dial calibrated in 0-30 inches and 0-3 lbs. Comes with rubber tubing for easy connection. Prefocused timing light features remote starting switch. For 6, 12 or 24 volt systems.

11 R 42090 Shpg. wt., 2 1/2 lbs. Net 10.95

PRECISION IGNITION POINT SETTING TOOL KIT

Set points without finding high spot on cam or removing distributor. Even does dual points in one operation. Includes 5-micro-precision rings with feeler gauges, adapters, and tool for hex-wrench GM points. List of popular cars displayed inside cover of box. Shpg. wt., 3/4 lbs.

11 R 31507 Net 5.50

SPARK PLUG AND 6 AND 12 VOLT TESTER



1.69

• With Retractable Test Probe Needle And Alligator Clip
For testing 6 and 12 volt wiring systems on cars, boats, trailers, or any low volt system. Test spark plugs, check fuses, find faulty sockets, shorts, broken wires. Quick easy visual test. Neon flash tells the story. Shpg. wt., 4 oz.

11 R 31515 Net 1.69

COMBINATION SPARK PLUG AND IGNITION GAUGE



• Gap Points & Spark Plugs with One Tool.

Handy combination of wire and narrow blade sizes to check majority of all required ignition gap tolerances. Fifteen 1 1/4 x 1/4" blades, thickness: .012, .013, .014, .015, .016, .017, .018, .019, .020, .022, .024, .025, .028, .030, .032. Eight wire gauges: .022, .025, .028, .030, .032, .035, .038, and .040. One Tungsten File.

14 R 52077 Shpg. wt., 8 oz. Net 2.39



(A) **COMPRESSION TESTER** shows worn or defective rings, pistons and cylinders. Easy-to-read 2 1/2" dial, calibrated from 0-300 lbs. Has offset stem and rubber nose cone to fit all spark plug holes.
11 R 42074 Shpg. wt., 10 oz. Net 3.19

(B) **VACUUM and FUEL PUMP TESTER** indicates worn or faulty parts in fuel pump or vacuum system. Easy to read 2 1/2" dial matches dial on compression tester, calibrated from 0-30 inches vacuum and 0-7 lbs. for pressure. Aids in setting timing, adjusting carburetor or tuning motor.
11 R 42066 Shpg. wt., 10 oz. Net 3.19

(C) **PISTOL-GRIP TIMING LIGHT** gives brilliant light for precision setting of ignition timing. Neon light for 6, 12 and 24 Volt system.
11 R 43528 Shpg. wt., 12 oz. Net 3.29

(D) **REMOTE STARTER SWITCH** permits operation of starter and turning over of engine from outside of car when adjusting points, valves, testing compression, etc.
11 R 12077 Shpg. wt., 6 oz. Net 2.49

"CUSTOM RALLY STYLED" Auto Gauges

3/4" 270
"WIDE-SWEEP"
TRANSISTORIZED
TACH

29⁹⁵

- Precision 0-10,000 RPM Scale
- For 4, 6, or 8 Cylinder

Our finest tachometer features a wide sweep 3/4" illuminated black and white scale, precision D'Arsonval movement calibrated to 2% accuracy. A shift set needle with 270° swing. Equal divisions between graduated markings for pin-point accuracy over the entire range. This handsomely styled instrument is virtually unaffected by vibration. Has deluxe 3/2" deep heavy chromed and black housing and 360° universal mounting for dash, console, or steering column mounting. For transistor or regular ignition systems at 6 or 12 volt positive or negative ground and zero adjust. Shpg. wt., 1 1/2 lbs.

11 R 42512

Net 29.95

3/4" SLIMLINE
TRANSISTORIZED
TACHOMETER

16⁹⁵

- Shift Set Needle
- 0-8,000 RPM
- For 4, 6, or 8 Cylinder

An attractive 3/4" illuminated black and white face tachometer with precision 0-8,000 RPM scale, 200 RPM divisions, and adjustable shift indicator. Factory calibrated transistorized circuitry with precision D'Arsonval meter assures steady, accurate readings throughout the entire range. Can be used with transistor ignition systems. Has 360° universal mount 1 1/2" depth slim line case with hooded bezel for easy dash mounting on compacts or on steering wheel column. Complete with installation kit. Heavy chrome and black wrinkle construction. For 6 and 12 V positive or negative ground.

11 R 42496 Shpg. wt., 1 1/2 lbs.

Net 16.95

DELUXE 270° OIL PRESSURE
GAUGE/AMMETER



9⁹⁵

- Gauges Tilt In Any Direction
- Internal Lighting-Lights The Gauges
- Separate Black and Walnut Panel Inlays Supplied

Attractive two in one oil-ampere gauge console. Large, illuminated 2" dials tilt in any direction. 270° full swing oil pressure gauge with precision geared brass bourdon tube movement detects trouble before it occurs... not after. Reads pressure accurately 0-80 lbs. psi. Sender units has a universal 1/4 PT connector. Ammeter gives accurate current readings for all generator or alternator equipped cars. Shows rate of charge or discharge from 60-0-60 amperes. Shpg. wt., 2 lbs.

11 R 42439

Net 9.95

DELUXE 270° OIL/WATER
GAUGES/AMMETER



17⁹⁵

Custom panel of three illuminated 2" gauges that tilt in any direction. 270° full swing oil pressure gauge with precision geared brass bourdon tube movement; reads accurately from 0-80 lbs. psi. Ammeter gives accurate charging rate of both generator and alternator systems from 60-0-60 amps. 270° full swing mechanical water temperature gauge also features a precision geared brass bourdon tube movement. Reads 100°-220° F. Complete with 72" capillary tube and adapter. Shpg. wt., 2 3/4 lbs.

11 R 42447

Net 17.95

LECTRA-SCOPE ENGINE ANALYZER

5⁹⁵



- Tests Ignition & Engine Performance

Shows what's going on in any 6 or 8 cylinder engine. Individual lights for each plug... glows with each spark. Steady glow all o.k.; weak flickering light shows dirty contacts, wasted gas; bright light shows heavy engine load, dragging brakes. Installation Instructions. Shpg. wt., 1 lb.

11 R 76502 8 Cylinders Net 5.95

11 R 76510 6 Cylinders Net 5.95

DELUXE AIRWAY
UNIVERSAL COMPASS

4⁹⁵

- Complete with Adhesive Plate for Windshield Mounting

Precision instrument features fingertip regulators with 8 gears and special magnets to provide added accuracy and quick compensation. Design allows up to 30° tilt. Calibrated in 5 degree intervals. Universal bracket mounts in any position on all craft and vehicles. Rigid crystal clear plastic with gleaming chrome and black finish. Illuminated. Shpg. wt., 12 oz.

11 R 65059

Net 4.95

AUTO/MARINE
BATTERY CLOCK

- Attractive Case—Chrome Bezel—Sweep Second Hand

11⁹⁵

OPERATES UP TO 1 YEAR ON SINGLE "C" CELL

A smartly designed and ruggedly constructed battery-operated clock designed for use in the car and cabin cruiser. Use it as a desk clock or take it with you on trips. Chrome bezel, with bright easy-to-read white face, has black markings and features a second pacing sweep hand. Employs a unique fiber mesh fastening arrangement on its base. Can be positioned on any metal, wood, plastic surface, including padded dashboards and yet is readily removable. Light in weight, only 13 ounces, this attractively styled conversation piece is mounted in a sturdy 3/4 x 3/2 x 2 1/2" gray plastic case. Wt., 1 lb.

11 R 17506

Net 11.95

99 R 62572 Battery for above

Net .16

Make Lafayette Your Headquarters For Test Equipment

Lafayette Cat. No. 720 375


Electronic Ignition Systems For Your Car

DELTA MARK 10 CAPACITIVE DISCHARGE IGNITION SYSTEMS



With Silicon Controlled

- Quick, Easy Installation
- Constant Spark to 10,000 RPM
- Extremely Low Input Power
- Less Load On The Engine



Rectifier

MARK 10
WIRED
39⁹⁵

MARK 10
KIT
29⁹⁵

MARK 10 WIRED Combines all the advantages of capacitive discharge with those of solid state circuitry. Eliminates point bounce problems and positively fires plugs regardless of point condition. Fast rise time spark prevents fouling from three to ten times. Point contacts last indefinitely. Eliminates mis-firing, reduces oil contaminants, prolongs engine life. Provides smoother and more efficient operation at all speeds; constant spark up to 10,000 RPM; with dramatically improved acceleration and economy. Provides faster, easier starting in all weather. Unit operates with all commercial and original tachometers. Installs immediately with two simple connections to the existing coil, leaving the standard system intact. No temperature limitations—mounts anywhere. Requires only a very small amount of input power—reduces load on engine and electrical load. For 12 volt negative ground system only. Shpg. wt., 2½ lbs.
11 R 84506 No Money Down* Net 39.95
MARK 10 KIT. Same as above in kit form. Net 29.95
11 R 84514 Shpg. wt., 2½ lbs.



MARK 10 B CAPACITIVE DISCHARGE IGNITION SYSTEMS

With VARI SPARK® Circuitry


NEW

49⁹⁵

- Handy Switch For Instant Return To Standard Ignition
- Restores Power Lost By Smog Control Devices



Offers every benefit of the Mark 10 system, plus more power and more features. The Vari Spark® circuitry controls the spark duration as well as the spark intensity over all ranges of operation. Specifically for modern day engines with emission control devices... helps overcome operational problems caused by poor manifolding, leaner mixtures, and variations in gasoline. Rough idling, surging, slow starting, hesitation during acceleration, and extremely poor mileage are now dealt with effectively and efficiently. Handy switch for instant comparison with standard ignition. Rugged housing with neoprene seals affords dust and moisture protection. For any 12 volt negative ground system. Installs immediately with two simple connections to the existing coil, leaving the standard system intact. 11 R 84522 Shpg. wt., 3 lbs. No Money Down* Net 49.95



JUDSON ELECTRONIC MAGNETO IGNITION SYSTEM

39⁹⁵

- Quick, Easy Installation
- Silicon Components
- Reduces Fuel Consumption

Positively improves performance! Like a mechanical magneto used on racing cars, the electronic magneto provides a minimum of 30,000 volts with the fastest rise time of any system available. Like having a permanent tune-up; doubles spark and point life, gives 2 to 6 miles more per gallon, allows instant starts in sub-zero weather... even with heavy carbon deposits and fouled plugs, helps your engine to develop its highest potential horsepower under any conditions. Operates on 6 or 12 volt systems; single or dual point. Will not interfere with operation of radio, electronic or ignition test equipment. Uses silicon components... is fully protected by zener diodes. Completely sealed against water and corrosion. Simple installation by transferring wires from present coil to the magneto and connecting an additional wire to ground and you're ready to go! Size: 7½x3½". Shpg. wt., 4¼ lbs.
11 R 35508 No Money Down* Net 39.95

MOTOROLA CAPACITOR DISCHARGE IGNITION SYSTEM

59⁹⁵

No Money Down*

- With Silicon Controlled Rectifier
- Extends Point And Plug Life
- Quick Easy Installation




A complete ignition modernizing kit giving your car the added efficiency and economy of electronic switching. Operates by a simple connection to the existing coil and distributor breaker point. For any number of cylinders. The "CDI 12" features a capacitor discharge current and higher constant voltages for maximum combustion and improved miles per gallon. The heavy-duty mounting unit is epoxy coated for moisture and dust proofing. Fully suppressed for excellent

radio reception. Installation is simplified by damage proof circuit protected from reverse polarity or open secondary leads. Shorter, more powerful sparks at plugs increase combustion, reduce plug wear, increase engine life many times. Overall increase in performance, acceleration and gas mileage. Designed for cars with 12-volt negative ground systems. Shpg. wt., 3¼ lbs.
11 R 75066 Net 59.95

JUDSON ELECTRONIC IGNITION SYSTEM

- Quick Easy Installation
- Improves Performance and Gas Mileage

19⁹⁵



Install a Judson SEE/DEE Electronic Ignition System on your car. It provides the dependability and performance required for the modern high speed engine. The current for the See/Dee system is completely controlled by a zener diode. It provides for a better and smoother running engine plus faster starting. In addition point and plug life are extended and there is a reduction of ignition failure and tune-up requirements. Good for a 6 or 12-volt battery and single or dual point negative ground systems. Shpg. wt., 1 lb.
11 R 35516 Net 19.95

"DO-IT-YOURSELF" Auto Accessories

REAR WINDOW DEFROSTER/DEFOGGER KIT

16⁹⁵

- Enjoy The Convenience and Safety of Clear Rear Vision

- Adjustable Louvers Direct Air Where Needed



Eliminates the hazardous driving conditions caused by Steam, Fog, Frost on rear windows. Air drawn from interior of car blankets rear window. Removes condensation and frost. Prevents accumulation of snow while car is in motion. Unit is easily installed in trunk; does not interfere with spare tire or luggage space. Adjustable louvers to direct flow of air are recessed; will not interfere with vision or rear deck space. Dash switch controls defroster operation. Kit includes heavy duty motor, defroster hoses, adjustable louvers, switch, wiring, templates, and installation instructions. Fits all cars, (except station wagons, convertibles, and rear engine cars) for 12 volt electrical system. Shpg. wt., 5¼ lbs.

11 R 12507

Net 16.95

REAR DECK AUTO FAN

- Defogs Rear Windows For Better Vision and Safer Driving

Keeps your rear window clear. Does not obstruct vision. Completely enclosed motor and fan for added safety. With universal mounting bracket for mounting on dash or rear deck shelf. Has variable height adjustment. With on-off switch, necessary hardware, 15 feet of wire, and instructions. For 12 volt cars.

11 R 51505 Shpg. wt., 1 lb. Net 5.95



SEQUENTIAL SIGNAL FLASHER

13⁹⁵

For 3-Bulb Tail light

- Convert Your Turn Signals To A Moving Line of Light



Convert your car's three lamp rear turn signals so that they flash in sequence, creating the effect of a moving line of light pointing the way you intend to turn. Rugged and reliable both right and left signal circuits are complete in one compact unit. A safety innovation. Easy-to-install... all wiring done at signal lamps. Shpg. wt., ¾ lb. For 12 volt negative ground only.

11 R 34519 For 3-Bulb Taillight

Net 13.95

LITE BUZZER

- Reminds You To Turn Off Your Lights When You Park Your Car
- Saves Battery and Service Charges



Sounds off with an audible noise when you turn off your ignition without turning out your lights. Saves your battery, service charge. Easy to install. Mounts under dash. Shpg. wt., 5 oz.

11 R 50010

Net 2.95

PRE-CUT SPARK PLUG WIRE SETS

- Radiation Suppression Type
- Molded Boots



4⁹⁵

Pre-cut universal spark plug wire set with molded angle boots at one end and molded straight boots at the other end. Features full pre-cut wire lengths. Simply clip off the unneeded boot to make a custom spark plug wire set. Radiation suppression type with Hypalon sheathing. Complete kit includes all the necessary parts for 6 and 8 cylinder applications. Shpg. wt., 1½ lbs.

11 R 19510

Net 4.95

ELECTRONIC SPEED CONTROL

EASY TO INSTALL

21⁹⁵



- Maintains Any Selected Highway Speed
- Does Not Affect Braking or Instant Pick-up
- Helps Adhere To Posted Speed Limits
- Sets Fast Idle for Quick Cold-Weather Warm-up

An Electronic Cruise Control which enables you to drive at a constant speed over relatively level surface by automatically holding the throttle steady. Eliminates the need to keep a foot glued on accelerator on long trips. Once you reach desired speed, simply pull out knob and the Speed Control will automatically hold that speed. Allows instant acceleration for passing but takes over again when the foot is taken off the gas pedal. Ceases to function the moment the brake is depressed and completely disengages in the event of any malfunction. Designed to fit all cars and trucks. Shpg. wt., 2 lbs.

11 R 59011

Net 21.95

MOTOROLA

ELECTRONIC ALTERNATOR SYSTEMS WITH TRANSISTORIZED VOLTAGE REGULATOR

64⁹⁵

No Money Down*

- For Automotive, Truck Industrial and Farm Equipment



Low cost solution to the heavy demands made on your car or truck's electrical system. Unlike D.C. generators, it supplies a charge at idle speeds and keeps the battery at a uniform high level of charge. The all-transistor voltage regulator has no contact points or mechanical relays. Fits nearly all cars and trucks and is less than half the size and weight of a similar capacity D.C. generator. Shpg. wt., 13¼ lbs.

11 R 75033 55-Amp

Net 64.95

QWIK CHANGE OIL DRAIN KIT

- Change Your Own Oil Quickly With Just a Twist of a Knob

10⁹⁵

Now anyone can change their oil simply and efficiently with just the twist of a knob. It is permanently installed under the hood and replaces the drain plug in the oil pan. The knob activates the valve on the oil pan to drain the oil out. Closed it seals securely. Valve is all steel, with light teflon seal and positive action flexible cable. Fits the following cars: Buick 59-71, Chevrolet 54-71, Chrysler, Dodge, Plymouth 62-71, Mercury 59-71, Oldsmobile 66-71, Pontiac 54-71. No more stripped drain plugs. Saves time and money. Perfect for the racing enthusiast, ideal for boat owners, saves bilge crawling. Shpg. wt., 1 lb.

11 R 52503


Net 10.95

12 FT. TANGLE-FREE BATTERY BOOSTER CABLE

New Tangle-free Cable twins with 100% Copper Conductor. Special Duplex Cable Construction. With one side color striped for quick polarity identification. Made with heavy-duty, flexible rubber-covered cable. Standard equipment for starting stalled cars, and charging batteries. Wt. 1½ lbs.

11 R 19528


Net 4.50



Automotive Theft Protection Devices

ON-GUARD PROFESSIONAL SIREN-OPERATED BURGLAR ALARM

2788



- Loud, Police-type Siren Protects All Doors, Trunk and Hood
- Complete—Easy To Install
- Pick-Proof On-Off Key Lock Mounts on Outside of Auto

Get 24-hour protection on your car, station wagon or truck with this complete burglar alarm system. The sharp penetration sound of the police-type siren will scare thieves away. The siren blasts off when anyone opens a door, the hood or trunk. The alarm can be shut off only with the alarm key. Complete system includes deluxe highly polished spun-aluminum siren with trumpet, 4 door switches, hood switch, trunk switch, 2 brackets, electrical lock with 2 keys, wire, mounting hardware, instructions and 2 warning decals. For 12-volt cars only.

11 R 62015 Shpg. wt., 6¾ lbs. Net 27.88
This item not intended for resale in States where its use is forbidden in motor vehicles by public regulation.

LOCATOR AUTO BURGLAR ALARM



- Loud Siren Gives Protection To Doors, Trunks, and Hood
- Pick-Proof Key Lock Mounts on Outside of Auto

19⁹⁵

A penetrating police siren and trumpet constructed of spun aluminum for loud piercing sound. System helps prevent break-in pilferage, damage, and inconvenience. Activator switches protect all access openings including trunk and hood. Siren blasts loud and clear and remains on until manually reset by pick-proof lock switch. Great for cars, wagons, trailers, trucks, and vans. Supplied with relay, six alarm activator switches, wire, terminals, screws, and pick-proof key lock with two keys. Shpg. wt., 6¾ lbs.

11 R 62064 Net 19.95

This item not intended for resale in States where its use is forbidden in motor vehicles by public regulation.

ON-GUARD HORN BURGLAR ALARM

As Low As

6⁸⁸



- Sounds Car Horn When Entry Is Forced
- Protection For All Doors, Trunk, and Hood
- Pick-Proof ON/OFF Key Lock Mounts on Outside of Auto

Protect your car, wagon, truck 24 hours a day. Easy to install auto alarm system activates when anyone opens a door, the trunk, or hood. When an entry point is opened a shrill sound of the vehicle horn will be heard. The alarm will not be silenced by closing the point of entry. Can be shut off only with the alarm key. System includes six alarm activator switches, lock, 2 keys, 2 relay switch unit, wire, mounting hardware, and simple instructions. Shpg. wt., 2 lbs.

11 R 62023 Net 6.88

PULSATING HORN BURGLAR ALARM

Similar to above except when an entry point is opened, a "Vibrating Shrill Beeping" pulsating sound of the vehicle horn will be heard.

11 R 62031 Shpg. wt., 2 lbs. Net 9.88

SECRET AUTO-IGNITION GUARD

- Stops Car Theft
 - Only You Can Start Your Car
- 2⁴⁹



Fits Every 6 and 12 Volt Car and Truck

With just a turn of a knob, the auto ignition guard will stop any car thief. Even master keys and "jumping methods" will not start your car—only you can start it. Hooks up in minutes; fits 6 and 12 volt cars and trucks. Shpg. wt. 1/2 lb.

11 R 13117

Net 2.49




ELECTRONIC AUTO BURGLAR ALARM

9⁹⁵ • Simple, Easy To Install

Protect your automobile or boat from intruders. Just opening a door, trunk, or hood will set off this sensitive system. Turning on headlights, ignition or any electrical accessory will also activate your car horn for an unmistakable warning. Cannot be shut off by closing door, hood, ignition, etc. Car engine can not be started until control unit is switched off. Only you know where the hidden switch is. Trunk and hood are automatically protected if they have a built-in light or the accessory light listed below can be installed. Connects simply to horn relay and battery with only two wires.

11 R 52511 Shpg. wt., 1 lb. Net 9.95


AUTO HOOK-LOCK ANTI-THEFT DEVICE



Car anti-theft device that makes your car theft-proof in seconds! Requires no wiring or special fittings. Fully adjustable steel rod with an individualized key lock attaches to the steering wheel and brake pedal making it impossible to drive your car away. 360 degree swivel top permits universal mounting for all makes and models of cars.

11 R 26507 Shpg. wt., 2½ lbs. Net 11.95

AUTO HOOD LOCK KIT



- Prevents Theft of Battery and Engine Parts

3⁴⁹

Hood can only be opened from inside of car. Protects battery, generator, distributor, etc. Complete with all parts for installation. Fits following cars:

61 Buick	67-68 Chevelle	68 Olds
64 Cadillac	63-65 Comet	63-68 Tempest
68 Camaro	63-67 Ford	62-66 Rambler
61-68 Chev.	63-65 Falcon	(not Classic)
67-68 Chevy II	63-67 Mercury	64 T-Bird
and other cars with striker bolt in hood.		

11 R 53014 Shpg. wt., 1½ lbs. Net 3.49

AUTOMATIC TRUNK & HOOD LIGHT

- For All Cars With 12 Volt System



As Low As 1⁹⁹

Light up your entire hood or trunk compartment. Bright diffused light illuminates trunk or hood compartment for loading or unloading trunk . . . for making engine inspection or repairs at night. Completely automatic with Honeywell mercury switch. Easily installed. All hardware and wire included.

11 R 43015 Shpg. wt., ½ lb. Net ea. 2.19
Lots of 2 1.99 each

Custom Horns - For Your Car

MUSTANG HORN

11⁹⁵

- Whinnies like a Wild Mustang

You've seen a mustang—now hear a mustang! Compact size horn "whinnies like a wild mustang" when you press the horn button in the car. Adds a new dimension of life to your Mustang or other make automobile. Conveniently mounts anywhere under the hood. Fits any car. Complete with horn button control, wire, and all necessary mounting hardware. Black enamel finish with chrome plated grill. Dimensions: 5" x 5½" x 6". Shpg. wt., 2½ lbs. 11 R 44526 For 12 Volt



Net 11.95

CONTINENTAL HORN

14⁹⁵

- With European Sound

Swing with the sounds of the continent! Twin continental electric horn automatically alternates from high to low notes like European police horns. Clear, crisp tones are sure to attract the attention of pedestrians and other motorists. Different from other horns, consists of a high note unit and a low note unit mounted on a single sturdy frame. Mounts under the hood of virtually any car, in any available space. Complete with horn button control, wire, mounting hardware, and complete installation instructions. Black enamel finish with bright chrome grill. For 12 volt. Dimensions: 3½" x 5½" x 9". Shpg. wt. 3¼ lbs. 11 R 44500




Net 14.95

BEEP-BEEP HORN

DISTINCTIVE TONE

Only **6⁹⁵**

Go mod! Newest sound sensation! Distinctive BEEP-BEEP sound awakens the daydreamer, gets immediate attention from the slow pokes... just two quick taps on the horn and you're way out. Powerful 4" x 5½" x 6½" H horn is easily installed in any car. Complete with mounting hardware and horn button control. Finished in 2-tone black and red enamel. For 12 V. 11 R 44534 Shpg. wt., 2¼ lbs. Net 6.95



EMERGENCY TIRE CLEATS

They're cleats — not chains — and that makes the difference. These heat treated, hardened steel cleats bite into ice and snow like tank treads — they dig deep, grip firmly, won't slip like chains. Quickly installed on most cars and light trucks with slotted rims. Each cleat is 1" W x 1¼" L x ½" D. Shpg. wt., 2 lbs. 11 R 28503 Set of 2 Net 2.95




AUTO "Lock-A-Matic

- Locks Steering Wheel To Automatic Shift Stick

Instantly immobilizes your car by locking your steering wheel and transmission lever. Easily attaches in seconds to cars with gear shift lever mounted on steering column. Double rustfree chrome plated locks and hardened steel shackle insure complete protection. Can also be adapted for use on motorcycles and bikes. Shpg. wt., 1 lb. Imported.


11 R 13133 Net 3.50



AH-000-GAH! HORN

11⁹⁵

- Chrome Plated Bell
- With Horn Button



A real joy for the sports car enthusiast. An authentic motor driven horn approved as an exact reproduction in sound and appearance by members of antique car, hot rod, and horseless carriage clubs the world over. Chrome plated bell with black wrinkle painted housing. With horn button, wire, bracket and instructions. Shpg. wt., 4¼ lbs. 11 R 30012 6-volt Net 11.95
11 R 30020 12-volt Net 11.95

"FIAMM" ELECTRO COMPRESSOR AIR HORNS

- Chrome Plated Brass Trumpet
- Range of ½ Mile
- Loud—Clear—Continental Tone

As Low As **18⁹⁵**



Model 32. Custom quality chromed trumpets with loud clear, piercing, continental tone. Range up to ½ mile. Ideal for use on trucks, sports cars, emergency vehicles, buses, boats, etc. Compressor pumps air to trumpets instantly when horn is pressed—there's no waiting for pressure to build up. Supplied with Town and Country Selector Switch which enables use of original horns for city driving. Complete with: 2 horns (7" & 9"), compressor, fittings, horn relay, and all necessary hardware. For 12 volts only. From Italy. 11 R 82500 Shpg. wt., 5 lbs. Net 21.95
Model 22. Same as above but trumpets are enameled die-cast metal. 11 R 82518 Net 18.95

"FIAMM" 4-TRUMPET MUSICAL HORN

Musical horn that plays Cavalry Call. Four trumpets made of sturdy enameled die-cast metal. Range one mile. A special cycle switch allowing 2 of the louder trumpets to sound simultaneously and a Town and Country selector switch permitting you to use your original horn, as well as the original horn button. Includes fittings, hose, relay and compressor. For 12V only. From Italy. Largest horn 14". 11 R 82526 No Money Down* Shpg. wt. 12¼ lbs. Net 69.95

King of the Road TRIPLE TONE ELECTRIC AUTO HORN

15⁹⁵

- 3 Horn Assembly

Get rid of your old horn—be a King of the Road. Blow the loudest, richest, most melodious horn around. Custom quality three horn assembly gives you a distinctive, attention getting sound. Complete with horn button, wire, and mounting bracket. Dimensions 5½" x 8" x 10¼" L. Black enamel finish. For 12 volt systems. 11 R 44542 Shpg. wt., 4¼ lbs. Net 15.95



Auto Warning Signal Lamps—Accessories



DELUXE REVOLVING BEACON

- Plugs Into Cigarette Lighter Outlet
- Rotates Like a Lighthouse Beacon

6⁹⁵

A red warning light that rotates 360 degrees and flashes in all directions. Suction mount holds the beacon firmly in place. Signals for help for miles around: creates a safety zone during a traffic emergency. For use on autos, boats, trucks, docks, etc.

For 12 volt use; complete with cigarette lighter adapter plug. Shpg. wt. 1 3/4 lbs.

11 R 13042 Net 6.95
BLUE TURRENT LENS, Converts Revolving Beacon for use by emergency vehicles, volunteer fire depts., CD units, etc. Shpg. wt. 5 oz.
 11 R 13059 Net .95

REVOLVING BEACON

3⁹⁵ • With Amber Lens

Giant size amber turrent lens flashes and rotates full 360°. Bright enough to signal help for miles around. Creates a safety zone while changing a flat or during a traffic emergency. For use on autos, boats, trucks, docks, etc. Big suction cup base will mount on any smooth surface. Giant size amber turret lens, brilliant finish. Uses 3 "D" batteries. (Not Included.) Shpg. wt. 1 3/4 lbs.

11 R 14503 Net 3.85
 Batteries for above. Net ea. .18
 99 R 62564

POWERFUL QUARTZ IODINE HAND SPOTLIGHT

19⁹⁵

- Throws a Beam More Than 1/2 Mile
- For Emergencies, Camping, Marine Use, etc.
- All Chrome Die Cast Metal Housing

A hand-held spotlight 3 times brighter than ordinary sealed-beam spotlights, and lasts 2 1/2 times longer. The super-energized Halogen Hs quartz iodine bulb projects a powerful, concentrated beam of light over distances of 1/2 mile. Wide 6" bulb face is perfect for spotting signs at night, house numbers, emergency breakdowns, marine navigation, or anytime precise, reliable illumination is needed quickly. Conveniently plugs into cigarette outlet. On/off switch. For 12V. DC. Shpg. wt. 2 lbs.

11 R 52529 Net 19.95

ELECTRO PLATING KITS

- Replate Worn Chrome, Silver, Gold, or Plate New Items
- Easy to Use

As Low As

6⁹⁵



Retouch worn, rusted or peeled areas of chrome, silver or gold plated articles. Restore old plating to its original beauty by electroplating with pure silver, 24K gold or chrome-like metal. Plate new articles with equal safety and ease. Kits come complete with battery case, plating brush, holder, wire and clip, plating solution and directions. Less batteries. Chrome Plating Kit: covers approx. 12-20 sq. Use 4 AA cells.

11 R 25509 Shpg. wt. 1 1/2 lbs. Net 8.95
 Silver Plating Kit: covers approx. 2 sq. ft. Use 2 AA cells. Net 6.95
 11 R 25525 Shpg. wt. 1 1/2 lbs. Net 6.95
 Gold Plating Kit: covers approx. 1 sq. ft. Use 2 AA cells. Net 13.95
 11 R 25533 Shpg. wt. 1 1/2 lbs. Net 13.95
 Refills for above. Material to do as much as in original kit.
 11 R 25517 For Worn Chrome Kit. Shpg. wt. 1 1/2 lbs. Net 3.95
 11 R 25541 For Silver Kit. Shpg. wt. 1 1/4 lbs. Net 3.95
 11 R 25558 For Gold Kit. Shpg. wt. 1 lb. Net 6.50
 99 R 62580 Batteries for above Net .10



QUARTZ-IODINE FOG AND DRIVING LAMPS

- 260,000 Candle Power
- Die-cast, Slim-Line Body

High power, long life lamp gives life saving illumination in poor weather, makes night driving safer and less tiring. Wide angle, sharp cut-off fog lamp beam penetrates heavy fog. Driving lamp has concentrated, narrow beam for reaching far ahead of normal high beams. Chrome plated body. Sealed lens and reflector keeps out dirt and moisture. Fully adjustable mounting bracket and 3 ft. attached wire. For 12 volt use. 5 3/4" diameter, 2 1/2" deep. Shpg. wt. 2 1/4 lbs.

Fog Lamp, amber
 11 R 26515 Net 12.95
 Driving Lamp, clear
 11 R 26523 Net 12.95
 Replacement Bulb
 11 R 26531 Net 4.95



12⁹⁵

CUSTOM HIGH INTENSITY DRIVING LAMPS

- Shutter Design Protects Lens

8⁹⁵

Sporty pre-focused, sealed-beam driving lamps penetrate through heaviest fog and darkest nights. Swivel bracket with single bolt mounting base easily attaches through grille or on bumper. Modern shutter design protects lens against breakage and prevents glare to oncoming motorists. Highly polished moisture-proof case with an attractive black leather-like face. For 12V. DC. Size: 5 1/4" H x 5 1/2" D. Shpg. wt., 1 lb.

11 R 52537 Fog Lamp—Amber Net 8.95
 11 R 52545 Driving Lamp—Clear Net 8.95




DELUXE PLUG-IN SPOTLIGHT


- 12 Volt GE Sealed Beam
- 10-Foot Cord with Plug
- All Chrome, Zinc Cast Housing

4⁹⁵

Plug-in portable spotlight is a real "life-saver" in emergencies—provides dependable, instant, powerful light for safety in every night-driving need. Finger-grip handle permits easy direction of light beam. Flexible 10-foot cord; GE sealed beam; convenient hang-up hook; rich chrome plate on die-cast metal. Fits most cigarette lighter sockets. 11 R 16250 Shpg. wt., 2 1/4 lbs. Net 4.95



CUSTOM SIDE LIGHTS



Two For

2⁹⁵



Custom side marker lights that keep pace with new automotive safety code. Button style design will enhance your cars appearance by day, prevent accidents by night... your cars visibility improves attracting attention of drivers coming from either side. Easy to mount and install into car's electrical system... Complete with hardware and instructions. Chrome finish.

11 R 27505 Set of 2 Amber for front. Wt., 6 oz. Net 2.95
 11 R 27513 Set of 2 Red for rear. Wt., 6 oz. Net 2.95

CIGARETTE LIGHTER PLUG

Run any 6 and 12 volt accessory from cigarette lighter receptacle of your car—battery chargers, shavers, CB radios, trouble lights, etc. Also use to replace defective plugs. Imported. Shpg. wt., 3 oz.

99 R 85136 Net .59



59^c

Popular Accessories for Your Car

WINDSHIELD DE-ICER

- Heavy Duty—Just Heat and Scrape

ONLY **10⁹⁵**



Heavy duty, fast acting de-icer with high capacity blower. Clears up iced windows long before your car's own heating system has a chance to take effect. No more frozen windshields to block or distort vision. Heavy gauge, 16 ft. cord is long enough to reach all windows. Plugs into cigarette lighter. Break-resistant, cyclocac housing. With mounting bracket and in-line fuse. Shpg. wt., 3 lbs.

11 R 22514

Net 10.95

INFRA-RED WINDSHIELD DEFROSTER



3⁴⁹

- Plugs into Cigarette Lighter

Quickly melt away mist, ice, and snow. You no longer have to wait for car to warm up before cleaning windshield—just plug it into your cigarette lighter, and start defrosting immediately. Complete with 12 foot cable for reaching back windshield. Two suction cups make mounting fast and easy. Length: 15". Shpg. wt., 1 lb.

11 R 13075

Net 3.49

PRIMETTA "FOGGLES"

FOR SAFER DRIVING:

- AT NIGHT
- IN RAIN
- IN FOG
- IN SNOW



Scientifically designed to protect eyes from glare of headlights, street lights, etc. without materially reducing vision. Filter lens exclude all ultraviolet rays. Ideal for driving at night, in rain, fog and snow. With case. Shpg. wt., 4 oz.

11 R 32018

Net 2.89

Clip-on "Foggles"—use on existing glasses.

11 R 32026

Shpg. wt., 4 oz.

Net 2.19

CHILTON'S AUTO MANUAL



9⁹⁵

CHILTON'S 1971 AUTO REPAIR MANUAL—A completely revised manual for every American car since 1964 plus Volkswagen. 4000 illustrations, 1500 pages. Helps pin-point trouble and correct it.

10 R 28018 Shpg. wt., 7 3/4 lbs. Net 9.95

RADIO TRANSVERTER

Now you can avoid the expense of buying a car radio with this radio transverter. Simple to operate—remove 9-volt battery from your transistor radio, connect contacts from transverter to battery contacts in the radio, and then plug into the cigarette lighter. Shpg. wt., 3 oz.

11 R 48014 For 12-volt cars ... Net 1.95



10 FT. NYLON TOW CABLE



3⁹⁵

The perfect cable for towing ANYTHING UP TO 5,000 LBS. Constructed of heavy-duty, 1" wide, DuPont Nylon webbing that stretches 25% to take up shocks for smooth, safe towing. Oil, grease and water resistant too! Dual, self-aligning clip attaches to any bumper. Shpg. wt., 1 3/4 lbs.

11 R 24023

Net 3.95

MAP MEASURER & COMPASS

Just trace along route on map and multiply miles per inch factor by reading on dial. Reads directly in inches up to 39". Built-in magnetic compass has cardinal and secondary points—full 360° markings in tenths. With leather sheath. Imported.

13 R 41015 Shpg. wt., 4 oz. ... Net 2.19

CAR VACUUM CLEANER

4⁹⁵

- Plugs into Cigarette Lighter Outlet



Portable and powerful! Cleans upholstery, carpeting, ashtrays, under mouldings. Picks up dust, dirt and lint into a removable container. Designed to give trouble-free service. Complete with two attachments—a utility pick-up and a long nozzle to reach hard to get at places. Supplied with handy 15' Power Cord. Power source: 12V, DC. Imported.

11 R 67519 Shpg. wt., 1 1/2 lbs.

Net 4.95

BonAire® SUPER POWER AUTO VACUUM CLEANER

9⁹⁵

Made in U.S.A.



- Super Power Suction
- Plugs Into Cigarette Lighter Socket

A smart portable accessory for every car owner. Super power suction cleans in seconds. Specially designed nozzle gives easy access to hard to get at places such as under seats, ash trays, and in crevices. Its lightweight, and durable rust and dent proof construction make this fine unit ideal for boats, planes, trailers, and tents also. Easy to handle and well balanced. Operates off standard 12V DC car battery. Plugs right into the cigarette lighter socket. Size: 17" long x 4" wide. Shpg. wt., 2 3/4 lbs.


11 R 22506

Net 9.95

DUO-VOLT® 12 VOLT and 110 VOLT HAND VACUUM CLEANER

22⁵⁰

- With Crevice Tool, Upholstery Nozzle-Dusting Brush



Compact, yet extremely powerful portable hand vacuum cleaner eliminates the need for separate house vacuum and car vacuum. In the house, plugs into 110 VAC, 60 Hz., and in the car plugs into 12V DC cigarette lighter outlet with supplied adapter. Durable steel body—yet remarkably lightweight. Long-reach, heavy-duty cord. Ideal for auto, home, office, boat, or workshop. "Toss-away" bags for easy disposal. Convenient handle. On/off switch. With wide "Pick-all" nozzle, dusting brush, and crevice tool. Decorator colors. Shpg. wt., 3 1/2 lbs.

11 R 67527

Net 22.50

25-FT. 12 VOLT TROUBLE LAMP

- Complete With 50 Watt Bulb

An all purpose emergency light for shop, garage or "on-the-road" use. 12-volt light taps directly from battery of cars, trucks or boats. Color coded alligator clips, yellow cord. Complete with bright 50 watt bulb. Shpg. wt., 2 1/2 lbs.

12 R 44516

Net 2.95

Replacement Bulb

12 R 44524

Net .95



ACME TIRE PRESSURE GAUGE

1⁹⁵

Accurate mechanic-quality pencil-type gauge. Triple chrome plated finish. 4-sided nylon indicator bar calibrated from 5-50 lbs. in one lb. units. Spring tip holds gauge in pocket. Built-in deflator tip.

11 R 30509 Shpg. wt., 6 oz. ... Net 1.88

Chambron

Liftmaster™ Garage Door Openers



Motor Control
139⁹⁵
 No Money Down*

ECONOMY GARAGE DOOR OPENER

• 1/4 HP Motor—For Doors Up To 16 Ft.
 Solid-state garage door opener. No need to get in and out of car in bad weather. Eliminate the physical strain of manual opening and closing. Easily and quickly installed on existing door. Adapts to single or double; sectional or 1-piece; wood, metal, or fiber-glass door. Up to 175 lbs. of pulling force; enough to handle most garage doors. Needs only 1½" Headroom between door and ceiling. Garage light is turned on when door is opened; remains on two minutes after door is closed for you to leave garage in safety. Wall mounted receiver with pushbutton for instant stopping, opening or closing door from the inside. Door automatically stops when it hits an object. Streamlined motor housing provides protection against dust and moisture. For 117 VAC, 60 Hz. UL listed. Shpg. wt. 55 lbs.
13 R 82175WX Net 139.95
 See Listing of Accessories Below



No Need To Get Out Of Car
 Door Opens Automatically

- With Exclusive "Velvet Glide"
- Gear-Head Chain Drive
- Opens—Closes—Securely Locks Garage Door
- Automatically Controls Garage Door and Lights from Inside Your Car
- Fully Transistorized Transmitter and Receiver with Private Tone Coding
- Operates 1-Piece or Sectional Doors



Receiver
 Transmitter
169⁹⁵
 No Money Down* Motor Control

DELUXE HEAVY DUTY GARAGE DOOR OPENER

• 1/3 HP Motor—For Doors Up To 22 Ft.
 Deluxe garage door operating system. Easily handles any residential, track guided garage door; metal, fiberglass or wood doors up to 22 ft. wide and 8 ft. high. Only your tone coded transmitter can open the door. Gear-head chain drive motor exerts 200 lbs. of push-pull force. Needs only 1½" of headroom space between high arc of door and ceiling. Fully automatic. Built-in light goes on as soon as door starts to open and stays on for approximately two minutes after door closes. If door hits obstruction, it stops automatically. Safety clutch prevents damage. When started again, it will reverse itself. Transmitter can be carried in pocket, kept in glove compartment, clipped to sun visor or mounted under dash. Motor operates on 117 VAC, 60 Hz. UL listed. Shpg. wt., 65 lbs.
13 R 82183WX Net 169.95
 See Listing of Accessories Below.

ACCESSORIES

Extra transmitter for second car.
13 R 82159 Shpg. wt., ¾ lb. Net 23.95
 Key Switch for outdoor operation, with 2 keys.
13 R 82043 Shpg. wt., ½ lb. Net 4.95

Outside quick release lock. Used to open door from outside when electricity fails. Shpg. wt., 8 oz.
13 R 82134 Net 5.49
13 R 82142 16 oz. Dry Spray Silicone Spray Lube Net 2.50

RADIO CONTROLS FOR ANY DOOR OPENER

- Transistorized Tone Coded Receiver and Transmitter
- Up-date or Convert Any Electronically Operated Garage Door Opener to Operate from Your Car

System consists of two units, a transistorized radio Tone Coded Transmitter and receiver. Operates any electrically controlled door opener up to 100 feet away. Tone modulation circuitry gives you complete security;


only your personal, pocket size Tone Coded Transmitter can trigger the receiver. Installs in minutes. Shpg. wt., 1¼ lbs.

13 R 82167 Net 59.95

59⁹⁵

No Money Down*

Radio Control for Any Door Opener.



Receiver

Transmitter

RADAR ALERT

- Warns of Traffic Zones!



- Miniature and Completely Transistorized
- Gives Advance Warning



Radar alert wired—miniature electronic detector gives an audible warning whenever it intercepts a radar beam. Dual-Band circuit detects all commonly used police radar speed meters and traffic control devices, both vertically and horizontally polarized, to promote safer driving. Miniaturized and completely transistorized. Top quality components; printed wiring; 8 transistors; two 1,000 hour mercury cell, self-testing batteries (equivalent to 35,000 miles of driving at 35 M.P.H.) Magnesium case eliminates radio, TV and other interference.

Weights only 13 ozs., measures 3¼x2¼x3¼"D; clips to sunvisor. Complete with batteries, sunvisor clip. Instructions included. Shpg. wt., 1½ lbs.

13 R 42017 No Money Down* Net 31.95

RADAR ALERT KIT. Same as above in kit form.

13 R 42462 Net 23.95

This item not intended for resale in States where its use is forbidden in motor vehicles by public regulation.

KIT
23⁹⁵

WIRED
31⁹⁵

Complete With Long Life Mercury Batteries

- Clips Easily on Sunvisor
- Rugged Printed Circuit

Books About IC's—Transistors—Tubes

TRANSISTOR CIRCUITS

By Rufus P. Turner
OVER 150 PRACTICAL
CIRCUITS



SOME OF THE HIGHLIGHTS
• Audio Amplifiers • RF and
IF Amplifiers • Radio Re-
ceivers • Triggers and
Switches • Control Devices
• Test Instruments • Mis-
cellaneous Circuits

GERNSBACK No. 63. Takes transistors out of the lab and puts them on the work bench. Over 150 practical circuits for amplifiers, oscillators, power supplies, amateur equipment and other units. All were designed by experts—some by the author himself. All were tested in the author's laboratory—and all of them work! No watering down with transistor testing or theoretical explanation circuits! Shpg. wt., 9 oz. Net 3.95
10 R 41011

SEMICONDUCTOR HANDBOOK (Sams 20520). A modern, complete sourcebook for industrial semiconductor data in one comprehensive, heavily illustrated volume. Covers a wide variety of the latest circuitry applications including grown-junction, alloyed-junction, drift MDT, mesa, planar and epitaxial mesa types, 288 pages. Shpg. wt., 14 oz. Net 5.75
10 R 23936

TRANSISTOR PROJECTS Gernsback No. 89. The best practical transistorized projects for building many types of radios, test equipment and other electronic gear, selected from Radio-Electronics magazine. Each one debugged and tested. 160 pages. Net 2.95
10 R 41045 Shpg. wt., 10 oz.

BASIC THEORY AND APPLICATION OF TRANSISTORS. DOVER. Prepared by U.S. Army. Requires only minimal knowledge of physics and theory of electron tubes. Covers crystal semi-conductors, function of transistors, applications and construction; structure of matter, characteristics of crystals, PN junctions, amplifier fundamentals, parameters and transistor analysis. 272 pages. Net 1.75
10 R 31202 Shpg. wt., 16 oz.

103 SIMPLE TRANSISTOR PROJECTS by Thomas S. Kneitel, Rider No. 0313. 103 fascinating experiments of transistors and semiconductor circuits. Gives detailed explanation of steps that may not be familiar to some experimenters. Each experiment gives purpose, schematic diagram and complete parts list. 128 pages. Net 3.45
10 R 10024 Shpg. wt., 9 oz.

TRANSISTOR BASICS: A SHORT COURSE by George C. Stanley, Jr. (No. 5819). Provides a fast way to gain a practical understanding of transistors. An excellent introduction to transistor principles, circuit analysis, applications and troubleshooting techniques. Simplified approach will enable the reader to determine desired circuit values with an accuracy adequate to almost any practical situation. 102 pages. 5 1/2" x 8 1/4". Softbound. Net 3.35
10 R 11964 Shpg. wt., 7 oz.

SOLID STATE POWER SUPPLIES AND CONVERTERS. (Sams 20310) by Allan Lytel. A complete guide to building advanced solid-state power supplies for longer life and smaller size. 112 pages. Shpg. wt., 7 oz. Net 2.95
10 R 23241

UNDERSTANDING AND USING UNIJUNCTION TRANSISTORS (Sams 20720) by Stu Hoberman. Details the construction, operation, characteristics and applications of the unijunction transistor (UJT). Includes timing, triggering and sensing circuits, oscillators, power-controlling devices, counters, and computer memory systems. 96 pages. Net 2.50
10 R 23944 Shpg. wt., 6 oz.



50 IC PROJECTS YOU CAN BUILD

by Ronald M. Benray

Providing a selection of practical, inexpensive author-invented projects that can be built in an evening or two and demonstrate the new technology of integrated circuits, this book is of special interest to electronic hobbyists. Projects cover a wide spectrum including an intercom, exposure timer, and a lie detector. 128 pages.

10 R 12780 Shpg. wt., 9 oz. Net 3.75

FUNDAMENTALS OF INTEGRATED CIRCUITS Hayden (5695) by L. Stern. A complete guide to integrated circuits—their theory, manufacture, and application. Presents basic approaches to IC electronics and practical circuit design. Discusses thin-film, monolithic and hybrid IC circuits, layout, and packaging principles. 208 pages, 7 x 10". Clothbound. Shpg. wt., 1 lb. 9 oz. Net 8.95
10 R 12509

TRANSISTOR FUNDAMENTALS by Training & Retraining, Inc. A four volume carefully planned, programmed course in semiconductor theory and circuitry. Progress self-checked by the reader via summary questions and tests.

Sams Publications

Vol. 1. Basic Semiconductor and Circuit Principles. 240 pages.

10 R 24090 Shpg. wt., 13 oz. Net 4.50

Vol. 2. Basic Transistor Circuits. 200 pages.

10 R 24108 Shpg. wt., 12 oz. Net 4.50

Vol. 3. Electronic Equipment Circuits. 192 pages.

10 R 24116 Shpg. wt., 11 oz. Net 4.50

Vol. 4. Digital and Special Circuits. 208 pages.

10 R 24124 Shpg. wt., 12 oz. Net 4.50

All four volumes in slipcase.

10 R 24132 Wt., 3 lbs., 4 oz. Net 15.95

TRANSISTOR FUNDAMENTALS WORKBOOK. Practical applications of theory fundamentals above. 264 pages.

10 R 24140 Shpg. wt., 15 oz. Net 4.50

FET CIRCUITS Sams (20585) by Rufus P. Turner. Explains the principles of construction and operation of field-effect transistors. Stresses the application of FET's in practical amplifier, oscillator, receiver, control, and test instrument circuitry. 160 pgs. Net 3.95
10 R 23662 Shpg. wt., 8 oz.

TRANSISTOR SUBSTITUTION HANDBOOK, 11th Edition. (No. 20835). By the Howard W. Sams Engineering Staff. Updated guide lists over 100,000 substitutions. Tells how and when to use substitute transistors. Also includes manufacturers recommendations for using popular replacement transistor lines. Easy to use format—no doublechecking necessary. 160 pages.

10 R 24165 Shpg. wt., 7 oz. Net 2.25

TRANSISTOR SPECIFICATIONS MANUAL 4th Edition. (Sams 20788). Contains the electrical and physical parameters for virtually all of the transistors now in use. Provides physical data, dimensions and other information required to install the unit; identifies leads and terminals for each transistor. 288 pages.

10 R 22524 Shpg. wt., 14 oz. Net 4.50

PINPOINT TRANSISTOR TROUBLES IN 12 MINUTES (No. 430). By Louis E. Garner, Jr. A virtual library of practical data of value to everyone who works with transistor circuits. Experienced technicians will find it one of the most valuable references ever published on servicing all types of transistor circuits. A quick-reference table tells exactly where to find appropriate troubleshooting charts and service procedures for practically every type of transistorized device. 495 pages, 243 illus. Shpg. wt., 1 1/2 lbs. Net 5.95
10 R 41813

RCA LINEAR INTEGRATED CIRCUIT FUNDAMENTALS

(IC-41) Provides an understanding of basic principles involved in design and application of linear integrated circuits. Covers general considerations, differential and operational amplifiers, transfer characteristics, equivalent circuit models, frequency response, phase compensation and circuit applications for communications, TV, radio, instrumentation, telemetry, data-processing and control. 350 pages. Shpg. wt., 1 1/4 lbs. Net 2.00
10 R 47075

GE TRANSISTOR MANUAL (7th edition). Expanded "Reader's List" of basic reference works on transistor theory and application; new chapter explaining transistor reliability, expanded and up-dated comparison charts, outline drawings, over 1200 JEDEC types. New experimenter's chapter with 17 circuits for building; expanded hi-fi chapters; expanded radio receiver chapter; and a complete explanation on how to interpret a spec sheet. 660 pages. Net 2.00
10 R 36201 Shpg. wt., 2 lbs.

GE SCR MANUAL. Complete data on silicon-controlled rectifiers. Includes SCR basic theory, ratings and applications. Covers regulating circuits and controls, test circuits, light-actuated devices, trigger and turn-off circuits. New information and applications for triacs and thyristors. Illustrated. 530 pages. Soft-bound. Shpg. wt., 1 lb. Net 3.00
10 R 36235

RCA TRANSISTOR, THYRISTOR AND DIODE MANUAL (5C-14). A comprehensive manual covering basic technology, operating principles, characteristics and ratings, applications and testing data for more than 770 semiconductor devices. 656 pages. Net 2.50
10 R 47042 Shpg. wt., 1 1/4 lbs.

RCA POWER CIRCUITS MANUAL (SP-21). Provides information for a broad range of power circuits using silicon transistors, rectifiers, thyristors and triacs. Discusses applications for rectification, filtering, power conversion and regulation, and control in both RF power and low frequency amplifiers. 448 pages. Shpg. wt., 1 1/2 lbs. Net 2.00
10 R 47083

TRANSISTORS—THEORY AND PRACTICE (No. 75). By Rufus P. Turner. New revised edition of this famous handbook. Covers semiconductor theory, transistor characteristics, equivalent circuits, transistor amplifiers, transistor oscillators, quality in transistor circuit design, triggers and switches, practical transistor circuit, tests and measurements, related devices, care and handling of transistors. 160 pages. Shpg. wt., 8 oz. Net 3.95
10 R 418C5

BOOKS ABOUT TUBES

RCA RECEIVING TUBE MANUAL RC-28. Contains complete technical data on all current tubes. Features tube theory written for the layman, application information and a circuit section. Tuner, receiver, amplifier, intercom and other circuit diagrams, socket diagrams, tube dimension drawings, resistance-coupled amplifier data, tube curves, etc. 672 pages. Net 2.00
10 R 47018 Shpg. wt., 1 1/4 lbs.

RCA RADIOFRON DESIGNERS HANDBOOK, 4th Ed. A comprehensive reference book for design and application of radio receivers and audio amplifier circuitry. 1000 illustrations and cross-reference index on 7000 items. 1500 pages. 5 1/2" x 8 3/4". Net 7.00
10 R 47026 Shpg. wt., 4 1/2 lbs.

As New Books are Released by Publishers, Lafayette Will Stock Them

Color TV Publications

SAMS COLOR TV BOOKS

COLOR TV TRAINING MANUAL (20736), 3rd Edition. Comprehensive manual to train the technician in servicing Color TV. Describes science of color requirements and makeup of composite color signal, servicing procedures. Outlines use of color test equipment. Illus. 240 pgs., 8½x11". Shpg. wt., 1 lb., 12 oz. Net 6.95
10 R 21286

SYMFAC GUIDE TO COLOR-TV SERVICING (20710) by PF Reporter Editorial Staff. A quick guide to better and faster color-TV servicing using observation and correct analysis of the picture on the screen to reveal which section of the set is faulty. Symptom analysis, waveform, voltage and component analysis for every trouble situation. 128 pages. Shpg. wt., 7 oz. Net 3.95
10 R 23969

TRANSISTOR COLOR-TV SERVICING GUIDE (20693) by Robert G. Middleton. Fills a definite need for servicing literature. Functionally divided according to sections in the transistor color-TV receiver and further subdivided according to symptoms. 8½x11", 112 pages. Shpg. wt., 11 oz. Net 4.50
10 R 23977

COLOR TV WAVEFORM ANALYSIS (20763) by Robert G. Middleton. A comprehensive presentation of waveform analysis as an analytical tool for efficient servicing of color TV. Practical application to RF, IF, video amplifier, color sync, demodulator, matrix and keyed-clamped DC-restorer circuits. 125 pages. Shpg. wt., 9 oz. Net 3.50
10 R 24173

COLOR TV SERVICING GUIDE (20358) by Robert G. Middleton. Follows the same picture-tube-and-trouble symptom format so successful in black and white TV servicing guides, showing how to apply fast troubleshooting procedures based on analysis of symptoms. Includes many full-color picture tube photos illustrating various operating troubles with concise explanations of probable causes and diagnosing procedures. 8½x11", 112 pages. Shpg. wt., 12 oz. Net 4.25
10 R 23159

KNOW YOUR COLOR-TV TEST EQUIPMENT SAMS (20256) by Robert G. Middleton. Written for the TV technician, this book explains the instrument function and circuit action in simple, easily followed terms. It shows how to service, maintain, and calibrate this equipment for continuing reliable performance. Numerous troubleshooting approaches are given in detail and tied in with symptoms of defective operation. 160 pages. Shpg. wt., 10 oz. Net 3.50
10 R 24298

COLOR TV SERVICING MADE EASY, NO. VOL. 1 (20155) by Wayne Lemons and Carl Babcock. Practical, service and set-up procedures explained. Covers all major color receivers from 1957 to 1964. Contains authoritative information on troubleshooting, adjustments providing the benefit of experience gained through actual service work on thousands of receivers. 192 pgs. 5½x8½". Shpg. wt., 10 oz. Net 3.95
10 R 21302

COLOR TV SERVICING MADE EASY VOL. 2 (20523) Brings you up-to-date on new color circuitry and developments since Volume 1. 288 pages. Shpg. wt., 12 oz. Net 4.95
10 R 23605

SELECTED PUBLISHERS

PRACTICAL COLOR TV SERVICING TECHNIQUES (GL/TAB No. 436) by R. L. Goodman. Shows simplified methods of servicing old and new color receivers, from antenna terminals to CRT. Includes portable and solid state TV, with full color illustrations, case histories and service instrument techniques. 297 pages. Net 5.95
10 R 41599 Shpg. wt., 15 oz.

COLOR TV REPAIR (Gernsback No. 123) by 10 Servicing Experts. A staff of 10 top technicians tells how to fix color TV receivers. Each trouble symptom is described in detail, and the perfect solution provided. Includes tips on how to pinpoint the defective color section quickly and describes unexpected causes of TV color failure. 100 pages, softbound. Shpg. wt., 7 oz. Net 2.95
10 R 41532

A NEW WAY TO SERVICE COLOR TV (Gernsback No. 136) by Carl Babcock. The serviceman author emphasizes the practical aspects of trouble-shooting and repairing the difficult-to-fix color TV sets, steering clear of the complex theory. The principal approach is visual examination. A few measurements pinpoint the trouble to definite components. 192 pages. Shpg. wt., 12 oz. Net 3.95
10 R 41581

COLOR TV FACTBOOK: Problems and Solutions (GL/TAB No. 519) by Editors, Electronic Technician. A guide to color TV troubles and solutions arranged by manufacturer and model. Includes repetitive troubles, field-factory changes, special adjustments and pertinent service information. 176 pages. Shpg. wt., 10 oz. Net 2.95
10 R 41748

CITIZENS BAND & 2-WAY RADIO BOOKS

99 WAYS TO IMPROVE YOUR CB RADIO

by Len Buckwalter



(Sams 20515) Tells how to operate, service and maintain CB equipment in top condition and get most use from it. Gives 99 down-to-earth highly useful hints that will prove invaluable to anyone interested in CB activity. 128 pp. Net 2.95
10 R 23597 Shpg. wt., 9 oz.

CITIZENS BAND RADIO HANDBOOK (4th Ed. Sams 20839), by David E. Hicks. Completely revised and updated. Discusses the various types of equipment, how to choose to fit your specific needs, and your licenses. Covers CB equipment, circuits, antennas, fixed and mobile installations, maintenance, repairs, measurements, and operating procedures. 192 pages. 5½x8½". Shpg. wt., 9 oz. Net 4.95
10 R 23613

ABC'S OF CITIZENS BAND RADIO Sams (20019), by Len Buckwalter. Explains the functions, operation, regulations, and setup and operating procedures. The book explains how to obtain an FCC license and how to efficiently set up and operate CB radio equipment. 96 pages. 5½x8½". Shpg. wt., 6 oz. Net 2.50
10 R 23266

CB RADIO ANTENNAS 2nd Ed. Sams (20567), by David E. Hicks. Thoroughly explains selection, installation, operation and servicing CB antennas for those who wish to buy or improve the performance of their CB gear. 144 pages. Shpg. wt., 8 oz. Net 3.50
10 R 23621

CB RADIO CONSTRUCTION PROJECTS Sams (20099), by Len Buckwalter. Complete step-by-step details for building inexpensive CB devices, accessories and test instruments to help CB operators get full efficiency from equipment. Field-tested, do not conflict with FCC Regulations. 112 pages. Net 3.95
10 R 23233 Shpg. wt., 9 oz.

UHF BUSINESS RADIO HANDBOOK

by Leo G. Sands

Sams (20088). Covers all aspects of Business Radio Service and UHF Radio communications systems. Describes its purpose, types of equipment, operation, UHF mobile and fixed stations, relay stations, antenna systems, servicing and FCC regulations. Complete guide in this fast growing field. 192 pages. Shpg. wt., 10 oz. Net 3.95
10 R 23175

101 QUESTIONS & ANSWERS ABOUT CB OPERATIONS Sams (20640) by Leo G. Sands. Handy reference source of answers to questions about CB radio. Each of four parts contains pertinent information on one generalized area of CB radio operations, including questions and answers about the four classes of CB radio and their permissible uses, licensing and FCC rules, operating procedures, and information about the selection of CB equipment. 96 pages. Shpg. wt., 6 oz. Net 2.50
10 R 24306

CB RADIO SERVICING GUIDE 2nd Edition Sams (20722), by Leo G. Sands. A practical "how-to" guide for locating all types of CB troubles. Gives detailed procedures for tuning up, testing, and trouble-shooting. Explains FCC regulations. Covers both single and multichannel receivers and transmitters. Step-by-step analyses of transmitter circuits. Trouble-shooting procedures aimed at rapid solutions. 160 pages. 5½x8½". Net 3.95
10 R 22094 Shpg. wt., 9 oz.

MOBILE RADIO SYSTEMS PLANNING (Sams 20780) by Leo G. Sands. Basic information about types of mobile radio systems; how they work, their capabilities and limitations, licenses, channels, band and frequency selections, choice of equipment, antenna systems, accessories, etc. 144 pages. Shpg. wt., 9 oz. Net 4.50
10 R 24191

ANTENNAS FOR CITIZENS RADIO SERVICE (Radio Publications) Features build-it-yourself antennas for the Citizens Radio Service with easy-to-follow construction information for efficient low-cost antennas. Net 3.95
10 R 50020 Shpg. wt., 4 oz.

PRACTICAL CB RADIO SERVICING

by Freeland and Sands (Mayden/Rider 0777).

A useful, well-organized and complete practical guide for servicing CB and two-way radio equipment. Covers operational checks, measurements, noise and interference and trouble-shooting receiver and transmitter. 192 pages. Net 5.25
10 R 12772 Shpg. wt., 10 oz.

CBer's HOW-TO-BOOK (No. 0718) by Leo G. Sands. A complete guide for selecting, installing, operating, testing, repairing and modifying CB equipment. Includes information on mobile unit and base station features, walkie-talkies and phone patches. A fully illustrated all-points guide with tables for all CB Codes and Channels. 128 pages. Shpg. wt., 9 oz. Net 3.50
10 R 12087

CB RADIO OPERATORS GUIDE (GL/TAB No. 499) by Robert M. Brown. A virtual CBer's bible. Includes buying base and mobile station equipment, installation, antennas, improvements, trouble-shooting, emergency assistance, etc. 192 pages. Softbound. Net 3.95
10 R 41680 Shpg. wt., 9 oz.

101 EASY CB PROJECTS (Sams 20663) by Robert M. Brown. A collection of simple, inexpensive yet practical CB radio equipment and accessories. Each easy-to-build device is a useful addition to any CB radio operator's gear. Complete description, parts list, and instructions for each construction project. 128 pages. Shpg. wt., 6 oz. Net 3.25
10 R 23993

ELIMINATING ENGINE INTERFERENCE Sams (20184), by John D. Lenk. Explains the "why" of engine interference with CB, amateur and Marine communications and the solution to this serious problem by noise-suppression, shielding and modifying equipment. 112 pages. Shpg. wt., 6 oz. Net 2.75
10 R 23217

Books About Amateur Radio



AMERICAN RADIO RELAY LEAGUE BOOKS

AMECO BOOKS

RADIO AMATEUR'S HANDBOOK. Latest edition used all over the world by both hams and professionals. Packed with theory and practical design, information on station equipment, audio and RF circuits, HF, VHF, and UHF, phone and C.W., receivers, transmitters, antennas, mobile equipment etc. 6 1/2 x 9 1/2". 10 R 89010 Wt., 2 1/4 lbs. Net 4.50

A COURSE IN RADIO FUNDAMENTALS. A study guide keyed to the Amateur's Handbook. Describes numerous experiments for easy understanding. Complete with questions and answers after each chapter. 103 pages. 10 R 89051 Shpg. wt., 10 oz. Net 1.00

MOBILE MANUAL FOR AMATEURS. Contains articles selected from QST magazine. Covers all aspects of mobile operation, including converters, receivers, transmitters, power supplies and antennas. 272 pages, illustrated. Shpg. wt., 1 lb., 1 oz. 10 R 89028 Net 2.50

ANTENNA BOOK. Gives antenna and transmission line theory, plus instructions for building amateur antennas for all bands from 160 meters up into the UHF regions. 330 pages. Shpg. wt., 1 lb. 6 oz. 10 R 89036 Net 2.50

RADIO AMATEUR'S VHF MANUAL. A thorough treatment of VHF with authentic VHF history. Covers receiving and transmitting principles, techniques and construction; antenna and feed system design; microwaves; test equipment; interference; VHF hints and kinks. Emphasis is on tried and tested equipment and practice. 6 1/2 x 9 1/2". 360 pages. 10 R 89184 Wt., 1 lb. 6 oz. Net 2.50

EDITORS AND ENGINEERS

RADIO HANDBOOK (No. 2420). 18th Edition. Tells how to design, build and operate the latest types of amateur transmitters, receivers and associated gear. Provides extensive simplified theory on almost every phase of radio practice, specifically written for the amateur, technician and engineer. Broadest reference coverage, up-to-date original data. 6 1/2 x 9 1/4". 896 pages. Hardbound. Shpg. wt., 3 lbs. 10 R 24017 Net 13.50

RADIO AMATEUR CALLBOOKS

RADIO AMATEUR CALL BOOK—UNITED STATES SECTION. Lists all (over 286,000) licensed amateurs in the United States, possessions and personnel in foreign countries with their call letters and addresses. Published quarterly. Latest edition will be shipped. 9 x 12". 10 R 50095 Wt., 2 lbs. 6 oz. Net 8.95

FOREIGN RADIO AMATEUR CALL BOOK. Covers all countries outside of 50 United States. Over 179,000 calls. Published quarterly. Latest edition will be shipped. 10 R 50103 Shpg. wt., 2 lbs. Net 6.95

RADIO AMATEUR DX GUIDE. The guide manual for DX enthusiasts. Features a listing of foreign prefixes, great circle maps, section map, time conversion charts, contest and field day log, world-wide postal information, great circle bearing tables and other information invaluable to the amateur. 10 R 50137 Shpg. wt., 10 oz. Net 2.00

UNDERSTANDING AMATEUR RADIO. Written for the beginner. Simply explains the elementary principles of electronic and radio circuits, transmitters, receivers and antennas. A must in setting up and operating the amateur station. 6 1/2 x 9 1/4". 320 pages. Shpg. wt., 1 1/4 lbs. 10 R 89192 Net 2.50

RADIO AMATEUR'S LICENSE MANUAL. Prepares for FCC exams for Novice, Technician, Conditional, General, Advanced and Extra Class ham license. Typical exam questions are answered. Contains study materials and complete regulations. 120 pages. 10 R 89085 Shpg. wt., 9 oz. Net 1.00

GATEWAY TO AMATEUR RADIO. Set of 4 books for all hams. In addition to "Radio Amateur's License Manual" above, contains "How to Become a Radio Amateur," "Learning the Radio-Telegraph Code," and "Operating an Amateur Radio Station." Everything needed to get started in ham radio. 10 R 89119 Wt., 1 lb. 5 oz. Net 2.50

SINGLE SIDEBAND FOR THE RADIO AMATEUR. A selection of the best SSB articles appearing in QST magazine. Thoroughly discusses the theory and practical methods of this popular new development. Shows how to build the needed equipment. 253 pages. 10 R 89069 Shpg. wt., 15 oz. Net 3.00

AMATEUR RADIO MAP OF THE WORLD. Made especially for amateur radio, this map shows distances, call prefixes for different countries and other required information. 30x40". 10 R 89127 Shpg. wt., 15 oz. Net 2.00

AMATEUR STATION LOG BOOK. Convenient amateur radio log book, with list of Q signals. Spiral bound. Shpg. wt., 10 oz. 10 R 89135 Net 1.50

RADIO PUBLICATIONS

BEAM ANTENNA HANDBOOK. By William I. Orr. 4th edition. Covers the construction, installation, and evaluation of rotary beam antennas. New, simplified designs using easily obtainable materials are given. Full dimensional charts are given for the 6, 10, 11, 15, 20 and 40 meter bands! All you need to know about beams. 200 pages. 10 R 50079 Shpg. wt., 13 oz. Net 4.95

BETTER SHORTWAVE RECEPTION. By William I. Orr. 2nd edition. Covers the exciting field of shortwave radio for the SWL and the radio amateur. The mysteries of shortwave transmission and reception explained in simple language. Jam-packed with data and such useful information as "do-it-yourself" radio projects, DX tuning hints, international broadcasting, etc. 156 pages. 10 R 50061 Shpg. wt., 10 oz. Net 3.95

CUBICAL QUAD ANTENNAS. By William I. Orr. 2nd Edition. Handbook of quad assembly and data. X-Q high gain, 7 MHz and 50 MHz quads. Tri-Gamma 3 band single feed. Gains, front/back, patterns. Simplified and improved construction. 112 pages. Shpg. wt., 8 oz. 10 R 50038 Net 3.95

WORLD RADIO TV HANDBOOK 1970. Contains details on every short-wave and TV station throughout the world. Each station identified by call, frequency, station personnel, address, power, programs and language, license fee, identification signals and network affiliation. 340 pgs. Imported. 10 R 12012 Wt., 1 lb., 6 oz. Net 6.95

AMATEUR RADIO THEORY COURSE (No. 102-01). Complete home study theory course covering Novice, Technician, conditional and general classes. Almost 400 typical F.C.C. questions to help prepare for exams. 6 x 8 1/2". 300 pages. Shpg. wt., 14 oz. 10 R 57041 Net 4.50

COMMERCIAL OPERATOR'S Q & A LICENSE GUIDE. These books cover the exam material for F.C.C. licenses. Includes questions and simplified answers and a sample F.C.C. type examination.

ELEMENTS 1, 2 & 9 (No. 8-01). Covers third class radio-telegraph and radio-telephone exam. 48 pages. Shpg. wt., 5 oz. 10 R 57066 Net 7.75

ELEMENT 3 (No. 9-01). This element plus elements 1 and 2 above. Covers the 2nd Class Radio-Telephone License. 160 pages. 10 R 57116 Shpg. wt., 11 oz. Net 2.25

ELEMENT 4 (No. 10-01). This element plus elements 1, 2, and 3 above. Covers the 1st Class Radio-Telephone License. 80 pages. 10 R 57124 Shpg. wt., 6 oz. Net 1.50

HOWARD W. SAMS

SHORT-WAVE LISTENER'S GUIDE (20798) 4th Edition by H. C. Woodruff. All the important and available information on International Broadcast Stations useful to the SWL. 104 pages. Shpg. wt., 7 oz. 10 R 22490 Net 2.95

FIRST-CLASS RADIOTELEPHONE LICENSE HANDBOOK (20804) by Edward M. Noll. Completely revised and updated. Contains questions and answers based on revised FCC element 4, needed to qualify for a 1st class license. Also provides essential knowledge required by communications engineer. 416 pages. Shpg. wt., 1 1/4 lbs. 10 R 23050 Net 6.50

ABC'S OF SHORT-WAVE LISTENING (20797) by Len Buckwalter 3rd Ed. Introduction to the exciting world of short-wave radio. Covers international, amateur, police, emergency, aircraft, ships-at-sea, and even orbiting satellite communications. Discusses receivers and antennas. 96 pages. Shpg. wt., 7 oz. 10 R 23514 Net 2.95

QUESTIONS & ANSWERS ON SHORT-WAVE LISTENING (No. 20783) by H. C. Woodruff. Contains 80 of the most often asked questions about short-wave listening—and their answers. Covers frequency allocations, international broadcasting in general, reception, receivers and their controls. Shpg. wt., 5 oz. 10 R 24256 Net 3.50

SECOND-CLASS RADIOTELEPHONE LICENSE HANDBOOK (20824) by Edward M. Noll. New 4th edition. Complete study course for elements I, II and III of latest FCC exams. Prepares you for license needed for communications and 2-way radio work. 336 pages. Shpg. wt., 14 oz. 10 R 24249 Net 5.95

SHORTWAVE LISTENING

SHORTWAVE VOICES OF THE WORLD by Richard E. Wood. Covers every aspect of international shortwave broadcasting. Emphasizes how to obtain QSL card verification from foreign broadcasters. Details when to listen for best overseas reception. 100 pgs. 10 R 14000 Shpg. wt., 9 oz. Net 3.95

As New Books are Released by Publishers, Lafayette Will Stock Them

Hayden/Rider Publications

TELEVISION AND SERVICING

HOW TO SELECT AND INSTALL ANTENNAS (No. 0786) by Lon Cantor. A unique guide covering all aspects of antenna selection and installation for color, and black and white TV, FM stereo, UHF, VHF, or complete master TV systems — mechanical as well as electronic. Includes special consideration of local, fringe and near fringe area problems. 112 pages. Shpg. wt., 7 oz.
10 R 12038 Net 3.95

FUNDAMENTALS OF TELEVISION (No. 0391). By Walter H. Buchsbaum. Provides a complete and modern course in television theory, operation, and servicing. Emphasis is placed on understanding essential working principles; mathematics is held to an absolute minimum. The key circuits are explained with practical troubleshooting procedures. 291 pages 6x9". Softbound.
10 R 11808 Shpg. wt., 1 1/4 lbs. Net 5.95

HOW TO TROUBLESHOOT A TV RECEIVER (No. 0152, 2nd Ed.). By J. Richard Johnson. Step-by-step guide tells where to start and how to continue in trouble-shooting all TV receivers. Discusses tools, equipment and accessories, preliminary observations and checks, use of test patterns and cross-hatch patterns, tubes, controls, sound troubles, etc. Softcover, 5 1/2 x 8 1/2", 128 pages.
10 R 10198 Shpg. wt., 9 oz. Net 4.25

1971 TUBE CADDY-TUBE SUBSTITUTION GUIDE (0802) by H. A. Middleton. Eight comprehensive sections listing over 15,000 direct substitutions, including the latest tubes. Covers foreign picture tubes on the American TV market. This year's edition of the Tube Caddy is bigger and easier to use. 140 pages. 4 1/4 x 5 7/8". Shpg. wt., 5 oz.
10 R 11915 Net 1.59

BASIC TELEVISION by Dr. A. Schure, Ph.D., D. Ed. A "picture book" course in the fundamentals of TV written in non-technical language so that anyone having a knowledge of radio can master TV in easy to learn, simplified steps. Teaches everything about TV theory and circuitry with a minimum of mathematics. 450 original illustrations, which make each idea completely understandable, are a feature of this series. The course is broken down into 5 volumes, and systematically covers every portion of the subject.
Vols. 1-5 Complete Set—(No. 0082).
10 R 10396 Shpg. wt., 2 1/2 lbs. Net 18.75

TV TROUBLE SHOOTING AND REPAIR (No. 0296—2nd ed.). By Robert G. Middleton. Newly revised and updated edition. Bridges the gap between "theory" and "hardware" treatment to cope with the real problems in repairing TV malfunctions. Each chapter is complete with itself. 216 pages, 5 1/2 x 8 1/2".
10 R 10214 Shpg. wt., 11 oz. Net 4.75

BOOKS ON AUDIO, HI-FI, RECORDERS

HI-FI LOUSPEAKERS AND ENCLOSURES. (No. 0721, 2nd Edition) by Abraham Cohen. This classic in hi-fi literature, completely covers this subject. Answers all questions about loudspeakers and enclosures: design, construction or crossover network; etc. Discusses the room as part of the acoustic circuit and the ramifications of stereo practices. 216 pgs.
10 R 12582 Shpg. wt., 1 1/2 lbs. Net 5.95

HOW TO SELECT AND USE HI-FI AND STEREO EQUIPMENT by Murray P. Rosenthal. All aspects of high fidelity are comprehensively covered in these 2 volumes, Vol. 1. (No. 0340). Spells out the Criteria and pitfalls when selecting new equipment. Fully covers loudspeakers and enclosures, receivers, tuners, amplifiers and headphones. 128 pages.
10 R 12046 Shpg. wt., 8 oz. Net 3.50

Vol. 2. (No. 0341) Presents full details on record players and tape recorders including operation, and maintenance. Discusses records, tapes, tone arms and styl. Features a section on hi-fi troubleshooting. 112 pages.
10 R 12053 Shpg. wt., 9 oz. Net 3.50

PRACTICAL PA GUIDEBOOK. (No. 0778). By Norman Crowhurst. Covers the entire field of public address systems. Shows how to properly install, operate and service. All aspects of the subject, from the initial survey to the selection of appropriate equipment, are detailed. Treats microphones, loudspeakers and their placement. 128 pgs. Shpg. wt., 9 oz.
10 R 12590 Net 4.45

UNDERSTANDING ELECTRONIC ORGANS (No. 0750) by Thomas Jaski. This guide covers the basics of organ operation and theory used in organ construction. Circuits—their necessity and effects—are discussed in detail, as well as the mechanical details of organ consoles such as keys, pedal, stops etc. Also includes tone generators, special effects, accessories and repairs. 224 pages.
10 R 12061 Shpg. wt., 12 oz. Net 5.45

HOW TO SERVICE TAPE RECORDERS. (No. 5736). By C. A. Tuthill. Presents in a balanced manner, an introduction to magnetic recording, an analysis of the operation of the mechanical and electronic systems of many modern tape recorders, and detailed directions for maintenance and trouble-shooting. Revised to incorporate the newest machines. 5 1/2 x 8 1/2" Softbound. 165 pages.
10 R 11832 Shpg. wt., 8 oz. Net 4.45

BOOKS ABOUT COMPUTERS

HOW TO BUILD A WORKING DIGITAL COMPUTER (No. 0748). By Alcosser, Phillips and Wolk. Features a unique approach to explaining how and why computers work. Detailed construction techniques for building an inexpensive working computer, with all component specifications and step-by-step assembly instructions. Complete theory explanations precedes construction. Includes programming explanation and solution of actual problems. 176 pages. Softbound.
10 R 11006 Shpg. wt., 11 oz. Net 4.45

BASICS OF DIGITAL COMPUTER PROGRAMMING (No. 0405). By John S. Murphy. This text provides a solid grounding in the use of procedure language for programming as well as a firm understanding of computer's applications to business. 150 pgs. 6x9".
10 R 11022 paperbound. Wt. 8 oz. Net 3.95

INDUSTRIAL ELECTRONICS

INDUSTRIAL CONTROL CIRCUITS (No. 0202). By Sidney Platt. This book looks at industrial control circuits through the eyes of the beginner. Circuits governing the initiation, processing, and finishing stages of industrial electronic equipment are explained in a comprehensive manner. Specific industrial applications are described to illustrate the problems of industrial control. There are chapters on electronic relay control timing circuits, photoelectric control, power controls, etc. Softcover. Shpg. wt., 12 oz. 200 pages, 5 1/2 x 8 1/2".
10 R 10602 Net 4.75

TEST EQUIPMENT BOOKS

IT'S EASY TO USE ELECTRONIC TEST EQUIPMENT (No. 0308). By Kevin and Gilmore. Describes and explains various basic electrical and electronic test instruments and outlines the various techniques for using these instruments. Emphasis is on practical application with more than 100-illustrations. 192 pages. 5 1/2 x 8 1/2".
10 R 11121 Shpg. wt., 11 oz. Net 4.95

HOW TO USE METERS (No. 0144). By John F. Rider. Explains use of panel meters, VOMs, and VTVMs when servicing radio and TV receivers, amplifiers, power supplies, and amateur transmitters. Shows what, how and where to use various meters. Discusses measurements and applications in different tests.
10 R 11063 Shpg. wt., 12 oz. Net 4.95

OBTAINING & INTERPRETING TEST SCOPE TRACES (No. 0146). By John F. Rider. Explains screen traces seen on test scopes in understandable, non-mathematical language. Contains over 800 scope traces in sinusoidal group—square, rectangular, trapezoidal, sawtoothed, differentiated and integrated waveforms. Gives examples with explanations. Shows how to connect and operate scope. Softcover, 5 1/2 x 8 1/2", 190 pages.
10 R 11055 Shpg. wt., 11 oz. Net 3.95

PRACTICAL OSCILLOSCOPE HANDBOOK. (0478) by Rufus P. Linton. Volume I introduces the oscilloscope and explains applications of interest primarily to general technicians, radio operators, servicemen, and hobbyists. Volume II is devoted to applications of interest to technicians in science and industry. Describes use of the oscilloscope for specific tests and measurements. Cloth bound.
10 R 12137 Shpg. wt., 2 lbs. Net 7.95

ADVANCED ELECTRONIC INSTRUMENTS AND THEIR USE (No. 0796) by Sol Premsky. Guide for scientific and engineering personnel. Fully covers the highly sophisticated new instruments for sensing, measurement, and control monitoring currently used in industry and research. More than 140 photographs and diagrams and principles and applications of such devices as femtometers, frequency synthesizers, solid-state multimeters, digital voltmeters, analog and digital computation elements. Shpg. wt., 1 1/2 lbs.
10 R 12129 Net 6.95

RADIO-THEORY AND REPAIR

RADIO TROUBLESHOOTING GUIDEBOOK (No. 0149). Vol. 1. By Rider & Johnson. Covers fundamental principles of radio receiver operation, written on an elementary level. Special section on trouble diagnosis, recognition of faults and their repair. Every type of AM and FM receiver is discussed. Softcover, 5 1/2 x 8 1/2", 160 pages. Illustrated.
10 R 10537 Shpg. wt., 9 oz. Net 3.75

HOW TO READ SCHEMATIC DIAGRAMS (No. 0208). By David Mark. Covering the symbols and abbreviations used in schematic diagrams related to the electronics field, this book starts with individual components and carries through to complete receivers and similar equipment. Components and circuits are identified and explained. Softcover, 160 pages. 5 1/2 x 8 1/2", illustrated. Shpg. wt., 9 oz.
10 R 11394 Net 3.95

BASIC RADIO (No. 0081) by Marvin Tepper. An exhaustive coverage of the fundamentals and circuitry of radio communications. Over 750 specially prepared illustrations, conceived and selected for their ability to make the "hard to hand" readily understandable, provide the "picture-book" approach to the subject matter. Six major sections thoroughly cover: DC electricity, AC electricity, electron tube circuits, AM and FM receivers, transistors and transmitters. 800 pages. Clothbound. Shpg. wt., 2 lbs. 13 oz.
10 R 10511 Net 14.85

Hayden/Rider Publications

BASIC TECHNICAL BOOKS

BASIC ELECTRICITY (No. 0039). By Van Valkenburgh, Nooger, Neville, Inc. Famous illustrated training course used by the Navy. Each page has at least one picture and explains one idea. Covers AC and DC components and circuits, AC and DC motors and machinery. Clothbound 6 x 9". Total 624 pgs. 10 R 11386 Shpg. wt., 2 lb. 5 oz. Net 12.75

BASIC ELECTRONICS-EXPANDED COURSE. By Van Valkenburgh, Nooger & Neville, Inc. (No. 0049). Famous illustrated standard Course covering vacuum tube diodes, power supplies, oscillators, amplifiers, detectors, receivers and transmitters plus semiconductors, transistors, and FM. Used by the Navy to train technicians. 666 pages. Clothbound. 10 R 10689 Shpg. wt., 2 lbs. 9 oz. Net 14.85

BASIC PRINCIPLES AND APPLICATIONS OF RELAYS (No. 0434). By Harvey Pollack. A comprehensive discussion of relay construction, operation and application at the technician level. 5 1/2 x 8 1/2". 112 pages. 10 R 10636 Shpg. wt., 7 oz. Net 3.95

USING THE SLIDE RULE IN ELECTRONIC TECHNOLOGY by Charles Alvarez is written for electronic students, both beginners and advanced. It can also serve as auxiliary text in math theory. All scales are discussed separately with detailed examples, graded in difficulty to develop speed and accuracy in use of the slide rule. 120 pp. 5 1/2 x 8 1/2 paperback. 10 R 11626 Shpg. wt., 7 oz. Net 2.95



HOW TO SOLVE PROBLEMS IN ELECTRICITY AND ELECTRONICS (No. 0302). By Henry Jacobowitz. Covers simple problems in DC circuits and progresses through more complex problems in AC electricity, tubes and transistors. All problems with solutions worked out. 152 pgs. 10 R 10594 Shpg. wt., 11 oz. Net 3.95

HOW TO SCORE HIGH ON THE SCHOLASTIC APTITUDE TEST (No. 0304). By Albert Genula. Treats questions of the type used in Scholastic Aptitude tests covering English and Mathematics. Contains practice exercises and answers. 224 pages, 8 1/2 x 11", illus. 10 R 11030 Shpg. wt., 1 lb., 9 oz. Net 3.59

LICENSE MANUALS

RADIO OPERATOR'S LICENSE Q & A MANUAL (No. 0771). Seventh edition by Milton Kaufman. Has been completely updated in accordance with the latest FCC examination requirements for any radio-telephone operator's license. Contains elements I, II, III, IV, VII and IX. Questions and answers for elements III and IV completely revised; all other elements have been updated. 576 pages. 5 3/4 x 8 1/4". Clothbound. 10 R 11980 Shpg. wt., 2 1/4 lbs. Net 8.95

RADIOTELEGRAPH OPERATOR'S LICENSE Q & A MANUAL (No. 0772) by Milton Kaufman. Completely updated study manual for obtaining FCC 3rd, 2nd and 1st class radiotelegraph licenses. Covers elements I, II, V, VI and VIII plus direction finder and automatic alarm equipment. 400 pages. Clothbound. 10 R 12095 Shpg. wt., 2 1/2 lbs. Net 11.95

THE ELECTRONIC INVASION

by Robert M. Brown

A Detailed Technical Explanation of Electronic Bugging and Debugging

(No. 0779) Discusses the secret techniques, devices, circuits, users and suppliers of bugs and anti-bugs. Covers all ramifications of electronic snooping, including miniature microphones and amplifiers, receivers, beepers, speech scramblers, techniques and circuitry. Includes a buyers directory and a section on eavesdropping and the law. 176 pages. 5 3/4 x 8 1/4". 10 R 11972 Shpg. wt., 10 oz. Net 4.95



LISTEN & LEARN LANGUAGE RECORD COURSE

6.95

Learn a language as it is actually spoken, for travel and study, for use in restaurants, shopping, sightseeing etc. Features dual language recording — first in English sentence, then its foreign equivalent. Each set contains 3 high-fidelity 3 1/2 LP records for 1 1/2 hours playing time plus convenient manual with full record text and phonetic transcription. Shpg. wt., 2 lbs. 9 oz.
24 R 20016 French 24 R 20040 Russian
24 R 20024 Spanish 24 R 20057 Italian
24 R 20032 German 24 R 20065 Japanese
Net ea. 6.95

SELECTED BOOKS ON SCIENCE & TECHNOLOGY



BASIC ELECTRICITY. Prepared by the U.S. Navy as a training course text. Provides a thorough coverage of the basic theory of electricity and its applications. Excellent for classroom use or for homestudy. 448 pgs. Shpg. wt. 1 lb., 11 oz. 10 R 31301 Net 3.50

TEACH YOURSELF SERIES

This Famous Series Published by the English University Press is an Ideal, Thorough, Yet Inexpensive Course in the Basic Branches of Mathematics and Mechanics. Clothbound

TEACH YOURSELF ALGEBRA by P. Abbott. A complete basic course in the most widely used branch of mathematics. Material simply presented with over 1200 problems (answers in the appendix) included to aid the student. All important areas of algebra are covered, with only an understanding of arithmetic necessary to master the techniques presented. Table of logarithms. 307 pages. 4 1/4 x 7". Clothbound. 10 F 31079 Shpg. wt., 11 oz. Net 2.50

TEACH YOURSELF GEOMETRY by P. Abbott is an excellent text both for a beginner and a refresher course in geometry. Divided into two parts, the first deals with the basic geometrical truths. The second presents the formal proofs of the geometrical propositions. Other areas treated are: parallel straight lines, theorem of Pythagoras, solid geometry, prisms, and much more. 334 pages. 4 1/4 x 7" Clothbound. 10 R 31129 Shpg. wt., 12 oz. Net 2.50

TEACH YOURSELF TRIGONOMETRY by P. Abbott. Requiring only a knowledge of high school algebra this course provides the essential of trig as applied to physics, navigation, surveying, and engineering. Over 465 problems with answers to aid the students progress. 204 pages. 4 1/4 x 7". Clothbound. 10 R 31087 Shpg. wt., 9 oz. Net 2.50

TEACH YOURSELF ELECTRONIC COMPUTERS by F. L. Westwater. Covers every aspect of digital computers in a lucid, interesting manner. Explains how a digital computer works and what it can do. Prepared specifically for laymen and beginning science and engineering students. Illustrated. 151 pages. 10 R 31327 Shpg. wt., 9 oz. Net 2.50

TEACH YOURSELF CALCULUS by P. Abbott puts calculus within the reach of anyone with an elementary knowledge of algebra and geometry. Presents simplified and shortened proofs to eliminate possible pitfalls by the beginning student. Tables of circular measures and hyperbolic functions. 380 pages. 10 R 31095 Shpg. wt., 12 oz. Net 2.50

TEACH YOURSELF ELECTRICITY by C. W. Wilman. Current, resistance, voltage, ohm's law, chemical effects of current, circuits, motors, inductance, capacitance, transformers, converters, measuring instruments, etc. Over 250 problems. Illustrated. Clothbound. 184 pages. 10 R 31103 Shpg. wt., 9 oz. Net 2.50

TEACH YOURSELF THE SLIDE RULE by Burns Snodgrass is a comprehensive course book enabling you to perform fast and accurate calculations with the slide rule. Full instruction covering A, B, C, D, LL, L, S, T, and other special purpose scales. 202 illustrations. 80 problems, 207 pp. 4 1/4 x 7". 10 R 31137 Shpg. wt., 10 oz. Net 2.50

THE PRINCIPLE OF RELATIVITY

by Albert Einstein

Dover Publication. This collection of original papers on the special and general theories of relativity is an unaltered, unabridged translation of original papers of Einstein, Lorentz, Weyl and Minkowski. 216 pages. 10 R 31178 Shpg. wt., 11 oz. Net 2.00

BASIC ELECTRONICS. Originally prepared by the U.S. Navy as a training course. Covers every important aspect of applied electronics, clearly illustrating important concepts, apparatus and techniques. 459 pages. 10 R 31319 Shpg. wt., 1 lb., 12 oz. Net 2.95

INTRODUCTION TO ELECTRONICS. A U.S. Navy training manual in the fundamentals of electronics. Profusely illustrated with nearly 150 charts, diagrams, photographs, schematics, drawings, etc. 145 pages. Shpg. wt., 10 oz. 10 R 31285 Net 1.25

HOBBY



The Scientific American Book of Projects for the Amateur Scientist by C. L. Strong. A magnificent volume of meaningful experiments in major areas of science, astronomy, biology, natural sciences, earth sciences, nuclear physics, mathematics, electronics, etc. Measuring metabolism in animals; studying hummingbirds; an electric sismograph; amateur rocketry; homemade interferometer. 256 illustrations. 608 pages. 10 R 75159 Shpg. wt., 2 lbs. 3 oz. Net 8.95

As New Books are Released by Publishers, Lafayette Will Stock Them

Howard W. Sams Books

BOOKS ON TV & RADIO — THEORY AND SERVICING

TV SERVICING MADE EASY 2nd Edition (No. 20811) by Wayne Lemons. Clearly explains, in serviceman's language, how to solve the tougher types of TV troubles. Based on actual experiences and case histories. Shows how to trouble-shoot, analyze and repair problems. 224 pages. 5½ x 8½". Shpg. wt., 9 oz.

10 R 22698 Net 5.25

TV TUBE SYMPTOMS AND TROUBLES (Sams 20476) by Robert G. Middleton. Second edition. A picture book of TV troubles caused by defective tubes. A handy 10-page TV tube trouble chart tells which tubes to replace to correct specific troubles. Tube caused defects are clearly explained and depicted in photos. Illustrated. 96 pages, 5½ x 8½". Shpg. wt., 6 oz.

10 R 23282 Net 2.50

TRANSISTOR-TV SERVICING GUIDE. (2nd Edition). (No. 20696) by Robert G. Middleton. Provides full information on latest circuitry and new test procedures. Lists symptoms encountered in each stage of receiver, and step-by-step procedures for analyzing and isolating each picture and/or sound defect. 128 pages, 8½ x 11". Shpg. wt., 12 oz.

10 R 24066 Net 3.95

TV SERVICING GUIDE (SAMS 20361) Trouble shooting procedures based on analysis of symptoms with picture tube photos with possible causes for each symptom. 132 pages. 8½ x 11". Shpg. wt., 1 lb. 2 oz.

10 R 21401 Net 3.25

CLOSED-CIRCUIT TELEVISION HANDBOOK (No. 20726) by Leon Wortman. Gives comprehensive detailed information in an easy-to-understand, up-to-date presentation. Suited for those who plan to use, install and service CCTV. Covers the subject from simple 5400 single-camera system to the most exotic systems. 288 pgs. Shpg. wt., 1 lb.

10 R 22425 Net 5.95

TUBE SUBSTITUTION HANDBOOK (14th Edition) (No. 20829) by Sams Staff. Completely updated with over 12,000 substitutions for receiving and picture tubes. Instructions on how to make correct substitutions and how to cross reference for additional substitutions. 96 pgs. Shpg. wt., 6 oz.

10 R 23365 Net 1.75

HOW TO READ SCHEMATIC DIAGRAMS (2nd Ed.) (SAMS 20568) by Donald E. Herington. Explains the purpose and meaning of various types of electronic equipment diagrams. Pictures and describes the different symbols used to schematically represent electronic and house wiring components. Tells how to interpret diagrams and follow signal paths. 160 pages. Shpg. wt., 9 oz.

10 R 23381 Net 3.50

TRANSISTOR RADIO SERVICING MADE EASY. (No. 20442) by Wayne Lemons. Written to provide the kind of help needed to repair transistor radios. Completely avoiding theory. He guides you in learning repair techniques that will help you repair practically any transistor radio trouble in minutes. 144 pgs. 5½ x 8½". Shpg. wt., 8 oz.

10 R 21344 Net 3.50

PRACTICAL TRANSISTOR SERVICING. (SAMS 20314) A guidebook to servicing all types of transistorized and all transistor equipment. Tells how the transistor works, circuit components and their functions, isolating trouble to a stage, normal transistor voltages, defective voltages and their meanings, servicing auto radios, and troubleshooting. 192 pages. 5½ x 8½". Shpg. wt., 10 oz.

10 R 21351 Net 4.25

RADIO SERVICE TRAINING MANUAL by Edward Rice. Helps speed up the location of troubles in the complete field of radio receivers, including tube and transistor types of auto, home and personal sets. "Programmed" troubleshooting charts show how to quickly isolate any type of trouble to a specific component. Hi-Fi amplifiers and stereo systems are also included. 288 pgs. Softbound (20343). Shpg. wt., 14 oz.

10 R 22409 Net 5.50

ELECTRONIC SERVICING

FOR THE BEGINNER. (SAMS 20090). A practical method to learn basic trouble-shooting methods for radio, TV, hi-fi and stereo, home-made and ham gear, etc. Learn by building equipment and then testing it. 160 pages. Shpg. wt., 4 oz.

10 R 21450 Net 3.95

HI-FI AND TAPE RECORDING

HOW TO BUILD SPEAKER ENCLOSURES (No. 20520) by Badmalfek and Davis. A thorough and comprehensive book providing practical and theoretical information on constructing high quality speaker enclosures. Contains many detailed drawings and instructions for building various enclosures, including testing techniques. Discusses drivers, horns and crossover networks. 144 pages.

10 R 23902 Shpg. wt., 8 oz. Net 3.50

HI-FI STEREO HANDBOOK (3rd Edition). (SAMS 20565) Covers fidelity and distortion, amplifiers and pre-amplifiers, loudspeakers, baffles and enclosures, program source equipment, and system design. 288 pages, 5½ x 8½".

10 R 23357 Shpg. wt., 14 oz. Net 5.50

TROUBLESHOOTING AUDIO EQUIPMENT (No. 20525.) by Marnie Horowitz. Stage-by-stage analysis of audio amplifiers and preamps, both vacuum tube and transistor. Covers pickups, microphones, phase inverters and drivers, tone controls, equalization, tape recorders and stereo systems. 160 pages. Shpg. wt., 9 oz.

10 R 23308 Net 3.95

TAPE RECORDERS—HOW THEY WORK. 2nd Ed. (No. 20445) by C. Westcott and R. Oubbe. Covers drive motors, volume indicators, bias oscillators, equalization circuits, amplifiers, and magnetic heads. Discusses frequency response, tape overload, bias settings and other subjects. 224 pages, 5½ x 8½", illustrated. Revised. Shpg. wt., 11 oz.

10 R 23340 Net 4.50

AUDIO CYCLOPEDIA (2nd Edition). (No. 20675). by Howard M. Tremaine. The most comprehensive and authoritative reference volume on audio covering ever phase of the subject. Includes the latest solid state and integrated circuits. Concise explanations of thousands of topics in acoustics, recording and sound reproduction. Covers basic principles, components and devices, film recording, studio techniques, audio installations, measurements and all phases of the audio art. Will be shipped postpaid directly from publisher. Over 1600 illustrations. 1757 pages.

10 R 24157Z Net 29.95

101 QUESTIONS AND ANSWERS ABOUT AUTO TAPE UNITS (20671) by Leo G. Sands. Easy-to-understand presentation of tape cartridge and cassette player installation, operation, circuitry, maintenance and troubleshooting procedures. Deals with tape cartridges and cassettes. 72 pages. Shpg. wt., 8 oz.

10 R 24082 Net 1.75

101 EASY AUDIO PROJECTS (No. 20608) by Robert M. Brown and Tom Kneitel. Contains complete discussion and instructions for building simple, useful and inexpensive audio projects. Includes intercoms, wireless microphones, AM and FM tuners, telephone amplifiers, PA, reverbs, etc., with detailed schematic and parts list for each project. 168 pages. Shpg. wt., 10 oz.

10 R 23910 Net 3.50



SAMS PHOTOFAC FOLDERS

PHOTOFAC FOLDER. Covers almost all post war radio and TV sets, record changers, and hi-fi equipment, etc. In addition to schematics, each folder contains pictures of chassis indicating parts location, parts lists, aligning procedures and troubleshooting tips. All folder sets are in stock. Use the free index listed below to determine the folder set you require. Folder sets 1 through 300 are special orders, and will be shipped postpaid directly from publisher to you as long as available. When ordering, remit in full and specify stock number 63R2 and the folder set number desired. When ordering Photofact Folders No. 301 and above, specify stock number 64R and the folder set number desired. Shpg. wt., each folder set, 15-oz.

STOCK NO.	PHOTOFAC NOS.	EACH
63RZ	1-300	3.25*
64R	301 and higher	3.00

*Shipped Postpaid

FREE ANNUAL INDEX. Helps you find the Sams Folder Set that contain the information you desire. Lists sets by make and model. Shpg. wt., 9 oz.

10 R 21229 Net 3.00

BINDER FOR FOLDER SETS. This attractive, durable, black leatherette binder holds 10 folders. Hardboard. Size, 9½ x 11½ x 6". 10 R 21237 Shpg. wt., ¾ lbs. Net 6.00

REFERENCE DATA FOR RADIO ENGINEERS. 5th Edition. This updated data book is a reference library in one fact-taden volume prepared under the direction of the IRT staff. 50% of the text is new material not covered in previous editions. It includes tables, formulas, standards, circuit information, charts, nomographs and diagrams. A truly time saving tool for the engineer, technician and student. Will be shipped postpaid directly from publisher to you. Over 1100 pages, 1350 illustrations.

10 R 23928Z Net 20.00

HOBBY BOOKS

ELECTRIC GUITAR AMPLIFIER HANDBOOK 3rd Edition. (No. 20848) by Jack Darr. Practical information for the musician and serviceman interested in musical amplification systems. Provides specific service information for commercial instruments. Includes schematics for most instruments. Describes faulty components, grid bias, voltages and wave forms in simple language. 224 pages. Shpg. wt., 10 oz.

10 R 24264 Net 5.95

388 Lafayette Cat. No. 720

To Speed Your Mail Order—Please Give Your Zip Code Number

Howard W. Sams Publications

TEST EQUIPMENT

101 WAYS SERIES TO USE YOUR TEST EQUIPMENT. By Robert Middleton. Invaluable for all users of test equipment. Each volume contains data on hookup connections required, equipment needed, test procedures, and evaluation of results. All 5½x8½". Illus. All 2nd Editions.

101 Ways to Use Your Sweep Generator. 160 pages. Shpg. wt., 9 oz.
10 R 22136 (20511) Net 3.50

101 Ways to Use Your Oscilloscope. 192 pages. Shpg. wt., 10 oz.
10 R 22144 (20416) Net 3.50

101 Ways to Use Your VOM and VTVM. 144 pages. Shpg. wt., 6 oz.
10 R 22151 (20510) Net 3.50

101 Ways to Use Your Signal Generator. 144 pages. Shpg. wt., 8 oz.
10 R 23522 (20548) Net 3.50

TROUBLESHOOTING WITH THE OSCILLOSCOPE. 2nd Ed. (20550) by Robert G. Middleton. Permits you to view and analyze instantaneous electronic circuit actions. Applications in troubleshooting are actually unlimited. 192 pages.
10 R 23555 Shpg. wt., 10 oz. Net 4.50

TRANSISTORS

49 EASY TRANSISTOR PROJECTS (No. 20617) by Robert M. Brown and Tom Kneitel. Provides complete, easy-to-understand instructions for building simple projects, such as radios, intercom systems, light relay controls, timers, test equipment, etc. Complete diagrams and parts lists. 64 pages.
10 R 23829 Shpg. wt., 5 oz. Net 1.75

ABC'S OF LASERS AND MASERS (No. 20262). By Allen Lytel. Explains how these special semiconductors are used in micro-wave and light frequency radiation application. Provides an understanding of Laser theory and its significance. 5½x8½". 128 pgs.
10 R 23001 Shpg. wt., 6 oz. Net 2.95

ABC'S OF VARACTORS Sams (20508) by Rufus P. Turner. Introduction to varactors, special semiconductors acting as voltage-variable capacitance. Explains basic theory, typical circuits, and practical micro-wave applications, as well as other use in receivers, transmitters and amplifiers. 112 pages.
10 R 23599 Shpg. wt., 8 oz. Net 2.75

AUDEL BOOKS

QUESTIONS AND ANSWERS FOR ELECTRICIANS EXAMINATIONS (No. 23164). A comprehensive guide to preparing for the various electricians license examinations. Contains the required theoretical information and a thorough understanding of the definitions, specifications and regulations of the National Electrical Code. 288 pages. Shpg. wt., 1½ lbs.
10 R 24504 Net 4.50

HOME REFRIGERATION AND AIR CONDITIONING (No. 23133). All the necessary data on modern units, systems, machines and refrigerants. Covers principles, operation and servicing procedures. 576 pages.
10 R 24512 Shpg. wt., 2½ lbs. Net 6.95

WIRING DIAGRAMS FOR LIGHT AND POWER (No. 23028). Explains in simple terms the wiring methods for practically all fields of electricity. Includes hundreds of self-explanatory diagrams. 320 pages.
10 R 24538 Shpg. wt., 1½ lbs. Net 4.95

HOME APPLIANCE SERVICING (No. 23016). Covers all aspects of every kind of home appliance and how to make electrical repairs. Includes vacuum cleaners, washing machines, dryers, irons, toasters, blenders, dishwashers, broilers, coffeemakers, fans, refrigerators, air-conditioners, ranges, and much more. Profusely illustrated. 608 pages.
10 R 24546 Shpg. wt., 1½ lbs. Net 6.95

ELECTRONICS

MODERN DICTIONARY OF ELECTRONICS 3rd Ed. (No. 20600). By Rudolf F. Graf. Revised. Includes more than 16,500 definitions applicable to electronics, special Pronunciation Guide, terminology expressed in Greek alphabet symbols, and electronic symbols and abbreviations. 608 pages, 6x9". Hardbound.
10 R 23878 Shpg. wt., 2¾ lbs. Net 9.95

UNDERSTANDING ELECTRONIC CIRCUITS (No. 20484). By F. J. Waters. Explains the basic electronic circuits used in most electronics equipment in simple terms. Illustrated; very little technical jargon or math. 160 pgs. Shpg. wt., 9 oz.
10 R 22367 Net 3.95

HANDBOOK OF ELECTRONIC TABLES AND FORMULAS (No. 20648). (3rd edition). Revised, up-dated and expanded. A one-step reference for all charts, tables, formulas, laws, symbols and standards. Full-color fold-out pages show assignments for the entire frequency spectrum. 232 pages. Hardbound. Shpg. wt., 1½ lbs.
10 R 23886 Net 5.95

ABC'S OF CAPACITORS (No. 20097) by William F. Mullin. Tells what capacitors are and how they are constructed. Explains capacitor operating principles, their uses and methods of testing them. 96 pages. Shpg. wt., 7 oz.
10 R 23860 Net 2.50

ABC'S OF ELECTRIC MOTORS AND GENERATORS (No. 20186). By Allen Lytel. A basic introduction. Explains how they operate. Both AC and DC motors and generators are covered. 128 pages. 5½x8½".
10 R 21492 Shpg. wt., 8 oz. Net 2.95

ELECTRICAL MOTOR CONTROLS & CIRCUITS (No. 20163). By David Fuchs and Stephen Garstang. A complete handbook for installers and maintenance technicians covering automatic and semiautomatic control circuits, starting, speed reduction, reversal, pilot devices, protection, and control circuit design. Illustrated. 288 pgs., 5½x8½".
10 R 21872 Shpg. wt., 14 oz. Net 5.75

ABC'S OF THERMISTORS. (20765). By Rufus P. Turner. Deals in detail with this simple, but extremely useful, electronic component with which many technicians and hobbyists are unfamiliar. 96 pages.
10 R 24199 Shpg. wt., 6 oz. Net 2.95

ELECTRONICS EXPERIMENTS & PROJECTS (No. 20194). By Len Buckwalter. Makes learning the principles of electronics easy. Projects include a low-power communications system, alarm detection device, weather station and electronic computer. All easily assembled from inexpensive parts. 128 pages.
10 R 21518 Shpg. wt., 10 oz. Net 2.95

HOW TO HEAR POLICE, FIRE, AND AIRCRAFT RADIO. (20781). By Len Buckwalter. A guide to VHF police, fire, and aircraft radio reception. Covers what there is to hear and the equipment necessary to receive it. Includes converters, receiver, and kits. Covers antennas and home and mobile installations. 128 pages.
10 R 24207 Shpg. wt., 7 oz. Net 3.50

SECURITY ELECTRONICS. (20767). By John E. Cunningham. Describes the principles of various electronic devices and systems used in providing security. 160 pages.
10 R 24215 Shpg. wt., 9 oz. Net 4.50

99 ELECTRONIC PROJECTS. (No. 20818) By Herbert Friedman. The projects presented in this book are intended for practical use in the following fields: audio; automotive; home protection; CB, ham, and swl; musical instrumentation; and more. All circuits employ solid state components, which are readily available at modest cost. 128 pages.
10 R 24280 Shpg. wt., 6 oz. Net 3.50

BRIDGES AND OTHER NULL DEVICES (No. 20564). By Rufus P. Turner. Explains the basic theory of bridge circuits, bridges, and bridge resembling devices. Covers resistance, capacitance, inductance, combination and r-f type bridges. Numerous actual use of these circuits are included. 144 pages.
10 R 23399 Shpg. wt., 8 oz. Net 3.50

101 QUESTIONS & ANSWERS ABOUT ELECTRICITY. (20806). By Leo G. Sands. A valuable source for experimenters and students. Explains electricity in easily understood terms. Covers the practical aspects with a minimum of theory. Discusses basic concepts, batteries and transformers, rectifiers and motors, switching devices, and more. 112 pages.
10 R 24272 Shpg. wt., 6 oz. Net 3.50

ABC'S OF RADIO-FREQUENCY HEATING. (20747). By John Shields. Acquaints the technician and experimenter with technology of radio-frequency heating. Discusses dielectric and induction RF heaters.
10 R 24223 Shpg. wt., 7 oz. Net 2.95

ELECTRONIC ORGANS (No. 20188). Pertinent specifications, schematics, and servicing information on representative organs. 272 pages. 5½x8½". Shpg. wt., 13 oz.
10 R 21526 Net 5.75

COMPUTER BOOKS

COMPUTER CIRCUIT PROJECTS YOU CAN BUILD (No. 20084). By Lee Boschen. Details construction of 13 basic computer-circuit projects explaining theory and applications. Gives working knowledge of fundamental computer circuitry. 144 pgs.
10 R 21674 Shpg. wt., 9 oz. Net 3.25

ABC'S OF COMPUTERS (No. 20012). A basic introduction to computers. Explains what they are, how they operate, and what they can be expected to do. 144 pages.
10 R 23027 Shpg. wt., 8 oz. Net 2.95

ABC'S OF COMPUTER PROGRAMMING (No. 20123). A full introduction to the principles and applications of digital computer programming — from simple sub-programs to intricate assembly and compiler programs. 5½x8½". 128 pgs. Shpg. wt., 6 oz.
10 R 21690 Net 2.95

COMPUTER DICTIONARY (No. 20102). By Charles Sippl. Essential reference defining over 5000 terms and concepts of computer technology. Includes sources for computer equipment, personal training, factual discussions and listings of information on electronic data processing. 336 pages.
10 R 23274 Shpg. wt., 1½ lbs. Net 5.50

G. L./Tab & Supreme Publications

HOW TO USE YOUR VOM-VTVM AND OSCILLOSCOPE (No. 438) by Martin Clifford.

A guide for the everyday application of the most frequently used test instruments and how to get more reliable test results in less time. 192 pages. Shpg. wt., 9 oz. 10 R 41607



Net 3.95

RADIO-CONTROL MANUAL (No. 135) by E. Z. Safford, Jr.

Completely Revised. Principles of radio-control planes, boats, and cars; from super simple to super sophisticated. Circuits (tube and transistor) you can build and use. 192 pages. Shpg. wt., 10 oz. 10 R 41615



Net 4.95

HOW TO TEST...ALMOST EVERYTHING ELECTRONIC (No. 132), by Jack Darr.

Practically every testing technique for almost every kind of electronic equipment. Hundreds of illustrations make text crystal clear. Soft-bound. 160 pages. Shpg. wt., 7 oz. 10 R 41557



Net 2.95

BOOKS ABOUT TRANSISTORS

SEMICONDUCTORS FROM A TO Z (No. 493) by Phillip Oahlen. Everything you need know about everything in semiconductors. Includes basic diodes and transistors, FET's, integrated circuits, photo devices, varicaps, SCR and zener diodes and much more. Explains operation, circuitry and applications in modern semiconductor technology. 256 pages. Soft bound.

10 R 41706 Shpg. wt., 14 oz. Net 4.95

UNDERSTANDING SOLID-STATE CIRCUITS (No. 513) by Norman Crowhurst. Provides practical information and working circuits for the technician and knowledgeable hobbyist. Includes IC's, control circuits plus practical systems applications. 192 pages. Soft-bound. Shpg. wt., 12 oz.

10 R 41755 Net 4.95

HOW TO FIX TRANSISTOR RADIOS AND PRINTED CIRCUITS (No. 504) 2nd Edition by Leonard C. Lane. The perfect reference and guide to the understanding and efficient repair of semiconductor circuits. 256 pages. Softbound. Shpg. wt., 13 oz.

10 R 41763 Net 4.95

WORKING WITH SEMICONDUCTORS (No. 501) by Al Saunders. A working guidebook to the understanding of semiconductor circuits via the construction of breadboarding of experiment-type projects having practical applications. 224 pages. Softbound.

10 R 41771 Shpg. wt., 12 oz. Net 4.95

AUDIO AND HIGH FIDELITY

AUDIO SYSTEMS HANDBOOK (No. 494) by Norman H. Crowhurst. A down-to-earth technical approach to the whole audio system. Covers amplifiers, equalizers, mixers, filters, distribution systems, program sources, reverberation, hi-fi home systems, public address, speaker systems, acoustics and more. 192 pages. Softbound. Wt., 11 oz. 10 R 41714

Net 4.95

HANDBOOK OF MAGNETIC TAPE RECORDING: Principles, Applications and Maintenance (No. 529) by Finn Jorgensen. Describes how to get optimum use from a recorder via specialized techniques, maintenance and tape selection. 256 pages. Softbound.

10 R 41789 Shpg. wt., 10 oz. Net 4.95

INSTALLING AND SERVICING HOME AUDIO SYSTEMS (No. 505) by Jack Hobbs. Covers the practical aspects of installing and servicing all kinds of audio communications equipment used in home, business and industry via up-to-date information and techniques. 256 pages. Softbound.

10 R 41797 Shpg. wt., 12 oz. Net 4.95

SERVICING RECORD CHANGERS (No. 59). Discusses every functional assembly as a unit so that even beginner can learn quickly. Illustrates intricate mechanisms. 224 pages. 10 R 41375 Shpg. wt., 12 oz. Net 5.95

HOBBY BOOKS

ELECTRONICS HOBBYISTS' HANDBOOK (No. 69) by Rufus P. Turner. Over 100 circuits for planning, designing and building your own electronic projects. Complete Parts list for each project. 160 pages, 114 illustrations. 10 R 41052 Shpg. wt., 9 oz. Net 2.95

RADIO-CONTROL HANDBOOK-3rd ED. (No. 93). By H. C. McEntee. An up-to-date version of the handbook which has become the standard in the field. New ideas for remote control of model boats, planes and cars by radio. Information on servos and actuators as well as receivers and transmitters. 320 pages. Shpg. wt., 1 lb. 10 R 41425

Net 5.95

MODEL RADIO CONTROL (No. 74). By Edward L. Safford, Jr. Covers coders, decoders, transmitters, receivers, control systems, troubleshooting, etc.—from theory to practical hints. Tells how to build successful models. Illustrated. 192 pages. 10 R 41227 Shpg. wt., 11 oz. Net 4.95

ADVANCED RADIO CONTROL (No. 122). Provides advanced techniques for the radio control enthusiast. A step-up from the previous basic R/C books. 192 pages. 10 R 41466 Shpg. wt., 10 oz. Net 4.95

SUPREME PUBLICATIONS

TELEVISION SERVICING MANUALS

For faster, easier TV repairs. Factory data on practically all sets. Complete circuits, all needed alignment facts, wiring board views, waveforms, voltages, production changes, and double-page schematics. Size: 8½x11". Shpg. wt., 1½ lb.

No.	Vol.	Year	Pages	Net
10 R 51622	C-70#	1970	192	4.00
10 R 51598	C-69#	1969	192	4.00
10 R 51630	TV-29	1970	192	4.00
10 R 51648	TV-28	1969	192	4.00
10 R 51564	TV-27	1968	192	4.00
10 R 51549	TV-26	1967	192	4.00
10 R 51531	TV-25	1966	192	3.00
10 R 51481	TV-24	1965*	192	3.00
10 R 51499	TV-23	1965*	192	3.00
10 R 51010	TV-22	1964	192	3.00
10 R 51028	TV-21	1963	192	3.00
10 R 51036	TV-20	1962†	192	3.00
10 R 51044	TV-19	1962*	192	3.00
10 R 51051	TV-18	1961	192	3.00
10 R 51069	TV-17	1960	192	3.00
10 R 51077	TV-16	1959†	192	3.00
10 R 51085	TV-15	1959*	192	3.00
10 R 51093	TV-14	1958	192	3.00
10 R 51101	TV-13	1957†	192	3.00
10 R 51135	TV-10	1955†	192	3.00
10 R 51150	TV-8	1954	192	3.00
10 R 51184	TV-5	1951	193	3.00

MASTER INDEX For Supreme TV and Radio. 10 R 51192 Shpg. wt., 7 oz. Free

PRACTICAL RADIO AND ELECTRONICS COURSE. Complete home study course of 53 lessons for the beginner. Covers every topic of radio, electronics, with lessons on test equipment, FM, radio, and an introduction to TV, etc. 3-in-1 volume includes all lessons, test questions. 8½x11" x 216 pages. Shpg. wt., 1 lb. 9 oz. 10 R 51457

TELEVISION SERVICING COURSES. Net 3.95. Covers everything in TV. Easy-to-follow well illustrated lessons on circuits, picture faults, shorts, UHF, alignment, antenna data and test equipment. Complete training in TV servicing. Profusely illustrated. 8½ x 11". 10 R 51218 Shpg. wt., 1½ lb. Net 4.00

RADIO DIAGRAM MANUALS

Simplify repairing. Cover home radios, stereo, combinations, transistor portables, FM, auto sets. Large schematics, all needed alignment facts, printed boards, voltages, dial stringing, hints. 8½ x 11". Shpg. wt., 1½ lb.

No.	Vol.	Year	Pages	Net
10 R 51606	27	1967-1969	192	4.00
10 R 51556	26	1966	192	2.50
10 R 51507	25	1965	192	2.50
10 R 51226	24	1964	192	2.50
10 R 51234	23	1963	192	2.50
10 R 51242	22	1962	160	2.50
10 R 51259	21	1961	192	2.50
10 R 51267	20	1960	192	2.50
10 R 51275	19	1959	192	2.50
10 R 51283	18	1958	192	2.50
10 R 51309	16	1956	192	2.50
10 R 51317	15	1955	128	2.50
10 R 51333	13	1953	168	2.50
10 R 51341	12	1952	192	2.50
10 R 51358	11	1951	192	2.50
10 R 51366	10	1950	192	2.50
10 R 51374	9	1949	160	2.50
10 R 51382	8	1948	192	2.50
10 R 51424	4	1941	192	2.50
10 R 51432	3	1940	208	2.50
10 R 51440	1	1926-1938	240	2.50

*Early †Additional #Color TV

AUTO RADIO DIAGRAMS MANUAL (No. AU-1). Covers all 1964-65 auto sets. Provides schematics, alignment-facts, complete service information. 8½x11". 128 pages. Shpg. wt., 10 R 51515 Shpg. wt., 1½ lb. Net 2.50

RADIO SERVICING BY COMPARISON. Introduces a remarkably simplified technique of radio repairing—the comparison method. Volt ohmmeter is only equipment needed—point-to-point circuit, cross-reference locates faults instantly. Applicable to any radio, old or new. 1000 service hints. Includes 26 large circuit diagrams. 48 pages. 8½x11". 10 R 51200 Shpg. wt., 6 oz. Net 1.50

LEARN ELECTRONICS BY BUILDING (No. 112) by John Schroeder. Learn electronics by building the units yourself. Start with basic theory; finish by constructing amplifiers and receivers. An easy, practical approach for beginners of all ages. 208 pages. 10 R 41201 Shpg. wt., 11 oz. Net 4.95

RADIO AND T.V.—THEORY AND SERVICING BOOKS

BASIC RADIO COURSE (No. 104). By John T. Frye. Everything—Ohms Laws, capacitance, tubes, transistors and how they work in a receiver—practical servicing techniques—discussed in a light-hearted style that makes what's being taught stick. 224 pages. 10 R 41342 Shpg. wt., 12 oz. Net 4.95

RADIO RADIO REPAIR (No. 78). By G. Warren Heath. Symptoms, troubles and repair techniques. Covers latest transistor sets, printed circuit repair, modular receivers, use of test instruments. 224 pages. Shpg. wt., 12 oz. 10 R 41359

Net 4.95

RAPID TV REPAIR (No. 60). Handy, practical service manual which lists hundreds of "tough-dog" troubles alphabetically, many cross-referenced. Will help you cut down troubleshooting time. 224 pages. Illustrated. 10 R 41334 Shpg. wt., 11 oz. Net 4.95



EVEREADY BATTERY APPLICATIONS AND ENGINEERING DATA BOOK

Contains all basic data on each Eveready battery now in production. Complete specifications, including dimensions, weight, drain data and cross reference information. Profusely illustrated; charts, graphs and tables. 704 pages.

10 R 16013 Shpg. wt., 2¼ lbs. Net 6.00

High Quality Lafayette Multitesters

DELUXE 30,000 OHMS PER VOLT MULTITESTER WITH MIRROR SCALE

18⁹⁵

- 30,000 Ohms per Volt DC, 15,000 Ohms per Volt AC
- Low Voltage Scale for Transistor Tests
- 1% Precision Resistors for High Accuracy
- Unique "Buzzer" for Fast Short Tests
- 27 Meter Ranges on 2-Color Scale
- Built-in Overload Protective Circuitry

Deluxe portable Volt-Ohm-Millammeter with a mirror scale. Provides wide voltage, current, resistance and db ranges clearly visible on a big 4" meter with 2 color calibrations. Built-in overload protective circuitry. Sensitivity is 30,000 ohms-per-volt DC and 15,000 ohms-per-volt AC. All multipliers used are 1% precision resistors for maximum accuracy and years of dependable service. Sensitive 33-micro-ampere meter provides full scale readings down to 1/4 volt on DC and .05 milliamps. Features a unique self-contained buzzer to give you fast in-circuit checks on opens, shorts. Audio output jack with DC blocking capacitor. Handsome, dust proof black plastic case. Complete with leads, batteries. Size: 4 1/4" W x 6 1/4" H x 2 3/4" D.

99 R 50718 Imported. Shpg. wt., 2 1/4 lbs. Net 18.95
38 R 01081 Texon Carrying Case for the above. Shpg. wt., 5 oz. Net 1.95

SPECIFICATIONS

Sensitivity: 30,000 ohms/volt DC, 15,000 ohms/volt AC. Ranges: DC volts: 0-25, 1, 2.5, 10, 25, 100, 250, 500, 1000; AC volts: 0-2.5, 10, 25, 100, 250, 500, 1000. Direct Current: 0-0.05, 5, 50, 500 ma; 0-12 amps Ohmmeter: 0-60K, 6M, 60 Megohms, Decibels: -20 to +56 db. Short Test: Internal Buzzer, Audio Output Jack, Controls: Range Switch, Ohms Adjust. Batteries: 1 type Z cell, 15-volt.

DELUXE 20,000 OHMS-PER-VOLT MULTITESTER WITH MIRROR SCALE

13⁹⁵

- 20,000 Ohms-Per-Volt DC, 10,000 Ohms-Per-Volt AC
- Low Voltage Scale for Transistor Tests
- 1% Precision Resistors For High Accuracy
- 40-Microamp 3 1/2" D'Arsonval Meter
- Built-in Overload Protective Circuitry

Handy pocket multi-tester with mirror scale. Has every needed range. Ideal for repair and service work, testing and troubleshooting electronic circuits and appliances in the labor shop. 40 micro-ampere meter movement permits a high input resistance on all ranges. Has a single range/function control for quick, simple operation, plus zero ohms adjust and built-in overload protective circuitry. With batteries, test leads 5 1/4 x 3 3/4 x 1 7/8" D. Imported. Shpg. wt., 1 1/2 lbs.

99 R 50734 Net 13.95
38 R 01073 Texon Carrying Case for above. Shpg. wt., 5 oz. Net 1.95

SPECIFICATIONS

Sensitivity: 20,000 ohms/volt DC; 10,000 ohms/volt AC. Ranges: DC volts: 0.6, 6, 30, 120, 600, 1200; AC volts: 0-6, 30, 120, 600, 1200. Resistance: 0-10K, 100K, 1M, 10Megs. Current: 0-60 μ A, 0-6, 60, 600 MA. Decibels: -20 to +63. Capacity: 200 mmf to 0.2 mfd.

20,000 OHMS-PER-VOLT MULTITESTER WITH MIRROR SCALE

10⁹⁵

- 20,000 Ohms/Volt DC, 10,000 Ohms/Volt AC
- 1% Precision Resistors
- Easy-to-Read 3" Meter
- Built-in Overload Protective Circuitry

Easy visibility is provided by the large 2-color 3" meter with mirror scale. The 40-Microampere D'Arsonval meter movement permits a high input resistance on all ranges. Built-in overload protective circuitry. Supplied with battery and test leads. Rugged, high impact plastic case. Size 3 1/4 x 4 1/4 x 1". Imported. Shpg. wt., 1 lb.

99 R 50726 Net 10.95
38 R 01073 Texon Carrying Case for above. Shpg. wt., 5 oz. Net 1.95

SPECIFICATIONS

Sensitivity: 20,000 ohm/volt DC, 10,000 ohms/volt AC. Range DC Volts: 0-3, 30, 60, 300, 600, 3,000V. AC Volts: 0-6, 60, 120, 1,200V. DC Current: 0-60 μ A, 0-12, 0-300 ma. Resistance: 0-60K, 0-6, 60, Megohms. Decibels: -20 to +63db. Audio Output Jack. Type "Z" 1.5V cell for resistance measurements.

"SUPER MINI" AC/DC VOM

6⁹⁵

- Compact Pocket Size: 3 1/2" H x 2 1/8" W x 1 3/8" D.
- Reads AC/DC Volts To 1200 Volts
- 8-Input Ranges • 4-Reading Scales
- Separate Red Scale For Low AC Reading

Highly accurate, low cost multimeter. Handy to use anywhere by technicians, hobbyist or home owners for trouble shooting electronic circuits and testing appliances. Ranges: AC/DC voltage, 0-12, 0-120, and 0-1200; DC current, 0-1mA and 0-120mA. Reads resistance from 0 to 200,000 ohms. Easy to read red scale for low AC readings. 1% resistors offer precise readings. Sensitivity: 1000 ohms per volt. Zero ohms adjust. Operates on 1.5 volt "Z" cell. Complete with test leads and battery.

99 R 50791 Imported. Shpg. wt., 10 oz. Net 6.95
99 R 50809 Pigskin Carrying Case for above. Shpg. wt., 5 oz. Net 1.49



Make Lafayette Your Headquarters For Test Equipment

Lafayette Cat. No. 720 391

LAFAYETTE'S Finest Multitesters

Super LAFAYETTE 50,000 Ohms Per Volt VOM

- Large 5½" Meter
- 50K Ohms Per Volt
- 5K Ohms Per Volt AC
- Built-in Overload Protection
- Low Voltage Ranges For Transistor Circuitry
- 1% Precision Resistors
- Accuracy $\pm 2\%$ DC, $\pm 3\%$ AC

32⁹⁵

Super-sensitive, self-contained, portable Multi-Tester! Employs 1% precision resistors and high quality components for an accuracy of better than 2% on DC; 3% on AC. Useable at frequencies up to 100Hz. Meter movement is self-shielded with spring-backed jewels. Also has polarity switch and easy-to-read range indicator. Built-in meter overload protection. Size: 5¼x2¾x6½". With batteries and test leads. Imported. Shpg. wt., 2 lbs.

99 R 50767

Net 32.95

SPECIFICATIONS

Ranges: DC Volts: 0-0.25-2.5-10-50-250-1000 @ 25K ohm/V; 0-0.125-1.25-5.0-25-125-500 @ 50K ohm/V. AC Volts: 0-3-10-50-250-1000 @ 2.5K ohm/V; 0-1.5-5.0-25-125-500 @ 5K ohm/V. DC μ A: 0-25 @ 125 mV; 0-50 @ 250 mV. DC mA: 0-5-50-500 @ 250 mV; 0-2.5-25-250 @ mV. DC amperes: 0-10-250mV; 0-5 @ 125 mV. Ohms: 0-2K, 10K, 100K, 1M, 10 Megs. DB: -20 to +81.5 in 10 AC volt ranges.



Deluxe LAFAYETTE Premier Line of Multitesters

- Especially Designed For Ease of Handling and Convenience
- Self Supporting—Meter Can Be Tilted at a 45° Angle for Easy Viewing
- Burnout Protected • Mirror Scale • Low Voltage Scale for Transistors



22⁹⁵


30,000 Ohms Per Volt Multitester RANGES

- AC Volts: 0-2.5, 10, 25, 100, 250, 500, 1000
- DC Volts: 0-.25, 1, 2.5, 10, 25, 100, 250, 500, 1000
- DC Current: 0-0.5, 5, 50, 500 MA; 0-12 Amps
- Ohms: 0-60K, 6M, 60 Megohms
- DB: -20 to +56

Deluxe VOM with mirror scale has professional "lab" styling, carrying-handle for portable or bench use. Provides wide voltage, current, resistance and db ranges clearly visible on a large, easy-to-read scale with 2 color calibrations. Built-in overload protective circuitry to assure a long trouble-free life. Sensitivity is 30,000 ohms-per-volt DC and 15,000 ohms-per-volt AC. All multipliers used are 1% precision resistors for maximum accuracy and years of dependable service. Sensitive 33 microampere meter provides full scale readings down to 1/4 volt on DC and .05 ma. Features a unique, self-contained buzzer to give you fast in-circuit checks on opens, shorts. Audio output jack with DC blocking capacitor. Sturdily housed in a handsome, dustproof black plastic case. With leads and batteries. Size: 7W x 4H x 2¼"D. Imported.

99 R 50817 Shpg. wt., 1½ lbs.

Net 22.95



15⁹⁵

20,000 Ohms Per Volt Multitester RANGES


- AC Volts: 0-6, 30, 120, 600, 1200
- DC Volts: 0.6, 6, 30, 120, 600, 1200
- DC Current: 0-60 μ A, 0-6, 60, 600 MA
- Ohms: 0-10K, 100K, 1M, 10 Megs.
- DB: -20 to +63

Handsome "lab-type" low profile design with carrying handle. Has every needed range and mirror scale for precise readings. Ideal for repair and service work as well as testing and troubleshooting electronic circuits and appliances in the shop. 40 microampere meter movement permits a high input resistance on all ranges. Has a single range/function control for quick, simple operation, plus zero ohms adjust and built-in overload protective circuitry. Complete with batteries and test leads. Specifications: Sensitivity: 20,000 ohms/volt DC; 10,000 ohms/volt AC. Ranges: DC volts, 0.6, 6, 30, 120, 600, 1200; AC volts: 0-6, 30, 120, 600, 1200. Resistance: 0-10K, 100K, 1M, 10 Megs. Current: 0-60 μ A, 0-6, 60, 600 MA. Decibels: -20 to +63. Capacity: 200 mmf to 0.2 mfd. Size: 7W x 4H x 2¼"D. Imported.

99 R 50825 Shpg. wt., 1 lb.

Net 15.95

QUALITY FET VOM'S & VTVM'S



NEW! LAFAYETTE SOLID STATE FET VOM with Giant 5½" Meter with Mirror Scale

ONLY **44⁹⁵**

with 3 ft. test leads and batteries

SPECIFICATIONS

RANGES:

DC VOLTS: 0.3-1.2-12-30-120-300-600-1200V. Accuracy $\pm 3\%$ at full scale.

AC VOLTS: 0.3-30-120-600V (RMS), 0.8-80-320-800V (P-P). Accuracy $\pm 4\%$ at full scale.

DC CURRENT: 0.12-1.2-12-120 mA. Accuracy $\pm 3\%$ at full scale.

RESISTANCE: (30 ohm mid-scale) X1, X10, X100, X10K, X1MEG (2K, 20K, 200K, 20M, 2000M). Accuracy $\pm 3\%$ at full scale.

DECIBELS: -20 to -31 db on two scales.

- Manual DC Polarity Selector Switch
- High Sensitivity—0.3 V. range with 11 Megohm DC and 1 Megohm AC Input Resistance
- Built-in Overload Protection Circuitry
- Direct Peak to Peak AC Voltage Measurements

A high quality, accurate FET volt-ohmmeter with the high impedance of a VTVM and big easy-to-read 5½" meter. Is capable of high sensitivity transistor bias measurements (250 mV full scale) up to 2000 Megohms. Direct Peak-to-Peak AC volt measurements capability at 1 Megohm impedance. Built-in overload protection circuit. "Zero Center" mark for null measurement built-in. Lightweight for easy use and portability. Has convenient battery check—eliminates going out on a job with weak batteries. Accessories Included; Batteries, Test Leads, and Instruction Manual. Size: 6¼"H x 4¼"W x 2"D. Shpg. wt., 3 lbs. Imported.

99 R 50593 No Money Down* Net 44.95

NEW! SENCORE FE 20 Hi-Lo Multimeter



- 15 Megohm Input Resistance on DC, 12 Megohms on AC
- Accuracy 1.5% DC, 3% on AC

129⁹⁵
including
hi-volt probe

A must for accurate resistance measurements in solid state circuitry. Has 9 DC voltage ranges from as low as a tenth of a volt full scale to 1000 volts. 3 hi-voltage ranges of 3KV, 10KV, and 30KV. 9 DC zero center ranges from .05 to 500 volts for transistor bias measurements. 9 AC RMS ranges from a tenth of a volt full scale to 1000 volts. 7 resistance ranges from 1000 ohms full scale to 1000 megohms. (Both HI and LO ohms read on same scale). 9 DC current ranges from 100 microamps to 1 amp. Complete battery test for the long life "C" cells. Special front panel .6 amp fuse to protect the ohms and milliamps scale. Size: 9½"H x 7¾"W x 3¼"D. Shpg. wt., 8 lbs.

38 R 53371W No Money Down Net 129.95

99 R 63687 "C" Long Life batteries (7 req.) Net ea. 22

NEW! PROFESSIONAL VTVM with Multi-Color 6" Meter



ONLY **49⁹⁵**

- Mirror Scale
- D'Arsonval Movement
- 11 Megohm Input Resistance

Provides a wide frequency response on AC Voltage for compatibility with Color TV servicing, FM multiplex trouble-shooting, and general industrial applications. DC Voltmeter: Ranges: 0-1.5, 5, 15, 50, 150, 500, 1500 volts full scale. Input Resistance: 11 megohms (1 megohm in probe). Accuracy $\pm 3\%$ of full scale. AC Voltmeter: 7 Ranges (RMS), 0-1.5, 5, 15, 50, 500, 1500 volts full scale. 7 Ranges Peak-to-Peak, 0-4, 14, 40, 140, 400, 1400, 4000 volts. Db scale—20 to +66 db in seven ranges. Ohmmeter: Ranges: Rx1 (0-1K ohm), Rx10 (0-10K ohm), Rx100 (0-100K ohm), Rx1K (0-1 megohm), Rx10K (0-10 megohms), Rx100K (0-100 megohms), Rx1 MEG (0-1000 megohms). 10 ohms center scale on Rx1 range. Power Requirements: 105-125 VAC, 50/60 Hz. Includes a 1.5 volt "C" cell battery. Size: 8¼"H x 6¼"W x 4½"D. Shpg. wt., 5 lbs.

38 R 37192W No Money Down* Net 49.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 393

Deluxe VOM'S and VTVM'S Accurate Measurement

NEW! Simpson MODEL 260-6 AC/DC VOM

- 20,000 Ohms/VDC, 5000 Ohms/VAC Sensitivity
- Accuracy: $\pm 2\%$ DC, $\pm 3\%$ AC
- 50 μ A Self-Shielding and Shockproof Movement

All the advancements of the previous 260 series plus these new features: 0-1 volt DC range, 0-500 volt AC and DC ranges, external access battery and fuse compartment, multi-purpose screw-on test leads with combination probe and alligator clips. DC polarity reversing switch, full wave bridge rectifier for fast easy readings. Ranges: DC mv, 0-250; AC and DC volts, 0-1, 2.5-10-50-250-500-1000; AF output V., 0-2.5-10-50-250; DC μ A, 0-50; DC mA, 0-1-10-100-500; DC amps., 0-10; DB, -20 to +50 in 4 ranges; Resistance, 0-20 meg in 3 ranges. Housed in bakelite case, 5 $\frac{1}{4}$ x7 $\frac{3}{8}$ ". With battery and test leads.

38 R 48710 No Money Down* Shpg. wt., 4 $\frac{1}{4}$ lbs. Net 65.00

New Simpson MODEL 260-6P—Same fine features and ranges as Model 260-6 but equipped with special sensor circuit to prevent burned components, bent pointers, and blown rectifiers. With battery and test leads. Shpg. wt., 6 lbs.

38 R 48702 No Money Down* Net 97.00

New Simpson MODEL 260-6PRT—Same as above, but with "roll top" safety case. Shpg. wt., 7 $\frac{3}{4}$ lbs.

38 R 48728 No Money Down* Net 103.00

New Simpson MODEL 270-4—Same as Model 260-6 but with mirror scale, knife edge pointer, self shielded annular meter. Higher accuracy $\pm 1.25\%$ DC, $\pm 3\%$ AC. Dimensions: 5 $\frac{1}{4}$ x7 $\frac{3}{8}$ ". Shpg. wt., 5 lbs.

38 R 48736 No Money Down* Net 78.00

New Simpson MODEL 240-4RT—Same as model 270-4 but with roll top case. Shpg. wt., 7 $\frac{3}{4}$ lbs.

38 R 48744 No Money Down* Net 84.00

ADD-A-TESTERS For 260 and 270 SERIES AC/DC VOMS


Add unlimited versatility to all Simpson 260 or 270 Series AC/DC VOMS made since 1947 except ROLL TOP models. Turns these VOM'S into 9 different type testers. Shpg. wt., 2 $\frac{3}{4}$ lbs.

Stock No.	Model	Type	Net
38 R 48108	650	Transistor Tester	44.00
38 R 48116	651	DC VTVM	52.00
38 R 48124	652	Temp. Tester	49.00
38 R 48132	653	AC Ammeter	30.00
38 R 48140	654	Audio Wattmeter	34.00
38 R 48181	661	DC Ammeter	33.00

ACCESSORIES for SIMPSON VOMS

Stock No.	Model No.	For Model	Description	Wt.	Net
38 R 48066	01818	260 & 270 Series	Leather Case	2	12.00
38 R 48074	07500	270	Leads†	1	2.75
38 R 48082	00509	260 & 270 Series	50KV HV Probe	1/2	17.00
38 R 48090	00508	260 & 270 Series	25KV HV Probe	1/2	17.00

†ALLIGATOR CLIPS



VERSATILE "ADD-A-TESTERS" Adapter Simply Plugs-In for Complete Unit

SIMPSON 92 PAGE BOOK "1001" USES OF THE 260 SERIES VOM. A MUST FOR EVERY STUDENT, TECHNICIAN, AND ENGINEER. WT., 7 OZ. 38 R 48611 Net. 1.00

NEW! B & K MODEL 179 SOLID STATE F. E. T. VOM

74⁹⁵
No Money Down*
• Diode Input Protection
• 55 Ranges Including AC Current

Large 4 $\frac{1}{2}$ " meter has a sensitive, 80 μ C movement, mirror scale. Specifications: DC Volts: 8 ranges—0-0.3, 1.0, 3.0, 10, 30, 100, 300, 1000. Accuracy 2%. DC Current: 8 ranges—0-30, 300 μ A; 0-1.0, 3.0, 10, 30, 100, 300 mA. AC Volts: 8 RMS ranges—0-0.3, 1.0, 3.0, 10, 30, 100, 300, 1000. 8 P-P ranges—0-0.84, 2.8, 8.4, 28, 84, 280, 840, 2800. Decibels: 25.5 to +62 db in 8 ranges. AC Current: 8 RMS ranges—0-30, 300 μ A; 0-1.0, 3.0, 10, 30, 100, 300 mA. Ohms: 7 ranges—R \times 1, \times 10, \times 100, \times 1K, \times 10K, \times 100K, \times 1 megohm. Convenient battery check. With Leads. Size: 5 $\frac{7}{8}$ x4 $\frac{3}{8}$ ". 38 R 17343 Shpg. wt., 3 $\frac{1}{2}$ lbs. Net 74.95

RCA WV-98C SR. VOLTOHMYST

99⁰⁰
No Money Down*

Big 6 $\frac{1}{2}$ " color-coded meter with 200 μ A movement and accuracy of $\pm 3\%$ on AC and DC. 1% precision multiplier resistors. Meter is burnout proof. Measures p-p voltages up to 4200 volts of sine waves. Range: DC volts, 0-5-1.5-5-15-50-150-500-1500; AC rms volts, 0-1.5-15-50-150-500-1500; Resistance, 0.2 ohms to 1000 ohms to 1000 megohms in 7 ranges. DC input resistance, 11 megohms. Sturdy, single-unit probe with built-in DC/AC/Ohms selector switch. Size: 7 $\frac{1}{2}$ x 6 $\frac{1}{2}$ x 3 $\frac{3}{4}$ ". For 110-130 volts 50/60 Hz. AC. Shpg. wt., 7 $\frac{3}{4}$ lbs.

38 R 46102 Net 99.00

RCA WV-510A SOLID-STATE MASTER VOLTOHMIST

128⁰⁰
No Money Down*

A hi-quality, solid-state electronic voltmeter designed for stable, drift-free operation. Measures DC voltage from 0.01 to 1500 V, direct current from 0.01 mA to 1.5 A, ACV from 0.2 to 1500 V, AC p-pv of complex waveforms from 0.5 to 4200 V, and resistance values from 0.2 ohms to 1000 megohms. Seven overlapping ranges for AC, resistance and current measurements; eight ranges for DC voltage measurements. Accuracy is $\pm 3\%$. With DC/AC-Ohms probe & cable, slip-on alligator clip and leads. 110-135 V, 50-60 Hz AC. Size: 6 $\frac{7}{8}$ x5 $\frac{1}{4}$ x3 $\frac{3}{8}$ ". Shpg. wt., 6 $\frac{1}{4}$ lbs.

38 R 46482W Net 128.00

Quality VOM'S, FET VOM'S and Power Monitors

TRIPLET MODEL 630 20,000 OHM PER VOLT VOM

67⁰⁰

No Money Down*

- Burnout-Proof in Ohmmeter Ranges
- Large Easy-To-Read 5½" Meter
- Single Selector Switch



5½" meter with spring-backed jewels and 1% precision Resistors. Accuracy, 2% on DC, 3% on AC. Ranges: DC and AC volts, 0-3-12-60-300-1200-6000 (DC at 20,000 ohms/volt, AC at 5000 ohms/v.); Ohms, 0-1k-10k- and 1.2-100 megohms, low reading to .1 ohm. DC current, 0-60 µA, 0-1-12-120 ma and 0-12 amps. DB. —20 to +77 (600 ohm line at 1 mw); output v., 0-3-12-60-300-1200; jack with condenser in series with AC ranges. Molded, fully insulated case, 3½x5½x7½". With batteries, leads.

38 R 73049 Shpg. wt., 4¼ lbs. Net 67.00
MODEL 630-NS. Deluxe VOM featuring 200,000 ohms/volts DC. Accuracy, 1½% DC, 3% AC. 62 ranges. AC/DC volts to 1200v. DB. —20 to +77 in 10 ranges. Current measurements from 0.1µa. With batteries, leads. 3½x7½x5½". Shpg. wt. 5 lbs.

38 R 73039W Net 122.00
 Black Cowhide Case for 630 and 630NS.
38 R 73171 Shpg. wt., 2 lbs. Net 13.90

TRIPLETT 310 FET POCKET VOM

78⁰⁰

No Money Down*

- 10 Megohm Input Resistance On All DC Ranges



Hand-held, battery operated volt-ohm-milli-ammeter featuring field-effect transistorized circuitry. 10 megohm input resistance on all DC voltage ranges. High Sensitivity (300 mv fs) allows transistor bias measurements. Features provisions for attaching clamp on AC ammeter adapter (see below). Accuracy of ±3% on DC and ±4% on AC, zero center for null measurements, and a polarity reversing switch. Ranges: DC Volts: 0-0.3-1.2-6-30-120-600; AC Volts: 0-3-12-60-300-600; Resistance: 0-5K-500K-50 megohms; DC Current: 0-0.12-1.2 ma. at 300 mv.

38 R 72009 Shpg. wt., 14 oz. Net 78.00

MODEL 10 AMMETER ADAPTER. Clamp on type ammeter, plugs into 310-FET. Jaws clamp around single conductor to measure 0-6-12-30-60-120-300 amp AC. Shpg. wt., 1 lb.

38 R 73072 Net 21.00

MODEL 379—Leather case, Holds 310 and 10.

38 R 73080 Shpg. wt., 12 oz. Net 8.80

MODEL 101 LINE SEPARATOR—Divides two conductor cords, increases sensitivity 10X and 20X. For Model 10.

38 R 73098 Shpg. wt., ½ lb. Net 8.40

DELUXE TRIPLETT 601 SOLID STATE F.E.T. VOM

166⁰⁰

With Batteries and Test Probes
No Money Down*



- 14 Ohmmeter Ranges With 7 Low Power Ranges At 75 mV. for Transistorized And IC Circuits

Lightweight, portable, battery-operated solid state volt-ohm-milliammeter with pushbutton function switches, and Field Effect Transistorized (FET) circuitry providing high input impedance (11 megohms) on all AC and DC ranges. Low Power Ohms for Integrated Circuit (IC) measurements. A total of 52 range selections can be accomplished using only one selector switch. Model 601 has an accuracy of ±2% of full scale on DC and ±3% on AC. Measures electrical parameters such as DC Volts: 0-1-3-10-100-300 and 1000; AC Volts: 0-1-.03-1-3-10-30-100-300-1000; Ohms: 1-10-100-1000-10,000-100,000—1 Meg with 10 ohm center scale—both conventional and Low Power; AC/DC current Ranges: 0-10-100-1000-10,000 µa; DB —40 to +60. Large 5" meter. 3½ x 5½ x 6½". Complete with (10) AA batteries, test probes.

38 R 77727 Net 166.00

Leather Case for Model 601.

38 R 77719 Shpg. wt., 1¼ lbs. Net 16.20

NEW SENCORE PM 157 POWER MONITOR



69⁵⁰

No Money Down*

- It Is A Zero To 1150 Watt Wattmeter
- It Is An AC Line Voltage Monitor
- It Is An AC/DC Ammeter
- It Is A Fuse Resistor Checker

One of the most practical service tools devised. Checks AC line voltage, 0-135 volts ±3% under actual operating load. As a wattmeter checks if an instrument is dissipating too much power-AC power scales are 0-115, 345, 1150 watts. Reads both AC and DC current: 0-1, 3, 10 amps. Checks fuse resistors with special scale for each fuse resistor. Determines value of blown out fuse resistor. In-circuit. The PM 157 is protected by a 10 ampere circuit breaker. Size: 8x6x5". All metal tilt handle. Includes test leads. Shpg. wt. 5 lbs.

38 R 53330 No Money Down* Net 69.50

UNIMETRICS 50,000 OHMS-PER-VOLT VOLT-OHM-MILLIAMMETER

24⁹⁵

With Batteries and Leads

- Big 4" Meter
- Low Voltage Scale for Transistor Tests
- All Ranges Burnout-Proof
- 50,000 Ohms Per Volt DC
- Mirror Scale
- Single Selector Switch
- Pocket Size—Lightweight

Advanced VOM with internal overload protection on all ranges. Eliminates burned-out resistors, meter movements, and bent pointers. Mirror scale and single selector switch. Carrying handle tilts at 20° angle for easy scale reading. Ranges: DC Volts: 0.25, 2.5, 10, 50, 250, 1000 (at 25K ohms/volt); 0-125, 1.25, 5, 25, 125, 500 (at 50K ohms/volt); AC Volts: 0-3, 10, 50, 250, 1000 (at 2.5K ohms/volt); 0-1.5, 5, 25, 125, 500 (at 5k ohms/volt); DC Current: 0-50, 0-25 ua; 0-5, 50, 500 ma; 0-2.5, 25, 250 ma; 0-5, 0-10 amps; DB: —20 to +81.5. Resistance: 0-10K, 100K, 1 Meg, 10 Meg. With batteries, leads and instructions. Imported. Shpg. wt., 2 lbs.


38 R 03004 Net 24.95



Quality Tube and Transistor Checkers

QUALITY LAFAYETTE TUBE AND TRANSISTOR CHECKER

LAFAYETTE FILAMENT
CONTINUITY TUBE CHECKER



Kit
29⁹⁵
Factory Wired
and Tested
39⁹⁵
No Money Down*

- Easy To Build Step By Step Instructions
- Checks Latest Compactrons, Nuvistors, Novar And 10 Prong Tubes
- Checks Tubes For Shorts, Leakage, Intermittents, and Quality
- Checks Transistors For AC Current Amplification

Easy, step-by-step wiring and assembly instructions. Enjoy big dollar savings when you build this fine tube and transistor tester kit. Tube section features testing of compactrons, nuvistors, novars, and 10-pin tubes in addition to 7- and 9-pin miniatures, octals, and loctal types. Short, leakage, and intermittent tests available. Quality is indicated directly on an easily read 3-color meter scale. Each section of multi-purpose tubes is checked separately. Hi-Fi, Magic-Eye, and voltage regulator tubes can also be tested. Obsolescent proof: Unique switching arrangement allows new tubes to be tested as they

become available. In addition, this fine tester also checks transistors: PNP and NPN, high or low power, for AC amplification. Tells immediately whether or not transistor is operable. Portable, rugged tester is ideal for serviceman and hobbyist alike. Enclosed in a high impact bakelite case with carrying strap. Supplied with batteries, full instructions, and ring bound manual of tube charts. For 110 VAC 60 Hz. Size: 8½ x 7½ x 4".
Shpg. wt., 5 lbs. Net 29.95
38 R 01123W As above wired and tested.
36 R 01131W Net 39.95

2⁹⁵

- Checks CRT's, Loctal, Octal, 9-Pin and 7-Pin Sockets



Small and compact as a cigarette box. Quickly checks filament continuity. Tests filaments of radio, TV picture tubes. Also can be used to test many other electrical devices and fine cords, fuses, lamps and bulbs. Has sockets for TV picture tube and loctal, octal, 9-pin, as well as 7-pin sockets. Provided with two test leads. Grey hammer-tone finish. Size: 4x3x1½". Imported.
99 R 50163 Shpg. wt., 10 oz. Net 2.95

**RCA WC-506A TRANSISTOR
AND DIODE CHECKER**

ONLY 18⁰⁰

- Checks NPN And PNP Types
- Large, Easy-To-Read Meter



Compact, battery operated instrument providing quick, simple checks of relative gain and leakage levels of out-of-circuit transistors. Panel switch provides for checking high-leakage transistors, with transistor socket, color coded test leads, and a large easy-to-read meter with a single red/green scale. Checks relative front-to-back current ratio of diodes. Powered by two 1.5v batteries. (Not included.) Size: 3¾x6¼x2".
38 R 48409 Shpg. wt., 1¼ lbs. Net 18.00
99 R 62580 "AA" Battery Net ea. .10

DELUXE PORTABLE TUBE AND CRT TESTER

Test All Modern Tubes Including Novars, Nuvistors, Compactrons, and Decals.
Test All Picture Tubes; Black and White—and Color

Only
54⁹⁵
No Money
Down*

- Tests Each Section of Multi-Section Tubes Individually For Shorts, Leakage and Cathode Emission
- Tests All Black and White Picture Tubes For Emission, Inter-Element Shorts and Leakage
- Red, Green, and Blue Color Guns Are Tested Individually For Cathode Emission, Leakage, and Shorts
- Large 4½" Dual Scale Meter

Versatile, reliable and highly accurate tube checker. Checks more than 2,500 tubes—and will accept new tubes as they become available. Tests Nuvistors; 10 pin types; Magnavols; Compactrons; Decals; and black/white CRT's with deflection angles from 50° to 114° including 110° RCA plus color CRT's. Tests each section of multi-section tubes individually for shorts, leakage and cathode emission. Indicates leakage up to 5 Megohms. Checks color guns (Red, Blue and Green) individually for shorts and leakage between control grid, cathode and heater elements. Front panel has complete set of tube pin straighteners. 4½" dual scale meter features a sealed damping chamber to assure accurate, steady readings. Unit comes complete with instruction book for current receiving and CRT tube listings. Size 14 x 3¾ x 9"D. For 117 VAC. 60 Hz. Shpg. wt., 7½ lbs.
38 R 01149W

Net 54.95



Housed in A Handsome, Sturdy, Portable Case Complete With All Adapters and Accessories Ready to Plug in and Use. No Extras To Buy!

Tube, Transistor, and IC Testers

NEW Sencore TC162 Mighty Mite Tube Tester



99⁵⁰

- Tests Over 3000 Tubes
- Stethoscope Shorts Tests

This deluxe solid-state tube tester with FET's gives you reliable and durable service. Push button function switches allow for instant and accurate measurement. Tests virtually every tube type, large or small, domestic and foreign. Checks each section of multi-grid tubes separately. Checks for all shorts, grid emission, leakage and gas. Special Stethoscope short test for checking each element of the tube. Tests for grid leakage to 100 megohms. New pin elimination switches permit testing more tubes than ever before. Eliminates "normal" shorts caused by internal connections in tubes. Complete portability in a rich vinyl-clad, brushed chrome trimmed case. Power Requirements are 115 volts AC at 32 watts. For 56/60 Hz. Size: 11 3/4 x 11 1/2 x 11 1/4". Shpg. wt., 9 lbs. No Money Down.

38 R 53348W

Net 99.50

B&K 466 CRT Tester/Rejuvenator



129⁹⁵

- Checks And Rejuvenates CRT's In TV Set
- Checks And Repairs Each Color Gun

Indicates picture tube quality. Checks color or black and white CRT's for leakage, shorts, opens, emission. Rejuvenates virtually all CRT's. Exclusive Feature: "Monitored Rejuvenation" — you can watch the emission change as you rejuvenate CRT. Unique "Super-Rejuvenate" function for restoring emission of otherwise worthless CRT's. Operates tubes at correct filament voltage. Handles H1, G2, and Lo G2 tubes. Comes equipped with 3 multisolet adapters for testing all new CRT's including Trinitrons. Measure G1 voltage. Color coded G2 controls. Large 4 1/2" precision meter with scale coded to front panel controls to prevent errors. Plastic/aluminum type attaché carrying case. Size: 13 1/4 x 9 1/2 x 5 3/4". For 105-125V 50-60 Hz AC. Shpg. wt., 8 lbs. No Money Down.

38 R 17327WX

Net 129.95

B & K 707 Mutual Conductance Tube Tester



209⁹⁵

- Tests All New And Old Type Tubes
- Virtual Obsolescent Proof

The deluxe "707" measures true dynamic mutual conductance in seconds. Tests all new type tubes including novistors, 10-pin types, 12-pin compactrons, hybrids, European types, voltage regulators, thyratrons etc. and provides for future new sockets. Checks for all shorts, grid emission, leakage and gas. Large 4 1/2" meter with easy-to-read "Replace-Good" scale for quick life tests. Checks each section of multi-grid tubes separately. Lists commonly used tube types on panel with complete listing of cover reference chart. Includes 7, 9, and 10-pin tube straighteners and handsome leatherette-covered carrying case. 117V 50/60 Hz AC. Size: 16 1/4 x 15 3/4 x 5 1/2". Shpg. wt., 16 1/4 lbs.

38 R 17152W No Money Down* 209.95

RCA Deluxe WT-501A Transistor Tester



68⁰⁰

- DC Beta From 1 to 1000
- Collector-to-Base Leakage As Low As 2 μ A

Completely portable — requiring no external power source, tests both low and high power transistors, and has both NPN and PNP sockets. Tests out-of-circuit transistors for d-c beta from 1 to 1000, collector-to-base leakage as low as 2 microamperes, and collector-to-emitter leakage from 20 microamperes to 1 ampere. Special low impedance circuitry assures reliable in-circuit testing. Collector current is adjustable from 20 microamperes to 1 ampere in four ranges. Three color-coded test leads are provided. With two 1.5 volt batteries. Shpg. wt., 6 lbs. 2 oz. No Money Down.

38 R 46342

Net 68.00

SENCORE TF151 "In or Out of Circuit" Transistor Tester



129⁵⁰

- With Special Reference Book for Testing Transistors and FET's

Accurate, easily read 6 meter. Tests for AC Beta and out of circuit I_{cb0} leakage. Increased current check for high power transistors make tests more accurate. Special tests for critical RF transistors like GE9's. Also makes the following special tests on FET's: True GM mutual conductance in or out of circuit; I_{gss} leakage checked out of circuit; Special Gate 2 check provided for two gate FET's; Special Id_{ss} (Zero Bias) current check provided for matching FET's or for Industrial "cutting"; Special positive bias test for new enhancement FET's. For 115 VAC. Size: 9 1/2 x 7 1/2 x 6". Shpg. wt., 12 lbs. No Money Down.

38 R 53272W

Net 129.50

NEW In-Circuit IC Tester



- For Testing and Troubleshooting IC's

120⁰⁰

- Complete with flexible cable and 9 adapter plugs

Self-powered IC tester features a clip probe and a flexible 24" cable for in-system testing of both 14 and 16-pin dual in-line TTL or DTL integrated circuits. Displays the logic states of all pins simultaneously. Circuit malfunctions can be quickly isolated and diagnosed. Suitable for design or service testing of gates, clocks, flip-flops, counters, and adders. Tester lamps are ON for IC logic highs and OFF for lows. When used for in-system testing, the IC tester is powered by the IC being tested. Requires no bezels or overlays. Voltage requirements: 5 V \pm 10% across two or more inputs. Temperature rating: 0 to 75° C. Comes with luggage-type foam lined carrying case. No Money Down*.

38 R 54007W wt., 3 lbs.

Net 120.00

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 397

Signal Generators — Color Bar Generators

NEW! RF SIGNAL GENERATOR

ONLY
39⁹⁵



SINE/SQUARE WAVE AUDIO GENERATOR

Only
59⁹⁵



- 120 kHz-130 MHz on Fundamentals
- 120 kHz-390 MHz on Calibrated Harmonics

Accurate, inexpensive wideband RF signal generator can be used for IF-RF alignment; audio signal tracing of TV, FM, and AM sets; TV Linearity checks, and 400 cycle audio testing. Dial accuracy of better than 1%. Features a wide frequency coverage from 120 kHz to 390 MHz with internal modulation of either 400 Hz or 1000 Hz. External modulation may be applied. Crystal Oscillator, 1 to 15 MHz (FT-243 type x'tal not included). For 115 V; 50/60 Hz. Size: 7½x10¾x4½"D; Shpg. wt., 7½ lbs. Imported.

38 R 40014W No Money Down* Net 39.95

- 20 Hz to 200 KHz in 4 Decade Bands
- Calibration Accuracy $\pm 3\% + 2$ Hz

Employs Wien Bridge configuration for sine wave generation from 20 Hz to 200 kHz. For square waves, a Schmitt trigger circuit is used over the 20 Hz to 20 kHz range for pulse shaping. Sine Wave Output Voltage, 7 V. rms, approx. Output Flatness within ± 0.5 db referred to kHz. Distortion, less than 2% (below 20 kHz). Square Wave, Range: 20 Hz to 20 kHz; Output Voltage, 6 V. p-p, max. Output Impedance 2 K ohms approx. Power supply for 115/230 V., 50/60 Hz; 10 VA approx. Size: 7½x10¾x4½"D; Imported. Shpg. wt., 6¼ lbs. 38 R 40022W No Money Down* Net 59.95

RCA WR 50B RF SIGNAL GENERATOR

75⁰⁰ with SWEEP FEATURES



Ideal for aligning and trouble-shooting AM, FM, TV, CB and Ham receivers. Provides tunable output from 85 kHz to 40 MHz in 6 ranges on fundamentals, CW or modulated RF. Dial calibration accuracy $\pm 2\%$. Built-in 400 Hz audio oscillator for internal or external modulation. Front panel crystal socket for oscillator calibration. Shielded outputs. 5¾x7¾x4¾"D. For 105-130 V., 50/60 Hz AC. Shpg. wt., 7¼ lbs. 38 R 46318 Net 75.00

B & K 200D SOLID-STATE RF GENERATOR

189⁹⁵

- Built-in Crystal Calibration
- 100 kHz to 216 MHz In 5-Bands



Features 100% silicon transistor circuitry, zener-regulated power supply, 6-individually shielded step attenuators, variable fine output level control, and calibrated 200 μ a D'Arsonval meter. Range: 100 kHz to 54 MHz on fundamentals (5 ranges), and 54 to 216 MHz on harmonics. Outputs: modulated RF, unmodulated RF, external modulated RF, 400 Hz audio. For 110-130V., 60 Hz AC. Size: 12¾x7¼x8"D. Shpg. wt., 14 lbs. 38 R 17319WX No Money Down* Net 189.95

SECORE CG-19 PORTABLE COLOR GENERATOR

84⁵⁰

No Money Down*



- 10 Standard Color Bars plus Standard Crosshatch, Dot, Vertical and Horizontal Lines

Battery operated, lightweight, solid-state. Uses standard RCA licensed color bars plus standard cross-hatch, dot, vertical and horizontal lines. Simple to use... just set selector switch to desired pattern, and connect the RF cable to the antenna terminals of color TV set. Features RF channel setting, timer adjustment and interlace control. Low current drain from two 6.5 volt batteries (not included). Size: 8¾x2½x5½"D. 38 R 53322 Shpg. wt., 4 lbs. Net 84.50 32 R 46790 Pkg. of 2-batteries for above Net 2.95

BOSCO "MOSQUITO" SIGNAL INJECTOR


14⁹⁵



Transistorized, pocket sized, and cordless. Oscillates at 1 kHz with harmonics to 30 MHz. Can be coupled into magnetic circuits and pickups without leads. Output 50v p-p. Output impedance, 10K. DC input voltage, 600V., max. Size: 5¾x1¾x2" O.D. 38 R 22103 Shpg. wt., 6 oz. Net 14.95 99 R 62580 "AA" Battery for "Mosquito" Net ea. .10

398 Lafayette Cat. No. 720

DELUXE COLOR BAR PATTERN GENERATOR



ONLY
159⁹⁵
No Money Down*

- 15 Patterns Including Single Dot and Single Cross
- Scope Sync Pulse

Extremely versatile color generator produces 15 patterns including the all important single dot and single cross. Trigger pulses available to sync oscilloscope. Composite video signals for video circuit testing. Gun killers for purity and convergence adjustments. Outputs: RF Output, Channel 5 and 6; Patterns-Color Bars: Gated Rainbow, R-Y, B-Y, and (R-Y); Rainbow; Oots: Fine 15 vert. x 21 horiz., Coarse 7 vert. x 11 horiz., Single Dot centered on raster; Cross-hatch: Fine 21 vert. x 15 horiz., Coarse 11 vert. x 7 horiz., Single Cross centered on raster; Vertical: Fine 21 lines, Wide 11 lines, Single line; Horizontal: Fine 15 lines, Wide 7 lines and Single line. Chroma Level control: 0-200% continuously adjustable. For 105-125 V., 50/60 Hz AC. Size: 3¼x7¼x7¾"D. Shpg. wt., 6¼ lbs. Imported. 38 R 40006WX Net 159.95

*See Page 22 for Full Credit Details on Easy Pay Plan

TV Circuit Analyzer and Oscilloscopes

**B & K MODEL 1077B COLOR
AND B&W TV ANALYST**



- For Checking Every Stage In a Color and B&W TV Receiver
- With Solid-State-Sweep Drive

399⁹⁵

No Money Down*

Designed to simplify and speed servicing of black and white, color, UHF, VHF, tube-type and transistorized TV receivers. Permits you to inject your own TV signals at any time, at any point . . . while you watch the generated test pattern on the picture tube or television set itself. Supplies a complete test pattern by means of a flying spot scanner system. Eight VHF RF channels, VHF channels 14-82, 20 to 45 MHz IF, audio, video sync, three color adjustment patterns, bias voltage, and AGC keying pulse ARE ALL AVAILABLE. Checks B+ boost and gives high voltage indication. Provides 3-color receiver test patterns: White dot, cross hatch, color bar. Complete with test leads and standard test pattern slide transparencies. For 105-125V., 60 Hz AC. Size: 17x10½x10". Shpg. wt., 32 lbs.

38 R 17301WX Net 399.95

**NEW 5" SOLID STATE
TRIGGERED SCOPE**



- Calibrated Triggered Sweep
- Vectorscope Input

339⁵⁰

No Money Down*

Professional 5" triggered scope with calibrated vertical input and calibrated time base. Features a vertical sensitivity of 20 mV/cm, 2 Hz to 10 MHz frequency response, rise time of 35 nanoseconds. Horizontal sensitivity: 200 mVpp/cm or better, 2 Hz to 200 kHz Bandwidth, 0.2 μ sec/cm sweep speed. 5x sweep magnifier. Edge Lighted graticule. Has a flat face 5" CRT with built-in calibrator and a vectorscope input. Power requirements: 115V 50/60 Hz; Approx. 50 VA. Size: 10½"H x 8"W x 16½"D. Imported. Shpg. wt., 21 lbs.

38 R 40030WX Net 339.50

**NEW B & K 1450B
OSCILLOSCOPE WITH
VECTORSCOPE FEATURE**



- Intermittent Analyzer with Visual Indicators and Electronic Memory Plus Remote Alarm

299⁹⁵

No Money Down*

Improved version of model 1450. Features Automatic Synchronization—that makes patterns stand still regardless of amplitude, and will actually sync a 10 MHz signal. Double Scale Calibrated Screen reads peak-to-peak voltage directly. Vectorscope inputs and controls. Shows vector patterns exactly as specified by color TV manufacturers. Z-axis input. Has horizontal/vertical push-pull amplification. Response: vertical, ±3 db., 1 Hz to 400 kHz. Sensitivity: vertical, 50 mV rms/inch; horizontal, 0.6 volts rms/inch. Sweep: 5 Hz to 500 kHz. Synchronization: automatic. + and - INT., 60 Hz. EXT. 17¼ D x 13¾ H x 8¾ W. For 110-120V., 60 Hz AC. 38 R 17350WX Wt., 27 lbs. Net 299.95

Substitution Boxes and Capacitor Analyzers

**SENCORE RC 146 SUBSTITUTION BOX
FOR CAPACITORS, RESISTORS, AND RECTIFIERS**

NEW



69⁹⁵

- Provides 75 Used Values of Carbon Resistors, Capacitors, Electrolytics, and Power Resistors.
- Also Provides Substitution Testing For 0.5 Amp. Universal Silicon and Selenium Rectifiers

Save valuable servicing time 'hunting up' exact components for substitution testing only. Provides twelve 1-watt resistors from 10 to 5.6k ohms. Twelve 1/2-watt resistors from 10k to 5.6 megohms. Ten 600-volt capacitors from 100 mmfd to 0.5 mfd. Ten electrolytics that can be used singly or as duals to form up to 25 different values. Electrolytic surge protector circuit prevents arc, spark or heating of electrolytic in set; 2mfd to 250mfd at 450 volts. Power resistors of 20 watts from 2.5 to 15,000 ohms, and a universal 0.5 amp. silicon and selenium rectifier for substitution. Size: 10½ x 4¾ x 4¾" Shpg. wt., 4 lbs.

38 R 53363 No Money Down* Net 69.95

**SPRAGUE MODEL TO-6
TELOHMIKE CAPACITOR ANALYZER**

149⁵⁰

No Money Down*



- Tests Low-Voltage Capacitors Used in Transistor Circuits Without Damage
- Designed for Versatility, Accuracy, Safety and Convenience

A moderately priced instrument for complete analysis of all types of capacitors, including low-voltage capacitors, at a guaranteed accuracy of ±3% for values to 200 mfd. and ±5% from 200 mfd. up. Capacitance bridge measures capacity in five ranges from 1 mfd to 2000 mfd. with color-keyed pushbutton range selection. Large meter directly indicates insulation resistance up to 50,000 megohms for paper, ceramic and mica capacitors. Wien bridge measures power factor of electrolytic capacitors from 0 to 50% in three ranges. Leakage current of electrolytic capacitors measured directly on meter, with continuously variable test voltage up to 600 volts. Burn-out-proof meter; safety switch. 8¾ x 14¾ x 6¾". For 110-120v 50/60 Hz AC. Shpg. wt., 18 lbs.

38 R 70011W Net 149.50

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 399

EICO VTVM's and VOM's—Kit or Factory Wired

NEW! MODEL 239 FET VOM



KIT
39⁹⁵

WIRED
59⁹⁵

• Battery Operated

Use the 239 on your bench or in the field. Checks semiconductor and vacuum tube circuits. 11 Megohm DC input impedance. Reads AC RMS and DC voltages in seven steps from 1 to 1000 volts on large 4½" meter. Measures and reads peak-to-peak AC to 2800 volts. Check resistance from 0.2 ohms to 1000 M-ohms on seven ranges. Includes exclusive time-saving Uni-Probe. Peak-to-peak AC Volts: 0-2.8, 8.5, 28, 85, 280, 850, 2800. AC RMS/DC Volts 0-1, 3, 10, 30, 100, 300, 1000. Ohmmeter: 0.2 to 1000 ohms. Operation on 3 "A" and 1 "D" batteries. Size 8½ x 5¼ x 5". Shpg. wt. 4 lbs.
38 R 27672 Model 239 Kit Net 39.95
38 R 27664 Factory wired Net 59.95

Model 240 FET VOM Kit



KIT
59⁹⁵

WIRED
79⁹⁵

• AC or Battery Operation

Transistorized volt-ohmmeter especially suited for semiconductor circuit testing. Low 1 v. scale allows accurate readings as low as 0.05 v. Features DC/AC-Ohms Uni-Probe and 7 non-skip ranges in professional 10 db steps. 4½" 200µa meter movement. DC impedance: 11 megs. AC impedance: 1 meg. Peak-to-Peak AC volts: 0-2.8, 8.5, 28, 85, 280, 850, 2800 AC RMS/DC volts: 0-1, 3, 10, 30, 100, 300, 1000. Frequency response: 25 Hz to 2 MHz (up to 250 MHz with optional PRF probe). Ohmmeter: 0.2-1000 Meg. Operates on 105-132 VAC or batteries. Size 8½ x 8¼ x 5". Shpg. wt., 8¾ lbs.
38 R 27466 Model 240 Kit Net 59.95
Model 240 Factory Wired
38 R 27474 Net 79.95

Deluxe Model 242 FET-VOM Kit



KIT
69⁹⁵

WIRED
94⁵⁰

FET volt-ohmmeter with single Uni-Probe for DC/AC-ohms-ma measurements. Large 6½" meter. Designed to be used effectively on vacuum tube and semiconductor circuits. 1 v. scale for accurate readings as low as 0.05 v. P-P AC volts: 0-2.8, 8.5, 28, 85, 280, 850, 2800 and milliamperes. AC RMS/DC and current: 0-1, 3, 10, 30, 100, 300, 1000 v. and milliamperes. Input impedance: DC 11 Meg. AC 1 Meg. Frequency response: 25 Hz to 2 MHz (up to 250 MHz with optional PRF probe). Ohmmeter: 0.2 ohms—1000 Megohms in 7 ranges. For 105-132 VAC or battery operation. 38 R 27482 Model 242 Kit Net 69.95
Model 242 Factory wired
38 R 27508 Net 94.50



KIT
59⁹⁵

WIRED
84⁹⁵

MODEL 235K PROFESSIONAL VTVM KIT

Deluxe VTVM features 6" 200 micro-amp meter, 1/2-volt full scale DC range for transistor servicing. AC/DC "Uni-Probe", and 1% precision multiplier resistors. Ranges: AC/DC volts, 0-0.5, 1.5, 5, 15, 50, 150, 500, 1500; p-p volts, 0, 4, 14, 42, 140, 1400, 4200; resistance, 0.2 ohms to 1000 megs in 7 ranges. Response: 3 Hz to 3MHz. Accuracy: 3% AC and DC. Has 11 megohm DC input supplied with uniprobe. For 117 v., 50/60 Hz AC.
38 R 27169 No Money Down* Net 59.95
Model 235. As above, but factory wired.
38 R 27177 Net 84.95



KIT
34⁹⁵

WIRED
49⁹⁵

MODEL 232K PEAK-TO-PEAK VACUUM TUBE VOLTMETER KIT

A precision-unit with advanced engineering features. 11 megs input impedance. 1% precision ceramic multiplier resistors used. Measures directly peak-to-peak voltage 0-4, 14, 42, 140, 420, 1400, 4200. DC/RMS sine volts: 0-1.5, 5, 15, 50, 150, 500, 1500 (up to 30,000 volts with HVP probe, and 250 MHz with PRF probe). Ohms: 0.2 ohms to 1000 megs in 7 ranges. Easy calibration. 4½" meter, can't-burn-out circuit. Zero center. With AC/DC Uni-Probe. Exceptional stability and accuracy. All components and instructions supplied. For 105-125 50/60 Hz AC. Size: 8½ x 5 x 5". Shpg. wt., 6 lbs. No Money Down*
38 R 26179 Model 232 Kit Net 34.95
Model 232. As above, but factory wired.
38 R 26187 Net 49.95

FAMOUS 500 SERIES VOM KITS



As Low As
16⁹⁵

MODEL 566K. Large 4½" meter features: AC/DC sensitivity of 1K ohm/v. totals 38 ranges: AC/DC volts: 0-1.5-10-500-5000AC/DC. Current: 0-1-10 ma. 0-0.1-1 amps. Ohms: 0-5K-100K-1 meg. DB: —20 to —69 in 6 ranges. All components and instructions supplied. 6¾x5¼x4¾". Shpg. wt., 3¼ lbs.
38 R 26013 Model 566 Kit Net 19.95
Model 566. As above, but factory wired.
38 R 26021 Net 29.95

Model 566K. Same as 566K but with 1% resistors. Shpg. wt., 3¼ lbs.
38 R 26039 Net 21.95
Model 556. As above, but factory wired.
38 R 26047 Net 29.95

MODEL 536K (Not Illustrated). Outstanding value. 3" meter features AC/DC sensitivity of 1K ohm/v. 31 ranges—AC/DC volts: 0-1.5-10-50-100-5000. AC/DC current: 0-1-10 ma., 0-0.1 amp. ohms: 0-5K; 100K-1 meg. DB —20 —69 in 6 ranges. All components and instructions supplied. 6¼ x 3¾ x 2¾". Shpg. wt. 2½ lbs.
38 R 26054 Model 536 Kit Net 16.95
Model 536. As above, but factory wired.
38 R 26062 Net 22.95

MODEL HVP-5 HI-VOLTAGE PROBE

with Built-in Meter

22⁹⁵

WIRED ONLY

Light, compact! Measures up to 30 kv. Barriers are provided to isolate high voltage tip from probe handle and meter. Wt. 6 oz.
38 R 27557 Net 22.95



EICO PROBES

• A Must For Servicemen, Engineers, and Technicians

HVP2 HV PROBE — wired only. Extend range of VTVM to 30,000 v. Shpg. wt., ½ lb.
38 R 26344 Net 9.95

PRF-11K—11 meg RF probe kit.
38 R 26286 Shpg. wt., ½ lb. Net 4.95

PRF-11—As above, factory wired.
38 R 26294 Shpg. wt., ½ lb. Net 6.95

EICO Tube and Transistor Checkers—Kit or Factory Wired

MODEL 680K TRANSISTOR & CIRCUIT TESTER KIT



KIT No WIRED
34⁹⁵ Money **54⁹⁵**
 Down*

- Measures Transistor ICBO, ICEO, DC Beta
- 20K Ohm per Volt VOM For Testing Transistor Circuits

Accurately measures basic transistor and diode characteristics. Checks ICBO, ICEO, DC Beta; simulated AC Beta. 20,000 ohms/volt meter includes 5 DC current range. ICBO/IC ranges: 50 μ a, 500 μ a, 5ma, 50ma, 500ma. Transistor DC Beta ranges: 2 to 30, 20 to 300 Test Positions: ICBO, ICEO, PWR, ICBO, PWR, ICEO, B Cal, Read B. DC voltage ranges: 5V and 50V, 3 resistance ranges: 0 to 2,000, 0 to 200,000, 0 to 20 megohm). \pm 3% accuracy. Self-powered. With leads, batteries. Bakelite case 6Hx5Wx3"D.

38 R 26856 Kit Shpg. wt., 3 1/4 lbs. Net 34.95
 Model 680. Same as above, but factory wired.
 38 F 26864 Net 54.95

MODEL 685 DYNAMIC SEMI-CONDUCTOR & CIRCUIT ANALYZER



KIT No WIRED
99⁹⁵ Money **149⁹⁵**
 Down*

- Measures FET and Bipolar Transistors
- Test Transconductance and Beta—In and Out of Circuit
- Built-in Voltmeter and Ohmmeter

Tests FET, Bipolar and Unijunction transistors, Silicon Controlled Rectifiers, Power Rectifiers, Signal Diodes, and Zener Diodes. Built-in DC voltmeter and ohmmeter, 0-500 volts, 400 ohms-10 megohms, 1% resistors, 50 μ a Taut Band meter. AC beta test from 2 to 1000 on power and small signal devices, from 2 to 100 on RF transistors. 0-50,000 micromhos AC transconductance readings, IGSS, IGSS and pinch-off voltage readings. Bipolar Transistor Tests: AC Beta 2-100 at IC=0. 2ma for RF devices. For 120 VAC, 60 Hz. Size (HWD): 12 1/2 x 8 1/2 x 6", wt., 9 lbs.

38 R 27623 Model 685 Kit Net 99.95
 Model 685. Same as above but factory wired.
 38 R 27631W Net 149.95

MODEL 443K SEMICONDUCTOR CURVE TRACER KIT



KIT No WIRED
99⁹⁵ Money **149⁹⁵**
 Down*

- Output of 443 Can be Displayed on Any General Purpose Scope

Tests power and signal transistors, diodes and rectifiers. Adopts to any general purpose oscilloscope and displays the DC characteristics of semiconductor devices. Built in oscilloscope calibrator voltage switch. Contains a flashing indicator light to indicate when high voltage is present at the diode test terminals. Transistor tests: Beta — 6 volts at 10 ma, maximum collector current for signal transistors and 6 volts at 1 amp. max. collector current for power transistors. Diode tests include: Forward current (0-1,100 ma). Reverse Current (IR) — (1,10,100 μ a/div). Peak Inverse Voltage (PIV) — (1,10,50, 100 volts/div). Size: 3x11 1/2 x 9 1/2.

38 R 27409 Shpg. wt., 10 1/2 lbs. Net 99.95
 Model 443 Kit as above but factory wired.
 38 R 27417 Net 149.95

MODEL 635K PORTABLE TUBE TESTER KIT



KIT No WIRED
49⁹⁵ Money **74⁹⁵**
 Down*

- Extremely Portable Design

Tests new Decals, Magnovacs, Novars, Nuvistors, Compactrons, 10 pin, foreign, hi-fi, industrial types, and all popular TV picture tubes. Rapid tests for dynamic cathode emission, shorts, grid leakage, and gas. Even where internal pins are tied or heater is tapped, shorts can be detected. 3 1/2" D'Arsonval type meter protected against burnout. Other features include: meter bridge circuit for assured accuracy; pin straighteners; long life phosphor bronze sockets; short and grid leak indicator; power indicator; modern luggage design, scuff-proof case. Includes complete tube chart. 8 1/2 x 11 1/4 x 3 3/4". Shpg. wt., 8 3/4 lbs.

38 R 27383 Kit Net 49.95
 Model 635—As above, but factory wired.
 38 R 27391 Net 74.95

MODEL 633K CRT TESTER AND REJUVENATOR KIT



KIT No WIRED
89⁹⁵ Money **119⁹⁵**
 Down*

- Tests, Repairs, Rejuvenates Color or B&W CRT's
- Luggage Case Holds 5-Socket Cable and Line Cord

Universal multi-socket cable accommodates any black and white or color CRT. 3-range filament voltage selector. Grid cut-off voltage and filament voltage read on 4 1/2" meter, also beam current on a 3-color BAD-7-GOOD scale. Neon-lamp circuit for short-open testing. 6 push-buttons enable instantaneous measurement without danger of CRT damage. Spring-return repair push-button is used to apply 1000 VDC for rejuvenate process. For 105-130 Volts AC, 60 Hz. Size: 12W x 9 3/4 x 4 5/8" D. Shoe. wt., 11 1/4 lbs.

38 R 27367 Kit Net 89.95
 Model 633 as above, but factory wired.
 38 R 27375W Net 119.95

MODEL 667K DYNAMIC CONDUCTANCE TUBE AND TRANSISTOR TESTER KIT



KIT No WIRED
99⁹⁵ Money **149⁹⁵**
 Down*

- Separate Plate, Screen, and Grid Switches

- Test All New Tube Types

Combines a mutual conductance test with a peak emission test to give a single reading of tube quality. Also checks transistors for leakage and beta. Tests almost every domestic or foreign tube including nuvistors, novars, compactrons, miniatures, subminiatures, octals and loctals. Tests special purpose tubes, voltage regulators, electron ray, etc. Multi-circuit level switch; 15 tube-element pushbutton switches. 4 1/2" 200 μ A'Arsonval meter; roll chart. Steel case. For 105-130v, 60 Hz AC, 12 x 15 x 4 1/2". Shpg. wt., 20 1/2 lbs.

38 R 26526W Net 99.95
 Model 667 as above, but factory wired.
 38 R 26534W Net 149.95

EICO Signal Generators - Kit or Factory Wired

MODEL 147AK DELUXE SIGNAL TRACER KIT



KIT **39⁹⁵** WIRED **59⁹⁵**

A deluxe instrument with superb testing facilities, engineered for high sensitivity as well as good audio quality. Features high gain RF and low gain audio channels. Both visual and aural monitors. With shielded RF crystal demodulator, valuable noise locator circuit, built in calibrated wattmeter, substitute test speaker, amplifier and output transformer. Output for VTVM or scope. Triode input circuit for extreme low noise. Hum free operation. Complete with all components and instructions with probes. For 105-125 VAC 50/60 Hz. 8x10x4 1/4". Shpg. wt., 11 lbs.

38 R 26617 Kit Net 39.95
Model 147A. As above, but factory wired.
38 R 26625 No Money Down* Net 59.95

MODEL 150K SOLID-STATE SIGNAL TRACER KIT



KIT **49⁹⁵** WIRED **69⁹⁵**

Multi-purpose signal tracer! Provides component substitution of output transformer and speaker. Has independent RF and audio inputs; speaker and calibrated meter output indicators. Ideal for troubleshooting AM, FM and TV receivers as well as hi-fi and PA audio equipment. High frequency RF point contact crystal demodulator probe and direct audio probes are provided. SPECIFICATIONS: Output—400 mw. Input for rated output—RF 1 mV, audio —63 mV. Hum—better than 60 db below 400 mw. Meter movement—200 uA. For 105-132VAC., 50/60 Hz. Size: 7 1/2 x 8 1/2 x 5" D. Shpg. wt., 8 3/4 lbs.

38 R 27516 Kit Net 49.95
Model 150 as above but factory wired.
38 R 27524 No Money Down* Net 69.95

MODEL 369K TV-FM SWEEP MARKED GENERATOR KIT



KIT **109⁹⁵** WIRED **159⁹⁵**

- Aligns TV and FM IF's
- Both Variable and Crystal Marker Oscillator
- Incorporated Marker-Adder
- Supplied with Cables

Features post injection marker and sweep circuit. Sweep gen. is independent of marker gen. and feeds sweep signal only to IF strip being aligned. 5 ranges, from 3.5 MHz to 220 MHz. Impedance: 50 ohms. Variable frequency Marker: 4 ranges, 2-225 MHz — 2.75 MHz in Fundamentals, to 225 MHz in Harmonics. Fixed Frequency Marker: 4.5 MHz. Crystal included. For 105-125V, 60 Hz AC. Size: 12 1/2 x 8 1/2 x 7". Shpg. wt., 16 lbs.

38 R 26674W Kit Net 109.95
Model 369. As above, but factory wired.
38 R 26682WX No Money Down* Net 159.95

MODEL 379 SOLID-STATE SINE/SQ WAVE GENERATOR KIT



KIT **69⁹⁵** WIRED **99⁹⁵**

- Covers 20 Hz to 2 MHz In 5-Bands

Simultaneous Sine and Square wave outputs! Frequency Range: Sine Wave — 20 Hz to 2 MHz, Square Wave — 20 Hz to 200 kHz; Output Voltage: Sine Wave — 0-7.5 volts rms into high impedance output, 0-6.5 volts into 600 ohms; Square Wave — 0-10 volts peak-to-peak into high impedance. Accuracy: 3%. For 105-132VAC., 50/60 Hz. 7 1/2 x 8 1/2 x 8 1/2".

38 R 27532 Shpg. wt., 11 1/4 lbs. Net 69.95
Model 379 as above but factory wired.
38 R 27540 No Money Down* Net 99.95

MODEL 377K AUDIO GENERATOR KIT



KIT **49⁹⁵** WIRED **64⁹⁵**

- Sine Wave: 20-20,000 Hz In 4 Bands
- Square Wave: 60-50,000 Hz

Model 377 features R-C (Wien Bridge) oscillator circuit with 1% precision resistors. Includes choke filtering in the power supply. Excellent calibration accuracy, stability and purity of wave-form. Response: ±1.5db, 60-150,000 Hz. Distortion less than 1%. Hum less than 0.4%. Accuracy 3%. For 117VAC., 60 Hz, 50 watts. Size: 7 1/2 x 11 1/4 x 7 3/4". Shpg. wt., 14 lbs.

38 R 26633 Kit Net 49.95
Model 377 As above, but factory wired.
38 R 26641 No Money Down* Net 64.95

NEW DELUXE 378K AUDIO GENERATOR




KIT **69⁹⁵** WIRED **99⁹⁵**

- Switch Selectable Frequency Output
- One Hz. to 110 kHz
- Metered Output Voltage

Switch selectable frequency output from 1 Hz. to 110 kHz: one Hz steps (1-110 Hz); 10 Hz steps (10-1100 Hz); 100 Hz steps (100 Hz - 1.1 kHz); 1 kHz steps (1 kHz to 110 kHz); FREQUENCY ACCURACY: ±5%. DISTORTION: Less than 0.1%. 20 Hz-20 kHz. OUTPUT VOLTAGE RANGES: 0-3. 10V into HI-Z (10K min.); 0-.003, .01, .03, .1, .3, 1V. into ext. or internal 600 ohm load. OUTPUT METER ACCURACY: ±5% of full scale. POWER REQUIREMENTS: 120V, 50/60 Hz, 40 watts. SIZE: 8 1/4 x 12 1/2 x 9" D. Shpg. wt., 16 lbs.

38 R 27706W Kit Net 69.95
Model 378. As above, but factory wired.
38 R 27714W No Money Down* Net 99.95

MODEL PSI SIGNAL INJECTOR PROBE KIT



Pocket size, cordless, pen type instrument generates and injects a signal covering the audio, IF, and RF spectrum. Contains a solid state oscillator powered by two long-life 1 1/2 volt pen-light cells. Can be coupled into magnetic pickups and circuits without leads. Oscillates at 1000kHz with harmonics to 30MHz. Impedance: 10K ohm. Size: 5 1/4" long x 1/2" diameter.
38 R 27359 Kit. Wt., 4 oz. Net 5.95
38 R 27342 Factory Wired Net 9.95

MODEL 385 SOLID STATE COLOR BAR GENERATOR KIT



NEW LOW PRICES!
KIT **69⁹⁵** WIRED **99⁹⁵**

- 10-Bar Color Display plus Dot and Cross-hatch Pattern

Crystal-controlled, portable unit. Feeds directly into antenna terminals on TV. Produces 10-bar color display plus a well defined dot and cross-hatch pattern. Provides individual horizontal and vertical lines for convergence adjustments. A color-coded gun killer can eliminate 1, 2, or 3 colors. Operates on 6 "C" cells. 2 1/2 x 8 1/2 x 8. Shpg. wt., 7 lbs.

38 R 27441 Kit. No Money Down* Net 69.95
38 R 27458 Factory Wired Net 99.95
99 R 62572 "C" batteries (6 req.) Net ea. .16

EICO Generator and Scopes—Kit or Factory Wired

MODEL 324K RF SIGNAL GENERATOR KIT



KIT
39⁹⁵

WIRED
54⁹⁵

- 150 kHz. - 435 MHz. in 7 Bands with $\pm 1.5\%$ Accuracy

For IF-RF alignment, signal tracing and trouble-shooting of TV, FM, AM sets all on fundamentals; marker generator for alignment of new HF and older LF TV IF's. Range: 150 kHz-145 MHz on fundamentals; 111-435 MHz on calibrated harmonics— $\pm 1.5\%$ frequency accuracy. Internal 400 Hz sine-wave modulation variable from 0-50%. Colpitts oscillator. Variable gain external modulation amplifier. Turret-mounted, slug-tuned coils. RF output 100,000 microvolts. AF output up to 10 volts. Output impedance is 50 ohms. For 105-125V. AC 50/60 Hz. Size: 8x10x4 $\frac{3}{4}$ ".

Shpg. wt., 9 $\frac{1}{4}$ lbs.

38 R 26591 Kit. Net 39.95

Model 324. As above, but factory wired.

38 R 26609 No Money Down* Net 54.95

EICO 330K SOLID STATE RF SIGNAL GENERATOR KIT



KIT
59⁹⁵

WIRED
89⁹⁵

- 100 kHz. to 54 MHz. in 5 bands
- Precision Vernier Tuning Control
- RF Coarse Attenuation—3 Steps
- RF Fine Attenuation—0 to 100%

Wide-range RF generator for aligning TV's, AM and FM radios and communications equipment. Coarse and fine level controls for both the modulated and unmodulated RF output. RF Fundamental Frequencies. 100 kHz to 54 MHz in 5 bands; Output: more than 300,000 μ V into 50 ohm load; RF Coarse Attenuation: three steps; RF Fine attenuation: 0-100%; Internal Modulation: approx. 400 Hz from 0-100%; Power requirements: 105-132 V. 50/60 Hz AC. Size: 7 $\frac{1}{2}$ "H x 8 $\frac{1}{2}$ "W x 5"D. Shpg. wt. 8 $\frac{1}{4}$ lbs.

38 R 27658 Model 330 Kit. Net 59.95

Model 330 as above but factory wired.

38 R 27649 No Money Down* Net 89.95

MODEL 950K R-C BRIDGE & RCL COMPARATOR KIT



KIT
29⁹⁵

WIRED
44⁹⁵

- Comparator Range Allows the Use of Complementary Components as Standards

Combination RC bridge and comparator, a direct reading ratio scale for comparison measurement of capacitance, resistance and inductance with a "standard" complementary component. Measures (in 4 ranges) 0.5 ohms to 500 megohms; 10 mmf to 5000 mfd. Comparator range: .05 to 20. Variable DC polarizing voltage from 0 to 500V tests capacitors for leakage and shorts. "Eye"-tube null indicator. Less leads. For 105-125V, 60 Hz AC. Steel case. 8Hx10Wx4 $\frac{3}{4}$ "D. Shpg. wt., 8 lbs.

38 R 26998 Kit. Net 29.95

Model 950. Same as above but factory wired

38 R 26906 No Money Down* Net 44.95

DELUXE MODEL 460K 5" WIDE BAND DC SCOPE KIT



KIT
109⁹⁵

WIRED
169⁹⁵

- For Color & Black & White
- 10 MV RMS/CM Sensitivity
- DC to 4.5 MHz Flat Response
- TV-V and TV-H Sweeps

Excellent lab precision scope featuring Push-pull direct coupled vertical amplifier with high sensitivity; 25 mv/in. Response flat from DC to 4.5 MHz, useful to 10 MHz, ideal for reproduction of 3.58 MHz color TV sync. burst. 4-step freq.-compensated attenuator in both AC, DC positions. Also internal voltage calibration. Automatic sync. limiter and amplifier. 2K-full screen horizontal positioning. Sweep-freq.: 10 to 100 Hz with external capacitor for lo-freq. sweeps. Preset TV V & H sweep positions (30 and 7875 Hz). Variable lighted graphed 5" screen. Very hi-input impedance. Complete with all components and instructions for easy assembly. 13x8 $\frac{1}{2}$ x 16". For 105-125 VAC, 50-60 Hz. Shpg. wt., 28 $\frac{1}{4}$ lbs.

38 R 26435W Kit. Net 109.95

Model 460 Kit. As above, but factory wired.

38 R 26443W No Money Down* Net 169.95

MODEL 465K PROFESSIONAL 5" OSCILLOSCOPE- VECTORSCOPE



KIT
179⁹⁵

WIRED
249⁹⁵

- DC to 8 MHz
- 12 MV RMS/CM Sensitivity

Preset TV-Vertical and TV-Horizontal sweep positions (30 and 7875 Hz) makes the 465 ideal for all aspects of color and B/W TV servicing. Zener diode controlled voltage calibration source; distortionless V and H trace expansion; drift-free V and H positioning; automatic sync limiter and amplifier; full retrace blanking; edge lit calibration grid. Vertical amplifier specs: response from DC to 8 MHz (+1 -5 db); sensitivity, 12 mv/cm rms; input impedance, 1 meg; Horizontal amplifier response from DC to 1 MHz (+1 -3 db); sensitivity, 17 mv/cm rms; input impedance, 1 meg; Sweep ranges: 10-100 Hz, 100-1kHz, 1kHz-10kHz, 10-100kHz. Plus: TV-VERT position (30 Hz) and TV-HOR position (7875 Hz); For 117v. AC. 60 Hz. 12 $\frac{3}{4}$ "Hx 8 $\frac{1}{2}$ "Wx17 $\frac{1}{2}$ "D. Shpg. wt., 34 $\frac{1}{4}$ lbs.

38 R 27425W. Net 179.95

Model 465 as above but factory wired

38 R 27433W No Money Down* Net 249.95

MODEL 955K IN-CIRCUIT CAPACITOR TESTER KIT



KIT
29⁹⁵

WIRED
44⁹⁵

- Test Capacitors In or Out of Circuit
- Electron Ray Tube Indicator Provides Easy Reading
- Tests For Shorts and Opens In or Out of Circuits

Checks for shorts (even in the presence or as little as 1 ohm shunt resistance). Checks for opens; capacitors as small as 15 mmf, in or out of circuit; Wien bridge circuit measures capacitance with $\pm 10\%$ accuracy between 0.1 mf and 50 mf at any point on the 4" lucite dial-product, convertible into dissipation or power factor-indications visible on electron ray tube. Includes fine adjust control. For 105-130 VAC. Size: 8 $\frac{1}{2}$ "H x 5 $\frac{3}{4}$ "W x 6"D. Shpg. wt., 6 $\frac{3}{4}$ lbs.


38 R 26914 Kit. Net 29.95

Model 955. Same as above but factory wired.

38 R 26922 No Money Down* Net 44.95

EICO Miscellaneous Test Instruments-Kit or Wired

RESISTANCE & CAPACITANCE SUBSTITUTION BOX KITS



AS
LOW
AS

24⁹⁵

1171K

1180K

1180K CAPACITANCE DECADE KIT

Range: 100mf to 0.111 mf in increments of 100mf. 3 decade assemblies. Rated 350 VDC continuous, 500 VDC intermittent, 1000 VDC test. Accuracy $\pm 1\%$. 9 x 3 1/2 x 3 1/2" D. Shpg. wt. 2 3/4 lbs.

38 R 26799 Kit Net 24.95

As above but wired Net 34.95

1171K RESISTANCE DECADE KIT

Substitute equivalent values of resistance in a circuit. From 0 to 99,999 ohms in 1-ohm steps in 5 decades. Uses 0.5% accurate resistors. Comparator switch permits instant substitution. 12L x 3 1/2" W x 3" D. Less leads. Shpg. wt. 3 3/4 lbs.

38 R 26773 Kit Net 29.95

Model 1171 Same as above but factory wired

38 R 26781 No Money Down* Net 39.95

MODEL 888 SOLID STATE DELUXE ENGINE ANALYZER KIT



KIT

54⁹⁵

WIRED

79⁹⁵

- Large 6" D'Arsonval 2 Color Meter

Seven professional engine and ignition systems in one. Determine the condition of battery, starter, ignition coil, distributor, voltage regulator, alternator or generator. Performs on 4, 6, or 8 cylinder, 6 or 12 volts, pos. or neg. grounded systems. Self-powered. (4 "D" cells not included). SPECIFICATIONS: Dwell 0 to 45° for 8 cyl., 0 to 60° for 6 cyl., 0 to 90° for 4 cyl.; RPM — 0 to 1200 and 0 to 6000 for 4, 6, and 8 cyl.; Voltage — 0 to 3.2 and 0 to 16V. DC; Ohms — 0 to 20K Ω for general continuity and alternator diode testing; Current — 0 to 90 amps. DC. 1 1/2" x 6 x 5" Shpg. wt. 9 lbs.

38 R 27227 Kit. No Money Down* Net 54.95

Model 888 as above but factory wired

38 R 27235 No Money Down* Net 79.95

NEW! MODEL 887 SOLID-STATE PORTABLE IGNITION/ ENGINE ANALYZER



49⁹⁵

WIRED ONLY

- For 6, 12, and 24 Volt Systems, 4, 6, or 8 Cylinder Engines, Positive or Negative Ground

Accurately checks voltage and current regulators, generators, alternator diodes. Checks distributor wear, condition of point surfaces, variation of dwell angle. Determines coil resistance, locates poor or open electrical ground circuits. Single function switch for operating ease. Big 4" meter has sensitive D'Arsonval movement; scales for 0-1200-5000 engine rpm; 0-13-15-30 volts; 0-90 amps; 0-100 ohms; 0-45-60° dwell angle; spark output and leakage. Size: 4 1/2" H x 5 1/2" W x 2" D. Shpg. wt. 1 1/2 lbs.

38 R 27680 No Money Down* Net 49.95

MODEL 1140 SERIES/PARALLEL RC.SUBSTITUTION BOX KIT



KIT

19⁹⁵

WIRED

29⁹⁵

A versatile series parallel RC combination substitution box with switching facilities for selection of any R alone, any C alone, or 1350 combinations of R and C in series or parallel. Resistance values from 15 ohms to 10 megohms; capacitance values from 0.0001 to 0.22 mfd. $\pm 10\%$ accuracy. Open and short circuit positions provided. Can be substituted in circuit to determine values. Convenient 5-way jack binding posts. 6 3/4" H x 5 1/4" W x 2 3/8" D. Shpg. wt. 3 lbs.

38 R 26872 Kit Net 19.95

Model 1140. Same as above but factory wired and tested.

38 R 26880 Net 29.95

MODEL 944K FLYBACK TRANSFORMER AND YOKE TESTER KIT



KIT

29⁹⁵

WIRED

44⁹⁵

- Large, Easy-To-Read 4 1/2" Meter
- Separate Calibration For Air-Core And Iron-Core Flybacks And Yokes

Provides a positive check. In just a few seconds, on all types of flybacks and yokes, both in and out of the circuit. Operates on extremely sensitive grid-dip principle to show up even one shorted turn. Separate calibration settings for air-core flybacks and yokes to assure accuracy in testing both types. Large, easy-to-read 4 1/2" meter, with three colored scales. Tube complement: one 6K6, 105-125V. AC, 60 Hz. 7" x 5" x 4" D. Shpg. wt., 5 3/4 lbs.

38 R 27011 Kit Net 29.95

Model 944. Same as above, but factory wired.

38 R 27029 No Money Down* Net 44.95

MODEL 540K UTILITY TESTER KIT



KIT

19⁹⁵

WIRED

29⁹⁵

An all-in-one Multi-Range AC/DC voltmeter, ammeter, ohmmeter, wattmeter and leakage checker. Indispensable in home repairs of electrical appliances, and in automotive trouble-shooting of batteries, generators, distributors, etc. 3 1/2" meter. Ranges: Volts AC/DC 0-7.5-15-150-300. AC/DC current: 0-15 amps. Ohms: 0-1000 ohms. Capacitof leakage test. All components and instructions supplied. 3 3/4" x 6" x 3 1/2" D. Shpg. wt., 2 3/4 lbs.

38 R 26245 Model 540 Kit Net 19.95

Model 540. As above, but factory wired.

38 R 26252 Net 29.95

MODEL 585K BATTERY TESTER



KIT

12⁹⁵

WIRED

15⁹⁵

Test all popular battery types rapidly under typical load. Specs: Test Positions(V): 1.5 (#6 cell) 1.5 (C, D cells), 1.5 (AA cell), 4.5, 6, 9, 12, 22, 45, 67.5, spare. Max. Battery Voltage and Current Spare Position: 250V, 500 ma. Meter: 15 ma. 90, weak-good scale. Size (HWD): 6 1/4 x 3 x 2" inc. test leads. Shpg. wt., 2 lbs.

38 R 27607 Model 585K Net 12.95

Model 585. As above, but factory wired.

38 R 27615 Net 15.95

EICO OSCILLOSCOPE ACCESSORY PROBES

Features: fully shielded rugged terminal board mounting of all parts. Shock-mounted floating construction. Probe bodies are color-coded for easy identification.

38 R 26450 Model PSD-K Demodulator Probe Kit. Wt., 1/2 lb. Net 4.95

38 R 26468 Model PSD as above but factory wired. Wt., 1/2 lb. Net 6.95


38 R 26476 Model PD-K Direct Probe Kit. Shpg. wt., 1/2 lb. Net 3.95

38 R 26484 Model PD as above, but factory wired. Wt., 1/2 lb. Net 4.95

38 R 26492 Model PLC-K Low Capacity Probe Kit. Wt., 1/2 lb. Net 4.95

38 R 26518 Model PLC as above, but factory wired. Wt., 1/2 lb. Net 6.95

EMC Test Equipment Kits



(A)



(B)



(C)



(D)

Kit **14⁹⁵** Wired **22⁵⁰**

A MODEL 212 TRANSISTOR ANALYZER KIT. Battery powered, checks all transistors for beta in 3 ranges to 200; leakage on 3-color scale. Tests all transistors in circuit without removing them. Can be used to signal trace AF, IF or RF circuits. Also measures battery voltages on 0-12 volt peak and DC current drain on 0-80 milliamperes scale. Checks condition of diodes. Supplied with test leads and instructions. Size: 3 3/4" x 6 1/4" x 2 1/2". Shpg. wt., 2 1/2 lbs.

38 R 2401B Model 212 kit Net 14.95
38 R 2402B Model 212 wired Net 22.50

B MODEL 213 TUBE TESTER KIT. Checks all new Compactrons, Nuvistors, Novars and 10 prong tubes in addition to Octals, Locals, Miniatures and 9-prong tubes. Tests for shorts, leakages, intermittents and quality. Quality is indicated directly on 3-color metal dial. Each section of multi-purpose tubes is checked separately. Also tests Magic Eye, Voltage Regulator and Hi-Fi tubes. Supplied complete with high-impact bakelite case and strap, instructions and tube charts in ring bound manual. Size: 8 1/2" x 7 1/2" x 4". Shpg. wt., 5 3/4 lbs.

38 R 2403A Model 213 kit Net 22.90
38 R 2404A Model 213 wired Net 35.40

Kit **29⁴⁵** Wired **47⁹⁵**

C MODEL 801 RESISTANCE COMPARATOR CAPACITANCE & CAPACITY CHECKER KIT. Measures condensers for actual value, leakage, and power factor. Detects in-circuit opens above 50 mmfd, shorts up to 20 mfd, and condensers that are intermittent in operation. Checks capacity values in 4 ranges from 10 mmfd to 5000 mmfd; resistance in 4 ranges from .5 ohms to 500 megs. Also checks capacitor, inductance or resistance ratio, or transformer windings with a ratio of 20:1 or less. Tests power factor and leakage at rated voltages between 0-500 VDC. Size: 10x7x5"D. Shpg. wt., 9 1/4 lbs.

38 R 24059 Model 801 kit Net 29.45
38 R 24067 Model 801 wired Net 47.95

D MODEL 802 SIGNAL TRACER AND GENERATOR KIT. Combination signal tracer and generator. In the absence of a signal it generates its own signal for audio, IF or RF testing. Incorporates a noise locator circuit for checking noisy components. Provisions are made for using the instrument as a substitute speaker or amplifier. Audio Freq., 400 Hz; IF Freq., 455 kHz (Mod.). Complete with demodulator and audio probes. 10x7x5". Shpg. wt., 9 1/4 lbs.

38 R 24075 Model 802 kit Net 29.45
38 R 24063 Model 802 wired Net 48.95

Test Leads and Probes

NEON CIRCUIT TESTER

49
A simple, safe, electrical circuit tester voltages from 60 volts AC to 550 volts AC or DC. Imported. Shpg. wt., 2 oz.
99 R B0715 Net ea. .49

STANDARD TEST LEADS

Standard test leads furnished with plastic prods and pin plugs which withstands chipping or breaking. Extra flexible kinkless vinyl covered 60" red and black leads. Prods are red and black. 4" long x 3/8" diameter. Supplied in pair of one red and one black. Available with either pin or banana plugs. Imported. Shpg. wt., 8 oz.

99 R 50015 With Banana Plugs Net .59
99 R 50023 With Pin Plugs Net .59

CRT 30KV TEST PROBE

19⁹⁵ • With Built-In Meter
This small self-contained probe featuring a built-in voltmeter, can be used for any color or B&W TV set. Easy to operate! Made of high-impact plastic, it requires no batteries or external power source—no warm-up time. 30,000 volts DC range; 20,000 ohms/volt sensitivity; accuracy of ±3%; multiplier resistance is 600 Megohm ±2%. Overall length is only 14 3/4". With ground wire and clip. Shpg. wt., 12 oz.

38 R 12013 Net 19.95

STRETCH-TYPE TEST LEADS

219
Cannot kink or become entangled. 16" coil extends to 9 feet. Includes red and black plastic handles on each end. Probe 6 1/2" long including tips. Imported. Shpg. wt., 6 oz.

99 R 50239 Net 21.9

HIGH VOLTAGE LEADS

For hi-volt testing in TV sets. Extra heavy duty. Special finger guards. High tension wire. 22,000 volts breakdown. 48" long.

Stock No.	Type	Wt.	Per Pair
32 R 64017	Phone tips	7 Oz.	2.20
32 R 64025	Spade lugs	7 Oz.	2.20
32 R 64033	Allig. Clips	7 Oz.	2.40

6 FT. COIL CORD TEST LEADS

119
Stretch-type color-coded coiled cord twin test leads. Furnished with 5/16" test prods on one end and pin plugs on the other end. Flexible vinyl clad wire cannot become entangled. 30" coiled leads extends to 6'. Imported. Shpg. wt., 5 oz.
99 R 50783 Net 11.9

KLIPZON ADAPTERS

Convert old test points to self holding prods. Pierces insulation of standard phone tips or needle tube.
32 R 60153 Red, 2 oz. Net ea. .44
32 R 60161 Black, 2 oz. Net ea. .44

UNIVERSAL TEST LEAD KIT IN PLASTIC CASE

only
195

Consists of: pair of red and black color coded 4 3/4" x 3/8" plastic handle pin prods with 30" plastic insulated leads terminating in coded 2" x 3/8" banana plugs; pair of spade lugs; pair of phono-tips; and pair of red and black insulated alligator clips. Handsome compartmented plastic case. Imported. Shpg. wt., 7 oz.
99 R 50031 Net 1.95

KEPS "SPRING LOADED" TEST PROBES

147
Completely flexible for difficult test situations. Plunger when pushed in enables steel forked tongue to grip wire or terminal you are testing. Accepts banana plug or bare wire. 6" long. Imported, Shpg. wt., 4 oz.
32 R 37005 Red Net 1.47
32 R 37013 Black Net 1.47

B & K FR3 3 POINT PROBE

12⁹⁵
Easy one-hand way to check transistors, diodes and components in Printed Circuit Boards. Needle tips are spring loaded for proper contact. Color-coded leads terminate in insulated alligator clips.
38 R 17269 Shpg. wt., 8 oz. Net 12.95

Prices and Specifications are Subject to Change Without Notice

Reliable Test Equipment... At Low Prices

LAFAYETTE SOLID-STATE DC POWER SUPPLY/BATTERY ELIMINATOR



Only
7⁹⁵

- Use As A DC Power Supply
- Use As A Battery Eliminator For Transistor Radios
- 4.5, 6, 9, and 12V Output Voltages
- Up to 140 MA Output

Essential instrument for repair of solid state equipment requiring constant low voltage. Doubles as a convenient battery eliminator for transistor radios. Highly filtered circuitry provides four output voltages: 4.5 v., 9 v., 6 v. and 12 v. Voltage selection is simplified with front panel slide switches. Up to 140 MA output. Features transformer power supply and pilot light. For 117 VAC. Overall size: 5 1/8" W x 2 3/8" D x 2 1/2" H. Imported. Shpg. wt., 1 1/4 lbs.
99 R 50742

Net 7.95

LAFAYETTE TRANSISTORIZED DC POWER SUPPLY



Only
16⁹⁵

- AC Ripple Less Than .025%
- Transistorized Regulation Circuitry

Provides continuously variable voltage and current with low ripple. Excellent for operation of transistorized devices. Panel meter reads either current or voltage. SPECIFICATIONS—Output voltage: 0-20 volts DC (continuously variable). Output Current: 0-20 MA, 0-200 MA (in two ranges). AC Ripple: less than .025%. Power Input: 110-120 volts, 50-60 Hz, AC. Fully fused. Size: 6 1/4 x 1 1/4 x 3 3/4". Imported. Shpg. wt., 2 3/4 lbs.
99 R 50684

Net 16.95

KINECOLOR CIRCUIT ANALYZER



19⁹⁵

- Instant Hook-up for Analyzing, Testing and Adjusting Color CRT's and Associated Circuitry Under Actual Operating Conditions

Speed color-TV servicing by using this analyzer. Turning off electron guns is as easy as opening switches. Each color gun has its own switch and any combination of colors may be chosen. Voltage and current tests are easily performed using single pin jacks provided on the panel. Simplifies purity adjustments, convergence, gray-scale and tracking, voltage test, current measurement, and wave form observations. Sturdy compact unit is fully insulated and enclosed. Complete with detailed procedure booklet. 6 1/4 x 3 3/4 x 2". Shpg. wt., 1 3/4 lbs.

38 R 14019

Net 19.95

LAFAYETTE RESISTANCE-CAPACITY SUBSTITUTION BOX

- 24 Resistance Values
- 9 Capacitance Ranges

Versatile service instrument enables rapid substitution of a wide range of resistor or capacitor values. Resistance values in two ranges (12 steps each)—Low: 15 ohms to 10K ohms; High: 15K ohms to 10 Meg ohms. $\pm 10\%$ accuracy. Capacitance ranges are: .0001; .0010; .0022; .0047; .010; .022; 0.47; .10; .22 MFD (rated at 400 volt working capacity). Size: 5 1/8 x 2 3/4 x 1 3/4 H. Imported. Shpg. wt., 3/4 lb.
99 R 50759

Net 4.95



4⁹⁵

PROTECT YOUR METER with METERGARD



2⁹⁵

- Easily Installed
- No Overload Damage

Protect your meter, regardless of make, against overloads. No more bent pointers, damaged pivots, or burnt out coils. Installation of metergard will allow your meter to withstand as much as a 10,000% overload. Shpg. wt., 2 oz.
38 R 68015

Net 2.95

CHEK-IT ELECTRICAL CIRCUIT TESTER

1⁸⁸



Here is a handy pocket size tester which is ideal for servicemen, schools, electricians and hobbyists. Completely portable and simple to use, checks electrical continuity of line cords, switches, coils, and fuses. Ideal for checking out buzzers, chimes, and various other electrical appliances. Uses 2 inexpensive penlight cells. Shpg. wt., 3 oz.
38 R 79087 Chek-It less batteries Net 1.88
Battery for "Chek-It." 2 required.
99 R 62580

Net ea. .10

LECTROCELL DC POWER SUPPLY FOR VTVM's



3⁹⁵

Quickly replaces 1 1/2 volt battery used in VTVM's for resistance measurements. Regular battery must be replaced at regular intervals. If it is forgotten the instrument may be ruined by chemical corrosion. Eliminate trouble by installing this power supply. Install it and forget it. Shpg. wt., 1/2 lb.
38 R 68023

Net 3.95

SHURITE AC/DC LINE VOLTAGE TESTER



4⁸⁵

Type 5406-LT. Sturdy, pocket sized tester has a range of 0-150 volts, AC/DC. Plug into any wall outlet and read the voltage, then plug in the appliance(s) and note the new reading. Find (and demonstrate) voltage drop or inadequate wiring as a source of service problems. Shpg. wt., 8 oz.
38 R 61697

Net 4.85

Bench Power Supplies—Battery Eliminators & Chargers

Lafayette SOLID-STATE REGULATED DC BENCH POWER SUPPLY

ONLY
39⁹⁵

No Money
Down*



- Automatic Protection Against Overload
- Continuously Variable Output Voltage 5-13, 12-20 VDC at 0-2 Amp
- Output Voltage Regulation: $\pm 1\%$

Lab-type regulated DC bench power supply with dual range voltage selector. Ideal for all types of transistor servicing and testing. Provides well filtered, continuously adjustable DC output of 5-13 or 12-20 volts. Fully regulated with continuous output current of up to 2 amp, with less than 5 mv RMS ripple at full load. Self-restoring overload protection. Two D'Arsonval meters for constant monitoring of voltage and current output. Both input and output of power supply are fused for maximum protection. Input: 115 or 230 VAC $\pm 10\%$ 50/60 Hz. Housed in a rugged steel case. Size: 6 $\frac{1}{2}$ "H x 4 $\frac{1}{2}$ "W x 8 $\frac{3}{4}$ "D. Imported. Shpg. wt., 9 lbs.

99 R 50775


Net 39.95

EICO BATTERY ELIMINATOR AND CHARGER KITS

As Low As

54⁹⁵

No
Money
Down*



A 1060S

B 1064S

A MODEL 1060S KIT. SPECIALLY DESIGNED FOR SERVICING ALL TYPES OF TRANSISTOR EQUIPMENT. Selection of voltage range automatically provides appropriate current range. Fused transformer primary. Continuous voltage adjustment with Variac. 2 DC ranges and dual-range ammeter for accurate readings. Ranges: high = 0-16V. 1.5% ripple at 2 amps; 2% at 6 amps; 6 amps, continuous, 12 amps intermittent; low = 0-8v. 0.3% ripple at 2 amps; 1.5% at 10 amps. 10 amps continuous, 20 amps intermittent. Heavy-duty silicon rectifiers. For 105-125 volts 50/60 Hz A.C. All components and instructions included. 8 $\frac{3}{4}$ " x 10 $\frac{1}{2}$ " x 7 $\frac{3}{4}$ ". Shpg. wt., 17 $\frac{1}{4}$ lbs.

38 R 27284 Kit Net 54.95

Model 1060S. As above, but factory wired and tested.

38 R 27292 Net 74.95

B MODEL 1064S KIT. IDEAL FOR TRANSISTOR, TUBE, "HYBRID" AUTO RADIO REPAIR. Features 2 DC voltage ranges, 6 or 12 V. DC. Separate voltmeter and dual range ammeter—up to 10 amperes continuous. Heavy duty silicon rectifiers. AC ripple: 0.3% @ 2 amperes. For 105-125 volts, 50/60 Hz; Size: 8 $\frac{1}{2}$ "H x 5 $\frac{3}{4}$ "W x 7 $\frac{1}{2}$ "D. Shpg. wt., 17 lbs.

38 R 27300 Kit Net 59.95

Model 1064S. As above, but factory wired and tested.

38 R 27318 Net 79.95

*See Page 22 for Full Credit Details on Easy Pay Plan


EICO MODEL 1032 SOLID STATE REGULATED POWER SUPPLY

KIT

44⁹⁵

WIRED

59⁹⁵



- Regulated Against Line and Load Variations
- 0-30 Volts Continuous Output With Loads Up to 500 MA
- Voltage and Current Monitored by Meters

Provides the voltages and currents most commonly needed in the service shop as well as in the engineering laboratory. Low ripple enables you to use 1032 for testing portable radios, tape recorders, hearing aids, etc. May also be used in the laboratory as a fixed bias supply or for fulfilling any other regulated voltage requirement. Milliammeter is fused to prevent burnout. Specifications: Output Voltage: 0 to 30 volts regulated. Output Current: 0 to 500 ma. Voltage Regulation: 0.2 volts change from 0 to maximum load with 105-135 volt line. Ripple: less than 2.5 mv peak-to-peak. DC Voltmeter: 0-10 volts. 0-50 volts. Milliammeter: 0-500 ma. Power Requirements: 117VAC/60 Hz. Size: 3 $\frac{3}{4}$ " x 8 x 4 $\frac{3}{4}$ ". Shpg. wt., 5 lbs.

38 R 27581 Model 1032 Kit. No Money Down* Net 44.95

MODEL 1032W: As above but factory wired and tested.

38 R 27599 No Money Down* Net 59.95

EICO 1020 TRANSISTOR DC POWER AND BIAS SUPPLY KIT

Kit

25⁹⁵

Wired

34⁹⁵



APPLICATIONS INCLUDE:

- 1) Universal Power Supply For Transistor Devices
- 2) Variable Bias Supply for TV or Radio
- 3) DC Filament Supply

Continuously variable output voltage to 30 volts monitored by a dual range voltmeter (0-6, 0-30 VDC). Ideal for servicing both tube and transistor gear. Maximum continuous output; 150 ma from 0-12V.; 200 ma from 12-24v.; 300 ma from 24-30v. Full-wave silicon-diode rectifier circuit with R-C input filter plus two power transistors in a cascaded filter circuit. Fuse protects unit against overload. Rugged steel case, 4W x 5H x 5 $\frac{1}{2}$ "D. For 105-125 v., 60 Hz AC.

38 R 26955 Model 1020 Kit. Shpg. wt., 5 lbs. Net 25.95

MODEL 1020W—As above but factory wired.

38 R 26963 No Money Down* Net 34.95

NEW SENCORE BE156 7 IN 1 DC BIAS SUPPLY

ONLY

24⁹⁵



Now align any black and white, tube or solid state TV set. The BE156 bias supply provides the bias that you need in any stage, negative or positive, as specified by the TV manufacturers. Three separate and independent 25 volt supplies offer a carefully calibrated output and a positive and negative polarity switch; Also has provisions to increase the output to a negative 75 volts for use on such sets as the RCA chroma amplifiers that specify 67.5 volts. 7"W x 4"D x 2"H. Shpg. wt., 2 $\frac{1}{2}$ lbs.

38 R 53355 Net 24.95




Panel Meters

METER SPECIFICATIONS

ACCURACY: Standard $\pm 2\%$ on AC and DC
POINTERS: Spade pointer is standard on all Phenolic series panel instruments. Lance type pointer is standard on G-series panel instruments.

D.C. INSTRUMENTS are the D'Arsonval type with linear scales, extra-light moving coil, rugged construction; Bar-Ring Magnet and 1 piece die-cast frames. A.C. Instruments are the moving iron vane type, and have light parts. Jewel types have selected bearings, highly polished and specially treated pivots; white enameled metal dials are standard; molded zero adjusters, and ceramic pointer stops.

Average shpg. wt., 1 1/4 lb.



* Indicates suspension type movement
 † Indicates pivot and jewel type

METER DIMENSIONS Round Flush Mounting

Mod.	Flange	Body Dia.	Depth	Scale
221-1	2 1/4"	2 1/4"	1 1/4"	1.76"
231-S	2 1/4"	2 1/4"	1 1/4"	1.58"
321-T	3 1/2"	2 3/4"	1 1/4"	2.49"
321-S	3 1/2"	2 3/4"	1 1/4"	2.22"

Rectangular Flush Mounting

Mod.	Flange	Body Dia.	Depth	Scale
227-T	2 3/4x2 3/4"	2 3/4"	1 1/4"	1.76"
237-S	2 3/4x2 3/4"	2 3/4"	1 1/4"	1.58"
327-T	3x3"	2 3/4"	1 1/4"	2.49"
320-G	3 1/2x3"	2 3/4"	2 1/8"	3.16"
330-G	3 1/2x3"	2 3/4"	2 1/8"	2.68"
337-S	3x3"	2 3/4"	1 1/4"	2.22"
420	4 1/2x4 1/2"	2 3/4"	1 1/4"	4.14"
420-G	4.55x4.068"	2 3/4"	2 1/8"	4.03"
430	4 1/2x4 1/2"	2 3/4"	1 1/4"	3.6"
430-G	4.55x4.068"	2 3/4"	2 1/8"	3.43"

† OVERALL DEPTH INCLUDING TERMINALS

DC MICROAMMETERS

Range	221-T 2 1/2" Rnd.	227-T 2 1/2" Rect.	Each	321-T 3 1/2" Rnd.	320-G 3 1/2" Rect.	Each	420 4 1/2" Rect.	420-G 4 1/2" Rect.	Each
0-50†	38 R 73312	38 R 73320	23.70	38 R 73338	38 R 77735	24.80	—	38 R 77800	25.90
0-100†	—	38 R 73379	22.10	38 R 73387	—	23.10	38 R 73403	—	24.30
0-200†	38 R 73411	38 R 73429	20.40	—	—	—	—	38 R 77826	22.60
0-500†	38 R 73460	38 R 73478	19.30	—	—	38 R 77768	20.40	38 R 77834	21.50
50-0-50*	38 R 73510	—	23.70	—	—	—	—	38 R 73551	25.90
100-0-100*	38 R 73569	38 R 73577	22.60	—	38 R 77784	23.70	—	—	24.80
500-0-500*	38 R 73619	38 R 73627	21.50	—	—	—	38 R 73650	—	23.70

DC MILLIAMMETERS

Range	221-T 2 1/2" Rnd.	227-T 2 1/2" Rect.	Each	321-T 3 1/2" Rnd.	320-G 3 1/2" Rect.	Each	420 4 1/2" Rect.	420-G 4 1/2" Rect.	Each
0-1	38 R 73668	38 R 73676	18.20	38 R 73684	38 R 77974	19.30	38 R 73700	38 R 78097	20.40
0-1.5	38 R 73718	38 R 73726	18.20	—	38 R 77982	19.30	38 R 73759	38 R 78105	20.40
0-5	38 R 73817	38 R 73825	18.20	38 R 73833	38 R 77990	19.30	—	—	—
0-10	—	38 R 73874	18.20	38 R 73882	38 R 78006	19.30	—	38 R 78121	20.40
0-25	38 R 73965	38 R 73973	18.20	38 R 73981	—	19.30	38 R 74013	38 R 78139	20.40
0-50	38 R 74021	38 R 74039	18.20	38 R 74047	38 R 78022	19.30	38 R 74062	—	20.40
0-100	38 R 74120	38 R 74138	18.20	38 R 74146	38 R 78030	19.30	—	—	—
0-200	—	—	—	—	38 R 78048	19.30	38 R 74260	—	20.40
0-300	—	38 R 74336	18.20	—	38 R 78055	19.30	38 R 74369	38 R 78170	20.40
0-500	—	—	—	—	38 R 78063	19.30	38 R 74468	38 R 78188	20.40
0-750	38 R 74476	—	18.20	—	—	—	—	—	—
0-1000	38 R 74526	—	18.20	38 R 74542	38 R 78089	19.30	—	—	—

DC VOLTMETERS 1000 Ohms Per Volt

Range	Model	Stock No.	Each
0-1	227T	38 R 75093	19.90
0-3	221T	38 R 75135	19.90
0-3	420	38 R 75176	20.10
0-5	420	38 R 75226	20.10
0-10	327T	38 R 75267	21.00
0-15	327T	38 R 75317	21.00
0-15	420	38 R 75325	22.10
0-25	221T	38 R 75333	19.90
0-25	321T	38 R 75358	21.00
0-25	420	38 R 75374	22.10
0-50	227T	38 R 75390	19.90
0-50	420G	38 R 78253	22.10
0-100	321T	38 R 75457	21.00
0-150	321T	38 R 75507	21.00
0-500†	227T	38 R 75697	21.00

† Has external Resistor

DC AMMETERS

Range	Model	Stock No.	Each
0-1	420G	38 R 77875	21.00
0-3	321T	38 R 74641	19.90
0-5	320G	38 R 77883	19.90
0-10	221T	38 R 74724	18.80
0-10	227T	38 R 74732	18.80
0-10	420	38 R 74765	21.00
0-15	221T	38 R 74773	18.80
0-15	321T	38 R 74799	19.90
0-15	327T	38 R 74807	19.90
0-25	420	38 R 74864	21.00
0-50	327T	38 R 74955	19.90
0-50	420	38 R 74963	19.90
0-50	420G	38 R 77917	21.00

AC VOLTMETERS

Range	Model	Stock No.	Each
0-150	231S	38 R 77487	18.80
0-150	237S	38 R 77495	18.80
0-150	330G	38 R 77925	19.90
0-150	331S	38 R 77503	19.90
0-150	337S	38 R 77511	19.90
0-150	430	38 R 77529	21.00
0-150	430G	38 R 77933	21.00
0-250	430	38 R 77578	21.00
0-300	430G	38 R 77941	21.00


AC AMMETERS

Range	Model	Stock No.	Each
0-1	237S	38 R 76604	17.60
0-1	430	38 R 76638	19.90
0-2	337S	38 R 76679	18.80
0-3	430	38 R 76737	19.90
0-5	237S	38 R 76752	17.60
0-10	430	38 R 76836	19.90
0-15	337S	38 R 76877	18.80
0-15	430	38 R 76885	19.90
0-25	231S	38 R 76893	17.60
0-25	337S	38 R 76927	18.80
0-25	430	38 R 76935	19.90
0-25	430G	38 R 77958	18.80
0-30	231S	38 R 76943	17.60
0-50	430G	38 R 77966	18.80
0-50	430	38 R 77040	19.90

DC MILLIVOLTMETERS

Range	Model	Stock No.	Each
0-50	227T	38 R 76059	18.80
0-100	420	38 R 76133	21.00
0-150	420	38 R 76182	21.00

Amprobe Voltprobes



(A) VT 100 AC/DC Probe

For easy voltage readings anywhere—anytime. Fits into shirt pocket. "Thermometer Style" illuminated window indicates voltage level, AC or DC. Operates over a wide 25-800 cycle range. Compact unit incorporates a sliding push-up probe and a retractable probe with expanding coil cord attached that permits measurements of points over 3 feet apart. Voltage Levels: AC 115-220-277-440-550 Volts, DC 115-220-400-500-750 Volts. DC Polarity Indicator. Size: 6 x 2 1/4 x 3/4" with probes retracted.
 38 R 13136 Shpg. wt., 1/2 lb. Net 9.50

(B) VT 124 AC Probe

Same as above but AC voltage levels only. Use for checking AC circuits including 24 and 48 VAC circuits in Climate Control Equipment, Switching Systems, Electric Garage Door Operators, and Industrial Equipment Control. Levels AC: 24-48-115-220-277-440-550 AC. Shpg. wt., 8 oz.
 38 R 13144 Net 14.85



JBT MODEL 31-EKW-5 ELAPSED TIME METER

Records operating time of AC equipment. Registers in 1/10th hour steps to 9,999.9 hours, then automatically resets. Flange 3 1/2". mounts in 2 1/4" hole, overall depth 3 3/4". For 110-120V., 60 Hz, AC. Shpg. wt., 1 lb.
 38 R 67058 Net 17.80



JBT AC FREQUENCY METERS

Vibrating reed meters for measuring frequency of AC power sources in 1-cycle steps! $\pm 0.3\%$ at 77°F. Flange 3 1/2", mounts in 2 1/4" hole, overall depth 3 3/4". For 100-130 volts. Shpg. wt., 1 1/2 lbs.
 Model 34-FX 56-64 Hz 38 R 67025 Net 31.10

SHURITE PANEL METERS



GLASS FRONT Type 950



CLEAR PLASTIC Type 850

O.C. VOLTMETERS

Range	Type 950	Net Each	Type 850	Net Each
0-1	38 R 60640	3.45	—	—
0-3	38 R 60657	3.45	38 R 61499	3.55
3-0.3	38 R 60665	3.45	—	—
0-5	38 R 60673	3.45	38 R 61507	3.55
0-6	38 R 60681	3.45	—	—
0-10	38 R 60699	3.45	38 R 61515	3.55
0-10	38 R 60707	3.45	38 R 61523	3.55
0-15	38 R 60715	3.45	38 R 61531	3.55
0-20	38 R 60723	3.45	38 R 61549	3.55
0-25	38 R 60731	3.45	38 R 61556	3.75
0-25H	38 R 60285	3.90	38 R 61564	4.00
0-50	38 R 60293	3.55	38 R 61572	3.65
0-50H	38 R 60301	4.15	38 R 61580	4.25
0-75	38 R 60319	3.65	—	—
0-100	38 R 60327	3.65	—	—
0-100H	38 R 60335	4.15	—	—
0-150	38 R 60343	3.85	38 R 61598	3.95
0-150H	38 R 60350	4.15	38 R 61606	4.25
0-300H	38 R 60368	4.35	38 R 61614	4.45
0-500H	38 R 60376	4.50	38 R 61622	4.60

A.C. METERS TYPE 850

A.C. VOLTMETERS		A.C. AMMETERS		
Range	Stock No.	Net	Range Stock No. Net	
0-10	38 R 59303	4.95	0-1 38 R 59238	4.85
0-15	38 R 59311	4.95	0-3 38 R 59245	4.85
0-25	38 R 59329	4.95	0-5 38 R 59253	4.85
0-50	38 R 59337	4.95	0-10 38 R 59261	4.85
0-150	38 R 59345	5.15	0-15 38 R 59279	4.85
0-300	38 R 59352	5.40	0-30 38 R 59287	4.95
			0-50 38 R 59295	5.20

A.C. MILLIAMMETERS TYPE 850

Range	Stock No.	Net	Range	Stock No.	Net
0-10	38 R 59170	5.05	0-100	38 R 59204	5.05
0-50	38 R 59196	5.05	0-500	38 R 59220	5.05

All models pre-calibrated and accurate within 5%. Styled to enhance appearance of electrical equipment. Meter movements: DC meters—"HI-TORQ" magnetic and AC meters—moving iron type. Model 13, 3/4x1 3/4x2 1/4" all plastic design. Screw terminals with soldering lugs. Supplied with all mounting hardware. Avg. shpg. wt., 4 oz.



EMICO PANEL METERS

DC AMMETERS

Stock No.	Range	Net
38 R 31773	0-10	3.30
38 R 31781	0-15	3.30
38 R 31799	0-30	3.30
38 R 31807	30-0-30	3.30

AC VOLTMETERS

38 R 31542	0-150	5.05
38 R 31559	0-300	5.35

AC MILLIAMMETERS

38 R 32227	0-500	4.50
------------	-------	------

DC VOLTMETERS

Stock No.	Range	Net
38 R 32037	0-3	3.30
38 R 32045	0-10	3.30
38 R 32052	0-15	3.30
38 R 32060	0-20	3.30
38 R 32078	0-30	3.30
38 R 32086	0-50	3.30

AC AMMETER

38 R 32185	0.5	4.50
------------	-----	------

DC MILLIAMMETERS

Stock No.	Range	Net
38 R 31377	0-1	4.40
38 R 31385	0-5	3.55
38 R 31393	0-10	3.40
38 R 31401	0-20	3.30
38 R 31419	0-30	3.30
38 R 31427	0-50	3.30
38 R 31435	0-100	3.30
38 R 31443	0-150	3.30
38 R 31450	0-200	3.30
38 R 31468	0-300	3.30
38 R 31476	0-500	3.30

Economy model panel meters with fast response, excellent torque-to-weight ratio, long scales, and accuracy well within standard 5%. All have zero adjust. AC are double-vane repulsion type with jeweled bearings. DC are polarized-vane solenoid type or moving magnet construction. Require a 2 3/4" hole. "H" indicates high resistance. Model 850: Attractive plastic meters with 2 1/2" x 2 3/4" H—Crystal polystyrene front for exceptional visibility and protection. Frosted finish interior. Model 950: Sturdy metal case, glass front meters. Flange-mounted. Average shpg. wt., 6 oz.

ALL SHURITE METERS FEATURE

1. 5% Accuracy
2. Zero Adjust

SHURITE BATTERY TESTERS

Pocket testers with bright plated cases, metal dials, and prongs. Sturdily built. Test batteries without load. Ideal for testing batteries used in transistor circuits, model railroads, hearing aids, portable radios, etc. Shpg. wt., 6 oz.



DC VOLTMETERS

TYPE	RANGE	NET
38 R 59709	0-5	3.80
38 R 59717	0-7	3.80
38 R 59725	0-50	4.35
38 R 59733	0-2-50	4.95
38 R 59774	0-2-150	4.95

DC AMMETERS

38 R 59782	0-3	3.80
38 R 59790	0-15	3.80
38 R 59808	0-40	4.05

HEARING AID BATTERY TESTER, ideal for checking 1.5, 15, 22.5, 30, 33, and 45 volt batteries. 38 R 61648 Net 4.95



AC DC LINE VOLTAGE TESTER

Type 5406-LT. Sturdy, pocket sized tester has a range of 0-150 volts, AC/DC. Plug into any wall outlet and read the voltage, then plug in the appliance(s) and note the new reading. Find (and demonstrate) voltage drop or inadequate wiring as a source of service problems. Shpg. wt., 6 oz. 38 R 61697 Net 5.20

AMPROBE "SNAP-AROUND" CLAMP-ON AC VOLT AMMETERS WITH ROTARY SCALE

AS LOW AS
25⁸⁵



RS-1-2-3



JUNIORS

Amprobe meters measure AC current and AC voltage without breaking the circuit. To measure current, snap the trigger-operated jaws around single conductor. Meter instantly indicates correct reading. Use furnished safety leads for voltage measurements. Rotary scale shows only scale in use. Accurate to ±3%. Designed for 60 cycle circuits. Have impact-proof cases, unbreakable plastic magnifying meter window, self-shielded meter movement. Complete with carrying case and voltage test leads. Shpg. wt., 1 3/4 lbs.

AMPROBE RS-1

Meter measures: AC AMPS: 0-6-15-40-100, AC Volts 0-150-600. Measures up to 1 1/2" dia. conductors, to 1 1/4" x 1/2" bars. 7 1/2" long, 2 3/4" wide, 1 1/2" thick. Scale length 2 1/4". 38 R 13011 No Money Down* Net 46.85

AMPROBE RS-2

Same as model RS-1 except has 0-150-300 volts AC range. 38 R 13029 No Money Down* Net 46.85

AMPROBE DELUXE RS-3

Extra versatile probe also includes 0-2000 ohm range, 25 ohms mid-scale. AC Volts ranges 0-150-300-600, AC Amps 0-6-15-40-100-300. Includes case, ohmmeter, battery attachment and volt-meter leads. 38 R 13037 No Money Down* Net 59.85

AMPROBE JUNIORS

Lighter duty, smaller versions of standard Amprobes. Will measure up to 1/2" dia. conductors 3/4" long, 1 3/8" thick, 2 1/2" wide. 1.8" long scale. Rugged construction with ribbed, non-slip case. For 60 cycle AC. Shpg. wt., 3/4 lb.

STOCK NO.	MODEL	AC AMPS	AC VOLTS	NET PRICE
38 R 13052	Y25	0-25	0-125-250	25.85
38 R 13094	Y50	0-50	0-150-600	25.85
38 R 13102	Y50	0-100	0-150-600	25.85

Model P1—Carrying Case for Amprobe Juniors. Wt. 1/4 lb. 38 R 1312E Net 3.50

LAFAYETTE Panel Meters

MINIATURE FM & AM TUNING METERS

- Moving Coil Principle
- Highly Sensitive
- Only $\frac{3}{4}$ " Square and 1" Deep



2.99

Can be easily installed on any tuner. The remarkable sensitivity enables you to tune in stations with surprising ease. Galvanometer movement of the indicator assures complete accuracy. Insulation resistance between case and terminals: 100 megohms/500 V. Solder lugs are provided at the back. Plastic case. Complete with instruction sheets. Shpg. wt., 2 oz.

FM TUNING METER

FM TUNING METER. Can be connected between radio detector and AF amplifier. The indicator will rest in the center when station is tuned in. Current sensitivity ± 100 microamps on both sides. DC. Internal resistance about 1200 ohms. Imported.

99 R 50262 Net 2.99

AM TUNING METER

AM TUNING METER. Can be connected into the second IF stage of AM radio. Graduated scale with maximum deflection of pointer indicating station being tuned in. Sensitivity 500 μ a. on full scale. Int. resistance about 410 ohms. Imported.

99 R 50254 Net 2.99

LAFAYETTE MINIATURE LEVEL METER

- Highly Sensitive
- Front Panel Area Only $\frac{7}{8} \times \frac{3}{8}$ " H
- Rubber Cushion Mount



A miniature clear plastic front level meter which will indicate relative audio levels for tape recorders, FM sets or transistorized audio equipment. Actual size of meter is $\frac{7}{8} \times \frac{1}{2} \times 1 \frac{1}{2}$ " L. Internal resistance—260 ohms. Full scale 500 microamps. Shpg. wt., 2 oz. Imported

99 R 50361 Net 2.15

ULTRA-MINIATURE TUNING AND BATTERY METER

2.15

ONLY $\frac{1}{2}$ " IN DIA.
 $\frac{3}{4}$ " IN LENGTH



Ultra-miniature meter can be installed easily in a $\frac{1}{4}$ " diameter hole. Current sensitivity: 500 μ a; $\pm 15\%$ at full scale. Internal resistance: 500 ohms $\pm 10\%$. Imported. Shpg. wt., 2 oz.

99 R 50353 Net 2.15

METER RECTIFIER


only .45



A full wave, economical meter rectifier of exceptionally linear characteristics. Universal electrical replacement for most multi-meters, such as Lafayette's miniature V.O.M.'s. Single screw mount. Long terminals. Imported. Shpg. wt., 2 oz.

99 R 52077 Net .45


PANEL METERS WITH D'ARSONVAL MOVEMENTS



(A) $3\frac{1}{2}$ " Square



(B) $3\frac{1}{2}$ " Square



(C) $1\frac{1}{2}$ " Square

- Jewelled Bearings

- Accuracy 2% Full Scale

High quality, precision built meters with better than 2% of full scale accuracy. All meters have 4 threaded mounting studs in corners, zero adjust screw and clear plastic fronts except (B) which has black bakelite. Terminal polarity on DC models is identified. (A) standard 3900 ohm "B" scale VU indicator. Includes full wave bridge rectifier, built-in bulb. Ammeters are highly damped, use linear calibrations. Dimensions: (A), (B), — $3\frac{1}{2}$ " square, $2\frac{3}{4} \times 1\frac{3}{8}$ " dial faces, $1\frac{1}{2}$ " overall depth, $1\frac{1}{2}$ " behind panel including terminals. Require $2\frac{1}{2}$ " diameter mounting hole. Except VU requires $2\frac{1}{4}$ " hole. (C) miniature meters with silvered dials, black pointers — $1\frac{1}{2}$ " square fronts, $1\frac{1}{2}$ " overall front-to-back, with $1\frac{1}{4}$ " behind panel including $\frac{1}{4}$ " terminals. Require $1\frac{1}{2}$ " diameter round hole in panel. $1\frac{1}{4}$ " dial face. Supplied with mounting screws. Imported. Average shpg. wt., $\frac{3}{4}$ lb.

STOCK NO.	FIG.	RANGE	EACH	STOCK NO.	FIG.	RANGE	EACH
99 R 50437	A	*V.U. Meter	4.95	99 R 50544	C	0-50 DC Milliamp.	2.75
99 R 50429	B	0-50 DC Microamp.	4.75	99 R 50551	C	0-100 DC Milliamp.	2.75
99 R 50403	B	0-1 DC Millamp.	4.25	99 R 50494	C	0-50 DC Microamp.	4.25
99 R 50528	C	0-1 DC Milliamp.	3.75	99 R 50478	C	0-15 DC Volt	2.95
				99 R 50502	C	0-150 AC Volt	3.25

*Standard 3900 ohm "B" scale volume indicator, 0-100% modulation scale, —20 to +3VU illuminated scale.

MINIATURE LAFAYETTE VU METERS



ONLY
2.99

- Jewelled Bearings
- Precision D'Arsonval Movement

Precision VU meters with scale calibrated from —20 to +3 VU and 0-100% Ranges. Impedance: 7.5K ohms. Accuracy: ± 0.5 db. Frequency Response: 25 to 10KC. With external zero adjust. Mount in $1\frac{1}{2}$ " D hole. Wt., 5 oz.

99 R 50577 $1\frac{1}{2} \times 1\frac{1}{2}$ " Net 2.99

LAFAYETTE MINIATURE ILLUMINATED VU METER



- D'Arsonval Movements
- Jewelled Bearings
- Accuracy 2% of Full Scale

Illuminated dial for easy, wide-angle readability at all times. Volume level indicator, calibrated in standard —20 to +3 VU and 0-100% ranges. Uses precision carbon film multiplier resistor and full wave rectifier. Damped in accordance with standard VU meter requirements. Reference level 1 mw in 600 ohm line. 3,900 ohms internal resistance. "0" VU is 1.228 volts sine wave AC across meter connected to 600 ohm source with 600 ohm load. May be used with T-pad attenuator. Size: $1\frac{1}{2} \times 1\frac{1}{2}$ " sq. face, $1\frac{1}{4}$ " overall behind panel. Imported. Shpg. wt., 5 oz.

99 R 50247 Net 4.29

LAFAYETTE EDGE-WISE PANEL METERS



(A)

VU METER (A)



(B)

Has precision D'Arsonval meter with 2% or better full scale accuracy. Calibrated and damped. Upper scale reads —20 to +3VU. Lower scale reads 0-100% modulation. Accurate to ± 0.5 VU from 30-15000 Hz. Size: $3\frac{1}{2} \times 1\frac{1}{2}$ " H. Overall depth is $3\frac{1}{2}$ " behind panel including terminals. Has stud-type solder terminals and zero adjustment screw. Shpg. wt., 9 oz. Imported.

99 R 50338 Net 5.95

BALANCE & TUNING METER (B)

Use these precision moving coil DC Ammeter meter movements as stereo balance indicators or as tuning indicators for FM tuners. Pointer at center of the scale indicates zero or null position. Current Sensitivity: ± 100 μ a on both sides. Complete with installation schematics. Clear plastic case. Meter body: $1\frac{1}{2} \times 1\frac{1}{2} \times 3\frac{1}{2}$ " D. Depth behind panel $1\frac{1}{2}$ "

99 R 50346 Shpg. wt., 3 oz. Imported. Net 2.99

A

Acoustic Padding 94

ADAPTERS

AC 248

Audio 92, 93

Crystal Holder 432

Four Channel 18, 52, 53, 468

Jack & Plug 92-93

Microphone 92-93, 196

Phono 92-93

Test-Point 256

Tube Socket 256

..... 93, 258

Adding Machines 234

Adhesives 307, 311

Alarms 229

Alarms 126, 212-213, 317, 419-421

Alignment Tools 346

Alkaline Batteries 46

Alternators 369

AMATEUR EQUIPMENT

Accessories 429, 432

Amplifiers 424

Antennas 430-432

Balun 430, 432

Clocks 323, 429, 431

Code Practice 212, 426-427

Converters 429

Crystals 432

Headphones 429

Interference Filters 432, 447

Keys 432

Lowpass Filters 432

Microphones 173, 191, 194-197, 205, 212

Mounting Bracket 447

Phone Patch 429

Preamplifiers 212, 429, 446

Receivers 424-425

Relay (Antenna) 432

RF Power Meters 428, 445

"S" Meters 428

SWR Bridges 428, 445

Transceivers 426

Transmitters 425

Kits 429

AMMETERS 374-375, 408-409

AMPLIFIERS

Amateur 424

Guitar 166-167, 170-172

Hi-Fi 2, 4-5, 12-15, 19, 25-29, 34, 48-49, 51-53

Kits, Hi-Fi 52-53, 214, 216-217

Modules 212, 216-217

Musical Instruments 166-167, 170-173

P.A. 178-180

Phono 141, 214

Telephone 203

TV 294

ANTENNAS

Amateur 430-432

Auto Radio 145

Citizens Band 439-440, 447

Ferrite 228-231

FM 285-286, 288, 290, 291

Marine 439

Shortwave 281, 292, 422, 431

TV, indoor 290, 293

TV, outdoor 284, 289

UHF 284

Window 287, 291, 431, 442

ANTENNA ACCESSORIES

Balun 432

Boosters 145, 294-296

Coaxial Cable 282, 283, 299, 440, 441

Colls 230, 233

Connectors 145, 300, 447

Couplers 296, 298-299

Dummy Load 431, 443

Distribution Units 294, 299

Ground Clamps 301

Ground Rods 301

Guy Rings 301

Guy Wire 283, 301

Installation Kits 302

Insulators 227, 302

Lightning Arrester 302

Masts 301

Matching Coil 298, 299

Mounts 300, 301

Outlets 303

Rotors 296, 297, 430

Splitters 294, 298-299

Switches 305, 445

Towers 300-301

Turners 431

TV Filters 276, 298

Twin-Line 280-283

Wire 145, 280-283, 447

Artists Materials 366

Atom Smashers 215

Attenuators, TV 298, 299

Audio Cables 92, 280, 281

Audio Generators 398, 402

Auto Mixers 188, 192

AUTO SUPPLIES

Accessories 124, 125, 145, 262-263, 271, 365, 377-381, 404

Alarms 378

Alternator System 377

Antennas 145

Defroster 377, 381

Fuses 277

Horns 377

Ignition Systems 376

Radar Warning Device 382

Radios 111, 146-149

Reverbs 148

Speakers 262, 263

Suppressors 145

Tape Mounts 125

Tape Units 111, 112, 121, 123, 124, 126

Test Equipment 372-375

Tire Gauge 377

Vibrators 145, 441

B

Baffles, Speaker 186

Balun Coils 430, 432

Barometer 215, 324

Barrier Strips 229

Bases, Record Changer 84, 85, 88, 90

BATTERIES

Booster Cables 246, 247

Chargers 248, 370, 371, 407, 450

Clips 247, 248

Eliminators 248, 381

..... 406, 407, 450

Holders 407, 428

Photo-Flash 332

Rechargeable 246, 247

Tester 404

Bell 315

Bench Frame 367

Blas Supply 407

Binding Posts 259

Binoculars 337, 361

Black & White 151, 152

TV Sets 341, 343

Blow Torch 226

Boards, Printed Circuit 226

Bongos 214

BOOKS

Amateur 385, 387

Audio & Hi-Fi 386, 388-390

Auto 381, 390

Citizens Band 384

Computer 386, 389

Experimenters 223, 294, 386-390

General Science 307, 387-390

Music 176, 388

Printed Circuit 223, 294, 383, 388-390

Recording 386, 390

Service 239, 384, 386, 390

Test Equipment 386, 390

Transistors 294, 383, 389-390

BOOSTERS

TV & FM 289, 294-296

Boxes, Plastic 279

Breadboards, 227, 229

Masonite

BRIDGES

Capacitance & Resistance 399

Standing Wave 428, 445

Broadcaster/Phono 210

Oscillator 210

Brushes 135, 309

Bug Killer 267

Bug Horn 218

Burglar Alarms 126, 212, 213, 317, 378

Bushings 227, 303

Buzzers 377

C

CABINETS

Accessories 366

Hi-Fi 77, 128, 143, 278, 279

Metals 278, 279

Parts 278, 358

Racks 278, 279

Record 77

Speaker 68, 186, 262

Tape 127, 128, 130

Utility 77, 279, 358, 366

CABLES (See WIRE & CABLES)

Callipers 361

Cam-Dwell Tester 372-375

Cameras

Accessories 327, 329, 330, 332, 333

Kits 326, 332

Lenses 331

Movie 326, 332

Rangefinder 329

SLR 328, 329

Subminiature 332

Tripods 333

CAPACITORS

Asported 272

Ceramic 274, 275

Electrolytic 272, 273

High Voltage 274, 275

Mica 275

Mylar 276

Padder & Trimmer 231

Paper 276

Substitution

Boxes 399, 404

Testers 399, 403

Transmitting 275

Variable 230

CARTRIDGES

Crystal-Ceramic 138-

..... 140, 143

Magnetic 82, 83, 139

Microphone 192, 195

Tape 126, 127

CASSETTE

Accessories 128, 130, 135, 113

Decks 8, 36, 98, 104-112, 114, 115

Splices 128, 131

Tapes 129, 131

Casters 278

Chassis, Metal 278, 279

Punch 361

Repair Cradle 346

Chargers, Battery 248, 370, 371, 407, 450

Chimes 316

Chokes, Filter 232, 233, 253

RF 232, 233

Circle Cutter 356, 357

Circuit Breakers 304, 316

CITIZENS BAND

Antennas 439, 440, 442-444

Crystals 444

Microphones 194, 195

Parts 446

CLIPS

Clocks 324, 375, 429, 431

Clock Radios 153, 156, 157

Closed Circuit TV 418

Code Equipment 216, 426-427

COILS

Antenna 233

Balun 432

Dope 229

Miniature 232, 233

Multiplex Stereo 233

Oscillator 231

Radio & TV 232, 233

Transmitting 432

Coil Form 232

Coil Winder 232

Color Bar Generator 398, 399, 402

Color Organ 54, 55, 164, 213

Color TV Sets 152, 153

COMMUNICATIONS RECEIVERS

..... 149, 150, 161, 209, 422-425, 375, 381

Compass 368

Compressor 374

Compression Tester 374

Computer Kits 210-211

CONDENSERS (See Capacitors)

CONNECTORS

Antenna 145, 300, 303, 447

Cable 145, 256-258, 432

Microphone 93, 257, 258, 432

RF 257, 447

Solderless 432, 443

Contact Cleaner 346

Continuity Tester 404-406

CONTROLS (See Potentiometers)

CONVERTERS

Amateur 212

Auto Radio 148

FM 148

Marine 212, 214

Police-Aircraft 212, 214, 437, 447

Power Short Wave 212

UHF 293

Copler 311

CORDS

Line 203, 282, 303, 316

Power 282

Zip 283

Counters 234

Counter-Sinks 357

Crimping Tools 347

Crossovers 74

CRT Tester/Rejuvenator 397, 401

CRYSTALS

Calibrator 429

CB, Amateur, and VHF 432

Color TV 225

Frequency Std. 432

Sockets 432

Cutters, Wire 362

Tubing 229

Pocket Pager 452

Preamplifier 212, 446

Selective Caller 453

Systems 452, 454-456, 464

Test Equipment 445-446

Transceivers 446, 448, 450, 454, 457-467

Walkie-Talkie 148-151

Cleaners 430

Ultrasonic 340

CLIPS

Clocks 324, 375, 429, 431

Clock Radios 153, 156, 157

Closed Circuit TV 418

Code Equipment 216, 426-427

COILS

Antenna 233

Balun 432

Dope 229

Miniature 232, 233

Multiplex Stereo 233

Oscillator 231

Radio & TV 232, 233

Transmitting 432

Coil Form 232

Coil Winder 232

Color Bar Generator 398, 399, 402

Color Organ 54, 55, 164, 213

Color TV Sets 152, 153

COMMUNICATIONS RECEIVERS

..... 149, 150, 161, 209, 422-425, 375, 381

Compass 368

Compressor 374

Compression Tester 374

Computer Kits 210-211

CONDENSERS (See Capacitors)

CONNECTORS

Antenna 145, 300, 303, 447

Cable 145, 256-258, 432

Microphone 93, 257, 258, 432

RF 257, 447

Solderless 432, 443

Contact Cleaner 346

Continuity Tester 404-406

CONTROLS (See Potentiometers)

CONVERTERS

Amateur 212

Auto Radio 148

FM 148

Marine 212, 214

Police-Aircraft 212, 214, 437, 447

Power Short Wave 212

UHF 293

Copler 311

CORDS

Line 203, 282, 303, 316

Power 282

Zip 283

Counters 234

Counter-Sinks 357

Crimping Tools 347

Crossovers 74

CRT Tester/Rejuvenator 397, 401

CRYSTALS

Calibrator 429

CB, Amateur, and VHF 432

Color TV 225

Frequency Std. 432

Sockets 432

Cutters, Wire 362

Tubing 229

D

Decade, Boxes 399, 404

Defroster, Auto 377

Degaussing Coil 305

DEMAGNETIZER

Head 127, 128, 134

Tape 127, 128, 132, 135

Depth Indicator 433

Desk 311

DIALS

Cords 230

Plates 269

Vernier 230

Delivery Information

Dimmers 416, 417

DIODES

..... 223-225

Direction Finders 433

Door Chime 316

Door Viewer 418

Drafting Equipment 308

Drawer 367

DRILLS

..... 348, 349, 354-357

Accessories 348, 349, 357

Bits 356

Sharpener 356

Stands 348, 356, 357

Driving Glasses 381

Drum Outfit 165, 176

Dwell Meter 372, 373

E

EARPHONES

..... 402, 207

EASY PAY PLAN

..... 22

Electrical Accessories 279, 316

Electrolytic Capacitors 272, 273

Electronic Flash 330

Electro-plating Kit 380

Enclosures, Speaker 68, 69, 186, 262, 263

Etchants 226

Engine Analyzer 373, 404

Engraving Tool 348

Equipment Cabinet

Hi-Fi 278, 279

Experimenter's Kits 208-210, 212, 215-217, 219, 222, 223, 226

Exposure Meters 330

Extension Cords 316

Extension Rods 230, 264

Eye Guards 361

F

Fahnestock Clips 255

Fans, Cooling 94, 309, 316

Fiber Optics 221

Four Channel Equipment

..... 2, 3, 8-10, 18, 19, 24, 32, 33, 35-37, 39, 41, 43, 46, 47, 49, 50, 98, 118, 198, 468

Field Strength Meter 428, 429

Files, Tools 357, 361

Film 332

FILTERS

Auto Ignition 447

Interference 276, 298, 305, 446

Fire, Alarms 212, 222, 317, 421

..... 317

Extinguishers 317

Fire/Police Receivers 149, 160-163, 212, 434-437, 457

Flash Bulbs & Guns 332

Flashlights 317

Flux, Soldering 345

LAFAYETTE

GENERAL INDEX



<p>FM Antennas 288-291 Boosters 291, 294-296 Communications Receivers 434-435 Splitters, Couplers 294, 296, 298 Receivers 52, 97, 153, 162 Tuners 52, 126</p> <p>FM-AM Radios 149, 150, 153- 163 Tuners 30-31, 49, 52, 53 Forming Tool 347 Fuses 277 Mountings 277 Fusible Resistors 304</p>	<p>Tape Decks 3, 103, 105, 113, 116, 117, 119, 120 Tape Players 10, 24, 101, 102, 104, 111, 112, 119, 121 Tape Recorders 8, 9, 35, 36, 101, 105, 110- 112, 114, 115, 120 Test Record 94 Test Tape 3, 129, 130 Tuners 30, 31, 49, 52, 108, 126 Turntables 84-90, 179 Hoist, Miniature 366 Home Auto 379</p> <p>HOW TO ORDER 416, 417</p> <p>Humidity Indicators 215, 216, 218, 219</p>	<p>Intercom 212, 214 Jewelry Making 218 Keyer 212 Lettering 309 Mineral 215 Motor Control 214 Oscilloscope 403 Photo Lab 219 Police/Fire 212, 214, 222 Power Supply 214 Preampifier 217, 222 Printed Circuit 216, 217, 222, 277 Probes 400, 402, 404 Psychedelic Lights 54, 55, 212, 213, 214 R-C Substitution Box 399 Receiver 53, 218 Rock Polisher 218 Rocket 219 Short Wave Receiver Light 209, 218 Signal Generator 398, 402, 403 Signal Traber 212, 398 Speaker Enclosure 68 Speaker System 73 Strobe Light 54, 135 Teknikits 215 Transmitter 429 Transistor Diode Checker 396, 397 Treasure Finder 214 Tube Tester 396, 401, 405 Tuners 52, 53 Turn Up 374 VOM 400-401 VTVM 400 Wireless Mike 213, 215 Voice Operated 215 Yoke Tester 404 Knives 349, 362 Knobs 231, 305</p>
<p>G Garage Door Opener 382 Garden Tools 350 Gauges, Stylus Pressure 144 Generator, Signal 398, 402, 403 AC Power 369 Geology Equipment 215 Glue Gun 364 Grid Dip Meter 429 Grinders, Speaker 94 Grommets 345 Ground Rods 307 Guarantee 415 Guitars 166-169</p>	<p>I IC Tester 397 IF Transformers 231, 233 Ignition Systems 376 Insect Killer 367 Inspection Light 313, 317 Mirror 346 Insulation, Acoustic 94 Insulators 227, 255, 283, 302 Stand-off 227, 302 Integrated Circuits 222</p> <p>INTERCOMS 20, 198, 199, 201, 212, 214, 418 Cable 280-282 Speakers 262 Interference filters 276, 298, 305, 446 Inverters 370, 371 Intrusion Alarms 212, 213, 317, 419-421</p>	<p>J JACKS Banana 259 D.C. Power 447 Phone 260, 261 Phono 92, 260, 261 Tip 259, 260 Jaw Saw 352, 353</p>
<p>H Hardware Radio-TV 301, 302, 347 Heads, Recording 136 Headphones 78-81, 153, 205-207, 429 Accessories 80, 81, 206, 207 Headphone Cushions 207 Hearing Aids 206 Heat Sinks 222, 225, 343</p> <p>HIGH FIDELITY Accessories 141, 144 Amplifiers 2, 4, 5, 12- 15, 19, 25-29, 34, 48, 49, 51-53 Amplifier Kits 53, 213 Cabinets 69, 77 Cartridges Phono 138-140 Tape 3, 82, 83 Cassette Recorders 104, 106-114 Changers 84, 86, 88-91, 300 Organ 54, 55, 164, 213 Connection Cables 93, 280, 281 Crossover Network 74 Enclosures, Speaker 68, 186, 262 Equalizers 188 Four Channel 2, 4, 5, 9, 10, 18, 19, 24, 32- 37, 39, 41, 43, 45, 46, 47, 52, 468 Headphones 78, 81, 153 Outdoor Speaker 185 Phonographs 99-101 Preampifiers 11, 49, 141, 188 Preamp Kits 52, 222 Receivers, FM 52, 97, 153, 162, 436 FM-AM 8-10, 12-17, 35, 40, 42, 43, 49, 51, 53, 98, 100-102, 106, 111, 120, 266, 267 Reverberation Units 50, 76, 172, 173 Speaker Crossover Kits 74 Speaker & Speaker Systems 56-76 Stereo Compacts 11, 96, 100, 101 Systems 11, 28, 33, 35, 36, 42, 43, 46, 47, 68, 96, 97, 99-101</p>	<p>K Keys, Code Practice 427</p> <p>KITS Aircraft Receiver 213, 222 Amplifier 52, 214, 216, 217 Antenna 281 Atomic Energy Lab 215 Audio Generator 398, 402 Battery Tester 404 Bias Supply 215 Bird Call 212 Black Light 210, 340 Bongo 214 Bridge, RC 399 Broadcast Radio 217, 213-215, 218 Capacitor Checker 217, 399, 403 Capacitor Substitution Box 404 Chemistry Lab 219 Code Practice Oscillator 212, 214, 216, 222 Color Organ 213, 214 Computer 210, 211 Converter 212, 214 Crystal Radio 214 Electroplating 380 Engine Model 219 Engine Analyzer 404 Experimenter 208, 217, 223 Fire Alarm Flyback and Yoke Tester 404 FM Radio 52, 214 Fuzz Box 214 Grid-dip Meter 429 Integrated Circuits 212, 222, 227</p>	<p>L L-Pads 266, 267 Label Maker 306 Tape 306</p> <p>LAMPS Adjustable 301, 313 Auto 380, 381 Driving 370 Fluorescent 312, 313, 316 Fixtures 203 High Intensity 312 Inspection 301, 313, 317 Neon 333 Movie 236, 237 Panel 236, 237 Pilot 236, 237, 447 Portable Beacon 317, 380 Projection 333 Replacement 237, 313 Stroboscopic 54, 126, 144 Typewriter 312 Ultra Violet 340 Language Records 387 Lantern 317 Lathes 349 Lettering Kits 309 Levels 366 Leveling Kit, Phono 94 Lightning Arrester 302, 440</p> <p>LINE CORDS Appliance 316 TV 395 Line Voltage Tester 395, 406, 408, 409 Locks 367, 378, 379, 419 Lubricants 134, 135, 143, 223, 225, 305, 346, 347 Lugs 259</p>
<p>M Magnets 367 Magnifiers 313, 339 Marine Equipment 433</p>	<p>M Masts, TV 301 Megaphone, Power 184, 433 Melodicas 176 Memory Card File 210 Mercury Batteries 246</p> <p>METERS Battery 410 Elapsed Time 408 Exposure 330 Field Strength 428, 429 Flow (Water) 369 Frequency 408 Panel 408-410 Power Line 395, 409 PS 428 Stereo Balance 94, 410 Tuning 410 VU 410 Wattmeter 428 Metronome 176, 212 Microammeter 408</p> <p>MICROPHONES 173, 190-197, 205 Accessories 188, 189, 192, 196, 197, 222, 258, 447 Cable 92, 93, 280, 281 Cartridges 192, 195 Connectors 189, 258, 447 Contact 193 Mixers 188, 192, 222 Stands & Booms 189 Transformers 197, 253</p> <p>MICROSCOPES 334-336 Accessories 335, 336 Illuminator 336 Stylus Inspection 144 Milliammeter 408-410 Minibikes 321 Mixers 188, 192, 222 Modules, Solid-State 212, 213, 427</p> <p>MOTORS 228, 319, 348 Phono 141 Speed Control 214, 348, 354 Movie Cameras 326 Editor 327 Lamps 333 Projector 327 Screen 333 Outfits 326 Viewer 327, 333 Musical Instruments 164- 166, 168, 169, 176 Accessories 166, 168, 170-177, 193, 212 Microphones 193, 212</p>	<p>N Needles 83, 140, 142, 143 Neon Lamps 236, 237 Sockets 237 Networks, Crossover (See Crossovers) 360 Nibbling Tool Nickel Cadmium Batteries 246, 247 Noise Suppressors 115, 145, 446, 447 Nut Cracker 361 Nut Drivers 363, 364</p>
<p>O OHM's Law Calculator 249 Oil Pressure Gauge 374-376 Organ 164, 214</p> <p>OSCILLOSCOPES 399-403 Kits 403 Oscillator Coils 231-233 Outlets, AC 315, 316</p>	<p>P Pagery 418, 452 Paint Sprayer 368 Panels, Rack 278 Panograph 308 Podometer 323 Pencil Sharpener 309 Pens 309</p> <p>PHONO EQUIPMENT 29, 141, 212-214, 216, 217 Amplifiers 84, 85, 88-91, 92, 93, 280-282 Cartridges 138-141, 143 Changers 84-91 Covers 144 Levels 144 Motors 141 Needles 83, 140, 142, 143 Oscillator 141 Preampifier 141 Plugs & Jacks 92, 93, 260, 261 Shut-off 141, 144 Spinners-Spiders 88-91, 140, 141 Tone Arms 141 Turntable 141 Phonographs 95-101 Photoacells 228, 314 Photoelectric Equipment 314, 419 Switch 314 Photographic Equipment 219, 326-333</p> <p>PICTURE TUBES 238, 239 Brighteners 304 Extension Harness 304 Restorers 304, 397, 401 Sockets 256 Pilot Lights 236, 237, 447 Planes 350, 351 Plating Kits 380 Pliers 362</p> <p>PLUGS AC 279 Banana 259 Cable 93, 203, 260, 261, 303 Phone 92, 93, 260, 261 Phono 92, 93, 212-214, 434-437, 454 Polystyrene Rods 229 Sheets 229 Tubes 229 Posts, Binding 259 Potentiometers 264-267 Power Plants 369 Power Supplies 126, 217, 222, 370, 371, 406, 407</p> <p>PREAMPLIFIERS Amateur & CB 212, 429, 446 Hi-Fi 11, 49, 141, 188</p> <p>PRINTED CIRCUITS 226, 227 Boards 226, 227 Connectors 226, 227 Sockets 256 Supplies 226, 227 Probes 259, 400, 404, 405, 408</p> <p>Projectors Movie 326 Opaque 339 Slide 329</p>	
<p>PUBLIC ADDRESS Accessories 183, 186 Amplifiers 173, 178-183 Baffles 183, 186 Megaphones 184, 218, 433 Microphones 173, 190, 191, 194, 195, 197 Mixer-Preamps 188, 192</p>		

Pagers 418, 452
Speakers 184-186
Systems 178-183
Pumps
Air 367
Submersible 369
Punches 357, 362
Chassis 361

R

RACKS
Steel 278
Radar Detector 382

RADIO CONTROL EQUIPMENT 220, 382

RADIOS
(Also See Receivers)
Automobile 111, 146-149
Marine 150, 161, 162, 433

Portable 149, 150, 153, 158-163
Table 150, 153-157
Radio-Telephone 433
Rain Gauge 215, 325
Reamers 357

RECEIVERS
Aircraft 160-163, 435-437
Communications 149, 150, 161, 209, 422-425

Fite/Police 149, 159-163, 212-214, 434, 437, 457
FM 153
FM-AM 6-17, 49-51, 102, 155

RECORD
Adapters 88-91, 140, 144

Albums 69, 144
Cabinets 77
Care Accessories 143, 144
Changers 84, 86, 88-91

Code Practice 426
Foreign Language 387
Guitar Instruction 176
Test 54
Recording Tapes 127, 132, 136, 137

RECTIFIERS
Meter 410
Rectifier Mounting Kits 224

Silicon 223-225
Reels, 8mm 333
Tape 133, 135
Refractometer, Sugar 340
Refrigerators 321

RELAYS 212, 234-235
Cleaning Tools 234
Remote Control Equipment (See Radio Control)

Remote Control (Switches) 314, 316, 372, 374

Remote TV/Radio Earphone Adapters 206

RESISTORS
Adjustable 250
Assortment 249
Color Code Guide 249
Fusible 364
Power 250
Substitution Box 393, 404, 406

Reverberation Equipment 50, 76, 148, 172, 173, 188

Rheostats 266
Rivets 367
Rocket Kit 297
Rotors, Antenna 296, 297, 430, 443
Router 351

S

Sanders 351
Saws 352, 353, 357, 361, 364
Blades 353, 367
Screwdrivers 357, 363
Semiconductors 223-225

Semiconductor Analyzer 396, 397, 401
Shaft Coupling 264, 363
Shelves 367

SHIPPING INSTRUCTIONS 416, 417

Shortwave Receivers (See Receivers)
Signal Generators 398, 402, 403
Kits 402, 403

Signal Tracers 212, 398, 402, 403
Siphon 381
Siren, 110 volt 420

SLIDE
Projector 329
Rules 307
Staining Kit 335
Viewer 328

SOCKETS
Cable 257, 258, 303, 447
Crystal 432
Pilot Light 237
Printed Circuit 256
Relay 257
Transistor 256
Tube 256

Socket Wrenches 356, 365
Solar Cells 228, 314

SOLDERING EQUIPMENT
Accessories 342-345
Guns & Irons 342-345
Solder 345
Sound Reproducer 76

SPEAKERS
Auto 125, 262, 263
Ceiling & Wall 75, 186
Coaxial 71, 72
Hi-Fi 56-76, 184
Extension 75, 184-187
Musical Instruments 177

Outdoor 184, 187
P.A. 184-187
Pillow 205-206
Replacement 262
Systems 56-68, 75, 76
Trumpets 177, 185
Tweeters 72, 73, 76
Woofers 72, 73

SPEAKER ACCESSORIES
Acoustic Padding 94
Cable 92, 280, 281
Controls 263-267
Crossovers 68, 69
Enclosures 262, 263

Grille, Auto Speaker 125, 263
Grille Cloth 94
L-Pads 263, 271
Switches 263, 271
T-Pads 263, 271

Spectroscope 340
Spotting Scopes 339
Sprayers, Paint 368
Standoff Insulators 227
Stands, Microphone 389
Staple, Gun 359
Staples 359

STEREO EQUIPMENT (See Hi Fidelity)
Store Addresses 20
Strobe Lights 54, 55, 128, 144, 213, 330
Styli 83, 140, 142, 143
Brush 144
Microscopes 144
Pressure Gauges 144
Submersible Pump 369

SWITCHES
Antenna 305, 432, 445
Automatic Light 270, 314
Coaxial 431, 432, 445
Delayed Action 268, 270
Dimmer (Light) 315
Foot 130, 268, 271
Intercom 268, 269
Knife 271, 305
Lever 269, 271
Lock 271
Master 271
Mat 419
Mercury 258, 271
Momentary 270, 271

Photoelectric 314
Potentiometer 264-267
Proximity 213, 271
Push-Button 268-271
Reed 223
Remote Control 314, 316
Rocker 268, 271
Rotary 269, 271
Slide 125, 267
Speaker 270, 271
Stepping 269
Time 318-320
Toggle 268, 270
Wall 268, 270
Whistle 314
Switch Plates 268
SWR Meter 428, 448

T

T-Pads 266, 267
Tachometer 372-375
Tap and Dies 361

TAPE
Alignment 128-130
Cartridges 3, 126, 127, 137
Cassettes 129-131
Demagnetizer 127, 128, 130, 132, 134

Editing Kit 128, 131, 134
Electrical 316
Eraser 127, 128, 132, 135
Heads 136
Labels 128, 134
Leader & Timing 128, 132, 137
Prerecorded 3, 129, 426
Recording 127, 132, 136, 137

Reels 137
Sensing 128, 134
Splicer 132, 128, 137
Test 3, 128-130

TAPE RECORDING EQUIPMENT
Accessories 115, 126-128, 130, 133-137
Auto, Portable Player 111, 118, 121, 122, 124, 126
Decks 3, 103, 105, 113, 116, 117, 119, 120
Home Player 10, 24, 98, 101, 102, 103, 118, 119, 121, 122, 9, 35, 36, 101, 105, 110-112, 114, 115, 120

Stereo Tape Head Conversion Kits 136
Telephones 202, 203
Amplifier 203
Answering Equipment 204
Extension Cord 203
Intercom 200, 418
Pickup 128, 130, 132, 134, 135, 203

Recorder 108, 204
Telescopes 338, 339

TELEVISION
Alignment Tools 346
Antennas 284-293
Antenna Couplers 294, 296, 298, 299
Attenuators 298, 299
Black & White 151-152
Boosters 294-296
Cheater Cord 304
Clock 324
Closed Circuit Camera 418

Color Set 152
Controls 264-267
Degasser 305
Distribution Units 289, 294-296
Extension Speakers 75, 187
Harness Kits 304
I.F. Coils 232-233
Knobs 305
Masts 301
Matching Transformer 185, 253, 254
Noise Filter 305

LAFAYETTE GENERAL INDEX

Picture Tubes 238, 239
Picture Tube Brightener 304
Picture Tube Tester/Rejuvenator 397, 401
Rotors 296, 297
Splitter 294, 298, 299
Towers 300, 301
Tuner 305
Twin Line 280, 283
Voltage Regulator 304
UHF Converters 293

Terminals 303, 309
Terminal Strips 227, 229

TEST EQUIPMENT (See Item Wanted)
Test Leads 255, 400, 405
Tester Battery 404
Tube 396, 397, 401, 409
Transistor 396, 397, 400, 401
Thermometers 324, 325
Timers 144, 318-320, 332
Timing Light 372, 374
Tire Cleats 379
Tire Pressure Gauge 381
Tone Arms 83, 141

TOOLS 346-351, 354, 355, 360-367
Cabinets 366, 367
Power 348-351, 354, 360
Sets 346, 348, 349, 363, 364, 374
Torches 341, 363
Torque Wrench 365, 366, 461
Towers 300, 301
T-Pads 266, 267

Transceivers (See Amateur, CB, or Marine)

TRANSFORMERS
Air Conditioner 253
Audio 254
Auto 250, 253
Bell 316
Control 252
Driver 252, 254
Filament 252, 254
IF 231, 233
Input 252
Intercom 254
Isolation Line 253, 254
Matching (See Line)
Microphone 197, 253
Modulation 253, 254
Output 251-253
Rectifier 252
Step-Down 250, 253
Transistor 254
TV Matching 185
Variable 250, 253
Voltage Regulator 253, 304

TRANSISTORS
Heat Sinks 223-225
Mounting Kits 223-225
Testers 396, 397, 400, 401
Transit 359
Transmitters 446
Transmitting Coils 432
Treasure Finder 80, 214
Triods, Camera 327, 330

TUBES
Adapters 256
Brighteners 304
Caddy 309
Cooling Fan 94, 309, 377
Manuals 239
Pin Straighteners 239
Pullers 239
Saver 304
Shields 257
Sockets 257
Tester 396, 397, 401, 409
Kits 396, 401, 405

Picture, TV 238, 239
Receiving 240-245

Special Purpose 418

Tubing 226

TUNERS
AM 217
FM Hi-Fi 52
FM Kits 52
FM-AM, Hi-Fi 30, 31, 49, 52, 53, 108, 126
TV, Front End 305
Tuning Dials 230
Turntables 84-90, 179
TV Filters 298, 299, 432
TV Sets 151-152
Tweezers 72, 73, 76
Typewriters 310

U
UHF Converters 293
Ultrasonic Alarms 420
Ultrasonic Cleaners 340
Ultra Violet Light 210, 340

V
Vacuum Cleaner 359, 381
Vacuum Gauge 374
Variable Voltage Transformers 250, 253
Vibrators 145, 447
Vises 349, 360
Voltage Regulators 253, 304
Voltmeters 408, 409

VOLUME CONTROLS 264-267
VOM'S 391-395, 400, 401, 404, 405
Kits 400, 401
VTVM 393, 394, 400, 401
Kits 400, 401
VU Meters 410

W
Wall Plates 303
Walkie-Talkie 448-451
Accessories 439, 447, 450
Watches 322, 323
Waterfall Kit 369
Wattmeter 428, 445
Weather Instruments 215, 324, 325
Welders 341
Wire Bending Jig 346

WIRE & CABLE
Antenna 145, 282, 283, 301, 447
Appliance 282
Coaxial 282, 283, 299
Extension Cords 145
Hook-Up 92, 93, 145
Intercom 280, 281, 283
Line 280, 281
Litz 280
Magnet 282
Microphone 280, 281, 447
Phono 280-282
Rotor 280, 281, 283
Shielding 280, 282
Spark Plug 379
Speaker 92, 280, 283
Telephone 280-282
Test Prod 281
Twin Line 280-283
Wire Strippers 362

Wireless Broadcaster Kit 213, 218
Wireless Microphone 193
Woofers 72, 73
Work Benches 367
Wrenches 361, 364-366

Y
Yoke Checkers 404

Z
Zener Diodes 224, 225

You Can Depend On LAFAYETTE... ...for Your Complete Satisfaction

When you buy from Lafayette, you buy with confidence. Lafayette's pledge to you, of "Satisfaction Guaranteed or Money Refunded," is your assurance that we mean what we say. For 50 years we have kept this pledge to you . . . and shall continue to do so in the future.

LAFAYETTE AAA GUARANTY

LAFAYETTE HIGH FIDELITY SPEAKERS = 5 YEARS
LAFAYETTE HIGH FIDELITY RECEIVERS = 2 YEARS
LAFAYETTE HIGH FIDELITY TUNERS = 2 YEARS
LAFAYETTE HIGH FIDELITY AMPLIFIERS = 2 YEARS

All Lafayette high fidelity components identified as covered by Lafayette's AAA guaranty are guaranteed to be free of defects in material or workmanship from the date of sale for the time period shown above. During that period we will repair (or at our option replace) them without charge for either material or labor. Material must be returned prepaid to us for our inspection. This guaranty does not apply to items which have been subjected to misuse, abuse, alteration, repair without our authorization or used in violation of operating instructions, nor to normal wear and tear. The speaker guaranty does not cover external parts such as cabinets, grille cloth etc. Serial number must not be defaced. Guaranty is not transferrable.

OTHER GUARANTEES

All merchandise not covered either by the special guarantees on this page or by other specific guarantees in the catalog are covered by a 90 day repair or replacement guarantee (at our option) against defects in material or workmanship.

LAFAYETTE AAM GUARANTY

This guaranty covers Lafayette items so indicated in our catalog which contain several integrated sections in a single unit such as compacts and integrated entertainment centers. The time period for each section is as follows:

SPEAKERS	5 YRS.
RECEIVER OR TUNER SECTION	2 YRS.
AMPLIFIER SECTION	2 YRS.
RECORDER SECTION	3 MOS.
CHANGER SECTION	3 MOS.

The terms and conditions of this guaranty are otherwise identical to the AAA Guaranty.

SATISFACTION GUARANTEED

If for any reason you are not satisfied with your purchase return it to us within 30 days in the original factory carton and we will exchange it or return your money (less transportation charges). Merchandise returned must be in good condition and not soldered or abused—no holes drilled or changes made in any other way. This policy does not apply to kits, nor to pre-recorded tape, records, books or merchandise not regularly stocked that has been ordered especially for you.

HOW TO RETURN MERCHANDISE

(Merchandise Returned Must be in New Condition)

We want you to be completely satisfied with every item you purchased from us. If there is an irregularity in your shipment and you find it necessary to return an item to us, follow these instructions:

- 1) PARCEL POST SHIPMENTS**
- Place all order papers, invoices, correspondence and your instructions in an envelope inside your package.



- 2)** On the outside of your package, mark "First Class Mail Enclosed" (directly below the postage) and add an additional 8c postage. Do not send the letter separately; it will delay our speedy adjustment handling.



- 3)** Pack the merchandise securely and send to:
Customer's Service Dept.,
LAFAYETTE RADIO ELECTRONICS,
111 Jericho Turnpike,
Syosset, L.I., N.Y. 11791

- 4)** For your protection, report damaged receipts to your postman and enclose his report with your papers.

BY EXPRESS OR TRUCK

If your shipment is received damaged, obtain a report from your express agent or trucker, and mail to us. Wait until you receive our instructions on how to return.

(NOTE—Merchandise not regularly stocked that has been ordered for you is NOT returnable for refund or exchange.)



IF IT IS NECESSARY TO WRITE US:

Before writing, please compare papers or invoices with merchandise received. You will find explanations on your order papers about how your order has been handled. Sometimes merchandise arrives before or after order papers. Please wait until you have both before writing. If you write, be sure to include all papers concerning the order. Please give names of items, catalog numbers, quantity, color, price, and any special information you think necessary. The more details you give us, the more quickly your adjustment will be made. On Easy Payment orders, be sure to include your EP account number on package and correspondence.

Fast Direct Air Shipping Service To West Coast

The Following Area will now receive speedy air shipping service: LOS ANGELES.

No more than 4 day door to door delivery via United Parcel Service to California, Washington and Oregon.

Parcels utilizing this rapid service must weigh no more than 50 pounds and measure up to 108 inches in combined length and girth. This system applies if the service or rates are to your benefit.

SHIPMENTS OUTSIDE OF THE UNITED STATES

We ship all over the free world. Allow up to 60 days for delivery. Write to our International Sales Division for details.

Make Lafayette Your One Dependable Source for Everything in Electronics

Lafayette Cat. No. 720 415

SHIPPING AND DELIVERY INFORMATION

HOW TO ESTIMATE PARCEL POST CHARGES



Less than 16 oz., all zones allow 8c for first 2 oz., 2c for each additional oz. Find the weight of your merchandise in the extreme left-hand column of the chart at right. Pay the amount listed for Parcel Post shipment to your zone. A fraction of a pound is charged as a full lb. For example, if the weight is 6 lbs. and 1 oz. to Zone 3, postage would be for 7 lbs. (1.10). Over 40 lbs. shpd. truck or exp. See below

AIR PARCEL POST SHIPMENTS

We will ship your order via Air Parcel Post upon your request. Rates are given in the table below. Size and weight limits: 70 lbs. and 100 in. (length plus girth).

11c per ounce, up to 8 ounces								
ZONES 1, 2 & 3			4			5		
1st LB.	2nd LB.	3rd LB.	4th LB.	5th LB.	6th LB.	7th LB.	8th LB.	9th LB.
1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
For Each	Add	Add	Add	Add	Add	Add	Add	Add
Extra Lb.	.48	.50	.56	.64	.72	.80		

MINIMUM ORDER CHARGE

ORDERS UNDER \$5.0050

PARCEL POST	\$ 5.00 to 15.00	20c
HANDLING	15.01 to 50.00	30c
CHARGE	50.01 to 100.00	40c
	100.01 to 150.00	50c
	151.01 to 200.00	60c

ABOUT C.O.D. ORDERS (Minimum Order \$10.00, 20% Deposit)

If you order C.O.D., the post office collects a handling charge, plus a money order fee, in addition to the regular parcel post charge. (We cannot accept C.O.D.'s for APO's,

FPO's or for special-order merchandise). The extra C.O.D. fees are:

PARCEL POST C.O.D. FEES:

\$10.01 to \$25.00	80	\$ 50.01 to \$100.00	1.00
\$25.01 to \$50.00	90	\$100.01 to \$200.00	1.10

MONEY ORDER FEES:

From 10.01 to 50.00	35
From 50.01 to 100.00	40

UNITED PARCEL DELIVERY

United Parcel Service Rate Chart (use if an * appears next to Zip Code). Items Keyed "WX" are not shippable UPS. (See REA Express Information.)

If your area is serviced by UPS and the service or rates are to your benefit, we will route your order via United Parcel Service. This fast, economical service is available for parcels up to 50 lbs. and 108 inches in length and girth.

ANY FRACTION OF A POUND OVER THE WEIGHT SHOWN TAKES THE NEXT HIGHER RATE

WEIGHT NOT TO EXCEED	ZONES								WEIGHT NOT TO EXCEED	ZONES							
	ZONE 2	ZONE 3	ZONE 4	ZONE 5	ZONE 6	ZONE 7	ZONE 8	ZONE 2		ZONE 3	ZONE 4	ZONE 5	ZONE 6	ZONE 7	ZONE 8		
1 lb.	\$.55	\$.57	\$.60	\$.62	\$.65	\$.68	\$.72	26 lb.	\$1.80	\$2.32	\$2.97	\$3.62	\$4.40	\$5.18	\$ 6.22		
2 lb.	.60	.64	.69	.74	.80	.86	.94	27 lb.	1.85	2.39	3.07	3.74	4.55	5.36	6.44		
3 lb.	.65	.71	.79	.86	.95	1.04	1.16	28 lb.	1.90	2.46	3.16	3.86	4.70	5.54	6.66		
4 lb.	.70	.78	.88	.98	1.10	1.22	1.38	29 lb.	1.95	2.53	3.26	3.98	4.85	5.72	6.88		
5 lb.	.75	.85	.98	1.10	1.25	1.40	1.60	30 lb.	2.00	2.60	3.35	4.10	5.00	5.90	7.10		
6 lb.	.80	.92	1.07	1.22	1.40	1.58	1.82	31 lb.	2.05	2.67	3.45	4.22	5.15	6.08	7.32		
7 lb.	.85	.99	1.17	1.34	1.55	1.76	2.04	32 lb.	2.10	2.74	3.54	4.34	5.30	6.26	7.54		
8 lb.	.90	1.06	1.26	1.46	1.70	1.94	2.26	33 lb.	2.15	2.81	3.64	4.46	5.45	6.44	7.76		
9 lb.	.95	1.13	1.36	1.58	1.85	2.12	2.48	34 lb.	2.20	2.88	3.73	4.58	5.60	6.62	7.98		
10 lb.	1.00	1.20	1.45	1.70	2.00	2.30	2.70	35 lb.	2.25	2.95	3.83	4.70	5.75	6.80	8.20		
11 lb.	1.05	1.27	1.55	1.82	2.15	2.48	2.92	36 lb.	2.30	3.02	3.92	4.82	5.90	6.98	8.42		
12 lb.	1.10	1.34	1.64	1.94	2.30	2.66	3.14	37 lb.	2.35	3.09	4.02	4.94	6.05	7.16	8.64		
13 lb.	1.15	1.41	1.74	2.06	2.45	2.84	3.36	38 lb.	2.40	3.16	4.11	5.06	6.20	7.34	8.86		
14 lb.	1.20	1.48	1.83	2.18	2.60	3.02	3.58	39 lb.	2.45	3.23	4.21	5.18	6.35	7.52	9.08		
15 lb.	1.25	1.55	1.93	2.30	2.75	3.20	3.80	40 lb.	2.50	3.30	4.30	5.30	6.50	7.70	9.30		
16 lb.	1.30	1.62	2.02	2.42	2.90	3.38	4.02	41 lb.	2.55	3.37	4.40	5.42	6.65	7.88	9.52		
17 lb.	1.35	1.69	2.12	2.54	3.05	3.56	4.24	42 lb.	2.60	3.44	4.49	5.54	6.80	8.06	9.74		
18 lb.	1.40	1.76	2.21	2.66	3.20	3.74	4.46	43 lb.	2.65	3.51	4.59	5.66	6.95	8.24	9.96		
19 lb.	1.45	1.83	2.31	2.78	3.35	3.92	4.68	44 lb.	2.70	3.58	4.68	5.78	7.10	8.42	10.18		
20 lb.	1.50	1.90	2.40	2.90	3.50	4.10	4.90	45 lb.	2.75	3.65	4.78	5.90	7.25	8.60	10.40		
21 lb.	1.55	1.97	2.50	3.02	3.65	4.28	5.12	46 lb.	2.80	3.72	4.87	6.02	7.40	8.78	10.62		
22 lb.	1.60	2.04	2.59	3.14	3.80	4.46	5.34	47 lb.	2.85	3.79	4.97	6.14	7.55	8.96	10.84		
23 lb.	1.65	2.11	2.69	3.26	3.95	4.64	5.56	48 lb.	2.90	3.86	5.06	6.26	7.70	9.14	11.06		
24 lb.	1.70	2.18	2.78	3.38	4.10	4.82	5.78	49 lb.	2.95	3.93	5.16	6.38	7.85	9.32	11.28		
25 lb.	1.75	2.25	2.88	3.50	4.25	5.00	6.00	50 lb.	3.00	4.00	5.25	6.50	8.00	9.50	11.50		

Additional charge for each COD delivery, 65 cents--and each address correction, 65 cents. WEIGHT AND SIZE LIMITS

Maximum Weight per package, 50 POUNDS. Maximum Weight of all packages from one shipper to one consignee in one day, 100 pounds.

Maximum Size per package, 108 INCHES IN LENGTH AND GIRTH COMBINED.

Minimum charge for a package measuring over 84 inches in length and girth combined will be equal to charge for a package weighing 25 pounds.

SHIPPING AND DELIVERY INFORMATION

Use our Order Blank . . . To assure fast delivery fill in all information requested (Please Print). Always give your Zip Code! We'll send you new order blanks each time you order.

How to figure Shipping Charges . . . See ZIP CODE CHART to find your shipping zone. To calculate charges refer to PARCEL POST chart or UPS chart if an asterisk appears next to your zip code. We will ship the most economical or fastest way. Items not shippable by Parcel Post or UPS will be shipped separately by Railway Express.

Cash Orders . . . Please remit full amount, including amount you calculate for shipping charges, tax, handling charge or insurance. Do NOT send Currency or Stamps. We refund any excess.

COD Orders . . . Ordering by COD is more expensive for you. You pay an extra fee (see COD Chart). For COD orders you must send a 20% deposit and pay the balance when your package arrives. No COD's under \$10.00.

Easy Pay Orders . . . Indicate on the order blank whether a "new" or "add-on" Easy Pay order and fill in all information requested on back of the order blank.

Shipping Weights . . . All weights shown in this catalog are as accurate as we can determine. Use these weights and rate charts to determine shipping charges.

USE YOUR ZIP CODE TO FIND YOUR SHIPPING ZONE OR UPS

This zone chart lists the first three digits (prefix) of the ZIP Codes of the sectional center facility of address. To determine the zone distance to a particular post office, ascertain the ZIP Code of the post office to which the

parcel is addressed. The first three digits of that ZIP Code are included in this chart, to the right thereof the zone. If an (*) appears to the left of your zip prefix refer to UPS chart for charges, otherwise use Parcel Post chart.

Zip Code Prefixes	Zone	Zip Code Prefixes	Zone	Zip Code Prefixes	Zone	Zip Code Prefixes	Zone	Zip Code Prefixes	Zone	Zip Code Prefixes	Zone	Zip Code Prefixes	Zone
006-009	7	*080-086	2	*178-199	2	*339	6	*469	5	*577	7	756-762	6
*010-013	2	*087-089	2			*350-364	5	*470	4	*580-585	6	763-770	7
*014	3	090-098	1	*200-218	3	*365-366	6	*471-472	5	*586-589	7	773	6
*015-018	2	*100-116	2	*219	2	*367-374	5	*473	4	590-593	7	774-775	7
*019	3	*117-118	2	*220-238	3	*376	4	*474-479	5	594-599	8	776-777	6
*020-024	2	*119-127	2	*239-253	4	*377-386	5	*480-489	4	*600-639	5	778-797	7
*025-026	3	*128-136	3	*254	3	*387	5	*490-491	5	*640-648	6	798-799	8
*027-029	2	*137-139	2	*255-266	4	*388-389	5	*492	4	*650-652	5		
*030-033	3	*140-149	3	*267	3	*390-392	6	*493-499	5	*653	6	800-812	7
*034	2	*150-154	4	*268-288	4	*393	5			*654-655	5	813	8
*035-043	3	*155	3	*289	5	*394-396	6	*500-503	6	*656-676	6	814	7
*044	4	*156	4	*290-293	4	*397	5	*504	5	*677-679	7	815	8
*045	3	*157-159	3	*294	5			*505	6	*680-692	6	816-828	7
*046-049	4	*160-161	4	*295-297	4	*400-402	5	*506-507	5	*693	7	829-874	8
*050-051	3	*162-163	3	*298-299	5	*403-406	4	*508-519	6	*723-724	6	875-877	7
*052-053	2	*164-165	4			*407-409	5	*520-539	5	*725-726	5	878-880	8
*054-059	3	*166-169	3	*900-324	5	*410-419	4	*540	6	*725-738	6	881-884	7
*060-067	2	*170-171	2	*325	6	*420-427	5	*541-549	5	*739	7	890-898	8
*068-077	2	*172-174	3	*326-329	5	*430-458	4	*550-554	6	*740-749	6		
*078	2	*175-176	2	*330-334	6	*460-466	5	*556-559	5	*750-754	6		
*079	2	*177	3	*335-338	5	*467-468	4	*560-576	6	755	6	900-999	8

REA EXPRESS INFORMATION

Items not shippable Parcel Post or UPS are sent Railway Express. The Letters WX or WUX identify these items. DO NOT SEND MONEY for express charges with your order. Express charges are collected upon delivery at no extra cost to you. Insurance is included in your express rates. Be sure to specify your nearest Express Office if there is no agent in your town.

APPROXIMATE REA EXPRESS CHARGES

Zone	Local	1 & 2							
		3	4	5	6	7	8		
		0-150 Miles	151-300 Miles	301-600 Miles	601-1000 Miles	1001-1400 Miles	1401-1800 Miles	1801 & over Miles	
Pounds									
1-25	\$ 8.30	\$ 9.20	\$10.50	\$11.50	\$12.80	\$14.10	\$15.50	\$18.40	
26-50	8.90	10.30	12.10	13.70	15.60	17.70	19.60	24.10	
51-75	9.50	11.40	13.90	16.00	18.40	21.20	23.80	29.90	
76-100	10.10	12.40	15.50	18.10	21.10	24.60	27.90	35.30	
over 100 lbs.									
Add per lb.	.10c	.12c	.15c	.18c	.21c	.24c	.28c	.35c	

TERMS:

The prices listed in our catalog are net. All trade and cash discounts have already been deducted.

All Prices are net, F.O.B. shipping point. PRICES, SPECIFICATIONS AND CONDITIONS OF SALE are SUBJECT TO CHANGE WITHOUT NOTICE.

Parcel post & UPS charges should be included with fully paid orders. We refund any not used.

Please do not send currency or stamps.

Prices and Specifications are Subject to Change Without Notice

EXPORT ORDERS

Minimum acceptable order \$10.00 in U.S. Currency. All prices are net F.O.B. our warehouse and subject to change without notice. Allow 20% over merchandise value for shipping costs. Overpayments are promptly refunded.


Parcel Post to APO and FPO Addresses are considered Domestic Mailings. Use Zone 1 & 2 Rates for New York, Zone 8 for San Francisco & Seattle.

C.O.D. orders are not acceptable out side continental Limits of the United States. Each order must be accompanied by payment in Cash or U.S. Dollar Draft Payable at a U.S. Bank. Foreign Currencies are not acceptable.

We Reserve the right to Route order by the best method where order does not indicate routing or when method suggested is impractical or not possible. Enclose import license and/or consular Declaration where so required by your Government.

Closed Circuit TV, INTERCOMS and PAGING Systems

Deluxe Solid State Closed Circuit Television Camera



199⁹⁵

No Money Down*

**For Sales Promotion
For Security
For Surveillance**

- Use With Any Home TV Set or Commercial Monitor
- Switchable Output Signals, Composite Video; up to 2.2v P-P at 75 ohms, RF Modulated: 50 mv
- Automatic Eye
- Provision For Intercom Permits Simultaneous Sound with RF Video Signal

High quality, moderately priced CCTV camera that has unlimited applications in industry, business, education, institutions, and the home. Easy to install all cables supplied are terminated with connecting plugs and leads. Simple to operate—can be used with either a commercial video monitor or any standard television set. Solid state circuitry—power consumed is very low. Provides cool and dependable operation. Lightweight, compact size permits inconspicuous mounting. Once focused, the camera needs no further attention. Automatic Eye (through the lens light control). Provisions for hooking up an intercom for intercommunication between CCTV camera and television receiver location. Specifications: Composite video output: 1.4V P-P to 2.2v P-P; RF modulated: more than 50

mv at 75 ohms; Scanning frequencies: Horizontal-15.750 kHz Vertical-50-60 Hz synchronized to power line. Horizontal resolution: more than 400 lines at center. Vertical resolution: more than 280 lines at center. Camera comes complete with 25 mm/f1.8 lens with adjustable Iris, C-mount, lens cap, vidicon cap, 32 ft. 75 ohm twin lead, 75:300 ohm line transformer and instruction manual. For 105-125 VAC, 50/60 Hz. Size: (less lens) 6¼"H x 3¼"W x 10½"D. 44 R 08019WX Imported. Shpg. wt., 9 lbs. Net 199.95 Heavy Duty Tripod for CCTV Camera. Shpg. wt., 3¼ lbs. 15 R 68021 Net 12.95

*Based on standard television test chart with 300 lux illumination at center.

LAFAYETTE 7735A VIDICON TUBE FOR CLOSED CIRCUIT TV CAMERAS

A small 1" diameter camera tube for televising live scenes in many industrial closed circuit TV systems. Its high sensitivity produces high quality pictures under normal room or industrial area lighting conditions. Has 600 to 900 line resolution. Size: 6¼"L x 1" dia. Imported. Shpg. wt., 5 oz.

99 R 36022L

Net 49.95

49⁹⁵



No Money Down*

Widely Used in Concord, Panasonic, Unimetric and Other CCTV Cameras

'PAGE ALL' 5 WATT PAGING/PHONE SYSTEM



- For Offices, Stores, Supermarkets, Warehouses, Restaurants: Where the Key Person You Want is On The Go!
- Localized Paging Eliminates 'Blasting' Over a PA System
- Wide Area Coverage—20 Station Capacity

Telephone Unit Only

27⁰⁰


Any one of the PT-7 phones in the 'Page-All' system can initiate a page call. This call is heard through a built-in speaker at every phone in the system. Called party picks up nearest phone and is immediately in direct contact with caller, automatically cutting off page. 'Page-All' is a common talking system, therefore, anyone can join in existing conversation by picking up any handset. No one can page through the system while a conversation is proceeding. Up to 20 stations may be installed in the system, in the event that it is required to extend the page call through large and noisy areas for which the sound from the phones is inadequate, a higher power PA amplifier may be added to the system. The paged call is then heard over the loudspeakers of the PA system in addition to the phone speakers. Suitable for desk or wall use. High impact styrene. Size: 9¼ x 3 x 3¼". For 117 VAC, 60 Hz. UL listed. Cable required: a 6-conductor cable regardless of the number of phones in the system.

MODEL PT-7, Paging Telephone Unit. Shpg. wt. 3 lbs. 44 R 30336 Each Net 27.00

MODEL APS-5, Amplifier and Power Supply. One req'd. Shpg. wt., 6 lbs. 44 R 30344 No Money Down* Net 58.50

SECURITY INTERCOMS AND VIEWERS

PROTECTO-COM SOLID STATE DOOR ANSWERING INTERCOM SYSTEM



Includes:

- 1 Master Amplifier Control Station
- 1 Door Station
- 1 16 Volt Transformer
- 50 ft. of 2 Conductor Cable
- All Hardware Necessary For Installation
- Provides Protection—Identify Callers Without Opening Doors

27⁹⁵ Complete System

A complete door answering intercom system designed for installation in new or existing homes. Easy-to-use "talk-listen" switch on master. Protects residents from unwanted callers. Inexpensive and easily installed. Comes complete with Master station, door station, transformer, 50 ft. of 2-conductor cable, and all hardware necessary for installation. Shpg. wt., 4 lbs.

44 R 37059

Net 27.95

32 R 30521 Extra 100 ft. coil of wire. Wt. ½ lb. Net 1.49

ONE WAY DOOR VIEWER

Permits thru-the-door identification without being observed. One way viewing only—you can look out, no one can see in. Provides wide-angle view—you can see anyone standing or crouching even at the side of the door. Installs quickly with a simple hand drill. Requires 1/2" in diameter. Length adjusts to fit any standard door thickness up to 1¾" thick. Cannot be removed from the outside. Rust-proof. Zinc die cast. Wt., 4 oz. 14 R 65020 Net .99



99^c


Electronic Burglar, Warning Systems

WORNER MODEL 4000 ELECTRONIC "WATCHMAN"



Economical indoor alarm system. Consists of exciter lamp unit and matching electronic relay, in attractive hammered cases. Exciter unit has 2 pre-focused 16 lenses for maximum light dispersion, infra-red filter to furnish invisible beam. Relay unit has toggle switch choice of momentary or continuous alarm operation, outside light rejector, sensitivity control. Built-in 6V. A.C. power supply permits use of external electrical alarms. Ranges: white light 50', invisible light 35'. Size each unit 5x5x5 1/2". For 110-120 V. 50-60 cycle AC. Total shpg. wt., 12 1/4 lbs.
12 R 88042 No Money Down* Net 101.88

WORNER ELECTRONIC RECEPTIONIST




61⁸⁶

With Chime

No Money Down*

MODEL 61 ANNOUNCER. Consists of "Photo-electric" unit, chime and mirror. Chime rings when light beam is intercepted. Unit has exciter lamp which projects beam across passage, and photocell which receives reflected beam from mirror; may be placed up to 10' from mirror. 8 1/2 x 6 1/2 x 2 3/4". For 110-120 V. 50-60 cycle A.C. Shpg. wt., 8 3/4 lbs.
12 R 88018 Net 61.86

WORNER MODEL 5150 ELECTRONIC BURGLAR ALARM




Indoor detection system. Infra-red beam operates amplifier up to 150 ft. Removable red filter. Both units have on-off switch. Amplifier relay unit features sensitivity control, extraneous light shielding and lock. Only keyholder can turn off alarm or reset trap. Steel cases. Light source 4 1/2 x 4 1/4 x 7"; amplifier 5 1/2 x 7 5/4" with split door, hinged bottom. For 110/120V 50-60 Hz. Shpg. wt., 13 lbs.
12 R 88059W No Money Down* Net 168.90

WORNER ACCESSORIES

60-1130 REPLACEMENT BULB 6 V., 32 CP., 2000 hours. For models 61, 4000, and 5150
12 R 88026 Shpg. wt., 3 oz. Net .95
EXTRA CHIME for Models 61 and 4000 and any other 6 VAC power source. Serves as an excellent warning device.
12 R 88034 Shpg. wt., 1 1/2 lbs. Net 7.41

LAFAYETTE PHOTO ELECTRONIC RELAY SYSTEM

Includes Photo Cell Receiver Plus Electronically Operated Relay Plus Exciter Lamp — — — Efficient 2-Unit, 3-Element Design



- Complete—Ready to Operate—NOT A KIT!
- Operates Bells, Buzzers and Counters
- The Perfect "Guard" for Homes, Stores and Industry
- Removable Infra-Red Filter For "Invisible-Light" Operation

19⁹⁵
A SET


The Lafayette Photo-Electronic Relay is your key to an inexpensive indoor warning or counting system. Consisting of a rugged exciter and relay unit and operating on 110-120V AC, it can be connected to signal persons entering a room, counting people or merchandise or function as an effective alarm system to warn of intruders. Effective up to 48 feet (without filter, 18 to 20 feet with filter, relay unit has a convenient variable sensitivity control and switch for intermittent alarm operation. Exciter has removable infrared filter. Mounts easily across area to be supervised. Metal case. Size: 4 1/4 x 3 W x 4 1/2" D. Imported.

99 R 90821 Shpg. wt., 4 1/2 lbs. Net 19.95
99 R 90276 6 Volt 20 Watt Replacement Bulb Net .49 ea.

ACCESSORIES FOR ABOVE

99 R 90235 Electric Bell, 110V AC. Shpg. wt., 12 oz. Net 2.95
99 R 90110 6-Digit Electric Counter. Shpg. wt., 1 lb. Net 12.95

TAPESWITCH MATS—STRIPS



(Fig. A) Tapeswitch Flexible Switch Mats. Less than 5 lbs. pressure activates these mats. Although rated and tested at 1 amp, 117VAC for floor switching, 24-volts or less is recommended. Only 3/8" thick; water-resistant durable covering. Shpg. wt.: 17 x 23" mat, 1 1/2 lb.; 6 x 23" mat, 1 1/4 lbs.
17 x 23" Mat with 6' Cord.

33 R 86010 Net ea. 14.95
6 x 23" Stair Tread Mat with 18" Lead.

33 R 86028 Net ea. 6.12

(Fig. B) Tapeswitch Ribbon Switches. These "Press at any point!" switches can be activated with only 12 oz. of finger pressure. Normally open, momentary contact type with 4' leads. Moisture-proof chrome yellow vinyl cover. Only 3/8" thick. Rated 1 amp., 117 VAC or 28 VDC. Shpg. wt.: 2' length, 7 oz.; 5' length, 7 oz.

33 R 86036 2' length Net ea. 4.48

33 R 86044 5' length Net ea. 8.18

(Fig. C) Cut To Length Switching Runner.

5-ft. long x 30" wide x 3/8" thick and can be cut to any length, 5 lbs. nominal foot pressure. Solder or twist connections easily made. Excellent extended area signaling for concealed indoor alarms and controls. Switching elements on 2 1/2" centers are wired in parallel and encased in a polyethylene envelope. For indoor use only. Install under rug, rubber runner, mat or tile. Wt., 2 1/2 lbs.

33 R 86077 Net 16.75

CHIME ANNUNCIATOR KIT



26⁹⁵

- Announces Visitors
Guards Against Theft

Signals entrance into office, store or shop by ringing chime. Includes concealable mat 18x24x3/8" thick, 2-note chime, transformer, wire and instructions. Shpg. wt., 4 lbs.
33 R 66051 Net 26.95

SECURITY TRAVEL LOCK

2⁹⁵



For salesmen, and travelers whenever a portable lock is needed. Fits doors, cabinets without permanent installation or tools. Stainless bar and chrome finish.
14 R 44512 Shpg. wt., 3/4 lb. Net 2.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Ultrasonic Intrusion Alarms

DELUXE ULTRASONIC INTRUSION ALARMS



Protects Your Home or Business Against Thieves, Prowlers, Vandals

99⁹⁵

- Easy Plug-In Installation
- 12 Volt Standby Battery Input
- Ultrasonic Beam Covers an Entire Room
- Turns on Lamps, Rings Bell-Siren

Protects with invisible, inaudible ultrasonic waves that create an elliptical zone up to 30 ft. in front of unit, depending on shape and contents of area. No special wiring... easily concealed and sets up in minutes. Automatically arms itself 15-25 sec. after it's turned on to permit you to leave without actuating the alarm. Operational mode includes immediate lights on and bell/siren after 10-20 seconds. This feature permits you to re-enter protected area. Lights and bell/siren remain on for 50-75 sec. and then the unit automatically resets for full time protection. Control circuit has provisions for use of 12 volt emergency battery in case of power failure. Controls: range/sensitivity, off/on switch. Operates on 117 VAC, 60 Hz. Size: 10 1/2 x 4 1/4 x 1". See accessory rings below. Shpg. wt., 3 3/4 lbs.

12 R 87069 No Money Down* Net 99.95
 12 R 87044 3 1/2" Bell for above. Shpg. wt., 1 lb. Net 5.95
 12 R 87051 Deluxe 6" Bell for above. Wt., 3 3/4 lbs. Net 22.95



ULTRASONIC INTRUSION ALARM
 Protects Your Home or Business Against Intruders and Burglars

64⁹⁵

- Easy, Plug-In Installation
- Turns On Lamps, Rings Bell-Siren

Will protect doorways, rooms, or any area that an intruder may enter. Ultrasonic beam covers an area up to 15-30 ft. in front of unit depending on shape of room and contents. When area is entered, lights, bell-siren or both are turned on to give a visual and audible alarm. Can be set as a convenience monitor to turn light on when you enter a room; shuts off 3 min. after you leave. Sensitivity/range and position easily set to allow pets to enter. Variable timer allows alarm to remain on from 8 sec. to 3 min.; automatically resets itself for continuous protection. No special wiring necessary; lights or bell-siren plug directly into unit. Handles up to 575 watts; 117VAC at 5 amps. Alarm system turns on 10 sec. after you activate system to allow you to leave area. Controls: on/off switch, sensitivity and range. Size: 10 3/4 x 3 1/4 x 3 1/4". Attractive walnut finish. Requires 110-130 VAC, 60 Hz. Shpg. wt., 3 lbs. See optional unit below which provides a built-in horn and a 20 sec. delay of bell-siren for extra time to enter protected area. See accessory siren below.

12 R 56510 No Money Down* Net 64.95
 12 R 87044 3 1/2" Bell for above. Shpg. wt., 1 lb. Net 5.95
 12 R 87051 Deluxe 6" Bell for above. Wt., 3 3/4 lbs. Net 22.95

ON-GUARD PROFESSIONAL DOOR BURGLAR ALARM

For: Apartment—Store—Home—Office



34⁹⁵

No Money Down*

- Fits All Doors
- No Lock Hole in Door
- No Wiring Necessary

Fully transistorized, battery operated burglar alarm for the home, apartment, store, and office. Universal mounting fits any door. Push-button control is provided for manual alarm to signal for aid at any time, another control has been included to permit you to open the door from the inside without setting off the alarm. Upon closing the door alarm is automatically reset. Slide switch control can be set for instant, or, 20 second delay before alarm sounds. Key operated switch controls on/off and reset functions. Mounts instantly, no wiring required. Constructed of heavy gauge, anodized aluminum with neutral sand colored finish. Comes complete with battery and mounting hardware. Size: 4 1/2 x 8 x 3". Shpg. wt., 4 1/4 lbs.

14 R 13509 Net 34.95



DELTA HORN

- Combination Horn/Delay

Plugs directly into above intrusion alarm. Provides delay of 20 sec. before built-in horn or external bell are activated to allow entering protected area and turning off alarm. Internal horn operates intermittently (10 sec. "on", 5 sec. "off"); external bell operates as long as above alarm is on. With built-in AC outlet, line cord and plug. Handles up to 575 watts; 115 VAC at 5 amps. Size: 3 1/4 x 3 1/4 x 3 3/4".

12 R 56528 Shpg. wt., 1 1/4 lbs. Net 24.95

110-VOLT POLICE TYPE SIREN



16⁹⁵

Provides a sharp penetrating sound which can be heard at a great distance. All rotating parts are precision balanced, extremely durable and may be used outdoors when housed in Siren cabinet below. Siren features: spun aluminum trumpet with heavy-duty motor and mounting bracket. Ideal for ultrasonic alarm systems above and for use with alarm systems in homes, stores and factories. For 110 V. 50/60 cycles, 1 amp. Size: 5 1/4" x 8". Shpg. wt., 5 lbs.

14 R 13574 Net 16.95

SIREN CABINET FOR MOUNTING SIREN OUTDOORS

Size: 6x8x10 1/2". Shpg. wt., 3 lbs.
 14 R 13582 Net 4.95



3⁹⁵

- Requires No Wiring

BURGLAR LOCKALARM

Automatically locks when unauthorized forced entry is attempted, plus emits a piercing sound capable of awaking the entire household. Inconspicuously mounts on doors, and windows in minutes with only a screw-driver. Uses a single penlite AA 1 1/2 volt battery. Complete with mounting hardware, horn, and latch mechanism. Shpg. wt., 1 lb.

14 R 63504 Net 3.95
 99 R 62580 Battery for above Net 1.10




MALLORY SONALERT ELECTRONIC AUDIBLE SIGNAL DEVICE

Solid-state circuitry, no mechanical wear—no arching—no RF noise. Small size, lightweight, and low current drain allow them to be used in most circuits where warning devices are needed. Type SC628P has pulsating tone. Extensively used in fault alarms in computers, fire signals, instruments, appliances, and communications as well as telephone signals and protection equipment. Application possibilities are limitless. Size: all 1 1/4" dia. x .781" long except, † are 1.38" long. Installed weight: all 1 1/4 oz. except † are 2 oz. All Models manufactured with silicon transistors, allowing operating temperatures of -40° to +185° F. Shpg. wt., 5 oz.

Stock No.	Type No.	Operating Voltage	Freq. Hz.	Intensity DB	Current MA.	Net 1-24	Each 25-49
12 R 74018	SC628	6-28DC DC	2800	68-80	3-14	5.50	5.40
12 R 74026	SC628H	6-28DC	4500	68-80	3-14	6.35	6.25
12 R 74034††	SC628P	6-28DC	2800	68-80	3-14	9.95	9.75
12 R 74042††	SC628A	6-28AC/DC	2800	68-80	3-14	8.75	8.60
12 R 74067††	SC110	110 AC	2800	80	14	8.75	8.60

PREVENT TOMORROW'S LOSS BY PROTECTING TODAY

EMERSON-RITTENHOUSE PROFESSIONAL INTRUSION SECURITY SYSTEM



49⁹⁵ No Money Down*

• Automatic Intruder Protection

Provides reliable automatic operation that's always alert... detects an intruder and sounds the alarm at the trip of the sensitive detectors. Unit surprises intruder with an alarm that can't be silenced by closing window or door, Alarm sounds off until manually reset at the control panel. Features tamperproof detection with "lock-in" automatic alarm, manual alarm switches for push-button signaling, and gold anodized control panel with activation light, off-on control, and alarm reset switch. Panel measures only 4 3/4" x 4 3/4" and mounts in a standard 2-gang electrical box. Control panel may be concealed in closet, etc. Package includes security control panel, indoor alarm horn, three flush magnetic door/window switches, two manual alarm pushbuttons, and power transformer. See Accessories Below.

13 R 83504 Shpg. wt., 4 1/4 lbs. Net 49.95

ACCESSORIES FOR ABOVE SECURITY SYSTEM

OUTSIDE KEY-LOCK CONTROL. Permits protection while owner is away from home. Indicator light illuminates to confirm system is activated. Mounts on standard single-gang box. Tamperproof... alarm sounds if intruder removes panel. Stainless steel finish. Dimensions: 4 1/2" x 2 3/4" W.

13 R 83546 Shpg. wt., 3/4 lb. Net 24.95

5-Conductor Cable for above control, 40 Ft.

13 R 83611 Shpg. wt., 12 oz. Net 3.39

OUTSIDE BEACON ALARM HORN. Provides warning light and alarm horn in one integral unit. Designed for installation outside of home. Tapered red cylindrical lens. Back plate dimensions: 4 1/2" x 6 3/4". Mounts on single-gang 3/4" or 4" outlet box. Extends from wall 4 3/4". Brushed aluminum.

13 R 83579 Shpg. wt., 3 lbs. Net 21.95

WIRE FOR ABOVE ALARM SYSTEM


18 Gauge Single Conductor Wire For Window and Door Switches.

13 R 83512 200 Ft. Roll. Shpg. wt., 2 1/2 lbs. Net 4.25

18 Gauge 2-Conductor Wire For Indoor Alarm Horn, Beacon Alarm Horn, and Alarm Push Button. Shpg. wt., 3 lbs.

32 R 36288 100 Ft. Coil. Net 2.90

SECURITY SWITCHES FOR CLOSED CIRCUIT ALARM SYSTEMS



A DOOR/WINDOW SECURITY SWITCH. For flush mounting in door and double hung wooden window frames. Need not be mortised, fits 3/4" hole.

14 R 13525 Shpg. wt., 4 oz. Net 1.50

B MAGNETIC DOOR/WINDOW SECURITY SWITCH. For use where surface mounting is necessary.

14 R 13533 Shpg. wt., 4 oz. Net 1.99

C GENERAL PURPOSE WINDOW SECURITY SWITCH. Surface mount fits all windows. Ideal for sliding windows and screens.

14 R 13541 Shpg. wt., 4 oz. Net 1.50

GULTON FIRE ALARM

- Always Fully Charged

12⁹⁵



Built-in 117 VAC charging circuit keeps internal batteries up to full power. Never needs replacement batteries. Works even in the event of a power failure. Loud continuous alarm sounds when room temperature reaches danger level (126°-140°). Convenient test button allows periodic checking of unit.

14 R 14507 Shpg. wt., 3/4 lb. Net 12.95

*See Page 22 for Full Credit Details on Easy Pay Plan

On-Guard PROFESSIONAL SELF-CONTAINED SOLID-STATE BURGLAR ALARM SYSTEM

49⁹⁵



4 Sets of Magnetic Switches



Exit / Entry Switch



With 8" Bell

- Heavy-Duty Tamper-Proof Steel WeatherProof Box.
- For Homes, Offices, Plants, ect.

Guards windows, doors or other entry points by sounding an extra loud 8" bell, upon intrusion. Self contained battery, bell, and master circuit are housed in a durable weatherproof grey hammertone box that has a built-in tampering protection circuit. Clipping wires or opening the outer box, as well as entering the protected windows or doors will sound the alarm. Sound continues until you turn it off by way of a dust proof key lock switch. Includes four sets of magnetic switches. Features key switch to permit exit and re-entry without sounding alarm. Panic button, which also operates as a test button, may be used to manually indicate an emergency. Operates on a standard 12-volt lantern battery, not supplied. Includes instructions, decal, 2 keys, and 100 feet of wire. Shpg. wt., 18 lbs.

14 R 13558W No Money Down* Net 49.95

100-Feet of Additional Wire. Shpg. wt., 3 lbs. Net 2.90

14 R 13566 Net 2.90

12-volt Battery For Above (1 Req.) Wt., 3/4 lb. Net 2.30

32 R 47772 Net 2.30

NuTone SOLID-STATE INTRUSION ALARM SYSTEM

only **34⁹⁵**

- Automatic Time Delay Switch Lets You Exit Or Re-Enter Without Setting Off Alarm
- Key-Controlled And Tamper Proof
- Battery Test Indicator Light

Electronic Early Warning System against intruders. Use in your home, office, or on business premises. Powerful horn blast, installs easily, no special tools required, the system is key controlled; once triggered it cannot be silenced by pulling off switches or cutting wires. Uses inconspicuous switches on doors and windows; Up to fifty additional switches can be attached to the master unit. Complete with one magnetic contact switch set of keys, 30 ft. of wire and instructions. Requires 3 "dp" batteries. Size: 12" x 3 3/8" x 1 1/2". See additional switches on this page.

14 R 29505 Shpg. wt., 3 lbs. Net 34.95

60 Ft. Additional Wire. Shpg. wt., 10 lb. Net 1.95

14 R 29521 Net 1.95

Batteries For Above (3 Req.) Wt., ea. 5 oz. Net 2.5

99 R 63661 Net 2.5

FIRE ALARM

- No Batteries—No AC Plug

5⁹⁵




Powered by its own self-contained hermetically sealed electronic energizer. Loud piercing siren sounds off for 2 hours or more. No maintenance—require replacement only after activated by fire. Special sensor tip will trigger alarm when temperature reaches 135° F. Easily installed on walls, doors, or ceilings. Ivory finish.

14 R 17500 Shpg. wt., 1/2 lb. Net 5.95

- Tiny and Powerful: Only 2" x 2 1/4"

The World At Your Finger Tips!



BRING HISTORY MAKING NEWS INTO YOUR HOME... FROM THE FAMOUS CAPITALS OF THE WORLD!

LAFAYETTE Explor-Air Mark V Shortwave + AM Broadcast Receiver

Only
54⁹⁵
No Money Down*

5 BANDS

Broadcast + 4 Exciting International Shortwave Bands

- 550 to 1600 kHz • 9.45 to 9.8 MHz
- 5.9 to 6.25 MHz • 11.45 to 12 MHz
- 15.05 to 15.5 MHz



SUPERHETERODYNE— Not Super-Regenerative!

NOT A KIT— COMPLETELY WIRED

Listen to world-wide exciting current events right in your own home... hear the actual broadcasts from the major news centers around the world in English and foreign languages; BBC London, Radio Moscow and many others. The Explor-Air Mark V receiver is refined in its ability to bring in stations loud and clear and features simplicity of operation. In addition to the standard AM broadcast frequencies, the receiver is designed to tune the popular international shortwave broadcast bands on 49, 31, 25 and 19 meters (each band occupies a select portion of the full shortwave spectrum) through the use of individual tuned circuits for each of the five bands. For greater ease of tuning on congested bands each shortwave band has been extended to cover the entire width of the 0 to 100 logging scale.

Operating features on the receiver include a self-contained 4" dynamic speaker, built-in loopstick antenna, large illuminated slide-rule dial calibrated in frequency and indicating place names, a front panel headphone jack for optional silent listening, controls for Volume Off/On, Tone and Band Selection, plus rear panel connection for external shortwave antenna. **SPECIFICATIONS:** Full coverage on 5-bands; AM Broadcast (0.55 to 1.6 MHz), and International Shortwave on 49 Meter (5.9 to 6.25MHz), 31 Meter (9.45 to 9.8MHz), 25 Meter (11.45 to 12 MHz), and on 19 Meter (15.05 to 15.5MHz). Receiver is AC transformer powered with efficient superheterodyne circuitry. Complete with beautiful walnut grained metal cabinet. For 105-125V., 50/60 Hz AC. Size: 14Wx8Dx6"H. Imported. Shpg. wt., 13½ lbs. 99 R 25850W 54.95

ECONOMY SHORT-WAVE PACKAGES WITH EXPLOR-AIR MARK V



Outdoor & Attic Antenna

Explor-Air Mark V plus Shortwave Window Antenna **61⁹⁵** **SAVE 2.95** From individual catalog prices. 40 R 90148WXM Shpg. wt., 16½ lbs. No Money Down* Net 61.95

Window Antenna

Explor-Air Mark V plus Shortwave Outdoor and Attic Antenna **58⁹⁵** **SAVE 2.95** From individual catalog prices. 40 R 90122WXM Shpg. wt., 15½ lbs. No Money Down* Net 58.95

HY-GAIN SW-9 SHORTWAVE WINDOW ANTENNA



Includes Universal Window Mounting Bracket


The ideal shortwave antenna for window installations, where roof-top antennas are impractical or cannot be used. Provides broadband performance comparable with other larger installations. Consists of one 9 foot aluminum tubular element with a universal mounting bracket and feedline. Simple to install. Answers the problems of apartment dwelling SWL's. Shpg. wt., 3 lbs. 40 R 31183W Net 9.95

HY-GAIN SW-6 SHORTWAVE ANTENNA



A completely assembled antenna, ready to install. Scientifically tuned for 1.8 to 30 MHz coverage. Can be installed on any existing structure: pole-to-pole, pole-to-tree, garage-to-house, under the eaves, in the attic... all provide excellent reception. Consists of 50 ft. copper wire attached at both ends to low-loss styrene insulators. 15' weather-proof-rope on each insulator, plus lead-in feedline. Shpg. wt., 2 lbs. 40 R 31175 Net 6.95

SHORTWAVE-AMATEUR-AM-BROADCAST- WEATHER AND MARINE BANDS



HA-600A

PRODUCT DETECTOR FOR SSB/CW

5 Band AM/CW/SSB Solid-State Amateur And SW Receiver

- 10 Transistors, 2 FET's, 7 Diodes, and 1 Zener Diode
- Mechanical Filter for Exceptional Selectivity
- Huge Edge-Illuminated Slide Rule Dial with "S" Meter
- 117-Volts AC and 12-Volts DC Negative Ground Operation
- Full 24½ Inches of Bandspeed On 10-80 Meter Bands
- Automatic Series Gate Noise Limiter With AVC on AM

5 BANDS INCLUDE

- BAND A: 150 kHz to 400 kHz
- BAND B: 550 kHz to 1600 kHz
- BAND C: 1.6 MHz to 4.8 MHz
- BAND D: 4.8 MHz to 14.6 MHz
- BAND E: 10.5 MHz to 30 MHz

Only

99⁹⁵

No Money Down*

The HA-600A general coverage receiver combines the latest solid state electronics with sleek, modern appearance to achieve a superb blend of performance and style. Advanced circuitry utilizes two Field Effect Transistors in the front end RF stages to assure high sensitivity with lowest noise factor. 10 high performance transistors and 8 diodes compliment the FET's to provide sharp response with exceptional stability. Series-Gate noise limiter and automatic volume control circuitry provide efficient noise and audio blasting suppression on AM. Built-in variable BFO permits clear reception of code and single sideband signals. 455 kHz mechanical filter assures superior selectivity. Receiver's operation is virtually undis-

turbed by harmonics or noise from antenna to speaker. Rear panel accessory socket provides convenient connection for audio output, 12 VDC, ground and AVC line, along with receiver muting connections. Huge fly-wheel operated slide rule dial has easy-to-read illuminated main tuning, logging, and bandspeed scales. Electrical bandspeed features wide calibration for easier tuning of crowded ham bands. Operates from 117 VAC 60 Hz or 12 VDC (negative ground only) . . . perfect for emergency use! Imported. Shpg. wt., 25¾ lbs.

99 R 25991W Net 99.95
Matching 3 x 5-Inch speaker in handsome cabinet.
99 R 25397 HE-48C Net 8.95

SPECIFICATIONS

Sensitivity: 1µv at 10 db signal to noise ratio. Selectivity: ± 6 KHz at 60 db down, ± 2 KHz at 6 db down. Intermediate Frequency: 455 kHz. BFO Frequency: 455 kHz ± 2.5 kHz. Antenna Impedance: 50—400 ohms. Audio Power Output: 3-watts at 4 ohms. Speaker Impedance: 4, 8, and 500 ohms. Headphone Impedance: 8 ohms. Receiving Modes: AM-CW-SSB. Power Requirements: 105-120 Volts 60 Hz (17 watts max.) 12 Volts DC (650 ma. max.). Size: 15W x 9¼D x 8¼"H.

Model HE-48C MATCHING AMATEUR SPEAKER

- Excellent Speaker for Lafayette or Other Receivers Which Require External Speaker
- Large 3 x 5 Inch Permanent Magnet Speaker

A quality 3x5-inch permanent magnet speaker designed into a handsomely styled cabinet with attractive finish. Provides clean, crisp, and clear audio response—even during single sideband reception. Made to mate with Lafayette HA-600A and HA-800B or other manufacturer's receivers which need external speaker provisions. Voice coil impedance: 8 ohms. Size: 7¼"Hx3½"Wx5"D. Shpg. wt., 2½ lbs. Imported.

99 R 25397

Net 8.95

*See Page 22 for Full Credit Details on Easy Pay Plan

ONLY
8⁹⁵

HE-48C



Lafayette Cat. No. 720 423



6-80 Meter SSB/AM/CW Solid-State Amateur Receiver



Featuring Built-in 12 Volt DC and 117 Volt AC Supplies

- ★ 6 Amateur Bands Including 6 Meters
- ★ Product Detector for SSB/CW
- ★ Built-in 100 kHz Crystal Calibrator
- ★ FET Front End Attenuates Overloads
- ★ Instantaneous Cool Performance

MODEL HA-800B,

NEW! ONLY **129⁹⁵**

- Varactor Tuning for BFO and Calibrator
- Two 455 kHz Mechanical Filters
- Zener Regulated Power Supply

The Lafayette Model HA-800B solid-state amateur receiver covers the 80 through 6 meter bands with superior reception of CW, AM, and SSB signals. Tuned RF, mixer, and oscillator stages feature FET's for outstanding front-end selectivity and sensitivity with automatic RF overload protection. Product detection plus varactor tuned BFO assure crisp CW and clear sideband copy. Built-in 100 kHz crystal calibrator ensures accurate pre-selection of proper frequencies (supplied less crystal). Rear panel accessory socket provides convenient access to audio output, receiver muting line, and 12-volt DC input. Tape output jack permits direct taping and front panel headphone jack facilities

15 TRANSISTORS + 13 DIODES
+ 4 FET's + 1 VARACTOR

- Series Gate Automatic Noise Limiting
- Dual Conversion on all Bands
- Illuminated Calibrated "S" Meter

operation in noisy areas. Sensitivity: better than 1 μ v. on 10-80 meters, 2.5 μ v. on 6 meters. Selectivity: 60 db down at \pm 6 kHz. Power requirements: 117 volts AC 50/60 Hz, or 12 volts DC. Size: 8 $\frac{1}{4}$ "H x 15W x 9 $\frac{3}{4}$ "D. Imported. Shpg. wt., 18 lbs.

99 R 26155WX No Money Down*	Net 129.95
Model HE-48C Matching 8 Ohm Speaker	
99 R 25397 Shpg. wt., 4 lbs.	Net 8.95
100 kHz. Calibrator Crystal for HA-800B	
40 R 09015L Shpg. wt., 3 oz.	Net 4.95

NEW! 100 WATT MOBILE LINEAR AMPLIFIER MODEL HA-250A


SMALL...COMPACT...ONLY 2 INCHES HIGH



Only **89⁹⁵**
No Money Down*

Boost flea power to high power for extended range and better readability. Provides up to 100 watts PEP (50 Watts DC) input into a 50 ohm load (with 10 watts RF drive). Unique RF sensing circuit automatically switches in linear when transmitter is activated. Absolutely no external switching is necessary. Built-in relay directly connects antenna to input SO-239 coaxial socket when receiving. No internal connections are required to your existing equipment. Simply insert the unit in series with your transmitter (or transceiver) and antenna and you're on the air with a real punch. Circuitry is broadbanded so only one tune-up is usually necessary on any band. Illuminated front panel meter indicates relative RF strength of linear's output signal when linear is on, or exciter's relative RF signal strength when linear is off. Self-contained power supply utilizes a high efficiency toroid power transformer. Rugged, attractively designed chassis with oversized heat sinks sturdy and cool operation. Supplied with comprehen-

- Covers 20-54 MHz . . . 6, 10, 11 and 15 Meters (Not permitted on 11 meters Class D CB in U.S.A.)
- Operates on 117 Volts AC with Optional Supply
- No External Switching Required
- Amplifies AM, FM, CW, DSB or SSB Signals From 1/2 to 10 Watts
- Self-Contained 12 Volt Power Supply



Model HA-255

sive manual, fused DC power cables and mounting bracket. Size: 7"D x 9"Wx2"H. Made in U.S.A. Shpg. wt., 7 lbs. 12 oz. 12 Volt DC Negative Ground Only.

99 R 25280W Net 89.95
SPECIFICATIONS: Frequency Coverage: 20-54 MHz. Plate Power Input: 50 Watts (100 Watts PEP). Minimum RF Drive: 1/2 Watt. Maximum RF Drive: 10 Watts. Input Impedance: 50 Ohms. Output Impedance: 40-600 Ohms (50 Ohms Nominal). Amplification Modes: AM, FM, SSB, DSB, CW. Power Requirement: 12 Volts DC (Neg. Ground only). DC Power 27-watts idling. 120-watts at full input.

Model HA-255 AC Power Supply For 117 volt AC 50/60 Hz. operation of HA-250A Linear Amplifier. Power connector mates directly with chassis socket of HA-250A. Size: 9W x 7D x 5"H Imported. 99 R 25298W No Money Down* Shpg. wt., 11 lbs. Net 32.95

High Performance Amateur and SW Gear

Deluxe Drake Model R-4B Triple Conversion Receiver



475⁰⁰

- Solid State Linear Permeability Tuned VFO
- Noise Blanker on CW, SSB, AM
- Crystal Lattice Filter

Triple conversion with exceptional features. Covers 80, 40, 20, and 15 meters completely and 28.5-29 MHz. Segment of 10 meters with crystals furnished. Ten accessory crystal sockets for any ten additional 500 kHz ranges from 1.5-30 kHz with the exception of 5.0-6.0 MHz. Selectivity control with 4 bandwidths: .4 kHz., 1.2 kHz., 2.4 kHz., and 4.8 kHz. Pass band tuning permits SB selection without returning and adjustment. Noise blanker, notch filter, 100kHz crystal calibrator. Crystal lattice filter 1st IF. Crystal oscillator and low frequency VFO outputs are pre-mixed. Receives SSB, AM, CW and RTTY with full RF gain. Product detector for SSB/CW—diode detector for AM. Transceive capability: transceives with T-4XB or T-4X transmitters, 5-meter. Less speaker. 60 watts. 120/240VAC. 50/60 Hz. 5½H x 10¾W x 11¾"D. Shpg. wt., 19 lbs.

40 R 65306W No Money Down* Net 475.00
Model MS-4 Matching Speaker for R-4B. Wt., 9½ lbs. Net 22.00
40 R 65041W

DRAKE 2C SSB/AM/CW RECEIVER



255⁰⁰

- Solid State AVC
- Product Detector For SSB/CW
- 3 Bandwidths of Selectivity

Covers the 80, 40, 20 and 15 meter ham bands plus 28.5 to 29.0 MHz of 10 meters with crystal furnished. Also tunes any 500 kHz range between 3.0 and 30 MHz with accessory crystal. Features include: USB/LSB, CW, AM, RTTY with full RF gain; solid state AVC with fast attack and slow release for SSB, or, fast release for high break-in CW; solid state audio with 1.8 watts output; selectivity control provides bandwidth choice of .4, 2.4, and 4.8 kHz. Set has 50 kHz selectable-passband filter and accurate S-meter. Rear panel jacks for antenna, loud-speaker, external muting and sidetone. Size: 11¾Wx6¾Hx9¾"D. Shpg. wt., 16 lbs.
40 R 65280W No Money Down* Net 255.00
Model 2-CS Matching Speaker for 2-C. Shpg. wt., 8¾ lbs. Net 22.00

DRAKE SW4A SW RECEIVER



No Money Down* 299⁰⁰

- Dual Conversion
- Crystal Lattice Filter
- Direct Frequency Dialing

Superb reception of European LF, American MF, and International SW broadcast bands. Frequency Coverage: 15-5, 5-1.0, 1.0-1.5, 6.0-6.5, 7.0-7.5, 9.5-10.0, 11.5-12.0, 15.0-15.5, 17.5-18, 21.5-22 and 25.5-26.0 MHz with crystals supplied. Crystal sockets are provided for coverage of any three additional 500 kHz ranges between 1.5 and 30 MHz except 5.0-6.9 MHz. Has S meter for signal strength indication. Preselector provides superb sensitivity. Crystal high frequency oscillator, Amplified AVC. Solid-state AF output. Impedance: 4-ohms. For 120/140VAC., 50/60 Hz. Size: 5½H x 10¾ W x 11¾"D. Shpg. wt., 20 lbs. Net 299.00
40 R 65330W Net 299.00
MS-4 Matching Speaker. Shpg. wt., 9½ lbs. Net 22.00
40 R 65041W

DRAKE 2-NT CW TRANSMITTER



164⁰⁰

- 100 Watts Input Power
- Built-in Power Supply

Covers all amateur bands 80 thru 10 meters crystal controlled. Features automatic transmit switching and antenna change over relay. Simplified tuning is provided by broadband, low level stages and fixed loading; PA Plate tuning only! Additional features include: Automatic receiver muting; built-in CW sidetone with adjustable level; low pass filter prevents TVI; spotting function; RF indicator light and built-in power supply, in standby position transmitter can be used as a code practice oscillator. Plate meter is red-lined for Nevice power. Delay control varies from full "break-in" to 4 seconds. Also has 2-front panel crystal sockets; rear panel mute, external switch, VFO and key jacks. For 120V., 50-60 Hz AC. Size: 9¾W x 6¾H x 6¾"D. Shpg. wt., 15½ lbs. Net 164.00
40 R 65272W


HAMMARLUND HQ-200 GENERAL COVERAGE RECEIVER



No Money Down* 338⁰⁰

Continuously tunable from 540 kHz to 30 MHz with five bands. Electrical bandspread calibrated for all amateur bands from 80 thru 10 meters. Eight tubes plus 5 diodes. Zener regulated and temperature compensated high frequency oscillator. Selectivity continuously variable from 12 kHz (AM) to 2.9 kHz (SSB) and 100 Hz (CW). Q multiplier operates independently of BFO. BFO variable ±2 kHz. Other features include antenna trimmer, AVC, series noise limiter, product detector, and "S" meter. Sensitivity: better than 0.5 µV. for CW and SSB. Audio output: 2.5 watts (EIA). Power requirements: 117/230 volts AC 50/60 Hz. Size: 16¾Wx8Hx9¾"D. Shpg. wt., 27 lbs. Net 338.00
40 R 28924W Net 338.00
Model S-101 Speaker for HQ-200. Net 19.95
40 R 28932W

HALLICRAFTERS SX-133 GENERAL COVERAGE RECEIVER



No Money Down* 275⁰⁰

Deluxe four band superhet receiver tunes 535 kHz to 31.5 MHz. Covers foreign and domestic short-wave broadcasts, amateurs, aircraft and marine plus standard AM. Receives code (CW), voice (AM), and single sideband (SSB), selectable upper or lower. Calibrated electrical bandspread on the 80, 40, 20, 15, 10 meter amateur bands, citizens band and the 49, 31, 25, and 19 meter shortwave bands. Fine features include selective crystal filter, calibrated BFO, product detector, antenna trimmer, "S" meter, effective noise limiter, and crystal calibrator. For 117 VAC 50/60 Hz. Size: 18¾Wx8Hx9¾"D. Shpg. wt., 31¾ lbs. Net 275.00
40 R 25656W Net 275.00
Speaker for SX-133. Shpg. wt., 2½ lbs. Net 8.95
99 R 25397 HE-48C

DRAKE T-4XB SSB/CW/AM TRANSMITTER




495⁰⁰

- 200 Watts PEP Input
- 6 Bands SSB, CW, AM and RTTY
- 2 Crystal Lattice Filters

Improved version of Model T-4X. Covers 160-10 Meters. Permeability tuned solid-state VFO has a calibration accuracy of better than 1 kHz. Rated at 200 watts PEP on SSB, 180 watts PEP on AM, and 180 watts CW. AM controlled carrier modulation is compatible with SSB linear amplifiers. Two crystal lattice filters for sideband selection. Plate/current relative output meter. Automatic transmit-receive switching on CW delivers true break-in to 60 wpm. VOX or PTT on SSB and AM. AGC operates on SSB to prevent flat topping due to overdrive. Size: 5½H x 11¾ D x 10¾"W. Less power supply. Shpg. 18 lbs. 40 R 65322W Net 495.00
AC-4 117VAC Power Supply for T-4XB Shpg. wt., 19½ lbs. Net 99.95
40 R 65249W

* See Page 22 for Full Credit Details on Easy Pay Plan

REGENCY HR-2 MOBILE 2 METER FM TRANSCEIVER



229⁰⁰

Supplied with crystals for 146.94 MHz, mike, and mounting bracket

- Power Output: 10 Watts or Better
- Automatic Adjustable Deviation Limiting

Double conversion receiver with 0.35 μ v sensitivity for 20 db quieting. Sharp selectivity of 6 db for 16 kHz and 50 db for 32 kHz assures single channel copy. Squelch circuit utilizes variable electronic noise compensation. Built-in 4" speaker. Transmitter utilizes automatic limiting for high carrier stability. Built-in SWR load mismatch circuitry provides protection against open or shorted antennas. Mike pre-amp. uses FET input circuit. Operates on 6 separate transmitting and receiving channels plus provisions for six additional receiving channels. 2 IC's, 24 transistors, and 7 diodes. Power Drain: 2.5 amps. under full transmit at required 12 volts DC. Supplied with a set of crystals for 146.94 MHz, push-to-talk ceramic mike, and mounting bracket. Size: 2 1/4" x 5 1/2" x 7 1/4" D. Shpg. wt., 6 lbs.

40 R 66338W No Money Down* Net 229.00
Additional Crystals—Specify Frequency—30 Day Delivery.
40 R 82129Y Transmit, Shpg. wt., 4 oz. Net 6.50
40 R 82137Y Receiver, Shpg. wt., 4 oz. Net 4.95

DRAKE "Marker Luxury" 2 METER FM TRANSCEIVER



329⁹⁵

Supplied with 2 channels, Mobile mounting bracket, mike, coax and Hustler Antenna

- For 12 Channel Operation
- Built-In 12 Volt DC and 117 Volt AC Supplies*
- Power Output: Greater than 10 Watts

Expressly designed to provide the flexibility needed for point to point or repeater operations. Covers the 144-148 MHz spectrum with full power performance. Solid state receiver incorporates crystal controlled double conversion superheterodyne circuitry. Sensitivity is better than 0.5 μ v. for 20 db. quieting and 1 μ v. for 30 db S+N/N at 10 kHz with 1 kHz modulation. Hybrid transmitter utilizes transistors with a rugged 6360 output tube. RF output is better than 10 watts with adjustable deviation to 15 kHz. Spurious radiation is greater than 80 db below the carrier. Built-in 12 volt DC and 117 volt AC supplies. Draws 4 amperes on full transmit @ 13.5 volts. Supplied with 146.34 MHz transmit and 146.94 MHz receive crystals for channel 1, and with 146.94 MHz (Simplex) crystal for channel 2, mobile mount, mike, coax, and Hustler Antenna. Size: 7 7/8" x 2 3/4" x 10 1/4" D. Imported. Shpg. wt. 8 1/4 lbs.

40 R 65439W No Money Down* Net 329.95
Additional Crystals—Specify Channel Frequency—30 Day Delivery.
40 R 65447Y Transmit, Shpg. wt., 4 oz. Net 5.00
40 R 65454Y Receive, Shpg. wt., 4 oz. Net 5.00

DRAKE MODEL TR-4 SSB / AM / CW TRANSCEIVER



- Full Frequency Coverage 10-80 Meters
- Automatic TR Switching on CW
- CW Side Tone Oscillator
- Vox or PTT on SSB or AM
- Adjustable Pi-Network
- Solid-State VFO Blanker

599⁹⁵

No Money Down*

Deluxe SSB/AM/CW transceiver with VOX and PTT on SSB and AM, automatic transmit/receive switching on CW. Ideal for mobile or portable work. Sensitivity less than 1/2 microvolt for 10 db S/N. Features: Selectivity 2.1 kHz at 6 db, 7.5 kHz at 60 db; Ranges 3.5-4 MHz, 7.0-7.6 MHz, 13.9-14.5 MHz, 21-21.6 MHz, 28-28.6 MHz, 28.5-29.1 MHz, 29.1-29.7 MHz; Transistorized permeability tuned oscillator which tunes 4.9-5 MHz. Less than 100 Hz drift after warmup; input power 300w PEP (SSB) 260w AM or CW; 20 tubes 6 diodes and built-in 100 kHz xtal calibrator. Size: 10 3/4" x 5 1/2" x 14 3/4" D. Less noise blanker.

40 R 65462WX Model TR-4. Shpg. wt., 2 1/2 lbs. Net 599.95

ACCESSORIES FOR DRAKE TR-4

40 R 65470 34NB Plug-In Noise Blanker, wt. 1 lb. Net 100.00
40 R 65041 MS-4 Matching Spkr. for TR-4, wt. 9 1/2 lbs. Net 22.00
40 R 65249W AC-4 AC Power Supply for TR-4, 19 1/2 lbs. Net 99.95
40 R 65397W DC-4 DC Power Supply for TR-4, 10 lbs. Net 125.00

AMECO RECORD CODE COURSES



AS LOW AS
3.95

Includes New Extra Class, Supplementary General, and Supplementary Extra Courses

Fast, accurate method for learning code. JUNIOR COURSE: one 33 1/2 RPM LP; from start to 7 1/2 WPM. ADVANCED: one 33 1/2 LP; 8 1/2 to 18 WPM. SENIOR: two 33 1/2 RPM LP's from start to 18 WPM. EXTRA CLASS COURSE: one 33 1/2 RPM LP; 13 to 22 WPM. SUPPLEMENTARY GENERAL CLASS COURSE: concentrated study from 12 to 15 WPM; one 33 1/2

RPM LP. SUPPLEMENTARY EXTRA CLASS COURSE: concentrated study from 19 to 24 WPM; one 33 1/2 RPM LP. Courses include 32 page manual with FCC-type exams.

Stock No.	Course	Speed	WL	Net
40 R 13058	Junior	33 1/2 RPM	3/4 lb.	3.95
40 R 13074	Senior	33 1/2 RPM	3/4 lb.	7.50
40 R 13090	Advanced	33 1/2 RPM	3/4 lb.	3.95
40 R 10518	Extra Class	33 1/2 RPM	3/4 lb.	3.95
40 R 10526	Supplementary general	33 1/2 RPM	3/4 lb.	3.95
40 R 10534	Supplementary Extra	33 1/2 RPM	3/4 lb.	3.95

TAPED CODE—LEARN CODE ON A TAPE RECORDER



AS LOW AS
5⁰⁰

Prerecorded magnetic tapes containing a complete course in the International Morse Code. The tapes are 7", 1200 ft. pre-recorded at 3 1/2 ips and can be played

on any standard tape recorder. Playing time 2 hours per tape. Shpg. wt., 1 lb.

40 R 49011 NOVICE Basic instructions & code 4-8 WPM Net 6.50
40 R 49029 ADVANCED Code at 9-18 WPM Net 5.50
40 R 49037 NEW EXTRA Code instruction at 22-31 WPM Net 5.50


BASIC AND ADVANCED CODE COURSES ON CASSETTE TAPE



4⁹⁵

BASIC COURSE, consists of 10 lessons, bringing the student up to 15 words per minute. With 20-page code course.
40 R 71007 Shpg. wt., 1/2 lb. Net 4.95
ADVANCED COURSE, consists of 12 lessons, 16 to 25 words-per-minute. With 20-page code course. Shpg. wt., 1/2 lb.
40 R 71015 Net 4.95

LAFAYETTE Amateur Keys and Oscillators



(A) LAFAYETTE SEMI-AUTOMATIC "BUG"

A quality "Bug" designed for clear, easy sending and wide range of speed. 7 adjustments for speed and comfort. Precision-tooled, anti-rust nickel-plated brass and stainless steel operating parts. Speed adjustable 10 wpm to as high as desired. 1/8" silver contacts; weight scale for reproducible speed settings. 6 7/8" x 3 1/2" x 2 1/4" H, exclusive of knobs and feet. Imported. Shpg. wt., 3 3/4 lbs. Net 12.95

(B) LAFAYETTE CODE PRACTICE SET

Ideal for the beginning amateur and code practice groups. Key has adjustable spring tension, and adjustable contact clearance. High frequency buzzer has frequency, and tension adjustment with lock nuts to assure constant frequency. There is provision for insertion of head set by means of binding posts with knurled tightening screws. For individual, group or remote listening. Uses Lafayette 1 1/2 Volt battery. Base 6 3/4" x 2 3/4" x 1 3/8" D, overall length 8 1/2". Imported. Shpg. wt., 1/2 lb.

99 R 25538 Net 1.79
99 R 62564 "D" Cell battery for above Net .18
99 R 25504 Stethoscope Headset Net 1.39

(C) LAFAYETTE "BRASS-POUNDER'S" KEY

A precision-made key designed for hard usage. Spring tension and contact clearance adjustments; 3/16" silver contacts; adjustable ball-bearing pivots; Circuit closing switch. Base 3 x 2"; overall size 5 x 2 3/8 x 1 1/4". Imported. Shpg. wt., 1/2 lb. Net 2.50

(D) LAFAYETTE BEGINNER'S KEY

Economical key for beginning amateurs. Solid, heavily chrome and nickel plated metal parts, molded phenolic base. Adjustable spring tension, adjustable metal parts and adjustable contact clearance. 2 mounting holes in base. Base 3 1/4" x 1 1/8" W. Overall length 5"; height 1 3/8". Imported. Shpg. wt., 1/2 lb. Net .79

99 R 25546

(E) HIGH FREQUENCY CODE PRACTICE BUZZER

Adjustable frequency buzzer ideal for individual or group code practice. Perfect code item for the ham shack. Black molded phenolic housing. Works with 1 1/2 volt battery. Screw adjustment for changing tone. 1 7/8" diam. x 1 1/4" high. Imported. Shpg. wt., 1/4 lb. Net .79

(F) MINIATURE CODE OSCILLATOR MODULE

Transistorized. Ready to connect to your telegraph key, any 1 1/2 to 6 volt battery and any PM speaker—ideal for learning Morse code or developing speed in receiving or sending—volume may be increased by using higher voltage battery up to 6 volts. Simple connecting instructions and schematic included. Shpg. wt., 3 oz. Net .98

19 R 15131

LAFAYETTE SOLID STATE WIRELESS CODE PRACTICE OSCILLATOR SET



Makes learning code as easy as possible. Ideal for students, hobbyists or aspiring amateurs. Portable, battery operated. Just place oscillator antenna next to any AM radio... turn radio on and you're ready to practice or improve your code speed. Includes hand key and 9-volt battery. Transistorized oscillator features low battery drain. Size: 3 1/4" x 2 1/4" x 1 1/4" H. Key: 4 3/4" x 1 3/8" W. Imported. Shpg. wt., 1/2 lb. Net 3.95
99 R 26080 Net .29
99 R 60212 Extra 9 volt battery.

Only 3⁹⁵

LAFAYETTE CODE PRACTICE OSCILLATOR



8⁹⁵

3-WAY OPERATION:

- Light Indicator
- Light-Tone Combined
- Variable Pitch Tone

A terrific aid for the beginning Morse Code learner to experienced hams who wish to improve their code speed. Completely self-contained. It can be carried wherever you go. Efficient built-in speaker provides loud, clear signal. Excellent for group practice sessions. Variable pitch control gives pleasing tone by changing frequency. For private use, without disturbing others, you have a choice of earphone tone operation, flashing light or both together. Uses low drain battery-operated transistor oscillator. Specifications: Tone frequency range: Approx. 500 to 2000 Hz variable Controls: Pitch, Tone, Light and Light/Tone. Terminals: Key, Earphone. Batteries: Includes 2 "C" cells. Case: Hi-impact bakelite. Size: 6 1/4" H x 3 3/4" W x 2" D. Imported.

99 R 25503 Shpg. wt., 1 1/4 lbs. Net 8.95
99 R 62572 Extra "C" cells for above, 2 required Net ea. .16
Lightweight Crystal Headset for above. Imported.
99 R 25504 Shpg. wt., 5 oz. Net 1.39

B & W/WATERS COXAD AUTOMATIC KEYS

- Automatic Spacing and Timing
- Solid State Circuitry



The Coxad automatic keys feature automatic spacing and timing for any speed from 5 to 50 WPM. Double paddle key adjusts to any list. Transistorized digital circuit and hermetically sealed "Reed" relay for lasting reliability. 1500 cycle audio output is at microphone level for use of VOX circuit. Keys grid block circuit or operates keying relay in AM/CX rigs. Self powered. Dot/Dash, 3:1. 2 3/4" x 3 3/4" x 6 1/8" H. Shpg. wt., 2 1/2 lbs.

40 R 16309 Model 361, Less Batteries Net 71.25
Package of 2 1.35v batteries for above (3 pkgs. req.)
32 R 46615 Net per package 2.28

VIBROPLEX SEMI-AUTOMATIC KEYS



Super Deluxe "Presentation." Patented jewel movement and Super-speed control. Polished chromium precision machined parts mounted on a 24K gold-plated base top with colorful red switch knob, finger and thumb piece. Jeweled movement reduces friction, maintains smoother, easier operation. Shpg. wt., 5 lbs. Net 47.95
40 R 88084 No Money Down

"Champion." Low priced Vibroplex with same high standards of high quality for clear, speedy and easy sending. Ideal for amateur or professional radio operators. Chromium finished top parts with grey crystal base. Single lever with 2 pairs of contact points. Shpg. wt. 3 1/2 lbs. Net 23.95
40 R 88013

"Original." Acclaimed by veteran operators for its extremely smooth, clear, rapid, effortless and accurate operation. A rugged, well built, expertly engineered machine for all classes of transmitting work. Large contact points. Die cut dot contact. Chrome-plated mechanism. Cast-iron base. Shpg. wt., 4 3/4 lbs. Net 29.95
40 R 88027

Deluxe "Original." As above but jeweled bearings, chrome-plated base. Shpg. wt. 5 lbs. Net 36.95
40 R 88035 No Money Down
CORD AND WEDGE for above. Shpg. wt., 1/4 lb. Net 2.75
40 R 88050

Vibro-Keyer. An efficient keying mechanism for an electronic transmitting unit. Smooth and easy operating trunion lever. Large contacts and frame. Size: 3 1/2" x 4 1/2". Shpg. wt. 3 3/4 lbs. Net 22.95
40 R 88068

Improve Your Amateur And CB Operating Effectiveness With LAFAYETTE Meters and Testers

SWR Bridge and RF Power Meter

1000 Watt Inline Wattmeter



22⁹⁵

- Measures Standing-Wave-Ratio in a Transmission Line
- Measures Up To 15 Watt Output Into a Built-In Dummy Load
- VSWR Measurement From 1:1 to 10:1 and Reflected Power to 1 KW

Highly accurate SWR and direct power readings up to 50 MHz. The unit may be permanently inserted in the transmission line for SWR and relative power monitoring. For 52 or 75 ohm lines. Insertion loss is negligible. Meter has 50 μ a movement; calibrated directly in watts from 0.15 and in SWR from 1 to 10 IF (reads infinity at full scale). . . Housed in an attractive grey metal cabinet, 3 $\frac{1}{4}$ x7 $\frac{1}{4}$ x2 $\frac{3}{8}$ ". Sits on 4 rubber feet. Imported. Shpg. wt., 2 $\frac{1}{4}$ lbs. 99 R 25082

Net 22.95



- 1000 Watts Continuous
- 2-30 MHz
- 3 Scales: 0-10, 0-100, 0-1000 Watts
- Dummy Load Position
- VSWR Function
- 50-Ohm Impedance

39⁹⁵

Provides all you need to get the most out of your transmitter. Absorbing negligible power, this inline unit will continuously monitor radiated power. Range selector switch allows monitoring on ranges of 0-10, 0-100, or 0-1000 Watts. A two-way load switch permits rapid change over from dummy load to the antenna, or between two antennas. VSWR measurements can be quickly arrived at by means of a nomogram which is supplied with the unit. Size: 6 $\frac{1}{2}$ x3 $\frac{3}{4}$ x2 $\frac{7}{8}$ ". 40 R 24006 No Money Down* Shpg. wt., 1 $\frac{1}{4}$ lbs. Net 39.95

R.L. Drake W-4 RF Wattmeter

Swr and Field Strength Meter



61⁹⁵

No Money Down*

- Frequency Coverage: 1.8-54 MHz.

Reads forward and reflected power directly in watts (VSWR from nomogram). Two scales in each direction. 200 and 2000-watts full scale. Calibration accuracy: \pm (5% of reading +2 watts) on 200 watt scale; \pm (5% of reading + 20 watts) on 2000-watt scale. Size: 5 $\frac{1}{2}$ Hx3 $\frac{3}{4}$ Wx4"D. Shpg. wt., 2 $\frac{1}{4}$ lbs. 40 R 65371

Net 61.95
DRAKE WV-4 RF WATTMETER. Same as above but for coverage from 20-200 MHz. Power Capability: 100 and 1000 Watts full scale. Shpg. wt., 3 $\frac{1}{4}$ lbs. 40 R 65413

Net 73.50



9⁹⁵

- SWR 1:1 to 3:1

A handy 2-in-1 meter for use in the amateur radio station to check transmitters for SWR measurements. Can be left continuously in the circuit for monitoring transmitter outputs, SWR: 1:1 to 3:1; Accuracy \pm 5 db, 2 to 30 MHz; Impedance: 52 Ohms; Antenna: 5-section, collapsible. Comparative RF field strengths can be easily determined with this fine meter. Sensitive 100 microammeter movement with easy to read 2-color dial. Impedance matches 52 Ohm coaxial lines. Attractive grey hammertone aluminum case. Size: 5 $\frac{7}{8}$ Hx3 $\frac{1}{4}$ D x 1 $\frac{1}{4}$ W. Imported. Shpg. wt., 1 $\frac{1}{2}$ lbs. 99 R 25835

Net 9.95

Miniature Illuminated "S" Meter

Deluxe "S" Meter



3⁹⁵

- Indicates Strength of Received Signal
- Jeweled Bearings
- Accuracy 2% of Full Scale
- High Quality D'Arsonval Movement
- Clear Plastic Front

Durable wrap-around plastic front panel provides wide-angle readability. Zero adjustment screw on front panel; jeweled bearing movement. Calibrated in "S" units from 0.9 with the scale terminating in +10 and +30 calibrations. Additional full scale calibrations of 0.5 and 0-10 in linear scale divisions. Silvered dials; black numerals and pointers. Illuminating lamp for either 6 or 12 volt operation. 1 $\frac{1}{2}$ " dial face; 1 $\frac{1}{4}$ " overall behind panel. Supplied with mounting screws. Imported. Shpg. wt., $\frac{1}{2}$ lb. 99 R 25132

Net 3.95



8⁹⁵

- Signal Strength Meter Using VTVM Principles
- Magnetic Feet For Mobile Dashboard Mounting
- Sensitivity and Zero Adjust Controls

Designed for use with any superheterodyne receiver employing AVC. Meter is calibrated in "S" units from 1 to 9, and in db up to 30db over S9. Partial peak clipping is provided for noise limiting. Simple installation—B+, filament and ground. It is adaptable to either 6 or 12-volt equipment, and to receivers using 150 ma or 300 ma series string filament systems. Requires 150-200 VDC for B+. Complete with 12AU7 and installation instructions. Imported. 99 R 25124 Shpg. wt. 1 $\frac{1}{4}$ lbs. Net 8.95

Miniature Illuminated Modulation "S" Meter

Full-Size Illuminated "S" Meter



3⁹⁵

- Combination "S" Meter, % Modulation Meter and RF Power Output Meter
- Accurate D'Arsonval Movement
- Jewel Bearings

Highly accurate. Features wide viewing angle and 3-color scale. Front panel zero adjustment. Calibrated scales (1 MA full scale), 0 to 100% modulation, "S" units 0-9, also +10 and +30. Linear full scale markings of 0 to 5. Dimensions: dial face, 1 $\frac{3}{8}$ "; depth 1 $\frac{1}{4}$ " overall. Supplied with 4 mounting screws and lugs. For 6 or 12 volts. Dust resistant case. Imported. Shpg. wt., $\frac{1}{2}$ lb. 99 R 25074

Net 3.95



4⁹⁵

- Indicates Strength of Receiver Signal
- 2 Jewel Movement
- Clear Plastic Front
- Calibrated to S9 +40 db

A quality "S" meter (basic 1 ma, 2 jewel movement) designed to replace many "S" meters used in communications receivers. Clear plastic front measures 2 $\frac{3}{8}$ " square and meter fits standard 2 $\frac{1}{2}$ " round hole. Perfect for the experimenter and amateur. Complete with mounting screws, instructions for installation and use. For 6 volt or 12 volt operation. Zero adjustment control on front panel. Imported. Shpg. wt., $\frac{1}{2}$ lb. 99 R 25140

Net 4.95

Amateur Meters, Clocks and Accessories

LAFAYETTE SWR AND FIELD STRENGTH METER



ONLY 995

- Measures SWR, Relative Forward And Reflected Power to 1 KW
- Reads Field Strength

A handy 2-in-1 meter for use in the amateur radio station to check transmitters for SWR measurements. Can be left continuously in the circuit for monitoring transmitter outputs, SWR: 1:1 to 3:1; Accuracy ± 5 db, 2 to 30 MHz; Impedance: 52 Ohms; Antenna: 5-section collapsible. Comparative RF field strengths can be easily determined with this fine meter. Sensitive 100 micro-ammeter movement with easy to read 2-color dial. Impedance matches 52 Ohm coaxial lines. Neatly designed attractive case. Size: 1 1/2" Wx 5 7/8" H x 2 3/4" D. Imported. Shpg. wt., 1 lb. 8 oz. 99 R 25835 Net 995

B & W/WATERS COMPRESS



3150 No Money Down*

- Boosts Effective Speech Power Output up to 4 Times
- For Transmitters, Transceivers,

Tape Recorders and P.A. Amplifiers. Connects between a 50,000 ohm dynamic or high impedance ceramic microphone and microphone input connector without any wiring change. May be switched in or out of circuit and compression level can be easily adjusted. Input Impedance: 100k ohms, nominal. Input Level: .005 to .020 volts. Voltage Gain: 10 db, nominal. Output Level: .060 volts. Output Impedance: 50k ohms, nominal. Self-contained battery powered. Size: 2 3/4" x 3 1/2" Shpg. wt., 1 lb. 40 R 16291 Less Battery Net 31.50 9 volt battery (1 req.) Net 48 32 R 48077

EICO 710 GRID DIP METER



Kit **39⁹⁵**
Wired **59⁹⁵**
No Money Down*

Extremely stable grid dip meter with a frequency range of 400 kHz to 250 MHz. Covers AM and FM broadcast bands, low and high band mobile radios, CB, and all ham bands through VHF. Use to tune transmitters, trim antennas to proper length, locate parasitic oscillations, measure circuit resonance, determine capacitance, "Q" values, and inductance. In addition, can also be used as a transmitter monitor and a wave-meter. Uses eight precision, plug-in coils, 0-500 μ a meter, and a rotating drum scale. Operates on 115 VAC, 60 Hz. Size: 2 1/4" x 2 1/4" x 6 7/8". Shpg. wt., 4 lbs. 40 R 74259 Model 710 Kit Net 39.95 Model 710 Factory wired and tested. Net 59.95 40 R 74266

DRAKE SCC-1 CRYSTAL CALIBRATOR



26⁹⁵

- 50 kHz. to 432 MHz.
- Zener Regulation

Crystal controlled 100 kHz FET oscillator. Uses two integrated circuits to produce 50 kHz. calibration points. Requires no tuning, band switching, or plug-in coils. Maximum stability attained through the use of zener regulation. Has provision for both local and remote on/off switch. 50 kHz to 432 MHz frequency range. Requires 15 to 18 VDC, 40 ma. Reverse polarity protection. Size: 3 3/4" x 4 3/4" x 2 1/4". 40 R 65389 Shpg. wt., 1 lb. Net 26.95

AMECO MODEL AC-17 AMATEUR TRANSMITTER KIT



Only **24⁹⁵**

- Ideal for Novice
- Self Contained

The ideal unit for beginner or novice. Contains transformer powered AC power supply. Uses a PI network output. Has full 15-watt input on 40 and 80 meters. Easy to build and operate. Complete with punched chassis, all parts, tubes (6V6 and 6X5) and instructions. Shpg. wt., 6 1/2 lbs. Complete with 1 coil kit. 40 R 10096 Transmitter Kit Net 24.95 40 10104 CK1 extra coil kit Net 1.10

SUPEREX AMATEUR HEADPHONE



24⁹⁵

Made especially for the Ham and short wave listener. Comfortable, removable and replaceable vinyl foam ear cushions make long hours at the rig a pleasure. Dual Impedance, 600 and 4-10 ohms, can be changed at plug. Shpg. wt., 2 1/2 lbs. 40 R 85015 Net 24.95

E. F. JOHNSON PHONE PATCH



25⁰⁰

A compact automatic hybrid-transformer type patch which accepts PTT, manual, or VOX keying. Separate receiver and transmitter input gain controls provide flexible operation without over drive. Effectively shielded and RF by-passed to virtually eliminate RF feedback into the telephone headset for undistorted, hum-free response. Adjustable "line null" control. Size: 2" Wx 6" x 2 1/2" D. Shpg. wt., 2 1/2 lbs. 40 R 46231 Model 250-46 Patch Net 25.00

QUALITY CLOCKS FOR YOUR AMATEUR STATION

24-HOUR ELECTRIC WORLD CLOCK



10⁹⁵

- 8" Overall diameter
- Adjustable for Various Time Zones
- South Polar Projection

Self starting, accurate electric clock. Tells world-wide and local time. Calibrated in hours—1 to 24, minutes and seconds—1 to 60. Black dial with white graduations.

Chrome plated case. U.L. Listed. 110-120 v. 60 Hz AC. Shpg. wt., 2 lbs. 13 R 26024 Net 10.95

24-Hour Tymeter Clock Only

16⁰⁰



Numerical type, 24 hour station clock. Self starting electric. Dome shaped full vision window. UL listed molpr and cord. For 110V-60 Hz. 40 R 91021

Net 16.00

DELUXE 24 HOUR ELECTRIC WORLD CLOCK



- Large 12" Clock Face
- Red Sweep Second Hand

19⁹⁵

Finely constructed, accurate 24 hour electric wall clock. Has 12" white dial face with black numerals and hands. Gray case is 13 1/4" overall diameter. UL listed electric movement. Shpg. wt., 5 1/2 lbs. 13 R 26578W Net 19.95

24 HOUR CALL-IDENT TYMETER CLOCK

- 10 Minute Repeat Timer **23⁵⁰**



24-hour direct reading dial shows minutes and hours. 10-minute repeat timer buzzes warning to sign your call letters. Timer independently switched. Self-starting electric. For 110-120V, 60 Hz AC. Walnut finish plastic case. Size: 7 3/4" W x 4 1/4" D. 40 R 91013 Shpg. wt., 3 1/2 lbs. Net 23.50

Amateur Base Station Antennas and Accessories

LAFAYETTE ALL-BAND VERTICAL TUNEABLE 10 TO 80 METERS ANTENNA



Only
15⁹⁵

- Omni-Directional, Vertically Polarized
- Irridite Treated To Mil Specs

Our best buy multi-band antenna. Can be tuned to any amateur band 10 through 80 meters by a single adjustment; Has amazing efficiency for DX or local contacts. Ground or roof top or tower installation. Can survive winds in excess of 50 mph. Overall height 18"; knocks down to only 5". Uses 3/4" diameter air wound coil as matching inductor. All steel parts irriridite treated to Mil Specs. Impedance 52 ohms. Maximum power 1000 watts AM or CW—2 KW PEP. Omni-directional; vertically polarized.

40 R 01046W Shpg. wt., 5 lbs. Net 15.95

CUSHCRAFT "TRIK STIK" ANTENNA

8⁹⁵

- For Amateur, SWL, TV, FM, Business Radio, CB, VHF Low and High band monitor, Aircraft Reception

Universal antenna designed for vertical or horizontal mounting. All aluminum construction. Supplied with U-bolt, bracket, and hardware for mounting on a mast or tower. Can also be mounted to a building using nails or screws. 2-54" element sections, 2-51" element inserts, 23" support boom. Complete instructions for frequency settings.

40 R 19188W Shpg. wt., 2 3/4 lbs. Net 8.95

HY-GAIN 18 AVT/WB 10-80 METER WIDE BAND VERTICAL ANTENNA

- Automatic Switching, 5 Band Capability
- True 1/4 Wave Resonance On All Bands

Ruggedly constructed of heavy duty tapered swaged seamless aluminum. Delivers outstanding wide band omni-directional performance. Automatic band switching is accomplished by using three beefed-up HY-Q traps. Features top loading coil; 1/4 wave resonance on all bands; SWR of 2:1 or less; low radiation angle on roof or ground mounted. Antenna height 25 ft. wt., 16 1/4 lbs. No Money Down*

40 R 31290W Net 59.95

MODEL 14 AVQ/WB 10 THRU 40 METER HY-Q TRAP VERTICAL ANTENNA. Self supporting, heavy duty aluminum automatic band switching vertical delivers omni-directional performance on 40 through 10 meters. HY-Q traps for 1/4 wave resonance on all bands. Low radiation angle. 12" double grip mast bracket insures rigidity whether roof or ground mounted. 18 ft. high. wt., 9 1/4 lbs. No Money Down*

40 R 31308W Net 39.95

ROOF MOUNTING KIT For 14 AVQ/WB includes 5 ft. mast, roof mount, ground plane radial wires, insulators, and all necessary hardware. Shpg. wt., 7 1/4 lbs.

40 R 31050W Net 19.95

HY-GAIN BN-86 BROAD BAND FERRITE BALUN




- For Use With 10-80 Meter Beams, Antennas And Doublets
- Impedance 1:1 at 52 Ohms

Can be used with any beam antenna in the range of 3 to 30 MHz. Provides optimum balance of power to both sides on any doublet. Power Capacity is 1 kHz DC. Weatherproof construction and built-in mounting brackets. Shpg. wt., 1 1/4 lb.

40 R 31282 Net 14.95

DELUXE MOSELY TA SERIES BEAM ANTENNAS FOR 10, 15, 20 METERS

Deluxe Model TA 33. 3-element beam providing up to 8 db gain on the 10, 15 and 20 meter bands. Trap design provides broadband performance and stability—beam easily handles a full kilowatt of AM signal. 25 db front-to-back ratio, SWR 1.1/1, or less, at resonance. Beam length 14 ft., element length 28 ft. Shpg. wt., 53 lbs. 40 R 58020WXY No Money Down*



Net 135.85

Model TA-33 "Junior," similar to above, but only 300 watts AM. Boom length 12 ft., Element length 26'8". Shpg. wt., 28 lbs. 40 R 58038WXY No Money Down*

Net 93.30

Deluxe Model TA36 6 Element Beam. Automatic band switching through high impedance parallel resonant trap circuits. Handles 1000 watts AM/CW or 2000 watts PEP. SWR 1.5/1 or better. Beam length 29 ft., boom length 24 ft. Shpg. wt., 71 lbs. 40 R 58079WXY No Money Down*

Net 167.90

CUSHCRAFT 2 METER FM ANTENNAS

(A) AR-2 FM RINGO ANTENNA: Power ring tuning gives a perfect match between cable and antenna. Ringo also features a 52-ohm direct coaxial feed, 5" ring diameter, 3.75 db gain, and direct DC ground. Takes PL-259 fitting. Factory preassembled and ready to install. Takes up to a 1 1/4" O.D. mast. 42" length at 147MHz. Shpg. wt., 2 lbs. 40 R 19253 135-175 MHz Net 12.50

(B) AFM-4D 4 POLE: Up to 9 db gain over a 1/2 wave dipole; 23 ft. o/a, pattern 360°—6 db gain, 180°—9 db gain, 52-ohm direct feed. Takes PL-259 connector. Includes 4 complete dipole assemblies on 10" mounting booms, harness and hardware. Will take up to a 2" O.D. vertical mast (not supplied). Shpg. wt., 6 lbs. No Money Down* 40 R 19261 146-148 MHz Net 42.50

CUSHCRAFT BEAM ANTENNAS FOR 2 and 6 METERS

Model A50-5 5-Element, 6 Meter Beam. Deluxe, rugged, full size, constructed of 3/4" 0.049 wall aluminum tubing. Boom is 0.058 wall drawn aluminum. Driven element is "Reddi" matched for direct coax feed. Light enough for any heavy duty TV rotator. Turning radius—7'6"; Forward Gain—9.5 db; F/B ratio—29 db. Comes with all parts marked for quick, neat assembly and center band operation. Shpg. wt., 12 lbs. 40 R 19121W Net 29.50

Model A50-3 3-Element 6-Meter Beam. 7.5 db forward gain, 6 foot boom, Shpg. wt., 8 lbs. 40 R 19238W Net 18.50

MODEL A-1447 7 ELEMENT 2-METER BEAM. Full size. Aluminum tubing. Beam length, 98". Forward gain 11 db F/B ratio 26 db. 40 R 19139W Shpg. wt., 7 lbs. Net 13.95

Model A-144-11. 11-Element 2-Meter Beam. Boom length 144". Forward Gain 13 db F/B ratio 28 db. Shpg. wt., 6 lbs. 40 R 19147W Net 17.95

DELUXE CORNELL-DUBILIER HEAVY-DUTY ANTENNA ROTORS

As Low As **69⁹⁵** No Money



- Heavy Duty Construction Down*
- Indicator Calibrated in Compass Points

MODEL TR-44 ANTENNA ROTOR For single bay amateur antenna application. Rotor contains 48 heavy duty bearings in two 6 1/2" ball races. 450 in.-lbs average torque. Indicator is calibrated in compass points and 3" increments. Double stage switch allows meter reading while motor is off. For mast or pipe to 2 1/4" O.D. For 110-120V. 50-60 Hz. Less cable. Shpg. wt., 19 1/2 lbs. 40 R 83028W No Money Down* Net 69.95

HAM M ANTENNA ROTOR—Heavy duty rotator. Meets all amateur radio applications. Supports antennas up to 1000 lbs. Uses same compass indicator unit as the TR-44, calibrated in 3" increments. Heavy duty stainless steel gears and pinions, solenoid brake release. For 110-120VAC, 50-60 Hz. Shpg. wt., 26 lbs. 40 R 83010W No Money Down* Net 129.95

100 ft. roll of 8 cond. cable for TR-44. HAM-M Shpg. wt., 5 3/4 lbs. 32 R 14574 Net 10.26

*See Page 22 for Full Credit Details on Easy Pay Plan

Mobile Ham Antennas — Shortwave Antennas and Accessories

**DELUXE LAFAYETTE "RAPID-GRIP"
MOBILE ANTENNAS FOR 2 AND 6 METERS**

**NEW-TRONICS "HUSTLER" MOBILE
ANTENNAS FOR 10-15-20-40-75 METERS**



As Low As **10⁹⁵**

- "Rapid-Grip" Mount Provides Permanent Antenna Installation In Seconds Without Drilling Holes

6 Meter Mobile Antenna with "Rapid Mount"

Features waterproof base loading phasing transformer, 43" stainless steel whip with adapter for extra fine tuning, and a cadmium plated trunk-lip "Rapid-Grip" mount with water resistant body seal. Offers ideal omnidirectional signal pattern. Mounts on lip of trunk without drilling holes. Shpg. wt., 1 3/4 lbs. Less coaxial cable.



40 R 01095 Net 12.95

2 Meter Mobile Antenna with "Rapid Mount"

Features rust-resistant cadmium plated "Rapid-Grip" Mount base and stainless steel whip approximately 19 inches long, which can be cut to precise operating frequency. Mounts on lip of trunk without drilling holes. Offers ideal omnidirectional signal pattern. Complete with 16 ft. of RG 58/U cable and PL-259 plug. Shpg. wt., 2 lbs.



40 R 01103 Net 10.95

- Fold Over Swivel Mast
- Power Rating Up To 400 Watts SSB

An outstanding antenna assembly permitting multi-band mobile operation with exceptional results. Buy only one mast and select the resonators for the bands you operate. No need for matching devices, use any feed line length of 52-ohm cable. Each of the five resonators has a coil specially designed for maximum radiation for a particular band. Center frequency tuning is by means of an adjustable stainless steel rod in the resonator assembly. The 54-inch fold-over, heat treated, 1/2" aluminum mast permits instantaneous interchange of resonators for the desired band. SWR is less than 2 to 1 for any center frequency within each band. Power Rating: AM input 75 watts; SSB input up to 400 watts PEP. Mast has 3/8"-24 base stud to fit all standard mounts.

Stock No.	Model No.	Description	Wt.	Net
40 R 55018W	MO-1	54" Mast Fender Mount	2 lbs.	11.95
40 R 55026W	MO-2	54" Mast Bumper Mount	2 1/4 lbs.	12.25
40 R 55034	RM-10	10 Meter Resonator	3/4 lb.	7.95
40 R 55042	RM-15	15 Meter Resonator	1/4 lb.	8.95
40 R 55059	RM-20	20 Meter Resonator	1 lb.	9.95
40 R 55067	RM-40	40 Meter Resonator	1 3/4 lbs.	11.95
40 R 55075	RM-75	75 Meter Resonator	1 3/4 lbs.	13.95

HY-GAIN SW-9 SHORTWAVE WINDOW ANTENNA

- Includes Universal Window Mounting Bracket

The ideal shortwave antenna for window installations; where roof-top antennas are impractical or cannot be used. Provides broadband performance comparable with other larger installations. Consists of one 9 foot aluminum tubular element with a universal mounting bracket and feedline. Simple to install.



Only **9.95**

Answers the problems of apartment dwelling SWL's.

40 R 31183W Shpg. wt., 3 3/4 lbs. Net 9.95

**MOSLEY MODEL SWV-7
FIXED VERTICAL SW ANTENNA**

Only **33.60** • For Roof or Ground Mounting

Model SWV-7 is designed for 11, 13, 16, 19, 25, 31, and 49 meters. Six specially designed trap assemblies, housed in a single weatherproof phenolic casing assure broad band coverage for top DX performance. Antenna incorporates only the finest alloy aluminum tubing, telescoped and swaged to reduce wind vibration. Molded plastic cap prevents water from entering element. Height: 13'3 3/8". Ground is required. Shpg. wt., 8 lbs.

40 R 39095W Net 33.60

HY-GAIN SW-6 SHORTWAVE ANTENNA

- Flat Top Design
- A completely assembled antenna, ready to install. Scientifically tuned for 1.8 to 30 MHz coverage. Can be installed on any existing structure: pole-to-pole, pole-to-tree, garage-to-house, under the eaves, in the attic... all provide excellent reception. Consists of 50 ft. copper wire attached at both ends to low-loss styrene insulators. 15' weather-proof rope on each insulator, plus lead-in feedline. Shpg. wt., 2 lbs.




6.95

40 R 31175 Net 6.95

DELUXE ANTENNA DUMMY LOAD

- 100 Watts Continuous 500 Watts For 15 seconds
- 52 Ohm Load

19.95



A must for troubleshooting your rig. 52 ohm load for easy RF power checks. Freq. Range: 0-100 MHz. VSWR 1:1. Size: 11x4x3 1/2" H. Shpg. wt., 2 lbs.

42 R 21081 Net 19.95

VHF and SHORTWAVE ANTENNA TUNER

Only **9.95**



- Works With Any Antenna Type
- Improves Reception On All Major Shortwave, Monitor, and Amateur Bands

Installs on any receiver in minutes. Permits antenna (especially indoor types) to operate efficiently on many frequencies. Greatly improves reception by increasing receiver sensitivity to weak signals, as well as, rejecting interference and annoying "image" signals. Covers following bands: Shortwave (meters)—13, 16, 19, 25, 31, 41, 49 and 60; Amateur (meters)—10, 15, 20, 40 and 80 plus all frequencies from 3 MHz to 30 MHz, including Marine, Public Safety, Citizens Band, Aviation and all other high-frequency services. 42 R 21073 Shpg. wt., 1/2 lb. Net 9.95

LAFAYETTE 5 POSITION COAXIAL SWITCH

ONLY **10.95**



- Frequency Range to 50 MHz
- Low Loss
- Grounded for Static Elimination
- 1 KW Power Rating
- Single Gang, Single Pole

Instantly selects any one of five transmitters, antennas, exciters, receivers, or transceivers using 52 to 75-ohm line. Single gang, single pole with positive ground. Rated 1 KW amplitude modulated. All positions not in use are grounded for static elimination. Long life, low loss ceramic switch. Complete with contrasting pointer knob and bracket for wall or panel mount. Size: 4 1/2 x 3 3/8 x 3 3/8". Shpg. wt., 2 lbs. 40 R 01228 Net 10.95

WORLD TIME ILLUMINATED ELECTRIC WORLD CLOCK

Only **64.95**



Modern, international electric wall time clock, showing the local time in 70 key areas around the world instantaneously and simultaneously 24 hours a day. Enlarged vivid time indicators for continental U.S. time zones. Clock automatically compensates for daylight savings time and indicates A.M. and P.M. hours. It also shows day and nighttime hours throughout the world with white and black backgrounds respectively. Set in handsome walnut frame. Illuminated. Powered by a heavy duty 115V. 60 Hz AC clock motor. Size: 15 1/2" H x 22 1/4" W x 4" D. Shpg. wt., 15 lbs. 40 R 30011W No Money Down* Net 64.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 431

Amateur Station and Antenna Accessories

LAFAYETTE
Coaxial Switch



(A) 10⁹⁵

B&W 425
Low Pass
Filter



(B) 28⁵⁰

Drake TV-1000LP
Low Pass Filter



(C) 18⁷⁵

Ameco HP45
High Pass Filter



1⁵⁰

Johnson 250-23-3
Matchbox



(E) 94⁹⁵

Johnson 250-39
TR Switch



(F) 29⁹⁵

W2AU BROAD BAND BALUNS



(G) 12⁹⁵

Solderless PL-259
Connectors



(H) .79

(A) LAFAYETTE Coaxial Antenna Switch—Instantly selects any one of five transmitters, antennas, exciters, receivers or transceivers using 52 or 75 ohm line. Single gang, single pole. Unused positions grounded for static elimination. Rated 1 KW. Shpg. wt., 1½ lbs.
40 R 01228 Net 10.95

(B) B&W 425 Low Pass Filter—usable with transmitters to 1-KW. Completely self contained—eliminates TVI. 85db attenuation. For 52 ohm coax. Shpg. wt., 2 lbs.
40 R 16085 Net 28.50

(C) Drake TV-1000LP Low Pass Filter—handles 1 KW: 160-10M. 200 watts on 6 meters. Shpg. wt., 2 lbs.
40 R 65140 Net 18.75

40 R 65132-Drake TV-42-LP—handles 100w, 160-10M Net 7.65

(D) Ameco HP-45-High Pass Filter—For attenuation of 40db at 14 MHz and 20db at 28 MHz, 300 ohms. Shpg. wt., 3 oz.
40 R 10054 Net 1.50

(E) Johnson 250-23-3 "Matchbox" Antenna Coupler—For 80, 40, 20, 15 and 10 meters. Matches balanced lines 25 to 1500 ohms and unbalanced lines 25 to 3000. Reads SWR. TR relay 750w PEP with directional coupler. Shpg. wt. 9¾ lbs.
40 R 46082—No Money Down* Net 94.95

(F) Johnson 250-39 TR Switch—Provides instantaneous high efficiency electronic antenna switching. Rated at 4KW. Instant break-in on SSB, DSB, CW, and AM. Shpg. wt., 4½ lbs.
40 R 46181 Net 29.95

(G) W2AU BROAD BANDS BALUNS—A transmitter and receiving balun with built in lightning arrester, and stainless steel hardware. Properly balances all coax fed antenna systems. Handles 1KW AM/CW, 2KW PEP. Completely weatherproof, withstands 650 lbs. of antenna tension.

BALUN I—1:1 model matches 50 or 75 ohm unbalanced to 50 or 75 ohm balanced load. Shpg. wt., ¾ lb.
40 R 47023 Net 12.95

BALUN II—4:1 model matches 50 or 75 ohm unbalanced coax line to 200 or 300 ohm balanced load. Shpg. wt., ¾ lb.
40 R 47031 Net 12.95

(H) Solderless PL-259 Low-Loss Coaxial Connectors—Two types—Fits either RG58/U or RG59/U cable. Quick, easy connections. No fuss, no bother, no adapter, no soldering required. Shpg. wt., 4 oz.
42 R 69106 Solderless PL259 for RG58/U Cables Net ea. .79
42 R 69114 Solderless PL259 for RG59/U Cable Net ea. .79

AMATEUR CRYSTALS, COILS, AND COAXIAL CONNECTORS

AMATEUR CRYSTAL PURCHASE CERTIFICATES



As Low As

2⁹⁵

Send filled out certificate, one for each crystal, to manufacturer. Manufacturer will ship crystal directly to you, postage paid. Available in types FT-243 and HC-17/U (pin diam., .093") and HC-6/U (pin diam., .050"). Pin spacing .486" for all types. Tolerance ± 500 Hz at designated frequency. No C.O.D.'s—allow 30 days for delivery. Specify exact frequency with your order. Specify FT-243, HC-17/U or HC-6/U type on Certificate.

40 R 54011Y 3500-4000 kHz Net 2.95
40 R 54029Y 7000-7425 kHz Net 2.95
40 R 54037Y 8-8.2MHz, 8.33-8.9 MHz Net 2.95

CRYSTAL SOCKETS

These Slettite insulated sockets will strongly hold the crystal contacts. Can be used for chassis or for panel mounting. The bushing will project through a round hole in panel. Av. shpg. wt., 2 oz.

Stock No.	Type	Pin	Spacing	Each
40 R 37123	CS-8	.125"	.750"	.45
40 R 37131	CS-6	.095"	.486"	.45
40 R 37149	CS-5	.125"	.500"	.45
42 R 09011	CS-7	.050"	.486"	.45

CRYSTAL HOLDER ADAPTERS

Mosley 5-75 adapts ½" spaced holder to ¾" spacing. Shpg. wt., 2 ozs.
40 R 58046 Net .40
Mosley 75-5 adapts ¾" spaced holder to socket with ½" spacing to octal socket. Shpg. wt., 2 ozs.
40 R 58053 Net .40

COAXIAL CONNECTORS



Shpg. wt. 3 oz.

42 R 69031 PL-259 Connector49

42 R 69049 UG-175/U Reducer—Adapts PL-259 to RG-58/U Diameter.16

42 R 69056 PL-258 Junction Adapter—Accepts PL-259 on both ends for cable extension.49

42 R 69064 UHF Double Male—.99 Free turning nuts

42 R 69072 SO-239SH Single hole .59 chassis mount

42 R 69080 GL-259PH PL-259—for quick .79 on-off application without threading.

Semi-Solderless PL-259 Connectors



• For RG-8/U or RG-11/U Cable

Package of 2 PL-259 type coaxial connectors. Eliminates difficult internal soldering to shield and gives positive electrical contact. Shpg. wt., 6 oz.
40 R 21028 Net 1.49

BARKER AND WILLIAMSON MINIDUCTORS



Highly efficient miniature coils offering extremely low losses and real space-saving economy. Ideal for compact circuits. Air wound, polystyrene insulation. Easily cut to size. Shpg. wt., 6 oz.

Stock No.	Type	Turns	Per In.	Dia.	L.	Net
40 R 16101	3001	4	1/2"	2"	1.20	
40 R 16119	3002	8	1/2"	2"	1.26	
40 R 16127	3003	16	1/2"	2"	1.38	
40 R 16135	3004	32	1/2"	2"	1.43	
40 R 16143	3005	4	5/8"	2"	1.20	
40 R 16150	3006	8	5/8"	2"	1.26	
40 R 16168	3007	16	5/8"	2"	1.38	
40 R 16176	3008	32	5/8"	2"	1.43	
40 R 16184	3009	4	3/4"	3"	1.31	
40 R 16192	3010	8	3/4"	3"	1.50	
40 R 16200	3011	16	3/4"	3"	1.56	
40 R 16218	3012	32	3/4"	3"	1.76	
40 R 16226	3013	4	1"	3"	1.34	
40 R 16234	3014	8	1"	3"	1.46	
40 R 16242	3015	16	1"	3"	1.59	
40 R 16259	3016	32	1"	3"	1.71	
40 R 16317	3017	4	1 1/4"	4"	1.38	
40 R 16325	3018	8	1 1/4"	4"	1.64	
40 R 16333	3019	16	1 1/4"	4"	1.95	
40 R 16341	3020	32	1 1/4"	4"	2.07	
40 R 16358	3021	4	1 3/4"	4"	1.64	
40 R 16366	3022	8	1 3/4"	4"	1.70	
40 R 16374	3023	16	1 3/4"	4"	2.00	
40 R 16382	3024	32	1 3/4"	4"	2.13	

UNIMETRICS Marine Electronic Equipment

UNIMETRICS SEAVOX-25 12 Channel 25 Watt Solid-State VHF/FM Marine Radiotelephone

- Priority Button For Instant Monitoring On Any Channel
- Factory Pre-Tuned And Pre-Aligned
- Solid-State Modular Construction
- FCC Type Accepted For Rules Parts 81 and 83

With Hi-Sensitivity Mike, DC Cable, Crystals Installed For 3 Channels, and Heavy Duty Mounting Bracket.

ONLY
499⁵⁰
No Money Down*



Especially designed for marine use, the Seavox-25 features a special Front Panel "Priority" push button for instant monitoring of U.S. Government E.S.S.A. marine weather stations or any other pre-selected channel. 25 watt output 12 channel radiotelephone VHF/FM operation from 156 to 162.55 MHz. Variable squelch and built-in speaker. Special low power 1 watt level for harbor operations. Operates on 13.8 volts negative ground DC. Self contained power supply and remote control provisions. Supplied with the following frequencies: CHANNEL 6 — 156.3 MHz. Intership Safety Channel, CHANNEL 16 — 155.8 MHz. Intership and Ship-To-Coast Safety and Calling Frequency, CHANNEL WX — 162.55 MHz. Official U.S. Weather Bureau Forecasts. Simplified maintenance with individual modules

and special transmit and receive test sockets. Pre-tuned and aligned for a "Do-it-yourself" installation with recommended antennas. Housed in a watertight metal cabinet with corrosion resistant components. 31 transistors, 15 diodes, 1 IC and 1 FET. Supplied with heavy duty mounting bracket, push-to-talk microphone, DC cable, and three crystals. Size: 9"D x 9"W x 3 1/8"H. Imported. Shpg. wt., 8 lbs.

40 R 69076W Net 499.50
Additional Transmit and Receive Crystals For Shipboard Use Specify Channel. Allow 3 weeks for Delivery.

40 R 69084YZ Net Per Pair 13.50


UNIMETRICS SEACALL 70 Watt Power Hailer and Sensitive Listening Device

- Automatic Fog-Horn, Manual Fog Horn
- Intership Intercom Facilities
- Separate Intruder Alarm Switch

Designed to be used for voice communication between vessels separated by fog, darkness, distance, noise or inclement weather, or for communication with marina when docking. Sounds a continuous fog horn signal every 3 seconds. Functions as a sensitive listening instrument for picking up faint or distant sounds such as: the other vessels, buoys, voices, signals, etc. at night or in fog. Also features intruder alarm provisions. Auxiliary input for tape player, FM tuner, etc. Watertight construction. 30 watt projector/speaker has 90° x 120° dispersion. Size: Speaker, 11"H x 6 1/2"W x 8 1/2"D; Hailer Amplifier, 3 1/2"H x 9"W x 9"D. Shpg. wt., 14 lbs. Imported.

40 R 69092W No Money Down* Net 168.00

including Hailer, Projector Horn, and Microphone.



168⁰⁰
No Money Down*

UNIMETRICS SeaDeep Depth Indicator with Built-In Depth Alarm



ONLY
114⁵⁰
No Money Down*

- Indicates Depths 0 to 200 Ft.
- Depth Alarm Sounding 1 1/2 to 40 Ft.
- Operates on 8 "C" Cells or 12 Volt DC Negative Ground

Reduces the risk of running aground. Built-in buzzer alarm system may be pre-set to any depth from 1 1/2 to 40 ft. For use with any type of vessel, either power or sail. Watertight corrosion resistant construction. 1,440 soundings per minute or 24 per second. Unit size: 6 x 6 1/2" x 6 1/2". Transducer: 2 1/2 dia. x 6 1/4" long. Imported. Shpg. wt., 6 lbs.
40 R 69100 Less Batteries Net 114.50
"C" Batteries for Portable Use (8 req.)
99 R 62572 Net ea. .16

Radio/Compass Direction Finder



19⁹⁵
With Battery and Earphone

- Accurate Navigation Day or Night

An all-in-one navigation system at a low, low price that boaters, fishermen, hunters, hikers, and pilots can now easily afford. Operating on the broadcast band you can home in on stations, fix your position, or correct your course—to compensate for drift, current or detours. Features fluid compass with azimuth points marked in 5° increments. Large rotating outer azimuth ring marked in 1° increments. Operates on inexpensive 9 volt battery (included). Includes earphone for private listening. Solid-State Circuitry. Shpg. wt., 2 1/2 lbs.
42 R 21099L Net 19.95
Extra 9 V battery for above. Net .29
99 R 60212 Net .29

Sonar DC-480 Combination Chart and Flasher Depth Recorder



249⁹⁵

Complete With Transducer, Gimbal, Fairing Block

No Money Down*

A highly sensitive depth recorder which both records your voyage as you sail and provides an instant flashing indication for safe navigation. The unit can serve as a reliable navigational guide in unfamiliar channels and to help find schools of fish and underwater wrecks. Illuminated two color chart is calibrated from 0 to 120, 120 to 240 ft. Has 4"x6" viewing area. 360° flasher dial indicates 0 to 480 ft. Takes 5 soundings per second. Only 5 amps. current drain. Size: 10 3/4"W x 6 3/8"H x 6 3/4"D. For 12 VDC positive or negative ground. Shpg. wt., 12 1/4 lbs.
40 R 43238W Net 249.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 433

MONITOR

State, County and
Municipal Police
Fire Department

Civil Defense
Trucking
Highway Maintenance

Forestry
Aviation
Conservation


Petroleum and
Industrial Activities
Railroads

LAFAYETTE POLICE AND FIRE DUAL BAND SOLID STATE FM RECEIVER

2 RECEIVERS IN 1

2 BANDS: 30-50 MHz
144-174 MHz

**2 Crystal Positions
In Each Band**



PF-200

CRYSTAL CONTROL PLUS TUNEABLE RECEPTION

ONLY **99⁹⁵**
No Money Down*

- 117VAC and 12 VDC
- 1 IC + 1 FET + 13 Transistors + 9 Diodes
- Separate, Large Tuning Dials
- Sensitivity, Less Than 1 μ V. for 20 db Quieting
- Tape Recorder Output Jack
- Headphone Jack for Private Listening
- Receives U.S. Weather Bureau Reports

Lafayettes' superb dual band, FM monitor receiver has been especially engineered for outstanding performance and dependability. The PF-200 covers both the high and low VHF communications bands, is fully tuneable and can be crystal controlled for reception of any two frequencies in either band. It also tunes to and receives 162.55 MHz U.S. Weather Bureau reports in parts of the country where these reports are broadcast. The PF-200 features a highly sensitive superheterodyne circuit that includes tuned RF and mixer stage with F.E.T., 3 ceramic IF filters for exceptional selectivity, and an integrated circuit for efficient FM detection. Its 100% solid state design offers top reliability and instantaneous monitoring of, and response to, emergencies. Built-in universal power supply assures continuous monitoring under any conditions since it operates on both 117VAC and 12 VDC (negative ground only). The

front panel features two large individual tuning dials for low and high bands, 2 selector switches for Xtal or tuneable reception, one for each band, and a variable Squelch control that lets you silence the receiver during no signal conditions. The PF-200 is also distinguished by professionally designed neatly contrasting front panel, knobs and enclosure. A large built-in speaker, an external phone jack for private listening and a tape recorder output jack are also included. Size: 13 $\frac{3}{8}$ "x7 $\frac{1}{2}$ "x4 $\frac{1}{4}$ "H. Shpg. wt. 10 $\frac{1}{4}$ lbs. 99 R 25983W Less Crystals. See Below for Crystals Net 99.95

Ground Plane Antennas. Shpg. wt., 4 lbs.

40 R 01178W 30-50 MHz	Net 9.50
40 R 01160W 130-174 MHz	Net 7.50

NEW! LAFAYETTE POLICE AND FIRE 3-BAND FM RECEIVER

3 BANDS: 30-50 MHz.
144-174 MHz.
450-470 MHz.

**2 Crystal Positions
In Each Band**

ONLY **179⁹⁵**
No Money Down*



Delivery December 15, 1971

Model PF-300

CRYSTAL CONTROL PLUS TUNEABLE RECEPTION ON ALL BANDS

- For 117 VAC Base Station and 12 VDC (Negative ground only) Mobile Operation
- 2 IC's + 3 FET's + 20 Transistors + 11 Diodes
- Sensitivity: 1 μ V. for 20 db Quieting
- Adjustable Broad and Sharp Selectivity On All 3 Bands
- Illuminated Jewel Indicators for UHF, VHF and Low Band Modes
- Headphone Jack for Private Listening

An outstanding universal FM monitor receiver for the 450-470 MHz UHF band, 144-174 MHz VHF band and 30-50 MHz low band. The PF-300 is fully tuneable and can be crystal controlled for reception of any two frequencies on all 3 bands. Receives U.S. Weather Bureau reports on 162.55 MHz. In parts of the country where they are broadcast. May be tuned to either wide or narrow-band razor sharp selectivity. Front panel features large tuning dials—one for 144-174 MHz and one for 30-50 and 450-470 MHz; concentric selector switches that select the desired band and selectivity; switches for crystal or tuneable reception for each band; and variable squelch control that silences the

receiver during no signal conditions. The PF-300 also features a large built-in speaker, phone jack for private listening, tape recorder output jack, and UHF, VHF and Low Band antenna jacks. A built in universal power supply permits operation on 117 VAC and 12 VDC (negative ground only). Size: 13 $\frac{3}{8}$ "x7 $\frac{1}{2}$ "x4 $\frac{1}{4}$ "H. 99 R 26163 Shpg. wt., 11 lbs. Net 179.95

Ground Plane Antennas. Shpg. wt., 4 lbs.	
40 R 01178W 30-50 MHz	Net 9.50
40 R 01160W 130-174 MHz	Net 7.50
40 R 01202 450-470 MHz	Net 24.95

CRYSTAL CERTIFICATE FOR PF-200 AND PF-300

Send filled-out certificate, one for each crystal, to manufacturer. Mfr. ships crystal directly to you postpaid within 30 days. Specify Exact

Monitoring Frequency.
40 R 82103Y Certificate. No C.O.D. Net 5.95

MONITOR

Business Service
Taxicabs
Railroads
Auto Emergencies

Police Department
Fire Department
Special Emergency
Local Government



LAFAYETTE

VHF Monitor Receivers

POLICE AND FIRE SOLID STATE MONITOR RECEIVERS



Mobile: For Car, Truck, Boat, etc.

Micro P-100 (148-174MHz.)

Micro P-50 (30-50 MHz.)

Tuneable Plus 2 Crystal Positions

- Self-contained 117 Volt AC and 12 VDC Supply
- Hear U.S. Weather Forecasts on Micro P-100†

Only
79⁹⁵

No Money Down*

Discover the everyday heroics in your community! Listen and thrill to the excitement of urgent police broadcasts, fire squads in action, to ambulances and to other public service communications on Lafayette's "Micro" monitor receivers. Monitor the U.S. Weather forecasts and disaster warnings on the Micro P-100†. Their compact size (13 1/4 x 4 7/8 x 7 3/4" D.) permits convenient mobile and base operation. Exceptional features include tuneable plus 2 crystal receive positions, better than 1 μ v sensitivity for 20 db S + N/N, 3 ceramic IF filters for superior selectivity, variable squelch, 2 watt audio output, and professional styling with an attractive illuminated dial. The Micro P-50 and Micro P-100 include built-in fused 12 volt DC (neg. ground) and 117 VAC 60 Hz. supplies. The Micro P-450 operates on 12 volts DC (neg. ground) as is and on 117V AC with an optional AC supply. All units include power cables and mounting bracket. Easy portable operation with optional power pack. Imported. Shpg. wt., 5 lbs. 99 R 26122W Micro P-100 (148-174 MHz) Net 79.95 99 R 26064W Micro P-50 (30-50 MHz) Net 79.95



Micro P-50, Micro P-100



Micro P-450 with HB-512

Base: For Home, Office, etc.

Micro P-50, P-100,
P-450 with HB-509A



Portable

NEW! MICRO P-450 (450-470 MHz.)
Tuneable Plus 2 Crystal Positions

- Self-Contained 12 VDC Supply
- Operates on 117 VAC with optional HB-512 Base Supply

Only
89⁹⁵

No Money Down*

99 R 25843W Micro P-450 (450-470 MHz) Net 89.95
HB-509A Portable Battery Pack with shoulder strap, battery strength meter and antenna. Less batteries. Shpg. wt., 3 1/2 lbs.
99 R 32260 For Micro P-50, P-100, and P-450 Net 19.95
Alkaline Batteries for HB-509A (8 req.) Shpg. wt., 4 oz. ea. Net ea. .48
99 R 63802 Alternate Nicad Batteries for HB-509A (10 req.) Net ea. 3.90
32 R 48887 Shpg. wt., 5 oz. ea. Net ea. 1.90
HB-512 AC Supply Permits operation of Micro P-450 on 117 volt AC 60 Hz. and charges nicad batteries used in HB-509A. Net 19.95
99 R 32278 Shpg. wt., 4 1/4 lbs. Net 19.95
CRYSTAL CERTIFICATE FOR MICRO P-50, P-100 and P-450. Send filled-out certificate, one for each crystal, to the manufacturer. Mfr. will ship crystal directly to you, postpaid, within 30 days. Specify Exact Monitoring Frequency.
40 R 82103Y No. C.O.D.'s Net ea. 5.95
†Consult your local weather bureau for reception in your area.

POLICE AND FIRE SINGLE BAND SOLID STATE FM RECEIVERS

4 IC's + 13 Transistors + 9 Diodes + 2 Thermistors



Model PF-30
30-50 MHz

ONLY

79⁹⁵

No Money Down*

Model PF-60
152-174 MHz

- 4 IC's Plus 12 Transistors For PF-30
- 117 VAC and 12 VDC Operation
- Phone Jack For Private Listening
- Tape Recorder Output Jack

CRYSTAL CONTROL PLUS TUNEABLE RECEPTION

An advanced solid-state band FM monitor receiver that covers the high or low bands with excellent sensitivity. These monitors are fully tuneable or can be crystal controlled on a single frequency. Outstanding performance results from meticulously engineered solid state superheterodyne circuitry that includes 4 IC's in the IF stages, plus tuned RF and mixer stages. Its solid state circuit permits instantaneous monitoring of, and response to, emergency situations. Features rugged design for trouble-free operation and has universal power supply for either normal 117 VAC operation or 12 VDC battery operation for field use or during emergencies. Model PF-60 can receive 162.55 MHz U.S. Weather Bureau reports in many parts of the country. Front panel controls included are Variable Squelch, On-Off

Volume, Tuning and Selector (Tune Xtal). Size: 13 1/4 x 7 1/2 x 6 5/8" H. Imported. Less crystal.
99 R 25906W PF-60 152-174 MHz. Shpg. wt., 16 1/4 lbs. Net 79.95
99 R 25918W PF-30 30-50 MHz. Shpg. wt., 16 1/4 lbs. Net 79.95
Ground Plane Antenna 130-174 MHz. Shpg. wt., 1 1/4 lbs.
40 R 01160W Net 7.50
40 R 01170W Ground Plane Antenna 30-50 MHz. wt., 4 lbs. Net 9.50
Crystal Certificate for PF-30 and PF-60. Send filled-out certificate, one for each crystal, to manufacturer. Mfr. ships crystal directly to you, postpaid, within 30 days. Specify exact monitoring frequency. No C.O.D.'s.
40 R 82103Y Net 5.95

*See Page 22 for Full Credit Details on Easy Pay Plan


Lafayette Cat. No. 720 435

UNIMETRICS DIGI SCAN-8


FM/VHF and FM/UHF Monitor Scanners

1 2 3

THE FIRST
8-CHANNEL VHF/UHF
CRYSTAL CONTROLLED
FM RECEIVER SCANNERS
with
DIGITAL READOUT!



"Drop-In" Interchangeable Front End Modules for Converting the Digi Scan-8 to either Low VHF/FM, High VHF/FM, or UHF/FM.



Individual channel "Lock-Out" Switches for channel programming.

"Easy-Open" compartment allows for instant crystal changing. No soldering required! No Removing Cabinet!

- 3 Models to Choose from:**
- Low Band VHF/FM—30-50 MHz
 - High Band VHF/FM—147-174 MHz
 - UHF/FM—450-470 MHz
- As Low As 139⁹⁵** Includes AC Cable, DC Cable and Mounting Bracket. No Money Down*
- Digital Read-Out Indicates the Channel Receiving a Signal
 - Automatic Scanning Stops When a Signal is Received, Continues Scanning After Transmission is Over
 - Listen to Police and Fire Calls on any one of 3 Bands
 - Manual Channel Selection • Variable Squelch Control
 - Will Operate on 12 volt DC or 117 VAC

Digi Scan-8 is the ultimate in an 8-channel, crystal controlled FM Monitor Scanner. Digi Scan-8's exclusive bold flashing digital readout indicator automatically seeks a voice signal on any of eight programmed channels. Digital Readout indicates which channel is receiving, and after transmission is over, automatically continues scanning. The interchangeable "Drop In" front end modules offer amazing versatility and economy. You can convert any Digi Scan-8 for either low band FM, high band VHF/FM, or UHF/FM monitoring. Ultra sophisticated solid state engineering will enable superior and accurate monitoring of the Public Service Band, which includes Fire, Police, Local Government, Special Emergency, VHF/FM Marine, Weather, and many other exciting channels. Deluxe features include: double conversion superhetrodyne circuit with .5 μ V sensitivity for 20 db quieting, variable squelch control, pushbutton switches for selecting automatic scanning or manual scanning mode, separate push-button On/Off switch, Built-in speaker plus back panel external speaker jack and professional PL-259 antenna jack, and attractive vinyl and metal cabinet with die-cast front panel. The all solid state circuit permits very low current on 12 volt DC for continuous monitoring with very little battery drain. Digi Scan-8 comes complete with all mounting hardware, AC and DC line cords. Size: 9W x 3 1/4 H x 7 D. Shpg. wt., 8 1/2 lbs. Imported. For 117 VAC 60 Hz and 12 VDC.

The Digi-Scan-8 operates properly within a specific frequency spread for each band, for 30-50 MHz the spread is 5 MHz. For 450 to 470 MHz and 147 to 174 MHz the spread is 7 MHz. When ordering specify Frequency Band and Frequency spread, i.e., Frequency Band 147-174 MHz, Frequency spread 351 to 158 MHz. No COD's.


40 R 69001Y	Digi Scan-8	For 30-50 MHz	(5 MHz spread)	139.95
40 R 69019Y	Digi Scan-8	For 147-174 MHz	(7 MHz spread)	139.95
40 R 69027Y	Digi Scan-8	For 450-470 MHz	(7 MHz spread)	154.94

Interchangeable Front End Modules. Shpg. wt., 6 oz. Imported.				
40 R 69035Y	For 30-50 MHz	(5 MHz spread)	12.95
40 R 69043Y	For 147-174 MHz	(7 MHz spread)	12.95
40 R 69050Y	For 450-470 MHz	(7 MHz spread)	22.95

Crystal Certificate for Digi-Scan-8 Monitors. Fill one out for each crystal, send directly to manufacturer.

40 R 82103Y Net 5.95

REGENCY 8 Channel 2-Band Hi/Lo Monitor Scanners



169⁰⁰ ea.
Less Crystals

- Automatic Cross Band Scanning
- Instant-On Solid State Circuitry

3 Models

TMR8H/LL	144-174MHz/33-39MHz
TMR8H/LM	144-174MHz/37-43MHz
TMR8H/LH	144-174MHz/41-47MHz

No Money Down

Three models to choose from. Automatic Cross Band Scanning. Automatically Monitors (SCANS) any mixture of 8 high and low band FM channels or Manual Pushbutton Channel Selection. Illuminated read-out lights indicate receiver is scanning for signals. When receiving a signal, it locks on, listens to signal until transmission is over, then resumes scanning. Audio Output: 5 watts; Sensitivity: Low Band—0.5 μ V, High Band—0.7 μ V. AC or 12 VAC Mobile operation. Comes complete with AC or DC power cords, mobile mounting bracket, removable telescope antenna, 4" built-in speaker and external speaker terminals. Size: 2 1/2 x 5 1/2 x 7 1/2". Shpg. wt., 7 lbs. For 117 VAC or 12 VDC. Specify High Band Frequency Coverage. Frequency Spread should not exceed 8 MHz. No C.O.D.'s (Allow 3 weeks for delivery.)

Stock No.	Model	Net ea.
40 R 60232Y	TMR8H/LL 144-174MHz/33-39MHz	169.00
40 R 60240Y	TMR8H/LM 144-174MHz/37-43MHz	169.00
40 R 60257Y	TMR8H/LH 144-174MHz/41-47MHz	169.00

Crystal Certificate for above models. Fill-out one for each crystal, send directly to manufacturer.

40 R 82103Y Net 5.95

UHF and VHF Police-Aircraft Receivers & Converters

NEW! Regency 8-Channel 450-470 UHF Monitorradio/Scanner

Only **159⁹⁵**

with AC and DC Power Cords,
Mobile Mounting Bracket, and
Removable Telescope Antenna




Automatically scan your choice of eight 450-470 MHz frequencies. Stops and listens to each transmission. At the end of transmission automatically continues scanning for another signal. Illuminated read out lights. Can also be operated manually. Pushbutton control for each channel. Built-in 4" speaker. Squelch control. Instant-on solid-state circuitry. Audio output 5 watts. Sensitivity: 0.7 microvolt for 20 db quieting. Size 2 1/4" x 5 1/2" x 7 1/2". Shpg. wt., 6 lbs. Specify Frequency Coverage When Ordering. Total Frequency Spread Should Not Exceed 8 MHz ie. 454-462 MHz or 458-466 MHz. No COD's. 40 R 60265Y Model TMR-8U 450-470 MHz. Net 159.95

Crystal Certificate for TMR-8U. Fill-out one for each crystal, send directly to manufacturer. 40 R 82103Y Net 5.95

• Automatically Scan Your Choice of Eight 450-470 MHz Frequencies

NEW SONY TR-8460 PORTABLE AIRCRAFT RECEIVER



49⁹⁵

With Batteries AC Adapter, and Earphone

- Frequency Range 108-136 MHz
- RF Stage For High Sensitivity
- Slide Rule "Cursor Scale" For Precise Tuning
- Squelch Control

Tunes in the most widely used civil aviation frequencies from air-to-ground pilot and controller transmissions, VOR omni-range broadcasts, and low frequency band pilot weather data. Operates on 4 "D" batteries or 117 VAC. "Instant on" solid state circuitry. Swing away carrying handle and telescopic antenna. 3 1/4" dynamic speaker. Size: 5 1/2" H x 10 1/4" W x 2 1/4" D. Imported. Shpg. wt., 3 1/2 lbs.

17 R 33070L No Money Down* Net 49.95

SOLID STATE MOBILE FM-VHF LOW AND HIGH BAND POLICE TUNERS

YOUR CHOICE
39⁹⁵ EA.



- Connects to Existing 12 Volt Neg. Ground AM Car Radio
- Listen to Police Calls, Fire Calls, Mobile Phones
- Tuneable—No Crystals Required

Three Models To Choose From

Model PC-200: 30-38 MHz
Model PC-201: 37-50 MHz
Model PC-202: 150-174 MHz

Hear police calls, fire calls, and mobile phones on your AM car radio. Deluxe solid-state FM-VHF High and Low Band Tuners mount under the dash. Tuneable—requires no crystals, no batteries, no special antenna. Connects in minutes to your existing AM auto radio and antenna. Automatic noise limiter provides exceptionally fine reception of all signals. Specifications: 8 transistors, 4 diodes. Sensitivity 2 μ v at 20db of quieting. Converts FM signals to 870 kHz on AM Band. Compact—only 6 1/2" x 3 1/2" x 1 1/2". For 12 volt Neg. ground systems. Shpg. wt., 2 1/2 lbs.

40 R 36018 Model PC-200—Tunes 30-38 MHz. No Money Down* Net 39.95
40 R 36026 Model PC-201—Tunes 37-50 MHz. No Money Down* Net 39.95
40 R 36034 Model PC-202—Tunes 150-174 MHz. No Money Down* Net 39.95

LAFAYETTE Hand-Held FM/VHF Police and Fire Monitor Radios



- Listen To Police and Fire Calls • Monitor Civil Defense and Public Services
- Receive Regional U.S. Weather Forecasts on 162.55MHz

Only an alert and informed citizen can keep up with the electrifying happenings of our everyday life. Two superb Lafayette FM/VHF receivers bring you live coverage of your city or town's daily drama on either 146-175 MHz or 27-50 MHz police and fire bands. 146-175 MHz receiver tunes to 162.55 and 163.275 MHz U.S. Weather Bureau weather reports and disaster alarms in many parts of the country. Has a built-in 2 1/2" speaker plus an external earphone jack for convenient private listening. Rugged construction and sleek styling combine to give a clear professional type appearance. Operates on 4 penlight batteries (included with set). This ultra-compact unit also features a built-in swivel telescoping antenna and provision for an external antenna. With batteries and carrying strap. Size: 6x2x1 1/2". Imported Shpg. wt., 1 1/4 lbs.

99 R 35313L 146-175 MHz FM VHF Receiver Net 17.95
99 R 35339L 27-50 MHz FM VHF Receiver Net 17.95

ACCESSORIES FOR HAND HELD FM VHF RECEIVERS

Stock No.	Description	Shpg. Wt.	Net Ea.
99 R 35362	117 VAC Adapter	12 oz.	3.95
99 R 62580	Extra "AA" Batteries (4 required)	3 oz.	.10
40 R 79018	Earphone for Private Listening	2 oz.	.59

HIGH BAND

146-175 MHz

17⁹⁵


with batteries and carrying strap

LOW BAND

27-50 MHz

17⁹⁵

with batteries and carrying strap



*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 437

LAFAYETTE Monitor VHF and UHF Antennas

DELUXE LAFAYETTE MOBILE FM VHF ANTENNAS

HIGH BAND MOBILE ANTENNAS

6⁹⁵

- For 130-174MHz
- With 12" Cable • For 450-470MHz

Mobile roof or trunk mount for 130-174MHz or 450-470 MHz operation. Terminates in 3/8" bolt. Whip has set screw-type adapter for easy tuning. Comes with 12' RG-58U cable and PL259 connector pre soldered to the antenna. Length 21½". Shpg. wt., 1 lb.
40 R 01137 Net 6.95

LOW BAND MOBILE ANTENNA

12⁹⁵

- For 30-50MHz
- Features "Rapid-Grip" Trunk-Lid Mount

Less Cable


3 deluxe new base loaded FM-VHF mobile antennas to choose from—30-36MHz, 36-42MHz, 42-50MHz. All 3 antennas include "Rapid-grip" trunk lid mounts for simple and easy installation. No holes to drill. Provides ideal omni-directional signal pattern. Consists of weatherproof phasing transformer, stainless steel whip and cadmium plated "rapid-grip" mount. Overall length 43". Wt. 2 lbs.

40 R 01145W 30-36MHz .. 12.95
40 R 01152W 36-42MHz .. 12.95
40 R 01129W 42-50MHz .. 12.95
20' Coaxial Cable Assembly for above antennas. Terminate with PL-259 on one end and universal lugs on other end.
42 R 70021 Net 2.95

LAFAYETTE MONITOR FM-VHF GROUND PLANE ANTENNAS

As Low As

7⁵⁰



Model LR-145 High Band Monitor

For 130-174 MHz and 450-470 MHz. Lightweight, omni-directional vertical ground plane antenna. 4 Radials are of stainless steel construction. Radiator is of chrome plated brass and highly corrosion resistant. Coaxial fitting on antenna base directly accepts the standard PL-259 coaxial plug. U-bolts are provided to accept up to 1½" diameter masts Shpg. wt., 1¼ lbs.
40 R 01160W Net 7.50

Model LR-40 Low Band Monitor

For 25-50 MHz. Omni-Directional vertical ground plane antenna. 3-solid aluminum radials, cadmium plated steel mounting brackets. Lug-Type connector. U-Bolt supplied to accept up to 1½" masts. Tuning Chart supplied. Shpg. wt., 4 lbs.
40 R 01178W Net 9.50

LAFAYETTE "RANGE-BOOST"™ 2 BAND FM VHF GROUND PLANE COMMUNICATIONS ANTENNA

19⁹⁵

- For 30-50MHz, 130-174MHz
- Boost your FM Receiving Range



An exceptionally efficient ground plane antenna for operation between 30 to 50MHz and 130 to 174 MHz (on the high band, maximum antenna cable length to receiver should be 50 ft. for best efficiency). Comprised of 4 easily assembled drooping elements tuned to 30 MHz and a vertical radiator with a matching transformer and a low and high band collinear collector. Ideal for use with Lafayette FM communications receivers. Constructed of heavy-duty aluminum alloy rods and stainless steel lip section. Antenna comes complete with mounting bracket for 1" pipe or 1¼" tubing. Shpg. wt., 5¼ lbs.
40 R 01053W Net 19.95

UHF Monitor Antennas—Base and Mobile

LAFAYETTE "UHF/RANGE BOOST" 450-470 MHz MONITOR BASE ANTENNA



24⁹⁵

- 4db Receive Gain Over 1/4 Wave Antenna
- Clamp Onto Any Mast Up to 1½" Diameter
- DC Grounded Shunt Fed for Lightning Protection

Get exceptionally high performance! Consists of two 1/2 wavelengths, employing both impedance matching and high Q phasing coils, encased in a weatherproof jacket. Precise factory tuning makes cutting unnecessary. All fittings are made of chrome plated brass for reliable operation and longest possible life. Shunt fed DC grounding provides lightning protection. Gain: 4 db over 1/4 wave antenna across entire band; VSWR: 1.5:1 or better; Antenna Power Rating: 100 Watts; Input Impedance: 50 ohms. Use RG-58/U cable with PL-259 coaxial connector. Shpg. wt., 4 lbs.
40 R 01202W Net 24.95

ANTENNA SPECIALISTS ASP 542 450-470 MHz MOBILE ANTENNA



16⁹⁵

With Quick Grip Trunk Lid Mount No Holes to Drill
Includes 17 ft. RG-58/U Cable and PL259 Connector

- 3 db Gain Doubles Effective Radiated Transmitter Power
- VSWR: 1.5:1 or Better
- Hi Q Phasing Coil

An exceptionally versatile 3 db gain, 450 to 470 MHz mobile heavy-duty antenna designed to fit every professional vehicular requirement. 3 db gain doubles effective radiated transmitter power. Phasing coils are shock-resistant, weatherproof, mounted in the center of the radiating element and encased in jackets. Whips are stainless steel and feature an adapter providing 1¼" adjustment for exact field frequency tuning by raising or lowering the bottom rod without cutting. Input Impedance: 50 ohms; Antenna Power Rating: 100 Watts. Wt., 3 lbs.
40 R 13256W Net 16.95

LAFAYETTE DUAL BAND FM-VHF INDOOR MONITOR ANTENNA

8⁹⁵

- For 30-50MHz 130-174MHz

Dual band indoor antenna enables you to operate your VHF FM communications receiver without having to put up an outdoor antenna. Consists of 2 section stainless steel whip with center loaded coils for 30-50MHz and 130-174MHz. Ideal for use with Lafayette Models PF175, PF60, PF30 FM VHF receivers. Overall length 48". Lug-type connector. Imported. Shpg. wt., 12 oz.
99 R 26106 Net 8.95

NEW! CUSHCRAFT HI-LO FM/VHF MONITOR STIK

Only

16⁹⁵

- 2 Antennas in 1
- For 30-50 MHz.
- For 135-170 MHz.

Mounts on mast, tower or attaches to window. Use nearly anywhere. Automatically receives high or low VHF band. Unusual vertically polarized design pulls in hard to reach signals. Accepts 52 ohm coax cable and PL-259 connector. Complete instructions supplied. Shpg. wt., 4 lbs.
40 R 19246W Net 16.95

Assorted Lafayette Citizens Band Antennas

LAFAYETTE 1/2 WAVE CB MARINE ANTENNA

Only **24⁹⁵**

With 22 Ft. Coax Cable, Connector, and Mounting Hardware

- No Ground Required
- Center Loaded
- Pre-tuned

Top performing CB Marine Antenna—can be mounted on a wooden or fiberglass boat. Single hole mount— $\frac{3}{4}$ " diameter stud, 2" long. Base cover cap is white polypropylene. Center loaded high efficiency Tuned Circuit. Stainless steel whip. Overall height 58 $\frac{1}{2}$ ". Feedpoint 52-ohms. Shpg. wt., 4 lbs. 42 R 01612W Net 24.95



LAFAYETTE MOBILE AM TO CB ANTENNA CONVERTER

6⁹⁵

- 1 Antenna Now Does the Job of 2 Antennas
- Converts Any AM Automobile Antenna to a Highly Efficient Combination CB and AM Antenna

Specialty designed Lafayette AM to CB antenna converter consisting of a weather-proof loading coil with a universal mount and adjustable matching 7/4" stub. Covers entire 27 MHz Citizens Band. Easily attaches to your existing AM automobile antenna. Includes dividing harness which couples your new combination AM and CB antenna directly to your Citizens Band Transceiver and AM auto radio. Imported. 99 R 31163 Shpg. wt., $\frac{3}{4}$ lb. Net 6.95



DELUXE LAFAYETTE BASE-LOADED FIBRE-GLASS CB ANTENNA

17⁹⁵

with 17 ft. of RG58/U Cable and PL-259 Connector
Made in U.S.A.

NEW

- Our Best Mobile Antenna
- "Pultrusion" Fibre Glass Whip
- Base Loading Coil
- Tapered Shock Spring

Only 46" long. Has high strength, and is extremely resistant to corrosion. Gleaming white "Pultrusion" fiberglass whip. Shock spring and all exposed metal fittings are chrome plated. May be mounted on any flat surface with unique $\frac{3}{8}$ " snap-in mount. Solderless lead connection with 17 ft. of RG58/U Cable. Shpg. wt., 5 lbs. 42 R 01638 Net 17.95



LAFAYETTE CENTER-LOADED CB WHIP ANTENNA

Only **4⁹⁵** With PL259 Connector

- Weather-Proof
- For Base Station or Portable Use
- Adjustable Whip Stub

Sturdy, attractive, portable chrome plated center-loaded whip antenna. Terminates in a PL-259 connector. Adjustable whip is 1 $\frac{1}{4}$ " in length. Also provided is an additional whip stub, 12 $\frac{3}{4}$ " total length. Center loading coil is completely weather-proof. Imported. Shpg. wt., $\frac{1}{2}$ lb. 99 R 31890 Net 4.95




LOW COST LAFAYETTE 1/4 WAVE GP ANTENNA

7⁹⁵

Made in U.S.A.

Sturdy, High performance—low cost, trouble free ground plane antenna for C.B. High quality solid aluminum elements—steel mounting bracket. 360° polar pattern provides complete 23 channel coverage. Overall height 106". Terminates with SO239 connector. Accepts PL259. SWR 1.5:1 or better. Shpg. wt., $\frac{3}{4}$ lbs. 42 R 01620W Net 7.95



LAFAYETTE CENTER-LOADED FIBRE-GLASS CB COWL MOUNT ANTENNA

8⁹⁵ With 5' of Cable Easily Mounts On Cowl or Rear Deck

Only 38" high but performs like 102" antennas. Designed for cowl mounting, provides an excellent radiation pattern. Substitutes for conventional 1/4 wave whips as well as base-loaded antennas in the 27 MHz band. The four foot whip eliminates the possibility of striking overhead objects. Specially designed rocker support assures 8-point grounding and permits mounting up to 35° angle on fender, cowl or rear deck—Fits any 15/16" to 1/4" mounting hole. Complete with 5 ft. of RC-58/U cable. Shpg. wt., 2 lbs. 42 R 01125W Net 8.95




DELUXE LAFAYETTE UNIVERSAL BASE LOADED CB WALKIE-TALKIE ANTENNA

1⁹⁵

- Replaces Broken Or Existing Recessed Antenna
- Instantly Attaches Without Tools

Universal base loaded CB walkie-talkie antenna. Only 16" in length. Replaces broken or existing recessed antenna. Instantly attaches without tools. Can be tuned to compensate for antenna length. Made of non-corrosive materials. Operates equal to long telescoping antennas. 99 R 32187 Wt. $\frac{1}{4}$ lb. Net 1.95



LAFAYETTE Citizens Band Walkie-Talkie Antenna Replacement Guide

Designed for the various Lafayette "Walkie-Talkie" portable CB Transceivers indicated. Will also fit many of the other "Walkie-Talkie" units manufactured by companies other than Lafayette. Check the specs of the antennas listed on the chart below for the antenna best suited to your present "Walkie-Talkie". All measurements are in inches. Imported. Average shpg. wt., 1/2 lb.

Antenna Stock No.	Diam. of Sections	Base	Collapsed		Extended		For LAFAYETTE Walkie-Talkie Model	Net Ea.
			Length	Length	Length	Length		
99 R 30082	12	1/2	6	52 $\frac{3}{4}$	53 $\frac{3}{4}$	51 $\frac{1}{2}$	HE-29 HE-29B	1.95
99 R 30443	11	7/16	5 $\frac{3}{4}$	51	51 $\frac{1}{2}$	51 $\frac{1}{2}$	HE-29C HE-29D	1.95
99 R 31114	11	13/32	5 $\frac{7}{8}$	51 $\frac{1}{4}$	51 $\frac{1}{4}$	51 $\frac{1}{4}$	HE-29E	1.95
99 R 30371	11	1/2	6 $\frac{1}{4}$	54 $\frac{1}{2}$	54 $\frac{1}{2}$	54 $\frac{1}{2}$	HA-60, HA-61, HE-86, HE-88, HA-100, 100A, 100B	1.95
99 R 30389	9	7/16	7 $\frac{1}{4}$	52 $\frac{3}{4}$	53 $\frac{1}{2}$	53 $\frac{1}{2}$	HE-25, HE-88, HA-711	1.95
99 R 30397	11	7/16	5 $\frac{3}{4}$	50	50	50	HE-66, HE-82, HE-83	1.95
99 R 30405	9	3/8	5 $\frac{7}{8}$	43	43	43	HA-70, HA-70A	.98
99 R 31122	8	5/16	5 $\frac{7}{8}$	36 $\frac{1}{2}$	36 $\frac{1}{2}$	36 $\frac{1}{2}$	HA-70B, HA-70C	.98
99 R 31130	11	3/8	4 $\frac{5}{8}$	38	38	38	HA-130, HA-130A	1.49
99 R 30173	10	7/16	7	58	58	58	HA-150	1.95
99 R 30074	11	7/16	7 $\frac{1}{4}$	62 $\frac{3}{4}$	62 $\frac{3}{4}$	62 $\frac{3}{4}$	HA-300, HA-300A	2.25
99 R 31155	11	7/16	7	58	58	58	HA-99, HA-303	2.95
99 R 31387	11	7/16	7	58	58	58	HA-300B	2.25
99 R 32021	8	5/16	7 $\frac{1}{4}$	49 $\frac{1}{4}$	49 $\frac{1}{4}$	49 $\frac{1}{4}$	HA-132	1.95
99 R 32039	9	3/8	7 $\frac{3}{8}$	55	55	55	HA-73A	1.95
99 R 32047	11	3/8	6	49	49	49	HA-73B, HA-305, HE-210A, HA-62	1.95
99 R 32054	10	3/8	7	55	55	55	HA-310, HA-310A	1.95
99 R 32070	10	3/8	8 $\frac{3}{4}$	67 $\frac{1}{2}$	67 $\frac{1}{2}$	67 $\frac{1}{2}$	Dyna-com 2, 2A, 3 and 3A	2.95
							Dyna-com 5 & 5A, 6 & 12	2.95

LAFAYETTE Base Station Citizens Band Antennas

DELUXE HEAVY DUTY LAFAYETTE 4 ELEMENT GROUND PLANE CB ANTENNA



- The Ideal Antenna For Your CB Base Station
- High Efficiency Ground Plane Antenna

12⁹⁵

Made in U.S.A.

- All Aluminum Construction
- Accepts PL-259 Connector

Solid aluminum 108" heat-treated radials and radiator. Elements supplied in two 54" lengths joined by threaded coupling nuts. Radial droop for 50 ohm match. Accepts 1 1/4" tubing, RG-58/U cable and PL-259 connector. Less mast and coax. Shpg. wt., 4 1/2 lbs.

42 R 01562W

Net 12.95

LAFAYETTE'S 3-ELEMENT VERTICAL BEAM CB ANTENNA



18⁹⁵

MADE IN U.S.A.

- Multiplies Power 8 Times
- Completely Precision Tuned and Ready to Assemble and Install
- Steel Parts Iridite Treated to MIL Specs

An exceptionally high gain, directional antenna system for Citizen's Band communications. It develops a forward gain of 8 db. Front-to-back ratio is 25 db; front-to-side, 40 db. 50 ohm feedline match for maximum efficiency. Comes with bracket for vertical or horizontal mounting. The 1 1/4" O.D. aluminum boom is 8 feet long, 3/8" to 3/4" O.D. aluminum elements are approximately 16 1/2 ft. long. All steel hardware is iridite treated to MIL specs. Accepts up to 1 1/2" mast. Completely factory pretuned. Furnished with simple mounting instructions. Less mast and coax cable. Shpg. wt., 7 3/4 lbs.

42 R 01133W

Net 18.95

LAFAYETTE "RANGE-BOOST/II"TM END FED 1/2-WAVE CB ANTENNA



Static Clover Leaf

19⁹⁵

Made in U.S.A.

- Heavy Duty Mounting Bracket
- Static Clover Leaf Ball Design Reduces Receiver Noise
- 3.75 db True Omni-Directional Gain
- VSWR—1.5 to 1 or less
- Signal to Noise Improvement of 6-20db

The "Range Boost/II" 1/2-wave CB base station antenna is one of the most popular of Lafayette's famous line of high performance CB antennas. Specially designed anti-static cloverleaf ball drastically reduces receiver noise by continuous dissipation of static discharge. Offers a 3.75 db true omni-directional gain. Tremendous signal to noise ratio improvement of 6-20 db giving you very clean reception. VSWR is 1.5:1. Includes a phasing transformer, rubber covered for moisture resistance. Vertical radiator consists of 3 seamless aluminum tube sections topped by a solid aluminum 108" top section. 3 54" radials provide proper transmission line decoupling. New heavy duty mounting bracket. Direct ground lightning protection. 50 ohm. 17'6" over-all length. Accepts up to 1 1/2" masts PL-259 cable connector. Shpg. wt., Less mast and coax. 6 1/2 lbs.

42 R 01448W

Net 19.95

DELUXE LAFAYETTE SUPER RANGE-BOOST/IITM OMNI-DIRECTIONAL BASE STATION CB ANTENNA



4 Element Static Ball

29⁹⁵

Made in U.S.A.

- End Fed 1/2 Wave
- 4 db Gain Delivers 13 Watts E.R.P.
- Hi-Q Phasing Coil Optimizes Impedance Match
- VSWR 1.4 to 1 or less
- Loaded Ground Radials For Optimum Performance

Our best base station CB antenna. 1/2-wave end fed 4 db omni directional type. Huge loading coil will safely handle 50 to 75 times normal CB power. Rubber covered, HI-Q phasing coil optimizes impedance match, VSWR less than 1.4:1. Three ground radials (54") are base loaded for optimum performance. 4 db gain delivers 13 watts E.R.P. (effective radiated power). Constructed of seamless aircraft tubing and corrosion-proof steel for best weatherability and wind resistance. Rated to withstand 100 mph winds. Four element static ball passes off perpendicular static smoothly and reduces receiver noise. Direct ground lightning protection. Overall height 18 ft. Stainless steel mounting hardware will accommodate up to 1 1/2" mounting mast. Less mast and coax.

42 R 01604W Shpg. wt., 8 1/2 lbs. Net 29.95

POLYFOAM COAX CABLE ASSEMBLY. FOR BASE STATIONS



As Low As **9⁶⁵**

Complete transmission line packages designed for better CB operating efficiency. The polyfoam dielectric insures low line loss important in getting the most from your base station. Ready to use. PL-259 connectors on both ends.

Stock No.	Type	Length	Wt.	Net
42 R 09102	RG8/U-50 ohms	50 ft.	4 1/4 lbs.	9.65
42 R 09110	RG8/U-50 ohms	100 ft.	9 3/4 lbs.	16.95

LAFAYETTE LIGHTNING PROTECTOR



3⁹⁵

Designed to eliminate static build up on coaxial cables. Provides a constant drain off, reducing chances of a direct lightning strike and in many cases eliminating noise problems. Employs one PL-259 plug and one DKCB connector.

42 R 20018 Shpg. wt., 1/4 lb.

Net 3.95

Steel Mast For Mounting CB Antenna

10 ft. 16 gauge Gold Kote steel mast—1 1/4" O.D. Shpg. wt., 4 lbs.
18 R 63281WX Net 3.19

LAFAYETTE Mobile Citizens Band Antennas

LAFAYETTE STAINLESS STEEL CB MOBILE ANTENNA

- 102" Stainless Steel Whip For Optimum 11-Meter Performance
- Heavy-Duty Cadmium Plated Stainless Steel Spring
- Aluminum Swivel Ball Jointed Mount Base

Only

8⁹⁵

Made in U.S.A.

Aluminum swivel mount base designed to be mounted on any surface. Plated steel spring holds rod in properly adjusted position and prevents rod damage from shocks and blows. Stainless steel whip for resiliency and strength. Less cable. Has lug terminals for 42 R 70021 cable assembly. Shpg. wt. 5 lbs.

42 R 01554WX

Net 8.95



DELUXE LAFAYETTE HEAVY-DUTY MOBILE CB-AM ANTENNA

- One Antenna Does the Job of Two
- Low Loss Cables
- All Connections Under Dash


9⁹⁵

with all connecting cable

Deluxe Cowl mounted antenna doubles for Citizens Band and broadcast reception. Eliminates two antennas on your car. Sturdy construction with heavy chrome plate. 46" long collapsing to 31". Fits the 7/8" to 1 1/4" space left by auto antenna. Includes automatic dividing harness, 1' cable to AM set, 2' cable to CB rig and 5' cable with PL-259 plug to antenna. Small divider unit fits under dash. Imported. Shpg. wt., 1 1/2 lbs.

99 R 30603W

Net 9.95



LAFAYETTE CENTER-LOADED MOBILE CB GUTTER CLAMP ANTENNA

- Easily Snaps on Rain Gutter of automobile
- Offers Outstanding 11 Meter Performance
- Portable—Easily Removable When Not In Use—Prevents Theft or Damage



7⁹⁵

with 12 ft. coaxial cable

Portable center-loaded CB antenna is ideal for the CB'er. Easily removable when not in use—prevents theft or damage. Gutter clamp snaps on rain gutter of automobile. Heavy spring assures positive grip. Clamp is heavily plated to resist corrosion. Only 20 inches in length—outstanding 11 meter performance. SWR 1:1. Furnished with 12' of RG58/U cable with PL-259 connector. Imported. Shpg. wt., 1 1/4 lbs.

99 R 31882

Net 7.95



LAFAYETTE BASE LOADED TRUNK MOUNTED MOBILE ANTENNA

- No Visible Holes in Car
- Trunk Groove Mount
- Installs in Seconds
- Phasing Transformer Completely Weatherproof
- 39" Stainless Steel Whip

10⁹⁵

MADE IN U.S.A.

Exciting mobile antenna from Lafayette permits the CB'er to mount his antenna without any visible holes on his car. Special trunk groove mount requires just two tiny 7/32" holes in groove of car trunk lid. Antenna holds securely and is adjustable to all cars. Features base loaded, weatherproof phasing transformer (only 4" high, 1" diameter) and a 39" stainless steel whip. Complete with all mounting hardware, simple mounting instructions. Less cable. Shpg. wt., 1 1/4 lbs.

42 R 01455

Net 10.95



LAFAYETTE BASE LOADED "AUTO-TOP" CITIZEN BAND ANTENNA

- Automobile rooftop application effects ideal omnidirectional signal patterns
- Mounts neatly from outside vehicle in 3/4" hole
- Base loaded Phasing Transformer, completely weatherproof
- 39" Stainless Steel whip

Only

8⁹⁵

Made in U.S.A.

The Lafayette Base Loaded "Auto-Top" Citizens-Band antenna offers the CB'er the ideal omni-directional signal pattern with very low signal to noise. This quality antenna consists of an inconspicuous base loaded, neutral gray weatherproof phasing transformer (only 4" high, and 1" in diameter), a 39" stainless steel whip, and all mounting hardware including complete and simple mounting instruction sheets. Antenna mounts in 3/4" hole. Comes less cable. Shpg. wt. 2 lbs.

42 R 01208W

Net 8.95



LAFAYETTE "RAPID-GRIP" MOUNT BASE LOADED MOBILE CB ANTENNA

- "Rapid-Grip" Mount Provides Permanent Antenna Installation In Seconds Without Drilling Holes



"Rapid-Grip" mobile antenna is especially suitable for trunk mounts. No holes to drill. Slips over trunk lip. Cable is completely hidden. Neat, trim, professional appearance. Offers ideal omnidirectional signal pattern. Water resistant body seal. 39" Stainless Steel whip. Base loaded phasing transformer completely weather proof. Overall length 43" Less cable. Has lug terminals for 42 R 70021 cable assembly. Wt., 11 oz.

42 R 01521

Net 12.95

Only

12⁹⁵

Made in U.S.A.



LAFAYETTE CB BUMPER MOUNT ANTENNA WITH STAINLESS STEEL STRAP

- Cadmium Plated Bumper Mount with Plated Steel Strap
- 102" Stainless Steel Whip
- Heavy-Duty Cadmium Plated Steel Spring

Only

10⁹⁵

Made in U.S.A.

An outstanding Lafayette CB antenna featuring a full-size 102" stainless steel whip and a fully adjustable steel plated mount with a steel plated strap which was specially designed to fit most cars. Heavy duty plated steel spring is built for extremely rugged mobile use. Less cable. Shpg. wt., 5 lbs.

42 R 01596WX

Net 10.95



20 FT. COAXIAL CABLE ASSEMBLIES

(A)

(B)



These cable assemblies are necessary for connection between Citizens Band Transceiver and Antenna.

TYPE A—Consists of 20 ft. RG-58/U cable with PL-259 plus UG-175/U on both ends. Required for Ground Plane and Mobile Antennas terminating in a coaxial jack. Shpg. wt., 12 oz.

42 R 70013 Type A; 20 ft. length

Net 3.25

TYPE B—Same as Type A except one end is terminated with PL-259 plus UG-175/U and other end with universal ring type terminal lugs for mobile antennas. Shpg. wt., 11 oz.

42 R 70021 Type B; 20 ft. length

Net 2.95

Antenna Specialists Citizen Band Antennas



Base Station Antennas

"SUPER MAGNUM" MODEL M-117 1/2-WAVE CB BASE STATION ANTENNA

32⁹⁵

No Money Down*

- Stati-Lite Ball for Additional Dissipation of Static Electricity
- HI"Q" Phasing Transformer Provides Resonance over entire CB Band



Rigid aluminum vertical radiator provides maximum improvement in signal-to-noise of 6 db, a 3.75 db of true gain as compared to a flat ground plane antenna. Top mounted orbital ball drastically reduces static discharge noise. Full 1/2 wavelength 108" radials offer maximum RF decoupling... low radiation angle intensifies signal coupling. Includes powerful phasing transformer and mounting hardware to take up to 1 1/2" masts. Treated against corrosion. Easy to install. Shpg. wt., 9 1/2 lbs.

42 R 10019W

Net 32.95

M227 "MIGHTY MAGNUM III" 1/2 WAVE OMNI-DIRECTIONAL CB BASE STATION ANTENNA

36⁹⁵

No Money Down*

- Power-Tip Radials Lower Radiation Angle
- Phasing Coil Optimizes Impedance Match—VSWR Less Than 1.4:1
- "Stati-Lite Diamond" Reduces Receiver Noise



Ruggedly constructed, omni-directional, base station antenna with 4 db gain. Increases radiated power to 13-watts. "Power-Tip" radials lower radiation angle and increase range. "Stati-Lite Diamond" reduces receiver noise. Phasing coil optimizes impedance match—VSWR less than 1.4:1. Completely waterproof transformer jacket. Four electrically shortened radials (only 60" long) permit easy installation and decreases wind resistance. Overall height: 17' 6". Takes masts up to 1 1/2" O.D. Parcel Post Shippable. Wt. 10 lbs.

42 R 10563W


Net 36.95

MR-119 "SUPER SCANNER" ELECTRONIC ROTATABLE CB FIXED ANTENNA

89⁹⁵

No Money Down*

- Electronically Scans A Full 360°
- Omni-Position for Locating Other Stations
- Includes Separate Scan Control Unit



Multi-element directional antenna system electronically rotatable for a full 360° in three 120° steps plus an OMNI-POSITION for quickly locating CB stations, particularly mobile. This is accomplished by use of the "Scanner's" separate electronic Scan Control unit. Compact array of 3 sector-phased 17 1/2 ft. vertical elements extend less than 3 feet from the mounting boom. Resists over 100 mph winds. 7.75 db directional gain—23 db front-to-back ratio. Requires 4-cond. rotor cable. Takes masts from 1 1/2" to 2". Shpg. wt., 20 lbs.

42 R 10571W

Net 89.95

100 ft. coil of 4-cond. rotor cable.

32 R 89105 Net 34.0


Mobile Antennas

M-180 ADJUSTABLE GUTTER CLAMP MOBILE ANTENNA

18⁹⁵

With 12' Coaxial Cable

- Clamps On In Seconds and Adjusts To 5-Positions From Inside The Vehicle



Easily snaps on rain gutter of car! Swing-away base design permits instant lowering while seated in the car. Heavy duty, chrome plated mount has spring loaded position adjustment for 0°, 45° or 90° mounting on either side of vehicle. Sleek black fiberglass center loaded whip is professionally designed for heavy-duty operation. Has all the things a CB'er would want in a mobile antenna: Ruggedness, reliability and high performance. Shpg. wt., 2 lbs.

42 R 10522W

Net 18.95

"QUICK-GRIP" MOBILE ANTENNAS

As Low As

19⁹⁵

With 16' Coaxial Cable



"Quick-Grip" Trunk Mount—No Holes to Drill—Simple Installation, Mounted in Seconds.

A Model M175. Stainless steel whip. Base loaded with attractive gray jacket and chrome end fittings. Whip adapter provides 1 1/4" adjustment for extra fine tuning. "Quick-Grip" mount. Solderless lead connection with PL-259 at set end of 16 foot coaxial cable. Shpg. wt., 2 lbs.

42 R 10498W Net 19.95

B NEW M304—White fibre glass whip, tapered stainless steel slim-line shock spring. Extreme resistance to corrosion. Only 46" long. Solderless lead connection with PL259 at set end of 17 ft. coaxial cable. Shpg. wt., 1 1/4 lbs.

42 R 10613W Net 23.95

M-168 MOBILE "GRIP-STICK" MAGNETIC ANTENNA

- Ideally Suited for Temporary Emergency, or Permanent Mounting
- No "Installation" Involved

17⁹⁵

with 15' coaxial cable

No "Installation" involved. Merely place it on the vehicle-center of the rooftop, or back deck, run cable thru window or trunk (under seats) to CB radio. Stainless steel whip, anodized aluminum base, black phenolic insulator, and grey center loading coil. VSWR under 1.5:1. With 15 ft. coaxial cable and PL-259 connector. Shpg. wt., 2 lbs.

42 R 10480W

Net 17.95

ANTENNA SPECIALIST'S M20 WINDOW MOUNT ANTENNA

For apartment installation where other outdoor antennas can not be used. Jointed, 9 ft. aluminum radiator is supported by adjustable heavy-duty cadmium bracket. Will accept either twin or coaxial feed line. Performance will improve with height above ground. (Not Illustrated) Shpg. wt., 2 lbs.

42 R 10092W

Net 10.95

M301 2-SECTION FIBERGLASS TUNEABLE MOBILE ANTENNA

14⁹⁵

Replace Your Old Steel 1/4 Wave Mobile Whip

72" tuneable white fiberglass split whip. Two-piece with nickel plated brass ferrule. Finger-tip tuning. Fits 3/8"-24 mounts and spring. Top loaded, totally encapsulated load coil. Parcel post shipped. Shpg. wt., 1 lb.

42 R 10605

Net 14.95

442 Lafayette Cat. No. 720

M-90 96" FIBERGLASS WHIP MOBILE ANTENNA

A 96" white fiberglass CB whip antenna designed for use only on the 27-MHz band. Mounting adapter consists of chrome plated brass ferrule with 3/8" 24 male thread to fit standard base or spring. Wt. 1 1/4 lbs.

42 R 10217WX Net 10.95

MODEL M-3B 102" WHIP. Similar to M-90 except stainless steel construction. Shpg. wt., 2 lbs.

42 R 10225WX Net 5.95



M-178 "STICK-SHIFT" MOBILE MAGNET ANTENNA

With 16' Coaxial Cable

For temporary or permanent mobile applications. Powerful magnet feature lets user shift position of antenna or change from one vehicle to another. Triple chrome plated metal base. Fine tuning adjustment, VSWR 1.5:1 or better. 38" stainless steel whip with 16 ft. RG-58/U cable termination in PL 259 connector. Shpg. wt., 2 lbs.

42 R 10530W

Net 17.95



*See Page 22 for Full Credit Details on Easy Pay Plan

Selected CB Antennas, Rotors and Mounts

ANTENNA SPECIALISTS M317 FIBER GLASS CB BASE STATION ANTENNA

59⁹⁵

No Money Down*

- Fiberglass Construction
- Provides 4 db Omnidirectional Gain

Gleaming white fiber-glass CB base station antenna for the 27 MHz band. Provides 4 db omni-direction gain and 1.5:1 VSWR. Features four "Power-tip" ground radials and super loading coil. 1000 watt power handling capability insures against burn-outs due to power surges or high level static buildups. Entire radiator encapsulated in "Armor-weave" fiberglass; construction is impervious to all corrosive elements. 115 mph wind rating. 17' overall height. 50-ohm input impedance. Accepts PL-259 cable connector. Includes mounting hardware for 1 1/2" mast. Shpg. wt., 5 1/4 lbs.
42 R 10621W Net 59.95

UNIVERSAL LAFAYETTE MOBILE ANTENNA ACCESSORIES



CHROME PLATED SWIVEL BALL MOUNT BASE. Can be mounted vertically or horizontally. With lug terminals. Imported. Shpg. wt., 1 lb.
99 R 30306 Net 3.49



HEAVY DUTY CHROME PLATED STAINLESS STEEL SPRING. Provide maximum support for long whips and heavy centerloaded whips. Imported.
Shpg. wt., 1 1/2 lbs.
99 R 30363 Net 2.95




CHROME PLATED BUMPER MOUNT WITH STAINLESS STEEL STRAP. Completely adjustable for vertical mounting on most types of automobile bumpers. Highly reliable and durable. Eliminates need of cumbersome link type chain mounts. Imported. Shpg. wt., 1 3/4 lbs.
99 R 30355 Net 4.95

ANTENNA SPECIALISTS ANTENNA MOUNTS



A MODEL M-191. Double Chain Bumper Mount. Cadmium plated. Accepts 3/8"-24 thread of spring or whip.
42 R 10183 Shpg. wt., 2 3/4 lbs. Net 10.45
B Model M147 Stainless Steel Bumper Strap Mount. No holes to drill—easily adjusted.
42 R 10399 Shpg. wt., 2 1/4 lbs. Net 11.95
C Model M-115 whip hold-down clip.
42 R 10191 Shpg. wt., 3 oz. Net 1.25
D Model M-161 Quick Grip Mount. Standard trunk-lid mount accepts all 3/8" snap-in type antennas. No holes to drill. Water resistant body seal.
42 R 10472 Shpg. wt., 1 lb. Net 4.95

AVANTI "Moonraker" BASE STATION ANTENNA



No Money Down*

129⁹⁵

Combines 1/2 wave cross dipole elements with the patented PDL UNQUAD design reflector. A simple flick of the switch changes mode, for transmitting or receiving, from vertical to horizontal polarization for interference-free communications. Uses only a 15 ft. boom to eliminate efficiency losses inherent in multiple in-line quad designs, thus better signal excitation is achieved to provide greater true gain. Designed along the lines of antennas used to pinpoint signals on "moon bounce". 14.4 db gain. 1.2:1 SWR. 50 ohms impedance. 38 db vertical to horizontal separation. 90 MPH wind survival. All aircraft quality aluminum with cast hubs and extruded clamps. Includes dual switch box for use with standby omni. Shpg. wt., 27 lbs.
42 R 34068WXY Net 129.95

AVANTI "ASTRO PLANE" BASE STATION CB ANTENNA

29⁹⁵

- Packs Maximum Signal Strength As Most Efficient Position
- Full Omni-directional Signal



"Astro-Plane" base station antenna provides full omni-directional communications. Its revolutionary design concentrates signal power on top for maximum, efficient operation. Heavy duty aluminum construction with corrosion resistant fittings, including solderless coax connector, assure a long, trouble free life. Double bracing withstands 120 mph winds. Impedance: 50 ohms; SWR: less than 1.4:1; power gain: 4 db; length: 12'. Can be mounted on a single mast up to 1 1/2". Shpg. wt., 4 3/4 lbs.
42 R 34019W Net 29.95

CUSHCRAFT "RINGO" 1/2 WAVE VERTICAL CB FIXED ANTENNA

2150

- 3.75 db gain
- Covers All 23 Channels with 1:1 SWR

A sturdy Citizen Band vertical antenna with power ring tuning for amazing full circle gain. Power ring gives a perfect match between antenna and feed cable to utilize all available transmitter power. Construction is all .049 wall aluminum tubing with solid hold telescope clamps and phenolic base insulator. Designed for 52 ohm direct coaxial feed. Overall height: 17'10". Direct DC ground to eliminate static discharge noise and lightning hazard. Shpg. wt., 4 3/4 lbs.
42 R 20026W Net 21.50



CORNELL DUBILIER AR-22R AUTOMATIC ROTOR



- Fingertip Control
- Control Unit Shows Direction of Rotation

Heavy-duty rotor unit will handle antennas up to 150 lbs. Simply set the control unit pointer to the desired direction, and the antenna will automatically rotate to this position and stop. Perfect for TV, Ham or Citizen Band applications. Rotor unit employs 12 heavy duty ball bearings in two 6 1/2" races. Reversible clamps on rotor will take masts from 7/8" to 2". O.D. Control unit is marked in compass points. N.S.E.W., NW, NE, SW, and SE. Housed in attractive black vinyl steel cabinet. For 110-120 volts, 50-60 Hz AC. Uses 4-conductor rotor cable.
42 R 86076W Shpg. wt., 15 lbs. Net 36.95

SOLDERLESS PL-259 LOW-LOSS COAXIAL CONNECTORS

One for either RG58/U or RG59/U cable. Quick, easy connections. No fuses, no bother, no adapter, no soldering required. Shpg. wt., 4 oz.
Solderless PL259s for RG58/U Cables 42 R 69106 Net ea. .79
Solderless PL259 for RG59/U Cable 42 R 69114 Net ea. .79

LAFAYETTE "DUMMY" ANTENNA LOAD FOR CB TRANSCEIVERS

159



A 52 ohm non-inductive load for testing and tuning-up Citizens Band transmitters up to 5 watts. Built into PL259 coaxial plug.
42 R 09029 Shpg. wt., 3 oz. Net 1.59

MOSLEY WEATHER-GUARD ANTENNA COAT

Fast drying, clear coating compound protects against corrosive action of salt, water, moisture, and ultra-violet radiation. Will not discolor antenna. Applies easily with a brush. Shpg. wt., 1 lb.
42 R 51112 Net 1.24



Lafayette... Headquarters for CB Crystals

A full line of transmitting and receiving crystals for LAFAYETTE CB Transceivers and Walkie-Talkies, the number one line on the market today. These crystals are available for any channel from 1 to 23. Extremely accurate "3rd overtone" crystals are precision made and more than meet F.C.C. tolerance requirements of .005%. *No crystal required in receiver circuit of these transceivers. Shpg. wt., 2 oz.

2²⁵
each

HOW TO ORDER CRYSTALS for Lafayette CB transceivers

Add two (2) digits representing the desired channel to the appropriate stock number listed below; i.e., the correct stock number for Lafayette Model HB-115 transmit crystal for channel 1 is 46 R 1801, likewise for channel 23 is 46 R 1823.

LAFAYETTE CB TRANSCEIVERS

Model	Stock Numbers Transmit Receive	Model	Stock Numbers Transmit Receive	Model	Stock Numbers Transmit Receive	Model	Stock Numbers Transmit Receive
HB-115, A	46R18	HE-20T, HA-450	46R65 46R10	HB-200	46R61 46R19	Comstat 19	46R61 46R17
HE-15, A, B	46R18	HE-43, A, B, C, HE-90	46R18 46R19	HB-500, A	46R15 46R16	Micro 12	46R15 46R10
HE-20, A, B, C	46R18 46R19		46R61 46R19	HB-555	46R65 46R13		
HE-20 D	46R11 46R10	HA-150	46R15 46R10	Comstat 9 Kit	46R61	46R17	

LAFAYETTE "WALKIE-TALKIE" CB TRANSCEIVERS

Model	Stock Numbers Transmit Receive	Model	Stock Numbers Transmit Receive	Model	Stock Numbers Transmit Receive	Model	Stock Numbers Transmit Receive
HE-29, A, B	46R18 46R17	HA-85, A; HA-99	46R15 46R10	HE-210, A, HA-295	46R15 46R10	Dyna-Com 2, 2, 3	46R15 46R10
HE-29C, D; GT-50, A	46R15 46R10	HE-88, HE-100, A, B	46R15 46R10	HA-300, A, B	46R11 46R10	Dyna-Com 3a	46R11 46R10
HA-60, A; HA-62, A	46R15 46R10	HA-130A, HA-132	46R15 46R10	HA-303, HA-305	46R15 46R10	Dyna-Com 5, 5a, 6	46R15 46R10
HA-73, A, HE-75	46R15 46R10	HA-135, 711, A	46R15 46R10	HA-310, HA-310A	46R15 46R10	Dyna-Com 12, 12A	46R15 46R10

CB Crystals for Popular Standard Brand Transceivers

NOW... Any transmit crystal or any receive crystal for any CB transceiver that uses a separate transmit crystal and a separate receive crystal for each channel. NOT APPLICABLE TO CRYSTALS USED IN SYNTHESIS CIRCUITRY.

SEND filled-out certificate, one for each crystal, to manufacturer. You will receive the crystal directly from the manufacturer, postage prepaid, within a maximum of 30 days.

2²⁵
each

FOR CRYSTAL CERTIFICATE


Specify Mr., Model No., Transmit or Receive and Channel No. No C.D.D.'s.
46 R 09004Y ... Each Net 2.25

Hy-Gain and Shakespeare CB Base Station and Mobile Antennas

HY-GAIN MOBILE HELLCATS

As Low As
16⁹⁵

Now with
Extra
Heavy Duty
Coils



- A** "HELLCAT 2" ROOF TOP MOUNT ANTENNA. Base loaded, and almost impervious to damage. The extremely short, strong, lightweight stainless steel tip rod provides a very flexible capability to withstand garages and low hanging obstacles. Only 23 inches high. Complete with 22' of coax and connector. 42 R 35164W Shpg. wt., 2 lbs. Net 16.95
- B** "HELLCAT 3" MAGNET ANTENNA. Magnetically mounted in an instant and requires no holes or tools. You'll talk loud and clear with a low SWR on all 23-channels. Complete with 16' of coax and connector. Overall height is 34 5/8". 42 R 35172W Shpg. wt., 2 lbs. Net 18.95
- C** "HELLCAT 4" TRUNK MOUNT ANTENNA. Mounts easily and quickly on the lip of your trunk lid. Is base loaded with an etched copper coil, giving a very low SWR on all 23 channels. With 22' coax and connector. Overall height 47". 42 R 35180W Shpg wt., 3 1/4 lbs. Net 21.95
- D** "HELLCAT 6" CAMPER AND TRAILER ANTENNA. Installs quickly and easily on all types of campers and house trailers. Mounting bracket is complete with low profile base and chrome plated brass automatic fold-over, providing necessary mechanical protection. With 22' coax and connector. Overall height 47". 42 R 35206W Shpg. wt., 3 3/4 lbs. Net 22.95
- E** "HELLCAT 7" THE FOLD-OVER ROOFTOP ANTENNA. Tension loaded base provides rigid support at all time, yet folds when struck by an obstacle or when the vehicle is garaged. Complete with 22' coax and connector. Shpg. wt., 3 lbs. 42 R 35214W Net 19.95

HY-GAIN CLR//II BASE STATION ANTENNA

32⁹⁵

- Electrically Extended 5/8" Wave Length Radiator
- Delivers 8 DB Circuit Gain

Deluxe collinear ground plane antenna. Rugged base mounting assembly insures survival in winds up to 100 MPH. Maximum (20 ft.) Radiator develops greatest possible gain. 3.4 db in measured field strength intensity plus improvement in signal/noise ratio resulting from vertical element being at DC ground. Total circuit gain in excess of 8 db. DC ground feature protects antenna and equipment from lightning damage. Element material top quality aluminum tubing 1 1/4" to 3/8". All seamless tubing. Mount on mast 1" to 1 1/2". SWR less than 1.2:1. Fed with 52 ohm coax. Shpg. wt., 8 1/4 lbs. 42 R 35016W No Money Down Net 32.95

NEW SHAKESPEARE MODEL 10-3 FIBER-GLASS MOBILE WHIP ANTENNA

9⁹⁵

- Mounts On Standard Ball, Cowl, or Bumper Mount
- Power Rating: 200 Watts
- SWR 1.5:1

Deluxe 96" quarter-wave fiber glass whip is light-weight, non-corrosive and anti-static. Mounts on standard ball, cowl, or bumper mounts. Fibre glass construction utilizes Shakespeare's exclusive oriented fibre process for superior strength. Fittings are of chromed brass. Standing Wave Ratio of 1.5:1 may be achieved when mounted on an automobile. Vertically polarized to conform with typical mobile to mobile or mobile to base operation. Matched to RG 58 or other 50 ohm coaxial cable. Thread size: 3/8-24. Shpg. wt., 1 lb. 6 oz. 42 R 17006W Net 9.95

SEE PAGE 442 FOR LAFAYETTE MOUNTS & SPRINGS

LAFAYETTE—Headquarters for CB Accessories & Equipment

NEW! LAFAYETTE CB Transceiver Multitester

Measures

- RF Power Output
- % Modulation
- Relative Field Strength
- Crystal Activity
- SWR
- DC Volts Up To 15V
- DC Amps Up To 1A
- RF Power Up To 8 Watts

Generates

- Crystal Controlled RF Signal
- 1 kHz Audio Signal
- Modulated RF Signal

Provides

- In-Circuit Connection To Antenna Without Removing Cables From Transmitter

Permits

- Aural Monitoring of Local Transmitters
- Visual Transmitter Monitoring with Oscilloscope



- 14 Test Functions
- Large 3" Meter

Only
39⁹⁵

with batteries

Features sensitive O'arsonval meter, jacks for aural and visual monitoring, audio generator output and RF signal generator output; ceramic jacks for standard miniature crystal sockets. Controls include 8-position selector switch—Sig. Gen./Crystal, Field Strength, DC Amps 0-100ma, AC Amps 0-1A, DC Volts 0-3V, AC Volts 0-15V, Modulation, RF Power/SWR, 4 lever switches for: RF Gen., Audio Gen./Modulator Power—SWR and Forward, Antenna—External and Internal. Also has—Push-to-Calibrate Switch, Meter Adjust Control, Modulation Calibrate Control. SO-239 sockets accept standard PL-259 connectors. Sturdy attractive metal case with brushed aluminum front panel. Size: 8"wx3 3/4"Dx5 3/4"H. Includes "AA" battery; 60" telescoping antenna. Imported. Shpg. wt., 4 lbs.

99 R 32195 No Money Down*

Net 39.95

NEW! Antenna Specialists CB Meters, Bridges, Matchers, and Switches

MODEL M-250 ANTENNA SWITCH. Four position coaxial switch with no insertion loss. This unit allows the use of horizontal, vertical, auxiliary or horizontal/vertical antenna systems. Shpg. wt., 2 lbs.

42 R 10639 Net 11.95



As low as
11⁹⁵

MODEL M-252 WATTMETER. Inline design. Accuracy on measurement is held to $\pm 5\%$ by laboratory standards. 10w and 100w scales. Easy to read meter indicates forward power at all times. Shpg. wt., 2 lbs.

42 R 10662 Net 27.95

MODEL M-253 ANTENNA MATCHER. Tunes wide range of impedances to allow perfect matching of antenna—coax—transceiver for full protection of final amplifier devices. A must for those using dual polarity antennas. Not illustrated. Shpg. wt., 2 lbs.

42 R 10647 Net 22.95



MODEL M-251 MODULATION BRIDGE. Allows full-time monitoring of modulation. Accurately measures modulation from 0 to 100% with minimal insertion loss. May be left in line. Shpg. wt., 2 lbs.

42 R 10654 Net 27.95

ANTENNA COAXIAL SWITCH

5⁹⁵



- 2-Position
- Rated At 1 KW AM, 2 KW PEP SSB

CBer's and Hams can stop reaching behind their rigs, wasting time and missing calls switching antenna leads. With this quality coaxial switch—just turn the knob and instantly change from one antenna to another. Size: 2 1/2 x 1 1/4". Shpg. wt., 6 oz.

42 R 21024 Net 5.95

CB ANTENNA MATCH

9⁹⁵



- 1:1 VSWR
- Gives a perfect antenna/transmission line match of 1:1:1 VSWR for full power. Requires no special tools for installation. Simply insert the CB MATCHER between the transmitter and antenna lead-in. Adjustable tuning knobs permit precise matching under various operating conditions.

42 R 21032 Shpg. wt., 6 oz. Net 9.95

CB and Ham SWR Mini-Bridge

13²⁵



- Handles A Full 500-Watts Average Power

Only 2 3/4" long by 1 3/8" high by 1 3/4" wide, yet, will handle a full 500-watts average power with negligible insertion loss. Gives stable meter readings of SWR plus an additional scale shows relative output power. Designed for 52-ohm impedance lines. Supplied with universal mounting bracket for inline applications. Shpg. wt., 8 oz.

42 R 21040 Net 13.25

CB INLINE WATT METER

14⁹⁵



- Rated at 5-Watts Continuous

Easy to use and very accurate! Tells you how many watts your CB rig is delivering. Reads true output power in watts when inserted in a 50-ohm line. Stays in-line for constant monitoring. Negligible insertion loss. Reads true output power and not relative power.

42 R 21065 Shpg. wt., 5 oz. Net 14.95

E. F. Johnson Antenna Meter

14⁹⁵



Model 250-849 Antenna Meter. Effectively minimizes power loss through your antenna system. Get maximum communication range from your transceiver. Direct reading antenna meter measures SWR up to 10:1. No external power needed. Size: 4 1/2 x 2 3/4 x 2 3/8". Shpg. wt., 14 oz.

42 R 39133 Net 14.95

E. F. Johnson CB Matchbox

15⁹⁵



Model 250-49 CB Matchbox. Compact self-contained antenna matching unit enables maximum energy transfer to antenna system. Simple adjustment of "Tune" and "Load" controls correct SWR up to 5:1 to give almost perfect 1:1:1 antenna match. Requires no external power source. Size: 4 x 3 1/2 x 2 3/8". Shpg. wt., 1 1/2 lbs.

42 R 39141 Net 15.95

Make Lafayette Your Headquarters For Citizens Band Equipment

Lafayette Cat. No. 720 445

Improve Your Citizen Band Performance

AMECO CB Transceiver RF Preamplifiers



As Low As **59⁹⁵**

- On the Air Sign
- Improve Receiver Sensitivity — AM or SSB
- FET Transistor Amplifier
- Connects to CB Transceiver No Modification Required

Model "PCB-U" solid-state preamplifier improves sensitivity, increases gain of receiver section of transceiver over 20 db. Improves signal-to-noise ratio. Automatic switching bypasses preamplifier when transmitting. Built-in gain control increases immunity to front-end overload. "ON THE AIR" sign automatically lights when transmitting base station or mobile. Size: 7½" x 3¼" x 4½". Shpg. wt., 4¼ lbs.
42 R 69098 No Money Down* Net 59.95
Deluxe Model PCB-Senior. In addition to the above, contains power switch to control entire station. It can feed a second receiver and automatically mutes second receiver while transmitting. Has double tuned pre-selector stage. For base station 117V AC only. Shpg. wt., 3¼ lbs.
42 R 69130 Net 69.95

NEW

Solid-State CB Emergency Call System For Cars

ONLY **44⁹⁵**

with
mike/speaker

- Complete CB Transceiver Operates on Channel 9
- Combination Mike and Speaker Saves Space




Monitor Channel 9, 24 hours per day in your car. Just pick up the push-to-talk mike and call for help in an emergency. Mike also includes built-in-speaker. Comes with Transmit and Receive crystal for Channel 9 installed. Powerful solid-state circuitry includes 7 transistors, 4 diodes, and 1 IC.

Includes mounting bracket for easy under dash installation. Power Input 5 watts. RF Power Output 3 watts. For 12-volt Negative ground systems. Size 1½"H x 3½"W x 7¼"L. Shpg. wt., 2½ lbs. Imported.
42 R 66052 Net 44.95

DRAKE Low Pass Filter

76⁵



- Avoid TV Interference

Effectively reduce TVI which may be emanating from your CB transmitter and interfering with TV sets. This four section filter is designed with a 43.2 MHz. cut-off and extremely high attenuation in all TV channels for citizens band and other transmitters 30 MHz. and lower. Rated 100 watts input. SO-239 connectors built-in. Shpg. wt., 3/4 lbs.
42 R 7700 Net 7.65

CB Nuvistor Preamplifier


12⁹⁵



- Improve Receiver Gain, Noise Figure, Spurious Signal and Image Rejection

Use ahead of a receiver or to improve the gain and noise figure considerably. Employs a completely neutralized 6CW4 Nuvistor. Requires 100-150 VDC at 8 ma. and 6.3 volts at .13 amps., AC or DC. Only 2½ x 3½ x 7". Shpg. wt., 3/4 lbs.
42 R 69015 Net 12.95

LAFAYETTE Auto-Marine Engine Noise Suppressor Kit



12⁹⁵

- A must for Mobile CB and Ham Operators
- 13 Components Plus Shielded Cable Bonding Strap and All Mounting Hardware

Easily installed kit will effectively suppress noise and interference created by the operation of electrical equipment in your car or boat such as spark plugs, circuit breakers, coils, generators, regulators, or distributor assemblies. Consists of 8-spark plug suppressors; 1-distributor suppressor; 12-ft. shielded cable; 18-inch bonding strap, 1/4"-wide, 4-coaxial capacitors. All necessary hardware and complete instructions for installation are included. Shpg. wt., 1¼ lbs.
42 R 09052 Net 12.95

E. F. Johnson Solid State In-Converter

22⁹⁵

Converts:
6VDC to 12VDC
6VDC to 18VDC
12VDC to 24VDC




Permits you to match voltage and polarity from any 6 or 12 volt DC power source to your citizens band equipment. Converts 6 volts DC to 18, 12 volts DC to 24. Inverts polarity from positive to negative to positive. Select any combination of connections in seconds by merely changing one jumper cable. Size: 5¼"L x 2½"H x 3¼"W. Shpg. wt., 2¼ lbs.
42 R 39190 Net 22.95

LAFAYETTE CB PHONE PATCH

15⁹⁵

- Ideal for Emergency Phone Calls Using Your CB Transceiver

Talk anywhere in the world from your car or truck. Simple installation allows your telephone to be connected to your CB communications system. For use with 3-16 ohm speakers and high impedance microphone inputs. Modulation gain control to compensate for varying line levels. On-off switch disconnects patch when not in use. Dimensions: 4¼"W x 1½"H x 2"D. Shpg., 1¼ lbs.
42 R D1638 Net 15.95



7⁹⁵

CB Transceiver Auto-Mount

- Adjustable—Fits all Transceivers
- Screws firmly to floor. 1" strap holds transceiver firmly in place. Easy access to all controls. Steel construction. Size: 10½" to 14¾" wide, 10¾" long. Rear height: 5¾", front height 9". Shpg wt., 5½ lbs.
42 R 68009W Net 7.95


Lafayette CB Replacement Parts & Accessories

12 VOLT DC POWER CABLE



Consists of one hot red lead and one black ground lead. One end of assembly terminates in a rugged 3 contact female plug, ready for mating with chassis power socket. The opposite end terminates in lugs for solid connections to the battery point and ground. Midway in the line is a durable plastic holder containing a protective fuse. Features well soldered connections, strong wire. Overall length approximately 6 feet long. For HB-500, A, HB-555, HB-525 Series, HB-625, HB-23, Telsat 150, Telsat 50, HA-750, PB-50, PB-150, HA-39, 42, 45, 46, 153, 155, HA-159. 99 R 31106 Imported. Wt., 4 oz. Net 2.50

DC POWER CHASSIS JACK



Mounts on chassis rear and accepts plug of 12 volt DC power cable 99-31106 above. Used in HB-500, A, HB-525 Series, HB-625, HB-23, HA-750, PB-150, PB-50, HA-39, 42, 45, 46, 153, 155, 159, Telsat 150 and Telsat 50, etc. Imported. 99 R 63638 Shpg. wt., 2 oz. Net .89

CABLE ASSEMBLIES



FOR COMSTAT 23, 25, 25A, 25B

AC Cable Assembly. 5 1/4 ft. of durable cable terminating in dual prong power plug on one end and in 8-prong octal socket on other. Shpg. wt., 5 oz. 99 R 32401 Imported Net 1.95

DC Cable Assembly. 4 1/2 ft. fused DC Cable fitted on one end and terminating in octal socket on other. Shpg. wt., 5 oz. 99 R 31825 Imported Net 2.50

For Comstat 23 MK V & MK VI AC Cable Assembly. Shpg. wt., 5 oz. 99 R 32419 Imported Net 1.95

AC CABLE ASSEMBLIES For HE-20, A, B, C; HE-43, A, B, C; HE-45, A, B; HE-50, A, HB-353. Shpg. wt., 5 oz. Net 1.95 32 R 09327

HEAVY DUTY CB MICROPHONE CABLE



• 3 Conductors Plus Shield

A durable coiled cord, retractable microphone cable with 3 insulated conductors, one of which is shielded. Extends to 5 feet and retracts to 10 inches. Is used with Lafayette HB-500, A, 525 Series, HB-625, Telsat 23, Telsat 50, Telsat 150, Micro-12, etc. Imported. 99 R 63620 Shpg. wt., 4 oz. Net 2.49

MOBILE MOUNTING BRACKETS



Complete with top mounting holes, and with adjustable side mounting holes for knurled screws. Used in Lafayette HB-525 Series, HB-625, HA-750, PB-50 and PB-150, Telsat 50, Telsat 150, etc. 6 1/2 x 2 1/4". Imported. 99 R 63588 Shpg. wt., 5 oz. Net 1.49 Same as above but for Lafayette HB-555, HB-23, HA-39, 42, 45, 46, 153, 155, HA-159, 6 1/2 x 2 1/4 x 3/4". Imported. 99 R 63596 Shpg. wt., 4 oz. Net 1.49

Depend on Lafayette For Complete Stocks, Lowest Prices, Fastest Service

27MC WALKIE-TALKIE TELESCOPING ANTENNA



Attractive and highly efficient 12 section chrome plated brass telescoping antenna for "walkie talkie" transceivers. Measures 52" fully extended and 5 1/2" retracted. Has #8-32 threaded stud and nut at bottom for easy mounting, and soldering lug for electrical connection. Shpg. wt., 5 oz. 99 R 30082 Net 1.95

LAFAYETTE MINIATURE MICROPHONE CONNECTORS



(A) Microphone Plug for CB and Amateur Microphones. Precision engineered and sturdily constructed. Plug takes any 4 conductor (or 3 conductor with shield), coiled cord or straight cable. Features threaded retaining ring for positive locking, integral cable retaining clamp, and polarizing keyway. Size: 1 1/4" L x 1/2" D. Used with microphone in Comstat 23, MKV, MKVI, Comstat 25, 25A, 25B, HB-444/25, HB-444/25A, Comstat 19. Imported. 99 R 62630 Shpg. wt., 3 oz. Net 1.49

(B) Microphone Chassis Socket Mounts on equipment chassis or panel and mates with 99-62630 plug. Size: 3/4" x 3/4" Dia. Requires 3/8" mounting hole. Used in Comstat 23, MKV, MKVI, Comstat 25A, 25B, HB-444/25A, Comstat 19. Imported. Wt. 3 oz. 99 R 62648 Net .89

MICROPHONE PLUG



Attractive, sturdy plug used with HB-555, HB-600, HB-600A, HA-650, HE-20D, HB-525 Series, HB-625, HE-20T, HB-23, HA-750, Telsat 23, Telsat 150, Telsat 50 and Micro-12 microphones. Four male prongs on one end with retaining cable clamp on the other end. Sturdy molded plastic body with plated metal housing. Size: 3/4" OD x 1 1/2" overall. Imported. Shpg. wt., 4 oz. 99 R 62838 Net .99

MICROPHONE CHASSIS SOCKET



Mounts on chassis rear of equipment. Accepts and mates with microphone plug 99 R 62838 above. Used in HB-555, HB-600, A, HA-650, HE-20D, HB-525 Series, HB-625, HE-20T, HB-23, HA-750, Telsat 23, Telsat 50, Telsat 150 and Micro-12. Imported. 99 R 63646 Shpg. wt., 2 oz. Net .99

ILLUMINATING PILOT LAMPS



5 Meter Illuminating Lamp. Operates on 6 volts AC or DC. Used in Lafayette Comstat 23, MKV, MKVI, Comstat 25, Comstat 25A, 25B, HB-444/25A. Imported. Shpg. wt., 3 oz. 99 R 62622 Net .34

Channel Selector Dial Indicator Lamp. Used in Lafayette HB-500, HB-525 Series, HB-625, HB-600, HE-20D, HE-20T, HA-39, 42, 45, 46, 153, 155, HA-159, HA-750, Telsat 150, Telsat 50, PB-50, PB-150, Micro-12. Imported. 99 R 63612 Shpg. wt., 2 oz. Net .29

CB CONNECTOR ADAPTERS



(A) Adapts from an auto antenna plug (Motorola type) to an SO-239 socket. Wt., 4 oz. 42 R 22014 Net 1.99

(B) Adapts from PL-259 plug to a standard auto radio antenna jack (Motorola type). 4 oz. 42 R 22022 Shpg. wt., 4 oz. Net 1.29


GENERATOR NOISE FILTER

- Freq. Range 3-30 MHz
- Simple to Install • Adjustable



Enables quiet receiver operation for Citizens Band, Amateur and industrial frequencies. Standard frequency range 3-30 MHz. Maximum current 25 amps. Imported. 99 R 60188 Shpg. wt., 5 oz. Net 2.29

VOLTAGE REGULATOR FILTER



Eliminates noises in communication receivers caused by points in voltage regulator. Not voltage or frequency critical—no tuning required. Wt., 5 oz. 42 R 89013 Net 3.95

ALTERNATOR NOISE FILTER



A highly effective filter for alternator equipped automobiles. Attenuates alternator noise by 50 db. Can operate up to 32 volts DC. Results in quiet mobile receiver operation. Shpg. wt., 4 oz. 42 R 49009 Net 3.49

TUNEABLE ALTERNATOR FILTER



- Handles Up To 52 Amps.
- 22-60 MHz Range

Designed for ultimate in mobile alternator noise suppression. Can also be used with Amateur and Business Band mobile rigs. Tunes 22-60 MHz. Adjustable frequency trimmer rating 52 amps continuous. Shpg. wt., 1 lb. 42 R 44026 Net 11.45

TRANSISTORIZED VIBRATORS



Ideal replacement for old-fashioned mechanical vibrators. Direct replacements for 4-pin, 12-volt vibrators in CB mobile rigs, auto radios and commercial communications equipment. Eliminate vibrator hash and replacements due to sticking contacts. Handles up to 4 amps because of matched transistor complement and exclusive transformer design. Size 3" H x 1 1/2" O.D. Shpg. wt., 8 oz.

For Vibrator Sockets with pin #1 Positive. 42 R 79006 Net 9.95
For Vibrator Sockets with pin #1 Negative. 42 R 79014 Net 9.95

KNURLED SCREW



For mounting mobile bracket onto Lafayette HB-525, A, B, C, HB-555, HB-625, HB-23, HA-750, Telsat 50, Telsat 150, PB-50, PB-150 and Micro-12. Imported. Shpg. wt., 3 oz. 99 R 63604 Net .45
For Lafayette Comstat 23, MKV, MKVI, Comstat 25, Comstat 25A, 25B, HB-444/25, 99 R 31833 Shpg. wt., 2 oz. Net .45

LAFAYETTE Industrial Pocket Pager

**REACH YOUR MAN ON THE MOVE
INSTANTLY, QUIETLY, PRIVATELY!**

EXCELLENT for: Factories, Hospitals, Warehouses, Farms, Research Compounds, Department Stores, Sports, etc.

CONTACT: Doctors, Nurses, Plant Engineers, Supervisors, Maintenance Men, Security Personnel, Department Heads, and other Key Personnel.



ONLY
49⁹⁵

- Up to 230 Vital People At Your Fingertips!
- Save Busy Switchboard Time and Money!
- Minimize Disturbing Non-Private Paging!

Lafayette's Industrial Selective Pocket Pager introduces a new concept in realistic, economical local communications with vital personnel normally on the move. By inserting or clipping the Pocket Pager into your shirt pocket you can easily be reached by your superior who operates a Lafayette solid state 27 MHz transceiver to which is connected a Lafayette selective Encoder-Decoder. With the Priva-Com IIIC Encoder-Decoder up to 23 different people can be called vocally with a private message. With the Lafayette Priva-Com 10 selective calling Encoder-Decoder up to 230 different people can be contacted privately. The selection of the transceiver channel corresponding to the frequency of the individual you wish to call, followed by the activation of the call button on the Priva-Com unit breaks the Pager's silence with an audible tone and permits the message to be heard through the Pager. Activation of the reset switch returns the Pager to silent standby. This amazing little Pager features an 18-transistor, 5-diode superheterodyne circuit with RF stage for 0.7 μ v. sensitivity, mechanical filter for superior selectivity, an internal ferrite bar antenna, an earphone/external speaker jack, etc. It is supplied complete with channel 6 crystal, plus 2 dummy filters required for operational check prior to actual use. It requires the insertion of any 2 of the tuning fork filters listed below. The Pager uses one 5.4-volt mercury battery or one 5-volt nickel cadmium rechargeable battery. Size: 5 1/2"H x 2 3/4"W x 15/16"D. Shpg. wt., 1 1/2 lbs. Less Tuning Filters and Battery.

99 R 35602L No Money Down* Net 49.95
Alternate Receive Crystal. For any CB channel from 1 to 23. (specify channel)†

46 R 10 Net 2.25

†See Page 444 on How to Order Crystals.

5.4 Volt Mercury Battery (1 required)

32 R 46741 Pkg. of 2 Net 3.84

Alternate 5-Volt Nicad Rechargeable Battery. Shpg. wt., 3 oz.

32 R 67010 Net 16.95

99 R 35610 Nicad Battery Charger. Wt., 1 1/4 lbs. Net 19.95

40 R 79018 Earphone for Pager Net .59

ACCESSORIES

Frequency Tuning Fork Filters (Any Two Listed Below)

99 R 35529	817.5Hz	99 R 35552	967.5Hz
99 R 35537	862.5Hz	99 R 35560	997.5Hz
99 R 35545	922.5Hz		Net ea. 4.95

LAFAYETTE RECOMMENDED



HE-20T

Priva-Com IIIC

Antenna

12 CHANNEL PAGING SYSTEM

- Lafayette Model HE-20T 27 MHz Transceiver Plus Channel 6 Transmit Crystal
- Lafayette Priva-Com IIIC Encoder-Decoder
- 1/2 Wave Indoor Antenna with cable and connector
- Lafayette Industrial Pocket Pager Plus Tuning Fork Filters

Recommended for systems requiring private communication with up to 12 different individuals or with any number of people using up to 12 different channel frequencies. The Pager channel frequencies are pre-determined by the frequencies of the crystals in the HE-20T which is supplied initially with crystals for channel 9. Eleven additional pairs of crystals are required for 12 channel operation. Crystal frequency in each pager must match the associated HE-20T channel. A channel 6 transmit crystal for the HE-20T and 2 tuning fork filters for the pager are supplied for complete compatibility. Complete system; Shpg. wt., 22 1/4 lbs.

42 R 92173WXM No Money Down* Net 204.95

See Page 444 for additional crystals for HE-20T.

ECONOMY PAGER SYSTEMS



Priva-Com 10

HB-600

23 CHANNEL PAGING SYSTEM

- Lafayette HB-600 27 MHz Transceiver
- Lafayette Priva-Com IIIC Encoder-Decoder
- 1/2 Wave Indoor Antenna with Cable and Connector
- Lafayette Industrial Pocket Pager Plus Filters

Recommended for systems requiring private communication with up to 23 different individuals, or with any number of people using up to 23 different channels. The HB-600 is supplied complete with all crystals required for the 23 different channels. The crystal frequency of each pager must match the transceiver's channel it is supposed to receive. Shpg. wt., 23 lbs. 8 oz.

42 R 92181WXM No Money Down* Net 329.95

230 CHANNEL PAGING SYSTEM

Same system as above except with Lafayette Priva-Com 10 instead of Priva-Com IIIC. Permits transmission of private messages to up to 230 different individuals and to many times that number with semi-private messages. Shpg. wt., 26 lbs. 8 oz.

42 R 92199WXM No Money Down* Net 389.95

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Priva-Com® Encoder-Decoders

SAVE MONEY - SAVE TIME - BOOST EFFICIENCY



Only
99⁹⁵
No Money
Down*

23 Transistors, 13 Diodes, and 5 Tuning Fork Filters

Expertly designed solid state circuitry features push-button selection and communications with any one of 10 mobile stations at any one time, or with any assorted quantity of remote stations using up to 10 different dual tone frequencies. The remote mobile remains quiet until the call signal from the Priva-Com 10 activates the receiver. When the remote or mobile station initiates a call to the base station, the Priva-Com 10 indicator lamps signal and identify the call. With a

PRIVA-COM® 10 SOLID STATE SELECTIVE ENCODER-DECODER

- Increases Paging Channels by 10 Times
- Push-button Selection of Any one of 10 Dual-Tone Frequencies
- Indicator Lamps Signal and Identify Incoming Calls
- External Speaker/Horn Switch and Terminals
- Dual Tone Minimizes False Triggering On Stray Signals
- Compatible With Priva-Com III, IIIA, IIIB, IIIC and IV
- Mates Directly With HB-555, HB-525A,B,C, HB-600, HE-20T, and Telsat 23 CB Transceivers With a Built-in Priva-Com Socket.

remote speaker or horn connected to the external speaker/horn terminals an audible signal can be heard with the incoming call. Increases number of channels by 10 times when used with Lafayette Pocket Pager, attractively styled with brushed aluminum panel and oiled walnut wood case. For 115 volt AC 50/60 Hz operation. Size: 10 1/4" W x 7 7/8" D x 3 3/4" H. Shpg. wt., 7 1/4 lbs. Imported. Net 99.95



Only
34⁹⁵
No Money
Down*

Real Tiny: 1 1/4"H x 3 3/4"W x 6 1/4"D.

Using an ingeniously designed ceramic and resonant tuning fork circuitry instead of conventional reed relays, the diminutive Priva-Com IIIC is exceptionally adaptable for reliable mobile as well as fixed station performance. Its dual tone signal minimizes the possibility of the transceiver speaker being turned on by stray ignition and power line signals. The Priva-Com IIIC mutes the receiver. When its call switch is activated, either at base or mobile stations, the CB receiver is activated and the indicator light goes on. This light stays on until

PRIVA-COM® IIIC SOLID STATE ENCODER-DECODER

For Lafayette 12 Volt Solid State CB Transceivers

- 9 Transistors plus 2 Diodes
- Dual Tone Minimizes Stray Signal Interference
- Mates Directly with Lafayette HB-555, HB-525A, HB-525B, HB-525C, HB-600, HE-20T, and Telsat 23 CB Transceivers that have a Built-in Priva-Com Socket.
- Compatible with Lafayette Priva-Com III, IIIA, IIIB, IV and Priva-Com 10

manually reset. The Priva-Com IIIC, features simple-to-operate push-button switches for Standby, Normal (Reset) and Call; a Volume Control; Indicator Light; and a sturdy mobile bracket for mounting under dash, under transceiver, etc. Supplied with 2 plug-in selective ceramic and resonant tuning fork filters, one for 817.5 Hz, and one for 997.5 Hz tone frequencies. Size: 1 1/4" H x 3 3/4" W x 6 1/4" D. Imported. Shpg. wt., 2 1/2 lbs. Net 34.95

PLUG-IN TUNING FORK SELECTIVE FILTERS FOR LAFAYETTE PRIVA-COM® IIIA, IIIB and IIIC

Choice of any two different frequencies listed below for those wishing to vary their Priva-Com IIIA, IIIB and IIIC frequencies. Shpg. wt., 2 oz.

- | | | |
|-------------------------|-------------------------|-------------------------|
| 99 R 35529 For 817.5 Hz | 99 R 35545 For 922.5 Hz | 99 R 35560 For 997.5 Hz |
| 99 R 35537 For 862.5 Hz | 99 R 35552 For 967.5 Hz | Each Net 4.95 |

LAFAYETTE PRIVA-COM IV ENCODER-DECODER

Similar to Priva-Com IIIC except used with Lafayette Comstat 25A and with Comstat 25B's that have selective call socket and circuitry. Compatible with Priva-Com 111 A, B, C, and 10. Shpg. wt., 3 lbs. Net 34.95

TUNING FORK FILTERS FOR PRIVA-COM® III and IV

To vary your Priva-Com frequencies. Select any two frequencies below not already supplied. Shpg. wt., 2 oz.

- | | | |
|-------------------------|-------------------------|-------------------------|
| 99 R 31189 For 817.5 Hz | 99 R 31205 For 922.5 Hz | 99 R 31221 For 997.5 Hz |
| 99 R 31197 For 862.5 Hz | 99 R 31213 For 967.5 Hz | Each Net 4.95 |



Only
29⁹⁵

PRIVA-COM® V ENCODER-DECODER

- 10 Dual-Tone Frequency Capability
- Incoming Call Indicator Light
- Operates Horn or External Alarm
- Mates Directly with Lafayette Comstat 25, 25A, 25B† Tube Type CB Transceivers that have Built-in Priva-Com Socket.

ADAPTER FOR PRIVA-COM V FOR SOLID STATE CB TRANSCEIVERS.

Adapts Priva-Com V for direct mating and efficient performance with Lafayette HB-525, A, B, and C, HB-600, HE-20T, and Telsat 23 solid state CB transceivers with built-in Priva-Com socket. Net 9.95

42 R 01570 Shpg. wt., 1 lb.

This highly dependable encoder-decoder mutes the CB receiver until a Priva-Com dual tone signal is received. Upon receipt of this signal the incoming call indicator light goes on, the horn or external alarm, if connected to the Priva-Com, is operated and the receiver speaker is activated for audible communications. Both base stations or mobiles can initiate calls. Is not compatible with Priva-Com IIIA, IIIB, IIIC or 10. Size 4 1/4" x 2 1/4" x 5 1/4". Shpg. wt., 2 1/2 lbs.

42 R 01497 For Tube Transceivers Net 29.95

*See Page 22 for Full Credit Details on Easy Pay Plan

†Present Comstat 25B no longer has Priva-Com socket.

Lafayette Economy CB 2-Way Radio Systems

MINI-MOBILE MICRO-12 2-WAY RADIO SYSTEMS



SAVE \$6.90

From Individual Catalog Prices Only

84⁹⁵

CB/AM

Mobile Systems

Consists of: Lafayette Mini-Mobile Micro-12, 12 Channel Crystal-Control Solid State CB Transceiver; stainless steel Body Mount Antenna; and 20' RG-58/U Cable Assembly. Shpg. wt., 10¾ lbs.

42 R 92009WXM Net 84.95

Same as above except with CB/AM Cowl Mount Antenna. One antenna for both AM broadcast and CB. Shpg. wt., 7¼ lbs.

42 R 92017WXM No Money Down Net 84.95

Same as above except with Bumper Mount Antenna. Wt., 10¾ lbs. Net 86.95



SAVE \$8.55

From Individual Catalog Prices Only

113⁹⁵

Micro-12 HB-512

Base Systems

Consists of: Lafayette Mini-Mobile Micro-12 12 Channel Crystal-Control Solid-State CB Transceiver; HB-512 AC Power Supply; heavy duty Ground Plane Antenna; 50' RG-8/U Cable Assembly. Shpg. wt., 18½ lbs.

42 R 92033WXM No Money Down Net 113.95

Same as above except with "Range Boost II" 1/2 wave end-fed antenna. Shpg. wt., 20¼ lbs.

42 R 92041WXM Net 120.95



MODEL HB-23A ECONOMY 2-WAY RADIO SYSTEMS



SAVE \$4.90

From Individual Catalog Prices

Only **106⁹⁵**

No Money Down*

Mobile Systems

Consists of: Lafayette Model HB-23A Solid-State CB Transceiver with 23 channel crystal control capability; stainless steel Body Mount Antenna; and 20' RG-58/U Cable Assembly. Shpg. wt., 11¾ lbs.

42 R 92207WXM Net 106.95

Same as above except with Bumper Mount instead of Body Mount Antenna. Wt., 11¾ lbs.

42 R 92215WXM Net 108.95



SAVE \$6.55

From Individual Catalog Prices

Only **135⁹⁵**

No Money Down*


Base Systems

Consists of: Lafayette Model HB-23A Solid-State CB Transceiver with 23 channel. Crystal control capability; HB-502B AC Power Supply; heavy duty Ground Plane Antenna; 50' RG-8/U Cable Assembly. Wt., 25 lbs.

42 R 92223WXM Net 135.95

Same as above except with "Range Boost II" deluxe 1/2 wave end-fed antenna. Wt., 27 lbs.

42 R 92231WXM Net 142.95



MODEL HB-525E 23 CHANNEL 2-WAY RADIO SYSTEMS



SAVE \$7.90

From Individual Catalog Prices

Only **153⁹⁵**

No Money Down*

Mobile Systems

Consists of: Lafayette Model HB-525E 23 Channel Solid-State CB Transceiver; stainless steel Body Mount Antenna; 20' RG-58/U Coaxial Cable Assembly. Shpg. wt., 13¼ lbs.

42 R 92249WXM Net 153.95

Same system as above except with Bumper Mount instead of Body Mount Antenna.

42 R 92256WXM Wt., 13¼ lbs. Net 155.95



SAVE \$9.55

From Individual Catalog Prices

Only **182⁹⁵**

No Money Down*

Base Systems

Consists of: Lafayette Model HB-525E 23 Channel Solid-State CB Transceiver; HB-502B AC Power Supply; heavy-duty Ground Plane Antenna; 50' RG-8/U Low Loss Cable Assembly. Wt., 21¼ lbs.

42 R 92264WXM Net 182.95

Same as above except with "Range Boost II" deluxe 1/2 wave end-fed antenna. Wt., 23 lbs.

42 R 92272WXM Net 189.95



LAFAYETTE Economy CB 2-Way Radio Systems

COMSTAT 23 MK VI 23 CHANNEL 2-WAY RADIO SYSTEMS




Ground Plane

SAVE \$6.60

From Individual Catalog Prices

Only **125⁹⁵**

No Money Down*



Cable



Range Boost II

Base Systems

Consists of: Lafayette Comstat 23 Mark VI 23 channel crystal-controlled CB transceiver; a heavy duty Ground Plane Antenna, and 50' of RG-8/U low-loss cable assembly. 42 R 91563WXM Wt., 25¼ lbs. Net 125.95 Same system as above except with "Range Boost II" deluxe ½ wave end-fed antenna instead of ground plane antenna. 42 R 91571WXM Wt., 27 lbs. Net 132.95



SAVE \$6.80

From Individual Catalog Prices

Only **132⁹⁵**

No Money Down*



DC Power Supply



Body Mount



Cable



Bumper Mount

Mobile Systems

Consists of: Lafayette Comstat 23 Mark VI 23 channel crystal-controlled CB transceiver; 12 volt DC Power Supply; stainless steel Body Mount Antenna; Mobile Mounting Bracket; 20' Cable Assembly. Wt., 27¾ lbs. 42 R 91569WXM Net 132.95 Same system as above except with Bumper Mount Antenna. Shpg. wt., 27¾ lbs. 42 R 91597WXM Net 134.95

TELSAT 924 23-CHANNEL 2-WAY RADIO SYSTEMS



Ground Plane

SAVE \$7.60

From Individual Catalog Prices

Only **154⁹⁵**

No Money Down*



Cable



Range Boost II

Base Systems

Consists of: Lafayette Telsat 924 23-channel crystal-controlled CB transceiver; heavy-duty Ground Plane Antenna; and 50' RG-8/U cable assembly. Shpg. wt., 23¾ lbs. 42 R 92280WXM Net 154.95 Same system as above except with "Range Boost II" high gain 1/2 wave length base station antenna. Shpg. wt., 25¼ lbs. 42 R 92298WXM Net 161.95



SAVE \$6.90

From Individual Catalog Prices

Only **144⁹⁵**

No Money Down*



Body Mount



Cable




Bumper Mount

Mobile Systems

Consists of: Lafayette TELSAT 924 23-channel crystal-controlled CB transceiver; stainless steel Body Mount Antenna. 20' RG-58/U coaxial cable assembly. Shpg. wt., 20¼ lbs. 42 R 92306WXM Net 144.95 Same system as above except with Bumper Mount instead of body mount antenna. Shpg. wt., 20¼ lbs. 42 R 92314WXM Net 146.95

COMSTAT 25B 23 CHANNEL 2-WAY RADIO SYSTEMS



Ground Plane

SAVE \$8.60

From Individual Catalog Prices

Only **163⁹⁵**

No Money Down*



Cable



Range Boost II

Base Systems

Consists of: Lafayette Comstat 25B 23 channel crystal-controlled CB transceiver; heavy duty Ground Plane Antenna; and 50' RG-8/U cable assembly. Shpg. wt., 28¼ lbs. 42 R 91605WXM Net 163.95 Same system as above except with "Range Boost II" high gain 1/2 wave length base station antenna. Shpg. wt., 30 lbs. 42 R 91035WXM Net 170.95



SAVE \$7.90

From Individual Catalog Prices

Only **153⁹⁵**

No Money Down*



Body Mount



Cable



Bumper Mount

Mobile Systems

Consists of: Lafayette Comstat 25B 23 channel crystal-controlled CB transceiver; stainless steel Body Mount Antenna; 20' RG-58/U coaxial cable assembly. Wt., 25¼ lbs. 42 R 91613WXM Net 153.95 Same system as above except with bumper mount instead of body mount antenna. 42 R 91621WXM Wt., 25¼ lbs. Net 155.95

*See Page 22 for Full Credit Details on Easy Pay Plan

LAFAYETTE Comstat 25B 23 Channel Crystal Control Two-Way Radio



FCC Type
Accepted


With Standby Switch for Low Current Instantaneous Operation

only **149⁹⁵** No Money Down*

**Famous 23 Channel
CB Best Seller!**

All Crystals Supplied!

FEATURES



1. Range Boost Switch
2. Illuminated "S"/"PRF" Meter
3. Illuminated Channel Indicator
4. Single-Knob Channel Selector
5. Modulation Indicator Light
6. Front Panel PM Speaker
7. CB/Public Address Switch
8. Headphone/External Speaker Jack
9. Positive-Lock Mike Connector
10. 2.5 kHz Fine Tuning Vernier
11. Volume Control/Power Switch
12. Adjustable Squelch Control with Standby Switch for Low Drain Instant Operation
13. T.V. Interference Trap (Rear)

- 17 Tube Performance with 11 Tubes, 2 Transistors and 11 Diodes
- Built-in 117 VAC, 12 VDC Solid-State Power Supply
- Dual Conversion Receiver Features 8/10 μ V Sensitivity
- Range Boost Circuitry for Added Talk Power
- PiNetwork and Low Pass Filter for Maximum Power Output
- Vari-tilt Mounting Bracket

The pace-setting Lafayette Comstat 25B, with its high performance circuitry for excellent mobile and base station operation, features a handsome midnight-black and contrasting brushed aluminum front panel with complementary multi-colored illuminated "S-PRF" meter and attractive control knobs. A 2.5 kHz total spread fine tuning vernier facilitates accurate reception. Highly selective circuits greatly suppress adjacent channel interference (-45db). Variable squelch quiets receiver between calls. Crystal frequency synthesizer enables operation on all 23 CB channels with crystals supplied. No extra crystals are necessary! Built-in dual purpose power supply allows 12-VDC mobile and 115-VAC base station operation. Front panel switch converts transceiver to a handy 4.5 watt public address amplifier. A convenient front panel jack for headphones or external extension speakers for CB/PA is provided. Comstat 25B also features push-to-talk relay switching and plug-in ceramic microphone with coiled cord. Complete with varitilt mounting bracket which facilitates both easy mounting and optimum positioning of set as well as serving as an adjustable table top base. With FCC License Application Form 505. Size: 12Wx8 1/2Dx5"H. Imported. Shpg. wt., 19 1/2 lbs. 99 R 32146W Net 149.95

The Popular Mobile Favorite!

LAFAYETTE HB-525E Solid-State Mobile CB 2-Way Radio

23 CRYSTAL CONTROLLED CB CHANNELS

FCC TYPE ACCEPTED
DOC APPROVED



ONLY 2 3/4" HIGH

- 19-Transistors, 10-Diodes, 1-Thermistor
- Dual Conversion For High Selectivity
- Variable Squelch Plus Series Gate Automatic Noise Limiting
- Pi-Network for Optimum RF Output
- Mechanical 455 kHz Filter
- Large Automatic S/Prf Illuminated Meter
- Advanced RF Overload Protection (Pat. Pend.)
- 3-Position Crystal Delta Tune
- Transmit and Receive Indicator Lights
- Advanced AGC for Outstanding Audio
- Range Boost™ Circuitry for Added Talk Power
- P.A. Amplifier with External Speaker
- 4 x 6" Speaker for Better Audio
- 12 Volt DC Operation (Neg. or Pos. Ground)
- 117 VAC Operation with Optional AC Supply


ONLY **149⁹⁵** No Money Down*

ALL CB CRYSTALS SUPPLIED

Lafayette's most advanced model of the famous HB-525 series of CB transceivers. With all the great features including large illuminated automatic S/Prf meter, receive indicator light and simulated leather front panel. Crystal controlled synthesizer provides 23 channel transmit and receive operation . . . all crystals supplied. Dual conversion receiver incorporates 455 kHz mechanical filter plus revised IF stage for high selectivity, superior adjacent channel rejection, and exceptional Automatic Gain Control and audio characteristics. Variable squelch quiets receiver when no signal is being received. 3-position crystal delta tune permits easy copy of off-frequency stations. Powerful 5 watt transmitter features range boost modulation circuit for greater effective range. Large illuminated automatic S/Prf meter indicates signal strength or receive and RF output on transmit. Full public address provisions include audio input jack for tape recorder, tuner, etc. Also features indicator lights for transmit and receive modes. Supplied with PTT dynamic mike, mobile mounting bracket, DC cable, and FCC license Form 505. Size: 2 3/4 x 6 1/4 x 8" D. Imported. 99 R 32369WUX Shpg. wt., 7 lbs. Net 149.95

MODEL HB-502B AC POWER SUPPLY/CHARGER
For 117 VAC base station operation of HB-525E; also charges HB-506A Nicad batteries. Shpg. wt., 5 lbs.
99 R 3208BW Net 19.95

MODEL HB-506A PORTABLE DC POWER PACK
Attaches to HB-525E for convenient portable operation. Shpg. wt., 2 lbs.
99 R 32336W Less Batteries Net 19.95



HB-506A
with
HB-525E

Portable

HB-525E

HB-502B

Base Station

*"C" Long Life Dry Cell (8 req.) for HB-506A. Shpg. wt., 4 oz.
99 R 63687 Net ea. .22; 10 for 1.80

"C" Alkaline, Alternate HB-506A Battery (8 req.)
99 R 63802 Shpg. wt., 4 oz. Net ea. .48

"C" Nicad, Alternate HB-506A Battery (10 req.)
32 R 48887 Shpg. wt., 5 oz. Net ea. 3.90

†0.D.C. Permits Legal Operation On 19 Channels only in 27.00 MHz Thru 27.30 MHz Range.

LAFAYETTE Comstat 23 Mark VI



FCC TYPE ACCEPTED

23 Channel Crystal Controlled Two-Way Radio

*Amazing
Low Price!*

Only

109⁹⁵


No Money
Down*

ALL CRYSTALS
SUPPLIED

- Dual Conversion Receiver Features 8/10 μ V Sensitivity
- 14 Tube Performance with 9 Tubes, and 9 Diodes
- Variable Squelch Control with Standby Switch for Low Drain Instant Operation

- Pi-Network and Low Pass Filter
- Internal Range Boost Circuitry for Greater Average Talk Power
- Built-in 117 VAC Power Supply, Operates Mobile with Optional 12 VDC Supply

FEATURES



1. Illuminated "S"/"PRF" Meter
2. Illuminated Channel Indicator
3. Single Knob Channel Selector
4. Large Front Panel PM Speaker
5. Tape Record Output Jack (Rear)
6. Transmit Modulation Indicator Light
7. CB/Public Address Switch
8. Headphone/External Speaker Jack
9. Variable Squelch Control with Standby Switch for Low Drain Instant Operation
10. Volume/Power ON-OFF Control
11. Positive-Lock Microphone Socket

Lafayette offers a truly great CB value, the Comstat 23 Mark VI deluxe 5-watt CB transceiver with 23 crystal-controlled channels at an amazingly low price. Crystal synthesizer circuit includes all crystals necessary for active coverage of all 23 CB channels. Features a sensitive and selective dual conversion superheterodyne receiver with 0.8 μ V sensitivity. A variable squelch control for quieting receiver during "no signal" conditions; full-time automatic noise limiter; and a tape recorder output jack on the rear panel. Audio output is 4-watts into a built-in 3 $\frac{1}{2}$ in. speaker. RF output is coupled through a highly effective pi-network and lowpass filter for maximum energy transfer to the antenna. Matches antennas from 50-75 ohms. Range Boost circuitry is incorporated for greater average talk power. Includes standby switch for low current drain and instant operation. With facilities for PA and external speaker or phones of 4-8 ohm impedance. For operation on 105-120 volts AC, 50/60 Hz or operates mobile with the use of the optional 12 volt power supply. Size: 12Wx8 $\frac{1}{2}$ Dx5 $\frac{1}{2}$ H. Imported. Shpg. wt., 16 lbs. 99 R 32237W Net 109.95

OPTIONAL ACCESSORIES

HA-19 DC POWER SUPPLY. Permits 12 volt mobile operation with negative or positive battery ground. 6Wx4Hx4 $\frac{1}{2}$ "D. Shpg. wt., 4 lbs. 42 R 47045W Net 14.95

Mobile Mounting Bracket facilitates under-dash mobile mounting. Imported. Shpg. wt., 2 lbs. 99 R 31874 Net 2.95

Another LAFAYETTE 2-Way Radio Exclusive!

2 MORE CHANNELS WITH EACH ADDED PLUG-IN CRYSTAL!

FCC Type
Accepted
DOC
Approved



23 CHANNEL CRYSTAL CONTROLLED MOBILE 2-WAY RADIO

ONLY **99⁹⁵**

with Crystals
For Operation
on Channels
9, 13, 19

- ★ Full 5-Watt Maximum Input Power
- ★ Dual Conversion Superheterodyne Receiver
- ★ With RF Overload Protection (Pat. Pend.)
- ★ 'Range Boost' for Greater Range
- ★ Burglar Alarm Switch

- Operates on 12 Volts DC Negative or Positive Ground and 117 VAC With Optional AC Supply
- Portable Operation With Optional Battery Pack
- Simulated Leather Front Panel
- 455 kHz Mechanical Filter
- Variable Squelch Plus Automatic Noise Limiting
- Large 5x3 inch Speaker for Superior Audio

Solid-state ultra compact synthesis CB transceiver features superior automatic gain control and sensitivity, greatly increased dependability, and lower current drain. Synthesis type frequency control section permits economical addition of 2 channels with each additional plug-in crystal. Carefully tuned 455 kHz mechanical filter assures razor sharp selectivity with excellent adjacent channel rejection. Dual conversion receiver with RF stage, features 0.7 μ v sensitivity, automatic noise limiting, variable squelch, and push-pull audio amplifier. Transmitter provides full 5 watt legal limit input and "Range Boost" circuitry for greater average modulation and transmitting range. Illuminated front panel meter monitors "S" units on receive and "PRF" output during transmit. PA Speaker/Earphone jack for silent listening or public address operation. Complete with automatic burglar alarm switch, dynamic push-to-talk microphone, power cable, mounting bracket, fixed crystals for channels 9, 13, and 19, and FCC application Form 505. Size: 6"Wx8"Dx2"H. Imported.

99 R 32351WX Shpg. wt., 6¼ lbs. Net 99.95

Package of 10 Plug-in Crystals. Converts HB-23A to full 23 channel operation. 99 R 31742 Shpg. wt., 1 lb. 2 oz. Net 25.00

HB-502B Solid State 117VAC Power Supply/Charger. Enables operation of HB-23A as a table top 117 VAC base station, also charges nickel cadmium batteries used in the HB-507. 99 R 32088W Net 99.95

Model HB-507 Portable Battery Pack. Adapts HB-23A for convenient portable operation with shoulder strap. Less "C" batteries. 99 R 31551 Shpg. wt., 4 lbs. Net 19.95

"C" Alkaline Battery for HB-507 (8 req.) Net ea. .48

99 R 63802 Shpg. wt., ea. 5 oz. Net ea. .48

Alternate Nickel Cadmium Battery. Shpg. wt., ea. 5 oz. (10 req.) Net ea. 3.90

32 R 48887 Net ea. 3.90

*See Page 22 for Full Credit Details on Easy Pay Plan

HB-507



Portable HB-23A
With HB-507
Power Pack

HB-23A
Base Station



HB-502B

OPTIONAL INDIVIDUAL PLUG-IN CRYSTALS

Each Crystal Adds 2 Operating Channels. Inserts Into Specified Crystal Sockets. Shpg. wt., 2 oz.

99 R 31635 Channels 1 and 5; For Socket A

99 R 31643 Channels 2 and 6; For Socket B

99 R 31650 Channels 3 and 7; For Socket C

99 R 31668 Channels 4 and 8; For Socket D

99 R 31684 Channels 10 and 14; For Socket F

99 R 31692 Channels 11 and 15; For Socket G

99 R 31700 Channels 12 and 16; For Socket H

99 R 31718 Channels 17 and 21; For Socket I

99 R 31726 Channels 18 and 22; For Socket J

99 R 31734 Channels 20 and 23; For Socket L

Any One of Above Crystals Net each 3.45

LAFAYETTE MODEL HE-20T 5-WATT SOLID-STATE CITIZEN BAND 2-WAY RADIO



FCC Type Accepted

For Base Station and Mobile Operation

- 12 Channel Crystal Controlled Transmit and Receive
- 23 Channel Tuneable Receive
- 455 kHz Mechanical Filter
- Priva-Com Private Tone Caller Socket
- "Range Boost" for Extra Talk Power
- Also a PA Amplifier with External Speaker

ONLY
89⁹⁵

- For 117 VAC Base Station and for 12 VDC (Negative or Positive) Mobile Operation
- TVI trap
- Spotting Switch for Accurate Reception
- With RF Overload Protection (Pat. Pend.)

Newest addition to the popular HE-20 series of CB transceivers. This 13 transistor, 10 diode Solid State transceiver is ideal for fixed and mobile communications. Solid-state circuitry features low battery drain and provides instant operation; full 5-watt transmitter input with efficient push-pull audio modulator plus "Range Boost" for greater talk power, and an extra-sensitive superheterodyne receiver with sensitivity of .7 μ V for 10 db signal-to-noise ratio. Fine selectivity and adjacent channel rejection is obtained through a 455 kHz mechanical filter. Receiver also incorporates automatic floating series-gate noise limiter and variable squelch control resulting in virtually no background noise between calls. Other features: dust-free transmit/receive relay, earphone jack for headphones or external extension speaker for CB/PA application, illuminated "S" and relative power output meter, mobile mounting bracket and front panel-mounted 4" speaker. Also features Priva-Com private tone caller socket. Complete with fused DC line cord for negative ground

battery, push-to-talk mike and set of crystals for channel 9. Includes FCC license application form 505. Size 8 $\frac{1}{4}$ "x4 $\frac{3}{8}$ "x1 $\frac{3}{8}$ "D. Imported. 99 R 30884W Shpg. wt., 15 lbs. No Money Down" Net 89.95

OPTIONAL ACCESSORIES

99 R 31064 Positive ground fused 12 VDC cord. Wt., 4 oz.	Net	1.50
46 R 65 Extra transmit crystal (specify channel)†	Net	2.25
46 R 10 Extra receive crystal (specify channel)†	Net	2.25
HE-20T Modified for 26.62 MHz (C.A.P.) operation		
99 R 31023WXY	Net	99.95
HE-20T Modified for 27.575 MHz (GOV'T) operation		
99 R 31031WXY	Net	99.95
HE-20T For 27.575 plus 27.585 MHz (FED. GOV'T) operation		
99 R 32385WXY	Net	109.95

†See Page 444 for "How To Order Crystals."

Base Systems

Model HE-20T ECONOMY 2-WAY RADIO SYSTEMS

Mobile Systems



SAVE \$5.60

From Individual Catalog Prices

106.95

No Money Down*

Cable

Consists of: Lafayette Model HE-20T 23 channel tuneable plus 12 channel crystal-controlled base and mobile solid-state CB transceiver; heavy duty Ground Plane Antenna; 50' RG-8/U low loss cable assy. 42 R 91639WXM Wt., 23 $\frac{3}{4}$ lbs. Net 106.95 Same system as above except with "Range Boost II" deluxe $\frac{1}{2}$ wave end-fed antenna. 42 R 91647WXM Wt., 25 $\frac{1}{2}$ lbs. Net 113.95



SAVE \$3.90

From Individual Catalog Prices

97.95

No Money Down*

Cable

Consists of: Lafayette HE-20T 23 channel tuneable plus 12 channel crystal-controlled base and mobile solid-state CB transceiver; stainless steel Body Mount Antenna; and 20' RG-58/U coaxial cable assembly. 42 R 91654WXM Wt., 20 $\frac{3}{4}$ lbs. Net 97.95 Same system as above except with bumper mount instead of body mount antenna. 42 R 91662WXM Wt., 20 $\frac{3}{4}$ lbs. Net 99.95



FOR YOUR WELL BEING... FOR YOUR SAFETY!

The World's Smallest 5 Watt 12 Channel Two Way Radio

1 3/4" HIGH!

Lafayette

MINI-MOBILE

Micro-12

Only **79⁹⁵**

FCC Type Accepted
D.O.C. Approved



★ 12-Channel Crystal Control 5-Watt 2-Way Radio ★

For: Car, Truck, Trailer, Boat, Tractor, Plane, Snowmobile, Cycle, Etc.

- 5-Watt Maximum FCC Legal Input Power
- 12-Channel Crystal Controlled
- Highly Sensitive Receiver with RF Stage
- Full-Time "Range-Boost" for Greater Effective Range
- Variable Squelch for Silent Standby
- Automatic Noise Limiting Minimizes Noise Pick-up

A boon to 5 watt mobile communications! The Lafayette Micro-12 miniature trail blazer embodies exceptional versatility and flexibility. Designed and built for extra reliable performance, its compactness and size make it ideal for mobile and portable communications. In addition to the outstanding features listed above the Micro-12 includes a 3-stage transmit circuit with up to 100% modulation capability, an antenna matching adjustment for maximum radiated power, and a highly sensitive receiver with RF stage for 1 μ v. sensitivity at 10db S/N. The Micro-12 also features superior zener diode voltage regulation, very low current drain that permits continuous mobile operation—even with the motor off, a TVI trap for minimizing TV interference, an illuminated channel indicator dial, and an 8-16 ohm external earphone/speaker jack for private or remote listening. Supplied complete with push-to-talk dynamic microphone with retractile cord, "quick-release" mobile mounting bracket, channel 10 crystals, DC power lead, and FCC Form 505. Size: 5W1 3/4"Hx 7 1/2"D. Shpg. wt., 5 lbs.

99 R 31957W	No Money Down*	Net 79.95
EXTRA CRYSTALS FOR MICRO-12.		
46 R 15† Transmit Crystal (specify channel)		Net ea. 2.25
46 R 10† Receive Crystal (specify channel)		Net ea. 2.25

- Mechanical IF Filter for High Adjacent Channel Rejection
- Operates on 12 Volts DC Negative Ground (Easily Convertible to Positive Ground), on 117 VAC with Optional AC Supply, and With Optional Portable Battery Pack
- Very Low Current Drain: Less than 0.7 Amp. on Transmit
- Miniature Size: 1 3/4"Hx5Wx7 1/2"D.

Micro-12 Modified for 26.620 MHz. C.A.P.		
99 R 32310WXY No Money Down*		Net 89.95
Micro-12 Modified for 27.575 plus 27.585MHz. U.S. Gov't.		
99 R 32328WXY No Money Down*		Net 99.95
Micro-12 Modified for 27.980 MHz (Coast Guard Auxiliary).		
99 R 32393WXY No Money Down*		Net 89.95

HB-509A Portable Battery Pack. Attaches to Micro-12 for conversion to portable operation. Supplied with telescoping whip antenna, battery condition meter, microphone clip and shoulder strap. Less batteries.

99 R 32260 Shpg. wt., 3 lbs., 5 oz.		Net 19.95
Alkaline Battery for HB-509A (8 req.)		
99 R 63902 Shpg. wt., 3 oz.		Net ea. .48
Alternate Nicad Battery for HB-509A (10 req.)		
32 R 48887 Shpg. wt., 5 oz.		Net ea. 3.90

HB-512 AC Power Supply. Permits 117 VAC operation of Micro-12 and charges optional nicad batteries used in HB-509A. Shpg. wt., 4 3/4 lbs.

†See Page 444 for "How to order Crystals."

BASE STATION AT HOME OR OFFICE



PORTABLE FOR HUNTING, CYCLING, SPORTS, ETC.



*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Telsat SSB-25 CB Two-way Radio

TRUE SINGLE SIDEBAND PLUS AM 2-WAY RADIO



23 Crystal Controlled AM Channels . . . Plus 46 Crystal Controlled Single Sideband Channels (Upper plus Lower Sidebands)


- Built-in 117 VAC and 12.6 VDC Power Supplies for Base and Mobile Operation
- Suppressed Carrier on Sideband for Greater Talk Power
- "Range Boost" and Automatic Modulation Control
- Dual Conversion Superheterodyne Receiver with Sensitivity of 0.5 μ V on AM and 0.15 μ V on SSB
- Built-in Product Detector for Outstanding SSB Reception
- Continuously Variable Fine Tuning for Clarifying SSB and for More Accurate AM Reception
- RF Noise Silencer Circuitry Plus Variable Squelch
- Large Illuminated Front Panel "S" and P-RF Meters
- RF Gain Control for Reduction of Overloading on Strong Local Signals and for Optimum SSB Reception
- Automatic Burglar Alarm Switch

Compatible with ALL AM, DSB, and SSB CB Transceivers!

Only **299⁹⁵** No Money Down*

- * 15 Watts P-E-P SSB Input Power
- * Provides 100% Talk Power
- * Crystal Lattice Filter

MORE FEATURES



1. Large Illuminated Signal Strength "S" Meter.
2. Illuminated Channel Selector Switch.
3. Large Illuminated P-RF Output Meter.
4. Noise Silencer, Automatic Noise Limiting and PA Selector Switch.
5. Lower Sideband, Upper Sideband, AM Selector Switch.
6. RF Gain Control.
7. Volume, On-Off Switch.
8. Fine Tuning Control.
9. Variable Squelch Control.
10. Public Address External Speaker Jack (Rear)
11. External Auxiliary Input Jack for Tuner, Tape, Phono, Etc. (Rear).
12. Tape Record Output Jack
13. External Remote Speaker/Headphone Jack (Rear)
14. Adjustable Antenna Loading Coil for Maximum RF Output. (Rear)
15. Adjustable TVI Filter Network for Minimum TV Interference. (Rear)

Lafayette's compatible Telsat SSB-25 AM-True Single Sideband Solid-State 2-way Radio has been meticulously designed and engineered for outstanding citizens band performance. In addition to the deluxe features that result in exceptional conventional 23 channel crystal-controlled AM transmission and reception, the Telsat SSB-25 forges ahead with True-Single Sideband features that result in the addition of 46 more channel modes of operation with much greater effective transmit power, as well as in low noise, highly sensitive reception with a minimum of interference. Its powerful "true" single sideband transmitter, instead of dissipating its power in the carrier and duplicate sideband, concentrates all its power in the single selected upper or lower sideband . . . You get 100% talk power with far greater effective output and range! The transmitter also features internal RANGE-BOOST circuitry and adjustable antenna loading for maximum RF output. In addition to the highly dependable reception of the 23 crystal controlled AM channels, the superbly engineered dual conversion superheterodyne receiver receives 46 frequency modes on single sideband (23 on upper and 23 on lower sidebands) and features a crystal lattice filter that provides maximum signal-to-noise ratio resulting in far greater usable sensitivity while rejecting adjacent channel interference. The receiver also features a built-in product detector for superior reception of SSB transmissions, continuously variable fine tuning to clarify reception of SSB transmissions and to improve reception of AM stations, as well as unique RF noise silencing circuitry to minimize ignition type noise interference. Supplied complete with Push-to-Talk Dynamic Microphone, AC and DC Power Cables, Mobile Mounting Bracket, and FCC License Form 505. Operates as base station on 117 VAC and mobile on 12.6 VDC. Negative Ground Only. Size: 9 $\frac{1}{2}$ " x 3 $\frac{3}{4}$ " x 11 $\frac{1}{4}$ " D. Imported. Shpg. wt., 15 $\frac{1}{2}$ lbs. **99 R 32377WUX** Net 299.95

**FROM
LAFAYETTE**

A 23 Channel Crystal Control CB 2-Way Radio

PLUS

An Emergency Channel 9 Monitor Receiver!



FLASH...FLASH...FLASH

**Blinks The Emergency Monitor... You Switch To CB Channel 9
To HELP SOMEONE IN DISTRESS!**

- Dual Conversion 23 Channel Receiver
- Single Conversion Channel 9 Monitor Receiver
- 7 μ v Main Receiver Sensitivity
- 3 Position Crystal Delta Fine Tuning
- Individual Variable Squelch for Each Receiver
- Public Address Facilities • R.F. Overload Protective Circuitry
- 455 kHz. Mechanical Filter
- "Range Boost" for Greater Effective Range
- Built-in 115 Volt AC and 12 Volt DC Power Supplies for Base Station and Mobile Operation

**LAFAYETTE
TELSAT-924**

ONLY **139**⁹⁵

No Money Down*


All Crystals Supplied!

A true milestone in the finest tradition of Citizens Band applications, the Lafayette Telsat-924 features a separate receiver for monitoring Emergency Channel 9 and a superb 23 channel crystal control synthesis type transmit and receive CB two-way radio in one attractively designed compact unit. When a channel 9 Emergency transmission is received, the emergency monitor light blinks without interfering with regular communications. Activate the Normal/Monitor pushbutton switch to the Monitor position and listen to the message. You can immediately try to summon help via phone, etc. If further information is required, push the variable squelch plus noise limiting, a 455 kHz mechanical filter for excellent selectivity, and R.F. overload protection. The channel 9 emergency monitor receiver features individual variable squelch, and a visual receive indicator light. Additional desirable features are output jacks for external public address speaker, for tape recorder and for headphone for private listening. An illuminated front panel meter monitors "S" units on receive and relative power output on transmit. Supplied complete with dynamic push-to-talk microphone, mobile mounting bracket, DC cable for negative ground vehicles, and FCC license application Form 505. For 115 VAC and 12 VDC operation. Size: 4 1/4" H x 11 3/4" W x 8" D. Imported. Shpg. wt., 13 3/4 lbs.

The Telsat-924 is excellent for base station and mobile base or personal communications and incorporates an outstanding transmitter with FCC maximum allowable input power and highly efficient power output. It includes "Range Boost" circuitry for high average talk power and greater effective range, adjustable antenna loading for maximum RF output to the antenna, a T.V.I. trap for minimum TV Interference, and a modulation indicator light.

The Telsat-924 features two superbly designed receivers. The main 23 channel receiver is dual conversion with .7 μ v sensitivity at 10 db S/N, image rejection of 42 db, ± 1.5 kHz crystal delta fine tuning for hearing "off channel" stations, individual variable squelch plus noise limiting, a 455 kHz mechanical filter for excellent selectivity, and R.F. overload protection. The channel 9 emergency monitor receiver features individual variable squelch, and a visual receive indicator light. Additional desirable features are output jacks for external public address speaker, for tape recorder and for headphone for private listening. An illuminated front panel meter monitors "S" units on receive and relative power output on transmit. Supplied complete with dynamic push-to-talk microphone, mobile mounting bracket, DC cable for negative ground vehicles, and FCC license application Form 505. For 115 VAC and 12 VDC operation. Size: 4 1/4" H x 11 3/4" W x 8" D. Imported. Shpg. wt., 13 3/4 lbs.

99 R 32435WUX Net 139.95
DC Cable for positive ground vehicles. Shpg. wt., 4 oz.
99 R 31064 Net 1.50




FEATURES

- 1—Illuminated "S"-PRF Meter
- 2—Emergency Monitor Blinker Indicator Light
- 3—Illuminated Channel Selector Dial
- 4—P.A. External Speaker Jack (Rear)
- 5—Tape Record Output Jack (Rear)
- 6—Adjustable Antenna Loading (Rear)
- 7—Adjustable TVI Trap (Rear)
- 8—Modulation Indicator Light
- 9—Microphone Socket
- 10— ± 1.5 kHz Crystal Delta Fine Tune
- 11—Individual Normal and Monitor Variable Squelch Controls
- 12—Volume, On-Off Control
- 13—Phone Jack for Private Listening
- 14—Norm/Monitor Push Button Switch

*See Page 22 for Full Credit Details on Easy Pay Plan

Lafayette Cat. No. 720 467

WHY aren't you listening to the two extra channels in your stereo records, tapes, and FM broadcasts?



Convert to 4 DIMENSIONAL STEREO with the LAFAYETTE 4-Channel Stereo Adapter

Just add the Lafayette 4-channel Adapter and two more speakers to convert your present stereo system to a sensational derived 4-channel stereo surround system.

Add the Lafayette 4 Channel Stereo Adapter and two additional speakers to any existing stereo amplifier or receiver and enjoy multi-dimensional derived 4-channel stereo sound from regular 2-channel stereo records, tapes, and FM broadcasts. In addition, the adapter is compatible for use with any 4-channel-encoded source material. The Lafayette 4-Channel Adapter actually recovers "reflected" sounds that already exist on regular stereo recordings but are "hidden" during conventional 2-channel stereo playback. During a stereo recording session, the microphones pick up two types of sounds: direct and reflected, both of which are always included on a stereo recording. Because of the limitations of a conventional stereo system with 2 speakers in the front only, the reflected sounds are not reproduced. The Lafayette 4 Channel Adapter recovers these "reflected" sounds and reproduces them thru two additional rear speakers along with the direct sound from the existing front speakers. Now, the acoustics of the original recording location have actually been introduced into your own listening room. This adds a dramatic new dimension to all existing 2-channel stereo programs—the sound literally envelops you and becomes astonishingly "live". Unlike others, this adapter preserves full channel separation and does not require an additional stereo amplifier. Connects to any standard stereo amplifier or receiver and 4, 8, or 16 ohm speakers. For even better results from your records, we recommend the Lafayette/Pickering Phase 44 magnetic stereo cartridge (See page 83). The Adapter has a 4-position Function switch (Balance, 4-CH, Front Speakers, Rear Only), plus a Rear Speaker Level Control. Phono jacks on rear for easy hook-up to 4 speakers and amplifier/receiver. 3 pairs of cables supplied with phono plugs at one end. One 6 ft. pair for adapter to receiver, one 15 ft. pair for adapter to front speakers, one 25 ft. pair for adapter to rear speakers. Dimensions: 5¼Wx4"Dx27/8"H. Imported.



LAFAYETTE'S Exclusive Geared Control Mechanism Patent Applied For

29⁹⁵
With All Connecting Cables

Exclusive Lafayette/Pickering Phase 44 Elliptical Diamond Needle Stereo Cartridge

44⁹⁵



Especially Designed for Derived 4-Channel Stereo Systems
See Page 83 for Complete Description

99 R 02594 Shpg wt., 3 lbs. Net 29.95

See page 18 for Money Saving Packages Featuring the Lafayette 4-channel Adapter and Lafayette Speaker Systems

LAFAYETTE RADIO ELECTRONICS

111 JERICO TURNPIKE SYOSSET, L.I., N.Y. 11791

BULK RATE
U.S. Postage
PAID
LAFAYETTE
Radio Electronics

157360777 M
T BUCKLEY
2831 FAIRHAVEN AVE
ALEXANDRIA VA 22303

Address Correction Requested