

LAFAYETTE

SUPER HOLIDAY Values!

GIFTS FOR ALL

CATALOG NO. 621



NEW! teleSpan™ CITIZENS BAND

TRANSISTORIZED

"WALKIE TALKIE"

Weighs only 8 oz. with battery and case!

The Ideal Set For Young People

15.45 Each
2 FOR 29.95

- No License, Test or Age Limit
- Superregen Receiver, Xtal Controlled Transmitter
- Transmits and Receives up to 1/4 Mile . . . More under favorable conditions
- Plastic Carrying Case, Earphone, Battery Included



NO MONEY DOWN



A compact, portable, low cost transceiver set with truly amazing performance. Simple enough for a child to operate—it requires no licenses or tests of any kind under Federal law. Perfect for camping, sports, etc. Rugged 2 transistor circuit features a powerful super-regenerative receiver with plug-in earphone for private listening. Will receive and transmit up to 1/4 mile under average conditions. Fingertip push-to-talk switch provides instant X-tal controlled transmitter operation. Durable printed circuit and 9-volt battery shock mounted, assure reliable operation. A removable telescoping antenna can be carried separately in the carrying case pouch when not being used. On-off switch is only other control. Complete with carrying cases, earphones, antennas and 1.9V battery. Nothing else to buy!

Size: 5 1/4" H x 2 1/2" W x 1 1/4" D. Shpg. wt., 3 lbs.

HE-37L Set of 2 Transceivers Net 29.95
HE-38L 1 Transceiver Net ea. 15.45
BA-2 Extra batteries for above. ea. .39

NEW! LAFAYETTE MULTIPLEX ADAPTER

- Superior Distortion & Stereo Separation Characteristics
- Self Powered
- Matches With Virtually All Recent Model Wide-Band Tuners Equipped With MPX Output Jacks
- Complete With Enclosure & All Necessary Connecting Cables



Made in U.S.A.

DELIVERY NOV. 15, 1961 47.50
NO MONEY DOWN

Now Enjoy All The Quality & Dynamic Brilliance of Stereo Through Your FM Tuner

Here's the easiest, most inexpensive way for you to enjoy stereo — not records, not tapes, but stereo with all the fidelity and convenience that only FM can provide. Add this exciting new method of stereo reproduction to your component High-Fidelity system with this brilliant new stereo multiplex adapter. Performs beautifully with virtually any late model, wide band tuner, equipped with a multiplex output jack. Requires no special knowledge or tools to hook up—as simple and easy to connect as were your original components. Supplied with all necessary audio cables. All that's required is to merely plug the unit into your tuner, amplifier and AC outlet. Engineered for simplicity of operation, a selector switch conveniently located on the front panel provides for On-Off, Mono-FC and Stereo-FM. Individual pilot lights indicate when power is on and when adapter is operating stereophonically. Beautifully styled to match any decor in textured beige finish cover and smart brushed brass anodized aluminum front panel. Measures 4 1/2" H x 6 1/4" W x 8" D. For 110-120 V, 60 cycle AC. Shpg. wt., 8 lbs.

Net 47.50

Award-Winning

TAPE RECORDER

Never Before Such Quality and Value!

LAFAYETTE Scoops The TAPE RECORDER INDUSTRY

- Up to 2-Hours at 3 3/4 ips on LP Tape
- Provision For External Speaker
- Permits Direct Recording From Radio or Phono
- 2-Speed: 3 3/4, 7 1/2 ips

NO MONEY DOWN 49.50



Perfect for home, school, or office. At home, the RK-400 proves ideal for parties or recording your favorite musical performance. Handy foot-proof operation has been provided by a single rugged function control. Speeds are adjustable and separate on/off volume control. At 3 3/4 ips the RK-400 provides up to two hours of recording time on a standard 600 ft. control (reverse, stop, play and record) and separate on/off volume control. At 3 3/4 ips the RK-400 provides up to two hours of recording time on a standard 600 ft. 2-hours recording on Long play 1/2 mil tape, up to one hour of recording time on an exceptionally fine tonal quality 5" reel of tape. Special 5" heavy duty permanent magnet speaker furnishes an exceptionally fine tonal quality. Record level indicator light facilitates recording by showing you when volume control is correctly set. Jacks are provided for microphone, phono and extension speaker (special alligator clip cord is supplied). These internal jacks permit making recordings directly from your radio or phonograph regardless of their volume control setting. This feature eliminates distortion, hum and outside noise that may be present and give you professional recording results. Complete with sensitive crystal microphone. Finished in attractive scuff resistant pyroxylin material. Dimensions: 11 1/4" x 9 7/8" x 7 1/8". For 110 volts 50-60 cycles. Net 49.50
RK-400WX Shpg. wt., 20 lbs. Net ea. .85
LAFAYETTE ACETATE BASE RECORDING TAPE. Features noise-free reproduction, low abrasion, uniform output, 1 1/2-mil thickness, 5" reel; 600-ft. Shpg. wt., 1/2 lb. lots of 25 up, Net ea. .90
RT-17 lots of 1-4, Net ea. .99 lots of 5-24, Net ea. .90

FOR HOBBYISTS & INTERMEDIATE STUDENTS


NEW! 1200X "MICRO-TECH" MICROSCOPE

- 80X to 1200X in 8 Ranges
- Built-in Sub-Stage Illuminator
- Dual Knob Lever Type Fine Focus
- Complete Set of Dissecting Instruments

19.95

The perfect microscope for the intermediate student or hobbyist. Hardcoated, Huygenian eyepieces, 10X and 20X. 4 achromatic objective lenses in a revolving "click-stop" turret. Available magnifications of 80X, 100X, 160X, 200X, 400X, 600X, 800X and 1200X. Dual knob rack and pinion, coarse focus control and dual knob, lever type fine focus. Stage includes optical condenser and revolving, 5 aperture, disc diaphragm. Sub-stage illuminator and revolving, adjustable down-stop on body tube can be preset to control down focus movement. Spring loaded rack prevents damaging objective against slide. Accessories include 2 prepared slides, 4 blank slides, spatula, scalpel, probe, scissors, tweezers and magnifying glass. All housed in a handsome wooden case with carrying handle and rubber feet. Illuminator operates on pen-light cells or house current, by means of transformer, listed below. Shpg. wt., 6 lbs.

F-700 Net 19.95
F-701 Replacement bulb for F-700 Net .11
BA-155 Battery (2 required) Net ea. .095
Transformer. Permits use of house current for illumination of F-700 "Micro-Tech" microscope.
F-761 Shpg. wt., 8 ozs. Net 1.80



EASY-PAY-PLAN PG. 54 • ORDER BLANK PG. 53

NOW! NO MONEY DOWN when you use Lafayette's NEW EASY-PAY PLAN!

NEW MAIL ORDER AND SALES CENTER


111 JERICHO TURNPIKE
SYOSSET, L. I., NEW YORK
Open Mon. & Fri. 'til 8:45 P.M.

LAFAYETTE RADIO ELECTRONICS


JAMAICA	NEW YORK	BRONX	NEWARK	PLAINFIELD	PARAMUS
165-08 Liberty Ave. Jamaica 33, N. Y. AXtel 1-7080	100 6th Avenue New York 13, N.Y. WOrth 6-5300	542 E. Fordham Rd. Bronx 58, N. Y. FOrdham 7-8813	24 Central Avenue Newark 2, N. J. MArket 2-1661	139 W. 2nd Street Plainfield, N. J. PLainfield 6-4718	182 Route 17 Paramus, N. J. COHax 1-8800
Open MON. and FRI., 'til 8:45 P.M.	Open THUR. 'til 8:45 P.M.	Open THUR. 'til 8:45 P.M.	Open WED. 'til 8:45 P.M.	Open THUR. 'til 8:45 P.M.	Open MON., WED. & FRI. 'til 8:45 P.M.

BOSTON—110 Federal Street, Boston 10, Mass.—HUBbard 2-7850—Open MON. & WED. 'til 8:45 P.M.

• ASSOCIATE STORES — SEE REAR COVER •



LAFAYETTE 7-Transistor Marine & Broadcast 2-Band Radio



A MUST for
Marine Enthusiasts

29.50

NO DOWN MONEY

9 SECTION
ANTENNA EXTENDED



EARPHONE



Carrying Case

- Covers AM Broadcast Plus 1.6-4.8 MC. Marine Band
- Sensitive Receiver Uses 7 Transistors, 2-Diodes, And 1-Thermistor
- 2 Built-In Antennas, Including 9 Section Telescoping Antenna for Marine Band
- Operates on 2 Inexpensive Penlight Batteries
- Complete With Carrying Case, Batteries, and External Earphone
- A Must For Marine Enthusiasts
- Compact and Light-Weight

With this new sensitive transistorized radio, Lafayette answers the needs of the marine enthusiast. Designed to be used by the week-end sailor as well as the serious yachtsman, the FS-223 is a power-packed, 7 Transistor, superheterodyne receiver. It receives both the standard AM broadcast band and the Marine Band (1.6-4.8 MC). A built-in antenna is used for the broadcast band and a 9 section telescoping antenna for the marine band. The telescoping antenna is readily detachable and may be carried in the same manner as a pocket pen. The receiver circuitry utilizes 7 transistors, 2 diodes and 1-thermistor for power-packed performance. Simple selector switch allows choice of Broadcast or Marine Bands and a clearly marked slide dial makes tuning simple. The built-in speaker can be shut-off by inserting an external earphone (supplied) for personal listening. Operates on 2 inexpensive Z cells giving up to 3 times longer life than ordinary 9 volt batteries. Comes complete with 9 section telescoping antenna, carrying case and earphone. Measures only 5 7/8"x3 1/2"x1 1/2". Shpg. wt. 2 lbs. Net 29.50
Replacement batteries for FS-223 7 Transistor radio, 2 required. BA-155 Z Cells Net each .095

POWERFUL 8-Transistor POCKET SIZE RADIO



PERFORMS AS WELL
AS RADIOS 10 TIMES
ITS SIZE!

• 8 TRANSISTORS
+ 1 THERMISTOR
+ 1 DIODE

19.48


NO MONEY DOWN

- MEASURES ONLY 1"x2 1/2"x4 3/8"
- PINPOINT VERNIER TUNING
- 2 1/2" SPEAKER

For music, sporting events or the latest news, carry this lightweight compact portable with you anywhere. Measuring only 1"x2 1/2"x4 3/8" and small enough to fit in your pocket, it provides phenomenal reception throughout the entire AM broadcast band. Constructed with watchmaker precision its 8-transistor circuit pulls in the weakest stations while a full 2 1/2 inch speaker provides clear undistorted sound even at high volumes. Additional features include earphone jack for private listening, magnifying optic glass over dial for easier tuning, thumbwheel on-off volume control, vernier tuning for pinpoint selectivity and a built-in easel stand. Complete with genuine leather case, magnetic earphone with case and battery. Shpg. wt., 1 lb.

FS-118L Net 19.48
BA-2 Replacement Battery Shpg. Wt., 3 oz. Net .39

LAFAYETTE



9-TRANSISTOR PORTABLE 3-BAND RECEIVER

WEATHER, AVIATION, BEACON, MARINE,
AND STANDARD BROADCAST BANDS

EMPLOYS 9 TRANSISTORS,
2 DIODES, PLUS A THERMISTOR
FOR HIGH GAIN PERFORMANCE

For The First Time A Radio That
Receives 190-400 KC Weather,
Airplane and Direction
Beacon Band Plus 1.6-5 MC
Marine Band Plus
Broadcast Band



For
Boats



For
Planes



Weather
Reports



- Adapter for External Speaker
- Earphones with Cord, Plug and Case
- PRECISION DESIGN FOR TOP PERFORMANCE

NO MONEY DOWN **48.95**

- Three Bands Long Wave Weather Band 190-400 KC Broadcast—540-1600 KC Short Wave Marine Band 1.6-5 MC
- Built-in Quality Speaker
- Telescoping 9 Section Antenna
- Earphone With Cord, Plug, and Leather Case
- Sensitivity Control
- Tone Control
- Powered by 4 Inexpensive 1.5V Batteries
- An Outstanding Value At Any Price
- Compact, Lightweight, Self-Contained
- Jack For External Speaker
- Microphone Adapter for P.A. Use

A mighty-mite in any class, the Lafayette 3 band portable outperforms many home radios. Combining extremely sensitive receiver circuitry with compact design, this receiver is the answer to many boatmen, aviators, weather observers, and outdoorsmen. Giving versatility rarely obtainable in other portable receivers, this unit covers Long Wave, Broadcast, and Shortwave Marine Bands. It can be used to receive Weather, Broadcast, Marine, Aviation, Beacon, and Ham Stations. Features a handsome cabinet with clearly marked slide-rule dial. Nine Transistors, 2 diodes, and 1 thermistor. Built for years of trouble-free operation. SPECIFICATIONS: BANDS—190-400 KC, 540-1600 KC, 1.6-5MC. CONTROLS—ON-OFF Switch, Volume, Tuning, Sensitivity, Tone, and Band Switch. Two antennas—A 9-section telescoping antenna for long and short waves and a powerful built-in ferrite antenna for Broadcast stations. PUSH-PULL AUDIO POWER OUTPUT STAGE. OUTPUTS—2 Phone jacks, phono. This compact, highly sensitive receiver comes complete with a handsome leather carrying case, earphone, plug, earphone case, cord, shoulder strap, battery and adapter for an external speaker. Size—8 1/2"x4 7/8"x1 7/8". Carrying weight—less than 3 lbs. Shpg. wt., 4 1/2 lbs.

FS-93L Net 48.95
Replacement battery for above receiver (Four Required).
BA-156 Net each .13

LAFAYETTE "MINI" 6 TRANSISTOR RADIO

ONLY 13.98

- 6 Transistors Plus Germanium Diode and Thermistor
- Vest Pocket Size—Only 3 1/2 H x 2 1/2 W x 1" D.
- Weighs only 7 ounces with batteries
- Penlight Powered For Economy—Long Life
- Earphone Jack Built-in For Private Listening
- Rich Tone Dynamic Speaker
- Trouble-Free Printed Circuit
- Built-in Ferrite Bar Antenna
- Superheterodyne Circuit

A truly remarkable radio, the "MINI" 6 is so compact and lightweight (just 7 oz.) you hardly know you're carrying it—turn it on and get the biggest, clearest sound yet, from a pocket 6 transistor set. Precision engineered—true superheterodyne printed circuit board assures long trouble-free operation. Push-pull audio output, 6 transistors, one diode and one thermistor are utilized to obtain really phenomenal reception across the entire broadcast band. Only 2 two inexpensive penlight cells are required. This cuts down battery drain and lengthens playing time considerably over ordinary single cell radios. "Jewel" black and gold case of durable plastic and soft attractive black leather carrying case with attached earphone pouch complete this smart set. Includes 2 batteries, carrying case and matched earphone for personal listening. All at our low, low price. Shpg. wt., 1.5 lbs. Net 13.98
FS-235L "MINI" 6 transistor Radio
Extra batteries for FS-235L Type Z (2 required). Shpg. wt., 4 oz. Net ea. .095
BA-155



CARRYING
CASE

EARPHONE

BATTERIES

NEW! *Textext*TM 2-TRANSISTOR PORTABLE with BUILT-IN SPEAKER



6.95

- 2-TRANSISTORS + 1 DIODE
- BUILT-IN SPEAKER
- COMPLETE WITH TELESCOPING ANTENNA,
EARPHONE & CARRYING CASE

A two-transistor powerhouse that will amaze you with its performance and sound quality. Here's the perfect gift for that youngster who has always wanted a portable radio or use it yourself—take it anywhere, it plays everywhere. Equipped with both a ferrite antenna and detachable telescoping antenna to assure outstanding reception. In addition to its own built-in speaker the radio is supplied with an earphone for private listening. Small enough to fit in the palm of your hand it measures a mere 4x2 1/2x1 1/4". Complete with earphone, telescoping antenna, carrying case and battery. Shpg. wt., 1 lb. Net 6.95
FS-117L
BA-2 Replacement Battery. Shpg. wt., 3 oz. Net .39

NEW! LAFAYETTE EXECUTIVE DESK RADIO



24.95


NO MONEY DOWN

- IT'S A 7-TRANSISTOR RADIO!
- IT'S A CIGARETTE BOX!
- IT'S A PEN HOLDER!

Now a Three-in-one desk set. A powerful 7 transistor AM broadcast radio specially designed to harmonize with the entire unit. Radio operates on four economical penlight cells to give long dependable service. The dial face is tilted and tuning knobs top mounted for maximum legibility and accessibility. Includes Earphone too for private listening! Right hand portion holds an extra large compartment useful for cigarettes or paper clips, etc. Two convenient penholders complete the set (Pens are not included). Beautiful black and gold finish make a most attractive addition to a desk. The ideal gift. Complete with 4 penlight cells and earphone. Size: 11 3/4"Wx2 3/4"Hx6"D. Net 24.95
FS-236L Shpg. wt., 6 lbs. 2 Yr. 19
Extra "Z" batteries, 4 required. Net ea. .095
BA-155

LAFAYETTE FM-AM TABLE RADIO

"Symphonette"



- For AC or DC
- 4 Inch PM Speaker
- Automatic Volume Control
- Streamline Design Cabinet
- Provision For External Speaker
- Outstanding Listening Pleasure
- 2 Super-Sensitive Built-In Antennas
- Lock-In Automatic Frequency Control

Now you can enjoy the pleasure of quality FM as well as AM radio at a price previously reserved for AM radios alone. The Lafayette "Symphonette" is a complete AM-FM table model radio for AC and DC operation. Incorporating features found only in more expensive units, it brings the luxury of FM reception right to your fingertips. Automatic Frequency Control, utilizing effective triode circuitry, assures drift-free FM operation. Lock-in of FM stations eliminates annoying retuning and adds to your listening pleasure. Automatic Volume Control softens any sudden blasts of volume and makes tuning stations of different levels a cinch. A supersensitive AM tuned-antenna brings in stations clearly while reducing unwanted noise. An FM antenna is provided for to assure all the benefits of clear, pure tone. The 4" PM speaker produces rich sound from low to high range to enhance your music-listening pleasure. A stylish polished plastic cabinet, in distinct, contrasting black and white, has an easy to read slide dial for AM and FM bands. Contains 7 tubes, 2 diodes, and 1 selenium rectifier for 12 tube power-packed performance. A receptacle on the rear of the radio allows quick addition of a second speaker. For 117 volts; 60 cps AC or DC. Size 10" wide, 5" deep, 5 1/4" high. Shpg. wt., 5 lbs.

NEVER BEFORE HAS SUCH HIGH QUALITY BEEN OFFERED AT SUCH A LOW PRICE


JUST COMPARE
29⁵⁰ NO MONEY DOWN

FS-221

Net 29.50

NEW!

LAFAYETTE AM/FM CLOCK RADIO



- Sleep-Switch - Lulls You To Sleep
- Completely Automatic
- AC Appliance Outlet
- Big Set Tone

39⁹⁵

NO MONEY DOWN

The FS-239 combines a fully automatic Telechron clock movement with a superb AM-FM broadcast radio. Handy sleep-switch permits you to slowly drift-off to dreamland while the radio shuts itself off at a preset time. A buzzer alarm is included. In addition to a standard AM broadcast radio, a quality FM radio will expand your listening pleasure plus a 600 watt appliance outlet — useful to turn on the coffee pot, light etc. Slide rule dial for easier tuning. Beautiful low boy plastic cabinet in antique white with gold trim. Tubes: 50C5, 12AU6, 12AL5, 12BA6, 12BE6, 17EW8 plus a selenium rectifier. Size: 14 1/2 x 6 1/2 x 6 1/2". Shpg. wt., 8 lbs.

Net 39.95

NEW! FM-AM DELUXE TABLE RADIO

WITH DUAL SPEAKERS



39⁵⁰ NO MONEY DOWN

- 7 Tubes plus 1 Selenium Rectifier
- Your Choice of Rich Walnut or Mahogany Wood Cabinets
- Two 4" Speakers
- Built-In Ferrite Core Antenna
- Provision For Remote Speakers & Tape Recorder

Sound, performance and features that are astounding in table model radio at this low Lafayette price. Powerful 7 tube plus rectifier FM-AM circuit pulls in stations loud and clear with an absolute minimum of distortion. Two high-quality 4 inch speakers assures you of full fidelity on both FM and AM. Controls include: Power Switch—Tone Control, Volume Control, FM-AM Band Selector and Tuning Control. Output terminals located at the rear provide for the addition of a remote speaker or for recording with your tape re-

recorder. Cabinets are beautifully crafted and finished in your choice of rich walnut or mahogany woods. Beautifully styled to fit with virtually any decor. Supplied complete with wire antenna for FM. Covers 88 mc - 108 mc on FM; 5.3 to 10 Kc on AM. Size: 17 1/2 W x 7 1/2 H x 5 3/4 D. For 117V AC 60 cycle operation.

FS-123 Mahogany Cabinet
FS-125 Walnut Cabinet

Net 39.50
Net 39.50

LAFAYETTE QUALITY RADIOS AT SENSIBLE PRICES

9 TRANSISTOR FM/AM PORTABLE RADIO

NOW HAVE HI-FI Wherever You Go!

- Full FM and AM Broadcast Bands
- 2 Antennas • 2 Antenna Extension Jacks
- 3 Outputs—Speaker, Earphone and Tuner
- Operates on 4 Inexpensive Flashlight Batteries
- 9-Transistor Superheterodyne Circuit
- Complete with Earphone, and Case




NEW! POWERFUL!

69⁹⁵ NO MONEY DOWN

Now you can have all the advantages of a portable radio with all the power of a console... at a price lower than you expect. A wonderful combination of advanced technique and design in an extremely efficient 9-transistor AM and FM portable radio. Features a tuner output that converts this portable to a transistorized AM/FM tuner—real hi-fi. Other highlights include speaker output, earphone output for private listening, separate AM and FM antenna extension jacks, built-in AM antenna, and 7-section telescopic FM antenna. Convenient carrying handle; on/off switch on volume control; vernier tuning knob. 2-position band selector—FM Band 86.5-108 MC, AM band 535-1605 KC. Economical Complete with Earphone, Batteries and Case. Overall 10x2 1/4x6 3/4".

FS-92L Shpg. wt., 5 1/2 lbs. Net 69.95
BA-156 Extra Burgess No. 1 Battery ea. Net .13

LAFAYETTE "LONG DISTANCE" AM-SHORTWAVE TABLE RADIO



SW VALUE of The Year

Only **26⁵⁰** NO MONEY DOWN


- Attractive Decorator Cabinet
- Power Packed 7 Tube Performance—5 Tubes (2 dual purpose)
- Large Slide Rule Tuning Dial with Automatic Indicator Lights
- Provision For External Phonograph • "Big Speaker" Sound

A smart new way to enjoy yourself—listen to short-wave radio! Never before has a SW receiver of this quality been offered at such a low, low price. Beautifully styled to fit into any room, the 231 features 7 tube performance from 5 tubes (2 dual purpose) for maximum station "pulling" power. Separate SW antenna terminal to permit antenna selection suitable for location. Large PM speaker and 3-step tone control enhance your audio pleasure. Extremely legible slide-rule dial has separate pilot lights of different color which automatically switch-on to quickly identify band in use. In addition a phono jack is provided in the rear of the set for connecting any external phonograph. Covers the entire broadcast band and SW band from 3.8—12 MC. Tubes: 6BE6, 6BD6, 6AV6, 6AR5, 6X4. For 117 V, 60 cycles AC. Size 16Wx5 1/4 Dx 5 1/2" H. Shpg. wt., 10 1/2 lbs. Net 26.50

FS-231

PACKED WITH POWER!

LATEST FM-AM PORTABLE RADIO FEATURES 14 TRANSISTORS PLUS 4 DIODES



- Drift-Free Non-Directional FM Tuning
- Precision Slide Rule Tuning
- External Hi-Fi Amplifier Jack
- Powerful FM Telescopic Antenna
- Automatic Frequency Control

54.88 NO MONEY DOWN

All the quality and performance of a high-fidelity AM-FM tuner in an easy to use portable radio you can carry anywhere. Two completely separate AM and FM sections employ 14 transistors plus 4 diodes for unmatched sensitivity and stability. Automatic Frequency Control together with a specially designed di-pole telescopic antenna provides drift-free FM reception. Additional features include: easy slide rule tuning; tone control knob, external hi-fi amplifier jack, earphone jack, built-in ferrite bar antenna and specially developed 3 1/2 inch speaker designed to provide exceptional tone quality even at the highest volumes. Operates on 4 low cost flashlight batteries—low drain provides up to 400 hours of operation from one set of batteries. Supplied less carrying case, but with earphone and batteries. Covers FM band range: 88 mc - 108 mc; AM: 535 Kc - 1600 Kc. Size: 9 1/4 x 7 1/2 x 2 3/8". FS-119L Shpg. wt., 4 3/4 lbs. Net 54.88
Attractive leather carrying case for FS-119L above Net 54.88
FS-121L Net 3.95
BA-156 Extra Burgess No. 1 Battery ea. Net .13

NEW! LAFAYETTE FM RADIO FEATURES QUALITY 5 TUBE CIRCUITRY WITH AFC



- Automatic Frequency Control Locks In Stations
- Full 4" Speaker • Rugged Printed Circuit

Here's the perfect FM radio for your bedroom, kitchen, office or anywhere you want the music that only FM can provide. Outstanding performance and quality for an FM radio of this size and low price. Specially designed 5 tube circuit together with a high quality 4 inch Alnico magnet speaker provides clear, undistorted reception. Automatic Frequency Control locks in the station and prevents drift while an AFC defeat switch permits tuning weak stations adjacent to strong stations. Front panel contains a pilot light, station selector (covers 88-108mc) and velvet smooth On-Off volume control. Rugged printed circuitry will provide years of trouble-free use. Supplied with antenna. Attractive modern two-tone cabinet is an asset to any decor. For 117V 60 cycle operation. Size: 5 1/2 H x 9 3/4 W x 4 1/2 D. Covers full FM band from 88 mc to 108 mc. Shpg. wt., 6 lbs. Net 21.50

FS-236

LAFAYETTE Xmas GIFT SPECIALS

TruText™

SUPER BUY AC/DC TABLE RADIO



8.95


- Power-Packed Performance — 5 Tubes (2-dual purpose)
- "Easy-Tune" Dial
- Attractive Decorator Cabinet
- For Home, Store, Office; Wherever Radio Pleasure is desired

This Lafayette SUPER-BUY features 5 tubes (2 Dual Purpose) giving peak performance for clear, steady sound. A sturdy 3 1/2" Alnico PM Speaker gives fine tone response. An unusual "Easy-Tune" dial makes station selection simple. The built-in antenna covers brings stations in loud and clear. Covers the entire broadcast band from 530 to 1600 KC. Tubes: 1-12BE6, 1-12BD6, 1-12AV6, 1-50C5, 1-35W4. Will operate on 105-125 volts AC or DC. Dimensions 4 1/2" high, 6 3/4" wide, 3 3/4" deep. Shpg. wt., 3 lbs. FS-240 Net 8.95

NEW FAMOUS BRAND 19 INCH PORTABLE TV

- Big Screen 19" 114° Picture Tube
- Thin-line Briefcase-type Styling
- Hand Wired Chassis
- Filament Transformer—17 Tubes
- Built-in Telescoping Antenna

Only **127.50**
No Money Down



Big screen 19" portable television is now yours at a sensible price. Stylish, with convenient top mounted tuning. 17 tubes—3 video IF stages and 2 sound IF stages plus adjacent channel traps provide sharp, clear pictures and sound even in fringe areas. Quality telescoping antenna is adequate for most reception areas, however a convenient outlet is built in for connection of an external antenna if desired. Features a completely hand-wired chassis and a heavy duty filament transformer for top performance and extended tube life. All

components are bolted in—no rivets are used and in addition, the set's tubes are accessible from the rear—important points in keeping down service costs. A full set of controls is included. Channel selector/fine tuning, contrast, off-volume, vert. hold, horiz. hold, brightness, AGC, vert. linearity and height. Finished in Ivory, it will grace any room. Size: 19x15 1/4x12 1/2"D. Shpg. wt., 60 lbs. FS-500WX Net 127.50

NEW!

8" PERSONAL PORTABLE TELEVISION RECEIVER

- Compact Size—Smart Styling
- Front Mounted Speaker For Crystal Clear Sound
- Built-In Telescoping Antenna/earphone Jacks

- Hand Wired Chassis
- 2 Earphones For Private Viewing.

Tomorrow's portable here today! Imagine a TV only 12 inches at its deepest point and weighing only 18 lbs. It is truly the "second" set you have been looking for. Ideal for sickrooms, den, children's room, bedroom or patio. AC operated, the specially designed chassis is completely handwired and constructed for maximum heat dissipation. Tubes are accessible from the rear for easy replacement. Some outstanding features including a built-in telescoping antenna and jacks for external antenna connections; a front mounted speaker for optimum sound dispersion; a local-distance switch for best reception and built-in earphone jacks which provide a choice of earphone listening only or speaker on, plus earphone listening. Powerful advanced design circuit with 13 tubes plus picture tube and silicon rectifier power supply. Cascade tuner, 3 video IF stages, 2 Sound IF stages and adjacent channel traps. Fused AC line. Complete with earphones. Size: 11 1/4"Wx7 3/8"Hx12"D. Shpg. wt., 25 lbs. FS-501WX No Money Down Net 119.50



Only **119.50**
No Money Down

Weights just 18 lbs. Carry it Anywhere!!

ULTRA-MINIATURE 3 TRANSISTOR HEARING AID

- Extremely Light In Weight - Less Than One Ounce
- Extremely Compact; Dimensions: 2 3/4" Long, 3/4" Wide and 1/8" Thick
- Uses Inexpensive, Long Lasting Mercury Cell



29.50
with Battery

Only 2 3/4" x 3/4" x 1/8" — almost as small as a tie clasp, this precision unit employs an advanced 3 transistor circuit powered by a tiny inexpensive mercury cell. A 180° rotating volume control provides exactly the amount of amplification necessary, while a MIC-VIDES exactly the amount of amplification necessary. Supplied with 3 ft. TEL lever readjusts sensitivity for telephone use. Supplied with 3 ft. flesh-tinted cord, earpiece, velvet lined leather carrying case. Mercury cell and instructions. Shpg. wt., 1 lb. Net 29.50
F-758L Net .30
BA-523 Extra Battery (Mallory RM 625R)

SUB-MINIATURE 4-TRANSISTOR HEARING AID

- Lightweight—Weights Less than 2 oz. Including Battery
- Small Enough To Be Carried in Breastpocket
- 4-Position Tone Control
- Unique Telephone Switch Allows Telephone Conversation
- Latest Electro-Magnetic Earphone and Miniature Crystal Microphone
- Utilizes Economical Penlight Battery

ONLY 2 1/2" LONG x 1 3/4" WIDE
22.50 x 3/8" THICK

Features an extremely advanced circuit with 4 transistors, a high performance crystal microphone. 3 ft. thin plug-in colorless flexible cord and a unique magnetic earphone providing the clearest reception and sound reproduction yet achieved. Supplied with leather carrying case, earphone and battery. Shpg. wt., 1 lb. F-480L Net 22.50


BA-153 Extra Battery (1 required) Burgess NE type. Net .08
Shpg. wt., 3 oz. Net .55
F-567 Extra Plug-In Cord For F-480 Net .55
F-568 Extra Earphone For F-480 Net 1.59



"CONTEMPORARY" AC/DC RADIO

- Styled For Any Decor!
- Priced For Every Pocket!
- Put One In Every Room!
- 5 Tubes For Peak Performance!

10.99



A "better" 5 tube radio — engineered and styled to last. Petite, contemporary design maintains clean, good looks and peak performance. 5 tubes (2 dual purpose), plus a Hi-Q ferrite rod antenna pulls in more distant AM stations. 3 1/2" P.M. speaker, properly baffled in a sturdy, vented cabinet for clear tonal quality. Muted colors to match any color-scheme; gold trim. Pedestal base swivels for sound and reception directivity. Cabinet measures 8 1/2" x 4 1/2" x 4" overall. Tubes: 35W4, 50C5, 12AV6, 12BA6, 12BE6. For 117 V. A.C./DC. Shpg. wt., 3 lbs. FS-233 Net 10.99

NEW! HOUSE N' CAR RADIO

- Plays In Any 12V. Car or Boat or on 117V AC/DC
- No Installation — Just Plug In Lighter
- Needs No Outside Antenna
- Complete With Generator Condenser and Noise Suppressor




18.66

Play this radio anywhere! In the home — car — boat — trailer! Any place you can obtain a 12 V D.C. or 117 V AC/DC supply! The radio (our FS-233) and the new Dynamo inverter form a customized package to suit a wealth of needs. You can even run your shaver in your car or boat! Shpg., wt., 5 lbs. SP-229 Net 18.66

NEW! FROM WESTCLOX — THE TRANSALARM®

THE AUTOMATIC TRANSISTOR CLOCK RADIO

- Automatic Radio Alarm—Turns on Radio at Preset Time
- 6 Transistor Radio—Powerful, Full Tone Speaker
- 32-Hour Keywound Clock
- Pocket or Purse Size
- Earphone For "Silent" Listening



21.95
No Money Down

Automatic Alarm Wakes You To Music or Favorite Program Dependable Keywound Clock Cannot Drain Battery Private Earphone Available For "Silent" Listening Shock Resistant Case

The world's largest manufacturer of timepieces, WESTCLOX has something new in the clock-radio design. Features automatic "wake-up-to music" alarm which turns the radio to any preset time selected. Clock operates for 32 hours on one winding—it cannot drain radio battery. Large dial face "shines" in the dark for visibility at night. Powerful 6-transistor radio with built-in ferrite antenna plays at room filling volume. Compact, only 6Wx3 1/4x1 1/2"D make it ideal for night table, desk or travel use. Lightweight tool Radio is keyed to receive

special CONELRAD Civil Defense broadcasts. Easy-to-read program selector—large station numbers pop into view. Beautiful black and gold break-resistant Polystyrene case. Makes a perfect gift for any occasion. Complete with battery and earphone, for private listening. Shpg. wt., 1 lb., 10 oz. FS-242L Net 21.95

Extra 9-V battery for above BA-2 Net .39

NEW GRANCO STEREO MULTIPLEX RADIOS



DR-17 **38.95**



DR-20 **28.95**



DR-18 **23.95**

NO MONEY DOWN

STEREO FM/AM RADIO

Compact, smartly styled table radio plays AF, FM and FM stereo multiplex with the SC-3 Speaker-Amplifier companion. Exclusive "Auto-G-Tuner" assures sensitive, drift free performance. Built-in Linetenna requires no installation. Phono input jack. High power 6 tube chassis provides 8 tube performance. Easy-view window dial and vernier tuning. Cabinet is completely enclosed. Attractive gray with white grill. 9 1/2"Wx4Dx5"H. Shpg. wt., 7 lbs. DR-17 Granco 703 Net 38.95

attaches the SC-3—no installation necessary. Powerful speaker and amplifier. Volume control and function selector switch. For quality stereo at a modest price. Available in Grey. Size: 9 1/2"Wx4Dx5"H. Shpg. wt., 5 lbs. DR-18 Granco SC-3 Net 23.95

Acoustically Matched Stereo Pair Models 703G & SC-3. Shpg. wt., 12 lbs. DR-19 Net 58.95

Low Cost Stereo FM Radio

Super powered, high sensitivity 5 tube chassis provides 7 tube performance. New hand wired detector circuit offers hi-fi and stereo-multiplex at exceptionally low cost with the use of the SC-3, matching FM multiplex speaker/amplifier unit. Other features include new auto-G tuner for drift free performance, easy-view window dial with vernier tuning, phono input jack and built-in antenna. Decorator cabinet encloses entire set. Gray only. Shpg. wt., 6 lbs. DR-20 Granco Model 603G Net 28.95

STEREO COMPANION FOR GRANCO FM RADIOS

- Acoustically Matched
 - Plugs In—No Attachments Necessary
 - Doubles your Sound
- Specifically designed to match Granco radios 603 and 703 both acoustically and aesthetically. For perfect stereo FM reception, an interconnecting plug-in cable

Combination of Model 603 FM Radio and SC-3G Stereo Companion. Shpg. wt., 12 lbs. DR-21 Net 51.50

LAFAYETTE SPECIAL PHONOGRAPH SALE

with **FREE DIAMOND STYLUS**

NO MONEY DOWN
49.95



With **FREE Diamond Stylus**

NO MONEY DOWN
62.95

WITH **FREE DIAMOND STYLUS**



WITH **FREE DIAMOND STYLUS**

NO MONEY DOWN
39.75



You get BOTH sapphire and diamond styli at no extra cost!

FREE DIAMOND NEEDLE OFFER EXPIRES JAN. 15, 1962

LAFAYETTE AUTOMATIC STEREO PHONOGRAPH

- Compatible—Plays Both Stereo and Monaural Records • 4-Speed British Changer

New, attractively styled automatic stereophonic phonograph featuring the latest Monarch 4-speed automatic intermix record changer. Complete with stereo crystal turnover cartridge with dual sapphire stylus. Plays both stereo and monaural records. Among many features are automatic record intermix mechanism, automatic motor shut-off at the end of last record, automatic arm return, free-floating motorboard eliminating acoustic feedback. Careful design assures long life and freedom from trouble. Takes all record sizes, and plays all 4 speeds: 16 2/3, 33 1/3, 45 and 78 RPM. Controls include separate volume controls for each channel and dual channel tone control. Built-in Alnico 5 PM speaker provide clean, balanced sound. Second Alnico 5 PM speaker is housed in the removable phonograph cover. 8 ft. cable supplied, permits placement of second speaker for optimum stereo effect. Covered in charcoal linen leatherette with oyster white trim. Tubes 2-50C5, 1-12AX7 and 35W4 rectifier. Size: 19 1/2 x 15 1/2 x 8 1/4". Shpg. wt., 23 lbs. Net 49.95

LAFAYETTE Deluxe AUTOMATIC STEREO PHONOGRAPH

- 3 Speaker System • 4-Speed V-M Changer • Plays Both Stereo and Monaural Records

New Lafayette deluxe automatic stereophonic phonograph features the famous 4 speed V-M changer. Plays all speeds: 16 2/3, 33 1/3, 45 and 78 RPM. Plays all sizes: 7", 10" and 12" records. Has such features as 4-pole motor, automatic shut-off after last record, etc. Supplied with turnover cartridge. Separate volume controls adjust optimum balance for perfect stereo realism. Separate bass and treble controls permit tonal adjustment of both channels. Has 3 Alnico V PM speakers: 1 in main case and 1 in each wing. Wings may be left in position or can be detached from the sides and placed apart for individual stereo requirement. Tubes: 2-35C5, 1-12AX7, 1-50EH5, 1-35W4 rectifier. Attractive black gold branch leatherette case. Size: 20 x 15 1/2 x 9". Shpg. wt., 29 lbs. Net 62.95

LAFAYETTE AUTOMATIC MONAURAL PORTABLE PHONOGRAPH

- Alnico V PM Speaker • Plays 4 Standard Record Speeds • Complete With Crystal Turnover Cartridge

New, attractively styled automatic monaural portable phonograph featuring 4 speed, 16 2/3, 33 1/3, 45, 78 RPM. Consists of the latest famous British-made Monarch automatic record changer. High-quality Alnico V PM speaker. Uses heavy-duty 4-pole induction type motor for constant speed and minimum "wows". Automatically plays all speeds, and takes all record sizes—7", 10", 12" intermixed in any order. Plays 12" records with lid closed. Arm automatically returns to the rest position and motor shuts off after last record. Lightweight pickup arm has high output crystal turnover cartridge with sapphire stylus. Controls: Tone, Off-On Volume. Durable and attractive cabinet covered in fine leatherette, black with white trim. For 110-120 volts, 60 cycles, A.C. Size 15 1/2 x 16 1/2 x 8 1/4". Shpg. wt., 20 lbs. Net 39.75

OUR finest PORTABLE PHONO!


With **FREE Diamond Stylus**

NO MONEY DOWN!

89.50

- FULLY AUTOMATIC GARRARD CHANGER
- TWO POWERFUL 10 WATT AMPLIFIERS
- SECOND SPEAKER EASILY DETACHED
- 3 SPEAKERS

Plays Both Stereo and Monaural!



9 Ft. Extension Cord

A complete portable and compact stereo phonograph, in one convenient case. System uses the well-known Garrard High-Fi 4-speed stereo changer which features true intermix of 12" and 10" records in any order with instant selection of either automatic or full manual operation. Uses a stereo turnover cartridge to play all your records—whether monaural or stereo. Two powerful 10 watt amplifiers provide a frequency response of 50 to 12,000 cps. Controls included: Master Volume; Remote

speaker volume; Master treble; Master bass. Detachable front speaker cabinet houses a 6" x 9" speaker with 9 ft. extension cord. Main unit houses two speakers—one 6" x 9" woofer and one 4" tweeter. Phonograph has easy-grip handle on attractive smart-looking Pyroxylin covered case. Size: 23x16x9 1/4". Shpg. wt., 40 lbs. Available in choice of 2 attractive coverings. PH-150WX Charcoal Silver Net 89.50 PH-151WX Tan Net 89.50

LAFAYETTE HI-FI "STAR" ★

With **FREE Diamond Stylus**

Better Than Ever!

NO MONEY DOWN!

37.50

- For All Monaural Records
- GE Reluctance Triple Play Cartridge With 2 Sapphire Needles
- Dual Speakers: 6" Wide Range and 4" Tweeter



The famous Lafayette "Star" now incorporates an extended-range speaker system with 50 to 15,000 cps. response. The 4-speed phonograph plays all record sizes up to 12" and has the famous GE variable reluctance "triple play" cartridge with two sapphire tipped needles. With retractable spindle for 45 rpm records. Separate bass and treble tone controls and volume control. The 2 speakers produce a real feeling of "presence." Size 19" x 9" x 16". Covered in your choice of charcoal or light tan shadow branch parchment leatherette. For 110-120 volts, 60 cps AC. Shpg. wt., 15 lbs. PH-155W Charcoal Black Net 37.50 PH-156W Light Tan Net 37.50

MONAURAL RECORD PLAYERS

STANDARD 4-SPEED MANUAL



13.95

"LEADER" 4-SPEED MANUAL

Plays up to 12" monaural records at 16 2/3, 33 1/3, 45 or 78 RPM. A single lever selects any speed. The lightweight pickup arm is equipped with a single all-purpose needle for all records. Has volume control with on-off switch. Fine quality Alnico 5 PM speaker. Attractive leatherette covered case. For 110-120 volts, 60 cycles. Size 11 1/2 x 10 1/2 x 5". Shpg. wt., 9 lbs. PH-148W Net 13.95



18.45

With this portable phonograph you can play any record up to 12" size at 33 1/3, 45 or 78 rpm, or at the new "Talking Book" speed of 16 2/3 rpm. A single lever selects any speed. The lightweight pickup arm is equipped with a turnover cartridge with dual sapphire stylus. Has both tone control and volume control with on-off switch. Has jack for adding extension speaker. Fine quality Alnico 5 PM speaker. Attractive 2-tone leatherette covered case. For 110-120 volts, 60 cps. AC. Dimensions 14x11 1/2 x 6 1/4". Shpg. wt., 10 lbs. PH-149W Net 18.45

DELUXE PORTABLE STEREO PHONOGRAPH "Triple-Source" Stereo Speaker System



109.50

No Money Down

- One 8" Speaker; Two 6" With 1 1/4" Whizzer Cones • Up To 24 Feet of Sound Spread • 4-Speed Automatic Record Changer • Stereo Cartridge with Diamond and Sapphire Needles

An elegant portable which sounds as good as it looks. One 8" speaker in main cabinet reproduces low bass tones for each channel of the stereo record. Two removable remote speaker cabinets each contain a 6" speaker with 1 1/4" whizzer cones, reproduce the medium and high tones taken from their own channels of the stereo record. 12 feet of cable is attached to each remote speaker to provide up to 24 feet of stereo sound spread. Automatic record changer is equipped with a heavy duty motor for rumble-free operation. Plays all 4-speeds. Intermixes all size records of the same speed. 45 RPM Adaptor. Automatic shut-off. Ceramic turnover cartridge has diamond and sapphire needles. Stacked amplifier has 20 watts of peak power. Wood cabinet is smoked gray and silver tweed leatherette. U.L. Approved. Size: Main Unit — 9 3/4 x 25 x 19 3/4", remotes 9 3/4 x 14 x 4 1/2". For 110-120V., 60 cps. AC. Shpg. wt., 40 lbs. PH-158WX No Money Down Net 109.50

PORTABLE STEREO-REVERB PHONO




99.50

NO MONEY DOWN

- 4-Speed Automatic Record Changer • Stereo Turnover Cartridge
- Built-in Reverberation • One 6" Speaker; Two 5 1/4" Speakers

Achieve the magic new sound of stereo plus reverberation. Adds a 4th dimension to high fidelity music which seems to put you in the middle of the orchestra. Reverberation control is variable. Main unit has a 6" speaker for bass tones and the removable remotes have two 5 1/4" speakers for treble tones. Each remote speaker cabinet has 12 feet of cable. 4-speed automatic record changer has heavy duty motor mounted on vibrating-free rotor board. Plays 10-12" or 12-10" records automatically. Automatic shut off at end of best record. Heat resistant ceramic turnover type cartridge, has diamond and sapphire needles. Accepts 45 RPM adaptor. Stereo amplifier puts out a total of 7 watts peak power. 4 controls: dual volume; dual tone, balance and reverberation. Finished in Bronze tone and ivory plastic coated leatherette. Size: Main unit — 20 1/2 x 20 1/2 x 9 1/2". Remotes (ea); 6 1/2 x 6 1/4 x 4 3/4" D. U.L. Approved. For 110-120 volts. 60 cps AC. Shpg. wt., 31 lbs. PH-159WX No Money Down Net 99.50

DELUXE PORTABLE STEREO-REVERB PHONO



139.50

NO MONEY DOWN!

- Triple-Source Speaker System • Variable Reverberation Control • Push-Pull Outputs — Plus Booster Center Channel • 20 Watts Total Peak Power

This magnificent phonograph with the addition of sound reverberation creates the magnificent illusion of a live music performance — right in your own home. Features one 8" speaker in main cabinet and two 6" speakers with 1 1/4" whizzer cones each set in removable remote cabinets with 12 feet of cable attached to each remote. Each speaker reproduces tones from the stereo record mixed electronically to give faithful stereo hi-fi sound. Rumble-free 4-speed automatic record changer plays all size records. Intermixes all size records of same speed. Automatic shut-off. 45 RPM spindle included. Plays 14-45's on one loading. Hi-fidelity amplifier has output of 20 watts total peak power with boosted push-pull bass for center speaker. Long life ceramic turnover cartridge with diamond and sapphire needles. 5 front panel controls — dual bass, treble and loudness and single balance plus reverberation control. Wood cabinet in contrasting antique white and bronze tweed leatherette. Main unit: 25 x 9 3/4 x 4 1/2" D. For 110-120 volts. 60 cps. AC. U.L. Approved. Shpg. wt., 40 lbs. PH-157WX No Money Down Net 139.50

LAFAYETTE RADIO

ENGINEERED FOR SUPREMACY



9950

NO MONEY DOWN

Made in U.S.A.



"Let Your Own Ears be the Judge"


LAFAYETTE 50-WATT STEREO AMPLIFIER Model LA-250 A

Impressive Performance... Handsome Styling
... Another Unbeatable Lafayette Value!

breathhtaking performance
at a price only LAFAYETTE can offer.



Clutch-Type Volume-Balance Control — Provides precise effective means of controlling volume and balancing stereo channels.



Dual Pre-amplifier Section — Inputs have been provided for every stereo-monaural function.

ASSURANCE OF COMPONENT QUALITY


ONE YEAR PARTS GUARANTEE
All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.

- 50 WATTS MONAURAL— 25 WATTS EACH STEREO CHANNEL
- RESPONSE 15-40,000 CPS ± .5 DB (at normal listening level)
- UNIQUE "BLEND" CONTROL
- PREMIUM EL86 OUTPUT TUBES
- SEPARATE BASS & TREBLE CONTROLS
- CLUTCH-TYPE VOLUME-BALANCE CONTROL
- 3RD CHANNEL OUTPUT

The Stereo 250A... a completely new stereo high fidelity amplifier with a high quality of reproduction, remarkable versatility and new distinctive styling—worthy of a place in the finest stereo hi-fi music system. A full range of controls enables you to enjoy the utmost in listening pleasure in any situation. A unique "blend" control which provides continuously variable channel separation—from full monaural to full stereo—may be used to eliminate the exaggerated channel separation found in some stereo source material. Included is a clutch-type Volume Balance control for independent or simultaneous control of both channels, concentric Bass and Treble controls which provide independent tonal control of each channel and a 4-position switch which selects phono, tuner, auxiliary or tape head stereo inputs. Simple slide switches provide channel reversal and phase reversal—or you can reproduce either channel through both amplifiers. A loudness switch permits the volume balance control to function as a compensated loudness control. The LA-250A also features a 3rd channel output which may be used to feed a 3rd single channel amplifier and speaker to provide a wider sound spread, a Tape Output jack for recording purposes, plus dual terminations for 4, 8 or 16 ohm speakers. Advanced circuitry includes DC operated preamp and tone control tube filaments for hum-free operation, 6CW5/EL86 push-pull output tubes, individual bias and balance adjustments on each channel and a hum balance control.


SPECIFICATIONS:
POWER OUTPUT & DISTORTION: 50 watts—25 per channel—1 db at less than 1% Total Harmonic Distortion at 1 KC. Less than 0.25% Total Harmonic Distortion at 1 KC at normal listening level (1 watt); less than 0.5% 1M distortion at normal listening level. FREQUENCY RESPONSE: 15-40,000 cps ± 0.5 db at normal listening level. HUM & NOISE: 70 db below rated output at max. volume (high level inputs). SENSITIVITY: For full output high level inputs 0.5V; Mag. Phono 3.5 MV at 1 KC. CHANNEL SEPARATION: Greater than 55 db at 1 KC; greater than 45 db from 20-20,000 cps. IMPEDANCE: 4, 8 and 16 ohms per channel. POWER: 200 watts; 110-125V AC 50-60 cycles.
Attractive beige vinyl laminated steel case. Handsomely designed three color brass etched front panel. Sienna brown molded legs and matching knobs with polished brass inserts. Dimensions with legs and knobs, 14 1/2" x 12 3/4" x 5 1/2" H. Shpg. wt., 28 lbs.
LA-250AWX Net 99.50

McIntosh Professional Quality HI-FI EQUIPMENT



C-20 STEREO COMPENSATOR

The C-20 is a stereo preamplifier which provides full stereo flexibility while at the same time protecting the listener's investment in monophonic records. Provides Fletcher-Munson compensation, continuously variable Rumble filter and 2-position (9KC and 5KC) high frequency cutoff. 180° phase reversal control. Input sensitivity: High level—0.25V; phono—2.5 mv; high 12.5 mv; tape—1.25 mv; high 6.25 mv; tape monitor 20 KC. Main—2.5V with rated input; tape—0.25V with rated input. Power requirements: 117VAC, 35 watts. A.C. Aux. outlets: 1 unswitched and 3 switched. Less case. Size: 14 1/2" x 12 1/4" H. Shpg. wt., 19 lbs.
G-170WX Net 234.00
Model L-66M Mahogany Cabinet for C-20. Net 25.00
G-177WX




NEW! MCINTOSH MC-225 TWIN 25-WATT STEREO AMPLIFIER

The MC-225 twin stereo amplifier consists of two separate identical 25-watt power amplifiers mounted on a single chassis. Combined monophonic operation, 50 watts output. Frequency response: +0, -0.1 db from 18 cycles to 30 Kc at full power output, and +0, -2 db from 14 cycles to 100 Kc at half power output. Harmonic and I.M. less than 0.5% at full output. Hum and noise better than 90 db below rated output. A 25 volt and a 70.7 volt output are available for both stereo and monophonic operation. Input level of 0.5 volts. Separate gain controls provided for mono and stereo inputs. Tube complement: 1-12AX7, 2-12AU7, 2-12BH7 and 4-7591 output tubes. For 117 VAC, 50-60 cps. Chromium and black finish. 14 1/2" x 9 1/2" x 6 1/2" H. Shpg. wt., 39 lbs.
G-341WX 198.00

H.H. SCOTT MODEL 299C

NEW SCOTT 72 WATT STEREO AMPLIFIER



A superb unit designed to accommodate every existing signal source. Aluminum chassis and D.C. heated preamp filaments for low hum. Uses 4-7591 Output tubes and rectifier.
FRONT PANEL CONTROLS: Input selector: 6 Mike, NAB tape head, RIAA record equalization, tuner tuner, extra. Selector Balance A, B, Monophonic Records; Stereo; Reverse stereo; Channel A, B; Tone Controls; Channels A, B, Stereo Balance; Derived Center channel Level Control; Loudness/Push-pull on/off; Pickup Selector; Tape Monitor; Scratch and rumble filters; Phase reverse; Loudness Compensation. Low Impedance Stereo headphone output on front panel; High Impedance Stereo headphone output on rear. Dimensions in accessory case 15 1/2" x 5 1/4" x 13 1/4" D. Shpg. wt., 28 lbs.
G-635WX (less case) Net 224.95
Leather finish steel case for above. Net 12.95
G-147W

SHERWOOD



S-5000 II 72 WATT STEREO AMPLIFIER


Featuring the same circuits and controls of the highly-rated S-5000. Features dual loudness, bass and treble controls; one knob varies both channels simultaneously. Other features include 12 db/octave scratch and rumble filters, which operate on all channels, presence-rise indicator lights to indicate mode of operation used. SPECIFICATIONS: POWER: 36 watts each channel, 72 watts on monaural. RESPONSE: 20-20,000 cps ± 1/2 db at full power. INPUTS: Phono (RIAA), tape head (NARTB), 6 high level. NOISE: -80 db (—60 db for phono). OUTPUTS: Dual 4, 8, 16 ohms, dual cathode followers for tape recorder. 12 Tubes: 4-7591, 6-12AX7, 2-silicon rectifiers. POWER CONSUMPTION: 30 watts, 110-120 volts AC, 50-60 cycles. 14x14 1/4" x 4" H. Shpg. wt., 30 lbs.
G-296WX Less Case Net 199.50
Brown Flextone Case for Model S-5000 II. Net 5.00
G-283W Shpg. wt., 8 lbs.

MARANTZ QUALITY STEREO COMPONENTS



MODEL 7C STEREO CONSOLE PREAMPLIFIER


New self-powered stereo preamplifier combines Marantz's high quality of construction with complete versatility and ease of operation. Front panel features 8-position selector switch, 5 position mode switch, volume balance, 4 independent bass and treble controls, Record Equalizer, Tape Playback on Monitor, High Filter, Rumble filter and power switch. Rear Controls feature: Output Level-sets, 3 pairs of outputs, Tape-head Equalizer Adjustments, 9 Pairs of inputs, 6AC convenience outlets and system grounding point. Frequency Response: 1/2 db 20-20,000 cps. 1M Distortion: 0.1%. Total Noise: in 20-20,000 cps audio range, 80 db below 10 mv, phono input with RIAA. Tubes: 6-ECC83/12AX7. Size: 14 3/4" x 5 3/8" x 8 1/2" D. Panel: 15 3/4" x 5 3/4" H. For 110-120V 50/60 cycle AC. Shpg. wt., 16 lbs.
G-251WX Marantz Model 7C less cabinet Net 264.00
WOOD CABINET FOR ABOVE. Specify Mahogany, Blonde, Walnut.
G-253W Shpg. wt., 4 lbs. Net 24.00



NEW MODEL 8B DUAL 35-WATT STEREO PHONIC POWER AMPLIFIER

A professional instrument in every respect. Built-in test meters and adjusting screws assure optimum performance. 35 watts Power output per channel (70-watts peak) "Ultra Linear" operation, 18 watts of triode operation possible by altering 2 connections. Response: 0.1 db from 20-20,000 cps at 35 watts. Distortion: harmonic, less than 0.1%, 1M, less than 0.5%. Hum: -90 db. Input sensitivity 1.3V Heavy duty components throughout. Output impedance: 4, 8 and 16 ohms. Tubes: 2-6BH6, 2-6CH7, 4-EL34/6CA7. Overall size: 13 1/2" x 7 1/4" x 10 1/2" D. For 117V, 60 cps. AC. Shpg. wt., 57 lbs.
G-259WX Marantz Model 8B less cabinet Net 249.00
Model 8G Gold Finish Perforated Snap-on Grille for above. Net 9.00
G-257W Shpg. wt., 1 lb.

THE FISHER



NEW X-202-B 75-WATT STEREO AMPLIFIER CONTROL AMPLIFIER

High power and versatility have been incorporated in the X-202-B compact amplifier system. Features exclusive Fisher tape monitor + playback with internal switching; front panel controls; 16 inputs and 10 output speaker (3 speaker outputs). Facilities for center channel phone connection, Fisher "Spacxpander", remote control and ear and low filters plus built-in subsonic filter cut noise. SPECIFICATIONS: Music power 75 watts total; distortion 1/2% harmonic, 1% intermod. at 70 watts RMS; Overall response (at 1 watt) 20-20,000 cps ± 1 db; Hum, and noise — 66 (low level) — 80 db (high level), damping factor 10. 12 tubes plus 4 diodes. Size: 5 1/4" x 15 1/2" x 12 1/2" deep.
G-401WX Less cabinet. Shpg. wt., 30 lbs. Net 249.50
G-109W MC-2 Metal Cabinet, Shpg. wt., 9 lbs. Net 15.95
G-101W Oiled Walnut Wood Cabinet, Shpg. wt., 6 lbs. Net 25.95

Pilot



240 STEREO PREAMP-AMPLIFIER

The 30-watt stereophonic preamp-amplifier that represents the best value in its class. Four independent tone controls. 3 pairs of high level inputs for permanent simultaneous connection of FM-AM tuner, Multiplex adapter and tape recorder. 2 pairs of low level inputs for permanent connection of record changer and turntable. Direct tape playback facilities. Terminals for extension speakers, with front panel speaker selector switch. Electronic crossover for monophonic bi-amplifier use. Automatic shut-off. Mono position on Mode switch automatically cancels out undesired vertical stereo response when playing monophonic records. Eleven front panel controls. Specifications— Power outputs: 30 watts total; 15 watts per channel, music power. Sensitivity for full output phono: 3 mv; FM-AM multiplex, tape recorder, 110 mv. Harmonic distortion 1%. Hum and noise 80 db below full output. Frequency response ± 1 db, 20 to 20,000 cycles. Size: 5 3/8" high x 14 3/4" wide x 10 3/4" deep. Shpg. wt., 23 lbs. Complete with enclosure.
G-386WX Net 134.50

A COMPLETE STEREO SYSTEM BASED ON THE SUPERB LA-250A

brehtaking performance at a price only LAFAYETTE can offer.

THE SMART WAY TO BUY HI-FI!

Lafayette's Most Popular Stereo Phono System

"LISTEN AT HOME GUARANTEE"

Prove to yourself in your own living room, that the hi-fi system you select sounds as good at home as it does in our showroom.

LISTEN at HOME and BE SURE!

With Lafayette's Famous 30 Day FREE Trial if not completely satisfied with your purchase once you get it home, you can return it within 30 days and get your Full Purchase Price returned to you, less only transportation charges.



LAFAYETTE LA-250A
50-WATT STEREO AMPLIFIER

CHOICE OF CARTRIDGE	
Audio Empire S108	Pickering 380C
Shure M7D	GE VR 1000-7




GLASER-STEERS GS-77



2 LAFAYETTE SK-58
FREE EDGE 12" COAXIAL SPEAKERS



LAFAYETTE
WOOD BASE



(OPTIONAL)
2 LAFAYETTE ELIPTOFLEX SERIES
BOOKSHELF ENCLOSURES



ALTERNATE
RECORD
CHANGER
GARRARD AT6



2 LAFAYETTE
SK-210 12"
3-WAY SPEAKERS



LAFAYETTE SK-180
"TRIHELIX" SPEAKERS

LAFAYETTE MATCHED STEREOPHONIC SYSTEMS

*Make Certain To Indicate Your Choice of either Empire S108, Pickering 380C, Shure M7D or GE VR-1000-7 Diamond Needle Cartridge.

System No.	Amplifier	Changer	Cart	Base†	Speaker Cabinet**	Shpg. Wt.	Net
LS-251WX	LA-250A	GS-77	CHOICE OF Audio Empire S108 or Pickering 380C or Shure M7D or GE VR 1000-7	2 ea SK-58	67 lbs.	199.50	
LS-252WX	LA-250A	AT-6		2 ea SK-58	67 lbs.	199.50	
LS-253WX	LA-250A	GS-77	Empire S108 or Pickering 380C or Shure M7D or GE VR 1000-7	2 ea SK-58	2 ea Eliptoflex 143 lbs.	265.50	
LS-254WX	LA-250A	AT-6		2 ea SK-58	67 lbs.	203.50	
LS-255WX	LA-250A	GS-77	Empire S108 or Pickering 380C or Shure M7D or GE VR 1000-7	2 ea SK-180	2 ea Eliptoflex 143 lbs.	269.50	
LS-256WX	LA-250A	AT-6		2 ea SK-180	70 lbs.	233.50	
LS-257WX	LA-250A	GS-77	Empire S108 or Pickering 380C or Shure M7D or GE VR 1000-7	2 ea SK-180	2 ea Eliptoflex 143 lbs.	269.50	
LS-258WX	LA-250A	AT-6		2 ea SK-180	70 lbs.	233.50	
LS-259WX	LA-250A	GS-77	Empire S108 or Pickering 380C or Shure M7D or GE VR 1000-7	2 ea SK-210	2 ea Eliptoflex 146 lbs.	299.50	
LS-260WX	LA-250A	AT-6		2 ea SK-210	70 lbs.	219.50	
LS-261WX	LA-250A	GS-77	Empire S108 or Pickering 380C or Shure M7D or GE VR 1000-7	2 ea SK-210	2 ea Eliptoflex 146 lbs.	299.50	
LS-262WX	LA-250A	AT-6		2 ea SK-210	70 lbs.	219.50	
LS-263WX	LA-250A	Model A		2 ea SK-58			

Any of above systems with addition of Lafayette LT-700 WX Multiplex Stereo Tuner (described on other pages) add \$114.50 to system price. When ordering add the letter T to the prefix.

Example: LS-251WX system with LT-700WX tuner is ordered as LST-251WX.

Eliptoflex—12" shelf type speaker Enclosure.

†—Specify Mahogany, Walnut or Blonde Base.

**—Specify Walnut, Oiled Walnut, Mahogany or Blonde.

AT-6—Garrard 4-Speed Record Changer. Model A—Garrard 4-Speed Record Changer.

SHURE M3D CARTRIDGE

Any of above systems with Shure M3D Diamond Stereo Cartridge (described on another page). In place of choice of above 4 cartridges, add 18.50 to system price.

MATCHED COMPONENTS

Lafayette LA-250A 50-Watt Stereo Amplifier	99.50
Glaser-Steers GS-77 4-Speed Record Changer	59.50
Lafayette Wood Changer Base	3.95
Audio Empire S108 Diamond Needle Stereo Cartridge	35.00
2-Lafayette SK-58 Famous Free Edge 12" Coaxial Speakers @ 29.50 Each	59.00

Regular Catalog Price ~~256.95~~

LAFAYETTE SYSTEM PRICE
You Save 57.45

199.50
NO MONEY DOWN

NEW LAFAYETTE CRITERION Hi-Fi CABINETRY....

decorate your home with music



Lafayette's Criterion Line — the standard of construction and design by which all others are judged.

The Criterion Stereo Furniture Ensemble


The Technical Know-How of Lafayette's Audio Engineers Combined with that of America's Finest Furniture Craftsman, bring to you the new Lafayette Criterion Line of Acoustically Correct Hi-Fi Furniture.

Now your high fidelity listening area can look as good as it sounds. Add the elegance, grace and timeless styling of this decorator inspired furniture grouping to your home music center, but lose nothing in performance. Painstaking acoustical design by Lafayette's audio engi-

neers provides the best possible relationship between equipment and furniture. The meticulous custom craftsmanship, rich, matched, natural wood veneers and custom hand-rubbed finishes of these fine cabinets are bound to please the most discerning taste.

THE CRITERION EQUIPMENT CABINET

Interior Dimensions each upper compartment
10" H
18 3/4" W
15 3/4" D



84.50

NO MONEY DOWN

Interior Dimensions each lower compartment

"Component Engineered" by Lafayette's audio experts to provide ample, convenient, well-ventilated accommodations for all of your components. When matched with its companion Criterion Eliptoflex speaker enclosure (described on the right) it forms a complete music center. Cabinets employ rigid tongue and groove construction of 3/4" lumber core woods throughout, with matched veneers inside as well as out. Swinging doors with brass pulls and magnetic catches. Smartly styled with tapered legs and gold side trim. Overall Dimensions: 40Wx18Dx32 1/2" H including legs. Shpg. wt., 70 lbs.
CAB-137WX Walnut Net 84.50
CAB-138WX Oiled Walnut Net 84.50
CAB-139WX Mahogany Net 84.50

THE CRITERION ELIPTOFLEX SPEAKER CABINET



55.50

NO MONEY DOWN

The same graceful styling and fine construction as the CRITERION equipment cabinet, which it matches. Designed to accommodate any 12" speaker, this enclosure incorporates the inner construction and acoustic principles of the famous Lafayette "Eliptoflex" enclosure. A specially designed elliptical port with diffracting ring broadens frequency response. This results in natural smoothness and unequalled performance in the low ranges. Constructed of 3/4" lumber core woods with hand-rubbed natural wood veneers. Smartly styled with matching grille cloth, gold trim and tapered legs. Overall Dimensions: 32 1/2 Hx18Dx16" W. Shpg. wt., 50 lbs.
CAB-140WX Walnut Net 55.50
CAB-141WX Oiled Walnut Net 55.50
CAB-142WX Mahogany Net 55.50

LAFAYETTE Criterion STEREO COMPONENTS

LAFAYETTE KT-600A STEREO PRE-AMPLIFIER MASTER CONTROL CENTER

MODEL KT-600A
79.50
IN EASY-TO-BUILD KIT FORM
COMPLETELY WIRED AND TESTED
LA-600A
134.50
NO MONEY DOWN!

The KT-600A represents a brilliant stereo achievement. This "no-compromise" stereo pre-amplifier and control unit offers unlimited versatility, includes every feature necessary for the finest reproduction. It has a total of 12 input jacks (6 stereo pairs) for program sources of any type and level—all of which may be selected by front panel control. Separate turnover and roll-off switches provide 24 positions of correct equalization—independent for each channel. Dual concentric stereo function selector for maximum flexibility in controlling selected program sources. A unique Bridge Control provides continuously variable channel separation from full mono to full stereo, or it can optionally be used to regulate the 3rd channel output. A clutch-operated Volume Balance Control provides independent or simultaneous level adjustment of channels. Low Impedance Plate Follower outputs are used, and a host of many other professional type features.


KT-600AWX Stereo Pre-amplifier Kit No Money Down Net 79.50
LA-600AWX Stereo Pre-amplifier, wired and tested No Money Down Net 134.50

SPECIFICATIONS

FREQUENCY RESPONSE: 5-40,000 cps \pm 1 db. DISTORTION: Less than 0.05% 1M at 2 volts out; Less than 0.1% Harmonic, at 2 volts out. SENSITIVITY: Low Level 2.2 mv for 1 volt out; high level 94 mv for 1 volt out; Tape Head inputs 1.8 mv for 1 volts out. HUM AND NOISE: High level inputs better than 80 db below 2.0 volts; low inputs better than 62 db below 2.0 volts. INPUT IMPEDANCES: High level—250K ohms; Mag—96K ohms; Ceramic—96K ohms in series with 68 uf; Tape Head—470K ohms. OUTPUT IMPEDANCES: Main Outputs—1500 ohms; Tape Outputs—2700 ohms; Bridged Output—1100 ohms. TONE CONTROL RANGE: Bass \pm 15 db at 30 cps; Treble \pm 15 db at 10Kc. RUMBLE FILTER: 12 db/octave slope, down 15 db at 30 cps. SCRATCH FILTER: 12 db/octave slope, down 15 db at 15 Kc. CROSSTALK: Greater than 55 db separation between channels. AUXILIARY AC OUTLETS: 4, 1 unswitched. TUBES: 7-7025, 2-Selenium Rectifiers. POWER REQUIREMENTS: 35 Watts, 105-125 volts AC, 50/60 cycles. SIZE: 14Wx4 $\frac{1}{2}$ Hx11 $\frac{1}{2}$ D, not including projections. Shpg. wt., 16 lbs.



MADE IN U.S.A.



PATENTS APPLIED FOR ON BRIDGE AND NULL BALANCE CIRCUITRY.

The KT-600A Solves every Stereo-Monaural problem

- RESPONSE 5-40,000 CPS • AMAZING BRIDGE CONTROL PROVIDES VARIABLE 3rd CHANNEL OUTPUT FOR 3-SPEAKER STEREO
- HIGHLY PRECISE "NULL" BALANCING & CALIBRATION—MORE ACCURATE THAN METERS • TAPE HEAD PLAYBACK EQUALIZATION FOR NEW 4-TRACK STEREO • 4-AUXILIARY AC OUTLETS

"LABORATORY STANDARD"

IN EASY TO BUILD KIT FORM


MODEL KT-550

134.50

MODEL LA-550

184.50

COMPLETELY WIRED AND TESTED
NO MONEY DOWN




MADE IN U.S.A.

the KT-550 100 WATT BASIC STEREO AMPLIFIER KIT

- 50 Watts—per channel—100 watts for monophonic use. Frequency response from 2-100,000 cps, \pm 0, -1 db at 1 watt • Unmeasurable Distortion • Hum and Noise Better Than 90 db Below 50 watts • Multiple Feedback Loop Design (over 50 db) Lowers Distortion Without Sacrificing Stability • Metered Control Panel With D.C. Bias and AC Balance Potentiometer • High Power 7027A Output Tubes • Massive Grain oriented steel transformers.

TECHNICAL SPECIFICATIONS

Power Output: 50-watts per channel continuous RMS from 20-20,000 cps; 100-watts monophonic operation. Total Harmonic Distortion: Less than .15% at 1,000 cycles at 50 watts each channel. 0.75% from 20-20,000 cps at 50 watts each channel. Intermodulation Distortion: Less than 0.5% at 50-watts equivalent sine wave power, 60 & 7,000 cps 4:1 ratio. 0.15% at 10-watts equivalent sine wave. Frequency Response: 12-45,000 cps, 0 -1db at 50-watts; 2-100,000 cps. \pm 0 -1db at 1 watt. Sensitivity: 1.0 volt RMS input for 50-watts output. Damping Factor: 15 at 1 kc—16 ohms. Feedback: Over 50db in six multiple loops. Hum and Noise: Better than 90 db below 50-watts. Output Impedance: 4, 8 and 16-ohms. Convenience Outlet: Single A.C. convenience outlet. Fuse: Externally accessible fuse. Controls: 4 Bias Controls, 2 AC Balance Controls, Meter Selector Switch and Power On/Off Switch. Tube Complement: (Total of 10) 4-7027A, 4-6CL6, 2-6BR8A plus 5 Silicon Diodes. Power Consumption: 350-watts.



COMPARE PERFORMANCE

These performance curves demonstrate the ability of the KT-550 to provide high power output with extremely flat response at both ends of the frequency spectrum—Furnishes phenomenal reproduction even at low listening levels and is perfect for today's low-efficiency speakers.

Lafayette introduces the KT-550 "Laboratory Standard" Dual 50-watt Stereo Amplifier Kit—the finest instrument possible to design and produce regardless of price. Advanced engineering concepts in audio design were used to achieve flawless performance at an output of up to 50 watts per channel for stereo operation or 100 watts combined for monaural. The sound reproducing capabilities of the KT-550 are in excess of the audible range... \pm 0, -1 db from 2 to 100,000 cps without evidence of ringing or instability. Perfect for low efficiency speaker systems. "Multiple loop" feedback design achieves very low distortion and high stability, with an absence of listening fatigue. Highest quality components were used throughout such as special massively designed output transformers, telephone grade electrolytics, and Cor-

ning deposited metal film glass case resistors. The 7027A output tubes are conservatively rated in the KT-550 to insure long life at lowest distortion levels. A well regulated power supply employing 4 silicon diode rectifiers is used. Engineered for the kit builder, two printed circuit boards virtually eliminate any possibility of error. Lafayette's famous step-by-step instruction manuals plus large pictorials provide ease of assembly equal to factory built units. Handsomely finished in contrasting brown and beige; control panel finished in brass. Complete with cover. 9 $\frac{1}{2}$ Hx12 $\frac{1}{2}$ D. 110-125V 50/60 cycles. Shpg. wt., 60 lbs.

KT-550WX No Money Down Net 134.50
Dual 50-watt stereo amplifier as above wired and tested.
LA-550WX No Money Down Net 184.50

NOW YOU CAN AFFORD The Very Finest LAFAYETTE BUILD-IT-YOURSELF PROFESSIONAL 100 WATT STEREO SYSTEM

COMPONENTS

- KT-600A
- SK-115A
- KT-550
- GARRARD MODEL A
- CHANGER BASE
- CK10 OPTIONAL
- PICKERING 380C
- GE VR1000-7
- AUDIO EMPIRE S108
- CHOICE OF ONE
- SHURE M7D

MATCHED COMPONENTS

Lafayette KT600A Stereo Pre-amplifier Kit	79.50
Lafayette KT-550 Dual 50-Watt Stereo Amplifier Kit (with enclosure)	134.50
2-Lafayette SK-115A 15" 3 Way Speakers @ 79.50	159.00
Garrard Model A Record Changer (less base)	79.50
Base for Model A Changer (Specify Finish)	3.95
Audio Empire S108 Diamond Needle Stereo Cartridge	35.00
Regular Catalog Price	491.45

LAFAYETTE KIT SYSTEM PRICE
437.75
NO MONEY DOWN
YOU SAVE
53.70

ALTERNATES

- LT-700
- SK-210WX
- CK-14 (ELIPTOFLEX KITS)
- KT-507A

LAFAYETTE 100 WATT MATCHED DE LUXE STEREO KIT SYSTEMS
*Be sure to specify Audio Empire S108, Pickering 380C, Shure M7D or GE VR-1000-7 Cartridge.

System	Amp. Kit	Preamp Kit	Changer	Cartridge*	Changer Tuner Base† Kit	Spkr.	Spkr. Cabinet	Shpg. Wt.	Net
LSK-551WX	KT-550	KT-600A	Garrard Model A	Choice of	Laf†	—	2 SK-115A	—	175 lbs. 437.75
LSK-552WX	KT-550	KT-600A	Garrard Model A	Empire S108,	Laf†	—	2 SK-115A	2 CK-10	283 lbs. 491.75
LSK-553WX	KT-550	KT-600A	Garrard Model A		Laf†	—	2 SK-210	—	135 lbs. 381.75
LSK-554WX	KT-550	KT-600A	Garrard Model A	Pickering 380C,	Laf†	—	2 SK-210	2 CK-14	183 lbs. 422.75
LSK-555WX	KT-550	KT-600A	Garrard Model A		Laf†	KT-500A	2 SK-115A	—	193 lbs. 512.25
LSK-556WX	KT-550	KT-600A	Garrard Model A	Shure M7D,	Laf†	KT-500A	2 SK-115A	2 CK-10	301 lbs. 566.25
LSK-557WX	KT-550	KT-600A	Garrard Model A		Laf†	KT-500A	2 SK-210	—	153 lbs. 456.25
LSK-558WX	KT-550	KT-600A	Garrard Model A	Or GE VR-1000-7	Laf†	KT-500A	2 SK-210	2 CK-14	201 lbs. 497.25

Any of above systems with addition of Lafayette LT-700WX Multiplex Stereo Tuner add \$114.50 to system price. When ordering add T to prefix. Example: LSK-551WX system with LT-700WX tuner is ordered as LSKT-551WX. † Specify Mahogany, Walnut or Blonde Base.
KT-500A AM-FM Stereo Tuner Kit. SK-210 12" 3 Way Speaker. CK-10 Base Reflex Unfinished Speaker Enclosure Kit for 12" or 15" Speakers. CK-14 Famous Lafayette Bookshelf Enclosure Kit for 12" Speaker.

For any of above systems with Shure M3D Diamond Stylus Stereo Cartridge In place of choice of above cartridges add \$18.50 to System Net Price.


NOW FROM LAFAYETTE THE REMARKABLE **KT-650** Criterion™ FM TUNER KIT

NO MONEY DOWN
KT-650 in KIT FORM

54.50

LT-650 Factory
Wired & Tested

79.95



**MADE
IN U.S.A.**

- Low Noise Front End With Triode Grounded Grid Amplifier and Triode Mixer • Double Tuned Dual Limiters and Foster Seeley Discriminator
- Sensitivity 1.25 uv For 20 db of Quieting • Variable AFC Literally "Lock In" Stations • Frequency Response $\pm 1/2$ db 15-35,000 cps • Multiplex Output For Stereo FM • Easy-To-Build Printed Circuits • Electronic Bar Tuning Indicator Tube • Pre-Aligned IF and Discriminator Coils • 3 Gang Tuning Condenser • Virtually Distortionless Performance—Less than .15% Distortion at 100% Modulation.

MONEY-BACK GUARANTEE

Each Lafayette Kit is guaranteed to meet, or exceed, its published specifications for performance or your money is refunded in full. LAFAYETTE GUARANTEES YOU COMPLETE SATISFACTION.

ASSURANCE OF COMPONENT QUALITY

ONE YEAR PARTS GUARANTEE

All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.

LAFAYETTE LT-200 WIRED MULTIPLEX ADAPTER WITH KT-650 TUNER KIT

Made in U.S.A.
LT-200

**PERFORMANCE
VALUE
COMBINATION!**



KT-650

NO
MONEY
DOWN

97.00

KT-650 KIT PLUS LT-200

Made For Each Other! Purchase your KT-650 tuner in combination with this new Lafayette KT-200 Multiplex Adapter and save \$5.00 off of their combined purchase price. You'll be completely equipped to receive the new FM stereo multiplex broadcasts. Supplied with necessary cables and instructions. Shpg. wt., 17 1/2 lbs. Net 97.00
HTA-14WX KT-650 Kit plus LT-200 Net 97.00
HTA-15WX LT-650 Factory Wired plus LT-200 Net 122.45

* Lafayette supplies this multiplex adaptor fully wired and aligned rather than in kit form, due to alignment difficulties requiring a mpx generator for exact alignment.

"I congratulate you people on the tremendous job you have done with this FM tuner."
Donald MacKenzie
Marlboro, Mass.

"The KT-650 performed as beautifully as it went together."
Curtis Frets,
Ontario, Calif.

**Some Letters
Out of
THOUSANDS**

"In this era of loose claims by many reputable manufacturers, you may feel a deep sense of pride in producing this kit. Every claim you made is true."
George F. Schaefer
Ramsey, N. J.

"A pleasure to build."
Francis J. Crowley
Henipstead, N. Y.

READY FOR MULTIPLEX!

Lafayette engineers have succeeded in developing an instrument with performance and flexibility that equals and surpasses factory-wired or kit tuners many times its modest cost.

The KT-650 incorporates every desirable FM Tuner feature. A Multiplex jack provides for addition of a Multiplex Adapter for FM Stereo Reception. Flywheel weighted tuning enables effortless station-to-station tuning. Pinpoint tuning accuracy by a special electronic bar tuning indicator tube. A variable AFC (Automatic Frequency Control) is featured—literally "locks in" the station and is adjustable for tuning weak stations adjacent to strong stations. The Tuner Level Control allows precise adjustment of the Tuner output level. Superb circuitry features a low noise front end with triode mixer plus double tuned dual limiters and wide band Foster-Seeley discriminator. Sensitivity is such that in many areas the only antenna needed will be a short piece of wire, except in remote locations. Plate follower

outputs permit using the tuner up to 50 feet from the amplifier. Time-saving printed circuit boards are utilized to make wiring errors almost nonexistent. IF and discriminator coils have been carefully factory prealigned—permits you to play the tuner as soon as assembled.


The superbly styled low silhouette enclosure will do justice to any decor. Beige cover is set off by a Cream and Sierra Brown etched panel and knobs with contrasting Black Dial Face. Complete with cage, legs, interconnecting cables with plugs, indoor folded dipole antenna and alignment tool. Overall Dimensions: 14x5 1/4x11"D. For 117V, 50-60 cycle AC. Power consumption 40 watts. Shpg. wt., 13 1/2 lbs. Net 54.50

KT-650WX FM Tuner Kit Net 54.50
HTA-14WX Combination of KT-650 and LT-200 FM Multiplex Adapter . You Save 5.00 Net 97.00
LT-650WX Factory Wired & Tested Net 79.95
HTA-15WX Combination of LT-650 and LT-200 FM Multiplex Adapter. You Save 5.00 Net 122.45

COMPARE THESE SPECIFICATIONS:

Sensitivity: 1.25 microvolts for 20 db of quieting. Image Rejection: 66 db. AM Suppression: 48 db. Discriminator Linearity 600 kc. Distortion and Noise: Better than 57 db below 1.5 volts at 100% modulation. Frequency Response: $\pm 1/2$ db from 15 to 35,000 cps with a standard 75 microsecond de-emphasis network. Audio Output: 1.75 volts at 75 KC deviation (100% modulation). Antenna Input: 300 ohm. Controls: Tuning; Level; AFC Control and Power Switch. Outputs: (2) Multiplex Adapter; Amplifier. Tube Complement: ECC85, 6BK7B, 6AL5, 2-7543, 2-6BA6, 6AV6, EM84 Electronic Bar Tuning Indicator Tube and a silicon diode rectifier.

**EASY FLY-
WHEEL
TUNING—**
Smooth, effortless tuning from one station to another.



**FRONT PANEL
LEVEL CON-
TROL—**Provides precise control of your tuner output level.

**MULTIPLEX AND
MAIN OUTPUTS—**Plate follower main output allows connection of tuner up to 50 feet from amplifier. Multiplex output for FM stereo.

VARIABLE AFC
—"Locks in" the station for positive drift free reception of both weak and strong signals.

FREE! LAFAYETTE FM STEREO MULTIPLEX BROCHURE
Lafayette has prepared an informative, fact-filled brochure describing FM stereo Multiplex Broadcasting. Write for your free copy of brochure BK-50, "Facts About FM Stereo Broadcasting."

The Most Flexible Tuner Ever Designed LAFAYETTE STEREO-TUNER KT-500A

MADE IN U.S.A.

**KT-500 AM-FM
STEREO TUNER KIT
Combined with
NEW LT-200
WIRED MULTIPLEX
ADAPTER**



**KT-500A
74.50
NO MONEY DOWN
IN KIT FORM**

**LT-50A
124.50
NO MONEY DOWN
COMPLETELY WIRED AND TESTED**

Use as a FM-AM Stereophonic Tuner for simulcast stereo or with a multiplex adapter for FM stereo reception



USE AS TWO INDIVIDUAL TUNERS
FM IN ONE ROOM . . . AM IN THE OTHER

- MULTIPLEX OUTPUT FOR NEW STEREO FM • TWO PRINTED CIRCUIT BOARDS AND IF'S PREALIGNED • FM AFC AND AFC DEFEAT • 17 TUBE PERFORMANCE—11 Tubes (4 dual-purpose) + Tuning Eye & Selenium Rectifier • ARMSTRONG CIRCUIT WITH DUAL LIMITERS AND FOSTER-SEELEY DISCRIMINATOR • 12 TUNED CIRCUITS AND DUAL CATHODE FOLLOWER OUTPUTS • EXTREME SENSITIVITY AND WIDE FREQUENCY RESPONSE

The KT-500A will receive simultaneous FM and AM stereo broadcasts or since the two sections are completely independent it may be utilized for normal FM or AM reception. The Tuner also provides an output for the new multiplex FM stereophonic reception. Apart from its unique flexibility, the KT-500A offers noise-free, drift-free, distortion-free performance the equal and in many instances superior to the highest priced tuners. Each FM & AM section is tuned with its own 3-gang tuning capacitor and is provided with individual cathode follower outputs. This means that long output cables can be used to connect tuner to amplifier or control center without fear of high frequency loss. Also, separate volume controls are provided for each channel so that when used for stereophonic reception, a proper balance between channels can be achieved. Convenient front panel switch changes from stereo to monaural use. Simplified accurate knife-edge tuning is provided by magic eye which operates independently on FM and AM. Automatic frequency control "locks in" FM signal permanently. Ferrite rod antenna with loading ring is supplied to bring in weak AM stations for quality reproduction.

Designed for easy assembly, the kit is built around two printed circuit boards and prealigned. IF's insuring fast accurate construction even for the beginner. Beautifully styled, the KT-500A employs a cream and brushed brass front panel plus matching brown knobs with copper inserts set in a beige finished vinyl enclosure.

KT-500AWX Stereo Tuner Kit Net 74.50
HTA-12WX Combination of KT-500A and LT-200 Multiplex Adapter . . . You Save 5.00 Net 117.00
LT-50AWX Same as KT-500AWX, completely wired and tested Net 124.50
HTA-13WX Combination of LT-50A and LT-200 Multiplex Adapter . . . You Save 5.00 Net 167.00

ASSURANCE OF COMPONENT QUALITY

ONE YEAR PARTS GUARANTEE

All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.

"... this kit is excellent all the way around. It would be difficult to improve upon."
Robert Meier
Washington, D.C.

"Instructions were very good. Performance is wonderful. Best all around design..."
S. B. Heberlig
Glendora, New Jersey

SPECIFICATIONS

FM CIRCUIT: Armstrong, low noise front end with triode grounded grid amplifier and triode mixer. Double tuned dual limiters, Foster-Seeley discriminator, AFC and AFC defeat. **AM CIRCUIT:** Superhet with 3 stages AVC, 10kc whistle filter, ferrite antenna. **DISTORTION:** Under 1% harmonic on FM; under 1% on AM for up to 80% modulation. **HUM LEVEL:** 60 db below 100% modulation. **SENSITIVITY:** FM—full limiting on signals as low as 1 uv, 2 uv for 30 db quieting; AM Terminal Sensitivity 5 uv. **SELECTIVITY:** FM 200 kc bandwidth; 6 db down, AM 8kc BW; 6 db down. **FREQUENCY RESPONSE:** FM 20-20,000 cps $\pm 1/2$ db, AM 20-5,000 ± 3 db. **IMAGE REJECTION:** FM 40 db; AM 30 db. **I. F. REJECTION:** FM 70 db, AM 50 db. **CONTROLS:** 5 controls; FM VOL, AM VOL, FM Tuning, AM Tuning, and five position function selector switch. **TUBES:** 3-6BA6, 2-6AU6, 1 each 6BK7B, ECC85, 6AL5, 6BE6, 12AU7 and 6U5 tuning eye. Selenium rectifier. **OUTPUT IMPEDANCE:** Low impedances cathode follower. Output jacks for FM, AM or Stereo. **ANTENNA INPUT:** 300 ohms. Size 13 3/4x10 3/4x4 1/2"H. Shpg. wt., 18 lbs. Kit comes complete with all parts and metal cover, a step-by-step instruction manual, schematic and pictorial diagrams.

117.00*
KT-500 KIT PLUS LT-200

With this outstanding new Lafayette LT-200 Multiplex Adapter your KT-500 will be equipped to receive the new FM multiplex stereo broadcasts in addition to monaural AM-FM and simulcast stereo AM, FM. And, by purchasing both units together you save an additional \$5.00 off, their combined purchase price. Supplied with necessary cables and instructions. Shpg. wt., 22 lbs.
HTA-12WX KT-500 A Kit plus LT-200 Net 117.00
HTA-13WX LT-50 Factory Wired plus LT-200 Net 167.00

* Lafayette supplies this multiplex adaptor fully wired and aligned rather than in kit form, due to alignment difficulties requiring a mpx generator for exact alignment.

Now! FROM THE
LAFAYETTE
high-fidelity
RESEARCH LABORATORIES

The ULTIMATE FM STEREO TUNER

THE New LAFAYETTE **Criterion**™ LT-700 FM STEREO MULTIPLEX TUNER



- Virtually Distortionless Performance — Less than 0.15% Distortion at 100% Modulation, Monaurally
- Low Noise Front End With Triode Grounded Grid Amplifier and Triode Mixer
- Double-Tuned Dual Limiters and Foster Sealey Discriminator
- Frequency Response $\pm 1/2$ db 15-35,000 cps, Monaurally
- Variable AFC Literally "Locks In" Stations
- Sensitivity 1.25 μ v for 20 db of Quieting
- 3 Gang Tuning Condenser
- Electronic Bar Tuning Indicator

The LT-700 is another impressive example of Lafayette's engineering leadership. For here is a tuner that achieves a level of distortionless performance and flexibility that sets the standard for professional FM multiplex reception. Its superb circuitry features a low noise front end with triode mixer, double-tuned dual limiters and wide band Foster Sealey discriminator. Distortion has virtually been eliminated with less than 0.15% distortion at 100% modulation (monaurally). Sensitivity of the LT-700 is such that in many areas the only antenna needed will be a short piece of wire, except of course in remote locations. Plate follower outputs permit using the tuner up to 50 feet from the amplifier. Designed for maximum versatility, the LT-700 features a convenient front panel volume control for precise adjustment of tuner output level. In addition a variable AFC (automatic frequency control) is provided. Once properly tuned, the AFC literally "locks in" the station and is adjustable for tuning weak stations adjacent to strong stations. Pinpoint tuning accuracy is assured by a special electronic bar tuning indicator that indicates maximum closure at the point of best tuning. Multiplex operation is achieved by a simple front panel switch. This also activates a stereo light when the station tuned to starts broadcasting stereo. Every LT-700 is individually aligned and tested to meet or exceed Lafayette's specifications. Attractively styled with a cream and brushed brass front panel set in a beige finished vinyl enclosure. Size 13 $\frac{1}{2}$ "x10 $\frac{1}{2}$ "x4 $\frac{1}{2}$ "H. For 117V. 50-60 cycle AC. LT-700WX Shpg. wt., 16 lbs. Net 124.50

FREE! LAFAYETTE FM STEREO MULTIPLEX BROCHURE

Lafayette has prepared an informative, fact-filled brochure describing FM stereo Multiplex Broadcasting. Write for your free copy of brochure BK-50, "Facts About FM Stereo Broadcasting."

124.50
NO MONEY DOWN

TECHNICAL SPECIFICATIONS

Sensitivity: 1.25 μ v for 20 db of quieting. Variable AFC. Harmonic Distortion: 0.15% at 1Kc 100% modulation. Signal-to-Noise Ratio: Better than 57 db. Freq. Response: $\pm 1/2$ db 15-35,000 cps monaurally. Image Rejection: -50db. Discriminator Linearity: 600 Kc. Audio output: 1.75v at 75 Kc deviation (100% modulation). Tubes: Simple manual switching for FM multiplex operation. Anode Follower for low impedance wide-band distortion-free output. Automatic FM stereo indicator light. 2-No. 47 Pilot Lights. Tubes: 12AX7, 6C4, 2-7543, 6AL5, 6AV6, EZ-81 rectifier, EM-84 tuning eye.

New! LAFAYETTE MULTIPLEX ADAPTER

Now Enjoy All The Quality & Dynamic Brilliance of Stereo Through Your FM Tuner

Only **47.50**
NO MONEY DOWN



DELIVERY NOV. 15, 1961

Made in U.S.A.

Here's the easiest, most inexpensive way for you to enjoy stereo—not records, not tapes, but stereo with all the fidelity and convenience that only FM can provide. Add this exciting new method of stereo reproduction to your component High-Fidelity system with this brilliant new stereo multiplex adapter. Performs beautifully with virtually any late model, wide band tuner, equipped with a multiplex output jack. Requires no special knowledge or tools to hook up—as simple and easy to connect as were your original components. Supplied with all necessary audio cables. All that's required is to merely plug the unit into your tuner, amplifier and AC outlet. Engineered for simplicity of operation, a selector switch conveniently located on the front panel provides for On-Off, Mono-FM and Stereo-FM. Individual pilot lights indicate when power is on and when adapter is operating stereophonically. Beautifully styled to match any decor in textured beige finish cover and smart brushed brass anodized aluminum front panel. Measures 4 $\frac{1}{2}$ "x6 $\frac{1}{4}$ "x8" $\frac{1}{2}$ "H. For 110-120V, 60 cycle AC. Shpg. wt., 8 lbs. LT-200 Net 47.50

★ COMPARE THESE ALL STAR FEATURES ★

- Superior Distortion & Stereo Separation Characteristics
- Self Powered
- Matches With Virtually All Recent Model Wide-Band Tuners Equipped With MPX Output Jacks
- Complete With Enclosure & All Necessary Connecting Cables

NEW! FM STEREOPHONIC MULTIPLEX ADAPTERS

NEW HARMAN KARDON MULTIPLEX ADAPTER MX700

H. H. SCOTT
MODEL 335



WIDE-BAND MULTIPLEX ADAPTER

Now owners of all H. H. Scott wide-band tuners, regardless of age or model, can enjoy multiplex reception by adding the Model 335 wide band multiplex adapter to their systems. Self-powered (all connections to the tuner are external), so FM tuner alignment is unaffected. The 335 can be switched out of your stereophonic system to allow stereo AM-FM reception with H. H. Scott stereo tuners 330, 331, 339. Controls: SELECTOR (Off, Monophonic FM, Stereo with subcarrier noise filter, stereo without subcarrier noise filter); LEVEL; ADAPTOR DEFEAT; STEREO NOISE FILTER. Matches H. H. Scott tuners in height and styling. Dimensions in accessory case: 7 $\frac{1}{4}$ "x5 $\frac{1}{4}$ "x13" $\frac{1}{2}$ "D. 105-125 V.A.C., 50-60 cycle, self-powered. Shpg. wt., 8 lbs. Uses H size case. Matching panel to LT-10 FM tuner kit available. Net 99.95

Pilot
MODEL 200
AUTOMATIC
MULTIPLEXER



- Self-Powered
- Indicator Light
- No Operating Controls

79.50

NO MONEY DOWN

The Pilot 200 multiplex adaptor is completely automatic. No controls are needed or used. When the tuned-to station is broadcasting stereo, the built-in indicator light goes on and the Multiplex automatically switches to stereo reception. All connections are external, made with jack cords simply plugged in. Will not affect reception of monaural FM. Completely self-powered. Contains three tubes plus one rectifier. Housed in an attractive black and brass enclosure (Included) designed to match Pilot components. Measures 5Hx3Wx14 $\frac{1}{2}$ L. G-681 Shpg. wt., 4 $\frac{1}{2}$ lbs. Net 79.50 Pilot 100 semi-automatic Multiplexer w/enclosure G-680 Shpg. wt., 2 $\frac{1}{4}$ lbs. Net 49.50



SHERWOOD
S3MX
SELF-POWERED
MULTIPLEX
ADAPTER


NO MONEY DOWN

69.50

Designed for use with many FM tuners—having either high or low multiplex signal output. For best performance a wideband FM tuner should be used with the S3MX. Unique features are 67 KC and hiss filters. Subcarrier sensitivity .01 to 2 volts. Audio output 2V @ $1/2$ % distortion. Power switch disconnects adapter in "off" position. 4 tubes plus rectifier. Size: 5 $\frac{1}{4}$ "x10 $\frac{1}{2}$ "x4". For 110/120 VAC. G-301 Less Case Shpg. wt., 8 lbs. Net 69.50

MODEL A3MX MULTIPLEX ADAPTER (NOT ILLUSTRATED)

Similar to S3MX but less power supply, designed specifically for use within the chassis of Sherwood S-2200 and S-3000III. Can be used with other tuners as well. Less S3MX hiss filter but with 67KC filter (always on). 2 tubes. Shpg. wt., 5 lbs. Net 49.50 G-302



59.95

NO MONEY DOWN

New self-powered FM multiplex adapter operates with all Harman Kardon tuners having multiplex outputs. Circuit has 2 stage subcarrier, main carrier amplifier followed by 19KC synchronous oscillator m-derived L-R filter, two section RC L + R filter, dual phase L-R detector and precision matrix. Crosstalk -40 db. Response ± 1 db at 15-15,000 cps. Size: 2 $\frac{1}{2}$ "x4 $\frac{1}{2}$ "x9" deep. Shpg. wt., 4 $\frac{1}{2}$ lbs. G-650 Net 59.95 Metal Enclosure for MX700. Shpg. wt., 1 lb. G-655 Net 8.95

MX600 ADAPTER Converts TA224, TA260 and TA230 into integrated multiplex receivers. Size: 7 $\frac{1}{4}$ "x1 $\frac{3}{4}$ "x3 $\frac{3}{4}$ ". G-651 Shpg. wt., 2 $\frac{1}{4}$ lbs. Not illustrated Net 49.95




FISHER
UNIVERSAL
MPX-100 STEREO
MULTIPLEX ADAPTER

NO MONEY DOWN **109.50**

Completely self-contained and self powered, the new Fisher MPX-100 is designed to bring FCC approved multiplex reception to all Fisher tuners and receivers including other makes employing wide band design and containing a multiplex output. Unit is equipped with a special "Stereo Beacon" circuit, which automatically signals the moment the station tuned begins broadcasting in stereo. A standby position allows listening to monaural FM program material, at the same time enabling the "Stereo Beacon" to function. Other features include: Front panel Stereo Balance control provides easy adjustment for optimum balance; Selector Switch; separate AUX inputs. Supplied with 3 cables and an attractive vinyl-clad case. Front panel is finished in brushed brass. Size: 12Dx4 $\frac{7}{8}$ x4 $\frac{7}{8}$ " G-118WX Shpg. wt., 10 lbs. Net 109.50

NEW! FM
MULTIPLEX
ADAPTOR
MODEL
MA-2G



Many G.E. FM tuners are now equipped with an output jack wired to provide an external multiplex adaptor with the electrical information necessary for stereophonic reception. The MA-2G is designed to operate in conjunction with such G.E. tuners to provide two stereophonic audio channels which may be connected to the inputs of a stereo amplifying system. Since this adaptor is completely self-contained and self-powered, the only required connections to the existing audio system are those to the multiplex output of the tuner and to the separate inputs of the stereo amplifier system. Frequency response of the adaptor is ± 3 db from 50 to 15,000 cycles. Hum and noise down 60 db. Mounting base is 10Lx2 $\frac{1}{4}$ "W, with mounting holes spaced 2 $\frac{1}{4}$ ". Clearance of 3" required for tubes and capacitor. G-336 Shpg. wt., 3 lbs. Net 39.15



CROSBY MX-101
UNIVERSAL FM
MULTIPLEX
ADAPTOR

69.95

- Pilot Light Indicator
- Dimension Control

NO MONEY DOWN

The Crosby MX-101 is self-powered and designed to attach to any recent model FM tuner. Main channel adjustment on chassis permits proper separation regardless of transmitter standards used by individual stations at outset. Exclusive dimension control varies stereo separation from mono to "expanded stereo." Other features include: 3 position selector switch for 1 mono, 2-stereo in weaker, noisier signal areas; push-button power on/off switch for optimum setting of controls without resetting. Power consumption 25 watts. Four tubes and two machined diodes. Size: 5 $\frac{1}{4}$ "x4 $\frac{1}{2}$ "x9" $\frac{1}{2}$ "D. Complete with enclosure. G-690 Shpg. wt., 8 lbs. Net 69.95



BOGEN-PRESTO

MODEL PX60
SELF-POWERED
MULTIPLEX
ADAPTER

69.50

NO MONEY DOWN

- For Bogen Tuners and Receivers Only
- Just Plug It In — No Complicated Connections

This adapter connects to the multiplex output of FM tuners to provide channel separation of compatible multiplex transmissions. Designed specifically for operation with the following Bogen receivers and tuners: R660, R710, FM51, RC412, RP40, SRB20, SRB40, T661, STP52, TC322, ST322, ST442, RP100, TC200, TC200A, TC100, RB140, TP40 and RB115. With metal case and connecting cables. Size: 4 $\frac{1}{4}$ "x3 $\frac{1}{2}$ "x8 $\frac{1}{4}$ "D. G-395W Shpg. wt., 3 lbs. Net 69.50


REVOLUTIONARY NEW LAFAYETTE LA-440 ALL-TRANSISTOR STEREO AMPLIFIER



Made In U.S.A.

- Dual Concentric Bass & Treble Controls
- Brilliant Design & Performance
- Frequency Response — ± 0.5 db 20 to 20,000 cps
- Instantaneous Operation—No Warm-Up Required
- Hum, Noise & Microphonics Virtually Eliminated
- Place Anywhere—Does Not Require Ventilation as No Heat Is Generated.

99.50
NO MONEY DOWN



- 20 Transistors plus
- 4 Germanium Diodes plus
- 3 Silicon Diodes plus
- 2 Thermistors

Now Lafayette applies space-age electronics to high-fidelity design to bring you this superb new 40-watt stereo amplifier (20-watts each channel). Utilizing the most advanced transistor circuitry, the LA-440 completely eliminates tubes and output transformers; substituting in their place a total of 29 solid state devices to provide an unmatched level of stereo high-fidelity performance. Here is an amplifier that: **GENERATES NO HEAT**—no need to worry about ventilation, you can place it anywhere and current drain is so low, it will operate efficiently not only at 110 V AC, but even from 12 to 28 volt batteries. **REQUIRES A MINIMUM OF MAINTENANCE**—since transistors last indefinitely maintenance problems are virtually a thing of the past and performance will not deteriorate, **VIRTUALLY ELIMINATES HUM, NOISE AND MICROPHONICS**—performance can best be described as transparent, the only sound you hear is that of the music, **PROVIDES INSTANTANEOUS OPERATION**, no need to wait for warm-up, the LA-440 plays as soon as it is turned on.

Controls are provided for every possible stereo, hi-fi function: Front panel contains dual concentric Bass and Treble controls, Volume control, Balance control and Selector switch for Phono, Tuner, Tape, Aux 1 and Aux 2 with corresponding inputs provided on the rear panel. In addition, slide switches are provided for Mono A—Stereo—Mono B, Loudness, Scratch Filter and Rumble Filter. Rear panel contains 2—switched AC outlets plus 3 tape outputs for recording stereo or mono (Tape A, Tape B, A & B).

Superbly styled, the LA-440 measures only 3Hx10½Wx8½"D and is finished in a brushed gold front panel, anodized aluminum knobs and is complete with matching enclosure. Shpg. wt., 10 lbs.

STUDY & COMPARE THESE SPECIFICATIONS

I.H.F.M. Music Power Output: 40 watts (20 watts per channel) based on 4-ohm load impedance
 Frequency Response: ± 0.5 db 20 to 20,000 cps measured according to IHFM standards
 Intermodulation Distortion: 0.9% at 1 db below clipping 60 and 6,000 cps
 Harmonic Distortion: 0.5% at 1 db below clipping
 Hum and Noise: Completely inaudible at all playing levels.
 Phono Input: —72 db Tuner Input: —85 db
 Output Impedance: May be used with 4, 8, 16 ohm loud-speakers.
 Power Requirements: 105-120 volts AC, 50-60 cps. 12 to 28 volts DC for battery operation.

40-WATT ALL TRANSISTOR LA-440 AMPLIFIER IN MATCHED STEREO SYSTEMS



194.50
NO MONEY DOWN



LAFAYETTE 40-WATT ALL TRANSISTOR AMPLIFIER IN MATCHED STEREO SYSTEMS

Lafayette LA-440 40-watt All-Transistor Stereo Amp.	99.50
Lesca CD 2/21 4-Speed Record Changer	44.50
Wood Base for Changer (Specify Walnut, Mahog. or Blonde)	4.75
Audio Empire S108 Diamond Needle Cartridge	35.00
2-Lafayette SK-58 Free Edge 12" Coaxial Speaker @ 29.50 each	59.00

LAFAYETTE SYSTEM PRICE 194.50 REGULAR CATALOG PRICE ~~243.76~~
YOU SAVE 48.25

System No.	Amplifier	Changer	Cart*	Base	Speaker	Speaker Cabinet**	Shpg. Wt. Lbs.
LS-441WX	LA-440	Lesca CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-58		48 194.50
LS-442WX	LA-440	Garrard Autoslim		+	2 ea. SK-58	2 ea. Eliploflex	48 194.50
LS-443WX	LA-440	Lesca CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-58	2 ea. Eliploflex	96 260.50
LS-444WX	LA-440	Garrard Autoslim		+	2 ea. SK-58	2 ea. Eliploflex	96 260.50
LS-445WX	LA-440	Lesca CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-180		45 198.50
LS-446WX	LA-440	Garrard Autoslim		+	2 ea. SK-180		45 198.50
LS-447WX	LA-440	Lesca CD 2/21	Choice of Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7	+	2 ea. SK-180	2 ea. Eliploflex	93 264.50
LS-448WX	LA-440	Garrard Autoslim		+	2 ea. SK-180	2 ea. Eliploflex	93 264.50

Any of above systems with addition of Lafayette LT-700WX Multiplex Stereo Tuner (described on other page) add 114.50 to system price. When ordering, add the letter T to the prefix i.e. LST-441WX. * Specify Mahogany, Walnut or Blonde Base. **: Specify Walnut, Oiled Walnut, Mahogany or Blonde.



* Be Sure To Specify Choice of Empire S108, Pickering 380C, Shure M7D or GE-VR1000-7 Cartridge.

FAMOUS H. H. SCOTT 299B 50-WATT STEREO AMPLIFIER



SAVE 60.45
at LAFAYETTE'S
Low, Low **PRICE**

Regularly 209.95
149.50
NO MONEY DOWN

For The First Time At This Price!

QUANTITIES LIMITED
 Check The Specs — Check The Name — Now Check The Price and you'll know why we feel this is the Hi-Fi buy of the year.

Famous for its performance, thousands purchased this sought after stereo amplifier for 209.95. Now you can have this same amplifier for your stereo system and save over \$60. The 299B is rated at 50 watts and includes two complete channels with dual preamps and 25-watt power sections. Offers complete stereo facilities — a third channel output is provided for three channel stereo. Controls include: Master Function Selector; separate Bass and Treble controls for each channel; Balance control; Loudness control; Rumble and Scratch filters; Phase Reversal switch and Input Selector. Stereo Tape Recorder facilities provide for recorder output, playback

input plus a front panel monitor switch. Frequency Response is flat from 20 to 30,000 cps. Hum level is better than 80db below maximum output. Harmonic Distortion is less than 0.8%. The low level stereophonic cartridge input has a 3 millivolt sensitivity for accommodating stereo cartridges with very low output. 4, 8, and 16-ohm speaker taps are furnished for each channel. For 105-125 volts, 50-60 cycle operation. Size including optional accessory case: 15¼x12½x4¾".
 G-135WX Shpg. wt., 25 lbs. Net 149.50
 Accessory Case for Scott 299B. Shpg. wt., 1 lb. G-147W Net 12.95

UNPRECEDENTED STEREO PERFORMANCE VALUE! A COMPLETE MATCHED STEREO SYSTEM FEATURING THE H. H. SCOTT 299B



Lafayette SYSTEM PRICE
256.60
 YOU SAVE 49.85



COMPONENTS

H. H. SCOTT 299B 50-WATT STEREO AMPLIFIER	149.50
GARRARD RC-88 Record Changer	59.50
BASE FOR RC-88 (Specify Finish)	3.95
AUDIO EMPIRE S108 Diamond Needle Stereo Cartridge	34.50
2-LAFAYETTE FAMOUS SK-58 Free Edge 12" COAXIAL SPEAKERS @ 29.50 each	59.00
Regular Catalog Price	308.45

Complete System as above with choice of Audio Empire S108, Pickering 380C or Shure M7D Stereo Cartridge. HS-736WX Shpg. wt., 65 lbs. Net 256.60
 Same as HS-736WX above, plus 2-Lafayette Eliploflex Series Bookshelf Enclosures (specify finish). HS-737WX Shpg. wt., 140 lbs. Net 322.60
 Complete system essentially the same as HS-736WX, but with the Garrard Model A Automatic Turntable. HS-738WX Shpg. wt., 67 lbs. Net 272.20
 Same as HS-738WX above, plus 2-Lafayette Eliploflex Series Bookshelf Enclosures (specify finish). HS-739WX Shpg. wt., 142 lbs. Net 338.20

NEW!



174.95
No Money Down

LAFAYETTE LA-225 FM-AM 40 WATT STEREO RECEIVER

A MATCHED FM-AM STEREO TUNER PLUS A 40-WATT STEREO AMPLIFIER (20-WATTS EACH CHANNEL) AT LAFAYETTE'S AMAZING LOW PRICE!

Designed for the control and reproduction of all stereo and monophonic sources including an FM Multiplex output. Receiver sensitivity 1.5 mv for 20 db of quieting on FM with AFC. Frequency response 20-30,000 cps ± 1 db at normal listening levels. 16 controls. Complete with handsome enclosure. 17½W x 15D x 5¼"H.
 LA-225WX Shpg. wt., 45 lbs. Net 174.95

A COMPACT PACKAGE with OUTSTANDING QUALITY

LAFAYETTE LA-225 FM-AM STEREO PHONO SYSTEM



at an unprecedented **LOW PRICE!**

SAVE 43.30 **299.95**

Compact Hi-Fi Stereo System with units at left. Choice of Pickering 380C or Shure M7D cartridge and mahogany, walnut or blonde changer base (specify finish). HS-410WX Shpg. wt., 86 lbs. Net 299.95
 Same as HS-410WX but with 2 "Eliploflex" Bookshelf Enclosures (Specify Finish). HS-411WX Shpg. wt., 162 lbs. Net 362.95
 Same as HS-410WX but with 2 famous Lafayette SK-58 Free-edge 12" 2-way speakers. HS-412WX Shpg. wt., 86 lbs. Net 295.95

NEW! OMEGA ALL TRANSISTOR 60 WATT STEREO AMPLIFIER



249.00
NO MONEY DOWN

Made in U.S.A.

- 31 Transistors
- Advanced "Quadra-Power Circuit"
- Flat Frequency Range Beyond Audibility
- Cool Operation
- Full Complement of Stereo Controls
- Unconditional 2-Year Guarantee

SPECIFICATIONS:

Controls: Master Bass and Treble; Independent bass and treble; Mode, Volume Balance; Blend, Loudness; Scratch filter rumble filter; phase switch; tape Monitor; 5-position selector switch; and Cartridge output compensator. Frequency response 18-20,000 cps ± 0.3 db at full output. Harmonic and IM distortion: less than 1%; hum and noise: 75 db below full output. Power output 30-watts (IHFM Music Rating) per channel Stereo — 60 watts monaural. 31 transistors, 4 diodes, 1 zener diode, 2 silicon rectifiers.

For the first time an all-transistor 60-watt stereo amplifier with the performance of the finest tube equipment plus all the big listening and maintenance advantages of transistors. Exclusive "Quadra-Power Circuit" employs four power transistors per channel with uniform power dissipation and powerful linear response extending the frequency range to well beyond normal hearing. Since transistors are non-microphonic and there isn't any tube heater hum, there is a wonderfully clear tone to the sound. The Omega provides master bass and treble controls which allow a simple simultaneous balance adjustment of both channels. Another advanced feature is the exclusive cartridge output compensator which permits adjusting the amplifier to the speaker output voltage of your ceramic or magnetic pickup cartridge. Thus all front panel controls operate over their optimum range regardless of the cartridge output level. Trouble free transistor circuit is unconditionally guaranteed for two years. Modern styling is at home in any decor. Only 3H x 15½W x 9"D. For 117 VAC/60 cycles. Shpg. wt., 12 lbs.
 G-685WX Net 249.00

AMAZING LAFAYETTE VALUE & PERFORMANCE



READY FOR MULTIPLEX!

MODEL LT-80A FM TUNER

A LAFAYETTE SPECIAL VALUE!
COMPARE FEATURE FOR FEATURE WITH THE MOST EXPENSIVE TUNERS

49.50

NO MONEY DOWN

- ARMSTRONG CIRCUIT FOSTER-SEELEY DISCRIMINATOR AND DUAL TUNED LIMITERS • AFC • AFC DEFEAT • EXTREMELY SENSITIVE—1.5 UV FOR 20 DB QUIETING • 10-TUBE PERFORMANCE—8 TUBES (2-DUAL PURPOSE) • 20-20,000 CYCLES ± 1/2 DB • SUPERB LOW SILHOUETTE STYLING • 3 GANG TUNING CONDENSER • TUNED GROUNDED GRID RF STAGE



PIN-POINT TUNING ACCURACY


is provided by this precision tuning meter; evaluates relative strength of the incoming signal... invaluable when tuning weak stations.

Remarkable... Quality, performance and styling that is in every respect the equal and in many instances superior to tuners priced far above the modest cost of this instrument. The same sensitive FM circuit employed in the LT-77 AM-FM Stereo Tuner (Specifications as listed above) has been incorporated in the LT-80... designed and constructed of the finest components, with jewel like precision (each unit is hand wired) in order to insure that each tuner will maintain its excellence year after year with a minimum of maintenance. Engineered to provide maximum FM versatility, the LT-80A is provided with a multiplex output, designed to accept a stereo multiplex adapter for reception of the new FCC approved FM stereo broadcasts. Controls consist of On-Off; FM; FM AFC and FM MPX. Flywheel action tuning control provides velvet-smooth tuning action. Tube complement consists of 2-6AQ8, 2-6BA6, 2-6AU6, 1 each 6AL5 and 6X4. Handsome low silhouette enclosure will do justice to any decor. Beautifully finished in gold and white with contrasting black dial face. Complete with cage and legs. Dimensions: 11 1/2" W x 8" D x 4 1/4" H.

LT-80A FM Stereo Tuner
HTA-11WX Combination of LT-80A and LT-200 FM Multiplex Adapter.

Net 49.50
You Save 5.00

STEREO COMBINATION! LT-80A FM TUNER WITH LT-200 MULTIPLEX ADAPTER



Save by purchasing your LT-80A Tuner together with Lafayette's exciting new LT-200 Multiplex Adapter and be fully equipped to receive the new stereo FM multiplex broadcasts.
HTA-11WX

\$92.00
You Save 5.00
Net 92.00



READY FOR MULTIPLEX!

MODEL LT-77A FM-AM STEREO TUNER

- 14 Tube Performance—10 Tubes (2-Dual Purpose + Rectifier Diode & 2-Tuning Meters • Armstrong Circuit with Dual Tuned Limiters and Foster-Seeley Discriminator • FM AFC and AFC Defeat • Tuned Grounded Grid R.F. Stage on AM & FM • Multiplex Output • Flywheel Tuning • AM Features Broad-Band Tuned I.F. Stage • 2-3 Gang Condensers • Individual Volume-Balance Controls for AM & FM

WEAK SIGNAL— STRONG SIGNAL

Lafayette's separate, precision twin-tuning meters for FM and AM insure pinpoint tuning accuracy every time.



A LAFAYETTE SPECIAL VALUE!
COMPARE THESE FEATURES AGAINST HIGHER PRICED TUNERS

74.50

NO MONEY DOWN

Simplicity, flexibility and superb styling have been carefully integrated in this quality instrument. Offering unlimited versatility, the LT-77 features separate AM and FM sections, allowing independent use of each section if desired for reception of FM-AM stereo simulcast broadcasts. In addition a multiplex output has been provided; designed to accept a stereo multiplex adapter for reception of the new FCC approved FM stereo broadcasts. Each unit has been hand wired and individually laboratory tested. Controls provide for every tuner function. Push-button on-off power switch; Separate AM/FM flywheel tuning; Individual AM/FM volume controls; Choice of AM, FM, FM multiplex stereo or AM/FM stereo reception. Variable AFC control is adjustable for tuning weak stations adjacent to strong stations. Plate follower output permits using the tuner 50 ft. or more from the amplifier. FM circuitry features Armstrong grounded grid low noise front end and triode mixer coupled with tuned dual limiters. Foster-Seeley discriminator with AFC and AFC defeat. FM Sensitivity of 1.5 uv for 20 db quieting insures long range reception. Superhet AM circuit with 3 stages AVC and ferrite loopstick antenna. Individual 3-gang tuning condenser and tuned RF stages for both AM and FM sections. Selectivity: FM 200 KC band width; 6 db down, AM 8 KC BW; 6 db down. Frequency Response: FM 20-20,000 cps ± 1/2 db AM 20-50,000 cps ± 3 db; Harmonic Distortion under 1% on FM; Under 1% on AM for up to 80% modulation. Hum Level —60 db. Image Rejection: FM, better than 40 db AM 70 db. I.F. Rejection: FM 70 db, AM 50 db Radiation meets FCC requirements. Tubes: 2-6AQ8, 4-6BA6, 2-6AU6, 1 each 6BE6, 6AL5 and 6X6 plus diode detector. Antenna Input: 300 ohms.

Superbly styled low silhouette enclosure finished in gold and white with easy to read black dial face. Complete with cage and legs. Dimensions: 14 1/2" W x 4 1/4" H x 10 3/4" D. Legs add 3/4" to height.

LT-77A AM-FM Stereo Tuner. Shpg. wt., 16 lbs.

HTA-10WX Combination of LT-77A and LT-200 FM Multiplex Adapter. You Save 5.00

Net 74.50
Net 117.00

SPECIAL AM-FM-MPX COMBINATION! LT-77A and LT-200 MULTIPLEX ADAPTER



A complete stereo package that will allow you to receive AM-FM monaural, AM-FM stereo simulcast and FM stereo multiplex. And, you save \$5 by purchasing both the LT-77A and LT-200 MPX adapter together.
HTA-10WX

117.00
You Save \$5.00
Net 117.00

NOW! LAFAYETTE LA-55 15 WATT MONAURAL AMPLIFIER



44.50

NO MONEY DOWN
AN UNBEATABLE VALUE!

The most extraordinary Hi-Fi value ever offered

- Frequency Response: 15-30,000 CPS
- Hum 65 Db Below Rated Output
- Rumble Filter
- Power Output 15 Watts
- Harmonic Distortion Less Than .3%
- EL84 Output Tubes in Push-Pull
- Sensitivity: 3 MV Mag. Phono
- 5 Input Channels
- Beautifully Styled

Outstanding Performance and Engineering + Beautiful Styling + Unbeatable Price—add up to make the Lafayette LA-55 truly the finest Hi-Fi monaural amplifier value today... Beautifully styled in gold and white, the LA-55 easily adapts to any room decor. Perfect for that music system in your living room, finished basement, store or office. Ruggedly constructed, this fully integrated amplifier-preamplifier employs premium quality EL84 tubes in push-pull and advanced circuitry for faithful reproduction of all monophonic sources... perfect for use as a second amplifier for stereo or for starting out monophonically and adding stereo at a later date. Engineered to include every practical feature... a worthwhile contribution to hi-fi reproduction.

... SPECIFICATIONS: Power Output 15 watts Institute of High Fidelity Manufacturers Rating (30 watts peak). Frequency Response 15-30,000 cps ± 1 db (at normal listening level); Sensitivity: For full power, High level inputs 0.5v. Mag. phono 3 mv. Hum and Noise: Volume control at max. High level inputs 65 db below rated output. Mag-Phono 55 db below rated output; Harmonic Distortion less than .3%. Inputs: Total 5—Aux, Tuner, Mag. Phono, Crystal Phono, Tape Head. Outputs: Tape Out, 4, 8 and 16 ohm speaker terminals; Tubes: Total of 5 plus rectifier—2-EL84, 1-6BL6, 1-6AV6, 1-12AX7, and 1-6CA4/WZ81. Controls: Monitor/On-Off; Volume/Power On-Off; Bass; Treble; Rumble Filter. Hum balance control. Selector: 4-position, Aux, Tuner, Phono, Tape Head. Complete with removable case and legs. AC receptacle on rear of chassis. Dimensions: 13 1/2" W x 4" H x 8 3/4" D. Knobs extend 3/4" in front of panel. Shpg. wt., 20 lbs.

Net 44.50

LAFAYETTE SUPER-VALUE HIGH-FIDELITY PHONO SYSTEM

PLAY STEREO & MONAURAL RECORDS MONAURALLY, NOW — ADD COMPLETE STEREO LATER. This economical high-fidelity system is the performance value of the year. Designed for ruggedness as well as beauty, these components will satisfy even the most critical music listener.

COMPONENTS

LAFAYETTE LA-55 15 Watt Complete Amplifier	44.50
LESA CD 2/21 4-Speed Record Changer	44.50
WOOD BASE FOR CHANGER (Specify Walnut, Mahog. or Blonde)	4.75
AUDIO EMPIRE S108 Diamond Needle Cartridge	35.00
LAFAYETTE SK-128 Full Range 8" Bixial Speaker	19.50

Regular Catalog Price 148.25


LAFAYETTE SYSTEM PRICE **109.50** YOU SAVE 38.75

LAFAYETTE 15 WATT MATCHED MONAURAL SYSTEMS

*Make certain to indicate your choice of either Audio Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7 Diamond Needle Stereo Cartridge.

System	Amplifier	Changer	Cartridge*	Base†	Speaker	Spkr. Cabinet	Shpg. Wt.	Net
LS-51WX	LA-55	Lesca CD2/21	Your Choice of Empire S108,	Lesaf	SK-128	—	39 lbs.	109.50
LS-52WX	LA-55	Garrard Autoslim	Empire S108,	Laf†	SK-128	—	39 lbs.	109.50
LS-53WX	LA-55	Lesca CD2/21	Pickering 380C,	Lesaf	SK-128	Miniduct†	62 lbs.	132.00
LS-54WX	LA-55	Garrard Autoslim	380C,	Laf†	SK-128	Miniduct†	62 lbs.	132.00
LS-55WX	LA-55	Lesca CD2/21	Shure M7D,	Lesaf	SK-58	—	45 lbs.	119.50
LS-56WX	LA-55	Garrard Autoslim	or	Laf†	SK-58	—	45 lbs.	119.50
LS-57WX	LA-55	Lesca CD2/21	GE VR-1000-7	Lesaf	SK-58	Eliptoflex	69 lbs.	154.50
LS-58WX	LA-55	Garrard Autoslim	VR-1000-7	Laf†	SK-58	Eliptoflex	69 lbs.	154.50

Lafayette LT-80A FM Tuner with any system above, add 49.50 to Net price. To order, specify system No. plus LT-80A. Autoslim—Garrard 4-Speed Record Changer. Miniduct—Shelf Speaker Enclosure for 8" Speaker. Eliptoflex—Shelf Speaker Enclosure for 12" Speaker—Specify Walnut, Oiled Walnut, Mahogany or Blonde. †—Specify Mahogany, Walnut or Blonde.



LAFAYETTE LA-55



LESA CD2/21



GARRARD "AUTOSLIM" (ALTERNATE CHANGER)



SK-58 12" COAXIAL SPEAKER (ALTERNATE)




LAFAYETTE LT80A (OPTIONAL TUNER)




CHOICE OF

Audio Empire S108 Pickering 380C Shure M7D GE VR 1000-7



SK-128 8" BIXIAL SPEAKER "MINIDUCT" ENCLOSURE (OPTIONAL WITH SK-128)



"ELIPTOFLEX" ENCLOSURE (OPTIONAL WITH SK-58)

THE NEW LAFAYETTE LA-240 40-WATT STEREO AMPLIFIER

**A COMPLETE STEREO CONTROL CENTER
UNSURPASSED CONSTRUCTION & PERFORMANCE!**

- Concentric Volume Balance Control
- Less Than 1% Harmonic Distortion at Rated Output
- Hum & Noise 80 db Below Rated Output
- Frequency Response: 12-100,000 cps \pm 1 db at 1 Watt
- Variable Separation Control Eliminates Exaggerated Channel Separation
- Dual Concentric Bass & Treble Controls
- High Sensitivity Allows Use With All Stereo Cartridges

COMPARE THESE FEATURES

Quality, Design and Performance That Are Remarkable—The Lafayette LA-240 represents the highest standards of stereophonic amplifier design—literally creating a new meaning for excellence. Use of the most advanced engineering techniques and finest components have resulted in a powerful 40-watt stereo amplifier incorporating two 20-watt power channels and dual preamplifier. A level of flexibility and performance have been achieved that can only be compared with units twice the price.

Separation Control—Provides continuously variable channel separation from full stereo to full monaural, thus insuring the correct degree of stereo separation for individual listening tastes and room acoustics.

Independent Tone Controls—Concentrically mounted bass and treble controls for each channel.

Volume—Balance Control—Individual level controls for each channel.

Loudness Switch—Allows the volume controls to function as compensated loudness controls and provides the frequency response changes required by the ear at low distortion levels.

Rumble Filter—Reduces rumble from a noisy turntable with a minimum effect on program material.

Mode Switching—Ch A and Ch B slide switches provide for normal stereo, reverse channel, monophonic A or monophonic B.

Selector Switch—Instant selection of Aux, Tuner, Phono or Tape Head Inputs—non-shorting position permits recording and playback using a permanently connected tape recorder.

Hum Balance Controls—Individual hum balance controls for each channel located at the rear for fast, easy minimum-hum adjustment.

Full Range of Inputs & Outputs—Inputs: (5 stereo pairs) Dual Aux—Dual Tuner—Dual Ceramic Phono—Dual Mag. Phono—Dual Tape Head; Outputs: Dual Tape Out—Dual 8 and 16 ohm speaker terminals.

Superb Low Silhouette Styling makes the LA-240 an amplifier you'll be proud to display. Gold finish cover is set off by an ivory and gold front panel with gold metal knobs. Complete with cage and legs. Overall Dimensions: 14 1/4" W x 10 1/2" D x 5 3/4" H. For 115V AC operation. Power consumption 185 watts. LA-240WX Shpg. wt., 25 lbs. Net 79.95




*Dual 20-Watt Power Amplifiers
Dual Stereo Preamplifier*

One Handsome Compact Unit

79.95
NO MONEY DOWN

SPECIFICATIONS

Power Output and Distortion—20 watts per channel at less than 1% total harmonic distortion at 1 Kc. Less than 0.25% total harmonic distortion at 14 watts; less than 0.12% at 1 watt. Intermodulation Distortion: .075% at 1 watt; .34% at 10 watts. Frequency Response: 12 to 100,000 cps \pm 1 db at 1 watt. 50 to 70,000 cps \pm 1 db at full output. Sensitivity: For full output: High Level inputs 0.75v Mag. inputs 5.5 Mv at 1 Kc. Tone Control Range: Treble: 12 db boost or cut at 10 Kc. Bass: 15 db boost or cut at 50 cps. Hum and Noise: Zero volume hum: 80 db below rated output. Maximum volume hum: High level inputs, 78 db below rated output; Mag. Phono inputs, 50 db below rated output. Outputs: Dual 8 and 16 ohm impedance speaker outputs, Dual Tape outputs. Tube Complement: 4—6BQ5/EL84, 2—6BL8/ECF80, 3—12AX7/ECC83, 1—GZ34/SAR4.



LAFAYETTE 40-WATT MATCHED STEREO SYSTEMS

COMPONENTS

Lafayette LA-240 40-Watt Stereo Amplifier	79.95
Lesca CD 2/21 4-Speed Record Changer	44.50
Wood Base For Changer (Specify Walnut, Mahog or Blonde)	4.75
Audio Empire S108 Diamond Needle Cartridge	35.00
2-Lafayette SK-128 Full Range 8" Bixial Speakers @ 19.50	39.00
Regular Catalog Price	203.20


LAFAYETTE 40-WATT MATCHED STEREO SYSTEMS

*Specify Choice of Audio Empire S108, Pickering 380C, Shure M7D, or GE VR-1000-7 Diamond Needle Stereo Cartridge.

System	Amplifier	Changer	Cartridge*	Base†	Speakers	Cabinet‡	Lbs.	Net
LS-341WX	LA-240	CD2/21	Choice of	Lesca	2 SK-128	—	50	162.95
LS-342WX	LA-240	Garrard Autoslim	Audio Empire S108,	Laf	2 SK-128	—	50	162.95
LS-343WX	LA-240	CD2/21	Audio Empire S108,	Lesca	2 SK-128	2 Mini-Duct††	95	205.95
LS-344WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-128	2 Mini-Duct††	95	205.95
LS-345WX	LA-240	CD2/21	Pickering 380C,	Lesca	2 SK-180	—	55	186.95
LS-346WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-180	—	55	186.95
LS-347WX	LA-240	CD2/21	Shure M7D	Lesca	2 SK-180	2 Eliofoflex‡‡	103	252.95
LS-348WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-180	2 Eliofoflex‡‡	103	252.95
LS-349WX	LA-240	CD2/21	Or	Lesca	2 SK-58	—	58	182.95
LS-350WX	LA-240	Garrard Autoslim	GE VR-1000-7	Laf	2 SK-58	—	58	182.95
LS-351WX	LA-240	CD2/21	Garrard	Lesca	2 SK-58	2 Eliofoflex‡‡	106	248.95
LS-352WX	LA-240	Garrard Autoslim	Lesca	Laf	2 SK-58	2 Eliofoflex‡‡	106	248.95

See Full Descriptions Elsewhere on SK-128, SK-180, SK-58, Mini-Duct & Eliofoflex. † Specify mahogany, walnut or blonde finish. ‡ Specify walnut, oiled walnut, mahogany or blonde finish.

Any of above systems with addition of Lafayette LT-700WX Multiplex Stereo Tuner (described on other pages) add 114.50 to system price. When ordering add the letter T to the prefix. Example LS-341WX system with LT-700WX tuner is ordered as LST-341WX.



YOU SAVE 40.25

LAFAYETTE SYSTEM PRICE

NO MONEY DOWN

ONLY **162.95**

For any of above systems with Shure M30 Diamond Stylus Stereo Cartridge in place of choice of above cartridges add \$18.50 to System Net Price.

Bogen

RP200 40-WATT STEREO MULTIPLEX RECEIVER

299.95

All in one music center—20/20 watt stereo amplifier, AM receiver, FM receiver, multiplex network and preamplifier. The specifications of the RP200 are superior to many separate component units, yet this system is more compact and more adaptable to console installation. Front panel controls: Function selector; dual volume; dual bass; FM tuning; AM tuning; power; AFC. Chassis circuitry employs 16 tubes, 3 crystal diodes and 7 rectifiers. SPECIFICATIONS: FM sensitivity 1.25 uv 20 db quieting, 3 uv IHFM standard; frequency response (amplifier) \pm 1 db 20-20,000 cps; audio sensitivity 4.5 mv (max.); hum and noise—58 db FM, —48 db AM; distortion FM 1.5%, AM 3%, mag. cart. 0.6% all at rated output. Built-in AM & FM antennas. Size: 16 1/2 x 5 1/2 x 14" deep. Shpg. wt., 29 lbs. For operation from 110-120 volts, 50-60 cycles AC. G-324WX Less Enclosure Net 299.95 Model EN-2 Metal Enclosure For RP-200 Shpg. wt., 6 lbs. G-397W Net 11.55

SHERWOOD

S-8000 64-WATT FM MULTIPLEX STEREO RECEIVER

Model S-8000 Includes the same advanced FM Multiplex receiver as the S-3000 IV and in addition it contains two 32 watt power amplifier - preamplifiers. High sensitivity FM tuner provides 20 db of quieting for 0.95 uv input. Available on the front panel are the following controls: Interchannel hush, flywheel FM tuning; friction-locked dual bass and treble controls; ganged loudness control; phono level control; stereo balance control; stereo function selector; input selector switches and 6 slide switches for activating scratch and rumble filters. AMPLIFIER SPECIFICATIONS (See S-3000 IV description for tuner specs.): Power output 32/32 watts music power, 30/30 watts continuous duty @ 1 1/2% IM distortion; frequency response 20-20,000 cps \pm 1 db @ 30 watts. Hum and noise, 60 db below 30 watts. Inputs: tape playback, tape monitor, phono, AM tuner plus 2 auxiliary outputs for recording and 4, 8 and 16 ohm speakers. "Acro-beam" type tuning indicator and 7" FM dial scale. Tube complement: 22 plus 4 silicon rectifiers. Size: 16 1/4 x 14 x 4 1/2". Power requirements: 110-120V, 50-60 cycles AC @ 225 watts. Tube filaments are D.C. supplied. Model S-8000 requires just 2 sockets to complete a system for FM stereo listening. G-300WX Less enclosure Shpg. wt., 36 lbs. Net 299.50 Brown leatherette case for S-8000. G-298W Shpg. wt. 10 lbs. Net 7.50

FISHER

500-B 65 WATT FM MULTIPLEX STEREO RECEIVER

The new 500-B receiver has 18 controls and switches for flexible control of its wideband FM multiplex tuner, dual channel preamplifier and dual channel 65 watt power amplifier. Front panel controls are: FM tuning; MPX filter, dual volume, dual bass, dual treble, high filter, low filter, tape monitor, dual selector, monostereo, channel reverse, balance, loudness. FM circuit has 4 IF stages, advanced multiplex design, special switchable noise filter and "Stereo Beam" tuning indicator. SPECIFICATIONS: Amplifier distortion less than 0.5%. Overall frequency response 25-25,000 cps \pm 1.5 db; FM sensitivity 0.7 uv into 72 ohm load; IHFM sensitivity 2.2 uv; signal/noise & hum 70 db. IF bandwidth 190 Kc; channel selectivity 52 db; FM response (after deemphas) 30-15,000 cps; Tubes: 4-ECC85, 6-6AU6, 4-12AX7, 2-7591, 2-EM84A, 1N-542, plus special multiplex tubes. Size: 17 1/2 x 5 3/4 x 13 1/4" deep. G-403WX Less cabinet. Shpg. wt., 35 lbs. Net 359.50 FISHER 30-U Oiled Walnut Cabinet for 500-B. G-404W Shpg. wt., 6 lbs. Net 24.95

THE OUTSTANDING

"Stereo 250 A" KIT

ASSURANCE OF COMPONENT QUALITY
ONE YEAR PARTS GUARANTEE
All components in this unit are conservatively engineered to operate well within their performance capabilities. As assurance of this quality, Lafayette guarantees all parts including tubes for one year.

50 WATT INTEGRATED STEREO AMPLIFIER KIT

- DC applied to all preamplifier and tone control tube heaters for hum-free operation
- RIAA equalization on phono inputs
- NARTB tape equalization on tape head inputs
- Individual bias and balance controls
- Hum balance Control
- Excellent DC power supply regulation provided by silicon diodes
- Total of 9 tubes, plus 3 silicon diodes—uses premium 6CW5/EL86 output tubes.

Made in U.S.A.

IN EASY-TO-BUILD KIT FORM
74⁵⁰
NO MONEY DOWN



SPECIFICATIONS

POWER OUTPUT: 50 watts (100 watts peak) 25 watts per channel ± 1 db. DISTORTION: Total Harmonic Distortion ± 1 db at less than 1% at 1KC at normal listening level (1 watt); I.M. Distortion less than 0.5% at normal listening level. FREQUENCY RESPONSE: 15-40,000 cps ± 0.5 db at normal listening level, 20-50,000 cps ± 1 db at rated output. HUM & NOISE: Zero volume hum 77 db below rated output; max volume hum high level inputs 70 db below rated output; Mag. phono inputs 50 db below rated output. Sensitivity: For full output high level inputs 0.5V; Mag. phono 3.5 MV at 1KC. CHANNEL SEPARATION: Greater than 55 db at 1KC; greater than 45 db from 20-20,000 cps. SPEAKER AUXILIARY OUTPUT: 1 switched. TUBE COMPLEMENT: 4-6CW5/EL86, 2-7199, 3-12AX7, 3 Silicon diodes. IMPEDANCE: 4, 8 and 16 ohms per channel. POWER: 200 watts; 110-125V AC 50-60 cps. MODEL KT-250AWX Net 74.50

THE new Lafayette KT-250A offers remarkable versatility, high quality of reproduction and new distinctive styling in one convenient low-cost unit. Designed and engineered for ease of assembly, the KT-250A is a fine stereo preamplifier and 50 watt stereo amplifier combined — with all the controls and features to enable you to enjoy the utmost in listening pleasure in any situation. Whether you use it as a stereo amplifier delivering 25 watts per channel or as a powerful 50 watt monophonic amplifier, you are assured of true high fidelity reproduction — free from hum, noise and distortion.

DELUXE FEATURES

- Unique Separation Control**—A new stereo control which provides continuously variable channel separation—from full monophonic to full stereo. Lets you select the amount of separation you want.
- Clutch-Operated Volume Balance Control**—Gives you a choice of independent or simultaneous control of both channels—you can use it as a master volume control without disturbing previously selected settings on each channel.
- 4 Independent Tone Controls**—Independent Bass and Treble adjustment for each channel. Concentric mounting for convenience—
- inner knob controls one channel, outer the other channel.
- Mode Switching**—Two slide switches provide Normal Stereo—Reverse Channel—Mon A (Channel A reproduced through both channels)—Mon B (Channel B reproduced through both channels).
- Input Selector**—4-position switch lets you select instantly any one of your connected monophonic or stereo sources—special non-shorting arrangement on one position permits recording and playback using a permanently connected tape recorder.

Loudness Switch—Provides the frequency response changes required by the ear at low listening levels and permits the Volume-Balance control to function as a compensated loudness control.

Phase Switch—Reverses the phase of one channel electrically—corrects for speakers connected out of phase or for reversed phase recordings sometimes found commercially.

3 Pairs of High Level Inputs—For connection of Crystal or Ceramic phono, Tuner, and auxiliary equipment.

2 Pairs of High Level Inputs—For connection of magnetic phono and Tape Head.

Main Speaker Outputs—Dual 4, 8 and 16 ohm terminals may be paralleled for 4 or 8 ohm operation at 50 watts.

Tape Output—Provides an output for Tape recording—unaffected by Volume and Tone Controls.

Bridged Output—A monophonic blend of both channels which can be fed to a third single channel power amplifier and speaker for a greater sound spread in stereo. May also be used for listening in another room.



NO TECHNICAL SKILL REQUIRED

Designed for ease of construction, the KT-250A can be assembled in a minimum of time. Assembly manual contains detailed step-by-step instructions... guides you every step of the way. Large full-scale pictorials show you where every wire and component goes.



Made in U.S.A.

NO MONEY DOWN

59⁵⁰

Lafayette 36 watt stereo amplifier

Fine wide-range stereo reproduction can be yours when you build this easily constructed 36 watt stereo amplifier (18 watts each channel). The KT-236A provides all the necessary inputs—lets you connect your stereo or monophonic sources permanently, with instant selection provided by the turn of a switch. Has built-in dual preamps for low level phono inputs—RIAA equalized for flat response. It includes a unique "Blend" control which provides continuously variable channel separation from full monophonic to full stereo—you select the exact degree of separation you want. Other features are: Concentric clutch-operated Volume control for independent or simultaneous level adjustment of both channels; Dual concentric Bass and Treble controls—give you 4 independent tonal adjustments; 3-position Selector Switch—Aux-Tuner-Phono; Mode (2 Slide Switches) provide Normal Stereo, Reverse channel, Mon A and Mon B; Phase switch—makes up for reversed-phase recordings sometimes found commercially and also corrects for speakers connected out of phase.

SPECIFICATIONS: POWER OUTPUT: 36 watts—18 watts per channel ± 1 db. Institute of High Fidelity Manufacturers Rating (72 watt peak). FREQUENCY RESPONSE: 15-30,000 cps ± 1 db at normal listening levels. SENSITIVITY: For full output; High level inputs 0.5V; Mag. Phono 3 mv. DISTORTION: Harmonic, less than 0.15% at normal listening level; I.M. less than 3%. HUM AND NOISE: (At full volume) High level inputs 70 db below rated output; Mag. phono 53 db below rated output. CHANNEL SEPARATION: Better than 50 db. SPEAKER OUTPUT IMPEDANCE: 8 and 16 ohms. INPUTS: (Total 8) Dual Aux, dual Tuner, dual Crystal Phono, dual Mag. Phono. OUTPUTS: (Total 4) Dual main speaker output, dual Tape Out jacks. TUBE COMPLEMENT: 4-EL84, 2-7199, 3-12AX7 plus 2 silicon diodes. Attractive beige vinyl laminated steel cabinet. Handsomely designed brass anodized aluminum front panel. Sienna brown molded legs, matching knobs with polished brass inserts. 14 1/2" wide x 11 1/2" deep x 5 3/4" high (with legs and knobs). Shpg. wt., 24 lbs. 36 watt integrated Stereo Amplifier Kit, complete with deluxe cabinet and legs, all necessary parts and detailed assembly MODEL KT-236AWX Net 59.50


THE AMAZING "STEREO 236" KIT

A NEW LOW-COST STEREO AMPLIFIER ANYONE CAN BUILD




Easy to Build!

Anyone can build these superb Lafayette stereo kits—no special skill is needed. Assembly manuals contain clearly-worded step-by-step instructions which guide you all the way. Large full-scale pictorials illustrate every stage of assembly—show you exactly where every part goes. Join the thousands who have already discovered this easy low-cost way of owning the finest audio equipment.



Deluxe Stereo Controls

- 1 3-position Selector switch
- 2 Dual concentric Bass control
- 3 Dual concentric Treble control
- 4 Concentric clutch-operated Volume control
- 5 Unique "Blend" control
- 6 Phase reverse switch
- 7 Mode switches



DO-IT-YOURSELF and SAVE with LAFAYETTE HI-FI STEREO KIT SYSTEMS

BUILD THIS 36-WATT STEREO KIT SYSTEM

COMPONENTS

Lafayette KT-236A 36 Watt Stereo Amplifier Kit	59.50
Lesa CD2/21 4-Speed Stereo Record Changer (less base)	44.50
Base for Record Changer (Specify Finish)	4.50
Audio Empire S108 Diamond Needle Stereo Cartridge	35.00
2 Lafayette SK-128 8" Ultra-Linear Bixial Speakers @ 19.50	39.00
Regular Catalog Price	182.00

ONLY 142.50

YOU SAVE 40.00

CHOICE OF ONE

AUDIO EMPIRE S108	SHURE M7D
PICKERING 380C	GE VR1000-7

OPTIONAL

LESAs CD 2/21
CHANGER BASE
SK-128W SPEAKERS

KT-650
KT-650 FM TUNER

CHOICE OF ONE

AUDIO EMPIRE S108	SHURE M7D
PICKERING 380C	GE VR1000-7

OPTIONAL

GLASER-STEERS GS-77
SK-58 SPEAKERS

Deluxe 50-WATT DO-IT-YOURSELF STEREO KIT SYSTEM

MATCHED COMPONENTS

Lafayette KT-250A 50 Watt Stereo Amplifier	74.50
Glaser-Steers GS-77 4-Speed Record Changer (less base)	59.50
Base for Changer (Specify Finish)	3.95
Audio Empire S108 Diamond Stereo Cartridge	35.00
2-Lafayette SK-58 12" Coaxial Speakers @ 29.50	59.00
REGULAR CATALOG PRICE	231.95

ONLY 184.75

YOU SAVE 47.20

LAFAYETTE MATCHED 36-WATT STEREO KIT SYSTEMS

*Be sure to Specify Choice of Audio Empire S108, Pickering 380C, Shure M7D or GE VR-1000-7 Diamond Needle Cartridges.

System	Amp. Kit	Changer	Cartridge*	Changer Base†	Speakers	Spkr. Cabinet	Shpg. Wt.	Net
LSK-231WX	KT-236A	Lesa CD2/21	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-128	—	50 lbs.	142.50
LSK-232WX	KT-236A	Garrard Autoslym	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-128	—	48 lbs.	142.50
LSK-233WX	KT-236A	Lesa CD2/21	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-128	2 Mini-Duct†	93 lbs.	185.50
LSK-234WX	KT-236A	Garrard Autoslym	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-128	2 Mini-Duct†	91 lbs.	185.50
LSK-235WX	KT-236A	Lesa CD2/21	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	—	61 lbs.	162.50
LSK-236WX	KT-236A	Garrard Autoslym	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	—	61 lbs.	162.50
LSK-237WX	KT-236A	Lesa CD2/21	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	2 CK-14	109 lbs.	203.50
LSK-238WX	KT-236A	Garrard Autoslym	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	2 CK-14	107 lbs.	203.50
LSK-239WX	KT-236A	Lesa CD2/21	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-128	KT-650	64 lbs.	192.00
LSK-240WX	KT-236A	Garrard Autoslym	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-128	KT-650	62 lbs.	192.00

"MINI-DUCT" ENCLOSURES

"ELIPTOFLEX" ENCLOSURES

ALTERNATES

SK-180
SK-58 SPEAKERS
GARRARD AUTOSLYM
GARRARD AT-6

LAFAYETTE MATCHED 50-WATT STEREO KIT SYSTEMS

*Be Sure to Specify Choice of Audio Empire S108, Pickering 380C, Shure M7D or GE VR-1000-7 Stereo Cartridges.

System	Amp. Kit	Changer	Cartridge*	Changer Base†	Speakers	Spkr. Cabinet	Shpg. Wt.	Net
LSK-351WX	KT-250A	Glaser-Steers GS-77	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	—	80	184.75
LSK-352WX	KT-250A	Garrard AT6	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	—	80	184.75
LSK-353WX	KT-250A	Glaser-Steers GS-77	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	2 CK-14	128	225.75
LSK-354WX	KT-250A	Garrard AT-6	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-58	2 CK-14	128	225.75
LSK-355WX	KT-250A	Glaser-Steers GS-77	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-180	—	74	188.75
LSK-356WX	KT-250A	Garrard AT-6	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-180	—	74	188.75
LSK-357WX	KT-250A	Glaser-Steers GS-77	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-180	2 CK-14	122	229.75
LSK-358WX	KT-250A	Garrard AT-6	Choice of Audio Empire S108, Pickering 380C, Shure M7D, GE VR-1000-7	Lesaf	2 SK-180	2 CK-14	122	229.75

Any of above systems with addition of Lafayette LT-700WX, Multiplex Stereo Tuner, add \$114.50 to system price. When ordering add T to prefix. Example: LSK-231WX system with LT-700WX tuner is ordered as LSKT-231WX.

†: Specify Mahogany, Walnut or Blonde Base. Mini-Duct: 8" Speaker Bookshelf Enclosure. CK-14: Eliptoflex 12" Speaker Enclosure Kit, Unfinished. KT-650: FM Tuner Kit.

Any system on this page with Shure M3D Diamond Stylus Stereo Cartridge in place of choice of above cartridges add \$18.50 to System Net Price.

Any of above systems with addition of Lafayette LT-700WX, Multiplex Stereo Tuner, add \$114.50 to system price. When ordering add T to prefix. Example: LSK-351WX system with LT-700WX tuner is ordered as LSKT-351WX.

†: Specify Mahogany, Walnut or Blonde Base. SK-180: "Trihelia" 10" 3-way speakers. AT-6: GARRARD 4-Speed Record Changer. CK-14: Eliptoflex Bookshelf Speaker Enclosure in Kit form, unfinished.

GARRARD • GLASER-STEERS • LESA.....

PICKERING 380C DIAMOND STEREO CARTRIDGE, SHURE M7D DIAMOND STEREO CARTRIDGE, GE VR-227 DIAMOND STEREO CARTRIDGE OR AUDIO EMPIRE S108 DIAMOND STEREO CARTRIDGE FOR ONLY . . .

1¢ SALE!

when you purchase any changer shown below



NEW! GARRARD AUTOSLIM AUTOMATIC INTERMIX CHANGER • 4 Speed
Wired for Stereo and Monaural
39.51
PLUS PICKERING, SHURE, GE OR AUDIO EMPIRE OR GE CARTRIDGE

An ultra-compact, automatic-manual changer at a remarkably low price. Only 6 1/4" overall height. Intermixes all records, i.e. records of different sizes can be stacked in any sequence. Separate manual and automatic controls—featuring Garrard's new center-changing mechanism. The Autoslim employs a new type of a turntable and a 4-pole shaded motor, achieving balance and quiet turning. Faun-colored unit plate with white trim. Dimensions: 1 1/4" left to right; 12 1/2" front to rear; 4 1/4" above top of motor-board, 2 3/4" below. For 100-130 VAC, 60 cycles. Imported from England.

- GR-168W Less cartridge. Shpg. wt., 9 lbs. Net 39.50
- Garrard "Autoslim" plus Pickering 380C Diamond Stereo Cartridge. PK-556W Shpg. wt., 9 lbs. Net 39.51
- Garrard "Autoslim" plus Empire 108 Diamond Stereo Cartridge. PK-557W Shpg. wt., 9 lbs. Net 39.51
- Garrard "Autoslim" plus Shure M7D Diamond Stereo Cartridge. PK-558W Shpg. wt., 9 lbs. Net 39.51
- Garrard "Autoslim" plus GE VR1000-7 Diamond Stereo Cartridge. PK-559W Shpg. wt., 9 lbs. Net 39.51



GARRARD RC88 "MARK II" RECORD CHANGER
Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE
ONLY 59.51

The Garrard RC88 is a deluxe auto-manual changer wired for stereo and monaural use. Plays all 4 speeds (16, 33 1/3, 45 and 78 RPM). An outstanding performer in an attractive style. Complete with line cord, pickup lead, plug-in shell, mounting hardware, standard and manual spindles, and 45 RPM adaptor. Shpg. wt., 16 lbs.

- GR-126W Garrard RC88 only. Net 59.50
- Garrard RC88 Changer PLUS Pickering 380C Diamond Stereo Cartridge. PK-526W Shpg. wt., 16 lbs. Net 59.51
- Garrard RC88 Changer PLUS Shure M7D Diamond Stereo Cartridge. PK-527W Shpg. wt., 16 lbs. Net 59.51
- Garrard RC88 Changer PLUS GE VR1000-7 Diamond Stereo Cartridge. PK-604W Shpg. wt., 16 lbs. Net 59.51
- GARRARD RC 88 PLUS Audio Empire S108 Diamond Stereo Cartridge. PK-547W. Net 59.51



LESA CD 2/21 AUTOMATIC CHANGER
Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE
only 44.51

Fully automatic jam-proof Lesa changer plays up to eight records of any size, with automatic intermix. Easy to operate—only two controls for all cycles, speed selection, start, stop and reject. Shpg. wt., 17 lbs. G-195W Lesa changer, less base & cartridge. Net 44.50

- LESA CD 2/21 PLUS Pickering 380C Diamond Stereo Cartridge. PK-506W Shpg. wt., 17 lbs. Net 44.51
- LESA CD 2/21 PLUS Audio Empire S-108 Diamond Stereo Cartridge. PK-507W Shpg. wt., 17 lbs. Net 44.51
- LESA CD 2/21 PLUS GE VR1000-7 Diamond Stereo Cartridge. PK-562W Shpg. wt., 17 lbs. Net 44.51
- LESA CD 2/21 PLUS SHURE M7D Diamond Stereo Cartridge. PK-538W Shpg. wt., 17 lbs. Net 44.51
- GR-197 Automatic 45 RPM Spindle. Net 3.75
- Base for changer—specify mahogany or blonde. GR-196W Shpg. wt., 3 lbs. Net 4.75



GARRARD MODEL "A" AUTOMATIC TURNTABLE
Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE
ONLY 79.51

The Garrard Model "A" is a precision turntable and tone arm with the convenience of automatic record changing. Plays all 4 speeds and is wired for stereo and monaural use. Features a built-in stylus pressure gauge. Complete with line cord, pick-up leads, plug-in shell, mounting hardware, standard and manual spindles, 45 RPM adaptor. Shpg. wt., 19 lbs.

- GR-166WX Garrard Model "A". Net 79.50
- Garrard Model "A" plus Pickering 380C Diamond Stereo Cartridge. PK-523WX Shpg. wt., 19 lbs. Net 79.51
- Garrard Model "A" plus Shure M7D Diamond Stereo Cartridge. PK-524WX Shpg. wt., 19 lbs. Net 79.51
- Garrard Model "A" plus GE VR1000-7 Diamond Stereo Cartridge. PK-551WX Shpg. wt., 19 lbs. Net 79.51
- GARRARD Model "A" plus Audio Empire S108 Diamond Stereo Cartridge. PK-548WX. Net 79.51



GLASER-STEERS GS-77 RECORD CHANGER
Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE
ONLY 59.51

Fully automatic, 4-speed stereo record changer. Transcription-type tone arm; inaudible wow, rumble and flutter. 4 pole motor. Shpg. wt., 13 lbs.

- GR-50W Changer only, less base, cart. Net 59.50
- GS-77 PLUS PICKERING 380C Diamond Stereo Cartridge, less base. PK-540W Shpg. wt., 13 lbs. Net 59.51
- GS-77 PLUS Shure M7D Diamond Stereo Cartridge, less base. PK-541W Shpg. wt., 13 lbs. Net 59.51
- GS-77 PLUS GE VR1000-7 Diamond Stereo Cartridge, less base. PK-564W Shpg. wt., 13 lbs. Net 59.51
- GS-77 plus Audio Empire S108 Diamond Stereo Cartridge. PK-550W. Net 59.51
- Wood base for changer. Ebony with gold trim. Shpg. wt., 5 lbs. Net 9.60
- PK-352 Automatic 45 RPM Spindle. Shpg. wt., 1 1/2 lbs. Net 2.95



GLASER-STEERS GS-400 STEREO RECORD CHANGER
Plus PICKERING, SHURE, GE OR AUDIO EMPIRE CARTRIDGE
47.51

Glaser-Steers 4-speed stereo record changer with automatic intermix; acoustically isolated and dynamically balanced transcription type tone arm; idler automatically disengaged in off position.

- GR-52W Changer only, less base. Net 47.50
- GLASER STEERS GS-400 PLUS Pickering 380C Diamond Stereo Cartridge. PK-471W Shpg. wt., 14 lbs. Net 47.51
- GLASER STEERS GS-400 PLUS Audio Empire S108 Diamond Stereo Cartridge. PK-472W Shpg. wt., 14 lbs. Net 47.51
- GLASER STEERS GS-400 PLUS Shure M7D Diamond Stereo Cartridge. PK-545W Shpg. wt., 14 lbs. Net 47.51
- GLASER STEERS GS-400 PLUS GE VR1000-7 Diamond Stereo Cartridge. PK-563W Shpg. wt., 14 lbs. Net 47.51
- PK-473W Black wood base for GS-400 changer. Net 5.90
- PK-352 Automatic 45 rpm spindle, 1 1/2 lbs. Net 2.95

PICKERING 380C stereo cartridge with .7 mil diamond stylus with exclusive "V-Guard."
Shpg. wt., 5 oz. Net 29.85
GD-214L

SHURE M7D moving magnet stereo cartridge with .7 mil diamond stylus. Shpg. wt., 5 oz. Net 23.52
GD-273L

GE VR1000-7 magnetic, variable reluctance cartridge with .7 mil diamond stylus. Shpg. wt., 6 oz. Net 24.45
GD-144L

AUDIO EMPIRE S108 stereo cartridge with .7 mil diamond stylus. Shpg. wt., 7 oz. Net 35.00
GD-315L

NEW!



LAFAYETTE AUTOMATIC 4-SPEED RECORD CHANGER

LESS BASE
ONLY 22.35
NO MONEY DOWN

MADE IN U.S.A.

- Quality Ronette Ceramic Cartridge • Automatic 3-Way Shut-Off
- Intermixes Records of Same Speed • Heavy Duty-Constant Speed Motor
- Plays Stereo, LP and 78 RPM

Feature for Feature, the Lafayette automatic record changer matches or exceeds costlier units. Built for compatibility with both stereophonic and monaural records, this changer offers superior performance for budget-sparing music systems. The balanced featherweight tone arm operates at only 5-7 grams of needle pressure to minimize record wear. Flip-Track, Ronette ceramic stereo cartridge is unaffected by heat and humidity. Heavy precision-balanced turntable and constant speed motor insure smooth rotation without hum rumble or "wow". Plays all 4 record speeds—automatically changes up to fourteen 7", twelve 10" or 12" records. Intermixes 10" and 12" records of same speed. Plays records manually if desired. 45 r.p.m. spindle optional. Automatic 3-way shut-off after last record (returns tone arm to rest, stops

turntable motor, turns set off.) neutral position disengages turntable drive wheel when not in use—prevents rumble producing flat spots. 117 volts AC, 60 cycles. Compact and exceptionally functional, only 13 1/2 x 12 x 7 1/2". 3" below and 5 1/2" above mounting board. Beautiful brown and gold finish. Shpg. wt., 12 lbs.

- PK-605W No Money Down. Net 22.35
- PK-606W Walnut Base. Net 4.50
- PK-607W Mahogany Base. Net 3.95
- PK-608W Mounting Board. Net 1.10
- PK-609 45 R.P.M. Spindle. Net 1.49

LAFAYETTE VISCOUS-DAMPED STEREO TONE ARM

—THE PROFESSIONAL 12" PK-90S

7.95



- JEWEL BEARING SUPPORT • INSTANT PLUG-IN CARTRIDGE CHANGE
- AUTOMATIC FLUID CONTROL • PERFECT RECORD TRACKING
- ACCOMMODATES MOST STEREO & MONAURAL HIGH FIDELITY CARTRIDGES

This Stereo/Monaural transcription arm assures dependable and stable operation, utilizing the floating-action principle of viscous-damping. The arm is supported at a single point by a pivot and jewel bearing having negligible friction. Damping is accomplished by a silicone fluid occupying the gap between a ball and socket. This damping control permits high compliance and negligible tracking error and prevents damage to either record or stylus should the tone arm be accidentally dropped. Low frequency resonance, skidding and groove-jumping are likewise minimized. The tone arm accepts all records up to 12" and accommodates virtually all Stereo or Monaural hi-fi cartridges by means of precisely engineered adapters which simplify installation and provide proper stylus pressure. The arm has a decorative glossy-black finish. Overall length is 12"; height adjustable from 3/4" to 2 1/4" above motorboard; round mounting base is 2 3/8" in diameter. Shpg. wt., 2 1/2 lbs. PK-90S—12" Viscous-Damped Stereo Tone Arm. Net 7.95

4 SPEED TRANSCRIPTION TURNTABLE and TONE ARM

LESS BASE



49.50

NO MONEY DOWN

- 3 lb. Balanced 12" Aluminum Turntable
- Rumble and Noise Better Than —50 db
- Speed Control Provides ± 7% Variation of Each Speed • Wow & Flutter Below 2%
- Precision Lightweight 12" Aluminum Tone-Arm • Plug-In Shell For Popular Stereo Cartridges • Adjustable Counterbalance Weight • Perfect Tracking Even at 2 Grams • Automatic On-Off Switch Built Into Tone Arm Rest • Perfect For Both Stereo and Monaural

Features a heavy duty 4 pole induction motor, free-floating and shock mounted to virtually eliminate vibration. 12" aluminum table constructed with a permanently lubricated oilite bronze bearing. Speeds—16 2/3, 33 1/3, 45 and 78 rpm. ("off" positions between all positions). Oversize idler disengages in off positions. Stylus force adjustment accomplished by rotating Knurled Knob. Ball bearing suspensions result in a high compliance lateral, vertical movement. With stroboscope disc, 45 rpm adaptor, shielded hook-up cables and AC line cord. Motor plate is spring suspended and measures 16 1/4 x 12 1/2", requires 4" below motor board. For 105-120 volts 60 cycles AC. Shpg. wt., 15 lbs. PK-449WX Less Base. Net 49.50

- Extra plug in cartridge shell with mounting hardware for PK-449. PK-499 Shpg. wt., 1 lb. Net 1.69
- WOOD BASE PK-449WX. Finest selected hardwood veneers. Mitered corners, 3/4" sides, 1/2" top. For turntable and 12" arm. Size 17 1/2 x 13 1/2 x 3 3/8" H. Specify: mahogany, walnut or blonde finish. PK-504W Shpg. wt., 5 lbs. Net 9.95

- SPECIAL LAFAYETTE COMBINATIONS**
- Save \$21.50—PK-449 Turntable and Arm with Empire S-108 Stereo Cartridge. Individually priced total \$84.50. Net 63.00 PK-516WX
 - Save \$19.85—PK-449 Turntable and Arm with Pickering 380C Stereo Cartridge. Individually priced total \$79.35. Net 59.50 PK-517WX

LAFAYETTE COMPLETE STEREO TRANSCRIPTION PLAYER

26.95 NO MONEY DOWN!

LESS BASE



- 5-CONTACT PLUG IN HEAD FOR ALL STEREO CARTRIDGES • 4-SPEED HEAVY DUTY 4-POLE TRANSCRIPTION TYPE INDUCTION MOTOR • MAGNETIC BRAKE FOR ± 7% SPEED ADJUSTMENT • STYLUS WEIGHT ADJUSTMENT SCREW ON TONE ARM • RUMBLE AND NOISE —40 DB
- LESS THAN 0.3% WOW

Features a 5-contact plug-in head to accommodate stereo as well as monaural cartridges. The lightweight tone arm is an integral part of the mounting plate and requires no installation. New 4-speed turntable assembly is equipped with a quiet, heavy duty 4-pole motor, with an exclusive magnetic brake. Stroboscope disc also included. 10" heavy turntable, fitted with rubber mat. Dimensions of mounting plate 12 3/4" left to right, and 10 7/8" front to rear. Requires 2 3/4" below and 3" above motor board. For 105-120V, 60 cps. Accessories: 45 rpm adaptor, output cable to amplifier and plug-in heads. Shpg. wt., 14 lbs. PK-160SW Complete stereo transcription player, less cartridge. Net 26.95

- PK-438W Same as above, but with new GE Model VR-225 compatible stereo cartridge with diamond stylus. Net 36.95
- PK-162W Wood base for above, finished in mahogany or blonde (Please Specify). Shpg. wt., 5 lbs. Net 3.95
- PK-163W Unfinished mounting board for above. Strong durable 3/4" gumwood. (Shpg. wt., 1 lb.) Net .95

LAFAYETTE PANASONIC

PERFECT BALANCE—TURNTABLE WILL TRACK RECORDS EVEN AT ANGLES IN EXCESS OF 45°



SALE PRICE 19.95 REG. 32.50

- Distortion Free From 20-16,000 cps • Flat Frequency Response 20-15,000 cps • Feather Light Stylus Pressure—Individually Adjusted For 3-Grams • Hum Free—Entire Arm & Cartridge Case Shielded with Mu Metal

Tone arm resonance is minimized by use of specially designed counter weight, sub weight and lateral damping mechanism. The arm counter balance is floated on a damped suspension bar. Precision bearings assure minimum lateral and vertical friction. Overall height of arm adjusts from 1 1/4" to 2 1/4". Signal to noise level of well over 100 db. Stylus replacement requires only a few seconds, pull out the old stylus and plug in the new. The diamond stylus is capable of supplying up to 2,000 hours of playing time. With .7 mil diamond stylus, mounting instructions, stylus cleaning brush, all hardware. Shpg. wt., 3 lbs. PK-448. Net 19.95

- Complete .7 Mil Diamond Stylus Assembly for PK-448 Lafayette Panasonic Tone Arm. Shpg. wt., 1/4 lb. PK-452. Net 7.95

TECHNICAL INFORMATION

Output Voltage . . . 5 millivolts • Channel Separation . . . More than 25 db • S/N Level . . . Over 100 db • Compliance . . . 5x10—6 cm/dyne • Suggested Load Impedance . . . 50,000 ohms • D. C. Resistance . . . 420 ohms • Tracking Force . . . 3 grams • Stylus . . . 7 mil • Frequency Response . . . Distortion free: 20-16,000 cps Flat. ± 2 db 20-15,000 cps • Overall Length . . . 11 1/2"

EICO HI-FI KITS LAFAYETTE



NEW! MODEL MX-99 FM MULTIPLEX ADAPTER

The EICO MX-99 is a self-powered multiplex adapter. It is free of phase-distorting filters and meets or exceeds the required suppression of all spurious signals including the SCA (67KC) background music carrier, reinserted (38KC) sub-carrier, the (19KC) pilot carrier and all harmonics thereof. This factor is very important for high quality stereo tape recording. This adapter will synchronize with any usable output from the FM tuner. Provides automatic stereo-monophonic operation and includes low impedance cathode follower outputs. An indicator lamp turns on when a station is broadcasting multiplex stereo. It can achieve channel separation of 35db. The MX-99 is designed for all EICO FM equipment (HFT-90, HFT-92, ST-96), and any other component quality ratio detector FM tuners provided with a multiplex output. Size: 9 1/4" x 6 3/4" x 3 1/4" H. Shpg. wt., 7 lbs.

G-442 Kit Net 39.95
G-443 Factory wired and tested Net 64.95

EICO MODEL HFT 90K FM TUNER KIT

factory pre-wired and pre-aligned front end. Pre-wired tuning eye assembly. Temperature-compensated components. "traveling" tuning indicator, fly-wheel tuning and AGC. SENSITIVITY: 1.5 uv for 20 db quieting; 2.5 uv for 30db quieting; full limiting from 25 uv INPUT: 300 ohm balanced. OUTPUTS: Cathode follower and multiplier. TUBES: 1-ECC85/6A08, 3-6AV6, 1-6AL5, 1-6CA4, 1-6X4, 1-DM70. HUM: 60db below 1 volt. POWER: 40 watts at 110-120 volts AC, 50-60 cycles. Complete with instructions. 12x8 1/2 x 3 1/4". Shpg. wt., 10 lbs.

G-422 Kit Net 39.95
HFT-90 Same as above, but factory wired Net 65.95
E-3 Cover for HFT-90 Shpg. wt., 3 lbs. Net 3.95
G-431

EICO ST-96K FM-AM STEREO TUNER KIT

features pre-wired, pre-aligned FM front end, FM and AM IF strips. SPECIFICATIONS: SENSITIVITY: (FM) 1.5 uv for 20 db quieting; (AM) 3uv for 1.0V average output at 20 db S/N ratio. SELECTIVITY: (FM) 250 Kc. IF bandwidth (6db down); (AM) overall IF bandwidth of 18KC at "broad bandwidth" 9KC at "narrow bandwidth." FREQUENCY RESPONSE: (FM) 20-15,000 cps \pm 1db; (AM) 20-9,000 cps on "wide bandwidth." 20-4500 cps on "narrow bandwidth." IMAGE REJECTION: (FM) 40db; (AM) 60db; HUM LEVEL: 60db down; DRIFT: (FM) less than 2 parts in 10,000 from cold start; (AM) negligible. OUTPUT LEVEL: (FM) 2.5v for 100% mod., (AM) 1.0v average. POWER REQUIREMENTS: 117 volts AC, 60 cps. 15 1/2 x 5 1/4". Shpg. wt., 19 lbs.

G-517WX Net 89.95
Model ST-96 Same as above, but factory wired. Net 129.95
G-516WX

EICO HIGH FIDELITY AM TUNER KIT HFT94K

The new HFT94K is a basic AM tuner kit designed for hi-fi applications. Features include: slide-rule dial, fly wheel tuning low inter-station noise, tuned RF stage, built-in ferrite loop antenna, pre-wired traveling eye indicator and pre-aligned RF & IF coils. SPECIFICATIONS: SENSITIVITY: 3uv at 30% mod. for 1v output. SELECTIVITY: (wideband) 14KC bandpass; (narrow band) 7KC bandpass. FREQUENCY RESPONSE: 20-9000 cps (wide), 20-5000 cps (narrow) OUTPUT: low impedance plate follower. Extra recording output. POWER REQUIREMENTS: 110-125 volts AC, 60 cps. 3 1/2 x 12 x 8 1/4". Shpg. wt., 12 lbs.

G-500 Net 39.95
HFT94 Same as above, but factory wired. Net 65.95
G-501

EICO MODEL HF85K STEREO DUAL PREAMP KIT

Self-powered preamp-control center offering complete switching and control facilities for any stereo program source. SPECIFICATIONS (both channels): Frequency response 5-200,000 cps \pm 0.3 db; IM distortion (60 & 7000 cps) 0.3% @ 1 v. RMS output; Harmonic distortion (20-20,000 cps) .1% @ 3 v. RMS output; Tone-control range \pm 15 db @ 50 and 10,000 cps; RIAA phono and NARTB tape head (15, 7.5, and 3.75 ips) equalization; Output-to-main amplifier impedance, 8000 ohms. Tubes: 5-12AX7/ECC83's, 1-6X4. Size: 3 1/2" high, 12" wide, 8 1/4" deep. Shpg. wt., 10 lbs. Cover supplied.

HF85K Stereo Dual Preamp Kit. Net 39.95
HF85 Same, Factory wired and tested Net 64.95
G-493

EICO ST-40K 40-WATT STEREO INTEGRATED AMPLIFIER KIT



The ST-40 contains 2 twenty watt amplifiers and a complete stereophonic hi-fi control center on one chassis. FEATURES: Switched sets of stereo inputs including magnetic phono (2), tape head, preamplified tape, FM-AM stereo tuner, FM-FM Multiplex, and Auxiliary. Balance Check switch. Loudness/level switch. Bass and treble controls. Other controls include: Six position mode selector, tape monitor, scratch and rumble. Output 4, 8, and 16 ohm. Third channel speaker connection. Specifications: IM distortion—2% at 40 watts; Harmonic Distortion—1/2% at 40 watts; Frequency response— \pm 1/2 db. 20-20,000 cps. Shpg. wt., 27 lbs.

G-520WX Net 79.95
Same as above, but wired. Net 129.95
G-521WX

EICO ST-70K 70 WATT STEREO INTEGRATED AMPLIFIER KIT



Consists of 2-35 watt amplifiers and a complete stereophonic hi-fi control center on one chassis. Stereo inputs in switched sets including: 2 magnetic phono (one for turntable, one for changer); tape head, preamplified tape, FM-AM stereo tuner, FM-FM Multiplex, and Auxiliary. Controls: Level with balance check switch and loudness/level switch; bass, treble, six-position mode selector, blend, tape speed, tape monitor, scratch, and rumble. Output: 4, 8, and 16 ohm speaker. Third channel output available. Specifications: IM distortion — 2% at 70-watts. Harmonic Distortion — 1/2% at 70 watts. Frequency response — \pm 1/2 db, 20-20,000 cps. Shpg. wt., 35 lbs.

G-518WX Net 94.95
As above, but factory wired. Net 149.95
G-519WX

EICO MODEL HF-81K STEREO DUAL AMPLIFIER- PRE-AMP KIT



3 inputs per channel: low level-mag phono, tape head and microphone. SPECIFICATIONS: OUTPUT POWER: rated 28 watts (continuous) for monaural, 14 watts for stereo. FREQUENCY RESPONSE: \pm 5 db, 10 to 100KC at 2 W out. IM DISTORTION: (60 and 6000 cps at 4:1): 0.5% at 10 watts out. HARMONIC DISTORTION: less than 1% from 40C-10KC at 20W output. SENSITIVITY: MAG PHONO: 4mv; TAPE HEAD: 2 mv; MIC: 6mv; TUNER AND AUXILIARY: 0.5v. HUM AND NOISE LEVEL (below 14W): -56 db. on low level, -75 db high level. OUTPUT: 4, 8, and 16 ohms. TUBE COMPLEMENT: 2-ECC82/12AU7, 4-EL84, 2-EZ31. POWER REQUIREMENTS: 115 volts AC, 50-60 cycles. 15x10 1/2 x 4 1/4". Shpg. wt., 24 lbs.

G-490WX Kit Net 69.95
HF-81 Same as above, but factory wired. Net 109.95
G-491WX

EICO MODEL HF 86K 28-WATT STEREO HI-FI DUAL POWER AMPLIFIER KIT



14 watts per channel. Williamson circuit with push-pull EL84 output stages. New type 12DW7 tubes for better performance of Williamson circuitry. SPECIFICATIONS: OUTPUT POWER: 28 watts continuous, 56 watts peak. FREQUENCY RESPONSE: \pm 0.5db 10c to 100KC. IM distortion: 0.5% at 10 watts (60 & 7000 cps at 4:1). HARMONIC DISTORTION: less than 1% at rated output. STABILITY MARGIN: 15db. HUM: 90db below rated output. SENSITIVITY: 1.15 V for 14W output. SPEAKER CONNECTIONS: 4, 8, 16, 32 ohms. TUBE COMPLEMENT: 2-12DW7, 4-EL84, 2-EZ81. POWER REQUIREMENTS: 115 watts at 117 volts AC, 50-60 cycles. 5x13 1/2 x 9". Shpg. wt., 16 lbs.


HF-86 Same as above, but factory wired. Net 43.95
G-495 Net 74.95

EICO MODEL HF-89K100-WATT STEREO DUAL AMPLIFIER KIT



A new ultra-linear dual 50-watt amplifier. SPECIFICATIONS: FREQUENCY RESPONSE: \pm 0.5db 5 cps—100KC. HARMONIC DISTORTION: less than 2.25% from 30 to 15,000 cps and less than 1% from 20-20,000 cps within 1 db of 100 watts. IM DISTORTION: 0.5% at 100 watts. CHANNEL SEPARATION: 60db. SENSITIVITY: 0.55V for full output. OUTPUTS: 4, 8, and 16 ohms. TUBE COMPLEMENT: 1-ECC83, 2-6SN7GTB, 4-EL34, 2 silicon diode rectifiers. Sargistor protected. POWER REQUIREMENTS: 215 watts at 117 volts AC, 60 cycles. 15x11x6". Shpg. wt., 37 1/2 lbs.

G-514WX HF-89 Kit Net 99.50
G-515WX HF-89 Wired Net 139.50
EICO E-8 enclosure for HF-89 Net 4.50
G-510W



NEW! EICO RP-100K TAPE DECK KIT

A new, precision stereo/monaural tape deck, the RP-100 provides stereo/mono 1/4 track erase, record, and playback, plus 1/2 track stereo/mono playback. Separate record and playback heads and preamps permit simultaneous stereo playback from tape while recording. Sound-on Sound recordings can be obtained without changing any connections. Features: Dual meters for monitoring stereo record levels and separate line and mic. (dynamic) mixing controls for each channel; SPECIFICATIONS: Tape speed—7 1/2 or 3 1/4 ips; up to 7" reel size; Flutter and Wow — 0.2% at 7 1/2 ips, 0.25% at 3 1/4 ips; Frequency response: 30-17,000 cps at 7 1/2 ips, 40-15,000 cps at 3 1/4 ips; Signal-to-Noise ratio — 53 db or better. Timing accuracy — 0.3%. Dimensions: 15 1/4" wide, 13 3/4" front-to-back, 7" deep. Shpg. wt., 28 lbs.

RP-100K semikit includes transport completely assembled and tested with 3 heads; stereo record, and stereo playback preamps in kit form. Net 299.95
RK-275WX Net 299.95
RP-100W wired and tested with 3 heads, stereo record, playback preamplifiers. Net 399.95
RK-276WX Net 399.95
Model CC-2 Luggage Type Carrying Case with detachable cover. Permits horizontal or vertical operation of deck. Shpg. wt., 13 lbs. Net 29.95
RK-277W

EICO TRANSISTOR RECEIVER KIT MODEL RA6-K



Here is a modern, 6-transistor portable—easy to build at remarkably little cost. Provides high sensitivity, selectivity, undistorted sound output. Features include: built in Ferrite loop antenna, pre-aligned RF and IF transformers, 4x6" oval PM speaker, vernier tuning, earphone jack. No test instruments needed. In simulated tan leather case with retractable handle. Size 8 1/2 x 4 1/2 x 2 1/2" D. Shpg. wt., 3 lbs. Requires battery (not included).

G-410 Kit Net 29.95
G-411 Factory wired Net 49.95
BA-180 Battery (NEDA 1602) wt., 5 oz. Net 1.30

EICO MODEL HF-32K HI-FI INTEGRATED AMPLIFIER KIT



An extremely versatile 30-watt pre-amp amplifier combination at a reasonable price. The HF32K combines a highly stable, wide frequency range power amplifier with a multi-use preamp. 3 low level inputs for magnetic phono, tape head, and microphone. 3 high level inputs for TV or Tuner, crystal or ceramic cartridge, or tape. Features: Frequency response — \pm 0.5 db, 15-50,000 cps; Output to match 4, 8 and 16 ohms; IM Distortion — 2% at 30 watts; Harmonic Distortion—Below 1%, 20-20,000 cps 1 db. below 30 watts; Sensitivity—(input for rated output) Mag. Phono—5 mv, Tape Head—2 mv, Microphone—4 mv, High Level—2 mv; Power output 30 watts continuous. For 117 volts, 60 cps AC. Size 15x4 1/2 x 10 1/2". Shpg. wt., 28 lbs.

G-420WX Net 57.95
HF32 Same as above, but factory wired. Net 89.95
G-421WX

EICO MODEL HF87K 70-WATT STEREO HIGH FIDELITY DUAL POWER AMPLIFIER KIT



A dual amplifier, this unit provides 35 watts output per channel. Ultra-linear connected, self-biased, push pull EL34 output stages for high stability. SPECIFICATIONS: OUTPUT: 70 watts continuous, 140 watts peak. FREQUENCY RESPONSE: \pm 0.5 db 5 cps—100KC. HARMONIC DISTORTION: less than 1%. From 20 to 20,000 cps within 1 db at 70 watts. DAMPING FACTOR: above 11. STABILITY MARGIN: 17 db. SENSITIVITY: 0.38V for full output. CHANNEL SEPARATION: 55 db. SPEAKER CONNECTIONS: 4, 8, 16, 32 ohms. TUBE COMPLEMENT: 1-ECC83/12AX7, 2-6SN7GTB, 4-EL34, 2 silicon diode rectifiers. POWER REQUIREMENTS: 215 watts at 117 volts AC, 60 cps. 15x11x6". Shpg. wt., 32 lbs.

G-496WX Kit Net 74.95
HF87 Same as above, but factory wired. Net 114.95
G-497WX

EICO 20-WATT HIGH FIDELITY AMPLIFIER KIT MODEL HF20K



High quality equalizer and control section plus 20 watt Ultra-Linear Williamson-type power amplifier. Low distortion feed-back equalization; 5 equalizations provided for LP's and 78's including RIAA. Variable turnover, low distortion feed-back tone controls. Six inputs: 4 high level switched inputs and 2 low level inputs (not switched). Hum balance control for balancing out 60 cycle residual hum. Power Consumption: 110-120 volts, 60 cps, 100 watts. Tubes: 2-12AX7, 2-12AU7A, 2-6L6GB, 1-5U4GB. Handsomely styled to eliminate the necessity for cabinets. Size: 8 1/2" H, 15" W, 10" D. Shpg. wt., 24 lbs.

G-502WX HF-20—Kit Net 49.95
G-503WX Factory Wired Net 79.95
G-428W ENCLOSURE FOR HF20 Net 4.50

• BUILD YOUR OWN HI-FI KITS •

10 WATT PUSH PULL HI-FI AMPLIFIER KIT


• BUILT-IN PREAMPLIFIER • SELECTOR SWITCHES PERMIT CHOICE OF THREE INPUTS • SEPARATE BASS AND TREBLE CONTROLS • 4, 8 AND 16 OHM OUTPUTS • EASY-TO-FOLLOW INSTRUCTIONS

This new, economy hi-fi amplifier has many deluxe features for exceptional performance. The three inputs are radio/crystal phono pickup, magnetic phono pickup and microphone. A selector switches the input from radio/crystal to microphone or magnetic pickup, depending upon the position of a rear apron slide switch. OUTPUT — Rated 10 watts, peak 18. FREQUENCY RESPONSE — \pm 1 db 30-15,000 cps. DISTORTION — 1.5% harmonic, 4% intermodulation at 8 watts. 4 CONTROLS — Input Selector; Volume; Treble; Power-On-Off-Bass. TREBLE CONTROL — Flat response up to 18 db cut.—BASS CONTROL — Flat response up to 15 db boost. OUTPUT IMPEOANCES — 4, 8 and 16 ohms. TUBES — 6SC7, 6SL7GT, 2-6V6GT and 5Y3GT rectifier. AUXILIARY AC OUTLET — Distinctive Hammer-tone finish. SIZE — 10 1/2 x 6 1/4 x 5 1/4". WEIGHT — 8 1/2 lbs. For 110-120 Volts. Complete kit with coded wire, highest grade solder and detailed instruction manual. Net 24.50
KT-91

MONAURAL HI-FI PHONO SYSTEM KIT

Have FUN — SAVE MONEY by assembling this top-value system yourself! Features Lafayette KT-91 10-watt amplifier kit; famous Telefunken 4 speed automatic record changer with intermixing, jam proof operation, and automatic shut off features, crystal turnover cartridge with dual sapphire stylus for stereo and monaural records, and 45 rpm automatic spindle adapter plus amazing Lafayette SK-124 Ultra-Compliance 2 way speaker system in mahogany or walnut (specify finish). Tuner can be added at any time for radio program reception. Less changer base. Shpg. wt., 34 lbs.

PK-600WX Net 62.50
PK-341W Mahogany base for changer Net 3.95
PK-342W Walnut base for changer Net 4.50
Unfinished mounting board cut for changer Net .95
PK-343W



LAFAYETTE KT-91 PUSH-PULL AMPLIFIER

10-WATT HI-FI AMPLIFIER KIT
24.50
NO MONEY DOWN



LAFAYETTE SK-124 ULTRA-COMPLIANCE SPEAKER SYSTEM



TELEFUNKEN AUTOMATIC RECORD CHANGER

NEW! JUST OUT

H.H. SCOTT

LM-35 MULTIPLEX ADAPTER KIT

The LM-35, as with all Scott kits uses unique kit pack which functions as a fold-away work bench. All wires are pre-cut to correct length Multiplex circuitry pre-wired and pre-aligned at factory. Self-powered (all connections to the tuner are external). The LM-35 can be used with all H. H. Scott wide-band tuners regardless of age or model. Controls: Selector (off, Monophonic FM, Stereo with subcarrier noise filter, stereo without subcarrier noise filter). LEVEL: ADAPTOR DEFEAT; STEREO NOISE FILTER.

Matches H. H. Scott Tuners in height and styling. Dimensions in accessory case: 7 1/4" x 5 1/4" x 13" D. 105-120 V.A.C. 50/60 cycles. Full size instruction book. Shpg. wt., 8 lbs.

G-642WX LM-35K Net 79.95
Metal H Case For LM-35 Net 9.95
G-627W



169.50 NO MONEY DOWN

are pre-cut. The KX-200 amplifier/preamp specifications are: 80 watts IHFM music power output; (35 watts RMS each channel) Harmonic distortion (at rated output) 0.4%; IM Distortion (SMPT), at rated output 0.8%; Frequency response (overall) 20-20,000 cps (\pm 1 db)—total hum and noise (below rated output on high level inputs) 80 db (450mv rep); Channel Separation at 1 KC better than 50 db. Tubes: 6 ECC83, 4-7591, 2-5D95A, 2-5D91A. Built-in D'Arsonval calibration meter and level control for center channel speaker. For 117V, 60 cycles AC. Size: 15 1/2" x 12 1/2" x 4 1/2" H. Shpg. wt., 30 lbs.

G-666WX KX-200 Amplifier, less case Net 169.50
G-109W MC-2 Metal Cabinet for KX-200 9 lbs. Net 15.95

NEW! JUST OUT

THE FISHER KX-200 80 WATT STEREO CONTROL AMPLIFIER KIT

Fisher engineers have developed a new concept of kit design known as Stratakit, i.e., each stage of construction corresponds to a particular page in the instruction manual and to a separate packet of parts. Major components are pre-mounted and wires are pre-cut. The KX-200 amplifier/preamp specifications are: 80 watts IHFM music power output; (35 watts RMS each channel) Harmonic distortion (at rated output) 0.4%; IM Distortion (SMPT), at rated output 0.8%; Frequency response (overall) 20-20,000 cps (\pm 1 db)—total hum and noise (below rated output on high level inputs) 80 db (450mv rep); Channel Separation at 1 KC better than 50 db. Tubes: 6 ECC83, 4-7591, 2-5D95A, 2-5D91A. Built-in D'Arsonval calibration meter and level control for center channel speaker. For 117V, 60 cycles AC. Size: 15 1/2" x 12 1/2" x 4 1/2" H. Shpg. wt., 30 lbs.

G-666WX KX-200 Amplifier, less case Net 169.50
G-109W MC-2 Metal Cabinet for KX-200 9 lbs. Net 15.95

HI-FI TUNERS, AMPLIFIERS, SPEAKER SYSTEMS and TURNTABLE KITS



NEW!
FAIRCHILD 440
2-SPEED
TURNTABLE
KIT OR
Wired

55.00

A new high fidelity turntable kit. 2-speed operation (33 1/3 and 45 rpm), single belt drive, Speed Sentinel control varies turntable speed $\pm 1\frac{1}{2}\%$, highly styled and precision turntable platter. Entire assembly supplied on a channel for easy mounting. Rotational speed controlled from top. Strobe disc included to determine correct speed. Size: 19x16x10". Complete with unfinished mounting board, but less base, 19x16". For 110V, 60 cycle AC. Requires 1 1/4" clearance above turntable, 3/2" below. GR-276W Shpg. wt., 21 lbs. Net 55.00
Same as above but completely wired and assembled. GR-274WX Net 69.95
MODEL 440CBW. Base for above. Includes walnut mounting board, walnut wraparound. 19x16x8". Shpg. wt., 12 lbs. Net 19.95



REK-O-KUT
MOEEL
K-33H
TURNTABLE
KIT
59.95

A new belt driven 33 1/3 rpm turntable in single kit form—takes approximately 30 minutes or less to assemble with simple tools. Has a high efficiency hysteresis synchronous motor. Uses a crown-spindle belt drive with adjustable tension to prevent noise transfer from motor. Noise level is 52 db below average recording level. Turntable disc is solid aluminum-lathe turned and tapered for easy disc handling. Built-in strobe disc; ribbed rubber turntable mat. Minimum dimensions for cabinet installation, using Rek-O-Kut S-120 arm: 17 1/2"x16 1/2". Height above deck —3"; Height below—4". Finished in silver tone aluminum. For 110-120 volts, 60 cycles AC. Shpg. wt., 18 lbs. GR-241WX Net 59.95
GR-242WX Same as above, but for 110-120 volts, 50 cycle AC. Net 69.95

REK-O-KUT 2 SPEED TURNTABLE KIT
K-34H TWO SPEED STEREO TABLE KIT. The same high quality and performance of the K-33H (described above) but with two speeds. Motor: Lifetime lubricated hysteresis—synchronous. Speeds: 33 1/3 and 45 RPM. Noise Level: 57 db. Wow and Flutter 0-15%. Chassis Deck: 12 1/2"x19". Shpg. wt., 17 lbs. GR-260WX Net 69.95
KB Walnut finish woodbase for K-34H turntable. GR-262W Shpg. wt., 8 lbs. Net 14.95

Electro-Voice **SPEAKER SYSTEM KITS**
The famous E-V Regal and Esquire Low Resonance Speaker Systems now available in completely engineered kits. All wood parts are pre-cut, with glue, screws and nails included. Complete with all speakers and components. Easy Step-by-Step instructions show you how to do-it-yourself.

REGAL 300 KIT
Achieve the same premium—quality performance of the factory assembled Regal 300 bookshelf speaker system by building this new kit. Response 35-18,000 cps. Birch exterior surfaces allow professional-like furniture finishes. Size: 22Hx31 1/2Wx11 1/4"D. Shpg. wt., 64 lbs. GB-82WX Net 122.50

ESQUIRE 200 KIT
The same fine extended bass response and performance of the factory assembled Esquire 200. Response 40-18,000 cps. Exterior surfaces of Birch provide a fine furniture finish. Size: 14Hx 23 1/2Wx12"D. Shpg. wt., 50 lbs. GB-81WX Net 91.14

Jensen 3-P/K SYSTEM KIT
• 5 Speakers
• 4-Way
97.50
Here is a speaker system kit which will provide 3-P performance in a home-built or separately bought cabinet. Includes the 5 speakers of the other 3-P systems, crossover network with H-F balance control and speaker leads, vent-tube for enclosure, and complete instructions. SPECIFICATIONS: Frequency Range: 20 cps to beyond audibility. Crossover: 600, 4,000, 10,000 cps. Speaker System Power Rating: 25 watts. Impedance 8 ohms. GS-312 Shpg. wt., 21 lbs. Net 97.50
Note: This is an integrated system, and components must be used only with each other.

Jensen KTF-3 SPEAKER KIT
57.75
Provides the necessary speaker components for TF-3 performance in a home-built or separately bought cabinet. Kit includes the woofer, two midrange units and tweeter of the TF-3 system. Includes M-F/H-F balance control, crossover network, wiring cable, enclosure vent tube and full instructions for enclosure construction. SPECIFICATIONS: Frequency Range: 25 cps to beyond audibility. Crossovers: 2,000 and 10,000 cps. Speaker System Power Rating: 25 watts. Impedance 8 ohms. GS-313 Shpg. wt., 11 1/2 lbs. Net 57.75

dynakit High-Fidelity Components

DYNATUNER FM-1 KIT
The Dynakit FM-1 tuner utilizes complete printed circuit design. Can be completely aligned without the need for auxiliary equipment or instruments—using only the built-in tuner indicator. Designed for maximum linearity and stability of operation—yet has high sensitivity. Tuned RF input provides 4 microvolt (IHFM) sensitivity and excellent rejection of spurious signals. IM DISTORTION: less than 0.25%. OUTPUT LEVEL: 1 1/2 volts. 7 tubes plus rectifier, tuning eye and 2 diodes. POWER REQUIREMENTS: 110-120V. AC, 60 cps. 13x4x8". Shpg. wt., 11 lbs. Net 79.95
G-467WX Model FM-1 wired and factory tested. Shpg. wt., 11 lbs. Net 119.95
New Model FM-1 SK . . . Same as FM-1, in semi-kit form. Shpg. wt., 11 lbs. Net 99.95
G-470WX

NEW FMX-3 MULTIPLEX ADAPTER KIT
The FMX-3 fits inside the chassis of the FM-1. Permits stereo reception of multiplex broadcasts. Shpg. wt., 2 lbs. Net 29.95
G-471 Model FMA-2 kit — 10 watt amp. converts FM-1 to FM radio (less speaker). Uses space allocated for multiplex adapter. Shpg. wt., 4 lbs. Net 29.95
G-472

DYNAKIT PAM-1 PREAMPLIFIER KIT
A quality preamp-control unit, incorporating a factory-wired printed circuit module. Current and voltage feedback loops include four stages of gain. Inputs: Low-level magnetic cartridge, high level magnetic, radio, TV, tape, plus "special" low level (option of extra RIAA phono input, tape head, or mike). Outputs: Tape and audio output. IM Distortion: Less than .05%. Response: ± 0.5 db 6-60,000 cps. Gain: 54 db @ 1000 cps (RIAA input). 20 db @ 20-20,000 cps (high-level input). Tubes: 2-ECC83/12AX7 plus selenium stack. Power requirements: 200-400 volts d.c. @ 3-4 ma; 6 volts A.C. @ .75 amps. Requires PS-1 (listed below) when used with other than Dynakit amplifiers. Size 2 1/2"Hx12Wx6"D. Shpg. wt., 7 lbs. Choice of bone white or charcoal brown vinyl finish.
G-465 Kit Net 34.95
G-466 As above, but wired Net 59.95
PM-1 Panel mounting kit for PAM-1. Shpg. wt., 2 lbs. Net 2.95
PS-1K Power supply kit. Powers either 1 or 2 PAM-1 preamplifiers. Shpg. wt., 4 lbs. Net 8.95
G-460 Net 14.95
G-461 PS-1, same as PS-1K but factory wired.

DYNAKIT PAS-2 STEREO PREAMPLIFIER KIT
Includes two independent high gain, low noise preamplifier-control channels. Inputs: 3 stereo low level and 4 stereo high level. Frequency response: ± 0.5 db 6-60,000 cps. Distortion: less than .05%. Noise: less than 3 uv. equivalent noise input on RIAA. Gain: 60 db at 1000 cps level. Tubes: 4-12AX7/ECC-83, 6X4, selenium rectifier. Textured vinyl finish. Size: 13x8x4". Shpg. wt., 11 lbs. Net 99.95
G-453WX Kit
Dynakit PAS-2 Stereo Preamp. Same as above, but completely wired. Shpg. wt., 11 lbs. Net 99.95
G-454WX
Model PM-3 Panel mounting kit for PAS-2. Shpg. wt., 3 lbs. Net 4.95
G-468

DYNAKIT STEREO 70 70-WATT STEREO AMPLIFIER KIT
The stereo 70 is rated at 35 watts channel or 70 watts for monophonic. Frequency response: ± 0.5 db 10-40,000 cps. IM distortion: less than 1% at 35 watts. Sensitivity: 1.3 volts rms input for 35 watts output. Output impedance: 4, 8, 16 ohms. Minimum channel separation: 55 db.
Vinyl coated charcoal brown cover. Size: 13x9 1/2x6 1/2". Shpg. wt., 32 lbs. Net 99.95
G-455WX Kit
Dynakit Stereo 70 Stereo Amplifier. Same as above, but completely wired. Net 129.95
G-456WX

DYNAKIT MARK IV 40 WATT POWER AMPLIFIER KIT
The Mark IV is a 40 watt basic amplifier. Power output: 40 watts continuous, 80 watts peak. Frequency response: ± 0.5 db 10-40,000 cps. IM distortion: less than 1% at 40 watts, less than .05% at 1 watt. Hum and noise: better than 90 db below 40 watts. Output impedance: 4, 8, 16 ohms. Sensitivity: 1.3 volts rms input for 40 watts output. Tubes: 2-EL-34, 7199, GZ-34, selenium rectifier. Finish with nickel chassis, and vinyl coated charcoal brown cover. Power consumption: 115 watts. Size: 5x14x6 1/2". Shpg. wt., 20 lbs. Net 59.95
G-449WX Kit
Mark IV 40 Watt Amplifier. Same as above, but completely wired. Shpg. wt., 20 lbs. Net 79.95
G-450WX

CITATION STEREO HIGH FIDELITY EQUIPMENT

HARMAN-KARDON CITATION I KIT Stereo Preamplifier Control Center
A high quality stereo-monaural preamp-control unit. Inputs: 12 (six pairs) — Aux, Tape Amp, Tuner, low-level phono, high-level phono. Outputs: 5-Two main preamp outputs plus a third channel output, two tape outputs for recording. Mode selector chooses output types: stereo, mono, stereo reverse. IM DISTORTION: Less than 0.05% at 2 volts. RESPONSE: ± 0.5 db 5-80,000 cps. Tubes: 9-ECC83/12AX7 plus silicon rect. POWER REQUIREMENTS: 110V AC, SIZE: 14 1/2"Wx12 1/4"Dx6"H. Shpg. wt., 20 lbs. Gold & Charcoal brown finish. Net 159.95
G-230WX Kit Net 249.95
G-231WX Wired Net 29.95
G-232W Walnut Enclosure

HARMAN-KARDON CITATION IV KIT STEREO PHONIC PREAMPLIFIER CONTROL CENTER
The Citation IV is a compact stereophonic preamplifier. FREQUENCY RESPONSE: $\pm 1/2$ db, 5-80,000 cps. DISTORTION: .05% at 2 volts. NOISE: 85 db below rated output (2v). SENSITIVITY: HI Level: 0.2v; LO Level: 2.5 mv in phono position. INPUTS: Aux, Tape Amp, tuner, Phono-TUBE COMPLEMENT: 6-ECC83/12AX7, 4-semiconductor rectifiers. POWER: 110-120 volts AC, 60 cps. 14 1/2"Wx11 1/2"H. Shpg. wt., 16 lbs. Net 119.95
G-367WX Citation IV Kit Net 189.95
G-368WX Citation IV Wired Net 29.95
Walnut Enclosure for Citation IV G-232W

NEW CITATION X SPEAKER SYSTEM
Unique cone design and mounting method blend direct and reflected sound to achieve a hemispheric radiation pattern. The result is depth and dimension—no ping-pong effect and no "hole-in-the-middle." Lowther driver has 7-lb. magnet, a midrange "whizzer" for 2000-7000 cps, and a stabilizer to place a damping load on the cone and diffuse and distribute the very highs. Hegeman enclosure is a split, slot-loaded conical horn. Mechanical resonances have been either eliminated or damped by careful design and choice of materials. Natural cone resonance below 30 cps. Cabinet comes pre-assembled and finished in hand-rubbed oiled walnut. Driver and grill cloth assembly come in separate package—assembly should take no more than 1/2 hour. 36 1/2" H x 20" W x 14 1/4" D. Shpg. wt., 48 lbs. Net 250.00
GB-410WX

HARMAN-KARDON CITATION II KIT 120 Watt Stereophonic Hi-Fi Power Amplifier
Two ultra-linear type amplifiers deliver 60 watts each channel or a total of 120 monaural. Frequency Response: 18-40,000 cps ± 0 to -1.0 db @ 60 watts, 2-80,000 cps ± 0 to -1.0 db @ 1 watt; IM Distortion: Less than .5% @ 60 watts, Harmonic Distortion: Less than 0.5%, 20-20,000 cps @ 60 watts, Output 4, 8, 16 ohms. Tubes: 6-12B7Z, 4-KT88, plus 4-Silicon Diodes & 1 Selenium rect. Dimensions: 16 1/2"Wx9Hx11 1/4"D. Charcoal Brown & Gold Finish. Shpg. wt., 60 lbs. Net 159.95
G-234WX Wired Net 229.95
G-235W Charcoal Brown Metal Enclosure Net 7.95

HARMAN-KARDON CITATION III KIT PROFESSIONAL FM TUNER KIT
The Citation III is a new, extremely sensitive tuner, utilizing the revolutionary new "Nuvistor" subminiature precision tube. Preassembled, factory-aligned Converter-IF subassembly. SENSITIVITY: 0.65 uv for 20 db quieting; 0.85 uv for 30 db quieting. IMAGE REJECTION: 65 db, FREQ. RESPONSE ± 0.5 db, 1-52,000 cps. ANTENNA IMPEDANCE: 300 ohms. DISTORTION: less than 0.1% at 100% mod. HUM: 65 db below 100% mod. OUTPUT LEVEL: 2v at 100% mod. OUTPUT IMPEDANCE: 1500 ohms. POWER: 110-120 volts AC, 60 cps. 14 1/2"Wx12 1/4"H. Shpg. wt., 24 lbs. Net 149.95
G-365WX Citation III Kit Net 229.95
G-366WX Citation III Wired Net 29.95
G-372W Walnut Enclosure for Citation III Net 89.95
G-373WX Citation III MA FM Stereo Adapter Wired Net 319.90
G-374WX Citation III X FM Stereo Tuner Wired Net 319.90
G-374WX Citation III X FM Stereo Tuner Wired

HARMAN-KARDON CITATION V KIT 80 WATT STEREO BASIC POWER AMPLIFIER
Conservatively rated at 40 watts/channel (continuous), 95 watts/channel (peak). HARMONIC DISTORTION: less than 0.5% at 40 watts. IM DISTORTION: Less than 0.5% at 40 watts. FREQUENCY RESPONSE: 7-45,000 cps ± 1.0 db at 40 watts, HUM AND NOISE: Better than 85 db below 40 watts. OUTPUT IMPEDANCE: 4, 8 and 16 ohms. TUBE COMPLEMENT: 2-12B7A, 2-6CG7, 4-7581 plus 4 silicon diodes and 1 selenium rectifier. POWER: 250 watts at 110-120 volts AC, 60 cps. 13 1/2"Wx5 1/2"x11 1/4". Shpg. wt., 40 lbs. Net 119.95
G-369WX Citation V Kit Net 179.95
G-370WX Citation V Wired Net 7.95
G-371W ACX Metal Cage for Citation V

H.H. SCOTT STEREO PHONIC HI-FI KITS

NEW MODEL LT-110 WIDE-BAND FM STEREO MULTIPLEX TUNER KIT
• First Kit With Built-In Multiplex
• Prealigned Multiplex Section
FM multiplex tuner in kit form. Both the multiplex section and silver plated front end are factory pre-assembled and prealigned. You need only align the tuner's wide-bandpass IF's and detector using the meter on the tuner itself. Special shielding protects against interaction of tuner and multiplex sections. Unique circuitry eliminates multiplex interference with bias oscillator of any stereo tape recorder. Features stereo Noise Filter, Vernier Tuning; Front panel tuning meter; and Stereo Tape recorder output. IHFM usable sensitivity 2.2 microvolts. 10 Tubes, 11 diodes. Shpg. wt., 20 lbs. 15 1/2"Wx5 1/4"Hx13 1/4"D. Net 159.95
G-633WX (less case) Net 12.95
Leatherette metal case C for LT-110. Shpg. wt., 5 lbs. Net 12.95
G-147W

MODEL LT-10 WIDEBAND FM TUNER KIT
The LT-10 meets the exacting standards of H. H. Scott factory units, yet you can align it without elaborate equipment. It uses the very same wideband design of H. H. Scott's factory units, and has the same silver-plated front end (preassembled and prealigned for you by the factory) as the 310D FM Broadcast Monitor Tuner. Usable Sensitivity 2.2 microvolts; Multiplex output permits use with Model 335 wideband Multiplex adaptor; the tuner's meter is used to align the tuner itself; 3 stages of I.F. and 2 full limiting stages with 2 MC detector bandwidth. Size: 13x4 1/2x9 1/4". Net 99.95
G-164WX (less case) Shpg. wt., 12 lbs. Net 99.95
Scott Leatherette Metal C case for LT-10. Net 12.95
G-147W

MODEL LK-72 72-WATT STEREO AMPLIFIER KIT
The LK-72 has the same output circuitry as the 299C wired stereo amplifier. Aluminum chassis and D.C. heated preamp filaments give low —80 db hum and noise. Frequency response 20 to 20KC ± 1 db; harmonic distortion at full output 0.8%. IM distortion 9.3% (CCIF); IHFM power bandwidth 21 to 20 KC; speaker output impedances 4, 8, 16 ohms. Front panel controls: input selector (phono or tape head, Tuner, Extra); Equalization (NAB tape head or RIAA record equalization); Stereo Selector Switch; separate tone controls for channels A & B Stereo Balance; Derived Center Channel Level Control; Loudness On-Off; Scratch Filter; Tape Monitor; Loudness Compensation. 15 1/2"Wx5 1/2"Hx13 1/4"D. Net 159.95
G-625WX (less case) Shpg. wt., 35 lbs. Net 12.95
Leatherette metal case for LK-72 kit. Net 12.95
G-147W Shpg. wt., 5 lbs.

LK-150 130-WATT STEREO POWER AMPLIFIER KIT
This remarkable stereo power amplifier is the perfect unit for the LC-21. Aluminum chassis and careful design for low —90 db hum; 6550 output tubes run at only 65 watts IHFM (60 watts steady state); though rated at 100 watts per pair; power bandwidth from below 19 cps to 25 KC (limits of test equipment); harmonic distortion at full output less than 0.5%; IM distortion less than 0.5%; input sensitivity switchable from 2.5 volts (for LC-21) to 1.5 volts to permit use with virtually all preamplifiers. Has built-in meter for bias adjustments. Dimensions 7 1/4"x15 1/4"x11 1/4". Shpg. wt., 52 lbs. Net 169.95
G-632WX

LC-21 STEREO CONTROL CENTER KIT
LC-21 Pre-amplifier Kit features 5 pairs of stereo inputs, derived center channel output—stereo tape recorder outputs PLUS dual magnetic pickup switch; rumble as well as scratch filter; microphone equalization, phase reverse and separate on/off; unique shielding of power supply stage together with aluminum chassis and D.C. heated tubes gives totally inaudible hum even on phono input. Frequency response: 8-50,000 cps ± 1 db; distortion 0.1% at 2.5 volts output (perfect match for input sensitivity of LK-150 stereo power amplifier. 15 1/2"Wx5 1/2"Hx13 1/4"D. Net 99.95
G-631WX (less case) Shpg. wt., 10 lbs. Net 99.95
Leatherette Metal case C for LC-21 Net 12.95
G-147W Shpg. wt., 5 lbs.

LK-48 48 WATT STEREO AMPLIFIER KIT
The most remarkable kit value today — H. H. Scott quality at a nominal price. Has same controls as LK-72 except center channel output does not have front panel level control. Power output — 24 watts per channel (IHFM); distortion at full output same as LK-72. IHFM Power bandwidth to 20 kc. D.C. heated preamp filaments and aluminum chassis for low —80 db hum and noise. Dimensions 15 1/2"Wx13 1/4"D. Net 119.95
G-640WX (less case) Shpg. wt., 35 lbs. Net 12.95
Leatherette Metal C case for LK-48. Shpg. wt., 5 lbs. Net 12.95
G-147W



SAVE WITH EXCLUSIVE LAFAYETTE HI-FI

now from Great Britain... **LAFAYETTE**
PERFORMANCE, DESIGN & VALUE

THE LAFAYETTE SOVEREIGN 12 . . .


3-Way High Performance

High-Fidelity Speaker



SK-210

49⁵⁰
NO MONEY DOWN




LAFAYETTE'S FINEST 12" SPEAKER

Constructed by master English craftsmen to Lafayette's rigid specifications, the "Lafayette SK-210 Sovereign 12" must be considered among the very finest 12" speakers available. Engineered to satisfy the most discriminating listener, the SK-210 achieves full 3 speaker performance through its advanced triaxial design. Woofer, midrange radiator and tweeter are all axially mounted within a single rigid, unitized die cast frame, to provide an integrated, efficient wide range speaker system. Construction features incorporate a 3 inch voice coil with an exclusive "Rigidflex" cone-bonding and cone-edge treatment process to form a virtually free-edged cone suspen-

sion. All irregularities of the audible frequency spectrum are smoothed out with standing waves and surround resonances eliminated. High efficiency and low distortion are further assured by use of a specially designed 2 1/4 lb. ceramic magnet. The quality of the Sovereign 12" is immediately evident in its uncompromising performance. Frequency response is 30-20,000 cps with a free-air woofer cone resonance of 35 cps. Bass response is tight and solid without boom or hangover to achieve a phenomenal realism. At 2000 cps, frequencies are channeled into a stiff-coned mid-frequency radiator by means of a smooth mechanical

crossover. High frequencies are reproduced with a silkiness and naturalness to beyond the limits of human hearing by means of a compression driver tweeter. This superb new tweeter incorporates a rigid, die cast, flared, hyperelliptical horn, a 1" diameter aluminum voice coil and diaphragm in a self-aligning assembly with air chamber and phase equalizer. A built-in crossover allows the tweeter to take over at 5,000 cps and is provided with a high-frequency L-pad level control with attractive escutcheon and knob. Shpg. wt., 15 lbs. Recommended with Eilptoflex® enclosures. SK-210 Net 49.50



ROYAL DANISH 12"
DUAL CONE SPEAKER


• HIGH FLUX DENSITY

7.95

Lafayette brings you this fine imported high fidelity speaker at a fraction of the price you would expect to pay for so much quality. Two cones are mounted on a single axis, and provide remarkable wide range frequency response from 45 to 14,000 cps. Reproduction of program material is exceptionally lifelike throughout the entire range. An exclusive, special formula cone rim treatment eliminates cone rim resonance and distortion. Also, the damping effect improves transient response and prevents "hangover." Overall depth, 5 3/4". Completely enclosed. 1" diameter voice coil with an impedance of 6 ohms. Shpg. wt., 6 lbs. SK-86. 12" Dual Cone Hi-Fi Speaker Net 7.95

the Revolutionary **LAFAYETTE**

Sphericon



SK-146

22⁵⁰

HIGH FREQUENCY SUPER TWEETER


- Frequency response from 3,000 cps to beyond 40,000 cps
- Uniform dispersion over 120 degrees in all directions
- High-sensitivity allows use with any 4-16 ohm speaker
- Requires no high voltage or power supply
- Built-in 3,000 cycle crossover network

Achieve unequalled brilliance and musical warmth from your present speaker system or the system you're now planning. The Lafayette's Sphericon is an entirely new concept in tweeter design. Equipped with a built-in 3,000 cycle crossover network and featuring a specially designed domed phenolic diaphragm with spherical diffractor. The Sphericon produces a virtually linear response from 3,000 cps to beyond 40,000 cps, ± 2 db. to 22,000 cps. High frequencies are radiated in a 120° pattern in all directions, vertically as well as horizontally—with absolutely no trace of stridency or harshness. Unlike electrostatic tweeters the "Sphericon" is highly efficient and may easily be matched with any speaker or speaker systems. . . especially the low efficiency high compliance type. Precise matching of the "Sphericon" with today's low and medium efficiency speaker is accomplished by means of a special built-in attenuator designed not to affect or lower the efficiency of the woofer. As a result less amplification is needed assuring lower distortion. Power capacity is 30 watts. May be employed with any 4-16 ohm speaker. Beautifully styled with an acoustically designed gold anodized grill set in a sturdy satin black plastic case. Dimensions: 9x4Hx2 1/2"D. SK-146 Shpg. wt., 4 lbs. Net 22.50

NOW FROM LAFAYETTE... THE "BIG 8"

34.95

NO MONEY DOWN



ONLY 8" SPEAKER/WITH
 1 1/4 LB. MAGNET

THE LAFAYETTE SK-212 . . . A new 8-Inch 3-Way High-Fidelity Speaker with Performance and Capabilities of a 12-Inch Speaker

ONLY 8", BUT LOOK AT THESE SPECIFICATIONS AND PERFORMANCE:

- FREQUENCY RESPONSE: 35-20,000 CPS
- CONE RESONANCE: 45 CPS
- MAGNET: 1 1/4 LB. ALCOMAX
- VOICE COIL: 3" DIAM.
- FLUX DENSITY: 175,000 GAUSS
- IMPEDANCE: 16-OHMS
- POWER HANDLING CAPACITY: 25-WATTS
- 2,000 CPS MECHANICAL CROSSOVER 5000 CPS ELECTRONIC
- CROSSOVER WITH BUILT-IN BRILLIANCE CONTROL
- SPECIALLY DEVELOPED "RIGIDFLEX" FREE EDGE CONE SUSPENSION
- DIE-CAST FRAME
- NEW COMPRESSION-DRIVER TWEETER

LAFAYETTE'S "BIG 8"—The remarkable quality and performance of this new speaker provide it with the largest 8" of sound we've ever heard! With almost uncanny ability, the SK-212 easily re-creates the entire musical spectrum from 35 to 40,000 cps; achieving a standard of natural balance distortionless performance and superb transient response normally associated with larger costlier speakers. Every musical tone is there—from powerful orchestral passages and deepest organ tones to the most delicate of solos. Precision engineered to meet Lafayette's uncompromising specifications and constructed by master English craftsmen, the SK-212 incorporates the design and construction features you'd expect to find in the finest speakers. This excellence of design is best demonstrated by its 3 inch voice coil, 1 1/4 lb. Alcomax magnet, and special "rigidflex" free edge cone suspension. Woofer, midrange radiator and tweeter are axially mounted to provide wide range speaker performance. A mechanical crossover separates bass and midrange frequencies at 2,000 cycles while 5,000 cycle electrical crossover provides a smooth transition from midrange to a newly developed compression driver tweeter. A high frequency level control allows matching of sound to individual taste and room acoustics. Recommended with Eilptoflex® enclosures. SK-212WX Shpg. wt., 11 1/2 lbs. Net 34.95

LAFAYETTE SK-130 8" WIDE-RANGE HI-FI SPEAKER

Check These Phenomenal Specifications

- ✓ Frequency Response: 40-18,000 cps
- ✓ Magnet Weight: 1 lb. High Efficiency Alcomax Magnet
- ✓ Flux Density: 13,500 Maxwells
- ✓ Power Handling Capacity: 15 Watts
- ✓ Cone Resonance: 55 cps
- ✓ Voice Coil: 1 Inch
- ✓ Impedance: 16 Ohms

ASTONISHING FIDELITY from a speaker of this size and modest price. Designed and finished with typical British craftsmanship, the SK-130 features an especially designed hyperbolic cone with a plastic surround suspension for wide compliance performance. Bass response is robust and full bodied, while the mid-range and highs are virtually transparent, with never a trace of shrillness or harshness.

The excellent wide-range response of the SK-130 make it ideal for stereo when used in pairs or perfect for use as a high quality extension speaker. Overall Diam. 8 1/2" x 4" Deep. Baffle cut-out 7 1/2". Rigid vibration-free frame is equipped with screw type terminals. See Eilptoflex® enclosures recommended for this speaker elsewhere in catalog. SK-130 Shpg. wt., 3 lbs. Net 12.95



NEW!

12⁹⁵



HK-3

CONE TYPE METAL-CASED HI-FI TWEETER

5.95

• FREQUENCY RESPONSE 2,000-16,000 CPS
 • HANDLES 20 WATTS • IMPORTED TO SAVE YOU MONEY

Without doubt one of the finest cone type high frequency tweeters we have ever tested, and is exceeded in performance only by diaphragm type tweeters. It is particularly efficient in the higher end of the audio spectrum where ordinary cone tweeters tend to lose clarity and volume. With this tweeter added to your present system, you will be able to hear all the fine transients and high notes of the upper register as they were actually recorded. Entirely enclosed in metal case with base for standing by itself, or mounting on a flat surface. Bracket is supplied for mounting on panel or in cabinet. Requires crossover network such as Lafayette LN-2. Diameter 3". Depth 2 1/2". Voice coil impedance 8-16 ohms. HK-3 Hi-Fi Tweeter—Shpg. wt., 4 lbs. Net 5.95



SK-121
 SK-122

NEW! METAL CASED TWEETER

2.95

- FREQUENCY RESPONSE 3,000-16,000 CPS
- HANDLES 20 WATTS OF POWER • CHOICE OF 8 OR 16 OHM IMPEDANCE


The modest price of this tweeter gives no indication as to its high quality. Smooth, silky reproduction of the high frequencies along with an even sound dispersion is insured by the use of the round cone. The tweeter assembly is protected by a heavy wire mesh screen and completely encased in an attractive Satin Gold metal. As a result of the rear casing on the tweeter, speaker interaction between speakers has been eliminated allowing for the placement of the tweeter in the same enclosure with the woofer and mid-range speakers. Supplied with sturdy attached mounting stand and 2 1/2 ft. hook-up cord. Size 2 7/8" diam. x 2" deep. SK-121 8 ohm Tweeter. Shpg. wt., 2 1/2 lbs. Net 2.95

SK-122 16 ohm Tweeter Net 2.95

SPEAKER AND ENCLOSURE COMBINATIONS

**NEW! 12" WIDE-RANGE
HI-POWER
HI-FI SPEAKER**

- 21.5 OZ. ALNICO 5 MAGNET
- RATED AT 30 WATTS
- RESPONSE 20-14,000 CPS
- SEAMLESS CONE
- SPECIAL HEAVY-DUTY CONSTRUCTION




ONLY 14.95

Incorporating a full 21.5 oz. magnet of high-flux density Alnico 5, this new wide-range 12" PM high fidelity speaker is rated at 30 watts and is excellent for use with any hi-fi system. With proper baffling, frequency response is 20 to 14,000 cps. Special constructional features include a 1 1/2" voice coil; epoxy bonding of the voice coil to the seamless cone; completely dust-proof enclosed magnet structure; fibre-to-metal bonds made with heat under extreme pressure; heavy cast-metal frame; metal parts heavily cadmium-plated, with exposed surfaces covered with a handsome mar-resistant hammeroid finish. Voice coil impedance 8 ohms. Outside diameter 12 3/4", mounting diameter 11 3/8", depth 6 3/4". Color-coded 4-way binding-post terminals.

SK-137 Shpg. wt., 7 lbs. Net 14.95

**NOW FROM LAFAYETTE
ADD-ON REVERBERATION**



**Works With Phono, TV
Radio or Tape Recorder**

Converts Your
Living Room Sound
to that of Concert
Hall Grandeur

69.95


- Marvelous For Existing Monaural Systems
- Enriches Your Present Stereo Systems
- Adds A Delightful Dimension to Sound Without Effecting Fidelity
- Completely Self-Contained, Has Own Amplifier and Speaker

Changes the acoustic dimensions of your room. A self-contained reverberation speaker-and-amplifier with its own internal power supply, that hooks into any existing stereo or monophone component sound system, FM and AM radio, Tape Recorder, T.V. set, or Electric Organ. More than just a simple "echo device," the "Reverb-Control" takes part of the original signal from a speaker system and feeds this signal through a carefully tuned device which delays the sound for 1/30th of a second. This delayed sound blends with the original sound to add acoustic dimension to your room. Uses 8" Dual diameter speaker. Power output of amplifier 3 watts R.M.S. (will work excellently with systems having up to 60 watt amplifiers). 2 sets of inputs—high level and low level (left and right)—use only one input for monaural. Comes supplied with 2 cables, 15' each with standard phono plugs on one end. Power requirement 110V to 120V AC. Cabinet size 10x20x10 1/2" deep. Available in walnut and mahogany. Shpg. wt., 22 lbs.

SK-204WX Walnut Finish Net 69.95
SK-205WX Mahogany Finish Net 69.95

SENSATIONAL SPEAKER SYSTEM

**JENSEN speakers + UNIVERSAL
WOODCRAFTERS cabinets +
LAFAYETTE low prices**



38.95

- Heavy 7-Ply Furniture Veneer Cabinets
- Fiberglass-loaded Cabinet for Better Bass Response
- Jensen 12" Woofer, 8" Midrange Driver, 3 1/2" Enclosed Tweeter


Now you can get unparalleled speaker performance at a low, low Lafayette price—the most outstanding value of its kind in the industry. The Uni-Voice hi-fi speaker system is a thrilling blend of fully integrated, unified 3-speaker systems engineered by Jensen with specially developed Jensen components, with cabinetry by Universal Woodcrafters. Contains special 12" woofer; 8" midrange driver independently pneumatically damped in its own hermetically enclosed acoustic surroundings, completely separated from woofer cavity; 3 1/2" fully enclosed, independently baffled tweeter. Woofer electric crossover at 600 cycles, midrange electric crossover at 2000 cycles. Impedance 8 ohms. Response: 35-18,000 cycles.

MODEL UV-30. Bookshelf enclosure finished on 4 sides. Speaker grille completely framed with brass inlay. 24Wx14 1/2 Hx13" D.
SK-185WX Walnut finish. Shpg. wt., 32 lbs. Net 38.95



Tweeter with baffle

Polyester resin treated tweeter edge



TWEETER BAFFLE

CONICAL STIFFENER

CROSSOVER NETWORK


Lafayette presents

**THE NEW ULTRA-LINEAR SK-128™ full range 8 inch
biaxial speaker with newly developed
tweeter baffle design.**

19⁵⁰

- 20 TO 20,000 CPS (40 TO 16,000 CPS ± 3 DB) ■ HIGH EFFICIENCY
- HIGH EXCURSION WOOFER WITH UNIQUE "CONICAL STIFFENER"
- HANDLES HEAVY BASS PASSAGES WITHOUT "DOUBLING"

*Eccentric Tweeter Mounting & Unique Elliptical Baffle
Completely Eliminates Interaction Between Woofer & Tweeter*



The SK-128 combines the best features of a multiple speaker system in one compact and economical unit. It offers full, even coverage of the entire audible range, with no distortion or coloration to mar your listening pleasure. The specially treated woofer cone has a unique "Conical Stiffener" at the apex which, coupled with its high compliance, enables the cone to operate in a piston-like manner—delivering a clean, powerful bass response. The 2-inch tweeter has its own voice coil and magnetic field. Special treatment of cone and cone edge provides even distribution of the high frequencies, with no peaks or resonances. The unusual off-center mounting of the tweeter and its elliptical baffle minimizes interaction between tweeter and woofer and insures an overall response free of intermodulation distortion. Electrical crossover from the woofer cone to the tweeter unit is provided by a built-in network. An adjustable brilliance control permits matching of sound to room acoustics. Efficiency of the speaker is such that it will operate from any amplifier with an output of 1 watt or more. Installed in a bass-reflex type of enclosure, it performs outstandingly, and is recommended for all high-quality music systems—whether monaural or stereophonic. SPECIFICATIONS: Overall Response: 20-20,000 cps (40-16,000 cps ± 3 db). Free air Resonance: 45-65 cps. Impedance: 8 ohms. Power Rating: 20 watts Integrated Program Material. Crossover: 2,500 cps. Overall Diam. 8 3/4". Overall Depth: 5 1/2". Baffle cut-out: 7 1/2". Rugged, vibration-free speaker frame with color-coded screw-type terminals for quick, easy connection of amplifier leads. Shpg. wt., 5 lbs.

SK-128 Full Range 8" Biaxial Speaker.....Net 19.50

**LAFAYETTE MINI-DUCT BOOKSHELF ENCLOSURE
WITH SK-128 8" ULTRA-LINEAR SPEAKER**

The perfect answer for those who demand realistic sound reproduction even where space is limited. Two of these systems are ideal for stereo. Shpg. wt., 28 lbs.

SY-343WX Speaker System in Walnut	Net 39.50
SY-344WX Speaker System in Mahogany	Net 39.50
SY-345WX Speaker System in Blonde	Net 39.50
SY-346WX Speaker System in Oiled Walnut	Net 39.50
SY-347WX Speaker System in Unfinished Birch	Net 37.50

SK-128 SPEAKER & MINI-DUCT FINISHED ON 4 SIDES

SY-403WX MAHOGANY	Net 41.95
SY-404WX WALNUT	Net 41.95




**LAFAYETTE MINI-DUCT™ BOOKSHELF ENCLOSURE
WITH SK-212 3-WAY SPEAKER**

A perfect match: The "Mini-Duct" enclosure and the remarkable Lafayette SK-212 3-way High Fidelity speaker. Reproduces the entire audio spectrum with a marvelous smoothness. Styled in attractive furniture finishes. Shpg. wt., 35 1/4 lbs.

SK-212 SPEAKER AND MINIDUCT ENCLOSURE FINISHED ON 3 SIDES	
SY-431WX UNFINISHED	Net 52.45
SY-432WX MAHOGANY	Net 54.95
SY-433WX WALNUT	Net 54.95
SY-434WX OILED WALNUT	Net 54.95
SY-435WX BLONDE	Net 54.95

SK-212 SPEAKER AND MINI-DUCT FINISHED ON ALL 4 SIDES

SY-436WX MAHOGANY	Net 56.40
SY-437WX WALNUT	Net 56.40



**FAMOUS LAFAYETTE MINI-DUCT™ BOOKSHELF ENCLOSURE
WITH SK-130 8" WIDE-RANGE SPEAKER**

As Low As **33⁹⁵**

A combination that rivals the performance of much larger speaker systems. This fine enclosure assures optimum performance from the SK-130. Only 23" W x 11 1/2" H x 11 1/4" D—ideal for mounting in a bookcase or record shelf. Finished on 3 sides in a variety of fine furniture finishes. Shpg. wt., 27 lbs.

SK-130 SPEAKER & MINI-DUCT ENCLOSURE COMBINATIONS	
SY-415WX Unfinished	Net 33.95
SY-416WX Mahogany	Net 35.95
SY-417WX Walnut	Net 35.95
SY-418WX Oiled Walnut	Net 35.95
SY-419WX Blonde	Net 35.95


SK-130 SPEAKER & MINI-DUCT FINISHED ON 4 SIDES	
SY-420WX Mahogany	Net 36.95
SY-421WX Walnut	Net 36.95



MINIDUCT

SK-130

THE FAMOUS LAFAYETTE ELIPTOFLEX



FINISHED ON 4 SIDES

Adapts to any room arrangement. Place horizontally on shelves or vertically on the floor.

ELIPTOFLEX®

COMPLETE SPEAKER SYSTEM with ENCLOSURE

NOW IT IS POSSIBLE TO HAVE THE ADVANTAGES OF A HIGH EFFICIENCY 12" SPEAKER IN A BOOKSHELF SIZE ENCLOSURE.

SPECIALLY DESIGNED 12" COAXIAL SPEAKER WITH SHEEPSKIN CONE EDGE SUSPENSION AND 1 1/4 LB. MAGNET PROVIDE A RESPONSE FROM BELOW 30 TO 15,000 CPS.

ENCLOSURE BEAUTIFULLY FINISHED ON FOUR SIDES IN HAND RUBBED VENEERS.

64.50

NO MONEY DOWN

The "Eliptoflex" is the result of an intensive research program whose 3-fold purpose was to:

Develop a speaker system that would meet space requirements of stereo.

Utilize the full advantages of efficient 12" speaker performance.

Provide optimum performance without use of large wattage expensive amplifiers.


The Results Were Remarkable . . . The Eliptoflex utilizes a unique elliptical port which broadens frequency response and provides better transient response. A specially engineered diffracting ring eliminates cancellation effects between front and rear radiation. These engineering advances are coupled with the famous Lafayette free edge SK-58 12" coaxial speaker 3" conetype tweeter, 1 1/4 lb. TSK-5 high flux density magnet and special 3/4" wide sheepskin cone-edge suspension and built-in crossover network level control. "Eliptoflex" achieves a degree of natural smoothness, low-distortion and rich robust bass hitherto found only in large enclosure speaker systems or inefficient bookshelf speakers many times its price requiring high powered amplifiers. Due to its highly efficient design characteristics the "Eliptoflex" does not require costly high wattage amplification.

The "Eliptoflex" speaker system is beautifully finished on 4 sides in a variety of hardwood veneers for attractive room placement either horizontally, or vertically. Dimensions are 14"Hx23-7/16"Wx13-5/16"D. Shpg. wt., 35 lbs.

SY-381WX "Eliptoflex" Speaker System Mahogany	Net 64.50
SY-382WX "Eliptoflex" Speaker System Walnut	Net 64.50
SY-383WX "Eliptoflex" Speaker System Blonde	Net 64.50
SY-384WX "Eliptoflex" Speaker System Oiled Walnut	Net 64.50
SY-392WX "Eliptoflex" Speaker System Unfinished furniture grade birch	Net 59.50

ELIPTOFLEX ENCLOSURE LESS SPEAKER—FINISHED ON 4 SIDES	
CAB- 83WX "Eliptoflex" Enclosure—Mahogany	Net 36.50
CAB- 84WX "Eliptoflex" Enclosure—Walnut	Net 36.50
CAB- 85WX "Eliptoflex" Enclosure—Blonde	Net 36.50
CAB- 86WX "Eliptoflex" Enclosure—Oiled Walnut	Net 36.50
CAB-124WX "Eliptoflex" Enclosure—Unfinished Birch	Net 29.50

PHENOMENAL ELIPTOFLEX PERFORMANCE



PERFORMANCE EXPLANATION

The loudspeaker is mounted on a baffle recessed in the cabinet shell with the front-plate extending partially across the front surface of the baffle forming ducts or tubes from the port openings to the outside air. The elliptical cutout changes the effective length of the duct across its area. This variation in path lengths provide an extremely smooth transition from duct to free air; broadens the frequency response and provide better transient response. A triangular shaped diffracting ring mounted on the front of the baffle board virtually eliminates undesirable cancellation effects normally produced by close coupling of front and rear cone radiation. This results in a "lens" effect, changing relative particle velocities and consequently, phase relationships so as to produce a smooth transition from front to rear radiation. Comparative laboratory and listening tests indicate that "Eliptoflex" performance is demonstrably superior throughout the audio spectrum.

Patents applied for in United States, England and Canada




66.50

LAFAYETTE ELIPTOFLEX® BOOKSHELF ENCLOSURE WITH SK-180 10" TRIHELIX 3-WAY SPEAKER

An ideal combination of speaker and enclosure that furnishes optimum 3-way speaker performance. Eliptoflex enclosures are finished on all four sides for vertical or horizontal placement. Shpg. wt., 32 lbs.

SY-398WX Mahogany	Net 66.50
SY-399WX Walnut	Net 66.50
SY-400WX Blond	Net 66.50
SY-401WX Oiled Walnut	Net 66.50



VALUE COMBINATION! LAFAYETTE SK-211 CAVALIER 12" 3-WAY SPEAKER WITH 1 3/4 LB. MAGNET AND FAMOUS ELIPTOFLEX ENCLOSURE

74.50

NO MONEY DOWN

Get the most in both value and performance with these speaker/cabinet combinations. Lafayette's famous Eliptoflex bookshelf enclosure assures you of top performance for your SK-211 "Cavalier 12" speaker. Enclosures finished on all four sides for vertical or horizontal placement. Your choice of fine finishes. Size: 14Hx23 1/2 Wx 13-5/16 D. Shpg. wt., 34 lbs.

SY-410WX SK-211 & Eliptoflex in Mahogany	Net 74.50
SY-411WX SK-211 & Eliptoflex in Walnut	Net 74.50
SY-412WX SK-211 & Eliptoflex in Blonde	Net 74.50
SY-413WX SK-211 & Eliptoflex in Oiled Walnut	Net 74.50
SY-414WX SK-211 & Eliptoflex in Unfinished furniture grade birch	Net 67.50


FAMOUS LAFAYETTE ELIPTOFLEX ENCLOSURE AND SK-210 SOVEREIGN 12" 3-WAY SPEAKER WITH 2 1/4 LB. MAGNET

PERFORMANCE MATCHED—Lafayette's famous Eliptoflex bookshelf enclosure matched with the exceptional SK-210 Sovereign 12" 3-way speaker. Finished on four sides in your choice of decorator finishes. Size: 14Hx23 1/2 Wx 13 1/2 D. Shpg. wt., 39 lbs.


SY-405WX SK-210 & Eliptoflex in Mahogany	Net 82.50
SY-406WX SK-210 & Eliptoflex in Walnut	Net 82.50
SY-407WX SK-210 & Eliptoflex in Blonde	Net 82.50
SY-408WX SK-210 & Eliptoflex in Oiled Walnut	Net 82.50
SY-409WX SK-210 & Eliptoflex in Unfinished furniture grade birch	Net 75.50

82.50

NO MONEY DOWN



HI-FIDELITY WOOFERS



SK-67W*

SK-68

23.95

15.50

15" HI-FI WOOFER

• 2 LB. ALNICO MAGNET
• 20 TO 5000 CYCLES—35 WATTS
This efficient 15" low frequency woofer incorporates many exclusive features. For original equipment or replacement, it provides highly efficient extended low-frequency response. Ideal for assembling 2- and 3-way speaker systems. Handles 35 watts of audio power. Frequency response ± 2 db 20 CPS to 1000 CPS, and ± 5 db from 20 CPS to 5,000 CPS with proper baffling. Voice coil dia. 2", impedance 8 ohms. 31.5 oz. Alnico V magnet.* Finished in beautiful brown enamel. Cone is seamless type, permanently bound to voice coil. Has 4-way binding posts. Shpg. wt., 13 1/4 lbs. Cone Resonance 45 cycles

Net 23.95

12" HI-FI WOOFER

21.5 OZ. ALNICO V MAGNET—25 WATT
Provides efficient, extended low-frequency response of ± 5 db from 35 to 8000 CPS, and features 25 watts of power handling capacity. Perfect for high-fidelity installations or for modernization of older equipment. Ideal for assembling 2- and 3-way speaker systems at a budget price. Enclosed magnet structure—completely dust-proof. Compliance of outer cone and inner spider carefully calculated for best bass response. 21.5 oz. Alnico V magnet, 1 1/2" dia. voice coil, 8 ohm impedance. All exposed surfaces are finished in beautiful brown enamel. Has 4-Way binding posts. Cone Resonance 50 cycles. Shpg. wt., 8 lbs.

Net 15.50

NEW! 2- and 3-way L/C CROSSOVER

NETWORK



• 4 CROSSOVER FREQUENCIES: 350, 700, 2000-3000, 5000 CYCLES
• 6 CROSSOVER COMBINATIONS • 2 OR 3 WAY CROSSOVER • ATTRACTIVE METAL CASE • BUILT-IN BRILLIANCE & PRESENCE CONTROLS

This versatile unit can be used either as a 2-way or 3-way 6 db per octave network. You can use this network for a 2-way system now, easily and quickly convert to 3-way later. Six crossover combinations are available—2-way crossover with 2000-3000 cycle or 5000 cycle crossover, and 3-way with crossover frequencies of 350 and 5000, 350 and 2000-3000, 700 and 2000-3000 or 700 and 5000 cycles—a total of four different crossover frequencies! Suitable for 8-16 ohm speakers. The network is housed in an attractive metal case, suitable for mounting inside enclosure or leaving out in the open. Two level controls—Brilliance and Presence controls—are mounted on the front panel. If desired, these level controls may be removed, along with the beautiful gleaming copper escutcheon plate, for external mounting; controls are wired with 3-foot long leads. High quality components are used for long life and top performance. Shpg. wt., 6 lbs.

Net 14.95

2 OR 3 WAY CROSSOVER NETWORK



• 4 CROSSOVER FREQUENCIES • L PAD BALANCE CONTROLS • EASY TO USE • IMPEDANCE 16-OHMS

The LN-7 Crossover Network combines quality performance, beauty and versatility at an unbeatable price. It can be used in a two-way system by crossing over at 500 cps or 3300 cps, and in a three-way system by utilizing the two simultaneously. The change from a two-way to a 3-way 6 db per octave network may be accomplished easily. Two level balance controls. Size 5 1/2 x 2 1/2 x 2 1/2". Shpg. wt., 2 1/2 lbs.

Net 8.75


HIGH FREQUENCY TWEETER WITH ACOUSTIC LENS

DIRECT IMPORTATION MAKES THIS PRICE POSSIBLE!
• FREQUENCY RESPONSE FROM 2000 CPS TO BEYOND AUDIBILITY • LOUVERED ACOUSTIC LENS FOR UNIFORM SOUND DISPERSION • HANDLES 25 WATTS OF POWER • PRICED EXCEPTIONALLY LOW

New high frequency tweeter featuring a louvered acoustic lens for uniform sound dispersion and capable of handling up to 25 watts of distortion-free power. The directional tendency of high frequency notes is overcome by the natural wide dispersion angle of the short horn and acoustic lens which disperses and radiates the high notes smoothly throughout the entire listening area. The lens is detachable for panel mounting, with a separate base for the tweeter furnished for external mounting where desired. Aluminum voice coil has 16 ohms impedance. Size 4 1/4" long x 3" diameter, lens extends 2 1/2". Requires a crossover network, preferably one with a level control, such as the LN-2. With full instructions. Shpg. wt., 5 lbs.

Net 14.95

**WORLD-RENOWNED
LAFAYETTE SK-115A 3-WAY 15"
HIGH FIDELITY SPEAKER**



Custom Built in England
to Lafayette's Rigid
Specifications

79⁵⁰

**MONEY BACK
GUARANTEE
YOU BE THE JUDGE**

Try the SK-115A for 30 days.
If not completely satisfied,
return it for full refund.
* 1 Year Service Guarantee

**NO MONEY
DOWN**

- Massive 5 lb. Magloy Magnet—The Most Efficient Magnetic Material Available
- Free-Edged Cone Suspension
- 3 Inch Long Main Voice Coil
- 12 DB/Octave Crossover Network with High Frequency Level Control
- Precision Pressure Driven Horn Loaded Tweeter with Aluminum Diaphragm & Coil

SUPERB PERFORMANCE—The finest British craftsmanship and advanced acoustic design, combined by Lafayette to bring you this outstanding 3-way 15" speaker. Designed and constructed to the most exacting laboratory standards, the SK-115A features a patented concentric twin gap magnetic system with a massive 5 lb. Magloy magnet. Woofer, mid-range radiator and speaker are axially mounted to achieve unexcelled, efficient, wide-range speaker performance. The woofer section with a cone resonance of 25 cps is vacuum constructed by an exclusive process. The cone rolls and edges are bombarded with minute particles of specially-blended plastic materials, to form a virtually free-edged cone suspension that eliminates standing waves and surround resonances. An automatic mechanical crossover separates bass and mid-range frequencies at 2,000 cps to a high stability mid-range radiator. A 12 db per octave LC crossover network provides smooth transition at 5,000 cps from mid-range to a precision pressure driven horn loaded tweeter employing an aluminum diaphragm and coil in a self aligning assembly with air chamber and phase equalizer. This crossover is provided with a high frequency level control for matching of sound to room acoustics and individual listening tastes. Dimensions: 8 3/4" Overall depth; 15 3/4" diam. Shpg. wt., 40 lbs.

SK-115AWX Net 79.50

*Repairs which become necessary due to manufacturing defects will be made by Lafayette at no charge during the Guarantee period.

COMPARE THESE SPECIFICATIONS

- Cone Resonance: 25 cps. • Overall Frequency Response: 20-20,000 cps. • Magnet: 5 lb. Magloy Permanent Magnet • Magnetic Flux Density: 306,000 Maxwells
- Crossover: 12db/Octave Twin 1/2 Section LC Network
- Power Capacity: 50-watts • Woofer Voice Coil Diameter: 3 Inches • Tweeter Voice Coil Diameter: 1 Inch
- Impedance: 16 ohms

LAFAYETTE "MINUETTE" HIGH-FIDELITY SPEAKER SYSTEM

Room Filling Music
Everywhere in Your Home!



TWO FOR STEREO 23⁵⁰ SINGLY 12.50

- Shelf Size — 8 1/4"Dx15 3/4"Lx5 7/8"H
- Use Two For Stereo—Perfect For the Small Apartment or Listening Area
- Genuine Walnut Finish on 4 Sides
- Complete with 6' Extension Cable and Phone Plug

An exceptional speaker value... the Lafayette "Minuette" Hi-Fi Speaker System will bring music to any room in your home — and for a remarkably low cost. Designed for use where space is at a premium — ideal for the small apartment or listening area. Expand your stereo system to other areas of your home... easily used in the den, kitchen, patio or bedroom. Employs a specially designed 5 1/2" speaker in a rear loaded reflex type enclosure. Provides an exceptionally fine musical quality yet measures only 8 1/4"Dx15 3/4"Lx5 7/8"H — small enough to fit anywhere. Superb Walnut finish on 4 sides allows placing speaker horizontally or vertically. Frequency Response 100-12,000 cps. Impedance 8 ohms. Rated at 10 watts. Supplied with 6 ft. of extension cable and phone plug. Shpg. wt., 5 1/2 lbs.

SK-181 Net 12.50
Save — Buy two for stereo. Shpg. wt., 11 lbs.
Set of two Net 23.50

**THE WIDELY ACCLAIMED LAFAYETTE
SK-58 12" COAXIAL SPEAKER
Now Offered Exclusively By Lafayette At
Tremendous Savings**

**SUPERB PERFORMANCE GUARANTEED
—OR YOUR MONEY BACK!**

**THE WORLD-RENOWNED
ORIGINAL LAFAYETTE SK-58[®]**

- RESPONSE 30-15,000 CPS
- SHEEPSKIN "FREE EDGE" CONE MOUNTING
- 1 1/4 LB MAGNET WEIGHT
- 3" COAXIALLY MOUNTED TWEETER
- BUILT-IN LC NETWORK
- RATED AT 20 WATTS CONTINUOUS POWER

Lafayette's exclusive 12" coaxial is a precision-made high fidelity loudspeaker, universally acclaimed by music lovers, hi-fi enthusiasts and professional experts alike as the greatest performance-value on the hi-fi market. It provides a truly faithful reproduction of sound without any "coloration" or distortion, its excellence being responsible for its use in innumerable high fidelity music systems today. The SK-58 incorporates such features as heavy, high flux density TSK-5 magnets for high efficiency; 3/4" wide sheepskin cone-edge suspension and special composition fibre cone material, specially treated for ultra-linear, distortion-free response; heavy rugged cast metal frame for freedom from resonances and for greater rigidity.

29.50

**NO MONEY
DOWN**



The coaxially-mounted 3" cone-type tweeter has a bell shaped mounting for maximum dispersion of high frequencies with no back radiation. With the built-in 3000 cps crossover network it contributes its share to the smooth delivery of the overall wide range response of 30-15,000 cps. Woofer resonance in free air is 40 cps. Speaker power handling capacity is 20 watts continuous sine wave, 35 watts peak program material. Impedance of the voice coil is 8 ohms, connections being made to chrome-plated screw terminals. Finished in gray-brown opalescent enamel, the speaker is supplied complete with "brilliance" level control. Shpg. wt., 11 lbs. SK-58W 12" COAXIAL SPEAKER Net 29.50

THE LAFAYETTE TRIHELIX[®]

Recreates The Entire Audio Spectrum With Concert Hall Faithfulness—The Lafayette "Trihelix" represents a major breakthrough in three way speaker design. Fresh engineering concepts have resulted in a single 10-inch speaker designed expressly for use in bookshelf size enclosures, that delivers a quality of performance with the unmistakable feel, presence and clarity of a 3-way speaker system. The "Trihelix" is in effect a complete three-way high-fidelity speaker system, with three mechanically and electronically independent speakers mounted within a single 10-inch frame.

Although they are individual units the 2-inch tweeter and 5-inch midrange speakers have been especially designed to compliment the woofer. Special treatment of the cones and cone edges with polyester resins provides an even distribution of mid and high frequencies without peaks or resonances. To minimize interaction between the three cones both the midrange and tweeter units are mounted eccentrically or off center in relation to the woofer. In addition the midrange and tweeter are completely enclosed by a specially designed baffle. These unusual design features result in effectively eliminating intermodulation distortion due to interaction between woofer, midrange and tweeter cones—a common fault in conventionally designed 3-way speakers.

The specially treated woofer cone employs a revolutionary "conical stiffener" located at the apex of the cone in order to stiffen the diaphragm and eliminate "breakup," thus providing a true piston action. This carefully designed cone-stiffening procedure, in addition to its very high compliance, enables the woofer to deliver a smooth, crisp, solid bass that balances naturally against a crystal clear midrange and natural treble. A built-in electrical crossover network with crossover points at 1500 cps and 5000 cps, allows each speaker to reproduce its portion of the audio range smoothly and efficiently. An adjustable brilliance control permits matching of sound to room acoustics. SPECIFICATIONS: Overall Response 20-20,000 cps (30 to 18,000 cps ± 3 db). Free Air Resonance 35-55 cps. Impedance 16 ohms. Power Rating: 20 watts Average Program Material. Crossover Points: 1500 & 5000 cps. Overall Diam: 10". Overall Depth: 7". Baffle cut-out: 8 3/4". Screw type terminals are color coded for quick easy connection of amplifier leads. Shpg. wt., 3 lbs.


SK-180 10" Lafayette "Trihelix" Net 32.50
SB-62W Adaptor Board To Fit SK-180 To 12" Cutout Net .89

**3 Completely Independent
Speakers With 3 Separate
Voice Coils In a Single
Compact Unit**

- Frequency Response 20 to 20,000 cps (30-18,000 cps ± 3 db)
- Revolutionary "Conical Stiffener"
- Eccentric Baffle Mounting of Midrange & Tweeter Eliminates Interaction Between Speaker Cones
- Built-in Crossover Network and Brilliance Control
- Extremely Efficient
- High Excursion Woofer
- Ideal For Stereo

32.50

NO MONEY DOWN




3-WAY CROSSOVER NETWORK
MIDRANGE & TWEETER BAFFLES
CONICAL STIFFENER

**THE LAFAYETTE CAVALIER 12"
High-Fidelity 3-Way Speaker**

- 1 3/4 lb. High-Efficiency "Alcomax" Magnet
- Special Design For Distortionless Performance From 30-20,000 cps.
- 1 3/4" Voice Coil
- Handles 25 Watts of Power
- Non-Resonant Rigid Frame Construction
- Crossover Complete With Brilliance Control

39⁹⁵


NO MONEY DOWN



AN OUTSTANDING PERFORMANCE VALUE . . .

This new Lafayette Cavalier 12 integrates the finest acoustic design with precise British craftsmanship. Its advanced 3-way design with woofer, mid-range radiator and tweeter axially mounted within a specially engineered non-resonant rigid frame is capable of faithfully reproducing the complete audio spectrum from 30-20,000 cps. The most violent crescendos are easily handled without tone coloration or distortion, with superior bass response achieved even at the lowest volumes. Construction features include a 1 3/4 lb. high efficiency "Alcomax" magnet, an especially engineered "Rigidflex" cone-bonding and cone edge treatment process for a virtually free-edged cone suspension, 1 3/4 inch voice coil

plus a stiff-coned midrange radiator with a 2,000 cps mechanical crossover. A 5,000 cps LC crossover equipped with brilliance control channels high frequencies into a compression-driver tweeter, incorporating a rigid die cast flared hyperelliptical horn, a 1" diameter aluminum voice coil and diaphragm in a self-aligning assembly with air chamber and phase equalizer. SPECIFICATIONS: Frequency Response: 30-20,000 cps, Fundamental Cone Resonance: 35 cps, Power Handling Capability: 25 watts. Magnet: 1 3/4" lb. "Alcomax" Voice Coil: 1 3/4" diameter; Crossover: Mechanical at 2,000 cps. Electrical at 5,000 cps; Impedance: 16 ohms. Shpg. wt., 10 lbs. SK-211 Lafayette Cavalier 12 Net 39.95



LAFAYETTE EXTRA LOW COST AUDIO & PHONO ACCESSORIES

NEW Lafayette BASS REFLEX SPEAKER BOOKSHELF ENCLOSURE KIT FOR 8" or 6" SPEAKERS

COMPARES TO CABINETS PRICED AT \$35

- Precision Cut — Fits Together Smoothly
- Adapts For 8" or 6" Speakers
- Easy To Follow Pictorial Instructions
- Versatile — Use As Floor or Bookshelf Enclosure



As Low As
10.95

BUILD IT YOURSELF . . . All that's required to construct this excellent bookshelf speaker enclosure is a screwdriver and thirty minutes of your time. Expensive woodworking equipment isn't needed—each cabinet component has been precision cut and fits together perfectly. There's nothing else to buy . . . acoustic padding, grill cloth and hardware are provided. Use any 8" or 6" speaker; the mounting board has been precut for 8" speakers and an adapter is supplied for 6" speakers.

Designed for horizontal placement in a bookshelf, along a wall etc. Constructed of 3/4" veneers on 3 sides with handsome picture frame molding. You save even more by finishing this kit yourself—the 3 sides are smoothly sanded furniture grade wood; ready for a finish you'll be proud of. (See Lafayette's professional finishing kits). Dimensions: 23x9 1/2 x 11". Available in either birch or walnut unfinished veneers.

- CK-31WX Birch Kit Shpg. wt., 15 lbs. Net 10.95
 - CK-35WX Walnut Kit Net 13.95
- Speakers for Lafayette CK-31 Cabinet Kit. Lafayette 8" Duo-Cone Speaker; 40-16,000 cps response.
- SK-98 Shpg. wt., 5 1/2 lbs. Net 9.95
 - Lafayette 6 1/2" Coaxial Speaker; 50-16,000 cps response.
 - SK-97 Shpg. wt., 3 1/2 lbs. Net 6.95

Not 1/2", But 3/4" Furniture Grade White Birch Or Walnut Veneer

Smooth, Sanded, Ready for a Fine Finish

Built-In Picture Frame Moulding

Assembles In Less Than 30 Minutes!

Adapter for 6" Speaker

Precut for 8" Speaker

Interior Acoustic Padding

Carefully Designed Bass Reflex Port

Decorative Acoustic Grill Cloth

NEW! LAFAYETTE SK-98® 8" DUO-CONE HI-FI SPEAKER



- MECHANICAL 2-WAY DESIGN
- OVERALL RESPONSE 40-16,000 CPS.
- LARGE MAGNET STRUCTURE
- PATENTED CONE CONSTRUCTION AND MATERIAL
- HIGH EXCURSION WOOFER

9.95

The dual-cone construction used in these high quality 8" speakers, provides the same type of wide-range response normally found only in true coaxial speakers or multiple speaker systems. Two separate cones act through a common voice coil. The outer edge of the tweeter cone is attached to the mid-section of the woofer cone; both cones "float" on flexible corrugated edges. This mounting results in true mechanical crossover, so that both cones operate at low frequencies, but only the tweeter cone operates at high frequencies. This gives improved high frequency directional characteristics and minimum distortion. Patented cone materials provide extremely smooth response over the range of 40-16,000 cps. Magnets are large and heavy, range of 10,500 gauss and total flux of with a flux density of 10,500 gauss and total flux of 56,000 maxwells. Terminals are screw-type for solderless connections. Sensitivity is 99.5 db/watt; free air resonance is 55-70cps; voice coil impedance is 8 ohms. Size is 8" diam., 4 1/4" deep and requires 6 3/4" diam. baffle opening. Shpg. wt., 5 1/2 lbs.

SK-98 8" 2-WAY SPEAKER Net 9.95
2 FOR STEREO Net 18.95

NEW! 6 1/2" COAXIAL SK-97® HI-FI SPEAKER



- OVERALL RESPONSE 50-16,000 CPS.
- SPACE SAVING & ECONOMICAL FOR STEREO
- BUILT-IN LC NETWORK
- LARGE, HEAVY MAGNETS

6.95

An excellent speaker with all the best features of coaxial design, the SK-97 will provide the finest sound reproduction available from a speaker of this size. It is especially recommended where space and/or cost are factors. The 6 1/2" woofer is equipped with large, heavy magnet for maximum efficiency and low distortion. The 2" tweeter is a separate speaker coaxially mounted in a housing which completely seals off back radiation; a mesh dispersion screen provides smooth, wide-angle high frequency propagation. When properly enclosed, the response of this low cost hi-fi speaker is genuinely impressive. Its small size makes it perfect for use in a wide variety of small enclosures—ideal for use in pairs for stereo music systems of up to 8-10 watts. Frequency range, 50-16,000 cps. Woofer free-air resonance, 70 cps. Voice coil impedance, 8 ohms. Built-in electrical crossover network. Color-coded screw-type terminals. Requires 5 1/2" diam. cutout. Size is 6 1/2" diam., 3 3/4" deep. Shpg. wt., 3 1/2 lbs.

SK-97 6 1/2" COAXIAL SPEAKER Net 6.95
2 FOR STEREO Net 12.95

LAFAYETTE DUCTED-PORT BASS REFLEX SPEAKER ENCLOSURE



14.50

- ACCOMMODATES EITHER AN 8" OR 6" SPEAKER
- DUCTED PORT DESIGN FOR EXTENDED BASS RESPONSE
- ECONOMICAL AND SPACE-SAVING
- RECOMMENDED FOR STEREO

An acoustically engineered loudspeaker enclosure designed to provide full wide-range response when used with any 8" or 6" wide range or coaxial hi-fi speaker. Incorporates a special long duct over the usual bass-reflex port for performance equal to many enclosures of much greater size. Only 11 1/4" high, 18" wide and 9" deep—perfect for bookshelf, table top or other limited-space applications. Made of hardwood veneers throughout, hand-rubbed to a high finish, and lined with heavy acoustical padding. Available in Blonde Mahogany, Mahogany or Walnut finishes. (Please specify your choice.) Shpg. wt., 15 lbs.

GAB-29W Net 14.50


LAFAYETTE'S ULTRA-COMPLIANCE 2-WAY SPEAKER SYSTEM

VERY SMALL IN SPACE — LESS THAN 1 CU. FT.

Absolutely Gigantic in Performance!

17.50

- Frequency Response 40-16,000 cps
- Especially Designed Vented, Tuned Duct Type Enclosures
- Unique Mechanical 2-Way Speaker With Extra Heavy Magnet
- Enclosure Finished on 4 sides • Excellent For Stereo




FULL SIZE PERFORMANCE — This outstanding Lafayette Ultra-Compliance 2-way speaker system achieves a purity of sound and musical quality that is astounding from a speaker system occupying less than one cu. ft. of space. A perfect speaker for use anywhere in your home or office . . . makes ideal extension units or use in pairs for stereo.

The speaker features a unique dual cone with an extra heavy magnet structure, employed in a specially designed tuned ducted port enclosure. Both tweeter and woofer "float" on flexible, corrugated edges, with the outer edge of the tweeter cone attached to the mid-section of the woofer. This results in a mechanical crossover so that both cones operate in phase at low frequencies, but only the tweeter cone radiates high frequencies. The same type of wide-range frequency response is achieved that normally is found only in true coaxial or multiple speaker systems. Frequency response is 40-16,000 cps — Impedance: 8-16 ohms.

Available in rich mahogany or walnut. Finished on four sides — place it horizontally on its side or vertically on its base. Easily adapts to bookshelf placement or modular use. Dimensions are only 10 3/8" H x 18 1/2" L x 8 7/8" D. Shpg. wt., 15 lbs.

AVAILABLE IN MAHOGANY OR WALNUT (PLEASE SPECIFY)
Lafayette Ultra-Compliance 2-Way Speaker System
SK-124WX Net 17.50

Set of Two SPEAKER SYSTEMS FOR STEREO Net 34.00



LAFAYETTE L PADS

1.39

New L pads for use as "brilliance" controls to vary tweeter level, or as "presence" controls to vary mid-range speaker level. Both wirewound elements are concentrically mounted within one plastic housing. With gold-finished metal escutcheon plate, mtg screws, and attractive black knob. Size: 1 1/4" dia., 7/8" deep (less shaft), 2 1/2" deep overall. Shpg. wt., 6 oz.

VC-49—L pad for 8 ohm circuits Net 1.39
VC-90—L pad for 16 ohm circuits Net 1.39

STEREO LEVEL BALANCE CONTROL

- Dual Concentric 8 ohm L Pads
- Logarithmic Curve

2.89

Provides individual level control for stereo speakers. Varies "brilliance" or "presence" Controls stereo extensions without mismatching. Dual control mounted on concentric shaft. Gold-finished brass plate and attractive black knobs, with gold trimming. L pad for 8 ohm circuits. Plate is 2 1/4" across; overall depth 3 1/4". Shpg. wt., 10 oz.

VC-55 Level Control Net 2.89




STEREO RUMBLE FILTER

2.49

Filters out turntable vibration and rumble—makes every low-priced turntable and changer quiet and rumble-free. Designed for use with ceramic or magnetic cartridges. 3-position selector switch—ceramic, magnetic cartridge, off. Just plug it in between cartridge and amplifier inputs. Overall size: 5x2 3/4x3/4". Shpg. wt., 14 oz.

PK-444 Stereo Rumble Filter Net 2.49



GARRARD PRESSURE GAUGE

For accurately measuring tracking force. Large circular scale, transparent plastic window. Gauge reads 0-12 grams with 1/2 gram markings. Scale pan is of swiveling balance type. Measures pressure at the stylus and at the actual record level. Easy to operate. Comes with 5 gram brass weight for checking calibration.

GR-165 Garrard SPG3 Imported from England Net 2.95

DUST COVERS

Molded to the contours of the players from sparkling, clear vinyl, these covers provide complete protection from dust and accidents to the precision bearings, levers and tone arm. Shpg. wt., 1 1/2 lbs.

PK-531 Fits Model A Net 4.95
PK-560 Fits Model AT6 Net 4.95
PK-561 Fits Autolim Net 4.95
PK-529 Fits Model 210 Net 4.95
PK-530 Fits 88/11 and RC88 Net 4.95



PHONO-TUNER ADAPTER

2-phono jack inputs; simple switch selects either. A convenient phono output jack for connecting to amplifier. Includes mounting screws. Av. shpg. wt. for above units is 1 lb.

MS-795 Net .98

SPEAKER PHASING CONTROL

Allows you to reverse speaker connection to obtain correct phasing without disconnecting leads from speakers. A must for stereo. Complete with screw terminals and all mounting hardware. Shpg. wt., 1 lb.

MS-756 Speaker Phasing Control Net .98

STEREO-MONAUERAL-REVERSE SWITCH

Lets you switch instantly from stereo to monaural or reverses stereo channels. 2 phono jacks Input . . . 2 phono jacks output. Completely shielded, ready to mount with all hardware. Shpg. wt., 1 lb.

MS-757 Stereo-Monaural-Reverse Switch Net 1.29

MULTI-INPUT SELECTOR CONTROL

Connects any one of 5 inputs to 1 output AM, FM, phono, tape, aux. Completely shielded to prevent hum. Complete with mounting hardware. 5 phono jacks Input, 1 phono jack output. Shpg. wt., 1 lb.

MS-758 Multi Input Selector Net 1.76

REMOTE MICROPHONE VOLUME CONTROL

No more running to the P. A. amplifier to adjust volume when you are using a mike. Now, control volume output right at the microphone. Attached between the microphone and the cable, this completely shielded control has practically no insertion loss and induces no hum. Can be used at any desired distance.

Fitted on one end with a female mike Connector and male mike Connector on the opposite end. Finished in gleaming chrome, its appearance will blend in with the most expensive microphones. Comes completely ready to use. Shpg. wt., 12 oz.


MS-755 Remote Volume Control Net 1.76

BUILD-YOUR-OWN SPEAKER ENCLOSURES

EASY-TO-ASSEMBLE HI-FI ENCLOSURE KITS and COMPLETE SPEAKER SYSTEMS

LAFAYETTE UNIVERSAL HI-FI BASS REFLEX ENCLOSURE KITS

AT TREMENDOUS SAVINGS TO YOU!



A LAFAYETTE BEST BUY AT ONLY 29.95

NO MONEY DOWN

- EASIEST TO ASSEMBLE—ALL YOU NEED IS A SCREWDRIVER!
- 3/4" WHITE BIRCH
- PRECISION-CUT—FITS TOGETHER SMOOTHLY
- PERFECT FOR SINGLE WIDE RANGE, 2-WAY OR 3-WAY SPEAKER SYSTEMS
- HIGHBOY OR LOWBOY STYLE

All pieces of these carefully designed bass reflex high fidelity speaker enclosures are accurately pre-cut of 3/4" Plywood to fit snugly together and eliminate spurious resonances. Surface is white birch veneer. Front panels have picture-frame moulding and plastic acoustic grilles to blend with any finish and room decor. Tapered offset legs are protected by brass ferrules. Acoustic lining material prevents reverberation and cabinet resonance. Cutouts are provided for 15" speaker plus adapter for 12" 8 1/2" or 8" midrange plus adapter for 5" and blank wood block if no midrange speaker is used; cutout with adapter horn tweeters plus blank block if no tweeter used. Thus, any single wide-range 12" or 15" speaker may be used, or any Lafayette 2- or 3-way speaker system, or almost any other combination of speakers. Kits are supplied unfinished, smoothly sanded and ready for finishing. The lowboy-style cabinet dimensions are (less legs) 28 1/2" x 23 1/2" x 16 3/4" D; legs are 7" high. Highboy has same dimensions with height and width interchanged. Instructions, all parts, hardware, and grille are included. Shpg. wt., 5 1/2 lbs.

CK-10WX Unfinished Highboy Enclosure Kit Net 29.95
CK-11WX Unfinished Lowboy Enclosure Kit Net 29.95

LAFAYETTE OILED WALNUT FINISHING KIT

AT TREMENDOUS SAVINGS TO YOU!




2.69

Use this professional walnut oiling kit to achieve a beautiful oil finish on all unfinished walnut furniture. Materials are identical to those used by professional finishers; kit contains walnut oiling mixture, walnut paste wax, sandpaper and instructions. Shpg. wt., 2 lbs.

MS-592 Net 2.69

LAFAYETTE HI-FI SPEAKERS AT POCKETBOOK PRICES



SK-103 **11.95**

SK-138* **5.25**

12" THREE-WAY HI-FI SPEAKER


This new 3-way speaker answers the needs of many hi-fi enthusiasts. Featuring an 8 oz. dual-diameter magnet it has a frequency response of 35-17,500 cps. The elliptical tweeter gives improved sound dispersion over cylindrical types. Voice coil: diam-1 1/2". Impedance-8 Ω. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 6 1/2 lbs.

SK-103 Net 11.95

6" MID-RANGE SPEAKER

An excellent mid-range direct-radiator type speaker for installation in 3-way or 4-way speaker systems. Gives clean, distortion-free reproduction at rated power. Features closed back to eliminate interaction with sound waves generated from other speakers in the same enclosure. Rated power handling capacity: 10 watts. Frequency response from 700 to 7000 cps. Magnet weight: 3.16 oz. Voice coil impedance: 8 ohms. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 3 lbs.

SK-138* Net 5.25



SK-106 **4.95**

SK-93W* **8.75**

LAFAYETTE 8" EXTENDED RANGE SPEAKER

- 45 to 13,000 cps
- SKIVER ROLLED CONE FOR SMOOTH RESPONSE
- 3.16 DZ. NEW TYPE MAGNET


Here is a price buster for the budget-wise hi-fi music lover. This is an extended range domestic speaker whose high sensitivity is achieved through a new hi-efficiency magnetic circuit. Ideally suited for medium and low level monaural or stereo reproduction. It has a 1" voice coil with 8 ohms impedance and will handle musical peaks of 10 watts. Size: O.D. 8 1/2"; Mtg. hole dimensions 7 1/4"; 3 1/2" deep; Brown enamel over heavily plated steel. 4-way binding posts. Shpg. wt., 2 lbs.

SK-106 Net 4.95

12" COAXIAL HI-FI SPEAKER

12" Alnico V PM with 1" voice coil and heavy one-piece cone. Specially designed 3" Alnico V PM tweeter completes this combination speaker. Range 40 to 15,000 cps. Built-in high pass filter. Power rating: 12 watts. 6.8 ohm. Alnico V magnet. Impedance 8 ohms. Shpg. wt., 8 lbs.

SK-93W* Net 8.75



SK-69 **6.25**

SK-164 **10.95**

8" HI-FI WIDE RANGE SPEAKER

50-13,000 CPS

Answers the need for a good quality but moderately priced speaker with a range of 50-13,000 cycles. An extremely smooth single cone reproducer — ideally suited for Hi-Fi systems. Excellent for limited space — good overall balance — power handling capacity: 10 watts — 6.8 ohm. Alnico V magnet — frequency response: 50-13,000 CPS when properly baffled. Rim treatment on cone minimizes possibility of diaphragm distortion. Voice coil impedance: 8 ohms. Cone Resonance 85 cycles. Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 4 lbs.

SK-69 Net 6.25

LAFAYETTE 8" WOOFER

- Rated 20 watts • Free edge cone
- 14.7 oz. alnico V magnet
- High Compliance • 35 to 7500 cps

Ideal for 2 or 3 way systems where space is at a premium, this 8" woofer provides coverage from 35 to 7500 cps. The 14.7 oz. magnet is extraordinarily heavy for this size speaker insuring the efficiency needed for good clean response. Other features include free edge, high compliance cone, 20 watt power dissipation, voice coil dust cover. Cone resonance 50 cycles, 8 ohm V.C. Has 4-way binding posts. Shpg. wt., 4 1/2 lbs.

SK-164 Net 10.95

8" MID-RANGE SPEAKER

Ideal for use with tweeter and crossover networks to make up a 2- or 3-way system. This 8" mid-range speaker is capable of producing undistorted response down to 350 cps, the crossover frequency. Back is enclosed. Power handling capacity: 25 watts. Frequency response 350-13,500 cycles. Recommended to crossover at 5000 cycles to a tweeter. Cone resonance 150 cycles. Impedance: 8 ohms. Plated steel framed finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 4 lbs.


SK-74 Net 6.50



Famous 3-WAY SYSTEM

LAFAYETTE — BEST BUY 3-WAY SYSTEM

with 15" WOOFER... 8" MID-RANGE SPEAKER... HORN TWEETER... CROSSOVER NETWORK



55.50 NO MONEY DOWN

- 15-INCH WOOFER WITH 31.5 OZ. MAGNET (SK-67W)
- 8-INCH MID-RANGE SPEAKER (SK-74W)
- NEW HIGH-FREQUENCY ACOUSTICAL LENS TWEETER (HW-7)
- 3-WAY CROSSOVER NETWORK (LN-5)

EXPLODED VIEW SHOWS HOW SYSTEMS MOUNT IN CABINET

CABINET NOT INCLUDED

Lafayette presents this outstanding 3-way speaker system designed for the high fidelity enthusiast who desires performance formerly possible in multi-speaker systems costing many times this price. You won't believe your ears when you hear the superb reproduction throughout the entire audio spectrum. The SK-67W 15" woofer provides phenomenal bass response, the SK-74W 8" speaker delivers full bodied, mid-range frequencies,

and the HW-7 high frequency acoustical lens tweeter faithfully reproduces the highest audible frequencies. Crossover points at 350 and 5000 cycles are provided by the LN-5 3-way inductance-capacitance network with continuously variable presence and brilliance controls that adjust tone balance to personal taste. Shpg. wt., 25 lbs.

SY-93WX Complete system as listed above Net 55.50

LAFAYETTE'S Amazing New! MINI-DUCT

A universal ducted-port bookshelf enclosure engineered for use with 1, 2 or 3-way speaker systems.

SOLIDLY CONSTRUCTED OF 3/4" WOODS START WITH A SINGLE SPEAKER AND BUILD INTO A 2- OR 3-WAY SYSTEM LATER ACOUSTICALLY LINED THROUGHOUT AVAILABLE IN A VARIETY OF FINISHES

23.50
NO MONEY DOWN



Now limited space need not necessarily mean limited sound. The Lafayette Mini-Duct is acoustically designed to achieve smooth, distortion-free reproduction with a remarkably full, clean extended bass response that gives no indication as to its small size. Reducing boards are supplied so that the Mini-Duct will accept an 8" Woofer, 6" Mid-Range and a variety of tweeters. This versatility makes it possible to start with an 8" speaker and eventually build into a 2-way or 3-way speaker system. Solidly constructed of 3/4" woods the Mini-Duct is beautifully finished in a variety of fine veneers on 3 sides. Designed for attractive placement anywhere in your home with dimensions 23Wx11 1/2Hx11 1/2D. Shpg. wt., 23 1/2 lbs.

CAB-47WX MINI-DUCT IN WALNUT	Net 23.50
CAB-48WX MINI-DUCT IN MAHOGANY	Net 23.50
CAB-49WX MINI-DUCT IN BLONDE	Net 23.50
CAB-50WX MINI-DUCT IN OILED WALNUT	Net 23.50
CAB-51WX MINI-DUCT UNFINISHED BIRCH	Net 21.50
Mini-Duct Enclosure finished on 4 sides for attractive horizontal or vertical placement. Choice of mahogany or walnut.	
CAB-105WX Mahogany	Net 24.95
CAB-106WX Walnut	Net 24.95

SPEAKER AND ENCLOSURE COMBINATIONS

A PERFECT COMBINATION: The "Mini-Duct" enclosure and the famous Lafayette SK-98 8" mechanical 2-way speaker with patented dual cone construction. This speaker combined with the Lafayette "Mini-Duct" enclosure will give the same wide-range frequency response (40-16,000 cps) normally found only in the coaxial speakers or multiple speaker systems. Shpg. wt., 29 1/2 lbs.

COMBINATION UNFINISHED "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-348WX	Net 31.25
COMBINATION MAHOGANY "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-349WX	Net 33.25
COMBINATION WALNUT "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-350WX	Net 33.25
COMBINATION OILED WALNUT "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-351WX	Net 33.25
COMBINATION BLONDE "MINI-DUCT" ENCLOSURE WITH SK-98 SPEAKER SY-352WX	Net 33.25

SK-98 SPEAKER AND MINI-DUCT FINISHED ON 4 SIDES

SY-377WX MAHOGANY	Net 34.25
SY-378WX WALNUT	Net 34.25



MINI-DUCT BOOKSHELF ENCLOSURE

Mounting boards accept all types of tweeters

33.25
NO MONEY DOWN



SK-98

WE'LL SEND YOUR GIFT TO ANY PART OF THE WORLD

Lafayette Catalog No. 621 Page 23

NEW! LAFAYETTE 4 TRANSISTOR PORTABLE TAPE RECORDER with BUILT IN SPEAKER



NO MONEY DOWN

29.95

4-TRANSISTOR TAPE RECORDER

Complete with TELEPHONE PICK-UP, EARPHONE, PATCH CORD, MICROPHONE, 3" REEL OF TAPE, EMPTY REEL, BATTERIES

- Camera Size—Only 6"Dx8 1/4"Wx2 3/4"H.
- Weighs a Mere 2 1/2 lbs.
- Fully Transistorized
- Records and Plays Up To 20 Minutes with 1 Standard 3" Reel
- Built-in Speaker and 4-Transistor Amplifier With Push-Pull Output
- Record, Rewind, Playback and Erase
- Powered By 3 Inexpensive Batteries
- 1/2 Track Head Provides Maximum Tape Economy

This is a precision, full function miniature tape recorder perfect for home, office or travel; weighs only 2 1/2 lbs. and slips easily into a briefcase or handbag. Utilizing sophisticated transistor circuitry with 4 transistors, the RK-125AL contains its own 2" x 3" PM speaker and amplifier with push-pull output stage. Engineered for ease of operation, with all controls readily accessible from the front panel. A single function control provides for Rewind, Stop and Forward with a second control furnishing variable Volume. Play or Record functions are chosen by a simple slide switch. In addition microphone and earphone jacks are located on front panel. Designed for maximum tape economy the RK-125 employs a half track tape head—upper half is recorded first and tape is turned over to record on lower half... records and plays up to 20 minutes on a 300 ft. 1/2 mil 3 inch reel of tape.

The attractive two-tone plastic and metal case features a carrying handle and snap open top for fast, easy tape loading. Power is supplied by 2 standard 1.5v flashlight cells and one 9v transistor battery. Complete with crystal lapel microphone, magnetic earphone, batteries, 100 ft. 3" reel of tape and an empty reel. Measures only 6Dx8 1/4Wx2 3/4"H. Shpg. wt., 5 lbs.

RK-125AL	Net 29.95
RT-20 3" REEL 300 Ft. 1/2 MIL MYLAR TAPE. Shpg. wt., 1/4 lb.	Net .89
BA-2 9V TRANSISTOR BATTERY. Shpg. wt., 2 oz.	Net .39
BA-156 1.5V BATTERY (2 required). Shpg. wt., 2 oz.	Net .13

ROBERTS "990" STEREO TAPE RECORDER



RT-10 (30 Reels)

PA-263

MS-474

12 Tape Cans and Storage Chest

399.50
NO MONEY DOWN

4-Track Stereo Record,
2-Track & 4-Track
Stereo Playback

A fully self-contained portable stereo tape recorder that offers professional capability and versatility. Use in conjunction with your stereo system as a tape deck or as a portable with its own twin monitor speakers and stereo amplifier. The exclusive Roberts multiple adjustment head allows instant selection of all recording and reproducing functions. Precisely aligns 1/4 track recording and playback heads for 4-track monaural record play. Frequency response: 40-15,000 cps at 3 3/4" ± 3 db. Wow and flutter: less than 0.12%. RMS. Signal to noise ratio: —50 db. Record Inputs: 2 high impedance inputs; 2 high level line inputs. Outputs: Head outputs from each channel. Operates in both vertical or horizontal positions and employs a new hysteresis-synchronous motor. Features dual VU Meters, accurate tape index counter and interlocking controls. For 105 to 120 volts; 60 cycles. Size: 20x14x9". Shpg. wt., 50 lbs.

RK-389WX

Net 399.50

COMPLETE "990" STEREO TAPE RECORDER SYSTEM

ONLY **429.50** YOU SAVE 46.42
NO MONEY DOWN

Complete system consists of: Roberts "990" Stereo Tape Recorder; 30 Reels of Lafayette RT-10 1200' 7" Recording Tape. 1 Lafayette PA-263 Stereophonic Recording Dynamic Microphone with base and cable; MS-474 Edital Tape Splicing Kit, plus 12 Tape Cans and Tape Storage Chest.

RKS-10WX

Net 429.50

NEW! LAFAYETTE DELUXE DUAL SPEED TAPE RECORDER MODEL RK-130

- Two Speeds 3 3/4 and 7 1/2 I.P.S.
- Plays Both 7" and 5" Reels
- Built-in Speaker and Amplifier
- Complete with Dynamic Microphone

TWO SPEEDS
3 3/4
and
7 1/2 IPS

NO MONEY DOWN

89.95


The perfect companion for language work, voice and instrument study, personal and family use, office work—a worthwhile investment for any classroom. This rugged tape recorder plays both 7" and 5" reels at speeds of 3 3/4 and 7 1/2 inches per second. Consists of a double track, high frequency bias recording system with a frequency response range of 80 to 10,000 cycles, and a high frequency erase system. Internal amplifier provides 1.5 watts audio output to a built-in 4 3/4" speaker. An additional speaker may be plugged into the output jack. The RK-130 features simplicity of operation for quick stopping, playing, recording, fast forward winding or rewinding. Two input jacks are provided to permit simultaneous recording from a radio or record player and a microphone. Dynamic microphone is included with the unit. Both volume and tone are adjustable, and a neon tube recording level indicator is provided to facilitate correct settings. A switch allows the user to hear the playback either through the speaker or through a set of headphones (not supplied). A 7" tape reel played on both tracks will last for 120 minutes at 3 3/4 i.p.s., or for 60 minutes at 7 1/2 i.p.s. A 5" reel will last 60 minutes at 3 3/4 i.p.s., or 30 minutes at 7 1/2 i.p.s. Internal amplifier tube complement: 1—12AD7, 1—6BM8, 1—6AR5, plus 1—6X4 rectifier. For 117 VAC, 50-60 cps. Recorder dimensions: 16.4x12.4x8". Complete with 7" empty reel, dynamic microphone, patch cord, instructions, and large, removable strap for easy carrying. Shpg. wt., 28 lbs.

RK-130WX	Net 89.95
7" reel with 1200 ft. of recording tape. Shpg. wt., 1 lb.	Net 1.59
RT-10	Net 1.59



NEW! RK-116WX 4-TRACK STEREO TAPE RECORDER

- Professional Quality Laminated Record/Playback Heads
- Records Sound-On-Sound
- 5-Watt Hi-Fi Quality Amplifier
- Electromatic Remote Control
- Response 40-15,000 cps
- 7 1/2 & 3 3/4 ips



149.50 NO MONEY DOWN

Performance and value make this a best buy in stereo tape recorders. Designed for stereo record and playback when used with the RK-117. Speaker/Amplifier as well as monaural record/playback when used singly. Features include special mu-metal shielded professional type laminated record/playback heads; beltless drive mechanism, magic-eye recording level indicator, electromatic remote control plus self-contained 5 watt amplifier and speaker. Frequency Response: 40-15,000 cps at 7 1/2 ips, 40-10,000 cps at 3 3/4 ips. Wow & Flutter less than .20% at 7 1/2 ips. Controls: Dual type volume control allows adjusting recording and playback level individually for left and right channels and tone control. Accepts up to 7" reel of tape. Complete with dynamic microphone, recording patch cord, monitoring earphone and attractive vinyl covered Philippine mahogany carrying case. For 60 cycles—110-120 volts AC. Shpg. wt., 26 lbs.

RK-116WX Net 149.50

COMPANION RK-117WX SPEAKER/AMPLIFIER



Identical in appearance to the RK-116. Contains its own 5-watt power amplifier and speaker to operate as a second channel power amplifier and speaker for the RK-116. Also functions as a second channel recording amplifier for making live stereo recordings or recording directly from radio or stereo records. For 60 cycles 110-120 volts AC. Shpg. wt., 12 lbs.

RK-117WX Net 59.00

NEW! RK-119WX PROFESSIONAL STEREO TAPE RECORDER



349.50

NO MONEY DOWN

- Contains 3 Separate Heads—Stereo Erase, 4-Track Stereo Record, 2-Track & 4-Track Stereo Playback
- Sound-On-Sound Recording
- Push-Button Controls
- Individual Tone & Volume Controls For Each Channel
- 3 Speeds—1 1/2 ips, 3 3/4 ips & 7 1/2 ips.
- Two 7" Speakers For Stereo

One of the finest tape recorders Lafayette has ever offered. A completely self contained portable stereo high fidelity music recording and playback system which may be used with its own speakers and amplifiers or through the amplifiers and speakers of your present music system. Employs 3 professional quality, laminated tape heads—stereo erase, 4-track stereo record, 2-track and 4-track stereo playback. Features include: sound-on-sound recording, push-button controls, individual recording level controls with VU recording level meters for each channel, separate tone and volume controls for each channel, master volume control and digital tape counter. Mechanism automatically stops at reel end. Interlocked recording controls prevent accidental erasure. Specifications: Tape Speeds: 1 1/2 ips, 3 3/4 ips, 7 1/2 ips; Frequency Response: 7 1/2 ips—30-20,000 cps, 3 3/4 ips—30-15,000 cps, 1 1/2 ips—50-8,000 cps; Signal to noise ratio: Better than 60 db. Flutter and wow: less than .15% at 7 1/2 ips. Output Level: 10 watts (5 watts each channel). Reel Size: 7" maximum. Supplied with the following accessories: 2 professional type sensitive dynamic microphones with stands, specially balanced for stereo recording, 2 recording patchcords, 1 patchcord for sound-on-sound recording, 1 speaker ext. patchcord for right channel ext. speaker, 1 7" empty reel, 1" roll of splicing tape. The attractively styled vinyl covered carrying case is ruggedly constructed of Philippine mahogany and incorporates the 2nd channel stereo speaker in the snap-off cover. 19 1/2 x 11 1/2 x 7" O. Shpg. wt., 50 lbs.

RK-119WX Net 349.50

LAFAYETTE COMBINATION SPECIAL!

The RK-116WX and RK-117WX combined to make a complete stereo portable tape system and to save you money at this special combination price.

SP-247WX Net 199.50

SAVE 9.00

CONTINENTAL '400' 4 TRACK STEREO RECORDER



289.95
NO MONEY DOWN

The new "400" model stereo tape recorder, guild-crafted by Philips of the Netherlands, reflects professional quality at a modest price. It is a recorder that was designed to be used and listened to by the music-lover, studio-recordingist, and high fidelity enthusiast. Four track stereophonic recording and playback with dual stacked heads plus 4 track monophonic operation. Three tape speeds: 7 1/2, 3 3/4, and 1 1/2 ips. FREQUENCY RESPONSE: 60-18,000 cps at 7 1/2 ips, 50-14,000 cps at 3 3/4 ips, 50-7,000 cps at 1 1/2 ips. Signal-to-Noise ratio 55 db or below. Cross-talk 55 db down. Instantaneous locking device for pauses in recording or listening. Wow and flutter less than 0.3% at 3 3/4 ips. Dubbing facilities for producing sound-on-sound. Self-contained record and playback amplifiers including dual hi-fi preamps. SPECIAL CONTROLS: For recording—ganged mike volume, and ganged radio/phone volume. For playback—2 channel tone (individual concentric controls but friction ganged); ganged volume and ganged channel balance. INPUTS: One 2-channel input for stereo microphone; two 2-channel inputs for stereo tuners or phonos. OUTPUTS: For extension speakers (2); for external amplifiers (2); for stereo headphones (1). MIXING CONTROL for electronic mixing of phono and mike inputs. TUBES—2-EF86, 3-ECC83, 2-EL84, 1-EM84. For 117 volts, 60 cps. AC. Size: 18 1/2 x 15 1/2 x 11 1/2". Includes a Norelco professional fidelity, dual element dynamic microphone for both stereo and monaural recording. Shpg. wt., 55 lbs.

RK-398WX Net 289.95

Sensational LAFAYETTE HI-FI TAPE SYSTEM SALE!

NEW! SONY PROFESSIONAL TRANSISTORIZED STERECORDER MODEL 777 With "Electro Bi-Lateral Heads"

725.00 NO MONEY DOWN



This exceptional tape deck promises to set a new standard in construction and performance. Engineered to meet the requirements of both the professional and consumer, the 777 provides complete facilities to record and playback both 1/2 track and 3/4 track stereo. Newly developed Electro Bi-Lateral heads combine individual 1/2 track and 3/4 track stereo head laminations into one head, completely shielded and isolated from each other. Erase, record and play heads are similarly constructed providing the equivalent of 6 stereo heads without any track width or alignment compromise. Four printed transistorized modular circuit boards comprise the entire electronic circuitry. Drive, supply and takeup functions are provided by 3 precision hysteresis synchronous motors. Frequency response: ± 2 db—30-20,000 cps @ 15 ips, 50-16,000 cps @ 7 1/2 ips, 60-10,000 cps @ 3 3/4 ips. Signal to Noise Ratio: 52 db. Flutter & Wow: less than 0.1 fms. Other features are: piano key push button controls, sound on sound recording, record and play monitoring, VU meters, separate damped rewind and playback level controls for each channel, digital tape counter, automatic tape lifters, inputs and output for every convenient tape deck function. Size: 16Wx17 3/4Hx9"D. For 117 volts, 60 cycles AC. Includes push-button remote control. Shpg. wt., 46 lbs. RK-285WX Net 725.00

COMPLETE TAPE RECORDER SYSTEM

745.25 YOU SAVE **75.56**
NO MONEY DOWN


System includes Sony Model 777 Professional 2 and 4 track Stereo Tape Recorder; 1-Lafayette Model ML-120 Professional Bulk Tape Eraser; 10 reels of Lafayette RT-12 1800 ft., 7" 1 mil Mylar tape; 12 reels Lafayette RT-13 2400 ft., 7" 1/2" Mylar tape; 12 Dustproof Tape Storage Cans with convenient Storage Chest and the Lafayette MS-474 Edital Professional Tape Splicing Kit consisting of cutting block, grease pencil and splicing tape with instruction booklet.

RKS-12WX Net 745.25

ROBERTS "1040" STEREO TAPE RECORDER

RECORDS NEW FM MULTIPLEX STEREOCASTS

299.50 NO MONEY DOWN



A compact self contained stereo tape recorder that offers the most advanced tape deck features and professional performance. Operates horizontally or vertically, through two stereo speakers and two amplifiers or through your existing components. Designed to provide 4-track stereo and monaural record/play, 2-track stereo and monaural playback, sound on sound record, and record facilities for the new FM multiplex stereo casts. Interlocking controls prevent accidental erasure of tape in rewind or fast forward. Other features include: push button function switches, professional edit lever, automatic shutoff, Index counter, dual concentric volume and tone knobs with clutch controlled balance, professional VU meter with channel switch. Record inputs: 2 high impedance mic inputs, 2 high impedance high level line inputs. Playback Outputs: 2 high impedance outputs independent of volume control for connection to any stereo hi-fi amps; two 8-ohm outputs for external speakers or headphones. Frequency Response: 40-15,000 cps at 7 1/2 ips. ± 2 db. 35-11,000 cps at 3 3/4 ips. ± 3 db. Signal to Noise Ratio: -42 db. Wow and Flutter: less than 0.18%. Accepts up to 7" reels. Size: 15 1/4x10 1/4x13 3/4". Shpg. wt., 30 lbs. For 105-125 volts 60 cycles AC. RK-390WX Net 299.50

COMPLETE ROBERTS TAPE RECORDER SYSTEM

324.95 YOU SAVE **32.22**
NO MONEY DOWN

Complete System consists of: Roberts 1040 2 and 4 track Complete Stereo Tape Recorder; 30 reels Lafayette RT-10 1200' 7" Recording Tape; 12 Dustproof Tape Storage Cans with Convenient Storage Chest; 1 MS-474 Edital Professional Tape Splicing Kit with instruction booklet. RKS-11WX Net 324.95

SONY STEREO HI-FI TAPE SYSTEM

MODEL CS-300 STEREO RECORDER

391.50
NO MONEY DOWN

A complete 4 and 2 track stereo tape recording and playback system with built-in stereo preamps, stereo recording amps, stereo playback monitor amps, dual stereo speakers and two dynamic microphones. Recording and playback also for 2 and 4 track monophonic tapes. 2 speeds—7 1/2 and 3 3/4 ips. 2 built-in VU meters insure accurate playback and record levels. Hysteresis-synchronous drive motor. INPUTS: stereo or monophonic 2 and 4 track recording from 2 or more microphones, AM/FM stereo tuners, stereo record players and tape players. Separate level controls for microphone and auxiliary inputs provide mixing facilities for sound-on-sound recordings. Low impedance outputs to match external preamp or power amp inputs. Instant Stop Lever insures precise editing and cueing. Safety Lock Recording Button prevents accidental erasure of pre-recorded tape. Specs: Freq. Resp: 30-18,000 cps at 7 1/2 ips; 30-13,000 cps at 3 3/4 ips. Signal-to-Noise Ratio 50 db or more per channel. Low distortion. Size: 17x14x8" high. 117V, 60 cps AC. Includes carrying case. Shpg. wt., 42 lbs. RK-280WX Net 391.50

Model DK-300 Same as CS-300 but without carrying case, speakers, and microphones. Shpg. wt., 35 lbs. RK-281WX Net 342.51

COMPLETE CS-300 TAPE RECORDER SYSTEM

407.95 YOU SAVE **56.95**
NO MONEY DOWN

Complete System consists of: Sony CS-300 Stereo Tape Recorder with carrying case and 2 dynamic mikes; 1 ML-120 professional bulk tape eraser; 12 reels Lafayette RT-13 2400 ft., 7" Mylar recording tape; 12 Dustproof Tape Storage Cans with convenient Storage Chest and the Lafayette MS-474 Edital Professional Splicing Kit. RSK-13WX Net 407.95



SONY MODEL 262-SL 4-TRACK STEREO RECORDER

195.50
NO MONEY DOWN

A stereo tape recorder with 4 and 2 track stereo playback plus 4-track monaural record facilities. Built-in monophonic preamp, recording amp and monitor power amp. Also second channel playback preamp. Sound-on-Sound recording for language and music training. Instantaneous selection of 7 1/2 or 3 3/4 ips tape speed. Features include record level indicator, tone control, level control for record and playback digital tape counter and safety lock record button. Inputs facilities furnished for Mic, Radio/Aux with outputs for Ext. Speaker and Preamp. Freq. Resp.: ± 2 db 50-15,000 at 7 1/2 ips. With portable case, earphone, monitor speaker, dynamic microphone and connecting leads. RK-283WX Net 195.50

COMPLETE TAPE SYSTEM

207.95 YOU SAVE **31.12**
NO MONEY DOWN

System consists of Sony Model 262-SL, 2 Speed Recorder with case, earphone and dynamic mike; 20 reels of Lafayette RT-10 1200' 7" Recording Tape; 12 dustproof tape storage cans with convenient storage chest; Lafayette MS-474 Edital Professional Splicing kit. RKS-14WX Net 207.95



NEW! VIKING MODEL 86 "STEREO COMPACT" TAPE DECKS

297.50
NO MONEY DOWN

Renown Viking 1/4 transport mechanism has been combined with a stereo/playback preamplifier of advanced design. System recording range of 30-16,000 cps is achieved with little roll-off. For minimum spurious noise when recording FM multiplex transmissions the 86 Compact employs a sharp cut-off filter to prevent beating of bias frequency with 38 Kc multiplex carrier frequency. Other Features: "Erase-Protek" recording interlock; monaural-stereo selector switch; automatic equalization for both 3 3/4 and 7 1/2 ips speeds; variable playback preamplification and "sound on sound" function without patching. Incorporates separate calibrated VU meters, digital tape counter and head shift control. Frequency response 30-16,000 cps ± 3 db. NAB standard equalization for 3 3/4 and 7 1/2 ips. Microphone and tape head inputs on front panel; high level input on rear panel. Stereo in-line heads of laminated core construction. Multiplex heterodyne trap attenuates 12 db/octave above 20 Kc. Flutter and wow less than 0.2%. Viking Flutter — Filter Capstan belt drive. Size: 13x13x9 1/2" deep. (fits 12 1/2x12 1/2" opening). Requires 110-115 v. 60 cycle AC @ 125 watts. "STEREO-COMPACT" RMQ. Records, erases and plays back 1/4 track stereo and monaural plus 1/4 & 1/2 track stereo playback. Anodized Aluminum. Shpg. wt., 25 lbs. RK-258WX Net 297.50

"STEREO-COMPACT" ESQ. Records, erases and plays back 1/2 track stereo and monaural plus 1/4 & 1/2 track stereo playback. Anodized Aluminum. Shpg. wt., 25 lbs. RK-257WX Net 297.50

COMPLETE TAPE RECORDER SYSTEM

327.95 YOU SAVE **26.60**
NO MONEY DOWN

System includes Viking 86 Stereo Compact Model RMQ; New Lafayette PA-263 Stereo Dynamic Microphone with desk base and cable; 17 reels of RT-10 1200 ft., 7 inch Recording tape; 12 dustproof Tape Storage Cans with convenient chest storage and MS-474 Edital Professional Tape Splicing Kit. RKS-15WX Net 327.95



SONY MODEL 262-D TAPE DECK



- 4-Track Stereo Record/Playback & Erase Heads
- 7 1/2 & 3 3/4 ips Tape Speeds
- 30-18,000 cps Response
- Full 7" Diam. Reel Capacity

87.70
NO MONEY DOWN

High quality, precision engineering and construction at a truly economical price make this unit an unbeatable value. Provides for every tape facility—Tape heads are wired to six outputs. With your present stereo amplifier you can play back 4 track stereo tapes or by adding a recording amplifier, make your own 4-track tapes. A 4-track stereo erase head is included. Features include Instantaneous selection of 7 1/2 or 3 3/4 ips tape speeds; instant stop lever; safety lock record button, automatic tape lifter and a digital counter. Freq. Response from 30-18,000 cps at 7 1/2 ips, ± 2 db 50-15,000 @ 7 1/2 ips and ± 2 db 50-12,000 @ 3 3/4 ips. For 110-117 VAC operation. Size: 13Wx10Dx5 1/4"H. Shpg. wt., 15 lbs. RK-262WX Net 87.70

Attractive Walnut Base for Sony 262-D described above. RK-284W Net 15.95

Model SRA-2 Stereo Recording Amplifier designed for Sony 262-D. RK-287WX Net 89.50



LAFAYETTE TOP QUALITY RECORDING TAPE

LAFAYETTE RECORDING TAPES

LAFAYETTE QUALITY IS BACKED BY OUR MONEY-BACK GUARANTEE



LAFAYETTE'S FAMOUS MONEY-BACK GUARANTEE

Lafayette's tape is made by outstanding nationally known manufacturers. It is first quality, splice free, red oxide coated, with full frequency response, uniform output and no "drop-outs". Resistant to moisture, heat, cold and abrasion. We guarantee absolute satisfaction or your money back. If you do not find it equal to tapes costing up to twice the price, if for any reason you are dissatisfied, return the tape in 30 days and we will refund your money. You are the sole judge.

LAFAYETTE MYLAR BASE RECORDING TAPE

AS LOW AS **1.42** RT-19 900 ft. 25 & up

Mylar base is especially strong, durable and break resistant, and is virtually impervious to heat, cold or humidity. All in clear plastic reels, individually boxed.

Stock No.	Feet	Reel	Mils	WL Lbs.	1-4	5-24	25 Up
RT-19	900	5"	1 3/4	1.75	1.58	1.42	
RT-12	1800	7"	1 1/4	2.50	2.25	2.13	
RT-13	2400	7"	1/2	3.69	3.39	3.22	

Tensitized Mylar
Prestretched, super-strong mylar base.

Stock No.	Feet	Reel	Mils	WL Lbs.	1-4	5-24	25 Up
RT-16	2400	7"	3/4	4.95	4.45	4.23	

3" REEL 300-ft. 1/2 mil Mylar tape. AS **.63**
Shpg. wt., 1/2 lb.

RT-20 Net ea. 1-4, .69; 5-24, .63

YOU BE THE JUDGE!

LAFAYETTE ACETATE BASE RECORDING TAPE

AS LOW AS **85¢** RT-17 600 ft. 25 & up

Acetate base magnetic recording tape with uniform standard red oxide coating provides wide range high fidelity response over the audio spectrum. Features noise free reproduction, low abrasion and uniform output. In 1 mil and 1 1/2 mil thickness.

Stock No.	Feet	Reel	Mils	Wt. Lbs.	1-4	5-24	25 Up
RT-17	600	5"	1 1/2	1/2	.99	.90	.85
RT-18	900	5"	1	3/4	1.35	1.20	1.08
RT-10	1200	7"	1 1/2	1	1.59	1.49	1.35
RT-11	1800	7"	1	1 1/4	1.98	1.88	1.79

LAFAYETTE BULK TAPE ERASER AND DEMAGNETIZER

PROFESSIONAL MODEL

- Erases 1/4" Tapes In One Operation — No Reversing
- For 3", 5", 7" or 10 1/2" Reels
- Completely Erases Tapes
- Two Erasing Coils
- Erases up to 1" Tape

18.95




A carefully designed and precisely manufactured tape "degausser" for complete erasing of tapes. Just place the tape reel on spindle of demagnetizer, slowly rotate 2 or 3 turns, take off, and that's all. Reduce tape hiss to the level of new "virgin" tape. Two completely separate coils are used for doubly-effective erasures, even of large, 10 1/2" reels. Will erase 1" wide tape. An extra powerful unit for heavy-duty use—draws over 9 amperes. Can be used to demagnetize tape, magnetically stripped film, plus tools and watches. Has a heavy, custom finished case, a rugged non-magnetic top, heavy duty on-off switch and power cord. Has built-in fuse. Pilot light prevents accidentally leaving it turned on. Size 6 1/4 x 7 1/2 x 3 1/2". Shpg. wt., 14 lbs.

ML-120 Net 18.95

STANDARD MODEL

- Takes Reels Up To 10 1/2"
- Reduces Noise Level
- Top Value

12.50




A bulk tape demagnetizer that erases existing recorded signals and noise from magnetic tapes quickly and efficiently. Also capable of demagnetizing metal parts and work tools. Ideal for the recording enthusiast desiring clean, noise-free tapes. Simply rotate reel of tape several turns over unit, turn over and repeat once. Has two spindle positions: Inner position for tape reel sizes up to 7" in diameter, and the outer one for 10 1/2" reels. Push button energizes the coil, and a pilot light installed on top of the unit indicates unit in operation. Non-magnetic bakelite plate for tape reel rest. One powerful coil is used for effective erasure of all quarter-inch tapes. Current consumption—5 amps. Heavy duty, rugged gauge metal case. Attractive finish. For 105-125 volts, 60 cycles. Size 7 1/2 x 4 3/4 x 3 1/2". Shpg. wt., 9 lbs.

ML-176 Net 12.50

BUY 12 TWIST LOCK TAPE CANS

NEW! FOR ONLY 4.95

AND GET STORAGE CHEST FREE!



12 dust-free, moisture-proof unbreakable styrene tape cans in storage chest. Can has foolproof twist lock feature and is ribbed for convenient stacking. Center locking stud prevents reel movement on all 7" reels and most 3" and 5" reels. Shpg. wt., 6 lbs.

ML-302 Net 4.95

TWIST LOCK CANS ONLY
ML-151 Lots of 6 ea. .45; Single ea. .49

NEW! Lafayette RECORD, PLAYBACK and ERASE HEADS

3.95 per set



- Ideal for Experimenters
- Half-Track Recording Playback and Erase

A Lafayette special—ideal for the experimenter interested in tape recorders. Recording head has impedance of 9K ohm at 1,000 cps, DC resistance 130 ohms, reproduction level — 40, recording at — 10db. Bias frequency 30KC, bias 10MA. Frequency 60-12,000 cps ± 5db. SN ratio — 40db. Erasing head: DC resistance 10 ohms, erasing current 15-20 milliam. AC bias, DC erase systems. Record head 7/8 x 3/4 x 3/4"; erase head 3/8 x 1 x 3/8". Shpg. wt., 8 oz.

F-687 Net 3.95

LAFAYETTE TAPE HEAD DEMAGNETIZER

3.95 • REMOVABLE POLEPIECES • EXTRA CONVENIENT

Lafayette Tape Head Demagnetizer uses removable polepieces. Three complete sets are furnished: straight, 45° and 90° (right angle), permitting quick and easy use with any tape head. Far from being a luxury, a tape head demagnetizer is necessary for best tape recorder performance. Although unmagnetized when new, tape heads gradually become magnetized by sharp switching pulses occurring while switching the recorder from play to record or vice versa. The solution is to use a demagnetizer to remove this permanent magnetism from the head, thus reducing the noise level. Periodic head demagnetization is required for all tape recorders to insure optimum signal-to-noise ratio. Now Lafayette enables anyone with even the most modest budget to perform this necessary demagnetization with a minimum of effort. For 110 volts 60 cycles. Shpg. wt., 1 lb.

PK-238 Tape Head Demagnetizer 3.95

CLEAR PLASTIC REELS

.26

IN LOTS OF 6

Individually boxed plastic reels for recording tape. Av. shpg. wt., 4 oz. singly.
MS-692 5" reel. In lots of 6, Ea. .26 Singly, Ea. .29
MS-267 7" reel. In lots of 6, Ea. .38 Singly, Ea. .45



LAFAYETTE SPECIAL

3.95 per set



RECORD PLAYBACK and ERASE HEADS for MINIATURE TRANSISTORIZED TAPE RECORDERS

A two-piece set consisting of one record/playback and one erase tape head. Designed for use in dual track miniature tape recorder. These units will replace the heads in most Japanese-built recorders, and are also excellent for the experimenter. Record/playback head specifications: impedance 2.2K at 1 KC; DC resistance: 160 ohms; reproduction level: — 45db (recording at — 10db); bias frequency: 35KC; bias current: 400ma; voice current: 100ma; response: 100-7000 cps ± 5db; S/N ratio: better than 45db; bias system: AC & DC reproduction: gap: .00024 in. (.006mm); dimensions: approx. 1/2 x 3/4 x 3/4". Erase head same dimensions. Total shpg. wt., 3 oz.

F-633 Net 3.95

MAGNETIC TAPE SPLICER

1.47

- Cut Both Ends Simultaneously
- Easy to Operate
- Durable & Sturdy

An excellent accessory that splices tapes accurately and eliminates joint noise. Both ends cut simultaneously. Nickel plated finish. Shpg. wt., 1 lb.

MS-289 Net 1.47

REEL LOCKS Set of Two 59¢

Holds tape recorder reel in place by locking spindle to reel. Especially useful if recorder is in vertical position. Will not interfere with normal operation of reels. Easily removable. Shpg. wt., 6 oz.

MS-564 Set of two .59

TAPE CLEANER

1.49

Simple, unique recorder head cleaner. Tape is impregnated with special formula cleaner. Simply run through like regular roll of tape. Entire job done in 2 minutes. Can be reused many times. 100' roll on plastic reel. Shpg. wt., 8 oz.

PK-283 Net 1.49

NEW TELEPHONE PICKUP COIL



1.89

This telephone pick-up coil is designed to feed into the microphone input of either a tape recorder or any high gain amplifier. The pick up can be easily attached to the telephone by the use of a rubber suction type attachment. The coil is electrostatically shielded to minimize hum pick-up. When properly positioned on telephone handset, the output of this device is more than adequate for a fully modulated tape recording. Complete with 5' shielded cable. Shpg. wt., 6 ozs.


MS-693 Net 1.89

METAL TAPE STORAGE CHEST



STANDARD CASE: Sturdy all steel carrying case. Holds 12 7" or 5" reels and cons. Twin snap locks for positive closure; perfect portability. Guards against exposure and accidental erase. Platinum gray hammerloid finish. Metal separators between reels. Includes index cords. Shpg. wt., 5 lbs.

ML-60 Net 2.99



(A) ROBINS "GIBSON GIRL" SPLICER

Cuts 2 rounded indentations in the tape splice, leaving the edges of the tape which contact parts of the recorder entirely free of adhesive. Adhesive deposited on initial parts of recorder is a frequent cause of wow and flutter. As little as 1/4" tape need be removed. Shpg. wt., 1/2 lb.

MS-288 Net 6.25
MS-473 Replacement Blade .98

(B) EDITALL TAPE EDITING KIT

This kit has all the equipment required to execute a complete editing job on a professional basis. The cutting block supplied is simple to operate but is precise in its application; made of duraluminum precisely machined and polished (makes straight or diagonal cut). All accessories such as grease pencil, blades, splicing tape (66 ft. roll of 1/2") supplied. Comes with instruction booklet—in a smart metal case. Shpg. wt., 1 lb.

MS-474 EDITALL KIT Net 8.82



(B) ROBINS SILICONE TAPE CLOTH

Cleans, lubricates and protects by depositing a microscopic film of silicone on the tape. Reduces head wear, tape wear, tape squeal and chatter. Eliminates "grime distortion". Washable. Shpg. wt., 5 oz.

MS-375 TAPE CLOTH Net .73

(C) ADHESIVE REEL LABELS

Convenient press-on adhesive labels for positive identification of tape reels. Easy to apply or remove. Shpg. wt., 5 oz.

MS-292 Pkg. of 30 .13



RCA TAPE CHESTS

Durable, chipboard storage cases covered in gold stamped simulated leather. Hold 5 reels in separate compartments. Type 501C1 for 5" Reels, size 5 1/2 x 4 1/4 x 5 3/8"; type 502C1 for 7" Reels, size 7 1/2 x 4 1/4 x 5 3/8". Shpg. wt., 1/2 lb.

RT-271 Type 501C1 for 5" Reels Net .75
RT-272 Type 502C1 for 7" Reels Net .82

RCA SPLICING TAPES

Pressure sensitive for editing and splicing. Shpg. wt., 3 oz.

RT-266	Type 515C1	1/4" x 100"	Net .17
RT-267	Type 511C1	1/2" x 100"	Net .22
RT-268	Type 512C1	1/2" x 150"	Net .30
RT-269	Type 513C1	3/4" x 100"	Net .32
RT-270	Type 514C1	3/4" x 150"	Net .39



METAL STORAGE CANS

Your best protection for valuable recorded tapes and movie film. Cans are ribbed for easy storage. Precision fit makes opening and closing easy. Attractively finished in grey. 3 sizes to choose from to fit any size reel. Av. shpg. wt., 8 ozs.

ML-154 3" Can. lots of 6, Ea. .18 Singly, Ea. .20
ML-155 5" Can. lots of 6, Ea. .27 Singly, Ea. .30
ML-61 7" Can. lots of 6, Ea. .36 Singly, Ea. .39



(A) ROBINS TAPE THREADER

No more awkward fumbling while threading a reel. Just place the tape against the reel, slip your Robins threader over the capstan shaft and over the empty reel. Tip of threader holds the tape firmly against the reel. A few turns on the crank and you're ready to play or record. Saves time and tape. Shpg. wt., 2 oz.

MS-222 .79

(B) TAPE THREADER

For quick and simple tape reel threading. Simply clip on and start recorder. Works on all size reels. Handsome chrome finish. In plastic case. Shpg. wt., 6 oz.

MS-374 TAPE THREADER List 2.50 Net 1.47

NEW! REVOLUTIONARY pioneer STEREOSCOPE!

SH-100

ATTACHES
in MINUTES!

UNCONDITIONALLY
GUARANTEED

Comes complete with one
headset—up to 4 people can
listen by adding accessory
earphone kits!

NOW! YOU CAN PLAY STEREO RECORDS

ON ANY TURNTABLE WITHOUT ANY AMPLIFIER — WITHOUT SPEAKERS!

—WITH ABSOLUTELY NO ELECTRONIC DEVICES BETWEEN THE RECORD AND YOUR EARS!

ALL YOU NEED IS THE AMAZING PIONEER STEREOSCOPE

AND ANY TURNTABLE OR RECORD PLAYER

15.95

Here is a truly remarkable achievement in stereophonic sound. The Pioneer Stereoscope enables the listener to enjoy his stereo or monaural records through a pair of headphones, with no amplifiers—no electronic devices of any sort—between his ears and the record! Headphones are driven by variations in pressure from the specially designed Stereoscope pick-up arm. The resultant full-bodied, distortion-free sound will make the listener search for the huge speakers he usually associates with such quality. An unconditional guarantee accompanies this amazing unit! A special volume control unit is inserted in the pipe which carries the sound to the earphones, which permits separate adjustment of left and right channel volumes. The mixing control located on the same unit

governs the channel separation and, in effect, can select stereo or monaural operation. Frequency response, 30 to 15,000 cycles. Tracking force for pick-up, 3-6 grams. Self-adjusting rubber rollers are provided to protect needle when pick-up is not on record. Accessory earphone kits permit as many as 4 persons to enjoy the same recording. The SH-100 comes complete with special pick-up arm, sapphire needle, mounting base, suction base, volume control unit, connecting tubes, earphones, and mounting screws. Shpg. wt., 4 lbs.

PK-596 SH-100 Stereoscope Net 15.95
PK-597 SH-101 Additional earphone kit Net 2.95
PS-97L NSH Diamond replacement needle Net 3.49

NEW! pioneer MODEL SE-1 STEREO HEADPHONES

- Actually 2 High Fidelity Dynamic Speakers
- Frequency Response 25 to 15,000 Cycles
- Soft Foam Rubber Ear Pads

F-770 19.95

- Frequency Response 25 to 15,000 Cycles
- Actually 2 High Fidelity Dynamic Speakers
- Soft Foam Rubber Ear Pads

For the audio connoisseur who demands the finest in stereophonic headphone performance, the Pioneer Stereophones combine broad frequency response and faithful reproduction with comfort-oriented design, to fulfill the most exacting requirements. The Stereophones are actually two 2 1/2" high fidelity dynamic speakers with a frequency response range of 25 to 15,000 cycles. Perfect for stereo and monaural operation, the headphones are rated at 1/2 watt maximum input; impedance, 8 ohms per phone. The soft foam rubber ear pads provide extremely comfortable listening, help to keep out noise and maintain an excellent bass response.

F-770 Shpg. wt., 2 lbs. Net 19.95
Model SE-2 resistor box for SE-1. Permits flexible one-switch changeover from speakers to Stereophones. F-800 Net 4.95
Model SE-3 "Y" connector for connecting 2 or more sets of headphones to a single source. F-801 Net 2.45
Model SE-4 12' extension cord for SE-1 phones. F-802 Net 2.95

NEW! LAFAYETTE HIGH FIDELITY STEREO HEADPHONES



13.95

- AIR-CUSHIONED HEADBAND
- SOFT FOAM RUBBER EAR CUSHIONS FOR MAXIMUM COMFORT AND BEST BASS RESPONSE
- HIGH SENSITIVITY—INPUT OF 1-2 MW PROVIDES AMPLE LISTENING VOLUME

These headphones will provide excellent high fidelity stereophonic listening and will perform beautifully with monaural equipment as well. They are designed for fatigue-free, comfortable use, even after the longest of listening periods.

The headband is covered with an air-filled vinyl bag which serves as a gentle air cushion, eliminating the discomfort which usually accompanies the weight of the phones on the head. Vinyl bag can be deflated, removed for washing, and re-inflated. Soft foam rubber ear pads keep out external noise, provide maximum bass response and make these headphones extremely comfortable to wear. Sensitivity is very high—a signal power of 1 to 2 mw will produce adequate listening volume. Frequency response, 30-15,000 cycles; impedance, 8 ohms per phone. The headphones come with a cylindrical junction box to protect the voice coils against power overloads. Phones plug into the box, and the two pairs of leads from the box are connected to a dual or single channel source for stereo or monaural operation. Complete with all cables, wires, overload junction box and 3-conductor phone plug. F-767 Shpg. wt., 2 1/2 lbs. Net 13.95


JUNCTION BOX
For connecting stereo headphones to an existing system without the need of continually disconnecting speakers. Impedance 4-16 ohms. Has separate earphone jacks for stereo or monaural, separate volume controls for each side of the headset, and a speaker on-off switch. 4 1/4" W x 1 1/4" H x 1 3/4" D. F-641 Shpg. wt., 1 1/4 lbs. Net 4.59



LAFAYETTE MINIATURE HI-FI SPEAKER and ENCLOSURE

- ATTRACTIVE MAHOGANY FINISHED WOOD CABINET
- COMPLETE WITH 25 FEET OF CABLE

Enjoy music everywhere in your home with this amazing Lafayette miniature speaker system. Perfect as an extension speaker for your den, basement, kitchen or bedroom. Use two as extension speaker units for stereo or with your TV and Radio. Housed in a beautiful mahogany—finished wood cabinet with ventilated back cover, the 5-watt 4x6" speaker is designed to work from either 4 or 8 ohm outputs. System is supplied with 25 feet of cable which should meet any hook up requirement. Over-all size: 9 1/2" W x 7 3/4" H (inc. feet) x 3 1/2" D. Shpg. wt., 5 lbs. SK-109 Miniature Speaker System Net 6.95



6.95

LAFAYETTE-GOODMANS SK-111 1 1/4 LB. 15" MAGNET SPEAKER



39.50

Reg. 1961
Catalog Price 54.50
• Frequency Response: 30-20,000 cps.
• Cone Resonance: 35 cps.
• Power Rating: 30 watts

15" speaker with power rating of 35 watts and cone resonance of 25 cps. Employs 1 1/4 lb. Alcomax magnet and 1 3/4" voice coil, 7" deep, 15 3/8" diam. Shpg. wt., 25 lbs. SK-111WX Net 39.50

KOSS STEREO HEADSETS and ACCESSORIES



Model SP-3 Stereophones (Fig. A)
The Koss SP-3 Stereophones are a specially constructed headset that provide a wide frequency range of 30-15,000 cycles by means of unusual 3 1/2 dynamic reproducers incorporated into each earphone. They are extremely comfortable to wear, light and rugged. Ideal for Stereo, they can also be used for monaural sound. Since they have an impedance of 4 ohms, they can be connected directly to amplifier outputs or across speaker voice coil leads. Shipping weight 2 lbs. G-600 Net 24.95

MODEL A-1220 AMPLIFIER
An Amplifier especially designed for use with the Stereophones. Can be connected directly to a Stereo ceramic cartridge or to the outputs of the pre-amps of a stereo recorder or tuner. Equipped with 2 Phono jacks, a gain control for each channel, and 2 Phone jacks. Attractively made and compact, this unit lends itself to a wide variety of uses. Three tubes plus rectifier. Transformer powered. Shipping weight, 4 lbs. G-603 Net 34.95

MODEL T-1
Contains matching transformers for monitoring 600 to 10,000 ohm outputs to output jacks for Stereophones and a terminal board is provided for connection to various types of equipment. Shipping weight 1 1/2 lbs. G-604 Net 6.95

MODEL T-5 JUNCTION BOX (Fig. B)
Junction Box for connecting stereophones to existing stereo or monaural system. Impedance 4-16 ohms. Contains 2 Volume controls for changing the Volume of each side of the headset independently. Has 2 output jacks for stereo or monaural use. Equipped with speaker on-off switch for personalized listening. Shipping weight 1 1/4 lbs. G-605 Net 7.95

KOSS PERSONAL LISTENER
An outstanding 4-speed phono with ceramic turnover stereo cartridge, diamond stylus for LP, and sapphire stylus for 78 r.p.m. Includes a set of the famous Koss Stereophones to form a complete, personalized stereo high fidelity system of the finest quality. Each channel has a separate volume control; phono has automatic shut-off feature. Portable, in brown leatherette case, 21 1/2" L x 13 1/2" W x 6" H. G-606WX Shpg. wt., 22 lbs. Net 99.50

PLASTIC RECORD COVERS
75c per pkg. of 15
Soft piazole plastic covers to protect records from dirt, dust and moisture. Available in square beaded bottom to fit 12" records in jackets and in round beaded bottom to cover 12" records without jackets. Shpg. wt., 1/2 lb. PK-456 Pkg. of 15 Square Any Pkg. PK-455 Pkg. of 15 Round 75

STEREO AUDIO ANALYST™

Single Needle Dual Channel VU BALANCE METER

11.95

- UNIQUE TWO COIL GALVANOMETER TYPE PRECISION METER MOVEMENT
- SEVEN RANGES OF METER SENSITIVITY
- PROVISION FOR USE AS VU METER AND TAPE RECORDER LEVEL INDICATOR
- MAXIMUM METER SENSITIVITY 120 ua

Provides the solution to all stereo balancing problems. When both signals are equal and balanced the resultant deflection on the scale will measure 0. Individual channels may be measured by two slide switches. Stable meter action and protection from peak voltages is provided by special damping networks. Single seven-step range control serves for both channels and facilitates use of meter with all amplifier power levels. By properly positioning this control the movements may be used as VU meters when terminated across the 600-ohm load. The scales are calibrated in "Volume Units". Sensitivity is 1.2 volts for 0 vu or 100 percent indication. Finished in a rich satin gold. Overall size is 4 3/4" L x 5 1/4" H x 4 3/4" W. TM-66 Audio Analyst Net 11.95

LAFAYETTE HIGH FIDELITY STEREO-MONAUROAL TEST RECORD

2.95

- TESTS RUMBLE EACH CHANNEL
- TESTS LEVEL EACH CHANNEL
- TESTS EQUALIZATION
- TESTS RESONANCE
- TESTS BALANCE
- INCORPORATES PHASE CHECK
- STYLUS WEAR TEST

For stereo testing this two-sided 12" LP stereo record has on its stereo side two 1000 cycle bands to check the level of each channel separately; balance check to set the level of each channel; there are special metronome recording; rumble test. There are stylus wear test grooves on both outer and inner edges of each side to check both stereo and monaural styli. Incorporates phase adjusting check to simplify phasing of speakers. For monaural testing it provides an RIAA equalization test in 9 steps from 30 to 15,000 cycles, a continuous glide band from 10 to 35,000 cycles, to test for resonances of tone arm or of cabinet. Also features sections of stereo sound effects of jet planes, boat whistles, etc. A terrific value and a "must" for the Hi-Fi enthusiast. Comes with complete instructions for use. Shpg. wt., 1 lb. PR-14 Net 2.95

NEW! 4-SPEED HI-FI TURNOVER PICK-UP



2.75

• ARM TAKES STEREO OR MONAUROAL CARTRIDGES • WITH WIDE RANGE MONAUROAL CARTRIDGE • ADJUSTABLE ARM HEIGHT AND STYLUS PRESSURE
Arm is wired for stereo, anticipating future conversion. Has a wide range turnover monaural crystal cartridge with dual sapphire styli. Output is 1 1/2 V. Easy height adjustment at base, 1 3/8" to 1 1/2". Also stylus pressure adjustment. Plastic arm 9 1/2" long overall. Base 1 3/4" with mounting holes on 1 3/8" centers. Shielded leads. Satin smooth light maroon finish. Shpg. wt., 2 lbs. PK-146 Net 2.75
PK-158 Sapphire LP replacement Needle Net .49
PK-159 Sapphire STD replacement Needle Net .49

MODERN RECORD RACK

1.79

Attractive, brass plated rack carries 60 records of all sizes. Spring steel separators numbered 1 to 60. Heavy carrying handle. Rubber tipped feet. Size 17Lx5 3/4Hx7"D. Shpg. wt., 4 lbs. PK-227 Net 1.79

LAFAYETTE for Outstanding Savings on TOP QUALITY STEREO RECORDS

PRESENTING THE PRICELESS SOUND OF **EVEREST** IN THIS OUTSTANDING COLLECTION OF STEREO RECORDS!

- CLASSICAL
- JAZZ
- INSTRUMENTAL
- POPULAR
- MOOD
- VOCAL

AT LAFAYETTE'S SENSATIONAL LOW PRICE!

1.69 each



SOBR-1003—THE HERO RIDES AGAIN IN STEREO—Popular jazz artist Woody Herman in Northwest Passage, Caledonia, Wildroot, The Good Earth, and others. STOCK NO. PR-351

SOBR-1006 — OICK MARTIN PRESENTS POLKA TIME with Mike Miskiewicz and his dance orchestra. Jolly Cholly Polka, Fire Alarm Polka and seven others. STOCK NO. PR-352

SOBR-1008 — CHEROKEE — Charlie Barnet and his orchestra bring you swing music at its best. Cherokee, Redskin Rhumba, Blue Juice, others. STOCK NO. PR-353

SOBR-1010—HERMAN'S HEAT AND PUENTE'S BEAT—Hot Jazz emerge with cool latin rhythm when Woody Herman and Tito Puente bring you Blue Station, Lullaby of Birdland, Balu and more. STOCK NO. PR-354

SOBR-1012 — THE GYPSY WANDERLUST — An exciting hour of popular gypsy favorites played by The Phantom Gypsies. Dark Eyes, Gypsy Tango, Zigeuner, others. STOCK NO. PR-355

SOBR-1014 — WILD BILL DAVIS SWINGS HIT SONGS FROM "MY FAIR LADY"—All the spectacular hits from My Fair Lady in the swinging style of Wild Bill Davis. STOCK NO. PR-356

SOBR-1020—MICHAEL TODD'S AROUND THE WORLD IN 80 DAYS—Complete score of the famous film with both words and music. STOCK NO. PR-357

SOBR-1024—MUSIC HALL BON BONS—Raymond Paige conducts the Radio City Music Hall Symphony Orchestra in a collection of Favorites. Our Waltz, Blue Tango, others. STOCK NO. PR-358

SOBR-1031—P.S. TONY PASTOR PLAYS AND SINGS SHAW—Tony Pastor and his orchestra in Artie Shaw hits such as Indian Love Call, Frenesi, etc. STOCK NO. PR-359

SOBR-1047—GERSHWIN IN BRASS—Featuring the World's Greatest Brass under the direction of Jack Saunders. Fascinating Rhythm, But Not For Me, and many others. STOCK NO. PR-360

SOBR-1051 — THE MUSIC OF GEORGE GERSHWIN AND COLE PORTER—A delightful assortment of pop hits conducted by Pollak, his chorale and orchestra. STOCK NO. PR-361

SOBR-1060 — SONGS OF HAWAII WITH CHARLES K. L. DAVIS—A selection of exotic Hawaiian numbers played by Tom (Komaki) Monte and His Orchestra. STOCK NO. PR-362

SOBR-1067 — A STRING OF TRUMPETS — Billy Mure, His Guitar and Orchestra. Exciting rhythms—Trumpet Cha Cha Cha, Sentimental Journey and many more. STOCK NO. PR-363

SOBR-1080 — AMOR — Raymond Scott and His Swinging Strings bring you How High The Moon, Summertime, Amor, etc. STOCK NO. PR-364

SOBR-1083 — DANCE ALONG WITH RUSS MORGAN AND HIS MUSIC IN THE MORGAN MANNER—Medley: Linger Awhile, Stumbling, Wabash Blues, Dolores, Johnson Rag and more. STOCK NO. PR-365

SOBR-1087—GORDON JENKINS with his orchestra PRESENTS MARSHALL ROYAL — Caravan, Ain't Misbehavin', Birth of the Blues, Take The A Train, others. STOCK NO. PR-366

SOBR-1093—INVITATION TO PARIS—Roger Roger and His Orchestra—La Seine, Beer Barrel Polka, Madonna Mia Rosa, Mademoiselle de Paris, Some of these Days, More. STOCK NO. PR-367

SOBR-1095 — WALTZ MASTERPIECES — Pollak conducting the Stadium Symphony Orchestra in a collection of famous waltzes by master composers. STOCK NO. PR-368

SOBR-3058—IRVING BERLIN—Great Man of American Music, A new Interpretation—Pollak and his orchestra and chorale: Easter Parade, What'll I Do?, and many more. STOCK NO. PR-369

SOBR-8002 — NELSON EDDY and GALE SHERWOOD with Harry Sosnik and the orchestra—Wonderbar, The Song is You, One Night of Love, This is My Beloved, others. STOCK NO. PR-370

SOBR-8004 — A STARRY NIGHT — Nelson Eddy with Skitch Henderson and His Orchestra. Tonight We Love, The Lamp is Low, My Reverie, Till The End of Time, and others. STOCK NO. PR-371

SOBR-3002—COPLAND: Appalachian Spring—Ballet (1941) Walter Susskind conducting the London Symphony Orchestra. GOULD: Spirituals For String Choir and Orchestra (1941). STOCK NO. PR-372

SOBR-3005—MAHLER—Symphony No. 1 In D Major. A modern classic. Sir Adrian Boult conducting the London Philharmonic Orchestra. STOCK NO. PR-373

SOBR-3010—SHOSTAKOVICH — Symphony No. 5 in D Major. Scored for full "romantic orchestra." Leopold Stokowski conducting The Stadium Symphony Orchestra of New York. STOCK NO. PR-374

SOBR-3011—TCHAIKOVSKY—Francesca da Rimini Fantasia For Orchestra Op. 32/ Hamlet (overture and Fantasy). Leopold Stokowski conducting the Stadium Symphony Orchestra of New York. STOCK NO. PR-375

SOBR-3015 — COPLAND — Billy the Kid (Suite From the Ballet)/Statements For Orchestra. Aaron Copland conducting the London Symphony Orchestra. STOCK NO. PR-377

SOBR-3023 — RICHARD STRAUSS — Till Eulenspiegel's Merry Pranks, Op. 28/Don Juan, Op. 20/Salome—Dance of the Seven Veils. Leopold Stokowski conducting the Stadium Symphony Orchestra of New York. STOCK NO. PR-378

2 GREAT MAHLER SYMPHONIES 2-RECORD SETS • OUTSTANDING RECORDINGS

3.38 STEREO per set

SOBR-3014-2 MAHLER—Symphony No. 5 in C Sharp minor. A "giant" symphony in five movements. This superb performance on Everest's Stereo Master Records is performed by the London Symphony Orchestra, conducted by Rudolf Schwarz. STOCK NO. PR-376

SOBR-3050-2 MAHLER—Symphony No. 9 in D minor. A soaring symphony beautifully captured on Everest's Stereo 35 mm Magnetic Film recording technique. The London Symphony Orchestra is conducted by Leopold Ludwig. STOCK NO. PR-388

Shpg. wt., 1 lb. each disc.



SOBR-3026—RIMSKY-KORSAKOV: SCHEME-RAZAOE — Symphonic Suite After "The Thousand Nights and a Night," Op. 35. Sir Eugene Goossens conducting the London Symphony Orchestra. STOCK NO. PR-379

SOBR-3027—RAYMOND PAIGE'S CLASSICAL SPICE SHELF—Raymond Paige conducting the Stadium Symphony Orchestra of New York. Works of Offenbach, Ravel, Chopin, others. STOCK NO. PR-380

SOBR-3030—BRAHMS—Symphony No. 3 in F Major, Op. 90. A Brilliant recording. Leopold Stokowski conducting the Houston Symphony Orchestra. STOCK NO. PR-381

SOBR-3033 — STRAVINSKY: Petrouchka — Complete Ballet (original version). Sir Eugene Goossens conducting the London Symphony Orchestra. STOCK NO. PR-382

SOBR-3037—BERLIOZ—Symphonie Fantastique, Op. 14, Symphony in five movements. Sir Eugene Goossens conducting the London Symphony Orchestra. STOCK NO. PR-383

SOBR-3039—TCHAIKOVSKY—Symphony No. 5 in E Minor, Op. 64. Sir Malcolm Sargent conducting the London Symphony Orchestra. STOCK NO. PR-384

SOBR-3044—GROFE: Grand Canyon Suite—Concerto For Piano and Orchestra in D Minor (World Premiere Recording). Ferde Grofe conducting the Rochester Philharmonic Orchestra. Jesus Maria Sanroma, piano. STOCK NO. PR-385

SOBR-3046—SCHUBERT: Symphony No. 8 in B Minor ("Unfinished"). MOZART: Symphony No. 40 in G Minor (K.550). Leopold Ludwig conducting the London Symphony Orchestra. STOCK NO. PR-386

SOBR-3049 — TCHAIKOVSKY — Violin Concerto in D Major, Op. 35. SPIVAKOVSKY—Walter Goehr conducting the London Symphony Orchestra. STOCK NO. PR-387

SOBR-3066—BRAHMS—Symphony No. 4 in E Minor, Op. 98. Great Everest Sound with the Pittsburgh Symphony Orchestra conducted by William Steinberg. STOCK NO. PR-393

SOBR-3051—RESPIGHI—The Fountains of Rome: The Pines of Rome. A fine interpretation of these famous tone poems by Sir Malcolm Sargent conducting the London Symphony Orchestra. STOCK NO. PR-389

SOBR-3052—KHACHATURIAN—Gayne Ballet Suite: Anatoly Fistoulari conducting The London Symphony Orchestra. STOCK NO. PR-390

SOBR-3053—MOUSSORGSKY — Pictures at an Exhibition—A Night on the Bald Mountain. Sir Malcolm Sargent conducting the London Symphony Orchestra. STOCK NO. PR-391

SOBR-3056—DVORAK—Symphony No. 5 in E Minor, Op. 95 ("From The New World"). Leopold Ludwig conducting The London Symphony Orchestra. STOCK NO. PR-392

SOBR-3067 — GEORGE GERSHWIN — Rhapsody in Blue—An American in Paris. Played in exciting manner by William Steinberg conducting the Pittsburgh Symphony Orchestra, Sanroma, piano soloist. STOCK NO. PR-394

RCA VICTOR LIVING STEREO

with the WORLD'S GREATEST ARTISTS

- POPULAR • CLASSICAL

YOUR CHOICE OF ANY 5 FOR 12.25

2.49

Shpg. wt., 1 lb. each disc.



LSC-2265—THE RUBINSTEIN STORY — The master of the keyboard, Artur Schnabel, plays two of Chopin's masterpieces—Concerto No. 2, and Andante Splanato and Grande Polonaise. With the Symphony of the Air. STOCK NO. PR-237

LSC-2112—VIENNA—Fritz Reiner and the Chicago Symphony take you to beautiful Vienna for waltz-time. Emperor Waltz, Village Swallows, etc. STOCK NO. PR-241

LSC-2299—WALTZES OF FRANZ LEHAR—An excellent library of waltz melodies comprising airs in many moods, by the London Proms Symphony. Wild Roses, Eva, Gypsy Love, more. STOCK NO. PR-242

LSC-2100—HI-FI FIEDLER—Arthur Fiedler conducts the Boston Pops in revitalized, resensitized, hi-fi versions of Le Coq d'Or, William Tell Overture, Marche Slave, and others. STOCK NO. PR-249

LSC-2302—GILBERT AND SULLIVAN OVERTURES—These 6 overtures to Gilbert and Sullivan entertainments are triple-gala compositions because they are festive as preludes, as souvenirs, as instrumental pieces. You'll recognize The Mikado, H.M.S. Pinafore, etc. STOCK NO. PR-240

LSC-2313—VENICE — Venice, the dazzling operatic center, is the inspiration for this album by the Orchestra of the Royal Opera House, Covent Garden, Georg Solti conducting. Excerpts from La Traviata, La Gioconda, etc. STOCK NO. PR-243

LSC-2325—MUSIC FOR FRUSTRATED CONDUCTORS—With this album you get a free baton, and the chance to make believe you're conducting the Mexican Hat Dance, Sabre Dance, and others. STOCK NO. PR-247

LSP-1900—THE KEYS AND I—An unforgettable trip across the 88 keys by the master, Eddie Heywood, with Joe Reisman and his Orchestra. Land of Dreams, All the Way, Hurricane, and more. STOCK NO. PR-276

LSP-1905—TWO SIDES OF WINTERHALTER—Versatility abounds from Hugo Winterhalter and his Orchestra as they play classical favorites and popular hit tunes. Warsaw Concerto, Gigi, One O'Clock Jump, and more. STOCK NO. PR-269

LSP-2010—COMO SWINGS — The nation's No. 1 singer brings you songs with a definite beat, backed by Mitchell Ayres and his Orchestra. St. Louis Blues, Linda, Mood Indigo, more. STOCK NO. PR-263

LSP-2070—STICKS AND BONES — A great musical talent of our time for percussion sounds and rhythms. Marty Gold and his Orchestra present Hall of the Mountain King, Love for Sale, etc. STOCK NO. PR-274

LSC-2308—DOUBLING IN BRASS — Morton Gould and his symphonic band present brilliant band music in abundance. Included are some of Mr. Gould's own compositions. Jericho, American Patrol, Yankee Doodle, others. STOCK NO. PR-256

LSC-2340—PORGY AND BESS/WEST SIDE STORY—Robert Russell Bennett conducts the RCA Victor Symphony in a vivid demonstration of American dramatic music from the scores of Porgy and Bess and West Side Story. STOCK NO. PR-255

LSC-2195—BILLY THE KID/RODEO—A recording triumph. Morton Gould and his orchestra give you his rendition of Aaron Copland's two famous ballets—Billy the Kid, and Rodeo. STOCK NO. PR-246

LSP-1866—MUSIC FOR BANG, BAAROOM AND HARP—The wildest sounds this side of Cape Canaveral yet thoroughly delightful music from Dick Schory. April in Paris, Baja, and more. STOCK NO. PR-271

LSP-1944 — MARCHING DOWN BROADWAY WITH THE BAND OF THE COLDSTREAM GUARDS—The tingling excitement that only a crack band like the "Guards" can evoke — 76 Trombones, Lida Rose, and more. STOCK NO. PR-273

LSP-1894—CUGAT IN SPAIN—Combine the fine rhythm of Xavier Cugat and his Orchestra with the fiery music of gay Spain for an album of musical favorites. Selections include Malaguena, Ritual Fire Dance, others. STOCK NO. PR-286

LSP-1617—TOP PERCUSSION: TITO PUENTE —An album of Latin percussion and terrific sounds containing the efforts of some of the greatest percussionists in this country. Elequana, Bragada, Ti Mon Bo, Mon-Ti, and more. STOCK NO. PR-287



STEREO RECORDS AT A NEW LOW PRICE!

ANY 5 12.25

2.49

Shpg. wt., 1 lb. each disc.



SR-60090—SQUEEZE ME! — Dick Contino and his accordion in contagious, exciting music as he tries original approaches to these great standard melodies: Yesterday, Dream, Blue Moon, more. STOCK NO. PR-298

SR-60082—JAN AUGUST — A dozen piano Cha-Cha selections including You're The Cream In My Coffee, Boogie Woogie, Cha Cha, etc. STOCK NO. PR-117

SR-80015—MAX ROACH with the BOSTON PERCUSSION ENSEMBLE—Max Roach, jazz foremost drummer, combines with the Boston Percussion Ensemble to provide an exciting excursion into the world of Percussion. Music Inn Suite, etc. STOCK NO. PR-306

SR-90134—FIESTA IN HI-FI—Howard Hanson conducts the Eastman-Rochester Orchestra in folk songs and dance rhythms from Mexico, Virginia and the Kentucky mountains. Mexican Rhapsody, Savannah River Holiday, etc. STOCK NO. PR-308

SR-90211—VIVE LA MARCHE!—Paul Paray and the Detroit Symphony Orchestra prove that the march is the province of the orchestra, not the band. Coronation March, La Marseillaise, more. STOCK NO. PR-312

SR-90172—AARON COPLAND—Antal Dorati conducts the Minneapolis Symphony Orchestra in three of the best of Copland. Rodeo, Four Dance Episodes, El Salon Mexico, Oanzon Cubano. STOCK NO. PR-310

Another Great LAFAYETTE Scoop!

SPECIAL LAFAYETTE PRICE!

16.95

Stock No. PR-350

The Complete **EVEREST STEREO** RECORDING OF ALL NINE **BEETHOVEN SYMPHONIES** Brilliantly Recorded by Josef Krips and The London Symphony Orchestra on 8 Stereo Records —Housed in a Beautiful Deluxe White Leatherette album with SUPERB 22-PAGE BOOKLET containing PROGRAM NOTES and PICTORIAL HISTORY OF BEETHOVEN'S LIFE AND TIMES.

HAILED BY LEADING CRITICS AROUND THE WORLD!



SOBR-3065-8

DIAMOND STYLI AT LOWEST PRICES ANYWHERE

LAFAYETTE DIAMOND and DIAMOND-SAPPHIRE STYLI

MADE FOR LAFAYETTE BY THE FOREMOST AMERICAN MANUFACTURERS

KEY TO POINT CODES HOW TO ORDER

The symbols in the column headed "PT SIZE" are explained in the table below.
 LP—SINGLE 1 MIL MICROGROOVE FOR 33 1/3 AND 45 RPM
 AG—SINGLE 2 MIL ALL GROOVE FOR ALL SPEEDS
 ST—SINGLE 3 MIL STANDARD FOR 78 RPM
 COMB—DUAL .1 MIL DIAMOND AND 3 MIL SAPPHIRE
 Identify your needle by cartridge number and illustration and order by stock no. Note that all needles listed here are for monaural cartridges.

ALL DIAMOND STYLI ARE NOT ALIKE
 MADE FROM WHOLE DIAMONDS • PRECISION GROUND AND POLISHED • VERTICALLY AND EDGEWISE GRAIN ORIENTED • SHADOWGRAPHED




Each Lafayette's diamond stylus is made from individual diamond, properly oriented and ground to close tolerance; shadowgraph tested to give you less wear per play and long service life.

The synthetic sapphire used in these styli are of the same fine quality used in precision watch bearings.

FULL 1 YEAR REPLACEMENT GUARANTEE AGAINST DEFECTS IN WORKMANSHIP AND MATERIAL ON ALL DIAMOND STYLI


2.39

ANY DIAMOND or DIAMOND-SAPPHIRE NEEDLE IN THIS LISTING



Stock No.	Size Pt.	Fig.	Cartridge	REPLACES JENSEN NO.	Stock No.	Size Pt.	Fig.	Cartridge	REPLACES JENSEN NO.	Stock No.	Size Pt.	Fig.	Cartridge	REPLACES JENSEN NO.
DIAMOND NEEDLES														
FOR ADMIRAL CARTRIDGES														
PS-10L	LP	1	409A11, 409A300, 98A54-1	JPS-30LPD	PS-35L	LP	54	560176, 560180	CRA-55LPD	PS-35L	LP	53	TO-200, TO-222, TO-284, TO-400 series, RA284, DT60 series.	CRA-55LPD
PS-16L	COMB	6	409B21	JPS-35SD	PS-70L	COMB	51	560161	S-66SD	PS-69L	LP	38	TX88, A	CRA-56LPD
PS-17L	LP	7	409A30	A81LPD										
FOR ASTATIC CARTRIDGES														
PS-20L	LP	3	AC Series, 40T, 41T, 40-1, 41-1, 42-1, 90T series, 10-L-3, 11L-3	A-75LPD	PS-56L	COMB	43	45-9612, 76-4649, 425-0016	PH-13SD	PS-16L	COMB	6	WC10, WC100, PC2 series, PC3 series, PC4 series, PC5 series	JPS-35SD
PS-23L	LP	12	408	M-70LPD	PS-56L	COMB	43	45-0009, 425-0011, 425-0014	PH-13SD	PS-10L	LP	1	P-72, P-73, P-73R, P-75, P-76, P-77, P-80, W-21, W-21AR, W-22A, WC-24, WC-25 Series	JPS-30LPD
PS-25L	COMB	14	GCD, 409, 55-T, 55TJ, 55TM	A-71SD										
PS-23L	LP	12	410	M-70LPD										
PS-17L	LP	7	CAC, CQ, CQ-1, LQD, LQD-1, QT, QT-33, 44-T, 46-1, 48-1, 166T Series	A-81LPD										
PS-35L	LP	54	118, 120, 124 series, 310T, 312T, 420, 422, 424TS series, 310-1, 310-TB, TS, 312-TB, TS, 414-1	CRA-55LPD										
FOR MAGNAVOX CARTRIDGES														
PS-51L	COMB	37	560176, 560180, 560133, 560151, 560169-1, 560170	M-50SD	PS-23L	LP	12	74067	M-70LPD	PS-32L	COMB	51	3T, 3TS, 3TD	S-61SD
FOR PHILCO CARTRIDGES														
FOR PERPETUUM EBNER CARTRIDGES														
FOR R.C.A. CARTRIDGES														
FOR SONOTONE CARTRIDGES														
FOR WEBSTER ELECTRIC CARTRIDGES														

STEREO DIAMOND STYLI AT LAFAYETTE'S 2³⁹ Low Prices!



Stylus Stock No. Fig. For Cartridges

- PS-88L G ACOS 73 .7 mil diamond and 3 mil sapphire stylus No. 73-1
- ADMIRAL CARTRIDGES
- PS-80L C 409B33-1(2-1)
- PS-81L B 409C37-1
- ASTATIC CARTRIDGES
- PS-92L M 17, 170
- COLUMBIA CARTRIDGES
- PS-84L J SC-1-2-7-8
- ELECTROVOICE CARTRIDGES
- PS-80L C 21 and 26 Series
- EUPHONICS CARTRIDGES
- PS-93L K E-1-3
- GENERAL ELECTRIC CARTRIDGES
- PS-87L A GC7
- PS-89L A VR227
- MAGNAVOX CARTRIDGES
- PS-80L C 560233-3-4
- PS-94L D 560260-1
- MONARCH (BSR)
- PS-86L F TC8S, TC-8SH
- MOTOROLA CARTRIDGE
- PS-80L C 59K643335
- PS-81L B 59B645397
- PERPETUUM-EBNER
- PS-81L B PE90 (M, M)
- PHILCO CARTRIDGES
- PS-80L C { 35-2809-1, 35-2824-1, 325-8047, 35-2825-1, 325-8036
- PS-81L B { 35-2820-1, 35-2826-1, 325-8048, 325-8049
- PS-86L F { 35-2827-1, 35-2829-1, 325-8051, 325-8052
- RCA CARTRIDGES
- PS-81L B T-1
- PS-85L E { 106770-1, 106690, 108213, 108718
- PS-86L
- RONETTE CARTRIDGES
- PS-81L B { OV, OV1, T1 Single BF40, 105, 105-1 (2,3,4), 106-1(2,3,4)
- SONOTONE CARTRIDGE
- PS-82L O { Combination .7 mil (stereo) diamond and 3 mil (78RPM) sapphire for 8T and 8TA
- PS-95L L { Same as above but for 9T Series
- PS-96L M { Same as above but for 12T Series
- SONOTONE
- PS-83L O { Same as above but with .7 mil (stereo) diamond and 1 mil (monaural LP) sapphire
- TELEFUNKEN CARTRIDGE
- PS-90L H T20-2
- VM CARTRIDGES
- PS-80L C 16707-A
- PS-82L O 16708-F
- WEBCOR CARTRIDGES
- PS-80L C 21P573
- PS-81L B 21P596, 21P598
- PS-82L O 21P700-1-2-3-4
- ZENITH CARTRIDGES
- PS-81L B 142-99B

REPLACEMENT STYLI FOR GE CARTRIDGES

FOR GE VR II CARTRIDGES (FIG. 35)
 Direct replacements for clip-in styli on GE VR II series models 4G-050, 4G-052, 4G-053, 4G-040, 4G-041, 4G-063, 4G-061 cartridges. Avg. shpg. wt., 2 oz.
 PS-48L-1 mil diamond LP clip-in stylus. Replaces GE 4G-010 Net 2.39
 PS-346-1 mil sapphire LP clip-in stylus. Replaces GE 4G-015 Net 1.15
 PS-348-3 mil sapphire 78 clip-in stylus. Replaces GE 4G-035 Net 1.15

MODERNIZATION ASSEMBLIES (FIG. 33)
 Modernize your old triple-play cartridge. These assemblies replace both the old and new series "A." Once installed, you can replace one point at a time.
 DIAMOND SAPPHIRE. Replaces old RPJ-013 and new RPJ-013A. Avg. wt., 2 oz. Net 2.39
 PS-46L
 DUAL DIAMOND. Replaces old GE RPJ-012 and new RPJ-012A. Net 4.50
 PS-79L
 DUAL SAPPHIRE. Replaces old GE RPJ-010 and new RPJ-010A. Net 2.10
 PS-345

STYLI FOR OLD TYPE GE CARTRIDGES (FIG. 32)
 Exact replacement for all old type single-needle GE cartridges. Avg. wt., 2 oz.
 PS-45L-Diamond 1 mil (LP) replaces GE RPJ-004 Net 2.39
 PS-54L-Sapphire 1 mil (LP) replaces GE RPJ-005 Net .99
 PS-540-Sapphire 3 mil (78) replaces GE RPJ-001 Net .99

FOR GE SERIES A CARTRIDGES (FIG. 34)
 Individual stylus replacements that clip in to all GE "A" series. Avg. wt., 2 oz.
 PS-47L-Diamond 1 mil (LP) replaces GE RPJ-010 Net 2.39
 PS-543-Sapphire 1 mil (LP) replaces GE RPJ-015 Net 1.15
 PS-542-Sapphire 3 mil (78) replaces GE RPJ-035 Net 1.15

DIAMOND STYLI FOR G.E.

AS LOW AS 2.39

MULTILINGUAL LANGUAGE COURSE

GERMAN SPANISH
 FRENCH ITALIAN


You can now learn to speak French, Italian, German or Spanish easily and pleasantly in your own home and progress at your own speed. Features the new simplified participation method that helps you to learn the lessons faster and retain them longer. It is a complete language course with 48 lessons on two 12" hi-fi long playing records. You learn with native speakers! The recorded lessons are printed in an illustrated conversation manual. Also included is a combination of grammar and dictionary book. When ordering, please specify the language desired. Shpg. wt., 4 lbs. Net 5.75
 PR-15

SPECIAL VALUE! INCLUDES RUSSIAN
 5 language combination course. French, Italian, German, Spanish, and Russian. 9-12" LP records, 216 lessons, 2 books. Shpg. wt., 10 lbs. Net 9.50
 PR-16

4 SPEED PHONO MOTOR WITH TURNTABLE

Quiet, dependable A-C operation assured by rubber shock-mounted friction drive motor. Speed change control through idler driving an 8" turntable. Mounting centers 4 1/2 x 3 3/4", 2 1/2" depth below base plate. Shpg. wt., 3 1/2 lbs.
 ML-24 Phono and turntable Net 5.35
 PK-149 Mounting board for motor Net .95

5.35



STATI-CLEAN .88

Sprays a fine mist which keeps your record clear of surface noise created by static (common to all vinyl records) and clean of dust attracted by the static charge. Prevents groove and needle wear caused by static-dust and keeps records lustrous. Extends their life. Two applications a year is sufficient. Enough for hundreds of records. Shpg. wt., 8 oz. Net .88
 PK-105

LAFAYETTE RECORD CLEANING KIT

Clean your valuable records the professional way with this Lafayette Kit. Contains a non-gumming anti-static detergent in polyethylene bottle. Squeeze to apply for complete elimination of static in the record grooves. Supplied with special velvet applicator in plastic pouch. Shpg. wt., 10 oz. Net 1.29
 PK-508



PHONO AMPLIFIERS


THREE TUBE AC-DC PHONO AMPLIFIER

(Fig. A) Equipped with a variable tone control and a separate volume control. Delivers two watts output. Phonograph motor connects to the amplifier. Uses 12AV6, 50C5, and 35W4 rectifier. For 110-120V, 60 cycles AC or 110-120V DC. Supplied with line cord and plug, but less tubes. Shpg. wt., 2 lbs. Net 2.95
 PK-23

2 TUBE AMPLIFIER WITH TUBES

(Fig. B) A two tube phono amplifier using a 50L6 and 35Z5 tube as rectifier. Well-built, good tone and volume. Contains volume control with switch. AT A BIG SAVING! Shpg. wt., 3 lbs. Net 4.50
 PK-24 with tubes

(Fig. C) Output transformer matches output tube to 3-4 ohm voice coil. Shpg. wt., 1/2 lb. ea. .49
 TR-10 Singly
 In lots of 5, ea. .45




A LAFAYETTE SPECIAL!

1.95 TONE ARM CONTROL

An absolutely essential addition for every Hi-Fi enthusiast. Ends groove and stylus damage caused by accidental dropping of tone arm onto record, greatly extending record life. Accurately and smoothly lowers tone arm into run-in groove and lifts arm off record at end of play. Ideal for "cueing." Designed to fit practically every known turntable arm as well as record changer with manual features. Supplied with adhesive mounting base to keep unit in position and with both wood and metal mounting screws for permanent installation. Shpg. wt., 6 oz. Net 1.95
 MS-785

NEW! EXCLUSIVE LAFAYETTE STYLOCHRON

More precious recordings are ruined by tardy replacement of the needle than by any other cause. Now, there is no need to let this happen, especially to your doubly precious stereo recordings. Lafayette Stylochron lets you know just how long your needle has been in use so that you can replace the worn needle at the proper time, before it can do damage to your records. The Stylochron is quickly and easily mounted on your motor board or other convenient place. The moment your record changer or turntable starts, the Stylochron begins to register. It stops when the turntable stops. The 1000 hour dial will tell you at any time how long you have been using the needle. Dial is marked off in 50 hour units. You can remove your stylus for inspection at any predetermined number of hours. Diameter of the face plate is 2 3/4". Extends 1 7/8" below or behind panel. Complete with instructions. Shpg. wt., 2 lbs. Net 4.95
 PK-224



- PROTECT YOUR PRECIOUS RECORDINGS.
- NO MORE GUESS WORK KEEPS AN ACCURATE RECORD OF NEEDLE USE.

NEW! .7 MIL DIAMOND STYLUS FOR SHURE M70 STEREO CARTRIDGE

PS-91L Net 6.25

ELECTROSONIC LAB "DUST BUG"

Automatically removes dirt and dust on each playing. Light plastic arm mounts by suction cup. Can be permanently mounted by rubber cement. The bottle of anti-static cleaning fluid has a built-in wick for application to a brush and pad at the end of arm. Shpg. wt., 6 oz. Net 5.63
 PK-156 Standard model (A)
 ESL CHANGER DUST BUG (B). The tuft and pad assembly clips onto arm of changer. Performs the same as the standard model. Shpg. wt., 4 oz. Net 4.65
 PK-246 Changer model (B)



DISPENSER OF ACTIVATING FLUID. For Dust Bugs. Net 1.22
 PK-173 Replacement plush pad .78
 PK-174 Replacement nylon brush .98

LAFAYETTE and MOTOROLA The MOST Complete Line of CAR RADIOS

MOTOROLA RADIOS for FOREIGN & DOMESTIC CARS

- Transistor Powered
- Custom Installation
- Perfect for Sports Cars

A **FOR 12 VOLT SYSTEMS**
Compact radio sets that are ideal for custom underdash or in dash installation. "Golden Transistor" circuit employs 2 transistors and 3 tubes. "Volumatic" constant level output eliminates fading and distortion. Antenna Band Pass Filter rejects adjacent signals. Size 6 1/2" Wx 2 1/2" Hx 7 1/4" D. Shpg. wt., 6 lbs.
CR-26 Model 310X for 12 volt negative ground systems Net 39.95
CR-27 Model 311X for 12 volt positive ground systems (in many foreign cars) Net 39.95

FOR 6 VOLT SYSTEMS
Similar to Model 310X but has 4 tubes and 2 transistors and is for 6 volt systems—reversible polarity. Shpg. wt., 6 lbs.
CR-28 Net 39.95

B **UNIVERSAL MANUAL TUNING AUTO RADIOS WITH OVAL PM SPEAKERS**
• Golden Transistor Circuit • Transistor Powered • Volumatic Level Control
• Low Battery Drain-1.4 Amps. • 2.8 Watts of Audio Output
A powerful in-dash mounted car radio employing 2 transistors and 3 tubes offering 7 tuned circuits. Variable tone control and automatic volume and gain controls. A 6x9" external oval, Golden voice speaker is provided. Size 6 1/2" Wx 2 1/2" Hx 5 1/4" D. For 12 volt systems. Shpg. wt., 7 lbs.
CR-106 Model 11MX Net 49.95
Similar to above except 2-transistor and 4 tubes, 5x7" external speaker. For 6 volt systems—reversible polarity. Shpg. wt., 9 lbs.
CR-11 Model 10M Net 54.95

C **TRANSISTOR-POWERED PUSHBUTTON RADIO FOR FOREIGN AND SPORTS CARS**
This new pushbutton radio has been designed for foreign and sports cars. Mounts into the dash or installs under dash in minutes. Full variable tone control, volumatic constant volume level between stations. Elimmoise circuitry and fast push button tuning. Transistor powered for low battery drain with 2 transistors and 3 tubes plus 7 tuned circuits. Supplied with 5x7" speaker. Size: 6 1/2" Wx 2 1/2" Hx 7 1/4" D. For 12 volt cars. Shpg. wt., 8 lbs.
CR-22 Net 54.95
Full 1-year warranty on all parts and labor. Manufacturer's guarantee covers free exchange or repair of any component proven defective in normal use. Removal and re-installation labor extra. Arranged through your local service dealer.



49.95

39.95

54.95



Lafayette
HOT CAR-GO
Starts
Your Car
INSTANTLY

- Starts Wet or Cold Motors Instantly
 - Saves Battery and Gasoline
 - Installs Easily and Quickly
 - 6 and 12 Volt Cars
- 3.49**
- Avoid excess wear and tear on your motor and battery—install Lafayette's Hot Car-Go. Provides 5 times the normal spark for fast starting in any weather, and automatically disconnects when engine is running. Will not damage plugs or distributor. Simple to install—instructions included. Shpg. wt., 1 lb.
MS-784 Net 3.49

THE GAUGES DETROIT LEFT OUT! LAFAYETTE AMMETER & OIL PRESSURE GAUGES



4.49


DON'T trust flashing indicator lights—a burned out bulb can ruin your motor or strand you with a dead battery. All cars with warning lights for oil and battery need these precision gauges. Lights only indicate when oil pressure falls below 15 lbs. or whether or not the generator is working. These Lafayette gauges will replace your panel lights (or if you wish to use both lights and gauges, buy the Tee fitting listed below). Keep a constant check on the condition and performance of your car's electrical and oil pressure systems. The ammeter calibrated in a 60-0-60 scale measures the actual rate of current flow... helps prevent generators from burning out and overcharging or discharging the battery. Exact oil pressure from 0 to 80 lbs. is indicated. Easily installs in any 6 or 12 volt car below the dash, without drilling or can be mounted right in the dash. Both meters are mounted in an attractive chrome panel. Easy to read meters feature 1 1/4" diam. black dial faces with calibrations in white. Size: 5 1/2" Wx 2 1/2" Hx 2 1/4" D. Supplied with all necessary fittings plus full instructions.
MS-788 Shpg. wt., 1 1/4 lbs. Net 4.49
MS-912 Tee fitting Net .49

ILLUMINATED TYPE
Same as above, but gauges are illuminated. Supplied with lamp sockets and both 6 and 12 volt bulbs.
MS-792 Shpg. wt., 1 1/2 lbs. Net 6.49

Consult This Chart To Determine Which Sets Fit American Cars, Sports Cars and Foreign Cars.
Listed on this page. Use this stock number when ordering. Also show your make, model and year and voltage of your car. *SPECIFY VOLTAGE!!

MAKE, MODEL AND YEAR	USE SET	MAKE, MODEL AND YEAR	USE SET
Austin Healy 1957-62	CR-22 or CR-27	Fiat 600-1100 1957-62	CR-106
Borgward 1957-62	CR-11 or CR-28	Ford 1956-62	CR-106
Buick 1954-62	CR-106	Hillman Minx 1957-62	CR-22 or CR-27
Buick Special (Compact) 1961-62	CR-106	Karmann-Ghia (V.W.) 58-62	CR-28
Chevrolet	CR-106	Mercedes Benz 1958-62	CR-26
Citroen ID-19, DS-19 6 Volt	CR-28	M. G. Magnette MGA 1957-62	CR-22 or CR-27
Citroen 1958-62 12 Volt	CR-26	Morris Minor 1957-62	CR-22 or CR-27
Comet 1960-62	CR-106	Oldsmobile F-85 1961-62	CR-106
Corvalz 1960-62	CR-26 or CR-106	Opel 1957-62	CR-11 or CR-28
Dodge Dart 1957-62	CR-106	Peugeot 1958-62	CR-22 or CR-26
Dodge Lancer 1961-62	CR-22, CR-26 or CR-106	Pontiac Tempest 1961-62	CR-106
English Ford 1957-62	CR-106	Porsche 1957-62	CR-11 or CR-28
Falcon 1960-62	CR-106	Plymouth 1956-62	CR-106
		Rambler 1959-62	CR-106
		Renault Dauphine 6 Volt 1955-58	CR-11 or CR-28
		Renault Dauphine 12 Volt 1958-62	CR-26 or CR-106
		Simca Aronde 1958-62	CR-106
		Simca Aronde 1300 1958-62	CR-26
		Studebaker Lark 1959-62	CR-22, CR-26 or CR-106
		Sunbeam Rapier 1957-62	CR-22 or CR-27
		Taunus 1958-62	CR-28
		Triumph TR-3 1958-62	CR-22 or CR-27
		Valiant 1960-62	CR-22, CR-26 or CR-106
		Vauxhall 1958-62	CR-22 or CR-27
		Volkswagen 1952-62	CR-11 or CR-28
		Volkswagen Bus 1952-62	CR-11 or CR-28
		Volvo PV-444, PV-544 1957-62	CR-11 or CR-28

REAR SEAT AUTO SPEAKER KITS



6" x 9" KIT WITH CHROME OR GOLD GRILLE
Complete kit for adding second speaker in rear of your car. Includes a 6x9" PM speaker, 3-position selector switch for cutting in front, rear, or both speakers; dial plate with mounting bracket, knob, and hardware; chrome or gold grille; wire; and wiring instructions. Simple to install. Shpg. wt., 5 lbs.
SK-94 Speaker kit chrome grille Net 3.45
SK-196 With gold grille Net 3.45

DELUXE 6" x 9" KIT with 2.15 oz. ANICO V MAGNET
Same as above but with deluxe speaker with extra-heavy Anico V magnet (2.15 oz.). This is same speaker used in kits selling at twice the price. Shpg. wt., 5 lbs.
SK-37 Speaker kit chrome grille Net 4.65
SK-197 With gold grille Net 4.65

5" x 7" KIT
Same as SK-94 but with 5x7" speaker and grille. 5 lbs.
SK-42 Chrome grille Net 3.05
SK-198 With gold grille Net 3.05

FADER TYPE AUTO KITS
Rear-seat speaker kits identical to those above except with fader-type controls to cut either speaker in or out or balance both. Shpg. wt., 5 lbs.
SK-55 5x7" kit. Same as SK-42 but with fader control. Chrome grille Net 3.29
SK-199 With gold grille Net 3.29
SK-96 6x9" kit. Same as SK-94 but with fader control. Chrome grille Net 3.69
SK-200 With gold grille Net 3.69

DELUXE 6" x 9" FADER KIT
Deluxe kit with extra-heavy-magnet 6x9" speaker, plus fader control. Shpg. wt., 5 lbs.
SK-56 6x9" kit. Same as SK-37 but with fader. Chrome grille Net 4.89
SK-201 With gold grille Net 4.89

HI-FI REAR SEAT AUTO SPEAKER KITS



ADD HI-FI LISTENING TO YOUR CAR
FEATURING 6x9 COAXIAL SPEAKER WITH TWIN TWEETERS
Identical to SK-37 auto speaker kit shown on this page except has hi-fi 6x9" coax speaker instead of single-cone unit. Excellent for music lover who wants quality reproduction. Shpg. wt., 6 lbs.
SK-77 With Chrome Grille Net 8.80
SK-202 With Gold Grille Net 8.80


FADER TYPE AUTO KIT
Coaxial speaker kit (same as SK-77) with fader for flexible control of both front seat and rear speakers and sound balancing. Shpg. wt., 6 lbs.
SK-78 With Chrome Grille Net 9.00
SK-203 With Gold Grille Net 9.00

ADJUSTABLE AUTO HEADREST




Fits Any Car Seat
Comfortable Foam Pillow Cushion
Washable Zippered Cover
Avoid auto fatigue with this adjustable headrest. Used by driver or passenger to relieve neck strain—ideal for long or short trips. Completely adjustable for any car or position. Comfortable foam pillow cushions with removable, washable zippered covers. Strong chrome frame fits any car seat. Hold-on-bars are latex coated.
AA-90 Shpg. wt., 3 lbs. Net 5.93

GRANCO FM CAR CONVERTER



NEW!
Add Hi-Fi to Your Present Car Radio
• Exclusive "Auto-G" Coaxial Tuner
• Automatic Frequency Control
• Quick, Under-Dash Installation
39.50
Get added pleasure from your auto radio listening with the new Granco FM car converter—lets the incomparable richness of High Fidelity FM travel with you. Features the exclusive "Auto-G" coaxial tuner for highest sensitivity and selectivity. Automatic frequency control locks in stations. Economical to operate too—uses the existing car radio antenna and circuits. Complete 12-volt battery operation. Compact design—book size, 1 1/4" thick. Stays in place with just 2 screws, 1 wire and antenna plug-in.
CR-105 Shpg. wt., 1D lbs. Net 39.50

AUTOMOTIVE TESTING EQUIPMENT



(A) MOTOR ANALYZER
All the advantages of a well-equipped service shop in a light, hand-held package. Ideal for do-it-yourselfers, sports car Rallyers, etc. The Analyzer enables you to test ignition coil output, spark plugs, insulation breakdowns; locates poorly adjusted carburetor, sticky or burnt valves, weak valve springs; checks valve timing, choke, muffler, vacuum tank, manifold, fuel pump vacuum and pressure and vacuum operated equipment.
14Wx7 3/8 Hx3 1/2" D. Shpg. wt., 5 1/2 lbs.
AA-49 Net 15.95

(B) REMOTE STARTER SWITCH
Eliminates the need of a second man when making compression, fuel pump, generator, starter, and electrical tests. Permits the mechanic to crank the engine from any position. Shpg. wt., 1/2 lb.
AA-50 Net 2.59

(C) MOTOR GUIDE-VACUUM FUEL PUMP TESTER
Combination motor guide, vacuum and fuel pump tester, 4 color zones: Economy Driving, Fast Pick-up, Coasting and Idle. Promotes good driving habits and economical gas mileage. Warns when tuneups are necessary. Shpg. wt., 12 oz.
AA-51 Net 3.75

(D) COMPRESSION TESTER
Gives quick, accurate readings of compression pressure. Merely unscrew the spark plug, plug tester into spark plug hole and read pressure. 2 1/2" dial reads to 300 lbs. Stem is offset 15° for reaching back cylinders. Complete with instructions. Shpg. wt., 12 oz.
AA-52 Net 3.75

(E) STANDARD TIMING LIGHT
Employs the stroboscopic principle of light synchronized with motion for adjustment and setting of ignition timing under actual operating conditions. Shpg. wt., 1 lb.
AA-53 Net 3.25

(F) TACHOMETER
Here's the instrument for the most important check of an engine's performance: the RPM test. Tests 4, 6 and 8 cylinder engines with both 6 and 12 volt systems. Operated by two inexpensive penlight batteries which last about a year. Large dial reads 0-1000 and 0-5000 RPM. Shpg. wt., 2 1/2 lbs.
AA-54 Net 28.50

CARDIO-MASTER

• Convert your Transistor Radio into a Car Radio
• For all Makes of Cars — Cabs — Trucks
2.98
Cardio master is a magnetic device designed to hold a portable transistor radio in the area of a car's windshield to make it operate as an auto radio. Car's owner can remove a radio from the Cardio master for use as portable or to avoid theft while the car is parked. Fits any "pocket" transistor radio. Will not come loose in the bumpiest roads. Includes magnetic base, brackets, hardware, adjustable band and complete, illustrated instructions.
AA-45 Shpg. wt., 2 lbs. Net 2.98

CAM-DWELL INDICATOR

A high quality instrument for solving all CAM-DWELL problems. Checks the number of degrees a distributor can rotate while the breaker points remain closed. Too much rotation means points are set too close, too little means breaker points are not closed long enough for adequate build up of the magnetic field in primary coil, permitting arcing across points. Requires no electrical outlet. Distributor need not be removed. Compact, portable. Complete with case and includes chart showing specifications for all popular cars.
AA-98 Shpg. wt., 2 lbs. Net 3.95



NEW! LAFAYETTE HE-20A CLASS D Deluxe CITIZENS BAND TRANSCEIVER



**Not A Kit!
COMPLETELY WIRED!**

109⁵⁰

NO MONEY DOWN

WITH Foolproof Dependable Relay Switching As Found In Most Expensive Equipment. NOT Electrical Switching With It's Voltage Hazards. NOT Electronic Switching With Inefficiency Due To Tube and Parts Deterioration.

Quality engineering, design, and features give this Deluxe transceiver a place all-its-own in the Citizens Band Field. Operating within the limits prescribed by the FCC, the HE-20A supplies you with a highly efficient 2-way radio-telephone communications system from your office, truck, auto, boat, store, home, etc. Two or more will serve as an effective communications system over a distance of up to 20 miles or more, depending on the terrain and the height of the antenna.

3 dual function tubes, 1-Quadri-purpose tube, 3 tubes, and 2 Silicon rectifiers give 14 tube performance. The transmitter section features precision engineering to insure power-packed communications. The 5 watt-input crystal-controlled transmitter may be operated on any 4 of the 23 channels assigned by the FCC. The operating channel can be selected by a knob on the front panel (transceiver comes with pair of crystals for channel 9). The receiver circuits provide for 4 crystal controlled receiving channels plus a tuneable superheterodyne receiver that covers all 23 assigned channels, with a sensitivity of 1 microvolt. Effective built-in Squelch circuit quiets the receiver when no signal is being received. Series Gate Noise Limiter materially reduces ignition noise and other unwanted interference. An illuminated dial with planetary vernier tuning is clearly marked with channel numbers and lights up when tuned to any channel. The receiver terminates in 4" speaker amply supplied by a 2-watt audio power output section. The unit comes complete with a push-to-talk ceramic microphone and a bracket for convenient mounting to the side of the transceiver.


Push-to-Talk operation is accomplished with a sturdy, dependable relay. An "S" meter calibrated in S units 1-9 and to 30 db. above S-9, allows measurement of incoming signal strength. The meter is wired with a switch to enable monitoring of final amplifier wattage. Incorporates Pi-network for optimum matching to 30-100 ohm antenna for high signal output. A low-loss antenna jack is mounted at the rear of the cabinet to accept the popular PL-259 connector used with dipole, ground plane, rod, and direct mounting (Lafayette HE-19) Antennas. Rugged, low silhouette case with a bracket handle for installation at any location and in any position. Tube line up 1-6AW8A, Oscillator/Amplifier; 1-6BA6, RF Amplifier; 1-6BA6 1st IF Amplifier; 1-6BE6, Converter 1-6EA8, 2nd IF Amplifier and 1st Audio Amplifier; 1-6AQ5 Audio Output/Modulator; 1-6T8, ANL, Detector, AGC, Squelch Clamp and 2nd Audio Amplifier. Size 12x5x8 1/2" D. With 115 Volts AC/12 Volts DC or 115 Volts AC/6 Volts DC Power supply. Shpg. wt., 14 lbs.

HE-20AWX 115 Volts AC/12 Volts DC	Net 109.50
HE-43WX 115 Volts AC/6 Volts DC	Net 109.50
HE-830L Transmit Crystal (Specify Channel or Frequency)	Net 2.25
HE-22L Receive Crystal (Specify Channel)	Net 2.25
Direct plug in antenna for short distance communications.	Net 3.95
HE-19 Shpg. wt., 1 lb.	

LAFAYETTE'S SENSATIONAL CITIZENS BAND TRANSCEIVER—NOW WITH THESE ADDED DELUXE FEATURES!

- Pi-Network gives optimum line and antenna matching for greater power output.
- Calibrated "S" Meter
- Improved Series Gate Noise Limiter

EXCELLENT FOR BUSINESS, FARM, INDUSTRY, CAR, BOAT, PERSONAL AND SPORTS USE





LOOK AT THESE QUALITY FEATURES

- 1 14 Tube Performance, 3 Diodes
- 2 } 4 Crystal-Controlled Transmit Positions
4 Crystal-Controlled Receive Positions
- 3 Tuneable Receiver over all 23 channels
- 4 Calibrated "S" Meter with Switch To Measure Signal Strength and To Check on Wattage Input to Final
- 5 Dependable Push-To-Talk Ceramic Microphone & Relay
- 6 Adjustable Squelch Control
- 7 Highly Effective Automatic Series Gate Noise Limiter
- 8 Illuminated Dial
- 9 Built-in 12 or 6 volt Power Supply for Mobile Use
- 10 Comes Complete with Matched Crystals For Channel 9



New! LAFAYETTE HE-15A 2-WAY SUPERHET CITIZENS BAND TRANSCEIVER!



Completely Wired - NOT A KIT!



Outstanding Performance, Design, and Ease-Of-Operation. Meets All FCC Requirements

CITIZENS BAND—The New Two-Way Personal Communications Method for Everyone—Fill out the FCC form enclosed with each Lafayette Transceiver. No examination or technical knowledge required—Any citizen 18 years or older is eligible for a license.

ONLY 59.50 NO MONEY DOWN

COMPLETE 2-WAY COMMUNICATIONS FOR BUSINESS, HOME, FARM, BOAT, AND SPORTS
Not Superregenerative but SUPERHET!
NOW WITH ADDED FEATURES

- Improved Selectivity and Power Output
- Effective Full-Wave Variable Noise Limiter
- RF Jack on Front Panel
- Ceramic Temperature-Free Microphone
- 5 Crystal-Controlled Transmitting Positions
- Superheterodyne Tuneable Receiver Over Full 23 Channels
- 4 Dual Function Tubes, plus 2 Single Function Tubes, plus 2 Rectifiers for 12 Tube Performance
- Planetary Vernier Tuning
- Complete with Transmitting Crystal for Channel 9

THE GREATEST VALUE in the CITIZENS BAND FIELD

The Lafayette HE-15A Superheterodyne Transceiver is both a compact precision transmitter and receiver designed to operate on the new class D "Citizens Band." Two or more of these units furnish your own communications system covering up to a 20 mile or more radius depending on antenna height and terrain. The Transceiver features 5 crystal controlled transmitting channels operating at a maximum legal power input of 5 watts fully modulated, RF stage in both transmitter and receiver. The 5 position crystal selector on the front panel selects any one of 5 transmitting frequencies. These 5 crystals are readily accessible by means of a removable front plate. The superheterodyne receiver is tuneable over the full 23 channel band with 3 watts audio output, AVC, and an amazingly effective Full-Wave Variable Noise Limiter. The Noise Limiter is continuously variable from the front panel for diminishing ignition and other unwanted noise pickup. RF jack on the front panel may be used to monitor the current in the final tube using external meter. Controls include a 3 position function switch (transmit, receive, and transmit with spring return), planetary vernier tuning plus variable noise limiter. Output impedance matches 52 and 72 ohm antenna with Amphenol type coax connector. Has large PM speaker; input jack for crystal or ceramic microphone; power receptacle in rear for AC


line and 6 or 12 volt external power supply. Supplied with single transmitting crystal for channel 9, high output ceramic microphone, and brackets for easy mounting of units in auto, boat, etc. Operates on 115 volts AC. Addition of 6 or 12 volt power supply (separately supplied) adapts transceiver for mobile operation. Size 10 1/2" x 5 1/2" x 6 3/4" D. Tube complement: 2-6U8A/6EA8, 1-6AL5, 1-6V6, 1-12AX7, 1-6AW8.

HE-15A WX Shpg. wt., 11 lbs. Net 59.50
POWER SUPPLY: Adapts HE-15A for mobile operation. Complete with cable, 6 or 12 volt vibrator and mounting flanges. Completely enclosed. Size 4 1/2" x 6 1/2" x 4" H. Shpg. wt., 4 lbs. Net 10.95
HE-16 W For 12 Volts Net 10.95
HE-18 W For 6 Volts Net 10.95
ANTENNA: Base loaded telescoping whip antenna with PL259 coax connector. Mounts directly on rear of cabinet. Telescopes to only 15". For short distances. HE-19 Shpg. wt., 2 lbs. Net 3.95

TRANSMITTING CRYSTALS: For any of the 23 channels. Specify channel or frequency. Net 2.25
HE-830L Net 2.25



NEW! LAFAYETTE (6 and 10) METER TRANSCEIVERS



LAFAYETTE NEW UNIVERSAL 6 METER AND BROADCAST MOBILE ANTENNA

ONE ANTENNA FOR BROADCAST AND 6 METERS!
AT A SENSATIONALLY LOW PRICE OF

475

Here is a highly efficient 6 meter antenna that replaces your Auto radio antenna for operation on both 6 meters and for regular AM broadcast reception. 59" stainless steel mast, all chrome ball type base adjustable to 180° for front rear or side mount. Complete with 54" lead. Highly versatile and durable. Shpg. wt., 4 lbs. ME-801WX Net 4.75

Hi-Par "SATURN 6" MOBILEER

A compact, horizontally polarized mobile antenna for 6 meters. Since most fixed 6 meter stations have adopted horizontal polarization, the "Saturn 6" offers a distinct advantage over the vertical whip. It is essentially an end-loaded folded dipole with 3 ring design, approximately 20" in diameter, 5" high. Design center is 50.5 Mc but resonant frequency may be varied between 50.5 and 53.0 Mc. Easily fed with RG58/U coax through a simple "Q" section. Strong and rigid aluminum construction; net weight under 2 lbs. Easily supported on pipe, tubing or stiff rod. Model S-1—"Saturn 6" Antenna, 2-piece adjustable aluminum mast, mast bracket, universal bumper hitch. No holes to drill. Less coax feed line. Shpg. wt., 5 lbs. ME-805W Net 16.59


5 ELEMENT 6 METER BEAM

A rugged, full size 6 meter beam constructed of 3/4" 0.050 wall aluminum tubing with hardwood dowling at high stress points. Boom is 0.058 wall drawn aluminum. Driven element is concentric gamma matched for direct coax feed. Light enough to turn on a 1/2" diameter rotator. Turning radius—7'8"; for any heavy duty TV rotator. Turning radius—29'. Comes with Forward Gain—9.5 db; F/B ratio—29 db. Comes with all parts marked for quick, neat assembly and center band operation. Shpg. wt., 15 lbs. ME-746WX Net 19.50

NEW! LAFAYETTE DELUXE 6 METER TRANSCEIVER MODEL HE-45

- Highly Sensitive Superheterodyne Receiver Section for 50-54 Mc • Effective Series Gate Noise Limiter • 3-Stage, 12-Watt Transmitter with 2E26 Final • Built-in 117 VAC and 12 VDC Power Supplies • Pi-Network Transmitter Output • Illuminated Panel Meter for Plate Current and "S" Readings • Complete With Push-To-Talk Ceramic Microphone

Now, for 6 meters, Lafayette offers a deluxe transmitter-receiver in a single package, with features which make the low price hard to believe. Provides maximum convenience and flexibility in either mobile or fixed operation. The superheterodyne receiver section employs an RF stage with peaking control on front panel, and two i.f. stages at 1650 Kc, for 1 μ v sensitivity and 35 db image rejection. Tunes the entire 6 meter band from 50 to 54 Mc, with calibrated illuminated vernier tuning dial. Features an adjustable series gate noise limiter, built-in speaker. Illuminated panel meter serves as an "S" meter when meter function switch is set to the proper position. Transmitter section employs a 6U8 oscillator and buffer/multiplier, driving a 2E26 final with a plate input of approximately 12 watts on AM. Pi-network coaxial output is adjustable for matching a wide range of antenna impedances. Sockets for five 8 Mc fundamental crystals plus an input for external VFO on the front panel, with corresponding 6-position selector switch. A spotting switch is provided for zero beating or for locating the transmitting frequency in the receiver. Panel meter reads plate current when switch is set to proper position. A dual power supply for 117 VAC and 12 VDC is built in, making the HE-45 perfect for mobile operation. Push-to-talk operation provided. Tube complement: 1-6BA6 RF amplifier, 1-6U8/6EA8 osc./mixer, 1-6BA6 1st i.f. amp., 1-6U8/6EA8 2nd i.f. amp./1st audio, 1-6CN7 detector/noise limiter, 1-6AQ5 audio output and transmitter modulator, 1-6U8/6EA8 transmitter oscillator and buffer/multiplier, and 1-2E26 transmitter final amplifier. Housed in a rugged, low-silhouetted case with attractive, metal panel, the HE-45 comes complete with push-to-talk ceramic microphone, crystal for 50.12 Mc, detachable mounting bracket, and all power cables. Only 12x5x8 1/2"D. Shpg. wt., 15 lbs. ME-45WX Net 109.50



MADE IN U.S.A.

109.50 NO MONEY DOWN

LAFAYETTE 6 METER TRANSCEIVER

SMALL, COMPACT COMPLETE 6 METER STATION—TAKE IT WITH YOU ANYWHERE!

- Ceramic Temperature-Free Microphone

57.50 NO MONEY DOWN



MADE IN U.S.A.

- Superhet Receiver Tunes Entire Band (50-54 mc)
- Efficient Adjustable Noise Limiter • 7 Watts Input to 6CX8 Pentode Final • New Efficient Pi-Network Output with Hi-Q Tuned Circuit • Separate Oscillator—Final Stage • Accessible Front Panel Socket With Crystal For 50.2 MC Output

Meet the enjoyable challenge of 6 meter operation efficiently and economically with the Lafayette HE-35 6 meter transceiver. This small, compact transceiver features a Transmitter with 7 watts input to a 6CX8 pentode final, high quality plate modulation, built-in adjustable TVI filter, and antenna matching network for 30 to 100 ohm antenna; Superheterodyne receiver tunes entire 6 meter band (50-54 mc) and includes variable noise limiter. The transmitter uses a 3rd overtone crystal in easily accessible socket located on front panel; has RF output and modulation indicator. Low-loss SO-239 coaxial antenna output jack. Complete with attractive high output ceramic microphone with on-off slide switch and mounting brackets for mobile mtg. 6 or 12 volt power supply separately available for mobile operation. Built-in power supply operates on 110-120 volts, 60 cycle. 10 1/2 x 5 1/2 x 3 1/4"D. Tubes: 2-6U8A/6EA8, 6AL5, 12AX7, 6V6GT, 6CX8. Shpg. wt., 11 lbs. ME-35 AWX Net 57.50


MOBILE POWER SUPPLIES
5 1/2 x 4 1/4 x 2 1/4" Shpg. wt., 4 lbs. Net 10.95
ME-16W 12 Volts Net 10.95
ME-18W 6 Volts Net 10.95
Additional Crystals—Specify Frequency
ME-36L Shpg. wt., 4 oz. Delivery 3 wks. Net 4.95

NEW! LAFAYETTE 10 METER TRANSCEIVER MODEL HE-50

- Superhet Receiver Tunes 10 Meter Phone Band from 28.5 to 29.7 Mc
- Effective Series Gate Noise Limiter • 12-Watt Transmitter with Pi-Network Output • Built-in Dual Power Supply for 117 VAC and 12 VDC—Ideal for Mobile or Fixed Operation


109.50 NO MONEY DOWN

• With Push-To-Talk Ceramic Microphone



MADE IN U.S.A.

Here is a new transceiver with the deluxe mechanical and electrical features of the HE-45, applied to the 10 meter amateur phone band. Receiver has 1 μ v sensitivity. The i.f. of 1650 Kc results in a 45 db image rejection on 10 meters. Includes automatic series gate noise limiter. Transmitter runs 12 watts input to a 2E26 final, with pi-network coax output to match any antenna. Uses 7 Mc fundamental crystals or external VFO. Sockets for 5 crystals plus VFO input, with corresponding 6-position selector switch, located on front panel. Physical layout is identical to that of the HE-45. Includes big illuminated tuning dial and illuminated panel meter which serves as "S" meter and final plate current meter. Built-in dual power supply for 117 VAC and 12VDC make the HE-50 the ideal solution to the problem of finding a compact, completely self-contained 10 meter rig which can be operated mobile or used at home without modification. The package make it a value that is hard to beat, at a price designed for the conservative budget. Transmitter and receiver features which are combined in this single package make it a value that is hard to beat, at a price designed for the conservative budget. Tube complement: 1-6BA6 RF amplifier, 1-6U8/6EA8 osc./mixer, 1-6BA6 1st i.f. amp., 1-6U8/6EA8 2nd i.f. amp 1st audio, 1-6CN7 detector/noise limiter, 1-6AQ5 audio output and transmitter modulator, 1-6U8/6EA8 transmitter oscillator and buffer/multiplier, and 1-2E26 transmitter final amplifier. Housed in a rugged, low-silhouetted case with attractive, metal panel, the HE-50 comes complete with push-to-talk ceramic microphone, crystal for 28.6 Mc, detachable mounting bracket, and all power cables. Only 12x5x8 1/2"D. Shpg. wt., 15 lbs. ME-50WX Net 109.50



NEW! LAFAYETTE TM-26 ILLUMINATED COMMUNICATIONS 2 1/2 "S" METER

- Replaces Many Communications Receiver "S" Meters
- 2 Jewel Movement • Clear Plastic Front
- Calibrated to S9 + 40db
- BIG BROTHER TO THE LAFAYETTE TM-11

A new signal strength meter (basic 1 ma, 2 jewel movement) designed to replace many "S" meters used in communications receivers. Clear plastic front measures 2 1/2" square and meter fits standard 2 1/4" round hole. Perfect for the experimenter and amateur. Complete with mounting screws, instructions for installation and use. For 6 volt or 12 volt operation. Zero adjustment control on front panel. Shpg. wt., 1 lb. Net 3.95

LAFAYETTE MINIATURE ILLUMINATED "S" METER **2.95**
Similar to TM-26 but dial face is only 1 3/8 x 1 1/4" overall behind panel. Illuminated for either 6 or 12V operation. Supplied with mounting screws. Net 2.95

LAFAYETTE RADIO FIELD INDICATOR

- A MUST FOR ALL HAM AND CB OPERATORS
- Continuously indicates transmitter output
- Rugged 200 μ a meter movement
- Requires no Electricity, Batteries, or Transmitter Connection
- Powerful Magnet on Bottom Plate for Mounting on Dashboard or Other Metal Surface

With this rugged, new radio field indicator you can check performance of your marine, mobile or fixed transmitter. Features a 200 μ a meter movement with variable sensitivity control. Earphones can be plugged in for an aural check of output. Antenna extends from 3 1/4" to 10 3/4". Powerful magnet on bottom plate allows easy mounting on car dashboard or metal surfaces. Use anywhere... requires no electricity or batteries. Dimensions: (less antenna) 3 1/4" W x 2 1/4" H x 2" D. TM-14 Shpg. wt., 7 oz. Net 6.95
High output crystal earpiece for use with TM-14. MS-439 Net 1.09



6.95 TM-14

NEW! LAFAYETTE TRANSISTORIZED FIELD STRENGTH METER

- Permits Easy Tune-Up For Maximum Transmitter Output
- Earphone Jack to Monitor Audio • Tuned Input from 2.53 to 57 MC

A transistorized, tuned field strength meter covering 2.530 Mc to 57.000 Mc in 3 bands, ideal for use with ham, Citizens Band or other transmitters within this frequency range. Enables user to tune his transmitter and antenna for maximum RF output. The RF is sampled by a plug-in telescoping antenna (supplied) and relative field strength is read on a 200 μ a meter calibrated from 0 to 10. Earphone jack provided for the monitoring of any audio on the signal. Electrical and mechanical zero adjustments on front panel. Other controls: gain/on-off switch, tuning, and band selector switch. Powered by single small 1 1/2 volt battery with lifetime approaching "shelf life"—can be operated anywhere. In attractive metal cabinet with telescoping antenna and battery. TM-16A Shpg. wt., 2 lbs. Net 15.95
High output earpiece for use with TM-16A. MS-439 Net 1.09
BA-155 Replacement battery for above Net .095



15.95 TM-16A

NEW! LAFAYETTE TM-59'er "S" METER

- Now For Hams, SWL's and CB'ers—A Signal Strength Meter Using VTVM Principles • Easy To Install and Operate
- Magnetic Feet For Mobile Dashboard Mounting
- Sensitivity and Zero Adjust Controls

Designed for use with any superheterodyne receiver employing AVC, the TM-59'er utilizes a high input Wheatstone bridge circuit which produces no detrimental loading effect upon the receiver. Meter is calibrated in "S" units from 1 to 9, and in db up to 40db over S9. Includes zero adjust and sensitivity controls. Partial peak clipping is provided for noise limiting. Installation is simple—only 4 leads to connect for input, B+, filament and ground. The use of a 12AU7 tube makes the TM-59'er adaptable to either 6 or 12 volt equipment, and to receivers using 150 ma or 300 ma series string filament systems. Requires 150-200 VDC for B+ which can be "stolen" from most receiver power supplies. Complete with 12AU7 and installation instructions. TM-59A Shpg. wt., 2 lbs. Net 8.95



8.95

novatech NEW! 4-BAND AIRCRAFT RECEIVER

Powerful 7 tube superhet receiver. On VHF, tunes 108-130 Mc for monitoring control towers, aircraft in flight, control centers, etc. On LF, tunes 200-400 KC; receives up-to-the-minute U.S. Weather Bureau Aircraft weather reports for a radius of 250 miles. On Marine & Police, tuner 1.6 — 5 MC which includes marine radio telephone, ship-to-ship and ship-to-shore, Coast Guard, fishing boats, police calls plus the 80 meter on amateur band. Receiver also covers standard AM broadcast band from 550 to 1600 KC. Built in squelch, headset and phono jacks, 6" oval speaker. 12x6x6". For 115 V. AC. Shpg. wt., 10 lbs. ME-903WX Net 99.95
Nova-Tech VHF Roof Antenna (NT-4), with 50 ft. coax. cable and connectors. Shpg. wt., 8 lbs. ME-901W Net 21.88
You Save 12.93 Lafayette Special HE-903WX and HE-901W. SP-251WX Shpg. wt., 18 lbs. Net 108.90



NEW! CODOME AUTOMATIC MORSE CODE INSTRUCTION MACHINE FOR THE NOVICE

The CODOME and its accompanying manual provide all the materials necessary to prepare the beginner for his Novice class amateur license examination. The machine itself sends groups of letters and numbers automatically, in random order. Built-in key permits the student to develop his sending technique in step with his receiving technique. As each group of characters is being practiced, the student is introduced, by means of the accompanying manual, to the basic concepts of electricity and radio, and to the FCC regulations pertinent to amateur communications. Each code group has a corresponding lesson in the manual, with exam-type questions and answers. Once the code and theory are mastered, the student should have no difficulty in fulfilling the Novice requirements. For 117 VAC. 2 1/4 x 5 1/4 x 6 3/4". ME-696 Shpg. wt., 2 1/2 lbs. Net 17.95

NOW FROM LAFAYETTE 2 NEW ADVANCED DESIGN RECEIVERS

69.50

NO MONEY DOWN

MADE IN U.S.A.



THE BRILLIANT NEW LAFAYETTE HE-41 ALL-BAND RECEIVER

Outstanding All Band Reception—Compare this new Lafayette HE-41 Communications Receiver feature for feature with units far above Lafayette's low price. One of the great all time buys in Amateur Equipment!

Utilizing advanced design and rugged printed circuit techniques, the HE-41 provides extra sensitivity with better, quieter reception even on the highest frequency bands. Has 6 tubes and is transformer powered (Not AC/DC) to give higher over-all gain plus better signal-to-noise ratio. In addition, high-Q, permeability-tuned coils are employed to provide high sensitivity, while a high image and spurious response rejection is made possible by a high-frequency single-conversion I-F.

Panel controls include: Main Tuning, Bandsread Tuning, Bandswidth, Audio Volume, Antenna Trimmer, Sensitivity and Function Selector. Two full-vision, illuminated, slide-rule type dials give instant identification

of broadcast and short-wave frequencies. The vernier tuning knob is counter-weighted for smooth, non-critical short-wave tuning. Amazing audio-fidelity is furnished by the HE-41's built-in speaker. However, jacks are provided for connection to a larger external speaker or for headphone use.

Attractively finished, the HE-41 utilizes a handsome diecast front panel assembly in a formed metal cabinet with aluminum trimmed plastic knobs. Tunes the following ranges: Band 1, 54-1.6mc; Band 2, 1.8-6mc; Band 3, 6-13mc; Band 4, 13-34mc. . . . bandsread dial provides logging scale and calibrated scales for amateur bands. Tube Complement: 6BE6 (conv.); 6BA6 (1st I-F); 6BA6 (2nd I-F BFO); 6AV6 (det. AVC. 1st audio); 6CM6 (2nd audio); and 6X4 (rect.). Size: 8Hx 10½Dx16¼"W. Shpg. wt., 24 lbs. For 117 V, 50/60 cycle AC operation.

HE-41WX Net 69.50

THE WORLD AT YOUR FINGERTIPS!

Near LONDON, PARIS, BERLIN, MOSCOW, plus the Standard Broadcast Band




- 4 Full Bands . . . 540 KC to 34 MC
- Bandsread Dial Provides Logging
- Transformer Powered (NOT AC/DC)
- High Q Permeability-Tuned Coils
- Two Full-Vision, Illuminated Slide-Rule Type Dials



MADE IN U.S.A.

THE NEW! HE-42 SSB-AM-CW 6 TO 80 METER RECEIVER



164.50

NO MONEY DOWN

PHENOMENAL PERFORMANCE & FEATURES:

- SSB-AM-CW Reception on 6 Amateur Bands—80-40-20-15-10-6 Meters
- Excellent Sensitivity and Signal-To-Noise Ratio On All Bands, Including 6 Meters
- Features AVC, Automatic Noise Limiter & Built-In "S" Meter
- Exclusive Peaking-Type "Q" Multiplier • Double Conversion, Two Second Detectors • Full-Vision Drum Dial

SPECIFICATIONS
 FREQUENCY RANGE: 3.5—4.0 mcs. 7.0-7.3 mcs. 14.0-14.35 mcs. 21.0-21.45 mcs. 28.0-29.7 mcs. 50.0-54.0 mcs. SENSITIVITY: Less than 1 microvolt for 6 db signal-plus-noise/noise ratio. SELECTIVITY: 3.1 KCS at 6 db down. 12.6 KCS at 60 db down. "Q" Multiplier in circuit: Continuously adjustable to maximum of 100 cps (approx.) at 6 db down. IMAGE REJECTION: Minimum 54 db all bands except 40 db, 6 meters. INPUT IMPEDANCE: 100-ohms unbalanced antenna input. OUTPUT IMPEDANCE: 3.2 ohms. I-F FREQUENCIES: 1st I-F, 2065 KCS, 2nd I-F, 263 KCS. Detectors: Diode detector for AM. Product detector for SSB/CW. Selected automatically by function switch. BFO: Adjustable for SSB/CW reception. NOISE LIMITER: Automatic, Operable on AM only. OPERATING VOLTAGE: 117V 50/60 cycle AC. Power requirement 65 watts. TUBE COMPLEMENT: 6BZ6 RF 1/2-6U8A 1st converter. 1/2-6U8A HF osc. 6BE6 2nd converter. 6BA6 1st I-F amp. 6BA6 2nd I-F amp. 6AL5 2nd det. AVC. ANL. 6BE6 product det. BFO. 1/2-12AX7 1st AF. 6AQ5 output and 5Y3GT rect. OB-2 voltage reg.

Phenomenal Stability..... Clear as Bell Performance that makes this new Lafayette HE-42 Communications Receiver a worthy addition to the finest ham shack. Employing the most advanced communications engineering techniques, the HE-42 achieves high sensitivity and excellent signal-to-noise ratio to—and through—the popular 6 meter amateur band. Since stability is a prime consideration in SSB reception, both oscillators, HF tunable and LF BFO are stable and have low frequency drift. Each amateur band is spread across the full vision, drum dial scale as an aid to precise tuning. In addition the circuitry features 2 second detectors—a product type for better SSB and CW reception plus a diode type for AM. The proper detector comes automatically into operation when the function switch is set to the desired mode. Double conversion employs a first I-F at 2065 KCS for maximum image rejection plus 2nd I-F at 263 KCS with multiple-tuned band-pass circuitry to produce desirable steep shoulder I-F response characteristics. An exclusive peaking-type "Q" multiplier allows continuous variation of I-F selectivity for CW down to the point where the curve is only 100 cps across the 6 db points. Also featured are AVC and an automatic noise limiter plus an "S" meter to aid tuning and for comparative signal reports. Ruggedly constructed and attractively finished in gun-metal grey with front panel in black and satin aluminum. Size 8Hx16¼Wx10½"D. Shpg. wt., 26 lbs. HE-42WX Net 164.50

NATIONAL NC-60 SPECIAL "B" RECEIVER



National's new all-wave low-priced receiver which features continuous coverage of AM Broadcast, Amateur and World Wide Short Wave Bands; brilliantly styled by Peter Quay Yang for easy operation, ready reading and attractive decor. Features include: 4 separate bands—540 Kc-1600 Kc; 1.6-4.5 Mc; 4-12 Mc; 10.5-31 Mc with police, CD, marine, aircraft, amateur, etc. stations clearly marked; plus 0-100 logging and bandsread scale. Bandsread operative on all bands. Audio section drives built-in speaker or front panel phone jack. Has AM, CW switch, standby-receive switch, 2 degrees of selectivity, complement of 4 tubes plus rectifier, superheterodyne circuit. Finish is two tone black and gray enamel. Size: 7¾ x 8¾ x 13½". Shpg. wt., 15 lbs. HE-200WX Net 59.95

FREE WITH PURCHASE OF NC-60 SPECIAL "B"

- ME-42 REGULAR PRICE 3.40
- KT-77 Shortwave Antenna Kit. Shpg. wt., 1½ lbs. Net 1.05
- ME-42 Headset. Shpg. wt., 1½ lbs. Net 2.35
- SPECIAL LAFAYETTE OFFER HE-200WX plus KT-77 plus ME-42. Shpg. wt., 18 lbs. SP-178WX Net 59.95



SX-110

MODEL SX-110 HAM-SWL RECEIVER

• CRYSTAL FILTER. 80, 40, 20, 15, AND 10 METER BANDS Superheterodyne receiver covers 540 KC (broadcast band) to 34 MC in four bands. Features slide rule type dial and electrical bandsread over the 10, 15, 20, 40 and 80 meter amateur bands. Separate bandsread tuning condenser. Switchable crystal filter and built-in "S" meter. All controls are on front panel. Output: 2 watts. Grey steel cabinet with chrome trim. Size 18¼Wx8Hx 10¼"D. 117 AC. Shpg. wt., 32 lbs. HE-108WX Net 169.95

MODEL S-108 RECEIVER

Same as SX-110 less S-meter, antenna trimmer, and crystal filter, but includes a built-in speaker. HE-107WX Net 139.95



S-118

NEW S-118 GENERAL COVERAGE RECEIVER

General coverage superhet receiver with extended low frequency tuning. Covers the broadcast, amateur and international short wave bands, plus consolan, aeronautical, mobile and international distress frequencies. Frequency range is 185 Kc to 31 Mc in 5 bands: 185 Kc to 420 Kc, 495 Kc to 1.620 Mc, 1.600 Mc to 4.950 Mc, 4.850 Mc to 15.000 Mc, and 14.800 Kc to 31.000 Mc. Features include electrical bandsread, BFO, noise limiter, separate sensitivity control, headphone jack and built-in speaker. Antenna: loopstick for two lowest bands with provisions for external antenna on all bands. The upper three bands have an antenna input impedance of 50-75 ohms. Tube complement: 6BL8 mixer/oscillator, 12BA6 1st i.f. (455 Kc), 6BL8 2nd i.f./BFO, 6T8 detector-ANL-AVC-1st audio, 6AQ5 audio output. Power supply contains 2 silicon diode rectifiers. For 105-125 VAC 50/60 cps. 13¾"Wx6¼"Hx 8½"D. Shpg. wt., 19 lbs. HE-131WX Net 99.95

NEW LOW COST RECEIVERS IDEAL FOR NOVICE AND SHORTWAVE LISTENER



S-120

S-119K

NEW! S-120 RECEIVER

Covers Broadcast Band 550-1600 KC plus 3 Short Wave Bands 1600 Kc to 30 Mc. 3 Antennas, Slide Rule Bandsread Dial, New Compact Styling.

This new precision built receiver features electrical bandsread with slide rule bandsread dial and separate bandsread tuning condenser. Front panel headphone jack which automatically disconnects self-contained speaker may be used to drive remote 8 ohm speaker. Has 3 antennas (ferrite loop for broadcast band; adjustable whip for short wave; wire antenna). Tube complement: 12BE6 Converter, 12BA6 I-F amplifier, B.F.O., 12AV6 Audio amplifier, AVC detector, 50G5 Audio, plus Selenium Rectifier, 455KC I-F. Attractive gray steel cabinet with silver trim. 13½Wx5¾Hx8¾"D. Shpg. wt., 12 lbs. Operates on 105-125V 50/60 cycles AC/DC. (U/L Approved). HE-127 Net 69.95

NEW! S-119K RECEIVER KIT

A low cost superheterodyne receiver kit covering the standard broadcast band plus two short wave bands: 2 Mc to 5.5 Mc and 6 Mc to 16.5 Mc. This range includes the 80, 40 and 20 meter amateur bands. The power supply utilizes a selenium rectifier, and is transformer operated! Tuning dial has 4 to 1 reduction. Receiver includes built-in speaker, headphone tip jacks, AM/CW switch. Designed for easy construction. Tube complement: 6BE6 oscillator/mixer, 6BA6 i.f. amplifier/BFO, 6CM8 first and second audio amplifier and output. The detector is a 1N295. Cabinet size: 10½"Wx5"Hx7½"D. Shpg. wt., 9 lbs. HE-136 S119K Receiver Kit. Net 39.95 HE-135—S119 Factory Wired & Tested Net 49.95

NEW! MOSLEY CM-1



CM-1

CM-1

SSB-AM-CW COMMUNICATIONS RECEIVER

169.95 NO MONEY DOWN

This new compact communications receiver provides fine receiver performance at an unusually low price. Performance and features include: • Double conversion with crystal controlled first oscillator • Diode detector for AM and product detector for SB and CW • Covers 80 meters through 10 meters • S-meter functions on AM, CW or SB, with or without BFO • Selectivity — 2.5 KC at —6 db. • Sensitivity: ½ microvolt for 10 db signal-to-noise ratio on 10 meters • Stability: less than 500 cycles compensated and voltage regulated • Image & IF Rejection: 35 db minimum • Audio Output: ½ watt at 6% distortion • Tube Complement: 5 dual-purpose tubes plus 2 diodes provide functions of 12 tubes 1-6AW8A triode mixer and crystal oscillator; 1-6AW8A, 2nd mixer and tunable oscillator; 1-6AW8A, 1st IF and 1st Audio; 1-6AW8A 2nd IF and product detector; 1-6AW8A, 2nd audio and BFO; 1N34, AM detector; 2F4, power rectifier • Facilities at rear: Transmitter relay terminals, Accessory power socket, External speaker/VOX terminals • Steel enclosure finished in grey and black • Size: 10½x7½x8" Deep. For 117V 50/60 cycles AC operation. Power consumption is 33 watts. Shpg. wt., 24 lbs. HE-796 WX Net 169.95

MODEL CMS-1 Matching Speaker for above. Shpg. wt., 3 lbs. HE-797 Net 18.95

NEW! SWI ANTENNA FOR INDOOR USE



Convenient Indoor Model SWI improves the performance of any shortwave receiver. Covers 5-30 Mc. Easy to install and operate. Six-foot cable (included) is attached to receiver, the telescoping "rabbit ears" extended, and the "match" and "tune" controls set for maximum signal strength. Attractively housed in unbreakable plastic with chrome-plated antennas. Model SWI. Shpg. wt., 2½ lbs. HE-973 Net 14.35

HYGAIN MODEL SWO FOR OUTDOOR USE

Model SWO high efficiency doublet antenna for outdoor use. Traps peaked on the 11, 13, 16, 19, 24, 31 and 40 meter shortwave bands. Only 40 feet long. With insulators, 100 ft. of lead-in wire and instructions. Shpg. wt., 2½ lbs. HE-972 (Not Illustrated) Net 14.35



Model 3163 MARINE-POLICE CONVERTER



New Gonset converter operates in conjunction with your present auto radio. It covers the frequency range of 1600 to 3000 kc, which includes various ship-to-shore and ship-to-ship services. Also covered are frequencies used by Police, Coast Guard, Weather, Time, Conelrad, and numerous others. The full-vision dial has calibrated scale. Installation is simple and non-technical. A switch-on converter panel gives instant selection of regular broadcast or short wave. Size 3½x4x4". Complete with plug and cable. Shpg. wt., 5 lbs. For 12 volt battery system only. HE-505 Net 29.50

Sensational Values In Lafayette Communication Receivers!

LAFAYETTE AMATEUR COMMUNICATIONS RECEIVER

SUPERHETERODYNE CIRCUIT UTILIZING 8 TUBES & RECTIFIER TUBE



KT-200 SEMI-KIT

64.50

HE-10 WIRED 79.95


- BAND SPREAD FOR EASY TUNING • BUILT-IN "S" METER WITH ADJUSTMENT CONTROL • EXCELLENT SELECTIVITY • ACCESSORY POWER SOCKET PROVIDED • ALL TRIMMERS PRE-ALIGNED • COVERS 550KC. TO 31MC. IN FOUR BANDS • VARIABLE BFO AND AF • IF GAIN CONTROLS • SWITCHABLE AVC & AUTOMATIC NOISE LIMITER • ALL MAJOR COMPONENTS PRE-MOUNTED • DUAL 4 AND 8 OHM OUTPUT IMPEDANCES • 1 RF + 2 IF STAGES FOR HIGH GAIN RECEPTION

The KT-200 represents a significant departure from usual kit designs. As soon as it is unpacked, it is already half finished. All of the mechanical mounting is completed. Tube sockets, transformers, main tuning capacitor, filter capacitor, controls, even knobs and pilot lamps are all in place. The tuning assembly is installed and operative. Most important of all, the complex coil assembly and alignment capacitors for the oscillator, mixer and rf amplifier stages are factory mounted and pre-aligned. Thus only a slight touch up will be required to achieve maximum sensitivity and selectivity. Features such as built-in "S" meter with

adjustment control, switchable AVC and automatic noise limiter make the KT-200 worth many times its low price. Supplied with all components.

KT-200WX Same as above, factory wired & Tested Net 64.50
HE-10WX Same as above, factory wired & Tested Net 79.95
 Ideal "SPEAKER MATE" for HE-10 and other communications receivers. Special 4" speaker in handsome, tapered, grey metal cabinet reduces QRN and peaks voice frequencies. Impedance 8 ohms. 7 1/2 x 5 1/2 x 4 3/4". Shpg. wt., 4 lbs. Net 7.95
HE-11 Net 7.95

ELECTRONICS ILLUSTRATED
 "... even the most inexperienced constructor should have no trouble..."
 "Sensitivity was so great the IF gain had to be turned all the way down to prevent overloading."
 "15 73 7"
 "... excellent value"
 "... rugged, well made, and uses good components."



RECEIVER SPEAKER-MATE

HE-11 7.95

SPECIFICATIONS:

AM, 80-40-20-15-10 meter bands. Pre-calibrated band spread. Sensitivity: 1.25 mv for 10 db Signal-to-noise ratio. Selectivity: ± 10KC. -60db (at 1MC). Audio Output: 1.5 watts. Tubes: 3-6BD6, 2-6BE6, 2-6AV6, 1-6AR5, 1-5Y3. Power: 100-125 V AC 50 60 cps. Size: 15 1/2 L x 8 1/2 H x 12" D. Shpg. wt., 22 lbs.



NEW!

LAFAYETTE Professional QUALITY AMATEUR COMMUNICATIONS RECEIVER

HE-30 WIRED

99.95

NO MONEY DOWN

KT-320 SEMI-KIT


79.95

SUPERHETERODYNE CIRCUIT UTILIZING 8 TUBES & RECTIFIER TUBE

- 8 TUBES PLUS RECTIFIER TUBE
- 1 RF + 2 IF STAGES FOR HIGH GAIN RECEPTION
- EASY-TO-READ, ILLUMINATED, SLIDE RULE DIAL
- BUILT-IN Q-MULTIPLIER FOR CROWDED PHONE OPERATION
- ANTENNA TRIMMER FOR OPTIMUM PERFORMANCE ON ALL BANDS
- CALIBRATED ELECTRICAL BANDSPREAD ON AMATEUR BANDS 80 THRU 10 METERS
- 0-100 LOGGING SCALE FOR SWL'S
- EFFECTIVE AUTOMATIC NOISE LIMITER
- AVC-MVC SELECTOR ON FRONT PANEL
- STABLE OSCILLATOR AND BFO FOR CLEAR CW AND SSB RECEPTION
- BUILT-IN EDGEWISE S-METER



HE-11 7.95
RECEIVER SPEAKER-MATE



DESIGNED FOR TODAY'S CROWDED AMATEUR BANDS
 FEATURE FOR FEATURE, SIGNAL FOR SIGNAL
 MATCHES RECEIVERS SELLING FOR ALMOST TWICE THE PRICE

Designed for today's crowded amateur bands and the discerning Short Wave Listener, the new Lafayette HE-30 offers features and performance previously unheard of at this price. Outstanding Bandspread, Selectivity with a built-in Q-multiplier, and sensitivity combine to make the HE-30 one of the "hottest" general coverage bandspread receivers ever priced below \$200. For the crowded amateur bands—illuminated Slide Rule Dial, bandspread with markings every 5 KCS on 80 and 40 meters (IT TAKES 16 REVOLUTIONS OF THE BANDSPREAD DIAL TO COVER EACH OF THESE BANDS), every 20 KCS on 20 and 15 meters, and every 50 KCS on 10 meters, plus an edgewise S-meter. For the SWL—a 0-100 logging scale for "instant reset" to a desired station plus coverage from 0.55-30 MCS. The 8 tube (plus a husky 5Y3 Rectifier) circuit provides an RF stage with an antenna trimmer for peak performance PLUS 2 IF stages for improved selectivity. Far from an "empty shell" receiver, the HE-30 utilizes a 5Y3 tube in a transformer Full Wave rectifier power supply. This suppresses ripple and hum that often produces poor CW and SSB reception in "stripped down" receivers. Receiver sensitivity—that important difference between hearing and not hearing

stations—1.0 microvolts for 10db Signal-to-Noise Ratio. The Built-in BFO can be used to separate CW stations by means of the pitch control, while the Q-multiplier adds the selectivity needed for crowded phone band operation. The front panel controls speak or themselves—FUNCTION SWITCH, AUDIO GAIN, SELECTIVITY (Q-Multiplier), FREQUENCY (BFO) BAND SELECTOR, IF GAIN, TRIMMER, AVC-MVC SWITCH, ANL SWITCH, MAIN TUNING BANDSPREAD TUNING, and headphone jack. We invite comparison. Selectivity—60db at 10KC. 0.8 KC @ 6db (with Q-multiplier), IF—455KCS. Speaker—External PM type (not supplied), 4 or 8 ohms impedance. Audio Output—1.5 watts. Tubes—6BA6—RF Amplifier, 6BE6 Mixer, 6BE6—Oscillator, 6AV6-Q-Multiplier—BFO, 2-6BA6—IF Amplifier, 6AV6—Detector—AF Amplifier—ANL 6AQ5—Audio Output, 5Y3—Rectifier. Size—7Hx15Wx10"D. For 105-120, 60 cps AC, 50 watts. HE-30WX Shpg. wt., 25 lbs. Net 99.95

NEW! KT-320 SEMI-KIT
 This receiver is also available in kit form with all major components and front end pre-mounted and pre-calibrated. All other components supplied for easy mounting. Net 79.95
 KT-320 Semi-Kit

LAFAYETTE RK-138 2-SPEED 4-TRACK TAPE RECORDER WITH STEREO PLAYBACK

SPECIFICATIONS: Response: 50-10,000 cps. Wow & Flutter: less than 0.3%. Signal-to-Noise Ratio: 40db. Outputs: Include 2 output jacks — 1) second-channel external amplifier, 2) external speaker.

99.95
 NO MONEY DOWN

- Plays Back 4-Track Stereo & Records Dual Track Monophonically
- Two Speeds — 7 1/2 ips & 3 3/4 ips
- Accepts Up To 7" Reel
- Digital Tape Counter
- Neon Recording Level Indicator

Loaded with features, precision engineered and built to last, this new Lafayette tape recorder must be classified a best-buy by any standards. Designed for complete flexibility, the RK-138 offers both stereo and monophonic facilities. In addition to being able to record and play back 2-track monaural material, through its own speaker and amplifier, you can use the RK-138 for 4-track playback of the latest stereo tapes through your own component stereo system. Or, if you wish, use its self contained 6-watt amplifier and speakers (5" woofer, 4" tweeter with electronic crossover) as a second stereo channel in association with your monaural hi-fi system, radio, T.V., or with RK-139 matching speaker/amplifier.

Functional design utilizes a single, easy-to-use lever to select "Play-Idle-Record" positions. A special safety Interlock in record position insures against accidental erasure of tapes. Fast rewind is accomplished by means of a lock-in lever control with tone and loudness adjusted by a concentric front panel control. Equipped with sensitive microphone, 7" reel of tape with 7" take up reel and patch cord. For 110-120V, 60 cycle AC operation. Shpg. wt., 24 lbs. Net 99.95
 RK-138WX

MATCHING AMPLIFIER/SPEAKER COMBINATION FOR STEREO PLAYBACK

This attractive speaker/amplifier is style matched and electronically balanced to provide a second stereo channel for the RK-138 Tape Recorder described above. Contains 6-watt amplifier, 5" woofer and 4" tweeter. Supplied with 8 ft. hook up cable. Shpg. wt., 6 lbs. Net 24.50
 RK-139W



24.50

LAFAYETTE VALUE COMBINATION!

BOTH THE RK-138 TAPE RECORDER AND THE RK-139 AMPLIFIER/SPEAKER COMPLETELY EQUIPPED WITH EVERYTHING YOU NEED FOR FULL TAPE RECORDER ENJOYMENT

A complete portable tape recorder and stereo playback system which in addition to the regularly supplied equipment contains 3 7" reels of tape, 12 tape storage cans, storage chest plus tape splicer and roll of splicing tape. Shpg. wt., 32 lbs. Net 124.45
 RK5-16WX



124.45
 NO MONEY DOWN



Made In U.S.A.

Lafayette OUTSTANDING VALUES FOR CITIZENS BAND ANTENNAS & ACCESSORIES

NEW ALL STAINLESS STEEL CITIZEN BAND MOBILE ANTENNA OUTSTANDING FEATURES

- 102 1/2" Stainless Steel Whip For Optimum 11 Meter Performance
- Heavy-Duty Chrome Plated Stainless Steel Spring
- Chrome Plated Swivel Ball Jointed Mount Base

6.95

Chrome swivel ball mount base designed to be mounted on any surface. Stainless steel spring holds rod in properly adjusted position and prevents rod damage from shocks and blows. Stainless steel whip for maximum resiliency and strength. Shpg. wt., 4 lbs. Has lug terminals for HP-52 cable assembly. HE-800WX Net 6.95

20 FT. RF COAXIAL CABLE ASSEMBLIES FOR CITIZENS BAND EQUIPMENT



A 2.95

B 2.45

These cable assemblies are necessary for connection between Citizens Band Transceiver and Antenna.

TYPE A—Consists of 20 ft. RG-58/U cable with PL-259 plus UG-175/U on both ends. Required for Ground Plane and Coaxial and Mobile Antennas terminating in a coaxial jack. Shpg. wt., 8 oz. Net 2.95
 HP-51 Type A 20 ft. length
 TYPE B—Same as type A except one end is terminated with PL-259 plus UG-175/U and other end with universal ring type terminal lugs for mobile antennas. Shpg. wt., 8 oz. RECOMMENDED FOR USE WITH HE-800WX MOBILE ANTENNA Net 2.45
 HP-52 Type B 20 ft. length

LAFAYETTE GENERATOR NOISE FILTER

- Frequency Range 3-30 mcs
- Maximum Current 25 Amps
- Adjustable
- Simple to Install



Eliminates whining and grinding noises created from generator brushes. Enables quiet receiver operation for Citizens Band, Amateur and industrial frequencies. Standard frequency range 3-30 mcs. Maximum current 25 amps. Installs quickly and easily. CF-135 Shpg. wt., 1 lb. Net 2.49

NEW! LAFAYETTE AUTO-MARINE ENGINE NOISE SUPPRESSOR KIT

- A Must For Mobile CB & Ham Operators
- 14 Components Plus Hook-Up Wire

This easily installed kit will effectively suppress ignition, generator and voltage regulator noise. Consists of 8 spark plug suppressors; 1 distributor suppressor, 1 voltage regulator suppressor; 4 coaxial capacitors; shielded cable and braid for wiring filter system. All necessary hardware and instructions for installation are included. Shpg. wt., 2 lbs. Net 9.45
 HP-204

NEW! "NOISTOP" IGNITION NOISE ELIMINATOR

Effective as both a noise limiter and a positive squelch the "Noistop" improves reliability and operating pleasure, when vehicle is in traffic. Measures only 1 1/2 x 2 1/2 x 4". Complete with tubes (6AL5 and 12AX7) and instructions for easy installation in most available transceivers. For use with super-heterodyne type transceivers. Furnished with cable and gold anodized cabinet with black perforated cover. Mounts in any position. Shpg. wt., 10 oz. Net 15.63
 HE-902

GENERATOR/REGULATOR FEED-THRU NOISE SUPPRESSORS .95

These 3-terminal network feed-thru capacitors act as extremely effective R.F. filters above 2 MC. Eliminates and suppresses the majority of noises due to regulators and generators interfering with 27MC citizens band frequencies. Rated .1 MFD/600 Volts DC 20 Amps.

- Feed-Thru Suppressor (Screw Terminals) 1/8" Diam. x 1 1/4" length. Shpg. wt., 4 oz. SP-221 Net .95
- Feed-Thru Suppressor 1/8" Diam. x 1 1/4" length. Shpg. wt., 4 oz. SP-222 Net .95

NEW LAFAYETTE 12 POSITION CRYSTAL SELECTOR

Houses and selects up to 12 crystals - increases channel coverage. Chassis has 12 ceramic crystal sockets, wired to a 12 position, no stop selector switch. Long reach shaft permits practical mounting. Chassis size: 2 1/4" D x 2 1/4" W x 2 1/4" H. Shpg. wt., 1 lb. Net 6.50
 HP-201

NEW! CB BEAM AND ROTATOR A Real Package Deal!



Get Both for only **33.75!**

NO MONEY DOWN

- Meter type DIRECTION INDICATOR

Nothing equals a yagi type beam antenna to pinpoint communications. Nothing adds to its directional capabilities like a rotator with an easy-to-read direction indicating meter. And nobody but Lafayette has the package at a price to save the CB'er dollars. The antenna is a rugged, all aluminum, 3 element beam. Full 108x1" boom. Elements of 1/2" O.D. seamless aluminum, reinforcing inserts at strain points. Double boom brace for added support. The rotator features a meter type directional indicator, instantly reversible, 360° revolution in 50 seconds. Takes masts up to 1 1/2" O.D. Instant locking to prevent drift. Fully sealed against weather. Uses 4 wire cable. Shpg. wt., 25 lbs. Net 33.75
 SP-248WX
 WR-24 4 cond. flat cable per ft. .03; per C ft. 2.39
 3 element CB Beam only. Shpg. wt., 12 lbs. Net 14.95
 HE-697WX

LAFAYETTE TELESCOPIC CITIZEN'S BAND WHIP ANTENNA

SENSATIONAL VALUE IN A DIRECT MOUNTING CITIZENS ANTENNA

3.95



Sturdy, attractive chrome plated whip antenna that telescopes from approx. 45" fully extended to only 15" to facilitate portability and storage. Ideal for shorter distances up to several miles. Has enclosed base loading coil for proper impedance matching. Complete with removable PL-259 connector that permits direct top, side or rear mounting to transceiver. Shpg. wt., 1 lb. Net 3.95
 HE-19

ANTENNA SPECIALISTS M-38 ANTENNA ISOLATING SKIRT

- Improves Performance Of All Citizen Band Ground Plane Antennas

Isolating skirt for use with Citizen's Band Ground Plane Antennas. Mounts 9 feet (1/4 wave length) below ground plane (i.e. 27 MC). Lowers angle of radiation and minimizes effect of mounting structure. Improves performance of ground plane. Clamps to 1/4 inch tubing or 1 inch pipe. Shpg. wt., 4 lbs. Net 11.14
 HE-681WX

MAGNUM-27 1/2 WAVE 27 MC ANTENNA

• 6 DB Effective Gain
 Compact vertical radiator with an actual 6 db gain over any single element omnidirectional antenna. Total height is only 18" - 2", (17" - 3" radiators, 4-5" radiators). Direct ground lightning protection. 50 ohm feed. Of durable aluminum and steel. Shpg. wt., 12 lbs. Net 27.88
 HE-487WX


NEW! DYNAMIC PUSH-TO-TALK MICROPHONE FOR CITIZENS BAND TRANSCEIVER

Specifically Designed for CB Use
 • Momentary-on Spring Return Switch
 • Lightweight • Deluxe Styling

A top quality dynamic microphone for C.B. and communications transceivers. Black and chrome; tapered styling. High impedance dynamic transducer will not be adversely affected by heat and smooth frequency response of 100 to 11,000 cycles make it suitable for communications work. Momentary push-to-talk switch, coiled rubber cable with a 5 prong plug, hang up bracket. PA-274 Shpg. wt., 1 lb. Net 8.95

MOSLEY A-311 3-ELEMENT CITIZEN'S BAND BEAM ANTENNA

36.75



NO MONEY DOWN
 • Durable Light Weight Aluminum
 • Delivers the Equivalent Power Input of 40-Watts from your 5-Watt Citizens Band Transmitter

Unequaled point-to-point communications for Citizens Band operators. 9.3 db gain over dipole means the effective radiated power is multiplied by 8. This means your 5 watt Citizens Band Transmitter can actually achieve a legal effective power input of 40 watts. Boom is 12" long with maximum turning ratio of 9.5 ft. Requires 1 1/2" mast and RG-8/U or R9-58/U Cable. Lugs are supplied for the other end. Shpg. wt., 30 lbs. Net 36.75
 AN-57WX

CDR AR-22 AUTOMATIC ROTOR FOR CITIZENS BEAM

This heavy-duty rotor unit will handle antennas up to 150 lbs. Simply set the control unit pointer to the desired direction, and the antenna will automatically rotate to this position and stop. Perfect for TV, Ham or Citizen Band application. Rotor unit employs 12 heavy duty ball bearings in two 6 1/2" races. Weather-proof motor reverses instantly and is factory lubricated for life. Reversible clamps on rotor will take masts from 7/8" to 2" O.D. Control unit is marked in compass points. N.S.E.W. NW, NE, SW, and SE. Housed in attractive brown plastic cabinet with rubber feet. Complete with rotor, control unit and instructions. For 110-120 volts 50-60 cps AC. Requires 4 conductor cable. HE-476WX Net 32.77

4-Conductor cable for HE-476WX rotor WR-24 ea. ft. Net .03; 100 foot length Net 2.39

NEW! CLR COLINEAR GROUND PLANE ANTENNA

• Double Power in All Directions
 • Built-to-Heavy-Duty Commercial Specifications

A new concept in CB antenna design. Achieves gain through colinear action which concentrates more power at lower angles to the horizon. Performs equally well receiving or transmitting, greatly increasing the range of consistent CB communications. Precision tuned and matched for 52-ohm coaxial cable, either RG-8/U or RG-58/U. Overall only 20-ft. high; radiator is 1 1/4" O.D. to 3/4" O.D. heavy wall heat-treated aluminum tubing. 9-ft. long radials of 3/8" O.D. aluminum tubing. Accepts all masts up to 1 1/2" diameter. Complete with matching stub and complete assembly instructions. Shpg. wt., 10 lbs. Net 29.37
 HE-775WX

MARK MOBILE HELIWHIP & MOUNT

The HW-11.4 "Heliwhip" is a fiberglass molded, continuously loaded whip antenna, four feet in length for the 11 meter Citizen Band. The HW-11.4 mounts in a MWM-1 molded mount or can be used with any good commercial mobile ball mount which will accept the 3/8" - 24 thread HE-895-WX HW-11.4 Fibre Glass Antenna Shpg. wt., 3 lbs. Net 9.95
 HE-896 MWM-1 Antenna Mount for HW-11.4 Shpg. wt., 2 lbs. Net 7.50

NEW! LAFAYETTE BROADCAST TO CITIZEN BAND COUPLER

Specially designed network permits any Citizen's band mobile antenna to be used also for broadcast reception. No switching necessary. With SO-239 antenna receptacle, 2 ft. lead with coaxial auto plug for broadcast radio connection and 2 ft. lead with PL-259 coaxial plug for transceiver connection. Shpg. wt., 1/4 lb. Net 6.95
 HP-202

NEW! LAFAYETTE "DUMMY" ANTENNA LOAD FOR CB TRANSCEIVERS

A 52 ohm non-inductive load for testing and tuning-up Citizens Band transmitters up to 5 watts. It permits tune-up into a non-radiating element instead of into antenna - in compliance with FCC regulations. Built-in PL-259 coaxial plug is easily connected and disconnected from equipment. Shpg. wt., 1 lb. Net .98
 HP-203

RG COAXIAL CABLES

These high quality coaxial cables are branded with RG type standard type numbers. Meets specifications outlined by U. S. Government Qualified Products List. R.G. 52-ohm cable is required for Ham and Citizens Band hook-up from the transceiver to antenna.

Stock No.	Type	Impedance	Net Per Ft.
WR-143	RG-8/U	52-ohms	.11
WR-144	RG-58/U	52-ohms	.05
WR-145	RG-59/U	72-ohms	.05

RIDERS CITIZEN BAND HANDBOOK No. 273

By Allan Lytel. Written for the user, prospective buyer and the service technician. Describes historical development, applications, classifications, and types of available equipment. Design features of different types of equipment are compared and analyzed in detail. The various elements of a CB station, and their maintenance, are all thoroughly treated. Includes a discussion of relevant FCC regulations. Soft cover. 160 pages. 5 1/2 x 8 1/2". BK-741 Postpaid in U.S.A. Net 3.82

CLASS D CITIZENS BAND CRYSTALS

2.25



Extremely accurate 3rd overtone crystals. Meet F.C.C. tolerance requirements of .005%. For use as transmit crystal for the following popular 11 meter CB Transceivers. Lafayette HE-29A & HE-15A, Citi-Fone CD-5, Globe CB100 & CB100A, Hallicrafters CB-2, Heath CB-1 and GW-10, Fomalne FCB-5, Philmore TC11 & TC612, Radson RP-612, Regency CBM 27, Vocaline ED27, Transcender 1000, Pierce and Impson CBD-5, RCA Mark VII, E. F. Johnson Messengers. Pin spacing, .486" pin diam., .050". Frequencies available:

27 MC TRANSMIT CRYSTAL FREQUENCY CHART

Channel	Meg.	Channel	Meg.	Channel	Meg.
1	26.965	9	27.065	17	27.165
2	26.975	10	27.075	18	27.175
3	26.985	11	27.085	19	27.185
4	27.005	12	27.105	20	27.205
5	27.015	13	27.115	21	27.215
6	27.025	14	27.125	22	27.225
7	27.035	15	27.135	23	27.235
8	27.055	16	27.155		

HE-830L Specify Channel or Frequency 2.25

LAFAYETTE SPECIAL 100 MILLIWATT WALKIE TALKIE MATCHED TRANSISTOR PACKAGE

- 9 Transistors • 1 Diode • 1 Varistor

ALL EFFICIENTLY MATCHED FOR TOP CITIZENS BAND 100 MILLIWATT PERFORMANCE! USED IN LAFAYETTE HE-29 ! Lafayette makes your job of building a 100 milliwatt citizens band "walkie talkie" easy as pie with this outstanding matched transistor package. Especially matched for outstanding performance in superheterodyne transceivers as used in Lafayette's famous HE-29. Consists of 9 transistors (used in receiver oscillator, mixer, IF driver, push-pull output, transmitter oscillator and output stages), 1 diode as detector and 1 varistor for circuit stability. No other semiconductors to buy! HP-71 Shpg. wt., 8 oz. Net 7.50

WALKIE-TALKIE PRINTED CIRCUIT BOARD (Used in Lafayette HE-29A) Neatly designed miniaturized printed circuit board ideally suited for Citizens Band "walkie-talkie." Cutouts for parts listed above. Designed to make wiring and assembly simple despite small size. 3 1/2 x 2 3/4 W x 1/4" D. Shpg. wt., 6 oz. Net .98
 HP-73

NEW! BPR "Hy-gain" UNIVERSAL BUMPER MOUNT with STRAP

• Chrome-Plated Mount
 • Stainless Steel Strap

6.44

An attractive new bumper mount, heavily chrome-plated and attaches easily and quickly to most auto bumpers. Stainless steel mounting strap replaces the old-fashioned bulky bumper chain. Fully adjustable for vertical alignment. Shpg. wt., 1 1/2 lbs. Net 6.44
 HE-774

RF COAXIAL CONNECTORS

Stock No.	Type	Description	Net
SP-174	PL-259	Male conn. For direct connection into transceiver or antenna	.59
SP-175	UG-175/U	Reducer—Adapts PL-259 to RG-58/U Diam.	.16
SP-176	PL-258	Junction Adapter—Accepts PL-259 on both ends for cable extension	.89

CITIZENS BAND CONNECTOR ADAPTERS

29-786 ADAPTER			
Adapts an SO-239 Socket to a Standard auto radio (Motorola type) socket. Av. Shpg. wt., 2 oz.			Net .44
HP-53			
29-782 ADAPTER			
Adapts a PL-259 Plug to a standard auto radio (Motorola type) plug. Avg. shpg. wt., 4 oz.			Net .54
HP-54			

27MC WALKIE-TALKIE TELESCOPING ANTENNA Attractive and highly efficient 12 section chrome plated brass telescoping antenna for "walkie talkie" transceivers. Measures 52" fully extended and 5 1/2" retracted. Has #8-32 threaded stud and nut at bottom for easy mounting, and soldering lug for electrical connection. F-703 wt., 10 oz. Net 1.95

LAFAYETTE CITIZENS BAND 27MC. COLLAPSIBLE ANTENNA .79

Ideal for mobile or fixed transceivers, miniature portable and pocket transistor radios, and a host of similar applications. The 4 section antenna is made of chrome-plated brass and plugs into a jack. Measures 48" fully extended and retracted is 11" to facilitate carrying in pocket. Complete with a flexible plastic case and slip-under protecting flap. Shpg. wt., 8 oz. Net .79
 F-440

LAFAYETTE — Citizens Band Headquarters


FOR: BUSINESS • INDUSTRY • CARS • BOATS • FARM • SPORTS AND PERSONAL USE

FREE!

23 recently assigned radio channels within the 26.965 to 27.255 megacycle range (11 meters) make possible 2-way communications in a great number of business and personal applications. Station license is easy to obtain — merely fill out single FCC form (supplied) . . . no exam or special skill is required.

FREE!

Any one of these Citizens Band Antennas with the purchase of any Transceiver listed below



NEW GROUND PLANE ANTENNA
15.63

Solid aluminum 108 inch heat-treated radials and radiator. Elements supplied in two 54 inch lengths joined by threading coupling nuts. Radials droop for 50 ohm match. Accepts 1/4 inch tubing RG-58/U cable and PL-259 connector. Shpg. wt., 4 lbs. HE-661W Net 15.63

FIXED COAXIAL ANTENNA
FREE! 14.95

The half-wave coaxial antenna is widely used in commercial and emergency communications. It consists of a quarter-wave vertical element (108" long) above a quarter-wave cylindrical "skirt" which surrounds and is concentric with the mast. The coaxial feed line is run inside the mast to a built-in coaxial connector. Constructed entirely of aluminum, this antenna requires 15 ft. 1/4" TV masting or 12 ft. aluminum tubing for support. Designed for RG-59/U or RG-11/U coaxial feed line. Overall height 17'6". Shpg. wt., 5 lbs. HE-804WX Net 14.95



MOBILE REAR COWL MOUNT ANTENNA

18.52


Complete Antenna Kit for rear deck or side mounting. Consists of cadmium plated base, special alloy cadmium plated spring, 102" stainless steel whip, cable and gutter clip. Furnished with 20 ft. RG-58/U cable having PL-259 connectors on both ends. Shpg. wt., 6 lbs. HE-674WX Net 18.52

MOBILE BUMPER MOUNT ANTENNA

15.95

Adaptable to virtually all American and Foreign cars. Includes double bumper mount with cable terminals, cadmium plated spring 102" stainless steel whip, 20 ft. of RG-58/U cable with PL-259 connector on one end, solder lugs on the other, and whip hold-down clip. Shpg. wt., 5 lbs. SP-198WX Net 15.95

NEW OSBORNE 300 ALL TRANSISTORIZED CB RADIO




- Crystal Controlled Transmitter/Receiver
- Fully Transistorized — 3.2 Watts P.E.P.
- Exceptionally Low Power Consumption
- Lightweight and Compact

The Osborne 300 employs 9 transistors in a deluxe, ultra-compact transceiver unit. Receiver sensitivity is better than 1 uv, typically 0.5 uv, for a 10 db (S+N)/N ratio. High selectivity (2.6Kc at 6 db down) results in adjacent channel attenuation of 50 db. Includes built-in squelch circuit. Total receiver power drain is 3 watts. Transmitter has input of 3.2 watts P.E.P., crystal controlled within a frequency tolerance of ± .005%. Includes push-to-talk microphone, power supply, 1 set of crystals. Modern decorator styling in jet black. Shpg. wt., 6 lbs. Net 149.50

HE-838WX Model 300, for 117VAC Net 15.00
Model 830 6VDC converter for mobile use with Model 300 HE-837 Net 15.00
Model 840, 12 VDC converter for mobile use with Model 300 HE-836 Net 5.90
Lafayette matched receive/transmit crystals for Osborne 300 HE-831L Net 5.90

JOHNSON VIKING "MESSENGER" CB TRANSCEIVER




- 5 Crystal Controlled Receiving Channels
- 5 Crystal Controlled Transmitting Channels
- Push-To-Talk microphone
- Built-in squelch

Designed for reliability and easy installation in your home, business location, car, truck or boat. Excellent receiver sensitivity and selectivity. Built-in squelch, Automatic Volume Control and Automatic Noise Limiter. Transceiver has 10 tubes (including rectifier). Compact modern styling—5 1/2"x7 1/2"x1 1/2" D. Complete with tubes, push-to-talk microphone, and crystals for one channel. Shpg. wt., 15 1/2 lbs.

HE-447WX Model 242-128 115VAC/12VDC Net 144.95
HE-448WX Model 242-127 115VAC/6VDC Net 144.95
HE-451WX Model 242-126 115VAC Net 134.95
Universal Dash Mounting Kit for HE-447WX, HE-448WX, HE-451WX. Shpg. wt., 2 lbs. Net 2.50
Lafayette transmit type crystal for Johnson "Messengers". HE-830L (Specify Frequency) Net 2.25
Lafayette receive type crystal for Johnson "Messengers". HE-833L (Specify Frequency) Net 3.25

NEW SONAR MODEL E 5-WATT CB RADIO

- 8 Crystal Controlled Channels for Transmitter
- Choice of 8 Crystal Controlled Channels or Continuous Tuning over all 22 Channels for Receiver
- Push-To-Talk Operation
- Built-in Power Supply for 117 VAC and Either 6 or 12 VDC



The Model E combines a highly sensitive superheterodyne receiver with a 5 watt transmitter in a completely self-contained, compact unit. Receiver features a sensitivity of 0.5 microvolt for 10 db quieting, an adjustable squelch and an automatic series noise limiter. Selectivity is 5Kc at 6 db down. Can be operated on 8 crystal controlled channels or tuned over all 22. Transmitter input is a full 5 watts (FCC limit), modulated up to 100%. Operates on 8 crystal controlled channels, with a frequency stability of .005% or better. Includes high impedance ceramic microphone with push-to-talk switch. Completely self-contained dual power supply. Measures only 1 1/4"x9 1/4"x4 3/4" H. Shpg. wt., 12 lbs. Net 179.50

HE-372WX For 117VAC/12VDC Net 179.50
HE-373WX For 117VAC/6VDC Net 5.90
Lafayette matched receive/transmit crystals for Model E HE-832L (Specify Frequency) Net 5.90

VOCALINE ED-27M "COMMAIRE" 4 CHANNEL CB RADIO



- Crystal Controlled — 4 Channel Transmit, 4 Channel Receive.
- Double Conversion Superhet Receiver
- Noise — Immune Patented Squelch Circuit
- Transistorized Power Supply
- Transmitter — 5 Watt Input; 3 Watts Output

Specifications — Sensitivity: 0.3 microvolts. Selectivity: ± 5Kc at points 6 db down; Audio Output: 4.5 Watts. Uses 10 tubes. 6 or 12 Volt transistorized power supply. Rugged, heavy gauge, attractive, salt water resistant steel cabinet 5 1/4"x9 1/4"x8 1/4" deep. Shpg. wt., 12 lbs. Complete with crystal for one channel, push-to-talk microphone, hanger, universal mount, antenna loading light and AC/DC power cords.

HE-253WX 115VAC/6VDC Net 151.60
HE-254WX 115VAC/12VDC Net 151.60
Lafayette transmit crystal for Vocaline ED-27M. HE-255L (Specify Frequency) Net 3.25

POLY-COM II G DELUXE CB TRANSCEIVER

- Dual Conversion Superhet Receiver
- Automatic Volume Control
- All-Electronic T-R Switching
- 4 Crystal Controlled T-R Channels



A rugged, reliable, compact 4-channel transceiver in the field, on vehicles, planes, boats and in the office or home. Precision engineered and superhet receiver, adjustable vacuum tube sensitive dual conversion automatic volume control, floating series gate squelch circuit; delayed carrier and modulation indicator, 3 full watts audio output, built-in 2.5 watts power output to antenna, separate mike pre-amp and oscillator. Adjustable antenna matching for 52 or 72 ohms weatherproof 4" speaker, enclosed carbon microphone has press-to-talk button. Retractable coil cord keeps mike handy. 11 tubes of which 5 are dual purpose for 16 tube performance. Comes complete with crystals for one channel, microphone, instructions. Size 11 x 7 1/2 x 5". Shpg. wt., 15 lbs.

HE-295WX 115VAC/6VDC Net 189.50
HE-296WX 115VAC/12VDC Net 189.50
Lafayette matched crystals (receive/transmit) for Poly-Com II G HE-297L (Specify Frequency) Net 5.90

NEW! GONSET CB COMMUNICATOR MODEL G-14

- 4 Crystal Controlled Transmit/Receive Channels
- Dual Conversion Receiver
- 5-Watt Transmitter
- Push-to-Talk Mike
- Sensitivity — 1 uv or Better at 10 DB Signal-to-Noise Ratio
- Selectivity — 6 Kc at 6 DB Down, 30 Kc at 80 DB Down



The new Gonset CB Communicator features a sensitive, highly selective double conversion receiver and a 5-watt, 100% modulated transmitter. Receiver sensitivity, 1 uv for 10 db S/N ratio; selectivity, 6 Kc at 6 db down, 30 Kc at 80 db down. Squelch adjustable from front panel. Transmitter includes a push-to-talk, heat-proof ceramic microphone. Entire unit employs 9 tubes, 3 silicon rectifiers. Complete with built-in dual power supply and one set of transmit/receive crystals. 4x7x1 1/4". Shpg. wt., 12 lbs. Net 149.50

HE-495WX For 117VAC/6VDC Net 149.50
HE-496WX For 117VAC/12VDC Net 5.90
Lafayette matched crystals (receive/transmit) for Gonset G-14 communicators. HE-538L (Specify Frequency) Net 5.90

VOCALINE 465 MC CB TRANSCEIVER



CLOSEOUT

19.95

QUANTITIES LIMITED

FOR MOBILE OPERATION

Operates directly from 6-volt car battery. Supplied with voltage dropping resistor for operation from 12-volt car battery.

The Vocaline JRC 400 is a ruggedly constructed Citizens Band Transceiver that operates on 465 MC line of sight frequency for private or personal short distance radio communications. It is capable of transmitting up to an average of 2 miles distance, depending on the terrain and height of the antenna (considerably more on water). No installation is required—just plug into any 115 volt AC outlet or attach to 6 volt DC power source, and is portable, lightweight, compact and durable. Its frequency is fixed and requires no tuning. It is FCC approved and any U.S. citizen over 18 years of age can obtain a station license by forwarding a filled out form enclosed with the transceiver. The JRC 400 comes complete with built-in vibrator power supply, 6AF4A, 6AV6 and 6AS5 tubes in a highly effective superregenerative circuit, microphone, AC and DC line cords, and plug-in antenna. Size: 5x6x9". Shpg. wt., 5 1/2 lbs. SP-225WX For 115VAC/6 Volts DC Net 19.95

Because of Lafayette's special low price, no free antenna will be offered with this Transceiver.



8.95

LAFAYETTE MODEL TM-15A WAVE-METER for AMATEUR and CITIZEN BANDER

A miniature wavemeter for checking transmitter output. Determines relative strength of fundamental frequency and any harmonic or parasitic radiation, and in so doing aids in elimination of these unwanted emissions. Complete and self contained, the TM-15A requires no power source. Telescoping antenna is included. Merely choose proper band and turn tuning knob until edgewise 3/4" panel meter indicates the

presence of RF. If indications occur at several points within the range of the wavemeter, the transmitter is probably radiating spurious frequencies. Tunes 1.6 to 150 mc in four calibrated bands. Only 3 1/2"x2 3/4"x1 1/2" D. Antenna is 10 3/4" extended. 3/4" telescoped, is fitted with a banana plug and is removable. Total shpg. wt., 8 oz. TM-15A Net 8.95

NEW! TM-58 SWR BRIDGE AND RF POWER METER

- Measures RF output Power Into Built-in 52 Ohm Dummy Load, Up to 15 Watts
- Measures SWR and Relative Power Up To 1 KW
- Can be Used in 52 and 75 Ohm Coaxial Lines

Here is a quality instrument which will give highly accurate SWR and direct power readings up to 50 Mc. The unit may be permanently inserted in the transmission line for SWR and relative power monitoring. When the 3-position selector switch is set to POWER, the meter will indicate the RF power up to 15 watts, into a built-in 52 ohm resistive load employing quality non-inductive resistors. Full scale accuracy is 10%. The selector switch is set to SWR SET to read relative forward power up to 1 KW and to adjust the sensitivity control for SWR measurements. For direct SWR measurements from 1:1 to 4:1 with powers up to a kilowatt, the selector switch is set to SWR. Unit is inserted into the transmission line by means of two standard coax connectors, and 2 slide switches are set to 52 or 75 to correspond with line impedances of 52 or 75 ohms, respectively. Insertion loss is negligible. Meter has 50 ua movement; calibrated directly in watts from 0-15, and in SWR from 1 to 4 (reads infinity at full scale). Housed in an attractive grey metal cabinet, 3 1/2"x7 1/4"x2 3/4". Sits on 4 rubber feet. TM-58 Shpg. wt., 2 lbs. Net 27.95

NEW LAFAYETTE HE-26 HYBRID PHONE PATCH


Enjoy the pleasure of handling phone patch traffic with this deluxe hybrid patch. Hybrid circuit permits use of AM or SSB with voice control by effectively isolating the receiver audio output from the transmitter audio input. Provides an accurate balance between 500 ohm line and station equipment—with negligible insertion loss. Four connections on rear for receiver output (voice coil, 3-4 ohms), transmitter input, station microphone, and telephone. Easy to operate after a few preliminary adjustments, all from the front panel. Null and balance controls are adjusted, with the aid of readings on the edgewise panel VU

meter, for balance and maximum receiver-transmitter isolation. Thus the receiver audio signal, which would ordinarily trip the VOX circuit, is balanced out from the transmitter audio section. The gain control is adjusted for proper transmitter and receiver audio level. VU meter continuously monitors line level. The patch can be switched in and out by means of a front panel switch, so that it may be permanently installed. Compact, sloping cabinet will fit into any station arrangement. Sits on 4 non-slip rubber feet. Size: 3 1/2"x5 1/2"x4" D. HE-26 Shpg. wt., 3 lbs. Net 24.50



24.50

SAVE! AMATEUR EQUIPMENT • BATTERIES • CHARGERS SAVE!



SUPER SPEED TELEGRAPH KEY

9.95

SEMI-AUTOMATIC "BUG"

Fully the equal of keys selling at almost twice the price! 7 adjustments for speed and comfort. Precision-tooled, anti-rust nickel-plated brass and stainless steel operating parts. Speed adjustable 10 wpm to as high as desired. $\frac{1}{2}$ " silver contacts; weight scale for reproducible speed settings. A real bargain for radio amateurs and professional CW operators! $6\frac{1}{2}$ "x $3\frac{1}{2}$ "x $2\frac{1}{4}$ "H, exclusive of knobs and feet. Shpg. wt., $3\frac{1}{2}$ lbs. MS-435—Net 9.95



1.79

LAFAYETTE SPECIAL

CODE PRACTICE SET

A budget item for the beginning amateur and code practice groups. Key has adjustable spring tension, and adjustable contact clearance. High frequency buzzer has frequency, and tension adjustment with lock nuts to assure constant frequency. There is provision for insertion of head set by means of binding posts with knurled tightening screws. For individual, group or remote listening. Uses Burgess #2 1 1/2 Volt Battery. Base $6\frac{1}{4}$ "x $2\frac{3}{4}$ "x $1\frac{3}{8}$ "D, overall length $8\frac{1}{2}$ ". Shpg. wt., 2 lbs. (less battery). MS-438—Code practice set Net 1.79
BA-157—Burgess #2 Net .13
MS-369—Stethoscope Headset Net 1.39



69¢

LAFAYETTE SPECIAL

SAVE ON NEW TELEGRAPH KEY

Economical key for beginning amateurs. Solid, heavily chrome and nickel plated metal parts, molded phenolic base. Adjustable spring tension and adjustable metal parts, molded phenolic base. Adjustable spring tension and adjustable contact clearance. 2 mounting holes in base. Base $3\frac{1}{4}$ "x $1\frac{1}{4}$ "x $1\frac{1}{4}$ "W. Overall length 5"; height $1\frac{1}{2}$ ". Shpg. wt., 12 oz. MS-319—Telegraph Key Net .69



1.95

79¢

LAFAYETTE "BRASS-POUNDER'S" KEY

- WITH BALL-BEARING PIVOTS
- SOLID POLISHED-BRASS BASE

A better quality precision-made key designed for hard usage. Spring tension and contact clearance adjustments; $\frac{1}{2}$ " silver contacts; adjustable ball-bearing pivots; Circuit closing switch. Base $3\frac{1}{2}$ "x $2\frac{1}{2}$ "x $1\frac{1}{4}$ "W. Shpg. wt., $1\frac{1}{2}$ lbs. MS-428—Telegraph Key Net 1.95

HIGH FREQUENCY CODE PRACTICE BUZZER

Adjustable frequency buzzer ideal for individual or group code practice. Perfect code item for the ham shack. Black molded phenolic housing. Works with 1 1/2 volt battery. Screw adjustment for changing tone. $1\frac{1}{2}$ " diam. x $1\frac{1}{4}$ " high. Shpg. wt., 6 oz. MS-436—Buzzer Net .79

TELEGRAPH TRANSMITTER

And Code Practice Oscillator

Only 2.95 2 for 4.90 4 for 8.75

- Send and receive for miles on one wire!
- Ideal for Network Practice
- For Individuals, Group, Classrooms, Hams, etc.

An ideal communications instrument that can be set up, with others, for network practice in classrooms, groups, house to house, etc. Adjustable spring tension and contact clearance. Crystal earphone—high output—lightweight. Molded Bakelite base. Lightweight, only 6 oz., yet designed to give good stability while in use. Complete with 50 ft. of wire on reel, ground spike, ground wire, earphone and Morse code sheet. Uses 1.5V battery (not included). Overall $4\frac{1}{4}$ "x $4\frac{1}{2}$ " high. Shpg. wt., 1 lb. F-552 Telegraph Transmitter Net 2.95
BA-157 Battery for above Net .13

TAPEDCODE

Prerecorded magnetic tapes containing a complete course in the International Morse Code. The tapes are 7"; 1200 ft. and can be played on any standard tape recorder. Playing time 2 hours per tape. Shpg. wt., $1\frac{1}{2}$ lbs. NOVICE Basic instructions & code 4-8 WPM. RT-14 Net 6.35
ADVANCED Code at 9-18 WPM. RT-15 Net 5.39

TRANSISTORIZED CODE PRACTICE OSCILLATOR



- MINIATURE-PORTABLE
- SELF CONTAINED BATTERY POWER SUPPLY
- PRODUCES CLEAR, CRISP, CW NOTE

Here is an ideal, inexpensive code practice oscillator for the amateur radio enthusiast. Long 38 inch wire from oscillator to earpiece, allows two persons to practice without interference. The unit is completely portable, and weighs only 6 oz. Tone produced is clear and crisp, similar to that received during F.C.C. licensing examinations. Low voltage transistorized circuit utilize 1.5 volt penlight type battery which completely eliminates any possible shock hazard. Earpiece is crystal type, and housed in sanitary plastic. Shpg. wt., 5 oz. F-429 Oscillator only Net 2.29

2.29

CODE PRACTICE OSCILLATOR WITH KEY

Above oscillator plus adjustable telegraph key (MS-319). Key has spade lug connectors, making it possible to disconnect the key from the oscillator and use it separately if desired. Shpg. wt., 9 oz. F-479 MS-319 Key and Oscillator Net 2.95

AMECO RECORD CODE COURSES

Fast, simple way to learn code for commercial and amateur licenses. Junior course designed to take you from start to $7\frac{1}{2}$ words per minute; Senior course from start to 18 words per minute; Advanced course from 8 to 18 words per minute. Junior set consists of 5 records for 78 and 45 rpm; 1 for 33 1/2 rpm. Senior Set consists of 11 records for 78 and 45 rpm; 2 for 33 1/2 rpm. Advanced set consists of 6 records for 78 and 45 rpm; 1 for 33 1/2 rpm. Number in bracket indicates shpg. wt.

Type	33 1/2 RPM		45 RPM		78 RPM	
	Stock No.	Net	Stock No.	Net	Stock No.	Net
JR.	PR-47 (1 lb.)	4.95	PR-41 (2 lb.)	5.95	PR-40 (4 lb.)	6.95
SR.	PR-48 (2 lb.)	9.50	PR-43 (3 lb.)	10.50	PR-42 (7 lb.)	11.50
ADV.	PR-49 (1 lb.)	4.95	PR-45 (2 lb.)	4.95	PR-44 (4 lb.)	5.95

LAFAYETTE SPECIAL CODE COURSE

Learn Morse Code the modern practical way. Supplied with 10 lessons and a non-breakable high quality 33 1/2 rpm long playing record, recorded with code sound to provide further aid. Perfect for home studying. Speed progresses steadily from 2 to 15 wpm. Complete with sturdy record album and instruction manual. Shpg. wt., $1\frac{1}{2}$ lbs. PR-13 Lafayette Code Course Net 3.50

10 LESSONS ON A 12" LP RECORD

3.50

VIBROPLEX SEMI-AUTOMATIC KEYS



LESS CORD AND WEDGE

"Champion". Designed for a low priced Vibroplex in the radio field. Of high quality for clear, speedy and easy sending. Ideal for amateur or professional radio operators. Chromium finished top parts with black crystal base. Single lever with 2 pairs of contact points. Shpg. wt., 4 lbs. MS-715 Net 17.95

"Original". Acclaimed by veteran operators for its extremely smooth, clear, rapid, effortless and accurate operation. A rugged, well built, expertly engineered machine for all classes of transmitting work. Large contact points. Die cut dot contact. Chrome-plated mechanism. Cast-iron base. Shpg. wt., 5 lbs. MS-716 Net 22.45

Deluxe "Original". As above but jeweled bearings, chrome-plated base. Shpg. wt., 5 lbs. MS-717 Net 26.95

"Blue Racer". Very similar to the "Original", but half size. Compact and light weight. Shpg. wt., 4 lbs. MS-718 Net 22.45

"Blue Racer" Deluxe. As above but jeweled bearings. Chrome Base. Shpg. wt., 4 lbs. MS-719 Net 26.95

Cord and wedge for above. Specify model of key. MS-854 Shpg. wt., 8 oz. Net 1.75

REMOTE CONTROL FOR SILENT TV VIEWING



- SIMPLE TO ATTACH TO ANY TV SET OR RADIO
- SEE AND HEAR—NOISELESSLY—CONVENIENTLY
- LOOK AT THESE FEATURES!

1. For LATE LISTENERS: One or two people can both see and hear the program with the loudspeaker cut off.
2. FOR HARD-OF-HEARING: They can see and hear without turning the set volume so high that others can't stand the noise.
3. FOR NOISY PROGRAMS: Don't let the kids' "Wild Westers" bother you. Let them view and listen with the speaker off.
4. FOR NORMAL OPERATION: Does not affect your regular use of the T.V. set. Does not have to be disconnected from set.
5. REMOTE CONTROL: Comes complete with 20 ft. of cable so it can be operated comfortably from a distance. Has its own volume control, speaker on-off switch, and two sets of jacks so either 1 or 2 ear phones can be connected.
6. DYNAMIC EAR PHONE: Set is supplied with one of ARGONNE exclusive Hi-Fi dynamic miniature earphone. Highly sensitive and efficient. Phone is complete with 3 ft. cord and tips, ready to insert in control box.
7. CONVENIENT: Size only $3\frac{1}{2}$ "x $2\frac{1}{2}$ "x $1\frac{1}{2}$ ". Complete with 1 earphone and 20 ft. cable. Completely wired with instructions. MODEL MS-125 Shpg. wt., 3 lbs. Net 6.50

EXTRA EARPHONE

MS-591 Shpg. wt., 8 oz. Net .79
10' extension cord for above. MS-590 Shpg. wt., 4 oz. Net .39

ECONOMY ALL-PURPOSE DYNAMIC EARPHONE



- For Transistor and Subminiature Receivers
- For Silent Radio and TV Listening

A sensitive all-purpose earphone designed with both your listening pleasure and pocket-book in mind. Extensive range and excellent tone combine, to provide excellent reproduction. Lightweight, equipped with a practically invisible ear support, that slips comfortably over either ear, from which the earphone can't slip out or fall. Ideal for use with TV and radio sets, amplifiers, miniature and transistor receivers, etc. Attractive unit with shiny chrome finish. Complete with a 3 ft. cord. A super value at this price. Shpg. wt., 5 oz. 6 ohm impedance, with subminiature phone plug. MS-591 Net .79

ONLY 79¢

LAFAYETTE "B" BATTERY ELIMINATOR and CHARGER for TRANSISTOR RADIOS



2.95

This simple "B" battery and eliminator has provision for replacing snap terminals on all 9-volt transistor batteries. Now when indoors you can operate your portable transistor set on regular 110V AC house current without using up your expensive "B" battery. Best of all you may also recharge your used battery for many extra hours of use. Complete with AC cord and assorted snap terminals to fit all 9-volt transistor batteries. Size: $3\frac{1}{2}$ "x $3\frac{3}{8}$ "x $2\frac{1}{2}$ "D. Shpg. wt., 1 lb. F-790 Net 2.95

NEW! LAFAYETTE AUTOMATIC PHOTO-ELECTRIC 'LUMINATOR



- Automatic Light Switch
- Lights on at sunset—off at sunrise

New photo-electronic, light sensitive switch turns lights on and off at dusk and dawn. Better than a clock—no setting and resetting of timer. Variance in "on-off" cycle adds extra protection when away from home. You need never come home to a darkened house. The controlled lamps go on as darkness falls—stay on until sufficient day light returns or until manually turned off. Just plug it in for protection from prowlers—to turn on night lights—illuminate outdoor areas—light up brigades—green houses—displays—show windows—any place you require automatic illumination. Mounts most anywhere on rubber suction cup feet. Unobtrusive—measures only $3\frac{3}{4}$ "x $2\frac{1}{2}$ "x $2\frac{1}{4}$ ". Use on 117 volt AC only. Maximum 300 watts lamp load. Instructions included. Shpg. wt., 1 lb. MS-790 Net 4.95

4.95

NEW! "STORAGE CELL" for TRANSISTOR RADIOS!



ONE CHARGEABLE BATTERY OUTLASTS 100 CONVENTIONAL BATTERIES

- Replaces 2U6, 216, BL-006P and BA-2
- Fluid Storage Type—Can't Leak Out
- Plays About 15 Hours on One Charging
- Battery Recharges Overnight
- Battery Can Be Used Over and Over Again
- Complete—Battery Plus Charger

ONLY 2.69

The next best thing to a battery that will last a lifetime—this battery can be used for 1100 to 1500 hours of playing time, AND MORE. Its long life is based on 2 new features: 1. A fine storage battery that cannot have fluid leakage; 2. Recharges Overnight—just plug the battery into the charger, the charger into your electrical outlet. Let it charge for 10-12 hours. It cannot burn out on recharge. After charging, the battery is good for about 15 hours of playing time. When the battery runs down, just charge it up and it's ready to play. Will outlast more than 100 conventional batteries. 9V Battery complete with charger. Battery $1\frac{1}{2}$ "x $1\frac{1}{2}$ "x $1\frac{1}{2}$ "; charger $3\frac{1}{2}$ "x $1\frac{1}{4}$ "x $1\frac{1}{4}$ ". Net 2.69
F-619 Battery and Charger. Shpg. wt., 6 oz. Net 2.69
BA-8 Battery Replacement for above. Net 1.48

LAFAYETTE BATTERIES AT TREMENDOUS SAVINGS



These popular batteries are for Portable and Transistor radios, R/C equipment, experimenters, labs, and hobbyists, etc.

FRESH STOCK — BRAND NEW GUARANTEED

Here are six of the most popular types used and at RIDICULOUSLY LOW PRICES

Stock No.	Voltage	Singly	Lots 10 Each	RCA	REPLACEMENTS FOR Burgess	Eveready	Others
BA-1	67 1/2	1.59	1.49	VS215 VS216 VS218	P45 P45M	477	BL-M145
BA-2	9	.39	.35	VS312 VS323	2U6	216	BL-006F
BA-3	9	.49	.44	VS300A VS314	P6 P6M	226	BL-M106
BA-5	67 1/2	1.29	1.19	VS318	UX45	416	BL-045
BA-6	67 1/2	1.45	1.35	VS016	UX45	467	BL-145
BA-7	9	.59	.53	VS309A	YL-6	E-177	TR-177

LAFAYETTE PHOTOFLASH, BC AND HEARING AID BATTERIES



Stock No.	V.	Singly Net Ea.	Lots 10 Ea. Fig.	Replacements for Burgess	Eveready	RCA	Shpg. Wt.
BA-11	15	.49	.44	A Y10	504	—	3 oz.
BA-14	22 1/2	.59	.53	A Y15	505	—	3 oz.
BA-12	22 1/2	.59	.53	B U15	412	VS084	3 oz.
BA-16	45	1.98	1.83	C M30	482	VS013	2 lb.
BA-15	90	2.36	2.12	D N60	490	VS090	1 lb.
BA-13	240	4.50	—	E U160	491	—	1 lb.

REPLACEMENT BATTERIES FOR BATTERY OPERATED TOYS

Stock No.	Eveready	Burgess	RCA	Size	Voltage	Wt.	Net.
BA-154	912	7	VS074	$\frac{1}{2}$ " Diam. x $1\frac{1}{4}$ "	1 1/2	$\frac{1}{2}$.10
BA-155	915	2	VS034	$\frac{1}{4}$ " Diam. x $1\frac{1}{2}$ "	1 1/2	$\frac{3}{4}$.095
BA-156	935	1	VS035	$1\frac{1}{2}$ " Diam. x $1\frac{1}{4}$ "	1 1/2	$\frac{1}{2}$.13
BA-157	950	2	VS036	$1\frac{1}{2}$ " Diam. x $2\frac{1}{2}$ "	1 1/2	$\frac{1}{2}$.13

"B" BATTERY ELIMINATOR and CHARGER



2.45

Replaces Eveready 416, Burgess UX-45, and RCA VS 318 67 1/2 V B batteries used in Radio Control units and many portables. Just plug in the AC cord and you can save your battery for outdoor use. Also recharges your battery. 110 volts. $3\frac{1}{2}$ "x $1\frac{1}{4}$ ". Shpg. wt., 7 oz. F-550 Net 2.45

LAFAYETTE SEMICONDUCTOR SPECIALS FOR EXPERIMENTER, KIT BUILDER, HOBBYIST

QUALITY SEMICONDUCTORS AT ECONOMY 'PACKAGE' PRICES

10 GERMANIUM DIODES
 Pkg. of 10 germanium diodes that replace 1N34, 1N34A, 1N46, 1N48, 1N51, 1N60, 1N64, 1N64A, 1N87, 1N105, 1N109, 1N147, 1N267, 1N268, 1N295, etc. Shpg. wt., 6 oz.
SP-234

10 SILICON DIODES
 Package of 10 silicon diodes. Replaces 1N34, 1N34A, 1N46, 1N48, 1N51, 1N60, 1N64, 1N87, 1N295, etc. Shpg. wt., 4 oz.
SP-235

4 PNP GERMANIUM TRANSISTORS
 SP-236
 Package of 4 PNP General Purpose Type Transistors similar in performance to: 2N107, 2N218, 2N1265, CK722, GT222, TR722, 2N1191, etc. Shpg. wt., 6 ozs.

.98
 per pkg.
 Any 4 Asst. Pkgs.
3.29

2 PNP TRANSISTORS
 SP-237
 Mixer/Oscillator Converter - Replaces 2N112, 2N114, 2N135, 2N136, 2N137, 2N140, 2N219, 2N411, 2N412, 2N414B, 2N415, CK760, CK766, 2S52, etc. Shpg. wt., 4 oz.

TRANSISTOR - DIODE PACKAGE SPECIAL
.79 Pkg.
 3 Pkgs. (can assort.) 2.09

5 GENERAL PURPOSE DIODES
 SP-218
 Package of 5 germanium glass diodes similar to 1N34A, 1N60, 1N64, 1N87A, etc.

4 PNP TRANSISTORS
 SP-220
 Package of 4 PNP Audio transistors similar to 2N107. Beta 15 minimum.

2 NPN TRANSISTORS
 SP-219
 Package of 2 NPN germanium transistors similar to 2N170 for Audio & RF. Beta 20 minimum.

2 PNP GERMANIUM TRANSISTORS IF AMPLIFIER
 SP-238
 Pkg. of 2 PNP germanium IF amplifier transistors that replace: 2N111, 2N111A, 2N112A, 2N139, 2N218, 2N409, 2N410, 2N413, 2N413A, 2N414, 2N414A, 2N416, GT760, 2S53, etc. Shpg. wt., 4 oz.

2 PNP GERMANIUM TRANSISTORS AF AMPLIFIERS (Up to 12 Volts)
 SP-239
 Pkg. of 2 PNP Germanium AF amplifier transistors that replace: 2N133A, 2N138A, 2N138B, 2N151, 2N186A, 2N187A, 2N215, 2N217, 2N319, 2N320, 2N359, 2N360-363, 2N407, 2N408, 2N1008, A, B, GT81R, GT109, 2S56, 2S838, etc. Shpg. wt., 4 oz.

2 GOLD PLATED SILICON RECTIFIERS 500 MIL - 400 PIV
 SP-240
 Pkg. of 2 miniature size exceptional 24 karat gold plated silicon rectifiers rated at 500 millamps, 400 PIV. Shpg. wt., 4 oz.

2 TOP HAT SILICON RECTIFIERS 750 MIL - 400 PIV
 SP-241
 Pkg. of 2 top hat type silicon rectifiers rated at 750 millamps, 400 PIV. Shpg. wt., 6 oz.

STUD MOUNT SILICON RECTIFIER 2 AMPERE 400 PIV
 SP-242
 Outstanding Buy! 2 amp. 400 Peak-Inverse-Volts Silicon Rectifier, stud mounting, 3/4" long less lug, 3/16" hex nut. Shpg. wt., 6 oz.

2-10 WATT POWER TRANSISTORS
 SP-243
 Package of 2 PNP 10 Watt germanium power transistors in popular TO-3 case. Similar to 2N155, 2N176, 2N235, 2N351, 2N242, 2N257, 2N268, 2N301A, 2N255, 2N554, 2N555, etc. Shpg. wt., 8 oz.

40 WATT HIGH POWER TRANSISTOR
 Amazing value is this 40-Watt high power PNP germanium transistor! Excellent for experimenter, hobbyist and kit builder for power supplies, auto

replacement, audio output, etc. Similar to 2N173, CTP1504, SFT266, etc. Bolt mounted. Shpg. wt., 8 oz.
SP-244

LAFAYETTE SPECIAL SILICON POWER RECTIFIERS
 Top hat lead type silicon rectifiers excellent for TV Radio and power supplies as half-wave, full wave rectifiers and voltage doublers.
 Type A: 750 Ma, 400 PIV @ 25°C.
 500 Ma, 400 PIV @ 90°C.
SP-196 Shpg. wt., 4 oz. Net .57
 10 for 5.13; 100 for 47.00
 Type B: 750 Ma, 200 PIV @ 25°C.
 500 Ma, 200 PIV @ 90°C.
SP-197 Shpg. wt., 4 oz. Net .47
 10 for 4.25; 100 for 38.50

LAFAYETTE PNP AUDIO TRANSISTOR SPECIAL!
AS LOW AS .31
 General audio type PNP transistor for experimenters and hobbyists, for code practice oscillators and similar small signal devices. In new JETC 30 welded case. Net, singly, each .30
SP-146
 10 for 3.00 50 for 16.95, 100 for 31.00

LAFAYETTE SPECIAL 7-TRANSISTOR SUPERHET PACKAGE
3.89
 • 6 Transistors plus Transistor Diode
 • Matched for Superheterodyne Push-Pull Circuit
 • Can Work on 9-Volts with Minimum Battery Drain
 • Highest Quality - All PNP
 Consists of 1 converter, 2 IF's, 1 driver, 2 push-pull output and 1 transistor diode. Packed in handy plastic case. Shpg. wt., 6 ozs.
SP-202 Net 3.89

GENERAL PURPOSE DIODES
.21
 EXCELLENT DETECTOR FOR TRANSISTOR AND VACUUM TUBE RADIO RECEIVERS
 EQUIVALENT TO: 10 for
 1N34 1N34A 1N38A 1.95
 1N48 1N56 1N69
SP-148 General Purpose Diode Net .21 each 10 for 1.95

NEW! RIDER TRANSISTOR SUBSTITUTION HANDBOOK
 • Over 6500 Direct Transistor Substitutions
 • 668 Substitutes for Japanese Types
 • 530 Diode Substitutions
 Includes basing diagrams, polarity identifications and manufacturers for over 2700 transistor types.
 BK-289 Postpaid in U.S.A. Net 1.50

POWER TRANSISTORS
 As Low As **.59**
 EACH UNIT Similar To: 2N256 2N307 2N554
 TESTED TO MEET SPECIFICATIONS
SP-147 Power Transistor Net 69c
 In lots of 100, Each Net 59c

NEW! ULTRA SUB-MINIATURE TRANSISTOR COIL KIT

3.45
 All in one kit—a complete set of matched micro-miniature coils, ferrite loop antenna, ultra-compact 2 gang variable condenser, tuning dial and schematic diagram for building a subminiature 6 transistor radio. Kit includes: Shielded and impregnated high-Q 455 KC IF transformers and oscillator coil—all slug tuned. Proper impedances are provided for optimum circuit performance. Variable condenser has protective case and rear trimmer adjustment. Flat ferrite loop antenna measures 2 1/4 x 1/4 x 1/4" thick. Clearly-printed circuit diagram indicates all parts necessary for a powerful 6 transistor receiver. Tuning dial and knob (1 1/4" dia.) fits securely on V.C. shaft. The ultra-compactness and quality of these essential components allow you to construct a broadcast radio, miniature by today's standards, at tremendous savings. Shpg. wt. of kit is 1 lb.
MS-828 Net 3.45

SUBMINIATURE TRANSISTOR AUDIO TRANSFORMERS
 A new series of miniature transformers for transistor and experimental miniature circuits. Ideal for miniature radio receivers, amplifiers, hearing aids, etc., using standard transistors. Incorporate special heat-treated high permeability magnetic cores—treated to resist corrosion. Designed for improved frequency response with low distortion. 3" color-coded leads. Average shpg. wt., 4 oz.
ONLY 79c
ONLY 1/2" x 1/2" x 1/2"

Stock No.	Circuit	Impedance Pri. Ω	Sec. Ω	O.C. Resistance Pri. Ω	Sec. Ω	Net
TR-97	INPUT	100,000	1000	1000	1000	.79
TR-98	DRIVER	10,000	2000 C.T.	240	60 C.T.	.79
TR-99	OUTPUT	500 C.T.	3.2	42 C.T.	0.7	.79
TR-120	INPUT	200,000	1000	1400	50.5	.89
TR-116	OUTPUT	500 C.T.	8	50 C.T.	1.7	.79

8 TRANSISTORS PLUS DIODE MODULE KIT
 • ALL 8 TRANSISTORS PLUS DIODE IN 2 NEATLY ASSEMBLED MODULES!
 • MAKES SUPERHET RADIO RECEIVER BUILDING EASY!
4.98
 These transistor modules are high quality semiconductor assemblies containing individual stages that perform all the functions of individually wired transistors and diodes. The converter-IF module is designed to achieve optimum gain, and the necessary matching of the audio output stages is accomplished for maximum gain with minimum distortion. May be operated at from 6 to 9 volts. Modules are mounted on schematic and terminations and connecting points are clearly indicated. Supplied with schematic parts list for a complete superhet receiver and alignment instructions for building 8 transistor modular radio. Shpg. wt., 8 oz.
SP-245 Net 4.98

NEW! 4 TRANSISTOR SUBMINIATURE PUSH-PULL AUDIO AMPLIFIER—
OUTPUT 100 MW
4.95
 Size: 3" x 1 1/4" x 1 1/4"
 • TERRIFIC FOR THE EXPERIMENTER, HOBBYIST AND KIT BUILDER!
 • COMPLETELY WIRED, NOT A KIT!
 • PRINTED CIRCUIT BOARD
 • COMPLETE WITH TRANSISTORS
 A tiny, transistorized push-pull audio amplifier with a multitude of applications. Only 3" x 1 1/4" x 1 1/4". It can be mounted inside other equipment to serve as a subminiature phono amplifier, tape recorder, amplifier, etc. Can be the complement of a homebuilt project which needs only an audio amplifier to make it complete and self-contained. Two stages of audio are followed by a push-pull output stage designed to deliver 100 mw to an 8-11 ohm impedance. Low impedance input, with a sensitivity of 0.9 mv. Input transformer for matching high impedances to the amplifier available as an accessory (see below). Includes leads for input, speaker, and volume control/on-off switch. Battery clips and leads supplied for 9 volt miniature battery (one required). Shpg. wt., 5 oz.
PK-543 Net 4.95
ACCESSORIES FOR ABOVE
 BA-2 9 volt battery. Shpg. wt., 2 oz. Net .39
 VC-31 50K ohm volume control w/switch. Shpg. wt., 2 oz. Net .69
 SK-193 8 ohm voice coil speaker. 3" Shpg. wt., 10 oz. Net 1.49
 SK-189 8 ohm voice coil speaker. 2" Shpg. wt., 8 oz. Net 1.49
 SK-191 8 ohm voice coil speaker. 1 1/2" Shpg. wt., 8 oz. Net 1.49
 Input transformer for matching high impedance (mike, etc.) to amplifier. Net .89
 TR-120

NEW! 5 TRANSISTOR PUSH-PULL AUDIO AMPLIFIER
6.95
 • ONLY 3 1/4" x 1 1/4" x 1 1/4"
 • 360 MW OUTPUT
 • COMPLETELY WIRED
 • DIRECT WIRING
 A more powerful and more sensitive version of the PK-543, this amplifier employs 3 stages of audio driving a push-pull output stage. Power output is 360 mw, designed for speakers with a voice coil impedance of 8-11 ohms. Low impedance input has sensitivity of 300 microvolts. Input transformer for matching high impedance to the amplifier input available as an accessory (see below). Comes with leads for low impedance input, speaker, volume control/on-off switch. Battery clips and leads supplied for 9 volt miniature battery (one required). Shpg. wt., 5 oz.
PK-544 Net 6.95
ACCESSORIES FOR ABOVE
 BA-2 9 volt battery. Shpg. wt., 2 oz. Net .39
 VC-28 10,000 ohm volume control w/switch. Shpg. wt., 2 oz. Net .69
 SK-193 8 ohm speaker. 3" Shpg. wt., 10 oz. Net 1.49
 SK-189 8 ohm speaker. 2" Shpg. wt., 8 oz. Net 1.49
 SK-191 8 ohm speaker. 2 1/2" Shpg. wt., 8 oz. Net 1.49
 Input transformer for matching high impedance (mike, etc.) to amplifier. Net .89
 TR-120

3 TRANSISTOR SUBMINIATURE AUDIO AMPLIFIER
3.75
 • FOR THE EXPERIMENTER, HOBBYIST, AND KIT BUILDER!
 • PRINTED CIRCUIT
 • COMPLETE WITH TRANSISTORS
 Here is an amazing little audio amplifier with a multitude of challenging applications, i.e., subminiature phono amplifier, tape recorder amplifier, hand-held public address amplifier, telephone pick-up amplifier, etc. Output sufficient for average listening. Has leads for any one of the following inputs: Tape recorder record/playback heads, radio-tuner, crystal or ceramic phono cartridge, and crystal or ceramic microphone. Has lead terminations for ON-OFF switch, Volume Control, 4 to 10 ohm speaker, and leads terminating in clips for a 9 volt miniature battery.
 Size 2 1/4 x 1 1/4 x 3/4". Can be readily mounted on chassis. Shpg. wt., 8 oz.
PK-E22 Net 3.75
BA-2 9 Volt Battery Net .39
5K ohm Volume Control with SPST Switch and Knob Shpg. wt., 2 oz. Net .59
VC-E2 Net .59
Miniature Crystal Microphone 1 1/4" Diam. x 3/4" Deep Shpg. wt., 6 oz. Net 1.49
MS-08 Net 1.49
Miniature Speaker 2 1/2" Diam. 10 ohms Voice Coil Impedance Shpg. wt., 8 oz. Net 1.49
SK-E6



LAFAYETTE AMATEUR and SWL


EQUIPMENT and ACCESSORIES

BUILD YOUR OWN NEW! EXCITING "EXPLOR-AIR" 4 BAND RECEIVER KIT



Made in U.S.A. **21⁹⁵**

The most sensational shortwave economy receiver kit ever offered. A complete shortwave and standard broadcast set which covers the entire region from 550 kilocycles to 30 megacycles. Four whole bands of fascinating programming unavailable elsewhere. Perfect for language students and radio amateurs. Only a regenerative circuit can offer such amazing performance and yet be so simple to build. Building this fine kit is an absolute pleasure — It's so well designed you can't go wrong. Kit includes all the parts you need, and the detailed step-by-step instruction book with its giant pictorial drawings shows you just how to put them together. One front panel knob does all the bandswitching at the flick of the wrist, immediately taking you from band to band. All coils are prewound for greater accuracy. This kit is so easy to build a child who can read could do it (and many already have!). The chassis is completely isolated from the circuit, so there is no shock hazard.



TUNE IN the WORLD


- 4 Bands for total coverage: • 550-1600 Kc broadcast band • 1.7-5.0 Mc., 5.0-14 Mc., 14-30 Mc. shortwave bands • Complete band-switching from front panel • Built-in Big 4" PM Loudspeaker

This precision radio kit is just full of extra features. Complete 4 band coverage of broadcast stations, international broadcast bands, amateur, maritime, fire and police services, yes, even satellite signals. Big 4" speaker and sensitive circuit with 50C5 output stage and 12A7 regenerative detector and amplifier stages give you all the volume you want. Phone jack for privacy automatically disconnects speaker. All controls are on the front panel: On-Off/Volume, Main Tuning, Band Spread, Bandswitch, Antenna Tuning, and Regeneration. 110 volt 50-60 cycle AC-DC power supply lets you use this fine set anywhere. Size: 10" x 7" x 5". Everything needed for unexcelled reception is combined in a compact, economical package.

- KT-135 EXPLOR-AIR RECEIVER KIT (Less Cabinet) wt. 5 lbs. Net 21.95
- ML-150 Leatherette covered Wooden Cabinet for above, 1 lb. Net 2.75



E. F. JOHNSON Adventurer




IN KIT FORM

NO MONEY DOWN! **54.95**

"ADVENTURER" TRANSMITTER 50 WATTS CW INPUT, 80 THRU 10 METERS

Completely self-contained transmitter in kit form. Features crystal or external VFO control, single-knob band-switching, clean break-in keying. 6AG7 oscillator/multiplier drives 807 final. Effectively TVI suppressed. 10% \times 8 $\frac{1}{2}$ " \times 7 $\frac{3}{8}$ ". Shpg. wt., 19 lbs.
MODEL 240-181-1. Above in Kit Form. With tubes. HE-423WX Net 54.95
MODEL 250-40. Speech amplifier/modulator kit for Adventurer. With tubes. Shpg. wt., 1 lb. HE-444 Net 12.25



EICO

720K TRANSMITTER KIT

Brand new 90 watt band switching rig for 80 through 10 meters. Features a 6146 final amplifier for 90 watts CW input, up to 65 watts phone with external modulation. 6AQ5 clamper tube protects final in case of loss of excitation. Variable pitch Pi-net output matches 50-1000 ohm loads. Oscillator keying permits full break-in operation. Panel meter indicates exact operating currents and helps in tuning up. Its "novice limit" calibration safeguards the novice against exceeding the 75 watt power limit. Tubes: 6CL6 Colpitts oscillator, 6AQ5 buffer-multiplier, 6146 final amplifier, 6AQ5 clamper, and GZ34 rectifier. Copper plated chassis, ceramic switches, ingenious metal case with complete shielding. 5Hx15Wx9 $\frac{1}{2}$ "D. Shpg. wt., 27 lbs. With all parts and instructions.
HE-310WX Kit Net 79.95
MODEL 720 above factory wired. Net 119.95
HE-311WX

VALUES IN AMATEUR CLOCKS!

24-HOUR STATION CLOCK

- Tell world-wide time at a glance!
- Ideal clock for amateur, short-wave listener

24 HOUR ELECTRIC WORLD CLOCK

- Adjustable for Various Time Zones
- South Polar Projection

"HAM" Station Call Timers

Net 21.90

TD-2400. Self starting, accurate clock for telling world-wide as well as local time. Calibrated in hours, 0100 to 2400; in minutes and seconds, 1 to 60. Shows time directly in all time zones. 10" dia. For 110-120 volt, 60 cycles, A.C. Shpg. wt., 4 lbs.
ML-82—Net including excise tax 14.85

Self starting, accurate electric clock. Tells world-wide and local time. Calibrated in hours—1 to 24, minutes and seconds—1 to 60. Black dial with white graduations. Chrome plated case. U.L. approved. 110-120 V. 60 cyc. AC. Shpg. wt., 1 $\frac{1}{2}$ lbs.
ML-210 including excise tax Net 8.47

24 hour "Tymeter" digital read-out clock with 10 minutes station call reminder. Buzzer sounds every 10 minutes as a warning to "sign-in" your call letters. Walnut finish case, 4Hx7 $\frac{3}{4}$ Wx4"D. UL approved. 110V. 60 c/s A.C. Shpg. wt., 3 lbs.
ML-216 Net 21.90
Same as above 12 hour "Tymeter" instead of 24.
ML-217 Net 18.55

NEW! HE-34 SWR AND FORWARD POWER METER

Net 16.95

- Reads SWR and Relative Power Output Up To 1 KW
- For Continuous Use in 52 Ohm Lines
- Highly Compact — Only 2 $\frac{1}{2}$ " \times 5" \times 2 $\frac{1}{2}$ "
- Switch Selects SWR or Forward Power — No Reversing Necessary

A compact SWR and relative power meter which can be permanently inserted into a 52 ohm coaxial line to monitor transmitter and antenna performance. The ideal aid in adjusting beams, trap antennas, matching networks, etc., or for tuning transmitters for maximum output. Designed for the frequency range from 3 to 200 mc, and for powers from 25 watts to a full kilowatt. Above 7 Mc, as little as 10 watts will provide adequate sampling; above 100 Mc, as little as 5 watts. The unit is installed by means of a standard coaxial connector on each side, and becomes part of the 52 ohm line. Insertion loss is negligible. Once installed the unit need never be reversed. A switch on the front panel is set to SWR SET for relative forward power readings up to 1 KW on a scale calibrated from 0 to 10, and for adjustment of the sensitivity control for SWR readings. The switch is set to SWR for measurement of reflected power, on an SWR scale calibrated from 1:1 to 100:1. The HE-34 measures only 2 $\frac{1}{2}$ " \times 5" \times 2 $\frac{1}{2}$ ", excluding coax connectors.
HE-34 Shpg. wt., 1 $\frac{1}{4}$ lbs. Net 16.95

NEW HQ-105TR CB AND HAM BAND TRANSCEIVER FOR 11 METER & 10 METER OPERATION

Net 219.50
NO MONEY DOWN

Versatile citizens band transceiver with built-in provision for ham band operation. Transmitter can easily be retuned for 10 meter operation—ideal for the citizens band operator who wishes to have immediate access to an amateur band upon the arrival of his general class license. Also ideal for the amateur operator wishing to use a single unit for both his hobby and his business. Transmitter has 5 watt input, 100% amplitude modulated, for both CB and 10 meter operation. Receiver is continuously tunable from 540 Kc to 30Mc, with accurately calibrated electrical bandspread on the 80, 40, 20, 15 and 10 meter bands, plus the citizens band. Other receiver features approximately equivalent to those of the new HQ-100A. Size 16 $\frac{1}{4}$ " \times 9 $\frac{1}{4}$ " \times 9 $\frac{1}{4}$ "D.
HE-148WX HQ-105TR, less clock. Shpg. wt., 34 lbs. Net 219.50
HE-149WX HQ-105TRC, w/clock timer Net 229.50
Model S-100 Matching speaker, shpg. wt., 10 lbs. Net 14.95
HE-152

LAFAYETTE 27 MC CITIZENS BAND CRYSTALS FOR POPULAR CB TRANSCEIVERS

- Selected Lafayette Receive and Transmit Crystals
- Transmit crystals for Lafayette HE-15A, HE-29A, HE-20A, RCA, Mark VII, E. F. Johnson Messengers HE-830L (Specify Freq.) Net 2.25
 - Transmit Crystal for Vocaline ED27M HE-255L (Specify Freq.) Net 3.25
 - Receive crystal for Lafayette HE-20A, RCA Mark VII HE-22L (Specify Freq.) Net 2.25
 - Receive Crystals for E. F. Johnson Messengers HE-833L (Specify Freq.) Net 3.25
 - Selected Lafayette Matched Crystals (Receive/Transmit) For Gonset G12 and G14 Transceivers HE-538L (Specify Freq.) Net 5.90
 - For Polytronics PC11G Transceiver HE-297L (Specify Freq.) Net 5.90
 - For Osborne 300 (all transistorized) CB Transceiver HE-831L (Specify Freq.) Net 5.90
 - For Sonar Model E HE-832L (Specify Freq.) Net 5.90

NEW! AMECO AC-1T AMATEUR TRANSMITTER KIT

- IDEAL FOR NOVICE
- SELF CONTAINED

The ideal unit for beginner or novice. Contains transformer powered AC power supply. Uses a PI-network output circuit to load random length wire antenna. No antenna tuner required. Has full 15 watt input on 40 and 80 meters. Easy to build and operate. Complete with punched chassis, all parts, tubes (6V6 and 6X5) and instructions. Shpg. wt., 8 lbs.
HE-394 Transmitter Kit Net 19.55
HE-395 CK1 extra coil kit Net .75

ASTATIC D-104 MICROPHONE

Used extensively by radio amateurs for its high intelligibility and "punch." Responds with rising characteristics from 500-4,000 cps. High output sealed crystal element is impervious to moisture. Output level - 46 db. Chrome finished mesh grille and body. With 5 ft. single conductor, shielded cable and adaptor to $\frac{5}{8}$ " - 27 thread. Shpg. wt., 1 $\frac{3}{4}$ lbs.
M-162 Net 18.60
Model GD-104 Same as D-104 except with push-to-talk stand Shpg. wt., 4 lbs. Net 30.72
M-161

MODEL CM-1 PUSH-TO-TALK CARBON MICROPHONE

Heavy-duty communications type for mobile operation. Black moulded plastic case. Available with retractable or straight cord. Frequency response 200-4000 cps. With hanging bracket. Bypassed for R.F. Single button type. D.P.S.T. switch. Shpg. wt., 1 lb.
M-81 CM-1-SC mike with straight cord Net 7.95
M-80 CM-1-CC mike with coiled cord Net 9.95

AMECO MODEL PH-II HF PREAMPLIFIERS

- For Mobile or Fixed Operation

Especially designed for citizens band transceivers, the PH-II increases receiving range considerably. This preamplifier has a better noise figure than most multi-band receivers. 20 db. minimum gain will improve image and spurious rejection with its two tuned circuits, and also increase sensitivity. Uses high gain 6CB6 pentode tube. Operates from 100-250v at 8ma. B+. Size only 3 $\frac{3}{4}$ " \times 2 $\frac{1}{2}$ " \times 3 $\frac{1}{2}$ ". Shpg. wt., 2 lbs.
HE-380 Factory wired and tested Net 13.67

TRANSISTORIZED 100 KC CRYSTAL CALIBRATOR MODEL TE-29

Net 11.95

- Generates Useful 100 Kc Harmonics Up To 54 Mc
- Transistorized, Self-Powered and Self-Contained
- Completely Wired — Not a Kit

Fully transistorized, the TE-29 will provide extremely accurate markings every 100 Kc up to 54 Mc. The calibrator is activated by an on/off switch on the front panel, and the output is taken from two binding posts at the rear. The output may be coupled to the receiver directly or by indirect pickup from a small antenna wire connected to the "hot" binding post. Powered by a small 9 volt battery, the transistor oscillator is completely self-contained — requires no "digging" into the receiver for power. As the battery runs down, the effect is to lower the amplitude of the oscillation without changing the frequency. Normal operation is easily restored with a new battery. Housed in a 4 $\frac{1}{4}$ " \times 2 $\frac{3}{4}$ " \times 1 $\frac{3}{8}$ " metal cabinet with sloping front panel. With battery. Shpg. wt., 1 $\frac{1}{2}$ lbs.
TE-29 Net 11.95
BA-2 Replacement battery for above. Net .39

"ON THE AIR" ILLUMINATION SIGN

Flip to transmit and the sign tells them you're "On The Air." Snap-out back plate for easy accessibility. Durable baked black finish in heavy gauge steel. 110V, AC. Size: 10 $\frac{1}{2}$ " \times L. 3 $\frac{1}{2}$ " \times M. 3"D. Shpg. wt., 6 lbs.
HE-645 Net 6.95

LAFAYETTE MODEL HE-11 SPEAKER FOR AMATEUR and SHORT WAVE RECEIVERS

Net 7.95

Efficient and attractive speaker especially designed as ideal mate for communications receivers. 4" speaker housed in handsome, tapered, grey metal cabinet reduces QRN and peaks voice frequencies. Impedance 8 ohms. 7 $\frac{3}{8}$ " \times 5 $\frac{3}{8}$ " \times 4 $\frac{3}{8}$ ".
HE-11 Shpg. wt., 4 lbs. Net 7.95
HE-14 As above, except 4 ohms impedance Net 7.95

TRANSISTORIZED 100 KC and 1 MC MARKER CALIBRATOR

Net 18.95

- Gives Markers Every 1 Mc, or Every 100 Kc, at the Flick of a Switch
- Tone Modulated 100 Kc Output, Unmodulated 1 Mc Output
- Fully Transistorized, Self-Contained and Self-Powered
- Completely Wired — Not a Kit

Consists of two crystal controlled transistor oscillators operating at 100 Kc and 1 Mc respectively. 3 Position front panel control function switch provides for Off, 1 Mc, and 100 Kc Mod. The 1 Mc oscillator operates alone, unmodulated and provides sufficient harmonics to give accurate markers every 1 Mc up to 54 Mc. At the 100 Kc Mod. position, the TE-27 will furnish tone modulated signals every 100 Kc up to 54 Mc, so that the calibration may be refined to intervals of tenths for megacycle. The modulated output in the 100 Kc position makes it easier to distinguish the marker signal from other continuous signals that may be received. It also helps in receiver alignment by providing an audible tone without need for a BFO. Completely self-contained and powered by a small 9 volt battery. Output is taken from two binding posts in the rear. Sloping front metal cabinet measures 4 $\frac{1}{4}$ " \times 2 $\frac{3}{4}$ " \times 1 $\frac{3}{8}$ ". With battery. Shpg. wt., 1 $\frac{1}{2}$ lbs.
TE-27 Net 18.95
BA-2 Replacement Battery for above Net .39

B & W 550A COAXIAL SWITCH

Net 8.25

An inexpensive multi-position coaxial switch that eliminates the annoyance of screwing and unscrewing coaxial connections. The B & W 550A permits you to instantly select any one of five transmitters, antennas, excitors, receivers, and other r-f generating devices 1 kw of modulated power with a maximum cross-talk of -45db at 30mc.
HP-91 Shpg. wt., 2 lbs. Net 8.25

LAFAYETTE—Build Your Own KITS....

NEW!
LAFAYETTE KT-199
2-TRANSISTOR
DIODE BROADCAST
RADIO KIT

Made in U.S.A. + **POWERFUL REFLEX CIRCUIT**

AR-50

- No Soldering—A Child Could Build It!
- Pre-wired Switch and Control
- 50 Mile Range
- Beautifully Styled Cabinet

Absolutely no soldering or hole punching is necessary. All wiring and components are connected to fahnstock clips mounted on a pre-punched board. It is the ideal kit for beginners interested in transistor circuits. The on-off switch and level control are already wired—just clip them in. A clear construction manual is included with simple How-To-Do-It instructions so that a child could build it. And that's not all. Lafayette engineers have designed this transistor radio to have a receiving radius of approximately 50 miles! Only one 9 volt battery powers its 2-transistor reflex circuit. Ferrite core loop antenna and a variable gang tuning condenser insure crisp reception on the entire AM broadcast band from 550-1600KC. Will accept any high impedance earphone for private listening. Size: 5½x2½x4¾"D. 2-2N165 PNP transistors, 1N48A diode. Complete with instruction manual. Shpg. wt., 1½ lbs. KT-199 Complete 2 transistor kit—less earphone and less battery Net 9.95

Recommended Earphone Net 1.39
 AR-50 Dynamic earphone 3,000 ohm Net .39
 BA-2 9-volt battery Net .39

New! LAFAYETTE KT-196 2-STATION INTERCOM SYSTEM KIT

Made in U.S.A.

- Attractive, Modern Styling
- Complete—One Master and One Remote Station Plus 50 Ft. of Cable
- Perfect as Baby Sitter or Sickroom Watcher
- 2 Complete Stages of Amplification

14.75

The perfect 2-station intercom kit beautifully styled and engineered by Lafayette's Kit Divisions, it will grace any room in the home, office, shop, school, etc. Consisting of a Master Station and a Remote Station, most useful to communicate with the basement, garage, playroom or nursery. The master unit features a highly sensitive 3-tube circuit with 2 complete stages of audio amplification for maximum talk-power and sensitive reception. Makes a marvelous "baby-sitter." Remote unit may be left in permanent "Talk" position. Master Station has a 3-way lever switch which provides Momentary Talk, Listen, and a lock-in talk position to free hands for other duties or for extended conversation. Master station front panel also includes a combined on/off switch, volume control. Only the master unit need be plugged into outlet—remote may be placed anywhere. The system may use up to 3 remotes. Famous Lafayette instruction manual simplifies assembly. Size of each unit: 4Hx8Wx4¾"D. Attractive metal enclosures. Tubes: 36AM3A, 60FX5, 18FY6. Complete with all parts necessary and 50 feet of 3-wire cable. For 105-125V 50-60 cycles AC or DC. KT-196 2-Station Intercom Kit. Shpg. wt., 7 lbs. Net 14.75
 LA-196 Factory Wired Net 19.50
 Extra Remote Station Kit—For use with above. Less cable. Net 3.45
 LA-197 Shpg. wt., 2½ lbs. Net 3.95
 LA-197 Factory Wired Remote Net 3.95
 Hook-up wire for above. per ft. Net .03
 WR-160

NEW!
LAFAYETTE KT-195
WIRELESS BROADCAST
AMPLIFIER KIT

Made in U.S.A.

Use it either as a Wireless Broadcaster or AM Audio Amplifier!

- POWERFUL SIGNAL
- PLAYS THROUGH ALL AM RADIOS
- WORKS WITH ALL CRYSTAL AND MAGNETIC MIKES AND PHONO CARTRIDGES

11.95

Treat yourself and your family to hours of fun with this new Lafayette Kit. Make your own radio programs, announcements, etc. through AM radios anywhere in the house, without wires or extra gadgets. Designed for easy construction by youngsters or extra the KT-195 combines in one compact unit a powerful 3-tube wireless broadcaster and an audio amplifier. Clearly written instruction manual makes it a cinch to build. Operates on any frequency between 900 and 1600 kilocycles on your radio dial. It will accept any crystal or magnetic microphone. In addition, the KT-195 may be used directly as a phono or microphone amplifier. No external preamp is required. Simple slide switch permits either form of operation. Just connect it to a PM speaker (4-16 ohms) instead of record broadcasts. Within this range, however, the unit can provide high quality voice or record broadcasts. No license or permit is necessary. Complete with crystal clear instruction manual. Less Mike. For 105-125V AC or DC cps. Attractive 4Hx8Wx4¾"D. KT-195 Shpg. wt., 3 lbs. Net 11.95
 LA-23 Same as above, but factory wired and tested. Net 14.45
 PA-73 Shpg. wt., 1 lb. Net 2.95
 Crystal microphone for above. Desk or hand held. 8 ft. cable. Net 2.95

SUPER-SENSITIVE PHOTOCCELL ELECTRONIC RELAY KIT

Made in U.S.A.

- WITH CLAIREX CAESIUM SULPHIDE PHOTOCCELL
- ADJUSTABLE SUPER SENSITIVITY—WORKS WITH JUST A FLASHLIGHT AT 250 FEET!
- NEEDS NO SPECIAL HIGH-INTENSITY LIGHTS
- INSTANTANEOUS OR SUSTAINED OPERATION ON THE FLIP OF A SWITCH!

12.95

Ideal for sustained operation required for burglar alarms, door buzzers and for instantaneous on-off operation required for counters, packaging, door opening, motor activation plus countless industrial applications. Switch converts unit from instantaneous "on-off" to sustained "on" operation. "RESET" switch opens the external circuit and turns off the alarm. The unit operates on 110 volts AC and incorporates the efficient 5823 cold cathode tube. A simple change in wiring (in instructions) as well as convenient input terminals, enable you to supply the external circuit with any desired voltage. Relay contacts rated at 3 amps permitting up to 300 watts external load on 110 Volts AC. Complete with all parts, photocell, tube, chassis, silk-screened metal cabinet and easy-to-follow illustrated instructions. Size: 3x4x5" Net 12.95
 KT-133A Kit. Complete. Shpg. wt., 3 lbs.

New! 20-in-1 TRANSISTOR Experimenters KIT

FUN TO BUILD — EDUCATIONAL — and all 20 projects result in a useful working instrument

PROJECTS YOU BUILD

1. TRANSISTOR TESTER
2. VOICE ACTUATED ALARM
3. PHOTO TIMER
4. AUDIO AMPLIFIER
5. CRYSTAL SET
6. SOLAR RADIO
7. RAIN ALARM
8. TIMER
9. ONE TRANSISTOR RECEIVER
10. CODE PRACTICE OSCILLATOR
11. METRONOME
12. TWO TRANSISTOR RECEIVER
13. ELECTRONIC GAME
14. HOME BROADCASTER
15. PHOTO ELECTRIC RELAY
16. BURGLAR ALARM
17. WIRELESS TRANSMITTER
18. REGENERATIVE RECEIVER
19. CITIZENS BANO MONITOR
20. AUDIO OSCILLATOR

Only 18.95

This new Educational Kit opens the field of transistor-electronics, with all its fascinating circuits and gadgets, in a simple, easy-to-follow manner. Excellent for beginners as well as advanced experimenters, this kit enables you to build and learn about 20 interesting and useful transistor circuits. By utilizing "bread-board" construction, each project can be simply wired and traced. After building the basic circuit, any of the 20 projects can be built by simply inserting a few preassembled component blocks and interconnecting leads between them. A soldering iron is only required for the basic wiring and not for subsequent projects. All wiring is covered in a step-by-step manner by the instruction manual. Each of the 20 projects is clearly presented with step-by-step instructions, large easy-to-read pictorial wiring diagrams, schematic diagrams, and an explanation of the circuit behavior. There are no AC voltages to produce shock hazard. Amaze your friends with a Voice-Actuated Alarm, Rain Alarm, Home Broadcaster, and other projects. Build useful projects for the home—Metronome, Burglar Alarm, and Timer. Learning Morse Code with the Code Practice Oscillator and receiving Short-Wave Citizens Band Stations. The kit is complete with perforated mounting board, 2-transistors, 1-diode, earphone, light sensitive plate, and all other parts required for construction. The detailed 28 page instruction manual contains a wealth of information about each project. Less batteries and tools. Shpg. wt., 6 lbs. Net 18.95
 KT-173 Complete Net .095
 BA-155 Z Cell Battery for Kit projects Net 1.61
 BA-270 22½ Volt Battery for Kit projects

LAFAYETTE 10-IN-1 LABORATORY KIT

Made in U.S.A.

WITH THIS KIT YOU CAN BUILD

1. RADIO RECEIVER
2. PHONO-MICROPHONE AMPLIFIER
3. PHONO OSCILLATOR
4. BROADCAST STATION
5. CODE PRACTICE OSCILLATOR
6. SIGNAL TRACER
7. CAPACITY OPERATED RELAY
8. ELECTRONIC TIMER
9. ELECTRONIC SWITCH
10. PHOTOCCELL RELAY

Here is a new laboratory tested experimenters kit designed to provide maximum instruction and entertainment and which is ideal for both the beginner and advanced experimenter. Features practical and interesting circuits which enable you to do many novel and interesting things while learning how these circuits function. You can broadcast your voice or play a phonograph through your radio from anywhere in the house, send code through a headphone or radio, or use light or body capacitance to activate electrical circuits. Safe, low voltage is utilized. Kit is complete with perforated mounting board, 3 vacuum tubes, microphone and all parts necessary for construction. A detailed 12 page instruction manual contains simple-to-follow pictorial and schematic diagrams for each project. Less headphone, photoelectric cell and socket, wire and solder. Net 15.50
 KT-36A Shpg. wt., 5 lbs. Net 3.75
 PHOTOELECTRIC CELL TUBE TYPE 868. Shpg. wt., 8 oz. Net .13
 CM-70 AMPHENOL 77MIP4 SOCKET FOR ABOVE. Shpg. wt., 1 oz. Net .18
 ME-33 CANNON AM-15-1 1000 OHM SINGLE HEADPHONE. Shpg. wt., 1 lb.

NEW! ELECTRONICS EDUCATIONAL KIT

"GUIDED-TOUR" INTRODUCTION TO THE WORLD OF ELECTRONICS

24.50

NO MONEY DOWN

- 194 ILLUSTRATIONS
- INCLUDES QUESTIONS & ANSWERS FOR EACH SECTION
- CLEARLY WORDED STEP-BY-STEP INSTRUCTIONS
- COVERS BOTH AC & DC IN THEIR ENTIRETY
- TEACHES, AS YOU BUILD
- 12 COMPLETE EXPERIMENTS RESULT IN A FINISHED AC & DC TEST INSTRUMENT
- ENABLES REPAIR OF HOUSEHOLD APPLIANCES

The fascinating world of electronics introduced in a simple, easy-to-follow manner through this new Lafayette KT-180 Electronic Educational Kit. Not a toy—this kit is a complete beginners electronics laboratory course featuring an extremely useful AC/DC Multimeter.

In the process of constructing this test meter, the fundamental principles of electricity and electronics are introduced in a "learn-by-doing" method. The focus of attention is on the basic sensitive meter for measuring the flow of electrical current. From this simple measurement, the meter is built up to indicative voltage and resistance. The detailed 116 page instruction manual contains 194 illustrations and is written in a simple, easy-to-read, step-by-step manner with questions and answers supplied for each section. Providing a virtual "guided tour" of electrical fundamentals, this kit furnishes a complete course in AC and DC including ohms law, series and parallel connections, making electro-magnets, producing electricity by induction and testing house appliances. The kit is supplied less batteries. Net 24.50
 KT-180 Shpg. wt., 5 lbs. Net ea. .095
 BA-155 (Burgess Z type battery, 2 required)

LAFAYETTE STEREO PHONO AMPLIFIER KIT

Made in U.S.A.

- 4 WATTS STEREO OUTPUT
- ISOLATION TRANSFORMER
- SEPARATE VOLUME CONTROLS
- GANGED TONE CONTROLS
- STEREO-MONAUROAL SWITCH

18.95

This is a complete 4-watt hi-fi stereo amplifier having 2 watts output per channel; ganged tone controls; stereo-mono switch to feed one channel to both speakers and to reverse the channels. Just ideal for custom mounting in even the tightest locations. Excellent for small apartments. Complete with instructions. For 3.2 ohm speakers. Tubes: 2-50C5, 2-12AX7 plus selenium rectifier. For 110-120 volts, 60 cycle AC. Net 18.95
 KT-126 Kit. Complete. Shpg. wt., 7 lbs.

5 WATT PUSH-PULL AC-DC HI-FI AMPLIFIER KIT

Made in U.S.A.

- SEPARATE VOLUME, BASS & TREBLE CONTROLS
- PUSH-PULL AUDIO OUTPUT STAGE
- INVERSE FEEDBACK CIRCUIT
- AC OR DC OPERATION

10.95

Here in kit form is an AC-DC hi-fi amplifier that presents unusual features despite its amazingly low price. The separate bass and treble controls permit adjustment of both low and high frequency response and balance. Works equally well with both crystal or ceramic cartridges. Has a 4-tube line up—a 12AX7 amplifier and phase inverter, a 35W4 rectifier and a pair of 35C5's in push-pull having a power-packed low distortion output. The circuit utilizes an inverse feedback loop to reduce the level of hum and distortion. Kit is complete containing all essential parts, tubes and detailed instruction manual showing pictorial and schematic diagrams. Shpg. wt., 4 lbs. Net 10.95
 KT-92

Complete With 116 Page Instruction Manual — Virtually A Textbook & Laboratory Manual

The process of constructing this test meter, the fundamental principles of electricity and electronics are introduced in a "learn-by-doing" method. The focus of attention is on the basic sensitive meter for measuring the flow of electrical current. From this simple measurement, the meter is built up to indicative voltage and resistance. The detailed 116 page instruction manual contains 194 illustrations and is written in a simple, easy-to-read, step-by-step manner with questions and answers supplied for each section. Providing a virtual "guided tour" of electrical fundamentals, this kit furnishes a complete course in AC and DC including ohms law, series and parallel connections, making electro-magnets, producing electricity by induction and testing house appliances. The kit is supplied less batteries. Net 24.50
 KT-180 Shpg. wt., 5 lbs. Net ea. .095
 BA-155 (Burgess Z type battery, 2 required)

NEW! LAFAYETTE PEAK-to-PEAK

V.T.V.M. KIT

An Outstanding Development In V.T.V.M. Design
The Only V.T.V.M. Available With These Features

NO MONEY DOWN

KT-174 | TE-31
44.50 | **57.00**
IN KIT FORM | COMPLETELY WIRED AND TESTED

LABORATORY TEST EQUIPMENT IN EASY-TO-BUILD KIT FORM

COMPARE THESE SPECIFICATIONS

DC VOLTMETER—Ranges: 0-1.5, 5, 15, 50, 150, 500, 1500V. Input Resistance: All ranges—11 Megohms. Sensitivity—1.5V Range: 7.3 Megohms/Volt. Accuracy: $\pm 2\%$ of full scale at 117VAC—deviation due to line voltage variation between 105-125 volts is negligible.
AC VOLTMETER—LOW AC—Ranges: RMS-0 to 50 mv, 0-150 mv, 0-500 mv. Peak-To-Peak—0-140 mv, 0-420 mv, 0-1400 mv. Accuracy: $\pm 5\%$ of full scale. Input Impedance: 1 megohm at 1 KC. Freq. Response: ± 1 db from 20 to 300,000 cps from 600-ohm source.
REGULAR AC—Ranges: RMS—0-1.5, 5, 15, 50, 150, 500, 1500 volts. Peak-To-Peak: 0-4.2, 14.0, 42, 140, 420, 1400, 4200V. Accuracy: 3% on all ranges except 5% on 0 to 5V. Freq. Response: ± 1 db 20 cps to 4 mc from 600-ohm source. Input Impedance at 1 KC: 0-1.5V, 5V, 15, 50-83 Meg. 0-150V, 1.3 meg—0-500V, 1500V—1.5 meg. Db.-10 to -5 OHMMETER—7 Ranges: 0-1000 RX1, RX10, RX100, RX1000, RX10K, RX100K, RX1M using precision 1% dividing resistors. Meter Movement: 200 μ a for full scale deflection. Tubes: 1—6BN8, AC full-wave peak rectifier and low AC amplifier; 1—12AU7 twin triode meter DC amplifier and balanced bridge. Incorporates Half Wave Selenium Rectifier and Well Filtered Fused Power Supply.

- Special Low AC Ranges Provide Noise & Gain Measurements (as low as 1 mv) for Audio & Hi-Fidelity Applications
- Scope Monitor Terminals For Direct Connection To Oscilloscope
- Newly Designed Lafayette Push-Button AC/DC Omni-Probe
- Calibration Controls—Accessible Without Removing Cabinet
- Measures AC Peak-To-Peak, AC RMS, DC Voltage & Resistance
- Direct Reading DB Scale
- Regulated & Balanced Bridge Circuit Provides Unequaled Accuracy & Stability
- Circuit Employs 12AU7 Twin Triode Operating Only Within Its Linear Capabilities • 1% Precision Multiplier Resistors
- Accurate 200 μ a Meter Movement with Large 4 1/2" face

In Every Respect A Professional Test Instrument—Engineered to meet and exceed the rugged standards, accuracy plus required sensitivity demanded in laboratory, industrial and service applications. The KT-174 offers in remarkably easy-to-build kit form, a Vacuum Tube Volt Meter that achieves a level of performance and versatility rivaling factory wired equipment many times its price. Unquestionably The Finest VTVM in its class. Utilizing a printed circuit board, Lafayette's famous step-by-step instructions and huge pictorial diagrams assure ease of assembly. Attractive dark grey front panel is set in a contrasting textured light grey metal case. Complete with tubes, battery and special Lafayette Omni-Probe. Size: 8 1/2x6x5 1/2". For 105-125 volts, 60 cycles AC. Shpg. wt., 8 lbs.

MADE IN U.S.A.

TE-31 Same as above, wired and tested Net 44.50
KT-174 Kit Form Net 57.00
TE-205 RF Probe KIT For KT-174 and any Other Net 3.75
11 meg Ohm Impedance VTVM

NEW! LAFAYETTE V.T.V.M. KIT

MODEL KT 202

25.95

NO MONEY DOWN

- Wide Band—AC Measurements on any Waveform from 30 Cycles to Over 5 MC, Without Additional Probes or Accessories
- 11 Megohm Input Resistance—Negligible Loading Effects on DC Circuits
- Direct Reading DB Scale
- Balanced Push-Pull Amplifier—Isolates and Protects Meter
- Etched Circuit Design Simplifies Construction
- Selected 1% Zero Temperature Coefficient Multiplier Resistors for Dependable, Accurate Readings
- Giant 6" Full-View Meter With Easy-To-Read Two-Color Scales

An indispensable test instrument for the service technician, experimenter or hobbyist. The KT-202 is a high quality V.T.V.M. in easy-to-build kit form, which offers features unusual at this low price. It is a highly accurate DC voltmeter, AC voltmeter and ohmmeter employing a giant 6", 400 μ a meter with clear black and red scales.

High input impedance of 11 megohms, accurately measure DC voltages up to 1500 volts while presenting a negligible load to the circuit under test. As a wide band AC voltmeter, it will measure AC peak-to-peak voltages up to 2,000 volts on any waveform. All this from 30 cycles to above 5 Mc—without any accessory probes! AC RMS voltages may be read directly up to 1,500 volts if the waveform is sinusoidal. The wide frequency response makes this meter ideal in audio, radio and TV applications. Resistances can be read directly on the Ohms scale from 0.2 ohms to 1,000 megohms. A direct reading decibel scale is calibrated from -10 to +18 db (reference 1.73 volts, 6 mw into 500 ohm line).

In addition, zero center measurements can be made. The KT-202 utilizes a 12AU7 balanced push-pull DC amplifier and two 9006 tubes as peak-to-peak voltage rectifiers. The meter is isolated making it virtually impossible to burn it out. Multiplier resistors are 1% zero temperature coefficient types, to assure maximum accuracy and minimum variation due to heat. Front panel controls: Function Selector—selects Pwr. Off, A.C.V./P.P.V., D.C.V. Neg., D.C.V. Pos., Ohms; Range Selector—for 7 voltage and resistance ranges; Ohms Adjustment; Balance (zero) Adjustment. There are 3 probes: Common, A.C.V.—Ohms, and a shielded D.C.V. probe with 1

megohm isolating resistor. Printed circuitry makes construction of this kit easy. Selenium rectifier transformer—operated power supply for 110-120 VAC, 60 cps. Dimensions: 7 1/2x6 1/2x5 1/2"D overall. Kit comes with 1 1/2 volt battery for ohmmeter circuit and complete instructions. Shpg. wt., 7 lbs.

KT-202 Net 25.95
Accessory RF probe for KT-202 or other 11 megohm V.T.V.M. Net 3.75
KT-205 Carrying case for KT-202, complete with handle. Net 2.95
KT-203 Shpg. wt., 1 lb.

SPECIFICATIONS

DC VOLTMETER RANGES: 0-3, 15, 75, 150, 300, 750, 1500 volts. Input resistance: 11 megohms (1 megohm in probe) on all ranges.
AC VOLTMETER RMS RANGES: 0-3, 15, 75, 150, 300, 750, 1500 volts. PEAK-TO-PEAK RANGES: 0-8, 40, 200, 400, 800, 2000 volts.
DECIBEL RANGES: -10 to +18db, +10 to +38db, +30 to +58db. Response: 30 cycles to above 5 Mc.
OHMMETER RANGES: 0-1000, 10,000, 100,000 ohms; 0-1, 10, 100, 1000, megohms. CENTER SCALES: 10, 100, 1000, 10,000, 100,000 ohms. 1 megohm, 10 megohms.
TUBES: 1—12AU7 twin triode balanced meter bridge, 2—9006 peak to peak rectifiers, 1 power supply selenium rectifier.
POWER: 110-120 VAC, 60 cycles.

NEW!

LAFAYETTE—RF SIGNAL GENERATOR

- Perfect for Engineers, Servicemen, Students and Experimenters
- Quality Assembled Equipment at a KIT PRICE!

NO MONEY DOWN

27.95

- FACTORY CALIBRATED AND TESTED • SIX BANDS: 120 KC - 260 MC • DUAL OUTPUT RF TERMINALS • SEPARATE VARIABLE AUDIO OUTPUT • DIAL CALIBRATION $\pm 2\%$ • ETCHED CIRCULAR DIAL - (Vernier Tuned)

A stable, wide-range signal generator engineered to fill the need for an accurate low cost service instrument. Saves you time and money compared to spent building a kit of lesser quality. Since the delicate oscillator coils and tuning assembly are factory mounted and adjusted for optimum performance, the TE-20 is ready to go to work for you the instant you unpack it. This top-flight signal generator can be used for IF-RF alignment, audio signal tracing of TV, FM and AM sets, TV linearity checks and 400 cycle audio testing. In addition, it can serve as a marker generator when used with a suitable sweep generator. Look at some of the TE-20's features which make it the service instrument buy of the year. Incorporates a large 4 1/4" etched circular dial for easy, accurate frequency adjustments. Provides a fundamental frequency output of 120 KC to 130 MC in 6 bands plus a calibrated harmonic output of 130 mc to 260 MC. The built-in audio oscillator operates at 400 KC with adjustable output to 8 volts. Continuously variable RF attenuator for proper signal attenuation and two plug-in RF output terminals provide a choice of high and low outputs for maximum flexibility. High output and tuning dial calibration of $\pm 2\%$ give evidence of features not found elsewhere at twice its price.

TE-20 Net 27.95

SPECIFICATIONS

Full frequency range: 6 Fundamental bands—120-320 Kc 320-1000 Kc. 1-3.4 MC, 3.2-11 MC, 11-38 MC, 36-130 MC. One harmonic band 130-260 MC.
Frequency Accuracy: $\pm 2\%$. Audio Output: to 8 volts. Large 4 1/4" Etched Circular Dial (Vernier tuned) High-Low RF Output Terminals.
Tube Complement: 12BH7A, 6AR5, Selenium Rectifier. Power Requirements: 105-125VAC 50/60 Cps., 12 Watts. Attractive gray wrinkle steel case with leather carrying handle. Complete with test leads. Size: 7Hx10 1/2Wx5 3/4"D. Shpg. wt., 9 lbs.

NEW!

LAFAYETTE—SINE SQUARE WAVE AUDIO GENERATOR

- FACTORY CALIBRATED AND TESTED • LOW DISTORTION • FREQUENCY RANGE - SINE: 20 cps—200 KC IN 4 BANDS; SQUARE WAVE RANGE: 20-25 KC (Vernier Tuned) • ETCHED CIRCULAR DIAL • FREQUENCY RESPONSE - ± 1.5 DB, 60CPS - 150KC 4 1/2" VERNIER DIAL

The Lafayette TE-22 is especially designed for radio-TV servicemen, Hi-Fi fans and students who require a dependable sine and square wave generator at low prices. A completely wired and tested instrument, it is equal in quality to higher priced generators and far more convenient to use. A terrific buy, this generator will outperform most higher priced kits with ease. Among its many applications are square wave testing of audio amplifiers, determining the frequency and transient response of loudspeakers, TV audio circuit testing and many other uses. Quality features consist of a frequency response of ± 1.5 db from 20 cps to 200,000 cycles in 4 bands. A large easy-to-read etched dial (vernier tuned) adds a professional quality touch. Variable attenuator prevents overloading circuits and permits proper tracking of test response. A full wave power supply is incorporated to provide low distortion and constant output. Factory wiring and calibration insure its accuracy to be within 5%. High output voltage is 7 volts (max.) across a 1 megohm load. A rugged steel cabinet and shock proof mountings protect components, complete with instructions and test leads. A handsome instrument—one which you will be proud to own.

TE-22 Net 32.50

NO MONEY DOWN

32.50

SPECIFICATIONS

Frequency range: Sine wave: 20-200,000 cps in 4 bands. Square wave—20-25,000 cps.
Output Voltage—Sine: 7V Square: 7V P-P.
Output Impedance—0-5000 Ohms. Frequency Accuracy: $\pm 5\%$. Distortion: Less than 2%.
Tube Complement: 1-6BM8, 1-12AT7, 1-6X4
Power requirements: 117V 50/60 cps. 19W.
Gray wrinkle steel case with leather carrying handle. Complete with a pair of test leads. Size: 7Hx10 1/2Wx5 3/4"D. Shpg. wt., 10 lbs.

The Sensational LAFAYETTE TE-15 TUBE TESTER

COMPLETELY WIRED — NOT A KIT

- Accurately Checks Over 1000 Different Tubes
- Tests for Cathode Emission, Leakage and Shorts plus Filament Continuity
- Completely Portable—Weights Only 6 lbs.
- Highly Accurate Easy-to-Read Meter with Replace—Good Scale
- Fast-Setting Slide Switches
- Slide Out Tube Chart

Highly dependable, the Lafayette TE-15 is equipped to test most of the tube types employed in Radio, Hi-Fi, Monochrome, Color TV, etc. Sockets have been provided for 7-pin miniature, 9-pin miniature, octal base, loctal base, hoval and sub-miniature types. A special alligator clip lead is furnished for testing tubes with top caps. Slide switches are employed to connect the various tube elements to their respective test circuits. A 3-position tube slide switch adjust for checking shorted elements, cathode emission and filament continuity. In conjunction with the leakage-quality switch a leakage indicator light is employed which glows when on. Inter-element short or leakage is present in a tube. A power switch turns the unit on and additionally serves to adjust for various AC line voltages. Large easy-to-read meter calibrated 0-100 has a red-green "Replace—Good" scale, plus a special scale for checking diodes.

A handy slide out metal tray contains tube charts which facilitate rapid selection of test settings. Metal case is attractively finished in cream and steel gray. Completely portable—weights only 6 lbs. and measures 8 1/4" D x 9 3/4" W x 2 3/4" H. Supplied with carrying case. For 105-125 volts, 60 cycle AC. Shpg. wt., 7 lbs.

TE-15 Tube Checker Net 19.95



LOW,
LOW PRICE!

19⁹⁵

FULL
SIZE
9 3/4" W
x 8 1/8" D
x 2 3/8" H

NO MONEY
DOWN

An accurate, versatile, precision instrument that actually tests over 1000 different tubes. The low cost and superior performance of the Lafayette TE-15 Tube Tester combine to make it the outstanding test instrument value today... the ideal tube tester for any radio-TV serviceman, experimenter, technician, etc.

20,000 OHM PER VOLT SEMI-KIT MULTITESTER



A New Kind
of Kit

ONLY
11.95

The semi-kit is a new concept in test equipment kits. All the important or difficult parts are already mounted. All that remains to be done is to mount and wire in a few small parts—a job so simple you'll finish before you realize it, and best of all, you'll have one of the finest high sensitivity multitesters on the market. When used in a circuit, the high input resistance on all DC and AC ranges does away with the highly inaccurate readings common to low resistance testers which load the circuit. Ranges: DC Volts, 0-10-50-250-500-1000; AC Volts, 0-10-50-250-500-1000; DC CURRENT, 0-500 ua, 0-10-250 ma; OHMS, 0-10K-100K-1 meg; DECIBELS, —20 to +36; PLUS 0-5000 henrys and 250 mfd. to .02 mfd. Black case 5 3/4 x 3 3/4 x 1 1/2". Complete with test leads, all parts, and instructions and battery. Shpg. wt., 3 lbs.

TK-10 KIT Net 11.95

FILAMENT CONTINUITY TUBE CHECKER



1.69

Small and compact as a cigarette box. Quickly checks filament continuity in a matter of seconds. Ideal for the serviceman or the technician working in the field. Tests filaments of radio, TV picture tubes. Also can be used to test many other electrical devices and line cords, fuses, lamps and bulbs. Has sockets for TV picture tube and loctal, octal, 9-pin, as well as 7-pin sockets. Provided with two test leads. Grey hammer-tone finish. Size: 4x3x1 1/2". Shpg. wt., 12 oz.

TE-11 Net 1.69

NEW! 10,000 OHMS PER VOLT MULTITESTER



OUTPERFORMS INSTRUMENTS
MANY TIMES ITS SIZE

9⁹⁵

- EXTRA LARGE 3 1/2" METER FACE
- ALL ACCESSORIES INCLUDED

• COMPLETELY WIRED (NOT A KIT)

FULL SCALE RANGES

DC VOLTS: 0-6; 0-30; 0-120; 0-600; 0-1200; AC VOLTS: 0-6; 0-30; 0-120; 0-600; 0-1200; DC CURRENT: 0-120 uA; 0-3M; 0-300M RESISTANCE: 0-30K; 0-3 MEG DECIBELS —20 to +63 in 5 scales; Capacity 50 uF to .01 uF; and .001 uF to .15 uF; OUTPUT RANGES 0-6; 0-30; 0-120; 0-600; 0-1200.

Unbelievable Bargain. Lafayette's new multitester is a complete factory wired and tested instrument (not a kit). It can be conveniently carried in the pocket, and features unusually sensitive 10,000 ohms-per-volt AC-DC meter, 1% precision resistors, and the largest meter ever placed on an instrument of this size. Single easy-to-use range selector switch can be appreciated by the novice and the engineer alike. Case and panel are made of durable bakelite. First capacity range requires 120 volts AC, second range requires 6 volts AC. Probes and flexible leads are plastic coated and color coded. Size: 4 1/2 x 3 1/2 x 1 1/4". Complete with leads and battery. Shpg. wt., 1 1/2 lbs.

TE-10 Net 9.95
Pigskin carrying case for TE-10. Shpg. wt., 8 ozs.
TE-14 Net 1.95

NEW! 20,000 OHMS PER VOLT MULTITESTER



13.50

- 20,000 OHMS PER VOLT DC—10,000 OHMS PER VOLT AC
- 40 MICROAMPERE 3" D'ARSONVAL METER MOVEMENT

• HIGH INPUT RESISTANCE
ON ALL DC AND AC RANGES

This new multitester has extra-luxury features, found in the most costly instruments. Easy visibility is provided by the large 3" meter with two color scales for resistance on all ranges: 20,000 ohms per volt on DC; 10,000 ohms per volt on AC. This plus 1% tolerance resistors all the measuring of voltages without unduly loading the circuit, thus preserving accuracy of readings.

Besides the extreme sensitivity and superior versatility of this instrument, it features ranges not found on other, competitively priced VOM's. Measures 0-10-50-250-500-1000 DC volts, 0-10-50-250-500-1000 AC volts; 0-10K-100K-1 meg ohms, 0-500 microamperes, 0-10-250 milliamperes, —20 to +36 decibels, PLUS two special ranges 0-5000 henrys inductance and 250 mfd to .02 mfd capacity. Employs one standard 1 1/2 v penlight battery. Size 3 3/4 x 5 1/4 x 1 1/4". Shpg. wt., 3 lbs.

MODEL RW-60 Multimeter Net 13.50

TE-37 Felt-Lined carrying case for above instrument Net 2.95

NEW HIGH SENSITIVITY MULTITESTER



- 20,000 OHMS PER VOLT DC
- 10,000 OHMS PER VOLT AC
- RESISTANCE RANGE 0-60 MEGOHMS
- 40 uA MOVEMENT
- 1% RESISTORS
- 0-0.6 VOLT DC RANGE FOR AUDIO AND TRANSISTOR WORK
- COMPLETELY WIRED
- 28 RANGES

17.95

A new high-quality, low-priced multitester. Its light weight makes it a perfect portable instrument for technicians, servicemen, etc. Rugged design withstands hard use. Features large easy-to-read meter and sensitive 40 microamp meter movement. 1% tolerance resistors provide extreme accuracy of measurements. Housed in rugged bakelite case. Single knob selector and clearly marked positions permit easy operation. Recessed zero-ohms knob adjustment provided. Features sensitivity of 20,000 ohms/volt DC, and 10,000 ohms/volt AC. Ranges: DC volts: 0-0.6, 0-6, 0-30, 0-120, 0-600, 0-1200, 0-3000, 0-6000 volts. AC volts: 0-6, 0-30, 0-120, 0-600, 0-1200 volts. Resistance: RX1, RX100, RX1K, RX10K, DC current: 0-0.06, 0-6, 0-60, 0-600 ma. Decibels: —20 to +17 (0 db — 0.774 V). Capacity: .0001-.01, .005-.20 mfd. Output ranges: 0-6, 0-30, 0-120, 0-600, 0-1200 volts. Complete with color-coded heavy duty test probes and battery. Size: 6x3 3/8 x 1 3/4". Shpg. wt., 1 1/4 lbs.

TE-12 Net 17.95

TE-37 Felt-Lined carrying case for above instrument Net 2.95

NEW! POCKET AC-DC VOM

ONLY

5.95



- Extremely Compact, Measures Only 3 1/2 x 2 1/4 x 1". Weighs 5 Ozs. • 1,000 Ohms Per Volt Sensitivity
- Completely Wired (Not A Kit) • 1% Precision Resistors • Reads 0-1000 Volts AC-DC 0-100K Ohm, 0-150 MA

Lafayette's new, pocket multitester features small physical size, and a wide selection of useful ranges. It can be used for trouble-shooting any type of electronic circuits or electrical appliances such as irons, lamps, radios, television, hi-fi equipment, etc. It is also useful for testing complex electrical circuits. Extreme portability allows unlimited usage either at home or in the field.

1000 ohms per volt sensitivity, and 1% precision resistor components assure accurate, precise readings. Operation is extremely easy, simply plug the leads into the desired scale, and you are ready to go, no switching or fiddling required. Ranges Volts: 0-15-150-1000 AC and DC. Ohms: 0-100K MA; 0-150. The VOM comes completely wired and tested, and is enclosed in durable plastic case. All accessories including battery are rubber insulated, color coded, flexible test leads are supplied.

TE-13 AC POCKET VOM Shpg. wt., 1 lb. Net 5.95

NEW! CAPACITANCE SUBSTITUTION BOX



2⁹⁵

- 36" Color Coded Test Leads & Clips

• 9 Ranges From .0001 to .22 MFD

A must for the serviceman, experimenter or student. Fast accurate selection of any one of 9 capacitor values from .0001 to 22 MFD. Condensers are porcelain cased tubular type impervious to moisture and are rated at 600 volts working capacity. 9 capacitance ranges are .0001, .0022, .0047, .01, .022, .047, .1 plus 22 MFD. Complete with 36" red and black test leads and alligator clips. Size: 4 3/4 x 2 3/4 x 1 3/8". Shpg. wt., 1 1/2 lbs.

TE-16 Net 2.95

NEW! RESISTANCE SUBSTITUTION BOX



3⁹⁵

- 24 Resistance Ratings
- Two Ranges — Low 15-10K Ohms. High 15K-10 Megohms.
- 36" Red & Black Test Leads with Alligator Clips

Ideal for laboratory or service application. Substitute resistance values fast and accurately in trouble shooting circuits where values may have changed. Easy to find bias resistance in experimental vacuum tube or transistor circuits. Slide switch selects two ranges—Low: 15 ohm—10K ohm (1 watt resistors) High: 15 K ohm—10 Megohms (1/2 watt resistors). Two rotary switches (12 steps each) selects 24 separate resistances. Size: 4 3/4 x 2 3/4 x 1 3/8". Shpg. wt., 1 1/2 lbs.

TE-17 Net 3.95

SPECIAL

SENIOR V.T.V.M with 6 1/2" METER



Not a Kit...
This is a
completely wired
and calibrated
instrument

29.35

- ± 3% Accuracy of Full Scale
- Giant 6 1/2" Meter Face
- Direct Reading DB Scale

COMPARE THESE FEATURES

D.C. VOLTMETER. Ranges 0 to 3, 30, 150, 300, 1500 volts. Accuracy ± 3% of full scale. Input resistance: 11 megohms. ZERO CENTER VOLTMETER (for discriminator alignment) Ranges 0 to 1.5, 15, 75, 150, 750 volts. Accuracy ± 3% of full scale. Input resistance: 11 megohms. AC VOLTMETER. RMS Ranges: 0 to 3, 30, 150, 300, 1500 volts. Peak to Peak Ranges: 0 to 8, 80, 400, 800 volts. Accuracy ± 3% of full scale. OHMMETER: Ranges 0 to 1000 megohms (5 overlapping ranges). Center scale values: 10, 100, 1000, 100,000 ohms. 10 megohms. DECIBEL METER (for all audio measurements) Ranges: —10 to +5, +6 to +25, +26 to +45 decibels. All bases on zero Db. at 1.73 volts on 500 ohm line. Pilot light indicates when unit is "on". Complete with D.C. V.T.V.M. probe and cable plus pair of standard test leads. Housed in a rugged grey high-impact case, with color matched etched aluminum panel and portable handle. Size: 5x6 1/2 x 7 1/2".

TE-500 Shpg. wt., 6 lbs. Net 29.35



PACO

Simpson



SUPERIOR

SIMPSON MODEL 260 SERIES III AC-DC V-O-M



Now offered in a new and improved form. Sensitivity — 20,000 ohms/V.D.C., 5,000 ohms/V.A.C. Ranges: DC: 0-25V, 2.5V, 10V, 50V, 250V, 1000V, 5000V; A.F.: 0-2.5V, 10V, 50V, 250V; DB: 20 to +10 db; —8 to +22 db; +6 to 36 db; +20 to +50 db. DC current ranges from 0-50 u amps, 0-1, -10, -100, -500 ma; 0-10 amps, DC resistance from 0-2000 ohms, 0-200,000 ohms, 0-20 megohms. Accuracy: DC volts $\pm 3\%$ F.S.; AC volts $\pm 5\%$ F.S.; DC resistance $\pm 3\%$ of arc from absolute value of resistance measured. Meter housed in Bakelite case, measures $5\frac{1}{2} \times 7\frac{3}{4}$ ". Comes with battery and test leads. Shpg. wt., 6 lbs.

TE-310 Net 93.07

PACO KITS


NEW MODEL C-25 IN CIRCUIT CAPACITOR TESTER



A new time saving trouble-shooting instrument for the service bench. Quickly detects open or shorted by-pass, coupling, and blocking capacitors without removing them from the circuit. The PACO Capacity Dial makes possible a direct in-circuit test of electrolytic capacitors by reading the capacitance right from the instrument dial. Tests electrolytics from 2 to 400 mfd in two ranges. Rugged ripple-finish steel cabinet with attractive two-color panel. Dimensions $7\frac{1}{2} \times 5\frac{3}{4} \times 4\frac{1}{4}$ ". Shpg. wt., 6 lbs.

TE-453 Kit Net 19.95
Model C-25W, as above, but factory wired. Net 29.95

NEW SUPERIOR MODEL 88 TRANSISTOR RADIO TESTER and DYNAMIC TRANSISTOR TESTER



- Features Built-in Transistor Signal Injector and Signal Tracer
- Dynamic Transistor Tester

The Model 88 was designed specifically to test all transistors, transistor radios, transistor recorders, and other transistor devices under dynamic conditions. Self-contained oscillator provides stable harmonic signal injection up to 30 megacycles. Diode "clamp" prevents overloading output stage. Front panel jacks enable external meter or oscilloscope connection. Dynamically measures leakage and gain (beta) of all transistor types, including NPN, PNP, germanium, silicon, gallium arsenide and the newer diffused junction and mesa types. Complete with cables, R.F. diode probe, audio probe and battery. Housed in handsome portable case. $11\frac{1}{2} \times 6\frac{3}{4} \times 4\frac{1}{2}$ ". Shpg. wt., 5 lbs.

TE-516 Net 37.73

SUPERIOR MODEL 70 UTILITY TESTER



Test Appliances
and Utilities

Appliance and utility tester. Will test toasters, irons, broilers, clocks, fans, fluorescent lamps, auto systems. Measures AC and DC voltages, AC and DC current, resistance, leakage (ohms scale from 0-5 Megohms). Voltage scales 0-150; 0-300. Amps Scales 0-15 amps. Comes with instructions and leads. Shpg. wt., 3 lbs.

TE-513 Net 15.53
TE-517 25V Battery Pack for Model 70 Net 1.00

SUPERIOR MODEL TV-50A GENOMETER



Provides all the outputs needed for servicing AM and FM, Amplifiers, and Black and White or color TV. 7 signal generators housed in one unit, producing these necessary signals: R. F. signal generator for AM and FM—for aligning AM and FM RF circuits. Generators from 100KC to 60MC on fundamentals and from 60MC to 180MC on powerful harmonics, separate or modulated RF available; Variable Audio-Frequency Generator—with 400 cycle sine wave or 300-20,000 cycle peaked wave audio signal available for checking distortion in amplifiers, amplifier gain, etc. Bar Generator, Cross Match Generator, Dot Pattern, and Marker Generator. Size $10\frac{1}{2} \times 16\frac{1}{2} \times 7\frac{1}{2}$ ". Shpg. wt., 13 lbs.

TE-510 Net 46.55

PARALAN IN-CIRCUIT TRANSISTOR TESTER



This amazing instrument can check all types of transistors (including power types), while they are still soldered in their respective circuits! Checks for shorts, open circuits, leakage, oscillation and comparative gain. Will test diodes and rectifiers of all types, and indicate whether a transistor is a PNP or NPN type. The in-circuit transistor checker comes complete with insulated test leads marked "emitter", "base", "collector", and is powered by two standard penlight cells (included). Ready to operate—test leads are connected to their respective transistor elements, and condition of the transistor is shown by neon indicators on front panel. Unit is extremely compact—only $6\frac{1}{2} \times 3\frac{3}{4} \times 2\frac{3}{4}$ ".

TE-502 Shpg. wt., 1 1/2 lbs. Net 15.95
Replacement batteries for above (2 required) Net ea. 0.95

EICO TEST EQUIPMENT KITS AND WIRED



MODEL 1060 K EXTRA-FILTERED BATTERY ELIMINATOR & CHARGER

This versatile, rugged unit incorporates an extra low-ripple filter circuit. Ideal for latest all-transistor 6 or 12 volt equipments and any conventional ones using vacuum tubes. Selection of voltage range automatically provides appropriate current range. Fused transformer primary. Continuous voltage adjustment with Variac. 2 DC ranges and dual-range ammeter for accurate readings. Ranges: high range = 0-16V, 1.5% ripple at 2 amps, 2% at 6 amps; 6 amps continuous, 12 amps intermittent; low range = 0-8V, 0.3% ripple at 2 amps, 1.5% at 10 amps, 10 amps continuous, 20 amps intermittent. For 105-125 volts 50/60 cycle a.c. All components and instructions included. $8\frac{3}{4} \times 10\frac{1}{2} \times 7\frac{3}{4}$ ". Shpg. wt., 19 lbs.

TE-193 Kit Net 38.95
Model 1060, As above, but factory wired and tested. Net 47.95

MODEL 460K NEW WIDE BAND SCOPE

Excellent Lab precision scope featuring Push-pull direct coupled vertical amplifier with high sensitivity: 25 mv/in. Response flat from DC to 4.5 mc, useful to 10 MC, ideal for reproduction of 3.58 mc color TV sync. burst. 4 step freq.-compensated attenuator in both AC, DC positions. Also internal voltage calibration. Automatic sync. limiter and amplifier. 2X-full screen horizontal positioning. Sweep-freq: 10 to 100K cps with external capacitor for lo-freq. sweeps. Pre-set TV V & H sweep positions (30 and 7875 cps). Variably lit graphed 5" screen. Very hi-input impedance. Complete with all components and instructions for easy assembly. $13 \times 8\frac{1}{2} \times 16$ ". For 105-125 vac, 50-60 cycles. Shpg. wt., 30 lbs.

TE-222WX Kit Net 79.95
Model 460, As above, but factory wired and tested. Net 129.50

MODEL 324K RF SIGNAL GENERATOR

For IF-RF alignment, signal tracing and trouble-shooting of TV, FM, AM sets all on fundamentals; marker generator for alignment of new h-f and older i-f TV IF's. Range: 150 kc-145 mc on fundamental: 111-435 mc on calibrated harmonics — $\pm 1.5\%$ frequency accuracy. Internal 400 cps sine-wave modulation variable from 0-50%. Colpitts oscillator. Variable gain external modulation amplifier; Turret-mounted, slug-tuned coils. RF output 100,000 microvolts. AF output up to 10 volts. Output impedance is 50 ohms. For 105-125V, AC 50/60 cps. Size: $8 \times 10 \times 4\frac{1}{4}$ ". Shpg. wt., 10 lbs.

TE-242 KR Net 26.95
Model 324, As above, but factory wired and tested. Net 49.95

MODEL 666K DYNAMIC CONDUCTANCE TUBE AND TRANSISTOR TESTER

An ideal tube tester for color and monochrome TV servicing. Tests all receiving tubes, including 4, 5, 6, 7-pin, octal, loctal, miniature 7 and 9-pin, sub-miniature, 5, 6, 7-pin (in-line base) and 8-pin (circular base) receiving tubes, transmitting and special-purpose tubes, VR, cold-cathode rectifiers, magic eye and ballast tubes. Tests color and black-and-white TV picture tubes with accessory adaptor. Measures transistor collector current and shows current amplification factor. Individual test of multi-section tubes. Measures Gp, Gm and also leakage in ohms. $4\frac{1}{2}$ " 200 μ A D'Arsonval meter movement, in clear Lucite case. For 105-130 volts, AC 50/60 cps. $12 \times 15 \times 4\frac{1}{2}$ ". Shpg. wt., 18 lbs.

TE-151WX Kit Net 69.95
Model 666, As above, but factory wired and tested. Net 109.95

MODEL 950K R.C. BRIDGE & R-C-L COMPARATOR

A precision unit with advanced engineering features. 11 M Ω input impedance. 1% precision ceramic multiplier resistors used. Measures directly peak-to-peak voltage 0-4, 14, 42, 140, 420, 1400, 4200. DC/RMS sine volts: 0-1.5, 5, 15, 50, 150, 500, 1500 (up to 30,000 volts with HV probe, and 250 mc with PRF probe). Ohms: 0.2 ohms to 1000 megohms in 7 ranges. Easy calibration. $4\frac{1}{2}$ " meter, can't-burn-out circuit. Zero center. With new AC/DC Uni-Probe—half turn to select DC or AC/ohms. Exceptional stability and accuracy. All components and instructions supplied. For operation of 105-125 50/60 cps AC. Size: $8\frac{1}{2} \times 5 \times 5$ ". Shpg. wt., 7 lbs.

TE-176 Kit Net 29.95
Model 950, As above, but factory wired and tested. Net 49.95

MODEL 232K PEAK-TO-PEAK VACUUM TUBE VOLTMETER

Latest bridge-type professional instrument featuring the valuable Comparator Range for measuring unknown capacitance, resistance and inductance with a complementary component as a standard. Transformer operated assures safe operation. Direct scale on panel reads 0.5 ohms — 500 megohms resistance (4 ranges), 10 mmfd — 5000 mfd capacitance (4 ranges), and power factor. Kit includes precision calibrating resistor. Unique comparator range has ratio from 0.05 to 20 (400 to 1). Leakage testing of all capacitors at rated dc working voltage with internal (variable) 0-500 vdc source. Electron-ray tube as both bridge balance and capacitor indicator. Attractive, durable case neat easy-to-read characters. Size: $8" \times 10" \times 4\frac{1}{4}"$. Shpg. wt., 8 lbs.

TE-214 Kit Net 19.95
Model 950, As above, but factory wired and tested. Net 29.95

B&K PROFESSIONAL TEST EQUIPMENT

NEW MODEL 600 TUBE TESTER



- Tests all standard TV and Radio Tubes including the new Nuvistors

A B & K professional quality tube tester at a low cost. In addition to all standard TV and radio tube types, the model 600 tests Nuvistors, the new 10-pin tubes and 12-pin compactors. The Model 600 also tests voltage regulators, thyristors, many industrial types and European $\#$ HI-FI tubes. Checks for all shorts, grid emission, leakage and gas and tube quality under dynamic

load conditions. Tests each section of multi-section tubes separately. Provides exclusive adjustable grid emission test. Sensitivity to over 100 megohms. Phosphor-bronze socket contacts. Complete tube listing in handy reference index. Extremely compact in handsome, sturdy leatherette-covered carrying case. Size $8\frac{1}{2} \times 11\frac{1}{4} \times 7\frac{1}{2}$ ". Shpg. wt., 7 lbs.

TE-647 Net 68.55

NEW! V O M A T I C 360 AUTOMATIC VOLT-OHM-MILLIAMMETER




First real VOM advance in 20 years, the Model 360 speeds testing in a great variety of measurement applications. Features Burn-out proof meter and individual direct reading, full-size scales. Only one scale is visible at any one time, automatically. Once the range switch is set, it is impossible to read the wrong scale. Mirrored scale and knife-edge pointer further facilitate precise readings. DC volts in 6 ranges at 20,000 ohms per volt. Sensitivity and AC volts in 6 ranges at 5,000 ohms per volt sensitivity. Polarity reversing switch. Accuracy $\pm 3\%$ DC $\pm 5\%$ AC (full scale). Also measures capacitance in 3 ranges, watts in 7 ranges and DBM in 5 ranges. Complete with batteries and test leads. Size: $6\frac{1}{2} \times 8\frac{3}{4} \times 3\frac{3}{4}$ ". Shpg. wt., 5 lbs.

TE-648 Net 58.75
TE-649 LG-8 leather carrying case for above Net 11.71

RCA TEST EQUIPMENT—KITS AND WIRED

RCA WV-77E(K) VOLTOHMYST IN KIT FORM




ONLY 29.95 43.95
KIT WIRED

- FAMED WV-77E VOLTOHMYST VTVM • 28 RANGES
- $\pm 3\%$ ACCURACY ON DC • DC INPUT 11 MEG.
- RESPONSE $\pm 5\%$ 40 CPS to 5 MC. | BURNOUT-PROOF!

This new kit makes possible substantial savings in a high quality vacuum-tube voltmeter. Its 28 ranges include 7 DC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with $\pm 3\%$ of full scale accuracy and input resistance of 11 megohms; 7 rms AC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with $\pm 5\%$ of full scale accuracy; 7 peak-to-peak AC voltages: 0-4, 14, 40, 140, 400, 1400, 4000 volts, with 5% accuracy; 7 overlapping ohms ranges from 0.2 ohms to 1000 megohms with center-scale values of 10, 100, 1000, 10K, 100K, 1 meg, and 10 meg. ohms. Other important features include zero-center for discriminator alignment; frequency response of 40 cps to 5mc. flat to within $\pm 5\%$ on the 1.5 to 15 volt rms and 4 to 40 volt p-to-p ranges; 1% deposited-carbon resistors; meter electronically protected against burnout. Power requirement is 5 watts at 105-125 v., 50-60 cps AC and VS035 battery. Supplied complete with DC and AC/ohms probes and cables and ground leads, battery, and instruction book.

TE-141 Shpg. wt., 5 1/2 lbs. Net 29.95
WV-77E Same, completely wired and factory-calibrated. Net 43.95

RCA WV-38A(K) VOLT-OHM-MILLIAMMETER KIT



ONLY 29.95 43.95
KIT WIRED

- 20,000 OHMS PER VOLT
- $5\frac{1}{2}$ " METER SCALE • EXTREME ACCURACY

Here is a new VOM by RCA that you can get either as a kit or as a factory wired instrument. A must for any kind of electronic servicing. DC voltage has 8 ranges: 0-0.25, 1.0, 2.5, 10, 50, 250, 1000, 5000 volts, with $\pm 3\%$ of full scale accuracy. DC input resistance is 20,000 ohms per volt. AC voltage has 6 ranges: 2.5, 10, 50, 250, 1000, 5000 volts, with $\pm 5\%$ full scale accuracy. Input resistance is 5000 ohms-per-volt. Frequency response, measured with reference at 1000 cps is flat within $\frac{1}{2}$ db from 10 cps to 50KC for 2.5, 10, 50-volt ranges. Resistance from 0-2,000 — 200,000 — 20,000,000 ohms in three ranges. DC current has 6 ranges: 0-1-10-100-500 milliamperes, and 0-10 amps, with full scale accuracy of $\pm 3\%$. Complete with batteries, ground lead and instruction booklet. Size $5\frac{1}{2} \times 3\frac{3}{4} \times 6\frac{1}{4}$ ".

TE-139 Shpg. wt., 4 lbs. Net 29.95
WV-38A Completely wired and factory tested. Net 43.95

RCA WO-33A(K) 3" SCOPE KIT




ONLY 79.95 129.95
KIT WIRED

- PORTABLE & COMPACT • WIDE GAIN & BANDWIDTH • VERY HIGH VERTICAL SENSITIVITY

The new, extremely portable and compact WO-33A 3-inch Oscilloscope is available as a kit or as a factory-wired instrument. It will handle any black-and-white or color-TV servicing job. Lots of gain and bandwidth. Vertical amplifier has two positions. On wide band position, sensitivity is 100 rms mv/in. and bandwidth within 3 db from 5.5 cps to 5.5 Mc. On narrow band position, sensitivity is 3 rms mv/in. and bandwidth within 3 db from 20 cps to 150KC. Has external and \pm internal sync. Sync range to 4.5 Mc. Sawtooth range from 15 cps to 75 Kc. Line sweep can be adjusted 160 \circ phase. Vertical circuit input impedance at lo-cap cable input is 10 megohms and 10 microfarads approximately. Complete with direct/lo-cap probe and cable, and instruction booklet. Assembly instruction sheet provided with the kit. Power requirement is 50 watt at 105-125 volts, 50/60 cps. Size $6\frac{1}{2} \times 10\frac{1}{4} \times 8\frac{3}{4}$ ".

TE-137WX Shpg. wt., 15 lbs. Net 79.95
WO-33A Completely wired and factory tested. Net 129.95

NEW! RCA WV-98B(K) SENIOR VOLTOHMYST KIT




ONLY 62.50 79.50
KIT WIRED

The famous RCA Senior VoltOhmyst now in easy-to-build kit form. All components and leads are pre-mounted and soldered on the etched-circuit board. Input cable with DC/AC ohms switch completely assembled and wired. Employs $6\frac{1}{2}$ " wide 200 microamp meter movement and 1% precision multiplier resistors. Specifications: DC Voltmeter: Ranges — 0 to 1.5, 5, 15, 50, 150, 500, 1500 volts. Accuracy $\pm 3\%$ of full scale. Input Resistance — 11 megohms; Sensitivity — 7.3 megohms-per-volt on 1.5 volt range. AC Voltmeter: Ranges: RMS — to 1.5, 5, 15, 50, 150, 500, 1500 volts, Peak-to-Peak — 0 to 4, 14, 42, 140, 420, 1400, 4200 volts. Accuracy — $\pm 3\%$ of full scale. Ohmmeter: Range — 0 to 1000 megohms (7 overlapping ranges) Center Scale Value — 10, 100, 1000, 10,000 ohms: 0.1, 1, 10 megohms. Rugged die-cast aluminum case has leather carryhandle. Complete with probe and cable, alligator clip and ground cable plus step-by-step instruction. Shpg. wt., 7 lbs.

TE-145WX Net 62.50
WV-98B Completely wired and factory tested. Net 79.50

120 Piece Professional Quality Tool Set



32.50

Compare —
Piece for Piece! Quality for Quality! Price for Price!
YOU'LL NEVER FIND A BETTER BUY!!

NO MONEY DOWN

HERE'S WHAT YOU GET:

- 1—Heavy Duty Tool Box
- 1—Removable Tray
- 8— $\frac{1}{2}$ " Square Drive Sockets: $\frac{3}{16}$ ", $\frac{1}{4}$ ", $\frac{5}{16}$ ", $\frac{3}{8}$ ", $\frac{1}{2}$ ", $\frac{5}{8}$ ", $\frac{3}{4}$ ", $\frac{7}{8}$ ", $1\frac{1}{4}$ " Openings
- 3— $\frac{1}{2}$ " Drive Attachments: Extension, Hex Handle Ratchet
- 7— $\frac{3}{8}$ " Square Drive Sockets: $\frac{3}{16}$ ", $\frac{1}{4}$ ", $\frac{5}{16}$ ", $\frac{3}{8}$ ", $\frac{1}{2}$ ", $\frac{5}{8}$ ", $\frac{3}{4}$ " Openings
- 3— $\frac{3}{8}$ " Square Drive Attachments: Reversible Ratchet, 3" Extension, Pouch
- 8— $\frac{1}{4}$ " Square Drive Sockets: $\frac{3}{16}$ ", $\frac{1}{8}$ ", $\frac{1}{4}$ ", $\frac{5}{16}$ ", $\frac{3}{8}$ ", $\frac{1}{2}$ ", $\frac{5}{8}$ ", $\frac{3}{4}$ " Openings
- 3— $\frac{1}{4}$ " Drive Attachments: Hinge Handle, Cross Bar, Metal Box
- 6—Open End Wrenches: $\frac{1}{2}$ "x $\frac{3}{4}$ ", $\frac{3}{8}$ "x $\frac{1}{2}$ ", $\frac{1}{2}$ "x $\frac{3}{4}$ ", $\frac{3}{8}$ "x $\frac{1}{2}$ " openings, Metal Clip
- 1—Combination Plier

ALSO

- 7-Pc. Nut Driver Set; 2-Pc. Hacksaw and Blade; 12 Blades; 10-Pc. Screwdriver Set; 14-Pc. Twist Drill Set; 6-Pc. Screw Extractor Set; 12-Pc. Hex Key Set; 7-Pc. File Set; 9-Pc. Combination Wrench Set.



EMERGENCY BLINKER

1.49

- MAGNETIC BASE
- VISIBLE FOR 1000 FEET
- OPERATES ON 2 FLASHLIGHT BATTERIES

Every motorist needs it. Bulb flashes 60 times a minute. Stands by itself on road; has hanger or magnetic base which holds it firmly to any metal surface. Rugged plastic dome. 5 $\frac{3}{4}$ " diam. x 3 $\frac{3}{4}$ " high. Shpg. wt., 2 lbs. With spare, non-blinking bulb for steady light, less batteries.

Net 1.49
 ea. Net .13

AUTO SAFETY BELT



- Exceeds 5,000 Lbs. Protection
- Metal To Metal Buckle for Instant Release
- For all cars except Cadillac

This 2" wide, 100% Nylon Webbing belt provides the maximum protection needed for automobile driver and passenger. Exceeds SAE & GSA strength specifications to provide better than 5000 lbs. protection. The metal to metal buckle eliminates slippage of webbing within the buckle and gives instant positive action without danger of accidental release. Each belt has 100 inches of easy-to-adjust nylon webbing so that one size fits everyone. It is also equipped with single bolt fittings for easy installation and 3" load distributing metal washers for cars where frame mounting is not available. Shpg. wt., 2 lbs.

Net 7.95

NYLON "BULLDOG" 10 FT. TOW CABLE

- 100% DuPont Nylon
 - 10-ft. Long
 - Guaranteed 5,000 lb. Test Strength
 - Attaches Instantly to Any Bumper
- 3.75**
- The perfect cable for towing ANYTHING UP TO 5,000 LBS. Constructed of heavy-duty, 1" wide, DuPont Nylon webbing that stretches 25% to take up shocks for smooth, safe towing. Oil, grease and water resistant too! Dual, self-aligning clip attaches to any bumper. Shpg. wt., 3 lbs.

Net 3.75

NEW! POCKET TIMER

Set It and Forget It

- Set Timer Up to 60 Minutes
- Swiss Precision Watch Movement
- Hairline Accuracy
- Hundreds of Uses

2.95



The new pocket timer is an invaluable aid for most anyone, anywhere. With its 60 minute time set, it can be used as a reminder when parking meter time runs out, for appointments, take pills or medicines, etc. Also use as a timer on phone calls, cooking, photography, etc. Shpg. wt., $\frac{1}{2}$ lb.

Net 2.95

- 120 Pieces—All Top Quality
- $\frac{1}{2}$ ", $\frac{3}{8}$ " and $\frac{1}{4}$ " Square Drive Sockets All in the SAME SET
- A Complete Selection for Home, Shop, Farm and Auto

One of the best tool values ever offered. Imagine—120 top quality pieces guaranteed against defects in workmanship and materials by the world's finest hand tool manufacturers. It's the most complete selection of mechanic's tools—where else could you find $\frac{1}{2}$ ", $\frac{3}{8}$ " and $\frac{1}{4}$ " sockets in the same set. Dependable and durable, they're extra fine at home or on the job. Shpg. wt., 25 lbs.

HO-979WX Net 32.50

INSTANT FLAT TIRE REPAIR

- No Jacks, No Tools, No Removing Tires
- Seals and Inflates Tires in ONLY 2 MINUTES
- For Tube-Type and Tubeless Tires

You'll never change a punctured flat on the road again. Just attach the valve of any tube or tubeless tire and the amazing sealant instantly plugs the puncture as the tire is inflated to a satisfactory driving pressure. Will not affect wheel balance. No tools needed, no removing tires, no dirty hands—any woman can use it too. Road tested for performance. Shpg. wt., 3 lbs.

AA-84 Net 3.95

2-IN-1 BATTERY CHARGER



- Full 1 Amp Charge Rate on 6 or 12 Volt Batteries
- Automatic Taper Rate—Can't Overcharge
- Manual Reset Circuit Breaker

End dead battery trouble in your car, boat, truck or tractor. This powerhouse battery charger keeps all 6 and 12 volt batteries fully charged for peak performance even at 40° below freezing. Full 1 amp, "safe" charge rate prevents flaking and plate buckling—same method used by storage battery dealers. Easy to use—plug the line cord into any 110V outlet, connect the two terminals and forget it. Warning trouble light indicates incorrect terminal connection. Can't overcharge—automatically tapers off. Welded constructed steel. Shpg. wt., 3 $\frac{1}{2}$ lbs.

CV-56 Net 4.95

8 ft. BATTERY BOOSTER CABLES



Standard equipment for starting stalled cars, charging batteries, etc. Made with heavy duty, flexible rubber-covered cable. Rugged copper-clad positive action grips identified by Black and Red heavy vinyl covered handles. Shpg. wt., 3 lbs.

- MS-766 8 ft. long, set of 2 Net 1.78
- MS-767 12 ft. long, set of 2 Net 2.25
- MS-491 12 ft. long, 6 gauge copper cable Net 3.15
- MS-492 Battery Booster Clip only (specify Red or Black) Net .49

NEW! AUTO SHAVER

Perfect companion to the motorist. Husky efficient, 12 volt electric razor plugs into auto cigarette lighter. Hi-speed, rotary type, cutting head for a quick easy shave. Only 3" x 1 $\frac{7}{8}$ " D. Easy grip shape and size. Complete with zippered case. Shpg. wt., 12 oz.

F-610 Net 3.95

AIR PURIFIER - IONIZER



- Breathe "Ionized" Air All Year 'Round
- Removes Dust, Pollen, Soot and Smoke
- Safeguard Nursery, Bedroom, Home, Office

69.95

NO MONEY DOWN

Enjoy clean, fresh air in your home, day and night, with this scientific, electronic air purifier and ionizer. No installation, no windows necessary... just plug in the Air Purifier. Quickly, it not only removes bacteria, soot, smoke and impurities from the air, it restores the natural, negative electricity to the purified, sanitized air. You not only breathe clean, your furniture, drapes and walls stay cleaner, longer. Lightweight and compact for use in any room—can purify the volume of air in a 15x12-ft. room in six minutes. 3-speeds. Size: 7Hx21 $\frac{1}{2}$ Wx10 $\frac{1}{4}$ "D. 110-120V, 60 cycles, 60 watts. Shpg. wt., 18 lbs.

Net 69.95



29.97

- Adds Negative Ions To The Air You Breathe
- Healthful, Removes Irritating Positive Ions

UTAH ION GENERATOR-AIR FILTRATOR

Negative ions (charges) speed up the action of the cilia in the respiratory system. In the blood stream negative ions increase oxygen absorption to provide more energy. The Utah Ion Generator-Air Filtrator consists of a blower, washable polyurethane dust filter, power transformer, rectifier tube and a pair of discharge points. A D.C. voltage of 3500 is applied between the discharge plates to ionize the air. For 110/120 V. AC. U.L. Approved. Model ION-2 covers approx. 10'x12' area. AP-74 Shpg. wt., 16 lbs. Net 29.97

Model ION-3 covers approx. 15'x18' area. AP-75 Shpg. wt., 18 lbs. Net 44.70

LAFAYETTE HOME FIRE ALARM



Sensitive thermostatic detectors—located in every potential fire area—react to heat instantly. The alarm alerts you and your family before flames spread. The system does not depend on house current for operation. Long life, heavy duty battery will last at least one year. System is readily checked by means of a heat button. The push button kept within easy reach of bed, serves as an intruder alarm. Provision is made in the signal unit for attaching another alarm (6 volt bell, buzzer or horn) for outside or remote locations. The signal unit is completely enclosed in a chrome plated steel housing. Measuring only 4 $\frac{1}{2}$ x5 $\frac{1}{2}$ x3 $\frac{1}{2}$ " overall—can be located in any convenient area. Detectors, only 2" in diameter, are unobtrusive and cover areas up to 400 sq. ft. System includes signal unit with 2 horns and provision for a 3rd, 6 thermostatic detector switches (four 135°, two 200°) 150 ft. of 18 gauge twisted pair control wire, test button, 2 boxes of staples, battery and instruction book. Shpg. wt., 8 lbs.

ML-290 Net 29.95

135° Detector Switches. Shpg. wt., 3 ozs. Net ea. 1.95

EL-103 Net ea. 1.95

200° Detector Switches. Shpg. wt., 3 ozs. Net ea. 1.95

EL-104 Net ea. 1.95

Test Button. Shpg. wt., 3 ozs. Net .16

EL-30 Net .16

18 Gauge, twisted pair control wire. Shpg. wt., 3 lbs. per 100 ft. Net 1.65

WR-122 100 ft. Net 7.50

WR-123 500 ft. Net 1.79

Replacement battery, Eveready 509. Shpg. wt., 1 $\frac{1}{4}$ lbs. Net .79

BA-161 Net .79

EXTRA CHIME. For Model 61, or any other 6 v. A.C. power source. Excellent warning device. Net 4.70

PC-22 Shpg. wt., 2 lbs. Net 4.70

3-WAY POWER CONTROL

- Individually Switched Outlets With Indicator Lights

2.49

Switchable power outlet box for wall or bench mounting. Three individually controlled outlets, each with its own indicator light. Measures 4x2 $\frac{1}{2}$ x1 $\frac{1}{8}$ ". Equipped with 3 polarized receptacles, 3 toggle switches, 3 indicator lights, 6 ft. line cord. Rated 5 amps at 125 volts AC/DC. Shpg. wt., 1 lb.

Net 2.49

EL-92

ALL PURPOSE LAMP



Ideal for factory benches, tables and drafting boards. Two bolts clamp base securely to any surface up to 3" thick. Spring-controlled swivel joints and double arm action give you light in any desired position. Arm extends 36". Uses two T8, 15-W. lamps. For 110-125V., 60 cycles AC. Shpg. wt., 10 lbs. Bronze finish. FL-10—less lamps. Net 14.38

Net ea., .92

SAVE 27%! SPRAY DE-ICER

Reg. 1.22

NOW **.89** 3 for 2.40

- Defrosts Instantly
- Melts Ice Fast
- Prevents Ice Formation
- Harmless to Car Finish

Defrosts the auto windshield and windows instantly, giving you complete visibility—melts ice fast. Prevents frost and ice forming for hours. Also ideal for preventing frozen locks and doors. The big 14-oz. aerosol bomb sprays an ideal pattern at least four feet, even in zero weather—cannot harm the car finish. Shpg. wt., 1 $\frac{1}{2}$ lbs.

AA-100 Net each, .89, 3 for 2.40

DESK LAMP

- Ideal Student or Utility Lamp
- Molded-in Pen and Pencil Holder
- Brass Finished Goose Neck
- Separate Stamp and Paper Clip Compartments

only 2.98



An attractive desk lamp. Fully louvered to give the best light transmission. With molded-in pen and pencil holder. Separate stamp and paper clip compartment with a hinged lid. White louvre with gleaming black hood and base; brass finished goose neck. About 14" high. Uses standard incandescent lamp. Shpg. wt., 1 $\frac{1}{2}$ lbs.

FL-20 Less lamp Net 2.98

GOOSENECK MAGNIFYING LAMP

- Ideal for Hobbyists—Stamp Collectors, Entomologists, etc.
- Gooseneck Arm Sets Lamp in Any Position

ONLY **18.95**

The perfect lamp for the hobbyist who needs plenty of light and magnification for close, precision work. The flexible, gooseneck arm adjusts and holds the lamp in the position you want. Five inch diameter magnifying glass; overall length about 2 $\frac{1}{2}$ feet. Sturdy, clamp-mount base. Uses 22-watt circline fluorescent lamp. FL-22 less lamp. Shpg. wt., 6 lbs. Net 18.95

FL-202 T9, 22-watt cool white lamp Net 2.80

SPRAY ON LIQUID TIRE TRACTION

Go on Ice and Snow Reg. 1.69

NOW **1.19** 2 for 2.14


- Just Spray it on Tires
- Eliminates Chains and Snow Tires
- Works on Any Kind of Tire
- Cannot Harm Rubber or Car Finish

A safe, speedy, harmless way to keep your car moving on ice or snow. If you're stuck, simply spray it on your rear tires, and away you go. Will not freeze and one application will last for miles. A must for every motorist, every winter. Shpg. wt., 1 $\frac{1}{2}$ lbs.

AA-101 Net each, 1.19, 2 for 2.14

Outstanding Values in Lafayette PA Equipment

• 2 Separate EXCLUSIVE OMNI-DIRECTIONAL PATTERNS 90° APART GIVING FULL 360° PICK UP.



Polar Pattern For PA-263



NEW

ONLY 17.95

TRANSFORMER CHANNEL 1
MICROPHONE CHANNEL 1
TRANSFORMER CHANNEL 2
MICROPHONE CHANNEL 2

STEREO


DYNAMIC MICROPHONE

LAFAYETTE Brings Quality to Stereo Sound Applications AT A PRICE YOU CAN AFFORD With The New Revolutionary STEREO DYNAMIC MICROPHONE

- Outstanding Performance Characteristics Compatible For Both STEREO and MONAURAL Operation.
- IDEAL FOR TAPE RECORDING OF LARGE Orchestras, Band Concerts, Stage Plays, Small Musical Combos, and All Other Microphone Uses.
- Excellent For Use With School Dramatic Groups.
- SEPARATE SWITCH FOR EITHER MONAURAL OR STEREO OPERATION.
- Satin Chrome-Plated, All-Metal Construction.

Lafayette offers a new, outstanding flexible stereo dynamic microphone. Designed by leading audio engineers, the PA-263 offers you outstanding performance at a price you can afford. Completely eliminates need for two mikes. Constructed and designed to obtain the optimum in stereo effect and monaural pick up. Also—excellent for pick up of "reverberation" for full dimensional sound. Mounted on topple-proof, heavily weighted, all metal base. Uses gland type swivel joint. Also—adaptable to all type floor stand mounts. Frequency response 50-15,000 cps. Practically flat 80-10,000 cps. Impedance 50K ohms. Polar Pattern—2 omni-directional patterns 90° apart—comes complete with mike cable. Shpg. wt., 6 lbs. PA-263 Net 17.95

HIGH QUALITY TOP NOTCH CRYSTAL MICROPHONE



PRICED EXTRA LOW!
COMPARE FOR VALUE

3.95

Lafayette makes history with a high quality CRYSTAL MICROPHONE at a price that is less than any comparable Crystal Microphone on the market today. Excellent for PA systems, home recorders and general applications. Frequency response 30 to 10,000 cycles. Output level—52 db. provides ample output for use with low gain amplifiers. Uses quality moisture sealed crystal. Die cast case in rich green baked enamel finish, with chrome grill. Completely equipped with 5 feet of Shielded cable. Mike may be used on any stand with 5/8"-27 thread. Grill diameter 2 3/4", depth 4 1/4", height 4 1/2". Shpg. wt., 3 1/2 lbs. PA-24 Net 3.95

ARGONNE ALL-PURPOSE DYNAMIC MICROPHONE

- IDEAL FOR TAPE RECORDING, PAGING, COMMUNICATIONS
- DUAL IMPEDANCE—250 & 50,000 OHMS
- USABLE RESPONSE 50-18,000 CPS
- FOR HAND-HELD, DESK OR FLOOR STAND USE

Here is a flexible dynamic microphone with characteristics suitable for almost any application. Ruggedly constructed, with tapered cast-metal body and removable base for desk use. Mounts to the base by means of a 360° swivel adjustable ball joint and fitted with an adapter for standard 3/8"-27 floor stand. SPECIFICATIONS: FREQUENCY RESPONSE—Practically flat 80-10,000 cps; ± 5 db 70-13,000 cps. OUTPUT—70 db below 1 volt/microbar at 1,000 cps. DUAL IMPEDANCE: Low (250 ohms), High (50,000 ohms) unbalanced. Size 9" high (with base), 2" diam. at head, tapering down to 3/4". Base diam. 4 1/4", 1 3/4" high. Shpg. wt., 6 lbs. AR-3 Dynamic microphone, complete with base, floor stand adapter, and 8' cable Net 13.95



COMPLETE WITH BALL-JOINT DESK STAND
13.95

NEW! DYNAMIC PUSH-TO-TALK MICROPHONE FOR CITIZENS BAND TRANSCEIVERS

- Specifically Designed For CB Use
- Momentary-on Spring Return Switch
- Lightweight
- Deluxe Styling


8.95



Lafayette now offers a new top quality dynamic microphone at an unusually low price. Specifically designed for citizen band and communication transceivers. Attractive design in black and chrome; tapered styling to fit the hand easily. High impedance dynamic transducer will not be adversely affected by heat and smooth frequency response of 100 to 11,000 cycles make it most suitable for communications work—indoors or out. Comes equipped with a momentary push-to-talk switch, coiled rubber cable with a 5 prong plug and a convenient hang up bracket. Shpg. wt., 1 lb PA-274 Net 8.95

STUDIO CRYSTAL MICROPHONE

- DUAL CRYSTAL CARTRIDGES
- ALL DIRECTIONAL
- FINE QUALITY
- HIGH OUTPUT



4.95

Here is a microphone with a 360° pickup, and the added power and sensitivity of two individually shock mounted and phased crystal cartridges. This arrangement assures you of maximum pickup from all sides. Swivel, mounted to give fuller flexibility. Case is chrome plated. Standard 5/8"-27 thread. Overall size 7Hx3"W complete with 4 ft. cable. Shpg. wt., 4 lbs. PA-17 Net 4.95



3 WAY SLIM CRYSTAL MICROPHONE

- May be hand-held, stand mounted or suspended by lavalier cord!
- RESPONSE 60-10,000 CPS
- ON-Off Switch

3.95

A tremendous value! Unique design, only 4 1/8"x1 1/2" diam. Comes complete with swivel adapter to fit all standard mike stands, and lavalier cord and bracket which leaves both hands free. Smooth wide range response. Locking type on-off slide switch. Detachable 7 ft. cable and connector. Shpg. wt., 2 lbs. PA-31 Singly Each 3.95

PUSH-TO-TALK CARBON MICROPHONE




6.95

- Retractable Coiled Cord
- Shaped to Fit Your Hand
- Convenient Push-To-Talk Switch
- Outstanding Performance at a Low Price

A hand-held microphone ideal for mobile communications. Designed to fit your hand comfortably with easy-to-reach, easy-to-use push-to-talk switch. Furnished with hanging bracket for convenient mounting. Sturdy plastic case. Frequency response: 200-4,000 cps. Low impedance. Shpg. wt., 1 lb. PA-262 Net 6.95

GUITAR MICROPHONE



MAGNETIC TYPE ALNICO V MAGNET

7.95

FOR GUITAR WITH F HOLES Complete with Individual Volume Controls

High impedance contact type microphone specially designed for use with guitar. Easily mounted under strings without special attachments. Separate variable tone and volume controls permit wide adjustment to suit personal requirements. While in mounted position, microphone unit can be raised or lowered easily on rod to create varying tonal effects. Supplied with 8 ft. cable and attached standard size phono plug for connection to amplifier. Shpg. wt., 2 1/2 lbs. PA-38 Guitar Microphone Net 7.95

Lafayette ACCORDION MICROPHONE



- Supplied with Backstrap
- Easy-to-Install
- Tone and Volume Controls
- Ideal for Beginners and Professionals

5.95

Now accordion owners may enjoy all the advantages of electronic amplification previously limited to stringed instruments. The PA-101, coupled with an amplifier-speaker or P.A. system, provides flexibility impossible with an accordion alone. Alone, it provides a direct pickup for tape recording, eliminating the extraneous noise picked up by a conventional microphone. Included are a case-mounted control bracket containing the volume and tone controls, an output jack, a 10' foot connecting cable complete with phone plugs on both ends, and installation instructions. Shpg. wt., 2 lbs. PA-101 Net 5.95

EASY-PHONE TELEPHONE AMPLIFIER



- Lends A Valuable Helping Hand
- Amplifies Telephone To Room Volume
- 4 Transistors + Varistor
- No Dangling Wires, Pickups To Connect
- A Reminder That Caller is Waiting On The Wire
- No Warm-Up, Instant Operation

17.50


with batteries

Why keep running over to the receiver to maintain contact with the other party? Instead, place the receiver on the Easy-Phone telephone amplifier and then proceed with important business while still within earshot of the telephone party. There is no need to use up one hand to hold phone, or grab receiver between neck and shoulder. With the receiver cradled on the Easy-Phone, there is complete freedom to take notes the party dictates, using either long hand, short hand or typewriter. When engaged in long distance conversation, Easy-Phone will clearly amplify the communication so relatives or business associates can hear every word as it is said. On occasion the search for some pertinent article of information prevents "holding on to the wire". Easy-Phone permits the information to be sought while keeping an ear "on the wire". Easy-Phone can be kept at office or at home—ready at all times for instant action. A four transistor, battery powered amplifier and inductive pickup, compactly in-

stalled in a most attractive plastic case, compose the Easy-Phone. Completely self-contained with no protruding plugs and twisted hook-up cords, it will not disarrange the orderliness of work space. Operation is this simple: Placing the receiver on Easy-Phone turns amplifier on, then adjust volume to the proper level. Volume control is independent of on/off switch (which is depressed by receiver's weight). SPECIFICATIONS: 4 transistor circuit with 1 varistor; powered by 4 pen-light, 1.5 volt cells, self-contained; 3" dynamic speaker, out of view under amplifier; battery life 6 months with moderate usage. Weight 25 ozs. Heavy black bakelite case measures: 8 1/4"x3 1/4"x2 3/4". H. Easy-Phone rests on two sturdy chrome plated runners. With miniature plug and jack for recorder input. Shpg. wt., 3 lbs. F-759 With Batteries Net 17.50

EXTRA BATTERIES FOR ABOVE BA-155 Penlite cell Net .095

THE AUTOMATIC ALL-TRANSISTOR FM AUTO RADIO CONVERTER



NO MONEY DOWN
54.95

- 6 Transistors and 4 Diodes
- Automatic Gain Control
- No Drift AFC

- Provision For Multiplex
- Plugs Into Regular AM Radio


Glorious Hi-Fi FM reception is available now for most makes of cars. Enjoy static-free broadcasts on 88-108 MC FM band. Smart and compact in design, this beautiful FM converter operates through your present radio's amplifier and standard antenna. Simple plug-in connection to AM radio and it's ready to play. Features 6 transistors and 4 diodes for extreme sensitivity and 3 gang tuners for unchallenged selectivity. Total of 12 tuned

circuits for unsurpassed performance! Includes automatic gain control to eliminate overload in exceptionally strong signal areas and advanced design automatic frequency control to prevent frequency drift even under battery voltage variations. For installation in 12 volt negative ground polarity systems only. Overall size 6 1/2"x4 1/4"x4 1/4". Shpg. wt., 3 lbs. CR-126 Net 54.95

NEW! LAFAYETTE 20-WATT MUSIC AMPLIFIER



MODEL LA-75 20-WATT MUSIC AMPLIFIER



INSTRUMENT CONTROL PANEL RECESSED FOR EASY ACCESSIBILITY

Here is a music amplifier which will deliver 20 watts of clean power, to a built-in 12" heavy-duty 20 watt speaker or to an external 4, 8 or 16 ohm speaker. There are 3 inputs: two instrument inputs and one microphone input for voice. The two instrument inputs have volume and tone controls separate from the corresponding controls on the voice input. Built-in tremolo circuit superimposes an oscillator signal on the audio signal to create a periodic fluctuation or "quiver" whose frequency and amplitude may be adjusted by the "speed" and "strength" controls, respectively. There is a jack provided for turning the tremolo on and off by means of a foot switch (available as an accessory). Frequency response: ± 3 db from 33 cycles to 20Kc on voice

- 20 Watt High-Fidelity Amplifier
- 2-7189's In Push-Pull
- For Presenting Amplified Live Music and Voice to an Audience
- Adjustable Tremolo for "Quivering" Effect
- Built-in 12" Heavy-Duty Hi-Fi Speaker
- Separate Volume and Tone Controls for Instrument and Voice Inputs

input; ± 3 db from 33 cycles to 15 Kc on instrument inputs. Mike input sensitivity is 9 mv RMS; mike jack is shorting type to minimize hum pickup when mike is not plugged in. Tube complement: 2-12AX7's, 1-6AU6, 2-7189 output tubes, 1-6CA4 rectifier. Dimensions: 15 $\frac{3}{4}$ "H (including rubber feet) x 19 $\frac{1}{2}$ "W x 8 $\frac{1}{4}$ "D. With carrying handle. Shpg. wt., 30 lbs.

69.50

NO MONEY DOWN

FOOT PEDAL

Net 69.50

LA-75 WX

FOOT SWITCH to remotely control the tremolo in the

LA-75. Equipped with cable terminated in standard phone

plug to fit corresponding jack on LA-75. Shpg. wt.,

1 $\frac{1}{2}$ lbs. Net 6.95

SW-103

THE AMAZING NEW Spacephone

A Two Way 4 Transistor Citizens Band Transceiver Just 5" High

23.98 2 for **43.98**

- No Licenses, Tests or Age Limits
- Transmits & Receives Up to 1/2 Mile
- Crystal Controlled for Channel 14



Now Lafayette brings you fast, efficient, low cost two-way communications with the amazing new Spacephone. For hunting, fishing, hiking, boating or around the house; in the office, around the plant, for fireman or police work—you'll find hundreds of uses for this new Citizens Band Transceiver. And, there are no requirements as to licenses, tests or age limits—anyone can own and use the Spacephone.

Utilizing the most advanced space-age circuitry, the Spacephone employs 4 transistors and is completely self contained with its own combination speaker/microphone. Weighs a mere 8oz. and measures only 2 $\frac{1}{2}$ " x 5", small enough to fit into the palm of your hand or shirt pocket. All you do is press to transmit—release to listen and you can communicate up to 1/2 mile away. Equipped with special 40 inch telescoping whip antenna, battery and crystal controlled for channel 14.

HE-698 Shpg. wt., 1 $\frac{1}{2}$ lbs. Net 23.98 Set of 2 Net 43.98

BUILD THE SPACEPHONE KIT AND SAVE ALMOST 50% 2 for 29.95 16.95

The exact same features and specifications as described above, only you save almost 50% by purchasing the Spacephone in kit form and building it yourself. Specially designed instructions and pictorials together with easy-to-use printed circuits make building a cinch. Equipped same as wired unit, but less battery. Shpg. wt., 1 $\frac{1}{2}$ lbs. Net 16.95 Set of 2 Net 29.95

BA-2 9 Volt Battery (1 required) Net .39

LAFAYETTE MODEL PA-62 30-WATT P.A. AMPLIFIER



30-WATT P.A. AMPLIFIER

Less phono-top


NO MONEY DOWN 52.50

FEATURES: Ideal for use in churches, schools, small theaters, lecture halls and industrial plants. Priced extremely low to give extra profits to rentals and sales. Separate bass and treble tone controls, permits adjustments to meet all acoustic requirements. Two mike inputs; optional 4-speed phono top. 70 volt constant voltage output tap. Provides coverage up to 100,000 square feet when used with trumpet type speakers. Chassis is equipped with 2-speaker plug-in output sockets. Unit is housed in sturdy steel, well-ventilated cabinet. Modern streamlined styling. Finished in baked hammerloid enamel. Removable escutcheon plate for rack and panel mounting.

SPECIFICATIONS: TUBES: 3-6EU7, 2-6L6GB, 5U4GB (Rectifier). POWER OUTPUT: 30 Watts. INPUT GAIN: Microphone 125 db, Phono 80 db. FREQUENCY RESPONSE: 30 to 15,000 cps, ± 1 db. TONE CONTROLS: Bass ± 15 db at 50 cps; Treble ± 15 db at 10,000 cps. HUM LEVEL: 70 db below rated output. INPUTS: 3; 2-Microphone and 1-Phono. CONTROLS: 6; Microphone-1, Microphone-2, Power off-on, Phono-Bass, Treble, Slide Switch for operating magnetic phono thru channel 2. OUTPUT IMPEDANCES: 4, 8, 16, and 250 ohms (70 volt line). High impedance output for coupling booster amplifier. POWER CONSUMPTION: 135 Watts, 110/120 V.A.C. 50-60 cycles. Fused. SIZE: 14Wx8Dx6"H. SHIPPING WEIGHT: 20 lbs. PA-62WX Complete with Tubes Net 52.50

4-SPEED PHONO TOP For above amplifier. Fits in place of cover. Plays all speeds—16 $\frac{2}{3}$, 33 $\frac{1}{3}$, 45 and 78 rpm. Has constant 4-speed motor, with turnover cartridge, complete with two precious metal needles. Has arm-rest and plug connection; for 110 Volt 60 cycle. Shpg. wt., 10 lbs. PA-65W 4-Speed Phono Top Net 17.95

10-WATT FIXED P.A. SYSTEMS



- COMPLETE PERMANENT SYSTEM
- CHOICE OF CRYSTAL OR DYNAMIC MIKE
- AMPLIFIER HAS LAFAYETTE'S MONEY-BACK GUARANTEE

High quality, low cost system engineered for smaller permanent installations. For areas up to 5500 sq. ft. For office, store, garage, small factory paging and music systems. THE COMPLETE SYSTEMS INCLUDE: The new Lafayette Model PA-60, 10-watt amplifier complete; your choice of either the Electro-Voice 727 crystal microphone complete with detachable desk stand and 5' cable—or the new Lafayette Model PA-29 weatherproof, blast-proof s/h/m dynamic mike complete with high or low impedance selector switch and detachable swivel-type stand adaptor; 8" heavy duty PM speaker; 35" speaker cable and plug; and attractive polished walnut speaker wall baffle. For 110-120 volts, 60 cps AC operation. Shpg. wt., 25 lbs. (Any other microphone may be substituted in all systems at additional cost. See microphones in index.)

PA-140WX Complete 10-watt Permanent System as described with E-V 727 Crystal Microphone. Shpg. wt., 24 lbs. Net 45.50

PA-141WX Same as above, with Lafayette PA-29 dual impedance dynamic microphone. Shpg. wt., 24 lbs. Net 44.00

NEW! LAFAYETTE 2, 3 & 4 STATION TRANSISTOR INTERCOM 19.95



- Instantaneous 2-Way Communication — No Waiting For Warmup, No Heat, No Hum
- Portable as Well as For Desk or Wall Mounting
- You Can Start With 2 Station System and add on Additional Remote and Door Remote Later

Lafayette's new transistorized intercom can be used anywhere for 2, 3 or 4 station communications. Master has printed circuit board in well designed 3 transistor plus diode circuit for plenty of output. Master also has volume control, 3 OFF-ON slide switches for calling or listening to up to 3 remote stations, and a spring return "TALK," "HEAR," and "OFF" (battery saving position) lever switch. Master can call and talk to each, any 2, or all 3 remote stations at the same time. With system in "OFF" battery saving position, remote can initiate a call to Master by transmitting a tone signal indicating that he wishes to speak to master. Perfect for baby sitting by simply placing lever switch on Master to "Hear." Absolutely no danger of shock since unit is 6 volt battery operated.

Neatly designed in sloping ivory cases with attractive blue front panels. Complete with battery holder, 4 "Z" type cells and 50' of 2 conductor wire. Units have rubber feet and can be placed horizontally on desk or table top or hung on vertical surface (wall, side of desk, etc.) 4 $\frac{3}{4}$ x5 $\frac{3}{4}$ x2 $\frac{3}{4}$ " max. dimensions of master and remote.

2 STATION SYSTEM — MASTER PLUS 1 REMOTE PA-285 Shpg. wt., 4 lbs. Net 19.95

ADD-ON REMOTE SUB-STATIONS

PA-286 Additional Remote as above. Shpg. wt., 1 $\frac{1}{2}$ lbs. Net 4.95

PA-287 Door Remote. Shpg. wt., 1 $\frac{1}{2}$ lbs. Net 4.95

REPLACEMENT BATTERY

BA-155 1 $\frac{1}{2}$ Volt Battery (4 required) Ea. Net. .095

WR-12 Additional 2 Conductor Wire 100 ft. coll Net .89

FAMOUS BRAND 2-STATION INTERCOM 13.95




- SMART STYLING
- ALL-METAL CABINET
- 4" SPEAKERS
- CABLE SUPPLIED

New! Low cost intercom system that combines smart new styling with quality performance. A Lafayette special, this 2-station intercom is a must for your home, store, or business office. Units come complete with 50 feet of interconnecting cable and will save you thousands of steps and needed energy. An additional remote station may be added if needed at very low cost. The Master unit has its own volume control with "on-off" switch. No switch is necessary on remote. Power consumption is only 29 watts. This set uses a 12AT7 Dual-triode amplifier plus a Selenium rectifier. 4" Alnico speakers are used in both Master and Remote. 110 Volts AC or DC. Measures only 6 $\frac{1}{2}$ " x 4 $\frac{1}{2}$ " x 4 $\frac{3}{8}$ ". Shpg. wt., 6 lbs.

PA-269 2-Station Intercom complete Net 13.95

PA-270 Extra Remote Station Net 5.83



BRAND NEW! TRANSISTORIZED "BULL HORN"

ONLY **10.99**

"BULL HORN"

- Weighs only 2 $\frac{1}{2}$ lbs.
- Range up to 2,000 ft.
- Completely Transistorized
- Can be Used as Long-Range Listening Device

Considered the most modern development in bull horns because it is completely transistorized—Instantly operates on 6 standard 1 $\frac{1}{2}$ V. "C" flashlight batteries (not incl.). With its range up to 2,000 ft., it is ideal for all outdoorsmen, for work or sports. Trigger switch is simple to operate—just press to talk. May be used as a sound detector and amplifier as well as a voice amplifier. Shpg. wt., 3 lbs.

PA-271 Net 10.99

BA-274 1.5 Volt Batteries (6 req.) Net ea., .16



The most popular system for schools, RR waiting rooms, gyms, churches, noisy factories. Ideal for rentals.



30-WATT PORTABLE DUAL-SPEAKER SYSTEMS

DUAL-SPEAKER 30-WATT PORTABLE SYSTEMS AS LOW AS 110.50

- CHOICE OF DELUXE DYNAMIC MIKES
- TWO 25-WATT SPEAKERS
- MONEY-BACK GUARANTEE

This 30-watt system is one of our most popular models. Large enough for the majority of sound system applications — used in thousands of school auditoriums, churches, theatres, dance halls, dance studios and lecture halls. The ideal system for rentals; these systems have been sold to many hundreds of dealers.

AND REMEMBER OUR MONEY-BACK GUARANTEE AND OUR LOW, LOW PRICE! DUAL SPEAKER 30-WATT PORTABLE SYSTEMS INCLUDE: The outstanding feature-filled Lafayette Model PA-62 30-watt amplifier; 2—25-watt PM speakers; 2—35" speaker cables and plugs; your choice of the popular Argonne AR-3 All-Purpose Dynamic dual-impedance microphone for hand-held, desk stand or floor stand use, with removable ball-joint desk stand and floor stand adapter and 8' cable; or the deluxe dual-impedance Electro-Voice 664 Cardiod dynamic microphone for use where high-feedback problems exist, with 40-15,000 cps response, on-off switch and 18" cable; the famous Atlas MS-10C floor mike stand; and the handsomely designed split-type portable carrying case covered in high quality dark blue leatherette. Size of case 22 $\frac{1}{2}$ "Hx16 $\frac{1}{2}$ "Wx15"D — provides a secure place for the system components. For 110-130 volts, 60 cps AC operation. Shpg. wt., 75 lbs. less phono; with phono 85 lbs.

PA-232WX 30-watt Portable System, Less Phono Top and less MS-10C floor stand, complete as described with Argonne AR-3 dynamic mike Net 110.50

PA-233WX Same as above, with E-V 664 dynamic microphone and MS-10C floor mike stand Net 140.50

PA-234WX Same as PA-232WX with 4-speed phono top Net 128.50

PA-235WX Same as PA-233WX with 4-speed phono top Net 158.50



ARGONNE AR-3 DUAL IMPEDANCE DYNAMIC MIKE

ATLAS MS-10C FLOOR STAND

TV ACCESSORY SPECIALS!



BLONDER-TONGUE UHF CONVERTER

The only converter with 3 section tuner for "Class A" signal areas with these exclusive features. Tuned input tracks with oscillator, rejects spurious signals, suppresses oscillator radiation. Precise impedance match gives maximum signal conversion—no line ghosts—no picture smear. Drift-free performance is achieved by use of a thermally compensated oscillator circuit. One knob tuning; no VHF channel switching; output on channel 4, 5, or 6. Complete with tubes and instructions. Shpg. wt., 4 lbs. TL-100 Net 16.41

B-T ULTRAVERTER DELUXE UHF-TV CONVERTER

Adds all UHF channels (primary, satellite, and translator) to standard TV sets. Insures finest picture even in weak areas. Features dual-speed channel selection with direct and fine tuning controls; stable, shielded oscillator. Max. signal transfer to channels 5 or 6 of TV; Precise 300 ohm match and triode amplification; Improved tuner design meets new FCC standards; UL approved; Tuning channels 14-83 (470-890 mc); Tubes: 6AF4A and 6ERS; Power: 117 volts at 60 cps AC, 20 w. Size 6 3/4 x 5 x 4 3/4" Shpg. wt., 4 lbs. TL-101 Net 27.44

"UHF" JFD ANTENNA COUPLERS

Join any combination of VHF, or VHF-UHF antennas to use one transmission line. Stable circuits separate all channels automatically and assure almost 100% signal transfer. Highest isolation between separate inputs eliminates interaction. Weatherproof. Complete with mast clamp. Shpg. wt., 1 lb.

Stock No.	To Couple Antennas	Net
TS-159	VHF(2-6) and VHF(7-13)	2.06
TS-160	VHF(2-13), UHF(14-83)	2.20



TRI-SET COUPLER 2.29

Highly efficient 3 set coupler. For coupling 2 or 3 TV or FM sets to one antenna of any type. No interaction—less than 6 db insertion loss. 40 to 50 db rejection ratio. Shpg. wt., 1 lb. TS-332 Net 2.29



TV TUBE 'BRITENER' .69 EACH In lots of 6

Absolutely no tools or soldering needed for installing this handy inexpensive tube rejuvenator. You simply attach two plugs as directed on the instructions. For magnetic tubes and PARALLEL CIRCUITS only. Restores brightness contrast. Wt., 8 oz. Ea. MS-12 In lots of 6, each .69 singly .79



TV TUBE RESTORER 3.23

- The Most Versatile "Booster" Made
- 120 Different Combinations
- Corrects Open Cathode—Heater to Cathode Short—Open Control Grid—Control Grid to Cathode Short—Low Emission
- Any or All in Combination
- For all picture tubes except 110° types

One simple unit provides the cure for most ailing picture tubes. Latest model features slide switches—not pin plugs as older units do. Rugged, well made socket—compact, single unit design. Works on electrostatic or electromagnetic focusing tubes, in series or parallel circuits. Includes instructions. Shpg. wt., 1 lb., 4 ozs. TS-333 Net 3.23

UNIVERSAL TWIN-LEAD CONNECTORS

The plug with one thousand uses. Fits all transmission line sockets as well as 1/2" crystal holder and octal tube sockets. Solderless. Shpg. wt., 2 oz. TS-329 Net ea. .16 Net ea. in lots of 5, .14



Solderless socket for above. Shpg. wt., 2 oz. TS-330 Net ea. .16 Net ea. in lots of 5, .14

UNIVERSAL TV-FM PLUG & SOCKET

Compact-low loss—300 ohm plug and socket combination. For all TV & FM lead in applications. Surface mounting socket—low loss polystyrene plug. Constant impedance design. Solderless screw terminals. Includes hardware and instructions. Shpg. wt., 2 ozs. TS-328 Plug & Socket Net .35




FUSIBLE RESISTORS
Replacements for Motorola, Crosley, Emerson, Raytheon, Philco, Hoffman, Hallicrafters, Trutone, Sears, Montgomery Ward, Sentinel, Arvin and many others. Shpg. wt., 5 oz.
TS-253—Kit of 4, 5.6 Ohms Net .76
TS-254—Kit of 4, 7.5 Ohms
TS-255—Kit of 4, 9.0 Ohms
TS-256—Kit of 4, 22 Ohms
TS-322—Kit of 4, 4.7 Ohms
TS-323—Kit 1 each of 5 values Net .95

NEW! MODEL AB-4 MAST MOUNTED TRANSISTORIZED TV/FM BOOSTER



- For up to 4 TV or FM Sets
- Transistorized Circuit
- Uses Inexpensive Flashlight Batteries

A complete, compact amplifier—distribution system for up to 4 TV or FM sets. Reliable transistor circuit provides low noise and high gain. Stripless 300-ohm terminals on booster, and remote power supply for fast, positive installation. Requires four 1.5 volts flashlight batteries for power. Noise Figure: 4 db avg. High TV gain from 2-17 db and FM 12 db avg. depending on number of sets connected. Shpg. wt., 1 1/2 lbs. Size: AB-4 2 1/4 x 3 1/4 x 1 3/4" H. RP-3 (power supply) 3 W x 7/4 x 1 7/8" H. TL-165 Net 18.62
8A-157 1.5 volt Battery (4 required) Shpg. wt., 15 oz. Net .13



TV-FM HI-PASS FILTER

- Eliminates Interference in FM-TV antenna circuits

Hi-pass filter passes all frequencies above 40 mc. Rejects all frequencies below 40 mc. Automatically eliminates electrical disturbances in the antenna circuit. Clears disturbances caused by neon, X-Ray, ignition, appliances, diathermy, short wave, etc. Shpg. wt., 1 lb. TS-331 Net 2.39




TWO SET COUPLER .39 In lots of 3

Uses one antenna for two sets. Compact electronic set coupler assures performance of two TV sets on one installation. Easy to connect. Nothing to go wrong. Shpg. wt., 1 lb. TS-326 Each .43 In lots of 3, Each .39



UNIVERSAL 110° CRT REJUVENATOR 2.20

A new Universal picture tube brightener designed for application on 110° picture tubes. A single heavy-duty unit which performs four ways. A simple adjustment adapts it for either series or parallel wired filaments and it can be used on electromagnetic or electrostatic focus tubes. Shpg. wt., 1 lb. TS-283 For Sylvania Type 110° Tubes Net 2.20
TS-284 For RCA Type 110° Tubes Net 2.20



TRIO NO STRIP CONNECTOR SAFEST—MOST POSITIVE—LEAD IN CONNECTION

No stripping—no exposed wire—no soldering—no broken leads at the set. Your TV set unplugs with ease—in electrical storms—for moving and cleaning—to add accessories. Safe, positive installation. Stronger than the lead in wire. Fast—easy—just insert the lead in—tighten a single knob. TS-339 Shpg. wt., 2 oz. Net .59



UHF-VHF LIGHTNING ARRESTER .35

Special saw-tooth washers grip transmission line securely without stripping or cutting wire. Designed for flat, tubular, oval or open types. Constructed of low-loss material that assures less capacity and inductance, resulting in less line loading on UHF. With mounting screw and steel strap. U/L approved. Shpg. wt., 10 oz. TS-11 — Lots of 10 Each .29
Singly .35




PEAK ROOF MOUNT

A heavy gauge steel peak roof mount. Heavily plated to resist corrosion. Will accommodate mast, up to 2" in diameter. Fully adjustable can be easily rotated. Complete with all necessary hardware. Shpg. wt., 5 lbs. TS-41 Net 1.10



99¢ ECONOMY MOUNT

Can be erected in minutes; without special tools or drilling. Adjustable, two-section design permits unlimited spacing between brackets for maximum support of masts 1/2" to 1 1/2" O.D. Complete with two 12-ft. lengths of 3/4" galvanized steel bands and hardware. Shpg. wt., 3 lbs. TS-82 Net Each .99



NO RUST BARGAIN MOUNT

The ideal chimney mount for life-long satisfactory service under the most severe conditions. Hot dip galvanized steel "Y" mount. Two 10 ft. stainless steel straps and stainless steel seals. And at Lafayette's bargain prices. Shpg. wt., 4 lbs. TS-90 Net Each 1.98 Lots of 3 Each 1.80

Blonder Tongue "IT-3" TRANSISTORIZED 4-Set TV/FM Booster

NEW


- Antenna Matched Input
- Highest Gain—Lowest Noise
- Simple "Stripless" Installation



19.60

The highest gain of any home TV booster. Boosts antenna signal up to five times. More power for up to 4 TV or FM sets. The perfect basic unit for a home master TV-FM system. Designed as a rugged, long life unit. Requires almost no maintenance. Draws so little current it need never be turned off—no tubes to replace. Engineered to provide an excellent impedance match and maintain necessary isolation between sets. Can also be used to boost amplification from most mounted boosters or in master systems. Simple "stripless" installation—solid electrical contact with the turn of a screw. Size 6 1/2 x 3 3/4 x 1 1/2" For 117 volts, 60 cy. A.C., .01 amp. Shpg. wt., 1 lb. TL-99 Net 19.60

ALLIANCE ANTENNA ROTATORS



Rotator redesigned and restyled to provide faster, smoother, better efficiency. Rotation speed is 2 R.P.M. and thus has the fastest change from station to station. Magnetic brake affords instantaneous stop without drift. There is full 360° rotation. Factory lubricated for life. Contacts are self wiping thus preventing arcing, loss of contact or interference in p.l.x. A reinforced zinc die cast housing affords all weather protection. Model U-98 (1 & 2)—Fully automatic, just set control knob and antenna rotates to desired position and stops automatically. Indicator shows position of antenna. Has positive mechanical stop at the end of rotation. Size: Rotator 7 3/4 x 5 1/4 x 8". Control Case 7 x 4 1/2 x 4". 110V. 60 cps AC at 65 watts. Shpg. wt., 12 lbs. TL-71W Net 25.77
T-12 (1 & 3)—Manually operated with direction indicator. Needle indicates position of antenna on control panel. Has clockwise and counterclockwise revolution. Highly styled decorator case. Size: Rotator 7 3/4 x 5 1/4 x 8". Control Case 6 1/2 x 2 1/2 x 4 1/2". Operates on 110V 60 cps AC at 30 watts. Shpg. wt., 12 lbs. TL-72W Net 22.12
Model K-22 (1 & 4)—Economy model—Provides positive instant finger tip control of rotation. Push on on end of bar and antenna turns clockwise. Push down on other end and antenna turns counterclockwise. Center disc automatic signal light indicates when limit of travel in either direction has been reached. Size: Rotator 7 3/4 x 5 1/4 x 8". Case 5 x 5 x 4". Shpg. wt., 12 lbs. TL-73W Net 18.08
TBB THRUST BEARING BRACKET increases stress capacity of Tenna-Rotors up to 300 lbs. Withstands winds up to 90 M.P.H. Prevents buckling and bending. Shpg. wt., 3 lbs. TL-74 Net 2.91
WR-24—4 conductor flat cable for above per ft. .03 per C ft. .23



LO-PASS LINE FILTER 2.49

- Dual Ferrite Core Coils


Exceptionally efficient line noise eliminator. Utilizing dual ferrite core coils, heavily wound. Eliminates line noises caused by motors, industrial RF, neons, appliances, etc. Particularly useful on TV and FM sets, radios, tuners, record players. Automatic attenuation of unwanted disturbances. Shpg. wt., 1 1/4 lbs. TS-327 Line Filter Net 2.49



TV PICTURE TUBE SHORT ELIMINATOR .99

- Burns off Picture Tube Shorts
- Lengthens Picture Tube Life

Eliminates expensive picture tube repairs. No elaborate equipment needed. Repairs grid and cathode shorts in two minutes—without pulling the chassis! Easy to use—decontaminates cathodes—restores operation of brightness control. Can be used as often as needed. Simple "plug in, switch-on" operation. Works with any TV picture tube. Shpg. wt., 1/2 lb. TS-282 Net .99



UNIVERSAL TV TUBE "BRITENER" 1.29 SINGLY EACH In lots of 6 1.39

Restores brightness to dim TV picture tubes. Operates on all types—magnetic or electrostatic—and in all circuits—parallel or series. Shpg. wt., 10 oz. Ea. TS-170 In lots of 6 each 1.29 Singly each 1.39



ALL PURPOSE ANCHOR KITS .74

Permanent—rustproof installations. Anchors of non-corroding Territe Buterate and pulverized aluminum. Ideal for use indoors or outdoors. Hang shelves—blinds—awnings—mirrors—fixtures—fasten key board to walls—signs—pipe straps—Use in concrete—tile—plaster board—brick. Complete kit includes 36 expansion shield anchors and 36 assorted screws, #6 to #10. Shpg. wt., 6 oz. TS-341 Net .74
Heavy Duty Kit: Contains 22 expansion shield anchors and 22 assorted screws, #10 to #14. Shpg. wt., 8 oz. TS-342 Net .74



TELESCOPING TV MASTS

Heavy-duty telescoping masts. Hot-dip zinc galvanizing inside and outside. Designed for easy installation and assembly. Husky thumb bolts lock sections automatically. Precision fitting. 18 gauge .003" wall. Supplied complete with all guy rings, clamps and necessary hardware. Total 5 10-ft. sections for height up to 50 ft.; O.D.: #1 (1 1/4"), #2 (1 1/2"), 50-FT. MAST—Consists of all 5 sections #3 (1 3/4"), #4 (2"), #5 (2 1/4"). Shipping express only. Listed above: Nos. 1, 2, 3, 4 and 5. Height 50 feet. Shpg. wt., 39 lbs. TL-63WX Net 13.73
40-FT. MAST. Consists of 4 sections; Nos. 1, 2, 3 and 4. Height 40 feet. Shpg. wt., 28 lbs. TL-62WX Net 10.05
30-FT. MAST. Consists of 3 sections. Nos. 1, 2 and 3. Height 30 feet. Shpg. wt., 21 lbs. TL-61WX Net 7.28
20-FT. MAST. Consists of 2 sections. Nos. 1 and 2. Height 20 feet. Shpg. wt., 14 lbs. TL-60WX Net 4.58



TV ANTENNA MASTS

STEEL MASTS. New corrosion-resistant 5 ft. steel mast made to fit all antennas. One end is tapered. "Jam Fit" construction with locking key. 1 1/2" O.D.
TL-12W 5 ft. Wt., 2 1/2 lbs. .69
TL-13WX 10 ft. Wt., 4 1/2 lbs. 1.29
TL-14WX 10 ft., 16 gauge. Wt., 8 lbs. 1.89
ALUMINUM MASTS. 19 gauge-heavy wall-high tensile strength. Rust and corrosion proof. Swaged for stacking.
TL-66W 5 ft. Wt., 1 1/2 lbs. .89
TL-17WX 10 ft. Wt., 2 1/2 lbs. 1.69
10 Ft. Mast shipped via express only.



WUERTH TUBE SAVER LENGTHENS TUBE LIFE—INCLUDING PICTURE TUBE! PROTECTS T.V.—HI-FI—P.A. Any Electronic Equipment Up to 450 Watts!

New device prolongs life of all electronic tubes including cathode-ray tubes! Protects components and tubes from destructive initial surge currents by "Thermal Cushion Action." Completely automatic. No complicated installation needed, just plug the "Tube Saver" into the wall, and appliances into it. Protects T.V.—Hi Fi Home equipment, etc. RATED: 300 watts, 110-120V AC/DC. Measures only 2 1/2 x 1 3/4". Shpg. wt., 8 oz. TS-315 (Type 150) Net 2.91
Same as above except for electronic equipment drawing up to 450 watts. Suitable for color television. Shpg. wt., 8 oz. TS-316 Net 3.50



NEW "BI-MOUNT" ANTENNA MOUNTING KIT

Does not use guy wires— is strong, easy to install. "BI-MOUNT" kit used to mount and support any 5 ft. 1 1/4" mast. Includes collar, support legs, base mount and screws. Shpg. wt., 1 1/2 lbs. TL-136 Net 1.82
SUPER "BI-MOUNT" kit used to mount and support any 10 ft. 1 1/4" mast. Includes 1" dia. support legs, collar, adjustable mast mount and all screws. Shpg. wt., 2 1/2 lbs. TL-137 Net 3.44




HEAVY DUTY 300-OHM LINE

Extra high quality. Heavier gauge wire and thicker insulation. Shpg. wt., 2 1/2 lbs. per 100 ft. WR-26 per ft. Net .025
WR-152 per 100 Net 1.58




BROWN 300 OHM TWIN LEAD 1.39 per 100 ft



COPPER CONDUCTORS LOW-LOSS POLYETHYLENE

High quality, low-loss lead-in for all TV and FM installations. Polyethylene dielectric—standard copper leads. Shpg. wt., 2 lbs. per 100 ft.
WR-25 100 ft. Net 1.29
WR-146 500 ft. Net 4.80
WR-147 1,000 ft. Net 8.95




U.H.F. TUBULAR AIR-SPACED TWIN LEAD

• UHF-VHF • Extreme Low Loss
300 ohm airspaced tubular lead with copperweld conductors. Shpg. wt., 3 lbs. per 100 ft. WR-46 per 100 ft. Net 2.50

TRY TO BEAT THESE ANTENNA PRICES!

LAFAYETTE ANTENNAS and "U-INSTALL-IT" KITS!

FULL 20 ELEMENT STACKED



- SNAP OPEN CONICAL
- ALL ALUMINUM
- NO LOOSE PARTS
- FASTEST INSTALLATIONS

5.25
singly each

4.95
each, in lots of 3

Best antenna deal yet for servicemen-dealer-and installation specialists. All the most wanted features. Quickest-easiest installation possible. No loose hardware. All elements snap open and lock in without tools. Most efficient conical design for all reception areas. Two complete bays with Q bars, less mast.

- AN-28WX—Singly, ea. Shpg. wt., 8 lbs. Net 5.25
- Lots of 3, ea. Net 4.95
- "U-INSTALL-IT" KIT With All Angle Roof Mounts. Includes AN-28 antenna and installation kit AM-11 with two 5 ft. masts. As shown below. Net 7.95
- AN-32WX—Shpg. wt., 18 lbs. Net 7.95
- "U-INSTALL-IT" KIT With Chimney Mount. Same antenna and accessories but includes chimney mount instead of roof mount. Net 8.75
- AN-43WX—Shpg. wt., 18 lbs. Net 8.75
- POW'R PAK KIT AK-58. Includes AN-28, 20 element stacked conical, TL-75 POW'R PAK booster, and installation kit, AM-11W as shown below. Net 16.50
- AK-58WX—Shpg. wt., 19 lbs. Net 16.50
- POW'R PAK KIT AK-5. Same as above except with accessory Kit AM-13W, as shown below. Net 16.80
- AK-59WX—Shpg. wt., 19 lbs. Net 16.80

FAMOUS BRAND COLOR 'TENNA

GOLD ANODIZED



- HIGH GAIN ON ALL VHF CHANNELS
- COMPLETELY FACTORY PREASSEMBLED
- ELECTRONIC LENS DESIGN
- HIGHLY DIRECTIONAL—YAGI PERFORMANCE

13.95

Lafayette is the FIRST to offer this nationally tried and proven antenna at more than 25% off the regular dealer price. This is the same fine antenna—with all its exclusive features—that sells for dollars more than our record-breaking price. Check these features: Electronic Focussing—High Gain—all VHF channel coverage—gold anodized quality construction—easiest installation—outstanding fringe area reception—compact design dynamically balanced. All-aluminum construction—automatic hardware.

- AN-51WX—Shpg. wt., 8 lbs. Net 13.95
- Net ea. in lots of 3, 13.25
- POW'R KIT AK-54. Includes AN-51WX Color 'Tenna, TL-75 POW'R PAK booster and AM-12 mounting kit (as shown on facing page). Shpg. wt., 16 lbs. Net 24.98
- AK-54WX Net 24.98

MAXIMUM PERFORMANCE FRINGE ANTENNA

- 21 Active Elements
- Snap Open Design
- Fiberglass Insulators
- Compound Yagi Array

Range to 100 Miles

11.88

NEW!

GOLD ANODIZED

Field proven design for fringe reception. Gold anodized to combat corrosion. Compound yagi array to "sock-in" signals where other designs fail. "Tension-loc" hardware. Heavy wall tubing throughout. Less mast.

- AN-67WX Gold Anodized. Shpg. wt., 8½ lbs. Net 11.88
- POW'R KIT AK-55. Includes AN-67WX, TL-75. POW'R PAK booster, 20 ft. Telescoping mast and accessories shown in Kit "A" on the facing page. Net 29.99
- AK-55WX Shpg. wt., 40 lbs. Net 29.99
- AK-38WX. Includes AN-67WX antenna, 20 ft. Telescoping mast and accessories. Shown in Kit "A" on facing page. Net 22.50
- AK-38WX Shpg. wt., 39 lbs. Net 22.50
- AK-39WX. Includes AN-67WX antenna, Alliance K-22 rotator, 20 ft. Telescoping mast and accessories. Shown in Kit "B" on facing page. Net 45.79
- AK-39WX Shpg. wt., 50 lbs. Net 45.79

LAFAYETTE TV/FM 4-SET POWER BOOSTER



- Boosts Signal For Up To 4 TV Sets
- Ideal for Master "Home" Installation
- Equally Useful In Primary and Fringe Areas

- The MOST Gain for the LEAST money
- Electro-Matched to Lafayette TV-FM Antennas
- Updates and improves any TV/FM antenna installation

Provide a stronger TV or FM signal to up to 4 sets anywhere in the home. Low noise-high output amplifier boosts and distributes the signal over ordinary twin lead. Special isolation circuitry prevents interaction and interference between sets. Provides as much as 7 to 10 db gain on all channels 2 through 13 when used with one TV set. From 2.5 to 5 db when used with 2 sets. Will often supply more gain when used with an indoor antenna than elaborate, unboosted outdoor antenna supply. Requires no tuning. Installs with just a screwdriver. Uses ordinary twin lead to "antenna-matched" terminals. Mounts behind set—or in any convenient location. Measures 5¼x3¾x1¼". For 117 V. A.C. 60 cycles.

- TL-75 Shpg. wt., 2 lbs. Net 9.95

"U-INSTALL-IT" KITS




- All the items for simple installation. You get an all angle roof mount—lightning arrestor—75 feet of 300 ohm twin lead—screw eyes—mast standoffs and 5 ft., 1¼ O.D. steel mast.
- AM-10W Shpg. wt., 7 lbs. ea. 2.95
 - AM-11W with 2-5 ft. masts. Shpg. wt., 10 lbs. ea. 3.55
 - AM-12W Same as AM-10W and chimney mount. ea. 3.25
 - AM-13W Same as AM-11W with chimney mount. ea. 3.75
 - AM-14W Same as AM-10W with aluminum wall bracket. ea. 2.95
 - AM-15W Same as AM-11 with aluminum wall bracket. ea. 3.55

FAMOUS BRAND SUPER COLOR 'TENNA

18 ELEMENTS—UP TO 125 MILES

- ELECTRONIC LENS DESIGN
- HIGHLY DIRECTIONAL—YAGI ENGINEERED
- COMPLETELY PREASSEMBLED
- MORE GAIN ON ALL VHF CHANNELS



16.98

All the exclusive features that have made this antenna a national favorite for "problem area" reception. Electronic focussing—18 elements for more gain—quality construction—1" square crossarm—1" round driven elements—1" tubing boom brace—easy installation—automatic hardware—all aluminum construction. Dynamically balanced design—outstanding fringe area performance.

- AN-63WX Shpg. wt., 10 lbs. Net 16.98
- POW'R KIT AK-57. Includes AN-63WX Super Color 'Tenna; TL-75. POW'R PAK Booster; 20 ft. Telescoping mast and accessories shown in Kit "A" on the facing page. Net 34.99
- AK-57WX Shpg. wt., 35 lbs. Net 34.99

ALL CHANNEL'S "RIVIERA"

WORLD'S MOST POWERFUL ULTRA-FRINGE VHF—UHF—FM ANTENNA
GUARANTEED 200 MILE VHF RECEPTION OR YOUR MONEY BACK

- Receives channel 2-83 from all directions without a rotor
- Broadband UHF-VHF and FM, motorless all direction reception
- All aluminum flip-out assembly



1985

Field tests reception on VHF of up to 200 miles has made possible this unprecedented guarantee. Here is an antenna with one transmission line for all UHF, VHF and FM stations in all directions without the use of a rotor. The nine position selector switch connected at the set electronically rotates antenna beam instantly without physically moving the antenna. Gain on channels 2-6 comparable to 4-bay conicals; on channels 7-13 comparable to stacked 10-element single channel yagis; on 14-83 comparable to bow-tie reflector. 16½" doweled aluminum elements are 60 inches long. Complete with switch, coupler, 45" stacking bars and 2 7½" angle type mast insulators for Polymicalene line listed below.

- AN-135WX Less Mast Shpg. wt., 10 lbs. Net 19.85

The Riviera is ideal for FM Stereo/Multiplex reception. Elements are a full wave length at FM frequencies.

"U-Install-It" Kit: Includes Riviera antenna, chimney mount, two five ft. masts, 100 ft. of Polymicalene 4 conductor lead-in wire, 8 stand off insulators and complete instructions. Net 29.95

AN-42WX Shpg. wt., 16 lbs. Net 29.95

THE RIVIERA MUST BE USED WITH THE LOW LOSS LEAD IN WIRE LISTED BELOW

- Special 4 conductors, matched impedance transmission line. Low loss, mica-filled Polymicalene copperweld conductors. Net 5.00
- WR-8W 50 ft. length Net 7.50
- WR-9W 75 ft. length Net 8.90
- WR-18W 100 ft. length Net 8.90

REMBRANDT

TV DIRECTION FINDER

- Receives Signals From All Directions—Without a Rotator!
- Supercharges Any TV Antenna—Boosts The Pick-Up Power!
- Filters Out Interference—Tunes Out Ghosts!
- Rejuvenates "Old" TV Antennas
- Amplifies The TV Signal
- No Installation Problem

5.95



The latest television invention! Seeks out—and beams in—TV signals from any channel, in any direction, without a mechanical rotator. Electrically rotates the polar-receiving pattern of your existing antenna and phases the ground wave picked up by the electrical wiring system with the sky wave picked up by the antenna. Improves any existing antenna: indoor, outdoor, master or built-in. Boosts pick-up power of any antenna—old or new. Just a flick of the selector control tunes out ghosts—filters out interference—tunes in those "hard-to-get" problem channels. Automatically amplifies TV signal strength for "snow" free, brighter, clearer pictures. Works on every channel—in any location—with any antenna—for any TV set. No installation problem—simply attach to antenna terminals in back of TV set—and plug into 110V AC/DC socket. Complete satisfaction guaranteed or your money back.

- AN-140 Shpg. wt., 2 lbs. Net, ea. 5.95
- In lots of 6 ea. Net 5.00

"MULTIPLEX 10" EXTENDED RANGE FM ANTENNA



GOLD ANODIZED

9.88


Ideally suited to Multiplex FM reception. Stereo (Multiplex) FM signals, for the average tuner, have a range of approximately half that of ordinary (monaural) FM signals. This 10 element, double driven, yagi array has the necessary added gain, sensitivity and directivity to compensate for the lack of signal strength. Assures full-fidelity reception and highest signal/noise ratio. All aluminum, gold anodized construction. Fibreglas insulators. Torsion lock hardware, sure-lock mast clamp. Broad banded to cover the entire 88 to 108 mc band. Shpg. wt., 7 lbs.

- AN-250WX Net 9.88

NEW "HI-5 FM YAGI"

- DESIGNED EXPRESSLY FOR FM

5.95




High gain antenna designed for the audiophile who seeks perfection in FM reception. Extra elements on this antenna serve to pull in stations where others fail. Trouble free operation even under severe weather conditions. The fully automatic snap-lock brackets insure easy, rapid and secure installation.

- AN-49WX Shpg. wt., 3 lbs. Net ea. 5.95

LIGHT AND TELEVISION CLOCK

8.14

Placed on top of TV cabinet the #700 Lite Clock provides proper amount of background light for televiewing. Accurate, rotating numeral type clock. Walnut finish plastic case. For 110V 60 cycle AC only. Size, 5x5¼x3¼". Shpg. wt., 2½ lbs.



- MT-11 Incl. excise tax 8.14

SPECIAL UHF ANTENNA

4.79

- Highest Gain on 70 UHF Channels
- Completely Preassembled
- Excellent Directivity
- Flat Response Across Each Channel

Four bay, UHF bowtie antenna. Exceptionally high (12db) gain—relatively flat across the entire spectrum. Fully factory assembled. Quickest and easiest to install. High efficiency screen grid reflector boosts front to back ratio. Unique "cross-over" phasing bars—open V elements. Rugged—rigid—corrosion resistant construction. Shpg. wt., 5 lbs.

- AN-200WX Net 4.79


UHF "TRANSLATOR" 4-BAY ANTENNA

Four bay bow-tie and screen reflector—tuned to the UHF translator frequencies. Average 16db gain on channels 70-83. Completely preassembled.

- AN-201WX Shpg. wt., 5 lbs. Net 4.79

8 ELEMENT CONICAL

2.29



All aluminum 8 element conical. Full sized. Rugged insulator block. Designed for rapid assembly. Fan front of 6 full length elements. Real value. Shpg. wt., 4 lbs.

- AN-11W Net 2.60

"U Install It" Kit includes AN-11 and roof-mount kit AM-10 as shown below. Shpg. wt., 11 lbs. Net 4.95

AN-33W Net 4.95

"U Install It" Kit. With chimney mount kit. AM-12 as below. Shpg. wt., 11 lbs. Net 5.50

AN-44W Net 5.50

VEE BEAM

Popular primary area antenna. Rugged aluminum construction. Light weight easy to install. Sharply directional. Shpg. wt., 4 lbs.

- AN-21W Net 2.29

AN-20W 2 bays stacked Net 4.59

"U Install It" Kit. Includes AN-21W and roof mount kit AM-10, as below. Shpg. wt., 11 lbs. Net 4.70

AN-45W Net 4.70

"U Install It" Kit. With chimney mount kit, AM-12 as below. Shpg. wt., 11 lbs. Net 5.29

AN-46W Net 5.29

NEW! FM ANTENNA KIT

- ALL DIRECTIONAL
- Ready To Install
- Fully Assembled

2.85



Provides excellent gain for areas up to 35 miles from the station. Use on existing masts—new installation—or as an attic installation. Gold anodized aluminum for years of trouble free operation. Exceptionally light—sturdy design. Capable of receiving FM signals from practically all directions with equal efficiency. Complete with 50 ft. of 300 ohm twin lead, mast standoff, screw eye standoffs, mast mount.

- AK-53 Shpg. wt., 5 lbs. Net 3.98

FM ANTENNA ONLY. Shpg. wt., 3 lbs. Net 2.85

AN-66 Net 2.85

NEW! REMBRANDT

RADAR COIL - X9

- Guaranteed 35 Mile VHF Reception or Your Money Back

6.95



A powerful indoor antenna utilizing 46" long arms to provide efficient reception to 35 miles, 12-position switch helps eliminate ghosts and snow. A real beauty to grace any decor—Brass plated coil and 4 section telescoping arms. Includes 6-foot transmission line. Available in Mahogany, Walnut and Ivory. Shpg. wt., 3 lbs.

- AN-141 Net 6.95

WIZARD 300 MASTER COUPLER

IDEAL FOR UNLIMITED SET COUPLING



Provides for the coupling of any number of TV (color or black and white) and FM sets to one antenna line. The first set is connected directly to the line, and each additional set is connected through a separate WIZARD 300, without the need for an amplifier or booster. Shpg. wt., 3 oz.

- TS-347 Net 1.15
- In lots of 3 Net ea. 1.03

AMPHENOL

2.59

Was ~~14.95~~

Designed for True video fidelity — featuring "slide rule" tuning with inductive reactance network for fine picture adjustment and transformer coupling for strict impedance matching. Elements fold from sight when not in use. Shpg. wt., 2 lbs.

- AN-65 Indoor TV Antenna Net 2.59

Christmas Special VALUE POWER TOOLS

8" TILT ARBOR "MOTERTOOL" SAW with G.E. 3/4 H.P. MOTOR

- You Also Get All This:
- Rugged All-Steel Stand
 - 2 Cast-Iron Table Extensions
 - 8" Combination Blade
 - Front & Rear Locking Rip Fence
 - Precision Mitre Gauge
 - Rubber Drive Belt
 - Safety Clutch
 - 8-Ft. Cord and Plug

99.95
NO MONEY DOWN



A complete, compact machine with enclosed motor—you just plug it in, flip the switch and it's ready to operate. With this all-in-one package you can add a room, build a garage, make cabinets, build furniture and much more. Does every sawing operation—cross cutting, ripping, beveling, mitering, dadoing, tenoning, sanding, molding, shaping. Table extends to 28 1/2 x 17 1/4" with extensions. Blade guard and motor tilt to 45°. Precision ball bearing arbor unit. Shpg. wt., 90 lbs. Net 99.95 HD-975WX

8" MOTERTOOL TILT ARBOR SAW. Same as above, without extensions, blade and stand. Table top 14 1/2 x 17 1/4". Shpg. wt., 58 lbs. HD-891WX Net 78.50

EXTENSIONS, Set of 2 for HD-891WX. Cast iron. Extends work surface to 28 1/2 x 17 1/4". Shpg. wt., 28 lbs. HD-892W Net 16.50

POWER TOOL STAND. Fits HD-891WX. Heavy steel; slotted for adjustments. Length 21"; width 17 1/4"; height adjusts 24-33 1/4". Shpg. wt., 33 lbs. HD-953WX Net 17.13

4 1/2" "MOTERTOOL" JOINTER

- Complete with Motor, Cord, Plug, Switch, 2-Way Tiltting Fence
- Ball-Bearing Construction




With 3/4 H.P. General Electric Motor built right in. This machine is permanently set up to operate. Has exclusive "Parallel Motion" design which assures 3/32" between the cutting knife and table edge at any depth of cut. All Ball Bearing construction. Outfeed as well as infeed table adjustable. Maximum cuts: width 4 1/2", depth 3/8", Rabbet depth 3/8". Over-all length 30 3/4". Cast iron tables and base. Comes complete with built-in 3/4 H.P. Motor, Cord, Plug and Switch, and 2-way Tiltting Fence. HD-890WX Shpg. wt., 53 lbs. Net 71.50

POWER TOOL STAND

Overall length 21". Height adjustable, 24-33 1/4". 17 1/4" wide. Heavy steel construction, slotted for adjustments. Shpg. wt., 33 lbs. HD-953WX Net 17.13

UNIMAT MINIATURE MACHINE SHOP



- Tolerances To .0005"
- Only 16" Long, 5" High
- 11 Spindle Speeds

This small scale combination drill press-lathe-grinder finds extensive application in electronic labs, hospitals, government research agencies, as well as in home workshops. Motor directly attached to headstock, may serve as a hand tool. Belt drive adjustable for speeds 225 to 4,000 r.p.m. Headstock rotates 360° for off center operation. Straight and taper turning. Adaptable for threading, milling, sawing. Cast iron lathe bed swing is 2.82"; center to center distance 6.69". "Special" unit includes 1/15 H.P. induction, fan-cooled motor, drill press vert. column and hand lever, face plate, lathe dog, grindstone arbor, tool post, 2 dead centers. Allen wrench, 17 1/2 x 10 1/2 x 5 3/4" wood chest. 32 page manual. Shpg. wt., 28 1/2 lbs. AC/DC 115 V operation. HD-956WX Net 99.50

"Basic" Unit. Same as above but with 3 jaw universal lathe chuck with reversing jaws, 1/4" Jacobs chuck and key. HD-957WX Shpg. wt., 30 lbs. Net 129.50

Universal lathe chuck for "Special" unit. HD-958 Shpg. wt., 2 lbs. Net 23.50

Jacobs drill chuck (1/4") for "Special" unit. HD-959 Shpg. wt., 1 lb. Net 9.75

TOOLKRAFT 10" RADIAL-ARM SAW

- Off-Set Motor Shaft Design Enables 3 3/4" Deep Cut With 10" Blade
- Rear Motor Shaft Takes Accessories
- Rotates 360° Horizontally



Among circular saws the radial-arm type offers the most in safety, performance and operating ease. This 10" radial-arm saw permits work to be held firmly where it can't fly-off and allows the least bodily exposure to the blade. GE 1 H.P. motor has "safety slip" clutch to prevent burn-out. Triple point ball bearing motor carriage suspension. Column of 3" diam. heavy-walled steel with 9" travel; rides in 12" cast iron pedestal. All 10 controls are in front for convenience. Recessed safety switch. Exclusive depth scale. Table of laminated maple. Cross-cuts 17 1/2", rips 31 3/4" of saw arbor. 4200 r.p.m. cutting speed. Motor requires 115/230 V. 60 cycles @ 12.4 amps (continuous duty). Ball bearings used throughout. HD-954WX Shpg. wt., 235 lbs. Net 221.30

Floor Stand for Radial-Arm Saw. HD-955WX Shpg. wt., 25 lbs. Net 14.90

FLEXI-SHAFT HOBBY TOOL

- A real hobby work horse
- Powerful—Versatile
- Hi-Speed—Hi Torque

Flexible shaft and motor combination to do all your hobby grinding—polishing—drilling—sawing—engraving—etching—routing—carving. Husky, 1 amp motor delivers plenty of power for hard, continuous use. Will not stall under normal usage. Lightweight finger tip control—for intricate hobby work. 36", easily handled, shaft is a sealed tamper proof unit. Will not heat up under prolonged use. Chuck accommodates standard 3/32 and 1/8 inch tool shanks. For use on wood—metals—glass and plastics. 110/120V. AC or DC. Shpg. wt., 3 lbs. HD-849 Net 6.60



6 PC. MOUNTED STONE SET

- Ideal Accessory For The Flexi-Shaft Tool



Six assorted grinding stones and wheels. Selected set of mounted grinding points, stones, wheels. For carving—routing—grinding—sharpening—de-burring—sawing—buffing—polishing. Mounted on 1/8" and 3/16" shafts. Shpg. wt., 8 oz. HD-920 Net 1.20

SPRAYIT 600 PROFESSIONAL-STYLE SPRAY UNIT

- Integral Compressor-Motor
- All-Aluminum Spray Gun
- Sprays Oil, Paints, Stains

26.21
NO MONEY DOWN



All-purpose spray unit that gives professional results from the start. Adjusts pattern from small-as-a-dime to a fan 10" wide—4 times faster than a brush, and cleans easier too. Easy-to-use 2-finger trigger gun. Never needs lubrication. Air delivery: 1.5-2.0 CFM @ 15-20 lbs. Complete with 6-ft. cord with plug, 8-ft. hose with connections. HD-933 Shpg. wt., 11 lbs. Net 26.21

Stanley 1/4" Power Drill



13.97

- APPROVED AND POWERED FOR FULL TIME USE
- 3 AMP—2500 RPM—AC MOTOR
- PRECISION GEARED CHUCK

The perfect drill for use with drill attachments. Designed for continuous duty—ease of maintenance. Advanced styling for comfort and balance. Dependable bronze bearings—extra long brush life. 2500 RPM no-load speed. 1600 RPM under full load. Capacity 1/4" in steel, 1/2" in hardwood. Trigger switch with locking pin for intermittent or continuous run. Accurately machined precision gears. High speed airflow ventilation. 8 3/4" overall length. Weighs only 3 1/4 lbs. 3 Amps, 115v. AC only. Shpg. wt., 4 1/2 lbs. HD-702 Net 13.97

STANLEY Heavy Duty SABRE SAW



27.97

- CUTS 2" LUMBER—1/2" STEEL BARS
- CUTS FLUSH TO A WALL
- FULL 3/8" STROKE—3300 STROKES PER MINUTE
- ANTI VIBRATION MECHANISM

New Stanley Heavy Duty Sabre Saw—rugged enough to cut 1/2" steel bars. Will do the work of rip, crosscut, band, jig, keyhole and hack saws. Particularly suited for use where it's difficult to use a circular or band saw. Cuts curves, scrolls, pockets, intricate patterns in wood, plastics, veneers. Cuts full 2" lumber—conduit—cable—1/2" steel bar—aluminum—brass. 2 position base plus flush cutting blade allows cuts right up to a wall. Improved chip blower—single screw blade lock—positive slide switch—cool, comfortable handle. 2.5 amp. 115v. AC/DC motor. Includes one each wood—metal—and flush cutting blade. Shpg. wt., 6 1/2 lbs. HD-701 Net 27.97

STANLEY Heavy Duty ROUTER



45.47


- HIGH SPEED PRODUCTION ROUTER
- 3/4 HORSEPOWER
- 23,000 RPM MOTOR
- BUILT-IN SPOTLIGHT
- MICROMETER DEPTH ADJUST—TO 4/1000"
- AUTOMATIC SHAFT LOCK—NEEDS ONLY 1 WRENCH

The most advanced router design in the world. Most perfect balance and control available. Highest safety and performance level. Cuts dovetails—dadoes—tenons mortises—rabbets—beading—molding—joints—grooves—decorative cuts—inlays—cuts soft metals. Built in spot-light increases brightness as work load increases. Recessed switch automatically locks shaft when changing bits. Precision micro-depth adjustment as fine as .004 inch. Cantilevered base and advanced design grips for stability and balance. Clamping lever holds or releases motor with a flip. 6 amp., 23,000 RPM, 115v. AC/DC. Shpg. wt., 9 1/2 lbs. HD-700 Net 45.47

Basic Bit Kit: Includes three most useful router bits 1/4" straight, 3/8" rounding over, 3/8" V grooving. Also includes a Silicon Carbide hone to keep cutting edges keen. Shpg. wt., 1/2 lb. HD-709 Net 6.97

Stanley Heavy Duty Builders Saw

- PERFECTLY BALANCED
- 9.5 AMPS—5000 RPM
- SELF-LUBRICATING BALL AND BRONZE BEARINGS



Power-packed 9.5 amp motor provides high cutting force. Wrought aluminum base connected to motor housing by spring steel beam. Rear position control panel. Rear-position wing-nuts for depth and bevel adjust. "Free Start" ball bearing guard—moves at slightest pressure. Big "window" for wide open view of cut. "Motor Saver" drive protects motor against damage when blade cuts nails or knots. Weighs only 9 3/4 lbs. Cuts 3/4" to 2" at 45°, 3/4" to 2 1/8" at 90°. Blade size 7 x 5 1/2". 5000 RPM no load speed. Ball and bronze bearings. 9.5 amps. 115/230 volts AC/DC. Shpg. wt., 13 1/2 lbs. HD-938 Net 34.97

GYRO-DRIVE

- Full-Power Full-Speed Drilling Up to 52 Degrees Off Center
- A Must For Electricians, Plumbers, Mechanics, TV Men, Telephone Installers



6.67

Here is the amazing drive which converts any 1/4" or 1/2" drill into a variable angle tool—drills in the tightest quarters, "around corners." Immediate angular positioning of the bit at angles up to 52°. Can be mounted into any 3/8"-24 male or female drill spindle. Threaded sleeve for 1/4" or 1/2" chuck, (chuck not supplied). May be permanently installed on drill or mounted in drill chuck, with additional chuck added on operating end. Removable hand grip bar for applying vertical pressure when drilling is difficult. Shpg. wt., 1 1/2 lbs. HD-95D Net 6.67

MODEL 4100 VERSAMATIC

11.25



- WITH YANKEE STYLE BIT HOLDER
- TURNS 1/4" DRILL INTO HIGH POWER TOOL
- REVERSES—INCREASES POWER—REDUCES SPEED

Seven to one speed reduction develops tremendous torque! Hand clutch control for easy, instant stop-start action! Look at these fabulous features! Power screw driver—handles largest screws—reverses to extract them! Power drill tapping head! Plenty of power for oversize drilling! Perfect for concrete or any kind of masonry drilling! Low speed and high power for hole saw attachments! A professional tool that anyone can use! Comes complete with screwdriver bit—Phillips bit—1/4 socket set adapter—wrench pin and instruction book. Shpg. wt., 5 lbs. HD-195 Net 11.25

1/2" CHUCK FOR VERSAMATIC
Geared chuck—3/4" to 1/2" capacity—#33 taper to fit Supreme Versamatic. Shpg. wt., 1/2 lb. HD-268 Net 7.38

JACOBS TYPE DRILL CHUCK



2.98

Comparable to Jacobs 1B. Key type geared tooth chuck. Capacity 0-1/4" thread 3/8x24". Ruggedly constructed. Polished finish. Used as standard equipment on most electric drills. Made to rigid specifications. Compare our really low price. You'll find this same chuck selling for twice as much! HD-186 Shpg. wt., 1 lb. Net 2.98

NEW CHASSIS PUNCH SET

- EASY-SMOOTH-HOLES IN SHEET METAL
- 5 SIZES: 1/2", 5/8", 3/4", 1", 1 1/8"



5.49

Five most often needed round hole punches. Do the job in minutes—save hours of tedious hand labor. Cuts smooth accurate holes for sockets—plugs—controls—panel lights—switches—terminals—most radio parts. Works equally well with sheet metal—sheet plastics—composition board, etc. Drive with any wrench—or with T handle included. Punch sizes included are 1/2", 5/8", 3/4", 1" and 1 1/8". Supplied complete with punches, dies, T drive handle, tapered reamer, fitted wooden case and instructions. Shpg. wt., 2 1/2 lbs. HD-471 Net ea., 5.49, Net ea., in lots of 3, 4.94

NEW! SQUARE PUNCH SET

- 3 NEEDED SIZES—1/2" — 3/4" — 1"
- SMOOTH, ACCURATE, EASY TO USE



6.95

Save time—save effort—cutting square holes in chassis—panels—sheet metal up to 1/8". Most often cuts allow any size square hole. Drive punches with any accurate square holes in metal—bakelite—plastic—composition board, etc. Complete with 1/2", 3/4", 1" case. Shpg. wt., 2 lbs. HD-48D Net 6.95

UNIVERSAL SQUARE



A versatile precision instrument for the workshop, this universal square can be used as a vertical level, horizontal level, 45° level, or as a square and sliding bevel. 7" steel blade is calibrated in inches and centimeters, can be accurately set at any angle meters, can be accurately set at any angle from 0 to 270°. Length is adjustable. Equipped with scriber. HD-967 Shpg. wt., 8 ozs. Net 1.63

ARC JOINT PLIERS

1.89

- Fully Chrome Plated

Heavy duty, slip-groove jointed water pump pliers. Fully chrome and polished. 5 adjustments. 1 1/4" parallel opening. Forged steel. Deep milled jaws. 9 1/2" long overall. Shpg. wt., 1 lb. HD-896 Net 1.89

THE RIGHT TOOLS AT THE RIGHT PRICE

THOR-SPEEDWAY 3/8" ELECTRIC DRILL



19.95

64-PIECE PROFESSIONAL POWER WORKSHOP

- A Complete Workshop For Do-It-Yourself Jobs
- Drills, Sands, Grinds, Buffs, Saws • Home, Garage, Shop

Here is the complete electric power workshop at Lafayette's typical low price. You can do almost every at-home job with this versatile 64-piece set. Look what you get: Thor Speedway 3/8" electric drill; 11-pc. power boring set with bits from 1/4" to 1 1/4"; 14-pc. twist drill set with metal index; 12-pc. sanding and polishing set; 7-pc. grind and buff set; 9-pc. 7-size hole saw; 7-pc. countersink and drill saw set; 3-pc. power screwdriver attachment. The Thor-Speedway 3/8" drill has 2.5 amp., 110 V AC motor. No-load speed, 1750 rpm; full load speed, 1150 rpm. Special alloy bearings throughout. U.L. approved. Shpg. wt., 10 lbs. **Net 19.95**

WEN 3 INCH BELT SANDER

MODEL 910



ONLY **33.05**
NO MONEY DOWN

- Extra-Duty 4 1/4 Amp Motor
- Compact, Balanced, Lightweight
- Forced Ventilation—Cools Motor and Removes Dust

Far more efficient than other sanding devices, the Wen Model 910 Belt Sander provides 850 square feet of abrasive material/minute. Its universal self-cooling motor may be used continuously for hours without overheating. Contour grip, 2 position knob, vibration-free bearings, balancing and lightweight (7 lbs.) remove fatigue from sanding. Belt changing in seconds. Flush design for close work. Complete gear drive with sealed bearings. Die cast polished aluminum housing. With 3 belts (coarse, medium, fine) and 6 ft. 3 conductor cord. Size: 5 3/4" H x 5 1/2" W x 10 1/2" L. For 115 V AC. Shpg. wt., 8 3/4 lbs. **Net each 33.05**
MD-937

In lots of 3, Each **29.37**

NEW!
FULL
POWER
1/4" DRILL

9.88



OUR
TOP DRILL
VALUE!

- UL APPROVED • GEARED CHUCK AND KEY
- UNIVERSAL 3/8 H.P. MOTOR

Lafayette's top drill value. 1/4" geared chuck drill rated at a full 3/8 hp horsepower. Universal motor. U.L. approved. 1/4" capacity in steel, 1/2" capacity in hardwood. 1200 to 1500 rpm speed under load, 2000 to 2400 rpm no load speed. Precision anti-friction bearings. Automatic trigger switch. Specially designed gear train for maximum torque transfer. Overall length, 8". For 115 VAC, 25-60 cycles. Shpg. wt., 4 lbs. **Net 9.88**
MD-708

Thor-SpeedWay SUPER SANDER

11.89



- 2.75 AMP MOTOR
- MOTOR DRIVEN 3450 RPM
- SANDS—SMOOTHS—BUFFS—POLISHES—RUBS!
- USE SHEET OR FREE (WET) ABRASIVES

Work-saving power for the master craftsman! The top sander with universal electric motor. Rough or finish sanding and buffing are done twice as fast! Hi-speed orbital action produces perfect finish every time. No load speed, 3450 r.p.m. Paper size, 4 1/2 x 6 1/2"; sanding area, 4 1/2" x 5 1/2"; overall length, 8". Sealed ball and oilite bearings. Neoprene ball guide and pad. Two pole induction motor, AC only; standard voltage 115V. 6 ft. 3 conductor UL approved line cord. UL approved push button switch. Shpg. wt., 6 lbs. **Net 11.89**
MD-865 Lambswool Polishing Pad **Net .79**
MD-866 18 Sheets, Ass'td Sandpaper **Net .98**



13.88

Thor-SpeedWay SUPER JIG SAW

- CUTS 2" WOOD—1/8" STEEL
- 3 AMP MOTOR
- 3000 STROKES PER MINUTE

Enjoy a new thrill in sawing! The powerful No. 5 jig saw cuts curves, scrolls, straight cuts and rips. Cuts 45° angle on either side. Cutting capacity: 2" soft wood, 1/4" in steel; length of stroke 3/8". Motor rating, 3 amps; no load speed, 3000 strokes per minute; oilite bearings. Base tilts 45°. Overall length 6 3/4", height 5". Universal series wound motor, AC or DC; positive on-off position, push-through slide switch UL-approved; 6 ft. 3 conductor lead cord UL approved. One wood cutting jig saw blade and wrench. 115V. AC/DC. Shpg. wt., 5 lbs. **Net 13.88**
MD-706

MD-439 Pkg. of 5 wood and metal cutting blades **Net .59**

34-PC. 1/4" POWER DRILL KIT



- Basic Kit for Home or Shop **14.95**
- Drills, Sands, Buffs, Saws

A value-packed electric drill kit with accessories for drilling, sanding, buffing, sawing, etc. The 1/4", UL approved, 3-wire drill features 2.9 amp. motor, mirror finish, and multiple thrust ball bearings. No load speed, 2000 rpm; full load, 1200 rpm. 34-piece set also includes: 9 drill bits; 1 drill stand; 10 sanding discs; lamb's wool bonnet; 6-pc. fittings; rubber base plate; buffing wheel; steel case; adaptor for 3-wire cord; 7-pc. countersink and drill saw set. Shpg. wt., 8 1/2 lbs. **Net 14.95**
MD-978

THOR SPEEDWAY 3/8" DRILL

- UL AND CSA APPROVED
- PRECISION GEARED CHUCK WITH KEY
- HI-TORQUE MOTOR
- RATED AT FULL 2.5 AMPS



Here is a professional 3/8" electric drill at an amazingly low price. Hi-torque 2.5 amp, 110 VAC motor with 3-conductor lead cord, precision geared 3-jaw chuck with key, all-steel precision hobbled gears and newly developed special alloy bearings throughout. Capacity in steel, 3/8", in hardwood, 1". No load speed, 1750 rpm, full load speed, 1150 rpm. Momentary contact switch with locking pin. Sturdy diecast aluminum alloy housings with attractive silicone bonded finish. Overall length, 8 1/4". Shpg. wt., 5 lbs. **Net 11.95**
MD-939

WEN 'SOUPED UP' SABRE SAW MODEL 909

- HEAVY DUTY—FULL 6 AMP.
- 1/2 H.P. MOTOR—1" STROKE
- LARGEST CUTTING CAPACITY
- 6" 90° CUT • 4" 45° CUT



NO MONEY DOWN
33.05

Bigger — more powerful — more versatile — faster cutting. Super-long blade easily cuts through 6x6" lumber. Cuts 4x4" at a 45° angle! Power enough to cut steel plate up to 1/2" thick—iron pipe up to 2" in diameter. Comfortable—conventional saw grip with auxiliary knob for 2 hand control. Saw tilts 45°—sole plate always remains flat. Finger control trigger-switch. Constant air stream flows dust from line of cut. 3400 1" strokes per min. Includes seven blades for cutting wood — steel — hardwood — sheet metal — pipe — leather — circle — formica — etc. Equipped with rip guide and circle cutter guide. 8 ft. 3 cord and adapter. 110 watts. 6 amp., AC-DC. 8Lx7Wx7 1/2"H. Shpg. wt., 8 1/4 lbs. **Net 33.05**
MD-466 **Net each in lots of 3 29.37**

RAM "88-3" 7" POWER SAW

27.95



- HEAVY DUTY, INDUSTRIAL
- 1 1/4 HP MOTOR
- 8 AMPS
- 4500 RPM
- CUTS 2 1/4" DEEP

Newly designed model features a powerful 1 1/4 horsepower motor with self lubricating Moly Sulphite bearings. 7" blade diameter, 5/8" round arbor hole. Cuts to a depth of 2 1/4". Angle of cut can be adjusted from 0° to 45°, with depth of cut of 2 1/4" at 45°. No load motor speed 4500 R.P.M. This rugged but lightweight saw is designed for effortless one-handed operation. For, 110-120 volts AC/DC. Lustrous mirror finish. Combination rip and cross-cut blade and rip-guide included. Slip clutch. UL approved, 3 conductor cord with 2 prong adaptor. Shpg. wt., 15 lbs. **Net 27.95**
MD-359 Saw **Net 27.95**
SAW TABLE. Perfect complement to the "88-3" Saw. Allows cutting at any angle between 45° and 90°. Complete with miter gauge and rip fence. Shpg. wt., 12 lbs. **Net 11.65**
MD-360 Saw table **Net 11.65**
COMBINATION OFFER. Consists of the MD-359 saw and MD-360 saw table, at a further saving in price. **Net 36.90**
MD-364 Saw and Table


THOR SPEEDWAY 1/2" DRILL

- FULL 5.5 AMP POWER RATING
- TWO-POSITION REAR HANDLE
- HEAVY DUTY SEALED THRUST BALL BEARING ON SPINDLE



This high power 1/2" Drill in the low priced field is built to professional standards throughout. Features safety switch with push button lock and removable top handle. The rear grip handle can be revolved to vertical or horizontal position. Specifications: 1/2" capacity in steel; 1" capacity in wood; 5.5 amp rating; 400 r.p.m. full load speed; 1 1/2" spindle offset. Universal series-wound AC-DC motor for 115 volts. Complete with 10 feet 3-wire, type SJ, UL approved lead cord; and 3-jaw geared chuck with key. Overall length with rear handle is 14 1/2". Shpg. wt., 14 lbs. **Net 23.95**
MD-862

ARC'D SCREW & NUT DRIVER ELECTRIC DRILL ATTACHMENT



- Complete 15 Piece Screw and Nut Driver

For rapid fastening of both screws (slotted and Phillips) and nuts (hex and square head). Has non-slip industrial type clutch for fast easy driving. Bit holder prevents screw head slippage. Includes flat bits and bit holders for #4-8 and #8-14 screws, #1-2 Phillips head bit, 6 hex socket wrenches (1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1") 2 sq. socket wrenches (1/4", 3/8", 1/2") and socket wrench holder with ball lock. **Net 5.84**
MD-944 Shpg. wt., 1 1/2 lbs.


25-PC. DELUXE TOOL KIT



2.79

Hardened, tempered alloy steel tools for handy use in the house or workshop. Kit consists of 1 plastic screwdriver handle with aluminum chuck; 4 screwdriver blades (1/4x1/4", 3/8x3/8", 1/2x1/2", 5/8x5/8" flat drivers and one No. 1 Phillips blade); 8 open and box end wrenches (1/4", 3/8", 1/2", 5/8", 3/4", 7/8", 1", 1 1/4", 1 1/2", 1 3/4", 2", 2 1/4", 2 1/2", 3", 3 1/2", 4", 4 1/2", 5", 5 1/2", 6", 6 1/2", 7", 7 1/2", 8", 8 1/2", 9", 9 1/2", 10", 10 1/2", 11", 11 1/2", 12", 12 1/2", 13", 13 1/2", 14", 14 1/2", 15", 15 1/2", 16", 16 1/2", 17", 17 1/2", 18", 18 1/2", 19", 19 1/2", 20", 20 1/2", 21", 21 1/2", 22", 22 1/2", 23", 23 1/2", 24", 24 1/2", 25", 25 1/2", 26", 26 1/2", 27", 27 1/2", 28", 28 1/2", 29", 29 1/2", 30", 30 1/2", 31", 31 1/2", 32", 32 1/2", 33", 33 1/2", 34", 34 1/2", 35", 35 1/2", 36", 36 1/2", 37", 37 1/2", 38", 38 1/2", 39", 39 1/2", 40", 40 1/2", 41", 41 1/2", 42", 42 1/2", 43", 43 1/2", 44", 44 1/2", 45", 45 1/2", 46", 46 1/2", 47", 47 1/2", 48", 48 1/2", 49", 49 1/2", 50", 50 1/2", 51", 51 1/2", 52", 52 1/2", 53", 53 1/2", 54", 54 1/2", 55", 55 1/2", 56", 56 1/2", 57", 57 1/2", 58", 58 1/2", 59", 59 1/2", 60", 60 1/2", 61", 61 1/2", 62", 62 1/2", 63", 63 1/2", 64", 64 1/2", 65", 65 1/2", 66", 66 1/2", 67", 67 1/2", 68", 68 1/2", 69", 69 1/2", 70", 70 1/2", 71", 71 1/2", 72", 72 1/2", 73", 73 1/2", 74", 74 1/2", 75", 75 1/2", 76", 76 1/2", 77", 77 1/2", 78", 78 1/2", 79", 79 1/2", 80", 80 1/2", 81", 81 1/2", 82", 82 1/2", 83", 83 1/2", 84", 84 1/2", 85", 85 1/2", 86", 86 1/2", 87", 87 1/2", 88", 88 1/2", 89", 89 1/2", 90", 90 1/2", 91", 91 1/2", 92", 92 1/2", 93", 93 1/2", 94", 94 1/2", 95", 95 1/2", 96", 96 1/2", 97", 97 1/2", 98", 98 1/2", 99", 99 1/2", 100", 100 1/2", 101", 101 1/2", 102", 102 1/2", 103", 103 1/2", 104", 104 1/2", 105", 105 1/2", 106", 106 1/2", 107", 107 1/2", 108", 108 1/2", 109", 109 1/2", 110", 110 1/2", 111", 111 1/2", 112", 112 1/2", 113", 113 1/2", 114", 114 1/2", 115", 115 1/2", 116", 116 1/2", 117", 117 1/2", 118", 118 1/2", 119", 119 1/2", 120", 120 1/2, 121, 121 1/2, 122, 122 1/2, 123, 123 1/2, 124, 124 1/2, 125, 125 1/2, 126, 126 1/2, 127, 127 1/2, 128, 128 1/2, 129, 129 1/2, 130, 130 1/2, 131, 131 1/2, 132, 132 1/2, 133, 133 1/2, 134, 134 1/2, 135, 135 1/2, 136, 136 1/2, 137, 137 1/2, 138, 138 1/2, 139, 139 1/2, 140, 140 1/2, 141, 141 1/2, 142, 142 1/2, 143, 143 1/2, 144, 144 1/2, 145, 145 1/2, 146, 146 1/2, 147, 147 1/2, 148, 148 1/2, 149, 149 1/2, 150, 150 1/2, 151, 151 1/2, 152, 152 1/2, 153, 153 1/2, 154, 154 1/2, 155, 155 1/2, 156, 156 1/2, 157, 157 1/2, 158, 158 1/2, 159, 159 1/2, 160, 160 1/2, 161, 161 1/2, 162, 162 1/2, 163, 163 1/2, 164, 164 1/2, 165, 165 1/2, 166, 166 1/2, 167, 167 1/2, 168, 168 1/2, 169, 169 1/2, 170, 170 1/2, 171, 171 1/2, 172, 172 1/2, 173, 173 1/2, 174, 174 1/2, 175, 175 1/2, 176, 176 1/2, 177, 177 1/2, 178, 178 1/2, 179, 179 1/2, 180, 180 1/2, 181, 181 1/2, 182, 182 1/2, 183, 183 1/2, 184, 184 1/2, 185, 185 1/2, 186, 186 1/2, 187, 187 1/2, 188, 188 1/2, 189, 189 1/2, 190, 190 1/2, 191, 191 1/2, 192, 192 1/2, 193, 193 1/2, 194, 194 1/2, 195, 195 1/2, 196, 196 1/2, 197, 197 1/2, 198, 198 1/2, 199, 199 1/2, 200, 200 1/2, 201, 201 1/2, 202, 202 1/2, 203, 203 1/2, 204, 204 1/2, 205, 205 1/2, 206, 206 1/2, 207, 207 1/2, 208, 208 1/2, 209, 209 1/2, 210, 210 1/2, 211, 211 1/2, 212, 212 1/2, 213, 213 1/2, 214, 214 1/2, 215, 215 1/2, 216, 216 1/2, 217, 217 1/2, 218, 218 1/2, 219, 219 1/2, 220, 220 1/2, 221, 221 1/2, 222, 222 1/2, 223, 223 1/2, 224, 224 1/2, 225, 225 1/2, 226, 226 1/2, 227, 227 1/2, 228, 228 1/2, 229, 229 1/2, 230, 230 1/2, 231, 231 1/2, 232, 232 1/2, 233, 233 1/2, 234, 234 1/2, 235, 235 1/2, 236, 236 1/2, 237, 237 1/2, 238, 238 1/2, 239, 239 1/2, 240, 240 1/2, 241, 241 1/2, 242, 242 1/2, 243, 243 1/2, 244, 244 1/2, 245, 245 1/2, 246, 246 1/2, 247, 247 1/2, 248, 248 1/2, 249, 249 1/2, 250, 250 1/2, 251, 251 1/2, 252, 252 1/2, 253, 253 1/2, 254, 254 1/2, 255, 255 1/2, 256, 256 1/2, 257, 257 1/2, 258, 258 1/2, 259, 259 1/2, 260, 260 1/2, 261, 261 1/2, 262, 262 1/2, 263, 263 1/2, 264, 264 1/2, 265, 265 1/2, 266, 266 1/2, 267, 267 1/2, 268, 268 1/2, 269, 269 1/2, 270, 270 1/2, 271, 271 1/2, 272, 272 1/2, 273, 273 1/2, 274, 274 1/2, 275, 275 1/2, 276, 276 1/2, 277, 277 1/2, 278, 278 1/2, 279, 279 1/2, 280, 280 1/2, 281, 281 1/2, 282, 282 1/2, 283, 283 1/2, 284, 284 1/2, 285, 285 1/2, 286, 286 1/2, 287, 287 1/2, 288, 288 1/2, 289, 289 1/2, 290, 290 1/2, 291, 291 1/2, 292, 292 1/2, 293, 293 1/2, 294, 294 1/2, 295, 295 1/2, 296, 296 1/2, 297, 297 1/2, 298, 298 1/2, 299, 299 1/2, 300, 300 1/2, 301, 301 1/2, 302, 302 1/2, 303, 303 1/2, 304, 304 1/2, 305, 305 1/2, 306, 306 1/2, 307, 307 1/2, 308, 308 1/2, 309, 309 1/2, 310, 310 1/2, 311, 311 1/2, 312, 312 1/2, 313, 313 1/2, 314, 314 1/2, 315, 315 1/2, 316, 316 1/2, 317, 317 1/2, 318, 318 1/2, 319, 319 1/2, 320, 320 1/2, 321, 321 1/2, 322, 322 1/2, 323, 323 1/2, 324, 324 1/2, 325, 325 1/2, 326, 326 1/2, 327, 327 1/2, 328, 328 1/2, 329, 329 1/2, 330, 330 1/2, 331, 331 1/2, 332, 332 1/2, 333, 333 1/2, 334, 334 1/2, 335, 335 1/2, 336, 336 1/2, 337, 337 1/2, 338, 338 1/2, 339, 339 1/2, 340, 340 1/2, 341, 341 1/2, 342, 342 1/2, 343, 343 1/2, 344, 344 1/2, 345, 345 1/2, 346, 346 1/2, 347, 347 1/2, 348, 348 1/2, 349, 349 1/2, 350, 350 1/2, 351, 351 1/2, 352, 352 1/2, 353, 353 1/2, 354, 354 1/2, 355, 355 1/2, 356, 356 1/2, 357, 357 1/2, 358, 358 1/2, 359, 359 1/2, 360, 360 1/2, 361, 361 1/2, 362, 362 1/2, 363, 363 1/2, 364, 364 1/2, 365, 365 1/2, 366, 366 1/2, 367, 367 1/2, 368, 368 1/2, 369, 369 1/2, 370, 370 1/2, 371, 371 1/2, 372, 372 1/2, 373, 373 1/2, 374, 374 1/2, 375, 375 1/2, 376, 376 1/2, 377, 377 1/2, 378, 378 1/2, 379, 379 1/2, 380, 380 1/2, 381, 381 1/2, 382, 382 1/2, 383, 383 1/2, 384, 384 1/2, 385, 385 1/2, 386, 386 1/2, 387, 387 1/2, 388, 388 1/2, 389, 389 1/2, 390, 390 1/2, 391, 391 1/2, 392, 392 1/2, 393, 393 1/2, 394, 394 1/2, 395, 395 1/2, 396, 396 1/2, 397, 397 1/2, 398, 398 1/2, 399, 399 1/2, 400, 400 1/2, 401, 401 1/2, 402, 402 1/2, 403, 403 1/2, 404, 404 1/2, 405, 405 1/2, 406, 406 1/2, 407, 407 1/2, 408, 408 1/2, 409, 409 1/2, 410, 410 1/2, 411, 411 1/2, 412, 412 1/2, 413, 413 1/2, 414, 414 1/2, 415, 415 1/2, 416, 416 1/2, 417, 417 1/2, 418, 418 1/2, 419, 419 1/2, 420, 420 1/2, 421, 421 1/2, 422, 422 1/2, 423, 423 1/2, 424, 424 1/2, 425, 425 1/2, 426, 426 1/2, 427, 427 1/2, 428, 428 1/2, 429, 429 1/2, 430, 430 1/2, 431, 431 1/2, 432, 432 1/2, 433, 433 1/2, 434, 434 1/2, 435, 435 1/2, 436, 436 1/2, 437, 437 1/2, 438, 438 1/2, 439, 439 1/2, 440, 440 1/2, 441, 441 1/2, 442, 442 1/2, 443, 443 1/2, 444, 444 1/2, 445, 445 1/2, 446, 446 1/2, 447, 447 1/2, 448, 448 1/2, 449, 449 1/2, 450, 450 1/2, 451, 451 1/2, 452, 452 1/2, 453, 453 1/2, 454, 454 1/2, 455, 455 1/2, 456, 456 1/2, 457, 457 1/2, 458, 458 1/2, 459, 459 1/2, 460, 460 1/2, 461, 461 1/2, 462, 462 1/2, 463, 463 1/2, 464, 464 1/2, 465, 465 1/2, 466, 466 1/2, 467, 467 1/2, 468, 468 1/2, 469, 469 1/2, 470, 470 1/2, 471, 471 1/2, 472, 472 1/2, 473, 473 1/2, 474, 474 1/2, 475, 475 1/2, 476, 476 1/2, 477, 477 1/2, 478, 478 1/2, 479, 479 1/2, 480, 480 1/2, 481, 481 1/2, 482, 482 1/2, 483, 483 1/2, 484, 484 1/2, 485, 485 1/2, 486, 486 1/2, 487, 487 1/2, 488, 488 1/2, 489, 489 1/2, 490, 490 1/2, 491, 491 1/2, 492, 492 1/2, 493, 493 1/2, 494, 494 1

LAFAYETTE HOBBY HEADQUARTERS



17⁹⁵

Ready-to-Run
Super Detailed
Scale Model

MERCEDES-BENZ W-196

- Scaled From Actual Blueprints of Mercedes-Benz W-169 Grand Prix Car
- Completely Enclosed Under The Hood Engine
- Starts Easily With a Spin of The Rear Wheels

Thimble-Drone presents the first model car with miniaturized big car engineering. An actual scale model of the famous Mercedes-Benz W-196 Grand Prix Car, powered by a .049 Cox engine completely enclosed under the hood. Fast, safe, and easy starts with a simple spin of the rear wheels. Counter balancing flywheel ensures smooth operation, easy starting fast "dig-out" and slow putting around. Automotive type individual spring suspension on all wheels enables the car to hug the ground better at unbelievable speeds. Comes complete with chrome wheel and spokes, knock-off type hub caps, exhaust pipes and life-like plastic driver for added realism. Overall length: 13.75 inches, wheelbase: 7.75 inches Shpg. wt., 4 lbs.

F-510 Net 17.95

5.95



Super Cub 150

- READY-TO-FLY!
- OFFICIAL CAP INSIGNIA!
- 17 1/2" WING SPAN!

World famous for ease of handling—smooth flying—maneuverability. Designed from the plane chosen for all-weather CAP patrol duty. Tough and rugged—of hi impact styrene. Realistic appearance. Transparent enclosed cabin—lots of authentic detail molded in. Famous Baby Bee, .049, 1/2 A engine. Long life nylon prop. Unbreakable spring starter. 17 1/2" wing span—12" fuselage—official chrome yellow coloring. Includes control handle and Dacron lines. Shpg. wt., 2 lbs.

F-521 Net 5.95
BA-160 Ignition Battery #6, Shp. Wt. 2 lbs. .84
F-512 Kit: reel, line, hose, etc. and fuel Net 2.23

7.49




P-40 FLYING TIGER

- "BIG PLANE" REALISM!
 - "COMBAT" MANEUVERABILITY!
 - SUPER POWERED SUPERBEE ENGINE!
 - 20" WINGSPAN — 15" FUSELAGE!
- Flying scale model of the most famous fighter plane of the past quarter century. The most accurate—most complete—ready to fly model airplane you've ever seen! From prop spinner to rudder—fron wheels to cockpit—every inch a richly detailed P-40 Flying Tiger! Powered by the special Super Bee engine. Designed just for this plane! Most powerful engine of its size — for loops, wingovers, combat maneuvers, perfect flight control. Like a real plane — it can be flown in "hot," brought in far a 3-point, or let down on the verge of a "stall." Hi impact styrene body — special nylon and vinyl fittings — official insignia — unbreakable spring starter — nylon prop. Includes control handle and Dacron lines. Shpg. wt., 2 1/2 lbs.

F-520 Net 7.49
BA-160 Ignition Battery #6, Shp. Wt. 2 lbs. .84
F-512 Kit: reel, line, hose, etc. and fuel Net 2.23

SUPER ACCESSORY KITS



• EVERYTHING YOU NEED FOR POWER MODEL OPERATION
Super Kit for Planes: Each accessory thoroughly tested for dependable operation. Includes Skyline reel with Dacron flying lines, fanguard, filler cap, stainless steel strainer, line snaps, filler hose, glow plug clip and glow fuel. Less battery. Shpg. wt., 1 lb.

F-512 Net 2.23
Super Kit for Cars: Contains glowfuel, filler cap, stainless steel strainer, hose, battery wires, glow plug clip, bridge, center post and cable. Less battery. Shpg. wt., 1 lb.

F-513 Net 1.52
Super Kit for Boats: Contains glow fuel, filler cap, stainless steel strainer, hose, battery wires, glow plug clip, hydro handle, tether lines, bridge, wrench and fanguard. Shpg. wt., 1 lb.

F-514 Net 1.32

FULLY TRANSISTORIZED PORTABLE BIKE RADIO



- Contains 4 Transistor Radio Plus Horn Plus Light In One Attractive Streamlined Unit
- Built-In Speaker
- Telescoping Antenna
- Sturdy Clip-on Mount

17⁹⁵

A sensitive 4 transistor radio, powerful horn plus a light, all in one streamlined unit. The perfect accessory for that new bike or for that matter your Golf-Cart, Baby Carriage or Boat. A sturdy handle bar clip-fitting allows you to attach this unit virtually anywhere. Radio covers full AM band from 530 to 1605 KC and is equipped with volume control, station selector and built-in speaker and earphone jack. In addition a detachable telescopic antenna is provided. Horn is activated by a simple to use push-button, while an On-Off slide switch controls light. Supplied with earphone for private listening plus 9V transistor battery for radio and standard D cell for horn and light. Shpg. wt., 3 lbs.

FS-122L Net 17.95

SPARKLE-LITE' DIRECTIONAL FLASHER

Bicycles, Go-Carts, Wagons, Soap Box Racers

- Runs on 2 standard flashlight batteries
- Can be seen from all angles
- Operates from handle bar
- Works just like a car's



2.99

Now all bicycles can have flashing directional signals like Dad's car—it's fun to use, makes bicycle riding much safer. The lever control can be mounted right on the handle bar, with left and right positions clearly indicated. Directional lights can be mounted on the front wheels, rear wheels or handlebars for greater visibility. Operates on 2 standard flashlight batteries (not included). Complete set includes all mounting equipment plus extra bulb. Shpg. wt., 1 lb.

F-546 Net 2.99
BA-157 Battery for above. Shpg. wt., 5 oz. Net .13

"ROCKET" GERMANIUM RADIO



- NO BATTERIES — NO POWER NEEDED
- INCLUDES CRYSTAL EARPHONE & ANTENNA
- A COMPLETE RADIO RECEIVER

This authentic plastic molded space rocket may not permit space travel, but the sensitive Germanium receiver it houses is capable of receiving the entire broadcast band. Easy tuning is assured by the collapsible nose "antenna." Supplied with Germanium Diode, crystal earphone and clip on antenna. Size 4-1/6" x 1-3/8" Diam. at base. Shpg. wt., 6 oz.

1.49

F-417 Net 1.49

AMAZING GERMANIUM RADIO



1.59

No batteries, no electricity, no transistors or tubes—nothing to wear out. Only 2 1/2" x 3 3/4" x 3/4" D. Perfect for news and civil defense broad-

casts in the event of power failures. This amazing radio utilizes the power furnished by the signals of your local radio station which are induced into all metal structures and wires in and around your home. A Germanium Diode and Ferrite Loop rectifies and tunes this signal energy, which when the antenna is clipped to a metal object, is amplified by the earphone. Complete with earphone and antenna wire with clip. Shpg. wt., 6 oz.

F-799 Net 1.59

NEW! TEKNIKIT™ UNIVERSAL SUN DIAL

- Includes Compass and Level
- Adjustable For Latitude/Longitude Variations
- Exceptionally Accurate

1.15

Pocket-sized modernized version of the worlds oldest "time piece." Perfect companion for Boy Scouts — hikers — hunters — campers — tourists — fishermen. Extra dial faces and adjustable arm allow for variations in longitude and latitude at point of use. Unusually accurate sun-time readings are possible by means of time/sun declination charts included. Sun dial, compass and level are incorporated in one solid case measuring 2 3/4 x 1 1/2 x 1/2". Weighs less than 2 ozs. Shpg. wt., 6 ozs.

F-627 Net 1.15

LENSATIC POCKET COMPASS



Jeweled-bearing metal scale with cardinal points in luminous paint. Twin scale, 0 to 64 and 0 to 360. Bezel rotates 360° — with 3° click stops for ease in computing. "Notch and hairline" sighting for accurate azimuth readings. Luminous reference lines on 2" diameter glass face plate. Black anodized aluminum case with brass fittings. Shpg. wt., 6 oz.

F-493 Net 2.25

ELECTRONIC POWERMEG



TRANSISTORIZED PORTABLE MEGAPHONE

8.66

- RANGE 100-300 FEET • LIGHTWEIGHT COMPACT
- COACHES • CHEERLEADERS • SCOUTING • HIKING • BOATING

This portable amplifier carries the voice 100-300 feet, loud and clear, and so has many uses both for fun and for serious work. Can be used at outdoor gatherings, picnics, song tests, square dances, hikes, camping trips — anywhere there is a need for a small portable P.A. system. The Powermeg is a valuable aid for the safe conducting of waterfront activities at camps and resorts, or for close range boat-to-boat communications. Use is simple: just press button and talk into microphone (included). Volume control regulates loudness. Requires 4 standard 1.5 volt flashlight cells. With shoulder strap, Shpg. wt., 4 lbs.

PA-275 Net 8.66
BA-274 1.5V Battery (4 required) Net ea. .16

LABORATORY MAGNET TEKNIKIT™

4.73

This set has been specially designed for schools, laboratories, and technicians, for testing and demonstrating the magnetic properties of permanent magnets. Fine hardwood case contains a pair of bar magnets 2" x 1/2" diam., a horseshoe magnet 1 3/4" high x 1 3/4" x 3/8" deep with 3/8" spacing between poles, and a bridge magnet 3/8" high x 7/8" x 3/8" deep with 1/4" space between poles. Shpg. wt., 1 1/2 lbs

F-58 Net 4.73

NEW! MAGNETIC STRIP

- Flexible-Versatile-Permanent Magnet
- Made in England

Remarkable, new magnet material. Flexible, extruded plastic strip, impregnated with Barium Ferrite magnetic powder. Can be cut with 1/16" thick. Pull is 3 ozs. per inch length with .000" gap (no intervening material) to 1.5 oz. per in. with a .015" gap. Limitless industrial, commercial and domestic applications. Used for magnetic closures, holders, locators, conveyors, displays, collectors, buffers, lifters. Will bend to a 3" circle, at room temperature, without breaking. May be warmed to increase flexibility without effect on magnetic properties.

F-751 3 ft. length, Shpg. wt., 8 ozs. Net 1.69
F-752 12 ft. length, Shpg. wt., 1 1/2 lbs. Net 5.50

NEW! REVELL "Slant-Six" MODEL KIT



- FOR MODEL MECHANICS
- MOTOR PARTS ACTUALLY WORK
- EDUCATIONAL • AUTHENTIC PROTOTYPE

Except for size, this Revell motorized plastic 1/4" scale working model kit of a slant six automobile engine duplicates its full size prototype. The design has been officially approved by the Chrysler Corporation. The more than 200 individual parts are precise in detail with those of the remarkable new engine powering the Valiant and Lancer automobiles. Just as the real engine, it can be built up and taken down as often as desired. A section of the block can be removed to see the interior parts actually working. In this motor-minded age the "Slant-Six" makes an ideal kit for any boy or man to own and build. It's fun—and according to educators, it's an excellent learning tool. Included is an elaborate educational instruction booklet and a sturdy stand for mounting the engine. Battery operated to provide realistic engine movements. Economical "C" cells are used.

F-769 Shpg. wt., 2 1/2 lbs. Net 9.55
BA-156 Extra "C" cells, 2 required. Net ea. .13

NEW! LAFAYETTE KT-181 MAGNETICS KIT



- FASCINATING MAGNETIC EXPERIMENTS
- STEP-BY-STEP ILLUSTRATED INSTRUCTION MANUAL
- COMPLETE WITH QUESTIONS & ANSWERS

Unlock the mysteries of magnetism with these fascinating, fun-filled experiments. Teach yourself by doing. Every phase of magnetism is covered: 1. Discovery and History of Magnetism. 2. Development of the Compass. 3. Discovery of Magnetic Poles. 4. How to Determine North and South Magnetic Poles. 5. Magnetic Attraction and Repulsion. 6. Terrestrial Magnetism. 7. Difference Between Magnetic and Geographic Poles. 8. The Magnetic Field. 9. Lines of Force. 10. Permeability. 11. "Molecular Magnets." 12. Artificial Magnets. Each experiment is fully detailed and illustrated. The kit contains a plexiglass viewing plate, a specially designed observation deck, two bar magnets; iron filings; compass; iron bar; lodestone; steel pins; aluminum and brass samples; wood float. Shpg. wt., 2 lbs.

KT-181 Net 2.95

SENSATIONAL NEW LIE-DETECTO MACHINE



An Action Packed Electronic Sensation!

- Employs The Same Method As The Famous Polygraph Machine
- Registers Emotions, Feelings and Reactions
- Absolutely Safe

Here's fascinating fun for the whole family. An exciting, different device that will provide hours of conversation and enjoyment. Based on the principles of the famous Polygraph Machine, the Lie-Detecto measures the change in resistance in the skin due to emotional response by means of a special hand-band which detects the amount of perspiration on the skin. Emotions, Feelings and Reactions are registered on an indicator which swings from Start thru Could Be, Are You Kidding, Little Whopper and Big Whopper, depending on the reaction of the person tested. In addition two panel controls provide for Sensitivity and Adjustment. Unit is enclosed in an attractive, rugged enclosure of non-breakable Norolon. Supplied with simple instructions and sample questions, hand-band and batteries. Shpg. wt., 4 lbs.

AP-84 Net 9.77

NEW! ELECTRIC MUSIC BOX MOVEMENTS

- Operates on a single flashlight cell
- Full 18 note scales
- Maintains perfect pitch

Uses limited only by your imagination! Battery operation opens a whole new field of applications. No springs to run down—no keys to wind! Precision built miniature motor and moving parts are designed to last a lifetime. Can be used anywhere ordinary movements are used—plus many more places. You can have a musical door "bell"! musical electric toy! work into model train layouts! store displays! annunciators. Measures only 3x1 1/2x7/8". Operates from any 1 1/2 volt battery of your choice. Shpg. wt., 6 oz.

MS-760 Moonlight Serenade Net 2.29
MS-761 Smoke Gets in Your Eyes Net 2.29
MS-762 How Dry I Am Net 2.29
MS-763 Around the World in 80 Days Net 2.29

Guarantee

LAFAYETTE GUARANTEES YOU 100% SATISFACTION OR YOUR MONEY BACK

Order with confidence from Lafayette — you must be completely satisfied or your money back in 30 days. You buy with confidence because you try your purchase at home for 30 days. If you decide to return it within that time for any reason, the full purchase price will be refunded to you, less only the transportation charges. Material including unwired kits must be returned in good condition and unaltered. Lafayette guarantees you complete satisfaction. Manufacturers' guarantees give you added protection for many more months. Lafayette does not sell merchandise not covered by manufacturer guarantees.

KITS:

All parts are warranted to be free from defects and will be replaced at no charge for one-year from date purchased. Kits fully wired by purchaser may be returned for inspection and repair at a moderate charge.

LOWEST NET PRICES:


The prices listed in this catalog are the lowest net prices at the time of printing. If the price of any item is reduced after the catalog is printed, we will fill your order at the lowest price at time of purchase and refund the difference. WE GUARANTEE YOU ALWAYS PAY THE LOWEST LAFAYETTE PRICE.

24 HOUR SERVICE:

Quick, courteous service is another daily guarantee at Lafayette. Most orders are fully processed within 24 hours after receipt in our Mail Order Division.

EASY-PAY PLAN:

It's simple to open an account — choose either standard or extended terms on orders as low as \$20. No down payment, up to 24 months to pay. No down payment for "Add-On" purchases.



Note: Hawaii and Alaska are in the 8th zone. Puerto Rico is in the 7th zone. All other U.S. possessions and territories in the 8th zone.

PARCEL POST RATES FOR ALL ZONES

Subject to post office rate changes

SHIPPING WEIGHT Up to but not including 16 ozs.	Local	ZONES							
		1-2 up to 150 Miles	3 151 to 300 Miles	4 301 to 600 Miles	5 601 to 1,000 Miles	6 1,001 to 1,400 Miles	7 1,401 to 1,800 Miles	8 Over 1,800 Miles	
		3c for the first 2 ounces and 1½c for each additional ounce							
to 2 lbs.	\$0.24	\$0.33	\$0.35	\$0.39	\$0.45	\$0.51	\$0.58	\$0.64	
3	.26	.38	.41	.47	.55	.64	.74	.83	
4	.28	.43	.47	.55	.65	.77	.90	1.02	
5	.30	.48	.53	.63	.75	.90	1.06	1.21	
6	.32	.53	.59	.70	.85	1.03	1.22	1.40	
7	.34	.58	.65	.77	.95	1.16	1.38	1.59	
8	.36	.63	.71	.84	1.05	1.29	1.54	1.78	
9	.38	.68	.77	.91	1.15	1.42	1.70	1.97	
10	.40	.73	.83	.98	1.25	1.55	1.86	2.16	
11	.42	.77	.89	1.05	1.35	1.67	2.02	2.34	
12	.44	.81	.95	1.12	1.45	1.79	2.18	2.52	
13	.46	.85	1.01	1.19	1.55	1.91	2.34	2.70	
14	.48	.89	1.07	1.26	1.65	2.03	2.50	2.88	
15	.50	.93	1.13	1.33	1.75	2.15	2.68	3.06	
16	.52	.97	1.18	1.40	1.85	2.27	2.81	3.24	
17	.54	1.01	1.23	1.47	1.95	2.39	2.96	3.42	
18	.56	1.05	1.28	1.54	2.05	2.51	3.11	3.60	
19	.58	1.09	1.33	1.61	2.15	2.63	3.26	3.78	
20	.60	1.13	1.38	1.68	2.25	2.75	3.41	3.96	
FOR EA. ADDED LB. ADD 2c		4c	5c	7c	9c	12c	15c	18c	

PARCEL POST HANDLING CHARGES

up to 5.00	.05	10.01 to 25.00	.15
5.01 to 10.00	.10	25.01 to 50.00	.20

FREE! LAFAYETTE'S NEW 1962 340-PAGE CATALOG from AMERICA'S "ELECTRONICS & HI-FI SHOPPING CENTER" featuring "THE BEST BUYS IN THE BUSINESS"

- ✓ Stereophonic Hi-Fi Equipment
- ✓ Cameras and Optics
- ✓ Citizens Band Equipment
- ✓ Amateur and Ham Equipment
- ✓ Radio and TV Supplies
- ✓ Industrial Supplies

Mail the coupon TODAY for your FREE Lafayette 1962 Catalog #620

Lafayette Radio, Dept. 621 P.O. Box 10
Syosset, L. I., New York

Send me the FREE Lafayette 1962 Catalog 620

Name _____

Address _____

City _____

Zone _____

State _____

PLUS EXCLUSIVE LAFAYETTE KITS

SATISFACTION GUARANTEED
OR MONEY REFUNDED
30 DAY FREE HOME TRIAL



USE THE LAFAYETTE EASY-PAYMENT PLAN — FOR YOUR CONVENIENCE, CUT ALONG DOTTED LINE

PRST
9876

TERMS:
The prices listed in our catalog are net. All trade and cash discounts have already been deducted. All prices are net, F.O.B. shipping point. Prices are subject to change without notice. Express or freight charges should not be sent with order (they are collected upon delivery.) Parcel post charges should be included with fully paid orders. We refund any not used. Do not send cash unless you register your letter.

THREE WAYS TO BUY
Enter Amount Enclosed FULLY PAID ORDER (Enclose full amount including postage and sales tax, if any).
DEPOSIT, BALANCE C.O.D. \$ (We advise ordering for amount less than \$5.00).
EASY PAYMENT ORDER
 Regular Plan Extended Plan
Down Payment \$ _____
If you have an Easy Pay account, show number here _____

DO NOT USE

TOTAL FOR GOODS

AMOUNT FOR SALES TAX (if any)
SHPG./HANDLING CHARGES (we refund any not used)
AMOUNT DUE LAFAYETTE FROM PREVIOUS ORDER
TOTAL AMOUNT

Lbs. Total Oz.


621

IMPORTANT—Any correspondence not connected directly with the order should be written on a separate full size letter sheet. This will speed handling of both order and letter.

NAME (First Name) _____ (Middle Initial) _____ (Last Name) _____
STREET ADDRESS _____
TOWN _____ POSTAL ZONE _____ STATE _____
SHIP TO ANOTHER ADDRESS? GIVE DIRECTIONS HERE _____
NAME _____
SHIPPING ADDRESS _____ ROUTE _____ BOX _____
TOWN _____ POSTAL ZONE _____ STATE _____
IF THIS IS YOUR FIRST ORDER TO US CHECK HERE

DATE _____
HOW SHALL WE SHIP?
 PARCEL POST
 EXPRESS
 FREIGHT
 OTHER _____
(PLEASE SPECIFY)
BULKY OR DELICATE ITEMS SUCH AS TUNERS, CHANGERS, AMPLIFIERS, ETC. ARE SHIPPED EXPRESS. THE LETTER "X" IS ADDED TO THE STOCK NUMBER OF THESE ITEMS.
DESCRPTION (Show Manufacturer's Name whenever Possible)
PRICE Ea., Lot, etc.
TOTAL PRICE DOLLARS CENTS
SHIPPING WEIGHT LBS. OZ.
If you have moved since last order give old address here.
STREET _____
TOWN _____
STATE _____
(PLEASE DO NOT USE)

LAFAYETTE RADIO ELECTRONICS CORPORATION
WORLD'S FOREMOST SUPPLIER OF ELECTRONIC COMPONENTS
111 JERICHO TURNPIKE • SYOSSET, L. I., NEW YORK



TELEPHONE: WAnut 1-7700
CATALOG Shop by Phone: WAnut 1-7500
CABLE ADDRESS: LAFRADELEC

(FOR EASY PAYMENT ORDERS — USE INK — SEE REVERSE SIDE)

ORDER BLANK

The NEW LAFAYETTE

CHOOSE THE PLAN THAT SUITS YOU BEST:

- (1) **REGULAR PLAN.** Monthly Payments as low as \$5. No Down Payment. (See Easy-Pay Payment Schedule.)
- (2) **E-X-T-E-N-D-E-D PLAN.** Up to 24 months to pay. No Down Payment. (See Easy-Pay Payment Schedule.)
- (3) **ALTERNATE 60-DAY PLAN** — No Credit Service Charge. Select the Regular or Extended Plan. Remit your payment within 30 days as scheduled. Pay the full balance, if any remains, within 60 days of shipment and you automatically convert to the Alternate 60-Day Plan and **SAVE THE ENTIRE CREDIT SERVICE CHARGE.**

Lafayette's Easy-Pay Plan
Makes It Easier For You To Buy Now ...
10 TIMES EASIER

1. **IT'S EASY TO OPEN AN ACCOUNT.** Fill in the agreement on the back of any order blank.
2. **IT'S EASY TO ORDER.** Use any regular Lafayette order blank. Initial orders may be as low as \$20.
3. **NO DOWN PAYMENT.** Whether you pay within 60 days, or 24 months, you need pay no money down.
4. **IT'S EASY TO MAKE "ADD-ON" PURCHASES.** No Money Down on orders over \$20.
5. **"ADD-ON" PURCHASES AT ANY TIME.** No need to pay the current balance in full before ordering again.
6. **UP TO 24 MONTHS TO PAY.** There's no need to wait—"buy what you want NOW, up to 24 months to pay.
7. **LOW CREDIT SERVICE CHARGES.**
8. **SEND NO MONEY FOR 30 DAYS.** First instalment payment due 30 days after shipment.
9. **ONE LOW MONTHLY PAYMENT** buys anything Lafayette sells. (Pre-recorded tapes, records, and items intended for resale excepted.)
10. **NO WAITING FOR MONTHLY STATEMENTS.** You always know the exact amount of your balance.

"DOLLAR POWER PLUS"

You Get "DOLLAR POWER PLUS" with Lafayette's 3-IN-1 Easy-Pay Plan. One Low Monthly Payment Buys More For You.

Monthly Payments FOR ONLY	Unpaid Balance (Total amount less down payment - if any) YOU CAN BUY UP TO
\$ 5	\$100.00
6	120.00
7	140.00
8	160.00
9	180.00
10	200.00
11	225.00
12	250.00
14	275.00
15	300.00
17	350.00
19	400.00
22	450.00
24	500.00

For monthly payments on balances over \$500, please write us.

3-IN-1

easy-1

pay plan

No Money Down

Here's How To Open Your Easy-Pay Account:-

Use the regular Lafayette order blank (more will be supplied upon request). Complete both sides of the form carefully, following the step-by-step instructions and illustration. Accuracy will speed handling of the form from the moment of receipt and permit immediate shipment upon approval of credit. Be sure to sign the agreement and indicate which Easy-Pay Plan you prefer — the liberal Regular or special Extended.

For both Plans, minimum order is \$20 and first instalment is not due until 30 days after shipment.

No Credit Service Charge for the alternate 60-Day Plan. For the Regular and Extended Plans, you are privileged to prepay the balance in full at any time to obtain a partial rebate of normal credit service charges.

Easy-Pay privileges are available to qualifying U.S. citizens or residents of all 50 States, Puerto Rico, Canada, and U.S. territories having comparable postal and express facilities. Any responsible individual over 21 years old with a steady source of income can apply.

FOR EASY PAY PURCHASE USE THIS SIDE AFTER FILLING IN MERCHANDISE ON REVERSE SIDE. Before filling out amounts see EASY PAY PLAN SCHEDULE and example. Figure your sums first on separate paper to avoid errors. USE INK. DO NOT ERASE OR CROSS OUT.

RETAIL INSTALLMENT CONTRACT

Buyer's Copy Mailed - Date _____ By _____

(Please Print)
 Name _____
 Present (A) Home Address _____
 City _____ Zone _____ State _____
 Telephone _____
 How Long At This Address _____

To fill in spaces below correctly refer to EASY PAY PLAN Schedule on this sheet and note example:

1. Total Cash Price
2. Sales Tax (N.Y.C. only)
3. Total (Items 1+2)
4. Down Pay't (Altho Not Required Reduces Svce. Chrgs. & Paymts.)
5. Unpaid Balance (Item 3 minus item 4)
6. Credit Service Charge (See EASY PAY SCHEDULE)
7. EASY PAY BALANCE (Add items 5+6)

Total EASY PAY Price (Add items 3+6)

Do not include shipping charges. Easy Pay orders are sent shipping charges collect, except for PARCEL POST CHARGES which are added to your account.

RETAIL INSTALLMENT CONTRACT

(L.S.) DATE _____

Combined Am't. you wish to pay monthly \$ _____

How to convert to Alternate 60-Day Plan. Pay 1st instalment within 30 days of shipment. Complete payment of balance, if any remains, within 60 days of shipment and Save Entire Credit Service Charge.

UP TO 20.00	20.01 - 30.00	30.01 - 40.00	40.01 - 50.00	50.01 - 60.00	60.01 - 70.00	70.01 - 80.00	80.01 - 90.00	90.01 - 100.00
2.00	3.00	4.00	5.00	6.00	7.00	8.00	9.00	10.00
100.01 - 110.00	110.01 - 120.00	120.01 - 130.00	130.01 - 140.00	140.01 - 150.00	150.01 - 160.00	160.01 - 180.00	180.01 - 200.00	200.01 - 225.00
11.00	12.00	13.00	14.00	15.00	16.00	18.00	20.00	22.50
15.00	17.00	19.00	21.00	23.00	24.00	27.00	30.00	34.00
225.01 - 250.00	250.01 - 275.00	275.01 - 300.00	300.01 - 350.00	350.01 - 400.00	400.01 - 450.00	450.01 - 500.00	On orders over \$500.00 Credit service charge and payments will be in proportion to amounts shown on schedule	
25.00	27.50	30.00	35.00	40.00	45.00	50.00		
38.00	42.00	45.00	51.00	58.00	66.00	73.00		

For purpose of receiving credit for above EASY PAY PLAN purchase, the buyer makes the following representation:

Parents' Name and Address _____
 Spouse Name and Address _____
 Home Address _____
 Age _____
 Draft Classification _____
 Real Estate Holdings - Address _____
 Recorded In Name of _____
 Name of Present Employer _____
 Business Address _____
 Name of Former Employer _____
 Bank Account With _____
 First Trade Reference _____
 Second Trade Reference _____
 Third Trade Reference _____
 Nearest Relative _____

Permanent or previous address if (A) above is temporary or occupied less than two years. _____
 How Long (Years) _____ (Months) _____
 Salary _____
 If yes, please give your Lafayette Time Payment Account Number. No. _____
 City _____ State _____
 Present Value \$ _____
 Position Bodge No. _____
 Any Other Income _____
 Mortgage \$ _____
 How Long (Years) _____ (Months) _____
 Source _____
 Highest Credit \$ _____ Still Owning \$ _____ Monthly Payment \$ _____
 Highest Credit \$ _____ Still Owning \$ _____ Monthly Payment \$ _____
 Highest Credit \$ _____ Still Owning \$ _____ Monthly Payment \$ _____
 Name _____ (DO NOT LIST THOSE WITH WHOM YOU RESIDE) Address _____

F15


IMPORTANT: Please sign this form before mailing. Be sure to give age. (Must be



LAFAYETTE HOBBY HEADQUARTERS

"CHAMPION" 6-CAR FREIGHT TRAIN SET

The magnificent era of steam railroading comes to life again in this authentic scale model HO gauge freight train set. Top notch quality throughout features authentic working valve gear and electric head light in the locomotive, with accurate markings on all cars. Set consists of 4-6-2 lighted pacific type steam locomotive and tender, 1 box car, 1 operating hopper car which unloads by remote control, 1 stock car, 1 refrigerator car, 1 flat car w/load skids and girder, 1 8 wheel caboose, 11 sections 18" radius curved track, 1 curved terminal track, 1 section 9" straight track, 1 straight re-railer track for a 45" x 36" oval. Complete with 1 NMRA portable, automatic uncoupling ramp. AP-77 Shpg. wt., 7 lbs. No Money Down Net 23.95



Value of components
if purchased separately **49.32**

Only
23.95
NO MONEY
DOWN

- Precision Engineered For Trouble Free Operation
- Authentic Scale Models • Complete with Tracks
- Operating Hopper Car—Lighted Locomotive
- Scientifically Weighted Cars For Best Roadability

TYCO HO Train Sets

AURORA Model Motoring

Fleischmann
Steam Engines

GILBERT AMERICAN FLYER Model

TERRIFIC PRODUCTS, INC.

SCINTILLA Power Packs



"SUNSHINE LIMITED"

A TYCO MODEL TRAIN SET

STREAMLINE DIESEL PASSENGER TRAIN

- Double GM "A" & "B" Diesel Units • Coaches-Cars Dual Lighted
- Authentic Markings • Scale Model • Complete with Tracks

A beauty to behold! Thrills young and old alike with powerful realistic "A" type diesel locomotive with front headlight, followed by a non-powered "B" type diesel. Other cars are: 1 streamline combine, 2 streamline coaches, and 1 streamline observation. All are dual lighted and authentic scale models of

their big brothers. Also included in this complete set are 11 sections 18" radius curved track, 1 curved terminal track, 1 section 9" straight track, 1 straight re-railer track. Makes oval layout of 45x36". 1 NMRA portable, automatic uncoupling ramp. AP-78 Shpg. wt., 7 lbs. Net 21.95



NO MONEY DOWN!

Value of Components
if purchased separately
21.95
\$38.72



"Pace Setter" 7-CAR DIESEL FREIGHT TRAIN

- Authentic Scale, Model • Complete with Tracks
- Lighted Twin Diesel Locomotives • Operating Hopper Car

Value of components
if purchased separately ~~\$32.39~~

16.77

Modern, powerful diesel freight—long in size and value. Powered by a lighted F9 "A" type Diesel locomotive followed by a matching non-powered "A" Diesel. Balance of set includes: 1 gondola w/calvert pipe load, 1 chemical tank car, 1 box car, 1 operating hopper car, 1 8 wheel caboose, plus 11 sections of curved track,

1 curved terminal, 1 section of 9" straight track and 1 straight re-railer track making a total oval of 45x36 inches. 1 NMRA portable automatic uncoupling ramp, completes the set. AP-67 Shpg. wt., 6 lbs. Net 16.77



"BOOSTER SPECIAL" 5 CAR STEAM FREIGHT

- Manufactured by Famous Tyco
- High Value • Precision Engineering
- 4 Freight Cars • Complete With Track

Value of components
if purchased separately
~~\$22.53~~

Only
9.98

Bring back the glory of steam railroading with this authentic 0-4-0 NYC steam locomotive. An amazing value in HO railroading. Featuring all the top notch engineering of TYCO. The freight train consists of 1 flat car w/snap on load skids and girder, 1 refrigera-

tor car, 1 gondola car, 1-4 wheel caboose, plus 11 sections of straight track, and 1 18" radius curved terminal track. Makes a 36 inch circle. Shpg. wt., 4 lbs. AP-68 Net 9.98

NEW! HO SCALE 4 LANE RACING SET

All the Thrills
of A Real Race!

26.99

NO MONEY DOWN!



- Speeds up to 150 Scale Miles Per Hour
- 2, 3, or 4 Persons Play Simultaneously
- Changeable Race Track - Different Layouts Possible

Exciting model motoring at its best. Now Four cars can compete at one time, each independently operated. Learn to handle a Jag at up to 150 scale miles per hour without spill or spin-out on curves. Hours of fun are yours with this table top raceway. Layout can be arranged in dozens of ways. Set consists of 8 - 9" radius curved sections, 6 - 9" straight road sections, 2 - 9" terminal road sections, 4 assorted cars, 4 speed control units, 1 transformer powered unit, 1 set of assorted trestle supports, posts, guard rails and rail posts. AP-76 Shpg. wt., 10 lbs. No money Down Net 26.99

6.88 ACTION HO TUNNEL BY TERRIFIC PRODUCTS

- Flashing Airplane Beacon Light
- 3-Dimensional Beach House and Patio
- 22 True to Life Colors
- Completely Assembled

With a Real Running Waterfall!

A scenic masterpiece. Adds action and color to any HO model train layout. Waterfall actually runs down mountain side into a water filled lake. Tunnel is constructed of tough, waterproof styrene plastic. Operates from A.C. terminals of standard power pack. Adjustment switch turns on beacon light, and starts, stops, or varies waterfall independently of train operation. Size: 18Lx12Wx8"H to top of beacon light. Shpg. wt., 2 lbs. AP-83 Net 6.88

HO MODEL RAILROAD POWER SUPPLY

- Heavy-Duty Transformer with Full-Wave Selenium Rectifier
- Operates Up to 2 HO Train Sets

6.75


SCINTILLA AMBASSADOR

A high quality, heavy-duty, precision built, HO power pack. Operates either two complete train sets or one set with lighted cars and smoke or sound features. Features Vis-O-Signal throttle, heavy-duty transformer and full protection circuit breaker. 16 volts A.C., 12 volts D.C. output at 1.5 amps. Black and brushed brass finish. Operates on 115V 60 cycle A.C. Shpg. wt., 3 1/2 lbs. AP-79 Net 6.75

All the Thrills of A Real Race!

21.59

NO MONEY DOWN



AMERICAN FLYER CORVETTE RACE

- Sets Up on Table Or Floor • Total of 67 Pieces • Action-Fun For The Entire Family


Imagine yourself at the wheel of a powerful Corvette as it races over a twisting course, around bends, up grades, skidding through hairpin turns. Each car is controlled by a separate pedal-type Accelerator and each car has its own DC electric motor with enough power to travel at collision speeds or to skid, spin, roll and flip. Scale model Red Corvette and Ivory Corvette include car customizing kit of decals, insignia, head and tail light reflectors, chrome bumper strips, race numbers, motor cowling covers. 24 pieces (20 curved, 4 straight E-Z Faster Roadway sections, 20 plastic fence set, 2 speed controls.) 1 1/4 amp D.C. output. Motor pack power unit. Shpg. wt., 9 lbs. AP-71 No Money Down Net 21.59

AMERICAN FLYER

(A) 1940 FORD COUPE. Completely assembled, ready to operate. Includes decal kit, D.C. motor. 5 1/4" long. AP-85 Shpg. wt., 1/2 lb. Net 4.98

(B) REVERSING SWITCH. Makes your model cars go forward or back. Shpg. wt., 1/2 lb. AP-86 Net 2.98

Fleischmann STEAM ENGINES



Finest model steam engines famous for quality the world over. All engines are ready stocked with "Esbit" dry fuel for initial run. Can be used to operate mechanical models. Imported from Germany.

(A) Brass Boiler dia. about 1 1/2 inches. Features Oscillating cylinder. Sturdy firebox housing for Esbit dry fuel. Safety valve. Grooved flywheel. Metal base 6x7 inches. Height including chimney about 7 inches. Shpg. wt., 2 lbs. AP-80 Net 6.88

(B) Brass boiler stained blue with a diameter 2 1/2 inches. Features oscillating cylinder. Sturdy firebox for Esbit dry fuel. Safety valve. Steam white, water level indicator and grooved flywheel. Flywheel mounting has railing. Metal base 8 1/2x10". Height including chimney 9 3/4". Shpg. wt., 3 lbs. AP-81 Net 10.33

ESBIT DRY FUEL Package of 20 pellets. Will operate all Fleischman steam engines. Completely safe and non-toxic. AP-82 Pkg. of 20 Net .40

CURTISS PUSHER TYPE



- Ready-to-Assemble and Fly
- 1911 Vintage Flying Machine
- A real "Show" Model—and it FLIES

7.49

All the fun of model building—all the thrills of model flying—combined in an historic vintage model that assembles easily and flies at scale speeds. Carefully scaled and detailed. Perfectly simulated "bamboo" members—appearance of taut fabric stretched over wing frames — 24" wingspan — Instant starting .049 Baby Bee engine — 6" Dobl-Tuf Nylon prop. Includes control handle and Dacron lines. Shpg. wt., 2 lbs. F-593 Net 7.49

BA-160 Ignition Battery #6. Shpg. wt., 2 lbs. .84
F-512 Kit: reel, lines, hose, etc. and fuel Net 2.23

Weather Instruments-Timers



4895

- Wind Direction and Velocity Indicator
- Direction and Velocity on One Dial
- Indicates Velocity from 0 to 100 m.p.h.
- New "Gyro" Design
- Starting Speed: 5 m.p.h.
- Accuracy for Speed $\pm 5\%$

Registers wind velocity and direction on a single dial. Completely self contained—no outside power source is required. A precision velocity/direction system designed to fill the needs of serious weather students, pilots, colleges, broadcast stations, marinas, airports, farms, testing labs, drilling rigs, forestry stations, yacht clubs, motels as well as private homes and executive offices. The transmitter assembly may be mounted on any suitable elevated position. Utilizes any 1/4" O.D. pipe or mast. Indicating unit can be wall mounted or set on a desk, table, mantle or shelf. The indicator is housed in a handsome wooden cabinet, 5 1/2" x 2 1/2" x 7 7/8", finished in black and gold. Highly legible dial face 4 1/2" x 3 1/2". Two scales for speed, 0 to 25 m.p.h. and 0 to 100 m.p.h. plus third scale for direction. Outdoor parts of aluminum and specially coated and treated steel for maximum corrosion resistance. Self contained battery—no drain except when reading wind direction. Simple installation—similar to TV antenna installation. New "Gyro" design for maximum stability and minimum wind loading. Complete with 60 ft. of 5 conductor, color coded cable, 1 1/2 volt battery and instructions. Shpg. wt., 15 lbs.

F-507WX Net 48.95

"WINDICATOR" MOUNTING KIT

• Guyless Universal Mounting Assembly
Consists of mini-tower for mounting on any peaked or flat roof or surface. 5 ft., 18 gauge, 1 1/4" O.D. aluminum mast. Special, hardened screw-nails for rigid fastening. Self sealing, adjustable feet. Five standoff insulators. Set up height 9 ft.
AM-20W Shpg. wt., 8 1/2 lbs. Net 7.17
Wire for extended runs, 5 cond., color coded.
WR-121 Shpg. wt., 2 1/2 lbs. Net, per 100 ft. 4.70

HUMIDICATOR—"SLIDE RULE" HYGROMETER

- Slide Rule Readings
- No Computing —
- No Conversion
- Exceptional Ease and Accuracy

The most recent innovation in weather instruments. Fastest—easiest method of determining relative humidity. With the cursor (slide) set on the temperature, the relating humidity is read directly off the humidity indicator graph. Does away completely with tables, charts and time consuming calculations. The "sliderule" calculator correlates wet and dry bulb readings and "calls-out" percent of relative humidity. The "Humidicator" graph is calibrated in increments of 2%. Lesser figures may be readily estimated. Both thermometers are calibrated in increments of 2° from 20°F. to 120°F. Background colors chosen for easy readability and instant reference to "Humidicator" graph. Specially treated gauze for wet thermometer has increased "wetting" capacity. Overall size, including cistern, is 13 1/2" x 3 3/4". All mounted on a mahogany board with provision for hanging. Shpg. wt., 1 lb.

F-496 Net 2.69

INDOOR-OUTDOOR THERMOMETER

Tell inside and outside temperature—Instantly—from the comfort of your room. Inside location—ideal for quick-easy reading. Dual tubes single scale for instant, visual comparison. Plastic case with modern tapered lines. 8" x 2 1/2" x 4 8" long copper capillary tube and bulb. Large scale numeral for ease of reading. No moving parts to become worn. Shpg. wt., 1 lb.

F-321 Net 2.58

MAXIMUM-MINIMUM THERMOMETER

For weather enthusiasts-gardeners-farmers, etc. Gives three readings at a glance—maximum, minimum and present temperatures. Self-registering—no knobs—magnets—or push buttons needed for reset. Magnifying lens case for ease of reading. Maintains automatic check on temperature variations. Makes you the local weather expert. Shpg. wt., 1 lb.

F-372 Net 4.70

HYGRO-THERMOMETER



650

Do you ever wonder what it is about the weather that makes you feel miserable? This instrument evaluates the physical discomfort that is caused by the relative fluctuation of temperature and humidity. A large 3 1/2" easy-to-read dial face is housed in a metal case fitted to hang on your wall. One scale records the humidity in the atmosphere and is marked in percent, the other scale indicates the temperature in degrees Fahrenheit. Each scale has its own individual dial pointer for at a glance readings. Shpg. wt., 1 lb.

F-788 Net 6.50




1/10TH SECOND "ELECTRONIC" TIMER

- Made to Gov't. Specifications
- Mil-W-6510 (USAF) Type A-8
- Exceptional Accuracy

Especially useful as timing components of electronic and radar equipment. Made in accordance with government specification number MIL-W-6510 (USAF) type A-8. Dial face calibrated in 1/10 seconds. Sweep hand completes turn in 10 seconds. Register divided in 10 sec. increments, completes turn in 5 minutes. Luminous figures on black face. Start, stop and fly back to zero by successive depressions of the crown. Balance staff shock protected, unbreakable mainspring, nickel finished case. Swiss made.

F-774L Shpg. wt., 8 ozs. Net 25.95

DECIMAL "TIME-OUT" TIMER



Ideal for industrial time-studies. Easy-to-read outer dial divided in 1/100 of a minute registering up to one minute. Inner dial graduated in minutes and registers up to 30 minutes. Push button, for timing out, brings both hands back to zero. Pressures on the crown will consecutively start, stop and again start the timer. Dependable 7-jewel movement. Swiss made. Shpg. wt., 8 oz.

F-664L Net 9.75

1/10th Second "Time-Out" Timer

Suggested for close timing. Large hand registers 1/10 of a second, up to 30 seconds; small hand in minutes, up to 15. Start, stop, and continue from crown; instant return to zero by push button. Accurate 1-jewel movement. Chromium plated nickel case. Shpg. wt., 8 oz.

F-665L Net 6.90

Same as F-665 (above) except 7 jewels. Net 9.33
F-773L

AIRCRAFT CLOCKS



- Made to Gov't. Specifications
- Mil-C-7939A, AN-5743-2 and AN-5743-L2
- Exceptionally Accurate, Precision Movement
- Panel Mounts In Lab, Plane, Car, or Rack.

Standard equipment in the better airlines. Made in strict accordance with USAF specification Mil-C-7939A, Type A-11, AN-5743-2 and AN-5743-L2. Exceptionally accurate, dependable, precision movement. Runs 8 days on one winding. Big luminous, hands and numerals (61 green phosphorescent), sweep second hand, 24 hour dial, 1 7/8" diameter. Winds and sets from the front. Readily mounted in rack panels, instrument panels, dash boards. Lightweight, unbreakable, oxidized black aluminum case. Shpg. wt., 1 lb.

F-775L Net 27.95

POCKET THERMOMETER

- Accurate Lab Type
- With Metal Case

1.80

Ideal for a wide range of testing and inspection jobs in the laboratory, factory, and the field. Mercury type—partial immersion. Easy-to-read white scale with black numerals. Sub-divided by 2°. Polished nickel-plated case with pocket clip and ring on top. Overall 6 1/4" long; tube length 5 1/2". Shpg. wt., 4 oz.

F-771 Range: -30° to 120°F Net 1.80
F-772 Range: 0° to 220°F Net 1.80

NEW! TIMED EXTENSION CORD

Set It and Forget It



5.11

- Automatic Time Switch & Extension Cord + 3-Way Outlet
- Controls up to 3 Appliances at Same Time
- Reduces Electric Bills

A 3-way combination for every home—an automatic time switch, extension cord, convenient outlet. 0-4 hour time cycle. Easy to operate—plug it into any wall outlet, connect one, two or three devices to be controlled, and turn the knob to the time period desired. At the end of this time period, the electricity is turned off automatically. 6-foot cord. Shpg. wt., 2 lbs.

MS-841 Net 5.11

LAFAYETTE SPECIAL

AUTOMATIC TIMER MECHANISM THAT DOES EVERYTHING



5.95

- Turns Appliances On Or Off
- Never Needs To Be Reset
- Handles 1650 Watts
- Operates From 30 Minute To 23 Hr. Cycle

Makes practically everything electrical completely automatic. Will handle load up to 1650 watts. Turns radio on and off—does not have to be reset each night. Defrosts refrigerator—turns lights on and off—controls roaster, electric blanket, washing machine, coffee makers, vaporizers, etc. 30 min. minimum on time—23 hours maximum. As easy to set as an electric clock. Easy to read 24 hour "day and night" dial. Operates day after day without attention. Can be controlled manually without automatic reset. For 110 volt 60 cycle AC only. Instructions included. Easily built into any case. 3 1/2" x 4 1/4" x 2 1/2" D. Shpg. wt., 2 lbs.

MS-810 Net 5.95

TELECHRON TIMER SWITCH

- Radio—TV—Appliance Timer
- 60 Minute Sleep Switch
- Simple Installation
- Rated to Handle 1650 watt load
- Efficient Accurate Time Control

5.40

Automatically turns on radios—TV sets—tape recorders "ham" rigs—electrical appliances—at any preset time in a 12 hour period. "Sleep-Switch" allows up to 60 minutes of continuous run prior to "shut-off." Built in alarm for added convenience of "signaling." As easy to set as any electric clock. All controls on front. On-off-auto, 0 to 60 sleep switch, alarm set and time set. Gold finish dial—black lettering. 3 1/2" square bezel. 1 1/4" deep. SPST rated 15 amps at 115 volts, 1650 watt load capacity. For 110-120V, 60 cy. AC only. Shpg. wt., 2 lbs.

MS-794 Net 5.40

NEW! AERO/MATCH SPRAY BRUSH




only 1.83

- SPRAYS EVERY TYPE OF PAINT

- CAN SPRAY MIXED COLORS
- COMPLETELY PORTABLE—NON-ELECTRIC

Now you spray and match exactly the same paint you buy for brushing. Since you fill the sprayer with your own paint, you can match anything—even multi-colors. The 15 oz. power unit is bigger, more powerful—outlasts about three aerosol paint cans. Operates on a non-toxic, non-inflammable, pressurized gas. Unsurpassed for small or medium paint spraying. Spray brush requires no special skill... easy to use... easy to clean. Precision spray needle is made of metal and set in metal. Not affected by paint solvents. Can spray any liquid paint, insecticide, polish, antiseptic, etc., and many powders.

HD-972 1.83
HD-973 Replacement Power Unit 1.24



INTERMATIC TIMERS MODEL A211 TIME-ALL

• THE AUTOMATIC TIMER WITH THE MIRACLE MEMORY Makes practically everything electrical completely automatic. Will handle load up to 1650 watts. Turns radio on and off—does not have to be reset each night. Defrosts refrigerator—turns lights on and off—controls roaster, electric blanket, washing machine, coffee makers, vaporizers, etc. 30 min. minimum on time—23 hours maximum. As easy to set as an electric clock. Stands on any surface—can be hung on wall. Easy-to-read 24 hour "day and night" dial. Operates day after day without attention. Special alloy "T" can be controlled manually without automatic reset. Plug-in receptacle for equipment to be controlled. For 110 volt 60 cycle AC only. Complete with 6 ft. cord and plug. Instructions included. 5 1/4" x 2 1/2" D. Shpg. wt., 2 lbs.

MS-81 Lots of 6, ea., 7.17. Singly, ea., 7.97
MODEL A221 TIME-ALL Similar to A211 except has capacity of 875 watts. Shpg. wt., 2 lbs.
MS-359 Lots of 6, ea., 6.57. Singly, ea., 7.29

TYPE T101 TIME SWITCH

Turns equipment "on" and "off" once in 24 hours, or from one to twelve "on" and "off" operations a day can be obtained by use of extra trippers. Extra trippers can be added without removing dial. Min. on or off time 1 hr., max. on or off time 23 hours. Can be turned on or off manually with reset SPST switch rated at 35 amps, 4000 watt capacity. Alloy "T" contacts carry incandescent lighting loads with inrush surge of over 8 times normal rating. Almost immune to pitting, arcing, sticking. Has convenient mounting holes and knockouts. Large numbers—easy to set. Gray steel case—hinged door—can be locked or sealed. UL approved. Operates on 110 volt 60 cycle AC only. Size 7 3/4" x 5 1/2" x 3" D. Shpg. wt., 4 lbs.

MS-82 Lots of 6, ea., 7.17. Singly, ea., 7.77

P-101 Similar to T101 except case is equipped with 6 ft. cord set for plug-in and receptacle. Capacity 1250 watts. Shpg. wt., 6 lbs.
MS-360 Lots of 6, ea., 8.37. Singly, ea., 9.07



MODEL 2130 PORTABLE 2-SPEED PRECISION TIMER

- TWO TIMERS FOR THE PRICE OF ONE!
- FOR PRECISE 1 SECOND TO 1 HOUR TIMING IN THE HOME, OFFICE AND LABORATORY

Indispensable for timing precise, short operations such as boiling eggs, pressure cooking, heat and sun lamp treatment, home permanents, photo developing, printing, long distance calls, etc. Times up to 60 minutes in seconds and up to 1 hour in minutes. Exclusive 2-speed feature permits instant timing speed change by flick of a lever. A clear, resonant bell sounds at end of timing period. Can be attached to any surface with handy wall bracket supplied or can stand upright. Smartly styled in white with dial face a rich color. 4 1/2" x 2 1/2" D. Shpg. wt., 2 lbs.

MS-294 Net 4.54

MODEL 2090 UTILITY HOUSEHOLD TIMER

- DEPENDABLE 1 MINUTE TO 1 HOUR TIMING

This reliable, low-priced timer in a neat durable white plastic case has innumerable household timing uses, i.e., cooking, baking, home permanents, games, remembering appointments, TV and radio programs, etc. Attractive modern design. Times any interval up to one hour accurately and gives resonant bell signal at end of period. Large easy to set and easy to read dial. 3 1/2" x 3 1/2" D. Shpg. wt., 1 1/4 lbs.

MS-295 Net 2.90



TELECHRON TIMER SWITCH

Turn on any Appliance up to 1650 watts.

3.95

Genuine Telechron mechanism. Complete 12 hour movement. Can be set to turn on any radio, TV or similar electrical appliance at any preset time. Gold finish dial—black lettering. Timer sets from rear. On-off-auto switch in front. Size 3 1/2" square, 1 1/4" deep. Set shaft extends 5 1/2" to rear. SPST switch, rated 15 amps at 115 volts. For 110-120V, 60 cy. AC only. Shpg. wt., 2 lbs.

MS-793 Net 3.95

NEW! IMPACT DRIVER



SPEEDY! TIGHTENS! LOOSENS!

Ever have trouble loosening a tightly turned, rusty screw, or a screw with the groove deformed? With this device, a small hammer rap is all that is required to loosen any corroded or rusty fastener. The driver will not damage the screw. Can be used to tighten screws also. Complete set consists of the driver tool, an adapter, 3/8" bit, 1/2" bit, No. 2 and No. 3 bit and cam. Comes complete with necessary instructions for use and metal tool case. Shpg. wt., 2 lbs.

HD-971 Net 6.95

LAFAYETTE ENGINEERING & DRAFTING SUPPLIES FOR SCIENCE AND TECHNOLOGY

NEW! LAFAYETTE VECTORLOG™ SLIDE RULE



The Slide Rule for Communications Engineers and Physicists **16.88**

- LAMINATED BAMBOO CONSTRUCTION • P, P', AND Q SCALES — FOR DIRECT VECTOR ADDITION • HYPERBOLIC SINE AND TANGENT SCALES • TWO SINE SCALES—ONE MARKED IN DEGREES, ONE MARKED IN RADIIANS • 5 LOG LOG SCALES PLUS A VOLTAGE DB SCALE • COMPLETE WITH BELT CARRYING LOOP AND LEATHER CASE

The Lafayette VECTORLOG Slide Rule provides a new concept in scientific calculation, incorporating scales and arrangement designed for quick-easy-manipulation. Twenty-seven (27) scales incorporate the many problems encountered in Electrical Engineering and Physics. The unique P, P', and Q scales allow direct right angle vector addition. No longer are several settings required to obtain right angle vector sums—these scales work in the same manner as the C and D for multiplication. The two Hyperbolic Sine and one Hyperbolic D for multiplication. The Tangent Scale, the Voltage db scale, and the five Log Log scales provide maximum coverage of these dynamic fields. VECTORLOG is the result of extensive tests for ease of manipulation. Several of these features are: C and D scales on both the front and back of the rule; Sine scales in both degrees and radians, removing the necessity of bothersome conversion of units; A problem-tested local-necessity of bothersome adjustment screws to allow variable tension on scales; and adjustment screws to allow variable tension on scales. Scales include: (FRONT) Tr-1, Tr-2, P, Q, ST, Sr, S-O, C, D, LLO1, LLO2, LLO3, LL1; (REAR) Sh-1, Sh-2, DF, A, B, Cl, CF, Th, C, O, LL3, LL2, db. With instruction book, leather carrying case, and belt carrying loop. F-686 Shpg. wt., 1 1/2 lbs. Net 16.88

LAFAYETTE'S ENGINE DIVIDED IMPORTED SLIDE RULES



10" LOG LOG DUPLI TRIG SLIDE RULE
• Laminated Bamboo Warp-Free Construction • Complete with Leather Carrying Case


Specially selected, laminated, non-hygroscopic bamboo. Scales machine engraved on white plastic in permanently accurate calibrations. Adjusting screws permit varying tension on slide. 21 scales including C, D and Cl on both sides. LLO and LLO0 scales refer to B scale. All other scales coordinate and refer to D scale. Scales are L, LL1, DF, CF, Cl, C, D, LL3, LL2, LLO, LLO0, A, B, K, Cl, C, D, S, ST, and T. Scale characteristics permit multiplication, division, proportion, inverse proportion, reciprocals, cotangents, squares, square roots, cubes, cube roots, logarithms, tangents, sines, etc. F-341 Shpg. wt., 1 1/2 lbs. Net 10.45



DELUXE LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE


• 25 Scales with 8 Log Log Scales • Extended Range Avoids "Going Off Scale" • Extra P Scale Simplifies Computations • Two Color Scales
10" log log duplex trig slide rule contains 25 scales including 8 Log Log Scales. Troublesome end-for-end resetting is eliminated by extensions of C and D scales. Twin set of Log Log scales run from 1.001 to 100,000 and .999 to .00001, enlarging the scale by one scale length each compared with ordinary log log slide rules. Extra features include P scale which enables direct "readout" of cosine value. Scales include LLO1, LLO2, LLO3, DF, CF, Cl, C, D, LL3, LL2, LL1, LLO0, L, K, A, B, S, ST, T, C, D, D1, P, and LLO. With instruction book, saddle leather case. Overall length is 14". F-428 Shpg. wt., 1 1/2 lbs. Net 15.95

NEW! DECI-LOG™ DELUXE 5" LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE




• Pocket Version of Lafayette's Most Popular Slide Rule • P Scale (Pythagorean) permits direct "readout" of Cosine Values
• Includes Leather Case With Pocket Clip
• 24 Scales Including 8 Log Log Scales **ONLY 6.88**

Designed to answer the demand for a pocket version of our 10" Log Dupli Decimal Trigonometric slide rule (F-428). Contains all the scales of the 10" rule except the "ST" scale. Two color scales—positioned for ease in use and rapid calculations. "C" and "D" scales on both sides of the rule. "P" scale for direct, cursor line reading of cosines of angles. Scales included, front face: LL1, LL2, LL3, DF, D, D1, P, LLO. Back face: LLO, L, K, A, B, S, T, C, boo. Complete with instruction book and leather case with pocket clip. Shpg. wt., 8 oz. F-681 Net 6.88



5" POCKET SLIDE RULE

5" Pocket Slide Rule: Convenient pocket sized slide rule of specially selected and treated bamboo. Will not warp, shrink or lengthen under varying atmospheric conditions. A, B, Cl, C, D and K scales engraved on white plastic surface. Reverse side of slide has standard S, L and T scales. The upper beveled edge of the rule is graduated in m/m to 13 cm. Other edge is divided into 5 inches by 32nds. Only 5 1/4" long over all. Carried easily in any pocket. Shpg. wt., 8 oz. F-340 Net 2.89




TECHNICAL DRAFTING SET

- Center Wheel Adjustment
- Professional Quality

6.59

A fine set of imported nickel plated brass instruments priced far below the usual price for this quality. Contains 6 1/2" self-centering compass, one leg knuckle joint with divider, pencil, pen parts and lengthening bar; 6 1/2" self-centering divider; spring bow divider 4 1/2"; center wheel adjustment with interchangeable needle points; spring bow pencil and spring bow pen, both 4 1/2" with center wheel adjustment and interchangeable needle point; two 5 3/4" ruling pens; extra handle for pen and pencil parts; adjustment tool; lead case and leads; and spare parts kit, all in velvet lined snap closing case. Shpg. wt., 1 1/2 lbs. F-65 Net 6.59

SUPER DRAWING KIT



7.95

- COMPARE OUR PRICE!

Contains all the necessary equipment for drafting, mechanical drawing, designing. Sturdy accurate components. Includes 20x24 1/2" drawing board 24" T square, 10" 30°/60° triangle, 8" 45° triangle, french curve, 12" triangular rule, 6" 180° protractor, 4 pencils, pencil pointer, erasing shield, thumb tacks, and art gum eraser. If purchased separately these components would cost many times our low price. An unbeatable value. Shpg. wt., 10 lbs. F-180 Net 7.95

SPECIAL COMBINATION OFFER

Consists of F-65 Technical Drafting Set and F-180 Super drawing outfit. F-181 Shpg. wt., 12 lbs. Net 13.06

HARD MAPLE PANTOGRAPH



- ENLARGES
- REPRODUCES!

3.75

21" adjustable pantograph—21 different ratios from 1 1/2 to 8. Enlarges, reduces or reproduces drawings—sketches—diagrams—pictures—maps, etc. Most rapid, accurate means of reducing or enlarging to scale. Lacquered highly finished bars are 21" long and 3/4" wide. Heavy metal standard, with bearing eliminates all friction. Chrome plated hardware—ratio thumb screws and nuts. Complete with lead, accessories and detailed instructions. Shpg. wt., 2 lbs. F-158 Net 3.75




GENIAC CYLINDRICAL SLIDE RULE

Uses a new concept in slide rule design to achieve graduations and accuracy of a 66 inch slide rule. May be used to give answers with up to 5 digit accuracy, and quickly solve problems involving multiplication, division, roots, powers, logarithms, proportions, percentages. All-metal construction with plastic coated spiral scales. 1 1/4" diameter and 10" long, collapses to 6", easily carried in a pocket. Almost indestructible, cannot warp. Shpg. wt., 1 lb. F-387 GENIAC Cylindrical Slide Rule Net 9.95

UTILITY DRAFTING SET

- Exceptional Value

Made in Germany of hard rolled, nickel plated brass. All instruments are nested in a fitted, velvet lined case. Contains three side wheel 3 3/4" bow instruments—one a divider, one a pencil and one a pen. All have reversible needle point. 5 1/4" compass with pen and pencil parts—and lengthening bar. 5 1/4" divider with straightening device. 5" ruling pen. Extra handle for use with pen and pencil parts. Capsule with extra leads. Perfect for schools, labs, industrial or wherever precision drawing sets are used. Shpg. wt., 1 lb. F-13 Net 3.10



4" CIRCULAR SLIDE RULE

- Continuous Scales
- Sturdy Construction
- Equivalent to a 10" Rule

2.45

A versatile calculating instrument specially constructed with special chemical resistant, 1/4" thick, plastic, it will not shrink or expand under varying climatic conditions. 12 scales to solve problems involving multiplication, division, proportions, squares, cubes, and all trigonometric functions. Special scales allow direct conversions of angles from radians to degrees. Ideal for quick calculations. With leatherette case. F-382 Shpg. wt., 4 oz. Net 2.45




PROFESSIONAL GIANT BOW

- 6" Size with Center Wheel Adjustment
- Finely Balanced—Professional Type

Professional quality utility set in a fitted, velvet lined case. Made in Western Germany of nickel plated, hard-rolled brass. 6" giant bow has preferred center wheel adjustment. Makes circles from 1/2" to over 10" in diameter. Set includes 6" giant bow, interchangeable pen and pencil parts, extra needle for using bow as divider, handle for use with pen and pencil parts, lead, lead box and repair parts. Shpg. wt., 1 lb. F-44 Net 3.50


NEW "draftette" SKETCH KIT



ONLY 7.80

A completely portable drafting drawing machine permanently mounted in a Vinyl binder (self-locking). A weather protected unit, it can be used for sketching, designing, drawing, and drafting. Great for traveling. Contains a precision portable drafting instrument with a 3x5" scale -180 degree protractor, pad of 50 sheets, drawing-tracing paper 8 1/2x11", all in one compact binder. Does not require tape, or tacks to hold paper in place for use. Only 9x13x11". F-805 Shpg. wt., 2 lbs. Net 7.80

draftette



PORTABLE DRAFTING MACHINE

Enables you to sketch, draw, design, draft, do layouts, diagrams, schematics. Place your creative ideas on paper in a professional manner in your office, home, shop, in the field, while traveling, or in the customer's office or plant. Draftette is constructed of the finest aluminum, satin black anodized to meet Federal specs., with one piece scale and protractor. Gives you all the advantages of a drawing board, T-square, triangle and protractor combined into one compact, rugged, versatile, precision instrument. Completely assembled, ready to use. Draftette with 4x6" scale, 180° protractor on 11x17" drawing board. Shpg. wt., 3 lbs. F-402 Net 7.65

Draftette with 4x6" scale (less board). Shpg. wt., 1 lb. F-401 Net 6.25

Draftette #12-B Senior with 6x9" scale, 360° protractor on 20x26" drafting board. Shpg. wt., 6 lbs. F-738 Net 19.95

Draftette #12 Senior (less board). Shpg. wt., 2 lbs. F-739 Net 15.30

NEW PORTABLE DRAWING KIT



ONLY 2.95

An easy to handle folding portfolio which can be conveniently carried or stored in a desk or briefcase. The kit includes a 12 inch T-square, a 180 degree protractor, a 6 inch French curve, a 4 inch 45/90° and a 4 inch 30/60°, a 50 sheet drawing pad and drawing pencil. Plastic portfolio is 9x13 1/2x1 1/2". All tools are made of crystal clear plastic, which are physically stable and individually housed in separate pockets. Shpg. wt., 3 lbs. F-806 Net 2.95

NEW JET-E-RASE ELECTRIC ERASING MACHINE


1.49

- PORTABLE MOTOR DRIVEN!
- FINGER TIP CONTROL!
- 4 ERASERS—4 COLLETS—2 BRUSHES

Battery operated erasing machine. Designed for convenience—ease and speed in erasing. Battery operation does away with bulky A.C. motors—trailing line cords—danger of shock. Safe enough for children to use. Entire unit—including battery—weighs only 4 oz. Fits the hand as naturally as a pen or pencil. Switch precisely located for finger-tip control. Permanently lubricated, precision bearings assure long, trouble free life. Includes four eraser cores. One soft—two medium hard—one gritty—to cover all erasing problems. Two brushes—one soft—one stiff—for clean up, and four collets that accept both the eraser cores and brushes. Easily replaceable battery is a No. 1 or "C" cell. Supplied with battery. Shpg. wt., 1/2 lb. F-416 Net 1.49

F-424 Kit of two each, erasers and brushes. Net 2.4

3.95




- Versatile Drafting Aid

NEW! "TECNO-SCALE"

Indispensable drafting tool for artists, architects, engineers, students, mechanical draftsmen. Made of non-hygroscopic, bone-white unbreakable plastic. Full 0 to 180° scale. Calibrated in increments of 1° with 5° and 10° divisions. Both scales are 12" long divided to 1/8" and 1/4". Opens the full 180° arc. Simple, positive cam lock. Easily adjusted without changing position on board. Engineered for speed in use and hairline accuracy. Machine beveled edges. Shpg. wt., 1 lb. F-572 Net 3.95

8" PROFESSIONAL DIVIDER




- IMPORTED FROM GERMANY

4.96

Extremely accurate finely made proportional dividers. Basic equipment for draftsmen—architects—engineers—students. Replaceable steel points—in hard, leather covered, felt lined case. Used for proportional reductions and enlargements, copying drawings in enlarged or reduced scale, dividing lines or circles into equal parts, quick solving of difficult measuring problems, finding distances on maps without scales, etc. Flat form-replaceable steel points. Pressure setting. Graduated for lines from 3/4" to 10"—Circles from 6" to 20". Excellent, accurate utility model. Shpg. wt., 8 ozs. F-167 Net 4.96

PROFESSIONAL STYLE OIL PAINT SET



6.77

Comes complete with—11, 2x3/4" tubes of oil paint; jumbo 3x1" tube of zinc white; 5 bristle brushes; 2 bottles linseed oil and turpentine; steel palette knife and cup; 12 1/4x9" wood paint palette; and 12x8 3/8" mounted canvas panel. This complete set is in a sturdy 13x10" wood box. Shpg. wt., 4 1/2 lbs. F-532 Oil Paint Set Net 6.77

COMBINATION: F-532 Paint Set & F-565 Easel Net 9.07

WATER COLOR PAINT SET

12 tubes of assorted color paint; 2 deluxe brushes; water holder; folding palette—all in a sturdy, hinged wood box. Size: 10 3/4" long, 5" deep, 1 3/4" high. Shpg. wt., 2 lbs. F-531 Water Color Set Net 2.25

COMBINATION: F-531 Paint Set & F-565 Easel Net 5.18

ADJUSTABLE OUTDOOR CANVAS EASEL

- For Oil and Watercolor Painting • Sliding Legs
- Sturdy Wood Construction

Adjustable easel ideal for student and amateur artist. Constructed of smooth-finished lightweight wood; braced fittings. Has 3 sliding legs, adjustable tray and canvas holder. Will hold canvas up to 40". Height closed about 28"; open about 43". Shpg. wt., 2 lbs. F-565 Easel Net 3.49

269.50
NO MONEY DOWN

NO MONEY DOWN!

For Science and Technology

LAFAYETTE TELESCOPES



Arcturus

• 454x with Barlow Lens

3" EQUATORIAL REFRACTOR

- Ultra Precise Helicoid Focusing • 7 Coated Eyepieces Plus Barlow Lens • 76.2 mm Clear Aperture
- Most Advanced Equatorial Mount • 25x, 42 mm Finder Scope

79-mm hard coated, air-spaced Fraunhofer achromat of 910-mm focal length with 3" clear aperture, focal ratio of f/12 and resolving power of 1.6". Seven coated eyepieces provide magnifications of 227x, 152x, 101x, 73x, 35x, 18x and 25x through viewfinder. Helicoid focusing by means of a massive wheel and helical gear. Finder Scope, with rack and pinion focusing, features a 1.6 inch clear aperture objective of 500-mm focal length. Micro-motion controls with extended flexible shafts and compression locks in all axes. Accessories include three sunglasses, moon-glass, sun diagonal, two star diagonals, sun projection screen, erecting prism, heavy extensible field tripod, brace, accessory shelf, separate wooden cases for telescope and mount. Shpg. wt., 100 lbs. VIA EXPRESS ONLY. F-385WX Net 269.50

Galactic

• 454x with Barlow Lens

RESEARCH QUALITY 3" EQUATORIAL REFRACTOR

- Viewfinder Scope 25x, 42-mm • 910 mm Focal Length • 76.2 mm Clear Aperture • Micromotion Controls for Declination and Right Ascension • Resolving Power 1.6 • Barlow Lens Included

189.00 No Money Down!

The objective lens is a 79-mm, hard coated, air spaced Fraunhofer achromat with a clear aperture of 76.2 mm (3"). Focal length 910 mm, focal ratio f/12, resolving power 1.6". Seven coated eyepieces provide magnifications of 227x, 152x, 101x, 73x, 45x, 35x plus 25x through the viewfinder. Barlow lens add ranges of 454x, 304x, 202x, 146x, 90x, 70x and 50x. Focusing by means of micro-precise rack and pinion drive. The viewfinder scope has a 42-mm (1.6 in. clear aperture) objective—500-mm focal length—rack and pinion focusing—and will accommodate various eyepieces. Finely calibrated hour and declination circles for rapid finding and setting. Body tube of white enameled aluminum. Accessories include three sunglasses, moon-glass, two star diagonals, sun diagonal, erecting prism, sun projecting screen, extensible field tripod, chain brace, accessory shelf, wooden cabinet. VIA EXPRESS ONLY. F-384WX Shpg. wt., 60 lbs. Net 189.00

Polaris

• 320x with Barlow Lens

2.4" EQUATORIAL REFRACTOR

- Eyepieces for 160x, 88x, 40x, Barlow Lens gives 320x, 176x, 80x • 800 mm. focal length • 62-mm objective • Micromotion adjustments on both axes • Coated optics throughout • Equatorial mount

79.50 No Money Down!

Objective: Fraunhofer-type achromat, hard coated, 62.5-mm., 800-mm. focal length. Collects about 75 times as much light as the naked eye, resolving power 2 seconds, faintest discernible star 10.7 magnitude. Eyepieces are hard-coated Huygenians, 160x (5-mm), 88x (9-mm), 40x (20-mm). Barlow Lens included give ranges of 320x, 176x and 80x. Finder scope is 6x, 30-mm. Tripod head with latitude adjustment. Clamp lever for declination and inclination. Accessories include sunglasses, star diagonal, erecting prism, sun projection screen, field tripod, wooden case. Rack-and-pinion focusing. Heavy plating to prevent rusting. F-342WX Shpg. wt., 30 lbs. Net 79.50
F-391 4-mm. orthoscopic eyepiece for 200x (400x with Barlow Lens) Net 8.95



(A) ZOOM SPOTTING SCOPE

- Any Power from 15X to 30X!
- Ideal for any "Spotting" Need!
- Pan-Head, elevator Tripod

True Zoom action—finger tip control—from 15 power to 30 power. Choose the right power for any "spotting" or viewing need. Brilliant image at any power. 50mm objective, hard coated for maximum light gathering power. Prismatic system greatly reduces length—only 15" overall. Precisely machined, all metal body. Lightweight "scope alone weighs only 2 lbs. May be hand held or used with tripod supplied. Precision fingertip focusing with oversized, milled ring. Aluminum and chrome-brass tripod adjustable from 12" to 18". Locking pan-head swivels and tilts to any angle. Optical train is fully hard coated. Shpg. wt., 5 lbs. F-685 Net 39.95

(B) 30x, 60mm SPOTTING SCOPE

• Coated Optics • Complete With Leather Case
Field of view is 85 feet at 1000 yds. Both front and rear optics are coated. High relative brilliance due to 60mm objective lens. Exceptionally small and light—weighs only 2 lbs, including metal tripod! The perfect companion for shooting—hunting—viewing—naturalists—and hobbyists. Equipped with 1 1/2" tripod and zippered leather carrying case. Shpg. wt., 3 lbs. F-149 Net 16.95

LAFAYETTE BINOCULARS

LOWEST PRICES • HIGHEST QUALITY



17.95

7X 35 CENTER FOCUS



Precise design—quality material—and expert workmanship. All lenses are hard coated—prisms clamped in lightweight alloy frame and body—sealed against dust and moisture—properly collimated and aligned. All are center focus with adjustable right eyepiece. Hard leather case and neckstraps included.

- F-183 7X35 Popular, versatile, all purpose binoculars. For the sportsmen—hunter—bird watcher—vacationer. High luminosity. Compact design. Shpg. wt., 3 lbs. Net 17.95
 - F-184 7X35 Wide Angle. Top performance—highest quality. Almost twice the field of view of ordinary 7x35 binoculars. Spots and holds a moving target faster and easier. Oversize oculars and prisms. Shpg. wt., 3 1/2 lbs. Net 27.50
 - F-164 7X50 Navy style night glasses. Favored for marine use. The choice of professionals because of exceptionally high light gathering power. Superior image brightness. Shpg. wt., 3 1/2 lbs. Net 21.95
 - F-185 20X50 King of the long range. Hunters, mountain climbers, plane spotters, forest rangers—any long distance viewing and observation requirement. Shpg. wt., 4 1/2 lbs. Net 27.50
- Add 10% Fed. Tax to the above prices.

TRU-ZOOM BINOCULARS



39.95

NO MONEY DOWN

• Not a "Vari-Power" One Control Zooms both barrels!
• 7X to 12X—or any Power in Between

• Center Focus—right Eye Adjust—Plus Single Synchronous Zoom Control! • The Perfect Power For Any View!

Sensational Zoom action holds even fast-moving subjects in perfect view. Sight in any subject at 7 power—then Zoom up to 12 power (or any four in between) for closeup viewing. Full 40mm. objective lenses, hard coated achromats. Field of view is 290 feet at 1000 yds. at 12 power (5.5°). Prisms clamped in shock-resistant mounts. Lightweight alloy frame and body. Sealed against dust and moisture. Includes plush-lined, hard leather case and straps. Shpg. wt., 5 lbs. F-793 Net 39.95*
*Add 10% Fed. Tax

STAR SPECTROSCOPE WITH 3 EYEPIECES



- Observe the spectra of magnitudes—1 to 3
- Identify Fraunhofer lines from C to G
- Drawtube focus arrangement
- Fits threads of 25.4mm O.D. and 24.5mm O.D. eyepieces

The Star Spectroscope (Amici-prism type) is excellent for visual observations of the spectra of bright stars, comets, and novae. The dispersion angle between the Fraunhofer C line (wave length 6600 angstroms) and the G line (4300 angstroms) is 9°. The resolution is enough to separate the yellow D lines of sodium. Body is made of black-coated brass. Fits Lafayette telescopes F-342, F-384 and F-385. All in plush-lined case. Shpg. wt., 8 oz. F-569 Net 29.95

ACHROMATIC BARLOW LENS




4.95

- Provides Greater Eye Relief!
- Improves Definition!
- Greater Illumination—Wider Field!
- Makes Any Good Telescope Better!
- Doubles Your Telescope's Power!

The Barlow Lens is a negative (diverging) lens which can increase the range of magnification of any given set of eyepieces. Sharpens definition and reduces image deterioration by permitting use of low-power eyepieces to achieve high magnification. Lafayette's Barlow lens will make any good telescope perform like a much larger one. Fits all Lafayette telescopes except F-330 Explorer. Accepts eyepieces of 24.5mm (.97") O.D. and fits draw tubes of that size. Shpg. wt., 1 lb. F-473 Net 4.95

ASTROGRAPHIC PLANETARIUM



• Locates and identifies all important constellations in our latitudes!
6.95 • Completely portable!
• Exceptionally fine "Star Finder"

Simplifies the study of the basic elements of astronomy. Locates and identifies all the major constellations—stars from the 1st to 5th magnitude—clusters—nebulae—Milky Way in our latitudes. Adjusts for any hour of any day of any month. Includes the mythical constellation configurations. Superimposed celestial equator and ecliptic—Month/Day and Hour Dial—cardinal compass points for viewing direction—"soft-lite" bulb. Includes batteries and instructions. Shpg. wt., 1 1/2 lbs. F-500 Net 6.95

"MICRO'DAPTER"



19.75

• Micro-photography! • Astro-photography!
• Inexpensive—accurate—easy to use • Use any camera/microscope or camera/telescope setup
• Photo-record your observations.

Permits the use of any camera—even movie cameras—with practically all microscopes and telescopes. No need to remove the camera lens. Cross hairs are superimposed on the image for centering. The image is automatically in focus for the camera when viewed in focus through the MICRO'DAPTER. Accessory sleeves permit the MICRO'DAPTER to be used with other than Society size microscopes. The MICRO'DAPTER may be used with any telescope by attaching to eyepieces of 29mm (1 1/2") maximum diameter. Shpg. wt., 1 1/2 lbs. F-506 Net 19.75

LAFAYETTE 14" TRANSPARENT CELESTIAL GLOBE



39.50

- Adjustable Satellite Orbits
- Satellites Travel around Earth Automatically
- Adjustable Sun and Moon
- 80 Constellations

The sphere will illustrate how the sky will appear at any hour—on any date—from any point on earth. With it you can tell time by the stars—learn to tell time by the sky—clearly illustrate and help solve navigational problems. Traces the orbits of man made satellites and finds their overhead positions. Sun and moon positioned by external controls. Artificial satellites automatically circle around the globe. The celestial globe is 14" in diameter with the terrestrial globe centered within. Equipped with horizon ring—time ring—fixed meridian ring—swinging meridian ring—sun and moon pointers—fixed ecliptic—detachable "planet" indicators—universal base—and complete instructions. Shpg. wt., 15 lbs. F-400WX Net 39.50



- (A) AMATEUR ASTRONOMER'S HANDBOOK. Covers the essential characteristics of telescopes and other factors affecting telescopic observation. Treats topics as magnification and resolution of telescopes, aberrations of lenses, types of telescope mountings and drives, micrometers, photometers. 580 pages, illustrated. BK-1455 Postpaid in U.S.A. Net 12.50
- (B) OPTICS AND OPTICAL INSTRUMENTS: AN INTRODUCTION WITH SPECIAL REFERENCE TO PRACTICAL APPLICATIONS by B. K. Johnson. 3rd Ed. Practical applications of optical theory for student, teacher, amateur lens designer, hobbyist. How to construct working models of optical instruments. 224 pp. 5 1/2"x8". Paperbound. BK-817 Postpaid in U.S.A. Net 1.65
- (C) THE SCIENTIFIC AMERICAN BOOK OF PROJECTS FOR THE AMATEUR SCIENTIST by C. L. Strong. Volume of experiments in major areas of science, astronomy, biology, natural sciences, earth sciences, nuclear physics, mathematics, electronics, etc. Measuring metabolism in animals; electric seismograph; magnetic-resonance spectrometer; amateur rocketry. Illustrated. 608 pages. BK-39 Postpaid in U.S.A. Net 5.95
- (D) DISCOVER THE STARS • BUILD A MODEL SATELLITE. Explains Astronomy in simple terms. Illustrated instructions on building a sextant, clinometer, sundial planetarium. Photograph star trails—tell time by stars—latitude, longitude. Discusses radio astronomy—navigation, satellites, etc. Illustrated. 146 pages. 5 1/2"x8". BK-1441 Postpaid in U.S.A. Net .89



17.95

VIEWFINDER 'SCOPES

These are the same fine viewfinders used on Lafayette's refractor telescopes. All have coated, achromatic objectives and eyepieces. Equipped with mounting brackets, and centering screws for collimation.

- (A) 30 mm (1.2"), 6X: Duraluminum tube finished in white enamel. Draw tube focusing. Eyepiece is interchangeable, 24mm (.97") O.D. Single mounting bracket, as shown with the Polaris, F-342. Shpg. wt., 2 lbs. F-629 Net 6.95
- (B) 32 mm (1.6"), 25X: Air spaced objective .500 mm focal lengths. Dual mounting brackets, as shown on the Arcturus, F-385. Suitable for use as a small celestial and/or terrestrial telescope. Duraluminum tube, finished in white enamel. Standard rack and pinion focusing. Chrome plated brass draw tube. 20 mm eyepiece supplied can be interchanged with eyepieces of other focal lengths. Shpg. wt., 8 lbs. F-628 Net 17.95

take a closer look with . . .

Lafayette PRECISION MICROSCOPE



8⁴⁹

FOR THE INTERMEDIATE STUDENT

600X "BI-OCULAR" MICROSCOPE

- NEW-TWIN LENS "BI-OCULAR" TURRET!
- BUILT-IN SUB-STAGE MICRO-LITE!
- 600X-400X-300X-200X-120X-80X!

Bi-Ocular turret permits instant variation of magnification without disturbing subject set-up. Triple objective click-stop turret in concert with 10X and 15X "Bi-Oculars" give six ranges of magnifications. "Micro-Lite" with automatic on-off switch. Dual knob, rack and pinion focusing, 8 1/2" high overall. All optics are achromatic. Ocular lenses are Huygenian type. Includes sub-stage mirror for viewing by reflected light. Dovetailed wooden carrying case and sample slides. Shpg. wt., 5 lbs. Less batteries. F-334

Net 8.49

BA-155 Battery (2 required) Net ea. .095

BI-OCULAR MICRO-LAB KIT: Complete portable laboratory kit. Consists of F-454 Micro Lab Kit, with all accessories and cabinet, F-334 600X Bi-ocular Microscope, 2 batteries and latest edition of "Hunting with Microscope." Shpg. wt., 13 lbs. F-621

Net 16.50



14⁹⁵

NEW! 50X STEREO-SCOPE

NEW! 50X STEREO-SCOPE

- STEREOSCOPIC BINOCULAR MICROSCOPE
- WIDE FIELD—3 DIMENSION VIEW
- VERTICALLY ERECT IMAGE

Indispensable for the examination of surface features of gross objects. Excellent hobby aid for the coin and stamp collector. Prismatic, binocular head with interpupillary adjustment. Ground glass stage, 3 1/4 x 2 3/4". Heavy modified horseshoe base. Overall height 8". Complete with wooden carrying case. Shpg. wt., 5 lbs. F-762

Net 14.95

Earth-Science Combination. Includes 50X Stereo-Scope (F-762) and 96 selected specimens, named, tagged and classified. (Vol. 1 and Vol. II Mineral Teknikits.) Shpg. wt., 8 lbs. F-763

Net 17.76



34⁵⁰

900X MICROBE "HUNTER"

- THE ONLY MICROSCOPE IN ITS CLASS FEATURING GRADE A OPTICS!
- POWER RANGE 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 900X

All of the most needed features for diversified micro-studies. Power range from 25X to 900X in 12 possible combinations. Micro-motion fine focusing—12 complete revolutions. 36mm (plano/concave) mirror. Fixed square stage, 70mm x 80mm. Rotating 5-hole, disc diaphragm. Three Huygenian eyepieces of 5X, 10X and 15X. Four achromatic objectives of 5X, 10X, 40X and 60X. Complete with upright, wooden carrying case. Shpg. wt., 8 lbs. F-338

Net 34.50

F-613 Mechanical stage for above Net 6.95



44⁵⁰

FOR STUDENT RESEARCH

1200X "RESEARCHER"

- 25X TO 1200X IN 12 RANGES
- FULL RANGE FINE FOCUS ADJUSTMENT
- INTEGRAL MECHANICAL STAGE

Closely parallels the "Society" grade microscope. Four Huygenian eyepieces, combine with four achromatic objectives to yield 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 800X, 900X, 1200X. Micro-motion fine focusing adjustment. Spring loaded to prevent objective from driving through slide. 85mm x 85mm stage can be moved in any direction. Sub-stage has rotating, 5 position diaphragm. Complete with set of 5 basic dissecting instruments, 10 slides, pack of cover slips, tube of mounting fluid. Wooden carrying case. Shpg. wt., 10 lbs. F-369

Net 44.50



89⁹⁵

CLINICAL AND ADVANCED ACADEMIC

1500X "MICRO-STANDARD" ADVANCED ACADEMIC MICROSCOPE

- 25X TO 1500X IN 11 RANGES
- INTEGRAL MECHANICAL STAGE
- VARIABLE SUB-STAGE CONDENSER WITH IRIS DIAPHRAGM
- FULL RANGE FINE ADJUSTMENT
- STANDARD SOCIETY SIZE OPTICS - BOTH OBJECTIVES AND EYEPIECES

OPTICAL SPECIFICATIONS: Three Huygenian eyepieces: 5X, 10X, 15X. Four achromatic objectives: 5X, 10X, 40X, 100X (oil immersion). BODY: Monocular tube 140mm long. STAGE: Square stage 95mm x 95mm. Integral mechanical stage. Adjustable in any direction. FOCUSING: Coarse focus with adjustable tension. Fine focus vernier adjustment. Spring loaded safety device prevents objective from driving through slide. SUBSTAGE: Focusing Condenser with variable iris diaphragm. 41mm plano/concave mirror. Overall 12 1/2" high, 6 1/2" deep, 5" wide. Includes fitted cabinet with lock and key, specimen slide, blank slide, bottle of cedar oil. Shpg. wt., 11 1/2 lbs. F-602X

Net 89.95

500X "MICRO-MECH" MICROSCOPE

- BUILT IN MECHANICAL STAGE!
- 100X - 200X - 300X - 500X
- QUADRUPLE REVOLVING TURRET

5⁹⁵



For the student — hobbyist — or budding scientist. Featuring a built-in, micro-drive mechanical stage. Permits the micro-movement necessary to properly examine micro objects. Promotes learning through ease of operation. Four achromatic objective lenses giving magnifications of 100X, 200X, 300X and 500X. Complete with wooden carrying case and slides. Shpg. wt., 4 1/2 lbs. F-357

Net 5.95

"MICRO-MECH" LAB KIT: Consists of F-357 500X "Micro-Mech" microscope and F-454 Micro-Lab Kit, with accessories and cabinet plus latest edition of "Hunting with the Microscope." Shpg. wt., 12 lbs. F-622

Net 13.90

50X-100X "MAGNI-SCOPE JR."

5²⁹



Direct viewing "projection" microscope affords viewing ease to small groups. Less tiring than viewing through a conventional microscope. The image is projected onto a self contained, translucent glass screen. Finger tip control switches from 50X to 100X. Thumb wheel focus for sharp definition. Projects the full colors present in the slide or specimen. Illumination by means of a battery powered, pre-focused bulb. Requires 2 standard flashlight batteries (not included). Overall size 4 1/2 x 3 x 6 1/2". Hooded viewing screen, inclined to 55°, optimum viewing angle. Supplied with bulb and three prepared slides. Shpg. wt., 1 1/2 lbs. F-760

Net 5.29

BA-157 Batteries (2 required) Net ea. .13

MICROSCOPE ACCESSORIES



A. SLIDE PREPARATION KIT. 30 glass slides, 3x1", in container. Slotted for easy indexing. Includes slide covers and vial of mounting fluid. Shpg. wt., 1 lb. F-533

Net .98

B. HUNTING WITH THE MICROSCOPE. How the microscope works. How to prepare and study cultures—set up a microscope zoo and garden—grow micro organism—perform micro surgery. Profusely illustrated with photographs and drawings. BK-1440

Net .89

C. MICRO SLIDE PREPARATION TEKNIKIT™ Seven dissecting instruments. 3 well slides, 22 blank slides, 25 cover glasses, 25 blank labels, blue stain, mounting fluid, pins and descriptive booklet. F-659 in fitted wooden case.

Net 3.49

WELL SLIDE TEKNIKIT™ 6 single well slides, 6 double well slides, all 3x1". 20 cover glasses, vial of neutral red solution. Shpg. wt., 8 ozs. F-691

Net 1.29

E. DISSECTING TEKNIKIT™ 2 scalpels, spatula, 2 dissecting needles, 2 dissecting forceps, blowpipe, magnifier, scissors, pins. In fitted case. Shpg. wt., 1 lb. F-451

Net 3.79

D. SR. DISSECTING TEKNIKIT™ All above plus 6" probe with eye, fine scissors, 2 cc syringe, slip on needle, large fitted case. F-450 Shpg. wt., 1 1/2 lbs.

Net 5.49

F. MICRO-SLIDE STAINING TEKNIKIT™ Each vial is a "dropper" type for direct application of stain to specimen. Kit consists of one vial each of Safranin, Methylene Blue, Fuchsin, Gentian Violet, Eosin and First Green. Complete detailed instructions. Shpg. wt., 8 ozs. F-605

Net 1.79

ADVANCED STAINING TEKNIKIT™ Three additional dyeing fluids. For staining blood smears, spirochaetes, bacteria, etc. With instructions. Shpg. wt., 6 ozs. F-624

Net 1.69

G. MICROSCOPY TEKNIKIT™ Contains equipment for collecting — fixing — dyeing — dehydrating — clearing — mounting — finishing — labeling — drying and storing subjects. 24 1x3" slides, cover slips, labels, tweezers, scalpel, dropper,

probe, rod, 2 collecting vials, 2 small dishes, 4 bottles of dehydrating fluid (70%, 80%, 90%, 100% alcohol), bottle of acid alcohol, xylol clearing fluid, Gates' fixing fluid, Canada balsam mounting fluid, 2 vials of dyeing fluid (acid fuchsin and gentian violet). With detailed instructions. Shpg. wt., 2 lbs. F-604

Net 3.95


H. MICROLITE. Provides a bright, evenly lighted field of view. Adjustable for transparent or opaque specimens, direct or indirect illumination. Invaluable where oblique light is necessary. Operates on 110-120 volts AC/DC. Self contained switch, cord and plug. Lamp is 5 1/2" long. Stand is 5 1/2" high. Shpg. wt., 1 lb. F-288

Net 2.95

J. SUBSTAGE "MICRO-LUMINATOR". Mounts in mirror forks of 35 to 40 mm (1 1/4" to 1 3/8"). Mirror forks of other sizes are readily spread or compressed to fit. Blue filter glass corrects light to proper color for micro-illumination. Complete with 5 1/2 ft. cord, plug, switch and spare bulb. For 110-120V. AC/DC. Shpg. wt., 8 ozs. F-612

Net 2.89

TEKNIKIT™ SLIDE LIBRARIES



- 72 Different Slides
- 6 Volumes of Subjects
- Reference Set for Serious Students

A 72 specimen library of slides carefully pre-selected to maintain continuing interest in microscopy. Consisting of 6 correlated series of subject matter in biology, zoology and botany. Each specimen is cultivated, cleaned, dissected, embalmed, stained, mounted, labeled and covered for permanence. All are large (1x3") size. Ideal ready-reference for the science-hobbyist. Shpg. wt., 2 lbs. F-803

Net 7.50

SR. Slide Library. 120 slides, all above plus bacteria, cell structure, blood structure, micro-organisms and animals. Total eleven volumes. Shpg. wt., 3 1/4 lbs. F-804

Net 11.90

MICROSCOPE MECHANICAL STAGE

6⁹⁵



- WITH GRADUATED SCALES
- VERNIER TO 1/10th mm

Attaches to any square microscope stage 70 mm x 80 mm or larger. Accommodates slides up to 75 mm x 50 mm. Both lateral and front-to-back movement by rack and pinion. Adjustment scales are graduated in single millimeters with verniers reading to 1/10th mm. Essential accessory for all high magnification examination. Permits relocating any portion of a slide or charting the entire slide. Spring clip automatically accommodates slides of varying dimensions. Shpg. wt., 12 ozs. F-613

Net 6.95

MICRO-SLIDE TEKNIKIT™



AS LOW AS 89¢ PER SET

- SPECIALLY SELECTED MICRO-SUBJECTS
- ADD TO THE ENJOYMENT OF YOUR MICROSCOPE

Specially selected slides of universal interest. Slides are professional size. Set includes 12 prepared slides and slotted, covered box for filling and storing. Shpg. wt., 8 ozs.

F-123 Parts of Insects	Net 1.49
F-124 Spiders, Disease Carriers	Net 1.69
F-125 Tiny Creatures	Net 1.59
F-126 Sea Life	Net 1.39
*F-128 Structure of Blood	Net 1.15
F-130 Life cycle of Insects	Net 1.59
F-131 Bacteria	Net 1.79
F-132 Sea Life, Plankton	Net 1.59
F-134 Micro-Animals	Net 1.29
F-135 Micro-Organisms	Net 1.29
*F-136 Substance of Cells	Net .89
*—Set of 6 Slides	

MICROTOME TEKNIKIT™

10⁹⁵

- Sections to 10 Microns (0.00039 inch)
- Micro-Pitch Screw Drive



Essential tool for free hand sectioning of biological specimens. Equally suitable for the serious hobbyist and student as well as lab applications where the accuracy of a hand operated feed is sufficient. The micro-fine pitch screw feed is graduated in 10 micron intervals. The dense, composition stage is absolutely flat, 75 mm in diameter. "Straight razor" type micrometer knife of surgical quality steel. Ground and tempered to take and hold a keen cutting edge. Supplied with microtome knife, pitch and compartmented wooden storage cabinet. Shpg. wt., 2 lbs. F-603

Net 10.95



8⁸⁰

MICRO-LAB TEKNIKIT™

A carefully preselected assortment of the most often used lab items for biology, botany, anatomy, zoology, microscopy, etc. Perfectly complements the many inexpensive microscopes already in use. The instruments and accessories are of excellent quality. The cabinet will accommodate any microscope of no more than 8 3/4 x 5 3/8" overall (such as our F-334 "BI-OCULAR" and F-357 "Micro-Mech") and contains the following accessories: 15 slides, slide labels, slide covers, vial of balsam, dissecting scissors, probe, scalpel, tweezers, spatula, applicator rod, eyedropper, magnifier, 5 test tubes with stoppers, 6 laboratory jars, alcohol burner, polishing cloth. All in fitted drawers. Shpg. wt., 7 1/2 lbs. F-454

Net 8.80

POLAROID® PICTURES IN ONLY 10 SECONDS

POLAROID® J-66

Completely Automatic Electric Eye Camera

• Everybody's Camera—If You Can Aim It, You Can Get The Picture! • Automatic—No Need To Focus! • Automatic—No Need To Set Speed! • Automatic—Nothing To Set! • Plus—A Built-in Flash Gun • More Camera For Less Money Than Ever Before • Postcard-size Pictures in 10 Seconds




NO MONEY DOWN
79⁹⁵

The Newest—SIMPLEST—Polaroid Electric Eye Camera. Nothing to set—nothing to focus—just aim and shoot—and 10 seconds later you have a perfect picture! Where "flash" is needed, the built-in bounce flash gun fills the bill! Automatically indicates when light is low. Takes close ups as near as 3 ft. Always in focus—even a mile away! Automatic shutter speeds to 1/1000. Built in flash gun uses AG-1 bulbs. F-710 Shpg. wt., 10 lbs. Net 79.95

Complete J-66 Kit—includes J-66 camera, new carry-all cowhide case, 2 picture rolls of 3000 speed film and 12 AG-1 flash bulbs. F-711 Net 95.88

NEW! POLAROID® J-33 ELECTRIC-EYE CAMERA KIT



74.95

NO MONEY DOWN
Complete J-33 KIT

Now—the least expensive Land Camera on the market... the Polaroid J33. Easy to use as one, two, three... in fact you just press 3 buttons, pull the tab, and ten seconds later you have the picture. Nothing to set, nothing to focus. Everything is sharp from 4 1/2 ft. to miles away, in bright sunlight, shadow and almost dark. One easy adjustment for closeups up to 32 inches. Built-in bounce flash uses tiny AG-1 bulbs. Offers all of the automatic features of the J66 in a smaller camera. Picture size 2 1/2" x 3 1/4". Kit includes J-33 camera, fitted carrying case, roll 3000 speed film, 12 AG-1 flashbulbs. F-821 Shpg. wt., 13 lbs. Net 74.95
F-820 J33 Camera only. Shpg. wt., 8 lbs. Net 64.95

EXCELLENT VALUE! POLAROID®

Electric Eye Camera Kit


10 Second Pictures!
143³³
Truly Eliminates Guesswork!

NO MONEY DOWN
The 850 Complete KIT

Polaroid's Finest, moderately priced, electric eye camera kit. Automatically sets the correct lens opening and shutter speed for every picture—indoors, outdoors, everywhere! Takes and makes pictures in sunlight—shade—or lamplight without changing your lens or shutter setting! The kit includes the model 850 camera; repeating wink-light; new slim-line case for camera and all accessories; 2 rolls of type 47, 3000 speed film; one packet of "postcarders"; and 2 "write-in" albums. The 850 camera features a coupled rangefinder; parallax—corrected viewfinder; synchronization for electronic flash, regular flash and wink-light; all die-cast body. Makes pictures 3 1/4" x 4 1/4". Shpg. wt., 12 lbs. F-706 Net 143.33
F-707 #850 Camera Only, Shpg. wt., 6 lbs. Net 116.66



The Incredible POLAROID® 900 Electric Eye Camera



NO MONEY DOWN
127⁷⁷

Leader of Land Cameras, Model 900 automatically sets the correct lens opening and shutter speed for every picture—indoors, outdoors. The tiny micro-eye, used with the wink-light, will make pictures anywhere indoors, day or night, without flashbulbs. Take pictures outdoors in the sun or shade up until dusk. In bright sunlight you no longer even have to focus. The shutter operates at speeds approaching 1/1000th sec.—fast enough for action. Illuminated projected-frame viewfinder shows exactly what your picture will include. The coupled rangefinder is right in the viewfinder window—the same control sets both. Synchronized for regular and electronic flash. Three-element lens is coated on all surfaces and color corrected. Picture size: 3 1/4" by 4 1/2"
F-708 Shpg. wt., 7 lbs. Net 127.77

COMPLETE MODEL 900 CAMERA OUTFIT
The complete kit includes the 900 camera, fitted case, wink light, 2 type 47 picture rolls, 1 pkg. of postcarders and 2 write-in albums. F-709 Shpg. wt., 12 lbs. Net 157.50

POLAROID CAMERA ACCESSORIES


PICTURE ROLLS 10 SECOND DEVELOPING TIME

32 and 42 are panchromatic types with an exposure index of 400 and 200 respectively. 37 and 47 have index ratings of 3000 and are used with the wink-light for indoor shots at normal room lighting levels. Shpg. wt., per roll, 5 ozs.

Stock #	Type	Camera Model	Net Per Roll	Net ea. in Lots of 3
F-712L	47	All Except 80 Series, J33	1.89	1.80
F-713L	42	All Except 80 Series, J33, J66	1.77	1.68
F-714L	37	80B, 80A, 80, J-33	1.48	1.40
F-715L	32	80B, 80A, 80	1.38	1.30

POLAROID CAMERA ACCESSORIES

PRINT COPIER 24.95



Make copies of your favorite Polaroid pictures at home in seconds. Fit your Polaroid camera to the copier—insert the picture—and make your copy! You can even improve over the original picture. Shpg. wt., 7 lbs.

F-719L for 80B, 80A, 80	Net 24.95
F-720L for 110B, 110A, 110	Net 24.95

POLAROID CAMERA ACCESSORIES

WINK-Light 14.75



Compact, automatic "fill-light". Companion to 3000 speed film—permits indoor pictures at night in ordinary room light. Clips to camera—"winks" automatically when shutter is snapped. Shpg. wt., 2 lbs.
F-716L Model 250 for all except 95A, 95B, 100, 700 Net 14.75
F-717L Model 252 for 95A, 95B, 100, 700 Net 14.75
NOT Needed for J66, J33

POLAROID CAMERA ACCESSORIES

CLOSE UP KIT 7.25



Focus as close as inches from your subject. Take portraits—small still lifes—do photocopying. Includes 3 snap-on close up lenses, leather case and built in tape for accurate focusing. Shpg. wt., 8 ozs.

F-721L for all except 110B, 110A, 110, J33, J-66. Net 7.25

Draft-a-Plan Kit

- Learn Use of Professional Drafting Tools
- Complete, Easy-to-Follow Instructions
- Includes Electric Drafting Desk



Make exciting drafting plans and blueprints without chemicals. Learn how to make your own scale drawings plus basic lettering, sketches, perspective drawings and layouts. "Drafting is Fun" book and design project sheets educate in each drafting instrument. Kit includes tracing and blueprint paper, drafting pencils, pencil sharpener, T square, triangles, French curve, scale, protractor, slide rule with instructions, electric drafting desk with lamp. F-817 Shpg. wt., 6 lbs. Net 7.49

Custom-Styling



Design your own boats, auto, planes and space vehicles. Stimulates interest in designing, encourages imaginative development of line, form, perception and color. Kit includes directions, portfolio, interchangeable component and design sheets, drawing paper, color pencils with sharpener, eraser, electric drawing desk with lamp. F-818 Shpg. wt., 5 lbs. Net 5.98

Draw-a-Cartoon



Provides hours of exciting fun drawing colorful comic strip or story characters. Cartooning sheets with dozens of funny heads, eyes, ears, noses and costumes, are reversible and interchangeable—draw and color any cartoon, any way. Kit contains directions, character and story idea sheets, portfolio, drawing paper, color pencils and sharpener, eraser, electric cartooning desk with lamp. For 5-year olds and up. F-819 Shpg. wt., 5 lbs. Net 5.98

SUPER SPACE SPIDER® KIT

- Educational and Creative in Mathematics, Geometry, 3-Dimensional Space and Occupational Therapy
- Fun for Ages 8-80



5.95

Contains 12, black, notched 6" square panels to assemble 4 perforated corners; 12 bobbins of special elastic string; instruction book; 40 black clips; blunt needles; complete instruction manual for basic weaving designs. Possible uses of the spider kit are limited only by your own creative ability. AP-58 Shpg. wt., 3 lbs. Net 5.95


SINGLE SPACE SPIDER KIT.

Similar to above but with 3 panels, 3 bobbins of string, instruction book, 10 black clips and blunt needles. Makes one corner. AP-57 Shpg. wt., 1 lb. Net 2.95

SUPER SPACE RING® KIT

- Visual Tool for Teacher and Student
- Teaches Spatial Geometry
- Unlimited Design Potential

ONLY 5.95



Opens up the entire field of spatial geometry and mathematics. Consists of 8 specially contoured and perforated aluminum rings, 4 bobbins of metallic elastic cord, 3 bobbins (45-yds.) of fluorescent cord, design suggestions, 22" diameter mobile wire hoop, adhesive ceiling hanger, instructions. AP-60 Shpg. wt., 1 1/2 lbs. Net 5.95


SINGLE SPACE RING® KIT

Similar to above but with 4 rings, 4 bobbins metallic cord, 30 yards fluorescent cord, hoop, hanger. AP-59 Shpg. wt., 12 oz. Net 4.95

NEW MIRACLE Astro-Phone

Talk on an Invisible Beam of Light

- Sends Voices Hundreds of Yards
- Self-contained, Transistorized Sender/Receiver
- Use Day or Night, Indoors or Out



2250
Per Pair



Now you can project your voice hundreds of yards, without wire, even through glass and around corners with mirrors. With the amazing Astro-Phone you just aim and talk... indoors or out... day or night... anywhere, anytime. Absolutely private, tap-proof, jam-proof line of sight communication. Each unit sends and receives. All-transistor amplifiers ready for instant use. Absolutely safe. Housed in unbreakable, high-impact styrene. Operated by 3 ordinary flashlight batteries (included). AP-65W Shpg. wt., 5 lbs. Net, per pair 22.50
BA-157 Extra Batteries, Burgess #2 (6 req.) Net each .13

LAFAYETTE DIRECT IMPORTS Compare for VALUE!

TESTED AND SELECTED FOR CONSISTENT QUALITY

35mm "RANGEFINDER III"



NO MONEY DOWN
28⁸⁸

4 ELEMENT F2.8 COATED LENS! • COUPLED RANGEFINDER

- LUMINOUS BRIGHT FRAME VIEW-RANGE FINDER!
- SINGLE STROKE RAPID FILM TRANSPORT!
- NINE SHUTTER SPEEDS TO 1/300!
- MX SYNCHRONIZATION
- F2.8 45mm COATED LENS!
- HI-SPEED REWIND!
- STANDARD PC FLASH TERMINAL!
- DOUBLE EXPOSURE PREVENTION
- BUILT-IN SELF TIMER!

Check the features — then compare Lafayette's price with any other brand. Fast 2.8 coated anastigmat lens and extra-wide lens aperture for brilliant, sharper color or black and white even in poor light. Sight and focus through coupled range-view finder. Fully synchronized at all speeds for class M and electronic flash. Speeds from 1 sec. to 1/300th. Rapid advance sets shutter, counts exposure and transports film. Built-in delayed action timer — automatic exposure counter and film stop. Hi-speed rewind with folding lever. Standard accessory shoe. All metal body with brushed chrome trim—black leatherette covering. 20 or 36 exposures on black and white or color 35mm film. PC flash terminal. Expertly made in Japan. Shpg. wt., 3 lbs. Use series 6 accessories.

F-778L Less Case Net 28.88
F-778L Case Net 3.95
F-779L Leather Eveready Case. Shpg. wt., 1/2 lb. Net 15.96
Auxiliary Wide Angle and Telephoto Lens Set for "Rangefinder III." F-808L Shpg. wt., 1 1/2 lbs. Net 3.39
Optical viewfinder for Wide Angle and Telephoto Lenses. F-647L Shpg. wt., 6 ozs. Net 14.95

MATCHED FILTER AND HOOD SET

Includes Type "A" conversion, "F" conversion, "80B" photohood, adapter ring and lens hood. Complete with leather case with room for additional filters.

F-781L Shpg. wt., 8 ozs. Net 14.95
Special Combination Offer: Includes camera above—Eveready case—folding BC flash gun—and clip-on exposure meter. Shpg. wt., 4 lbs. Net 38.95
F-780L

NEW! TRANSISTORIZED ELECTRONIC STROBE FLASH



Operates from Batteries and AC

24⁹⁵

NO MONEY DOWN

• Lightweight & Compact—No Power Pack Needed • Fully Transistorized • Operates on 4 Economical "Z" Cell Batteries • Fits any Camera Shoe

Now you can have a high-powered, transistorized electronic flash that operates from standard AC house current or 4 economical "Z" cell batteries. Compact and featherweight—no power pack is required. Flash duration of 1/2000 sec. for fast pictures. Recycling time: 6-10 seconds; color temperature: 6000° Kelvin. Guide number dial for F stop on back. Complete with AC cord. Less batteries.

F-807 Shpg. wt., 2 lbs. Net 24.95
Batteries for above (4 required). BA-155 Net each .095

AUTO-DIAL EXPOSURE METER


Holds its reading indefinitely. Meter is aimed and dial stopper depressed, the dial then swings to correct reading and remains fixed when stopper is released. Ideal for widely variant light conditions. Color and black and white calibration with ASA speeds to 25,000. Reflected and incident light read on same scale. EVS 1 to 19. Lens: f/1.0 to f/32. Direct reading cine speeds 8-64 fps. Meter has zero adjust. Leather carrying case and neck strap.

6.75



F-791L Shpg. wt., 1 lb. Net 6.75

35MM LAFAYETTE "ELECTRICK 2.8"



NO MONEY DOWN

49⁹⁵

• Automatic Exposure Control
• Built-in, Cross Coupled, Exposure Meter
• Match The Pointer—Focus and Shoot!
• Coupled Rangefinder

Perfect exposure every time is assured by the cross coupled photoelectric exposure meter; merely set shutter speed and ASA film speed, aim camera, and line perfect exposure at any speed. Superimposed coupled range finder with automatic parallax correction enables accurate focusing from 2.5 ft. to infinity on the f2.8 coated anastigmat lens. Shutter features speeds from a full second to 1/500, MX flash synchronization, and a self timer. Fast-action film advance cocks shutter, or black-and-white. Made in Japan to Lafayette's own specifications.

F-656L Leather Eveready Case Shpg. wt., 3 lbs. Net 49.95
F-656L Case Shpg. wt., 1/2 lb. Net 4.95
Auxiliary Wide Angle and Telephoto Lens Set for "Electrictick 2.8." F-809L Shpg. wt., 1 1/2 lbs. Net 15.96
Optical viewfinder for Wide Angle and Telephoto lenses. F-647L Shpg. wt., 6 ozs. Net 3.39
Folding BC flash gun. With battery and leather case. F-209 Shpg. wt., 1 lb. Net 3.99

LAFAYETTE AG FLASH GUN

• Compact in Size
• Made for the New AG Bulbs



The new Lafayette AG flash gun is a compact, palm size yet offers dependable B-C operation. Made for the new AG flashbulbs which are small in size and big in performance. The Lafayette flash gun has a fan-type reflector which measures 2" in diameter when opened. Standard shoe fits all standard accessory clips. Features a Computer Dial for determining correct F stop, Testlight for checking battery and bulb, and Bulb Ejector. Complete with cord. Operates on 15V battery (not incl.). Shpg. wt., 8 ozs.

F-699 Net 2.99
BA-116 15-Volt Battery for above Net .81

MANSFIELD 300 WATT 35MM PROJECTOR

Self Contained

• Brilliant 300 Watt Blower Cool
• 4 Inch, F2.8 Coated, Corrected Lens
• Designed for Easy Operation

28.95
NO DOWN PAYMENT

• For All 35 mm, 2 x 2 and Super Slides

Compact, convenient, semi-automatic, plus big-picture, 300 watt brilliance. Takes all 2x2 inch slides—35mm 828 (bantam) and 127 (super-slides). Semi-automatic "Presto-Matic" changer, one push-pull movement picks, shows and replaces 36 slides in sequence. Self-contained storage for over 100 slides. Die cast aluminum. Self-contained case. All optics hard coated. Designed for optimum projection brilliance. For 110-120V. AC/DC. Shpg. wt., 12 lbs. Net 28.95
F-667

PROJECT-A-SCOPE

• Projects Giant Pictures in Color Or Black and White Without Films or Negatives
• For Lectures — Study — Classroom or Just Plain Fun!

5.95

Amazingly versatile! Delightfully simple! Adjustable professional lenses. Just place it over anything flat—magazines, books, photos, drawings, coins, stamps, documents, maps, natural objects—and see a brilliant giant enlargement projected on any white wall or screen in glowing true-to-life color or black and white. A boon to students, artists, collectors, lecturers, demonstrators. Children can project their favorite comics or story books to amuse themselves and their friends. Molded of heat resistant, hi-impact polypropylene. Rigid transparent base, flattens and protects photos, prints and stamps. Uses ordinary household bulbs. U/L Approved 110V. AC/DC. Shpg. wt., 2 lbs. F-694 Net 5.95

ELEVATOR TRIPOD

• Folds to 16" including Panhead!
• Extends to 47" PLUS 7" Elevator!
• Tri-Tilt head — Moves in 3 planes!

8.59

For any small camera—35 mm—reflex—or movie. Professional quality for professional results. Strong—steady—lightweight. Pencil slim, chrom plated, brass legs. Lock securely in place—fold down readily. Single action tilt-pan—and swing over for taking pictures in vertical or horizontal format. Geared elevator center-post with positive lock and folding crank. Weighs only 31 ozs. All the most wanted features in one tripod. Shpg. wt., 2 1/2 lbs. F-339 Net 8.59


MATCHED 35MM CAMERA OUTFIT

Complete, ONLY **65.95**



A complete 35mm camera outfit for indoor and outdoor picture taking, in color or black-and-white. You get \$16.26. You get: Lafayette "Electrictick 2.8" 35mm camera with automatic exposure control (F-655L); leather carrying case for the camera (F-656L); transistorized electronic strobe flash that operates on batteries and (F-807); 4 batteries for the flash (BA-155); roll 35 Kodachrome film with processing (F-581L). F-810L No Money Down. Shpg. wt., 6 lbs. Net 65.

GENUINE LEATHER GADGET BAG



4.95


Genuine pigskin—not plastic. Full 10x8x4". Holds your camera and all accessories. 20" zipper top. Pouch in lid holds filters, etc. Outside pouch with strap and buckle. All brass hardware. Loops and straps on bottom to hold tripod. Includes shoulder strap and pad. Shpg. wt., 1 lb. F-320 Net 4.95

LAFAYETTE "SPEEDLITE"

ELECTRONIC PHOTOFLASH SYSTEM

• 110V AC or MIDGET BATTERY PACK
• COLOR BALANCED LIGHT
• 35 WATT SEC. OUTPUT
• BUILT IN DIFFUSER
• SUPER POWERED
• FEATHERWEIGHT


25.95
NO DOWN PAYMENT



Thousands of flashes from one lifetime tube—less than 1/2 cent per flash. Coiled cord extends 5 ft. Universal bracket fits any camera with a tripod socket. Gun also mounts on side of portable pack. Light is balanced (6200° Kelvin) for color pictures. Kodachrome guide 25-Tri-X guide 120. Recycles in 6 to 7 seconds. Speed 1/1000 sec. flash duration. Socket for extension or multiple flash use. For any camera having X (zero delay) synchronization. Complete with battery, portable pack, 5 ft. coiled cord, shutter cord, 15 ft. A.C. cord, mounting bracket, clamp and instruction book. Shpg. wt., 4 lbs. F-370 Net 25.95
Replacement Battery for above. Shpg. wt., 1 lb. BA-13 Net 4.50

KODAK FILM WITH PROCESSING INCLUDED

• Slides Returned Mounted, Ready for Viewing or Showing!
• Rigid Processing Controls Assure highest Quality
• Convenient, direct-mail "mailers" in every roll
• A full number of Prints guaranteed for Kodachrome and black and white.



You get factory-fresh film plus a convenient direct-mail maller. After the complete roll has been filmed, put it into the maller, drop into a mailbox and in a few days your finished films are delivered postpaid to your door. You get 3 1/2" square or 3 1/2x5" giant prints with Kodachrome and Black & White—and a full number of prints is guaranteed. Should you get less than the full number of prints of Kodachrome or Black & White printable negatives per roll, you will receive coupons for additional FREE prints. DO NOT MAIL FILM TO LAFAYETTE RADIO.

KODACHROME COLOR MOVIE FILM

Stock No.	Description	Net	Net ea. ea. lots of 6
F-575L	8mm, 25 ft. roll, Daylight	3.55	3.40
F-576L	8mm, 25 ft. roll, Indoor	3.55	3.40
F-577L	8mm, 25 ft. Mag., Daylight	4.60	4.42
F-578L	8mm, 25 ft. Mag., Indoor	4.60	4.42

NEW! KODACHROME II COLOR MOVIE FILM

- 2 1/2 Times Faster; ASA Index Daylight 25, Indoor 40

F-794L	8mm, 25 ft. roll Daylight	4.49	4.22
F-795L	8mm, 25 ft. roll, Indoor	4.49	4.22

KODACHROME 35mm COLOR SLIDE FILM

F-580L	35mm, 20 Exp. Daylight	2.98	2.85
F-581L	35mm, 20 Exp. Indoor	2.98	2.85
F-582L	35mm, 36 Exp. Daylight	4.38	4.20
F-583L	35mm, 36 Exp. Indoor	4.38	4.20

NEW! KODACHROME II 35mm COLOR SLIDE FILM

• ASA Index Daylight 25, Indoor 40.			
F-796L	35mm, Daylight, 20 Exp.	3.59	3.39
F-797L	35mm, Daylight, 36 Exp.	5.49	4.98

KODACOLOR COLOR SNAPSHOTS

F-584L	127 Indoor/Outdoor	3.72	3.56
F-585L	120 Indoor/Outdoor	3.72	3.56
F-586L	620 Indoor/Outdoor	3.72	3.56

KODAK BLACK & WHITE ROLL FILM

F-587L	127 Verichrome Pan	1.28	1.17
F-588L	120 Verichrome Pan	1.28	1.17
F-589L	620 Verichrome Pan	1.28	1.17
F-590L	35mm, 20 Exp., Plus X	2.32	2.24
F-591L	35mm, 36 Exp., Plus X	3.45	3.35

BOOSTER EXPOSURE METER

• Includes booster—Leather cases—neck cord
• Stills or Movies • ASA Scale—LVS Scale

6.45

WITH BOOSTER

Extremely versatile—extremely simple. Highly legible direct reading dial. Speeds from 4 sec. to 1/1000 sec. Lens aperture settings from f:1 to f:32. ASA scale 6 to 800. LVS scale 1 to 18. Cine scale 8, 16, 24 and 32 frames per second. Booster cell makes possible readings at extremely low light levels. Small-rugged-lightweight. Includes booster cell, leather cases, neck cord and instructions. Shpg. wt., 1 lb. F-349L Net 6.45

"35" CLIP-ON EXPOSURE METER

3.95

• FITS CAMERA ACCESSORY SHOE
• ASA SCALE 10 TO 1000
• MEASURES REFLECTED AND INCIDENT LIGHT

Exceptionally convenient exposure meter. Clips right on camera—quick easy reading. Gives better, more accurately exposed pictures with a minimum of effort. Speeds 1/1000 to 1 Sec. Lens aperture f:1.4 to f:22. Mounts on camera or may be hand held. Complete with leather case and instructions. Shpg. wt., 1/2 lb. F-351L Net 3.95

LAFAYETTE CAREER-BUILDING SCIENCE SETS



NEW! LAFAYETTE'S SUPER-TROL R/C EQUIPMENT RADIO CONTROL TRANSMITTER • MEETS FCC REGULATIONS

Assembled—tested—guaranteed. Crystal controlled with .01% tolerance crystal as per FCC regulations. Uses powerful 3A5 tube for range of approximately one mile. Will operate any 27.255 MC R/C receiver. Overall dimensions only 8 1/2 x 2 3/4 x 1 3/4". A neat little handful! Includes antenna, tube, crystal with FCC approved tolerance, and instructions. FCC license applications enclosed — no examination required. Less batteries. Shpg. wt., 2 1/2 lbs.

F-249 Net 14.95
BA-124 Batteries Burgess U30 (3 Needed) 1.75 ea.
BA-157 #2 Batteries (1 Needed) .13 ea.

14.95



RADIO CONTROL RECEIVER

8.95

RADIO CONTROL RECEIVER: Completely wired and tested receiver—extremely sensitive and stable. Completely enclosed—ideal in boats—or case may be removed if desired. Ingeniously constructed to withstand vibration and shock. Features external fine tuning—antenna "snap" lead—plug for power and actuator connections. Ideal Companion for F-249 Transmitter and F-327 Servo shown elsewhere on this page. Requires one 1.5V battery and one 67.5 Volt battery. Size determined by use. Measures only 3x2 1/4 x 1 1/2". Complete with tube and instructions. Less batteries. Shpg. wt., 8 oz.

F-208 Net 8.95
BATTERIES REQUIRED:
BA-5 LAFAYETTE (1 needed) 1.29
Burgess No. 2 (1 needed) BA-157 .13 ea.

SPECIAL COMBINATION OFFER

Consists of R/C Transmitter (F-249), and R/C Receiver (F-208) F-259—Combination 22.90

"DOUBLE" NEW! GENIAC®



Reg. 19.95

Over 800 Parts **15.95**
For Schools Science Fairs
Advanced Experimenters.

- Computes • Reasons • Plays Games
- Composes Music • Forecasts Weather
- Design Your Own Computers

The newest kit in famous Geniac® series! The "Double" Geniac contains over 800 parts. Two of everything in the Standard model. Offers the advanced experimenter a far wider range of activities. Perfect for school demonstration. Multiple setup is ideal for Science Fair projects—submit one or more designs. Build "electric trains" that test intelligence—code and decode—add, subtract, multiply and divide—solve puzzles—play games—forecast weather—reason in syllogisms—information and logic circuits. No soldering required. Easily assembled and operated. 64 page guide and reference book, beginners manual, wiring diagrams and many extra pamphlets outlining projects and methods. Complete with mounting rack and batteries. Shpg. wt., 12 lbs.


KT-176 Net 15.95

Standard GENIAC

COMPUTES, REASONS, PLAYS GAMES
COMPOSES MUSIC FORECASTS WEATHER
DESIGN YOUR OWN COMPUTERS
OVER 400 PARTS & COMPONENTS **9.95**

You build up to 125 exciting "electric brain" machines. Has special circuits for forecasting weather. No soldering required. Comes complete with extra pamphlets including 64-page "Simple Electronic Brains and How To Make Them", "Symbolic Analysis of Relay and Switching Circuits", "Beginner's Manual, Machine to Compose Music, Wiring Diagrams, etc. Complete with battery. 16 1/2 x 11 1/4". Shpg. wt., 6 lbs.

KT-175 Net 9.95



PHYSICS LAB

- Professional Laboratory Equipment
- Provides Real Stimulus for Serious Study
- Answers Questions about Everyday Physics
- Hours of Endless Fun

10.98

A popular physics lab set, chock-full of laboratory equipment offering fascinating experiments in solar heat, light bending, optics, fluid dynamics, and scores of others. The equipment includes professional radiometer, parabolic reflector, polarizing filters, optical bench beaker, illuminator, thermometer, ring stand and many related pieces. Colorful instruction manual teaches basic principles of physics and gives step-by-step procedure. Shpg. wt., 5 lbs.

KT-190 Net 10.98

ERECTOR ROCKET LAUNCHER SET

Build Toys That Actually Work

- All-Steel Parts
- Includes Powerful Electric Motor
- Supplied With Rugged Steel Chest

13.88




A thrilling, action-filled construction set that will provide the lucky builder with a wonderful feeling of achievement along with hours of fascinating fun. Completed set consists of a true-to-life rocket launcher, that actually raises, while radar scans the sky. With the press of a button, a rocket streaks off the launching track and into space. And, this fascinating model is only one of the hundreds possible to build with this excellent construction set. In addition to a large quantity of all-steel parts, set includes a powerful electric motor with forward and reverse gear shift and power take-offs. Complete with a steel chest designed like factory, as local point for industrial park. Size 16 1/4 x 10 1/4 x 3 1/4". Shpg. wt., 10 lbs.

KT-182 Net 13.88

GILBERT CHEMISTRY EXPERIMENT LAB

- Perform Experiments
- Complete Assortment of Chemicals
- Includes New Molecular Model Building Kit
- Sturdy Steel Storage Cabinet

7.44



Fully safety-tested and approved this worthwhile Chemistry Experiment Lab has been designed by leading Science Teachers. Furnishes the budding young scientist with the equipment and know how for such exciting experiments as: making Liquid Gold, changing White Cloth to Red, making Liquid Rock, the White Smoke Mystery and many more. Also included are interesting Crime Detection experiments and a new Molecular Model Building Kit, containing colored spheres representing atoms which joined together make and illustrate various chemical compounds. Supplied with a large assortment of chemicals in a fold-out steel cabinet. Size: 9 1/2 x 13 1/4 x 4 1/2". Shpg. wt., 9 lbs.

KT-183 Net 7.44

NEW!

LAFAYETTE 27.255 MC CITIZENS BAND REMOTE CONTROL TRANSMITTER KIT KT-127A

WITH .005% TOLERANCE CRYSTAL TWICE AS GOOD AS FCC REQUIRES! OVER 1 MILE LINE-OF-SIGHT TRANSMISSION! EXCEPTIONAL STABILITY FOR FOOLPROOF CONTROL OF MODEL PLANES, BOATS AND CARS.

You'll marvel at the neatness, simplicity and dependability of Lafayette's RC Citizens Band Transmitter. Crystal-controlled with a .005% tolerance crystal for extra frequency stability; exceeds FCC tolerance requirements. Fits comfortably in the palm of your hand, yet is unaffected by hand capacitance or motion. Has new attractive wide scale meter for visually tuning transmitter. Wide, non-critical tuning for optimum foolproof performance. Tuning for proper output and antenna loading easily accessible. Complete with telescoping antenna, meter, tube, crystal, alignment tool, all parts and easy-to-follow instructions. FCC license required.

KT-127A Net 17.25
BA-157 Burgess No. 2 battery Net .13
BA-1 BATTERY (2 needed) Imported 1.59 ea.



SAVE 16.26

NEW! ANALOG COMPUTER KIT

- Ideal Introduction to Basic Elements of Analog Computers
- Work Over 50 Experiments
- Easy-to-Assemble with Screwdriver and Pliers
- Learn the Way to Sound Scientific Knowledge

9.95

The latest Analog Computer Kit offering a basic introduction to computer theory—gives accurate answers to practical problems. Perform over 50 experiments—multiplication, division, powers, square roots, rocketry, interest, radioactive decay, light, kinetic energy, etc. Level of accuracy better than 5%. The computer consists of a masonite, solid instrument panel, kits, potentiometers, meter, specially calibrated scales, guide and operating booklet. Easy-to-assemble. Shpg. wt., 6 lbs.

KT-178 Net 9.95

MINERAL "TEKNIKIT"™, VOL. I

- 48 Carefully Selected Specimens
- Named—Tagged—and Classified



• Removable for Study
Forty-eight specimens—pre-selected to illustrate such physical characteristics as cleavage, hardness, color, luster, specific gravity, crystal form, etc. Contains specimens of ore—organics—fossils—elements—Plutonics—oxides—volcanics—hypabyssals—effusives crystals—common and uncommon minerals. An aid in the study of mineralogy, petrology, structural geology, physiography, economic geology. Each specimen is tagged and removable from its compartment. Each compartment is correspondingly tagged and named. All are named as well as classified. An excellent introduction to rock and mineral identification. Handy reference for the advanced "rock hound." Shpg. wt., 1 lb.

F-566 Net 2.95

NEW! MINERAL TEKNIKIT™ VOL. II

- 48 Additional Specimens! • No Two Alike!
- Many Uncommon Minerals! **2.95**

Volume 2 of Lafayette's popular Mineral TEKNIKIT™ has been as carefully pre-selected and packaged as its predecessor. Includes specimens of Carbonates—Tantaline Phosphates—Gemstones—as well as additional Plutonics—Volcanics—Sulphides—Metamorphics—Silicides—Oxides and many others. Specimens are tagged, compartments identified and the entire collection is indexed for type and classification. Shpg. wt., 1 lb.

F-676 Net 2.95

TRANSISTOR CODE PRACTICE OSCILLATOR KIT

For those interested in mastering the international code, an audio tone oscillator is essential. The circuit of this transistorized feedback oscillator has the simplicity of the neon glow, the signal strength of the vacuum tube, and requires only two penlite cells for weeks of service. It may be used for solo practice, or two may send and receive with the same unit. Kit comes complete with Transistor, Telegraph Key, Resistors, Condensers, Masonite Board, etc., and Schematic Diagram.

KT-72 LESS BATTERY, Shpg. wt., 1 1/2 lbs. Net 3.95
ME-33 Cannon AM-15-1—Single headset Net 1.18
BA-154 Battery Burg. #7 or eq. (2 required) Net ea. .10



3.95

COMPLETE WITH TELEGRAPH KEY & TRANSISTOR

MAGIC-GLO BLACK LIGHT TEKNIKIT™

- Educational—Scientific
- Enjoyable—Interesting
- Learn Invisible Detection
- Write Secret Messages



This new Black Light Kit enables you to see the invisible. Guaranteed completely safe and harmless. This kit allows children to study the phenomena of fluorescence and phosphorescence. Set contains black light, socket and cord, laboratory lamp stand, 4 jars of fluorescent paints, invisible ink, invisible crayon, tracer powder, 3 fluorescent mineral specimens, phosphorogram, optical bleach, brushes and pen, and a box of fluorescent specimens. Enables the student to perform endless numbers of fascinating experiments. The amply illustrated 48 page booklet "The Story of Black Light—The Unseen World Around Us," explains the use of black light in fields such as mineralogy, electronics, crime detection, medicine, stamp collecting, and many others. Shpg. wt., 4 1/2 lbs.

AP-61 Net 11.95
AP-73 Replacement U.V. Bulb for AP-61 Net 2.70

NEW! REVELL "Chicken-Little" MODEL KIT



- EDUCATIONAL
- FUN TO BUILD • AUTHENTIC MODEL
- FOR GRADE SCHOOL TO COLLEGE AGE

A fascinating Revell model kit which reveals the mystery of the birth of a chicken. Molded in real life colors, the easily assembled and take-apart seven stages start with a 3 1/2" chicken so real you'd expect it to "cheep". There is even yellow fluff for the feathers. An authentic kit, CHICKEN LITTLE was created under the supervision of Dr. Bruce M. Harrison, Professor of Embryology, University of California. It is a real boon for educators who formally had to rely on illustrations. Parents and teachers as well as youngsters will be delighted with this fun-while-learning model kit. Teaches children important biological functions. For ease in handling, and for magnification of detail, the eggshells are larger than actual size, each measuring approximately 3 1/2" in length, with a 2 1/4" diameter. 7 model stages are: Fertile egg, 2 to 3 days; 6 to 8 days, 19 to 20 days and new born chick. An educational booklet is included. Shpg. wt., 2 lbs.

F-768 Net 4.41

NOVATRON A SCIENTIFIC INSTRUMENT FOR THE EXPERIMENTERS

- POWERFUL, 110 VOLT AC/DC MOTOR
- MINIATURE ATOM SMASHER
- PRODUCES 75,000 VOLTS
- ABSOLUTELY SAFE

COMPLETELY WIRED (NOT A-KIT)




In no sense of the word a toy or gadget. This machine is a scientific instrument capable of producing 75,000 volts—makes sparks up to 2" long—yet it is absolutely safe because the current is infinitesimal. The science teacher—science lover—or hobbyist can perform experiments to astound students—friends—family. Makes smoke disappear—defy gravity—turns propellers at a distance—transforms atomic energy into light—makes artificial lightning—smashes atoms—demonstrates ionic space ship drive—and many other experiments. Constructed of the finest materials. Will do exactly—for instruction purposes—what generators that cost 3 to 10 times more will do. The perfect device to teach the secrets of atomic physics and electricity. Will hold an audience spellbound as it performs trick after amazing trick. Includes an experiment kit and illustrated experiment manual. Manual explains the "how" and "why". You will invent many new experiments of your own. A fine research tool that will give years of beneficial service to the institution or individual who owns one. 110 V. AC or DC.

F-371 Assembled—Shpg. wt., 4 lbs. Net 11.95

New! LAFAYETTE REFLEX TYPE F/1.8 ZOOM MOVIE CAMERA

WITH AUTOMATIC
ELECTRIC EYE
PHOTOMETER



ONLY
69.95

NO MONEY DOWN

- SINGLE LENS REFLEX SYSTEM LETS YOU SEE WHAT THE LENS SEES
- ULTRA FAST F/1.8 Lens—ZOOMS from wide angle to Telephoto
- Built-in Coupled Electric Eye Exposure Meter
- 4 Speeds—Including Slow Motion
- Single-Frame (animation) Exposure
- USES ANY FILM—ASA 10-40
- AUTOMATIC FOOTAGE COUNTER
- TRIGGER ACTION PISTOL GRIP

See exactly what the camera lens sees with this true single-lens reflex system. The bright viewfinder shows exactly what will appear on the film. No more parallel errors—no more focusing problems! Fast F/1.8 zoom lens is directly coupled to the electric eye photometer. Simply look through the viewfinder, line up the arrows and shoot! Needle sharp zoom pictures are yours from 10 mm. wide angle through 30 mm. telephoto. Trigger action, pistol grip handle

provides a firm, comfortable grip for smoother, steadier movies. Fast, simple drop-in spool loading. Adjusts for films of ASA 10-40 speed rating. Film footage counter returns to the starting position automatically when roll is finished. Four motor speeds for 12-16-24 and 32 per second plus single frame for animation. Quiet ratchet-wind motor with a 6 ft. run. Die-cast aluminum body. Trigger action pistol grip handle and leather wrist strap included.

F-822L Shpg. wt., 5 lbs. Net 69.95

Zoom Case: Holds camera with pistol grip attached. Room for accessories. Measures 10x8 1/2 x 3 3/8".

F-784 Shpg. wt., 2 lbs. Net 5.79



ZOOM MOVIE OUTFIT

Complete
SAVE 14.79 from
catalog prices **136.50**

Complete ZOOM movie outfit contains all the equipment needed for success in taking and showing dramatic home movies. Included are the exclusive Lafayette 8 mm Zoom Camera (F-822), "Ultra" 500 watt projector (F-785), 30x40" folding tripod projection screen (F-536), bar light (F-651) with lamps and case, 2 reels and case (F-538), Zoom case (F-784) and 25 ft. of Kodak film with processing included. Net 136.50

SYLVANIA SUN GU

- ELIMINATES BULKY BAR LIGHTS
- FITS ANY CAMERA
- LIGHT OUTPUT EQUALS 4 PHOTOFLOOD LAMPS
- TILTS FOR BOUNCE LIGHT

17

MANSFIELD "ULTRA" 500 WATT 8 mm MOVIE PROJECTOR



- Fast, Easy Loading
- Forward, Still & Reverse
- Self-Contained Carrying Case

52.95

NO MONEY DOWN

The new "Ultra" 8 mm projector features several unusual conveniences to uncomplicate movie showing. Has swing-out gate for fast threading. Forward, Still and Reverse positions. Bright 500 watt DFA lamp gives uniformly bright picture. Cinepar .750" f/1.6 lens. Self contained carrying case.

F-785WX Shpg. wt., 10 lbs. Net 52.95

F-786 Replacement Lamp (DFA) Net 2.70

"HOLIDAY" 500-WATT 8mm PROJECTOR

- High Intensity Blower Cooler!
- 400-ft. Reel Capacity
- Swing-Out Gate—Easy Loading
- Coated 3/4" f1.6 Lens!

37.95

NO MONEY DOWN



Show your movies sharp and clear! Swing-out gate for fast, easy loading. Scientific Marex film extends life of your film with less wear and tear. High intensity blower for cooling. Coated 3/4" f1.6 lens for wide-angle viewing. Separate switches for blower and lamp. Rapid rewind and quick-tilt features for ease of operation. Lifetime lubrication with oil light bearings. All-aluminum, die-cast construction. 500-watt bulb. Lifetime guarantee.

F-526WX Shpg. wt., 10 lbs. Net 37.95

F-649 Carrying Case for F-526. Net 6.44

Shpg. wt., 2 lbs. Net 1.89

F-746 Replacement Lamp (DAK) Net 1.89


4-LAMP MOVIE "BOUNCE" BAR LIGHT

- For all 8mm & 16mm cameras
- For color or b-&-w
- Complete with flood lamps and case

8.95

Trapeze camera mount keeps lamps above camera, eliminating shadows. Swirls 90°. V-case accepts unit while lamps are hot. Exposure guide; on-off switch. 4 lamps and case.

F-651 Shpg. wt., 6 lbs. Net 8.95



THE REMARKABLE LAFAYETTE f 1.8 TRIPLE TURRET 8 mm MOVIE CAMERA with Built-In Exposure Meter

Only

NO MONEY
DOWN

39.50



- 3 TURRET INTERCHANGEABLE f 1.8 LENS — Wide Angle — Normal View-Telephoto
- Built-in Wide Scale Electric Eye Exposure Meter With Exposure Guide
- THREE Built-in Filters — For Color, Normal and Bright Scenes
- Pistol Grip With Trigger Release
- "Combo-View" Finder — For Normal, Wide Angle and Telephoto Areas
- Ratchet Spring Wind

Lafayette is proud to offer a modern 8 mm movie camera that is ready for "rapid fire" shooting. A three turret assembly for instant change over to one of three lenses, electric eye exposure setting, and pistol grip trigger release are time saving features the serious moviemaker should not overlook. A twist of the turret selects wide angle (f = 6.5 mm), normal (f = 13 mm), or telephoto (f = 25 mm), f 1.8 coated and color corrected lens. Turret action is smooth and positive. There is no need to fumble with focusing adjustments—all lens are prefocused. The built-in exposure meter takes all the guess work out of exposure setting. Wide scale meter is matched with exposure guide to obtain proper lens opening, for perfecting filming. Also built-in are 3 filters: "conversion" for color film, "haze" for normal black and white and "neutral density" for extremely bright scenes. A choice of 4 speeds, 12, 16, 24 and 32 frames per second plus single exposure. Slide rule footage counter. Spring wound ratchet type motor runs 6 feet of film on a single winding. Exposure guide is calibrated for ASA 10 to ASA 40 film speeds. Direct optical viewfinder. Rugged die cast case in blue and gray. Trigger action, pistol grip handle and leather wrist strap included. Made to our specifications in Japan. Shpg. wt., 5 lbs. Net 39.50

F-702L Net 39.50

F-648 Holster Case for F-702. Shpg. wt., 8 oz. Net 2.95

MATCHED MOVIE OUTFIT



Everything you need for movie-making and showing fun. No need to "shop" for unmatched equipment, no need to pay more. You get all this: Lafayette's F-702, f1.8, Triple Turret movie camera with exposure meter; holster type camera case; "Holiday," F-526, 500-watt projector; F-536 30x40" screen; F-537 Bar Light; 2 F-539 photo flood lamps; 2 F-538 400' reels and cans. Unbeatable for foolproof shooting and showing of indoor and outdoor movies. Net 87.95

F-789WX Shpg. wt., 20 lbs. Net 87.95

LAFAYETTE 9-TRANSISTOR CITIZENS BAND "WALKIE TALKIE"



KORDEX™

TRANSISTORIZED TAPE RECORDER IN ECONOMICAL SEMI-ASSEMBLED KIT FORM

- Extra Small • Fully Portable
- Battery Powered • A Mere 2½ lbs. in Weight • Prewired 3 Transistor Amplifier
- Half Track Recording For Maximum Tape Economy • Records/Playsback Up To 20 Minutes With 3" Tape Reel • Record, Rewind, Playback, Erase

SIMPLY ASSEMBLED IN LESS THAN AN HOUR

17.95


INCLUDING: Telephone Pickup-Microphone, 3" Reel of Tape, Earphone, Empty Reel, Batteries

This is a precision full function miniature tape recorder in money saving semi-assembled kit form. In less than one hour the Kordex Tape Recorder can be assembled — ready for operation. The amplifier comes already wired, so there is no tedious soldering to do. Complete, it weighs only 2½ lbs. and slips easily into a briefcase or handbag. This miniature recorder has been designed for ease of operation, with all controls readily accessible. Forward-rewind-erase selector is on front panel. Record — playback switch and volume control appear above amplifier subchassis. In addition, microphone and earphone jacks are located on the front panel. For maximum tape economy, the Kordex tape recorder employs a half track head. The upper half of the tape is recorded and the tape is turned over to record on the lower half — records and plays up to 20 minutes on a 300 ft. ½ mil 3 inch reel of tape. A powerful 3 transistor precision wired amplifier is utilized to drive a 2 x 3" PM speaker. Speaker is built-in. With its attractive carrying case the Kordex recorder is equally suitable for home, office or travel. Power is supplied by 2 standard "C" flashlight cells and one inexpensive 9 volt transistor battery. Complete with combination microphone-pickup, batteries, 2-3" reels, 100 feet of tape and Instructions. Measures 6" O x 8¼" W x 2¾" H.

KT-201 Kit Shpg. wt., 6 lbs.	Net	17.95
RT-20 3" Reel 300 ft. ½ mil Mylar tape. Shpg. wt., 4 oz.	Net	.60
BA-2 9 volt transistor battery for above. Shpg. wt., 2 oz.	Net	.39
BA-156 1.5V battery for above (2 req.) Shpg. wt., 2 oz.	Net	.13



plus Diode and Thermistor



NO LICENSES, TESTS OR AGE LIMITS



Complete with LEATHER CASE, EARPHONE, ANTENNA & BATTERIES

- Transmits & Receives Up to 1.5 Miles
- Crystal Control on Both Transmit & Receive
- Leather Case with Shoulder Strap
- Requires 8 Inexpensive Penlight Batteries
- Up to 70 Hours Battery Life
- 46" Telescoping Antenna
- Push-To-Talk Operation
- Earphone For Personal Listening

OTHER CHANNELS ARE AVAILABLE

If desired with any channel other than channel 10, order HE-31L and specify channel.

NOW NO MONEY DOWN
39⁹⁵
2 for 78.88

"MIGHTY 9"

The MOST POWERFUL

9 TRANSISTOR PERSONAL

PORTABLE

NO MONEY DOWN!



No License or Permit Required—Complete portable two-way communications for everyone, everywhere. Perfect for hunting, fishing, boating, virtually all sports; use at work in construction, warehouse, office, on the farm, etc. for all communications. Receives on ONE channel up to 1.5 miles under average conditions as your telephone and twice as handy—weighs only 18 ounces and as simple and easy to use as a push-to-talk button is depressed for transmitting the built-in speaker. Private monitoring of conversation is made possible by means of earphone. Telescoping antenna extends to 46 inches. Accuracy and precision of a fine watch, this new Lafayette Citizens Band walkie-talkie offers maximum reliability and performance by use of sophisticated transistor design. Full transistor circuitry employs 9 transistors plus 1 diode and thermistor controlled and delivers a power input of 100 milliwatts, and units in the 27mc Citizens Band spectrum. Crisp reception and transmission by superheterodyne receiver. Power is supplied by 8 penlight batteries.

96

as a flash gun—as powerful as four
center beam candlepower while drawing 650
photo floods require. Replaceable quartz-halogen
light, color rated at 3400K. Eliminates "hot-spots"
dims-out," light output and color balance remain constant
is swivel mounted. For 110-120 V.A.C., draws 6 amps.
F-677 Shpg. wt., 2 lbs. Net 17.96

SUN GUN CASE

Heavy duty Texon case for the Sun Gun. French stitched, brass trimmed, and with a specially made strap. Full protection for your gun. Measures 10x5½x3½"
F-722 Shpg. wt., 1 lb. Net 3.50



NEW 8 mm MOVIE EDITOR

This new 8 mm movie editor, compact designed—sturdily constructed, has an extremely bright hooded screen (2½x1¾") for edge-to-edge sharpness and brilliance, 3:1 geared ratio rewriter for high speed rewinding. Built-in hand framer adjusts the frame properly on the screen; built-in individual frame marker makes editing easier. Folding winder and rewriter arms with 400-ft. capacities. Includes new dry splicer. Shpg. wt., 10 lbs. F-652 Net 22.50



LAFAYETTE ZOOM LENS

• Fill the Screen From 12 to 15 feet—then ZOOM in!

The very latest in projection accessories for the movie fan. Coated, f1.5, 15 to 25mm focusable zoom lens fits most popular priced projectors. Converts our own "Holiday" (F-526) into a modern, zoom projector. Adds realism and depth to old "reels." Fills a 30x40" screen at from 12' to 15'—then zooms in for exciting closeups. Show your movies at the size you want—without moving projector or screen. F-690L Shpg. wt., 6 ozs. Net 6.95



2 LIGHT BAR 2.50

Holds still or movie cameras. Grip-handle prevents light bar from turning. 6 ft. cord. (Bulbs not included). F-537 Shpg. wt., 1½ lbs. Net 2.50
PHOTOFLOOD BULBS, 300-watt, reflector type. F-539 Shpg. wt., 1 lb. Net ea. .95



FOLDING TRIPOD PROJECTION SCREEN

7.50

Fine grain glass beading for extra brilliance, excellent viewing. Heavy-duty folding tripod adjustable to various heights. Large 30x40" size. F-536 Shpg. wt., 10 lbs. Net 7.50

MOVIE & SLIDE PROJECTION LAMPS



Exact replacement projection lamps for most movie and slide projectors. Make your pictures sparkle with a new, efficient lamp. Avg. shpg. wt., 6 ozs.

Stock No.	ASA Code	Watt	Base Type	Net Ea.
F-741	CLS	300	Bayonet	1.49
F-742	CLX	300	Bayonet	1.49
F-743	CMV	300	S.C. Bay	1.49
F-744	CYC	300	S.C. Bay	1.49
F-750	CWD	300	Prefocus	1.69
F-747	EDK	500	Bayonet	1.79
F-745	CZX	500	Prefocus	1.79
F-746	DAK	500	Prefocus	1.89
F-748	DOB	750	Prefocus	2.15
F4749	DFD	1000	Prefocus	2.90

Set of 6 SLIDE TRAYS

1.79

Trays fit any Bell & Howell (except Explorer), TDC, Keystone and Viewflex projectors. Tray holds 30 slides; slots numbered for indexing. Shpg. wt., 1 lb. F-816 Set of 6 Net 1.79



ROLLAPRINT CHEMICAL SET

F-697 Shpg. wt., 2 lbs. Net 1.95


ROLLAPRINT PAPER

F-698 Box of 100. Shpg. wt., 8 ozs. Net 2.95

ROLLAPRINT 35 MM ENLARGER

37.50


NO MONEY DOWN



- Enlarges 35mm Negatives in Normal Room Light
- Uses B & W Negative or Color Slide
- It's Fun! It's Easy

Now you can enlarge your 35mm black-and-white negative or color slide. Just place your 35mm negative, or slide, into the enlarger, insert Rollaprint paper and press exposure button 2-4 seconds. Then run paper through Rollaprint Printer developing section and PRESTO!—a clear, clean, permanently-finished 3¼x4¼" B/W print. F-812 Less paper. Shpg. wt., 5½ lbs. Net 37.50
ROLLAPRINT PAPER. Box of 100. Shpg. wt., 8 ozs. F-698 Net 2.95

12 TRAY SLIDE CARRY CASE



- Pyroloxin covered Kiln-dried Lumber
- FREE! 132-Letter Titrting Set

A sturdy 12-tray slide case, covered with scuff-proof Pyroloxin coated material, holds TDC, Wollensak, Keystone, Argus, etc. trays. Special protected fiber inserts guarantee perfect fit for all length trays. Included is a complete titling set with 132 letters. Overall size 11x11x9½" Shpg. wt., 5 lbs. F-814 Less paper. Net 3.59

- Make Your Own Finished Prints EVERYTIME
- No "Lab" or "Darkroom" Needed
- Complete with Chemicals and Paper

Regularly 19.95

NOW ONLY!

12.49

Make your own prints in 10 seconds—no darkroom needed, nothing else to buy. Prints popular-size black and white or color negatives up to 3¼x4¼", in daylight or room light. Dries immediately, has permanent finish, won't fade. For use at home, camera stores, studios, commercial uses, etc. Complete with chemical set (makes 100 prints) and box of 100 special formula paper (makes 3¼x4¼" prints). F-811 Shpg. wt., 5½ lbs. Net 12.49

ROLLAPRINT ROLLAKIT




Develops 35mm and 120-620 Films

9.95

Now you can develop your own pictures wherever you are, with the new Rollakit. Develops all 35mm and 120 to 620 films in normal room light. In only minutes you go from exposed film to beautifully finished dry prints, in conjunction with the Rollaprint printer. The Rollakit includes light-proof bag, Rollatank, Rollabath and clips. Shpg. wt., 2 lbs. F-813 Net 9.95

COMPACT 6-TRAY SLIDE CASE




- WITH 6 UNIVERSAL TDC SLIDE TRAYS
- STURDY WOOD CONSTRUCTION

3.79

Will accommodate Keystone, A0, TDC, Viewflex slides. Scuff-resistant Pyroloxin coated, all-wood construction. A convenient and compact way to store and carry your slides. Includes 6 Universal TDC slide trays. Overall 15x7¼x2¾" F-815 Shpg. wt., 3½ lbs. Net 3.79

NOW! NO MONEY DOWN WITH LAFAYETTE'S NEW 3-IN-1 EASY-PAY PLAN



POP
with 2 DIODES
and 1 THERMISTOR
ONLY **25⁸⁸**
NO MONEY
DOWN

- LIGHTWEIGHT SHIRT-POCKET SIZE • PLAYS FOR HOURS ON 2 MOST INEXPENSIVE BATTERIES • SEPARATE MIXER AND OSCILLATOR • 2 IF STAGES • 4 AUDIO STAGES • 2 DIODES • AVC AMPLIFIER • PERSONAL, BUILT-IN EARPHONE JACK • COMPLETE WITH LEATHER CARRYING CASE, BATTERIES, EARPHONE • FULL-TONE SPEAKER

Lafayette's new "Mighty-9" portable, the most powerful transistor radio, is the answer for those who want the best, without spending the most. Compare this portable with others selling for much more—compare feature for feature and you'll see why the Lafayette "Mighty-9" is your best buy. Inside the sturdy, attractive plastic case you'll find an engineer's dream—separate mixer and oscillator, diode detector and diode bias stabilizer, 2 IF stages, AVC amplifier, 4 audio stages including push-pull audio output. Lightweight (only 9 ozs.), pocket size (4½Hx3Wx1¼"D), self-contained stand. Best of all it operates on two of the most inexpensive "Z" cell batteries—plays up to 3 times longer than on other 9 volt batteries. Complete with leather carrying case, batteries and earphone for private listening. Shpg. wt., 2 lbs.

FS-91L Net 25.88
BA-155 (Burgess Z type battery 2 required) Net ea. .095



Complete with carrying case, batteries and earphone

...sly into your pi
...d push-to-talk. When
...acts as a sensitive micr
...of a special jack and ea
...Constructed with the care
... "Walkie Talkie" achieves opti
...istor techniques and advanced o
...diode. Transmitter section is crystal
...meeting FCC specifications for unlicensed
...clear reception is furnished by the efficient se
...8 miniature standard penlight batteries with a life
...Housed in a handsome black and gold aluminum case with
...strap. Supplied with earphone, antenna, batteries and
...6½x3¼x1½". Shpg. wt., 3 lbs.
HE-29AL

Set of 2
Replacement batteries for HE-29 "Walkie-Talkie," 8 required.
BA-155 Z Cells

Net Each .095

**FAMOUS PICKERING
MARK IIC CARTRIDGE**



**SPECIAL
SALE PRICE
9.88**

REG.
24.00

with D3707A Stylus

QUANTITY
LIMITED

- .7 Mil Diamond Stylus
- Response ± 2 db 10-30,000 CPS

Here is the famous Pickering Mark II C Cartridge with .7 mil diamond stylus that reproduces both mono and stereo perfectly. Uses "T-Guard" stylus assembly. Tracking force: 3-7 grams; separation: 25 db; output: .025 volts per channel. Shpg. wt., 3 ozs.
PK-803L Net 9.88

Complete with D9007
Diamond Stylus

NOW! NO MONEY DOWN when you use LAFAYETTE'S NEW EASY-PAY PLAN!

**LAFAYETTE RADIO ELECTRONICS
"ASSOCIATE STORE"
DEALER LOCATIONS**

Lafayette Radio Electronics "Associate Store" Dealers own and operate their own stores as independent franchised dealers. They establish their own terms and prices, which may vary slightly, and do not handle mail orders.

SAN FRANCISCO, CALIF. 1480 Market St.	WATERBURY, CONN. 386 West Main St.	DETROIT, MICH. 1326 Broadway	ROCHESTER, N. Y. 792 W. Main St.
DENVER, COLO. 1455 So. Sheridan Blvd.	TAMPA, FLA. 3328 Henderson Blvd.	ASBURY PARK, N. J. 1027 Highway No. 35	AKRON, OHIO 34 North Main
BRIDGEPORT, CONN. 2710 Fairfield Ave.	SPRINGFIELD, MASS. 527 Belmont Ave.	CAMDEN, N. J. 305 Broadway	CLEVELAND, OHIO 2001 Euclid Ave.
GROTON, CONN. 171 Thames St.	BALTIMORE, MD. 2014 No. Charles St.	TRENTON, N. J. 229 South Warren St.	COLUMBUS, OHIO 122 E. Long St.
STAMFORD, CONN. 85 Prospect St.	BEL AIR, MD. 139 Thomas St.	ALBANY, N. Y. 335 Central Ave.	HARRISBURG, PA. 1419 No. 3rd St.
			PITTSBURGH, PA. 640 Grant St.

MAIL ORDERS NOT FILLED BY "ASSOCIATE STORE" DEALERS

**LAFAYETTE
RADIO**

111 JERICHO TURNPIKE
SYOSSET, LONG ISLAND, NEW YORK

BULK RATE
U. S. POSTAGE
PAID
New York, N. Y.
Permit No. 8486



**PRST
9876**