

**GTE** LENKURT

# DEMODULATOR

JANUARY/FEBRUARY 1980



## WARC 79



Also in this issue

**FCC Rule  
Part 94**



The January/February 1979 issues of the Demodulator discussed the then upcoming World Administrative Radio Conference. At that time, the industrialized nations were concerned that the lesser developed nations might try to reserve orbital slots and portions of the frequency spectrum for future satellite use. The conference has been held. The results are discussed in the following article.

**T**he 1979 World Administrative Conference (WARC) was held in Geneva, Switzerland. The conference began September 24, 1979 and ended, with the signing of the Final Acts, December 6, 1979.

The conference was held under the auspices of the International Telecommunications Union (ITU). The ITU is the principal agency concerned with international civil communications. Founded in 1865, the Union is the oldest of the inter-governmental organizations which form the specialized agencies of the United Nations.

The purpose of the ITU is to provide standardized international communications procedures, including international radio regulations and frequency allocations. The Acts of the ITU have the force of treaties, so they

must go through the treaty ratification procedure to be adopted by the United States.

Two semi-independent organs of the ITU are, the International Telegraph and Telephone Consultative Committee (CCITT) and the International Radio Consultative Committee (CCIR). The CCITT studies technical, operative and tariff questions about telegraphy and telephony. The CCIR studies technical and operating questions directly related to radio communications.

Both committees issue recommendations in their specific spheres of interest. The recommendations do not have the same force as the Acts of the ITU. Therefore, the recommendations do not require ratification.

A third sub-organ of the ITU is the

International Frequency Registration Board (IFRB). The Board's responsibilities include recording all radio frequency assignments and preparing the International Frequency List.

Returning to our discussion of the WARC, the Final Acts will be published by the ITU in September, 1980 and will enter into force January 1, 1982. There are many individual effective dates for specific provisions. For example, the new frequency tolerances will take effect in two stages; one in 1984 and the other in January 1994.

### **FCC Staff Report**

After the conference, the FCC staff prepared a report to the Commission on the results of the conference and that report is available to the public. It is the basis for the following statements:

The anticipated politicalization did not occur. The conference generally concerned itself with technical matters.

The developing countries did support each other in areas where they had common interests. This is also true for the industrialized nations. All participating nations appeared to be guided by their perceptions of their best national interests. There was no evidence of bloc-voting along ideological lines, without reference to national interests.

The U.S. delegations submitted reservations on a few conference decisions because the delegates believe the decisions would adversely affect

important national interests. A reservation is a formal protocol statement that the nation submitting the reservation will not necessarily be bound by a particular decision.

In any event, the Final Acts have the force of a treaty. Therefore, they must be ratified, which means approved by the Senate and signed by the President. It is not unusual for reservations to be included in the Final Acts ratified by the United States. After ratification, the FCC Rules and Regulations will have to be amended as required to implement the changes.

Even without the delays resulting from this U.S. domestic process, the Conference decisions will not cause any immediate changes in the structure or operation of the U.S. telecommunications systems, since most of the changes mandated by the Conference are intended to be phased-in over a long period of time.

The primary purpose of the WARC was to accomplish a general revision of international radio regulations. This purpose was achieved. Numerous changes were made in the areas of frequency allocation, frequency tolerances and spurious radiation limits.

A discussion of all these changes is beyond the space limitations of the Demodulator. However, some of the changes are discussed, because they are of particular interest to many of our readers.

As reflected by the following quotations, the FCC Staff believes

the changes are beneficial.

“It is rather evident that allocation actions, as they affect or will affect the non-government community, were highly favorable and the Commission’s expressed desire for flexibility was achieved.”

Another part of the Staff Report:

“The Final Acts incorporated the various effective dates of results of other conferences, either adopting them, or abrogating them, as needed, to make the 1979 Final Acts a cohesive, non-contradictory set of International Radio Regulations.”

In its summary, the Staff stated:

“The recently completed 1979 WARC should be viewed as substantially a success for the United States. While we did not achieve all our objectives, and many issues were deferred—either for further study by the sub-organs of the ITU or for consideration by subsequent Conferences—it is clear that the fears of impending disaster expressed by many, prior to the Conference, were not justified.”

The forgoing excerpts, from the FCC Staff Report, were largely taken from the introductory matter and general discussion portions. The report also has four attachments:

- I. Allocations
- II. Regulatory
- III. Resolutions and Recommendations
- IV. Future Conferences

Parts of each of these attachments are briefly discussed in the following paragraphs.

## **Allocations Attachment**

A number of new bands were identified to accommodate amateur satellite operations. All of the newly identified bands, below 40 GHz, were in bands already allocated to the terrestrial amateur service.

### **2.5 GHz Band**

The 2.5 GHz band was substantially opened up to the Fixed Satellite Service. The FSS now shares this band coequally with the Broadcasting Satellite Service; at the same power flux density levels.

### **12 GHz Band**

According to the FCC Staff Report, “The WARC decisions at 12 GHz met nearly all of the U.S. objectives.” These objectives were:

- a) The elimination of arc segmentation to enable the entire geostationary orbit to be used by both the fixed satellite and broadcasting satellite services.
- b) The elimination of the possibility of planning the fixed satellite service at the 1983 Region 2 Conference.

c) The maintaining of the viability of direct to home satellite broadcasting for the United States.

As a result of the conference decisions, the 10.7 to 11.7 GHz band is now available for world-wide use. The 11.7 to 12.1 GHz is available only to Region 2 (The Americas).

The countries of Region 2 agreed that the 11.7 to 12.1 GHz band will be used by the fixed satellite service

and the band from the 12.3 to 12.7 GHz will be used by the broadcasting satellite service. The division of the 12.1 to 12.3 band, between these two services, will be decided at the Region 2 Broadcasting-Satellite Planning Conference in 1983. In other words the upper limit of the fixed satellite and the lower limit of the broadcast satellite services will be established at the Region 2 Conference. The United States is hopeful that the division will be established at 12.2 GHz.

The following information about the 12 GHz band comes from other sources that the FCC Staff Report. All sources are listed in the Bibliography.

The WARC Final Acts provide primary coequal status for the fixed (terrestrial) service in the 11.7 to 12.75 GHz band. In Region 2, this band is allocated in four segments.

The first, 11.7 - 12.1 GHz, band is allocated for fixed, fixed-satellite (space to earth) and mobile except aeronautical mobile services. The second, 12.1 - 12.3 GHz, band is for fixed, fixed-satellite (space to earth), mobile except aeronautical mobile, broadcasting and broadcasting satellite.

The third allocation, 12.3 - 12.7 GHz, is for fixed, mobile except aeronautical mobile, broadcasting and broadcasting satellite. The fourth, 12.7 - 12.75, band is for fixed, fixed-satellite (earth to space) and mobile except aeronautical mobile.

The following information is derived from the indicated footnotes to the international regulations adopted at the WARC:

— 2785A. The broadcasting-satellite service in the band 12.5 - 12.75 GHz is limited to community reception with a power flux-density of -111 db (referenced to one watt) per square meter, as defined in Annex B of Appendix 29A.

— 3787C. The bands 12.1 - 12.3 GHz in Brazil and Peru and 12.2 - 12.3 GHz in the U.S. are also allocated to the fixed service on a primary basis.

— 3787F. For Region 2 stations in the broadcasting satellite service, assignments in the 12.3 to 12.7 GHz band will be made available in a plan to be established by the 1983 Region 2 Administrative Radio Conference. Assignments in the plan may also be used for transmissions in the space-to-earth fixed satellite service providing such transmissions do not cause more interference, or require more protection from interference than do the broadcasting satellites operating under the same plan. With respect to the space services, this band shall be principally used by the broadcasting satellite service. The lower limit of this band shall be modified in accordance with the decisions of the 1983 Region 2 Conference.

### **BSS Uplinks**

For Region 2, the WARC allocated the 14.5 - 14.8 GHz and the

17.3 - 18.1 GHz to the FSS exclusively for uplinks to broadcasting satellites. The 17.3 - 18.1 GHz band is preferred for Region 2 and will be the subject for detailed planning at the Regional Conference. Of course, other fixed satellite (earth-to-space) bands can be used for the same purpose.

### **3 and 4 GHz Downlinks**

The conference identified the bands 3400-3700 MHz and 4500-4800 MHz for downlink use by international systems, particularly INTELSAT. Although the United States had recommended the expansion of the 2 GHz spectrum, for this purpose, it accepted the conference decision.

However, two caveats were expressed. The first is in a footnote to the allocation table for the 3400-3600 MHz band. The sense of this footnote is that the Radiolocation Service and the Fixed-Satellite Service are on a co-equal basis in Regions 2 and 3 until the Radiolocation Service can be reaccommodated.

The second is in the form of a declaration by the USA, Canada, UK, Netherlands, Australia and Belgium. The declaration says that these nations will not withhold support for INTELSAT implementation of the FSS in these bands in any country other than those listed in the footnote 3748B. Furthermore, these nations will make reasonable efforts to accommodate FSS, consistent with footnotes 3736, 3736A and 3748B.

### **14 GHz Mobile-Satellite Service.**

The WARC provided an allocation in the 14.0 - 14.5 GHz band for mobile-satellite service on a secondary basis. This service could accommodate mobile earth stations. Such stations could be used for on-the-spot, real-time coverage of current events.

### **Regulatory Attachment**

Only minor changes were made to the provisions dealing with the advance publication, coordination, notification and registration of space telecommunications services. Similar changes were made in the provisions for terrestrial stations operating in bands shared with the space services.

Many of the provisions regarding terrestrial services were revised for clarification and increased emphasis. Several resolutions and recommendations were adopted to provide technical assistance to developing countries.

As a result, the IFRB will select frequency assignments for countries in need of special assistance and will assist in the identification of sources of interference to stations of countries in need for special assistance. Numerous other resolutions and recommendations were passed to provide methods for transferring telecommunications technology and urging the developing nations to participate in the CCIR and CCITT.

The WARC adopted the CCIR studies and recommended new meth-

ods of classifying and designating emissions. The new procedure will allow more efficient use of the spectrum by improving international frequency registration techniques. This will enable potential interference to be more accurately identified while planning new systems in shared frequency bands.

The WARC also adopted the CCIR recommendations regarding station keeping of space stations. Under this regulation, future satellites in the BSS and FSS services must limit their unintentional arc displacement to  $\pm 0.1$  degrees in the East-West direction. This action is designed to reduce interference problems resulting from the large number of satellites in geostationary orbit around the earth's equator.

Space stations which have made application before January 1, 1987 do not have to comply with the  $\pm 0.1$  degree requirement. They will be governed by the old requirement which is  $\pm 0.5$  degree in most cases.

The questions of equitable access to the Geostationary Orbit was extensively debated at WARC. As a result, the conference decided to convene a World Administrative Conference on the Geostationary Orbit and the planning of space services.

This conference will be held in two sessions. The first will take place about 1984 and the second, 18 months later. Quoting from the FCC Staff Report; "Although the terms of reference are indefinite, the intent is to develop plans to insure equitable

access by all countries to the geostationary orbit and appropriate frequency bands."

## **Resolutions and Recommendations**

A total of 87 Resolutions and 90 Recommendations was adopted by the WARC. Twenty Resolutions and 46 Recommendations were referred to the CCIR for study.

## **Future Conferences**

The WARC recommended that three future world conferences and seven regional conferences be held. Specific dates or agendas were not established. This is a function of the ITU Administrative Council.

In addition to the above Conferences, the ITU schedules an Administrative Council meeting annually (in the May/June time frame) and Plenipotentiary Conferences periodically to revise the Convention. The next Plenipotentiary is scheduled for Nairobi in the fall of 1982. Furthermore, CCIR Plenary sessions are held every four years, with interim and final meetings held in the intervening period. The relevant Resolutions and Recommendations of WARC 79 will be among the matters considered at these CCIR meetings.

## **Conclusions**

WARC 79 was a definite success, considering that it was the first conference in twenty years to address an overall revision of international radio

regulations. Also, given the time limitations of the conference, it is not surprising that the delegates confined themselves to establishing broad general policies and left the detailed planning, required to implement these policies, to future conferences and to the specialized suborgans of the ITU.

The January/February and March/April 1979 issues of the Demodulator discussed satellite communications problems resulting from limitations of the frequency spectrum and geostationary orbit. The WARC allocated more of the frequency spectrum to the fixed satellite service to partially alleviate the frequency crowding and consequent interference problems. The actions to make the entire geostationary orbit available to segments of the 12 GHz band and the

new station keeping tolerance will reduce interference problems and, to a lesser extent, orbital congestion.

Meanwhile, applied research and development projects are underway to provide solutions to these problems. One such program to reduce spectrum crowding was described in the May/June 1979 Demodulator. It is the 19/29 GHz propagation experiment conducted by GTE and the University of South Florida.

The Demodulator also described NASA's ongoing experiments, involving space stations and orbital antenna farms. These are designed to provide solutions to the problem of orbital congestion. When these devices become operational, the ITU will probably be heavily involved in establishing regulations to govern their use.

---

#### BIBLIOGRAPHY

1. Public Notice 25215 *Staff Report to the Commission on the Results of the 1979 World Administrative Radio Conference*, Washington D.C.
2. *Preliminary Results of WARC-1979 at a Glance* January, 1980 IEEE Spectrum, Piscataway, N.J.
3. Richard C. Kirby, *WARC Plots Spectrum Use* February 1980 IEEE Spectrum, Piscataway, N.J.
4. *Industrial Communications*, January 4, 1980, Washington, D.C.
5. *From Semaphore to Satellite*, 1965, International Telecommunications Union Geneva, Switzerland.



# FCC Rule Part 94

The following discussion is in response to numerous inquiries about how Part 94 FCC Rules and Regulations impacts existing and new "Industrial" microwave stations. At the time of this writing, Part 94 requires that all, "Private Operational Fixed Microwave", systems be totally compliant to the provisions of Part 94 by August 1, 1985.

The discussion presents information of a general nature, which should not be used as a basis for engineering or legal decisions involving an actual system. Questions regarding specific systems should be referred to the FCC or a competent engineering/legal authority.

In November 1975, the FCC released a memorandum and order establishing a "Private Operational Fixed Microwave Service." A private operational fixed microwave link provides communications between specific fixed points. Stations are authorized to transmit the licensee's own communications, those of its parent corporation or of other subsidiaries of the same parent. This is in contrast to "Domestic-Public Radio Services" which offer common-carrier telephone services to the general public.

## FCC Rules, Part 94

The objectives of the FCC's 1975 memorandum were to improve spec-

trum utilization and provide a more uniform quality of service in the affected frequency bands. To realize these objectives, a new Rule Part, designated Part 94, was formulated and became effective July 1, 1976.

Part 94 contains the following provisions:

1. Stringent technical standards for microwave systems authorized after July 1, 1976.

2. Less stringent standards for microwave systems authorized between July 20, 1961 and July 1, 1976. However, these systems must meet the stringent standard after July 31, 1985.

3. No technical standards for non-interfering systems authorized before

July 20, 1961. However, these systems must also meet the stringent standards after July 31, 1985. The following paragraphs discuss each of these provisions in turn.

### Stringent Standards

Systems authorized after July 1, 1976 preferably operate on prior coordinated frequency pairs chosen from specific lists provided in Part 94. The frequency of each transmitter must be maintained, within the tolerances shown in Table 1, over a  $-20^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  ambient temperature range.

Antennas must comply with certain minimum standards for directivity, to minimize interference to and from other systems. The requirements are stated in terms of maximum beamwidth and minimum off-axis radiation suppression. Category A and Category B antenna requirements are specified for each frequency band. For example, in the

6525-6875 MHz band, the maximum Category A antenna, half-power beamwidth is 1.5 degrees; for Category B the maximum beamwidth is 2.0 degrees.

Category A is mandatory in frequency congested areas which are identified in FCC Public Notice 64123. Category B is for uncongested areas. However, a current licensee in an uncongested area cannot deny area access to a new applicant, if an upgrade of an existing Category B antenna to Category A will reduce interference to an acceptable level. These levels are established in Section 94.63 of Part 94.

For a given frequency range, the beamwidth decreases with increasing diameter of the antenna dish. So, Part 94 effectively prescribes certain minimum antenna sizes. In the 6525-6875 MHz and 1850-1990 MHz bands, this equates to an 8 foot dish for Category A and a 6 foot dish for Category B.

*Table 1. Frequency Tolerances.*

FREQUENCY BAND (MHz)	FREQUENCY TOLERANCE (%)
952 - 960	0.0005
1,850 - 1,990	0.002
2,130 - 2,150	0.001
2,180 - 2,200	0.001
6,525 - 6,875	0.005
12,200 - 12,700	0.005
12,700 - 40,000	0.03
ABOVE 40,000 TO BE SPECIFIED IN AUTHORIZATION	

In the 2130-2150/2180-2200 MHz (for most antenna manufacturers) and in the 12,200 to 12,700 MHz bands, the minimum diameter is 6 feet for Category A and 4 feet for Category B. Two-foot diameter dishes are permitted for some paired 12 GHz frequencies, with restrictions on bandwidth, transmitter power and system length.

The off-axis radiation criteria are expressed in terms of minimum radiation suppression required at angles from 5 to 180 degrees from the centerline of the main beam. Separate criteria are listed for various frequency bands. Passive reflectors are exempt from these beamwidth and off-axis radiation requirements and continue to be allowed.

Part 94 does not specifically prohibit periscope antenna systems. However, their uncertain, and often unpredictable, off-axis radiation characteristics make it very difficult for new periscope systems to meet the radiation envelope standards required for certification. An exception is occasionally made for periscopes used at electric power facilities. On a case-by-case basis, these antennas may be excluded from the directivity requirements, if it can be shown that technical considerations preclude the use of other antenna types.

Passive reflector and periscope antenna systems often use the same type antenna and reflectors. Perhaps some latitudinal and/or longitudinal displacement from the antenna may qualify a reflector as a passive.

However, the FCC may disallow such a definition, on a case-by-case basis.

### **Less Stringent Standards**

FCC Part 94 permits the continued use, through July 31, 1985, of microwave systems authorized between July 20, 1961 and July 1, 1976, providing they were in compliance with the technical standards of the then appropriate Rule Part 87, 89, 91 or 93. Until Part 94 became effective, these other rule Parts governed operational-fixed microwave stations in the aviation, public-safety, industrial and land transportation services respectively. The older Rule Parts continue to provide the basis for VHF systems licensing and the eligibility requirements for prospective Part 94 licensees.

In the 6525-6875 MHz band, these older parts specified a frequency stability of  $\pm 0.02\%$  over an ambient temperature range of  $-30^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$ . A  $5^{\circ}$  antenna beamwidth limitation made it practical to use a 4 foot diameter dish alone or coupled into a 4 foot by 6 reflector (Periscope antennas were allowed in any area).

### **Least Stringent (No) Standards**

Part 94 also authorizes continued non-interfering use, through July 31, 1985, of radios and antennas which were authorized before July 20, 1961. These stations were originally licensed under old FCC Parts 7, 9, 10, 11 and 16. A transmitter frequency stability of  $\pm 0.05\%$  is typical of the

technical standards in these parts. Continuing operation of these older systems under Part 94 is also contingent on their not interfering with systems which conform to closer tolerances. The provisions for older systems are generally referred to as "grandfathering" rules.

Section 94.61 in Part 94 specifically states that all systems in the covered services must comply with the stringent standards after July 31, 1985. The pertinent part of this paragraph is reproduced below:

*SUBPART C — TECHNICAL STANDARDS*

*Section 94.61 Applicability*

*(a) The technical standards of this subpart shall govern, effective July 1, 1976, the issuance of authorizations for new stations and changes in authorized stations as specified in Section 94.45. Stations authorized prior to this date not meeting the provisions of this subpart may continue to be authorized for operation under previous technical standards as show in Section 94.92 through July 31, 1985. Except as provided in Section 94.65, effective August 1, 1985 all stations will be required to operate in accordance with the provisions of this subpart.*

Section 94.45 defines what changes in authorized stations will require FCC approval by license modification or special temporary authority. Section 94.65 contains tables of frequencies which are normally available for licensing under Part 94. These sections are discussed later.

The last sentence in Section 94.61 states that "effective" August 1, 1985,

all stations will be required to operate in accordance with the provisions of this subpart." "This subpart" is Subpart C-Technical Standards. Nevertheless, there is confusion among some users of microwave licensed before July 20, 1961.

The confusion apparently results from Section 94.92, paragraph (b). Taken out of context, this paragraph seems to authorize the operation of these older systems beyond August 1, 1985. However, it can be seen that this is not so when paragraph (b) is considered as a part of Section 94.92 and the whole Section is considered within the context of Part 94.

Section 94.92 follows:

*Section 94.92 Technical Standards for Stations Authorized prior to July 1, 1976.*

*(a) The technical standards indicated in the table in this section (Table 2 in this article) apply to private microwave systems using the frequency bands above 952 MHz listed in the table and which were authorized prior to July 1, 1976, but after July 20, 1961.*

*(b) These standards shall not be applicable to transmitting equipment (including antennas) which were authorized to be operated on these frequencies prior to July 20, 1961, or for which an authorization is issued based on an application filed with the Commission prior to July 20, 1961. Such licensees of equipment and systems not subject to these technical standards, including their successors or assigns in business, will be permitted to utilize such equipment provided such operation does not result in harmful interference to another station or system which is conforming to these*

Table 2. Part of Section 94.92\*

FREQUENCY BAND (MEGAHERTZ)	POWER (WATTS)	TOLERANCE (PERCENT)	BANDWIDTH	BEAMWIDTH (DEGREES)
952-960 .....	30	0.0005	100 kHz	20
1850-1990 .....	18	.02	8 MHz	10
2130-2150 .....	15	.001	800 kHz	10
2150-2160 .....	15	.001	10 MHz	360
2180-2200 .....	15	.001	800 kHz	10
2450-2500 .....	12	-	-	-
6525-6575 .....	7	.02	25 MHz	7
6575-6875 .....	7	.02	10 MHz	5
10550-10680 .....	5	-	25 MHz	4
12200-12700 .....	5	.05	20 MHz	4
ABOVE 16000 .....	5	-	50 MHz	-

\* FOOTNOTES AND EXPLANATORY MATTER DELETED FROM THIS ABRIDGED TABLE, BECAUSE THEY ARE NOT PERTINENT TO OUR DISCUSSION.

technical standards. In case of such harmful interference, such nonconforming licensee will be required to take whatever measures are necessary to alleviate the interference.

When Section 94.92 is taken as a whole, it is apparent that the standards referred to in the first line of paragraph (b) are the relaxed standard in the Table which is a part of the Section. If paragraph (b) is taken out of context "These standards" may be interpreted as meaning the Technical Standards in Subpart C, thereby leading to the mistaken conclusion that pre-1961 radios are "grandfathered" beyond August 1, 1985.

Paragraph (a) states that the standards in the Section 94.92 Table apply to systems "which were authorized prior to July 1, 1976 but after July 20, 1961." From our previous discussion and from Section 94.61 in the rule, it is clear that the standards in the Table will be completely

superseded by the Subpart C-Technical Standards, effective August 1, 1985. At that time Section 94.92 will have no reason to exist and will become null and void because it is subservient to Section 94.61.

In administering Part 94, the FCC has routinely granted approval for moving a non-compliant, pre-7/1/76 or pre-7/20/61 transmitter from one location to another providing the move is justified by the user as expediting a Part 94 upgrade of other parts of his system. Such changes in any part of his system will probably not jeopardize the "grandfathering" of any other part of his system through July 31, 1985.

### Sections 94.45 and 94.65

As previously stated, Section 94.45 defines what changes in authorized stations require FCC authorization by license modification or special temporary authority. The following

changes in antenna characteristics are listed as requiring license modification or special temporary authority:

- Any change in antenna azimuth.

- Any change in antenna beamwidth. (even if beamwidth is made narrower by using a larger parabola etc.).

- Any change in antenna or passive repeater location greater than 1 second or which involves a requirement for special aeronautical study.

- Any change in antenna height (up or down.)

- Any changes in antenna polarization.

- Any change in size of passive reflectors or repeaters associated with the facilities of an authorized station.

The following changes in radio parameters are also listed as requiring license modification or special temporary authority:

- Any change in frequencies used.

- Any increase in emission bandwidth beyond that authorized.

- Any change in type of emission.

- Any change in authorized effective radiated power (ERP) in excess of 3dB.

- Substitution of equipment having a different frequency tolerance.

An equipment change involving only a reduction in emission bandwidth or a change, within 3dB, of effective radiated power may be made by notifying the FCC. Formal license modification is not required in these cases.

All license modifications must be preceded by an interference protection analysis except:

- Any improvement in transmitter frequency stability.

- Any decrease in transmit power.

- Any decrease in antenna beamwidth while still maintaining the median ERP within 3dB of the licensed value (up or down).

The provisions of Section 94.45 are not only applicable to transmitter change outs. They also apply to any new transmitter installation. For example, if an "as-built" waveguide or coax run is longer than originally estimated and results in a decrease of more than 3dB in the median ERP, a major license modification must be initiated. The modification must be preceded by another interference protection analysis.

Section 94.65 of Part 94 contains tables of paired frequencies which are normally available for assignments in the Private Operational Fixed Microwave Service. New systems should make every effort to use these pairings.

This may not always be practical since systems licensed prior to July 1, 1976 may continue to use non-standard transmitter-receiver spacings. New systems may find it necessary to deviate from the standard frequency pairings to avoid interference into and from these older systems.

However, non standard pairings should be considered a last resort,

rather than an easy expedient, in solving frequency coordinating problems. Otherwise, the newer system may someday stand alone as an impediment to orderly growth in an area.

---

#### BIBLIOGRAPHY

1. *Rules and Regulations, Part 94 Private Operational-Fixed Microwave Service* Federal Communications Commission, Washington, D.C.
2. Public Notice 64123 *Private Microwave Congested Areas* Federal Communications Commission, Washington, D.C.

### *ANNOUNCEMENT*

Effective May 1, 1980, the U.S. domestic price of Selected Articles from the GTE Lenkurt Demodulator will be \$7.50 per volume — the Foreign price will be \$17.50. The new prices defray our costs for the books, including shipping charges. The books may be obtained by writing to:

GTE Lenkurt Demodulator  
M/S C134  
1105 County Road  
San Carlos, CA 94070

**GTE LENKURT**1105 COUNTY ROAD  
SAN CARLOS, CALIFORNIA 94070

ADDRESS CORRECTION REQUESTED


Bulk Rate  
U. S. Postage**PAID**San Carlos, CA  
Permit No. 37

E S

77024CRUE2315W0

W F CRUESS  
PFL INDUSTRIES INC  
12315 WOODTHORPE  
HOUSTON TX 77024

**GTE Lenkurt's  
high-performance,  
low-cost, 2 GHz,  
microwave system—  
the 79F1 is type  
accepted under FCC Rule  
parts 21 and 94. The 79F1  
also conforms to CCIR  
Recommendation 382-2.**

**Features:**

- Frequency Stability— $\pm 0.00025\%$ .
- Power Output—0.25, 5 or 10 watts.
- Programmable, digital AFC—all frequencies selected by strapping plug.
- Threshold extension.
- Self contained deviation test facilities.
- Occupies 7 vertical mounting spaces on a standard rack.

**GTE LENKURT****VIDEO, VOICE & DATA  
TRANSMISSION SYSTEMS**

The GTE Lenkurt Demodulator is circulated bimonthly to selected technicians, engineers and managers employed by companies or government agencies who use and operate communications systems, and to educational institutions. Permission to reprint granted on request.