



IN THIS NUMBER

- Tape Recorder Accessories A Special Survey
 Field Trial of a Brand New Battery Portable
- Using the Parabolic Reflector in Spain
 Teaching Tape Part 2 of a Special Series for Beginners
- You can start a Club
 The Collaro "Studio" Deck Reviewed
 Readers' Problems
 News and
 Pictures from Here, There and Everywhere




MAGAZINE TAPE DECK




SIMPLE — anyone can operate this deck controls reduced to an absolute minimum.

ROBUST — no need to worry about maintenance costs. Brilliant design has removed the complications.

ELEGANT — beautifully styled to tone with modern home furnishing.





THE GARRARD ENGINEERING ANDMANUFACTURING CO. LTD.Factory and Registered Office : NEWCASTLE ST., SWINDON, WILTSHIRE,Telephone : SWINDON 5381 (5 lines)Telex 44-271



CHOOSE IN PERSON– CHOOSE BY POST– NO INTEREST CHARGES

All makes of Tape Recorders and Hi-Fi Equipment. Make sure you get exactly what you want and what you need. Make sure you get it at the best H.P. terms offered anywhere today — No interest charges on orders over £30. Make sure you choose from the Tape Recorder Centre. Choose in person — compare different makes on the spot in the Tape Recorder Centre Showroom; or choose by post — get a Free copy of the unique 72-page illustrated Tape Recorder Centre catalogue, listing hundreds of models and types.






...with the wonderful

TAPE RECORDER

Speech, music, sound effects . . . you get VIVID REALISM every time with this fine tape recorder. This isn't surprising when you consider its many 'professional' features. What is surprising is that such a quality machine should be so modestly priced. Hear it at your dealer's and you'll realize that "His Master's Voice" offers TODAY'S FINEST TAPE RECORDER VALUE!

- * Two speeds: 7½ i/s and 3¾ i/s
- * Frequency response: 50-10,000 c/s at $7\frac{1}{2}$ i/s \pm 3dB
- * Takes 7" spools
- ₭ Half-track operation
- ★ Three-motor drive
- * Separate record and playback amplifiers
- * Three head system for instantaneous playback
- * Pause control for instantaneous stop/start



Complete with 1,200' Emitape, spare spool and crystal microphone.



11111


THE GRAMOPHONE COMPANY LIMITED . HAYES . MIDDLESEX

PHILIPS TAPES... better for all tape recorders!

On any tape recorder, Phillips Tape gives you better results. It has great sensitivity, a very wide frequency range, and extremely low noise level. This superlative tape is equally good for music or voice recording. Available in all reel sizes from $3^{"}$, $5^{"}$, $5^{3^{"}}$ and 7". For those building up a reliable tape library, Philips 5", 53" and 7" reels are specially packed in durable books designed for convenient storage, and quick easy reference.




- Strong puc base.
- Resistant to stretch, snapping and tearing
- Powerful adhesion of magnetic coating
- Unvarying high-quality performance
- Standard, long-play, and double-play tapes available



NUSOUND RECORDING CO.

TAPE RECORDER SPECIALISTS







IN STOCK:

Recorders by: FERROGRAPH * VORTEXION * SIMON H.M.V * REFLECTOGRAPH * GRUNDIG * KORTING COSSOR ★ MINIVOX ★ HARTING ★ WYNDSOR ★ Etc. TAPES * MICS * STANDS YOU ARE INVITED TO VISIT US MIXERS * TUNERS * Etc.

MAIL ORDERS by return

- Send for lists
- Continuous demonstrations
- After Sales Service
- **Deferred Terms**

RECORD HOUSING Equipment and L.S. Cabinets

LONDON SHOWROOM

35 Craven Street. Trafalgar Square, W.C.2.

Telephone : TRA. 2080

THORNTON HEATH (CROYDON) SHOWROOM (1st Floor)

3/8 Brigstock Parade. London Road,

Thornton Heath, Surrey

Telephone : THO. 7609 (Opp. Thornton Heath Bus Depot)

Amplifiers by: LEAK * QUAD * ROGERS * Etc. Speakers by: WHARFEDALE * GOODMAN * TANNOY VITAVOX * LOWTHER * ACOUSTA-TWIN AND

ACOUSTA * QUAD ELECTROSTATIC Etc.

RECORDERS FOR EVERY REQUIREMENT

Where Portability Counts!



The STUZZI MAGNETTE

Really portable:

8lb. Transistorised, Battery Operated.

Really reliable: B.O.A.C. use it operationally on the Comet.

Really good quality:

And all the facilities of a mains recorder. Price: 69 gns.

Where only the best will do!



The STUZZI TRICORDER

HONEST VALUE FOR MONEY! SENSATIONAL NEWS!



WITH ALL THESE FACILITIES

Made possible by many years of experience and large scale production

- ★ Built-in Mixer * Tone Control * Twin Track Recording
- * Monitor on Record ★ Inclusive of Mic
- * Magic eye
- * Superimposition ★ 90-9000 cycles * Best quality Tape
 - and 53" Spool

ALL THIS 27 GNS.

7. D.C. Heating

9. Built-in Mixer

12. Tone Control

10. Monitor on Record

8. Auto Stop

- I. 3 Speeds
- 2. 40-16,000 cycles
- 3. 12 hours on one reel
- 4. Remote Control
- 5. Slide Projector Control 11. Variable superimposition
- 6. Twin Loudspeakers


Price 75 gns.

Choice of Mics extra

For further details Write Now or Phone:

Recording Devices Ltd.

44, Southern Row, Kensington, London, W.II. Telephone : LADbroke 4775



Notice to Manufacturers

Whatever your product, and whatever its state of development, a photographic record can be invaluable — for future reference — for publicity — and for sales. We specialise in the photography of industrial products — particularly electronics — in black-and-white (as above) or in colour, for showcards and catalogues. We are the official photographers for Hi-Fi News and The Tape Recorder. Our prices are very competitive, and we invite your enquiries.

COLOUR PRINTERS (LONDON) LTD. 29 GEORGE STREET - LONDON - W.I - HUNTER 1771

There are two kinds of people who'll want this new

2.0



.... Two quite different kinds of people will want the new TK 24 — the inexperienced and the experienced. The inexperienced because they don't know any better and the experienced because they don't know any better either: because there isn't any better than this brilliant new four track Grundig model.

The new TK 24 makes no compromises. It doesn't ask you to choose whether you want high fidelity or long play—it gives you both! All the time! Six hours record/playback.

It doesn't ask you to scrap all your existing conventional twin track 3³/₄ i.p.s. tapes — it lets you play them back as well (and how good they sound !).

It doesn't expect you to have to make complicated arrangements to produce special trick effects — *it allows two tracks to be recorded separately and then played back together*. (Normally, of course, you would play them back separately to get the doubled playing time that four track gives you).

In fact it's the most accommodating tape recorder ever made—even by Grundig!

No matter how much you know—or don't know—about Tape Recorders, go to your nearest Grundig Approved Dealer and have him demonstrate the TK 24.

See and hear Grundig quality for yourself;

the simplicity, the compactness, the styling, the really first rate performance of a new model that will stay 'new' for years.



Advertising & Showrooms : 39/41 New Oxford Street, London, W.C.I Trade enquiries to : Newlands Park, Sydenham, London, S.E.26. (Electronics Division, Gas Purification & Chemical Company Limited)

of the	send me the free fully illustrated leaflet wonderful new TK 24 four track model corder.
Name	
Addre	S
Neare	t Town GS. TR. 23



Going for Britain's most popular tape recorders

It's happening everywhere. Suddenly everyone is seeing the sense of buying a British tape recorder. Finding that British electronics, British engineering have no equals in this world. And finding that now here else do electronics and precision engineering combine so effectively as in the Elizabethan range. Noothertaperecordersavailabletoday offersuchadvanced features, such sheer technical accomplishment at such ridiculously reasonable prices.

Without exaggreation, this superlative new machine offers a standard of performance and a range of facilities only found previousand a range of facilities only found previous-ly in highest grade professional equipment. Specially fitted 3 micron gap recording head gives phenomenal frequency response and the 6 watts push-pull output ensures sound reproduction of a uniquely high order. Supplied with 7" reel of 2,400' double-play tape 65 gns

Microphone optional extra



TAPE RECORDERS



GOING FOR THE PRINCESS! Going for tremendous performance ... terrific value ... and getting both. 3 speeds, 7" spools, four hours' playing time. Facilities for mixing and superimposing.





Going for today's most astonishing tape recorder value. A first-class machine with excellent recording quality and sound re-production. With facilities for sound mixing and superimposing. With simple controls, elegant styling-and all at a record low price.

27 gns complete

ELIZABETHAN (Tape Recorders) LTD., ROMFORD, ESSEX. Tel: Romford 62366/7

FILL IN AND POST TODAY! To Elizabethan (Tape Recorders) Ltd., Bridge Close, Romford, Essex. I'd like to know more about the Elizabethan range. Please send me your free illustrated leaflets by return of post. NAME ADDRESS. TRR1

th				7	Λ						
1	A	Į	Ĩ			ŀ	Ţ		K	C	ORDER
											MILES HENSLOW

Assistant	Editor	-	-	**	•	w	•	-	•	٣	-	÷	- Ju	lian	Berri	sford
Editorial	Offices	-	-	•	•	99	9	M	loi	ti	me	er	Street	, Lo	ndon,	W.1

MUSeum 3967 to 3969

*

Telephone - - - -

EDITORIAL

LAST year saw its beginning: this year the tide is beginning to run at the flood. The small, battery-operated portable tape recorder is finding its way into the holiday luggage sideby-side with the camera, the portable radio and the cine camera. The forthcoming Autumn months promise to be enlivened with sound recordings of the annual event on a scale that was quite unthought of eighteen months ago. And, month by month, new versions of these small portables are appearing on the market. Last year there were about five: today there are about a dozen, and news comes of more on the way. In many ways the pattern seems to be following that of radio.

The only difference between the two is that radio has been with us for about 35 years, whereas tape has had barely ten years in which to establish and popularise itself. It is this difference, however, which really points to the tremendous potentialities of tape—this and the fact that tape offers itself as a creative medium, whereas radio must be classed as "entertainment on tap".

It is interesting to see how tape is already being used in its portable form, and with particular emphasis on holiday use. First comes its most obvious use, the holiday "sound snaps' that are now being collected, in much the same way as "photo snaps" are collected, of growing children, parties, picnics and animals. Next, the business use to which portables are put. Authors and journalists are using recorders in increasing numbers, for odd-moment chapters, articles and notes. Business men use them for dictating spools of letters and memoranda which they send back to their offices for action-a nice, lazy way of permitting urgent business to interfere with holiday pleasure! Then come the growing army of cine enthusiasts who are using portables for recording on-the-spot sound effects and commentary for linking up with their films-either for dubbing on to Zonal stripes, or for building up into edited lengths for recorder/projector synchronisation. Next come the Colour Transparency enthusiasts who prepare tapes to accompany their home slide projection. Finally, there are those who carry around with them their own prepared spools of musical entertainment, e.g. for use in the car.

So far, the battery-operated portable recorder seems to be falling into two fairly distinct classes. On the one hand we have the really small, note-book type: on the other hand we see the medium-sized instrument, which is just big enough to do service as a domestic recorder, but which is also small enough to be carried around as a means of entertainment. There is no doubt that the coming twelve months will see big developments in the field of portables, and there is still less doubt that the portable will find its way into many more homes, doubling up for the less portable mainstay. But, as a concluding note for those who intend to make tape a feature of this year's holiday, let us add the warning that many *are* thinking that way, so do not leave it too late!

JULY ---- 1960

Dago

- CONTENTS -

		Page
		275
		281
		285
		286
		289
		291
ş		292
		297
		301
		305
		308
		310
	···· ···· ···· ····	··· ··· ··· ··· ··· ··· ··· ···

-COVER PICTURE -

GOOD equipment is always good to look at, particularly for the eyes of the real enthusiast. We do not know the accurate details of all that is shown here, so we will risk no mistakes and subsequent apologies! Suffice it to say that what is shown is at once the hobby and the work of one of America's most sincere disc producers—Mr. E. D. Nunn. He is the president of Audiophile Records Inc. In the June number of *Hi-Fi News* we showed a corner of Mr. Nunn's living room, as an example of living spaciously with hi-fi. Here is his laboratory, where he is at work cutting a disc from a tape master.

- NEXT MONTH -

A PARTICULARLY full schedule of features is lined up for our August issue. Firstly, there is a Survey of Microphones, which will make an excellent guide to prospective shoppers, and will clear up some of the doubts about impedances, etc. Then we have the complete wiring and setting up instructions for the *Time Switch*, an introduction to which appears on page 286-287 this month. *Field Trials of Battery Portables* is devoted to a most interesting new recorder from Germany—the Butoba, and there will be the usual full coverage of *News*, *New Products*, and *Equipment Reviews*, plus a further article by James Moir on *Reviewing Tape Recorders*.

The Tape Recorder for August-On Sale July 22.

SUBSCRIPTION RATES

The subscription rate to *The Tape Recorder* is 21/- per annum (U.S.A. \$3.00) from The Tape Recorder, 99 Mortimer Street, London, W.1. Subscription+Index, 24/-(U.S.A. \$3.25).

Sensational success of **audiotape**

... on the sensational C-SLOT REEL!

Tape Recording experts and enthusiasts all over the country are changing to AUDIOTAPE for its flawless perfection of sound reproduction over the entire audio range and its *consistent*, *uniform quality* from reel to reel.

Available on all standard reel sizes, there are eight different types to meet every recording requirement. AUDIOTAPE, manufactured in the U.S.A., by Audio Devices Inc., gives you the truest sound your recording equipment can produce—try AUDIO-TAPE . . . it speaks for itself.

Sensational C-SLOT REEL

All 5" and 7" reels of AUDIOTAPE are supplied on the exclusive C-Slot Reel—the fastest-threading tape reel ever developed. The tape end, dropped into a slot in the hub, anchors itself automatically at the first turn of the reel.





A NAME FOR BETTER PERFORMANCE

Concessionaires to the United Kingdom

LEE PRODUCTS (Gt. Britain) LIMITED

"ELPICO HOUSE," LONGFORD STREET, LONDON, N.W.I

Telephone: EUSton 5754 (all lines)

Telegrams : Leprod, London

HERE AND THERE ANDEVERYWHERE

Congratulations, Stan Futter!

WE learn with pleasure that Mr. H. S. (Stan) Futter, Publicity Manager of The Gramophone Company, has been elected Mayor of Twickenham. His many friends will echo our congratulations. Mr Futter has been a councillor for Hampton Hill Ward since May 1949. He was elected to this new office at the annual meeting of the Corporation on 26th May last.

Romford is on Tape-Toes

A BRIGHT idea on the part of the Surveyor's department of Romford Borough Council resulted in a novel and successful traffic census last month. On 25 and 27 May, at nine census points surrounding the town, the numbers of all motor vehicles entering and leaving Romford were recorded; and at four of the busiest points the numbers were spoken into tape recorders. Elizabethan, the local manufacturers, loaned the recorders, and these were set up on tables beside the checkers. All but buses and motorcycles were noted. The object was to determine points of entry and exit of vehicles using the town in peak hours. The census was very successful, and it provided statistics that will greatly assist the Borough Council in planning a ring road to intercept and direct all "through" traffic from the town centre.



Australian TV reporter Panda Lisner uses a Fi-Cora municiture battery-operated recorder to interview Maureen O'Hara in Hollywood for her programme on GTV Channel 9, Melbourne. (Photograph by courtesy of GTV Channel 9, Melbourne, and the Australian "TV Week").



Nine Elizabethan tape recorders, at selected checkpoints, helped Romford Borough Council with a traffic census. (See story elsewhere on this page.)

Parabolic Reflectors

OUR current series of articles on dish or parabolic reflectors for microphones has created a very great interest, and many readers have written to us to ask whether we know any sources of supply. We now learn from Grampian Reproducers Limited, The Hanworth Trading Estate, Feltham, Middlesex, that they have been carrying out a number of practical experiments in this field and that they intend shortly to market a Parabolic Reflector for use with their type DP4 and DP5 microphones. No details of this proposed product are yet available from Messrs. Grampian, but we suggest that readers who are interested should write direct to the above address. We know from our own postbag, and from conversations with manufacturers of tape recorders during the past eighteen months, that there is a very real need for such an accessory, and particularly among the bird-watching enthusiasts. We therefore look forward to more news and suggestions on this subject.

New Tape Recorder Centre Catalogue

THE Tape Recorder Centre, 75 Grand Parade, Green Lanes, Harringay, London N.4., have just completed their new 1960 catalogue, which is available to readers from that address. This well-illustrated booklet lists some 28 of the better known makes of recorders and decks, plus tapes, mixer units, microphones. It also includes a selection of amplifiers, control units, speakers and cabinets, etc.



HOW OTHERS USE TAPE

A silver microphone is presented by the South Manchester T a p e Recording Club to the member producing the best 5 minute "Tape of the Month".



Tape and tape recorders are cropping up everywhere these days, and yet this special issue postage stamp took even us by surprise (details below).

And now a "Tape" Postage Stamp

A^N interesting news item has reached us from Tom Morgan, editor of *The Philatelic Magazine*, 27 Maiden Lane, Strand, London W.C.2. It is about the first postage stamp to feature "tape" (illustrated on this page).

Collectively, the postage stamps of the countries of the world picture almost everything, and the tape recorder is not one of the exceptions. A tape recorder and a spool of tape is to be shown on a new stamp to be issued by the Republic of China, or in other words Formosa. Purpose of the issue is to publicise the Chinese Phonopost Service. This service was inaugurated on an experimental basis on 20 March, 1959 for the purpose of promoting the morale of the Armed Forces and meeting the requirements of the public. Instead of writing letters, men and women on active service could make recordings, send the tape home, and the family could reply in similar fashion.

So far, the Phonopost Service has been limited to the post offices at Kinmen, Taipei, Taichung, Tainan, Koahsiung and Hwalien but it will be extended to other places when it is considered necessary. The design of the new stamp shows a soldier speaking into a microphone, a spool of tape winging its way across the centre, and a woman apparently knitting while listening to a recording. The face value of the stamp is NT\$2.00 and it is due to be issued towards the end of June.

Some 20 years ago, Argentina issued three Recorded Message Stamps, the designs showing gramophone records. They were payment of special fees for postage on messages recorded on discs for transmission by post. But tape is coming very much into its sister hobby of philately. The American First Day Cover Society of New Jersey offers five tape recorded programmes to societies. Among them is an interview on the Steinway collection of music on stamps; a talk by an official of the British Crown Agents; and James Roosevelt on the famous FDR collection.

A Twinset for the Clarion

A REALLY novel and practical idea for extending the use and efficiency of a small portable is Clarion's new "Twinset," the first pre-production model of which has just reached this office. It is a neat shoulder-strap type carrier, divided into two compartments. The lower half contains a transistorised amplifier and speaker. The upper half is tailored to take the Clarion recorder. Merely by slipping the Clarion into this compartment and by plugging in one lead, the additional electronics and speaker are brought into use, thus increasing its effectiveness to the extent of an approximate $\frac{1}{2}$ -watt output, and bringing it into line with the smaller domestic recorders. Production of this "Twinset" device is now under way, and it is probably that supplies will be available by the time this number of *The Tape Recorder* is on sale. The price is 8 gns. Price, complete with Clarion, 33 gns.

* * *

Ferrograph change of address


WE have recieved the following note on address changes: "Pending the completion of new offices at Cromwell Road, Kensington in 1961, The British Ferrograph Co., Ltd., are moving on 24th June to temporary offices at 88 Horseferry Road, Victoria, S.W.1. Telephone SULlivan 5426/7/8."



Eric Robinson, photographed in his home complete with Grundig, is a keen tape recorder user. BBC viewers have come to know him through "Music For You", but he conducts a great deal of "off vision" music besides.

HOW OTHERS USE TAPE cont.

A prize worth winning; David Nixon holds up one of 15 Grundig Cub recorders presented in a recent Mondart Ltd. "Ton of Silver" competition.



Wyndsor aid screen publicity

Rank Screen Services Limited have recently produced a fifteen seconds filmlet which is specially designed for dealers in tape recorders to use for advertising in their local cinema. Wyndsor Recording Company were asked to co-operate in the making of this film at a time when the Wyndsor "Victor" recorder was in final development in the laboratory.

Presentation is in model animation form, and shows three British made tape recorders in beautiful colours. A local dealer may have a print of this film carrying his own name and address and with a suitable sound commentary. The initial outlay is exceedingly small, only a few pounds, and representatives of Rank Screen Services of 11 Hill Street, Mayfair, London, W.1, are available to visit dealers to explain the details and to quote terms to dealers who may be interested.

We hope the response was good

A READER sends us a cutting from the Cambridge Daily News, in which a Classified "For Sale" advertisement offers: "1916 Army Dress Sword and amplifier with speaker." He remarks that he cannot quite see the connection, but that it might apply to top or base cut.

M.M.M. Most Sincere apologies

OUR reporter announced (June number, page 236) that M.M.M.'s new One-Five Special is a 3-inch spool of No. 200 Tensilized Polyester Double Play. This is incorrect. Minnesota ask us to confirm that it is in fact a 3-inch spool of standard grade Magnetic Tape. We apologise for this mistake, and for any inconvenience it may have caused our readers and its manufacturers.

A New Recorder from Philips

The new Philips "Family" tape recorder (Model EL 3541) has been completely restyled and sells at 34 gns. Its four tracks give up to eight hours recording with double play tape and a new tape deck layout simplifies operation. It is supplied complete with a 5 in. reel of long play tape, crystal microphone, and spare take up spool. Speed is $3\frac{3}{4}$ i/s.

Take Your Pick-and Recorder

THE immense popularity of tape recorders is constantly being reflected in the "prize lists" of contests and television games and programmes where, it seems, scarcely a week passes without some lucky winner walking away with one model or another. We have already noted several of these events in recent numbers of *The Tape Recorder*. Two more have just been announced. A major prize in the Associated-Rediffusion quiz game "Take Your Pick" was a *Wyndsor* "Victor," and was won by Mrs. Coles of Smethwick, Staffs. Again, at a recent contest sponsored by Mondart Ltd., at a reception in London's Dorchester Hotel, fifteen *Grundig* "Cubs" were presented to runners-up. This contest, "Ton of Silver," attracted over 28,000 entries. Our photo shows David Nixon presenting one of the fifteen!

Free-Seven Old-fashioned Villains!

FOR readers who would like an amusing booklet, which at the same time gives 7 useful pointers towards avoiding tape troubles, we recommend a letter to Wilmex Limited, 70 St. Stephens House, Bridge Street, Westminster, London S.W.1. The booklet is illustrated below.



Autumn Audio Fair for Southport

THE 1960 Autumn Audio Fair, already announced for Southport, has now been definitely arranged for Friday, Saturday and Sunday, 7, 8, and 9th October, at the Palace Hotel. Further details will be announced shortly.

Tape healing

Mr. P. Ager N.D., D.O. has had over thirty years experience in dealing with psychological ailments in his clinic. For several years he investigated the use of recorded tapes in connection with the treatment of various psychological disorders including nervous fears, stammering, blushing. Further details may be obtained from Educational Recordings Psycho Tapes Institute, 27 York Road, Ilford, Essex.

NEWS AND PICTURES FROM THE CLUBS

Tape Clubs Congress

The first ever Congress of British Tape Recording Clubs was organised by the Federation of British Tape Recording Clubs, and took place on Saturday, June 11th in the Russell Hotel, London. The Chairman, Alan Stableford, had drawn up a most interesting programme.

Sandwiched between the morning introductions and the evening A.G.M. there was a highly instructive and entertaining type of open discussion. For approximately one hour, the delegates—some 40 representatives of about 20 clubs—divided into four discussion groups and then "came together" to shoot questions at a panel representing various facets of the tape recording world.

The four headings were as follows:—"Future developments in tape recording equipment", "Amateur tape recording and the BBC", "The tape recording press", "The function of tape recording clubs".

The panel consisted of Mrs. Marguerite Cutforth and Mr. L. G. Dive (BBC); Miss Brenda Marriott and Mr. H. Spring (Grundig); John Borwick (*The Tape Recorder*), and the editors of "Amateur Tape Recording" and "Tape Recording", with Alan Stableford in the chair.

Amongst the questions asked (and for the most part satisfactorily answered!) were, "What constitutes a good tape recording?", "Could manufacturers fit less gold trim and more facilities?", "Does the BBC encourage or accept recordings from amateurs?", "What useful work can clubs do through the Council for Social Service, etc.?", "Why no CCIR standard for $3\frac{1}{4}$ i/s?", "How can experts be invited to talk to clubs?"

The Federation are to be congratulated on a highly successful experiment, which, like their sponsorship of the National Contest, we hope to see repeated each year.

As a spur to wayward members, the Nottingham Co-operative Amateur Tape Recording Club committee are sending "tapespondence" requesting ideas and views for future meetings



Les Wake is a recording engineer with R.S.C.A. Recordings, Thanet, and something of a genius at producing gadgets and special effects. The electronic mixer, seen here in use with a Ferrograph is all his own work.

to those members who attend infrequently. Members who do not wish to pay the full subscription will be admitted on payment of one shilling as Guest Members. Meetings are held on alternative Thursdays. At a recent meeting a ten minute feature programme entitled "Saturday roundabout visits the London Planatarium"—which was produced at the Third National Tape Recording Course held at Sidcup—was played and discussed. Their Social Evening is planned for the 7th July.

A colour film entitled "Shakespeare's Avon", which spotlights the beauty of the local countryside, entertained the **Rugby Amateur Tape Recording Society** members at a recent meeting.

A demonstration tape highlighting the differences between four popular makes of microphone concluded a recent gathering by the **South-West London Tape Recording Society**. The Society recorded a reply to a letter received from an American correspondent—their response, which covered all subjects from Caryl Chesman to Russian leadership in space exploration, sounds highly controversial. Prospective members should write to the Secretary, 6 Disraeli Gardens, Fawe Park Road, Putney, S.W.15.

The Grapes, Bridge Street, Stafford, is the new meeting place for the **Staffordshire Tape Recorder Society**. They hope to buy some communal equipment shortly, and have already organised a dance in aid of funds. The Stafford Amateur Cine Society teamed up with them at one meeting, to present several films, with taped commentary and dialogue: a great success.

Several enthusiastic members of the Warwick and Learnington Amateur Tape Recording Society visited the London Audio Fair, to catch up on all the latest models, domestic and foreign. A party also visited the Coventry Tape Recording Club to hear a representative of E.M.I. talk on magnetic tape.

"Youth" was the accent at one recent meeting, and experts from the recent "Marathon Jive" session held at Royal Leamington Spa, together with recordings of the Blackdown High School Choir, held the members enthralled. A tape entitled "Ghosts"—made at Squire Wills's home, which is believed to be "haunted"—certainly achieved some frightening and strange man-made sounds. Five of the latest portable tape recorders were given a "side-by-side" test recently, and a special demonstration of portables was conducted by Mr. W. Tyson.

We have received a request from Mr. B. J. Race, 30 Ashford Road, Whitnash, Royal Learnington Spa, that any lonely or crippled person who lives in the area should contact him for details of a special tape service. Please do not ignore his offer if this applies to anyone who needs, or would like, this service.

The Urmston Tape Recording Club, 30, Kirkstall Road, Urmston, Lancs. is a young club. They meet twice a month, and would like to hear from any prospective members.

Members of the London Tape Recording Club were given the opportunity of acting in a play written by Mr. Terry Devereux. The scripts were given to the members ten minutes before the recording. Mr. Roger Aslin produced and Mr. Alan Pierce recorded the play which lasted for 30 minutes. The tape was then given to the Club Library.

NEWS AND PICTURES FROM THE CLUBS continued....

Surely one of the best things about joining a tape club is the opportunities a newcomer has to benefit from the experience of others. In nearly every club there will be at least one member, or a nucleus of members, who have dabbled in tape recording for quite a few years, and who like nothing better than ironing out wrinkles for others. Even if your club arranges a full lecture season of visiting experts, there is no substitute for these informal "nattering" sessions such as that illustrated (right), in which four members of the Nottingham Co-operative Amateur Tape Recording Club gather round an opened-up Ferrograph and Telefunken



The Butoba was demonstrated at the West Middlesex Tape Recording Club and members were impressed when the tapes recorded on the portable were reproduced on the mains recorders. New members wishing to join this Club should note the address of future meetings:—The Red Lion Hotel. Hampton.

The Windsor Youth Theatre Company is changing its name and constitution on July 1st. It will then become the **Phœnix Drama and Tape Recording Society** with the existing members of the old company forming the nucleus of the new Society. There will be no age limit. Any person wishing to join should contact Mr. A. C. C. Smith, 73, Kings Road, Windsor, Berks. who will supply them with further details.

A tape recording of the Renegades rehearsing their recent production of Arthur Miller's play "A view from the Bridge" was featured in the fifth edition of What Goes On Here presented by Mr. Walter Gillings Sound Features to the Blind Club at Fellowship House, Ilford.

Two representatives of the **Ipswich Tape Recording Club**, Messrs. John F. Cooper and Malcolm Wilding, attended the Annual Congress of British Tape Recording Clubs held on Saturday 11th June. At their last meeting Mr. John Glover spoke on the recent course given at the Rose Bruford Training College.

Thanks to the generosity of a famous local dealer, who kindly placed a stand at the disposal of the Leicester Tape & Hi-Fi Club, the latter presented an ambitious display on amateur tape recording at the Leicester Audio Fair. A special commentary was recorded for the occassion, showing the endless possibilities of tape. Many new members have been attracted by this display.

Mr. R. V. Huddlestone, Chairman of Grantham and District Tape Recording Club would like to hear from any readers interested in forming a Stereo Recordists Club. Letters to be sent to R. V. Huddlestone, 33 London Road, Grantham.

The South Manchester Tape Recording Club has been in existence for three months and now have twelve members.

Club meetings are held at the British Legion, Wilbraham Road, Chorlton-Cum-Hardy.

More than 70 district ministers of the Methodist Church are now using taped material, recorded on a Philips tape recorder, in their work. The tapes are supplied by a unique library service started last December by the Rev. John Davies B.A of Maple Avenue, Horwich, Bolton, Lancs.

Mr. P. Holloway, 29 Fishery Road, Hemel Hempstead would like to hear from any person in that area interested in tape recording. A Club has already been formed and new members. can be assured of an interesting evening.

Mr. M. H. Eatly, Area Manager of Grundig (Great Britain) Ltd. gave a demonstration of their latest equipment to a well attended meeting of the West Wales Tape Recording Club. Stereo and Monaural tapes were played and questions were dealt with after the demonstrations had finished.

Waterloo enquiries reply-by tape

HAVE you heard this one? If not, ring Waterloo Passenger Enquiries at a busy time. "This is Waterloo 5100. I am sorry to keep you waiting, but all the telephones in the enquiry bureau are for the moment engaged. Please hold on, and you will be put through automatically to the first line that is free. This is a recorded announcement." And so on, with a pause of 20 seconds between each. How very much better than the interminable "burp-burp...burp-burp." of the engaged line. Full marks, British Railways.

Tape recorder work bench

There is no instalment in the Workbench series this month, due to the author, A. Bartlett Still, being on holiday. He will return next month with a discussion on the use of the Magic Eye to avoid overload distortion.



By E. D. H. JOHNSON

DESIGNING AND USING A REFLECTOR

PART FIVE ALL TYPES OF RECORDING IN SPAIN

Flamenco singing and a local Forestry workers' dance was recorded by hanging the microphone from a carbide lamp. (photo Eric Hosking).

A^T the beginning of last year I was invited by Eric Hosking, the internationally famous bird photographer, to join him in an expedition which he was leading to the Sierra de Cazorla, a mountainous and remote region in southern Spain. The object of the expedition was to study the birds, reptiles and some of the mammals of the district, which is a national forestry and game reserve, difficult of access and extremely rugged and precipitous. My principal role in the ten-man expedition was to be that of cinematographer, one of a team of three, but in addition I had the task of recording as much of the bird voice as possible, for use in conjunction with the film of the expedition as well as for scientific study and broadcasting.

The rolling plains of northern Andalucia stretch as far as the eye can see, the red soil dotted with regularly spaced olive trees or hatched by the lines of vineyards. A sixty-mile drive through such country was over some of the worst roads in Europe, where every rock and pot-hole threatened to shake the filaments out of the valves in the recorder, but at the end of the journey we were rewarded by the sight of the Sierra, rising sheer out of the plain to a height of over seven thousand feet, like a gigantic fortress. The road to the only pass through which we could enter clung to the jagged limestone cliff-face like a goat-track and whisps of cloud capped the highest peaks.

Our preliminary exploration during the next few days showed a tremendous variety of scenery and landscape. Vertical limestone cliffs towering two thousand feet high were weathered into fantastic shapes, with Choughs, Ravens and Alpine Swifts wheeling about the peaks, Griffon Vultures nesting on the ledges and an occasional Lammergeier, the rare bearded vulture, with its eyrie in a cave in the cliff-face. Deep gorges with swiftflowing mountain streams alternated with high plateaux where the vegetation was strangely park-like. The few inhabitants tilled the shallow, black, stony soil in the more gently-sloping upland valleys, or *navas*, using ploughs which have remained unchanged since biblical times.

The melodious warbler

The lower slopes of the *navas*, were covered with berberis and oak scrub and in the alpine meadows above was the most wonderful profusion of wild flowers, of which the peonies and asphodels will always remain with us as a lasting memory. It was here that we found the majority of the song-birds which were to provide most of my recorded material. Spectacular though the many species of eagles and vultures were, they provided little for the microphone to record, although they made magnificent material for the ciné cameras.

One of the commonest birds in the berberis scrub on the



slopes of the valleys was the Melodious Warbler, a most vociferous songster whose prolonged babbles continued for minutes at a stretch with no apparent pause for breath. There is tremendous variation in the song, which includes phrases from the songs of neighbouring species. Truly the Melodious Warbler lives up to its scientific name of Hippolais polyglotta, which suggests that it speaks "with the gift of many tongues" It often shared a habitat with the Nightingale whose phrases could be detected in its song, perhaps as an example of mimicry as a means of keeping birds of other species out of its territory. It was not a difficult bird to record. I had simply to stop the car near a convenient patch of scrub, set up the tripod and reflector, put down the earth pin and train the parabola on to the bush in which the bird was singing. The greatest difficulty was to know when to stop, since it took a long time to record a representative selection from his repertoire. One of my recordings contains an interesting passage with a Melodious Warbler and Nightingale singing together.

Nightingale and tape recorder duet

The Nightingale has been recorded so many times that I feel I need hardly mention it, but something which occurred early one morning is perhaps of interest. I had just finished taping a fairly long passage of Nightingale song and was playing it back as a test for quality, when the bird I had recorded began repeating it, phrase for phrase with the recorder. Each group of notes from the loud-speaker was exactly imitated by the bird, to the end of the passage, which was of about a minute's duration. It did not wait for the ends of the phrases, but followed note for note, a second or so behind the recorder.

One of the most important facilities a tape recorder can possess, from the point of view of the bird-recordist, is the ability to play back at a substantial level in the field. This is invaluable for inducing a bird to sing at a time when it may be disinclined to do so. Song is fundamentally a means of proclaiming ownership and occupation of a territory and an intruder of the same species is normally greeted during the breeding season with a loud burst of song. A good example of the use to which playback can be put occurred when I was trying to record Bonelli's Warbler, in the pines at the edge of the same scrub area in which I had already recorded his cousin the Melodious Warbler. He presented an entirely different problem, with intervals of several seconds between each short song-phrase and a habit of changing his perch at short intervals to sing arond the perimeter of his territory. It was necessary to obtain as long a recording as possible, to show the interval and the timing, and he did not help matters when he stopped singing almost as soon

	on INTEREST	PE RECORDERS
Model Grs.	Deposit from 20 I know how difficult it is to choose <i>the</i> Tap come to the Royal Opera Arcade, because r given. Full demonstrations at any time and most interesting machines. Remember—I	can buy by post with perfect confidence 0% 12 months to pay be Recorder. That is why more and more people my advice, personal attention, and help are freely d you can always examine and hear the latest and am here to help you. LAURENCE DICKINSON. if you are unable to call.
Philips 3515	PHI	
Perth Saja Deluxe 56 Brenell 3 Star 58 Veritone 58 Mobile 58 Ficord 59 Grundig TK25* 62 Telefunken Deck* 63 Korting Stereo* 68 Telefunken 4 track with Mic 69 Brenell MKV with Mic 69	earphone SERVICING. We undertake Rapid and Efficient Servicing of all Tape Recorders. TAPES. Audio, Agfa, B.A.S.F., E.M.I. GELOSO, Scotch Boy, Telefunken, etc. Send for lists.	12s. 6d. Packed with Information. TELEFUNKEN DA CAPO RADIO, 39 gns. Call and Hear this fine instrument. TELEFUNKEN TAPE DECK, 63 gns.
Grundig TK 30*	CAMERAS. By Zeiss, Agfa, Eumig, Voigtlander, etc. Send for lists. Dickinsons of Pal II ROYAL OPERA ARCADE, PALL M.	Telefunken Radio. Mall Ltd. The Royal Overa Arcode lies behind Her Majesty's Theotre in the Haymarket (one minute from Bircodilly, Circus, er
	BOOKLETS! dings" (Irish Tape) and Our SENSATIO DIFFERENT MODELS!	ONAL
! R. B. TAPES DO Brand-new FAMOUS FOREIGN T offered at the Fantastic Price of 35 including TAPE, MIC, AUTOMATIC MIXING, FREQU. 50–16,000 cps. 2 output!	GNS Balance 24 mths. TAPE STOP, FULL	
GRUNDIG Cub £27- 6-0 dep. £ 5 FIDELITY Argyll £30- 9-0 dep. £ 6 SIMON Minstrelle £40-19-0 dep. £ 8 WYNDSOR Victor £47- 5-0 dep. £ 9 TELEFUNKEN 85KL £82-19-0 dep. £16 FREE AFTER-SALES SERVICE WITH	-16-0 -9-0 -9-0 -15-0 -15-0 -19-0 SATURDAY	Agents or GRUNDIG TELEFUNKEN WYNOSOR SIMON VENITONE SABA ELIZABETHAN SOUND SPECTONE and many others
		Write NOW for ALL Your FREE Literature
179 STOKE NEWINGTON H LONDON NI6 CLISSOLD 9 also at 89-91 Gt. Ancoa		ADDRESS

282

.T.R.

RECORDING IN SPAIN—(continued)

as I had set up the reflector. I kept it trained on to his favourite bush, however, but in the course of the next half-hour I only managed to record one song-phrase. It was only a rather halfhearted phrase, at that, but it was enough for my purpose.


I played it back to him at full volume at intervals of about five seconds and at once he began to take an interest, assuming a perch much closer to me and singing for all he was worth at the recorder, ordering it out of his territory. I was able to record a long series of song phrases during which he did not once change his perch, and when I played this back to him he gave me a series of anxiety calls as an encore.

The plateaux and slopes of the high sierras are grazed by numerous flocks of lean, wiry sheep which find food in the most improbable places. They are tended by shepherds who control their movements from place to place, and chase the stragglers, with a constant bombardment of stones from slings of the kind which slew Goliath. These they plait from esparto grass, as they wander behind their charges. I was recording a Chaffinch one morning, at the edge of a belt of pine forest (as a contribution to the study of variation in Chaffinch song), when a shepherd led his flock past the microphone. The result was an extremely attractive recording of a chaffinch singing against a background of deep-toned sheep-bells, with the sharp crack of the shepherd's sling and the partridge-like sound with which he called his dog.

Passo dobles and fandangos

During the expedition we were housed in one of the Spanish forestry commission rest houses which was maintained by a caretaker and his wife for the convenience of visiting officials. It was solidly constructed, with a shady court-yard and outbuildings and we learned towards the end of our stay that it was going to be the scene of one of the periodical dances which are the only form of amusement of these mountain people. At about ten o'clock at night little groups of shepherds and crofters, on foot or riding mules and donkeys, straight from their flocks and fields, began to converge on the house. Two of the forestry workers began to strum lazily on a guitar and mandoline, seated on the window-sill of a large garage, immediately below





a single carbide lamp which was the only illumination. Soon the garage was crowded to capacity with a heaving mass of men, women and children of all ages, dancing solemnly through a long succession of waltzes, passa dobles and fandangos, drinking from a large wine-flask which was passed from hand to hand or just talking and joking with friends they had not seen since the last similar occasion.

I had been careful to hang the microphone from the only possible place, the hook holding the carbide lamp. Fortunately the accoustics were quite reasonable and I was able to obtain nearly two hours of folk music, with some flamenco singing and a delightful "cabaret" act which told of a farmer who bought a mule from a gipsy against the advice of his wife. It went on long into the night. The recordings contain some wonderful tunes, against an atmosphere which still conjures up a vision of sheep-skin-clad shepherds and peasant girls in aprons, stamping through the routine of a fandango in semi-darkness.

Searching with the parabola

A few days later the Quails arrived in the young corn at the head of the valley in which we were then working. Their calls of "Wet my lips! Wet my lips" echoed and re-echoed between the high limestone crags and were so ventriloquial in character that it was impossible by unaided ear to align the parabola. It was equally impossible to find them by sight, as the calling birds never for a moment showed themselves. The only method was to swing the reflector gently to and fro until the signal, when monitoring through the loudspeaker, was at its maximum, and this was no easy task since the bursts of calling were of short duration. The resulting tape represented the first time that the Quail has been recorded in Europe.

In the very highest part of the Sierra de Cazorla, amidst a landscape which can only be described as lunar in its desolation, there is a race of the Skylark which is restricted to these altitudes in the Iberian Peninsular. I particularly wanted to obtain a recording of the song of this Skylark of the sierras in order to compare it with typical songs of the same species elsewhere in Europe. It was only on the last day of the expedition that we caught up with it, however, and then, in the heat of the afternoon there was a steady force-four wind blowing across the plain and not an inch of cover in sight. Eventually, I did manage to find a shallow depression on the stony ground and this was in the lee of a slight hummock of rock.

After experimenting for a while, I discovered that I could just keep the reflector out of the wind if I lay on my back with it on my chest. There was always the prospect of Lataste's Viper slithering across my neck as I did so, but by then I was desperate. Another difficulty was the fact that, due to a long recording programme the day before, my battery was not in very good shape and, in addition, the terrain was so jagged that I could not take the car off the track. I was faced with the problem of using as little current as possible to cope with a bird which rose to sing at long intervals when I was in no position to switch on the recorder in the car over a hundred yards away.

The parabola again

It was solved by my blowing a whistle when a likely-looking bird rose from the ground, so that my wife, who was assisting me, could switch on the recorder. The first bird rose nearby. I sighted the parabola on to it and blew hard as I followed it upwards. A few seconds later it began singing and I held on to it until I thought my neck would break in my cramped position. Then it began to descend and finally it stopped as it neared the ground again. The wind rose to gale force and all possibility of repeating the recording was gone. Fortunately the whole song-flight had been perfectly recorded in the nick of time.

Such are the situations which face the bird recordist and which are different with each new species. The equipment and methods I have described in this series should have provided you with a good working background from which to tackle your own problems and I wish every success to those of you who have followed me so far.



YOU CAN START A TAPE CLUB

TODAY there are some 86 tape recording clubs in this country, which makes us, in proportion to the size of our islands, just about the most tape-club-concious nation of any! And yet it is still true that many big towns, and scores of smaller ones are without clubs. If you live in one of these clubless towns, and you are a keen tape recordist, how would you like to form a club yourself? Read on, and you will learn how.

To start a club you need the following: — enough tape recording enthusiasts, a meeting place.

Luckily finding prospective members isn't all that difficult. For a start you can write to *The Tape Recorder*, who will be pleased to inform readers through the "News from the Clubs" feature, of your proposed club. From this editorial publicity you should receive a number of enquiries, but you will probably want to try a few other ideas as well.

You will almost certainly know a hi-fi dealer or a radio dealer handling tape equipment in your area. Go along to his shop when he's not busy, and explain that you hope to form a club. Ask his permission to display a notice in his window or on the door inviting people interested to contact you. Also get him to spread the news by word of mouth.

Another idea is to write a "Letter to the Editor" of your local newspaper, for inclusion in the correspondence column. Make your letter interesting or it will not get published.

Naturally you will tell any of your friends or acquaintances who are interested in tape about the proposed club. When you have found about ten people who are definitely willing to turn up regularly at meetings, you can start your hunt for accommodation.

This is rather a more difficult task at present. So many clubs, with interests ranging from stamp collecting to "preserving beautiful canals" need a meeting place, that your search may prove a long one. If the worst comes to the worst, you can, as some clubs have done, temporarily hold your meetings in members' homes. But the disadvantages of this are obvious.

The club of which I was for a time Secretary, "B" TRAC, uses a public house as a meeting place. "Pubs" do generally offer quite good facilities. Tables and chairs are provided, and "liquid refreshments" are (of course) always available. One other great advantage of a "pub" for a meeting place is that there may be rooms available free of charge.

Other places you might use are cafés, hotels, another club's room (i.e. the local cine or photographic societies' H.Q.), school rooms, a dealers "back-room", a church hall.

When you are fully satisfied that the room you have chosen is the one for you, have arranged the charges, and dates for meetings, inform all your prospective members of these developments, and in so doing fix the date of your first meeting.

The first meeting

As founder of the club you should get to the club first, and greet each person as he arrives. Talk for a little while together before leaving him to the mercy of the other "strangers".

Promptly at the time arranged (now is as good a time as any to let members know meetings will not wait for stragglers), open the meeting. Make a few introductory remarks and try to break the tension which often occurs on these occasions. Then call for an official proposal that the club be formed, and get it seconded. (In case you are not as yet aware of club procedure, I should explain that every suggestion made at an official meeting



Demonstrations of members' equipment form an essential part of any club's activities. The photo (by F. W. D. Hodgson) shows the Northallerton Club.

is in the form of a *proposal*. Someone usually agrees with this, and they *second* or voice their agreement with it. The matter is then discussed by all and a vote is taken. If the majority vote in favour of the proposal, or as it is sometimes termed: the *motion*, it is then *adopted* and becomes a *resolution* of the club, which may then be put into force.)

Next propose a name for the club. The current trend is to a simple "(District) Tape Recording Club", rather than a more elaborate title. Big names for little clubs is a maxim which holds good.

Now comes the adoption of a constitution. This is a written list of rules as to how the club shall be governed. Those interested can obtain a specimen of a constitution from my office 161, Stuarts Road, Birmingham 33. One of the clauses in the constitution of every democratic club, is that a committee be elected to administrate the workings of the club. To help you select a Committee here are a few notes on the subject:—

Chairman. He needs to be an authoritative type, whom other members will respect. He must keep the meeting in order, and his "beady eye" must at a sideward glance freeze the blood of those who go on talking when he bangs his little hammer on the table. But he must not be a "hot and cold" type, who rushes in to a pro or con decision and then lets all hell loose on anyone who challenges his views. On the contrary, he must always be able to see the other person's point of view, and be a person who can assess an argument without entering into it.

President. He is the honorary head of the club, chosen because of his notability in public life. If possible a "Sir", "Lord", or "Almightly by the will of Allah", should precede his name, and at least ten initials must follow it! He is not expected to attend committee meetings but may himself preside at the AGM or on special occasions.

Secretary. He is the backbone of the club. He can be termed the key man, for if something goes amiss, he gets the blame. He must never shirk his responsibilities, nor the enormous amount of work which is placed upon him. He must have plenty of time for clubwork, get on well with people, and preferably own a typewriter. But that doesn't mean he has to sit on the Chairman's lap. That's a different kind of Secretary altogether!

Treasurer. He should preferably be engaged in financial activity as his full-time profession. He must be a man of integrity. Retired keepers of the crown jewels are highly desirable. He must be over 21. His job is to look after the financial affairs of the club. If subscriptions are not going to run to double figures he must be rather tight-pursed. Look out for someone wearing a sporon!

When the Committee have been elected your job as *founder* is pretty well over. Probably you will have been elected as an official yourself, in which case your job as such is just beginning. If not don't be disappointed. The committee have a hard task before them to keep things lively . . . but that's another story.


A DELAYED ACTION TIME SWITCH

BUILD THIS SIMPLE UNIT AND YOUR RECORDER WILL SWITCH ON AND OFF AUTOMATICALLY

THERE are without doubt countless numbers of tape recording enthusiasts who upon reading through the day's sound broadcasts often say to themselves: "Now that's a good programme, what a pity that I shall be at work", or "but it's far too late to sit up and wait for the programme to end".

The writer having been faced with this problem on numerous occasions decided that it was about time something should be done to overcome this. A practical way, of course, would be to leave someone with instructions to press the necessary buttons, etc. This is quite all right until someone happens to forget to turn the volume up or press the wrong button, or even forget completely! It was decided that the whole apparatus would have to be pre-set but without any power supply. i.e. in the case of recording with a microphone, the tape recorder would have to be turned on, the record button depressed, and the volume set to the necessary level. The power would first be switched ON and then OFF and the apparatus would become alive and then go dead at the end of the predetermined period of time.

At first, a normal "street lamp" type of time switch was thought the ideal thing, but on further investigation it was found that these could only be selected to switch ON and OFF (wo operations at different times). Further to this they are only accurate to within plus or minus five minutes. This was considered impractical since one would wish to use the full length



This exploded diagram of the case indicates the pieces required and the basic outline of assembly. Future photographs and diagrams will show the detailed construction. $\frac{1}{4}$ in. oak was used throughout.

of a tape, and not to have, for instance, five minutes of the previous programme and then possibly have five minutes clipped off the end.

A point to be considered, as far as the average enthusiast is concerned, is the outlay. The "street lamp" type of switch referred to above—apart from the uncertainty in the time that it goes off—is quite an expensive piece of apparatus. The total cost of the unit built by the writer was about £3 10s. If all new parts were used this would be a little more, but most keen "do it themselves" types will have a small stock of electrical equipment at hand that will fulfil some of the requirements of the parts listed below.

A further point to be considered was that "the thing would have to be lived with" and a mass of wires and switches would not be accepted readily by the female member of the household, so, it was decided to house the apparatus in a polished wood case

To use a single clock that would perform two operations at different times would mean a very cumbersome looking affair with a fair amount of light engineering to the works. So two standard alarm clocks were chosen as the basis of the unit. The alarm winding keys were found to be the best place to take off mechanical movement, and these are used to operate two micro-switches.

Further facilities were made available by installing within the unit, two 3-pin output sockets, and a system of switches that would allow various functions to be performed. There are six combinations of switching to give the following operations:

(1) Switch both outputs ON at a pre-determined time, and switch them both OFF at a later pre-determined time. (2) Switch both outputs ON and allow them to remain ON indefinitely, or until attended to manually. (3) Switch both outputs OFF and allow them to remain OFF. (4) Switch one output ON at a pre-determined time, and switch the second output OFF at a pre-determined time, and switch the second output ON at a pre-determined time, and switch the second output ON at a pre-determined time, and switch the second output ON at a pre-determined time. (6) Switch one output OFF at a pre-determined time, and switch the second output OFF at a nother pre-determined time.

Suggested applications

The writer has used this apparatus to perform the above functions and gives here a list of probable applications:

(1) With the tape recorder set to record, the radio set to the desired station, and both plugged into the output sockets I and II. i.e. recording a programme of a certain duration of time. The writer has also used this setting when recording the birds' dawn chorus. With a microphone hidden outside and a long lead to the inside of the house, one can listen to this at one's leisure and at a more sociable hour.


(2) This would be used to switch ON a radio perhaps to be awakened by morning music.

(3) Could be used to switch OFF the radio at night after listening to late night music.

(4) This setting has been used to switch ON the television (to avoid missing a programme through not noticing the time), and after recording a radio programme during the same time, to switch it OFF at the end.

(5) With this setting the television could be switched ON as in (4), and the tape recorder switched ON to record a

A DELAYED ACTION TIME SWITCH cont.



Have you ever wished for a robot to record programmes while you are out, or "viewing", or asleep? These two alarm clocks wired according to next month's instructions will do just that.

programme. This would avoid having to break away from viewing to attend the recorder.

(6) This could be used to switch OFF sound effects at different times.

These are only a few suggestions. Readers will no doubt find other uses to which the unit could be applied.

The time switch described utilises two alarm clocks of 4 in. diameter (on the face), and the overall dimensions are $10\frac{1}{4}$ in. $\times 5\frac{1}{2}$ in. $\times 5\frac{1}{2}$ in. $\times 5\frac{1}{2}$ in. Smaller clocks are obtainable at a little extra cost. This would make for a more compact unit, but the one described looked quite attractive after its final polish.


Construction of Case

First cut boards to dimensions shown, and mitre all edges shown with an 'M'. Cut the remaining edges square. Cut all holes as shown (for equipment suggested), but if different equipment is used, these will be altered accordingly. The main case should then be fixed together using a good hot glue. To make this job easier, small diameter panel pins can be used (about 3-4 in the long edges). These can be partly driven home, and then removed after the glue has set. To avoid splitting the wood with the panel pins, first drill a hole the same diameter as the shank of the pin in the top piece of wood being fixed.

To give the case stiffness, triangular fillets of wood are glued along all the inside corners. The fillets running from front to back should be cut so that they finish $\frac{3}{4}$ in. from the rear opening, as the door fits in the inside of the case. Two stops for the door are then glued and pinned as shown. These are pushed in until the recess formed is just the thickness of the wood used for the door. The case is then set aside to allow the glue to set—preferably overnight.

The remainder of the woodwork comprises a plinth and a door. The plinth is made from a piece of board the shape of the base, but with a quarter of an inch added all round the edge. A radius is cut on all four sides of the top and sanded smooth. The plinth is attached to the main case by six countersunk woodscrews. These screws should be sunk deep enough to avoid the heads projecting below the base, and scratching any polished surface they come in contact with.

Next month: full constructional details, and operating notes.



Inside view of rear door showing wiring and operating guide.

List of Parts Required

Where some of the parts are given a suggested name, these are only as a guide. This is not important as long as the parts meet the requirements in the remarks column.

Description	Qty.	Suggested makers name	Remarks
Alarm clock	2	"Timecall"	The alarm winding key must rotate when the alarm goes off to give the necessary movement to operate the micro-switch.
Micro-switch (5 Amp)	2	"Burgess" or "Bulgin"	Must be of the—normally closed and normally open- type in order that they can be used as two way switches. The ones used by the writer were obtained from ex-govt. instruments.
Two-way switch (5 Amp)	2		Any standard 2-way tumbler switch will suffice. (A panel mounting type could be used with a little modification to the mounting blocks).
3-pin outlet socket (5 Amp)	2		These are ordinary mains wall plugs. The ones used by the writer were of the round pin type. The reader will of course use the type common to the household in which the unit will be used.
3-pin input socket and plug	2	"Radio- spares"	This is a shielded male and female plug to facilitate the removal of the mains cable and place the unit on a shelf.
4-pole rotary switch	1		This was also obtained from ex-govt. equipment, but com- mercial equivalents can be obtained. A reversing switch could be modified to perform the functions shown on the wiring key.
3-pin plug (5 Amp)	1		For connection to the mains.
3-core flex Single-core rubber- covered wire	1 yd. 2 yds.		For connection to the mains. It is preferable to use a stiff wire so that it can be bent out of the way of the apparatus.

Small quantity of light-gauge aluminium sheet or similar, for mounting micro-switches.

6 ft. of $5\frac{1}{2}$ in. $\times \frac{1}{4}$ in. seasoned and planed oak board. Hot glue, panel pins, $\frac{1}{2}$ in. countersunk screws.



For easier and economical tape editing



Everyone who uses a tape recorder will need this little tool. It is indispensable. P. Wilson. "The Gramophone."


The easy-to-lift clamps on the new Mark II Bib Recording Tape Splicer are both hinged on the same side of the splicer, making the jointed tapes easy to remove. Precise, rapid tape jointing is ensured, and because you can use all the odd lengths of tape, you soon save the cost of the splicer.

18/6d each

If you have difficulty obtaining a Bib splicer locally, let us know the name and address of your dealer.

Send a stamped, addressed envelope for a helpful leaflet on tape editing.

MULTICORE SOLDERS LTD., MULTICORE WORKS, HEMEL HEMPSTEAD, HERTS. Tel: BOXMOOR 3636






With a Valradio DC/AC converter you can really start enjoying the full use from your tape recorder. Take it with you in the car to record outdoor events or dictation; or in the caravan when you go on holiday; or in the country cottage you visit. Now you can take it anywhere, even though there's no mains lighting.

Valradio converters step up the DC voltage from your car battery enabling you to make your tape recorder really mobile.

We have an interesting leaflet we'd like to send you. Why not write for it today?



Feltham 4242 London Office: 57 Fortess Road, N.W.5 GULiver 5165



FIELD TRIALS OF BATTERY PORTABLES

(7) THE CASIAN "TRAV-LER"

• Continuing this series in which operational "handiness" and portability are reckoned to be of first importance. As our photograph shows, a recorder is something for the whole family to use.

COMPARED with previous recorders reviewed in this series, the subject of the present Field Trial has the heightened interest of being absolutely brand new. In fact, very few of our readers can have ever seen one. Because of this, it will be best to begin with a brief description.

As may be gathered from the photographs, the Casian Trav-ler is physically larger than is usual for battery-operated portables. The writer found the recessed control knobs difficult to grip, particularly with the perspex cover in position, and disliked the black and gold styling. He was in a minority, however, being out-voted by distaff and off-spring alike. The 10×8 in. top area accommodates the 7×4 in. elliptical, upward-facing loudspeaker, the tape channel and the 3-in. spools, and all the controls. The latter comprise (a) volume control; (b) a five-position selector



Rear view, with back removed, showing the printed board, batteries, and microphone storage compartment.



switch for Rewind, Record, Off, Replay and Wind On; (c) a Run/Wind lever, the two extreme positions of which are self-explanatory. This control also gives a Pause facility, a slight movement from the Run position withdrawing the pressure roller and bringing the tape to rest.

Neon level indicator

There is a slide switch near the loudspeaker, which operates on recording only and gives the option of listening during recording—say from the radio or the telephone. A neon lamp gives an indication of the recording level, and—unlike most level indicators—it shows the level on the playback too. There is not much point to this in the present case, since the only method of playing back is through the built-in loudspeaker. There is no outlet for feeding an external amplifier or loudspeaker, though this may be added at a small extra cost.

Two different Lustraphone microphones were tried out—the LD/66 moving coil which is the included accessory, and the VR/64 ribbon. The latter was found to be slightly less sensitive, necessitating a small increase in the volume setting, but gave smoother recordings. It must be said that the reproduction of recordings made from all sources tended to be "toppy". The reason is two-fold; firstly, there is the absence of bass inevitable with any small loudspeaker, and secondly—as the manufacturers confirmed—the overall frequency response has been held flat up to at least 5 kc/s since a bright quality is preferred by "Pop" music fans, who are expected to be major purchasers of this new machine.

On a picnic

To test the "Trav-ler's usefulness in this capacity, we recorded a series of "Pop" tunes from a certain Saturday evening programme—the Pause control came in handy for cutting out the announcements, and was simplicity itself to operate—and used this to supply music on a family picnic. The venue was a deserted stretch in Ashdown Forest, so we were not creating a nuisance, and the young fry voted the music a "hit". In fact, they are threatening to bring the complete Top Twenty Pops on the next picnic.

A more ambitious outing was arranged on the evening before the Derby. Knowing that the Fun Fair and gypsies would be in full swing, it was decided to have a pre-view of the famous Epsom course, and make a few "on-the-spot" recordings at the same time. Excellent static recordings were obtained, but it was



in the service of sound

D88

World-famous AKG microphones cover a range to meet the needs of those who use tape recorders at home to those whose work is with the world's giant broadcasting, television, film and recording organisations. Models D.11/N and D.9 (Mono) and D.88 (Stereo) are particularly recommended for private as well as professional users.

石町む

C12

Condenser microphone for highest professional requirements. Its pattern may be varied at will during actual use.

C12

D88 STEREO

High-quality double cardioid microphone unit for stereo recording. Can also be used as a wide angle mono instrument. Frequency range 60-15,000 c/s.


D11/N

An entirely new dynamic microphone for use specially with modern tape recorders. Cardioid pattern. Frequency range 80–15,000 c/s. 180° discrimination. Sound incidence ratio (front to back) 15 dB. Maintains working conditions over range from -30° to $+70^{\circ}$ c. In elegantly styled case. High or low imp.

D9

Dynamic general purpose microphone of robust design and excellent performance characteristics well suited to tape requirements.

Details of AKG Microphones gladly sent on request.



D11/N



FIELD TRIAL-(Continued)

found that the "Trav-ler" cannot conveniently be used at much of an angle to the horizontal. For one thing, there is no system of locking the spools on to the spindles, and although a recessed panel on the Perspex cover prevents the reels from actually falling off, the tape ceases to track correctly past the heads perhaps recording on the Big Dipper, and the Moon Rocket *was* expecting a bit too much!

Clearly the designer has seen this machine as more in the nature of a static recorder or playback unit, to be taken anywhere, and there is no provision for shoulder-strap operation as on some smaller recorders. The zip carrying case is quoted as an extra, but most people would consider it essential. In the model tested, there are two neat little holes to allow access to the input and external 9 volt supply sockets, but the main controls cannot be got at without unzipping the case.

The technical performance of this recorder is well up to the fairly modest figures claimed. A signal to noise ratio of 30 dB for example, is not calculated to "set the world on fire", and makes it more than ever desirable to record at as high a level as possible while avoiding overload distortion. The overall gain is more than ample and the volume control never required

The Casian Travler has fast wind and rewind, and D.C. erase. Its performance compares favourably with that of mains machines in the domestic category.



to be advanced more than half way. Speed fluctuations were commendably absent on all kinds of programme material and even on recordings of steady tone. A full reel of standard tape took 75 seconds to rewind in either direction.

The normal power supply consists of 3 Vidormax T6009 9-volt batteries, but connection can be made to a car battery, and a mains converter is available so that the recorder can be used as a dual purpose unit, operated on the mains supply indoors and on batteries out of doors. Other accessories which may be obtained include a radio connecting lead, car battery lead, telephone adaptor, and the waterproof carrying case.

Final impressions

Summing up, this new recorder must be strongly commended for specifying—and sticking to—an honest, and highly acceptable technical specification. At the price, which includes a superior microphone to that offered with many mains recorders, and considering the high engineering standard and such features as the D.C. erase circuitry (not permanent magnet) the Casian Trav-ler represents good value for money.

Technical Specification

Battery complement: 3×9 volt Vidormax T6009 or equivalent. Battery life: 40-50 hours. One motor. Transistors: $3 \times 0C78$, $2 \times 0C71$, 0A81. Neon level indicator. Tape speed: $3\frac{3}{4}$ i/s. Frequency response: 150-5,000 c/s ± 3 dB. Recording sense: Top track, left to right. Inputs: moving coil microphone or radio. Maximum spool size: 3 in. Fast forward and rewind: $2\frac{1}{2}$ minutes for double play tape. Power: 400 mW. Dimensions: $10 \times 8 \times 5$ in. Weight: 9 lb. Price: with Lustraphone LD/66 moving coil microphone and 450 ft. reel of double play tape £30 9s.

Manufactured by: Casian Limited, 37 Grayton House, Golden Square, London, W.1.



Windshields


Dear Sir: Is there any simple method of reducing the rumbling background noise on so many of my outdoor recordings? It is presumably wind noise, and I have occasionally improved matters by sheltering the microphone or shielding it by holding out my jacket. If these is a fair breeze blowing, however, none of these dodges are successful.

There must be many people who are in the same boat as myself, and the professionals seem to have found a solution, so any suggestions you have would be most welcome. My microphone is an Acos Mic. 39. Yours truly, F. T. M., Hastings.

As an emergency measure, you will find that three or four folds of a handkerchief over the end of the microphone, fixed with an elastic band or held in the hand, will reduce the worst effects of wind noise. This is a partial cure only, however, and has the serious drawback of filtering out high frequencies and, in fact, cuts down the level overall.

Microphones in the professional class may often be fitted with specially designed windshields. The Standard Telephones and Cables moving coil types 4032 and 4035, for example, have, as an accessory, a dome-shaped shield which fits over the diaphragm face of the microphone. The outer surfaces are of wire gauze, and they enclose a fibrous material which is designed to be transparent to sound waves while attenuating wind movements.

The photograph shows the type of windshield favoured by A.K.G., Vienna, (Akustiche u. Kino Geräte Ges.) whose domestic and professional microphones are well-known in this country. This is made in the form of two hemispheres which completely enclose the microphone. The model in the photograph used on the is D20B moving coil microphone. It is a feature of efficient windshields that they take up a lot of space, and the version fitted to the



C12, condenser microphone, for example, is about the size of a melon.

Amateur windshields have been constructed from a sandwich as a last resort many excellent recordings have been made by of chicken wire, with silk screens and wool as the "filling", and simply holding one's coat out to shelter the microphone, as you mention.

Record/Playback Heads

Dear Sir:-I was disappointed, on removing the plastic cover over the sound channel on my recorder, to find only two heads. I expected to find the three which are usually drawn out in text books and articles, namely recording, replay, and erase. Is it usual to omit one of these, and if so, why? Also, a friend of mine has a tape recorder with a Collaro Transcription Deck which has four heads. Does nobody have the official number, Yours faithfully, W. R., Carlisle. three?

Virtually all professional tape recorders, and a limited number of less expensive domestic recorders "stick to the book," and employ three heads. The order is then invariably, Erase, then

Readers' Problems

Record, then Replay. This allows the programme which has just been recorded to be monitored continuously through the playback circuitry. There is a fraction of a second's delay, of course, equal to the tape speed divided by the distance between the Record and Replay heads, e.g., a distance of $2\frac{1}{2}$ -inches would give $\frac{1}{3}$ second delay or echo at $7\frac{1}{2}$ i/s.

In the majority of domestic tape recorders, the recording and playback functions are combined in a single head, it being the job of a more or less complicated system of switches to changeover the function. To keep cost and weight down even further, it is very often the practice to combine the amplifiers too, the switchery then swaps over a microphone/amplifier/head chain on Record to a head/amplifier/loudspeaker chain on Playback.

On the famous Collaro Transcription Deck, and a number of other machines which will "scan" either the upper or lower track without the need of turning over the tape, e.g., the Simon SP4, two pairs of Erase and Record/Replay heads are fitted. The left hand pair is aligned to scan the upper track, and the right hand pair (reversed in order) the lower track. Additional "track change" switches are then necessary.

* Artificial recording

Dear Sir: I would like to know whether there is any way of producing Artificial Sounds on tape-that is by using a permanent magnet to produce varying strengths of magnetism like the record head on the machine. It is possible to do this on the sound track of films, by drawing on them. I would very much like to know if any of your readers have

ever tried this, and if so, with how much success. Yours truly, D. Kay, 314, Lordship Lane, E. Dulwich, London, S.E.22.

In the drawing of artificial sound tracks on films, the actual envelopes of the shaded areas can be arranged to give varying tonal qualities just as the waveforms of a clarinet differ from those of a violin, etc., but there are difficulties in trying to adapt the technique to magnetic tape. Take first of all the question of speeds. If the artificial track is to be anything other than a series of clicks and boings, it is necessary to magnetise it in such a way that, playing back at a standard speed, A.C. fluctuations are produced at an audible frequency.

Of course this corresponds to extremely small recorded wavelengths, which make the dimensions of any fixed magnet impractically large, unless the tape is run fast as the magnet is moved during recording, or else the magnet itself is rotated or vibrated at high speed. The level of the recorded signal is likely to be a hit or miss too, and we can think of a few other snags. But none of these is likely to deter the true enthusiast seeking for new ways of creating sounds, and we invite readers who have experimented with these artificial recordings to get in touch with Mr. Kay either direct, or through these columns.

Using a bulk eraser for head demagnetisation

Dear Sir: I have just discovered your excellent magazine, and have placed a regular order at my newsagent. I have constructed the bulk-eraser described in your March issue, and I find it works very well indeed. Is it possible to use such a device as this for demagnetising tape-heads? I don't see why this shouldn't do the job providing there is no obstruction between the heads and the effective area of the bulk-eraser. Or is there a risk of degaussing the loudspeaker magnet in the recorder, and what would you consider is a safe distance for magnetised materials from a bulk-eraser of this type,

Yours sincerely, E. Watson, Blackpool.

We do not think that the bulk-eraser described recently would be suitable or adaptable for depolarising tape heads. In commercial depolarisers the AC magnetic field is relatively weak, and is concentrated on a pole-piece shaped to facilitate head demagnetising. At distances of 12-18 inches there is unlikely to be any ill effect on the loudspeaker magnet.

Tape Splicing

IT is a very useful feature of the tape recording medium that different recordings or excerpts can be easily spliced together, and it isn't very long before one finds that sticking the ends together with sellotape or stamp edging (!) is far from ideal. To make really firm joints, which will not foul the tape heads and guides or "bleed" on to adjacent turns making the whole tape sticky, two methods are available—jointing tapes and jointing fluids.


Full instructions on tape editing by both methods are given, with step-by-step photographs, in a handy booklet entitled "How to Splice Tape." This is based on articles by I. W. Jarman which appeared in *The Tape Recorder* during 1959, and may be obtained, price 2s. 6d. postage paid, from 99 Mortimer Street, London, W.1.

The special jointing tapes may be had $\frac{1}{2}$ in. or $\frac{1}{4}$ in. wide or just under. Examples are Agfa 80 ft. $\times \frac{1}{4}$ in., price 5s. 6d.; M.S.S. Mastertape, price 5s.; BASF, 30 ft. $\times \frac{1}{4}$ in., price 3s. or 5s.



in plastic box; Emitape AP103 $\frac{1}{2}$ in. price 7s. 6d.; Sonocolor, price 7s.; "Scotch" Brand type 41, 66 ft. $\times \frac{1}{2}$ in. price 6s. 6d. and 66 ft. $\times \frac{1}{2}$ in., price 3s. 6d. Philips EL 3916/0, 80 ft., price 10s.

Jointing fluids produce a truly permanent welded joint and may normally be used only on Acetate or P.V.C. tapes. An exception is on M.S.S. Mastertape compound which is specially designed for polyester tapes. Jointing fluids include Emitape Jointing Compound AP35 for C.A., AP 37 for P.V.C., 7s. 6d. per bottle; BASF LG 7s. 6d. per bottle; M.S.S. 4s. 6d. per bottle; Sonocolor Type C2 6s. per bottle.



Tape Splicers and Editing Blocks

There are a number of efficient tape splicers and editing blocks on the market, all designed to simplify the business of cutting and joining tapes. There will usually be some provision for holding the loose ends of tape—spring-loaded flaps in the splicers and overhanging flanges on the editing blocks—and slots to allow accurate cutting at 90° or 45° across the tape.

Splicers include the Multimusic "Bib" splicer, price 18s. 6d.; Emitape AP46, price 17s. 6d.; Irish Brand SP-3, price £3 7s. 6d.;



TAPE RECORDER ACCESSORIES

A SURVEY OF USEFUL AIDS TO RECORDING



ROMAGNA EDITING BLOCK *

Sonocolor CM6, price £1 12s. 6d.; Romagna Editing Block, price 7s. 6d.; Easysplice Editing Block, price 5s.

Editing Kits

It is possible to acquire a complete kit of editing accessories, and examples of these are as follows: Sonocolor Splicing and Editing Kit, comprising CM6 splicer, 3 reels coloured Leader Tape, 1 reel Adhesive Tape, 1 bottle C2 special glue, 1 box

E.M.I. KIT OF EDITING ACCESSORIES TYPE AP110



Filmpic Clips, 1 spare Grooved Guide, price £3 12s. 6d.; E.M.I. Accessory kit, type AP110, includes jointing block and cutter, jointing compounds and tape, and 6 reels of P.V.C. leader tape, price £1 17s. 6d.; "Scotch" Brand, including "Bib" splicer, jointing tape, and leader tape price £1 9s. 6d.; M.S.S. Mastertape including "Bib" splicer jointing fluid and tape, and leader tape, price £1 17s. 6d.



* A.K.G. HEADPHONES TYPE K50 *

Headphones

A wide range of headphones or stethoscope-type sets are to be had, and are invaluable for monitoring purposes—when the recorder incorporates this facility—or listening without disturbing other people in the room. An example of the latter application is the transcribing of recorded dictation on to a typewriter. Here extreme lightness will be more important than quality, but, for monitoring, high fidelity headphones will be preferred.

It is important to select the appropriate impedance. For plugging into an External Loudspeaker socket, for example, low

TAPE RECORDER ACCESSORIES


A SURVEY OF USEFUL AIDS TO RECORDING

continued....

impedance headphones are best; and high impedance headphones will suit most other purposes.

A complete range of headphones is manufactured by S.G. Brown Ltd., including the Type "F," 4,000 ohms, price £1 17s 6d. and the type "K." 52 and 1,500 ohms, price £5 10s. and £7 3s. respectively. Other headphones sets include: A.K.G. type K50, impedance 800 ohms, price £8 4s. 6d.; Sound Stethoset,

SOUND STETHOSET HEADPHONES



impedance 50 ohms, weight $1\frac{3}{4}$ oz., price £2 1s.; Elizabethan Stethoset, lightweight, high impedance, price £3 13s. 6d.; Simon Stethoscope headset, operates from extension L/S socket, price £2 12s. 6d.; Telefunken (Welmec) Crystal earphones, price £2 6s.; Truvox, low impedance, price £3 3s.; Philips Stethoset headphones, price £3 10s; Walter featherweight, price £2 12s. 6d. Grundig Stethoscope, type STET 3 price £3 3s.




Head Defluxers

The record/replay and erase heads are basically electro-magnets, consisting of fine wire coiled round an iron core. Ideally, in the absence of any current through the coil, the core should





be in a completely de-magnetised state, but can become accidentally magnetised due to a number of causes. These include switching surges from the motor, unbalanced bias oscillator, and bringing magnetised tools close to the heads, and produce




noisy or distorted recordings. Worse than this, magnetised heads may put noise on to pre-recorded tapes. The cure is a periodic dose of "demagnetisation" using an AC magnetic field. This is most conveniently carried out using one of the proprietary defluxers, such as:—Cinesmith Depolariser, price £1 14s.; Wearite defluxer, price £2 10s.



Bulk Erasers

The simple process of erasing whilst recording is all right in its way, but there are times when a quicker and more complete method of erasure is desirable. This is the job of a bulk eraser, and is applicable to users who frequently exchange tapes with others whose machines may not track at the same precise horizontal line, or where complete erasure is essential, as in Library work, etc. The principle of all bulk erasers is the same, namely that the tape should rest on a spindle and be rotated slowly by hand through a concentrated AC magnetic field. The whole operation need take no longer than about one minute.



A range of bulk erasers is manufactured by Harvey Electronics Ltd., to take all sizes of spools, and costing from £6 5s. to £15 10s. Other models include the LeeRaser in 3 sizes, price £6 5s., £9 10s. and £15; Osmabet Instant Bulk eraser, price £1 7s. 6d.; WAL Eraser, price £7 18s. 6d.

Telephone Attachments

When it is required to record the two ends of a telephone conversation, or perhaps "broadcast" them via an amplifier to a group of people, a telephone attachment is necessary. This consists of an electromagnetic transducer, which may be laid

Spans Nine Octaves!

Mart Contectors

The Frequency Response curve above was produced under the following conditions:

BEAT FREQUENCY OSCILLATOR Type 1014 producing a signal of 2.5 V. (modulated to 32 c/s with a swing of 30 c/s) to SUPER K EARPIECE close coupled to ARTIFICIAL EAR Type 4109 with 6 c.c. coupler, measured signal being amplified by MICROPHONE AMPLIFIER Type 2603 and recorded on a Type 2304 LEVEL RECORDER.

Recorded Medium shows Response flat ± 1 dB 20 c/s-6000 c/s; 6 dB reduction to 8000 c/s: 6 dB reduction to 12000 c/s with continued reduction to 20,000 c/s. Nine octaves pianoforte coverage from 24 c/s to 7800 c/s.

Write now for full information to:



SHAKESPEARE STREET · WATFORD HERTS . Telephone : Watford 27241

MSS MASTERTAPE ACCESSORIES FOR YOUR TAPE RECORDER



THE MSS TAPE CALCULATOR

An indispensable aid for everyone owning a tape recorder. Gives playing times for grades, spool sizes, tape lengths at each one of four speeds, at a glance. Price 2/6



MASTERTAPE SPLICING KIT Contains a generous supply of

jointing tape, leader tape, jointing fluid with brush and bib splicer. In attractive box with full instruc-Price 37/6 tions.

MEMBER OF THE BILC GROUP OF COMPANIES

Splicing kits and calculators are obtainable at all suppliers of MSS Mastertape. In case of difficulty obtainable direct, post free from the address below. Send also for free literature on all MSS tapes and accessories.

MSS Mastertape

MSS RECORDING COMPANY LIMITED, COLNBROOK, BUCKS. **TELEPHONE: COLNBROOK 2431** SHOWROOM & STUDIO: 21 BLOOMSBURY ST., LONDON, W.I TELEPHONE: MUSEUM 1600

294

The "Super K" Headphones are the newest product of S. G. Brown Ltd., and are designed especially for High Fidelity Stereo requirements. They are attractive in appearance, extremely comfortable to wear and incorporate plastic head band and earpieces



SS Mastertape


www.americanradiohistory.com

ACCESSORIES SURVEY—(continued)

near the telephone or fastened to it by a suctioned cap. Suitable units are manufactured by a number of firms, including:— Cosmocord, Dektron Telecon, Telefunken (Welmec) Elizabethan, Walter, Grundig, Philips, and Wyndsor.

Microphone Matching Units

The majority of inexpensive recorders have a high impedance input socket, only. This matches satisfactorily the crystal microphone, which is the most popular type supplied as an "included accessory". It is a limitation of crystal microphones, however,



that they cannot conveniently be used on long leads, and for this reason—and perhaps to obtain improved quality—many people decide to change over to a low impedance microphone. To make this possible there are a number of Microphone Matching Units on the market, but it is a good idea to check that the given recorder has sufficient gain for the microphone in question before purchase. Examples are:—Grampian Microphone Matching Unit G.7, 15-30 ohms to high impedance, price £3 5s.; Wearite Matching Unit TU/30G, incorporating transformer, 30 ohms to high impedance, price £2 6s.



Miscellaneous


Some of the useful tape recording accessories not mentioned above are:—Truvox Radio Jack, price £3 8s. 4d.; Teletron Tapejack, price £5 9s., high gain version, £6 13s. 9d.; T.S.L. Radio Jack, price £3 5s.; Metrosound Klenzatape, a complete kit for keeping tape heads free from oxide deposits, etc., price 12s. 6d.; Metro-tabs, 20 pairs of coloured identification labels, price 3s. 11d.; Swains polythene tape covers, price per dozen, $3\frac{1}{2}$ in., 1s. 6d.; 4 in., 1s. 8d.; $5\frac{1}{4}$ in., 2s.; 7 in., 2s. 4d.; 8 $\frac{1}{4}$ in., 2s. 8d.; Valradio DC/AC Converters, prices from £6 10s.



ADDRESSES OF MANUFACTURERS

FOR the convenience of readers we give below the addresses of the manufacturers or agents for all the accessories mentioned in this survey. Most of the accessories are available through your retailers, but enquiries for further information should go to the addresses below:—

Agfa Ltd., 27 Regent Street, London, W.1; AKG, U.K. Agents: Politechna (London) Ltd., 357 Euston Road, N.W.1: BASF, U.K. Agents: F. A. Hughes & Co. Ltd., 4 Stanhope Gate, London W.1; S. G. Brown Ltd., Shakespeare Street, Watford, Herts.; Cinesmith Products, Britannic Works, Regent Street, Barnsley, Yorks.; Cosmocord Ltd., Eleanor Cross Road, Waltham Cross, Herts.; Dektron, 2 Westbourne Road, Waltham Cross, Herts.; Elizabethan EAP (Tape Recorders) Ltd., Bridge Close, Oldchurch Road, Romford, Essex; Easysplice Co., 30 Lawrence Road, Ealing, W.5; EMI Sales & Service Ltd., Blyth Road, Hayes, Middx.; Grampian Reproducers Ltd., Hanworth Trading Estate, Feltham, Middx.; Grundig (G.B.) Ltd., 39/41 New Oxford Street, London, W.C.1; Harvey Electronics Ltd., 273 Farnborough Road, Farnborough, Hants; Irish Brand—see Wilmex Ltd.; Leevers-Rich Equipment Ltd., 78b Hampstead Road, London, N.W.1; Metro-Sound Manufacturing Co. Ltd., 19a Buckingham Road, London, N.1; Minnesota Mining and Manufacturing Co., 3M House, Wigmore Street, London, W.1; M.S.S. Recording Co. Ltd., Colnbrook, Bucks.; Multicore Solders Ltd., Multicore Works, Hemel Hempstead, Herts.; Osmabet Ltd., 2 Median Road, Lower Clapton Road, London, E.5; Philips Electrical Ltd., Century House, Shaftesbury Avenue, London, W.C.2; Romagna Reproducers, U.K. distributors: K. H. Williman & Co. Ltd., 29 The Highway, Sutton, Surrey; Scotch Brand-see Minnesota Mining and Manufacturing Co.; Simon Equipment Ltd., 48 George Street, London, W.1; Sonocolor, U.K. Agents: Tape Recorders (Electronics) Ltd., 784/788 High Road, Tottenham, London, N.17; Swain Papercraft Ltd., Queens Road, Buckhurst Hill, Essex; Technical Suppliers Ltd., Hudson House, 63 Goldhawk Road, London, W.12; Telefunken-see Welmec Corporation; Teletron Co. Ltd., 112b Station Road, Chingford, London, E.4; Truvox Ltd., Neasden Lane, London, N.W.10; Valradio Ltd., Browells Lane, Feltham, Middx.; Walter Instruments Ltd., Garth Road, Morden, Surrey; Wellington Acoustic Laboratories Ltd., Farnham, Surrey; Welmec Corporation Ltd., 147/148 Strand, London, W.C.2; Wilmex Ltd., 131 Sloane Street, London, S.W.1; Wright & Weaire Ltd., 131 Sloane Street, London, S.W.1; Wyndsor Recording Co. Ltd., 2 Bellevue Road, Friern Barnet, London, N.11.






UNIQUE DESIGN · RENEWABLE BLADE PRECISE, SPEEDY OPERATION ONLY 32s. 6d. COMPLETE

You can achieve professional results **immediately** with the SOUND/Sonocolor CM6 Splicer—the only splicer that has a renewable cutting blade.

The CM6 splicer holds the tape ends firmly, cuts them accurately, and has a special flat surface which can be brought to bear on the finished joint, thus ensuring perfect adhesion. It can achieve any type of splice on any type of tape.

You will like the look, the feel and the efficiency of the CM6 Splicer. This fine instrument costs only 32s. 6d., and will virtually last a lifetime.

The CM6 Splicer is also available as part of the SOUND/Sonocolor Jointing and Editing Kit, which contains all you need for perfect results and costs 72s. 6d.



Photographic Distributors to the trade :-- **THE PULLIN OPTICAL CO. LTD.** 93/97, New Cavendish Street, London, W.1.

LETTER FROM NEW YORK

IN England you have your Components Exhibition: in America we have our Parts Show. A three-day run at the Conrad Hilton in Chicago was estimated in advance to bring in at least 12,000 visitors from the electronic and radio industries. It is too early for me to tell you exactly how many turned up, but the attendance was good, and the many conferences, educational seminars and lectures for distributor management, Trade Association meetings and all the rest that were held concurrently, gave a fine impression of a healthy trade that is still busting to expand. This, remember, was a get-together for the Trade only. On the consumer side we, too, have our Audio Show, just as you have your Audio Fair; and if you are wondering why this month's letter column is being devoted to shows, it is because the events of this year indicate a very marked trend of inter-country interest. For example, let me quote from our Trade publication Audio Times: Under the headline "U.S. Lines a Hit at London Audio Fair" a 14-inch column was devoted mainly to British products, as follows:

"The fifth Annual London Audio Fair, which closed its doors at the end of April, saw a welter of new products, and some new names among manufacturers since last year's show. Ampex, for example, accounted for two exhibits—the first time the company's products have appeared in the London Show. Irish Tape has followed Audio Devices onto the British market, and displays of both companies' merchandise attracted the attention of tape fans. One of the sensations of the show was the Shure stereo pickup, which was shown publicly here for the first time.

"The news was in the new products, and here are some of the more interesting ones: Acos displayed its new 'Hi-Light' pickup, which tracks at two grams. Quad's AM and FM tuners, stereo amplifier and electrostatic loudspeakers drew long queues. The Ampex professional equipment exhibit included the professional models 301 and 601, and some amplifiers and preamps. The domestic equipment exhibit included an assortment of United Stereo Tapes, Ampex home tape recorders, and consoles. Armstrong Wireless introduced a new tuner and stereo control unit, and the British Broadcasting Corporation demonstrated studio recording and stereo monitoring apparatus. The Brenell tape deck has been updated with a new Mark 5 stereo recorder. A. R. Sugden showed a new two-speed turntable, designed for stereo use, and Decca has two new heads for its pickup.

"Electrical & Musical Industries had one exhibit for its equipment, another for its records and tapes. In the former, the highlights were two new studio recorders, the TR 90 and BTR 2, and a new portable recorder, the TR 52. Ferrograph took the occasion to introduce its newest stereo recorder, the Model 808. Highlight of the Garrard exhibit was the magazineloading tape deck, which eliminates threading problems from what looks like a standard tape deck. Not all the news was tape, however: Goldring showed its new 700 stereo cartridge; and Goodmans displayed a new version of the Triaxiette and a new bookshelf speaker system. Harold Leak displayed his complete line of amplifiers, loudspeakers, pickups and tuners.

"Rogers Development had one of the few really new stereo amplifiers, a 'Junior' model. Shure Brothers, in addition to displaying the M7D and M3D cartridges, showed the Shure microphone and pickup arm line, plus a line of styli. The Steelman battery-operated tape recorder made its debut, as did a home portable from Stuzzi. A new addition to the Tannoy line is the Mark 2 pickup. The French-made Teppaz line drew some attention.

Again, at what is claimed to be the largest "outside British Isles" exhibition of "Buy British" goods, being held in New York from June 10th through 26th, your BREMA group have a large showing of electronic products, and others, such as Pye, are also showing independently.

This to my mind is all good news. You, on your side, are beginning to see a number of our hi-fi and tape products; but make no mistake, we over here are beginning to see a lot more of your products, and they are well thought of in many quarters.




... about labels for tape spools

From: R. Strudwick, 891-3, Uxbridge Road, Hillingdon Heath, Middx.

Dear Sir:—Here is an idea aimed at keeping recordings in some sort of order, I have had this system in use for some years now, but have recently redesigned the labels.

It occurred to me that the identification of tapes could be done in the same way as discs, i.e. to have a centre label on

Used in conjunction with an Index, these handy labels (one of which is reproduced here actual size) make the identification of one's tape recordings as easy as that of a gramophone record.



the reel, carrying information about it. The printing of these labels was achieved by making six indian ink drawings with stencils on tracing paper, and getting prints from this via a standard drawing-office print reproducer Incorporated with the circles, were lists with ruled columns, and other useful lettering. The blank section was left for odd bits of information, or to cut away, thus providing a clearance around the tape slot (which I never use!). After printing, the edges, and centres are cut away, and the labels stuck on with Durofix. Printing a dozen copies gives me 72 labels, more than enough! Yours sincerely

... about recording station signals

From:-C. de Silva, Laboratory, Radio Ceylon, Torrington Square, Colombo 7, Ceylon.

Dear Sir:—I am writing this letter with the hope that you will be able to send me a copy of your very first issue. We in Ceylon can buy almost all the recorders advertised in your magazine. Your reviews are very helpful. Also your magazine is within reach of almost every tape enthusiast.

Unfortunately there are no tape clubs as such in Ceylon. Quite a number of people have tape recorders and most of them are used for entertainment purposes. I don't think anyone here has used one for any serious work.

I wonder whether any of your readers have recordings of the theme music of foreign stations. I started recording some whenever I could and, so far, have the themes of the following stations:—France (Paris), Sweden, Switzerland, Germany, Praha, Rome and Radio Brazil. I would like to get some recordings of the medium wave stations of Europe if anyone can help. More strength to your pen, Sir, Yours faithfully

Sorry, but our first issue is out of print. (Editor).

... about tape and carpentry

From:-G. R. Ogram, 12 Victoria Road, Harborne, Birmingham, 17.

Dear Sir:—Tape recording is now well established in my blood and the pressure has built up sufficiently for me to venture forth with one or two tips which may interest your readers.

Eighteen months ago I bought a Brenell Mark V deck and R/P amplifier and fixed them into my own box. Thus, I had no qualms about any modifications to the woodwork, and this



enabled me to carry through with the following: (1). The mains lead was made removable by connecting a Bulgin 3-pin socket adaptor (the pins are flush) to the recorder case, and the other half (with inset sockets—no risk of a shock) to the lead. This is a useful feature, I have found, for it allows one to attach different leads of varying lengths. (2). On the inside I tapped two wires from the "live" and "neutral" pins of the Bulgin adaptor to a two-pin wall socket mounted outside the recorder (not flush—my carpentry is poor!). This means that I have a separate power point in use when the machine is switched on. I use this for plugging in a Jason FM tuner, which is now very conveniently close to the recorder for recording and listening purposes.

I use my recorder mainly for musical purposes. I am building a library of music by Gordon Jacob, the contemporary English composer. In this connection I would be very pleased to hear of anyone with any recordings of music by this very fine composer. Maybe I could add to my collection. Yours sincerely

... about the TR52 review

From:-C. Rae, 32 Whiteclosegate, Carlisle.

Dear Sir:—Mr. J. Moir's review of the E.M.I. Recorder TR52 makes it apparent that the higher the price of a recorder the more limited is the frequency bandwidth. There is something not quite right when a price of £285 can give a response up to 10 Kc/s at $7\frac{1}{2}$ i/s whereas a fraction of this price gives up to 16 Kc/s at $3\frac{1}{4}$ i/s. This amazing discrepancy surely cannot be dismissed as professional reserve on the one hand and pure sales exuberance on the other. It cannot be agreed too strongly that a completely smooth response within 40 c/s—10 Kc/s is more important than an extended response up to 15 Kc/s, but can one only be attained by the sacrifice of the other? If so, there we have an explanation, if not it can only be concluded that E.M.I. are using heads having moderately wide gaps or that the advertised claims of lower priced domestic recorders are untrue.

There are some interesting details about the E.M.I. TR.52 deck that deserve mention, namely that no pressure pads are used, tape-head contact being maintained by the tape tension. As a result, presumably, head wear is very much reduced with a consequent stability in recording characteristics. Another professional feature is that the capstan is driven directly from the motor shaft which, running at 1,425 rpm, necessitates a very small capstan diameter, and any eccentricity in this would cause wow at a frequency of 25 c/s and would not give such a noticeable effect as eccentricity of a lower rotating large diameter capstan. Yours sincerely

... Converting the Collaro Deck to I 7/8

From:-John A. Bell, Radio Officer, s/s "Serbistan", c/o F.C. Strick and Co., Ltd., London, E.C.3.

Dear Sir:—I have recently been introduced to the delights and fascinations of tape recording as a pastime, by the 3rd Officer of the ship in which I am now serving. He owns a Grundig TK30 machine and we are using it for, amongst other things, supplying the drive for a series of loudspeakers in radio receivers

CAPE SUBAMPLIFIER UNITS

coupling Tape head, Microphone. Pick-up, etc., to preamplifier with additional gain. Frequency correction; monaural or stereo. Ten Models, from £3.10.0. Write for data sheet S.A.

CAPE ELECTROPHONICS LTD. 43-45 SHIRLEY HIGH STREET, SOUTHAMPTON



Those who sell recommend . . .



WORLD'S LARGEST SALES OF MAGNETIC TAPE

READERS' LETTERS-(continued)

in other cabinets. This is very popular, and with each parallel line fitted with a volume control pot. it provides an alternative programme when medium and short wave reception is not very entertaining.

I do not yet have any recording gear of my own, but fully intend to build a tape recorder myself in the very near future. In the meantime I am studying as many books on the subject as I can get hold of, and at this point I would like to say what an excellent magazine *The Tape Recorder* is. You achieve a perfect balance of material in the way you combine the semitechnical data with the more straight forward non-technical articles and reviews, etc. I am still reading back numbers of the magazine belonging to the 3rd Mate, but am devouring every word and gaining a good overall appreciation of tape recording from all angles. Thank you for such an informative and interesting magazine.

Next voyage, I intend to build a Mullard type "A" (Model HF/TR3) tape amplifier for use (I hope!) with a Collaro Mark IV transcription deck which I will buy separately. These I will fit into a rexine-covered wooden case incorporating a Rola/Celestion 10 in. \times 6 in. speaker, and hope the result will be an average, fairly good quality tape recorder.

Now for a few queries, more on the technical side which I hope the Technical Editor will answer for me. Firstly, I would like to know if the Collaro Mark IV deck can be modified (by me or an expert) to work at the slower speed of $1\frac{2}{3}$ i/s, either instead of, or in addition to 15 i/s. I would also like to know if it is possible to modify (at a later date) the deck for stereo, by using two of the four heads provided (making stacked heads for stereo) and using them for the second channel signal on the bottom tape track (with tape transport running left to right only).

There is just one other point I would like advice on. What precautions (if any) should I take to protect a tape recorder against the intense heat of the Persian Gulf? Eventually I hope to own a battery portable tape recorder in addition to the one mentioned above, and with it obtain an interesting sound record of my travels round the world, a practice which ought to offer me very wide scope indeed. Yours faithfully

Your first question on converting the Collaro Mark IV deck to $1\frac{2}{8}$ i/s is neatly answered in the next letter. Using the existing heads for stereo sounds attractive, but we have not heard of it being done. The manufacturers of tape and audio equipment will always advise on the use of their gear in the tropics, and often supply special tropicalised versions.

... a pulley for 17/8

From:-Frank Ely, 6 Cranmore Drive, Belle Isle, Leeds, 10.

Dear Sir:—First of all I must congratulate you, for real honest to goodness value in your magazine, which I have taken since it first came out and which I have recommended to a few of my friends. Anyway to get to the point of why I am writing, I have had a Wyndsor Viscount recorder, with the Mark IV deck, and I have often wondered if it was possible to convert the three speeds from $3\frac{3}{4}$ — $7\frac{1}{2}$ —15 i/s to $1\frac{\pi}{8}$ — $3\frac{3}{4}$ — $7\frac{1}{2}$ i/s. Well, I enquired at a shop and was advised to get a new pulley, so I ordered a stepped pulley for $1\frac{\pi}{8}$, $3\frac{3}{4}$, $7\frac{1}{2}$ i/s, and to my surprise when I called at the shop to collect, I received two pulleys and an adaptor to change the engraving on the speed selector also, for the nominal sum of 4s. Well I have fitted one of these pulleys on the right hand motor, and so if I leave it at this, I have four speeds, $1\frac{\pi}{8}$, $3\frac{3}{4}$, $7\frac{1}{2}$ i/s on one track and $3\frac{3}{4}$, $7\frac{1}{2}$, 15 i/s on the other.

The procedure is simple. First remove speed selector knob, then the plastic top which covers the whole deck, next remove the tape tensioning arm assembly which is made possible by removing three screws, in the triangular plate, at the rear of assembly. Two of the screws locate two compression springs, used for lining up spool carrier. Attached to the triangular plate is a fine coil spring which has to be unhooked from the chassis, then the spool carrier, together with tensioning arm is removed. All that remains is to loosen two grub screws in the 3 step motor pulley and pull upward, replace new pulley, and adjust for proper height, the whole operation only took about half an hour. Yours truly

... about Tape Recorders and Slide Projectors

From:-J. Pritchard Jones, Tanycoed, Talysarn, Penygroes, Caernaryonshire.

Dear Sir:-I am using a Grundig TK.830 Tape Recorder, and an Aldis Automatic 35 mm Slide Projector. I wish to change the slides automatically from the tape and would be glad to know if details are available for the home construction of a unit for this purpose. Yours faithfully

We don't know of a suitable home construction unit, but will be glad to publish details, if someone can oblige. (Editor).

... about breaking the language barrier

From:-Victor Sheppard, P.O. Box 1073, Cape Town, South Africa.

Dear Sir:-Some while ago I took along my Telefunken and power unit when I went on a tour of duty into the bush. At first I thought to record Native songs and dancing, and this was successful. The accompaniment being especially effective, the rhythm of hundreds of feet stamping the earth, the leg rattles, the shrill whistles of control, the nose flute, and the "Mbila" a "piano" of filed down hacksaw blades vibrating over a gourd; but in all this I was greatly handicapped by knowing only a few words of the native language. Having passed from the territory of the "Xhosa" (pronounced Kloser, the first syllable is a click and glottal stop combined!) even these few words were useless amongst the Zulu. There are five native tongues and perhaps 200 dialects! So, through the medium of men who had worked in the cities, and some cigarettes, I was able (sometimes) to get a recording done to my requirements of positioning of singers and instrumentalists, not forgetting a fair translation of the lyric.

Before going on my next trip, I took the trouble to seek out native people here who really spoke good English (Schoolteachers, Clergy, etc.), and got them to record a message in their own tongue. In this they introduced me, said a little about the family (children's names and ages went down very well); simply explained the recording process, and requested co-operation; and silence at a pre-arranged signal, from the onlookers.

The results were highly gratifying; where before I was barely understood, and suspect, the help now received was intelligent, and the kindnesses touching. It strikes me that this would be applicable to anyone contemplating a continental holiday, a bit of thought in writing a script to introduce your family (occupation and hobbies) briefly, and with the help of e.g. the local schoolmaster for French and German, or the Restaurateur (Italian or Greek) and you will break through the language barrier straight to the hearts of your hosts. Yours sincerely

... about changing standards

From:-N. C. Robinson, Arlynden, 2 Brookwood Avenue, Sale, Ches.

Dear Sir:-You have in your editorials commented in some detail as to along what lines tape recorder design of the future is likely to move. For example, will 3³/₄ i/s be accepted as a speed perfectly satisfactory for musical recordings of high quality? Can twin track recorders on a $\frac{1}{4}$ in. wide tape compete much longer with those of 4 track? Or possibly twin tracks on a tape of only $\frac{1}{8}$ in. wide? Those who have used a 4 track machine (I have one) will, I feel, never wish to go back to one of twin track design; new converts to tape will, I feel, be encouraged to purchase 4-track machines if only on the score of tape economy.

No doubt the price of tape is held at a level the manufacturers estimate the public will pay; the present level can hardly withstand pressure to reduce the price. An example of one such challenge is, I think, the recent price reductions in L.P. (continued overleaf)







JACK PLUGS, SOCKETS AND LEADS, ETC., FOR ALL MAKES IN STOCK. Standard Jack Plugs 1/11; Chrome 4/6. Wearite Defluxer 50/-. Instant Bulk Tape Eraser and Defluxer 27/6. Bib Splicer 18/6. Easy Splice Tape Splicer 6/9. Klenzatape 12/6. Teletron Tape-Jack £5-9-0. Truvox Radio Jack £3-8-4. Microphone Cable 9d. per yd.; Twin screened 1.6 yd. Light-weight pick-up Screened Cable, Single 1/- yd., Twin 1/6 yd. Philips/Stellaphone Leads 12/6; Grundig/Telefunken Leads SL3 8/6, SL3X 13/-, SL33 10/6, SL33S 11/6, SL233 15/-. Grundig/Telefunken Leads 5LS 6/6, SLSX 15/-, SLSS 10/6, SLSSS 11/6, SLSSS 15/-. Grundig/Telefunken 3-pin Plugs 5/-. Matching Socket SJSS 10/6. Extension Mike Leads MEC5 30/-, MEC10 37/6, MEC15 45/-. Volume Controls. Condensers. Resistors. Etc., Etc., and of course all the best Tape-Recorders. P. & P. 1/6. Over £2 free. S.A.E. all enquiries.

C.O.D. 1/6 extra.

WYNDSOR TELEVISION SERVICE ST. ALBANS ROAD, BARNET, HERTS. BAR. 1769



READERS' LETTERS—continued

records which, with their new stereo appeal, must surely be regarded as likely to make a potential buyer ask, "Record Player or Tape Recorder?'

A wise choice is difficult to make if quality reproduction is required and, on balance, a player unit plus amplifier plus loudspeaker system would appear to cost less than a tape recorder plus amplifier plus loudspeaker system. My problem is whether or not to consider stereo reproduction. For two years I have steadily recorded radio programmes on tape via an F.M. tuner fed into a high quality pre-amplifier/amplifier system instead of buying discs. If, however, I wish to repro-duce stereophonically it would seem that this can be only by disc.

The serious amateur interested in music does not record on to tape via a microphone even for monaural reproduction; he is less likely to contemplate stereophonic recording on to tape by microphones. Is it likely that B.B.C. future radio broadcasting will be twin channel thus enabling stereophonic listening? If so, this means stereophonic tape recording in the home-however much it may be argued that this is an infringement.

The ideal for the serious amateur music lover would seem to be a 4-track recorder capable of recording two channels on two tracks simultaneously in the same direction on $\frac{1}{4}$ in. wide tape if and when radio programmes are broadcast at V.H.F. stereophonically. But until the B.B.C. provide the latter I see no means of using the former to full advantage.

Yours truly

... about a distant relation

From:-Clive Hastie, 246 Wickham Chase, West Wickham, Kent.

Dear Sir:-While on a recent visit to Miami, Florida, I came across a most interesting portable tape recorder, the details of which I thought might interest you. It was the name which first caught my eye, and made me wonder if E.M.I. knew that they had a branch in Japan.

The instruction leaflet spells out the name Emi-Corder, and judging by the demonstration I was given in the shop, its claim regarding wow and flutter and frequency response are perfectly justified. The price asked for this machine was \$56.00 retail, approximately £20—but with U.K. import duty (which I believe is 16s. 6d. in the pound?) it rather took the "gilt off the gingerbread", and being the proud owner of a Stuzzi Magnette, which I took with me, I resisted the temptation. Many thanks for a Yours faithfully fine magazine.

... about taking up Cine

From:-R. Allen, The Eagle Film Unit, 7a Grand Avenue, West Worthing.

Dear Sir: While normally full of praises for your magazine, I feel I really must protest about the article on pp. 254-5 of the June issue "About Taking up Cine" in that it completely omitted mention of the 9.5 mm. film gauge. I use this gauge myself and quite honestly consider its omission unjustifiable as without doubt excellent results can-and are-obtained with it. The actual definitional quality is virtually as good as 16 mm., the frame size being about 15 per cent. smaller than that of 16 mm. Much high quality precision equipment is available from the precision Pathe-Webo "M" Special at £180 less lenses down to the humble but efficient Pathe " Prince " at £17 17s. including f/2.5 Colotar lens. On the same basis as your comparisons, 9.5 mm. cameras, with single lens, cost about £12-15 s/h and about £50 new with high quality lens and refinements; 9.5 mm. projectors can be had for as little as £6 19s. 6d. new (Pathe "Ace" handturned) but an average new price is about £40 (Specto), with a high quality silent projector (Europ) at £60. The Peterson mag. sound attachment costs nearly £70 new and magnetic sound attachments can be had for about £40. No optical sound projectors are at present available new, but a good s/h one can be had for £40-45 ("Son"). Film: 50' (2 min.) b and w 19s. 11d. per roll, 50' Pathe Color 35s. 8d. Yours faithfully

EQUIPMENT REVIEWED

REPS PORTABLE TAPE RECORDER TYPE R.40



Manufacturer's Specification

Mains Voltage: 200-250 volts A.C., 50 c/s. Export model 100-120 volts, 60 c/s. Level Indicator: meter. Collaro Mk IV deck. Position Indicator: 3-digit counter. Tape speeds: 15, 7 $\frac{1}{2}$, $3\frac{1}{4}$ i/s. Frequency Response: 15 i/s, 35-20,000 c/s; $7\frac{1}{2}$ i/s, 40-15,000 c/s, $3\frac{3}{4}$ i/s, 50-8,000 c/s, all \pm 3dB. Recording Sense: Standard half track. Signal to Noise Ratio: 47dB unweighted @ $7\frac{1}{2}$ i/s. Outputs: 12 watts peak @ 15 ohms, and 0.5 volts Cathode Follower. Inputs: microphone 0.4 mV to 60mV @ 2.2 ohms; radio 60mV to 2 volts @ 0.5 megohms. Bass and treble tone controls. Size: $16\frac{1}{2} \times 16 \times 9\frac{3}{4}$ ins. Weight: 44 lbs. Price: £73 10s., including tape, Acos 39/1 microphone and stand, and radio lead.

Manufactured by Reps (Tape Recorders) Ltd., 118 Park Road North, South Acton, London, W.3.

THE REPS R40 recorder is not a mass-produced machine, indeed each one is virtually hand made and individually adjusted for optimum mechanical and electrical performance. For instance, all rotating parts in the Collaro deck are reground to very tight tolerances to reduce wow and flutter to the lowest possible level, special greasing and lubrication are used which give a sweet touch to the controls, and great care has obviously been taken in the playback equalisation, which together with the wow and flutter performance, and signal/noise ratio, reach professional standards.

Introducing the "fluttergram"

Wow and flutter come first on our list of performance criteria, and I am going to expand this section slightly to introduce the "fluttergram" which is a pen recording of the instantaneous short term speed variations and gives much more information than a simple flutter bridge reading. Also it allows analysis of the causes of the wow and flutter in any given machine. The usual total RMS reading is also given with each graph.

The pen recordings of fig. 1 cover time intervals of one second, and were taken at different times during the replay of a 15 i/s 3 Kc/s recording. The difference is due to the fact that small cyclical variations of speed may be out of phase on playback, so that they cancel as in A, or in phase, so that they add together as in B. The actual speed variation is half that shown in B. It is unusual to get such a clear recording of this effect, as it is generally obscured by other sources of wow and flutter in the drive mechanism, and by tape flutter due to the elastic nature of the tape base. The culprit in this case is probably the rubber-tyred idler pulley which couples the stepped motor shaft to the captan flywheel, and the very clearness of the demonstration is a tribute to the work done in

eliminating wow from the capstan and flywheel, and flutter from the motor pulley. The frequency of the cyclical variation is approximately 20 c/s at 15 i/s, and, as will be seen from figs. 2 and 3, falls to 10 c/s at $7\frac{1}{2}$ i/s, and 5 c/s at $3\frac{3}{4}$ i/s.


Excellent wow and flutter figures

At the lower speeds the wavelength of the recorded disturbance on the tape becomes only a fraction of an inch, and the cancellation takes place from cycle to cycle so that the RMS readings are steadier, and do not show the almost complete sustained cancellation which is so easily obtained at the higher speed. In case this should be thought to be a criticism let me underline the fact that the mean RMS wow and flutter readings for the three speeds are 0.1 %, 0.12 %, and 0.14 % which are excellent by any standards, and are quite undetectable musically.

C.C.I.R. test tapes having surface induction characteristics of 35 microseconds, 100 microseconds, and 200 microseconds, were used to measure the playback only responses of fig. 4. The solid line curves are with the bass tone control full on, and the treble control at 0, and the dotted curves show the effect of the tone controls at the $7\frac{1}{2}$ i/s speed. It will be seen that the most level response from the C.C.I.R. tape at this speed is obtained with the treble tone control at +1. I should also explain that all these responses were taken from the external L/S jack rather than the low level line output jack.

The line output jack

This was because I soon found that the response and level from the line jack varied with the loading of the power amplifier, the reason being that the line jack is connected to a point within the feedback loop, and the amount of feedback depends on the L/S load. This trouble could be cured by arranging for a 15 ohm load resistor to bridge the secondary of the output transformer whenever the L/S is switched off, or the external load unplugged. At present, a bass rise of 5dB occurs at 60 c/s if the line jack is used with the L/S off. The result of this bass peak is to give a pessimistic signal to noise—or rather signal to hum—ratio of -35dB on test tape level,



High speed pen recordings of a one second 15 i/s tape of 3 Kc/s tone give useful indications of speed fluctuations.

or 47dB below theoretical peak recording level. When tested from the L/S jack the figures were -41dB, and -53dB respectively. As the playback response is level at 50 c/s under these conditions, the 53dB below peak is the true signal to noise ratio, providing of course that a level +12dB on test tape level can be recorded with negligible distortion.

Recording tests were next carried out at $7\frac{1}{2}$ i/s, and it was found that the test tape level of 10 lines per sq. cm. at 1 Kc/s, was recorded at 8 on the recording level meter, i.e. on the lower edge of the red segment. Full scale, or 10 on the meter,

Don't let



spoil your recordings


The recording head of any Tape Recorder tends to become magnetised in use. Small at first but gradually building up, this residual magnetism can seriously affect the quality of your recordings by progressively increasing the hiss level. It can also impart a noisy background—which can never be removed—to any pre-recorded Tape at the first time of playing.

Fortunately residual magnetism can be instantly removed with the Ferrograph De-fluxer. Get one to-day and, if you use it from time to time, you'll always enjoy tape recordings with a background as silent as the night.



Sold by all Hi-Fi Dealers and made by BRITISH FERROGRAPH RECORDER CO. LTD., Note new Temporary Address : 88 HORSEFERRY RD., WESTMINSTER, S.W.I Tel: SULivan 5426/7/8

Quality Starts With LOW BACKGROUND NOISE



Harvey Electronics Bulk Eraser under test by an independent recording studio show an appreciable reduction in background noise. These units are available to amateur recorders as well as professionals and a complete range is available.

Model 102/103 200-250v/100-115v 3"-8¹/₄" reels **£8-15-0** Model 104/105 200-250v/100-115v 3"-12" reels **£14-5-0** (Special models available for ¹/₂" and 1" tape)

Write or phone for leaflet No. 109

HARVEY ELECTRONICS LTD. Farnborough Road, Farnborough, Hants. Tel. 1120

A professional splice in seconds—

irish S.P.3 Tape Splicer

- ★ Neat blip-free splices
- Unique bow trim leaves edges free of adhesive
 Built-in replaceable blades of high-grade steel for exceptionally long life
 - ★ Only ¼" of splicing tape per splice
 - ★ Removable base allows splicer to be mounted on recorder



The 'Irish' Splicer is five times better at only

67/6

Sole Distributors: WILMEX LIMITED, 70 St. Stephen's House, Bridge St., London S.W.I



ALL YOUR RECORDINGS CAN BE FOUND QUICKLY AND EASILY BY USING —

METRO-TABS 3/11 per set

A new and scientific device designed to clean the record and erase heads of your tape recorder, and to reduce faults caused by oxide deposits. Price 12/6




Write for illustrated leaflets to: **METRO-SOUND MFG., CO. LTD.** 19a BUCKINGHAM ROAD LONDON - N.1 Telephone: CLIssold 8506/7

302

REPS R.40 REVIEW—(Continued)


recorded a level only 6dB above test tape level, and the input had to be increased by a further 6dB to record true peak recording level. This recording was completely clean, showing no visible distortion on a C.R.T., and confirms the peak signal to noise ratio as 53dB. Programme tests with the meter kicking only occasionally into the red were slightly underrecorded, which shows that the electrical and mechanical



• Frequency response curves—playback only

dynamics of the meter allow it to indicate peaks to an accuracy of 2 or 3dB, and that the internal pre-set should be readjusted so that test tape level is recorded at a meter reading of 5, or mid-scale. Under these conditions, full-scale would truly indicate peak recording level, and occasional kicks into the red segment would give a fully recorded tape.

Record Play frequency runs were next made at the three speeds, and the responses with the tone controls out of action are shown by the solid line curves of fig. 5. This indicates that



• Record | Replay frequency response

pre-emphasis at 15 i/s is almost exactly to the C.C.I.R. 35 microsecond characteristic, and that, with the tape sample provided, a slight over-correction of the high frequency preemphasis occurs at the two lower tape speeds. At this point we have to abandon professional review standards, as it is not practicable in a machine in this price range to provide separate recording equalisers for each speed, which are adjustable for different samples of tape. A compromise pre-emphasis must be adopted, and in the interest of signal to noise ratio it is better to err on the side of slight over pre-emphasis than the other way round. The dotted curves show that the overall Record/Play responses can be made sensibly level by judicious use of the treble tone control.

Using a White Noise tape


The acoustic response of the loudspeaker and cabinet was next tested by loading the machine with a White Noise test tape, and measuring the acoustic output on each of the 25 noise bands on a calibrated microphone. The tone controls were set to give a level electrical response. Fig. 6 shows the response to be level within \pm 4dB from 150 c/s to 10,000 c/s with the usual fall in bass response due to the small cabinet. The response sounds smooth and well balanced, and as the cone resonance is about 60 c/s one gets the impression of a much greater bass response than that revealed by the measurements. The lack of cabinet colouration, and the forward facing speaker, allows critical appraisal of recorded quality on location, although only a full range external speaker shows the full capabilities of the recorded.

Steady tone maximum undistorted power output was a little above 4 watts, but a pulsed tone test showed that peaks of a few milliseconds duration reached 8 watts without distortion. This is presumably due to the regulation characteristics of the power supply, and to the fact that the output stage is working in class AB.

The 1 Kc/s noise band gave reference sound level of 10 dynes per sq. cm. at one foot from the L/S fret with a noise voltage across the internal speaker of 0.7 volts RMS, so that the calculated maximum undistorted steady tone level is 105 phons and the output on short duration peaks can be about 108 phons.

Two refinements not mentioned so far are the head demagnetising switch, which operates when the volume control is turned fully anticlockwise, and the superimposing switch which is in the same position on the tone control. Details of these and all the other controls are given in the very comprehensive instruction book supplied with the recorder, which also gives full servicing data and maintenance instructions for the deck.

I found it very refreshing to test a British-made recorder which not only met its specification, but exceeded the claimed



Acoustic response, using White Noise test tape

performance at almost every point. The design and workmanship is such that the high performance is likely to be maintained for a very long working life, and I feel confident in recommending it to anyone who is looking for a machine with a semi-professional performance at a domestic recorder price.

Manufacturer's Comment

This review was submitted to the manufacturer, who commented as follows:—"The output stage is operated under low load conditions and Bias is higher than class AB. Sine wave test will not give an indication of maximum power output. But under speech or music conditions peak power output is 10-12 watts, before distortion occurs.

This mode of operation was adopted to reduce the size of power supply with consequential reduction in weight and internal heat generated."





HIGH QUALITY TAPE **RECORDING EQUIPMENT**

TAPE DESKS AVAILABLE:								
Model 5D (taking up to 101 in. reels)					£50	0	0	
Model 5C (taking up to 9% in. reels)					£47	10	0	
Model 5B (taking up to 7 in. reels)					£42	0	0	
Model 5DF (7½/15 i.p.s.)					£62	0	0	
HALF TRACK HEADS AVAILA	BLE							
Model 5RP Record/Play Head					£3	5	0	
Model 6RP Super Fidelity Record/Play	Hea	ds			£3	15	0	
Model 5R Record Head (Used in conjunction with 6RP Head	1)				£3	5	0	
Model T5E Erase Head					£3	5	0	
Commercial " friction " type mountin	g ste	ms			4/-	ext	ra	
Standard Heads-High Impedance, I	.ow	Impeda						
STEREOPHONIC HEADS:								
Type ST/RPB (without fixing stem)					£6	0	0	
STEREO/MONAURAL HEADS:								
Type 2TK/RC (Record) Type 2TK-RPC (Playback) }					£17	10	0	
supplied					Ser	d i	for	List
	Model 5D (taking up to 10½ in. reels) Model 5C (taking up to 9⅔ in. reels) All with two speeds, 3⅔ and 7½ i.p.s. T button control. Three heavy duty mo shielded heads. Model 5DF (7½/15 i.p.s.) HALF TRACK HEADS AVAILAI Model 5RP Record/Play Head Model 6RP Super Fidelity Record/Play Model 6RP Super Fidelity Record/Play Model 5R Record Head (Used in conjunction with 6RP Head Model TSE Erase Head Commercial "friction" type mountin Standard Heads—High Impedance, L and Special Heads made to order. Fu STEREOPHONIC HEADS: Type ST/RPB (without fixing stem) STEREO/MONAURAL HEADS: Type 2TK/RC (Record) Type 2TK/RCP (Playback) }	Model 5D (taking up to 10½ in. reels) Model 5C (taking up to 9½ in. reels) Model 5E (taking up to 9½ in. reels) All with two speeds, 3½ and 7½ i.p.s. Twin button control. Three heavy duty motors shielded heads. Model 5D (7½/15 i.p.s.) Model 5D (7½/15 i.p.s.) HALF TRACK HEADS AVAILABLE: Model 5R Record/Play Head Model 6R Super Fidelity Record/Play Head Model 6R Super Fidelity Record/Play Head Model 5R Record Head (Used in conjunction with 6RP Head) Model TSE Erase Head Model TSE Erase Head Commercial "friction" type mounting ste Standard HeadsHigh Impedance, Low and Special Heads made to order. Full tr: STEREO/MONAURAL HEADS: Type 2TK/RC (Record) Type 2TK/RC (Playback)	Model SD (taking up to 10½ in. reels) Model SD (taking up to 9½ in. reels) Model SE (taking up to 9½ in. reels) All with two speeds, 3½ and 7½ i.p.s. Twin track hbutton control. Three heavy duty motors. Three shielded heads. Model SDF (7½/15 i.p.s.) Model SR Record/Play Head Model SR Record/Play Head Model SR Record/Play Head Model SR Record Head (Used in conjunction with 6RP Head) Model TSE Erase Head Commercial " friction " type mounting stems Standard Heads High Impedance, Low Impeda and Special Heads made to order. Full track head STEREOPHONIC HEADS: Type ST/RPB (without fixing stem) Type 2TK/RC (Record) Type 2TK/RC (Playback)	Model 5D (taking up to 10½ in. reels) Model 5D (taking up to 9½ in. reels) Model 5E (taking up to 9½ in. reels) Model 5B (taking up to 7 in. reels) All with two speeds, 3½ and 7½ i.p.s. Twin track heads. button control. Three heavy duty motors. Shielded heads. Model 5DF (7½/15 i.p.s.) HALF TRACK HEADS AVAILABLE: Model 5RP Record/Play Head Model 6RP Super Fidelity Record/Play Heads Model 5R Record Head (Used in conjunction with 6RP Head) Standard HeadsHigh Impedance, Low Impedance Hand Special Heads made to order. Standard HeadsHigh Impedance, Low Impedance Full track heads avai STEREOPHONIC HEADS: Type ST/RPB (without fixing stem) STEREO/MONAURAL HEADS: Type 2TK/RC (Record) Type 2TK/RC (Playback)	Model 5D (taking up to 10½ in. reels)	Model 5D (taking up to 10½ in. reels)	Model 5D (taking up to 10½ in. reels)	Model 5D (taking up to 10½ in. reels)

BRADMATIC LIMITED STATION ROAD · ASTON · BIRMINGHAM 6 Phone: EAST 2881-2 Grams : Bradmatic, Birmingham

QUALITY TAPE RECORDER SPECIALISTS

* TANDBERG

* VORTEXION

Officially Appointed Agents for:-

- ★ FERROGRAPH
- * REPS ★ REFLECTOGRAPH ★ BRENELL
- * SIMON
- * GRUNDIG

ALSO IN STOCK

TELEFUNKEN STUZZI-MAGNETTE SPECTONE MAGNAFON REGENTONE SOUND

FERGUSON BALMORAL SABA CLARION KURLAND PERTH-SAJA REPS

Tape Recorder (Hi-Fi) from 63 gns.

ELECTRON

HARTING

TRUVOX

FI-CORD

ARGYLL

VERITONE

NO INTEREST TERMS!

With Free Insurance on your Payments

150 MODELS ON DISPLAY - FREE MAINTENANCE 2/- IN THE £ DEPOSIT

BEST PART EXCHANGE

on your Tape Recorder, Record Player

REW EARLSFIELD LTD, 545 Garratt Lane, S.W.18. WIM 0709 10 mins. from Tooting Broadway 100 yds. from Earlsfield Station



British-made high quality dynamic microphone

This LUSTRAPHONE Dynamic (Moving-coil) MICROPHONE has been produced specially to meet the demand for a model embodying first-class design, robust construction and professional standards of reproduction. MODEL LD/66 is available as a Hand/Table model or with special swivel for stand mounting. In high or low impedance for direct connection to all types of recorders. With 6' cable. In cream colour polystyrene housing. LEAFLET ON REQUEST



BRITISH IN DESIGN AND MANUFACTURE

LD /66

LUSTRAPHONE LTD.

ST GEORGE'S WORKS, REGENTS PARK ROAD, LONDON, N.W.I

RESPONSE-Substantially flat, 70-12,000 c/s

IMPEDANCE-Low, Line, High, Condenser

ACCORDING TO IMPEDANCE AND MOUNTING FROM

£4 - 2 - 6

• Size-31" × 21" × 1"



ZONAL FILM FACILITIES LIMITED THE TOWER, HAMMERSMITH BROADWAY, LONDON, W 6 Tel. Riverside 8741

304

TAPE DECKS ANALYSED

(7) THE COLLARO "STUDIO"

THERE can be few people, interested to any degree in tape recording, who have not seen the Collaro Transcriptor tape deck, used on so many machines. It will be readily understood, then, that the opportunity of reviewing its younger brother, the "Studio" deck, was quickly seized upon. Let it be made plain from the start that although I have criticism, and indeed found faults, in the sample submitted for review, I am convinced that it will prove to be even more popular than its predecessor, and justly so.


Much I believe, has been learnt by the manufacturers in the hard school of experience, resulting in a unit that is altogether simpler in mechanical design . There is every reason to believe that reliability has thereby been increased. There must be many also, who will commend the use of three motors, asserting that 'One motor—One job' is the only satisfactory way of working.

In fact, this deck is so unlike its predecessor that comparison should be taken no further.

Mention must be made of the very favourable impression created by the clean and attractive appearance. One has only to look in a few dealers' windows, or glance at one or two advertisements elsewhere in this and other issues, to see how suitable this deck is for various cabinet stylings.

5-inch or 7-inch spools

The simplicity of mechanical design has already been noted, closer inspection brings favourable comment on a number of features. The Push-Button interlocking, for example, is simple in the extreme, but so far I have been unable to make it misbehave, and, believe me, I've tried! Ingenious also is the arrangement for moving the tape spool hubs. Briefly, this offers the alternative of a deck using $5\frac{3}{4}$ in, spools all inside the



Showing the disposition of the three motors, the flywheel, and the tag-strip for making all electrical connections to the deck. The top view (in the next column) shows 7-inch spools in use.



dimension of the deck, $12\frac{1}{2}$ in. $\times 10\frac{5}{8}$ in., or, if more room is available, the assembly can be built up to accommodate 7 in. spools which will, of course, overlap the deck itself by several inches. I was pleased to note that facilities for making such a change are complete, even to a second pulley to alter the ratio of the three-digit counter.

Fitting a third head

Full marks must also be given for the provision of facilities for the fitting of a third head, a point that will appeal particularly to more serious enthusiasts. A slightly different form of pressure pad would be required, but it is understood that these will be readily available, either with a third head as a kit, or separately for those who would prefer to use a head of different manufacture.

Mention of pressure pads, however, brings me to what is, in my estimation, the only black mark in the design. I belong to the school who consider that the natural path of the tape through the sound channel should be snugly against the heads, pressure pads being used, if at all, only to "iron out" the wrinkles, so to speak. With such a design, the tape is lifted clear of the heads for fast winding etc. Collaro's have adopted the opposite course, the straight line of the tape is about 1/16 in. clear of the heads, and the pressure pads are used to take the tape up to the heads for record or playback. In my submission, this places too much reliance on correct adjustment of the pressure pads. A small point perhaps, but worthy of mention against the background of what I consider to be a fine design.

Practical tests

So much for the theory, but how does this unit perform in practice? It is obviously impossible to test a tape deck entirely without building it into a complete recorder, and then amplifier performance becomes a major consideration. Sufficient is already known about the Collaro type of head to warrant it necessary only to connect temporarily to existing apparatus.


The operation of the push-button controls certainly requires favourable comment, they are light to the touch yet allowing one to "feel" that something is happening. Fast winding is carried out at quite a good speed, braking is efficient but without snatch. It should be noted that "Double Play" tape was handled extremely well. Spooling of tape on "Rewind" tended to be rather untidy, it is felt that modification of the Left hand tape guide to restrain the tape more closely would be an improvement.

Selecting the playing speed is simplicity itself, but the writer was a little dubious over a warning in the Instructions against changing speed whilst running—only to find that an interlock again defeated all my efforts! It would be very pleasant if I were able to end my remarks here, but, alas, that cannot be.

COLLARO STUDIO DECK-(Continued)

Although the three tape speeds on the deck reviewed were extremely close to nominal, the level of wow and flutter was of a higher order than claimed.

It is believed that the main offender was one of the brake mechanisms on the spooling motors. Slight flutter, though not of a very high order, was traced to the idler pulley, and also, more important, the pressure roller could be seen to be running eccentric. If it is remembered that the sole function of a tape



The space for a third head is seen top right.

deck is to transport tape past the heads, these charges must be considered to be serious. It may well be that only slight attention would make all well, indeed some recorder manufacturers give such attention, in varying degrees, to the decks they buy before fitting, but should the onus be on them?

Should this be an isolated example of such a fault, then my remarks will be considered rather harsh. Of one thing I am confident, the production of a deck having the performance of which this design should be capable, will ensure that at least one Tape Deck Manufacturer has a contented Sales Manager. **A. Bartlett Still**

Technical Specification:

Medium: 1/4 in. Plastic or paper base coated tape. Track Width: 0.087-0.091 in. Number of Tracks: Two. Record Playback Sense: Upper Track, Left to Right only. Number of Motors and Type: Three. Four pole, Induction, fully screened. Voltage: 200-250v, 50 c/s, 110v. 50 c/s and 110v. 60 c/s by change of motors. Consumption: Max. 40 watts at 230v. Operating Speeds: $1\frac{2}{8}$, $3\frac{3}{4}$ and $7\frac{1}{2}$ i/s. Number of Heads: Two. Space provided for the fitting of a monitor head or a stereo playback head. Record Head Gap: 0.00025 in. Record Head Impedance: 30 K ohms at 10 Kc/s. Attainable Frequency Response: 12 Kc/s at $7\frac{1}{2}$ i/s ± 3dB with Record/Playback equalisation. Recommended Erase and Bias Frequencies: 45-60 Kc/s. Erase Head Impedance: 200/ 300 ohms at 45-60 Kc/s. Erase Voltage: Approximately 25 volts at 120 mA. Playing Time: 120, 60, or 30 minutes per standard 1,200 ft. reed. Rewind Times: 65 seconds per 7 in. spool of 1,200 ft. 45 seconds per 53 in. spool of 850 ft. Wow and Flutter: Not greater than 0.15 per cent. at 71 i/s. Long Term Speed Stability: Better than 0.5 per cent. Dimensions: $12\frac{1}{2}$ in. $\times 10\frac{5}{8}$ in. With 5³/₄ in. spools within the confines of the Plate. With 7 in. spools overlapping Unit Plate. Depth: 4 in. below Unit Plate Beaded Edge. Weight: 14 lbs. Price: £17 10s.

Manufactured by Collaro Ltd., Ripple Works, By-Pass Road, Barking, Essex.

Manufacturer's Comment

Before publication, this report was submitted to the manufacturers, who commented as follows: "The sample deck reviewed is an early model, and subsequent machines incorporate a number of modifications which bring the wow and flutter well within our published limits."

YOUR TAPE DEALER -

Specialists in Hi-Fi Equipment and Tape Recorders

CHELSEA RECORD CENTRE 203 KINGS ROAD, S.W.3 FLA 25%

Open till 8 p.m. (except Thursdays)

LONDON AREA, W.1

Stockists of leading makes of Tape Recorders

Comparative demonstrations at any time

H. C. HARRIDGE 8 MOOR STREET W.1 Telephone: GERrard 7108



LONDON AREA

MUSICRAFT

20/22 HIGH ST., SOUTHALL, MIDDX. SOU 3828 13 KING ST., RICHMOND, SURREY RIC 6798 80-82 UXBRIDGE ROAD, EALING, W.13 EAL 6995 Hours of business: 9.00 a.m.-6 p.m. Mon.-Sat. (Wed. early closing)


ESSEX TAPE RECORDER and HI-FI CENTRE

PART EXCHANGE SPECIALISTS APPROVED DEALERS FERROGRAPH, BRENELL, SIMON, GRUNDIG, REPS, PHILIPS ETC., ETC. and ALL HI-FI EQUIPMENT

PHILIPS ETC., ETC. and ALL HI-FI EQUIPMENT 2 MARYLAND STATION STRATFORD, E.15 MARyland 5879

Disc and Tape Reproducing Equipment and Tape Recorders by Leading Manufacturers CUSTOM BUILT INSTALLATIONS All High Fidelity Requirement and Services Available Estimates Free Personal Service Custom High Fidelity 371 Green Lanes, Palmers Green, London, N.13 Tel.- PALmers Green 5228

R.E.S. of COVENTRY SPECIALISTS IN HIGH FIDELITY and all makes of Tape Recorders All leading makes of High Fidelity Equipment stocked and demonstrated under ideal conditions. * The Best Selection—Terms and After Sales Service in the MIDLANDS. R.E.S. (Coventry) Ltd. 128 Far Gosford St. Coventry 60913



YOUR TAPE DEALER -

LEADING TAPE RECORDER STOCKISTS

BEXLEYHEATH

NORTH KENT

BROADWAY RADIO,

228 BROADWAY.

Bexleyheath 4184

ALL DEMONSTRATION FACILITIES

BIRMINGHAM

TAPE RECORDERS on "NO-INTEREST" Terms! NO EXTRA CHARGES FOR EXTENDED CREDIT. You pay the Retail Price only. Grundig, British Ferrograph, Philips, Vortexion, Telefunken, etc. Comparative daily demonstrations of all Leading Makes of Stereo Hi-Fi Equipment and Recorders.

JEWKES & CO. LTD.

The Midlands Hi-Fi and Tape Recorder Specialists 285 BROAD STREET, BIRMINGHAM I. MID 4829/20

ACOUSTIC PRODUCTS

HI-FI Stereo Tape Recorders

Specialised Loudspeaker enclosures and Equipment Cabinets Designed to order

Write or ask for Mr. Pendreich

54 ELM ROW, EDINBURGH, 7. Tel.: WAV 6338

FARNHAM, SURREY

- ★ Stockists of all the leading makes of High-Fidelity Equipment ★ Comparative Demonstrations ★ Cabinet Manufacturers and Designers ★ Personal service and satisfaction guaranteed

LLOYD & KEYWORTH LTD, The Record Shop 26/7 Downing Street, Farnham, Surrey Telephone: SURREY AND HAMPSHIRE'S HI-FI SPECIALISTS Telephone: Farnham 5534

Tape Recorder Centre (Halifax)

Yorkshire's Leading Tape Recorder Specialists Comparative Demonstrations Daily O HI-Fi Stockists Official Telefunken Service Agents

SOUND INSTALLATIONS 17 Rawson Street, Halifax

Phone: Halifax 66832



LEICESTER CO-OPERATIVE SOCIETY LTD.

HIGH STREET Telephone: 20431



Offer unique sales and service facilities throughout the Northwest. Stockists of FERROGRAPH

REFLECTOGRAPH, GRUNDIG, etc., etc.

FREE H.P. up to 12 MONTHS

18 HACKINS HEY, (off Dale St.,) L'POOL 2. CEN: 5245



CLASSIFIED ADVERTISEMENTS

Advertisements for this section must be pre-paid, and accompanied by a postal order, money order, or cheque, made payable to "The Tape Recorder", 99 Mortimer Street, London, W.1. They must be clearly written or typed, and must be in the form of a separate sheet of paper if included with a letter dealing with other subjects.

The rate is 6d. per word, with a minimum charge of 7s. 6d. Box numbers may be used for an extra charge of 1s. 6d. The trade rate is 9d. per word, plus 2s. for a box number, conditions on application.

No responsibility will be accepted by the editor, the publishers, or the printers of "The Tape Recorder", for the quality of any goods offered, bought, or exchanged through the medium of these columns, or for any failure in payment, etc., though the greatest care will be taken to ensure that only bona-fide advertisements are accepted.

For Sale

Tape Recorders. Large selection of used models, most as new with three months guarantee. Part Exchanges with Cameras, Binoculars, Radios, etc. Good quality Recording Tape at competitive prices. Coøks Store, 159 and 187 Praed Street, W.2. (both opposite Paddington Station) PAD. 6464.

A binder will keep your copies of The Tape Recorder clean and ready for easy reference, price 15s. posted from 99 Mortimer Street, London, W.1.

Tape/Disc/Tape transfer, editing, copying. If quality and durability matter (especially with LP's from your precious tapes) consult Britain's oldest transfer service. (LP's from 16s.). Limited quantity 1,800 ft. American super LP tapes 35s. Sound News, 10, Clifford Street, London, W.1.

Use up those odd lengths of tape, splice them together professionally after reading "How to Splice Tape" price 2s. 6d. posted from The Tape Recorder, 99 Mortimer Street, London, W.1.

Find that review you want-get a copy of the index to volume one Tape Recorder. Price 2s. posted.

Grundig TK30 new with accessories. Cost £83 accept £60 or near. Guaranteed.—Box No. 245.

Reflectograph 500 recorder. Purchased in Dec. '59. Faultless and as new. Reasons for sale are personal and financial. \pm 75. Macpherson, Khyber, Crookham, Hants.

Harting stereo deck HM5SD. £27. Cost £44, new condition only 12 months old. 77, Queniborough Road, Leicester.

Ferrograph 4A/N's 808's Vortexion WVA, WVB, Simon SP4, Reflectograph 'B', etc., always in stock and ready for immediate delivery as well as over 200 latest 1960 recorders at London's largest tape recorder specialists. The best, lowest H.P. terms and the finest selection of new and S/H recorders from £18. Generous P/E allow-ances. Essex Tape Recorder Centres, 2, Maryland Parade, Stratford, E.15 and 205, High Street North, East Ham, E.6.

Grundig TK5 excellent condition Tape/mike £30 o.n.o. Bryne, 24, Brandville Gardens, Ilford. CRE 8033.

WHITE NOISE TEST TAPE FOR ACOUSTIC MEASUREMENTS, as reviewed WHITE NOISE TEST TAPE FOR ACOUSTIC MEASUREMENTS, as reviewed in April issue. 25 one-third octave bands of filtered white noise recorded to C.C.I.R. characteristic so that the noise power fed to the speaker is constant for each band when played on a recorder equalised to C.C.I.R. playback response. Voice announcements identify each band. C.C.I.R. PURE TONE TEST TAPES. Original recordings of single frequencies covering the range 10,000 cps to 40 cps, with voice identification of each frequency. frequencies covering the range 10,000 cps to 40 cps, with voice identification of each frequency. LABORATORY OR FACTORY C.C.I.R. 'REPEATER' TEST TAPES. Original recordings of 10 tones from 7,500 cps down to 60 cps, repeating every 30 seconds throughout reel. LABORATORY OR FACTORY AZIMUTH ALIGNMENT TEST TAPES. IS seconds of 1,000 cps tone followed by 45 seconds of 7,500 cps tone recorded to an azimuth accuracy of plus or minus 5 minutes of arc. Repeating throughout real. throughout reel. All above tapes are normally recorded at 7.5 inches per second, and are issued on $3\frac{1}{4}^{\alpha}$ diameter reels. Level accuracy is within plus or minus I dB. 33"/sec. recordings available to special order. PRICE 39s. 6d. PER REEL. TRADE ENQUIRIES INVITED TUTCHINGS ELECTRONICS LTD., 14 ROOK HILL ROAD, FRIARS CLIFF, CHRISTCHURCH, HANTS

308

FREE H.P. YOU PAY THE CASH PRICE ONLY - OVER 24 MONTHS!

We sell and stock more Tape Recorders than any other dealer in England, Wales, Scotland or N. Ireland. Why do thousands of people buy from us? Because we give the best terms—terms which include No-Interest Charges at all—Only Is. in the £ deposit any make—Up to 2 years to pay—Free Servicing— Free Delivery—No Purchase Tax—Free Tape offers—Commission on Sales—and lots more besides.

If you want to know why it will pay you to buy from us, write, phone or call in NOW for full details of all our terms, and free brochures on all the best makes:



Please rush me full details of your terms and tape recorder brochures:

Name...

..... Address

Add below any models you are particularly interested in :

ER/I

YOUR TAPE DEALER -

MANCHESTER

THE NORTH'S TAPE RECORDER CENTRE Stockists of Ferrograph, Reflectograph, Brenell, Grundig, Elizabeth, Tandberg, Telefunken, Wyndsor, etc., etc. HIGH FIDELITY DEVELOPMENTS LTD. 8 DEANSGATE · MANCHESTER 3 (Next to Grosvenor Hotel)



PETERBOROUGH, NORTHANTS Tel: 2759 Hi-Fi Equipment and Record Specialists Tape Recorders - - Record Players

Comparative demonstrations of all leading makes of Audio equipment **CAMPKIN'S RECORD SHOP**

12 PARK ROAD also at KP Camera Shop, Kings Parade, Cambridge

SOUTHAMPTON - SALISBURY


- ★ All the best makes of Tape Recorders
- ★ Hi-Fi Systems and Records
- ★ Expert knowledge and advice
- The West of England High Fidelity Specialists

F. SUTTON 421 SHIRLEY ROAD, SOUTHAMPTON 15-18 QUEEN STREET, SALISBURY

WORTHING, SUSSEX

We Stock Hi-Fi Equipment by Leak, Quad, Goodsell, RCA, Acos, Garrard, Collaro, Tannoy, Wharfedale and Goodman and give fully comparative Demonstrations

BOWERS & WILKINS LTD. I Becket Bldgs., Littlehampton Road Worthing 5142



EASYSPLICE CO. 30 LAWRENCE ROAD, EALING, LONDON

AUDIO FAIR SI	ELECTIC		ipment taken in EXCHANGE
Installa	tions and R	epairs a speciality	-
Grundig Cub Port Grundig Mains Unit Ferguson Crown Audio Simon Minstrelle Sound Studio Philips 4 Track Brenell M5 Grundig TK20 Brenell 3 Star	7 gns. 28 gns. 39 gns. 39 gns. 42 gns. 59 gns. 64 gns. 52 gns. 58 gns.	Quad II Amp. Quad II Control Quad Stereo Contro Garard 301 Garrard 301 Garrard 4 H.F. Viking Enclosure Super Hi-Fi Cabinet E.M.I. Chassis IO Wa Tannoy Canterbury	£28-17-6 £22-7-3 £18-9-9 £10-10-0 £19-19-0
Korting Stereo Harting Stereo Ferrograph 808 Stereo Grundig TK35	68 gns. 86 gns. 105 gns. 82 gns.		to 3 Years
Write or call to RAPP TA 181 Dalston Lane, E		RDERS, LOND	ON lerst 5253-2238

CLASSIFIED ADVERTISEMENTS-(continued)

For Sale-(continued)

Tape Recorders. Sale of demonstration models, all in excellent order and with guarantees:—Grundig TK35 £65: TK30 £58: TK25 £50; "Cub" with mains power pack £30. Wyndsor "Viscount" console model with stand, in contemporary styling £50. E.A.P. 'Escort' £35. All carriage paid. Cosmic Radio Ltd., 6 and 8, Clifton Crescent Birkenbead Clifton Crescent, Birkenhead.

Tape—Tape, BASF, Irish, Scotch. All types in stock. Send for price lists c.w.o. post free. Tape Recorder Centre (Halifax), 17, Rawson Street, Halifax.

Mark IV., Truvox Recorder mic., radio jack, tapes, extension speaker "Axiome" 300 in sherwood hi-fi cabinet. Price £60.—Box (London) 247.

Miscellaneous

Tape to Disc-all speeds s.a.e. for leaflet, Omega Recording Company, 112 Sunnybank Road, Potters Bar, Middx. Tel: 6428 (evenings only).

Tape Recorder need repairing? Let the specialists do it for you at an economical price. Essex Tape Recorder Centres, 2, Maryland Parade, Stratford, E.15. MAR 5879.

Tape to Disc-Comprehensive 78-45-33 service available from Rendezvous Records, 19 Blackfriars Street, Manchester 3.

Tapes? Transfer? Consult Sound News for better rates. See above.

Tape Recorder repairs, all makes, also trade servicing-Telefunken rvice agents. Tape Recorder Centre (Halifax), 17, Rawson Street, service agents. Halifax 66832.

Wanted

Tape Recorders, players, radios, etc. (modern) wanted for cash. Callers or particulars, Cooks Store, 159 and 187 Praed Street, W.2. (opposite Paddington Station). PAD 6464.

TK20 or similar good Grundig wanted. F. Riddle, 113, Church Road, Northolt, Middx. Viking 4734.

ADVERTISERS' INDEX

Page

ANG IN Her Laster Laster La							290
A.K.G. (Politechna London Lto	a.)		 		 		304
Bradmatic Ltd			 		 		302
British Ferrograph Recorder C		d.	 		 		294
Brown, S. G			 		 		294
Cape Electrophonics Ltd.			 		 		300
Chelsea Record Centre			 		 		
Colour Printers			 		 		268
Dickinsons of Pall Mall Ltd.			 		 		282
Easysplice Co			 		 		310
Elizabethan (Tape Recorders)	Ltd.		 	•••	 		270
Francis of Streatham			 •••		 •••		288
Garrard Engineering & Mfg. C	o. Lto	1	 		 •••		262
Gramdeck			 		 		280
The Gramophone Co. Ltd.			 		 	•••	265
Grampian Reproducers Ltd.			 		 		284
Grundig (G.B.) Ltd			 		 		269
Harvey Electronics Ltd			 		 		302
Hi-Fi Year Book			 		 		306
Howard Photographic			 		 		309
How to Splice Tape			 		 		280
Lanes (Radio) Ltd			 		 		300
Lee Products (Gt. Britain) Ltd			 		 		272
Lustraphone Ltd			 		 		304
M.S.S. Recording Co			 		 		294
Metro-Sound Mfg. Co. Ltd.			 		 		302
Multicore Solders Ltd			 		 		288
Nusound Recording Co.			 		 		266
Philips Electrical Ltd			 		 		266
R.B. Tapes Co. Ltd			 		 		282
R.E.W. Earlsfield Ltd			 		 		304
Rapps Tape Recorders (Londo	n) Ltd	I	 		 		310
Recording Devices Ltd			 		 		267
Romagna Reproducers Ltd.			 		 		280
Sands Hunter			 		 		284
Scotch Brand Tape			 		 	298	8-299
Simon Sound Ltd			 		 		263
Speedtape Ltd			 		 		300
Tape Recorder Centre			 		 		264
Tape Recorder (Electronics) L	td.		 		 		296
Tutor Tape Co			 		 		284
Valradio Ltd			 		 		288
Wilmex Ltd			 		 		302
Wyndsor Recording Co. Ltd.			 		 		311
Wyndsor Television Service			 		 		300
Zonal Film Facilities Ltd.			 		 		304



LISTEN BEFORE YOU LEAP

THOSE of us who know little about decibels and flat frequency responses might not raise our eyebrows at the facts and figures describing the much-talked-about new Wyndsor "Victor" portable. Those who are genned up to translating the specification into words and music are not surprised that the "Victor" sounds better than some tape recorders nearly twice the price. But make no mistake if you are about to plunge: the Wyndsor "Victor" is a qualityall-the-way portable, so beautifully designed and executed as to bring professional-sounding recordings within the reach of the most non-technically-minded amongst us.

Mark these following features and ask yourself how does Wyndsor do it at the price.

- * frequency responses:---
 - $7\frac{1}{2}$ i.p.s.—50 to 15,000 c.p.s. better than \pm 3 dB.
 - $3\frac{3}{4}$ i.p.s.—50 to 9,000 c.p.s. better than \pm 3 dB.
 - 1⁷/₈ i.p.s.—50 to 5,000 c.p.s.
- * full frequency equalisation at all speeds.
- * $10'' \times 6''$ elliptical speaker in detachable lid.
- * up to 8 hours playing time on one D.P. tape.
- * monitoring through its own speaker with independent control.
- * finger-tip controls closely grouped.
- * mixing facilities for mic and gram/radio inputs.
- * additional output with automatic speaker cut-out.
- * facility for use as an amplifier.
- * three independent 4-pole motors.
- * unique styling in two-tone grey with gilt fittings.
- * twin tracks * pause control * tone control.
- * guarantee: 12 months (valves 90 days) and the name of Wyndsor.

And how *do* they do it? By the experience that ten years manufacture of quality tape-recording equipment only can bring. By design-creation only after intensive market research and nation-wide trade inquiries, so that Wyndsor taperecorders virtually sell themselves, without sales-force, without large advertising campaigns, without exhibiting at you-knowwhere, and with minimum servicing requirements after sales. All these overheads are conspicuous in the price by their absence.

If history is anything to go by, widely publicising the "Victor" would overwhelm the Wyndsor factory. Wyndsor policy is never to sacrifice quality for quantity and the fact is that there were never enough of the "Victor's" predecessor, the "Viscount", to satisfy the demand. So now is the time for all good enthusiasts to inquire at Wyndsor dealers or to send postcards (clean variety still preferred) to the modestly proud makers for the names of nearest stockists. There is nothing more annoying than hearing a Wyndsor just after buying an ordinary tape recorder.



The Wyndsor "VICTOR" complete with crystal microphone, 1,200 feet of tape, and a spare jackplug, is only 45 guineas

WYNDSOR RECORDING CO. LTD.

(Contractors to H.M. Government)

Wyndsor Works, 2 Bellevue Road, Friern Barnet, London, N.11

> Telephone: ENTerprise 2226/7 Telegrams: Wyndreco, London













HI-FI NEWS

is a reliable magazine for everyone who needs reliable reviews, news and information about all audio matters. From bookstals at 2/- monthly, or posted direct–12 copies plus annual index, for 27/-HI-FI NEWS

99 Mortimer Street · London · W.1.

Hi-Fi News











Published by Miles Henslow Publications, 99 Mortimer Street, London, W.1 Printed by STAPLES PRINTERS LTD., (Incorporating F. Howard Doulton) Warton Road, Stratford, London, E.15.