

Color Video Monitors

This equipment includes video monitors suitable for display of standard, HDTV and computer generated video signals. Under component inputs, YCrCb refers to equi-band R-Y/B-Y components, rather than unequal bandwidth I/Q, and YCwCn are HDTV format components. Models marked with a diamond (◆) include a μ P-controlled auto setup system. Except for those models marked with a bullet (•), the image aspect ratio is 4:3. H-V delay and cross pulse display is standard except on models marked with (‡). Abbreviations N (NTSC), S (SECAM), P- (PAL).

Manufacturer	ASACA/ShibaSoku				
Model/Series Number	CM44A1 (CM43A1)	CMM7 series	CMM11 series	◆CM22A6 (CM65A)	CM99A
Application	Master, utility	Master, utility	Master control	Master control HDTV	Portable
CRT diagonal	14" (15")	20" (14", 26")	20" (14", 26")	20" (26")	9"
CRT type	Inline dot (flat)	Inline dot (slot-26")	Delta-dot	Inline (delta) dot	Inline dot
Dot/stripe pitch in mm	0.31 (0.38)	0.31 (0.37, 0.43)	0.26 (0.37)	0.30
Beam feedback CRT	Yes	No	No	No	No
Suggested resolution (TVL)	500	600	>600	1000	500
Luma bandwidth	60Hz-7MHz	To 7MHz	>7MHz	To 30MHz	To 7MHz
Chroma bandwidth	500kHz R-Y/B-Y	1.3MHz	I-1.3, Q-0.5	To 7MHz	To 1.3MHz
Aperture correction	0-8dB @ 2.8MHz	-10, 0dB	>10dB range	-10,0dB range
Chroma decoder	Comb filter	Comb filter	Comb filter	Comb filter
Demodulation axes	R-Y, B-Y	R-Y, B-Y	I, Q	R-Y, B-Y
X-Y outputs	Yes	Yes	No
Blue gun only test	No	No	No	No
Underscan	Yes	To 95%	To 95%	To 92%	To 95%
Available for	N, RGB	N, P, S, RGB	N, P, S, RGB	RGB	N, P
Multistandard unit	No	Switch selected	Switch selected	No	No
Composite inputs	3 inputs	N, P, S	N, P, S	No	N, P
Component inputs	RGB 8-pin	RGB	RGB, YCrCb forms	RGB, YCrCb, YCwCn	RGB
VCR input/output	No	No	No	No	No
Integral AF amp/speaker	No	No	No	No	No
Reader Service Number	611	612	613	614	615

If you don't have room for a 10 x 20 routing system, we have a little suggestion.

Introducing the latest low cost additions to our compact video and audio router family: the full-function TEN-20™ or our 20-TEN™. Each requires just one rack unit per matrix.

When you need to save space — and money — there's always room for a little innovation.

Grass Valley Group
STRENGTH YOU CAN RELY ON

THE GRASS VALLEY GROUP, INC. — P.O. Box 1114 — Grass Valley, CA 95945 USA
Telephone (916) 478-3000 — TRF: 160432 —
OFFICES: New York (201) 845-7988; District of Columbia (301) 622-6313; Atlanta (404) 493-1255;
Chicago (219) 264-0931; Minneapolis (612) 483-2594; Dallas-Fort Worth (817) 485-7447;
Los Angeles (818) 999-2393; San Francisco (415) 968-6680. A TETRAONIX COMPANY

Do You Want To 'Talk' Audio?

AESNET ON COMPUSERVE

John Hoffman
Net Administrator
76703, 1036

Circle (73) on Reply Card